John Baldwin Long • 988 Blvd. of the Arts #212, Sarasota, Florida 34236

To:

Mrs. Terry Levinson
U.S. Department of Energy
1000 Independence Ave, S.W.
Mail Stop 5E-052
Washington D.C., 20585

Nov. 23, 1992

DOE/CE/15479--T4

DE93 003303

OST

Subject: Quarterly Report for Grant DE FG 01 90CE 15479

Dear Terry:

Because of delays in each of the tasks of the subject grant, it was requested that the grant be extended at no cost to the government. The grant would have ended on 9/25/92, and has now been extended to 9/25/94.

TASK 1

This task refers to a user test to determine the acceptability of the Sundyne Solar Cooker and to discover possible mechanical difficulties in its use. As described in previous reports, 150 cookers were sent to Haiti. One hundred had been placed with Haitians in villages near Fort Au Prince. Since the coup, communications have been interrupted. U.S. mail was stopped, and only recently telephone communication on an intermittent basis became possible. The marketing firm, SKA of San Juan, Puerto Rico, had not been able to contact their employee in Haiti since his first report had been received from him. However, through Canadian contacts met at the Stockton World Cooking Conference, we have referred SKA to a native Haitian who has been in charge of a Canadian Solar Box Cooker program in a Haitian village. He will find and interview the natives who have now had their Sundyne Cookers for the better part of a year. In addition, we plan another similar test with the remaining cookers in a village on Haiti's west coast, and with a Catholic Church effort in which a dozen or so locations prepare hot meals daily for hungry children. Letters can now be sent unofficially through Lynx Air, a volunteer air service from Florida to Haiti. Our new representative in Haiti receives his mail in this unofficial way.

TASK 2

VITA has now completed the correspondence exchange with the original 70 replies expressing interest. Of these about ten are seriously interested in using the Sundyne Cooker. VITA is completing its final report as of this writing. The final report will include plans for dealing with the organizations showing interest.

MASTER

TASK 3

M.D. Juan has completed two of its contracts. The remaining contract involves using an ALCOA polished aluminum with a protective anodized coating as a substitute for the lens

John Baldwin Long • 988 Blvd. of the Arts #212, Sarasota, Florida 34236

material. Final testing of ALCOA's product was unsatisfactory. The material called "Everbrite" proved to be difficult to form into the lens configuration. ALCOA's engineering department has produced a more formable product which does not carry the Everbrite trade name, but seems equal in reflectivity and specularly. This material is untempered, and so shows possibilities of being compatible with the existing lens dies. Samples of this new material have been sent to M.D. Juan and is being tested at this time.

I attended the Worldwide Conference on Solar Cooking sponsored by the College of Pacific in Stockton, California on June 19th and June 20th. A working display of the Sundyne Cooker was provided, and a paper written by myself was presented to the conference. A copy of the paper is enclosed. Robert Ware, the coinventor of the Sundyne Cooker and Bienvenido Juan, the manufacturer of the cooker also attended. Mr. Juan came from Manila for the conference. A wide spectrum of information was offered from historical to technical concerning Solar Cookers. All of the cookers displayed were Solar Box type except for ours and two others, which were concentrator types. The Sundyne Cooker at this time is the only cooker manufactured in a mass production manner, and is therefore the only concentrator design that is economically viable.

At this conference we met two of the people from British Columbia Canada who were sponsoring a solar box cooker program in Haiti. They referred us to their program supervisor who is Haitian. He has agreed to complete our testing program which was interrupted by the coup.

If there are questions or comments, please call me.
(813 954-6562

Sincerely,

John B. Long

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

THE SUNDYNE SOLAR COOKER

The Sundyne Solar Cooker is a concentrating type cooker designed to be used by a single household for cooking the midday meal. The cooker will boil a quart of water in about 12 minutes' time assuming midday sun conditions and an initial water temperature of 75 degrees F. This is roughly the time required to boil a similar quantity of water using a conventional heating element on an electric range.

Figure 1 shows an exploded view of the Sundyne Solar Cooker with a listing of the parts. The cooker is comprised of three major assemblies; a reflecting lens; a support stand; and a pot holder assembly.

The 48-inch diameter Fresnel type reflecting lens is designed to reflect parallel sun's rays and to focus these rays in a roughly spherical region located about 30 inches above the plane of the reflector lens. The focal region is 5 to 6 inches in diameter. The lens is assembled from four identical pie-shaped quadrants to form a flat circular lens. The reflecting surface consists of five conic surfaces arranged in a concentric annular configuration. Each of the reflecting surfaces is flat and tilted at a slightly different angle to give the desired image size and position. The reflector quadrants are cold formed from 18 gauge carbon steel. An adhesive-backed polyester film coated with vapor deposited aluminum is applied to each of the reflector surfaces to give a solar reflectance of about 0.90.

The stand provides structural support for the entire cooker and allows adjustment of the reflector lens in both azimuth and elevation. The reflector lens pivots on a ball joint support and is locked into position with two wing nuts. In use, the reflector is positioned so that its plane is perpendicular to the sun's rays. A sighting tube attached to the rim of the lens provides a visual indication that the orientation is correct. The support stand is designed so that the tilt angle of the lens can be moved from horizontal to 45 degrees to the horizontal, depending on the time of day and the season of the year. The apparent motion of the sun requires the user to reposition the lens about every 30 minutes to maintain the focal region in the proper position for cooking.

The potholder assembly consists of a pot holder, post, and a two section swivel arm. The assembly is designed to keep the pot level at all times, and to support the weight of a 12-cup cooking pot. Adjustment of the pot position is independent of adjustment of the lens. Adjustment of the horizontal position of the pot to assure uniform cooking is required at 10 to 15 minute intervals by rotating one of the swivel arms.

The disassembled solar cooker is shipped, with all hardware and instructions for assembly, operation, and maintenance in a carton 24 inches square and 9 inches high, which weighs about 35 lbs. To use the cooker, the cook first aligns the reflector to the sun using the sighting tube. The cooking pot is then filled and placed on the pot holder, which is positioned so the bottom of the pot is at approximately in the center of the focal region. Raising or lowering the pot holder changes the diameter of the focal image, which might be desirable if different diameter pots are used.

A major mechanical feature of the Sundyne design is the ease with adjustments can be made, so that the lens is properly positioned with relation to the sun's rays, and the pot is positioned correctly in the focal region. As stated above, the lens is designed to move independently of the cooking pot. In previous designs of concentrating solar cookers, the cooking pot support was attached directly to the reflector thus necessitating the inconvenience of briefly removing the pot from the cooker while the reflector is repositioned. With the Sundyne cooker, the pot remains in a level position on the pot holder, while adjustments can be made to the lens position or the position of the pot. As the sun moves, if no adjustments are in the lens position, the focal region changes from circular to slightly larger in size and elliptical in shape. The concentration of heat energy in the focal region produces quite high temperatures. The actual temperature of course depends on the absorbing characteristics of the material in the focal region. However, frying of meats, bacon eggs, etc. is accomplished as easily as on a conventional stove top. Adjustments of the lens need be made no more often than 30 minute intervals. At 10 to 15 minute intervals, the pot holder should be moved back to the center of the focal region. Reaction to previous concentrator designs has been that the cookers were awkward and even difficult to use. The ease of use of the Sundyne design is an important technical feature that can make a significant impact on market acceptance, and therefore its commercial feasibility.

Cost of the finished product was a primary consideration in the over-all design. All of the parts were designed to be made in presses. The lens quadrants are cold formed in a 400 ton hydraulic press. No machining is required in the manufacture of the parts. They can be assembled as stamped. The manufacturing plant is located in Manila in the Philippines, known as M.D. Juan Enterprises. The major output of the plant is body parts for jeeps and small buses that are an integral part of the public transportation system in Manila. The low cost of labor as well as materials in the Philippines produced a cost per unit that was about 25% of the best cost estimates we were able to obtain in the U.S. It was necessary to obtain a price as low as possible in order to serve a world market consisting of people in developing countries who still use wood as a cooking fuel.

The Sundyne Solar Cooker design was submitted to the National Institute of Science and Technology under its Energy Related Inventions Program for a review, and was recommended to the Dept of Energy as a candidate to receive a grant under its Energy Related Inventions Program. A grant was approved by the DOE for the purpose of making technical improvements to the design, and to do a world wide market analysis to identify areas in which the Cooker was needed, and to locate possible sources in those areas through which marketing could be accomplished.

Some 350 letters were sent world wide by Volunteers in Technical Assistance, A Washington D.C. nonprofit organization. Some 70 institutions or businesses have indicated an interest in promoting and distributing the Sundyne Cooker in their areas. The study is still ongoing and probably will not be complete until the end of summer.

Previous attempts to market concentrating solar cookers had not met with success for a variety of reasons, among which was the fact that cooking with the sun was not culturally acceptable. From these previous attempts, it was not possible to determine whether the customer resistance to solar cooking was related to the cooker design, or simply to a reluctance to use an untried method which replaced cooking over a wood fire. For this product, it was decided to select a population that was poor, that had traditionally used wood as a cooking fuel, and for which wood was a depleted source of fuel. Haiti was chosen as the location that met these criteria. The plan was to place 150 Sundyne Cookers with Haitians who were willing to participate in a 90 day user test. A marketing firm in Puerto Rico was selected to place the units and to monitor their use over a 90 day period. The units were placed about one month before the coup in Haiti. We received one report that all of the cookers were being used when weather permitted. Also that the users wished there was more than one potholder per unit, and that on cloudy days the performance of the cooker was poor. Apparently even on cloudy days there were enough parallel suns rays to provide some sort of focus. Generally though the response from the participants was positive. Then the U.S. placed an embargo on Haiti. No shipments in or out were allowed. Even mail was not permitted. We have had phone contact with our Haitian people conducting the survey, but there is no gasoline available to the non-military people, and our marketing people have not been able to get to the outlying areas where these cookers were placed. Since charcoal which had been imported from Jamaica is no longer available and firewood has not been available for some years, the cookers should be filling a real need.

One technical improvement that would be desirable, would be a replacement for the material from which the lens is made. The present lens is made from steel, painted, and an overlay of a vapor plated milar is applied as a reflective surface. The lens made up the greater portion of the 35 pound weight of the unit. An aluminum substitute for the steel would save 17 pounds of weight. The vapor plated Mylar

is responsible for nearly one third of the total manufacturing cost. As a solution to both the weight and cost problems, Alcoa Aluminum has developed a product marketed under the tradename "Everbrite". This product has one surface chemically polished and the polished surface is protected by a transparent anodized coating. The reflectance is 88% and the weathering performance is excellent. Under the grant, research has been done to cold form this material. After a considerable amount of effort, die modifications have been made to produce successful parts. A modification to the potholder design has been made to provide a screw adjustment for leveling the pot when the pot weight produced too much deflection in the potholder support. Also dies have been produced to size the tubing diameters in the rotary joints that are a part of the stand. All of these items have been completed this last month. We are hoping to display the new lens at this conference.

As a result of our effort in developing the Sundyne Solar Cooker over the last five years, we have developed criteria for the successful commercialization of the Solar Cooker. It is as follows:

There are four principal requirements for a solar cooker to be successfully introduced in an appropriate market.

1. The unit must be technologically satisfactory. It must be capable of providing solar energy at a sufficient rate, at the needed temperature, to cook the desired quantity of food.
2. It must be sturdy enough to withstand rough handling and to resist damage by natural hazards (such as wind) for the desired lifetime.
3. It must be socially acceptable and fit with the cooking and eating habits of the intended users.
4. It must be economically possible for the user to obtain a cooker at an affordable price.

Despite the variety of solar cookers available, the technology has not received widespread acceptance. The reasons for this lack of commercialization are generally attributed to failure to meet all of these criteria. It is believed that with appropriate designs, solar cookers may replace wood burning cookers, thereby saving energy and also reducing deforestation rates in many of the developing nations.

Submitted by John B. Long

KEY NO	PART NO	PART NAME
(24)	QA0011	SIGHTING TUBE
(23)	QA0010	HEXAGONAL BOLT 1/4"ØX
(22)	WB0004	WING BOLT
(21)	PH0005	POT HOLDER
(20)	PH0004	LOCK WASHER
(19)	PH0003	POT HOLDER POST
(18)	PH0002	SWIVEL ARM NO. 2 (6)
(17)	QA0009	HEX. NUT W/WASHER (
(16)	PH0001	SWIVEL ARM NO. 1 (6
(15)	WB0003	WING BOLT 1/4"ØX 1 1/2
(14)	QA0007	ROTATOR PLATE
(13)	QA0006	REFLECTOR NO. 1
(12)	QA0005	REFLECTOR NO. 2
(11)	QA0004	REFLECTOR NO. 3
(10)	QA0003	REFLECTOR NO. 4
(9)	QA0002	REFLECTOR NO. 5
(8)	QA0001	QUADRANT
(7)	SA0004	PIVOT BALL
(6)	QA0008	ANGLE STOPPER
(5)	SA0003	EXTENSION PIPE
(4)	WB0002	WING BOLT 1/4"ØX 1'
(3)	WB0001	WING BOLT 1/4"ØX 5
(2)	SA0002	LEG HOLDER
(1)	SA0001	LEG

SUNDYNE SOLAR COOKER PARTS DRAWING

**DATE
FILMED**
12/23/92