DOE/PC/89764--T6

RECEIVED
USDCE/PETC

November 19, 1989

89 NOV 24 AM 7:29

RE: DOE-PETC Grant No. DE-FG22-89PC89764,

"Permeability Changes in Coal Resulting from Gas Desorption"

2 years: August 16, 1989 - August 15, 1991

Principal Investigator: Jeffrey R. Levine

Co-Principal Investigator: Frank Tsay

Participating Faculty: Duk-Won Park

DOE/PC/89764--T6

DE92 019734

FIRST QUARTERLY REPORT: 8/16/89 - 11/15/89

Copy 1 of 7:

Sayeed Akhtar
PM-40, MS922-206
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Copy 2 of 7:

→ Cynthia Y. Mitchell
Contract Specialist
AD-22, 921-165
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Copy 3 of 7:

Kay Downey
Office of Technology Transfer
Mail Stop 58-M217
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Copy 4 of 7:

Johnny M. Rogers, Director
Office for Sponsored Programs
The University of Alabama
Box 870104
Tuscaloosa, Alabama 35487-0104

Copy 5 of 7:

Jeffrey R. Levine
Department of Geology
The University of Alabama
P.O. Box 1945
Tuscaloosa, Alabama 35487

Copy 6 of 7:

Frank M. Tsay
Department of Mineral Engineering
The University of Alabama
P.O. Box 870207
Tuscaloosa, Alabama 35487-0207

Copy 7 of 7:

Duk-Won Park
Department of Mineral Engineering
The University of Alabama
P.O. Box 870207
Tuscaloosa, Alabama 35487-0207

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

"Permeability Changes in Coal Resulting from Gas Desorption"

Quarterly Report:

8/16/89 - 11/15/89

PROJECT OBJECTIVES

To test the hypothesis that the desorption of gases (particularly methane) from coal results in shrinkage of the coal matrix, bringing about a net increase in permeability.

This project has been subdivided into 5 component tasks:

- 1) Sample Collection, Specimen Preparation, and Compositional Characterization
- 2) Physical Strength Testing
- 3) Determination of Sorption/Desorption Isotherms
- 4) Experimental Measurement of Swelling and Shrinkage of Coal Specimens during Sorption and Desorption
- 5) Experimental Measurement of Changes in Permeability to Gas Flow during Sorption and Desorption

MAJOR ACCOMPLISHMENTS.

Task 1 (Sampling, Specimen Preparation, Characterization):

Sampling: Several blocks of a coal have been procured from the Jim Walter Resources No. 7 coal mine in the Black Warrior basin, Alabama. These samples will be used to develop analytical methods and specimen preparation procedures, particularly in the preparation of "powder pack" samples for permeability testing and cores for other tests. Only moderate care has been taken to protect the compositional integrity of these coal samples.

The p.i. (Levine) has collected 7 blocks of coal from the Colchester (No. 2) coal bed and the Springfield (No. 5) coal bed, in the northwestern part of the Illinois basin, west of Peoria, Illinois. These coals are of high volatile C bituminous rank, which is lower rank than coals in the

Black Warrior basin. The Illinois samples will provide an essential element in a sample suite covering the bituminous rank series.

Samples were collected from an active working faces of two surface mines and were as fresh as possible. In order to protect the coal from oxidation and desiccation, the samples were triple-wrapped in cellophane, enclosed in "zip-lock" bags, and placed in air-tight plastic buckets in the field. Once returned to the laboratory, the samples were unwrapped, cleaned, labeled, and immersed in water in air-tight buckets where they will be stored until ready for further work.

Sampling Procedure: This project requires a carefully coordinated sample preparation procedure that will ensure that specimens of the proper size and physical characteristics are available for the various measurement methods used. The proposed sampling scheme is preliminary. It will certainly be modified according to our needs during the course of the project.

Coal is comprised of sedimentary layers or bands termed "lithotypes", reflecting variations in 1) the maceral composition of the organic matter and 2) in the relative proportion mineral matter present. Inasmuch as one of our research goals is to compare the behavior of different lithotypes, the sampling method must allow for several specimens to be collected from the same lithotype band, so that results from different project components can be compared.

Coherent blocks of coal will be collected in the field, with subsamples being removed in the lab by 1"-diameter core drill. At least 5 separate cores will be drilled from each block. Coal blocks sampled in the field will be approximately 10" X 10" X 6". Coal blocks must be reasonably coherent. Ideally they should be broken to expose a planar bedding surface on the top and bottom faces. The sides will probably be broken along cleat surfaces.

Distinctive compositional lithologies should be selected for sampling. For example, a section of the seam containing particularly thick vitrain or durain bands might be selected; or the block might include a mineral matter rich layer. If necessary, several blocks should be selected to represent a range in compositions.

Sampling procedure must include a method for retaining moisture. The sample must not be allowed to dry out. Exposure to atmospheric oxygen should be limited as much as possible. The samples must carefully packed for shipment so as to preserve their integrity.

Subsamples for analysis will be removed from the main sample by drilling in the lab with a 1"-diameter diamond core bit. Present anticipated needs indicate that 5 cores will be required:

Core: Preparation:

- 1 Careful coring. Preparation of coherent, perfectly cylindrical samples will be very difficult. Perhaps lathe preparation will be required
- 2 Careful coring, as above
- 3 Careful core drilling or cutting by diamond saw
(It is possible, and perhaps preferable that these tests be done on rectangular (polished) blocks of coal rather than on cylindrical specimens.)
Strain gauges will be affixed parallel and perpendicular to bedding. Several pairs of gauges will be affixed to each core, on different lithotype bands.

Test or Analysis:

- Permeability testing in triaxial load cell
- Uniaxial strength testing to determine Poisson's ratio and Young's modulus
- Sorption-related strain measurements using strain gauges in high pressure chamber.

- 4 Careful core drilling, followed by cutting with diamond saw. Sample must be coherent, but need not be perfectly cylindrical. Sample will be painted with epoxy resin to maintain integrity, then cut into two halves along its axis with a diamond saw.

Petrographic analysis,
including:

(Polished block:)
One half will be impregnated with fluorescent epoxy, then polished; to be used for:

- lithotype analysis
- microlithotype analysis
- cleat study

(Particulate pellets:)
The other half of each core will be divided into segments corresponding to the lithologic bands studied in the sorption-strain experiments. Samples will then be ground in mortar and pestle to pass a 20 mesh sieve, mounted in 1"-diameter epoxy pellets, then polished; to be used for:

- vitrinite reflectance
- maceral analysis

- 5 Core drilling. Sample need not be coherent, since it will be ground to a powder. However, the core may be divided into segments corresponding to lithologic bands designated above.

Analyses on particulate coal:

After division, the coal will be very coarsely ground, to be used for:

- powder pack permeability experiment

followed by fine grinding to pass a 60 mesh sieve, to be used for:

- Chemical analyses:
proximate,
ultimate,
BTU

as well as for:

- gravimetric sorption studies

Labeling Procedure: The following labeling scheme be used to designate samples. While the sample labels are long and somewhat cumbersome, they contain a great deal of information that will help us to stay organized.

Samples will be given a number of the following form:

ST-SI-CB-SN-CN-SS

where:

ST - signifies the state where the sample came from. We expect samples from at least:

AL - Alabama
CO - Colorado
NM - New Mexico
IL - Illinois

SI - signifies a sampling site or locality, e.g. JW4 might signify Jim Walter Resources #4 mine

CB - signifies the coal bed from which the sample was collected, e.g. BC would signify Blue Creek, or S5 the Springfield (#5) coal bed in Illinois

SN - signifies the sample block number from that particular site

CN - signifies the core number drilled from a particular block, and

SS - signifies a subsample removed from a particular core

Major Accomplishments, Task 2 (Physical Strength Testing):
No progress to date.

Major Accomplishments, Task 3 (Sorption Isotherms):

The laboratory apparatus (a high pressure TGA) that was to have been used for sorption studies for this project was unexpectedly removed this past summer from the University lab where it had resided for several years. We are currently completing arrangements to have the equipment returned to the University for use in this project. Current arrangements call for the equipment to be loaned by the U.S. Bureau of Mines Tuscaloosa Research Station to DOE-PETC, who will in turn loan the equipment to the University of Alabama.

Major Accomplishments, Task 4 (Measurement of Swelling and Shrinkage):

The goal of this task is to accurately measure the elongation and shrinkage exhibited by coal as it sorbs and desorbs methane gas at elevated pressure. Our research group has discussed several possible methods to measure this strain, including: optical microscopy, laser interferometry, conventional strain gauges, and LVDT strain gauges. There are advantages and disadvantages of each method. We had planned to use optical microscopy, but on further investigation, but this approach will be less satisfactory than the strain gauge method. Accordingly, we have switched our focus to the use of strain gauges. Conventional strain gauges also involve potential problems which must be overcome, including: 1) Contrast in strength between the coal and the strain gauge must be minimized, 2) The proper glue that is either too strong or too weak must be used to affix the strain gauge to the coal or the strain in the coal will not be accurately transmitted to the gauge, and 3) We must be aware that the total strain in the coal may not be homogeneously distributed through the specimen (due either to boundary effects or contrast in composition of the coal layers).

A high pressure chamber for sorption-strain experiments is currently being tested and modified and tested. The chamber will accommodate several small blocks of coal simultaneously. This will optimize efficiency, owing to the long times required to reequilibrate the coal blocks to changes in methane pressure.

Constant temperature and relative humidity will be maintained during the experiments. Various aqueous salt solutions will be placed in the vessel to maintain a constant relative humidity, so as to preserve the moisture content of the coal samples. Tests will be conducted at several different levels of moisture saturation. Several of the salts that may be used are listed in Table 1.

Bands of differing petrographic composition will be selected for testing. Pairs of strain gauges will be affixed to the coal samples parallel to and perpendicular to sedimentary banding. Wiring for strain gauges, temperature and relative humidity sensors will be passed out of the pressure vessel via a high pressure fitting.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Table 1. Approximate Relative Humidities of Salt Solutions
@30°C

<u>Saturated Solution:</u>	<u>Approximate Relative Humidity:</u>
Drierite	0%
LiCl	12%
K-Acetate	20%
K ₂ CO ₃	44%
NH ₄ NO ₃	60%
NaCl	75%
KCl ("recrystallized")	79%
KCl (A.R.)	82%
BaCl ₂	88%
KNO ₃	91%
Na-tartrate	91%
K ₂ SO ₄	96%

Major Accomplishments, Task 5 (Permeability Testing):

1. Completed construction of core flood control panel for pressure regulation and measurement, and flow rate metering for coal powder pack and solid coal assembly.
- 2) Completed construction of coal powder pack core holder, several test runs have been conducted to develop standard testing procedures.
- 3) Completed cleaning and repairing of the tri-axial core holder for solid coal plug flooding.
- 4) Completed collection of catalogs for digital pressure gauges, pressure regulators, and mass flow meters and controllers. Purchase of new equipment is in progress.
- 5) Initiated the preliminary stage of coal sample collections. Study of the standard procedures for testing and preparation of samples is in progress.

END

**DATE
FILMED**

10 / 26 / 92