SINGLE PASS COLLIDER MEMO

CN- 172-R1

AUTHOR: Rae Stiening

DATE: 7/12/84

REPLACES CN# 172

TITLE: LINAC QUADRUPOLE CONNECTIONS

SLAC-CN--172-R1

DE84 014694

Linac type QC and QCH quadrupoles are mounted on the accelerator with their power connection side facing the injector. The connections are on the top of the magnet. The following picture describes a horizontally focusing quadrupole for electrons:

This is the correct polarity for magnets with a "+" sign before their strength given in the tables of CN-151.

The magnetic centers of all magnets are measured. If the magnetic center is above the geometric center, the distance δy is positive. If the magnetic center is to the right of the geometric center, the distance δx is positive. (To the right is in the direction of San Jose). Why?

All quadrupoles have the white power lead attached to the San Francisco side and the black power lead attached to the San Jose side. Then, at the power supply in the alcove:

WHITE + BLACK - : HORIZONTAL FOCUS/ELECTRONS

WHITE - BLACK + : VERTICAL FOCUS/ELECTRONS

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NOTICE
PORTIONS OF THIS REPORT ARE ILLEGIBLE. It
has been reproduced from the best available
copy to permit the broadest possible avail-
ability.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

HF quadrupole for ELECTRONS

HD quadrupole for ELECTRONS

Fig. 1. Sketch of power connections for type QC and QCH quadrupoles. The +/- signs at the terminals indicate the direction of current flow. The white/black color refers to the color of the insulation of the wire connecting the magnet to the power supply.

HF quadrupole for ELECTRONS

HD quadrupole for ELECTRONS

Fig. 2. Sketch of power connections for type QW quadrupoles. The +/- signs at the terminals indicate the direction of current flow. The white/black color refers to the color of the insulation of the wire connecting the magnet to the power supply.

1. Type QC and QCH Quadrupoles. These magnets are mounted on the accelerator with the power connections on the west side (the side facing the injector). The connections are on the top of the magnet as shown in Fig. 1.

2. Type QN Quadrupoles. These magnets are mounted on the accelerator with the power connections on the west side. The connections are on the top-north edge of this face as shown in Fig. 2.

3. Polarity of Quadrupoles. A quadrupole that focuses electrons in the horizontal plane is an "F" quadrupole and has a "+" strength. Likewise a quadrupole that defocuses electrons in the horizontal plane is a "D" quadrupole and has a "-" strength.

4. Color Code. Regardless of the polarity of a quadrupole (F or D) the power lead of a given color (white or black) is always attached to the same geometric terminal as illustrated in the figures. Then at the power supply the connections are as follows:

Polarity of Quad	Color of Wire	Polarity of PS
HF	White	+
HF	Black	-
HD	White	-
HD	Black	+

5. Alignment Data Sign Conventions. When the magnetic center of a quad is above the geometric center, the distance dy is positive. When the magnetic center is to the south of the geometric center, the distance dx is reported by the precision alignment group as positive (whereas in the SLC convention this same distance would be negative).

6. Reference. Additional information can be found in the SLCHelp file under UNITS_AND_NAMES.