OAK RIDGE NATIONAL LABORATORY

OPERATED BY MARTIN MARIETTA ENERGY SYSTEMS, INC.
POST OFFICE BOX 2008, OAK RIDGE, TENNESSEE 37831-6285

ORNL

FOREIGN TRIP REPORT

ORNL/FTR-3736

DATE: September 13, 1990

SUBJECT: Report of Foreign Travel of C. D. West, ANS Project Office

TO: Alvin W. Trivelpiece

FROM: C. D. West

PURPOSE: The purpose of this journey was to learn from Interatom, the organization responsible for the design and safety analysis of the only new high performance research reactor project besides ANS; to present an invited paper at the Seventh ASTM-Euratom Symposium on Reactor Dosimetry; and to learn from researchers at the Kernforschungszentrum Karlsruhe who were pioneers in concepts for ultra-high flux research reactors, and who are experts on the ex-reactor measurement of materials irradiation effects.

SITES

VISITED: Interatom GmbH, Bergisch Gladbach, F. R. Germany
Palais de l'Europe, Strasbourg, France
Kernforschungszentrum, Karlsruhe, F. R. Germany

ABSTRACT: The lead in most aspects of research reactor design and use passed from the U.S.A. about 15 years ago, soon after the construction of the HFIR and HFBR. The Europeans have consistently upgraded and improved their existing facilities and have built new ones including the HFR at Grenoble and ORPHEE at Saclay. They studied ultra-high flux concepts ($\sim 10^{20}/\text{m}^2 \cdot \text{s}^{-1}$) about 10 years ago, and are in the design phase of a new, highly efficient medium flux reactor to be built at Garching, near Munich in Germany.

I visited Interatom, the firm - the equivalent of the Architect/ Engineer for the ANS project - responsible, under contract to the Technical University of Munich, for the new Munich reactor design. There are many similarities to the ANS design, and we reviewed and discussed technical and safety aspects of the two reactors. I specifically asked for, and will probably receive, some new, hitherto proprietary, experimental data on reactor thermal hydraulics and cooling that will be very valuable to the ANS project. I presented a seminar on the ANS project.

MASTER

DISTRIBUTION OF THIS REPORT IS UNLIMITED

The seventh ASTM/EURATOM Reactor Dosimetry Symposium was well attended. I had been invited to present a paper on the ANS, as the ASTM Program Committee for the symposium recognized that such a reactor will call for new or improved dosimetry techniques. Following the presentation, the session chairman approached me and proposed that a special session be set aside at the eighth symposium (to be held in the U.S. in 1992) to provide input and recommendations on responsibilities and techniques for dosimetry at the ANS facility; I accepted the idea enthusiastically, of course, and will pursue the issue further with him.

I also visited the Kernforschungszentrum Karlsruhe and learned from Dr. Kuchle, a true pioneer of ultra-high flux reactor concepts, of their work. Dr Kuchle kindly reviewed the ANS reference core and cooling system design (with favorable conclusions). I then talked with researchers working on materials irradiation damage and activation of structural materials by neutron irradiation, both key issues for the ANS. I was shown some new techniques they have developed for testing materials irradiation effects at high fluences, in a short time, using accelerated particle beams.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

1. INTERATOM GmbH, BENSBERG, F. R. GERMANY

I first met with the manager of the research plants and facilities department, Dr. Roegler. Interatom is primarily a nuclear company. They are strong in the gas-cooled reactor field, have recently begun a large new experiment on natural convection cooling in liquid metal systems, were responsible for the new Indonesian research reactor that went critical last year, and are currently the design and safety team for the new FRM-II reactor project at Munich.

As part of their work on research reactors, Interatom and their collaborators have generated new data on the thermal-hydraulic performance of narrow, rectangular cooling channels. Interatom have assembled all these data into a single electronic data base. To repeat the collection would take us 2-3 man months of effort (at a cost of approximately \$30,000). I discussed with Interatom staff the possibility of getting a copy of that data tape for our use; one of the key people involved was not present (my visit had been rescheduled at short notice), but I believe that they will agree to share the data with us when their internal discussions are complete.

The Interatom designers working in the FRM-II project are very experienced, and so their attendance, comments and questions at my seminar on the ANS reactor design gave valuable insight into issues that might be raised by future review or licensing committees. They apparently feel that the new ANS cooling system layout is a strong design. I was cautioned about the temptation to introduce potentially expensive safety features (such as main and decay heat exchangers in series and submerged components in the cooling system) that may really add only a little to safety margins; the ANS project in fact addresses exactly that temptation (as well as others) by the early use of probabilistic risk assessment (PRA), which apparently the FRM-II group have not yet done. A reservation was expressed about our reference core pressure boundary tube (CPBT) design, which involves bolted flanges. The reservation concerned the difficulty of accurately calculating the stresses arising from differential movement of the CPBT and reflector tank. This question was addressed during the ANS workshop that led to selection of the bolted flange reference design, and clearly we must carefully and explicitly document the issue for future reviews.

Anton Axmann, Director of the BER-II reactor at the Hahn-Meitner Institute in Berlin, was present and gave me information about their new upgrade of the BER-II. The upgrade (in which Interatom were heavily involved) was aimed at the increasing the thermal neutron beam flux by a factor of 10 and the cold neutron flux by a factor of 130. It was also aimed at bringing the safety systems to present-day requirements. The main features of the upgrade are:

- an increase of power from 5 MW to 10 MW
- a reduction of core size to 7 x 6 MTR fuel elements
- installation of a 300-mm thick beryllium reflector

- installation of a supercritical hydrogen cold source
- complete renewal/replacement of the reactor control and safety system, the emergency power system, and the fire protection system
- installation of double valves on all containment penetrations
- strengthening the pool against loss of water

The upgrade and refurbishment was completed last year, but the license to restart has not yet been granted. The Berlin Senate voted in favor of licensing the reactor, but even so the environment minister in the coalition Berlin government (a member of the Green Party) refused to sign off. Federal intervention seems to be almost the only remaining hope for them, but is not certain.

Strasbourg, France

The Seventh ASTM-EURATOM Symposium on Reactor Dosimetry involved six oral sessions, three workshops and a workshop summary session, and two poster sessions. Much information was exchanged.

Proposals have been made, especially by the Japanese, that the ANS should include a facility for boron neutron capture therapy (BNCT) of brain tumors. BNCT uses epithermal neutrons that penetrate fairly deeply into the brain before thermalizing to an energy at which they can be captured by ^{10}B that has been absorbed by the cells; the energy released by the $n - ^{10}\text{B}$ reaction destroys the cancer cells.

A BNCT facility must, therefore, provide a filtered and collimated beam of epithermal neutrons, with an acceptably low-high energy background. The Joint Research Centre (JRC), a European community reactor facility in the Netherlands, is carrying out very thorough design studies - as a collaborative West European venture - on such a facility. I was able to spend some time with staff of this project and to get copies of their most recent report. The studies involve both analytical work and experiments on the HB7 beam line at the 45 MW Petten reactor. A substantial effort was involved - ten people from four different organizations have worked for almost two years so far. The methods and the results will be directly useful to the ANS designers if a BNCT facility is to be considered.

I also got a copy of a report, from the Technical Research Center of Finland, on the use of personal computers for the conversion of neutron spectra and cross sections. Depending on the neutronics calculations being performed, one needs to convert the measured cross section points into average or effective cross sections in various energy ranges. The ANS project has performed many such operations while studying the reactor and cold source performance and will need to perform many more as the design evolves. The use of a PC rather than a main-frame, with a more user friendly and less expensive environment, may benefit the project significantly.

My ANS overview paper was received with interest and aroused many questions. The neutronic characteristics of the ANS reactor - a small, undermoderated, high-powered core in a low-loss reflector - lead inevitably to steep gradients in the neutron flux and spectrum and to a rather time-dependent spectrum near the core. At the same time analysis of materials irradiation experiments, and evaluation of radiation damage to the reactor structural materials, will require accurate and reliable dosimetry. In addition, the essence of the neutron beam facilities is flexibility and accessibility; thus, personnel dosimetry is also important. These issues should be debated early in the ANS design process by knowledgeable people, including especially the community represented at this symposium.

Afterwards, the U.S. chairman of the session (Professor J. Williams from the University of Illinois and the ASTM Programme Vice-chairman for the symposium) discussed with me the possibility of devoting some time at the eighth symposium to consideration of techniques and responsibilities for dosimetry at the ANS. We agreed that, with some preparatory work, a workshop session would be an appropriate and effective way to get guidance and input. I believe that this initiative will help address a very important issue in a timely way and involve the right expert groups.

Kernforschungszentrum, Karlsruhe

This is a leading "National Laboratory" in the Federal Republic of Germany, having a heavy emphasis on fission reactor performance and safety, with substantial fusion and basic research programs as well. I spent the whole of Labor Day there.

I met first with Dr. Kuchle, a very well respected reactor design engineer who worked in the 1970's on various concepts for high-flux and high-efficiency reactors. He and his colleagues have been following the progress of the ANS through our published work and their contacts at Interatom.

We discussed the ANS core design in some detail. Dr. Kuchle said that he thought our new reference design, the offset split core combining a short heated length with an effectively greater neutronic length, a great improvement over the earlier version. In particular, he felt that the older design had insufficient thermal-hydraulic margins, that is, too high a power density (so did we; that was the reason for the change). He also told me that he had proposed a similar offset core design for an ultra-high flux reactor, many years ago; unfortunately, the idea remained in his notebook and was never published. Nevertheless, Dr. Kuchle's independent, and earlier, consideration of the idea provides some additional reassurance of its basic soundness.

At and after lunch, I met with Dr. Cierjacks. My contact with him in the first place was through his preparation, for Nuclear Energy Agency on Nuclear Data Computing (NEANDC), of a list of new and proposed

reactor facilities. His main work now concerns activation products in fusion reactor materials and, of course, the same calculational techniques apply to activation studies for the ANS. Dr. Cierjacks told me that in Europe, political figures are just beginning to ask a deceptively simple question about fusion power: "What waste would be generated by a fusion power station?". The calculations of activation product inventory are surprisingly difficult, he told me, and simple calculations are usually wrong by several orders of magnitude. Near the plasma, the neutron flux is high enough that multiple neutron absorption chains are probable; the rate of creation, and destruction, of activation products is therefore both a highly nonlinear function of neutron flux and extremely sensitive to the exact neutron cross sections of the structural materials. Unfortunately, a complete calculation for all likely construction materials requires hundreds of chains to be considered, and for many of the reactions the cross sections are not, in fact, known well enough. All of these remarks will apply to ANS structures near the core as well, except that fewer materials need to be considered (because of ASME code requirements on fission reactor materials).

Dr. Cierjacks believes that the answer to the political question is that, at the moment it is switched off, the fusion reactor would actually have about the same radioactive inventory as a fusion reactor (although of different nuclides, of course). Furthermore, only one or two materials (e.g. vanadium) will decay to "hands on" levels of surface radiation in less than a few centuries; and even those materials would have to be pure to the ppm level, to avoid higher radiation levels from the activated impurities than from the base material. His work in this field is integrated with other European programs, including NET and ITER.

I then visited the cyclotron facility. They have two machines, one old one (built by AEG in 1964) and one more modern one (1983). The facility is very impressive, with good housekeeping and a general air of pride. They are doing some exciting work, including work on radiation damage effects.

They use two beams, one from each cyclotron, to study damage effects with a variable ratio of atomic displacement to helium deposition (e.g. for fusion materials research). One beam, of protons, is energetic enough to pass through the specimens, simulating displacement damage by fast neutrons. The other beam, of alpha particles, has an energy that allows it to penetrate into, but stop inside, the specimens, thus forming helium. Such work has been done elsewhere, including ORNL, but I believe that Karlsruhe is the only place that is able to apply independently controllable alpha and proton beams simultaneously, by using beams from their two cyclotrons. The two independent beam lines are combined a short distance before the sample. After irradiation, the samples are tested - e.g. mechanically - in the usual way. As a new capability, they have almost finished building a new apparatus that will allow them to carry out fatigue testing during the actual dual-beam irradiation.

The newer cyclotron is also used for isotope production, mainly for medical use, which is a very business-like operation. They make a production run on most days - actually, at night so that the isotopes, or isotope generators, can be taken to hospitals all over Europe for use when the working day begins.

They also use the cyclotron to measure (by creating a precise but thin layer of a radioactive label) wear and corrosion. This is a service sold to industry including the automobile industry.

Reports and Papers Received

"The BER II Upgrade" A. Axmann, H. Bucholz, H. Krohn, and C. O. Fischer

"Fallout Hits Research" Steven Dickman (an article in Nature about the BER II licensing problem)

"PC Programs for the Conversion of Neutron Spectra and Cross Sections Between Different Group and Point Representations" by Tom Serén

"Progress in Neutron Beam Development at the HFR-Petten (Feasibility Study for a BNCT Facility)" G. Constantine et al

"A Review of the Development of a Luggage Explosive Detection System" (abstract) J. Bartko

"Calibration and Intercomparison Efforts for Neutron Fluence Monitoring", D. W. Vehar

"-RTM- Wear and Corrosion Diagnostics for Industrial and Research Applications" Kernforschungszentrum Karlsruhe

"Die Karlsruher Zyklotrone" Kernforschungszentrum Karlsruhe

Appendix

ITINERARY

August 22-23, 1990	Travel from Washington, D.C. to Bergisch Gladbach, FRG, by plane and by car
August 24, 1990	Interatom GmbH, Bergisch Gladbach, FRG Dr. H-J Roegler Dr. H. Reutler Prof. A. Axmann
August 27, 1990	Travel from Bergisch Gladbach, FRG, to Strasbourg, France, by train
August 27-31, 1990	Seventh ASTM-EURATOM Symposium on Reactor Dosimetry, Strasbourg, France
August 31, 1990	Travel from Strasbourg, France to Karlsruhe, FRG, by train
September 3, 1990	Kernforschungszentrum, Karlsruhe Dr. M. Kuchle Dr. S. Cierjacks Dr. V. Bechtold
September 4, 1990	Travel from Karlsruhe, FRG to Knoxville, TN, by train and by plane

1. John J. Easton, Jr., Assistant Secretary for International Affairs and Energy Emergencies (IE-1), DOE, Washington, D.C.
2. Donald K. Stevens, Associate Director for Basic Energy Sciences, Office of Energy Research, ER-10, DOE, Washington, D.C.
3. I. L. Thomas, Director, Division of Materials Sciences, Office of Energy Research, ER-13, DOE, Washington, D.C.
4. B. Chalmers Frazer, Division of Materials Sciences, Office of Energy Research, ER-132, DOE, Washington, D.C.
5. J. A. Reafsnyder, Assistant Manager, Energy Research and Development, DOE/ORO
6. D. J. Cook, Director, Safeguards and Security, DOE/ORO
- 7-8. Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831
9. Ray A. Hunter, Director, Office of Facilities, Fuel Cycle/ Test Programs, DOE, NE-47, 19901 Germantown, MD 20874
10. Carl R. Klee, Division of Energy Research Reactors, Office of Nuclear Energy, NE-473, DOE, Washington, D.C.
11. Manfred Leiser, Division of Materials Sciences, Office of Energy Research, ER-132, DOE, Washington, D.C.
10. C. D. West
11. A. W. Trivelpiece
12. B. R. Appleton
13. W. Fulkerson
14. R. M. Harrington
15. J. B. Hayter
16. B. H. Montgomery
17. F. J. Peretz
18. D. L. Selby
19. P. B. Thompson
20. K. R. Thoms
21. A. Zucker
- 22-23. Laboratory Records Department
24. Laboratory Records - RC
25. Laboratory Protection Division
26. ORNL Patent Section
27. ORNL Public Relations Office

END

DATE FILMED

10 / 24 / 90