Progress Report for

DOE/ER/40302--7

DE93 004600

Chaotic Dynamics in Accelerator Physics

John R. Cary

Principal Investigator

Department of Astrophysical, Planetary, and Atmospheric Sciences

University of Colorado

Boulder, CO 80309-0391

November 30, 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Co

Abstract

We have made substantial progress in several areas of accelerator dynamics. For developing understanding of longitudinal adiabatic dynamics, and for creating efficiency enhancements of recirculating free-electron lasers, we have substantially completed a design of an FEL wiggler with adiabatic trapping and detrapping sections. We have developed a computer code for analyzing the critical KAM tori that bound the dynamic aperture in circular machines. We have begun studies of modes that arise due to the interaction of coasting beams with a narrow-spectrum impedance. During this research we have strengthened our educational and research ties with the accelerator community at large.

Table of Contents

Abstract	ii
I. Introduction.....	1
II. Spatial adiabatic trapping and emittance growth due to separatrix crossing: applications to free-electron lasers	7
A. Background and Accomplishments.....	7
B. Recent Accomplishments	9
1. Design Goals and Constraints	10
2. Dynamical Model and Simulations	12
III. Determination of integrable accelerator transport systems.....	17
A. Background	17
B. Accomplishments.....	18
IV. Excitation of cavity modes by coasting beams.....	20
V. Education.....	23
VI. Contacts with the accelerator community.....	24
VII. References	25
Appendix A: Particle Dynamics in a Large-Amplitude Wave Packet	
Appendix B: Adiabatic Particle Motion in Slowly Varying Wave Structures	
Appendix C: Lyapunov exponents in a field of many randomly phased waves	

Reprints + Preprints removed

I. Introduction

In the last year of our program on accelerator dynamics we have made progress in several areas. We have developed a design for a free-electron laser that has adiabatic trapping and detrapping sections in the wiggler so that transport through this wiggler leads to less emittance increase than is the case for standard wigglers. We have started our development of a computer code for analyzing transport in circular machines. This code, currently only having one transverse degree of freedom, is capable of finding the fixed points that determine the dynamic aperture. We have begun work on BGK modes for coasting beams that arise in the coupling of the beam to a narrow-band impedance. We have continued our work on determining whether tracking data can be modeled by a diffusion equation and our work to understand Lyapunov exponents in strongly chaotic systems.

Our efforts in previous years led to several advances in the field of the dynamics of particles in accelerators. We derived the adiabatic invariant for accelerating structures with slow spatial variation.¹⁻³ This invariant is useful for understanding trapping in, e.g., radiofrequency quadrupoles and free-electron lasers. We further analyzed the loss of the adiabatic invariant due to the trapping process (separatrix crossing) in spatially varying systems.¹ We also developed nonperturbative Hamilton-Jacobi methods for determining transverse invariants in nonlinear transport systems.⁴ These research efforts resulted in the training of two graduate students, David Bruhwiler and Bill Gabella, who are now working in the area of accelerator physics.

One work on the design of a free-electron laser experiment to test adiabatic trapping theory is a new direction – started this year. Separatrix crossing theory predicts that the emittance growth due to trapping in a free-electron laser can be greatly diminished by trapping adiabatically. This would be especially advantageous in a recirculating free-

electron laser, where the longitudinal emittance growth due to each interaction of the beam with the wiggler must be eliminated by cooling.⁵ Less cooling would be needed if adiabatic trapping were used.

A possible location for such an experiment would be at the Accelerator Test Facility⁶ at Brookhaven National Laboratory, where there is a high-brightness electron beam of energy up to 50 MeV. As there is also a CO₂ laser at this facility, only an appropriate wiggler would be needed. Preliminary considerations show that adiabatic trapping and detrapping wiggler can be made that would be of the order of 2 meters long.

With the arrival of Carson Chow as a postdoctoral research associate on this project, we began looking at the possibility of finding integrable nonlinear accelerator transport systems. Without constraints this is trivial – one simply constructs a system with only linear elements. But in a practical system this is not possible, because dipole magnets have associated nonlinearities. In addition, sextapole magnets are needed for chromaticity adjustment. Years ago we developed⁷ a method for finding integrable systems for another class of Hamiltonians, those that give flow along the magnetic field lines of external, toroidal, helical conductors. We believe that such methods will also apply to accelerator systems.

In the last year we developed a simple, one-transverse-degree-of-freedom tracking code for following trajectories through accelerator rings. Our code differs from previous in that we have added modules for finding fixed points, as the fixed points determine the integrability properties of an accelerator map: The work of Greene⁸ shows that the residues (a quantity of the tangent map that determines the rate of rotation or exponential divergence of nearby trajectories) of the fixed points with winding number near that of a given irrational number determine whether the KAM torus of that winding number exist. Existence provides a lower bound on the dynamic aperture of the system. Our code also

calculates the continued fraction expansion of a given trajectory. This is needed as the continued fraction expansion determines the correct nearby rationals to use in this analysis.

This year we, with Andrei Gerasimov of Fermilab, also began a project of determining the linear and nonlinear properties of modes that arise in the interaction of a coasting beam with a narrow-spectrum impedance. In the first part of this analysis we determined the linear stability of this system. We clearly identified the regimes of instability that correspond to the cold-beam and Landau limits of the interaction. Our results, properly generalized, will contribute to an understanding of multibunch instabilities. Next we began a study of the nonlinear state. So far our nonlinear studies rely on the beam acting as a single macroparticle. Here we derived a two-degree-of-freedom Hamiltonian governing the evolution of both the beam macroparticle and the cavity mode that yields the narrow-band impedance. Upon adding dissipation to the system, we find that the beam slows down. Yet it stays in resonance with the mode because the mode frequency decrease at the same time. These results may be relevant to *bucket coalescence*⁹ a manipulation of the Tevatron beam.

In addition to the above studies, which will be covered in more detail later in this progress report, we have continued other studies that we mention only here. These studies are of Lyapunov exponents in strongly chaotic systems, diffusion models for tracking data, and symplectic integration methods.

In strongly chaotic systems, previous researchers had shown the existence of enhancements of the diffusion coefficients at intermediate values of the nonlinearity parameter.¹⁰ These enhancements were often connected with accelerator modes - remnants of integrability in the chaotic system. However, this interpretation became suspect with our observations¹¹ of a diffusion enhancement even when the perturbations were randomly phased, so that correlations in the motion should not be present.

We have now added more evidence to the case that the diffusion enhancement in the randomly-phase case is not due to the appearance of integrable regions.¹² If it were, then the Lyapunov exponent would be expected to be smaller at values of the nonlinearity parameter where the diffusion enhancement is observed. Our numerical experiments did not find this. Where the diffusion enhancement is observed, the Lyapunov exponent is as large as it is in the chaotic limit.

Our research to model tracking data by a diffusive model has the goal of understanding whether simple chaotic diffusion underlies the results of tracking calculations. In the tracking calculations, particles are launched at various distances from the design orbit. On average the confinement time increases as the launch point of the particles is moved towards that of the design orbit. However, the confinement time is not unique, because trajectories launched at the same distance, but at different locations around the ring, have different confinement times. The presence of this statistical aspect leads one to believe that the loss may be described by a chaotic diffusion, as is the case in other dynamical systems. We have been developing a method for determining whether chaotic diffusion is consistent with SSC tracking data. We show that there is a consistency relation among the first three moments of the confinement time if the loss is describable by a diffusion equation. We are in the midst of developing computer codes to see whether this consistency relation is satisfied for the given tracking data.

The ultimate goal of this research is to seek a dynamical basis for the diffusion equation, as has been found in other cases. Such a dynamical basis would allow one to derive the diffusion coefficient. Use of the diffusion equation rather than tracking data would greatly decrease the computational requirements for accelerator simulation. Moreover, with an understanding of the basic process, methods for diminishing the chaotic loss might be found.

Finally we mention our work on symplectic integration schemes. This work has the goal of providing numerical methods for modeling Hamiltonian systems, with the methods preserving the long-term stability properties of the original system. We have developed and tested implicit integration schemes for arbitrary Hamiltonian systems. More recently we showed how such methods could be made explicit for self-consistent simulations of, e.g., the interaction of a beam with a cavity mode. A code has been developed and applied to a problem in plasma turbulence.¹³ We are now in the process of modifying this code for studies of accelerator modes.

To maintain strong ties between our university based accelerator research program and the accelerator research at the national laboratories and other universities, we have continued to maintain a high level of contact with the accelerator community. An example is this year's sabbatical of the principal investigator at Fermilab. This sabbatical enabled the P.I. to interact with the accelerator physicists of the Accelerator Physics group led by Steve Peggs. Since then one of the graduate students (Peter Stoltz) of this program has visited Fermilab to study modes of coasting beams with Andrei Gerasimov.

This research program has also been instrumental in training new accelerator physicists. As mentioned above, past funding allowed two graduate students to receive their Ph.D.'s in accelerator physics. At present, Peter Stoltz and Scott Hendrickson are carrying out the research for their Ph. D. theses. Both are likely to finish their theses in 2-3 years. The current funding also provides for the training of one postdoctoral fellow. This person, Carson Chow, completed his thesis in plasma physics and nonlinear dynamics. During his fellowship at the University of Colorado, Carson Chow has learned the techniques and jargon of accelerator physics while doing research in this area. All three of these researchers attended the school on accelerator physics in the summer of 1992.

In the following three sections we provide brief overviews of three areas of the

proposed research: design of free-electron laser wigglers with adiabatic trapping and detrapping sections, determination of integrable nonlinear transport systems, and modes arising from the interaction of a coasting beam with a narrow-band impedance. Section V discusses the educational aspects of this research program, while Sec. VI notes the contacts made between the present research group and the accelerator community at large. The appendices contain reports produced under past years of this research program.

II. Spatial adiabatic trapping and emittance growth due to separatrix crossing: applications to free-electron lasers

In previous years of this research project we developed the theory of spatial adiabaticity. We calculated the adiabatic invariant applying to the situation when an accelerating structure varies slowly in space rather than time. We also showed how to calculate the increase of emittance due to separatrix crossing. We are now designing experiments to test these analyses. Our calculations, both analytic and simulations, show that these tests could be carried out in a free-electron laser experiment at the Accelerator Test Facility at Brookhaven National Laboratory. If successful, such experiments would point to a way of designing a recirculating free-electron laser with diminished beam cooling requirements, as sufficiently adiabatic trapping gives arbitrarily small emittance increase.

A. Background and Accomplishments

For a Hamiltonian $H(q,p,\epsilon t)$ depending slowly on the time variable, the action,

$$I(E,\epsilon t) \equiv \oint p|_{H=E} dq, \quad (2.1)$$

the phase-space area enclosed by a closed contour of H at fixed time, is the adiabatic invariant. *Slowly* means that the particle executes many oscillations before the parameters of the Hamiltonian change significantly. Invariance of the action, $I(E_i, \epsilon t_i) = I(E_f, \epsilon t_f)$, allows one to solve for the energy at one time in terms of the energy at another time. Adiabatic theory has also been used to predict the phase-space area occupied by a beam adiabatically trapped in an accelerating potential.

In the early years of this line of research, we pioneered the theory of adiabaticity loss due to separatrix crossing in adiabatic systems. We review this theory first for the case of a Hamiltonian, $H(q,p,\epsilon t)$, with one degree of freedom and slow time-dependence,

i.e. small ϵ . Adiabatic invariance theory states as the contours of H change in the course of time, for small ϵ a given trajectory can always be found on a contour containing the same area as did the contour of the trajectory at the initial time. The requirement for ϵ is that it must be small compared with the orbit frequency ν_0 calculated by neglecting the change of the Hamiltonian function with time.

Unfortunately, adiabatic invariance breaks down for particles near the separatrix. (A separatrix is a contour of H containing an x-point, a saddle point, which is a fixed point of the dynamics for $\epsilon = 0$. Contours of a typical Hamiltonian with a separatrix are shown in Fig. 2.1.) This causes adiabatic invariance to break down in a large number of cases, because a separatrix can sweep across large regions of phase space in the course of time. For example, if the separatrix in Fig. 2.1 is growing in time, it collides with a trajectory in region-c at the time t_x given by $Y_c(\epsilon t_x) = J_i$, in which $Y_c(\epsilon t_x)$ is the area enclosed by the entire separatrix, and J_i is the initial value of the adiabatic invariant. This time t_x is called the pseudo-crossing time. In the vicinity of this time the adiabatic invariant is inapplicable.

Figure 2.1. Contours of a typical Hamiltonian with a separatrix.

We analyzed the consequences of crossing a separatrix in detail previously.¹⁴ It was found that the new value of the adiabatic invariant depends on the lobe of the separatrix into which the trajectory becomes trapped. For a trajectory becoming trapped into, say, lobe-a, (See Fig. 2.1) the new value of the adiabatic invariant, J_{fa} , is close to $Y_a(\epsilon t_x)$, the phase-space area enclosed by lobe-a of the separatrix at the pseudo-crossing time. The deviation, $\delta J_{fa}(M_c) \equiv J_{fa} - Y_a(\epsilon t_x)$, is found to depend on a crossing parameter M_c , which is related to the initial phase, or adiabatic angle, of the trajectory. This implies that an ensemble initially distributed on an adiabatic invariant ring, a single contour, is ultimately distributed throughout an adiabatic invariant annulus after a separatrix crossing. Thus, separatrix crossing leads to a spread of the adiabatic invariant.

More recently, we applied separatrix crossing theory to determine the heating that occurs in adiabatic trapping in an accelerating bucket.¹ We explicitly calculated the growth of emittance for a set of trajectories passing through accelerating fields with spatial variation. We showed, by comparison with direct numerical integration, that the analytic theory is accurate in the appropriate regime, i.e., when the typical synchrotron length is small compared with the scale length of the wavepacket.

B. Recent Accomplishments

We would now like to see if experimental tests of adiabatic trapping theory can be performed. Adiabatic theory predicts that the increase of longitudinal emittance of a beam in trapping process is proportional to the adiabaticity parameter. Our goal is to design an experiment to test adiabatic trapping theory based on our present understanding. Should such an experiment be built, it will give us information on the importance of other factors, such as transverse motion and experimental errors.

We choose to design experiments for a free-electron laser system. Such experiments would ultimately be useful if they did show a decrease in emittance growth, as

this would help in the design of recirculating free-electron lasers, where the smittance growth per pass must be kept small. Such experiments could be carried out at the Accelerator Test Facility (ATF) at Brookhaven National Laboratory, where there are both a high-power CO₂ laser and an electron linac capable of producing electrons with energies of five to 50 MeV. Combining these two items with an appropriate wiggler could produce a free-electron laser amplifier with a large ponderomotive potential and, hence, a synchrotron length sufficiently short that adiabatic trapping theory should apply. Thus, our calculations have been geared towards finding an experimental setup within the restrictions of available laser power and beam energy such that an adiabatic wiggler could be constructed.

1. Design Goals and Constraints

In a free-electron laser, an electron beam of relativistic factor γ passes through a spatially oscillating magnetic field of wavelength $\lambda_w \equiv 2\pi/k_w$. The strength of the magnetic field is represented by the dimensionless vector potential,

$$a_w = \frac{eB_w}{mk_w c^2}, \quad (2.2)$$

where $k_w \equiv 2\pi/\lambda_w$ and B_w is the peak wiggler field. If a laser of wavelength λ_s is present, ponderomotive potential buckets of wavenumber $k_s + k_w$, frequency ω_s , and, hence, phase velocity $v_\phi = \omega_s/(k_s + k_w)$, are produced. This potential is resonant with the electrons when¹⁵ the condition,

$$\gamma_\phi^2 = \lambda_w/\lambda_s, \quad (2.3)$$

is satisfied, where the reduced relativistic factor is given by

$$\gamma_\phi = \gamma(1 + \frac{1}{2}a_w^2)^{1/2} \quad (2.4)$$

for a linearly polarized wiggler.

If the electrons are trapped, and the wavelength λ_w and vector potential a_w change adiabatically (slow on a synchrotron length), the relations (2.3) and (2.4) remain satisfied. Then, by decreasing λ_w or a_w the electron relativistic factor can be decreased, and so energy is extracted from the electron beam. The energy lost by the electrons is gained by the laser beam.

The adiabaticity requirement is satisfied if the electrons execute many synchrotron-bounce oscillations in the distance the beam takes to slow down. The synchrotron-bounce wavenumber is given by

$$k_b^2 = k_s^2 a_w a_s \left(1 + \frac{1}{2} a_w^2\right) / 2 p_r^2 \gamma^2 = 2 k_w^2 a_w a_s \left(1 + \frac{1}{2} a_w^2\right) \gamma_\phi^4 / p_r^4 \quad (2.5)$$

where $a_s \equiv eA_s/mc^2$ is the dimensionless laser vector potential, and p_r , which satisfies

$$v_\phi = p_r / \sqrt{1 + \frac{1}{2} a_w^2 + p_r^2}, \quad (2.6)$$

is the resonant momentum. Thus, adiabaticity is satisfied when $\lambda_b \equiv 2\pi/k_b$, the synchrotron wavelength, is small compared with the characteristic length over which the system changes.

The same condition is required for adiabatic trapping. To satisfy this condition, we desire several synchrotron bounces over the trapping length μL of the wiggler. (We take a wiggler of length $2L$ going over $z = [-L, L]$ and with the field rising to full strength over the distance μL .) As γ_ϕ is typically close to p_r and a_w is typically order unity, the last expression (2.5) implies that we want large wiggler and laser fields, small wiggler wavelength, and a long system. Unfortunately, these requirements conspire against each

other. For the laser beam not to diverge in a long system, the beam must have a large waist. But a large waist causes the magnetic field on axis (which decays away from the polefaces as $1/\cosh(k_w r)$, where r is the laser-beam radius) to be small. Lengthening the wiggler wavelength to counteract this requires a longer system.

To see what is possible, we developed a spread sheet that calculates the various parameters of the free-electron laser. This spread sheet takes into account the dispersion of the laser beam, the decay of the wiggler field away from the pole faces and the finite parallel emittance of the electron beam. Our calculations show that the integrated number of synchrotron wavelengths,

$$N_b \equiv \frac{1}{2\pi} \int_{-L}^0 k_b dz \approx 0.62 \mu L / \lambda_{b \min}, \quad (2.7)$$

can be made as large as 4.1 in a 2 meter wiggler with 20kG at the polefaces, a 10GW CO₂ laser, and wiggler wavelength of 1.2cm.

2. Dynamical Model and Simulations

With our preliminary calculations giving approximately four synchrotron bounces per wiggler length, it was necessary to carry out numerical simulations of the trapping process, as analytic theories (developed for large N_b) are suspect for moderate N_b . Our simulations are, so far, one dimensional and not self-consistent, as we wish to address only the fundamental issue of whether adiabatic trapping can be obtained, and to what degree will it prevent heating of the beam.

In developing a one-dimensional model of electron dynamics we begin with the relativistic hamiltonian, $H = \sqrt{1 + (p - a)^2}$. (We choose units to have $m=c=e=1$.) Because the purpose is to study electron dynamics, we operate our FEL as an amplifier with the laser

power emitted by the electron beam small compared to the initial laser power. Therefore, we have the vector potentials,

$$a = a_w + a_s, \quad (2.8a)$$

$$a_w = \hat{y} a_{w0}(z) \sin\left(\int^z k_w dz\right), \quad (2.8b)$$

and

$$a_s = \hat{y} a_{s0}(z) \sin(k_s z - \omega_s t). \quad (2.8c)$$

We approximate the Hamiltonian via $a_s \ll 1$, $a_w \ll \gamma$, and $z = z_0 + \zeta$ with ζ small and z_0 defined implicitly as

$$t(z_0) = \int_{-L}^{z_0} dz_0' / v_\phi(z_0') \quad (2.9)$$

the lowest-order integrated position. We then arrive at the Hamiltonian,

$$K = \sqrt{1 + p^2 + \frac{1}{2} a_{w0}^2(z_0)} - v_\phi p + \frac{a_{w0}(z_0) a_{s0}(z_0) \sin(k_p \zeta - \omega_s t)}{2 \sqrt{1 + p^2 + \frac{1}{2} a_{w0}^2(z_0)}}. \quad (2.10)$$

We chose to integrate in the time domain, as we had more experience with this formalism. In the future we plan to use z for our independent variable as is more common in the free-electron laser literature. To complete the specification of the Hamiltonian, we define

$$a_{w0}(z) = a_w \max\left[1 + \sin(2\pi|z/\mu L|)/2\pi - |z/\mu L|\right]. \quad (2.22)$$

This profile minimizes the first and second derivatives of the field strength subject to the

restriction of a certain total change of a_{w0} .

We first carried out several simulations with constant k_w and varying a_w . These simulations found trapping efficiencies not as good as desired. From that point we carried out *constant-resonance* simulations. These are wigglers designed to have constant p_r . Allowing p_r to move up and down leads to inefficient trapping as particles are left behind by the moving bucket. Since k_s is constant, Eqs. (2.3) and (2.6) give the local wiggler wavelength as a function of the wiggler amplitude.

Our code, AdFEL, allows us to integrate particles through the wiggler with a variety of initial conditions and wiggler configurations. AdFEL uses an adaptive step size, 4th-order Runge Kutta integrator and records momentum and position along the wiggler. This code produces histograms of the final beam momenta for direct comparison with measurements.

Simulations are run with a warm beam of 300 electrons. The initial momentum spread of the beam is $\Delta p/p = 1\%$. Electrons are distributed uniformly along the wiggler, spanning two bucket lengths. We carried out simulations for wigglers with $N_b = 1, 2, 4$ and 8, but of constant total length. The variation of N_b was obtained by varying the fraction μ over which the wiggler grew to full amplitude. In the following simulations, the beam traps and detrays at constant resonance, so no energy is extracted from the beam.

Fig. 2.2 shows exit momenta from the simulations. The average exit momentum in each case is equal to the average launch momentum. The number labeled by P sig is σ_{pf} , the standard deviation of the momentum of the exit beam. This is a measure of the beam's final temperature.

Figure 2.2. Exit momenta profiles for adiabatic wigglers with $N_b=1, 2, 4$ and 8 .

This figure clearly shows that the beam heating is less with larger N_b .

In Fig. 2.5 we plot $h \equiv (\sigma_{pf} - \sigma_{pi}) / \sigma_{pi}$, where σ_{pi} is the initial beam temperature. Hence, h measures the relative heating of the beam. This plot shows a decrease in beam heating by a factor of 4 from $N=1$ wiggler configuration to $N=8$ wiggler configuration.

Figure 225. Relative beam heating verses adiabatic paramter N_b . The solid line is proportional to $1/N_b$.

Spacial adiabatic theory predicts that the beam heating goes like $1/N_b$ (the solid line in Fig. 2.5) at large N_b . The simulations do not agree with prediction. We expect this is due to not being in the asymptotic regime and/or the oscillations¹⁴ of the heating as a function of the adiabaticity parameter.

We have now carried out the preliminary simulations of our system. We are ready to proceed with detailed parameter studies to determine exactly how well we diminish beam heating in free-electron lasers.

III. Determination of integrable accelerator transport systems

A. Background

With the arrival of Carson Chow as postdoctoral fellow on this grant, we have begun our studies of integrable accelerator transport systems. Present accelerators are designed to be linear to as great a degree as possible. There are several reasons for designing for linearity, i.e., the independence of the betatron tune on the amplitude. Two of the reasons are that (1) linearity makes the prediction of the beam characteristics particularly simple, and (2) because the particles of the beam have the same tune, one can select an operating point for the accelerator that across the beam avoids low-order resonances with error fields, for example.

However, it is also possible to avoid the dangerous effects of the resonances by making the system strongly nonlinear. Resonances are dangerous when they produce islands in phase space sufficiently large to cause overlap. The result is¹⁶ chaos: the invariant curves are lost, and, correspondingly, the dynamic aperture is reduced. Large shear, i.e. dependence of tune on the amplitude, minimizes the island size for a given perturbing field. Thus, if one can design an integrable, nonlinear accelerator with large shear, one can also avoid the effects of resonances with error fields.

The standard approach of designing accelerators without shear has an analog in fusion machines. The Garching stellarator experiment¹⁷ is designed so that the *rotational transform*, the stellarator equivalent of tune, has no shear. The second approach also has an analog in stellarators. One example is the ATF stellarator¹⁸ at Oak Ridge National Laboratory, which is designed with large shear at the edge to provide stability against fields produced by winding errors and instabilities. Indeed, the vast majority of stellarators now operating have high shear. We would like to explore the possibility of developing high

shear (integrable, nonlinear) accelerators.

It may be noted that complete absence of nonlinearity is impossible in any machine in any case. Nonlinear elements, such sextupoles and octupoles, are needed in machines to reduce chromaticity, the variation of tune with energy. In addition, there are present the unavoidable fringe fields and nonlinearities present in close-fitting magnets. Thus, we are not proposing to add nonlinearity so much as to modify that which already exists to make the accelerator integrable.

The P. I. previously developed a method for finding integrable systems with one and a half degrees of freedom.⁷ This method involved finding the dominant fixed points of the return map, i.e., the closed orbits, then changing parameters to reduce the residue, a measure of the surrounding island size that can be obtained from the linearized map of the fixed point. Reducing the island size eliminates chaotic motion, thereby increasing the dynamic aperture. Similar ideas should apply to eliminating chaos in a single degree of freedom of betatron motion. One needs only a realistic accelerator map with a few parameters to vary.

B. Accomplishments

The intent of the research is to create integrable, realistic accelerator systems. In order to facilitate this goal a highly adaptable, motif-based X-window application has been created. The advantages of using X windows are in its portability and wide spread use. Our code can be run from any other unix based workstation running X windows. X also provides an interactive graphical interface for very powerful machines such as the IBM RS6000 workstations we have used to develop the code. This combines the ease of a mouse based interface with high speed computing power.

Motif is also designed to be conducive to object oriented programming.

Applications can be written in both C and C++ concurrently. This allows great adaptability and future stability of the code. In the future other investigators can ammend or append to the code according to their needs. Also, Leo Micheloti and Jim Holt of FNAL are developing their own objected oriented software toolkit for linear and nonlinear accelerator design, analysis and simulation. Our work could easily be integrated to theirs.

Currently, the code takes any dynamical mapping independent of how complicated it is. The structure and input format of the map can be completely individualized. It then can provide surface of section plots, along with fixed point and residue analysis. In fact, this code may be used to analyze any one-and-a-half-degree dynamical system.

A single superstructure of the ALS ring in Berkeley is currently under study. A faithful thin lens approximation mapping with realistic tunes is used. Elements can be shifted, altered or added. Fixed points may be found and their residues calculated. In addition the code does an anlysis of trajectories. The winding number (tune) is calculated, and its continued-fraction expansion is found. The continued-fraction expansion is used to determine the critical nearby fixed points for determining whether a particular trajectory is a stable (KAM) torus or one that has broken up.

A fixed point is first located approximately by eye on the surface of section plots. This approximate location, either typed in or entered by the mouse pointer, is then used as the initial guess for the fixed point solver. The fixed point is then found precisely by a one- or two-dimensional secant method. Finally, the residue is calculated by integrating the linear map of the fixed point. Many fixed points are found and then catalogued. By examining the residues of a sequence of fixed points with winding numbers limiting to a particular irrational number the existence of a KAM curve of that winding number may be determined.

IV. Excitation of cavity modes by coasting beams

The goal of this research is to understand how a coasting beam excites electric field modes in the driving cavity. Using a simple model, we find fully non-linear, BGK-like solutions of the governing equations, and we examine the stability of such solutions. Rather than the more common driven, bunched beam, we choose to study coasting beams for mathematical simplicity and to develop intuition for studying multibunch instabilities. However our analysis can be directly extended to bunched beams and in addition we believe the coasting beam case may apply to certain beam coalescing scenarios used in injector rings.

Using the Vlasov equation to describe the evolution of the coasting beam particle distribution function and Maxwell's equations to describe the beam-cavity interaction, we derive the following equations to describe the system:

$$\frac{\partial f}{\partial t} + \dot{z} \frac{\partial f}{\partial z} - e\dot{q}D\delta_L(z) \frac{\partial f}{\partial p} = 0 \quad (4.1a)$$

$$\ddot{q} + \omega_c^2 q = D \int dp f(z=0, p, t) \dot{z} \quad (4.1b)$$

where z is the coordinate around the ring, q is the amplitude of the cavity mode, ω_c is the cavity frequency, D is a constant of coupling between the cavity and beam (basically just the charge of the particles), and δ_L is the periodic delta-function, with period L .

We have carried out a standard linear analysis of this system of equations. We find an instability much like the beam plasma case. There is an important difference. In the beam-plasma case there is no natural spatial quantization. This implies that one can always find a k for which the system is unstable. However, in the accelerator problem, the modes must fit within the ring. None of these discrete k -values may be unstable.

Another difference is in the nonlinear evolution. In the beam-plasma problem after one state saturates, the neighboring state may also grow. However, in the accelerator problem discretization may prevent but one wave from being unstable. With this in mind we search for a single nonlinear wave corresponding to a saturated wave.

We look for a periodic solution. This implies that the right side of Eq. (4.1b) is a sum of harmonics of the fundamental frequency. We keep only that harmonic most nearly in resonance with the cavity. Thus, the cavity equation becomes that of a simple harmonic oscillator driven at a single frequency and we can then easily write down a solution. Plugging this solution back into Eq. (4.1b) and rewriting the periodic delta function into Fourier harmonics, again keeping only the harmonic most resonant with the particles and cavity, we thus put the Vlasov equation in the form,

$$\frac{\partial f}{\partial t} + z \frac{\partial f}{\partial z} - \frac{e\omega F}{(\omega_c^2 - \omega^2)L} \cos(kz - \omega t) \frac{\partial f}{\partial p} = 0, \quad (4.2)$$

where ω is the harmonic most resonant with the cavity mode, and k is that spatial mode (integer $\times 2\pi/L$ for a ring of circumference L) most nearly resonant with the beam velocity. The quantity F is the amplitude of the resonant term on the right side of Eq. (4.1b). Solving self-consistently for F is now the goal.

To solve for F , we note that the above Vlasov equation is identical to that for motion in a Hamiltonian:

$$H = \frac{p^2}{2} + \frac{e\omega F}{kL(\omega_c^2 - \omega^2)} \sin(kz - \omega t) \quad (4.3)$$

By transforming to the rest frame of the wave, we arrive at a time-independent Hamiltonian and, thus, just as in BGK formalism, we note that any function of the Hamiltonian will solve the Vlasov equation. By then plugging these BGK-like solutions back into the cavity

equation and requiring that F be self-consistent, we obtain an expression for q , the cavity field strength, in terms of ω , the particle revolution frequency.

One simple case to which we can apply this formalism is that of a single particle sitting at a fixed point of the Hamiltonian (distribution function is a delta function in both position and momentum). Such a distribution function satisfies the criterion that it be a function of the Hamiltonian only. In this case, we find that there is always a stable BGK-like mode for particles moving below the cavity frequency. Consequently, under the action of any damping present in the cavity, we expect the particles to remain close to this BGK-like state and slide toward zero momentum.

We believe this case to be applicable to beam coalescing used in injector rings to increase beam intensity. In the coalescing scenario, the particles of many adjacent buckets are coalesced into a single bucket by a method which involves decreasing the amplitude of the driving frequency to near zero and manipulating the particles with other frequencies of small amplitude. Because the particle bunches interact with much smaller amplitude waves during coalescing, we expect they may exhibit some of the properties predicted by our formalism (where the amplitudes are zero).

Our goal now is to develop computer models for this system and try to observe numerically some of these predictions, as well as work with Pat Colestock at Fermilab to look for ways to experimentally measure these effects.

V. Education

This project continues to have an educational mission. This year Peter Stoltz and Scott Hendrickson made substantial progress on their Ph. D. theses. Carson Chow, a postdoctoral fellow, attended an accelerator school and learned about accelerator elements.

VI. Contacts with the accelerator community

The PI completed his sabbatical at Fermilab, where he is worked in the Accelerator Physics Department of the Accelerator Division. During this sabbatical the PI had the opportunity to interact with many of the accelerator physicists and to learn about accelerator physics operations. The PI did a week in the control room. He became involved in discussions with Pat Colestock, Kathy Harkay, and Andre Gerasimov on collective instabilities in the booster and the Tevatron. He also discussed basic accelerator physics experiments with Todd Satogata and Bill Gabella, an accelerator physicist whose thesis research was supported under this grant.

One of the graduate students, Peter Stoltz, also had an opportunity to visit the Accelerator Physics Department at Fermilab during the summer of 1992. In that time he and Andre Gerasimov developed nearly all of the theoretical framework of the BGK-like modes in beam-cavity interactions. They also had the opportunity for many discussions with Pat Colestock on practical applications and possible experimental verification of their work at the cyclotron in Indiana. This opportunity for Peter Stoltz to interact with the people at Fermilab was extremely valuable to his study of accelerators and produced some of his most fruitful work.

VII. References

- ¹ D. L. Bruhwiler, *Scattering and Diffusion of Particles in Slowly-Varying Large-Amplitude Waves*, Ph. D. thesis, University of Colorado, Boulder (1990).
- ² D. L. Bruhwiler and J. R. Cary, Phys. Rev. Lett. **68**, 255 (1992). Included as App. A.
- ³ D. L. Bruhwiler and J. R. Cary, *Adiabatic Particle Motion in Spatially Varying Wave Structures* submitted to *Particle Accelerators* (1992). Included as App. B.
- ⁴ W. E. Gabella, *Numerical Solution of the Hamilton-Jacobi Equation in 2 1/2 Degrees of Freedom*, Ph. D. thesis, University of Colorado, Boulder (1991).
- ⁵ A. Renieri, Nuovo Cimento **53B**, 160 (1979).
- ⁶ I. Ben-Zvi, Bull. Am. Phys. Soc. **36**, 1512 (1991).
- ⁷ J. R. Cary, Phys. Rev. Lett. **49**, 276 (1982); J. R. Cary, Phys. Fluids **27**, 119 (1984); J. D. Hanson and J. R. Cary, Phys. Fluids **27**, 767 (1984); J. R. Cary and J. D. Hanson, Phys. Fluids **29**, 2464 (1986).
- ⁸ J. Greene, J. Math Phys. **20**, 1183 (1979).
- ⁹ J. E. Griffin, J. A. MacLachlan, and J. F. Bridges, *Preparation and Study of Bunches Containing 10^{11} Protons in the Fermilab Main Ring*, IEEE Trans on Nucl. Science, **NS-28**, 2037 (1981).
- ¹⁰ A. B. Rechester and R. B. White, Phys. Rev. Lett. **44**, 1586 (1980); A. B. Rechester, M. N. Rosenbluth and R. B. White, Phys. Rev. A **23**, 2664 (1981); J. R. Cary, J. D. Meiss and A. Bhattacharjee, Phys. Rev. A **23**, 2744 (1981).
- ¹¹ J. R. Cary, D. F. Escande and A. D. Verga, Phys. Rev. Lett. **65**, 3132 (1990).
- ¹² Peter H. Stoltz and John R. Cary, "Lyapunov exponents in a field of many randomly phased waves," Bull. Am. Phys. Soc. **37** (6), 1542 (1992). Included as App. C.
- ¹³ Cary and Doxas, "Explicit Symplectic Integration Scheme for Plasma Simulations,

- submitted to J. Comp. Phys. (1992).
- ¹⁴ J. R. Cary, D. F. Escande, and J. L. Tennyson, Phys. Rev. **A34**, 4256 (1986); J. R. Cary and R. T. Skodje, Phys. Rev. Lett. **61**, 1795 (1988); J. R. Cary and R. T. Skodje, Physica **36D**, 287 (1989).
 - ¹⁵ N. M. Kroll, P. L. Morton and M. N. Rosenbluth, IEEE J. Quantum Electron. **17**, (1981); T. J. Orzechowski, B. R. Anderson, J. C. Clark, W. M. Fawley, A. C. Paul, D. Proznitz, E. T. Scharlemann, S. M. Yarema, D. B. Hopkins, A. M. Sessler and J. S. Wurtele, Phys. Rev. Lett. **57**, 2172 (1986).
 - ¹⁶ B. V. Chirikov, Phys. Rep. **52**, 263 (1979).
 - ¹⁷ R. Chodura, W. Dommaschk, W. Lotz, J. Nührenberg, and A. Schlüter, Proc. of the 8th International Conference on Plasma Physics and Controlled Fusion Research, Brussels, 1980 (IAEA, Vienna, 1981), Vol. 1, p. 807.
 - ¹⁸ J. F. Lyon, B. A. Carreras, K. K. Chipley, et al Fusion Technology **10**, 179 (1986).

END

**DATE
FILMED**

2 / 5 / 93