Studies of Relativistic Heavy Ion Collisions at the AGS (814/877)

W. E. Cleland

University of Pittsburgh

Department of Physics and Astronomy

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Annual Progress Report

DOE Grant No. DE FG02 87ER40363

1 May 1992 - 30 April 1993

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Studies of Relativistic Heavy Ion Collisions at the AGS (E814/E877)

During the past year, the Pittsburgh group has continued its analysis efforts in the area of peripheral and central collisions of relativistic heavy ions. The main progress in the area of peripheral collisions has been a completion of the analysis of the $1n$ and $2p$ decay channels, which we are now preparing for publication. In the area of central collisions, we have completed the first measurement of E_T distributions in Au-Au collisions at the AGS, through the use of the participant calorimeter, and compared these results with those obtained in collisions with Si projectiles. This work has been submitted to Physical Review Letters for publication. In addition, we have carried out a thorough study of two-particle correlation functions, using the data from our silicon pad multiplicity detector. We plan to prepare a paper on this subject within the next few months. We present here a brief history of the experiment, followed by a detailed report our analysis work.

In May 1987, during the heavy ion run at the AGS, we mounted a test setup, which was used (a) to understand the behavior of the modified uranium/scintillator calorimeters, (b) to test the prototype forward scintillation counters, (c) to carry out a set of albedo measurements, and (d) to carry out a measurement of the E_T spectrum for a 10 GeV/nucleon beam incident upon a variety of nuclear targets. Preliminary results [3] from this run indicate that there is almost complete stopping of the ions at 10 GeV/nucleon, as the limit in E_T reached seems to depend little on the A of the target nucleus. In November 1987, we mounted a smaller test in order to study the properties of scintillation counters in relativistic ion beams. In December 1988, the apparatus in its final configuration (but still incomplete) was exposed first to proton beams, in which debugging and testing was carried out, and then to 15 GeV/c ^{28}Si beams, during which a significant data sample was taken on each of the three major physics topics we are studying. The 1988 data have been analyzed, resulting in the publication of three papers [4, 5, 6].

In June 1989, another run was carried out, in which all of the forward calorimeters were in place, while the drift chambers and the participant calorimeter were being tested. Results from this run on central collisions have been recently published [7]. Another ^{28}Si run was carried out in June 1990, in which the apparatus was finally complete, including the participant calorimeter, the drift chambers, and a new device, the beam vertex detector. There was a strong emphasis on peripheral data in this run, and a paper on $1p$ emission has recently been submitted for publication [8](included here as Appendix A). Other peripheral channels are still being analyzed, and the progress in this area is one of the main topics of this report. In addition, a set of data on central collisions were taken using the silicon multiplicity detector as the trigger.

The analysis of these data was the main topic of the Ph.D. thesis of M. K. Jayananda, which was finished last year. In addition, we published a paper on the charged multiplicity distribution [9]. In 1991 we carried out a calibration run on the participant calorimeter as well as a data run on central collisions, with PCAL as the main trigger. These data have been analyzed, and the results were presented at the APS meeting in Washington in March 1992. In April/May 1992, the AGS delivered for the first time Au beams of energy 11.4 A GeV/c. E_T distributions were measured in both PCAL and TCAL, and we have analyzed the PCAL data. The results of this study were presented at the APS meeting in Sante Fe in the fall of '92 and at the HIPAGS meeting in Boston in January 1993.

Experiment 814 is a study of both extreme peripheral collisions and the transition from peripheral to central collisions in relativistic heavy ion-nucleus interactions. We are studying relativistic heavy ion interactions with nuclei in two types of collisions: (a) extreme peripheral collisions of large impact parameter, and (b) central collisions with high transverse energy in the final state. The experiment emphasizes the measurement of overall event characteristics, in particular energy flow measurements and a precise measurement of the particle charge, momentum, and energy in the forward direction. This permits measurements of cross sections and rapidity densities as a function of the transverse energy for leading baryons emitted into regions of larger rapidity. Combining the energy flow measurements as a function of rapidity with the spectra of leading baryons provides information on the impact parameter dependence of the nuclear stopping of the projectile in relativistic heavy ion collisions.

1 Detectors in Experiment 814

A diagram of the experiment is shown in Figure 1. We give a brief description of each of the detector systems below. More detailed information is available in our previous annual reports and in the publications and conference reports of the experiment.

- Beam vertex detector. The beam vertex detector is a pair of silicon strip detectors used to locate the horizontal position and angle of the incoming beam particle. This system was installed before the June 1990 run, in order to improve the resolution in the center of mass quantities in certain exclusive peripheral interactions.
- Beam counters. The beam detectors serve to define the presence of a beam projectile, to establish the time of the collision, and to identify the charge of the projectile. The telescope consists of two counters in coincidence and two other counters, with a hole for the beam, in anticoincidence. The geometrical coincidence signifies that a track has crossed the target. A pulse height measurement from one of the counters is used to establish the charge of the projectile, and the timing of the other counter is used to establish its time of arrival. The problems posed by large dynamic range in making good amplitude and timing measurements for scintillation counters operating in a heavy ion beam are nontrivial. Tests

Fig. 1: Diagram of the apparatus of Experiment 814. M1 and M2 are dipole magnets. DC1, DC2, and DC3 are drift chambers used to track particles in the forward spectrometer. Solid lines in the figure represent trajectories for neutral particles, beamlike particles (with $Z/A = 1/2$) and protons with 14.6 GeV/c momentum.

on the suitability of various scintillators and phototubes were carried out in a heavy ion run during the fall of 1987. On the basis of these tests, NE102 was chosen as the scintillator material, Hamamatsu R2083 as the phototube for good timing, and EM 9954 as the tube for good charge resolution.

- Target. The target for E814 is a simple disk target with a remote positioning control. The rotating target assembly was built by the McGill group and was installed in the mount which supports the multiplicity counter. The disk has eight positions, so that up to seven targets plus an empty frame may be used at any one time. The complement of targets is changed for the different programs, as peripheral, central, and strangelet running require different materials and thicknesses.
- Multiplicity Detector. The silicon multiplicity counter consists of two 512 pad silicon detectors which are positioned immediately downstream of the target. They are used both at the trigger level and in offline studies of the multiplicity as a function of rapidity. This detector was fabricated at BNL, and the electronics was supplied by BNL, CERN, and New Mexico. K. Jayananda, a Pitt graduate student, was responsible for the pad layout and for designing the electronics for integrating it into the trigger. The detector was used successfully as a multiplicity trigger in the June 1989 run, and it was the source for most of the central triggers for the 1990 and 1991 runs. Details of the detector and analysis of the multiplicity data are given in Jayananda's Ph.D. thesis[1].
- Target Calorimeter. The target calorimeter is used to detect the products of the target fragmentation and covers the region of θ between 45 and 180 degrees. It consists of a box composed of 900 blocks of NaI, 4 x 4 cm in cross section and 6 radiation lengths thick. It serves to measure E_T in central collisions and it also acts as a veto for the peripheral collisions. The NaI is read out using photodiodes followed by preamplifiers and shaping amplifiers. Summing electronics for the first and second level trigger has been designed and fabricated at Stony Brook. The construction and calibration of this detector is the responsibility of the Stony Brook group.
- Participant Calorimeter. The participant calorimeter, constructed by Los Alamos and Texas A& M, is azimuthally symmetric, covering the polar angle region θ between 2 and 45 degrees. It has both azimuthal and polar angle segmentation. The radiator is lead and iron plates, and the sampling layer is plastic scintillator, coupled to phototubes via wavelength-shifting fiber light guides. The electromagnetic and hadronic sections of the calorimeter are read out separately. Fast trigger sums, using E_T weights, are formed separately for each azimuthal section, both for the electromagnetic and hadronic sections of the calorimeter. Z. Zhang, a Pitt graduate student, is responsible for the PCAL and its trigger electronics, including the problem of on-line and off-line gain monitoring and adjustment.

- Tracking Chambers. In order to measure the momenta of the charged particles emitted in the collisions, we use a spectrometer consisting of three sets of tracking chambers and two magnets. This configuration is chosen due to the wide range of particle momenta. One of the chambers, DC1, has highly segmented pad readout and interpolation by charge division. It is positioned between the two magnets. The chamber has 1000 pads, and the density varies across the plane in accordance with the expected track multiplicity. The design of this chamber was carried out in the Instrumentation Division of BNL. One of the key people in this group was Bo Yu, a graduate student at the University of Pittsburgh who has recently completed his Ph.D. thesis[2], which contains several studies relevant to the E814 tracking chambers, especially DC1. It should be noted here that this type of chamber has been chosen by the GEM collaboration for their central tracking detector. The other drift chambers for the experiment, DC2 and DC3, consist of six drift planes and two planes with cathode pad readout. They have been designed at BNL, with the fabrication of the frames carried out at Yale. These chambers were installed just before the June 1989 run and were fully operational in the June 1990 run. The drift chambers have worked very well, giving about 300 micron resolution for both minimum ionizing particles and relativistic heavy ions. The pad sections are being modified for the running with Au beams in order to accommodate the higher track densities. In addition a set of MWPCs are being added to help resolve the ambiguities in the pattern recognition and to make possible the development of a trigger based on tracking.
- Forward Calorimeters. Charged particles with momenta greater than 6 GeV/c and all neutral particles emitted in a cone of θ less than 1 degree are measured in the forward calorimeters. In 1988, we had only 13 of these units, since they were obtained from CERN and were still required in HELIOS. The remaining 12 units were shipped to BNL in early 1989 and were modified and installed in the experiment before the June 1989 run, completing the set of uranium/scintillator calorimeters in the forward spectrometer. Just upstream of each of the calorimeter stacks are a bank of scintillation counters, two counters associated with each stack, which are used to measure the charge and the vertical position of the track. Because fragments emitted in the forward direction have approximately the velocity of the beam particle 15 GeV/nucleon, the energy measurement in the calorimeters is a good measure of the nucleon number. The use of calorimeters in the detection of final state neutrons is particularly attractive, as the good energy and spatial resolution of these calorimeters permit studies of correlations among leading neutrons in order to get information on transparency in nuclear collisions and to search for bound multineutron states. Thus it is important for us to understand the detailed response of these units to the forward emitted baryons.
- Scintillation Counters. There are three sets of scintillation hodoscopes used in the experiment: (a) the target counters, used in conjunction with the target calorimeter to identify charged particle fragments and neutrals; (b) magnet scintillators, which line the

sidewalls of the two magnets, used to detect pions produced in the forward direction; and (c) forward scintillation counters, to be used in conjunction with the forward calorimeter to measure the charge of nuclear fragments. The target counters have been constructed and installed by the Stony Brook group. The magnet counters and forward scintillation counters have been constructed and installed by the Pitt group, and their operation and calibration has been the responsibility of U. Sonnadara.

2 Analysis of Peripheral Collisions

During the past few years, the Pittsburgh group has developed a set of powerful software tools which exploit the detectors in the E814 spectrometer to identify and explore the various decay channels produced via peripheral interactions. This year, we continued our studies extending the analysis in two separate directions. The first involved finalizing values for the cross sections for various peripheral channels and the full event reconstruction of 1p, 1n and 2p decay channels. The cross section measurements and reconstruction of 1p and 1n channels are part of the thesis work carried out by U. Sonnadara, included as Appendix A in this report. The second involved the study of complex channels with an α particle in the final state. This analysis required an improvement in the performance of the tracking chambers as well as a better understanding of the scintillation counters and calorimeters. A summary of the work carried out in both of these areas is given below.

2.1 Data Sample

In June 1990, during 10 days of running, we collected a large, high quality sample of data to study peripheral collisions. The recorded sample consists of two major parts, namely, (a) a single nucleon emission (1p-1n) and (b) two or three nucleon emission (2p-2n). These were recorded over 6 different targets including data taken with an empty target frame. In addition, a majority of the events were recorded with an online veto requirement to enrich the data sample. A small percentage of data were taken without the online veto requirement to study trigger efficiencies. In a normal data run, the trigger was set up to record, in addition to the peripheral events, a small fraction of events with minimal trigger requirements (pre-triggers), events with no interactions (beam triggers), and random events with no beam particles present (empty events). These were used to study gain variations and other systematic effects. The recorded data sample is shown in Table @refdata.

In addition we recorded 18 beam trigger tapes, 18 pre-trigger tapes and 18 pulser tapes, also used for systematic detector studies.

These data were originally written into 6250 magnetic tapes (one tape for each run). The policy of the collaboration is to keep the original copy of the data at BNL and produce copies

Table 1: Sample used in the analysis of peripheral data.

Target	No of tapes for single nucleon	No of tapes for two or three nucleons
Pb	8	36
Sn	7	36
Cu	3	37
Al	5	35
C	3	-
MT	4	33

for individual institutions onto 8mm tapes which can be read via hexabyte tape drives. Each 8mm tape is used to record up to 12 runs from 6250 tapes. The peripheral sample with which we are working consists of 6 (one for each target) 8mm tapes for 1p-1n triggers and 22 tapes for 2p-2n or rare triggers. This sample consists of about 2,400,000 events.

2.2 Kinematic Reconstruction of the 2p Decay Channel

During the last year we carried out the initial steps in the reconstruction of the invariant mass of the $2p+^{26}\text{Mg}$ decay. A detailed description of this work was provided in the previous DOE Report submitted by the Pittsburgh group. This year, we continued to study this channel in order to bring the analysis to a more mature level.

One of the major problems we observed was regarding the shape of the decay angular distributions. The decay angular distributions generated with 2p events indicated that the Mg is emitted preferentially in the forward direction with respect to the di-proton system. However, we did not observe such an effect in the previous work done on the Al fragments in the 1p emission channel.¹ Our simulation program indicated that the angular distribution can be easily distorted by the misalignment of detectors. The simulation program takes given shapes of angular distributions and allows us to perform the full reconstruction to test various stages in the analysis. This program modelled the experimental conditions as accurately as possible. For this analysis a full set of alignment constants was generated for all detectors both in the horizontal and the vertical directions.

In addition, our analysis suffered due to the low efficiency in selecting 2p events, especially when the protons were close together in the tracking chambers. The original programs used to extract data from tracking chambers were developed mainly to study cases where a single proton and a heavy ion traverse the chambers together. They were found to be inadequate for

¹The reconstructed resolution in the angular distributions for Si fragments generated for the 1n emission was far too crude to draw any conclusions for this channel. This is primarily due to the poor energy resolution (compared to magnetic momentum measurements for charged particles) in the Ur/Cu calorimeters.

the analysis of the 2p data. We have implemented the following modifications in the tracking programs for the 2p events.

- The threshold values used to select the protons in the pad sections of all three chambers were lowered to improve the efficiency of 2p selections.
- A noise correction algorithm was implemented for the DC1 pad section. This was developed by following the studies done by B. Yu on this chamber[2]. This procedure was found to be essential as some wires occasionally report large negative shifts in the pad section.
- The vertical position estimations in DC2 and DC3 were improved to work with different pad sizes in different regions. With these modifications, we were able to achieve a 2mm resolution in DC2 and a 5mm resolution in DC3 for the smallest size pad sections.
- The forward scintillators were removed from the fitting procedure used to predict the initial position of the proton in DC1, and also in the calculation of other quantities. These detectors are no longer needed since a better resolution in the vertical measurements has been obtained with the drift chambers.
- The second beam silicon strip (vertex) detector failed to report its readout roughly 15% of the time. The vertex routine was updated to calculate the beam convergence point, and used this whenever the second vertex detectors failed. We were able to obtain a resolution of 400 μm for this location. However, events of this type were used only in estimating cross sections, and not in the kinematic reconstruction.

In addition to these modifications, two problems were encountered in the reconstruction program. The first problem was related to the selection of the best TDC hits by the pattern recognition program. Instead of including the best TDC hits, the reconstruction was performed with the first 12 hits reported. The second problem was connected with the rejection of 50% of the DC1 hits in the final reconstruction. All reconstruction resolutions improved after the modifications were made and the problems duly corrected.

Figure 2 shows the reconstructed angular distributions for $2\text{p} + {}^{26}\text{Mg}$, which show angular symmetry in the 2p decay and gives us confidence in our event reconstruction. However, the polar angle of the momentum vector of the proton going forward with respect to the momentum vector of the rest frame of the di-proton (θ_p) peaks slightly near zero. This could be attributed to problems in the reconstruction of 2p events where the protons are very close together. In this case, the vertical positions extracted from the pad sections in DC2 and DC3 can report incorrect results due to the overlapping of the image charge produced by each proton. Elimination of this problem will require additional improvement to the tracking software.

We analyzed the full data set for all targets consisting of Pb, Sn, Cu, Al and the empty target frame to produce excitation energy distributions. Beam trigger and pre-trigger data were used to determine the efficiency corrections in the integrated cross sections. The final cross

Fig. 2: Decay angular distributions of 2p. (a)-(b) heavy fragment (c)-(d) di-proton

sections observed for 2p decay are listed in Table 2. For comparison, we have included the previous cross sections measured with the E814 apparatus[5] for the same decay. Although the agreement between the two measurements is quite poor, one should take into consideration the difficulty in measuring the 2p cross sections without using the tracking detectors (as was done in the previous analysis). However, it was observed that the measured cross sections for simple channels agree remarkably well.²

Table 2: Measured EMD cross sections for 2p emission. For comparison, earlier cross section measurements through our experiment are also listed.

Target	2p cross sections (mb)	
	This work	[Ref 1989]
Pb	74.7 ± 0.8	55.6 ± 3.7
Sn	34.4 ± 0.5	21.4 ± 2.1
Cu	13.1 ± 0.2	
Al	4.3 ± 0.1	3.2 ± 0.8

All excitation energy distributions were normalized according to the integrated cross sections given in Table 2 for each target. In this manner, the additional inefficiency in the excitation energy reconstruction arising from the failure due to the convergence of kinematic and geometrical constraint fitting was included. However, it was assumed that these inefficiencies are uniform and do not depend on the excitation energy. Figure 3 shows the reconstructed excitation energy distributions for Pb, Sn, Cu and Al targets, where the kinematic threshold for the ^{28}Si into $2p+^{26}\text{Mg}$ is indicated by the arrows. The reconstruction resolution was found to be ≈ 3 MeV for all distributions. The major contribution to the resolution comes from the multiple scattering in the target and the surrounding media. For the 1p and 1n channels, we obtain satisfactory agreement with data from the inverse photo-nuclear reactions for direct comparisons. However, such experiments have not been carried out for the 2p case, and therefore these data appear to be the only direct measurement of this channel.

One of the major goals in studying peripheral collisions is to look for signatures in double photon excitation. Instead of excitation via a single photon, the projectile can absorb one or more photons from the same target nucleus. Since the kinematic threshold for the $2p+^{26}\text{Mg}$ channel is at 19.8 MeV, which is already close to the peak of the GDR in the Si nucleus, the 2p channel has an advantage over the 1p channel.

The simplest method of finding signatures of double photon excitation is to look for target charge (Z_T) dependence in differential cross sections. The single photon excitation has a Z_T^2 dependence whereas the double photon excitation exhibits a Z_T^4 dependence. This can be extracted by taking ratios of the excitation energy spectra. Figure 4 shows the ratios of the excitation

²see Appendix A for a full detail of efficiency corrections and cross section estimations.

Fig. 3: Reconstructed excitation energy distributions of 2p.

energy spectra for (a) Pb and Sn and (b) Pb and Al targets. The two dashed lines indicate the expected ratios for event production of pure electromagnetic or pure hadronic nature. The double photon excitation would produce an enhancement close to 40 MeV for the Pb/Al ratio. Our data indicates no evidence of this process. However, one should consider the effects of not detecting the emitted γ rays when ^{26}Mg decays via an excitation energy level before reaching the ground level.

Fig. 4: Ratios of excitation energy distributions of 2p.

The comparison between the charge changing cross sections for Si previously measured by Brechtmann et al.[13] and our measurements has an added advantage over the comparison between the photonuclear results and our individual cross section measurements. They report the differential cross section of Si for $\Delta Z \leq 1$ without correcting for the effects due to the emission of γ rays. We add our reconstructed cross sections for 1p, 1n and 2p, which contribute about 75% of the total EMD cross section for comparison with their data. Table 3 shows the comparison between their measurements and our measurements. Good agreement was found in the cross section estimations.

Figure 5 (a) shows the reconstructed excitation energy distributions for 1p, 1n and 2p decay channels. Excitation energy distributions for 1p and 2p follow each other at the trailing edge. The slight enhancement of the 1n data at the tail was due to the poor reconstruction resolution for this channel. Figure 5 (b) shows the excitation energy distributions for 1p, 1n and 2p

Table 3: Total EMD cross sections for Si on Pb.

Reference	$\Delta Z \leq 1$	2p+1p+1n	Total
This work	1170 ± 100	992 ± 35	1410 ± 100
Brechtmann et al.	1190 ± 170		
Calculated	~ 1250		~ 1500

Fig. 5: (a) Excitation energy distributions for 1p, 1n and 2p channels. (b) Comparison with γ absorption data.

(added together) compared with the resulting distribution with the cross sections of total photo-absorption in ^{28}Si , multiplied by the virtual photon number spectrum and folded with our experimental resolution. The agreement is good if we take into account that our distributions miss the energy corresponding to the de-excitation of the residual heavy ion from the dissociation of ^{28}Si , and thus are shifted downwards compared to the excitation energy distribution of ^{28}Si [9]. We also see that the reconstructed channels are the most significant ones in the EMD of ^{28}Si .

Preliminary results of 1n and 2p were presented in the April 1992 APS meeting held at Washington DC. In addition, we presented the 2p results in July 1992 IUPAP conference in Germany. We are currently preparing a paper on this analysis.

2.3 Decay channels with α particles

One aspect of the reconstruction of complex channels in peripheral collisions was the detailed study of events in which an α particle was part of the final state. The full scope of this analysis included the development of a methodology for identifying candidates for reconstructable α particle events, the exploration of methods to improve tracking resolution in drift chambers and hence boost efficiency, the development of algorithms to locate and confirm the presence of α particles in the downstream forward scintillator hodoscopes and associated calorimeters, and the collection and reconstruction of a sample of such particles.

In order to acquire a sample of events which included α particles as part of the final state, an algorithm had to be developed which could identify an α particle, with reasonable confidence, by its electronic signature in the various components of the forward spectrometer. Suitable candidates for such events were searched for in the 2p triggered data, which requires that there be sufficient energy to produce at least 2 protons in the proton calorimeters and that a heavy fragment charge of $Z < 13$ be detected in the downstream end of the spectrometer. The reason for selecting this type of trigger was to maximize the rigidity difference between the α and the heavy ion so that the separation in the drift chambers would also be maximal.

First, events which originated from peripheral interactions were extracted by requiring that there be a minimum of activity in the target region detectors. The permitted level of activity was defined with respect to the activity of pure beam particles.³ These events were then classified according to the charge (Z) of the heavy ion fragment. Figure 6 (a) shows the magnetic rigidity (P/Z) of the residual heavy ion fragment for selected $Z=10$ events. The different peaks correspond to different isotopes arising from the number of neutrons in the fragment. However, we found only two protons present in the proton calorimeters for most of the selected events. Figure 6 (b) shows the neutron calorimeter energy vs. the P/Z with the requirement that only 2 protons be present in the proton calorimeters. One can see that in each of the labeled clusters, the state with 2 protons and 2 neutrons appears to be depressed. Figure 6 (c) shows the second largest pulse height measured in the downstream scintillation counters for these events. Here, one can easily recognize a peak corresponding to $Z=2$ as indicated. This is only possible if the

³See Appendix A for the recipe for the selection of good peripheral events.

missing 4 nucleons are bound together to form an α particle.

Fig. 6: Selection of α channels.

Further studies show that the beam region calorimeters strongly suggest the presence of an α particle in these events. However, we do not impose any selection using the beam region calorimeters due to their poor energy resolution.

Due to the similarity in rigidity between the α particle and the heavy ion fragment, these particles would more or less travel in closely spaced trajectories. In order to identify a track in the drift sections which could be associated with the passage of an α , it was necessary that the track not coincide with the same drift cells in which the heavy ion fragment passed through, and that the signal of the α in the pad section of these detectors be discernable and separable from the image charge produced by the passing heavy ion tracks.

Figure 7 shows the signals seen in the pad sections of the tracking chambers DC2 and DC2 for a heavy ion and an α particle. In addition to the two charge clusters created by these particles, one can recognize another peak in DC2, the existence of which could be attributed to the presence of a δ ray produced by the heavy ion fragment. Due to the rarity of this type of decay, in addition to the problems associated with the particles traversing a region in the drift chambers that is gain reduced to suit heavy ions, only a very small fraction of the 2_{γ} trigger events create recognizable tracks. Thus the kinematic reconstruction of this channel was unfortunately not possible, and the only information we could extract was a measurement of

Alphas in DCII

Alphas in DCIII

Fig. 7: Lego plot of the signals seen in the pad sections of the tracking chambers DC2 and DC3 for a heavy ion fragment and an α particle.

the cross section.

3 Analysis of Central Collisions

3.1 Results

After corrections for the detector energy leakage, trigger efficiency and empty target subtraction, we obtain absolute differential cross-sections of total transverse energy productions for various colliding systems in the acceptance of the participant calorimeter, $0.83 < \eta < 4.7$. Events with total transverse energy less than 1 GeV are not collected since it has rather large cross-sections and belongs to a different category of physics interest (see Appendix A).

The cross-section is calculated from the number of events in each E_T interval, the beam rate and the target thickness. The number of nuclei in the target is

$$N_T = \frac{N_A S \Delta t}{A}$$

where $N_A = 6.022 \times 10^{23}/\text{mol}$ is the Avogadro constant; Δt is the target thickness in g/cm^2 , as listed in Chapter 2; A is mass number of the target and S the area illuminated by the beam. The number of events δN in an E_T interval is then

$$\delta N = \delta \sigma N_{beam} \frac{N_T}{S}$$

where N_{beam} is the number of beams. The differential cross-section is then

$$\frac{\delta\sigma}{\delta E_T} = \frac{1}{N_{beam}} \frac{\delta N}{\delta E_T} \frac{A}{N_A \Delta t}.$$

Fig. 8 shows the differential cross-sections of transverse energy productions in collisions with 14.6 A GeV/c ^{28}Si beams on fixed targets of ^{28}Al , ^{63}Cu and ^{208}Pb . Fig. 9 shows the same distributions for 11.4 A GeV/c ^{197}Au beams on targets of ^{28}Al , ^{63}Cu , ^{197}Au and ^{208}Pb .

The overall shape of these distributions is dominated by the geometry of the collisions. In Fig. 10, the shape of Au+Au collision differential cross-section is compared with that of the center of mass energy calculated with the impact parameter of the collisions. The center of mass energy in the overlapping regions of a collision is a function of the impact parameter b ,

$$E_{c.m.} = f(b)$$

and the differential cross-section of $E_{c.m.}$ is

$$\frac{d\sigma}{dE_{c.m.}} = \frac{bdb}{dE_{c.m.}}.$$

The center of mass energy in the figure is scaled by an arbitrary factor 0.33 to emphasis the similarity of the two distributions.

Both Fig. 8 and Fig. 9 show strong increases in transverse energy production with the target mass. No sign of saturation with target mass is observed. Even between Au+Au and Au+Pb collisions, There is still a clear increase in transverse energy production, as shown in Fig. 9.

We can compare our measurements with the calculations of FRITIOF. As shown in Fig. 11, generally FRITIOF predictions are close to the data, and it shows better agreement for heavier systems. For Si+Al collisions, FRITIOF calculation over-predicts the transverse energy by about 14%. The differences in the shape of the distribution for lighter systems such as Si+Al and Si+Pb indicate that the data have more fluctuations at the tails of transverse energy distributions than the FRITIOF calculations. For heavy system such as Au+Au, FRITIOF calculation matches data even to several orders of magnitude down at the tail of the distribution. The version of FRITIOF we presently use can not properly calculate when projectile is heavier than target nuclei, so the comparison is not shown here for those systems.

In order to compare maximum transverse energy productions of various colliding systems, we calculate the average E_T in top 1% of the total geometrical cross-sections each of the system. Total geometrical cross-section is defined as

$$\sigma = \pi(R_p + R_t)^2$$

where R_p and R_t are the radii of the projectile and the target, respectively. For a nucleus of mass A , the radius is defined as

$$R = 1.2A^{\frac{1}{3}}$$

	RQMD[19]	Landau[18]	ARC[20]	HIJET	FRITIOF
Si+Al	1.6%	0.67%	2.0%	2.1%	1.1%
Au+Au	0.19%	0.27%	0.18%	0.17%	0.26%

Table 4: The fraction f of cross-section with $E_T > E_T^0$, calculated with various models.

As shown in Fig. 12a, the maximum E_T increases rather linearly with the maximum center of mass energy of the lighter colliding systems, namely 14.6 GeV/c ^{28}Si on targets of ^{28}Al , ^{63}Cu and ^{208}Pb . The slope of this linear relation is 0.30. When the slope is extrapolated to Au+Au system, the linear relationship fails to hold on, as seen in Fig. 12b. Au+Au system appears to have a higher efficiency in converting initial energy into transverse energy, which is an encouraging signal for going to heavier colliding systems.

To better understand the excess in transverse energy production as colliding system gets heavier, we compare the two systems of Si+Al and Au+Au, which are both symmetric in the center of mass frame. we avoid comparing asymmetric systems because other processes such as secondary scattering of produced particles can complicate the E_T production. These effects appear to be more significant for asymmetric systems.

Consistency is required when comparing the values of E_T , since different systems have various level of fluctuations. The method we use here is listed in the review article of Stachel and Young[14]. The method is illustrated in Fig. 13. The histogram is the E_T distribution of Au+Au calculated from FRITIOF. The Gaussian curve is the E_T distribution when impact parameter $b < 0.5$ fm. Its centroid E_T^0 is defined as the average transverse energy for $b = 0$. The fraction f of cross-section with $E_T > E_T^0$ is defined as

$$f = \frac{\sigma_{E_T > E_T^0}}{\sigma_{geom}}$$

where σ_{geom} is the total geometrical cross-section. The fraction f is calculated for Si+Al and Au+Au from various models. As listed in table 4, they are in the same order and averaged to give

$$f(Au + Au) = 0.22\%$$

and

$$f(Si + Al) = 1.5\%$$

E_T^0 of data is extracted by finding

$$\frac{\sigma_{E_T > E_T^0}}{\sigma_{geom}}|_{data} = f$$

for each of the two systems respectively. It gives

$$E_T^0(Au + Au) = 318.5 \text{ GeV}$$

and

$$E_T^0(Si + Al) = 40.2 \text{ GeV}.$$

The ratio of these two values is 7.9. If we define the available energy of a colliding system as

$$E^* = \sqrt{s} - (A_p + A_t)m_N$$

where

$$s = Am_N\sqrt{2 + 2\gamma_p}, \text{ when } A_p = A_t = A$$

is the center of mass energy of the system; A_p and A_t are mass numbers of the projectile and target respectively; m_N is nucleon mass. The ratio of E^* of Si+Al and Au+Au is

$$\frac{E^*(Au + Al)}{E^*(Si + Al)} = 5.9$$

which is 34% less than the ratio of the E_T^0 of the two systems. The excess in E_T production is the inclusive result of several mechanisms, of which significantly higher temperature and higher energy density are ones that are particularly intriguing.

To compare the fluctuations in transverse energy production between the lighter system of Si+Al and heavier system of Au+Au, Si+Al data are scaled up by a factor of 7.9, according to the ratio of E_T^0 , as shown in Fig. 14 with dashed histogram. It is obvious that the fluctuation at maximum transverse energy is much smaller for the heavier system of Au+Au.

3.1.1 Pseudo-rapidity distribution of transverse energy

Data with 14.6 A GeV/c ^{28}Si $dE_T/d\eta$ distributions in collisions with 14.6 GeV/c ^{28}Si beams on targets of ^{28}Al , ^{63}Cu and ^{208}Pb are shown in Fig. 15. Again all distributions are corrected for detector leakage and missing channels. Events are selected with total transverse energy above the knee of their respective E_T distributions. The granularity of the distributions are limited primarily by the radial segmentation of the participant calorimeter.

The distributions appear to have a Gaussian shape. The height of the distribution increases as the target becomes heavier, from ^{28}Al to ^{208}Pb . This is directly related to the fact that the total transverse energy production grows with target mass, as seen in the previous section. The width of the Si+Pb is narrower than that of the Si+Al collisions. The centroid of the $dE_T/d\eta$ distribution shifts towards lower rapidity as the target changes from ^{28}Al to ^{208}Pb . This effect is in part due to the geometry of the collision, as explained in detail below.

Fig. 16 shows the $dE_T/d\eta$ distributions of Si+Pb collisions at different total E_T intervals. The maximum $dE_T/d\eta$ increases with the total E_T . The width narrows and the centroid moves towards smaller η as E_T increases.

One of the unique features of the E814/E877 experiment apparatus is its nearly 4π calorimetric coverage around the target. Fig. 17 shows the $dE_T/d\eta$ distributions in regions covered by PCAL of TCAL of the experiment. Event selection here is that transverse energy in the PCAL acceptance is the top 7% of the total geometrical cross-section. The match at the joint of the two acceptance lends credence to our measurement, since the two part are processed independently, from calibration to data analysis. As seen in the figure, the shape of the $dE_T/d\eta$ distribution is Gaussian in the range covered by the experiment.

Data with 11.4 A GeV/c ^{28}Si beams $dE_T/d\eta$ distribution of Au+Au collisions is shown in Fig. 18, with total transverse energy $E_T < E_T^0$. The curve represents the corrected distribution. It is constrained into a Gaussian shape for stability reasons. The assumption of a Gaussian shape is justified from previous analysis of Si beams and results from other experiments and theoretical predictions. The raw $dE_T/d\eta$ distribution is shown with dashed histogram. Its fluctuation from bin to bin is due to the finite granularity of the calorimeter segmentation and the assignment of E_T according to the position of the center of each tower. The corrected distribution is processed through the calorimeter simulation, as indicated by open circles, to compare with raw distribution. The agreement shows the reliability of the correction procedure. Corrected data in the η region covered by TCAL is also shown for a complete picture. Again the match at the joint of the two acceptances is rather smooth.

The corrected distribution is compared with the calculation from FRITIOF, as shown in Fig. 19. FRITIOF calculation shifts the peak of the distribution towards larger rapidity and the distribution is not as Gaussian. This is in part due to a combination of distributions pions and protons, which are centered at different rapidities, as shown in Fig. 20 and discussed in the next subsection.

General trends In Fig. 21, parameters of Gaussian fits to the $dE_T/d\eta$ distributions, namely the height B , the centroid η_0 and the width σ are displayed as functions of the centrality of the collision, which is roughly indicated by the relative transverse energy E_T/E_T^0 .

As shown in 21a, the maximum value of the $dE_T/d\eta$ distribution grows continuously for all colliding systems as the centrality increases. Again this is directly connected with the increase of the total transverse energy. one notices that the ratio of maximum $dE_T/d\eta$ between Au+Au and Si+Al systems is a factor of 8.7, 48% more than the ratio of their available energies(a factor of 5.9)

An interesting feature of the centroid η_0 of the Gaussian fits for various systems is displayed in Fig. 4(b). It shows a clear dependence on the symmetry of the colliding systems. This feature can be interpreted with a simple geometrical argument. The assumption is that the angular E_T distribution is dominated by the effective center-of-mass of the collision. As shown in Fig. 22a, for collisions of a heavy projectile on a light target, such as Au+Al, when the centrality increases, the length of the shadowed region in the projectile increases, thus the effective center-of-mass shifts forward and the centroid of $dE_T/d\eta$ moves toward larger η . The same dependence can be seen in the Si+Pb system where the centroid moves backward as does the effective center-of-mass when centrality of the collision increases. This interpretation is further supported by the independence on centrality of the symmetric systems of the Au+Au and Si+Al, where the effective center-of-mass does not change as centrality increases, as shown in Fig. 22.

Fig. 21c shows the width parameter σ_η of the Gaussian fit as a function of the relative transverse energy. The width of all systems decreases as the centrality increases. This is partly due to the fact that the nucleon angular distribution shifts backward with increasing centrality. The width of Au+Au system(0.77) is significantly narrower than that of the Si+Al system(1.02).

Predictions on the shifts of the centroids by FRITIOF are compared with data in Fig. 23. The general trends are similar to the data, but FRITIOF systematically moves the centroids towards larger η values. This is in part due to the fact that FRITIOF has a larger value for the ratio of number of pions and number of nucleons. As seen in Fig. 20, the $dE_T/d\eta$ distribution of protons is significantly shifted to larger η when compared with dE_T/dy distribution. This is primarily due to the large rest mass of nucleons. On the other hand, the shift of pion's $dE_T/d\eta$ distribution from dE_T/dy is rather small because of its smaller rest mass.

In Fig. 24, the widths of the data are compared with calculations of FRITIOF. The calculations of FRITIOF shows the same narrowing effect as centrality increases.

Fig. 8: Total transverse energy production in collisions with 14.6 A GeV/c ^{28}Si beams on fixed targets of ^{28}Al , ^{63}Cu and ^{208}Pb in the PCAL acceptance $0.83 < \eta < 4.7$

Fig. 9: Total transverse energy production in collisions with 11.4 A GeV/c ¹⁹⁷Au beams on fixed targets of ²⁸Al, ⁶³Cu, ¹⁹⁷Au and ²⁰⁸Pb in the PCAL acceptance 0.83 < η < 4.7

Fig. 10: Shape of E_T distributions in collisions with 11.4 A GeV/c ^{197}Au beams on ^{197}Au target compared with the shape of the center of mass distributions. $E_{c.m.}$ is scaled by a factor of 0.30.

Fig. 11: Differential E_T cross-sections of Au+Au and Si+Al collisions compared with FRITIOF predictions

Fig. 12: Average E_T in top 1% of the total geometrical cross-section scaled with E_{cm} for 14.6 GeV/c ^{28}Si on ^{27}Al , ^{63}Cu and ^{208}Pb . The slope of a line fit is 0.30.

Fig. 13: Definition of the quantity E_T^0 . The histogram is the minimum biased total E_T distribution calculated by FRITIOF for Au+Au collisions. The Gaussian is E_T distribution when impact parameter $b < 0.5$ fm.

Fig. 14: Comparison of fluctuations between Si+Al and Au+Au. Solid histograms are E_T distributions and the dashed histogram is Si+Al data scaled up by a factor of $\times 7.9$.

Fig. 15: $dE_T/d\eta$ distributions of 14.6 GeV/c ^{28}Si on targets of ^{208}Pb , ^{63}Cu and ^{27}Al . Total E_T cut is around the knee of their respective E_T distribution.

Fig. 16: $dE_T/d\eta$ distributions in different total E_T intervals in collisions with 14.6 GeV/c ^{28}Si on target of ^{208}Pb

Fig. 17: $dE_T/d\eta$ distributions in ^{28}Si on ^{208}Pb collisions with total E_T in top 7% of the geometrical cross-section. The right side of the data is from PCAL and the left side of the data is from TCAL. The Gaussian curve is one that covers most of the data points in the entire range.

Fig. 18: $dE_T/d\eta$ distribution of Au+Au collisions with total transverse energy $E_T < E_T^0$ (318.5 GeV). Dashed histogram shows the raw distribution without any correction. The Gaussian shaped curve is the corrected distribution. Circles represent how well the curve fits the raw data by processing the the corrected distribution through the detector again to compare with the raw data. On the left, data from TCAL acceptance are shown as dotted histogram. Its agreement with the PCAL data lends credence to the measurement.

Fig. 19: $dE_T/d\eta$ distribution of Au+Au collisions(solid) compared with FRITIOF calculation(dashed). Total transverse energy $E_T < E_T^0$ (318.5 GeV)

Fig. 20: Distributions of pions and protons in Au+Au collisions plotted as dE_T/dy (solid) and $dE_T/d\eta$ (dashed). calculated with FRITIOF.

Fig. 21: Three parameters, height B , centroid η_0 and width σ , of Gaussian fits to the $dE_T/d\eta$ distributions as functions of centrality, which roughly indicated as E_T/E_T^0 .

Fig. 22: A simple geometry of the nucleus-nucleus collisions.

Fig. 23: Centroids of $dE_T/d\eta$ distributions compared with calculations from FRITIOF.

3.2 Measurement of the two-particle correlation function

3.2.1 Introduction

The study of correlations in multiparticle production processes is very important for understanding the mechanisms of multiple productions, the role of resonances, minijets, strings, fireballs and so on. The correlation function, constructed in a proper way, could be a very sensitive tool for the investigation of special features of models and dynamical assumptions. The recent interest in intermittency has once more placed special emphasis on the study of two-particle correlations. The two particle correlation function can be simply connected with second order factorial moments. Observation of intermittent behavior of factorial moments in many experiments implies the existence of short range two-particle correlations, which should be seen in a direct measurement.

There exist a number of different definitions of the correlations functions. In the current analysis we use one of the simplest normalized two-particle correlation function:

$$R(x_1, x_2) = \frac{\rho^{(2)}(x_1, x_2)}{\rho(x_1)\rho(x_2)} - 1, \quad (1)$$

where $\rho^{(2)}(x_1, x_2)$ and $\rho(x)$ are two and one particle densities

$$\rho^{(2)}(x_1, x_2) = \frac{1}{\sigma} \frac{d^2\sigma}{dx_1 dx_2}, \quad (2)$$

$$\rho(x) = \frac{1}{\sigma} \frac{d\sigma}{dx}. \quad (3)$$

x can be any variable, such as rapidity, pseudorapidity or azimuthal angle.

It is well known that mixture of events with different total multiplicities causes large positive artificial pseudo-correlations sometimes called long range correlations. To avoid this effect one should use so called semi-inclusive correlation functions, that is to calculate correlation function using the events with fixed total multiplicity N

$$R_N(x_1, x_2) = \frac{\rho_N^{(2)}(x_1, x_2)}{\rho_N(x_1)\rho_N(x_2)} - 1. \quad (4)$$

To avoid confusion we note here that the correlation function defined by Eq. 4 is not zero for the case of no dynamical correlation, which for this case gives $R = -1/N$. It is also worthwhile to note that function R has some scaling properties with respect to total multiplicity. If the correlations are mostly due to resonance decays, jet production and analogous mechanisms and under the assumption that the relative number of these resonances or jets are the same for different multiplicities, the peak value of R scales as $1/N$ or as $1/(dn/dy)$. For Bose-Einstein correlations it does not depend on multiplicity.

In this work we *always* discuss the semi-inclusive correlation functions, using relatively small multiplicity windows. We study pseudorapidity correlations as a function of two variables and

present the results for R for different control bin η_1 as a function of η_2 , for different total multiplicities. and different azimuthal windows $\delta\phi$. For azimuthal correlations we present the results as a function of azimuthal angle difference $\Delta\phi$ between two sectors in ϕ space within fixed pseudorapidity window $\Delta\eta$.

3.2.2 Method of calculation

The E814 experimental setup is described elsewhere[9]. In this analysis we used data from the silicon multiplicity detector (Fig. 25), which consists of two silicon pad detectors each segmented into 512 pads. There is no charge identification in this detector. The size of pads approximately correspond to 0.1 in both η and ϕ . For multiplicities around 100 the mean pad occupancy ≈ 0.1 and although there is no possibility to distinguish between one or more hits in the same pad there is no need to correct for this effect for the normalized correlation function R . For autocorrelation the effect could be important (see below.) It is, however, very important for the correlation analysis to take into account the beam movement. The horizontal beam position in E814 was measured by a silicon strip detector, and this information is used on an event by event basis. The vertical beam displacement caused by beam divergence is important mostly for correlation study in the azimuthal angle space. The distribution of vertical beam position was assumed to be Gaussian, and the width of this distributions $\sigma_y \approx 1.6$ mm was extracted from distribution of event multiplicity centroids[1]. The correction procedure is described below.

It is also important that the participant calorimeter of the E814 covers the same pseudorapidity window as multiplicity detector, so we could select events using the transverse energy deposited in the same pseudorapidity window. Note also that the signals from neighboring pads located along a radial line go to the same discriminator module. During the analysis it was found that there exist, strong correlated noise within some discriminator modules.

We often use the usual mixed events technique for calculation of the correlations between two different bins (areas in pseudorapidity and azimuthal angle space) i and k :

$$R_{ik} = \frac{\langle n_i n_k \rangle}{\langle n_i n'_k \rangle} - 1, \quad (5)$$

where n_i is the multiplicity in the i -th bin and n'_k is the multiplicity in the k -th bin in some other event with the same beam position and the same total multiplicity. As already mentioned above, there were no possibility to distinguish multiple hits in the same pad. This effect is important only for calculation of auto-correlations. To avoid this effect we use the definition:

$$R_{auto} = \frac{\langle n_i n_i - \sum_j k_{ij} k_{ij} \rangle}{\langle n_i n'_i - \sum_j k_{ij} k'_{ij} \rangle} - 1. \quad (6)$$

Here k_{ij} is the pad occupancy (0 or 1) for the j -th pad in the i -th bin.

Fig. 24: Widths of $dE_T/d\eta$ distributions compared with calculations from FRITIOF.

Fig. 25: E814 Multiplicity Detector ($0.8 < \eta < 3.8$)

Fig. 26: Event distribution in E_T for multiplicity window [80,100]. A minimum value E_T is shown by arrow.

3.2.3 Corrections and Cuts

In this section we enumerate the corrections and cuts performed in the analysis. The standard event selection procedure for E814 data is described elsewhere[9]. Due to very high sensitivity of correlation functions during current analysis some additional selection criteria were added.

1. Events with unusually low E_T in the participant calorimeter were rejected. The events are triggered on the multiplicity detector, which exhibited occasional bursts of noise, and by demanding a reasonable value of transverse energy, such false triggers were very effectively removed. A minimum value E_T is defined for each multiplicity window well below the peak of the distribution (see Fig. 26).

2. It was found two different types of events which show pathological noise patterns in the hit distribution. One of these, illustrated in Fig. 27b, occurs when noise fluctuations occur on a particular set of preamplifier channels. These events are detected by a strong cross-correlation (see Fig. 27a) between particular channels, which permits them to be identified and removed from the sample.

The second pattern, shown in Fig. 28b occurs due to unusually large noise fluctuation at the boundaries of the detectors. Such fluctuations result in a very high number of hits in one of the outermost rings (numbers 12 and 20). These events were cut out demanding the multiplicities in the outermost rings be not more than some threshold, which is determined from the ring multiplicity distributions (see Fig. 28a). The definition for maximum multiplicity in these rings was analogous to the definition of minimum E_T .

During the analysis of selected events some additional precautions were taken to avoid as much as possible other unphysical contributions to the correlations under study:

1. The signals from noisy pads were ignored and these pads were treated as dead, as was done in the multiplicity analysis. The total number of such pads is approximately 5%.
2. For pseudorapidity correlations we exclude contributions coming from the same discriminator

Fig. 27: (a) Correlation of the pad number 9, ring 13 with pads from rings 3,4,15,16. (b) One of the "cross type" events from multiplicity display.

Fig. 28: (a) Multiplicity distributions in one of the inner rings (ring 10) and one of the outermost rings (ring 12). The arrow indicates the threshold used in the analysis. (b) One of the events with unusually high multiplicity in the 20-th ring

module. This procedure simultaneously allows us to avoid the contribution of charge to the correlation function (see below).

3. For azimuthal correlations we exclude from the analysis the outermost rings.
4. For the most suspicious pads the correlations with all other pads were calculated. (As an example see Fig. 27a.) It was shown that a few pairs of pads of the detector are strongly correlated and these correlations cannot have physical origin. Such pairs were also excluded from the analysis.

There are also some other effects which could bias the results:

1. It was found in the previous analysis[1] that the charge sharing between two neighboring pads could give rise to signals from both pads from a single particle. The contribution of this effect to the total multiplicity is approximately 1%, but the contribution to the correlation function could be significant. We estimate the contribution to R to be $\Delta R_{ch.sharing} \approx 0.01 / \langle n \rangle$ where $\langle n \rangle$ is mean multiplicity in the bin in question. The problem can be easily solved by subtracting the contribution to the correlation function coming from neighboring pads.
2. The above procedure avoids also a second problem arising from γ -conversions. As was shown using FRITIOF event generator[1], due to the very small opening angle, leptons from γ -conversion contribute only to the same pad or adjacent pads.
3. It was found that corrections for the vertical beam movement are significant for calculations of correlations in the azimuthal angle space. Fortunately, knowledge of $dn/d\eta$, which is measured in the same experiment, and the distribution of the vertical beam offset allow one to calculate the corrections analytically without needing to know the exact beam position in each event. The correction procedure for the normalized two particle correlation function due to vertical beam movement can be described by the formula:

$$R_{1,2}^{corrected} = (R_{1,2}^{uncorrected} + 1) / C_{1,2}^{corr} - 1, \quad (7)$$

where the correction coefficient $C_{1,2}^{corr}$ is:

$$C_{1,2}^{corr} = \frac{I_{1,2}}{I_1 \cdot I_2}, \quad (8)$$

$$I_{1,2} = \int dy P(y) \int_{\Delta\eta_1 \delta\phi_1} d\eta_1 d\phi_1 \int_{\Delta\eta_2 \delta\phi_2} d\eta_2 d\phi_2 \frac{d^2 n}{d\eta_1 d\phi_1}(\eta_1, \phi_1; y) \frac{d^2 n}{d\eta_2 d\phi_2}(\eta_2, \phi_2; y), \quad (9)$$

$$I_1 = \int dy P(y) \int_{\Delta\eta_1 \delta\phi_1} d\eta_1 d\phi_1 \frac{d^2 n}{d\eta_1 d\phi_1}(\eta_1, \phi_1; y), \quad (10)$$

$$I_2 = \int dy P(y) \int_{\Delta\eta_2 \delta\phi_2} d\eta_2 d\phi_2 \frac{d^2 n}{d\eta_2 d\phi_2}(\eta_2, \phi_2; y). \quad (11)$$

Here $P(y)$ is normalized beam vertical position distribution function, and pseudorapidity η and azimuthal angle ϕ are calculated in the coordinate system centered on the detector.

Fig. 29: FRITIOF predictions for correlation function $R(\eta_1, \eta_2)$ for $\eta_1 = 1.3$ and $\eta_1 = 2.15$ indicated by arrows on the pictures, as a function of η_2 . Multiplicity window [120,130].

3.2.4 Results

Using the described procedure we have calculated two particle pseudorapidity correlation function for different targets, multiplicity windows, different control bin (position of η_1) as a function of η_2 , and also azimuthal angle correlation functions as a function of $\delta\phi$. The pseudorapidity correlations were also calculated within fixed sectors of different size in the azimuthal angle space. We present here only the results from lead target. The results from Si+Cu and Si+Al data are similar, although the analysis of these data are incomplete.

The data from FRITIOF event generator, which are presented in Fig. 29 (pseudorapidity correlations within a whole ring in the azimuthal angle space, $\delta\phi = 2\pi$) show no pseudorapidity correlation at the level of a few tenths of a percent. The dashed lines in Figs. 29-32 show the value $-1/N$, which one should expect for the case of no dynamical correlation. Results for other multiplicity windows are almost the same. Due to the scaling properties of the normalized two-particle correlation function it is possible to make some estimates from hadron-hadron and hadron-nucleus interactions at higher energies[21, 22, 23]. All of them, scaled to our multiplicities, give for the correlation function values around 0.02 to 0.03.

Our results for pseudorapidity correlations, presented in Fig. 30 and Fig. 31 for multiplicity windows [80,100] and [130,150], are between the FRITIOF predictions and the scaled correlation function from hadron-hadron and hadron-nucleus results at higher energies. There is no significant difference in the heights of the correlation functions, calculated within rather small sector in the azimuthal angle space and within the whole ring. For higher multiplicity the correlations are smaller.

The correlation functions in the azimuthal angle space, calculated within pseudorapidity window [0.96,1.61] show nonzero back-to-back correlations (see Fig. 32a) and are consistent with FRITIOF results (Fig. 32b) and the ISR pp results[24]. Our corrections for the azimuthal angle correlation function due to the vertical beam position distribution is sensitive to the assumed

Fig. 30: The correlation function $R(\eta_1, \eta_2)$ for $\eta_1 = 1.3$ and $\eta_1 = 2.15$, indicated by arrows on the pictures, as a function of η_2 calculated within different azimuthal angle sector sizes $\delta\phi$. Multiplicity window $[80,100]$. 27000 events.

Fig. 31: The same as Fig. 30 for multiplicity window [130,150]. 55000 events.

Fig. 32: The correlation function $R(\Delta\phi)$ as a function of azimuthal angle difference $\Delta\phi$ between two bins of azimuthal angle size $\pi/8$ and pseudorapidity $0.96 < \eta < 1.61$ for FRITIOF (multiplicity window [70,80]) and E814 Si+Pb data (multiplicity window [80,100]).

width of this distribution. We are currently studying the magnitude of this systematic error. The correlation functions for different multiplicity windows consistent with $1/N$ scaling.

4 Personnel

1. W. E. Cleland, principal investigator. Cleland's principal role in Experiment 814 has been in the area of organization of the trigger electronics. His efforts include planning of the trigger system, decisions regarding the purchase of commercial units for the trigger, supervision of the modification of existing electronics, and the design of new electronics which must be constructed. He also was responsible for the integration of the detector systems which make up the experiment. During the past year his major activity has been directing the analysis activities of the Pitt group.
2. S. Voloshin. Voloshin is a visitor from Moscow Engineering Institute, who has been with us since September 1992. He has undertaken the job of understanding the two-particle correlation signal in our data, as measured by our silicon pad multiplicity detector. Through a very careful analysis of systematic errors and noise problems in the detector, he has established that the correlations seen in E814 are in agreement with those predicted by Fritiof. He plans to be with us until May, 1993, and he hopes to join us again in E877 in the analysis of the multiplicity data from that experiment.
3. D. E. Kraus. Kraus is a part-time instructor at the University of Pittsburgh with considerable experience in experimental high energy physics. He has spent approximately two-thirds of his time as a research associate for Experiment E814 during the years 1987-90. His principal technical responsibilities in E814 have been in studies of the behavior of photomultiplier tubes in the environment of heavy ion experiments; design, construction, calibration and maintenance of the forward and magnet scintillators; and development of a DC light source for use in the participant and beam calorimeters. Currently he is spending a small fraction (1/6) of his time participating in the analysis of the E814 data.
4. K. Jayananda. Jayananda was a graduate student who carried out his thesis research in central collisions. He returned for a visit during the period November 1992-January 1993 in order to help with our detailed analysis of the two-particle correlation functions. While he was a student here, he took responsibility for the design and commissioning of the silicon multiplicity detector. His thesis was finished in October 1991, and included several studies of the charged multiplicity data. He now holds a faculty position at the University of Sri Jayewardenepura in Sri Lanka.
5. U. Sonnadara, postdoctoral research associate. Sonnadara was a graduate student who joined us in the summer of 1988. His thesis, a study of the $1p$ and $1n$ peripheral channels, was completed in December 1992 and is included in this report as Appendix A. In January 1993 he was appointed as a research associate, and he is interested in working on the trigger system for E877.
6. Z. Zhang. Zhang is a graduate student who joined our group in April, 1989, having passed the comprehensive exam in May, 1987. His principal responsibility is for the data taken

with the participant calorimeter, so much of his effort in previous years has been spent on the calibration and gain matching of this device, including a study of the triggering electronics. In addition Zhang built a trigger monitoring workstation based on expert systems techniques, installed in E814 before the June 1990 run. He has completed the data analysis for his thesis, which is a comparison of the E_T production in Si and Au induced collisions. He expects to defend his thesis in March 1993.

7. Tomas Joyce. Joyce is an undergraduate engineering student who has been working with our research group on a part time basis since the spring of 1991. He has carried out a number of data analysis tasks, including studies of the gains of photomultiplier tubes required for the peripheral analysis and studies of neutron calorimeter using calibration data taken with a proton beam.
8. Brian Lopresti. Lopresti is an undergraduate physics major who has been working with our group on a part time basis since the spring of 1991. He has been helping with analysis tasks, including studies of the timing properties of the time of flight counters installed in the experiment in 1990. One of his important contributions was the analysis of peripheral collisions with α particles in the final state, which included an understanding of the drift chamber behaviour in the presence of double tracks.
9. J. Rabel. Joe Rabel is an electronics engineer in our group who who has spent considerable effort on the E814 electronics during the past several years. His expertise in digital logic has been invaluable in carrying out the design and testing of the CAMAC modules needed for our trigger processor. Mr. Rabel also maintains the electronics modules which are used in E814/E877, including the large number of current monitors used for calibrating the calorimeters. During the past year, in connection with our RHIC R&D project, he constructed a prototype logic unit based on field programmable gate arrays, which will likely be used in the E877 trigger system.

References

- [1] K. Jayananda, Ph.D. thesis, University of Pittsburgh, 1991.
- [2] Bo Yu "Gas Proportional Detectors with Interpolating Cathode Pad Readout for High Track Multiplicities", Ph.D. thesis, University of Pittsburgh, December 1991
- [3] B. Bassalleck, et al. *Z. Phys C* 38 (1988) 45
- [4] J. Barrette et al. *Phys. Rev. Letters* 64 (1990) 1219.
- [5] J. Barrette et al. *Phys. Rev. C* 41 (1990) 1512.
- [6] J. Barrette et al. *Phys. Letters B* 252 (1990) 550.

- [7] J. Barrette et al. *Phys. Rev. C*, to be published.
- [8] J. Barrette et al., E814 Collaboration, *Phys. Rev. C* **45**, 2427(1992);
- [9] J. Barrette et al., E814 Collaboration, *Phys. Rev. C* **46**, 312(1992).
- [10] J. Fischer et al., *IEEE Trans. Nucl. Sci.*, NS-37 (1990).
- [11] R. Debbe et al., *IEEE Trans. Nucl. Sci.*, NS-37, (1990).
- [12] D. Lissauer and H. Takai, *Phys. Rev. C* **41** (1990) 2410.
- [13] C. Brechtmann, W. Heinrich, and E. V. Benton, *Phys. Rev. C* **39** (1989) 2222.
- [14] J. Stachel and G.R. Young, *Annu. Rev. Nucl. Part. Sci.* **42**, 237(1992)
- [15] T. Ludlam, A. Pfoh, and A. Shor, in *Proceedings of the RHIC Workshop I, Upton, 1985*, eds. P. Hausteiner and C. Woody (BNL Report No. 51921)
- [16] B. Andersson, G. Gustafson, and B. Nilsson-Almqvist, *Nucl. Phys.* **B281**, 289(1987); J. Costales, "Lund Model Results at or Near AGS Energies", E802 Internal Report E-802-MEM-8, 1988.
- [17] R.K. Bock et al., *Nucl. Instr. Methods* **186**, 533(1981)
- [18] L.D. Landau. *Izv. Akad. Nauk. SSSR, Ser. Fiz.*, 17:51, 1953. see also *Collected Papers of L. D. Landau*, edited by D. Ter Harr (Gordon and Breach, New York, 1965).
- [19] H. Sorge, H. Stöcker, and W. Greiner, *Ann. Phys.* **192**, 266(1989)
- [20] Y. Pang, T. J. Schlagel, and S. H. Kahana, *Phys. Rev. Lett.* **68**, 2743(1992), and priv. communication.
- [21] F. Botterwede et al., *Z. Phys.* **51C** (1991) 37.
- [22] R. E. Ansorge et al., *Z. Phys.* **37C** (1988) 191.
- [23] J. Whitmore, *Phys. Rep.* **27** (1976) 27.
- [24] S. R. Amendolia et al., *Nuovo Cimento* **31A** (1976) 17.

END

DATE
FILMED

5/03/93