DOE/PC/92540--T1

RECEIVED
MAR 03 1993
OSTI

Predictive Modeling of Particle-Laden,
Turbulent Flows

DOE/PC/92540--T1

DE93 008208

Quarterly Progress Report No. 1

covering the period of September 1 to December 1, 1992

to the Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, PA

Project Manager: Frank Shaffer

from the Department of Chemical Engineering
Carnegie Mellon University
Pittsburgh, PA 15213

Graduate Students: E.J. Bolio and C.M. Hrenya

Jennifer L. Sinclair
Principal Investigator

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Grant No. - DE-EG22-92PC92540

TABLE OF CONTENTS

List of Tables.....	ii
List of Figures	ii
Notation.....	iii
Abstract	iv
1. Introduction	1
2. Single-Phase Turbulence Models.....	3
3. Model Comparison.....	10
4. Conclusions	16
Sources Cited.....	17

List of Tables

Table 2.1 Numerical Values for the constants c_{μ} , c_1 , c_2 , σ_k , and σ_ϵ	7
Table 2.2 Summary of the functions f_μ , f_1 and f_2	8
Table 2.3 Summary of the terms D and E, and boundary conditions for k and ϵ	9
Table 3.1 Physical parameters for the experimental system of Schildknecht et al. (1979)	10

List of Figures

Figures 3.1a, 3.1b Comparison of the model predictions for the mean velocity with the experimental data of Schildknecht et al. (1979).....	11
Figures 3.2a, 3.2b Comparison of the model predictions for the turbulent kinetic energy with the experimental data of Schildknecht et al. (1979).....	13
Figures 3.3a, 3.3b Model predictions for the eddy viscosity for the system of Schildknecht et al. (1979).....	14
Figure 3.4 Model predictions for the turbulent kinetic energy dissipation rate in the wall region for the system of Schildknecht et al. (1979).....	15

Notation

Variables:

c_{μ}, c_1, c_2	constants in k- ϵ model
D	term included in the k equation
E	term included in the ϵ equation
f_{μ}, f_1, f_2	functions in k- ϵ model
k	gas fluctuating kinetic energy
P	pressure
r	radial coordinate
R	pipe radius
Re	Reynolds number based on the centerline velocity
R_T	turbulent Reynolds number
R_y	turbulent Reynolds number based on y
t	time
U_{τ}	frictional velocity
V	fluid mean velocity
V_{CL}	centerline fluid velocity
v'	fluid fluctuating velocity
x	spatial coordinate
y	spatial coordinate normal to the wall
y^+	dimensionless spatial coordinate

Greek symbols:

ϵ	fluid fluctuating kinetic energy dissipation rate
λ	Taylor's length scale
μ	fluid intrinsic viscosity
ν	fluid kinematic viscosity
ν_T	eddy viscosity
ρ	fluid density
σ_k	Prandtl turbulent number for k
σ_{ϵ}	Prandtl turbulent number for ϵ

The subscript *next* indicates the property value at the point next to the wall.

Abstract

The successful prediction of particle-laden, turbulent flows relies heavily on the representation of turbulence in the gas phase. Several types of turbulence models for single-phase gas flow have been developed which compare reasonably well with experimental data. In the present work, a "low-Reynolds" k - ϵ closure model is chosen to describe the Reynolds stresses associated with gas-phase turbulence. This closure scheme, which involves transport equations for the turbulent kinetic energy and its dissipation rate, is valid in the turbulent core as well as the viscous sublayer. Several versions of the low-Reynolds k - ϵ closure are documented in the literature. However, even those models which are similar in theory often differ considerably in their quantitative and qualitative predictions, making the selection of such a model a difficult task.

The purpose of this progress report is to document our findings on the performance of ten different versions of the low-Reynolds k - ϵ model on predicting fully developed pipe flow. The predictions are compared with the experimental data of Schildknecht, *et al.* (1979).

With the exception of the model put forth by Hoffman (1975), the predictions of all the closures show reasonable agreement for the mean velocity profile. However, important quantitative differences exist for the turbulent kinetic energy profile. In addition, the predicted eddy viscosity profile and the wall-region profile of the turbulent kinetic energy dissipation rate exhibit both quantitative and qualitative differences. An effort to extend the present comparisons to include experimental measurements of other researchers is recommended in order to further evaluate the performance of the models.

1. Introduction

Two-phase, particle-laden, turbulent flows occur in a variety of engineering applications. Examples include the processes of fluid catalytic cracking, coal gasification, calcination of alumina, desulfurization of flue gases, and combustion of a wide variety of fuels to environmental standards (Rhodes and Geldart, 1989). These flows cannot be described simply due to the complex interaction of the gas and solid velocity fields. The radial non-uniformity of voidage, high gas-solid slip velocities, and the downflow of solids in the riser annulus in dense-phase conveying, are all types of flow phenomena resulting from this interaction.

Previous modeling efforts have been able to qualitatively predict the flow phenomena mentioned above by treating the particle-particle and particle-wall collisions analogous to molecular collisions as described by the kinetic theory of gases (Sinclair and Jackson, 1989; Pita and Sundaresan, 1991). However, a quantitative comparison of these model predictions with experimental two-phase data would have been premature since these models did not incorporate gas-phase turbulence. Louge *et al.* (1991) proposed the first two-phase model which included a description of gas-phase turbulence. This model employs a high-Reynolds one-equation turbulence closure model and a kinetic-theory based approach which is valid only at the limit of very dilute flows with elastic particle-particle collisions. Although their predictions were in agreement with reported experimental measurements, they also concluded that a better turbulence closure is required to improve the model performance.

The overall goal of this research is to expand on the previous efforts in order to develop a model which accurately predicts the behavior of gas-solid mixtures in fully developed

isothermal pipe flow. This effort begins by introducing a more general gas-phase turbulence closure scheme, namely a low-Reynolds version of the k - ϵ closure model. Several versions of this model have been documented in the literature. Although these versions are similar in form, they have been developed using different approaches and therefore are expected to predict differently. In a review of the existing low-Reynolds k - ϵ models, Patel *et al.* (1985) confirmed that important differences do exist between the predictions of these models. Hence, the selection of one of these versions to serve as the basis for the two-phase model becomes a non-trivial task. Unfortunately, Patel's review did not compare the model predictions with experimental data obtained from pipe flow. In addition, since the publication of this review, more versions of the k - ϵ model have been published. Thus, the immediate focus of this research is to evaluate the ability of all existing low-Reynolds k - ϵ closure models to predict fully developed pipe flow.

2. Single-Phase Turbulence Models

The description of turbulent flows for a single phase is still very much an active research area. The different approaches to the problem are divided into those models that solve the Navier-Stokes (NS) equations in an exact form, and those models that solved the time-averaged NS equations, i.e., the Reynolds equations. Currently, the exact solution of the NS equations is only possible for relatively simple problems due to the high computational cost of resolving the small scale of the turbulent phenomena. Thus, those models based of the Reynolds equations offer the most viable choice from the engineering standpoint.

For a pressure-gradient driven flow, the Reynolds equations are:

$$\rho \frac{\partial V_i}{\partial t} + \rho V_j \frac{\partial V_i}{\partial x_j} = - \frac{\partial P}{\partial x_i} + \frac{\partial}{\partial x_j} \left(\mu \frac{\partial V_i}{\partial x_j} - \rho \overline{v'_i v'_j} \right) \quad (2.1)$$

where V_i and P are the mean velocity and pressure which result from the time-averaging process.

The term $\rho \overline{v'_i v'_j}$, which is also introduced by the averaging process, represents the transport of momentum due to the fluctuating turbulent motion. It is the determination of this correlation of the fluctuating velocities which is the central problem of all the turbulence models based on the Reynolds equations. Several alternatives are available to approximate this correlation, ranging from the simplest model based on Prandtl's mixing length to the rather sophisticated Reynolds stress models which utilize one transport equation for every correlation $\overline{v'_i v'_j}$. Among these choices, a two-equation closure model, the k- ϵ model, has proven to be the most widely tested and successfully applied

turbulence model (Rodi, 1979). Recent studies (Martinuzzi and Pollard, 1989a, 1989b) indicate that the k-ε model performs better than the conceptually superior Reynolds stress models.

The k-ε model is based on the concept of the eddy viscosity ν_T . An assumption of this concept is that the turbulent stresses, like the viscous stresses, are proportional to mean-velocity gradients:

$$\overline{v'_i v'_j} = - \nu_T \left(\underline{\underline{\nabla V}}_i + \underline{\underline{\nabla V}}_j^T \right) \quad (2.2)$$

This analogy is further extended by assuming that the eddy viscosity is proportional to a velocity scale and a length scale that characterizes the turbulent motion, just as the intrinsic viscosity is proportional to the average velocity and the mean free path of the molecules. Kolmogorov and Prandtl independently proposed to choose the turbulent kinetic energy, k , as the variable representing the velocity scale. For the length scale, several variables such as the kinetic energy dissipation rate ϵ , the turbulent frequency, the turbulent vorticity, and others have been suggested. The choice of ϵ as the length scale variable has proven the most successful (Rodi, 1979). Hence, ν_T is prescribed via the Kolmogorov-Prandtl expression:

$$\nu_T = c_\mu \frac{k^2}{\epsilon} \quad (2.3)$$

The profiles for k and ϵ are obtained by solving two transport equations. For this reason, the k-ε model is known as a two-equation closure scheme. The k and the ϵ equations are given in cylindrical coordinates for a fully developed flow at steady state:

$$\frac{1}{r} \frac{\partial}{\partial r} \left[r \frac{\nu_T}{\sigma_k} \frac{\partial k}{\partial r} \right] + \nu_T \left(\frac{\partial V}{\partial r} \right)^2 - \epsilon = 0 \quad (2.4)$$

$$\frac{1}{r} \frac{\partial}{\partial r} \left[r \frac{v_T}{\sigma_\epsilon} \frac{\partial \epsilon}{\partial r} \right] + \frac{c_1 v_T \epsilon}{k} \left(\frac{\partial V}{\partial r} \right)^2 - \frac{c_2 \epsilon^2}{k} = 0 \quad (2.5)$$

The k transport equation describes the balance between the diffusive transport by turbulent motion (first term), the production by interaction of turbulent stresses and mean velocity gradients (second term), and the destruction by dissipation (third term). Similar processes are represented by the three terms of the ϵ equation. σ_k and σ_ϵ are the empirically determined turbulent Prandtl numbers for k and ϵ , respectively. c_μ , c_1 and c_2 are also constants.

The particular form of the k- ϵ model outlined above is the original one as first published by Jones and Launder (1972). This form is very successful in the prediction of single-phase flows with sufficiently high Reynolds number where viscous effects are negligible. Hence, this form of the model is not applicable near a solid boundary. For confined flows, wall functions are often applied at a small distance away from the wall, bridging over the viscous sublayer. These functions, which are based on experimental data, cannot easily be extended to two-phase flow. In order to avoid using wall functions, modifications to the original k- ϵ model have been made. The modified forms of the k- ϵ model, known as "low-Reynolds" k- ϵ models, can be applied continuously throughout the turbulent core and the viscous sublayer. The modifications to the original model are:

1. The dissipation rate ϵ is replaced by a "dissipation variable" $\epsilon^* = \epsilon - D$.

Physically, ϵ^* represents the isotropic part of the dissipation of the random kinetic energy. The use of the dissipation variable ϵ^* generates an additional term D in the k equation. The term D is chosen in such a way so that the dissipation variable ϵ^* can be equated to zero at the wall, a numerically convenient boundary condition.

2. An extra term E is added to the ϵ equation in order to yield realistic k and ϵ distributions in the viscous sublayer.
3. Viscous diffusion of k and ϵ is accounted for by the addition of the intrinsic viscosity to the corresponding diffusion terms.
4. The functions f_μ , f_1 and f_2 are introduced to modify the constants c_μ , c_1 and c_2 . These functions depend on different dimensionless numbers related to the turbulence phenomena, the velocity field, and the geometry:

$$R_T = \frac{k^2}{\nu \epsilon} \quad (2.6) \quad R_y = \frac{\sqrt{k} y}{\nu} \quad (2.7) \quad Re_{avg} = \frac{2R \langle V \rangle}{\nu} \quad (2.8)$$

$$y = R - r \quad (2.9) \quad y^+ = \frac{U_T}{\nu} y \quad (2.10) \quad \lambda^2 = \frac{10 \nu k}{\epsilon} \quad (2.11)$$

5. The use of wall functions is eliminated, and boundary conditions for k and ϵ are enforced at the wall.

With these modifications included, the equations (2.3), (2.4) and (2.5) become:

$$\frac{1}{r} \frac{\partial}{\partial r} \left[r \left(\nu + \frac{\nu_T}{\sigma_k} \right) \frac{\partial k}{\partial r} \right] + \nu_T \left(\frac{\partial V}{\partial r} \right)^2 - \epsilon - D = 0 \quad (2.12)$$

$$\frac{1}{r} \frac{\partial}{\partial r} \left[r \left(\nu + \frac{\nu_T}{\sigma_\epsilon} \right) \frac{\partial \epsilon}{\partial r} \right] + \frac{c_1 f_1 \nu_T \epsilon}{k} \left(\frac{\partial V}{\partial r} \right)^2 - \frac{c_2 f_2 \epsilon^2}{k} + E = 0 \quad (2.13)$$

$$\nu_T = c_\mu f_\mu \frac{k^2}{\epsilon} \quad (2.13)$$

Several single-phase "low-Reynolds" k - ϵ models have been proposed and excellent reviews on this subject are offered by Patel *et al.* (1985) and Shih (1988). However, since the publication of these reviews, more versions have been published. All of the

versions differ in the numerical values assigned to the constants, the expressions used for D , E , f_μ , f_1 and f_2 , as well as in the boundary conditions for k and ϵ . Table 2.1 summarizes the numerical values assigned to the constants of ten versions and the original k - ϵ model. The models are listed in chronological order.

Model	Initials	c_μ	c_1	c_2	σ_k	σ_ϵ
Original k - ϵ	k - ϵ	0.09	1.45	2.0	1.0	1.3
Jones and Launder (1972)	JL	0.09	1.45	2.0	1.0	1.3
Launder and Sharma (1975)	LS	0.09	1.44	1.92	1.0	1.3
Hoffman (1975)	HO	0.09	1.81	2.0	2.0	3.0
Hassid and Poreh (1978)	HP	0.09	1.45	2.0	1.0	1.3
Dutoya and Michard (1981) ¹	DM	0.09	1.35	2.0	0.9	0.95
Chien (1982)	CH	0.09	1.35	1.8	1.0	1.3
Lam and Bremhorst (1981)	LB	0.09	1.44	1.92	1.0	1.3
Lai and So (1990)	LSO	0.09	1.35	1.8	1.0	1.3
Myong and Kasagi (1990)	MK	0.09	1.4	1.8	1.4	1.3
So, Zhang and Speziale (1991)	SZS	0.096	1.5	1.83	0.75	1.45

Table 2.1 Numerical Values for the constants c_μ , c_1 , c_2 , σ_k , and σ_ϵ

Table 2.2 shows the different functions f_μ , f_1 and f_2 for the same group of models. Table 2.3 lists the terms D and E , and the boundary conditions for k and ϵ .

¹ In the definition of R_T , ν_T and λ , this model requires the substitution of ϵ by $\epsilon + D/\rho$

Initials	f_μ	f_1	f_2
k r	1	1	1
JL	$\exp\left[\frac{-2.5}{1 + R_T/50}\right]$	1	$1 - 0.3 \exp(-R_T^2)$
LS	$\exp\left[\frac{-3.4}{(1 + R_T/50)^2}\right]$	1	$1 - 0.3 \exp(-R_T^2)$
HO	$\exp\left[\frac{-1.75}{1 + R_T/50}\right]$	1	$1 - 0.3 \exp(-R_T^2)$
HP	$1 - \exp(-0.0015 R_T)$	1	$1 - 0.3 \exp(-R_T^2)$
DM	$1 - 0.86 \exp\left[\left(-\frac{R_T}{600}\right)^2\right]$	$1 - 0.04 \exp\left[\left(-\frac{R_T}{50}\right)^2\right] + \left(\frac{0.25}{c_1}\right)\left(\frac{\Delta}{y}\right)^2$	$1 - 0.3 \exp\left[\left(-\frac{R_T}{50}\right)^2\right] - \left(\frac{0.08}{c_2}\right)\left(\frac{\Delta}{y}\right)^2$
CH	$1 - \exp(-0.0115 y^+)$	1	$1 - \frac{0.4}{1.8} \exp\left[\left(-\frac{R_T}{6}\right)^2\right]$
LB	$[1 - \exp(-0.0165 y^+)]^2 (1 + 20.5/R_T)$	$1 + (0.05/f_\mu)^3$	$1 - \exp(-R_T^2)$
ISO	$1 - \exp(-0.0115 y^+)$	$1 + \left[1 - 0.6 \exp\left(-\frac{R_T}{10^4}\right)\right] \exp\left[\left(-\frac{R_T}{64}\right)^2\right]$	$1 - \frac{2}{9} \exp\left[\left(-\frac{R_T}{6}\right)^2\right]$
MK	$[1 - \exp(-y^+/70)][1 + 3.45/R_T]$	1	$1 - \frac{2}{9} \exp\left[\left(-\frac{R_T}{6}\right)^2\right] \left[1 - \exp\left(-\frac{y^+}{5}\right)\right]^2$
SZS	$[1 + 3.45/R_T] \tanh(y^+/115)$	1	1

Table 2.2 Summary of the functions f_μ , f_1 and f_2

Initials	Term D	Term E	B.C.
k-e	0	0	Wall Functions
JL	$2\nu \left(\frac{\partial v k}{\partial r} \right)^2$	$2\nu v_T \left(\frac{\partial^2 v}{\partial r^2} \right)^2$	$k = \varepsilon = 0$
LS	$2\nu \left(\frac{\partial v k}{\partial r} \right)^2$	$2\nu v_T \left(\frac{\partial^2 v}{\partial r^2} \right)^2$	$k = \varepsilon = 0$
HO	$\frac{\nu}{r} \frac{\partial k}{\partial r}$	0	$k = \varepsilon = 0$
HP	$\frac{2\nu k}{y^2}$	$-2\nu \left(\frac{\partial \varepsilon}{\partial r} \right)^2$	$k = \varepsilon = 0$
DM	$2\nu \left(\frac{\partial v k}{\partial r} \right)^2$	$-c_2 f_2 \frac{\varepsilon}{k} D$	$k = \varepsilon = 0$
CH	$2\nu k / y^2$	$(-2\nu \varepsilon / y^2) \exp(-0.5 y^+)$	$k = \varepsilon = 0$
LB	0	0	$\frac{\partial k}{\partial r} = 0, \quad \varepsilon = \nu \frac{\partial^2 k}{\partial r^2}$
LSO	0	$2\nu c_2 f_2 \frac{\varepsilon}{k} \left(\frac{\partial v k}{\partial r} \right)^2 + \exp \left[- \left(\frac{R_T}{64} \right)^2 \right] \left[\left(\frac{7}{9} c_2 - 2 \right) \frac{\varepsilon}{k} \left(\varepsilon - 2\nu \left(\frac{\partial v k}{\partial r} \right)^2 \right) - \frac{1}{2k} \left(\varepsilon - \frac{2\nu k}{y^2} \right)^2 \right]$	$k = 0, \quad \varepsilon = 2\nu \left(\frac{\partial v k}{\partial r} \right)^2$
MK	0	0	$k = 0, \quad \varepsilon = \frac{4\nu k_{next} \varepsilon_{next}}{y_{next}^2}$
SZS	0	$\left[2\nu f_2 c_2 \frac{\varepsilon}{k} \left(\frac{\partial v k}{\partial r} \right)^2 + \exp \left(- \left(\frac{R_T}{64} \right)^2 \right) \right] \left[- \frac{2\varepsilon}{k} \left(\varepsilon - 2\nu \left(\frac{\partial v k}{\partial r} \right)^2 \right) + \frac{3}{2k} \left(\varepsilon - \frac{2\nu k}{y^2} \right)^2 \right]$	$k = 0, \quad \varepsilon = 2\nu \left(\frac{\partial v k}{\partial r} \right)^2$

Table 2.3 Summary of the terms D and E, and boundary conditions for k and ε

3. Model Comparison

In this section, comparisons are made between the predictions of the ten different versions of the "low-Reynolds" k- ϵ model with the experimental measurements of Schildknecht *et al.* (1979). The primary purpose of this comparison is to gauge the success of each of the different closures in an effort to determine which closure should be used as the base turbulence model for the two-phase flow description.

The data of Schildknecht *et al.* was obtained using a hot-wire probe to measure the velocity profiles for the fully-developed flow of air in a cylindrical pipe. The Reynolds number based on the centerline velocity is 21,800. Other details of the experiment are listed in Table 3.1.

Pipe radius [m]	0.025
Air density [kg/m ³]	1.204554
Air viscosity [kg/m-s]	0.0000175
Centerline Velocity V_{CL} [m/s]	6.3438
Frictional Velocity U_τ [m/s]	0.29

Table 3.1 Physical parameters for the experimental system of Schildknecht *et al.* (1979)

Figures 3.1a and 3.1b show a comparison of the mean gas velocity prediction of the ten closures with the experimental data. In these plots, the frictional velocity matches the measured value. The predictions of the ten versions are divided in two plots for clarity, and the model predictions are organized chronologically. Figure 3.1a shows the first five models, and Figure 3.1b shows the five most recent models.

Figures 3.1a, 3.1b Comparison of the model predictions for the mean velocity with the experimental data by Schildknecht et al (1979). The frictional velocity U_τ is 0.29 m/s.

All of the models are in good agreement with the experimental measurements, within 15% of the V_{CL} experimental value, except for the model of Hoffman which has a 31.5% error. The reasonable agreements obtained for the mean velocity predictions should not be surprising since the prediction of this profile was the primary purpose of all of the models. The LS and CH models offer the best overall agreement, while the HO presents the worst overall agreement.

In Figure 3.2a and 3.2b, we show a comparison of the predicted turbulent kinetic energy k with the experimental data. Even though all of the predictions have the same qualitative trend as the experimental data, significant variations in the quantitative predictions exist. With the exception of the MK model, all of the models overpredict the centerline turbulent kinetic energy, with differences as large as 77.5% (HP model). The predictions of the location of characteristic peak of these profiles are very good. However, the predicted magnitude of the peak differs from model to model. Three models, DM, LSO and SZS, overpredict the peak value for k , and the largest overprediction has a difference of 9.2% (LSO model). The rest of the models underpredict the k peak with differences as large as 29.7% (LS model).

In Figures 3.3a and 3.3b, we show the model predictions of the eddy viscosity. The agreement of all the models with respect to each other is poor. Differences in the predicted centerline values can vary more than 100%. Furthermore, qualitative differences in the profiles are also noticed. While the majority of the profiles have a parabolic shape, the MK presents a change in concavity near the centerline, which is in agreement with the observed behavior.

Figures 3.2a, 3.2b Comparison of the model predictions for the turbulent kinetic energy with the experimental data by Schildknecht et al (1979). The frictional velocity U_τ is

Figures 3.3a, 3.3b Model predictions for the eddy viscosity for the system of Schildknecht *et al.*

In Figure 3.4, we show a plot of the prediction of the dimensionless dissipation rate ε at the wall region. The model predictions for the MK and the SZS models are shown. An important qualitative difference is noticed. The MK ε profile has a peak near the wall. The same behavior is predicted by all the other models, except the SZS model. The SZS model predicts a plateau where the other models reach the maximum value, but thereafter the dissipation rate increases reaching the maximum value at the wall. This behavior has been predicted by the direct numerical simulation of the Navier-Stokes equations.

Figure 3.4 Model predictions for the turbulent kinetic energy dissipation rate in the wall region for the system of Schildknecht *et al.* The frictional velocity U_τ is 0.29 m/s.

4. Conclusions

Before modifying a single-phase turbulence model to account for the presence of particles, we must be certain that the model can accurately predict single-phase pipe flow. From the comparisons of the ten low-Reynolds k - ϵ closure models with the experimental measurements of Schildknecht *et al.*, it is concluded that significant qualitative and quantitative differences exist among the closures. In order to further evaluate the ability of each of the models, comparisons of model predictions with additional experimental data which includes turbulent kinetic energy and eddy viscosity profiles are needed. Specifically, the measurements to be considered include those of Laufer (1954) and Lawn (1971).

Sources Cited

- Dutoya, D. and P. Michard. 1981. A Program for Calculating Boundary Layers and Heat Transfer along Compressor and Turbine Blades. In *Numerical Methods in Heat Transfer*. Edited by R. W. Lewis K. Morgan and O.C. Zienkiewicz. 413-428. John Wiley and Sons, Ltd.
- Chien, K. 1982. Predictions of Channel and Boundary-Layer Flows with a Low-Reynolds-Number Turbulence Model. *AIAA J.* 20(1): 33-38.
- Hassid, S. and M. Poreh. 1978. A Turbulent Energy Dissipation Model for Flows With Drag Reduction. *J. Fluid Eng.* 100: 107-112.
- Hoffman, G. H. 1975. Improved form of the low Reynolds number k- ϵ turbulence model. *Phys. Fluids* 18(3): 309-312.
- Jones, W. P., and B.E. Launder. 1972. The Prediction of Laminarization with a Two-Equation Model of Turbulence. *Int. J. Heat Mass Transfer* 15: 301-314.
- Jones, W. P. and. B. E. Launder. 1973. The calculation of low-Reynolds-number phenomena with a two-equation model of turbulence. *Int. J. Heat Mass Transfer* 16: 1119-1130.
- Lai, Y.G. and R.M.C. So. 1990. On near-wall turbulent flow modelling. *J. Fluid Mech.* 221(641-673).
- Lam, C.K.G. and K. Bremhorst. 1981. A Modified Form of the k- ϵ Model for Predicting Wall Turbulence. *J. Fluids Eng.* 103(Sep. 1981): 456-460.
- Laufer, John. 1954. The structure of turbulence in fully developed pipe flow. National Advisory Committee for Aeronautics (NACA). *NTIS*, 1174.
- Launder, B. E. and. B. I. Sharma. 1974. Application of the Energy-Dissipation Model of Turbulence to the Calculation of Flow Near a Spinning Disc. *Letters Heat Mass Transf.* 1: 131-138.
- Martinuzzi, R. and. A. Pollard. 1989. Comparative Study of Turbulence Models in Predicting Turbulent Pipe Flow Part I: Algebraic Stress and k- ϵ Models. *AIAA J.* 27(1): 29-36.
- Myong, H.K. and N. Kasagi. 1990. A New Approach to the Improvement of k- ϵ Turbulence Model for Wall-Bounded Shear Flows. *JSME Int. J. Series II*, 33(1): 63-72.
- Patel, V., W. Ródi, and G. Scheuerer. 1985. Turbulence Models for Near-Wall and Low Reynolds Number Flows: A Review. *AIAA J.* 23(9): 1308-1319.
- Pita, J. and. S. Sundaresan. 1991. Gas-Solid Flow in Vertical Tubes. *AIChE J.* 37(7): 1009-1018.

Pollard, A. and R. Martinuzzi. 1989. Comparative Study of Turbulence Models in Predicting Turbulent Pipe Flow Part II: Reynolds Stress and k-e Models. *AIAA J.* 27(12): 1714-1721.

Rhodes, M.J. and D. Geldart. 1989. The Upward Flow of Gas/Solid Suspensions, Part 1: A Model for the Circulating Fluidized Bed Incorporating Dual Level Gas Entry into the Raiser. *Chem. Eng. Res. Des.* 67: 20-37

Rodi, W. 1982. Examples of Turbulence Models for Incompressible Flows. *AIAA J.* 20(7): 872-879.

Schildknecht, M., Miller, J.A. and G.E. Meier. 1979. The influence of suction on the structure of turbulence in fully developed pipe flow. *J. Fluid Mech.* 90, part I: 67-107.

Shih, T. I. 1988. Mathematical Models for the Numerical Study of Turbulent Flows. *J. Chinese Inst. Eng.* 11(2): 121-136.

So, R. M. C., H.S. Zhang and C.G. Speziale. 1991. Near-Wall Modeling of the Dissipation Rate Equation. *AIAA J.* 29(12): 2069-76.

END

**DATE
FILMED**

3 / 25 / 93