MASTER

Meteorological Validation Program

CANDIDATE WIND TURBINE GENERATOR SITE
ANNUAL DATA SUMMARY
FOR
CULEBRA, PUERTO RICO
OCTOBER 1978 THROUGH SEPTEMBER 1979

Prepared for U.S. Department of Energy
Division of Distributed Solar Technology
Wind Systems Branch, Washington, DC
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

CANDIDATE WIND TURBINE GENERATOR SITE
ANNUAL DATA SUMMARY
FOR
CULEBRA, PUERTO RICO
OCTOBER 1978 THROUGH SEPTEMBER 1979

Prepared for
U.S. Department of Energy
Division of Distributed Solar Technology
Wind Systems Branch
Washington, DC

July 1980

PACIFIC NORTHWEST LABORATORY
Richland, Washington 99352

1.0 INTRODUCTION

This report summarizes wind speed and direction data collected on meteorological towers at 14 candidate and wind turbine generator installation sites from October 1978 through September 1979. The basic method of data collection is by digital data cassette recording systems. For the digital data reported, an instantaneous sample is recorded every 2 minutes.

Section 2.0 of this report provides an explanation of each data summary table as well as information on how specific values were computed. The rest of the report presents the annual summarized data for each site. This report was prepared for the Department of Energy's Wind Systems Branch, Division of Distributed Solar Technology, by the Pacific Northwest Laboratory (PNL). Comments regarding this or other data reports should be directed to Mr. William F. Sandusky of PNL at 509-376-4823 (FTS 444-4823) or Dr. David S. Renné of PNL at 509-376-4623 (FTS 444-4623).

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

2.0 SUMMARY TABLES

Summarized data for each site are presented in eight (8) tables. Discussion of data represented in each table and the method of calculation are given below. Wind speeds are reported in meters per second, elevation in meters, and direction in degrees.

A value reported less than -900.00 indicates missing data. A value less than or equal to -900.00 or zero at the mid-level indicates that data are not collected at this level.

TITLE AND FUNCTION

Table 1.1

Sensor Performance. Sensor performance provides the percentage of time the recording system was operating and the percentage of time acceptable data were acquired by the meteorological sensors. The values given under the label "% on-line" are obtained by dividing the total number of data scans collected by the total possible number of data scans. The values given under the label "% recovered" are obtained by dividing the total number of acceptable data scans collected by the total possible number of data scans.

Table 1.2

Annual Means and Standard Deviations. This table provides the mean wind speed, wind direction, and standard deviation of wind speed for each sensor level.

Table 1.3

Maximum Wind Speed. The highest recorded wind speed for each level is given along with date and time of occurrence. Corresponding wind direction and wind speed values at the other sensor levels are also given.

Table 1.4

Wind Speed and Direction Versus Time-of-Day. Mean wind speed and direction values and standard deviation of wind speed are reported for each hour of

the day for the month. Data reported for 00:00 represent the average of the data recorded between 23:00 and 00:00. Data are provided for each level of instrumentation.

Table 1.5

Frequency Distribution of Wind Speed. For each sensor level, the total number of observations and percentage of occurrence are given for a number of classes of wind speed. The recovery rate for each wind speed sensor is given at the bottom of the table.

Table 1.6.

Cumulative Frequency Distribution of Wind Speed. Both the cumulative number of observations and percentage of cumulative frequency distribution of wind speed are given for various intervals. The value of 2.0 under the wind speed column represents wind speed occurrences up to and including 2.0 m/s. Information is given for each sensor level.

Table 1.7.

Wind Speed Persistence Frequency. The occurrence of the duration of wind speed in various speed class intervals is given as a function of time. The value of 3.0 under the hours column means that the wind in the indicated speed class persists between 2.5 and 3 hours. Data are given for the top sensor level.

Table 1.8.

Power Law Exponent. The power law exponent between sensor levels is computed as indicated in the notes. These values are averaged according to wind direction intervals from the highest wind direction sensor. The value under the Alpha (A, B, C) column indicates a best fit value of the other three values. If the site only has two levels of instrumentation, no best fit value will be calculated. The percentage of occurrence of wind direction for each sensor level is also given.

Table 1.9.

Turbulence Intensity. The turbulence intensity for each sensor level is given as a function of wind direction. Values reported are based on first computing an hourly turbulence intensity, as noted in the table, from the 30 instantaneous values obtained during the hour. All the hourly values are summed and then divided by the number of hours in the month to produce a monthly average value.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

SITE ID: PR
 SITE LOCATION: CULEBRA, PR.
 DATA : OCTOBER 1978 THROUGH SEPTEMBER 1979

 1.1 SENSOR PERFORMANCE

TOTAL POSSIBLE SAMPLES: 8760

SENSOR	% ON-LINE	% RECOVERED
WS(A)	100.0	71.7
WD(A)	100.0	73.8
WS(C)	100.0	72.5
WD(C)	100.0	72.1

 1.2 ANNUAL MEANS AND STANDARD DEVIATIONS

	HEIGHT (METERS)	MEAN WS	MEAN WD	STD DEV SPEED
SITE DATA (A)	45.7	7.4	267.5	2.6
(C)	9.1	6.5	137.6	2.5

 1.3 MAXIMUM WIND SPEED

ELEVATION (METERS)	WIND SPEED	WIND DIR.	DATE	TIME	OTHER LEVELS
(A) 45.7	31.7	65.3	09/01/79	02:00	(B)-999.9 (C) 29.1
(C) 9.1	29.1	70.2	09/01/79	02:00	(A) 31.7 (B)-999.9

 NOTES:

1. SITE ELEVATION: 80 METERS ABOVE SEA LEVEL.
3. SENSOR LEVEL B NOT AVAILABLE AT SITE PR.

SITE ID: PR
SITE LOCATION: CULEBRA, PR.
DATA : OCTOBER 1978 THROUGH SEPTEMBER 1979

1.4 WIND SPEED AND DIRECTION VERSUS TIME-OF-DAY

TIME OF DAY	LEVEL A		LEVEL B		LEVEL C	
	WS	WD	WS	WD	WS	WD
00:00	7.3	270.2	0.0	0.0	6.3	28.3
01:00	7.3	202.4	0.0	0.0	6.3	311.7
02:00	7.2	268.5	0.0	0.0	6.2	186.3
03:00	7.2	231.8	0.0	0.0	6.2	185.2
04:00	7.2	342.2	0.0	0.0	6.2	226.6
05:00	7.3	180.1	0.0	0.0	6.2	334.5
06:00	7.2	333.6	0.0	0.0	6.2	125.2
07:00	7.2	168.2	0.0	0.0	6.3	266.7
08:00	7.3	167.6	0.0	0.0	6.6	202.1
09:00	7.5	277.2	0.0	0.0	6.9	54.2
10:00	7.8	248.2	0.0	0.0	7.0	118.8
11:00	7.7	247.7	0.0	0.0	7.0	46.5
12:00	7.7	233.6	0.0	0.0	7.0	98.9
13:00	7.6	260.1	0.0	0.0	6.8	127.4
14:00	7.5	112.9	0.0	0.0	6.7	334.6
15:00	7.3	171.5	0.0	0.0	6.5	118.0
16:00	7.1	229.7	0.0	0.0	6.3	51.9
17:00	7.2	32.7	0.0	0.0	6.3	117.7
18:00	7.4	301.8	0.0	0.0	6.4	149.2
19:00	7.5	299.2	0.0	0.0	6.5	110.7
20:00	7.5	323.0	0.0	0.0	6.4	141.7
21:00	7.5	0.3	0.0	0.0	6.5	188.7
22:00	7.5	198.7	0.0	0.0	6.5	162.1
23:00	7.3	328.6	0.0	0.0	6.3	83.7

SITE ID: PR
 SITE LOCATION: CULEBRA, PR.
 DATA : OCTOBER 1978 THROUGH SEPTEMBER 1979

1.5 FREQUENCY DISTRIBUTION OF WIND SPEED

WIND SPEED	LEVEL A COUNT	LEVEL B % COUNT	LEVEL C % COUNT	%
0.0- 0.5	0	0.0	0	0.0
0.5- 1.0	11	0.2	0	0.0
1.0- 1.5	3	0.0	0	0.0
1.5- 2.0	13	0.2	0	0.0
2.0- 2.5	31	0.5	0	0.0
2.5- 3.0	52	0.8	0	0.0
3.0- 3.5	78	1.2	0	0.0
3.5- 4.0	137	2.2	0	0.0
4.0- 4.5	262	4.2	0	0.0
4.5- 5.0	357	5.7	0	0.0
5.0- 5.5	426	6.8	0	0.0
5.5- 6.0	526	8.4	0	0.0
6.0- 6.5	636	10.1	0	0.0
6.5- 7.0	602	9.6	0	0.0
7.0- 7.5	590	9.4	0	0.0
7.5- 8.0	505	8.0	0	0.0
8.0- 8.5	440	7.0	0	0.0
8.5- 9.0	321	5.1	0	0.0
9.0- 9.5	219	3.5	0	0.0
9.5-10.0	222	3.5	0	0.0
10.0-11.0	328	5.2	0	0.0
11.0-12.0	195	3.1	0	0.0
12.0-13.0	121	1.9	0	0.0
13.0-14.0	77	1.2	0	0.0
14.0-15.0	31	0.5	0	0.0
15.0-16.0	34	0.5	0	0.0
16.0-17.0	21	0.3	0	0.0
17.0-18.0	13	0.2	0	0.0
18.0-19.0	8	0.1	0	0.0
19.0-20.0	4	0.1	0	0.0
20.0-25.0	7	0.1	0	0.0
>25.0	9	0.1	0	0.0

RECOVERY RATES
 LEVEL A LEVEL B LEVEL C
 71.7 0.0 72.5

SITE ID: PR
 SITE LOCATION: CULEBRA, PR.
 DATA : OCTOBER 1978 THROUGH SEPTEMBER 1979

1.6 CUMULATIVE FREQUENCY DISTRIBUTION OF WIND SPEED

WIND SPEED	LEVEL A		LEVEL B		LEVEL C	
	CFD (ABS)	CFD (Z)	CFD (ABS)	CFD (Z)	CFD (ABS)	CFD (Z)
0.5	0	0.00	0	0.00	0	0.00
1.0	11	0.18	0	0.00	7	0.11
1.5	14	0.22	0	0.00	25	0.40
2.0	27	0.43	0	0.00	69	1.11
2.5	58	0.92	0	0.00	160	2.58
3.0	110	1.75	0	0.00	324	5.22
3.5	188	2.99	0	0.00	544	8.77
4.0	325	5.18	0	0.00	807	13.01
4.5	587	9.35	0	0.00	1246	20.08
5.0	944	15.03	0	0.00	1656	26.69
5.5	1370	21.82	0	0.00	2246	36.20
6.0	1896	30.20	0	0.00	2830	45.62
6.5	2532	40.32	0	0.00	3412	55.00
7.0	3134	49.91	0	0.00	3952	63.70
7.5	3724	59.31	0	0.00	4387	70.71
8.0	4229	67.35	0	0.00	4783	77.10
8.5	4669	74.36	0	0.00	5078	81.85
9.0	4990	79.47	0	0.00	5340	86.07
9.5	5209	82.96	0	0.00	5533	89.18
10.0	5431	86.49	0	0.00	5688	91.68
11.0	5759	91.72	0	0.00	5914	95.33
12.0	5954	94.82	0	0.00	6031	97.21
13.0	6075	96.75	0	0.00	6098	98.29
14.0	6152	97.98	0	0.00	6146	99.07
15.0	6183	98.47	0	0.00	6167	99.40
16.0	6217	99.01	0	0.00	6176	99.55
17.0	6238	99.35	0	0.00	6185	99.69
18.0	6251	99.55	0	0.00	6188	99.74
19.0	6259	99.68	0	0.00	6193	99.82
20.0	6263	99.75	0	0.00	6198	99.90
21.0	6270	99.86	0	0.00	6198	99.90
22.0	6279	100.00	0	0.00	6204	100.00

SITE ID: PR
 SITE LOCATION: CULEBRA, PR.
 DATA : OCTOBER 1978 THROUGH SEPTEMBER 1979

1.7 WIND SPEED PERSISTENCE FREQUENCY (LEVEL A)

HOURS	NUMBER OF OCCURENCES			
	PERS. < 4	WIND SPEED, M/S		
		4-12	12-20	>20
<.1	0	0	0	0
.1-.2	0	0	0	0
.2-.4	0	0	0	0
.4-.8	0	0	0	0
.8-1	0	0	0	0
1.5	51	34	27	0
2.0	19	16	9	0
2.5	0	0	0	0
3.0	15	8	5	1
3.5	0	0	1	0
4.0	9	12	1	0
4.5	0	0	0	0
5.0	4	4	0	0
6.0	3	4	1	1
7.0	1	3	1	0
8.0	0	5	2	0
9.0	1	5	4	0
10.0	1	4	2	0
12.0	2	2	2	0
14.0	0	3	1	0
16.0	0	8	0	0
18.0	0	3	0	0
20.0	0	3	0	0
>20	1	49	1	0

SITE ID: PR
 SITE LOCATION: CULEBRA, PR.
 DATA : OCTOBER 1978 THROUGH SEPTEMBER 1979

 1.8 POWER LAW EXPONENT

WIND DIR (ELEV A)	ALPHA (A,B)	ALPHA (B,C)	ALPHA (A,C)	ALPHA (A,B,C)	%A	%B	%C
N	0.00	0.00	0.20	0.00	0.92	0.00	0.71
NNE	0.00	0.00	0.21	0.00	1.94	0.00	1.08
NE	0.00	0.00	0.17	0.00	10.78	0.00	6.00
ENE	0.00	0.00	0.03	0.00	40.02	0.00	38.65
E	0.00	0.00	0.07	0.00	29.03	0.00	41.89
ESE	0.00	0.00	0.18	0.00	9.32	0.00	5.46
SE	0.00	0.00	0.27	0.00	3.97	0.00	1.98
SSE	0.00	0.00	0.34	0.00	1.74	0.00	1.32
S	0.00	0.00	0.29	0.00	0.78	0.00	0.92
SSW	0.00	0.00	0.38	0.00	0.32	0.00	0.58
SW	0.00	0.00	0.04	0.00	0.11	0.00	0.32
WSW	0.00	0.00	0.17	0.00	0.06	0.00	0.16
W	0.00	0.00	0.08	0.00	0.08	0.00	0.08
WNW	0.00	0.00	0.37	0.00	0.05	0.00	0.05
NW	0.00	0.00	0.17	0.00	0.27	0.00	0.24
NNW	0.00	0.00	0.21	0.00	0.61	0.00	0.55

NOTES:

$$\begin{aligned}
 & \text{ALPHA} \\
 & 1. \frac{WS(UP)}{WS(LO)} = \frac{Z(UP)}{Z(LO)} \\
 & \text{ALPHA} = \frac{\log(WS(UP)/WS(LO))}{\log(ZUP/ZLO)}
 \end{aligned}$$

WHERE; Z=ELEVATION
 WS=WIND SPEED