F
O
S
S
I
L

E
N
E
R
G
Y**MEASUREMENT AND MODELING OF ADVANCED
COAL CONVERSION PROCESSES**

22nd Quarterly Report #523043
January 2, 1992 to March 31, 1992

By

Peter R. Solomon
Michael A. Serio
David G. Hamblen

L. Douglas Smoot
B. Scott Brewster

Work Performed Under Contract No. DE-AC21-86MC23075

For

U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
Morgantown, West Virginia
Dr. Richard Johnson
COTR

By

Contractor

Advanced Fuel Research, Inc.
87 Church Street
East Hartford, CT 06108
(203) 528-9806

Subcontractor

Brigham Young University
Provo, Utah 84602
(801) 378-4326

Program Director

Peter R. Solomon
President

Program Director

L. Douglas Smoot
Dean and Professor

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

DE93 004061

The overall objective of this program is the development of predictive capability for the design, scale up, simulation, control and feedstock evaluation in advanced coal conversion devices. This technology is important to reduce the technical and economic risks inherent in utilizing coal, a feedstock whose variable and often unexpected behavior presents a significant challenge. This program will merge significant advances made at Advanced Fuel Research, Inc. (AFR) in measuring and quantitatively describing the mechanisms in coal conversion behavior, with technology being developed at Brigham Young University (BYU) in comprehensive computer codes for mechanistic modeling of entrained-bed gasification. Additional capabilities in predicting pollutant formation will be implemented and the technology will be expanded to fixed-bed reactors.

The foundation to describe coal-specific conversion behavior is AFR's Functional Group (FG) and Devolatilization, Vaporization and Crosslinking (DVC) models, developed under previous and on-going METC sponsored programs. These models have demonstrated the capability to describe the time dependent evolution of individual gas species, and the amount and characteristics of tar and char. The combined FG-DVC model will be integrated with BYU's comprehensive two-dimensional reactor model, PCGC-2, which is currently the most widely used reactor simulation for combustion or gasification. The program includes: i) validation of the submodels by comparison with laboratory data obtained in this program, ii) extensive validation of the modified comprehensive code by comparison of predicted results with data from bench-scale and process scale investigations of gasification, mild gasification and combustion of coal or coal-derived products in heat engines, and iii) development of well documented user friendly software applicable to a "workstation" environment.

Success in this program will be a major step in improving the predictive capabilities for coal conversion processes including: demonstrated accuracy and reliability and a generalized "first principles" treatment of coals based on readily obtained composition data.

The progress during the twenty-second quarter of the program is summarized below.

For Subtask 2.a., One of the two papers on char reactivity submitted to the 24th symposium (International) on Combustion was accepted for presentation. The main objective of the work during the past quarter was to relate the char reactivity at high temperature (i.e., in the pore diffusion regime) to physical parameters of the char. The fact that the reactivity of high heating rate and low heating rate fluid chars is very different suggests that the structure of these chars depends strongly on the pyrolysis conditions.

To determine the contribution of pyritic sulfur to H_2S evolution, Illinois #6 and Pittsburgh #8 coals from the Argonne Premium sample bank were demineralized using ASTM D-2492. In the case of pyrolysis, the low temperature SO_2 peak was significantly reduced while the high temperature SO_2 peak was eliminated. In the case of combustion, the "sharp" portion of the SO_2 peak was eliminated.

Many numerical improvements were done in the last quarter on the swelling model, and the model has been strengthened so that it can predict particle swelling over a range of conditions, including high pressure.

For Subtask 2.b., The high-pressure, controlled-profile (HPCP) reactor, including the char, tar and gas separation and collection system has been successfully operated in coal devolatilization, char preparation and char oxidation experiments. More than 50 char oxidation tests at atmospheric and 5 atm pressure, with successful *in-situ* measurement of char particle size, velocity and temperature, were completed during the reporting period.

For Subtask 2.c., Discussions continued with BYU on implementation of the soot oxidation and particle ignition submodels.

For Subtask 2.d., No work was scheduled.

For Subtask 2.e., The recent work has focused on completion of literature reviews in two areas: 1) data on tar yields from laboratory scale pyrolysis studies with Pittsburgh Seam bituminous coals (and comparable coals); 2) data for the yields of tar from actual gasifier systems. Some experiments were done at AFR to assess the relative importance of tar gasification and tar cracking reactions. It was found that, while the thermal cracking effects were significant, the addition of CO₂ did not have much effect on the yield or composition of tar. Consequently, it was concluded that the tar destruction in the top part of a fixed-bed gasifier can probably be attributed primarily to thermal cracking rather than gasification reactions.

For Subtask 2.f., The oxidation measurements of large char particles at atmospheric pressures for six different coals have been organized into a manuscript and submitted for publication. A thick-ash-layer theory was developed and was supported by the experimental observation that the cube root of the char particle mass declined linearly with time in all tests of the 35 particles.

A recent observation has been made as to whether multiple large particles in a crucible oxidize as one large particle or as individual particles each alone in a separate crucible. The data suggested that four large particles together in the crucible oxidize as one large particle of about the same total mass.

For Subtask 2.g., An option for capturing H₂S was added to the sulfur/sorbent reactions submodel, and testing was initiated.

For Subtask 3.a., The new version of FG-DVC with swelling was incorporated into PCGC-2 and is being tested. A char reactivity submodel was also received and incorporated. The problem in simulating the Imperial College reactor was at least partially resolved by using a finer grid in the near-burner region. Development of code graphics continued. A portable, user-friendly graphical interface was created and demonstrated at the ACERC annual review meeting.

For Subtask 3.b., During the last quarter, work continued on developing and evaluating the fixed-bed model, FBED-1. The FBED-1 code was applied to the design of a fixed-bed gasifier for the DOE/METC Gasification Product Improvement Facility (GPIF). The code was demonstrated both as a design tool and as an analysis tool. Work was also continued to consolidate the input data for the final simulations of a high-pressure, Lurgi gasifier and an atmospheric-pressure, Wellman-Galusha gasifier.

For Subtask 3.c., Work was initiated to simulate sidewall injection of sorbent with sulfur capture in the BYU gasifier.

For Subtask 4.a., Work continued on collecting information for simulating the two application cases: the Coal Tech cyclone combustor and the Texaco gasifier (with dry coal feed). A third application case was selected: a Solar Turbine combustor.

For Subtask 4.b., During the past quarter, work continued on collecting fixed-bed design and test data from organizations and individuals involved in fixed- or moving-bed gasification or combustion research or in research on non-reacting fixed- or moving beds. No new data sets were obtained. Work also continued on collecting fixed-bed experimental data from the open literature.

"MEASUREMENT AND MODELING OF COAL CONVERSION PROCESSES"

Contract No. DE-AC21-86MC23075

Table of Contents

DISCLAIMER	i
ABSTRACT	ii
I. INTRODUCTION	1
I.A. Program Background and Description	1
I.B. Objectives	1
I.C. Approach	1
I.D. Critical Technical Issues	2
I.E. Twenty-Second Quarter Progress	3
II. TASK 2 - SUBMODEL DEVELOPMENT AND EVALUATION	7
II.A. Subtask 2.a. - Coal to Char Chemistry Submodel	8
II.B. Subtask 2.b. - Fundamental High-Pressure Reaction Rate Data	24
II.C. Subtask 2.c. - Secondary Reaction of Pyrolysis Product and Burnout Submodels	33
II.D. Subtask 2.d. - Ash Physics and Chemistry Submodel	34
II.E. Subtask 2.e. - Large Particle Submodels	35
II.F. Subtask 2.f. - Large Char Particle Oxidation at High Pressures	52
II.G. Subtask 2.g. - SO _x -NO _x Submodel Development	57
III. TASK 3 - COMPREHENSIVE MODEL DEVELOPMENT AND EVALUATION	59
III.A. Subtask 3.a. - Integration of Advanced Submodels into Entrained-Flow Code, with Evaluation and Documentation	60
III.B. Subtask 3.b. - Comprehensive Fixed-Bed Modeling Review, Development Evaluation and Implementation	66
III.C. Subtask 3.c. - Generalized Fuels Feedstock Submodel	81
IV. TASK 4 - APPLICATION OF INTEGRATED CODES	83
IV.A. Subtask 4.a. - Application of Generalized Pulverized Coal Comprehensive Code	84
IV.B. Subtask 4.b. - Application of Fixed-Bed Code	85
V. REFERENCES	86
APPENDIX A - "Calculation of Carrier Gas Flow Rate for Sidewall Sorbent Injection"	
APPENDIX B - "The Prediction of Coal Char Reactivity Under Combustion Conditions"	

SECTION I. INTRODUCTION

I.A. PROGRAM BACKGROUND AND DESCRIPTION

During the past several years, significant advances have been made at Brigham Young University (BYU) in comprehensive two-dimensional computer codes for mechanistic modeling of entrained-bed gasification and pulverized coal combustion. During the same time period, significant advances have been made at Advanced Fuel Research, Inc. (AFR) in the mechanisms and kinetics of coal pyrolysis and secondary reactions of pyrolysis products. This program presents a unique opportunity to merge the technology developed by each organization to provide detailed predictive capability for advanced coal characterization techniques in conjunction with comprehensive computer models to provide accurate process simulations.

The program will streamline submodels existing or under development for coal pyrolysis chemistry, volatile secondary reactions, tar formation, soot formation, char reactivity, and SO_x - NO_x pollutant formation. Submodels for coal viscosity, agglomeration, tar/char secondary reactions, sulfur capture, and ash physics and chemistry will be developed or adapted. The submodels will first be incorporated into the BYU entrained-bed gasification code and subsequently, into a fixed-bed gasification code (to be selected and adapted). These codes will be validated by comparison with small scale laboratory and PDU-scale experiments. The validated code could then be employed to simulate and to develop advanced coal conversion reactors of interest to METC.

I.B. OBJECTIVES

The objectives of this study are to establish the mechanisms and rates of basic steps in coal conversion processes, to integrate and incorporate this information into comprehensive computer models for coal conversion processes, to evaluate these models and to apply them to gasification, mild gasification and combustion in heat engines.

I.C. APPROACH

This program is a closely integrated, cooperative effort between AFR and BYU. The program consists of four tasks: 1) Preparation of Research Plans, 2) Submodel

Development and Evaluation, 3) Comprehensive Model Development and Evaluation, and 4) Applications and Implementation.

I.D. CRITICAL TECHNICAL ISSUES

To achieve the goals of the program, the computer models must provide accurate and reliable descriptions of coal conversion processes. This will require the reduction of very complicated and interrelated physical and chemical phenomena to mathematical descriptions and, subsequently, to operational computer codes. To accomplish this objective, a number of technical issues must be addressed as noted below. The status of each of these tasks is also included:

- A Separation of Rates for Chemical Reaction, Heat Transfer, and Mass Transfer
- A Particle Temperature Measurements Using FT-IR E/T Spectroscopy
- A Functional Group Description of Coal, Char and Tar
- A Tar Formation Mechanisms
- A Char Formation Mechanisms
- A Viscosity/Swelling
- A Intraparticle Transport
- A Pyrolysis of Volatiles and Soot Formation
- A Secondary Reaction of Tar
- I Particle Ignition
- A Char Reactivity
- I Ash Chemistry and Physics
- A Particle Optical Properties
- A Coupling of Submodels with Comprehensive Codes
- I Comprehensive Code Efficiency
- I Turbulence
- A SO_x and NO_x
- I Generalized Fuels Models
- A Fixed-Bed Model

(o) to be addressed; (I) initiated; (A) almost completed; (C) completed. These technical issues are addressed in the three Tasks as described in Sections II-IV.

I.E. TWENTY-SECOND QUARTER PROGRESS

Subtask 2.a. Coal to Char Chemistry Submodel Development and Evaluation

One of the two papers on char reactivity submitted to the 24th symposium (International) on Combustion was accepted for presentation. The main objective of the work during the past quarter was to relate the char reactivity at high temperature (i.e., in the pore diffusion regime) to physical parameters of the char. In order to observe the influence of the char structure on the onset of pore diffusion limitations for a wider range of chars, low temperature reactivity measurements were performed on a Pittsburgh No.8 char produced in an entrained flow reactor at approximately 5000 K/sec up to 1100 K and a demineralized lignite char produced at 30°C/min up to 900°C. In contrast with the Pittsburgh chars produced at 30°C/min, these two chars did not show any change in activation energy before getting into the external diffusion limited regime of the TGA apparatus. The fact that the reactivity of high heating rate and low heating rate fluid chars is very different suggests that the structure of these chars depends strongly on the pyrolysis conditions.

To determine the contribution of pyritic sulfur to H₂S evolution, Illinois #6 and Pittsburgh #8 coals from the Argonne Premium sample bank were demineralized using ASTM D-2492. The ASTM procedure had similar effects on both coals. In the case of pyrolysis, the low temperature SO₂ peak was significantly reduced while the high temperature SO₂ peak was eliminated. In the case of combustion, the "sharp" portion of the SO₂ peak was eliminated. The SO₂ evolution curves for pure pyrite indicate that it decomposes at a higher temperature than pyrite in the presence of coal.

Many numerical improvements were done in the last quarter on the swelling model, and the model has been strengthened so that it can predict particle swelling over a range of conditions, including high pressure. Although the pressure effect on swelling can be well predicted for coals with medium range fluidity, the prediction for highly fluid coals, such as Pittsburgh seam coal, is untenable. For these coals, the fluidity submodel has predicted the highest fluidity at the prevailing conditions and higher pressure only causes small changes in the fluidity.

Subtask 2.b. Fundamental High-Pressure Reaction Rate Data

The high-pressure, controlled-profile (HPCP) reactor, including the char, tar and gas separation and collection system has been successfully operated in coal devolatilization, char preparation and char oxidation experiments. More than 50 char oxidation tests at atmospheric and 5 atm pressure, with successful *in-situ* measurement of char particle size, velocity and temperature, were completed during the reporting period. Titanium analyses to determine char burnout were completed for most of the samples. Char preparation for all of the coals for this study also continued.

Subtask 2.c. Secondary Reaction of Pyrolysis Products and Char Burnout

Discussions continued with BYU on implementation of the soot oxidation and particle ignition submodels.

Subtask 2.d. Ash Physics and Chemistry Submodel

No work scheduled.

Subtask 2.e. Large Particle Submodels

The recent work has focused on completion of literature reviews in two areas: 1) data on tar yields from laboratory scale pyrolysis studies with Pittsburgh Seam bituminous coals (and comparable coals); 2) data for the yields of tar from actual gasifier systems. The overall conclusions are as follows: 1) The effects of particle size on devolatilization time are very important- the effects on tar yield are not; 2) The residence time of tar in the gasifier is inversely correlated with tar yield because of cracking and gasification reactions; 3) The reduced yields for pressurized gasifiers are due to increased residence time, increased gasification rate and/or a related temperature effect; 4) Both increased particle size and pressure would tend to move the tar evolution zone toward the hotter part of the gasifier.

Some experiments were done at AFR to assess the relative importance of tar gasification and tar cracking reactions. It was found that, while the thermal cracking effects were significant, the addition of CO₂ did not have much effect on the yield or composition of tar. Consequently, it was concluded that the tar destruction in the top

part of a fixed-bed gasifier can probably be attributed primarily to thermal cracking rather than gasification reactions.

Subtask 2.f. Large Char Particle Oxidation at High Pressure

The oxidation measurements of large char particles at atmospheric pressures of six different coals have been organized into a manuscript and submitted for publication. A thick-ash-layer theory was developed and was supported by the experimental observation that the cube root of the char particle mass declined linearly with time in all tests of the 35 particles. Test variables were coal type, oxidation temperature, and initial char particle mass. The cube root of particle mass declined linearly with time in all tests. Ash layers formed and usually remained in place around the coal particle. Average mass reactivities were correlated with initial char particle mass, temperature, and ash fraction.

A recent observation has been made as to whether multiple large particles in a crucible oxidize as one large particle or as individual particles each alone in a separate crucible. The data suggested that four large particles together in the crucible oxidize as one large particle of about the same total mass.

Subtask 2.g. SO_x - NO_x Submodel Development

An option for capturing H_2S was added to the sulfur/sorbent reactions submodel, and testing was initiated.

Subtask 3.a. Integration of Advanced Submodels into Entrained-Flow Code, with Evaluation and Documentation

The new version of FG-DVC with swelling was incorporated into PCGC-2 and is being tested. A char reactivity submodel was also received and incorporated. The problem in simulating the Imperial College reactor was at least partially resolved by using a finer grid in the near-burner region. Development of code graphics continued. A portable, user-friendly graphical interface was created and demonstrated at the ACERC annual review meeting.

Subtask 3.b. Comprehensive Fixed-Bed Modeling Review, Development, Evaluation, and Implementation

During the last quarter, work continued on developing and evaluating the fixed-bed model, FBED-1. The FBED-1 code was applied to the design of a fixed-bed gasifier for the DOE/METC Gasification Product Improvement Facility (GPIF). The code was demonstrated both as a design tool and as an analysis tool. Work was also continued to consolidate the input data for the final simulations of a high-pressure, Lurgi gasifier and an atmospheric-pressure, Wellman-Galusha gasifier. A poster was presented at the Sixth Annual NSF Site Visit. A poster and product demonstration of the fixed-bed code were also presented at the ACERC Sixth Annual Technical Review Meeting. An overview of the fixed-bed code development was presented at the METC/AFR/BYU Contract Review Meeting. Two papers were accepted for publication in professional journals.

Subtask 3.c. Generalized Fuels Feedstock Submodel

Work was initiated to simulate sidewall injection of sorbent with sulfur capture in the BYU gasifier.

Subtask 4.a. Application of Generalized Pulverized Coal Comprehensive Code

Work continued on collecting information for simulating the two application cases: the Coal Tech cyclone combustor and the Texaco gasifier (with dry coal feed). A third application case was selected: a Solar Turbine combustor.

Subtask 4.b. Application of Fixed-Bed Code

During the past quarter, work continued on collecting fixed-bed design and test data from organizations and individuals involved in fixed- or moving-bed gasification or combustion research or in research on non-reacting fixed- or moving beds. No new data sets were obtained. Work also continued on collecting fixed-bed experimental data from the open literature.

SECTION II. TASK 2. SUBMODEL DEVELOPMENT AND EVALUATION

Objectives

The objectives of this task are to develop or adapt advanced physics and chemistry submodels for the reactions of coal in an entrained-bed and a fixed-bed reactor and to validate the submodels by comparison with laboratory scale experiments.

Task Outline

The development of advanced submodels for the entrained-bed and fixed-bed reactor models will be organized into the following categories: a) Coal Chemistry (including coal pyrolysis chemistry, char formation, particle mass transfer, particle thermal properties, and particle physical behavior); b) Char Reaction Chemistry at high pressure; c) Secondary Reactions of Pyrolysis Products (including gas-phase cracking, soot formation, ignition, char burnout, sulfur capture, and tar/gas reactions); d) Ash Physics and Chemistry (including mineral characterization, evolution of volatile, molten and dry particle components, and ash fusion behavior); e) Large Coal Particle Effects (including secondary reactions within the particle and in multiple particle layers; f) Large Char Particle Effects (including oxidation); g) SO_x - NO_x Submodel Development (including the evolution and oxidation of sulfur and nitrogen species); and h) SO_x and NO_x Model Evaluation.

II.A. SUBTASK 2.a. - COAL TO CHAR CHEMISTRY SUBMODEL DEVELOPMENT AND EVALUATION

Senior Investigators - David G. Hamblen and Michael A. Serio
Advanced Fuel Research, Inc.
87 Church Street, East Hartford, CT 06108
(203) 528-9806

Objective

The objective of this subtask is to develop and evaluate, by comparison with laboratory experiments, an integrated and compatible submodel to describe the organic chemistry and physical changes occurring during the transformation from coal to char in coal conversion processes.

Accomplishments

One of the two papers on char reactivity submitted to the 24th symposium (Informational) on Combustion was accepted for presentation. The main objective of the work during the past quarter was to relate the char reactivity at high temperature (i.e., in the pore diffusion regime) to physical parameters of the char. We observed that, using the Thiele model to calculate the reaction rate in the pore diffusion regime, values of 6 Å for the mean pore radius were appropriate for low heating rate, fluid chars. On the other hand, pore size distribution measurements on chars obtained at high heating rates were performed by White (1990) and show a mean pore size of 100 Å for a Zap char, and a bimodal distribution at 6 Å and 170 Å for a Pittsburgh No.8 char. Using values of 100 Å for the Occidental and 170 Å for the FMC and Toscoal led to fairly good predictions of the data, with the reactivity predicted within a factor of 1.5 for the Occidental and the Toscoal and within a factor of 4 for the FMC.

In order to observe the influence of the char structure on the onset of pore diffusion limitations for a wider range of chars, low temperature reactivity measurements were performed on a Pittsburgh No.8 char produced in an entrained flow reactor at approximately 5000 K/sec up to 1100 K and a demineralized lignite char produced at 30°C/min up to 900°C. In contrast with the Pittsburgh chars produced at 30°C/min, these two chars did not show any change in activation energy before getting into the external diffusion limited regime of the TGA apparatus. The fact that the

reactivity of high heating rate and low heating rate fluid chars is very different suggests that the structure of these chars depends strongly on the pyrolysis conditions.

To determine the contribution of pyritic sulfur to H_2S evolution, Illinois #6 and Pittsburgh #8 coals from the Argonne Premium sample bank were demineralized using ASTM D-2492. Both the raw coals and the ASTM modified coals were analyzed with the TG-FTIR technique using the post-oxidation accessory. The sulfur analysis technique involves oxidizing the volatile gases evolved during pyrolysis (post-oxidation) and then combusting the remaining char. H_2S is therefore monitored through SO_2 evolution.

The ASTM procedure had similar effects on both coals. In the case of pyrolysis, the low temperature SO_2 peak was significantly reduced while the high temperature SO_2 peak was eliminated. In the case of combustion, the "sharp" portion of the SO_2 peak was eliminated. The SO_2 evolution curves for pure pyrite indicate that it decomposes at a higher temperature than pyrite in the presence of coal. What then is the chemistry between coal and pyrite during pyrolysis which allows earlier decomposition of pyrite? In the next quarter, work will focus around this question.

Many numerical improvements were done in the last quarter on the swelling model, and the model has been strengthened so that it can predict particle swelling over a range of conditions, including high pressure. The original governing equation set of this model was found to be ill-conditioned and unstable numerically. One problem was solved by reducing the overall FG-DVC time step size so that the temperature step size is equal to or less than $1^\circ C$ when the coal becomes fluid. A second problem was solved by using a better numerical integration scheme with an adjustable step size and error control, and by variable substitution in the governing equation set so that $d(r_2-r_1)/dt$ is being integrated instead of dr_2/dt . Although the pressure effect on swelling can be well predicted for coals with medium range fluidity, the prediction for highly fluid coals, such as Pittsburgh seam coal, is untenable. For these coals, the fluidity submodel has predicted the highest fluidity at the prevailing conditions and higher pressure only causes small changes in the fluidity.

Char Reactivity

One of the two papers on char reactivity submitted to the 24th symposium

(International) on Combustion was accepted for presentation. The revised version of the paper is included in Appendix B.

The main objective of the work during the past quarter was to relate the char reactivity at high temperature (i.e., in the pore diffusion regime) to physical parameters of the char. A specific objective was to estimate the value of the mean pore radius. We observed that, using the Thiele model to calculate the reaction rate in the pore diffusion regime, values of 6 Å for the mean pore radius were appropriate for low heating rate, fluid chars. This value of 6 Å corresponds to the size of the micropores, implying that the char is fairly microporous. On the other hand, pore size distribution measurements on chars obtained at high heating rates were performed by White (1990) and show a mean pore size of 100 Å for a Zap char, and a bimodal distribution at 6 Å and 170 Å for a Pittsburgh No.8 char. The Occidental char (from Smoot, 1984) described in our Combustion Institute Paper (Appendix B) is probably very similar to the Zap (both are high heating rate chars produced from a low rank coal), while the FMC and the Toscoal probably have similar structures to the Pittsburgh No.8 char (high heating rate chars produced from a bituminous coal). Using values of 100 Å for the Occidental and 170 Å for the FMC and Toscoal led to fairly good predictions of the data, with the reactivity predicted within a factor of 1.5 for the Occidental and the Toscoal and within a factor of 4 for the FMC. This is an encouraging result and shows that it may be possible to extend low temperature reactivity models to high temperatures.

In order to observe the influence of the char structure on the onset of pore diffusion limitations for a wider range of chars, low temperature reactivity measurements were performed on a Pittsburgh No.8 char produced in an entrained flow reactor at approximately 5000 K/sec up to 1100 K and a demineralized lignite char produced at 30°C/min up to 900°C. In contrast with the Pittsburgh chars produced at 30°C/min, these two chars did not show any change in activation energy before getting into the external diffusion limited regime of the TGA apparatus (i.e., for these chars, the onset of pore diffusion limitations occurs at a higher rate than approximately 1 g/g-min). With regard to the demineralized char, this is not surprising since the char is probably fairly macroporous. For the Pittsburgh No.8 char, the result is in agreement with the data of the FMC and Toscoal chars. The fact that the reactivity of high heating rate and low heating rate fluid chars is very different suggests that the structure of these chars depends strongly on the pyrolysis conditions. This may be due to the fact that chars (which become fluid) produced at low heating rates may have more time to reorganize their structure during the longer period in which the char is fluid.

In order to clarify this point, surface area, porosity, density and pore size distribution measurements will be performed on selected chars. Correlations between char structure and char behavior in the pore diffusion regime will also be developed.

Sulfur and Nitrogen Evolution

To determine the contribution of pyritic sulfur to H_2S evolution, Illinois #6 and Pittsburgh #8 coals from the Argonne Premium sample bank were subjected to ASTM D-2492. In this procedure, the sulfates are extracted from the coal using dilute hydrochloric acid and the pyrites are extracted with dilute nitric acid. Both the raw coals and the ASTM modified coals were analyzed with the TG-FTIR technique using the post-oxidation accessory. The sample is first heated at $30^\circ C/min$ to $900^\circ C$ in a pyrolysis cycle, then the sample is cooled and reheated in the presence of air in a combustion cycle. The sulfur analysis technique involves oxidizing the volatile gases evolved during pyrolysis (post-oxidation) and then combusting the remaining char. H_2S is therefore monitored through SO_2 evolution. The balance and thermocouple curves and the SO_2 evolution and weight curves are presented in Figs. II.A-1 through II.A-4. Table II.A-1 lists the pyritic and organic sulfur amounts obtained from TG-FTIR analysis compared with the results reported by Argonne National Laboratory. In general, good agreement was obtained.

The ASTM procedure had similar effects on both coals. In the case of pyrolysis, the low temperature SO_2 peak was significantly reduced while the high temperature SO_2 peak was eliminated. In the case of combustion, the "sharp" portion of the SO_2 peak was eliminated. During pyrolysis, pyritic sulfur is contributing to both the low and high temperature SO_2 peaks, probably through the decomposition of pyrite to form pyrrhotite (FeS). Thus, the low temperature SO_2 peak is a product of tar sulfur, organic H_2S , and pyritic sulfur while the high temperature SO_2 peak is from pyritic sulfur only. In the combustion regime, the "sharp" portion of the SO_2 peak is thought to be from FeS decomposition while the broader portion of the peak is probably from char sulfur.

Does pure pyrite decompose in a similar manner? To answer this question, a pure pyrite sample ground for 20 minutes as well as a 50:50 mixture of Illinois #6 and pyrite ground also for 20 minutes were analyzed for H_2S using the technique described above. The balance and thermocouple curves and the evolution and weight curves for

Table II.A-1. Results for Pyritic and Organic Sulfur Weight Percents from Raw and ASTM Modified Illinois No. 6 and Pittsburgh No. 8 Coals.

	TG-FTIR		Argonne Values	
	AF Wt. %		AF Wt. %	
	<u>Pyritic S</u>	<u>Organic S</u>	<u>Pyritic S</u>	<u>Organic S</u>
Illinois No. 6	3.26	1.90	3.02	2.16
Pittsburgh No. 8	1.76	0.88	1.48	0.88

Table II.A-2. H₂S Activation Energies and Rate Constants for Raw and ASTM D-2492 Modified Coals.

	Low Temperature SO ₂ Peak		High Temperature SO ₂ Peak	
	<u>E (Kcal)</u>	<u>Ko(sec⁻¹)</u>	<u>E (Kcal)</u>	<u>Ko(sec⁻¹)</u>
Raw Pitt. No. 8	46.4	5.34 x 10 ¹¹	34.9	6.48 x 10 ⁶
ASTM Modified Pitt. No. 8	35.9	2.24 x 10 ⁸	---	---
Raw Ill. No 6	57.6	7.3 x 10 ¹⁵	57.5	1.51 x 10 ¹³
ASTM Modified Ill. No. 6	33.2	1.08 x 10 ⁸	---	---

Figure II.A-1. Post Oxidation Results for Illinois #6. a) Balance and Thermocouple Curves and b) SO₂ Evolution and Weight Curves.

Figure II.A-2. Post Oxidation Results for ASTM D-2492 Modified Illinois #6.
a) Balance and Thermocouple Curves and b) SO₂ Evolution and Weight Curves.

Figure II.A-3. Post Oxidation Results for Pittsburgh #8. a) Balance and Thermocouple Curves and b) SO₂ Evolution and Weight Curves.

Figure II.A-4. Post Oxidation Results for ASTM D-2492 Modified Pittsburgh #8.
a) Balance and Thermocouple Curves and b) SO₂ Evolution and Weight Curves.

pure pyrite and the Illinois #6/pyrite mix are presented in Figs. II.A-5 and II.A-6, respectively. The SO_2 evolution curves indicate that pure pyrite decomposes at a higher temperature than pyrite in the presence of coal: the temperature of maximum SO_2 evolution (T_{max}) for pure pyrite is 625°C , and the SO_2 T_{max} for the Illinois #6/pyrite mix is 594°C . Furthermore, both the low and the high temperature SO_2 T_{max} 's for the Illinois #6/pyrite mix are in agreement with the T_{max} 's for the raw Illinois #6 (Fig. II.A-1b).

What then is the chemistry between coal and pyrite during pyrolysis which allows earlier decomposition of pyrite? In the next quarter, work will focus around this question. Experiments will include repeating the Illinois #6/pyrite mix, running a Pittsburgh #8/pyrite mix for reproducibility, and heating pure pyrite in the presence of H_2O , CO_2 and H_2 to assess the reactivity of these gases.

Activation energies and rate constants were determined for Pittsburgh #8, Illinois #6, ASTM modified Pittsburgh #8 and ASTM modified Illinois #6 and are presented in Table II.A-2. These kinetic values were calculated from data obtained from post-oxidation experiments done at $10^\circ\text{C}/\text{min}$, $30^\circ\text{C}/\text{min}$, and $100^\circ\text{C}/\text{min}$. This information will be used to develop kinetic parameters for the evolution of sulfur species in the FG-DVC model.

Swelling Model

Many numerical improvements have been done in the last quarter and the model has been strengthened so that it can predict particle swelling under various conditions.

Improvements in the Numerical Integration

The original governing equation set of this model was found to be ill-conditioned and unstable numerically under various circumstances due the reasons listed below:

- 1) For softening coals, the coal viscosity η varies very rapidly in the fluidity window. Results change with the choice of the time step size.
- 2) Once swelling starts, the bubble shell can become so thin that the difference between the particle radius and bubble radius $r_2 - r_1$ is very often 10^{-3} times

Figure II.A-5. Post Oxidation Results for Pyrite. a) Balance and Thermocouple Curves and b) SO₂ Evolution and Weight Curves.

Figure II.A-6. Post Oxidation Results for Illinois No. 6/Pyrite Mixture.
a) Balance and Thermocouple Curves and b) SO₂ Evolution and Weight Curves.

smaller than r_2 . A very small time step size has to be used in integrating the differential equation of dr_2/dt to ensure that $r_2 - r_1$ is evaluated with enough accuracy.

The first problem was solved by reducing the overall FG-DVC time step size so that the temperature step size is equal to or less than 1°C when the coal becomes fluid. The second problem was solved by using a better numerical integration scheme with an adjustable step size and error control, and by variable substitution in the governing equation set so that $d(r_2 - r_1)/dt$ is being integrated instead of dr_2/dt .

Effect of Ambient Pressure on Swelling

Literature results show that, for most coals, there exists an optimal pressure at which the coal particle swelling amount reaches a maximum and that the swelling amount will start decreasing with a further pressure increase. The initial increase in the swelling amount is due to the fact that coals become more fluid at higher pressure. On the other hand, the high pressure makes the bubble expansion physically difficult. The net effect depends on the result of competition between these two opposite influences. In some coals, the increase of fluidity is not enough to overcome the expansion difficulty by high pressure, so the swelling amount decreases monotonically with increasing pressure. To predict the pressure effect, the ambient gas diffusion equation was integrated along with the evolved gases, and the ambient gas pressure difference is now calculated and contributes to the swelling.

In Figure II.A-7, the temperature variations of the pressure difference and the stress in the bubble shell are plotted: a) original model with Euler integration, b) with ambient gas diffusion and Runge-Kutta-Fehlberg integration algorithm, and c) additional improvement by integrating $d(r_2 - r_1)/dt$. In this example, Pittsburgh seam coal at a heating rate 5000°C is used. The noise in Figure II.A-7b is from the inaccuracy in the $r_2 - r_1$ evaluation.

The predicted ambient pressure effects on the particle swelling of a Illinois #6 coal in a entranced-flow reactor with a furnace temperature of 700°C are plotted in Figure II.A-8, at a) 1 atm and b) 10 atm. The maximum particle swelling ratio is about 2.9 at 10 atm and 2.3 at 1 atm, due to the substantial increase of fluidity.

Figure II.A-7. Particle Swelling of an Illinois #6 Coal Particle in an Entrained Flow Reactor at a Furnace Temperature of 700°C. a) 1 atm and b) 10 atm.

The ambient gas diffusivity is expected to be lower than that of the evolved gases, and is assumed to be $7.5 \times 10^{-4} \text{ cm}^2/\text{s}$, so that the predicted pressure effect matches the experimental data by Lee et al. (1991).

Although the pressure effect on swelling can be well predicted for coals with medium range fluidity, the prediction for highly fluid coals, such as Pittsburgh seam coal, is untenable. For these coals, the fluidity submodel has predicted the highest fluidity at the prevailing conditions and higher pressure only causes small changes in the fluidity.

Particle Burst at High Heating Rate

At high heating rates, the rapid pressure increase by accumulation of evolved gas and insufficient time for gas to diffuse out is expected to cause the bubble to burst before it swells. As depicted in Figure II.A-7c, the pressure difference is high before swelling but the bubble shell stress is low, because the bubble is small and the shell is thick. The pressure difference drops to a very low level once the bubble starts expanding, because the quick expansion increases the bubble volume and reduces the internal pressure. There is an instantaneous increase in stress, since the shell is getting thinner, but it eventually decreases to a low value with the very small pressure difference. At very high heating rates, the stress increase will be high enough to burst the bubble, and no swelling will happen. This is expected to be true for most of the combustion cases, where the heating rate exceeds $10,000^\circ\text{C}/\text{s}$. The critical stress has been determined to be 1 atm.

Work to be done

Additional experimental data for high pressure conditions will be collected and the necessity for further model modifications will be determined.

Plans

Complete work on the models for swelling, char reactivity and the evolution of sulfur and nitrogen species.

Figure IIA-8. Pressure Difference and Bubble Shell Stress during Pyrolysis at 5000°C/s Calculated with a) Euler Scheme, b) Runge-Kutta-Fehlberg Scheme and c) Additional Improvement by Integrating $d(r_2 - r)/dt$.

II.B. SUBTASK 2.B. - FUNDAMENTAL HIGH-PRESSURE REACTION RATE DATA

Senior Investigators - Geoffrey J. Germane and Angus U. Blackham
Brigham Young University
Provo, Utah 84602
(801) 378-2355 and 6536

Student Research Assistants - Charles R. Monson, Ken Bateman and Layne Pincock

Objectives

The overall objectives of this subtask are to measure and correlate fundamental reaction rate coefficients for pulverized-coal char particles as a function of char burnout in oxygen at high temperature. The effect of high-pressure will be investigated.

The specific objectives for the quarterly reporting period included:

1. Review appropriate literature in pertinent areas.
2. Calibrate the HPCP optical pyrometer and particle imaging system for char preparation and oxidation studies.
3. Continue characterization of chars prepared in the HPCP from the coals selected for this study.
4. Continue oxidation tests in the HPCP reactor with chars produced from several of the coals selected for study.

Accomplishments

Three components of the subtask have been identified to accomplish the objectives outlined above: 1) design and construction of a laminar-flow high-pressure controlled-profile (HPCP) reactor, 2) char preparation at high temperature and high pressure, and 3) determination of the kinetics of char-oxygen reactions at high pressure.

The HPCP reactor, capable of functioning at 400 psi (27 atmospheres), has been constructed and successfully instrumented to perform the fundamental

reaction rate measurements required for the study. The test program was established and initiated after considerable effort to successfully complete and characterize the optical pyrometer and particle-imaging system. For the determination of kinetic parameters, data will also be included from a char oxidation study conducted with an atmospheric-pressure reactor constructed under independent funding at Brigham Young University.

HPCP Reactor and Optical Instrumentation Development

The reactor has been essentially complete and ready for char preparation and oxidation tests since the end of the previous annual reporting period. Some minor modifications to the preheater and the particle injection tube were completed during the quarter. The main effort expended in this area involved characterization and calibration of the particle imaging and pyrometry system.

Char Preparation at High Temperature and High Pressure

The main objective of this aspect of the study is the preparation of chars from five different coals with three different reactors at atmospheric and elevated pressure. The coals are Pitt. HVA, UT Blind Canyon HVB, IL #6 HVC, Wyodak SUBC, and Beulah-Zap LIGA. These are all relatively common U.S. coals that have been used in char oxidation studies. All of the coals are included in the Penn State, the Department of Energy and the Argonne National Laboratory coal banks. They are also standard ACERC coals. The kinetics of oxidation of selected samples of these coal chars will be determined at elevated pressure and the data compared with those obtained at atmospheric pressure.

The principal facility focus of this study is the use of the HPCP reactor in the determination of the kinetics of oxidation of the chars and the preparation of selected char samples from the coals indicated. An important objective is to determine just how different the oxidation kinetics will be for chars prepared under different conditions when the kinetic parameters are determined at high temperature and high pressure.

Cooperation with separately-funded researchers in this research area at BYU continued with the selection of the UT Blind Canyon HVB coal as a primary reference coal for which char will be produced in a flat-flame burner operated

by the other research group. Chemical and physical property comparisons will be available to the present study in the analysis of char reactivity in the HPCP at atmospheric and elevated pressures.

Kinetics of Char-Oxygen Reactions at High Pressure

Char oxidation experiments will be performed with five coals varying in rank from lignite to high volatile bituminous: Pitt. HVA, UT Blind Canyon HVB, IL #6 HVC, Wyodak SUBC, and Beulah-Zap LIGA. These are all relatively common U.S. coals that have been used in other char oxidation studies. All of the coals are included in the Penn State, the Department of Energy and the Argonne National Laboratory coal banks. They are also standard ACERC coals.

Samples of these coals have been ground and size classified with a combination of sieving and aerodynamic classification to produce tight size fractions of 64-74 μm and 38-44 μm . The size fractions are being verified by scanning electron microscope and Coulter Counter measurements.

Chars for each of the coals have been prepared in the HPCP furnace in a nitrogen environment. All of the chars were prepared at the same reactor conditions in order to eliminate devolatilization effects on the reactivity of the chars. Char preparation conditions were as follows: atmospheric pressure, wall and gas temperatures of 1500 K, an initial particle heating rate of 10^4 K/s (calculated using gas and wall temperature measurements), and particle residence times of 350-400 ms.

Char Oxidation Tests - Approximately fifty char oxidation tests were performed during the reporting period with the Utah Blind Canyon char at 1 and 5 atm total pressure. The conditions for each of the tests and some resulting measurements are listed in Table II.B-1. Both 40 and 70 μm particle sizes were tested, reactor temperatures were varied between 1170 and 1520 K, bulk gas compositions ranged from 4 to 21% oxygen, and both cooled and uncooled injection probes were used at a variety of axial locations. This resulted in average particle temperatures from 1578 to 2101 K and burnouts from 33 to 90%. Individual particle temperature, size and velocity were determined for approximately 75 particles at each test condition. Burnouts, calculated using titanium as a tracer, are listed for the samples that have been analyzed for titanium. Elemental analysis is continuing on the remaining samples.

Table II.B-1. Completed Tests for the Utah Blind Canyon Char.

Wall Temp (°C)	Press (atm)	O ₂ Con (%)	O ₂ Pres (atm)	Inj Probe (cm)	Probe Type*	Size (μm)	Part Temp (K)	Burnout (%)	App Dens (g/cc)
900	1	10	0.10	22	C	70	1613	37.2	.756
900	1	10	0.10	7	U	70	1663	25.5	.632
900	1	10	0.10	10	U	70	1679	37.9	.618
900	1	21	0.21	17	C	70	1834	68.4	.644
900	1	21	0.21	4	U	70	1856	75.2	.585
900	1	21	0.21	7	U	70	1832	56.2	.627
900	1	21	0.21	10	U	70	1826	58.5	.565
900	1	21	0.21	10	U	70	1815	76.1	.629
900	1	21	0.21	17	C	40	1827		.764
900	1	21	0.21	4	U	40	-		.669
900	1	21	0.21	7	U	40	1831		.601
900	1	21	0.21	10	U	40	1834		.683
1000	1	10	0.10	22	C	70	1691	61.9	.664
1000	1	21	0.21	13	C	70	1890	62.1	.651
1000	1	21	0.21	17	C	70	1879	49.0	.742
1000	1	21	0.21	17	C	70	1823	84.2	.535
1000	1	21	0.21	17	C	70	1872	72.2	.522
1000	1	21	0.21	21	C	70	1857	78.7	.582
1250	1	10	0.10	8	C	70	1780	48.8	.658
1250	1	10	0.10	2	U	70	1825	59.1	.619
1250	1	10	0.10	5	U	70	1863		.758
1250	1	10	0.10	8	U	70	1834	78.9	.825
1250	1	21	0.21	8	C	70	1959	90.0	.496
1250	1	21	0.21	2	U	70	1940	56.2	.565
1250	1	21	0.21	3.5	U	70	2000		.639
1250	1	21	0.21	5	U	70	2006	81.0	.695
1250	1	21	0.21	6	C	40	1913	75.9	.609
1250	1	21	0.21	2	U	40	1917		.586
1250	1	21	0.21	3	U	40	1984		.759
950	5	4	0.20	35	C	70	No	Reaction	-
950	5	10	0.50	17	C	70	1694	66.3	.644
950	5	10	0.50	8	U	70	1652	49.8	.637
950	5	10	0.50	11	U	70	1668	56.6	.632
950	5	10	0.50	14	U	70	1662	67.7	.646
950	5	21	1.05	2	U	70	1848	72.1	.693
950	5	21	1.05	3.5	U	70	1912		.712
950	5	21	1.05	5	U	70	1900	82.1	.805
950	5	21	1.05	2.5	U	40	1842		.662
950	5	21	1.05	5	U	40	1904		.687
1250	5	4	0.20	8	U	70	1601	34.4	.619
1250	5	4	0.20	12	U	70	1578	33.4	.695
1250	5	10	0.50	5	U	70	1787	78.4	.710
1250	5	10	0.50	7	U	70	1817		.844
1250	5	10	0.50	9	U	70	1823	78.8	1.128
1250	5	21	1.05	2	U	70	2000	80.0	.830
1250	5	21	1.05	3.5	U	70	2051		1.124
1250	5	21	1.05	5	U	70	2101		1.349
1250	5	21	1.05	2	U	40	1967		.734
1250	5	21	1.05	5	U	40	2013		.998

* Injection Probe: C - Cooled, U - Uncooled

Apparent densities were calculated from measured bulk densities, assuming a void volume of 0.45.

Figure II.B-1 shows the burning mode for the Utah data set. The burning mode parameter, a , is defined as

$$\left(\frac{\rho}{\rho_o}\right)_{daf} = \left(\frac{m}{m_o}\right)_{daf}^a$$

where an "a" value of 0 indicates constant density, decreasing diameter burning (zone 3) and an a of 1 indicates decreasing density, constant diameter burning (zone 1). The burning mode parameter most consistent with the data, determined from a least squares regression, is 0.65. This indicates that the oxidation experiments occurred in the pore diffusion regime. There doesn't seem to be any effect of pressure on the burning mode.

An updated plot of mass reactivity vs. reciprocal particle temperature for all tests to date is shown in Figure II.B-2. Particle temperatures were measured during the Utah tests and calculated for the other chars. The upper line corresponds to the best fit of the reactivity data for the Zap char oxidized at atmospheric pressure while the lower line is the best fit of the Pittsburgh char reactivity as determined at atmospheric pressure. The Utah char exhibits reactivities between these extremes. Reactivities of the chars oxidized at 5 atm pressure do not appear to be significantly different from their respective atmospheric pressure reactivities. The activation energy is approximately 25 kcal/mol for the chars, indicating that the reaction occurred under zone 2 conditions where pore diffusion is significant. This is in agreement with the burning mode as discussed above.

Global chemical reaction rates were calculated for the Utah and Zap chars by accounting for film diffusion, assuming the quasi steady-state condition that the reaction rate was equal to the film diffusion rate. Film diffusion rates were determined using classical transport methods and accounting for the effects of Stefan flow. A least squares regression of the Utah data determined the apparent reaction order to be in the range of 0.3-0.5; thus, the rates were calculated assuming an order of 0.5. These reaction rates are plotted against reciprocal temperature in Figure II.B-3. It is seen that the reaction rates for the chars oxidized at pressure are

Figure II.B-1. Burning Mode for Utah Char.

Figure II.B-2. Char Mass Reactivities for a Number of Coals.

Figure II.B-3. Char Global Reaction Rate Coefficients.

Figure II.B-4. The Effect of Pressure on Particle Temperature.

significantly lower than the reaction rates determined for the same chars at atmospheric pressure. Increasing pressure also seems to slightly decrease the activation energy as indicated by the slope of the rate data. This trend of decreasing reaction rate with increasing pressure is also seen in the particle temperature measurements of the Utah char. Figure II.B-4 shows average particle temperature as a function of O_2 partial pressure and total pressure. At a given O_2 pressure the particle temperature is much higher for the chars oxidized at 1 atm total pressure. The char would not even ignite at a gas condition of 5 atm total pressure, 0.20 atm O_2 pressure and 1100 K. An examination was made to determine if increased heat transfer from a char particle at elevated pressure could account for this temperature decrease. For the conditions of the experiments, the heat transfer coefficient increases by 5% as the total pressure is raised from 1 to 5 atm. This amounts to a maximum particle temperature difference of only 20 K, not enough to explain the pressure effect. Analysis of these new data is preliminary.

Other Activities

During the reporting period the research team made a presentation in the semi-annual technical review meeting at BYU with AFR, BYU and METC representatives present. In addition, the team was involved in three technical posters which were displayed for the attendees of the Sixth Annual Technical Review Meeting of the Advanced Combustion Engineering Research Center (ACERC) in Provo, Utah. The research team is also collaborating with researchers from another university to make on-line measurements of coal devolatilization products in the HPCP with a highly sensitive mass spectrometer.

Plans

The char oxidation tests for the primary reference coal and the other four coals will be largely completed during the next quarter. Oxidation tests will continue with the Utah char. A few tests will be conducted at 1 atm total pressure and a gas composition of 4% O_2 , allowing more accurate determination of reaction order. Testing will then continue at 10 and 25 atm pressure, where approximately 20 tests will be carried out. A number of replicate tests will also be conducted with the Utah char at 1 and 10 atm total pressure to determine the uncertainty in the experiments and analyses.

A few select tests will then be conducted on the remaining coal chars to determine if their high pressure behavior is similar to the Utah char. Some modification to the plan may be dictated as particular characteristics of the HPCP and the UT Blind Canyon HVB coal are discovered.

II.C. SUBTASK 2.c. - SECONDARY REACTION OF PYROLYSIS PRODUCTS AND CHAR BURNOUT

SUBMODEL DEVELOPMENT AND EVALUATION

Senior Investigator - James R. Markham and Michael A. Serio
Advanced Fuel Research, Inc.
87 Church Street, East Hartford, CT 06108
(203) 528-9806

Objective

The objective of this subtask is to develop and evaluate by comparison with laboratory experiments, an integrated and compatible submodel to describe the secondary reactions of volatile pyrolysis products and char burnout during coal conversion processes. Experiments on tar cracking, soot formation, tar/gas reactions, char burnout, and ignition will continue during Phase II to allow validation of submodels.

Accomplishments

Discussions continued with BYU on implementation of the soot oxidation and particle ignition submodels.

Plans

Complete work with BYU on submodels for ignition and soot formation.

II.D. SUBTASK 2.d. - ASH PHYSICS AND CHEMISTRY SUBMODEL

Senior Investigator - James Markham
Advanced Fuel Research, Inc.
87 Church Street, East Hartford, CT 06108
(203) 528-9806

Objective

The objective of this task is to develop and validate, by comparison with laboratory experiments, an integrated and compatible submodel to describe the ash physics and chemistry during coal conversion processes. AFR will provide the submodel to BYU together with assistance for its implementation into the BYU PCGC-2 comprehensive code. To accomplish the overall objective, the following specific objectives are: 1) to develop an understanding of the mineral matter phase transformations during ashing and slagging in coal conversion; 2) to investigate the catalytic effect of mineral matter on coal conversion processes.

Accomplishments

No work scheduled.

Plans

Complete work on submodel for ash chemistry and physics.

II.E. SUBTASK 2.e. - LARGE PARTICLE/THICK BED SUBMODELS

Senior Investigator - Michael A. Serio
Advanced Fuel Research, Inc.
87 Church Street
East Hartford, CT 06108
(203) 528-9806

Objective

The objectives of this task are to develop or adapt advanced physics and chemistry submodels for the reactions of "large" coal particles (i.e., particles with significant heat and/or mass transport limitations) as well as thick beds (multiple particle layers) and to validate the submodels by comparison with laboratory scale experiments. The result will be coal chemistry and physics submodels which can be integrated into the fixed-bed (or moving-bed) gasifier code to be developed by BYU in Subtask 3.b. Consequently, this task will be closely coordinated with Subtask 3.b.

Accomplishments

The recent work has focused on completion of literature reviews in two areas: 1) data on tar yields from laboratory scale pyrolysis studies with Pittsburgh Seam bituminous coals (and comparable coals); 2) data for the yields of tar from actual gasifier systems. The overall conclusions are as follows: 1) The effects of particle size on devolatilization time are very important- the effects on tar yield are not; 2) The residence time of tar in the gasifier is inversely correlated with tar yield because of cracking and gasification reactions; 3) The reduced yields for pressurized gasifiers are due to increased residence time, increased gasification rate and/or a related temperature effect; 4) Both increased particle size and pressure would tend to move the tar evolution zone toward the hotter part of the gasifier.

The recommendations are as follows: The effect of particle size on shifting and broadening the devolatilization zone should be included. This is more realistic and may help solve the numerical problems introduced by the occurrence of the tar spike using the current model. The second recommendation is to allow the tar gasification to occur at the same rate as for the char, but at the gas temperature, and to allow the tar cracking to occur at the same rate as for coal pyrolysis, also at the gas

temperature. These recommendations are short term solutions which could probably be incorporated under the current contract.

Some experiments were done at AFR to assess the relative importance of tar gasification and tar cracking reactions. A post-pyrolysis unit was used to heat tar in the presence of helium or helium/CO₂ mixtures at temperatures up to 900 °C. It was found that, while the thermal cracking effects were significant (note increase in acetylene and C₂H₄), the addition of CO₂ did not have much effect on the yield or composition of tar. Consequently, it was concluded that the tar destruction in the top part of a fixed-bed gasifier can probably be attributed primarily to thermal cracking rather than gasification reactions.

Modeling of Tar Destruction in a Moving-Bed Gasifier

The recent work has focused on completion of literature reviews in two areas: 1) data on tar yields from laboratory scale pyrolysis studies with Pittsburgh Seam bituminous coals (and comparable coals); 2) data for the yields of tar from actual gasifier systems.

Particle Size Effects

The first area that was surveyed concerned the effects of particle size. Some data was examined from the work of Karner (1992) who studied pyrolysis of baskets of large particles of coal (5-60 mm) that were immersed in a hot gas stream (500-850 °C) that was generated by burning natural gas in air. The idea of his study was to simulate pyrolysis as it occurs in a fixed-bed gasifier. Their work shows clearly that large particles take a long time to devolatilize, as shown in Table II.E-1, but that the ultimate tar yield is not reduced very much for the larger particles in the size range that was studied (<60mm), as shown on Table II.E-2. There is also a lot of data available on the effects of particle size on devolatilization time from studies in fluidized bed pyrolysis of coal. Unfortunately, in relatively few cases were measurements of tar yield made or calculated. One exception was the work of Stubington and Sumaryono (1984) where the tar yield (plus H₂O) was determined by difference of the starting coal, gas and char yields for fluidized bed pyrolysis over a range of particle sizes and temperatures. Three Australian coals were studied of a range of coal ranks. The results suggested that at low pyrolysis bed temperatures (T ~ 750 °C) the particle

Table II.E-1. Effect of Particle Size on Time to Reach Ultimate Tar Yield for a German Coal.

Time (min)	Tar Yield (wt.% AR)
5	8
10	21
30	21

$D_p = 20-40 \text{ mm}$

$T_{\text{GAS}} = 810^\circ\text{C}$

Data of Karner (1991)

Table II.E-2. Effect of Particle Size on Ultimate Tar Yield From Fixed-Bed Pyrolysis of a German Coal.

D_p (mm)	Ultimate Tar Yield (wt.% AR)
Powder (< 0.075)	20*
5-10	23
20-40	21
50-60	20

* Measured in TGA

Other data from Karner (1991) from fixed-bed of particles heated with an entering gas flow temperature of -800°C .

size effects were small for all three coals (see Table II.E-3). At high bed temperatures ($T \sim 950^\circ\text{C}$) evidence of a particle size effect begins to emerge (see Table II.E-4). This could be due to the diffusion of tar out of the particle through much hotter char layers.

However, this result cannot be confirmed since the tar yield was not measured directly. It is possible that the "reduction" in tar yield with particle size was due to the loss of H_2O through gasification reactions. If one looks at data for actual gasification systems for particle size effects, the limited amount available also does not point to a significant particle size effect on yields, as shown in Table II.E-5. In summary, most of the data on particle size effects on tar yields from pyrolysis systems or gasifiers indicate that there is only a small effect on the ultimate tar yield. However, the pyrolysis of larger particles in gasifiers is likely to be influenced by internal heat transport limitations which will spread out the tar evolution in time and cause the tar evolution to occur lower in the gasifier where the ambient gas temperature is higher.

Pressure Effects

The second area that was surveyed was the effect of pressure, which is important since moving-bed gasifiers are usually run at high pressure. The effects of pressure in bituminous coal pyrolysis were demonstrated by the work of Suuberg (1977) in a wire grid heater (see Fig. II.E-1). More recently, Ko et al. (1988) have developed a correlation which describes the variation of tar yield with pressure, using primarily data from grid heaters. However, a survey of data in tar yields from fixed bed pyrolysis in the presence of a gas flow does not indicate an effect of pressure if the residence time is maintained constant (Dryden and Sparham 1963), the results of this survey are summarized in Table II.E-6. Although, the data from actual gasifier systems is widely scattered, the effect of residence time is fairly clear, i.e., increased gas flow (decreased residence time) leads to an increase in the amount of tar produced, as shown in Fig. II.E-2. When exceptions to this generalization were found, it was the case that the ratio of the amount of oxygen/coal was increased, as shown in Fig. II.E-3. This would lead to a higher gasifier temperature, higher partial pressure of CO_2 and increased gasification and cracking of tar.

Despite the lack of an "intrinsic" effect of pressure in flow systems, it is clear that the tar yields from pressurized gasifiers are usually much lower than from

Table II.E-3. Effect of Particle Size on Ultimate Tar Yield for Three Coals Pyrolyzed in a Fluidized Bed at 750°C.

$$T_{\text{GAS}} = 750^{\circ}\text{C}$$

Tar Plus Pyrolysis H₂O*
(dry wt.%)

D_p (mm)	Bulli	Great Northern	Greta
3-5	8	20	29
5-7	12	18	30
7-11	10	18	29

* Data of Stubington and Sumaryono (1984) Determined by Difference.

Table II.E-4. Effect of Particle Size on Ultimate Tar Yield for Three Coals Pyrolyzed in a Fluidized Bed at 960°C.

$$T_{\text{GAS}} = 950^{\circ}\text{C}$$

Tar Plus Pyrolysis H₂O*
(dry wt.%)

D_p (mm)	Bulli	Great Northern	Greta
3-5	13	---	22
5-7	10	16	24
7-11	10	15	23

* Data of Stubington and Sumaryono (1984) Determined by Difference.

Table II.E-5. Particle Size Effect On Tar Evolution in an Atmospheric Pressure Gasifier

Coal	Dry Gas Flow (lb/hr)	Particle Size (inches)	Tar Yield (AR wt.%)
Illinois No. 6	6357	+3/4	14.1
Illinois No. 6	6361	+1/4	14.7
Elkhorn	8718	+3/4	14.3
Elkhorn	8505	+1/4	14.6

Table II.E-6. Summary Of Data On Tar Yields From Pyrolysis Of Coal Under The Pressure Of Various Gases In Flow Systems (Dryden And Sparham, 1963)

Ambient Gas	Effect
Nitrogen (a)	Yield unchanged, heavier, less low-boiling fractions, more phenols.
Nitrogen (b)	Lower yield, more low-boiling fractions, less phenols.
Steam (a)	Much higher yield, heavier, less low-boiling fractions.
Steam (b)	Lower Yields, heavier, more low-boiling fractions, less phenols.
Product Gas (b)	Much lower yield, lighter, less phenols

^a Denotes increasing pressure at constant volatile residence time.

^b Denotes volatile residence increasing in direct proportion to pressure.

Figure II.E-1. Effect of Pressure on Pyrolysis Product Yields from Pittsburgh Seam Coal (Suuberg, 1977).

Figure II.E-2. Effect of Gas Flow Rate on Tar Yield at Constant Pressure.

Figure II.E-3. Effect of Oxygen/Coal Ratio on Tar Yield.

atmospheric pressure gasifiers. Examples of results from both systems are shown in Table II.E-7. This is true even when the pressure is increased at constant volatile residence time, as shown in Fig. II.E-4. This could be due to an increased gasification rate due to higher partial pressures of CO_2 and H_2O and/or a shift in the devolatilization zone toward the lower (and hotter) portion of the gasifier at higher pressures.

In summary, it is not clear whether the data of Suuberg (1977) and the correlation of Ko et al. (1988) is relevant to the effects of pressure in fixed bed gasifiers. The increase of pressure in a wire grid system will affect internal transport, the evaporation rate of tar from the coal melt and the diffusion rate away from the heated zone in these systems. Except for the work done at AFR for the FG-DVC model development (Solomon et al., 1988), the tar transport from wire grids has been modeled assuming external transport controls. It is likely that for a moving bed gasifier, internal transport of tar (or heat transfer) is limiting since the particles are large and there is a high external gas flow rate. The effects of pressure observed in gasifiers are probably due to increased gasification of tar or a related temperature effect, i.e., a shift in the tar evolution zone to the hotter part of the gasifier.

Summary and Conclusions for Literature Data

The overall conclusions are as follows: 1) The effects of particle size on devolatilization time are very important- the effects on tar yield are not; 2) The residence time of tar in the gasifier is inversely correlated with tar yield because of cracking and gasification reactions; 3) The reduced yields for pressurized gasifiers are due to increased residence time, increased gasification rate and/or a related temperature effect; 4) Both increased particle size and pressure would tend to move the tar evolution zone toward the hotter part of the gasifier.

The recommendations are as follows: The effect of particle size on shifting and broadening the devolatilization zone should be included. This is more realistic and may help solve the numerical problems introduced by the occurrence of the tar spike using the current model. One possibility is to use the simplified version of the model developed by Agarwal and coworkers (1984, 1986), which is shown in Fig. II.E-5, for devolatilization in fluidized beds. These calculations could then be compared to the same calculations using a kinetic model in order to develop a correction factor for the values of A and/or E in the FG-DVC model.

Table II.E-7. Comparison of Tar Yields from Atmospheric Pressure (Wellman Galusha) and Pressurized Gasifiers (ar wt.%).

Gasifier	Coal	O ₂ /Coal Ratio	Steam/Coal Ratio	Tar Yield	Pressure (psig)
W-G	Jetson	0.5	0.4	12.9±5.4	0
W-G	Illinois No. 6	0.5	0.5	14.4±4.2	0
British Gas	Pittsburgh No. 8	0.5	0.3	6.4±3.1	335
METC	Pittsburgh No. 8	2.8	0.5	4.4±4.6	150
GE	Illinois No. 6	2.4	0.9	3.4±1.0	300

**METC Gasifier-Pittsburgh No. 8
88-210 psig**

Figure II.E-4. Effect of Increasing Pressure (and gas flow rate) on Tar Yields When the Pressure Increases in Proportion to the Gas Flow Rate, Tar Yields Decline

The second recommendation is to allow the tar gasification to occur at the same rate as for the char and to allow the tar cracking to occur at the same rate as for coal pyrolysis, but at the gas temperature. These two assumptions will probably underestimate the gasification and cracking rates which could be compensated for by a single adjustable parameter (or two if necessary) in order to allow the predicted tar yields to match the measured tar yields. These recommendations are short term solutions which could probably be incorporated under the current contract.

Results from Laboratory Studies of Tar Cracking and Gasification

Some experiments were done at AFR to assess the relative importance of tar gasification and tar cracking reactions. A post-pyrolysis unit was used to heat tar in the presence of helium or helium/CO₂ mixtures at temperatures up to 900 °C. Spectra from the TG-FTIR analysis of Pittsburgh Seam coal with the post-pyrolyzer on or off are shown in Figs. II.E-6a and b, respectively. Comparable spectra with and without the addition of CO₂ are shown in Figs. II.E-7a and b, respectively. It was found that, while the thermal cracking effects were significant (note increase in acetylene and C₂H₄), the addition of CO₂ did not have much effect on the yield or composition of tar. Some literature data on the fluidized-bed pyrolysis of coal in the presence of CO₂ (under conditions where tar cracking was significant) also did not reveal an effect of CO₂ on tar yields or composition (Tyler, 1980). Consequently, it was concluded that the tar destruction in the top part of a fixed-bed gasifier can probably be attributed primarily to thermal cracking rather than gasification reactions.

Additional evidence for this conclusion can be found in a study of data from actual gasifiers (Thimsen and Maurer, 1990). The high pressure gasifiers, which have the lowest yields of tar, have longer gas phase residence times, and significantly increased yields of dust. The composition of the dust indicates a high carbon content and hydrogen content which is consistent with the composition of soot formed from tar cracking. The increased yields of light hydrocarbon species are also consistent with results from tar cracking. Consequently, the destruction of tar should be largely accounted for by allowing it to crack at the gas phase temperature using similar pyrolysis rates as are used for the coal. A recommendation was made to BYU to include this change.

Figure II.E-6. Spectra from TG-FTIR during Pyrolysis of Pittsburgh No. 8 Coal.
a) Post-Pyrolyzer off, b) Post-Pyrolyzer at 900°C. The Spectra were Taken at a Sample Temperature of 480°C.

Figure II.E-7. Spectra from TG-FTIR during Pyrolysis of Pittsburgh No. 8 Coal. a) Post-Pyrolyzer at 800°C, b) Post-Pyrolyzer at 800°C with CO₂ Flowing Through. The Spectra were Taken at a Sample Temperature of 480°C.

Plans

Complete development of tar destruction submodel. Complete development of single particle model with BYU.

II.F. SUBTASK 2.F. - LARGE PARTICLE OXIDATION AT HIGH PRESSURES

Senior Investigators: Angus U. Blackham and Geoffrey J. Germane
Brigham Young University

Provo, Utah 84602

(801) 378-2355 and 6536

Student Research Assistants: Ken Bateman and Parvin Yousefi

Objectives

The overall objective for this subtask is to provide data for the reaction rates of large char particles of interest to fixed-bed coal gasification and combustion systems operating at pressure.

The specific objectives for this quarter include:

1. Continue the construction of the cantilever beam balance unit.
2. Conduct additional oxidation experiments at atmospheric pressure.

Accomplishments

The two components of this subtask that have been suggested earlier for accomplishing the overall objective are: 1) reactor design, fabrication, and preliminary data; 2) experimental reaction rate data for chars from five coals. Construction of a cantilever beam balance unit to be connected to an optical access port of the HPCP reactor has continued during this quarter.

The data previously presented as preliminary oxidation measurements of large char particles of six different coals have been organized into a manuscript and submitted for publication. A thick-ash-layer theory was developed and was supported by the experimental observation that the cube root of the char particle mass declined linearly with time in all tests of the 35 particles. Average mass reactivities were correlated with initial char particle mass, temperature, and ash fraction.

Reactor Design

Cantilever Beam Balance Unit - The cantilever beam balance unit was designed to give mass loss readings and to precisely locate the sample during

oxidation experiments using 0.5-1.0 cm char particles. The three components of the cantilever beam balance unit are: a) a balance unit; b) a two-axis slide; and c) a heat-shielded, water-cooled valve. The entire assembly will be bolted directly to the HPCP reactor of Subtask 2b.

The balance unit measures the mass loss of the particles as they oxidize in the HPCP reactor. It consists of a force transducer, a ceramic cantilever beam and a platinum wire-mesh sample basket. The basket is secured to the cantilever beam and extends into the reactor tube through one of the optical access ports of the HPCP reactor.

In order to test multiple samples during each run, a mechanism has been designed to insert and retract the samples from the reactor tube. The balance unit is mounted on a mobile platform. The two-axis slide that was discussed previously has been improved to move along three axes. With this improvement the particle can be moved in all directions while being oxidized. First, the entire unit will move toward and away from the reactor tube in the horizontal direction by way of a stepper motor. The remaining two directions will be performed by way of a manual positioner. The positioners will allow for 10 mm of movement. Construction of the main components of the three-axis slide have been completed. Assembly of the components has begun.

A poster was prepared illustrating the design and construction of the cantilever beam balance unit for the 6th Annual ACERC Technical Review Meeting. This poster was also presented in the AFR review meeting.

Oxidation Measurements

Large Particle Oxidation Measurements - The data previously presented (Solomon et. al, 1990, 1991, 1992) as preliminary oxidation measurements of large char particles in platinum crucibles heated in a muffle furnace or with Mekker burner have been organized into a manuscript and submitted for publication. Both thin- and thick-ash-layer theories were developed and tested with these data from the oxidation of 35 char particles in which six different coals were represented. Test variables were coal type, oxidation temperature, and initial char particle mass. The cube root of particle mass declined linearly with time in all tests, which supports the thick-ash-layer theory. Ash layers formed and usually remained in place around the char particle. Average mass reactivities increased with decreasing

initial char particle mass and possibly with decreasing char ash percentage. Increasing furnace temperature had little impact on char reactivity. These correlations of average mass reactivity are presented in Figure II.F-1. Observations are consistent with oxidation being controlled by diffusion of oxygen through the ash layer.

A recent observation is given in Figure II.F-2. The question to be answered was whether a few large particles in a crucible with no convective flow oxidized as one large particle of equivalent mass or as individual particles each alone in a separate crucible. The figure suggests that four large particles together in the crucible oxidize as one large particle of about the same total mass.

A poster was prepared summarizing the data and theory of the oxidation of these large particles for the 6th Annual ACERC Technical Review Meeting. This poster was also presented in the AFR review meeting.

Plans

During the next quarter, the construction of the cantilever beam balance unit will be completed and tested for its accuracy and reproducibility in positioning the sample char particle in the reactor. The rates of oxidation of the selected coals will then be measured at pressures above atmospheric pressure.

Additional preliminary oxidation runs will be made in air in platinum crucibles to resolve some of the issues raised with the previous preliminary experiments.

Figure II.F-1. Correlations of average mass reactivity (AMR) with three variables and selected combinations where $m = [\text{initial char mass(g)}]^{-2/3}$, $F = (1 - \text{fraction of ash})$ and $T = [\text{temperature(K)}]^{0.6}$.

[Char Mass Remaining (Ash Free)]^{1/3}
Vs. Time (Coal: ILL)

Utah Bituminous Coal T = 1073 K

■ One Particle ✕ Four Particles

■ Four Particles ✕ One Large Particle of Mass Equivalent to Four Particles

■ One Particle ✕ Four Particles

■ Four Particles ✕ One Large Particle of Mass Equivalent to Four Particles

Figure II.F-2. Comparison of the oxidation of four large particles together in a single crucible to one large particle of about the same total mass.

II.G. SUBTASK 2.G. - SO_x/NO_x SUBMODEL DEVELOPMENT

Senior Investigators: L. Douglas Smoot and B. Scott Brewster
Brigham Young University
Provo, Utah 84602
(801) 378-4326 and (801) 378-6240

Research Assistant: Richard D. Boardman

Objectives

The objectives of this subtask are 1) to extend an existing pollutant submodel in PCGC-2 for predicting NO_x formation and destruction to include thermal NO, 2) to extend the submodel to include SO_x reactions and SO_x-sorbent reactions, and 3) to consider the effects of fuel-rich conditions and high pressure on sulfur and nitrogen chemistry in pulverized-fuel systems.

Accomplishments

An option for capturing H₂S was added to the sulfur/sorbent reactions submodel. The shrinking-core, grain sulfation model of Silcox (1985) was used to predict the capture of H₂S by the calcined limestone or calcined calcium hydrate:

The reaction was assumed to be first order with respect to H₂S. The rate constant was obtained by correlating experimental data of Borgwardt (1984) and Borgwardt and Roache (1984). The diffusivity of H₂S(g) through the solid product layer, CaS, was also deduced from the measurements of Borgwardt and Borgwardt and Roache. Table II.G-1 lists the solid-state diffusion and reaction rate parameters for H₂S and SO₂.

When SO₂ is captured, the void space is gradually filled by the CaSO₄ product, which has a much larger molar volume than CaO (see Table II.G-1). This pore plugging limits the conversion that can be obtained with SO₂

Table II.G-1 Parameters for Sorbent/Sulfur Reactions Submodel

<u>Parameter</u>	<u>SO₂ Sulfation</u>	<u>H₂S Sulfation</u>
CaO molar volume, mol cm ⁻³	16.9	16.9
CaSO ₄ molar volume, mol cm ⁻³	52.2	N/A
CaS molar volume, mol cm ⁻³	N/A	28.9
Solid-state product diffusivity: $D_{sp}=D_o\exp(-E/RT)$, cm ² s ⁻¹		
D_o	0.36	0.118
E	12,200	15,900
First-order reaction rate: $k=k_o\exp(-E/RT)$, cm s ⁻¹		
k_o	291	67,700
E	7,510	13,400

capture. The molar volume of CaS is only a little over one-half the molar volume of CaSO₄. Thus, higher conversion is possible with H₂S capture.

Plans

The H₂S capture subroutine will be tested.

SECTION III. TASK 3. COMPREHENSIVE MODEL DEVELOPMENT AND EVALUATION

Objectives

The objective of this task is to integrate advanced chemistry and physics submodels into a comprehensive two-dimensional model of entrained-flow reactors (PCGC-2) and to evaluate the model by comparing with data from well-documented experiments. Approaches for the comprehensive modeling of fixed-bed reactors will also be reviewed and evaluated and an initial framework for a comprehensive fixed-bed code will be employed after submission of a detailed test plan (Subtask 3.b).

Task Outline

This task is being performed in three subtasks. The first covers the full 72 months of the program and is devoted to the development of the entrained-bed code. The second subtask is for fixed-bed reactors and is divided into two parts. The first part (12 months) was devoted to reviewing the state-of-the-art in fixed-bed reactors. This led to the development of the research plan for fixed-bed reactors, which was approved. The code development is being done in the remaining 60 months of the program. The third subtask is to generalize the entrained-bed code to fuels other than dry pulverized coal and will be performed during the last 36 months of the program.

III.A. SUBTASK 3.A. - INTEGRATION OF ADVANCED SUBMODELS INTO ENTRAINED-FLOW CODE, WITH EVALUATION AND DOCUMENTATION

Senior Investigators - B. Scott Brewster and L. Douglas Smoot
Brigham Young University
Provo, UT 84602
(801) 378-6240 and 4326

Research Assistants - Ziaul Huque and Susana K. Berrondo

Objectives

The objectives of this subtask are 1) to integrate the FG-DVC submodel into PCGC-2, 2) incorporate additional submodels and improvements developed under Task 2, 3) evaluate the improved code, 4) improve user-friendliness and robustness, and 5) document the code.

Accomplishments

Submodel Integration

A new version of the FG-DVC submodel, with sulfur and nitrogen pools and swelling, was incorporated into PCGC-2. A char reactivity submodel was also incorporated. Both submodels are being tested.

Code Evaluation

The code is being evaluated by comparison with data from five reactors: the AFR transparent wall reactor (TWR), the BYU/ACERC controlled-profile reactor (CPR), the Imperial College reactor, the BYU gasifier, and the Combustion Engineering (CE) drop-tube furnace. Calculations were performed during the past quarter for the CPR and Imperial College reactor.

BYU/ACERC Controlled-Profile Reactor (CPR) - A diagram of the CPR and results of gas flame simulations were given in the 5th Annual Report (Solomon et al., 1991). Input conditions and predictions for coal combustion were given in the 21st Quarterly Report (Solomon et al., 1991). These predictions were made using a swirl no. of 0.8 rather than the reported value of 1.4, consistent with the recommendations of Harding (1980) for theoretical

and measured swirl numbers. Using the reported swirl no. resulted in the particles travelling along the front wall of the reactor due to an incorrectly predicted external recirculation zone. During the last quarter, it was found that the external recirculation zone could be predicted reasonably well at the reported value of swirl no. (1.4) if a finer grid were used. Velocity vectors and particle trajectories for this simulation are shown in Fig. III.A-1. The particles penetrate farther into the reactor before reversing direction, consistent with observations reported in the Imperial College reactor, which has a similar geometry.

Imperial College Reactor - A description of available datasets for the axisymmetric, Imperial College reactor was given in the 5th Annual Report (Solomon et al., 1991). A schematic diagram of the reactor was shown in the 21st Quarterly Report (Solomon et al., 1991). In the 5th Annual Report, it was reported that the directions of both the internal and external recirculation zones are incorrectly predicted. No flow reversal was seen on the centerline near the inlet. In the 21st Quarterly Report, the effects of swirl no. were investigated, but flow reversal on the centerline was not predicted.

During the last quarter, flow reversal was obtained at swirl nos. greater than approximately 0.35 by using a finer grid. Predicted velocity vectors and particle trajectories are shown in Fig. III.A-2. The particles penetrate the reactor to a depth of approximately 0.5 m, reverse in direction due to the internal recirculation zone and then flow along the front wall due to not predicting the external recirculation zone correctly. Predicted temperature and oxygen concentration profiles are compared with measurements reported by Costa et al. (1990) in Figs. III.A-3 and 4.

Only one data point for burnout was reported, i.e. 96 percent at the exit, compared with the predicted value of 100 percent. Burnout is probably overpredicted early in the reactor due to increased particle residence time by not correctly predicting the external recirculation zone.

User-Friendliness and Robustness

A working version of the graphical user interface (GUI) for preparing code input was developed and demonstrated at the 6th Annual Technical Review Meeting of ACERC. The GUI is intended to allow the inexperienced and

SCALE: 1 inch = 0.290 m = 10.27 m/s

Figure III.A-1. Velocity vectors and particle trajectories for CPR coal combustion using Utah Blind Canyon bituminous coal with a secondary swirl number of 1.4.

SCALE: 1 inch = 0.334 m = 37.68 m/s

Figure III.A-2. Velocity vectors and particle trajectories for Imperial College coal combustion with secondary swirl number of 1.03.

Figure III.A-3. Comparison of predicted radial temperature profiles with experimental data for Imperial College coal combustion with secondary swirl number of 1.03.

Figure III.A-4. Comparison of predicted radial O_2 concentration profiles with experimental data for Imperial College coal combustion with secondary swirl number of 1.03.

experienced users of PCGC-2 to quickly prepare code input for new cases. Its focus is on the standard coal combustion case with simple geometry. It is not intended to provide access to all of the code options; these can be accessed from the input data files once they are generated. A tutorial explaining its use is included in Appendix A.

Plans

During the next quarter, integration, testing, and evaluation of the code with graphics will be completed. The user's manual will be completed. Simulation of the application cases will be initiated.

III.B. SUBTASK 3.B. - COMPREHENSIVE FIXED-BED MODELING REVIEW, DEVELOPMENT, EVALUATION, AND IMPLEMENTATION

Senior Investigators - Predrag T. Radulovic and L. Douglas Smoot
Brigham Young University
Provo, Utah 84602
(801) 378-3097 and (801) 378-4326

Research Assistant - M. Usman Ghani

Objectives

The objectives of this subtask are: 1) to develop an advanced fixed-bed model incorporating the advanced submodels being developed under Task 2, particularly the large-particle submodel (Subtask 2.e.), and 2) to evaluate the advanced model.

Accomplishments

During the last quarter, work continued on developing and evaluating the fixed-bed model, FBED-1. The FBED-1 code was applied to the design of a fixed-bed gasifier for the DOE/METC Gasification Product Improvement Facility (GPIF). The code was demonstrated both as a design tool and as an analysis tool. Work was also continued to consolidate the input data for the final simulations of a high pressure, Lurgi gasifier and an atmospheric pressure, Wellman-Galusha gasifier. A poster was presented at the Sixth Annual NSF Site Visit. A poster and product demonstration of the fixed-bed code were also presented at the ACERC Sixth Annual Technical Review Meeting. An overview of the fixed-bed code development was presented at the METC/AFR/BYU Contract Review Meeting. Two papers were accepted for publication (Hobbs et al., 1992a, b).

FBED-1 Code Development

The analysis of the fixed-bed code to improve the model predictions was continued. The individual submodels were studied to obtain a better agreement between the predictions and the experimental temperature profile. Corrections were made in the module htcoef.f, which calculates the heat transfer coefficients. The effects of heat transfer between the gas and the solid

phases, and between the fixed-bed and the gasifier wall were analyzed. The model appears to simulate correctly the heat transfer effects. However, during devolatilization, spatial and temporal heating rates for the solid are an order of magnitude higher than expected. In order to analyze these results, the effects of devolatilization, gasification, and oxidation reactions were studied further. The results showed that the devolatilization causes steep changes in the temperature fields. In addition, slightly higher temperatures are obtained when the gases generated in the drying and devolatilization zone are allowed to react to equilibrium.

In order to improve the predicted effluent gas composition, simulations were made for the Wellman-Galusha gasifier fired with the Jetson bituminous coal with two additional options. The first option provides for the gases to be kept chemically frozen and out of equilibrium throughout the reactor bed. The second option allows the gases generated in the drying and devolatilization zone to be kept out of equilibrium and to switch to total chemical equilibrium when devolatilization rate falls below a specified threshold value. The simulations with the chemically frozen option yielded negative concentrations for some species. Figure III.B-1 shows the results with this option. In the above simulations, when the concentration of any species became negative, it was set to zero. The temperature and composition profiles beyond that point are, therefore, not realistic. This indicates the importance of accurate starting composition for the gas phase, while integration is being carried out from the top to the bottom of the reactor.

Figure III.B-2 shows the results when the devolatilized gases are kept out of equilibrium only in the drying and devolatilization zone. Once the net devolatilization rate falls below a threshold value, total chemical equilibrium is assumed for the gas phase. With this option, the solid and gas phase temperatures are lower at the end of the devolatilization zone. The gasification and oxidation zones are elongated, and the peak temperatures are also slightly lower. The composition profiles show sharp jumps when the switch is made to total chemical equilibrium. These jumps can be eliminated by integrating from the bottom of the reactor. In addition, an improved criterion is essential to switch to or from total equilibrium, depending upon the direction of integration, since at high pressures devolatilization proceeds slowly and the rates may not fall below the threshold value even in the oxidation zone. A threshold temperature or a specified percent completion of devolatilization may be a better criterion.

Figure III.B-1. FBED-1 predictions with chemically frozen gas phase composition.

Figure III.B-2. FBED-1 predictions keeping the devolatilized gases out of equilibrium in the drying and devolatilization zones.

The simulations made with the above options indicated that more realistic heating rates are obtained when the devolatilized gases are kept out of equilibrium in the drying and devolatilization zones. Furthermore, integration from the bottom of the gasifier may yield improved effluent composition. Procedures to provide the option to integrate from the bottom of the reactor were considered. This option requires good estimates for the functional group composition, the bond population, and the carbon content of coal at the bottom of the bed. These estimates are not readily available. A better approach being considered is alternating integration from the top and from the bottom of the reactor. This approach has the advantage that it uses the known initial conditions for the coal while integrating from the top, and uses the known initial conditions for the gas phase while integrating from the bottom of the gasifier.

Additional simulations were made to study the effect of the effluent gas temperature. The results were found to be very sensitive to the starting gas temperature. An increase of one hundred degrees for the gas stream temperature at the reactor top leads to oxidation and gasification rates which are an order of magnitude higher. This results in a much shorter gasification and oxidation zone. New kinetic parameters for the gasification and oxidation reactions were incorporated in the code. These parameters allows the user to choose between the rank independent or the rank specific kinetic constants.

FG-DVC Code Improvements

Results for the tar evolution rates computed by FG-DVC submodel, and spatial and temporal heating rates for the solid during devolatilization were requested by AFR. These results were sent to AFR for their analysis and recommendations to improve the sharp transient behavior during devolatilization. AFR recommended to decrease the number of active tar pools to seven by increasing the effective molecular weight of the remaining six tar pools. In addition, the code was slightly modified to ensure computational stability. These recommendations were implemented into the FG-DVC submodel of the fixed-bed code. Simulations made with the modified FG-DVC still show similar behavior as shown in Fig. III.B-3. The devolatilization occurs about fifteen seconds earlier. However, the tar evolution rates from the individual mass bins are even higher when computed with the modified FG-DVC subroutine. In order to investigate this behavior further, the effects of energy exchange between the solid and the gas phases, associated with devolatilization, were

Figure III.B-3. FBED-1 computed tar evolution rates from individual mass bins: A) FG-DVC old version; B) FG-DVC modified version.

analyzed. The results showed that the energy exchange between the two phases causes the steep temperature gradients which lead to higher devolatilization rates and a temperature runaway in the devolatilization zone. This behavior was eliminated by turning off the energy exchange between the two phases. More realistic temporal and spatial gradients and heating rates were observed. The sharp transient evolution behavior of tar was eliminated and tar evolution occurred over a more realistic time span as shown in Fig. III.B-4. It is pointed out that there are energy exchange effects between the solid and the gas phases during devolatilization and the above procedure is an overcorrection. Efforts are underway to formulate an internally consistent solid phase enthalpy and to properly account for the energy exchange between the solid and gas phases during devolatilization.

FBED-1 Code Applications

The applications of the fixed-bed code as a design and analysis tool were explored. The code was applied to the design of a fixed-bed gasifier for the DOE/METC Gasification Product Improvement Facility (GPIF) in West Virginia. In addition to the explicit design requirements as specified by DOE, which include the maximum coal throughput, the minimum gasifier diameter, the gasifier type, and the range of operating pressure, the implicit design requirements were also taken into account. These requirements include the minimum heating value of the product gas, the maximum fines carryover, and the peak solid temperature. Other factors, such as engineering and economic considerations, which may play an important role in the final design, were not taken into account in these application runs. The DOE/METC specifications, and the range of the operating and design variables explored in these simulations are given in Tables III.B-1 and III.B-2.

TABLE III.B-1
DOE/METC Design Specification

Gasifier type	Dry-bottom, Air-blown
Coal throughput	6 Short tons/hr (maximum)
Gasifier diameter	1.524 m (5 ft) minimum
Operating pressure	15 - 42.4 bars (200 - 600 psig)

Figure III.B-4. FBED-1 computed tar evolution rates from individual mass bins without energy exchange between solid and gas phases during devolatilization.

$p = 28.6 \text{ bar}$ $D = 2.85 \text{ m}$ $L = 6.25 \text{ m}$

$\dot{m}_{\text{coal}} = 1.51 \text{ kg/s}$ $\dot{m}_{\text{air}} = 3.80 \text{ kg/s}$ $\dot{m}_{\text{steam}} = 1.18 \text{ kg/s}$

Gas heating value (dry) = $6,170 \text{ kJ/m}^3$

Gas yield (dry) = $5.36 \text{ m}^3/\text{s}$

Gas heating value (dry) = $26,400 \text{ kJ/kg}_{\text{coal}}$

Figure III.B-5. FBED-1 predictions for a high pressure, air-blown, dry-bottom gasifier.

$p = 15.0 \text{ bar}$

Gas heating value (dry) = $6,570 \text{ kJ/m}^3$

Gas yield (dry) = $5.21 \text{ m}^3/\text{s}$

Gas heating value (dry) = $26,300 \text{ kJ/kg}_{\text{coal}}$

Figure III.B-6. FBED-1 predictions for a high pressure, air-blown, dry-bottom gasifier showing the effect of lower gasifier pressure.

$$D = 3.42$$

Gas heating value (dry) = 6,170 kJ/m³

Gas yield (dry) = 5.36 m³/s

Gas heating value (dry) = 26,800 kJ/kg_{coal}

Figure III.B-7. FBED-1 predictions for a high pressure, air-blown, dry-bottom gasifier showing the effect of larger gasifier diameter.

$d_p = 2.00 \text{ cm}$

Gas heating value (dry) = $6,170 \text{ kJ/m}^3$

Gas yield (dry) = $5.36 \text{ m}^3/\text{s}$

Gas heating value (dry) = $26,800 \text{ kJ/kg}_{\text{coal}}$

Figure III.B-8. FBED-1 predictions for a high pressure, air-blown, dry-bottom gasifier showing the effect of smaller particle size.

$$\dot{m}_{\text{steam}} = 0.60 \text{ kg/s}$$

Gas heating value (dry) = 6,530 kJ/m³

Gas yield (dry) = 4.68 m³/s

Gas heating value (dry) = 24,300 kJ/kg_{coal}

Figure III.B-9. FBED-1 predictions for a high pressure, air-blown, dry-bottom gasifier showing the effect of lower steam flow rate.

TABLE III.B-2
Range of Design/Operating Variables Explored

Coal feed rate	1.2 - 1.51 kg/s
Air flow rate	3.0 - 4.6 kg/s
Steam flow rate	0.6 - 1.5 kg/s
Gasifier pressure	15 - 42.4 bars
Particle size	0.02 - 0.03 m
Blast gas preheat	Up to 100 K above saturation temperature
Coal type	HVBA, HVBB
Gasifier diameter	1.51 - 3.5 m
Gasifier length	3 - 7 m

Figures III.B-5 to III.B-9 show the results of these simulations. The results for the optimal case are shown in Figure III.B-5. The peak solid temperature is below the melting temperature of ash which is a requirement for the dry-bottom gasifier. Figure III.B-6 shows the effect of pressure. At a pressure of 15 bars, devolatilization rates are higher as expected. A much longer bed is needed for gasifying the same amount of coal. Figure III.B-7 shows the effect of gasifier diameter. A 20% increase in diameter leads to a much shorter bed. The gasification and oxidation rates are also increased. The effect of particle size is shown in Figure III.B-8. A 20% reduction in particle size leads to considerably higher devolatilization, gasification and oxidation rates. The peak solid temperature is still below the melting temperature of ash. A much shorter bed is needed to gasify the coal. Figure III.B-9 shows the effect of steam flow rate. When the steam flow rate is reduced from 1.18 kg/s to 0.6 kg/s, the peak solid temperature is higher than the ash melting temperature. These simulations also provided new insights and helped to isolate the portions of the code needing improvement. One of these improvements is the inclusion of axial heat and mass transfer effects.

NSF Site Visit, ACERC Technical Review Meeting, and METC Contract Review Meeting

A poster was presented at the NSF Site Visit. A release announcement for the fixed-bed model was prepared. The fixed-bed code was

demonstrated at the ACERC Technical Review Meeting. A poster was also presented at the Review Meeting.

A METC/AFR/BYU Contract Review Meeting was held at BYU. An overview of the fixed-bed code development was presented at the meeting. The devolatilization and the tar repolymerization submodels were discussed and analyzed with AFR. Recommendations for the implementation of secondary reactions and cracking of tar in the fixed-bed code were received from AFR. The schedule, the milestones, and the graphics were discussed with METC and AFR.

Plans

During the next quarter, work will continue to complete the final version of the comprehensive fixed-bed model, FBED-1. Additional portions of the code will be rewritten to further improve the structure, modularity, and user-friendliness. Internally consistent solid phase enthalpy calculations will be incorporated in the code. Energy exchange between the solid and the gas phases during devolatilization will be properly modeled. Axial heat and mass transfer effects will be added. A procedure for alternating integration from the top and from the bottom of the gasifier will be implemented. The iteration method will be further modified to improve the convergence and the robustness of the code. After completion, the code will be validated and a sensitivity analysis will be performed. Work will be completed to support spreadsheet graphics on Macintosh as well as DISSPLA graphics on SUN and Silicon Graphics. Preparation of the FBED-1 user's manual will be initiated.

SUBTASK 3.C. - GENERALIZED FUELS FEEDSTOCK SUBMODEL

Senior Investigators - B. Scott Brewster and L. Douglas Smoot
Brigham Young University
Provo, UT 84602
(801) 378-6240 and 4326

Objective

The objective of this subtask is to generalize PCGC-2 to include sorbent injection, as outlined in the Phase II Research Plan.

Accomplishments

Simulation of the BYU gasifier with sidewall sorbent injection was initiated. The case that is being simulated is case no. I9-12-2-3 from Table II.H-2 in the 3rd Annual Report (Solomon et al., 1989). The coal type is Illinois No. 6, and sorbent was injected through three ports spaced 120° apart around the circumference and 0.65 m from the inlet. A schematic diagram of the reactor, showing the sorbent injection ports, was included in the 3rd Annual Report. The injection ports were simulated in axisymmetric geometry by an annular slit of area equal to the total area of the three ports. The flowrate of the carrier gas was calculated using the definition of jet-to-free-stream momentum ratio given by Eqn. II.H-2 in the 3rd Annual. Details of the calculation are given in Appendix A.

Key input parameters for the simulation are shown in Table III.C-1. The sorbent carrier gas was assumed to be identical in temperature and composition to the coal carrier gas. Simulation results will be included in the 23rd Quarterly Report.

Plans

Complete testing of sorbent injection submodel.

Table III.C-1. Input parameters for simulation of BY gasification with sorbent injection.

MASS FLOW RATES

Primary gas	0.00111 kg/sec
Primary solids (coal)	0.00823 kg/sec
Secondary gas	0.00525 kg/sec
Sorbent carrier gas	0.0013 kg/sec
Sorbent	0.0156 kg/sec

GAS PROPERTIES

	Primary	Secondary	Injection inlet
Temperature (K)	356	589	356
Pressure (KPa)	183.4	183.4	183.4
Swirl number	0.0	0.0	0.0

GAS COMPOSITION (mole fraction-dry basis)

Species	Primary	Secondary	Injection inlet
O2	0.00000	1.00000	0.00000
AR	1.00000	0.00000	1.00000

SECTION IV. TASK 4. APPLICATION OF INTEGRATED CODES

Objective

The objectives of this task are to evaluate the integrated comprehensive codes for pulverized coal and fixed-bed reactors and to apply the codes to selected cases of interest to METC.

Task Outline

This task will be accomplished in two subtasks, one for the entrained-bed lasting 57 months and one for the fixed-bed lasting 48 months. Each of these subtasks will consist of three components: 1) Simulation of demonstration cases on BYU computers; 2) Implementation on a work station at AFR; and 3) Simulations of demonstration cases on the workstation.

IV.A. SUBTASK 4.A. - APPLICATION OF GENERALIZED, PULVERIZED-COAL
COMPREHENSIVE CODE

Senior Investigators - B. Scott Brewster and L. Douglas Smoot
Brigham Young University
Provo, UT 84602
(801) 378-6240 and 4326

Research Assistant - Ziaul Huque

Objectives

The objectives of this subtask are to 1) demonstrate application of the code by simulating reactors of interest to METC and 2) implement the code at METC and conduct training.

Accomplishments

Work continued on collecting information for simulating two application cases: the Coal Tech cyclone combustor (a Clean Coal Technology project) and the Texaco gasifier with dry-coal feed. The inside dimensions of the Texaco gasifier are proprietary, and so a "Texaco-like" gasifier with similar geometry will be simulated at high pressure. A Solar Turbines combustor was also added to the list of application cases and will be simulated.

Plans

Initiate all application cases.

IV.B. SUBTASK 4.B. - APPLICATION OF FIXED-BED CODE

Senior Investigators - Predrag T. Radulovic and L. Douglas Smoot
Brigham Young University
Provo, Utah 84602
(801) 378-3097 and (801)378-4326

Research Assistant - M. Usman Ghani

Objectives

The objective of this subtask is to apply the advanced fixed-bed code developed in task 3.b. to simulate fixed-bed gasifiers of interest to METC.

Accomplishments

Fixed-Bed Data Collection

During the past quarter, work continued on collecting fixed-bed design and test data from organizations and individuals involved in fixed- or moving-bed gasification or combustion research or in research on non-reacting fixed- or moving beds. No new data sets were obtained. Work also continued on collecting fixed-bed experimental data from the open literature.

Application of Fixed-Bed Code

No new cases were simulated.

Plans

During the next quarter, work will continue on collecting fixed-bed design and test data. Efforts will continue to identify additional test cases for simulation, and the code will be applied to the cases of interest to METC.

REFERENCES

- Agarwal, P.K., Fuel, 65, 803 (1986).
- Agarwal, P.K., Genetti, W.E., and Lee Y.Y., Fuel, 63, 1157 (1984)
- Borgwardt, R. H., "Surface area of calcium oxide and kinetics of calcium sulfide formation," Env. Prog., 3, 129 (1984).
- Borgwardt, R. H. and Roache, N. F., "Reaction of H₂S and sulfur with limestone particles," Ind. Eng. Chem. Process Des. Develop., 23, 742 (1984).
- Costa, M., Costen, P. and Lockwood, F. C., Data package for the validation of a mathematical model of the Imperial College large-scale pulverised-fuel furnace, Report no. FS/90/08, Imperial College of Science, Technology and Medicine, London, (1990).
- Dryden, I.G.C., and Sparham, G.A., "Carbonization of Coals Under Gas Pressure", B.C.U.R.A. Monthly Bull., 27, 1 (1963).
- Harding, N. S., "Effects of secondary swirl and other burner parameters on nitrogen pollution formation in a pulverized coal combustor," Ph.D. dissertation, Brigham Young University, Provo, UT, (1980).
- Hobbs, M. L., Radulovic, P.T., and Smoot, L.D., "Prediction of Effluent Compositions for Fixed-Bed Coal Gasifiers," Fuel, accepted for publication, 1992.
- Hobbs, M.L., Radulovic, P.T., and Smoot, L.D., "Modeling Fixed-Bed Coal Gasifiers," AIChE J., accepted for publication, 1992.
- Karner, M.A., Research Project on Pyrolysis of Large Coal Particles, unpublished work from Institut Für Verfahrenstechnik, (October, 1991).
- Ko, G.H., Sanchez, D.M., Peters, W.A., and Howard, J.B., "Correlations for Effects of Coal Type and Pressure on Tar Yields from Rapid Devolatilization," Twenty-Second Symposium (International) on Combustion, pp. 115-124, The Combustion Institute, (1988).
- Lee, C.H., Scaroni, A.W., and Jenkins, R.G., "Effect of Pressure on the Devolatilization and Swelling Behaviour of a Softening Coal During Rapid Heating," Fuel, (1991).
- Silcox, G. D., "Analysis of the SO₂-lime reaction system: Mathematical modeling and experimental studies emphasis on stoker applications," Ph.D. dissertation, The University of Utah, (1985).
- Solomon, P. R., Serio, M. A., Hamblen, D. G., Smoot, L. D. and Brewster, B. S., Measurement and modeling of advanced coal conversion processes, 3rd Annual Report, DOE-METC Contract No. DE-AC21-86MC23075, Advanced Fuel Research, Hartford, CT, (1989).
- Solomon, P. R., Serio, M. A., Hamblen, D. G., Smoot, L. D. and Brewster, B. S., eds., Measurement and modeling of advanced coal conversion processes, Quarterly and annual technical reports, eds., work performed for the U.S. Department of Energy under contract no. DE-AC21-86MC23075, (1986-1991).

- Solomon, P. R., Serio, M. A., Hamblen, D. G., Smoot, L. D. and Brewster, B. S., Measurement and modeling of advanced coal conversion processes, 5th Annual Report, DOE-METC Contract No. DE-AC21-86MC23075, Advanced Fuel Research, Hartford, CT, (1991).
- Solomon, P.R., Hamblen, D.G., Carangelo, R.M., Serio, M.A., and Deshpande, G.V., "A General Model of Coal Devolatilization", Energy and Fuel, 2, 405, (1988).
- Stubington, J.F. and Sumaryono, Fuel, 63, 1013 (1984).
- Suuberg, E.M., "Rapid Pyrolysis and Hydropyrolysis of Coal", Sc.D. Thesis, Dept. of Chemical Engineering, Mass. Inst. of Tech., Cambridge, MA (1977).
- Thimsen, D.P., and Maurer, R.E., "Coal Devolatilization in a Moving Bed Gasifier" Research Project 2225-14 Final Report (October, 1990).
- Tyler, R.J., Fuel, 59, 218 (1980).
- Wells, W.F., Kramer, S.K., and Smoot, L.D., Twentieth Symposium (International) on Combustion, p. 1539, The Combustion Institute, (1984).
- White, W.E., Bartholomew, C.H., Hecker, W.C., and Smith, D.M., Absorption Science and Technology, Vol.7, No.4, 180, (1990).

APPENDIX A

"CALCULATION OF CARRIER GAS FLOW RATE FOR SIDEWALL SORBENT INJECTION"

APPENDIX A

Annular slit width

$$d_j = 0.00104 \text{ m}$$

$$n = 3$$

$$D = 0.2 \text{ m}$$

$$t$$

$$A_j$$

$$A_\infty$$

Diameter of sorbent injection port

Number of sorbent injection ports

Diameter of the reactor

Width of annular slit

Total area of injection ports

Total annular injection area

$$A_j = A_\infty$$

$$n \times \frac{\pi d_j^2}{4} = \pi D t$$

$$t = 0.00041 \text{ m}$$

Sorbent carrier gas flow rate

The sorbent carrier gas flow rate is calculated using the definition of jet-to-free-stream momentum ratio, J , given by equation II.H-2 in the 3rd Annual Report. For a jet diameter of 0.00104m, a J value of 75 ensures the jet penetration to the center of the reactor.

$$\text{Jet-to-free-stream momentum ratio, } J = \frac{\rho_j u_j^2}{\rho_\infty u_\infty^2} = 75 \quad (\text{A.1})$$

where, ρ_j = density of the injection gas = 1.7 kg/m³
 u_j = velocity of the injection gas
 ρ_∞ = density of the main flow = 0.353 kg/m³
 u_∞ = velocity of the main flow

Velocity of the main flow is obtained as

$$u_\infty = \frac{m_\infty}{\rho_\infty A_\infty} = \frac{0.00636 \text{ kg/s}}{(0.353 \text{ kg/m}^3) (0.03142 \text{ m}^2)} = 0.573 \text{ m/sec}$$

where, m_{∞} = Total main flow rate
 A_{∞} = Cross-sectional area of the reactor

plugging the values in equation A.1 the jet velocity is obtained as

$$75 = \frac{(1.7) (u_j^2)}{(0.353) (0.573)^2}$$

$$u_j = 2.987 \text{ m/sec}$$

Therefore the mass flow rate of sorbent carrier gas (argon) is obtained as

$$\begin{aligned} m_{AR} &= (A_j) (\rho_j) (u_j) \\ &= (0.000255 \text{ m}^2) (1.7 \text{ kg/m}^3) (2.987 \text{ m/sec}) \end{aligned}$$

$$m_{AR} = 0.0013 \text{ kg/sec.}$$

APPENDIX B

"THE VARIATIONS IN CHAR COMBUSTION REACTIVITY WITH PYROLYSIS CONDITIONS AND COAL TYPE"

THE PREDICTION OF COAL CHAR REACTIVITY UNDER COMBUSTION CONDITIONS

Sylvie Charpenay, Michael A. Serio and Peter R. Solomon
Advanced Fuel Research, Inc.
87 Church Street, East Hartford, CT 06108

The main objective of the current work was to develop a char reactivity submodel that could be used in a comprehensive code for entrained coal combustors and gasifiers. The requirement of a char reactivity model is to predict the reactivity of chars from a wide range of coals, over a wide range of temperatures, and for various degrees of burnoff. In order to predict intrinsic reactivity, correlations of reactivity with char hydrogen content, coal oxygen content and coal mineral content were used. A random pore model (high rank coals) and a volumetric model (low rank coals) were included to predict variations of intrinsic reactivity with burnoff. The correlations combined with those models gave good predictions of reactivity (within a factor of 2 to 4) and reactivity variations with burnoff (within 20%) for the range of chars studied.

In the pore diffusion regime, the model uses the Thiele modulus to calculate the reaction rate as a function of the intrinsic rate (obtained using the correlations) and char properties such as porosity, tortuosity and mean pore radius. Predictions of reactivity required an estimate of the tortuosity and the mean pore radius. The tortuosity was kept constant at a value of 2. Using a value of 6 Å (corresponding to the size of micropores) for the mean pore radius led to good predictions of the onset of diffusion limitations for low heating rate, fluid chars. For high heating rate chars, pore size distribution measurements showed that values of approximately 100 Å were more appropriate. The corresponding predictions using this value gave a fairly good fit of the literature data investigated. This analysis shows that it may be possible to extend a low temperature reactivity model to high temperatures.

THE PREDICTION OF COAL CHAR REACTIVITY UNDER COMBUSTION CONDITIONS

Sylvie Charpenay
Michael A. Serio*
Peter R. Solomon

Advanced Fuel Research, Inc.
87 Church Street
East Hartford, CT 06108

Subject Matter:

- (1) Coal and Organic Solids Combustion
- (2) Heterogeneous Combustion
- (8) Kinetics

Submitted to Presentation at the Twenty-Fourth International
Symposium on Combustion

Length of Paper:	Text = 1	3354
	Equations =	included in word count
	Nomenclature = 27	X 7 = 189
	Figures & Tables = 7 X 200 =	1,400
	TOTAL	4,943

* To whom correspondence should be addressed
(tel. 203-528-9806; fax 203-528-0648)

THE PREDICTION OF COAL CHAR REACTIVITY UNDER COMBUSTION CONDITIONS

Sylvie Charpenay, Michael A. Serio and Peter R. Solomon
Advanced Fuel Research, Inc.
87 Church Street, East Hartford, CT 06108

The main objective of the current work was to develop a char reactivity submodel that could be used in a comprehensive code for entrained coal combustors and gasifiers. The requirement of a char reactivity model is to predict the reactivity of chars from a wide range of coals, over a wide range of temperatures, and for various degrees of burnoff. In order to predict intrinsic reactivity, correlations of reactivity with char hydrogen content, coal oxygen content and coal mineral content were used. A random pore model (high rank coals) and a volumetric model (low rank coals) were included to predict variations of intrinsic reactivity with burnoff. The correlations combined with those models gave good predictions of reactivity (within a factor of 2 to 4) and reactivity variations with burnoff (within 20%) for the range of chars studied.

In the pore diffusion regime, the model uses the Thiele modulus to calculate the reaction rate as a function of the intrinsic rate (obtained using the correlations) and char properties such as porosity, tortuosity and mean pore radius. Predictions of reactivity required an estimate of the tortuosity and the mean pore radius. The tortuosity was kept constant at a value of 2. Using a value of 6 Å (corresponding to the size of micropores) for the mean pore radius led to good predictions of the onset of diffusion limitations for low heating rate, fluid chars. For high heating rate chars, pore size distribution measurements showed that values of approximately 100 Å were more appropriate. The corresponding predictions using this value gave a fairly good fit of the literature data investigated. This analysis shows that it may be possible to extend a low temperature reactivity model to high temperatures.

INTRODUCTION

The objective of a char reactivity model is to predict the reactivity of various coals and chars over a wide range of temperatures and at various degrees of burnoff. The current work focused on the development of a char reactivity submodel that could be used in a comprehensive code for entrained coal combustors and gasifiers.

Intrinsic reaction rates (regime I) can be measured at low temperature in a TGA apparatus. However pore diffusion effects (regime II) are important under many practical combustion and gasification conditions and need to be accounted for. The external diffusion limitation (regime III) can also be important, but was not included in the present model since several studies¹⁻³ indicate that it is not usually the rate limiting step under pulverized coal combustion conditions.

A model which can be used in regimes I or II must include a description of intrinsic char reactivity and how it varies with temperature, coal type, and char formation conditions. In order to predict intrinsic reactivity, the measurement and evaluation of the number of active sites on chars surfaces have been the object of extensive work^{4,5}. However, the current methods (TPD, TGA, transient kinetics, etc...) do not allow a direct measurement of the number of active sites. In the absence of such a method, our approach has been to develop correlations of reactivity with known parameters of coals and chars. Correlations of reactivity with the concentrations of minerals and oxygen in the starting coal and hydrogen in the char as well as pyrolysis heating rate have been found. These correlations reflect the fact that the amount of active sites is dependent on the following: 1) The degree of pyrolysis, which can be characterized by the hydrogen content of the char; 2) The degree of disorder of the char, which varies with the pyrolysis heating rate (valid for fluid coals only); 3) The coal rank, which can be characterized by the oxygen content; 4) The amount of catalytic impurities present in the starting coal, which

can be characterized by the dispersed mineral content (calcium in particular).

For high rank coals, reactivity variations with burnoff (in the kinetic regime) have been associated with changes in internal surface area⁶. Consequently, reactivity predictions will require a description of the char morphology. For this purpose, the Random Pore Model derived for the kinetic regime by Bhatia and Perlmutter⁷ and Gavalas⁸ was used, which calculates surface area changes during reaction. For low rank coals, the intrinsic reactivity is primarily dependent on catalytic effects. In that case, the important parameter is the number of catalytic sites distributed through the volume of the particle, and reactivity can then be represented by a volumetric model⁹.

In order to predict reactivity at high temperatures (regime II), one has to account for pore diffusion limitations. The model follows the approach described by Smith¹⁰, using the Thiele model¹¹ to derive the value of the global reaction rate as a function of the intrinsic reaction rate and char properties such as char porosity, tortuosity and mean pore radius.

The transition region from kinetic to pore diffusion control was not explicitly investigated, since numerical solutions are usually necessary to calculate the reactive gas concentration profile in the particle, and would be too detailed to be included in a comprehensive combustion code. However, this region represents a relatively narrow range in temperature and most of the available data can be considered to fall in either the kinetic or pure pore diffusion regime.

EXPERIMENTAL

T_{crit} Measurements - Correlations have been developed using an extensive database of "Critical Temperature" (T_{crit}) measurements obtained in our laboratory. T_{crit} is an index of char reactivity

which is related to the concentration of accessible active sites¹². The determination of T_{crit} relies on a TGA technique in which the weight loss is measured while the sample is heated at a constant heating rate in the presence of the reactive gas. The temperature (T_{crit}) at which the rate of weight loss reaches a value of 0.065 g/g-min (on an original char mass basis) is recorded and gives an indication of the reactivity of the char. The value of the reaction rate used for measurement of T_{crit} was chosen to be high enough to be easily measurable but low enough so that it is still in the kinetic regime, based on a Thiele modulus calculation¹¹. In practice, depending on the nature of the char, T_{crit} has been observed to occur either in the kinetic regime or at the beginning of the pore diffusion regime. The chars used for the development of correlations were produced in several different reactors and under widely different pyrolysis conditions¹³.

Isothermal Reactivity Measurements - The reaction rates at low temperatures were measured isothermally using a Dupont 951 TGA. All experiments were performed using an oxygen partial pressure of 17.2 kPa, a flow rate of 240 cc/min, and a coal sample size of 10 mg. The chars were prepared by heating at 30°C/min in helium up to the pyrolysis temperature, followed by immediate cooling to the gasification temperature.

MODEL DEVELOPMENT FOR KINETIC REGIME

Reactivity Model - Following the usual approach (e.g. see Smith¹⁰) the reaction rate in the kinetic regime is given by:

$$r_p = S k_i v M_p C_s \quad \text{with} \quad k_i = A \exp\left(-\frac{E}{RT}\right), \quad C_s = \frac{P}{RT} \quad (1)$$

where S = internal surface area of remaining char, k_i = intrinsic rate coefficient, v = stoichiometric factor, M_p = molecular weight of carbon, and C_s = oxidant concentration. A reaction order of 1 was assumed, although studies¹⁴ showed the reaction order to vary between 0 and 1 with the type of char and coal. This approximation, however, typically leads to an error in rate of less than a factor of 1.5 if the "true" reaction order is, for example, 0.5. Future developments of the model will include a fractional reaction order.

For high rank coals, the value of S is given by the Random Pore Model^{7,8}: $S = S_o (1-X) (1-\Psi \ln(1-X))^{0.5}$, where S_o = internal surface area of original char, Ψ = structural parameter, X = char burnoff. For low rank coals, the volumetric model is used and S becomes: $S = S_o (1-X)$.

The pre-exponential factor, A , of the coefficient k_i , includes the number of active sites. The variations of A with coal type and pyrolysis conditions can be estimated with correlations based on T_{crit} measurements, and can be written for high rank coals (HRC) as: $A = A_{HRC} f(H_{char}) g(O_{coal})$, where $f(H_{char})$ and $g(O_{coal})$ are char hydrogen and coal oxygen correlation functions, respectively, and A_{HRC} is the baseline frequency factor for high rank coals. The corresponding factor for low rank coals (LRC) is given by: $A = A_{LRC} f(H_{char}) g(O_{coal}) h(Ca_d)$, where $h(Ca_d)$ is a correlation function based on the dispersed calcium concentration.

Development of Correlations - Correlations derived from T_{crit} measurements can be used to calculate intrinsic reactivity. The functions f , g and h are expected to be increasing functions of the char hydrogen content, coal oxygen content and coal mineral content, respectively. Since T_{crit} decreases with reactivity, $1/T_{crit}$ was found to be a more appropriate quantity to use to develop

correlations. Linear correlations of $1/T_{crit}$ versus the above parameters were obtained, as discussed below.

H_{char} Correlation - Good correlations of $1/T_{crit}$ vs the char hydrogen concentration (H_{char}) were obtained for all coals. It can be seen from Fig. 1 that all the correlations have similar slopes, which implies that the degree of pyrolysis of the char has a similar influence for all coals. The data also seem to show a plateau for values higher than 3.5% H_{char} . The initial loss of hydrogen during pyrolysis is primarily aliphatic, which does not have the annealing effect of the loss of aromatic hydrogen during the latter stages of pyrolysis^{12,13}.

O_{coal} Correlation - For similar values of H_{char} , the value of $1/T_{crit}$ for different coals is expected to correlate with oxygen and/or mineral content of the coals. As shown in Fig. 2, $1/T_{crit}$ (using chars produced at 30°C/min up to 900°C) and the coal oxygen content show a reasonable correlation. The data points with low oxygen content which fall well below the line correspond to very fluid coals. In that case, the low heating rate used to produce the chars also has an impact on its reactivity.

Mineral Correlation - Since mineral concentration is important only for low rank coals, a correlation was obtained using coals of oxygen content higher than 13%. Dispersed calcium was found to be the main mineral responsible for reactivity enhancement¹³ and was used to develop the correlation shown in Fig. 3. For low rank coals, the influence of calcium needs to be separated from the effect of coal rank. Since demineralized low rank coals show a reactivity similar to that of medium rank coals (of oxygen content approximately 13%), the effect of oxygen content is minor compared to that of calcium. In order to account for this in the model, the value of O_{coal} is kept constant and set equal to 13% for coals of oxygen content higher than 13%.

Other second order effects include the combined effect of fluidity and pyrolysis heating rate on char reactivity. This can be important for fluid coals, and leads to separate $1/T_{crit}$ vs H_{char} correlations for different heating rates. At this point, few measurements have been done on low heating rate, fluid chars, and this will be the object of a future study.

Individual correlation plots (shown in Figs. 1-3) give an uncertainty in T_{crit} within $\pm 20^\circ\text{C}$, which is approximately equivalent to a factor of 2 in rate. With the H_{char} , O_{coal} , and Ca_g correlations used simultaneously, T_{crit} can be predicted within $\pm 40^\circ\text{C}$. It should be noted that the experimental uncertainty of the measurement of T_{crit} is $\pm 10^\circ\text{C}$.

To overcome potential shortcomings of using several correlations simultaneously, it would be reasonable to use the H_{char} correlation alone, associated with one T_{crit} measurement as input. However for the cases presented below, the three correlations were used.

Intrinsic Rate Predictions - At T_{crit} , the rate of weight loss is 0.001/sec. By substituting the values of $1/T_{crit}$ and r_p into equation (1), the functions f , g and h can be calculated. It is implicitly assumed that $1-X$ is constant and equal to 0.85 (which is the experimental value usually observed) at the point where T_{crit} is measured. S_0 is also kept constant and was taken as a first approximation to be $300 \text{ m}^2/\text{g}$. The value of the activation energy, E , was evaluated from TGA isothermal data, and was found to vary between 28 and 34 kcal/mol for the chars studied. As a first approximation, a value of 30 kcal/mol was used in the model.

For high rank coals ($O_{coal} < 13\%$), equation (1) becomes:

$$r_p = 8.22 \exp \frac{-15000}{T} \exp (1.4 H_{char}) \exp (0.263 O_{coal}) S \quad (2)$$

For low rank coals ($O_{\text{coal}} > 13\%$), the equivalent of equation (1) is

$$r_p = 6.86 \times 10^2 \exp \frac{-15000}{T} \exp (1.4 H_{\text{char}}) \exp (1.54 C_{a_d}) S \quad (3)$$

The reaction rates correspond to the case where the oxygen partial pressure is 17.2 kPa.

Predictions of reaction rates using equations (2) and (3) have been compared with data obtained in our laboratory (Zap lignite chars) as well as literature data from Wells et al.¹⁵ (FMC, Occidental and Toscoai chars). The parameters used are indicated in Table I. The parameters for the literature chars were directly taken from reference 15. The reactivities of the Pittsburgh No.8 chars were not predicted (since good correlations of low heating rate, fluid coals have not been developed yet), but were fit to the data. Figures 4 and 5 show the good agreement obtained between the predictions and the low temperature TGA data for the chars studied.

Predictions of reaction rates as a function of burnoff are presented in Fig. 6 for Pittsburgh No. 8 (high rank coal) 600°C char and Zap lignite (low rank coal) 900°C char using the random pore model and volumetric model respectively. The predictions were done using a single adjustable parameter (without using the correlations) in order to demonstrate the adequacy of the burnoff models chosen. The good fit (within 20%) obtained in the full range of burnoff supports the use of these models.

MODEL DEVELOPMENT FOR PORE DIFFUSION REGIME

Calculation of Reaction Rate - In the diffusion regime, the observed reaction rate can be expressed as a function of the intrinsic reaction rate:

$$r_p = \eta S_o k_l v M_p C_s \quad (4)$$

where η = effectiveness factor. According to Mehta and Aris,¹⁶ the effectiveness factor can be determined using the relations between η and $\eta\phi^2$, where ϕ is the Thiele modulus¹¹. In the case of high Thiele modulus, $\eta\phi^2$ tends to $1/\eta$, i.e. η tends to $1/\phi$.

The Thiele modulus is given by:

$$\phi = \frac{d}{6} \left(\frac{\sigma S_o k_l}{D_e v M_p / M_o} \right)^{0.5} \quad (5)$$

with d = particle diameter, σ = apparent particle density, D_e = effective diffusivity, M_o = molecular weight of oxidant. From the simple pore-structure model of Wheeler¹⁷, D_e can be calculated:

$$D_e = 9.7 \times 10^2 r_{pore} \left(\frac{T}{M_o} \right)^{0.5} \frac{\epsilon_o}{\tau_o} \quad (6)$$

where r_{pore} = mean pore radius, ϵ_o = porosity, τ_o = tortuosity.

The global reaction rate used in the model can then be written:

$$r_p = \frac{6}{d} \left(D_e v \frac{M_p}{M_o} \frac{S_o k_l}{\sigma} \right)^{0.5} C_s \quad (7)$$

The reaction rate depends on the intrinsic rate and char properties such as the tortuosity, porosity and the mean pore radius. The tortuosity parameter has been introduced to account for the connectivity of pores. Its value has generally been taken between 1.5 and 10, usually equal to 2. The porosity and the mean pore radius can be measured. However their determination may be difficult in the case of a non-uniform pore size distribution.

Comparison of Predictions with Data - Using the physical and chemical parameters indicated in Table I and kinetic parameters derived earlier, predictions in the pore diffusion regime for the Pittsburgh No. 8 and Zap lignite chars produced at 30°C/min are shown in Fig. 4. For low rank coals we used a "deactivation" function to account for the fact that catalysts have less impact on reactivity at high temperatures^{12,13}. Following this deactivation function, at high temperatures the reactivity of a low rank coal is made to be equal to that of a coal of 13% oxygen. Although the number of data points in the diffusion regime is limited, the transition between kinetic and diffusion control is fairly well represented by the theory for the two Pittsburgh No. 8 chars using a mean pore radius of 6 Å, which corresponds to the size of micropores. Concerning the Zap char, no internal diffusion limitations are present (since there is no change in activation energy), but a leveling off of the rate is observed. This behavior is due to external mass transfer resistances in the TGA. Under our conditions, the maximum measurable rate in the TGA is approximately 1 g/g-min. However, under "true" pulverized coal combustion conditions, external diffusion limitations are not encountered until temperatures typically higher than 1500 K. Since no pore diffusion limitations are observed for the Zap char in the range of TGA measurements, the choice of parameters such as the mean pore radius and tortuosity for that coal cannot be confirmed.

The model predictions for the high heating rate chars used in Ref. 15 are presented in Fig. 5 (dashed lines) together with correlations based on drop tube reactor data¹⁵ (symbols). As for the chars produced in our laboratory, a value of $r_{\text{pore}} = 6 \text{ Å}$ was used. In agreement with the Thiele model, the apparent activation energy in the diffusion regime is well described by half the intrinsic activation energy. However, predictions of the reaction rates give much lower values than the correlations based on the data. For the low rank Occidental coal char, this may be due to uncertainties on the "deactivation" process. However, the choice of parameters, and particularly the value of the mean pore radius r_{pore} , also needs to be evaluated in more detail. This parameter represents a measure of the size of the pores which feed the reactant gas into the char. Those

pores can be significantly larger than the micropores (of pore radius 6 Å), especially if the char is fairly macroporous. Pore size distribution measurements on chars similar to Occidental and FMC (produced at high heating rate) have been performed by White¹⁸ and show a mean pore size of 100 Å for a Zap char, and a bimodal distribution at 6 Å and 170 Å for a Pittsburgh No. 8 char. Using values of r_{pore} of 100 Å for the Occidental and 170 Å for the FMC and Toscoal, predictions are shown in Fig. 5 with solid lines, and fit the data more accurately, especially considering that the temperature in the literature data may have been underestimated by as much as 200°C¹⁹. This underlines the importance of precisely characterizing the structure of the char in order to determine r_{pore} . Also, the fact that different values of r_{pore} are needed in order to fit low heating rate and high heating rate char data implies a basic difference in structure between the two types of chars. This is not surprising since low heating rate chars have been found to be effectively less porous⁶ probably because some reorganization of the structure is possible during the long period in which the char is fluid. However, pore size distribution measurements on low heating rate chars are needed in order to resolve that question. Also, direct diffusivity measurements²⁰ would eliminate any ambiguity of Wheeler's model in the estimation of the mean pore size and tortuosity parameters. This may give more reliable values of the effective diffusivity in order to calculate the reactivity in regime II.

CONCLUSIONS

It was shown that correlations developed at low temperatures using the char hydrogen content, coal oxygen content and coal mineral content have given good predictions of intrinsic reactivity for different coals and chars. Using these correlations combined with a random pore model for high rank coals and a volumetric model for low rank coals, reactivity and reactivity variations with burnoff can be predicted.

The reactivity in the pore diffusion regime was calculated using the intrinsic reactivity correlations and the Thiele model. This approach necessitates the knowledge of char properties such as porosity, tortuosity and mean pore radius. Using a value of 6 Å for the mean pore radius leads to fairly good predictions for 30°C/min Pittsburgh No. 8 chars, while being inconclusive for Zap chars. In the case of high heating rate chars, pore size distribution measurements showed that values of approximately 100 Å are more appropriate, and predictions using this value give a good fit of the literature data investigated. Direct diffusivity measurements could also be performed and would eliminate any uncertainty in the estimation of the mean pore size and tortuosity parameters. In conclusion, this analysis shows that it may be possible to extend low temperature reactivity models to high temperatures.

ACKNOWLEDGEMENTS

The authors are grateful for the support of the Morgantown Energy Technology Center of the United States Department of Energy under contract DE-AC21-86MC23075, for support of the study of char reactivity. The authors wish to acknowledge the contributions of Hsisheng Teng and Marie DiTaranto of Advanced Fuel Research, Inc. to the experimental work, and helpful discussions with Prof. Eric Suuberg of Brown University.

REFERENCES

1. Field, M.A., Combust. Flame, 14, 237, (1970).
2. Smith, I.W, Combust. Flame, 17, 421, (1971).
3. Mitchell, R.E. and J.W. McLean, Nineteenth Symposium (Int) on Combustion, The Combustion Institute, 1982, pp. 1113-1122.
4. Radovic, L.R., Walker, P.L., Jenkins, R.G., Fuel, 62, 849, (1983).
5. Suuberg, E.M., Calo, J.M., and Wojtowitz, M., ACS Div. of Fuel Chem. Preprints, 31, (3),

186, (1986).

6. Su, J.L., Perlmutter, D.D., AIChE J., 31, 6, 973 (1985).
7. Bhatia, S.K., Perlmutter, D.D., AIChE J., 26, 379 (1980).
8. Gavalas, G.R., AIChE J., 26, 577, (1980).
9. Ishida, M., Wen, C.Y., Chem. Eng. Sci., 26, 1031 (1971).
10. Smith, I.W., Nineteenth Symposium (Int) on Combustion, The Combustion Institute, 1982, pp. 1045-1065.
11. Thiele, E.W., Ind. Eng. Chem., 31, 916 (1939).
12. Solomon, P.R., Serio, M.A., Heninger, S.G., ACS Div. of Fuel Chem. Preprints, 31, (3), 200, (1986).
13. Serio, M.A., Solomon, P.R., Charpenay, S. and Suuberg, E.M. to be submitted to Fuel (1992).
14. Suuberg, E.M., Wojtowicz, M., Calo, J.M., Twenty-Second Symposium (International) on Combustion, p. 79, the Combustion Institute (1988).
15. Wells, W.F., Kramer, S.K., Smoot L.D., Twentieth Symposium (International) on Combustion, p. 1539, The Combustion Institute, 1984.
16. Mehta, B.N., and Aris, R., Chem. Eng. Sci., 26, 1699 (1971).
17. Wheeler, A., Adv. Catal., 3, 249 (1951).
18. White, W.E., M.S. Thesis, Brigham Young University (1990).
19. Smoot, L.D., Personal communication (1992).
20. Smith, I.W., Harris, D.J., Valix, M.G., Trimm, D.L., in Fundamental Issues in Control of Carbon Gasification Reactivity, J. Lahaye and P. Ehrburger (Eds), Kluwer Academic Publishers, p. 49, 1991.

NOMENCLATURE

A = pre-exponential factor, m/s

C_s = reactant concentration, mol/m³

Ca_d = % (daf) dispersed calcium in coal

d = particle diameter, m

d_o = initial particle diameter, m

D_e = diffusivity, m²/s

E = activation energy, kcal/mol

H_{char} = % (daf) hydrogen in char

k_i = reaction rate coefficient, m/s

M_o = molecular mass of reactive gas, g/mol

M_p = molecular mass of carbon, g/mol

O_{coal} = % (daf) oxygen in coal

P = partial pressure of reactive gas, atm

R = gas constant, m³ atm/(g mol K)

r_{pore} = mean pore radius, m

r_p = reaction rate, 1/s

S = internal surface area of remaining char per mass of initial char, m²/g

S_o = internal surface area of initial char, m²/g

T = particle temperature, K

X = burnoff

GREEK SYMBOLS

η = effectiveness factor

ϵ_o = initial porosity

τ_o = initial tortuosity

σ = apparent particle density, g/m³

Φ = Thiele modulus

ν = stoichiometric factor

Ψ = structural parameter

TABLE I
PARAMETERS USED IN REACTIVITY CALCULATIONS

Char	PIT 900°C & 600°C	ZAP 900°C	FMC	OCC	TOS
Parent Coal	Pittsburgh	Zap	Pittsburgh	Wyodak	Utah
Rate (°C/s)	0.5	0.5	10 ³	10 ⁴	10 ³
ϵ_o	0.1*	0.3*	0.13	0.55	0.11
τ_o	2*	2*	2*	2*	2*
d (μm)	70	70	90	63	55
r_{pore} (Å)	6*	6*	170*	100*	170*
S_o (m ² /g)	300*	300*	300*	300*	300*
σ_o (g/cm ³)	1.3*	1.3*	1.52	0.86	1.43
O _{coal} (%)	---	21	9	21	11.8
H _{char} (%)	---	0.74	2	2.1	3.18
M (%)	---	1	0	1.1*	0

NOTE: 900°C and 600°C Pittsburgh No. 8 chars and 900°C Zap lignite char have been produced in our laboratory. FMC, Occidental and Toscoal are chars from Reference 15.

* estimated from measured values for similar chars or coals.

LIST OF FIGURE CAPTIONS

- Figure 1. Correlation of $1/T_{crit}$ with the percent (daf) hydrogen content of the char (H_{char}) for Zap, Rosebud, Illinois No. 6 and Pittsburgh No. 8 coals. The chars were produced in different reactors and under different pyrolysis conditions.¹³
- Figure 2. Correlation of $1/T_{crit}$ with the percent (daf) coal oxygen content (O_{coal}) for the Argonne coals and a set of Exxon coals. The chars were produced at 30°C/min up to 900°C, and have similar hydrogen contents.
- Figure 3. Correlation of $1/T_{crit}$ with the percent (daf) of dispersed calcium (Ca_d) for a set of Exxon coals. The chars were produced at 30°C/min up to 900°C.
- Figure 4. Comparison of predicted reactivity vs. TGA data for 600°C and 900°C Pittsburgh No. 8 chars and 900°C Zap lignite chars. The chars were produced at 30°C/min up to the indicated temperature.
- Figure 5. Comparison of predicted reactivity (lines) vs. correlations (symbols) derived from experimental data from Wells et al.¹⁵ The low temperature data was measured using TGA. High temperature data was obtained in a drop tube reactor. The symbols do not correspond to actual data points, but serve to identify the different correlations. The dashed lines correspond to predictions using a mean pore radius of 6 Å. The solid lines correspond to predictions using a mean pore radius of 100 Å for Occidental and 170 Å for FMC and Toscoal.
- Figure 6. Comparison of TGA data (symbols) and model predictions (lines) for the reaction of a) 600°C char from Pittsburgh No. 8 at 500°C using the random pore model with $\Psi=50$; b) 900°C char from Zap lignite combusted at 380°C using the volumetric model. The small fluctuations in the predictions correspond to slight variations in measured temperature.

Figure 1. Correlation of $1/T_{crit}$ with the percent (daf) hydrogen content of the char (H_{char}) for Zap, Rosebud, Illinois No. 6 and Pittsburgh No. 8 coals. The chars were produced in different reactors and under different pyrolysis conditions.¹³

Figure 2. Correlation of $1/T_{crit}$ with the percent (daf) coal oxygen content (O_{coal}) for the Argonne coals and a set of Exxon coals. The chars were produced at $30^{\circ}\text{C}/\text{min}$ up to 900°C , and have similar hydrogen contents.

Figure 3. Correlation of $1/T_{crit}$ with the percent (daf) of dispersed calcium (Ca_d) for a set of Exxon coals. The chars were produced at $30^\circ C/min$ up to $900^\circ C$.

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PATENT STATUS

This technical report is being transmitted in advance of DOE patent clearance and no further dissemination or publication shall be made of the report without prior approval of the DOE patent Counsel.

Figure 4. Comparison of predicted reactivity vs. TGA data for 600°C and 900°C Pittsburgh No. 8 chars and 900°C Zap lignite chars. The chars were produced at 30°C/min up to the indicated temperature.

Figure 5. Comparison of predicted reactivity (lines) vs. correlations (symbols) derived from experimental data from Wells et al.¹⁵ The low temperature data was measured using TGA. High temperature data was obtained in a drop tube reactor. The symbols do not correspond to actual data points, but serve to identify the different correlations. The dashed lines correspond to predictions using a mean pore radius of 6 Å. The solid lines correspond to predictions using a mean pore radius of 100 Å for Occidental and 170 Å for FMC and Toscoal.

Figure 6. Comparison of TGA data (symbols) and model predictions (lines) for the reaction of a) 600°C char from Pittsburgh No. 8 at 500°C using the random pore model with $\Psi=50$; b) 900°C char from Zap lignite combusted at 380°C using the volumetric model. The small fluctuations in the predictions correspond to slight variations in measured temperature.

END

**DATE
FILMED**

1 / 27 / 93