EGG-AFO--10531

DE93 007222

FESDIF - FINITE ELEMENT SCALAR DIFFRACTION THEORY CODE

H. G. Kraus

September 1992

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, ID 83415**

**Prepared for the
U.S. Department of Energy
Under DOE Idaho Field Office
Contract DE-AC07-76ID01570**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

This document describes the theory and use of a powerful scalar diffraction theory based computer code for calculation of intensity fields due to diffraction of optical waves by two-dimensional planar apertures and lenses. This code is called FESDIF (Finite Element Scalar DIffraction). It is based upon both Fraunhofer and Kirchhoff scalar diffraction theories. Simplified routines for circular apertures are included. However, the real power of the code comes from its basis in finite element methods. These methods allow the diffracting aperture to be virtually any geometric shape, including the various secondary aperture obstructions present in telescope systems. Aperture functions, with virtually any phase and amplitude variations, are allowed in the aperture openings. Step change aperture functions are accommodated. The incident waves are considered to be monochromatic. Plane waves, spherical waves, or Gaussian laser beams may be incident upon the apertures. Both area and line integral transformations were developed for the finite element based diffraction transformations. There is some loss of aperture function generality in the line integral transformations which are typically many times more computationally efficient than the area integral transformations when applicable to a particular problem.

Key Terms: Fraunhofer diffraction, Fresnel diffraction, very-near field diffraction, finite element methods, plane waves, spherical waves, Gaussian laser beams, secondary mirrors, secondary mirror spider supports, screens, synthetic aperture arrays, multiple mirror and segmented mirror telescopes, phase plates, apodization, off-axis beams and apertures

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	i
1.0 INTRODUCTION	1
2.0 SIMPLIFIED KIRCHHOFF SCALAR DIFFRACTION THEORY FORMULATIONS	4
2.1 Kirchhoff Aperture Plane Formulation for Spherical Waves Diffracted by a Circular Aperture	7
2.2 Kirchhoff Wavefront Formulation for Focused Spherical Waves Diffracted by a Circular Aperture	12
2.3 Kirchhoff Aperture Plane Formulation for a Gaussian Laser Beam Diffracted by a Circular Aperture	19
2.4 Kirchhoff Wavefront Formulation for a Focused Gaussian Laser Beam Diffracted by a Circular Aperture	24
3.0 FINITE ELEMENT FOURIER AREA AND LINE INTEGRAL TRANSFORM FORMULATIONS FOR GENERALIZATION OF FRAUNHOFER DIFFRACTION THEORY	35
3.1 Finite Element Fourier Area Integral Transform	36
3.2 Finite Element Abbe Line Integral Transform	41
3.3 Discussion of Finite Element and Fraunhofer Diffraction Integral Transforms	45

TABLE OF CONTENTS (CONT.)

	<u>Page</u>
4.0 FINITE ELEMENT KIRCHHOFF AREA AND LINE INTEGRAL TRANSFORM FORMULATIONS FOR GENERALIZATION OF FRESNEL AND VERY-NEAR-FIELD DIFFRACTION THEORY	49
4.1 Finite Element Kirchhoff Area Integral Transform	
Formulation: General	51
4.1.1 Spherical waves	56
4.1.2 Gaussian laser beams	56
4.2 Finite Element Asvestas Line Integral Transform	
Formulation: General	58
4.2.1 Spherical waves	62
4.2.2 Gaussian laser beams	63
4.3 Computational Considerations	65
4.3.1 Choice of transform method	65
4.3.2 Numerical integration convergence and accuracy	66
4.3.3 Computer programming for increased efficiency	67
5.0 CALCULATION OF THE DIFFRACTION FIELDS	69
5.1 Numerical Integration of Diffraction Integrals	70
5.2 Normalization of the Calculated Diffraction Fields	73
6.0 SUMMARY	74
7.0 ACKNOWLEDGEMENTS	75
8.0 REFERENCES	76

TABLE OF CONTENTS (CONT.)

	<u>Page</u>
APPENDIX A – FESDIF CODE USER’S MANUAL	A-1
I. GENERAL DESCRIPTION	A-2
II. INPUT DATA BLOCKS	A-11
APPENDIX B – FESDIF EXAMPLE PROBLEMS	B-1
(See Appendix B Table of Contents for listing of 29 different example problems illustrating a broad range of the capabilities of FESDIF)	
APPENDIX C – FESDIF CODE SOURCE AND RUN FILES	C-1

LIST OF FIGURES

	<u>Page</u>
2.1.1. Geometry used for Kirchhoff aperture plane formulation for a spherical wave diffracted by circular a aperture.	8
2.1.2. Illustration of obliquity factor angles θ'_I and θ'_{II} for Kirchhoff spherical wave aperture plane formulation.	9
2.2.1. Geometry for "ideal" lens used in Kirchhoff wavefront diffraction formulation for focused spherical waves.	13
2.2.2. Geometry used for Kirchhoff wavefront formulation for a spherical wave diffracted and focused by a circular aperture "ideal" lens.	15
2.3.1. Geometry used for Kirchhoff aperture plane formulation for a paraxial Gaussian laser beam diffracted by a circular aperture.	20
2.4.1. Geometry for "ideal" lens used in Kirchhoff wavefront diffraction formulation for focused Gaussian laser beam.	25
2.4.2. Geometry used for Kirchhoff wavefront formulation for a Gaussian laser beam diffracted and focused by a circular aperture "ideal" lens.	27

LIST OF FIGURES (CONT.)

	<u>Page</u>
2.4.3. Geometry used for derivation of characteristic pathlength Fresnel number equation for a spherically focused Gaussian laser beam.	33
3.1.1. Nine-node bi-quadratic isoparametric finite element geometry: (a) global coordinates, (b) local coordinates.	37
4.1.1. Geometry for general finite element Kirchhoff area diffraction integral transformation formulation.	52
4.1.2. Geometry for spherical wave and Gaussian beam finite element Kirchhoff area and line diffraction integral transform formulations.	55

1.0 INTRODUCTION

The design of optical instruments involves the careful layout of the optical components and the analysis of what happens to the light entering the instrument. This document deals with the latter aspect of the instrument design. Proper optical design of the light progressing along the optical path of the instrument is critical to the performance of the instrument. As instrument performance becomes more and more demanding, this aspect of the instrument design often determines the overall instrument performance and limitations. This light may be reflected, scattered, or diffracted in the instrument. However, it is true that diffraction can actually be interpreted as light which has been reflected and scattered by the optical components of an instrument, e.g., aperture stops, shutter blades, lenses, mirrors, etc. Therefore, when talking about diffraction in this document it will also be interpreted to mean reflected and scattered light. The diffraction field, in this context, is then composed of the optical interference of the reflected and scattered light with the light which has passed an aperture or optical component undeviated.

The FESDIF computer code was written based upon scalar diffraction theory and computational methods development reported in a series of journal articles by Kraus.¹⁻⁷ These routines have been assembled into a moderately sized dynamically dimensioned computer code (< 10,000 lines). The code has been logically structured into three sets of capabilities or routines. These capabilities are all for the diffraction of light by two-dimensional apertures. Two of the sets include general aperture function capabilities. The next three sections of this document present the theoretical diffraction formulations upon which these capabilities are based.

The first set of capabilities or routines, the theoretical formulations for which are described in Section 2.0, is for calculating very-near, Fresnel, and Fraunhofer or far-field diffraction fields for circular apertures. Incident waves may be spherical or Gaussian laser beam. The circular apertures may contain a lens or lens system which is described in terms of "ideal lens" parameters. Focal shift in the diffraction field (see Stamnes⁸ for a discussion of focal shift) can be analyzed for both waves types. Transverse or axial diffraction fields can be calculated for all these configurations. Characteristic pathlength Fresnel number equations are presented, (similar to but theoretically more accurate than those presented by Hecht⁹), which allow prediction of the character of the diffraction field a priori in the Fresnel or Fraunhofer regions in the absence of focal shift effects. No mesh generators are used for these simplified diffraction routines as the meshes used for integration of the diffraction integrals are generated internally in FESDIF.

The second set of routines, the theoretical formulations for which are described in Section 3.0, is for calculating Fraunhofer or far-field diffraction patterns for apertures with arbitrary geometries and arbitrary aperture functions. Focusing systems may be analyzed in which case the diffraction field calculated is that which will occur at the image plane or focal plane of the instrument. Finite element meshes are used to define the aperture geometry as well as the aperture function.

Section 4.0 presents the theoretical formulations developed for calculation of very-near, Fresnel, and Fraunhofer or far-field diffraction fields for apertures with arbitrary geometries and arbitrary aperture functions upon which the third set of routines is based. As with the second set of routines, finite element meshes are used to define the aperture geometry as well as the aperture function.

Section 5.0 presents the Gaussian quadrature method of numerical integration used for all of the diffraction integrals described in Sections 2.0, 3.0, and 4.0. This section also explains how the diffraction intensity fields are normalized by FESDIF in preparing the results for plotting.

Appendix A gives the names and a general description of all the routines contained in each of the above three sets of routines. As part of this description the necessary Input Data Blocks needed to utilize the routines within each of the three sets of routines is given. This is followed by the actual Input Data Block description section. Appendix B contains a description of the requirements for using FESDIF such as the FORTRAN compiler used, the plotting package needed, computer memory requirements, etc. Following this, Appendix B gives 29 examples which illustrate many of the numerous capabilities of FESDIF. Finally, Appendix C gives a source file listing of this code and a compilation/run file for using FESDIF.

2.0 SIMPLIFIED KIRCHHOFF SCALAR DIFFRACTION THEORY FORMULATIONS

Perhaps the most commonly occurring aperture in optical instruments and systems is the circular aperture. Most often lenses and filters are of this configuration. In addition, most laser beams used in optical applications have a circular cross-section. For this reason several diffraction formulations developed by Kraus¹⁻⁵ are presented here as used in FESDIF for diffraction by circular apertures/circular lenses. These formulations were used for the first of the three sets of routines contained in FESDIF. This section is broken down into four subsections: (1) uniform intensity spherical waves diffracted by circular apertures, (2) uniform intensity spherical waves diffracted and focused by circular aperture ideal lenses, (3) paraxial Gaussian laser beams diffracted by circular apertures, and (4) paraxial Gaussian laser beams diffracted and focused by circular aperture ideal lenses. The formulations for calculating full diffraction fields transverse to the optic-axis as well as the diffraction along the optic-axis are included for each of these four configurations. Incident plane waves can, of course, be simulated by using large incident spherical wave radii.

All the diffraction formulations of this section are in fact solutions to the scalar wave equation also known as the Helmholtz equation¹⁰

$$\nabla^2 u + k^2 u = 0 \tag{2.0.1}$$

where u is the wave function and k is the propagation number equal to $2\pi/\lambda = \omega/c$, where λ is the optical radiation wavelength, ω is the frequency, and c is the speed of light. Note that the time dependence of the wave equation as derived from Maxwell's equations has been removed in Eq. (2.0.1), ie the time average field is being considered.^{11,12} Through use of Green's theorem, Kirchhoff formulated an integral

solution to this scalar wave equation for diffraction of the incident wave, u , by an aperture opening.¹² The resulting equation is^{10,12}

$$E(P) = -\frac{1}{4\pi} \iint_{\Sigma} \left[u \frac{\partial v}{\partial \hat{n}} - v \frac{\partial u}{\partial \hat{n}} \right] d\Sigma \quad (2.0.2)$$

where u is the incident wave function, v is the Green's function solution to the integral equation, Σ is the surface of integration covering the aperture opening (which may or may not lie in the plane of the aperture), $E(P)$ is the amplitude of the diffraction field at a point P with coordinates (r', ϕ') in the observation plane at axial location z' beyond the diffracting aperture, and $\hat{n}$ is a unit vector inward normal (i.e., on the Green's function source side) to the surface of integration. Kirchhoff assumed the following boundary conditions

$$u = u_i, \quad \frac{\partial u}{\partial \hat{n}} = \frac{\partial u_i}{\partial \hat{n}} \quad \text{On the surface } \Sigma \text{ covering the aperture opening} \quad (2.0.3)$$

$$u = 0, \quad \frac{\partial u}{\partial \hat{n}} = 0 \quad \text{Elsewhere} \quad (2.0.4)$$

where the "i" subscript designates the incident wave in the absence of the aperture. These boundary conditions are only approximations because optical radiation is in reality an electromagnetic wave for which, strictly speaking, boundary conditions on the electric and magnetic fields are required. This in turn requires solving the electromagnetic wave equation derived from Maxwell's equations. However, scalar diffraction theory is very accurate for numerous applications where diffraction calculations are needed and this is what the FESDIF code is based upon. Scalar diffraction theory usually begins to break down as you calculate the diffraction field within one to three diameters beyond a circular aperture and when the aperture diameters begin to approach the wavelength of the optical radiation used.^{8,13}

Equation (2.0.2) is integrated numerically in FESDIF using Gaussian quadrature (see Section 5.1) for all of the diffraction formulations below. However, in order to obtain accurate results, the circular apertures must be sectioned into radial-angular blocks when full diffraction fields are being calculated and into radial blocks when axial diffraction fields are being calculated. This is because the wave function phase variations of the diffraction integrals are too rapid to obtain accurate integration over the entire aperture at once. Transformations are performed upon each of these radial-angular or radial blocks in order to place them into the $(-1,1)$ orthogonality interval of the Gaussian quadrature. Gaussian quadrature is then performed on each of these blocks. The number of such blocks required for accurate integration of this diffraction integral varies from problem to problem and is a user controllable parameter in the FESDIF Input Data Blocks (see Appendix A).

2.1 Kirchhoff Aperture Plane Formulation for Spherical Waves Diffracted by a Circular Aperture

The Kirchhoff aperture plane formulation for an on-axis uniform intensity spherical wave diffracted by a circular aperture is presented here. This formulation is based upon related developments in two journal articles by Kraus.^{1,3}

The geometry used for this formulation is given in Fig. 2.1.1. Let the source spherical wave be represented as

$$u = E_o \exp\{ikR\}/R \quad (2.1.1)$$

where E_o is the emission amplitude of this point source, k is the propagation number equal to $2\pi/\lambda$, λ is the wavelength of the optical radiation, and R is the distance from the point source to some point in the plane of the aperture opening. Let the spherical wave Green's function source located at the observation point P be represented as

$$v = \exp\{ikR'\}/R' \quad (2.1.2)$$

where R' is the distance from the Green's function source point at the observation point P to some point in the plane of the aperture opening. The appropriate form of Eq. (2.0.2) for this problem is

$$E_p(r', \phi') = -\frac{E_o}{4\pi} \iint_{\Sigma} [ik(\cos\theta'_I + \cos\theta'_{II}) - (\cos\theta'_I/R' + \cos\theta'_{II}/R)] \times \frac{\exp\{ik(R + R')\}}{R R'} d\Sigma \quad (2.1.3)$$

where Σ is the aperture opening in the plane of the aperture opening and

$$\cos\theta'_I = -\cos(\hat{n}, \vec{R}') \quad (2.1.4)$$

$$\cos\theta'_{II} = \cos(\hat{n}, \vec{R}) \quad (2.1.5)$$

where the inner product angles θ'_I and θ'_{II} are illustrated in Fig. 2.1.2.

Figure 2.1.1. Geometry used for Kirchhoff aperture plane formulation for a spherical wave diffracted by a circular aperture

Figure 2.1.2. Illustration of obliquity factor angles θ'_I and θ'_{II} for Kirchhoff spherical wave aperture plane formulation.

It can be deduced from Eq. (2.1.3) that the Kirchhoff obliquity factor corresponding to this case of an incident spherical wave is

$$O(\theta') = -(1/4\pi)[ik(\cos\theta'_I + \cos\theta'_{II}) - (\cos\theta'_I/R' + \cos\theta'_{II}/R)] \quad (2.1.6)$$

This Kirchhoff obliquity factor may be broken into two parts and re-written as

$$O(\theta') = \frac{1}{2} [O_{R-S,I}(\theta') + O_{R-S,II}(\theta')] \quad (2.1.7)$$

where

$$O_{R-S,I}(\theta') = -(1/2\pi)[(ik - 1/R')\cos\theta'_I] \quad (2.1.8)$$

$$O_{R-S,II}(\theta') = -(1/2\pi)[(ik - 1/R)\cos\theta'_{II}] \quad (2.1.9)$$

By replacing Eq. (2.1.7) by Eq. (2.1.8) or Eq. (2.1.9) this Kirchhoff diffraction integral formulation becomes either the Rayleigh-Sommerfeld I or the Rayleigh-Sommerfeld II diffraction formulation, respectively.¹³ However, in FESDIF only the Kirchhoff diffraction formulation has been included. This is because comparison of theoretical calculations to experimental results shows that Kirchhoff theory is generally the most accurate of the three formulations. The known exceptions to this generalization are discussed by Stamnes.⁸

Equation (2.1.3) may be more specifically defined for this problem as

$$E_P(r', \phi') = C \int_0^{2\pi} \int_0^a [ik(\cos\theta'_I + \cos\theta'_{II}) - (\cos\theta'_I/R' + \cos\theta'_{II}/R)] \exp\{ik(R + R')\} \times \frac{r dr d\phi}{R R'} \quad (2.1.10)$$

where, with the aid of the geometry of Fig. 2.1.1,

$$C = -(E_o/4\pi)$$

$$R = (r^2 + z^2)^{1/2}$$

$$R' = [r_p'^2 + r^2 - 2rr_p'\cos(\phi - \phi_p') + z'^2]^{1/2}$$

$$\cos\theta' = (-\bar{a}^2 + \bar{b}^2 + \bar{c}^2)/2\bar{b}\bar{c}$$

$$\bar{a} = [r_p'^2 + r_q'^2 - 2r_p'r_q'\cos(\phi_q' - \phi_p')]^{1/2}$$

$$\bar{b} = [r_Q'^2 + r^2 - 2rr_Q' \cos(\phi - \phi_Q') + z'^2]^{1/2}$$

$$\bar{c} = R'$$

$$\phi_Q' = \phi$$

$$r_Q' = r(z + z')/z$$

When calculating the diffraction field along the optic-axis beyond the aperture plane, Eq. (2.1.10) reduces by integration in the ϕ direction to

$$E_p(r', \phi') = C \int_0^a [ik(\cos\theta_I' + \cos\theta_{II}') - (\cos\theta_I'/R' + \cos\theta_{II}'/R)] \times \frac{\exp\{ik(R + R')\}}{R R'} r dr \quad (2.1.11)$$

where

$$C = -(E_o/2)$$

The equation for determining the pathlength Fresnel number for this problem has been derived by Kraus.¹ Using Fig. 2.1.1., the optical pathlength difference between S to O to O' and S to the aperture edge to O' is set equal to the number of multiples of $\lambda/2$, m or the Fresnel number Fr_p , and solved for Fr_p to arrive at

$$Fr_p = (2/\lambda)[(z^2 + a^2)^{1/2} + (z'^2 + a^2)^{1/2} - (z + z')] \quad (2.1.12)$$

Equation (2.1.12) can also be solved for z' to determine the axial location where a particular Fresnel number will occur. Imaginary or negative roots to the z' equation indicate that the particular Fresnel number used does not occur in the diffraction field anywhere.

2.2 Kirchhoff Wavefront Formulation for Focused Spherical Waves Diffracted by a Circular Aperture

The unique Kirchhoff wavefront diffraction formulation for diffraction of an on-axis uniform intensity spherical wave by a circular aperture lens by Kraus⁴ is presented here as implemented in FESDIF. The lens for this diffraction formulation will be considered to be "ideal" in that it is without optical aberrations. It will also be assumed that this lens can be defined in terms of effective thin lens parameters. This approach is much more general than might first be apparent as long as you can identify the effective focal length and aperture (exit pupil) of the actual diffracting lens system for use in this formulation. For more exact formulations and solutions to this problem the reader is referred to the text by Stamnes⁸ on the subject of waves in focal regions.

The geometry of this "ideal" lens is shown in Fig. 2.2.1. The incident spherical wave may either be diverging or converging. The basic assumption used here is that in passage through the lens there is an effective truncating circular aperture diameter and the wave will emerge from the ideal lens being spherical in form. Therefore, the optical pathlengths for all points across the incident wavefront to the corresponding points on the emerging wavefront are equal. It is not important to this formulation what this pathlength is as it passes through the true optical system, ie the true thickness of the lens is not important as long as the equivalent thin lens theory parameters can be defined. The true thickness of the lens system is simply subtracted out of the distances of the geometry in terms of an optical pathlength constant as done below. For a thin lens then, the image distance, s_i , may be determined from the Gaussian thin lens relationship⁹

Figure 2.2.1. Geometry for "ideal" lens used in Kirchhoff wavefront diffraction formulation for focused spherical waves.

$$s_i = (1/f - 1/s_o)^{-1} \quad (2.2.1)$$

where s_i is the image distance from the lens, f is the lens focal length, and s_o is the object distance from the lens.

In order to provide generalization to this formulation, the object to lens distance will be defined as the distance from the on-axis point source spherical wave to the axial location where the linear projection of the wavefront matches the effective aperture radius, a , of the lens system as illustrated in Fig. 2.2.1. It is considered positive when to the left of the effective aperture plane (diverging incident waves) and negative when to the right of the effective aperture plane (converging incident waves). Similarly, the image location, s_i , is the distance from the on-axis image location to the axial location where the linear projection of the converging spherical wavefront matches the effective aperture radius of the system as depicted in Fig. 2.2.1. The interest here is in real image diffraction patterns only because virtual images are of no practical concern in the design of optical instruments.

The geometry used for this formulation is given in Fig. 2.2.2. This formulation is based on the Kirchhoff¹⁰ diffraction integral formulation by Kraus.⁴ Let the source spherical wave be represented as

$$u = E_o \exp\{iks_o\}/s_o \quad (2.2.2)$$

and the spherical wave Green's function source located at the observation point P be represented as

$$v = \exp\{ikR'\}/R' \quad (2.2.3)$$

where k is the propagation number equal to $2\pi/\lambda$, λ is the optical radiation wavelength, s_o is the image distance determined from Eq. (2.2.1), and R' is the distance from the observation point P to a point on the emerging spherical wavefront, surface Σ . The appropriate form of the Kirchhoff diffraction integral of Eq. (2.0.2) is

Figure 2.2.2. Geometry used for Kirchhoff wavefront formulation for a spherical wave diffracted and focused by a circular aperture "ideal" lens.

$$E_p(r', \phi') = -\frac{E_o}{4\pi} \iint_{\Sigma} [ik(1+\cos\theta') - (1/s_o + \cos\theta'/R')] \times \frac{\exp\{ik(s_o + R')\}}{s_o R'} d\Sigma \quad (2.2.4)$$

where Σ in this case represents the surface of the emerging wavefront, and from Figs.

2.2.1 and 2.2.2

$$R' = [r^2 + r_p'^2 - 2rr_p' \cos(\phi - \phi_p') + (z' - h)^2]^{1/2}$$

$$h = s_i(1 - \cos\theta)$$

$$r = s_i \sin\theta$$

$$\cos\theta' = [-\bar{a}^2 + \bar{b}^2 + \bar{c}^2]/(2\bar{b}\bar{c})$$

$$\bar{a} = [r_p'^2 + r_q'^2 - 2r_p'r_q' \cos(\phi_p' - \phi_q')]^{1/2}$$

$$\bar{b} = R'$$

$$\bar{c} = [r^2 + r_q'^2 - 2rr_q' \cos(\phi - \phi_q') + (z' - h)^2]^{1/2}$$

$$r_q' = n_f(z' - s_i) \tan\theta$$

$$n_f = -1, z' < s_i$$

$$n_f = 1, z' > s_i$$

$$\phi_q' = \phi, \quad z' < s_i$$

$$\phi_q' = \phi + \pi, \quad z' > s_i$$

It is easily deduced that the Kirchhoff obliquity factor corresponding to this case of an incident spherical wave is

$$O(\theta') = -(1/4\pi)[ik(1+\cos\theta') - (1/s_o + \cos\theta'/R')] \quad (2.2.5)$$

In this case, θ' is equal to θ'_I of Fig. 2.1.2 and $\theta'_{II} = 0$ because the direction of propagation and the normal to the surface of integration coincide. Note that the emerging wavefront is the surface of integration and is of constant phase. Therefore the pathlength and thus the phase and intensity terms for propagation from the source to the wave emerging from the lens form a constant which can be removed from the

integral. Doing this, defining dA as in Fig. 2.2.2, and defining the integration limits, Eq. (2.2.4) may be expressed as

$$E_p(r', \phi') = C \int_{\theta=0}^{\theta_1} \int_{\phi=0}^{2\pi} [ik(1+\cos\theta') - (1/s_o + \cos\theta'/R')] \times \frac{\exp\{ikR'\}}{R'} \sin\theta \, d\theta \, d\phi \quad (2.2.6)$$

where

$$C = -(E_o s_i^2 / 4\pi s_o) \exp\{iks_o\}$$

$$\theta_1 = \tan^{-1}[a'/(z' - h_{a'})]$$

$$h_{a'} = s_i(1 - a'/a)$$

When calculating the diffraction field along the optic-axis beyond the diffracting aperture, Eq. (2.2.6) reduces to

$$E_p(r', \phi') = C \int_{\theta=0}^{\theta_1} [ik(1+\cos\theta') - (1/s_o + \cos\theta'/R')] \times \frac{\exp\{ikR'\}}{R'} \sin\theta \, d\theta \quad (2.2.7)$$

where

$$C = -(E_o s_i^2 / 2s_o) \exp\{iks_o\}$$

The characteristic pathlength Fresnel number equation for this formulation as developed by Kraus^{4,5} will be presented next. This equation allows calculating the axial location where a particular Fresnel number occurs in the diffraction field or alternately allows calculating the Fresnel number for a given z' observation plane location. It is therefore of great utility in the analysis of the diffraction fields.

Consider some point O' with axial coordinate z' , either inside or outside s_i , on the optic axis beyond the effective aperture plane as shown in Fig. 2.2.2. The optical pathlength difference of interest is between the aperture plane and z' on axis, O to O' ,

and the distance from the edge of the emerging converging wavefront and z' on axis, E to O' . This difference must be equal to the number of multiples, m , of $\lambda/2$ in accordance with the classical definition of the pathlength Fresnel number as

$$z' - [(z' - h_{a'})^2 + a'^2]^{1/2} = n_f m \lambda / 2 \quad (2.2.8)$$

Using the geometry of Fig. 2.2.2,

$$h_{a'} = s_i (1 - a'/a) \quad (2.2.9)$$

$$a'/a = s_i / (a^2 + s_i^2)^{1/2} \quad (2.2.10)$$

From Eq. (2.2.8), the pathlength Fresnel number, $Fr_p = m$, may be solved for as

$$Fr_p = (2n_f/\lambda) \{z' - [(z' - h_{a'})^2 + a'^2]^{1/2}\} \quad (2.2.11)$$

Note that in Eq. (2.2.5) the value of Fr_p may be either for $z' < s_i$ or for $z' > s_i$ depending on the value of n_f [defined in Eq. (2.2.4)]. These are referred to as the inside and outside pathlength Fresnel numbers, Fr_p^- and Fr_p^+ , respectively. Using Eqs. (2.2.9) and (2.2.10), and evaluating $z' = s_i$, Eq. (2.2.11) reduces, through some algebraic simplification, to $Fr_p = 0$, as expected at focus. The location, z' , at which a particular value of Fr_p occurs can be found by solving Eq. (2.2.8) for z' to obtain

$$z' = \frac{h_{a'}^2 + a'^2 - (m\lambda/2)^2}{(2h_{a'} - n_f m \lambda)}, \quad m = Fr_p \quad (2.2.12)$$

Negative values of z' from this equation indicate that the particular Fresnel number being used does not occur in the diffraction field being investigated. Additional analysis and examples of the use of these pathlength Fresnel number equations have been presented by Kraus.^{4,5}

2.3 Kirchhoff Aperture Plane Formulation for a Gaussian Laser Beam

Diffacted by a Circular Aperture

The Kirchhoff aperture plane formulation for an on-axis incident paraxial Gaussian laser beam diffracted by a circular aperture, which can be deduced jointly from two journal articles by Kraus,^{2,3} is presented in this section.

The geometry used for this formulation is given in Fig. 2.3.1. The scalar amplitude-phase relationship for a paraxial Gaussian laser beam is¹⁴

$$u(r,z) = \frac{E_o \omega_o}{\omega(z)} \exp \left\{ -i \left\{ k \left[z + \frac{r^2}{2R(z)} \right] - \tan^{-1} \frac{z}{z_o} \right\} - \frac{r^2}{\omega^2(z)} \right\} \quad (2.3.1)$$

where E_o is the amplitude of the beam and ω_o is the beam waist at the source point S, k is the propagation number equal to $2\pi/\lambda$, and λ is the wavelength of the optical radiation. Also in Eq. (2.3.1)

$$\omega(z) = \omega_o [1 + (z/z_o)^2]^{1/2} \quad (2.3.2)$$

$$R(z) = z [1 + (z_o/z)^2] \quad (2.3.3)$$

$$z_o = \pi \omega_o^2 / \lambda \quad (2.3.4)$$

Let the spherical wave Green's function source located at the observation point P be represented as

$$v = \exp\{ikR'\}/R' \quad (2.3.5)$$

where R' is the distance from the Green's function source point, ie the observation point P, to some point in the plane of the aperture opening. The appropriate form of Eq. (2.0.2) for this problem is

Figure 2.3.1. Geometry used for Kirchhoff aperture plane formulation for a paraxial Gaussian laser beam diffracted by a circular aperture.

$$\begin{aligned}
E_p(r', \phi') = & -\frac{E_o \omega_o}{4\pi} \iint_{\Sigma} \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' \right. \\
& + i \left[k \left[1 - \frac{r^2(1-(z_o/z)^2)}{2R^2(z)} \right] - \frac{z_o}{zR(z)} \right] \\
& \left. - \left[\frac{1}{R(z)} - \frac{2r^2}{\omega^2(z)R(z)} \right] \right\} \\
& \exp \left\{ -i \left\{ k \left[z + \frac{r^2}{2R(z)} \right] - \tan^{-1} \left[\frac{z}{z_o} \right] \right\} - \frac{r^2}{\omega^2(z)} \right\} \exp\{ikR'\} \\
& \times \frac{d\Sigma}{\omega(z) R'} \quad (2.3.6)
\end{aligned}$$

where Σ is the opening in the aperture plane. The Kirchhoff obliquity factor corresponding to this case of an incident paraxial Gaussian laser beam may be deduced from Eq. (2.3.6) as

$$\begin{aligned}
O(r, z, \theta') = & -(1/4\pi) \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' \right. \\
& + i \left[k \left[1 - \frac{r^2(1-(z_o/z)^2)}{2R^2(z)} \right] - \frac{z_o}{zR(z)} \right] \\
& \left. - \left[\frac{1}{R(z)} - \frac{2r^2}{\omega^2(z)R(z)} \right] \right\} \quad (2.3.7)
\end{aligned}$$

where $\cos \theta'$ is defined in Eq. (2.3.8) below. More specifically for this problem, through evaluation at the aperture plane location $z = z_w$ and use of the geometry of Fig. 2.3.1, Eq. (2.3.6) may be written as

$$\begin{aligned}
E_p(r', \phi') = & C \int_0^{2\pi} \int_0^a \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' \right. \\
& + i \left[k \left[1 - \frac{r^2(1-(z_o/z_w)^2)}{2R_{z_w}^2} \right] - \frac{z_o}{z_w R_{z_w}} \right] \\
& \left. - \left[\frac{1}{R_{z_w}} - \frac{2r^2}{\omega_{z_w}^2 R_{z_w}} \right] \right\} \\
& \exp \left\{ ik \left[R' - \frac{r^2}{2R_{z_w}} \right] - \frac{r^2}{\omega_{z_w}^2} \right\} \exp\{ikR'\} \\
& \times \frac{r dr d\phi}{R'} \quad (2.3.8)
\end{aligned}$$

where

$$C = - \left[\frac{E_o \omega_o}{4 \pi \omega_{z_w}} \right] \exp \left\{ -i \left[k z_w - \tan^{-1} \frac{z_w}{z_o} \right] \right\}$$

$$\omega_{z_w} = \omega(z) \Big|_{z=z_w}$$

$$R_{z_w} = R(z) \Big|_{z=z_w}$$

$$R' = [r^2 + r_p'^2 - 2rr_p' \cos(\phi - \phi_p') + z'^2]^{1/2}$$

$$\cos \theta' = [-\bar{a}^2 + \bar{b}^2 + \bar{c}^2] / (2\bar{b}\bar{c})$$

$$\bar{a} = [r_p'^2 + r_q'^2 - 2r_p'r_q' \cos(\phi_p' - \phi_q')]^{1/2}$$

$$\bar{b} = [r^2 + r_q'^2 - 2rr_q' \cos(\phi - \phi_q') + z'^2]^{1/2}$$

$$\bar{c} = R'$$

$$r_q' = r (1 + z' / R_{z_w})$$

$$\phi_q' = \phi$$

$$z_w = z$$

When calculating the diffraction field along the optic-axis beyond the aperture plane, Eq. (2.3.8) reduces by integration in the ϕ direction to

$$E_p(r', \phi') = C_1 \int_0^a \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' + i \left[k \left[1 - \frac{r^2 (1 - (z_o/z_w)^2)}{2R_{z_w}^2} \right] - \frac{z_o}{z R_{z_w}} \right] - \left[\frac{1}{R_{z_w}} - \frac{2r^2}{\omega_{z_w}^2 R_{z_w}} \right] \right\} \exp \left\{ ik \left[R' - \frac{r^2}{2R_{z_w}} \right] - \frac{r^2}{\omega_{z_w}^2} \right\} \exp \{ ik R' \} \frac{r dr}{R'} \quad (2.3.9)$$

where

$$C_1 = - \left[\frac{E_o \omega_o}{2\omega_{zw}} \right] \exp \left\{ -i \left[kz_w - \tan^{-1} \frac{z_w}{z_o} \right] \right\}$$

The general pathlength Fresnel number equation as developed by Kraus^{2,3} is presented here. Using this relationship, the Fresnel number at a specified z' or the z' needed to achieve a given Fresnel number can be determined. Using Fig. 2.3.1 and the phase portion of the beam Eq. (2.3.1), the optical pathlength difference between S to O' and S to the edge of the aperture to O', can be expressed in terms of m multiples of $\lambda/2$, to give

$$\begin{aligned} & \left\{ k \left[z + z' + \frac{r^2}{2R(z)} + \frac{\lambda m}{2} \right] - \tan^{-1} \frac{z}{z_o} \right\} \bigg|_{\substack{r=0 \\ z=z_w}} \\ &= \left\{ k \left[z + R' + \frac{r^2}{2R(z)} \right] - \tan^{-1} \frac{z}{z_o} \right\} \bigg|_{\substack{r=a \\ z=z_w \\ r'_p=0}} \end{aligned} \quad (2.3.10)$$

This follows the usual definition of Fr_p as being as measure of the multiples of $\lambda/2$ or half-period zones that are due to this path-length difference. Solving for z' from this equation produces

$$z' = \frac{a^2 - \left[\frac{m\lambda}{2} - C_R \right]^2}{(m\lambda - 2C_R)}, \quad m = Fr_p \quad (2.3.11)$$

where

$$C_R = \frac{a^2}{2R_{zw}}$$

2.4 Kirchhoff Wavefront Formulation for a Focused Gaussian Laser Beam Diffracted by a Circular Aperture

This section presents the Kirchhoff wavefront diffraction formulation for diffraction of a on-axis paraxial Gaussian laser beam by a circular aperture "ideal" lens as developed by Kraus.⁵ "Ideal" in this formulation means that the lens is without optical aberrations. It will be assumed that this lens can be defined in terms of effective thin lens parameters. This approach is much more general than might first be apparent as long as you can identify the effective focal length and aperture (exit pupil) of the actual diffracting lens system for use in this formulation. The geometry of this ideal lens system is shown in Fig. 2.4.1. The incident Gaussian beam wavefront may either be diverging or converging. However, the point to note is that in passage through the lens there is an effective truncating aperture diameter and the wave will emerge from the ideal lens being spherical in form. Therefore, the optical pathlengths from all points across the incident wavefront to the corresponding points on the emerging wavefront are equal. It is also true that the optical pathlengths for all points across the beam waist to the corresponding points on the emerging spherically converging wavefront are also equal. This pathlength is therefore not important to this formulation as it passes through the true optical system; that is, the true thickness of the lens is not important as long as the equivalent thin lens theory parameters can be defined. The true optical thickness of the lens system, from O to O'' , can simply be subtracted out of the distances of the geometry in terms of an optical pathlength constant as necessary.

For a thin lens, then, the image distance, s_i , may be determined from the Gaussian thin lens formula

$$s_i = (1/f - 1/s_o)^{-1} \quad (2.4.1)$$

In order to provide generalization to this formulation, the effective source or

2-0087

Figure 2.4.1. Geometry for "ideal" lens used in Kirchhoff wavefront diffraction formulation for focused Gaussian laser beam.

object-to-lens distance, s_o , will be defined as the distance from the beam center of curvature, point C, to the axial location where the wavefront is truncated by the aperture of radius, a , of the lens system as illustrated in Fig. 2.4.1. It is considered positive when to the left of the effective aperture plane (diverging incident waves) and negative when to the right of the effective aperture plane (converging incident waves). The image location, s_i , is the distance from the on-axis image location to the axial location where the linear projection of the converging spherical wavefront matches the effective aperture radius, a , of the system as depicted in Fig. 2.4.1. The image location is considered positive or real when it is to the right of the effective aperture plane location. The interest here is in real image diffraction problems so that virtual images will not be considered.

The geometry of the diffraction formulation is given in Fig. 2.4.2. Consider a paraxial Gaussian beam aligned with the optic-axis and incident upon the lens system. The paraxial Gaussian beam equation of propagation is¹⁴

$$u(r,z) = \frac{E_o \omega_o}{\omega(z)} \exp \left\{ -i \left\{ k \left[z + \frac{r^2}{2R(z)} \right] - \tan^{-1} \frac{z}{z_o} \right\} - \frac{r^2}{\omega^2(z)} \right\} \quad (2.4.2)$$

where E_o is the amplitude of the beam at the source waist at point S, k is the propagation number equal to $2\pi/\lambda$, and λ is the wavelength of the optical radiation.

Also in Eq. (2.4.2)

$$\omega(z) = \omega_o [1 + (z/z_o)^2]^{1/2} \quad (2.4.3)$$

$$R(z) = z [1 + (z_o/z)^2] \quad (2.4.4)$$

$$z_o = \pi \omega_o^2 / \lambda \quad (2.4.5)$$

Let the spherical wave Green's function source located at the observation point P be represented as

$$v = \exp\{ikR'\}/R' \quad (2.4.6)$$

9-0663

Figure 2.4.2. Geometry used for Kirchhoff wavefront formulation for a Gaussian laser beam diffracted and focused by a circular aperture "ideal" lens.

where R' is the distance from the Green's function source point, ie the observation point P , to some point on the surface of the emerging wavefront. The appropriate form of Eq. (2.0.2) for the intensity at some point P in the observation plane, which may or may not coincide with the image plane at s_i , is

$$E_P(r', \phi') = -\frac{E_o \omega_o}{4\pi} \iint_{\Sigma} \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' + \left[\frac{ikr}{R(z)} - \frac{2r}{\omega^2(z)} \right] \sin \alpha \right. \\ \left. + \left[i \left[k \left[1 - \frac{r^2(1-(z_o/z)^2)}{2R^2(z)} \right] - \frac{z_o}{zR(z)} \right] - \left[\frac{1}{R(z)} - \frac{2r^2}{\omega^2(z)R(z)} \right] \right] \cos \alpha \right\} \\ \times \frac{\exp\{-ikL\} \exp\left\{-i \left\{ k \left[R' + z + \frac{r^2}{2R(z)} \right] - \tan^{-1} \left[\frac{z}{z_o} \right] \right\} - \frac{r^2}{\omega^2(z)} \right\}}{\omega(z) R'} d\Sigma \quad (2.4.7)$$

where $\alpha = \tan^{-1}[-1/(dr/dz)]$, dr/dz is defined below in Eqs. (2.4.17) and (2.4.18), and where Σ is the spherical wavefront surface emerging from the lens as shown in Fig. 2.4.2.

Other parameters in Eq. (2.4.7) are

$$R' = [r'^2 + r_p'^2 - 2r' r_p' \cos(\phi - \phi_p') + (z' - h)^2]^{1/2}$$

$$h = s_i(1 - \cos \theta)$$

$$\cos \theta' = [-\bar{a}^2 + \bar{b}^2 + \bar{c}^2]/(2\bar{b}\bar{c})$$

$$\bar{a} = [r_p'^2 + r_q'^2 - 2r_p' r_q' \cos(\phi_p' - \phi_q')]^{1/2}$$

$$\bar{b} = R'$$

$$\bar{c} = [r'^2 + r_q'^2 - 2r' r_q' \cos(\phi - \phi_q') + (z' - h)^2]^{1/2}$$

$$r_q' = n_f(z' - s_i) \tan \theta$$

$$n_f = -1, \quad z' < s_i$$

$$n_f = 1, \quad z' > s_i$$

$$\phi_q' = \phi \quad z' < s_i$$

$$\phi_q' = \phi + \pi, \quad z' > s_i$$

and L is some lens-independent constant optical pathlength from the incident wavefront to the emerging wavefront. The Kirchhoff wavefront obliquity factor for this formulation can be shown to be^{3,5}

$$\begin{aligned}
O(r, z, \theta') = & -(1/4\pi) \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' + \left[\frac{i k r}{R(z)} - \frac{2r}{\omega^2(z)} \right] \sin \alpha \right. \\
& + \left[i \left[k \left[1 - \frac{r^2(1-(z_o/z)^2)}{2R^2(z)} \right] - \frac{z_o}{zR(z)} \right] \right. \\
& \left. \left. - \left[\frac{1}{R(z)} - \frac{2r^2}{\omega^2(z)R(z)} \right] \right] \cos \alpha \right\} \quad (2.4.8)
\end{aligned}$$

Note that as the emerging wavefront approaches planarity, $\sin \alpha \rightarrow 0$ and $\cos \alpha \rightarrow 1$ so that Eq. (2.4.8) becomes identically equal to the aperture plane formulation Kirchhoff obliquity factor of Eq. (2.3.7) as would be expected. Since the emerging wavefront is the surface of integration and is of constant phase, the pathlength and intensity terms for propagation from the beam waist to the wave emerging from the lens are constants which can be removed from the integral. Doing this and defining $d\Sigma$ as in Fig. 2.4.2, Eq.(2.4.7) becomes

$$\begin{aligned}
E_p(r', \phi') = & C \int_{\theta=0}^{\theta_1} \int_{\phi''=0}^{2\pi} \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' + \left[\frac{i k r}{R(z)} - \frac{2r}{\omega^2(z)} \right] \sin \alpha \right. \\
& + \left[i \left[k \left[1 - \frac{r^2(1-(z_o/z)^2)}{2R^2(z)} \right] - \frac{z_o}{zR(z)} \right] - \left[\frac{1}{R(z)} - \frac{2r^2}{\omega^2(z)R(z)} \right] \right] \cos \alpha \Big\} \\
& \times \frac{\exp \left\{ i k R' + \frac{r^2(\theta)}{\omega^2[z(\theta)]} \right\}}{w[z(\theta)]R'} \sin \theta d\theta d\phi'' \quad (2.4.9)
\end{aligned}$$

where

$$C = -(E_o \omega_o s_i^2 / 4\pi) \exp\{-ikL\} \exp\left\{-i \left\{ k \left[z + \frac{r^2}{2R(z)} \right] - \tan^{-1} \frac{z}{z_o} \right\} \right\}$$

$$\theta_1 = \tan^{-1}[a'/(s_i - h_a)]$$

$$h_a = s_i(1 - a'/a)$$

Note that $r(\theta)$ and $z(\theta)$ in Eq. (2.4.9) are incident wave coordinate parameters of Fig. 2.4.1 that are intentionally expressed in terms of the emerging wave coordinate θ . The Gaussian amplitude distribution across the emerging wavefront must be identical in relative scale and truncation level to that of the incident wavefront. However, the curvature and radial extent of the emerging wavefront is not the same as that of the

incident wavefront. This makes direct use of the fact that the exponential term corresponding to the Gaussian amplitude profile [last term of Eq. (2.4.2)] is inappropriate.

The approach used here to describe the amplitude distribution of the emerging wavefront was to reference it to the known incident wavefront amplitude distribution through a coordinate transformation. This was accomplished through defining the relationships for $r(\theta)$ and $z(\theta)$ in Eq. (2.4.9). Let η be the distance along the arc $\overline{OE_1}$ of the incident wavefront as shown in Fig. 2.4.1. By multiplying this arc length by the proportionate distance along the arc $\overline{O''E_1''}$, that is η'' in Fig. 2.4.1, the position on the incident wavefront corresponding to the θ of the emerging wavefront can be determined. By observing that the emerging wavefront is exactly spherical, $\overline{O''E_1''}$ may be defined in terms of a circular arc and the η position may therefore be expressed as

$$\begin{aligned}\eta &= (\eta''/\overline{O''E_1''})\overline{OE_1} \\ \eta &= \sin^{-1}(r''/s_i)\overline{OE_1}/\sin^{-1}(a'/s_i)\end{aligned}\quad (2.4.10)$$

Using Eq. (2.4.10) and the geometry of Figs. 2.4.1 and 2.4.2, $r(\theta)$ may be fully defined as

$$r(\theta) = s_o \sin \alpha(\theta) = R_{z_w} \sin \alpha(\theta) \quad (2.4.11)$$

where

$$R_{z_w} = R(z) \Big|_{z=z_w} \quad (2.4.12)$$

$$\alpha(\theta) = \eta/R_{z_w} \quad (2.4.13)$$

$$r'' = s_i \sin \theta \quad (2.4.14)$$

Eq. (2.4.10) was next used in defining $z(\theta)$ of Eq. (2.4.9). From Fig. 2.4.2 it can be seen

that

$$z(\theta) = z_w - h$$

or since

$$h = R_{s_w} - r(\theta)/\tan\alpha(\theta)$$

use of Eq. (2.4.13) gives the result

$$z(\theta) = z_w - [R_{s_w} - r(\theta)/\tan\alpha(\eta/R_{s_w})] \quad (2.4.15)$$

Eqs. (2.4.11) to (2.4.14) are then used in Eq. (2.4.15) which is, in turn, used in Eq.

(2.4.3) to define $\omega(z)$. Finally, the arc length $\overline{OE_1}$ of the incident wavefront may be determined exactly by integrating the relationship developed by Kraus^{2,5} from z_w to z_a for the differential $ds(z)$ along the surface of the wavefront in the z -coordinate direction as

$$\overline{OE_1} = \int_{z_w}^{z_a} ds(z) dz = \int_{z_w}^{z_a} \left[1 + \left[\frac{dr(z)}{dz} \right]^2 \right]^{1/2} dz \quad (2.4.16)$$

where

$$\frac{dr(z)}{dz} = \frac{\left[-4z + \frac{2}{k} \left[f_2^{1/2}(z) + \frac{(z/z_o)}{f_1^2(z)} \right] - \frac{\omega_o^2 z_o}{z^2} f_2^{1/2}(z) + \frac{\omega_o^2}{z f_1^2(z)} \right]}{2r(z)} \quad (2.4.17)$$

$$r(z) = \{[-z + (\tan^{-1}(z/z_o) - C_w)/k]2R(z)\}^{1/2}, \quad z_a \leq z \leq z_w \quad (2.4.18)$$

$$f_1(z) = [1 + (z/z_o)]^{1/2}$$

$$f_2(z) = [-C_w + \tan^{-1}(z/z_o)]^2, \quad f_2^{1/2}(z) = -C_w + \tan^{-1}(z/z_o)$$

$$C_w = \tan^{-1}(z_w/z_o) - kz_w, \text{ wavefront phase constant}$$

Accurate numerical integration of Eq. (2.4.16) using thousands of sub-intervals, with a 16-term Gaussian quadrature within each subinterval, shows that the arc length $\overline{OE_1}$ is very close (within 0.01%) of the arc length found by assuming that the wavefront is spherical. The assumption that the wavefront is spherical is valid when $z \gg a$. When

the wavefront is essentially spherical, the following relationship is used

$$\overline{OE_1} = R_{z_w} \sin^{-1}(a/R_{z_w}) \quad (2.4.19)$$

Calculations using both Eq. (2.4.16) and Eq. (2.4.19) are made in FESDIF and compared. The spherical wavefront approximation is used as long as it is highly accurate; otherwise the non-spherical wavefront relationship is employed.

Knowing $r(\theta)$, $z(\theta)$, $w[z(\theta)]$ and $\overline{OE_1}$ completes the definition of the terms in Eq. (2.4.9).

When axial diffraction field calculations are being performed, Eq. (2.4.9) reduces through integration in the ϕ'' coordinate direction to

$$\begin{aligned} E_p(r', \phi') = C \int_{\theta=0}^{\theta_1} & \left\{ \left[ik - \frac{1}{R'} \right] \cos \theta' + \left[\frac{ikr}{R(z)} - \frac{2r}{\omega^2(z)} \right] \sin \alpha \right. \\ & + \left[i \left[k \left[1 - \frac{r^2(1-(z_o/z)^2)}{2R^2(z)} \right] - \frac{z_o}{zR(z)} \right] - \left[\frac{1}{R(z)} - \frac{2r^2}{\omega^2(z)R(z)} \right] \right] \cos \alpha \Big\} \\ & \times \frac{\exp \left\{ ikR' + \frac{r^2(\theta)}{\omega^2[z(\theta)]} \right\}}{w[z(\theta)]R'} \sin \theta d\theta \end{aligned} \quad (2.4.20)$$

where

$$C = -(E_o \omega_o s_i^2 / 2) \exp\{-ikL\} \exp\left\{-i \left\{ k \left[z + \frac{r^2}{2R(z)} \right] - \tan^{-1} \frac{z}{z_o} \right\} \right\}$$

The derivation of the characteristic pathlength Fresnel number equation for this formulation is identical to that for the focused spherical wave of Eq. (2.2.11) of Section 2.2. Referring to Fig. 2.4.3 for defining the parameters, the result is

$$Fr_p = (2n_f/\lambda) \{ z' - [(z' - h_a)^2 + a^2]^{1/2} \} \quad (2.4.21)$$

Note that in Eq. (2.4.21) the value of Fr_p may be either for $z' < s_i$ or for $z' > s_i$ depending on the value of n_f [defined in Eq. (2.4.7)]. These are referred to as the inside

9-0675

Figure 2.4.3. Geometry used for derivation of characteristic pathlength Fresnel number equation for a spherically focused Gaussian laser beam.

and outside pathlength Fresnel numbers, Fr_p^- and Fr_p^+ , respectively. Evaluating Eq. (2.4.21) at focus results in $Fr_p = 0$, as expected. The location, z' , at which a particular value of Fr_p occurs can be found by solving Eq. (2.4.21) for z' to obtain

$$z' = \frac{h_a^2 + a'^2 - (m\lambda/2)^2}{(2h_a' - n_f m\lambda)}, m = Fr_p \quad (2.4.22)$$

Negative values of z' from this equation indicate that the particular Fresnel number being used does not occur in the diffraction field being investigated. Additional analysis and examples of the use of these pathlength Fresnel number equations have been presented by Kraus.^{4,5}

3.0 FINITE ELEMENT FOURIER AREA AND LINE INTEGRAL TRANSFORM FORMULATIONS FOR GENERALIZATION OF FRAUNHOFER DIFFRACTION THEORY

Methods for calculating Fraunhofer intensity fields resulting from diffraction through two-dimensional apertures are presented as developed by Kraus⁶. These methods are based on the geometric concept of finite elements and on Fourier and Abbe transforms. The geometry of the two-dimensional diffracting aperture(s) is based on bi-quadratic isoparametric elements, which are used to define aperture(s) of complex geometry. These elements are also used to build complex amplitude and phase functions across the aperture(s) which may be of continuous or discontinuous form. The transform integrals can be accurately and efficiently integrated numerically using Gaussian quadrature. Typically, the finite element Abbe transform based method results in significant gains in computational efficiency over the finite element Fourier transform method, but is also subject to some loss in generality.

Contemporary optical imaging systems are becoming increasingly complex and include a myriad of folded optical path systems ranging from refracting and catadioptric camera lenses and telescopes, to systems with off-axis (or partial circle or partial annular ring) elements, to the large effective aperture multiple mirror telescopes. Secondary mirrors (obstructions to the incident wavefront) with or without opaque supports are common in such optical instruments. It is in this area of calculation of complex and multiple aperture system Fraunhofer diffraction patterns that this section is focused. In addition, generalized phase and amplitude aperture function capabilities will be developed for these complex aperture systems.

3.1 Finite Element Fourier Area Integral Transform

This section is devoted to developing the mathematical details of the two-dimensional finite element Fourier transform. Note that in order to obtain an accurate Fourier transform result, the aperture function and the aperture geometry must be described accurately using the biquadratic isoparametric finite elements as discussed by Kraus.⁶ These requirements will be illustrated in the examples of Appendix B and are very easy to meet.

A nine-node bi-quadratic isoparametric finite element, as illustrated in Fig. 3.1.1(a), was chosen for application in defining two-dimensional planar apertures because of its capability to define curved as well as straight aperture edges. It is customary to define this element in terms of the local, ξ - η , coordinate system shown in Fig. 3.1.1(b) for two reasons. The first is that the local coordinate system allows the element to take on the desired quadratic curvature on the element edges in the global or x - y coordinate system.¹⁵ The second reason is that the required Gaussian quadrature numerical integration of the diffraction integral utilizes in this local coordinate system.

The procedure for developing local to global coordinate geometric transformation or interpolation functions for isoparametric elements is given in any standard finite element methods textbook. The particular nine-node bi-quadratic isoparametric element used here could not be found and so is presented in detail below. When used in this context only, $\{ \}$ denotes a single column matrix, $[\]$ denotes a single row matrix, and $[\]$ denotes a square matrix. Let the x and y global coordinates be defined in terms of nine-term ξ - η local coordinate polynomials as

$$\begin{aligned} x = x(\xi, \eta) = a_1 + a_2\eta + a_3\eta^2 + a_4\xi + a_5\xi\eta + a_6\xi\eta^2 + a_7\xi^2 \\ + a_8\xi^2\eta + a_9\xi^2\eta^2 = [G]\{a\} \end{aligned} \quad (3.1.1)$$

(a) Global coordinates

(b) Local coordinates

9-1319

Figure 3.1.1. Nine-node bi-quadratic isoparametric finite element geometry: (a) global coordinates, (b) local coordinates.

$$y = y(\xi, \eta) = b_1 + b_2\eta + b_3\eta^2 + b_4\xi + b_5\xi\eta + b_6\xi\eta^2 + b_7\xi^2 + b_8\xi^2\eta + b_9\xi^2\eta^2 = [G]\{b\} \quad (3.1.2)$$

where

$$[G] = [1 \quad \eta \quad \eta^2 \quad \xi \quad \xi\eta \quad \xi\eta^2 \quad \xi^2 \quad \xi^2\eta \quad \xi^2\eta^2] \quad (3.1.3)$$

$$\{a\} = \begin{Bmatrix} a_1 \\ a_2 \\ \vdots \\ a_9 \end{Bmatrix}, \quad \{b\} = \begin{Bmatrix} b_1 \\ b_2 \\ \vdots \\ b_9 \end{Bmatrix} \quad (3.1.4)$$

and the a's and b's are constants. The first step to determine the value of these constants is to evaluate Eqs. (3.1.1) and (3.1.2), in ordered geometric correspondence of local coordinate node for global coordinate node for relative position in the element.

This forms a set of nine equations which may be written as

$$\{x\} = [\mathcal{D}]\{a\}, \quad \{x\} = \begin{Bmatrix} x_1 \\ x_2 \\ \vdots \\ x_9 \end{Bmatrix} \quad (3.1.5)$$

and

$$\{y\} = [\mathcal{D}]\{b\}, \quad \{y\} = \begin{Bmatrix} y_1 \\ y_2 \\ \vdots \\ y_9 \end{Bmatrix} \quad (3.1.6)$$

where each row of $[\mathcal{D}]$ is the evaluation of $[G]$ at one of the nine local coordinate nodes. The constants $\{a\}$ and $\{b\}$ are then solved for as

$$\{a\} = [\mathcal{D}]^{-1}\{x\} \quad (3.1.7)$$

$$\{b\} = [\mathcal{D}]^{-1}\{y\} \quad (3.1.8)$$

so that

$$x = x(\xi, \eta) = [G][\mathcal{D}]^{-1}\{x\} \quad (3.1.9)$$

$$y = y(\xi, \eta) = [G][\mathcal{D}]^{-1}\{y\} \quad (3.1.10)$$

Note that $[\mathcal{D}]^{-1}$ needs to be found only once for all elements because the set of local coordinate nodes is identical for all elements. The x and y coordinate interpolation functions for any element may then be expressed in terms of local coordinates as

$$\mathbf{x} = \mathbf{x}(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) \mathbf{x}_i = [\mathbf{N}] \{\mathbf{x}\} = [\mathbf{G}][\mathcal{D}]^{-1} \{\mathbf{x}\} \quad (3.1.11)$$

$$\mathbf{y} = \mathbf{y}(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) \mathbf{y}_i = [\mathbf{N}] \{\mathbf{y}\} = [\mathbf{G}][\mathcal{D}]^{-1} \{\mathbf{y}\} \quad (3.1.12)$$

where $\mathbf{x}_i, \mathbf{y}_i$ are the global coordinate node points, $n = 9$, and

$$[\mathbf{N}] = [\mathbf{G}][\mathcal{D}]^{-1} \quad (3.1.13)$$

Consider a monochromatic light wave incident in the normal direction upon a two-dimensional planar aperture. The aperture function, $A_j(x, y)$, of each element of the diffracting aperture may, in general, involve an amplitude term, $\mathcal{A}_j(x, y)$ and a phase term, $\exp\{i\phi_j(x, y)\}$, where $\phi_j(x, y)$ is the phase function within an element. These can also be defined in local coordinates similar to Eqs. (3.1.11) and (3.1.12)

$$\mathcal{A}_j(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) \mathcal{A}_i = [\mathbf{N}] \{\mathcal{A}\} = [\mathbf{G}][\mathcal{D}]^{-1} \{\mathcal{A}\} \quad (3.1.14)$$

and

$$\phi_j(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) \phi_i = [\mathbf{N}] \{\phi\} = [\mathbf{G}][\mathcal{D}]^{-1} \{\phi\} \quad (3.1.15)$$

In global coordinates, the general Fourier transform for calculating the far-field diffraction pattern, using the generalized aperture function $A(x, y)$, may be written as,

$$E(\chi', \psi') = \iint_{\Sigma} \mathcal{A}(x, y) \exp\{i\phi(x, y)\} \exp\{i2\pi[\chi'x + \psi'y]\} d\Sigma \quad (3.1.16)$$

where $\chi' = x'/\lambda R$, $\psi' = y'/\lambda R$ are the transformation wave numbers in the x' and y' directions, respectively. By replacing the distance R by the focal length of a lens f , this diffraction field becomes the Fraunhofer diffraction field at the image plane of the lens.

By division of the aperture(s) into M finite elements and making the transformation into local coordinates to permit Gaussian quadrature numerical integration, Eq. (3.1.16) may be expressed as

$$E(\chi', \psi') = \sum_{j=1}^M \int_{-1}^1 \int_{-1}^1 \mathcal{A}_j(\xi, \eta) \exp\{i\phi_j(\xi, \eta)\} \\ \times \exp\{i2\pi [\chi' [N] \{x\} + \psi' [N] \{y\}] \}_j |J|_j d\xi d\eta \quad (3.1.17)$$

where

$$|J| = \begin{vmatrix} \frac{\partial x}{\partial \xi} & \frac{\partial x}{\partial \eta} \\ \frac{\partial y}{\partial \xi} & \frac{\partial y}{\partial \eta} \end{vmatrix} \quad (\text{ie the area Jacobian})$$

$$\frac{\partial x}{\partial \xi} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \xi} x_i$$

$$\frac{\partial x}{\partial \eta} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \eta} x_i$$

$$\frac{\partial y}{\partial \xi} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \xi} y_i$$

$$\frac{\partial y}{\partial \eta} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \eta} y_i$$

Equation (3.1.17) is the general finite element Fourier transform diffraction integral with full aperture function capabilities.

3.2 Finite Element Abbe Line Integral Transform

For many applications, Eq. (3.1.17) may be reduced to a simpler form through use of the Abbe transform¹⁶ which allows the conversion of the area integral into a line integral around the boundaries of the aperture opening. The motivation for its use is to save computer computation time in the many evaluations of Eq.(3.1.17) which are required in order to form a detailed representation of the far-field diffraction pattern in the transformation wave number coordinates, $\chi'-\psi'$ (or the $x'-y'$ coordinates). This is possible only with some restrictions in the aperture function as presented below. With the goal of making use of the Abbe transform in this finite element diffraction formulation, let radial vectors in the aperture plane and the observation plane, respectively, be defined as

$$\vec{r} = x \hat{i} + y \hat{j} \quad (3.2.1)$$

$$\vec{r}' = x' \hat{i} + y' \hat{j} \quad (3.2.2)$$

Equation (3.1.16) may then be expressed as

$$E(\vec{r}') = \iint_{\Sigma} \mathcal{A}(\vec{r}) \exp\{i\phi(\vec{r})\} \exp\{ik\vec{r}' \cdot \vec{r}/R\} d\vec{r} \quad (3.2.3)$$

Let a scalar function be defined as

$$\nu(\vec{r}') = \exp\{ik\vec{r}' \cdot \vec{r}/R\} \quad (3.2.4)$$

which satisfies the Helmholtz or scalar wave equation

$$\nabla^2 \nu + \frac{k^2 r'^2}{R^2} \nu = 0 \quad (3.2.5)$$

Equation (3.2.5) may be solved for ν and used with Eq. (3.2.4) to re-write Eq. (3.2.3) as

$$E(\vec{r}') = -\frac{R^2}{k^2 r'^2} \iint_{\Sigma} \mathcal{A}(\vec{r}) \exp\{i\phi(\vec{r})\} \nabla^2 \nu d\vec{r} \quad (3.2.6)$$

Recall next, Gauss's divergence theorem which states that for a vector $\vec{v}$

$$\iiint_V \vec{\nabla} \cdot \vec{v} \, dV = \iint_{\Sigma} \vec{v} \cdot d\vec{\Sigma} = \iint_{\Sigma} \vec{v} \cdot \vec{n} \, d\Sigma \quad (3.2.7)$$

where Σ is the surface area of the volume, V , and $\vec{n}$ is the unit vector outward normal to the surface area Σ . For a unit depth, Eq. (3.2.7) reduces to

$$\iint_{\Sigma} \vec{\nabla} \cdot \vec{v} \, d\Sigma = \oint_{\Gamma} \vec{v} \cdot \vec{n} \, dl \quad (3.2.8)$$

where Γ represents the line boundaries of the area Σ and $\vec{n}$ is the unit vector outward normal to Γ . Equations (3.2.4), (3.2.5), and (3.2.8) form the essential elements of the Abbe transform. In order to allow use of Eq. (3.2.8) in Eq. (3.2.6), it is necessary to let $\vec{v} = \vec{\nabla} \nu$ and to impose the severe restriction that the aperture function, $A(\vec{r}) = \mathcal{A}(\vec{r}) \exp\{i\phi(\vec{r})\}$, be constant throughout the aperture. Then Eq. (3.2.6) may be written as

$$E(\vec{r}) = -\frac{iR}{k r'^2} \mathcal{A} \exp\{i\phi\} \oint_{\Gamma} \exp\{ik\vec{r}' \cdot \vec{r}/R\} \vec{r}' \cdot \vec{n} \, dl \quad (3.2.9)$$

There is a singularity in Eq. (3.2.9) at $r' = 0$. However, as $r' \rightarrow 0$, Eq. (3.2.9) does have a limiting and very useful form. Kraus⁶ has shown by careful application of l'Hopital's rule twice to Eq. (3.2.9) that

$$\lim_{r' \rightarrow 0} -\frac{iR}{k r'^2} \mathcal{A} \exp\{i\phi\} \oint_{\Gamma} \exp\{ik\vec{r}' \cdot \vec{r}/R\} \vec{r}' \cdot \vec{n} \, dl = \mathcal{A} \exp\{i\phi\} \times \frac{1}{2} \oint_{\Gamma} \vec{r} \cdot \vec{n} \, dl \quad (3.2.10)$$

so that

$$E(\vec{r}' = 0) = \frac{1}{2} \mathcal{A} \exp\{i\phi\} \oint_{\Gamma} \vec{r} \cdot \vec{n} \, dl \quad (3.2.11)$$

Equation (3.2.11) results exactly agree with those calculated using Eq. (3.1.17) for $r' = 0$ which verifies that Eq. (3.2.11) is correct. Equation (3.2.11) is a very powerful and useful equation by itself for aperture design studies because it allows on-axis Fraunhofer diffraction field intensities to be calculated and compared based only on differences in the aperture geometry. Equations (3.2.9) through (3.2.11) form the

non-finite element Abbe transform version of this formulation and is included as a precursor to the geometrically more powerful finite element version of these equations.

The first step in developing the finite element version of Eq. (3.2.9), is to divide the aperture area, Σ , of Eq. (3.2.6) into M bi-quadratic finite elements. In this case, use of Eq. (3.2.8) in Eq. (3.2.6) requires that $\vec{v} = \vec{\nabla} \nu$ within each element of the aperture and that the aperture function within the j th element, $A_j(\vec{r}) = \mathcal{A}_j(\vec{r}) \exp\{i\phi_j(\vec{r})\}$, be constant. Note that the latter specification has allowed the constant aperture function restriction to be reduced from the global level to the element level. Finally, by performing the transformation into the local coordinate interval $(-1,1)$ to permit Gaussian quadrature numerical integration, the finite element Abbe transform based version of Eq. (3.2.9) may be written as

$$E(\vec{r}') = -\frac{iR}{k r'^2} \sum_{j=1}^M \mathcal{A}_j \exp\{i\phi_j\} \left[\sum_{\mathcal{A}=1}^4 \int_{-1}^1 \left[\exp\{ik\vec{r}' \cdot \vec{r}/R\} \vec{r}' \cdot d\vec{l}_n \right]_{\mathcal{A}} d\gamma \right]_j \quad (3.2.12)$$

where the index $\mathcal{A}$ designates the element side, $d\vec{l}_n d\gamma = \vec{n} dl$, and $d\gamma = d\xi$ for the horizontal element sides and $d\gamma = d\eta$ for the vertical element sides for the element as oriented in Fig. 3.1.1(b). To complete the definition of the terms in Eq. (3.2.12), let $d\vec{l}_t$ be the vector tangent to l with magnitude $|dl|$. For the element sides where $\eta =$ constant, the vector $d\vec{l}_t$ may be written as

$$d\vec{l}_t = \frac{\partial x}{\partial \xi} \hat{i} + \frac{\partial y}{\partial \xi} \hat{j} \quad (3.2.13)$$

whereas for the element side where $\xi =$ constant,

$$d\vec{l}_t = \frac{\partial x}{\partial \eta} \hat{i} + \frac{\partial y}{\partial \eta} \hat{j} \quad (3.2.14)$$

A rotational transformation may then be used to rotate $d\vec{l}_t$ so that it is normal to the edge of the element to form the vector $d\vec{l}_n$ as

$$d\vec{l}_n = \left[\frac{\partial x}{\partial \xi} \cos(\rho) + \frac{\partial y}{\partial \xi} \sin(\rho) \right] \hat{i} + \left[-\frac{\partial x}{\partial \xi} \sin(\rho) + \frac{\partial y}{\partial \xi} \cos(\rho) \right] \hat{j} \quad (3.2.15)$$

for the element sides for which $\eta = \text{constant}$, and

$$d\vec{l}_n = \left[\frac{\partial x}{\partial \eta} \cos(\rho) + \frac{\partial y}{\partial \eta} \sin(\rho) \right] \hat{i} + \left[-\frac{\partial x}{\partial \eta} \sin(\rho) + \frac{\partial y}{\partial \eta} \cos(\rho) \right] \hat{j} \quad (3.2.16)$$

for the element sides for which $\xi = \text{constant}$. The rotation angle ρ is equal to $\pi/2$ for the bottom and right sides of the element and equal to $-\pi/2$ for the top and left sides of the element as oriented in Fig. 3.1.1(b). The on-axis diffraction field intensity finite element version of Eq. (3.2.11) is

$$E(\vec{r}' = 0) = \frac{1}{2} \sum_{j=1}^M \mathcal{A}_j \exp\{i\phi_j\} \left[\sum_{\ell=1}^4 \int_{-1}^1 \left[\vec{r} \cdot d\vec{l}_n \right]_{\ell} d\gamma \right]_j \quad (3.2.17)$$

3.3 Discussion of Finite Element Fraunhofer

Diffraction Integral Transforms

To calculate the far-field diffraction for an aperture, either Eq. (3.1.17) is needed or Eqs. (3.2.12) and (3.2.17) are needed. These will be referred to as the finite element Fourier transform and the finite element Abbe transform methods, respectively. If the aperture function is constant in each and every one of the elements, but possibly different from element to element, then Eqs. (3.2.12) and (3.2.17) can be used to calculate the diffraction field at all desired points of the observation field. If the aperture function varies within each of the elements, then Eq.(3.1.17) is required for calculating the wave amplitude at all points of the observation field. Note that the finite element Abbe transform does not require evaluation of the line integrals where the aperture function is of the same value for elements which share a common edge. This is because their unit vectors, $\vec{n}$, are in opposing directions resulting in cancellation of these terms in Eqs. (3.2.12) and (3.2.17). For apertures in which the aperture function is constant throughout, this means that only the element edges which have no edge in common with another element need to be evaluated in Eqs. (3.2.12) and (3.2.17). This situation results in greatly decreased computational requirements for calculating the diffraction field.

The amplitude and phase functions of the above methods can also easily be used to define the amplitude and phase of laser beams incident upon geometrically complex diffracting apertures. FESDIF allows such a generalized incident wave capability through specification of the aperture function amplitude and phase via node by node data input for the mesh defining the diffracting aperture.

The finite element Fourier transform and Abbe transform based methods have advantages over discrete Fourier transform methods. The positive attributes of the finite element Fourier and Abbe transform methods are listed here as described by Kraus.⁶

1. Unlike a discrete fast Fourier transform, which requires as many points in the aperture as will be calculated in the frequency space, the finite element Fourier and Abbe transform methods allow the aperture geometry and aperture function to be accurately defined using a relatively small number of points, which are in turn used to define finite elements within the aperture. Any number of frequency space values may be calculated in the transform space instead of being fixed by the number of points defining the aperture as required when using discrete fast transform methods.
2. The aperture may be of any desired geometry no matter how complex, making possible an infinite spectrum of design studies based upon aperture shape, obstructing secondary mirrors, secondary mirror supports shapes and placements, multiple apertures, synthetic apertures arrays, etc.
3. Multiple apertures are easily handled by defining each aperture using different sets of elements. This is supported theoretically by the principle of linear superposition for diffraction which states that under monochromatic coherent illumination, the Fraunhofer diffraction field will be a superposition of the individual fields due to each separate aperture.⁹
4. The aperture function within each aperture can be defined by sectionally continuous elements which can be used to accurately define very complex and continuous aperture functions.
5. Each aperture may have a different aperture function.

6. Aperture function discontinuities are easily defined anywhere within each aperture by superimposing two sets of nodes at the geometric interface between two adjacent elements. The discontinuity can then be defined as a step change in the aperture function value from the first element edge to the second element edge.
7. There is an increase in accuracy of the computed transforms over a discrete Fourier transform due to the accuracy with which complex aperture function and aperture geometries can be defined. The geometric advantage of the finite element based transforms is manifested as a virtual absence of calculated diffraction field magnitude and phase errors which it is not possible to achieve when using discrete methods as shown by Kraus⁶. The phase errors which typically result when using discrete Fourier transform methods have also been documented by Hudson.¹⁷

The primary negative attribute of the finite element Fourier and Abbe transform methods is listed here.

1. Increased computer computation time when compared to a discrete fast Fourier transform. This increase varies according to the particular problem being solved but is typically less than one order of magnitude. However, even for very complex aperture Fraunhofer diffraction applications, the required execution time for calculating either the finite element Fourier or Abbe transform has typically been a few minutes to about 1 hour on a 32-bit PC computer. This is an attractively small amount of computer time to use in exchange for the power, versatility, and accuracy provided by use of these finite element Fourier and Abbe transform methods.

Finally, it is important to note that the finite element transform methods are the only means currently available for accurately solving many of the modern complex aperture diffraction problems.

4.0 FINITE ELEMENT KIRCHHOFF AREA AND LINE INTEGRAL TRANSFORM FORMULATIONS FOR GENERALIZATION OF FRESNEL AND VERY-NEAR-FIELD DIFFRACTION THEORY

The light that is diffracted or scattered along the optical path of an instrument, due to the presence of the primary aperture, aperture stops, aperture obstructions, baffles, etc., is very important in the design and performance of numerous optical instruments and systems. Rather than just dealing with far-field or image plane diffraction, as was done in Section 3.0, this section deals with the broad topic of diffraction in general anywhere beyond a diffracting aperture. The region immediately beyond a diffracting aperture or optical component is considered to be the near-field diffraction region. Beyond this, and up to but not including the far-field or the focal plane, is referred to as the Fresnel diffraction region. The Fresnel diffraction region is often quantified as the region where the expansion of the exponential term in the diffraction integral can be well approximated by quadratic terms.^{9,18} For circular apertures, this results in the well-known Fresnel integrals.⁹ Using this definition, the near-field region begins where this approximation becomes invalid and extends up to the diffracting aperture. Such near-field and Fresnel diffraction patterns exist at various critical locations throughout an optical instrument up to the final image plane, where it is then considered to be far-field or Fraunhofer. The nature of the diffraction field does change when progressing from the Fresnel region through the near-field region. This is characterized by deviations of the diffraction field intensities from those of the classical Fresnel patterns. This section deals with both the near-field and Fresnel diffraction regions, in general,

recognizing that Fraunhofer diffraction is simply the far-field limit or focal plane case of Fresnel diffraction.

The Kirchhoff diffraction theory which is the basis for the development of the finite element diffraction integral transforms of this section was presented in Section 2.0. The transformations developed below allow calculation of the near-field and Fresnel diffraction field for virtually any planar single or multiple aperture geometry. A major advantage of the finite element based methods over any other methods, such as discrete transform methods, is the ease with which complex aperture geometries can be accurately defined. These finite element based methods can be used to calculate diffraction fields, not only for any of the aperture configurations found anywhere in the literature, but also for any newly conceived aperture shape. Additionally, the finite element formulation includes accurate, continuous or stepwise, aperture function amplitude and phase specification capabilities at the element level in order to accommodate apodizing and phase plate components. For these reasons, the methods presented, in combination with the finite element based methods of Section 3.0, form a state-of-the-art tool for design and analysis studies of optical instruments.

Two different finite element based diffraction integral transformations are developed below. The first is an area integral and the second is a line integral. These mathematical formulations are first developed in general form, and then specifically developed for spherical waves and Gaussian laser beams. The latter two specific formulations were chosen because they are the ones most often encountered in practical applications.

4.1 Finite Element Kirchhoff Area Integral

Transform Formulation: General

The mathematical development of the two-dimensional finite element Kirchhoff diffraction integral is presented in this section. As with the finite element Fourier and Abbe transforms, use of these formulations requires that the geometry of the aperture, as well as the aperture function, be accurately defined using the finite elements as has been discussed by Kraus⁷. The nine-node bi-quadratic isoparametric finite element used in Section 3.0 and shown in Fig. 3.1.1 was employed here also.

Consider a monochromatic light wave incident in the normal direction upon a two-dimensional planar aperture, as illustrated in Fig. 4.1.1. The light proceeding through or scattering off of the edge of the aperture will be composed of the incident light wave function $U(x,y,z)$ and the aperture function $A(x,y)$, which may modify the amplitude and phase of the incident wave as it passes the aperture plane opening. The incident wave function, $U(x,y,z)$, of the diffracting aperture will involve an amplitude factor, $\mathcal{U}(x,y,z)$, and a phase factor, $\exp\{i\psi(x,y,z)\}$, where $\psi(x,y,z)$ is the phase function. The aperture function, $A(x,y)$, of the diffracting aperture may also, in general, involve an amplitude factor, $\mathcal{A}(x,y)$, and a phase factor, $\exp\{i\phi(x,y)\}$, where $\phi(x,y)$ is the phase function. The incident wave function, combined with the aperture function, produces the effective wave, u , incident upon the aperture opening as

$$u(x,y,z) = U(x,y,z)A(x,y) \quad (4.1.1)$$

or

$$u(x,y,z) = \mathcal{U}(x,y,z)\exp\{i\psi(x,y,z)\} \mathcal{A}(x,y)\exp\{i\phi(x,y)\} \quad (4.1.2)$$

These functions can be defined in terms of the local coordinates of the aperture

plane, for each element j defining the aperture, using interpolation functions analogous to Eqs. (3.1.14) and (3.1.15)

$$u_j(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) u_i = [N]\{u\} = [G][\mathcal{D}]^{-1}\{u\} \quad (4.1.3)$$

$$\psi_j(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) \psi_i = [N]\{\psi\} = [G][\mathcal{D}]^{-1}\{\psi\} \quad (4.1.4)$$

$$\mathcal{A}_j(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) \mathcal{A}_i = [N]\{\mathcal{A}\} = [G][\mathcal{D}]^{-1}\{\mathcal{A}\} \quad (4.1.5)$$

$$\phi_j(\xi, \eta) = \sum_{i=1}^n N_i(\xi, \eta) \phi_i = [N]\{\phi\} = [G][\mathcal{D}]^{-1}\{\phi\} \quad (4.1.6)$$

The general Kirchhoff integral for calculating the amplitude at a point, P , in the diffraction field may be written in global coordinates as¹⁰ (see also Section 2.0)

$$E_P(x', y') = \frac{1}{4\pi} \iint_{\Sigma} \left[u \frac{\partial v}{\partial n} - v \frac{\partial u}{\partial n} \right] d\Sigma \quad (4.1.7)$$

where, as depicted in Fig. 4.1.1, x' , y' are the coordinates in the plane of observation of the diffraction field, v is the Green's function spherical wave source, and $\hat{n}$ is a unit vector inward normal to the surface Σ . The surface Σ is in the plane of the aperture and represents the region of the aperture opening. The outgoing free-space Green's function is defined as

$$v = \frac{\exp\{i k R'\}}{R'} \quad (4.1.8)$$

where k is the propagation number equal to $2\pi/\lambda$, λ is the wavelength, and R' is the distance from the point of origin of the Green's function spherical wave, which is the same as the observation field point, P of Fig. 4.1.1, to a point in the region of the aperture opening. Substituting Eqs. (4.1.2) and (4.1.8) into Eq. (4.1.7) gives

$$E_P(x', y') = \frac{1}{4\pi} \iint_{\Sigma} \left\{ \frac{\mathcal{U} \mathcal{A} \exp\{i[\psi + \phi + kR']\}}{R'} \left\{ (ik - 1/R') \cos(\vec{R}', \hat{n}) - \left[i \frac{\partial \psi}{\partial n} + \frac{1}{\mathcal{U}} \frac{\partial \mathcal{U}}{\partial n} \right] \right\} \right\} d\Sigma \quad (4.1.9)$$

By division of the aperture(s) into M finite elements and making the transformation into local coordinates to permit Gaussian quadrature numerical integration, Eq. (4.1.9) may be expressed as

$$E(P) = \frac{1}{4\pi} \sum_{j=1}^M \int_{-1}^1 \int_{-1}^1 \left\{ \frac{\mathcal{U} \mathcal{A} \exp\{i[\psi + \phi + kR']\}}{R'} \left\{ (ik - 1/R') \cos(\vec{R}', \hat{n}) - \left[i \frac{\partial \psi}{\partial n} + \frac{1}{\mathcal{U}} \frac{\partial \mathcal{U}}{\partial n} \right] \right\} |J| \right\} \bigg|_{z=z_s} d\xi d\eta \quad (4.1.10)$$

where z_s is the source to aperture plane distance as shown in Fig. 4.1.2,

$$|J| = \begin{vmatrix} \frac{\partial x}{\partial \xi} & \frac{\partial x}{\partial \eta} \\ \frac{\partial y}{\partial \xi} & \frac{\partial y}{\partial \eta} \end{vmatrix} \quad (\text{i.e., the area Jacobian})$$

$$\frac{\partial x}{\partial \xi} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \xi} x_i$$

$$\frac{\partial x}{\partial \eta} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \eta} x_i$$

$$\frac{\partial y}{\partial \xi} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \xi} y_i$$

$$\frac{\partial y}{\partial \eta} = \sum_{i=1}^n \frac{\partial N_i(\xi, \eta)}{\partial \eta} y_i$$

Equation (4.1.10) is the general finite element Kirchhoff diffraction integral formulation.

Figure 4.1.2. Geometry for spherical wave and Gaussian beam finite element Kirchhoff area and line diffraction integral transform formulations.

K92 0133

4.1.1 Spherical waves

Let a uniform intensity spherical wave source be located off-axis at the point (x_s, y_s) as shown in Fig. 4.1.2. The incident wave function for this spherical wave is $U = (\mathcal{U}_0/\rho)\exp\{ik\rho\}$, where $\mathcal{U}_0$ is a constant and ρ is the distance from the source to some point in the plane of the aperture opening as shown in Fig. 4.1.2. Therefore, $\mathcal{U} = \mathcal{U}_0/\rho$ and $\psi = k\rho$ in the incident wave function $U = \mathcal{U}\exp\{i\psi\}$. For the spherical wave case, Eq. (4.1.10) becomes

$$E_p(x', y') = \frac{\mathcal{U}_0}{4\pi} \sum_{j=1}^M \int_{-1}^1 \int_{-1}^1 \left\{ \frac{\mathcal{A} \exp\{i[k(\rho + R') + \phi]\}}{\rho R'} \right. \\ \left. \times \left[(ik - 1/R') \cos(\vec{R}', \hat{n}) - (ik - 1/\rho) \cos(\vec{\rho}, \hat{n}) \right] |J| \right\} \bigg|_{z=z_s} d\xi d\eta \quad (4.1.1.1)$$

where

$$\rho = \rho[x(\xi, \eta), y(\xi, \eta)] = [(x - x_s)^2 + (y - y_s)^2 + z_s^2]^{1/2} \quad (4.1.1.2)$$

$$R' = R'[x(\xi, \eta), y(\xi, \eta)] = [(x - x_p')^2 + (y - y_p')^2 + z'^2]^{1/2} \quad (4.1.1.3)$$

4.1.2 Gaussian laser beams

Consider a paraxial Gaussian laser beam incident upon the planar aperture, as also represented in Fig. 4.1.2. The incident wave can be defined by the function¹⁴

$$U(r, z) = \mathcal{U} \exp\{i\psi\} = \frac{E_o \omega_o}{\omega(z)} \exp \left\{ -i \left\{ k \left[z + \frac{r^2}{2R(z)} \right] - \tan^{-1}(z/z_o) \right\} \right. \\ \left. - r^2/\omega^2(z) \right\} \quad (4.1.2.1)$$

where

$$\mathcal{U}(r, z) = \frac{E_o \omega_o}{\omega(z)} \exp \left\{ -r^2/\omega^2(z) \right\} \quad (4.1.2.2)$$

$$\psi(r, z) = - \left\{ k \left[z + \frac{r^2}{2R(z)} \right] - \tan^{-1}(z/z_0) \right\} \quad (4.1.2.3)$$

$$\omega(z) = \omega_0 [1 + (z/z_0)^2]^{1/2} \quad (4.1.2.4)$$

$$R(z) = z[1 + (z_0/z)^2] \quad (4.1.2.5)$$

$$r^2 = (x - x_s)^2 + (y - y_s)^2 \quad (4.1.2.6)$$

$$z_0 = \pi \omega_0^2 / \lambda \quad (4.1.2.7)$$

For the Gaussian laser beam, Eq. (4.1.10) takes the form

$$E_p(x', y') = \frac{E_0 \omega_0}{4\pi} \sum_{j=1}^M \int_{-1}^1 \int_{-1}^1 \left\{ \frac{\exp\{-r^2/\omega^2(z)\} \mathcal{A} \exp\{i[-k(z + r^2/2R(z)) + \tan^{-1}(z/z_0) + \phi + kR']\}}{\omega(z) R'} \right. \\ \left. \left[(ik - 1/R') \cos(\vec{R}', \hat{n}) - i \left[k \left[1 - \frac{r^2[1 - (z_0/z)^2]}{2R^2(z)} \right] - \frac{z_0}{zR(z)} \right] + \left[\frac{1}{R(z)} - \frac{2r^2}{\omega^2(z)R(z)} \right] \right] |J| \right\} \bigg|_{j=\vec{s}_s} d\xi d\eta \quad (4.1.2.8)$$

where

$$R' = R'[\vec{x}(\xi, \eta), y(\xi, \eta)] = [(x - x_p')^2 + (y - y_p')^2 + z'^2]^{1/2}$$

4.2 Finite Element Asvestas Line Integral

Transform Formulation: General

The finite elements used for this formulation are the same as those used in Section 4.1. The additional development in the formulation presented here is the conversion of the finite element Kirchhoff area integral into a finite element line integral, as developed by Kraus.⁷ The basic area to line integral transformation used is based upon that presented by Asvestas^{19,20} who used a little known mathematical theorem and developed it for application to the Kirchhoff integral. Previous methods, including those by Rubinowicz²¹ and Miyamoto and Wolf,^{22,23} encounter mathematical difficulties at the observation point and computational problems when attempting to compute the diffraction field at the geometric shadow boundary.²⁰ The latter formulations are based upon a straight vector potential transformation. In contrast, the displaced vector potential transformation used by Asvestas²⁰ eliminates the mathematical singularity at the observation point and results in none of the shadow boundary computational problems. It was therefore chosen as the basis for development of the finite element versions of this line integral as presented below.

The line diffraction–integral formulation is presented here as a basis for understanding the subsequent development of the finite element version of these equations. Figure 4.1.2 will again be used. All source origins must lie on the incident side of the aperture, and therefore must produce divergent waves. The source point and the observation point are restricted from lying in the plane of the aperture. The boundary of aperture, Σ , is denoted as Γ . The unit vector $\hat{n}$ is normal to the aperture plane and is positive when directed toward the observation plane.

The Kirchhoff diffraction integral of Eq. (4.1.7) may be re-written as

$$E_p(x', y') = \frac{A}{4\pi} \iint_{\Sigma} \hat{n} \cdot \vec{V}(\vec{R}') d\Sigma \quad (4.2.1)$$

where

$$\vec{V}(\vec{R}') = U(\vec{R}') \nabla v(\vec{R}') - v(\vec{R}') \nabla U(\vec{R}') \quad (4.2.2)$$

U and A are as defined in Eq. (4.1.1), A was assumed to be constant over Σ , $\vec{R}'$ is the position vector from the Green's function source location (the observation point, P) to a point in the aperture opening or on the aperture boundary. The Green's function, or aperture side source function, v , is as given in Eq. (4.1.8). Note that the divergence of $\vec{V}(\vec{R}')$ is zero everywhere on the observation side of the aperture plane, except at the observation point P . Wherever $\nabla \cdot \vec{V}(\vec{R}') = 0$, $\vec{V}(\vec{R}')$ may be expressed in terms of a vector potential $\vec{W}(\vec{R}')$, where $\vec{V}(\vec{R}') = \nabla \times \vec{W}(\vec{R}')$, because $\nabla \cdot [\nabla \times \vec{W}(\vec{R}')] = 0$ is always true. However, these vector potential functions are not unique. By introducing a new vector defined as

$$\vec{\mathcal{V}}(\vec{R}') = \vec{V}(\vec{R}') + U(P) \nabla v_o(\vec{R}') \quad (4.2.3)$$

where $U(P)$ is the incident wave function $U(\vec{R}')$ or $U(x, y, z)$ of Eq. (4.1.1) evaluated at the observation point P which has coordinates $(x', y', z_s + z')$ relative to the source point S of Fig. 4.1.2, and

$$v_o(\vec{R}') = \frac{1}{R'} , \quad (4.2.4)$$

then the divergence of $\vec{\mathcal{V}}(\vec{R}')$ is zero everywhere on the observation side of the aperture plane, including the observation point P . Under these conditions, a theorem exists²⁰

which relates $\vec{\mathcal{V}}(\vec{R}')$ and $\vec{W}(\vec{R}')$ as

$$\vec{W}(\vec{R}') = \int_0^1 \vec{\mathcal{V}}(\tau\vec{R}') \times \vec{R}' \tau d\tau \quad (4.2.5)$$

where $\vec{\mathcal{V}} = \nabla \times \vec{W}$ on the observation side. Using Eq. (4.2.3) and (4.2.4) in Eq. (4.2.5) produces

$$\vec{W}(\vec{R}') = \hat{R}' \times \int_0^1 \exp\{ik\tau R'\} \nabla U(\tau\vec{R}') d\tau \quad (4.2.6)$$

Stokes' theorem states that²⁴

$$\int \int_{\Sigma} \hat{n} \cdot \nabla \times \vec{W}(\vec{R}') dS = \oint_{\Gamma} \hat{t} \cdot \vec{W}(\vec{R}') dl \quad (4.2.7)$$

where, as shown in Fig. 4.1.2, Σ is a regular surface bounded by the closed curve Γ , the direction of integration around Γ is positive with respect to the side of Σ in which $\hat{n}$ is directed, and $\hat{t}$ is the unit vector tangent to Γ . Using Eqs. (4.2.3) and (4.2.7), Eq. (4.2.1) may be expressed as

$$E_p(x', y') = \frac{A}{4\pi} \left\{ \oint_{\Gamma} \hat{t} \cdot \vec{W}(\vec{R}') dl - U(P) \int \int_{\Sigma} \hat{n} \cdot \nabla v_o(\vec{R}') d\Sigma \right\} \quad (4.2.8)$$

The last term of Eq. (4.2.8) may also be converted to a line integral by using a theorem that states^{19,20}

$$\int \int_{\Sigma} \hat{n} \cdot \nabla v_o(\vec{R}') d\Sigma = \oint_{\Gamma} \hat{t} \cdot \vec{W}_o(\hat{R}', \hat{q}) dl - \chi(\hat{R}' \cdot \hat{q}) \quad (4.2.9)$$

where Γ must be a piecewise regular curve, $\hat{q}$ is any unit vector bound to P such that $\hat{q} \cdot \hat{n} \leq 0$,

$$\vec{W}_o(\hat{R}', \hat{q}) = \frac{\hat{R}' \times \hat{q}}{R' (1 - \hat{R}' \cdot \hat{q})} \quad (4.2.10)$$

and

$$\chi(\hat{R}' \cdot \hat{q}) = 0, \text{ if } \hat{R}' \cdot \hat{q} \neq 1, \text{ for all } \hat{R}' \text{ endpoints } \in \Sigma \quad (4.2.11)$$

There are also cases associated with Eq. (4.2.11) for which $\chi(\hat{R}' \cdot \hat{q}) \neq 0$ which occur when $\hat{R}' \cdot \hat{q} = 1$. However, these were avoided by always choosing $\hat{q}$ such that

$\hat{R}' \cdot \hat{q} \neq 1$, while also maintaining $\hat{q} \cdot \hat{n} \leq 0$ as required by the theorem. [Conforming to the above two requirements for choosing $\hat{q}$ is straight forward. In FESDIF,

when this line integral formulation was used, $\hat{q} = 1/\sqrt{2} \hat{i} + 1/\sqrt{2} \hat{j} - 0 \hat{k}$. This unit vector has its origin at point P and lies in the observation plane $x'-y'$. Note that $\hat{R}' \cdot \hat{q} \neq 1$ (except when the point P lies within the plane of the aperture opening which was forbidden at the outset of this formulation) thus fulfilling the first requirement. Also, $\hat{q} \cdot \hat{n} = 0$ which fulfills the second requirement. Changing this $\hat{q}$ vector, while still meeting the above two requirements, should not and did not make any difference in the results of the examples of Appendix B.] Substituting Eq. (4.2.9) into Eq. (4.2.8) gives the result

$$E_P(x', y') = \frac{A}{4\pi} \left\{ \oint_{\Gamma} \hat{t} \cdot \vec{W}(\vec{R}') dl - U(P) \oint_{\Gamma} \hat{t} \cdot \vec{W}_o(\hat{R}', \hat{q}) dl + U(P) \chi(\hat{R}' \cdot \hat{q}) \right\} \quad (4.2.12)$$

where, as just explained above, the last term was always made equal to zero. Equation (4.2.12) is the generalized line integral form of the Kirchhoff diffraction integral. Because Eq. (4.2.12) is a linear function with respect to the enclosed area of the aperture, linear superposition may be used and the aperture function $A = \mathcal{A} \exp\{i\phi\}$ need only be constant at the element level. Using this fact, dividing the aperture Σ into M finite elements, and making the transformation into local coordinates to permit Gaussian quadrature numerical integration, this integral may be written as

$$E_P(x', y') = \frac{1}{4\pi} \sum_{j=1}^M \mathcal{A}_j \exp\{i\phi_j\} \left[\sum_{\mathcal{L}=1}^4 \int_{-1}^1 \left[\vec{W}[\vec{R}'(\xi, \eta)] \cdot d\vec{l}_t - U(P) \vec{W}_o[\hat{R}'(\xi, \eta), \hat{q}] \cdot d\vec{l}_t \right] d\gamma \right]_j \quad (4.2.13)$$

where the index $\mathcal{L}$ designates the element side, $d\vec{l}_t d\gamma = \hat{t} dl$, and $d\gamma = d\xi$ for the bottom element side, $d\gamma = -d\xi$ for the top element side, $d\gamma = d\eta$ for the right

vertical element side, and $d\gamma = -d\eta$ for the left vertical element side as oriented in Fig.

3.1.1 (b). The changing sign on these differentials accounts for the counterclockwise direction of integration around these elements required by the line integrals of Eq.

(4.2.13) relative to the positive cartesian coordinate directions. To complete the

definition of the terms in Eq. (4.2.13), let $\vec{dl}_t$ be the vector tangent to Γ with magnitude

$|dl|$. For the element sides where $\eta = \text{constant}$, the vector $\vec{dl}_t$ may be written as

$$\vec{dl}_t = \frac{\partial x}{\partial \xi} \hat{i} + \frac{\partial y}{\partial \xi} \hat{j} \quad (4.2.14)$$

whereas for the element side where $\xi = \text{constant}$,

$$\vec{dl}_t = \frac{\partial x}{\partial \eta} \hat{i} + \frac{\partial y}{\partial \eta} \hat{j} . \quad (4.2.15)$$

4.2.1 Spherical Waves

Consider a uniform intensity spherical wave source located off-axis at the point (x_s, y_s) as shown in Fig. 4.1.2. This incident wave may be represented as

$$U(\vec{R}') = \frac{\exp\{ik|\vec{R}' - \vec{R}^*\| \}}{|\vec{R}' - \vec{R}^*|} \quad (4.2.1.1)$$

where $\vec{R}^*$ is a vector from point P to point S. Point P is the observation point and is considered the origin. Therefore,

$$\vec{R}' = R'_x \hat{i} + R'_y \hat{j} + R'_z \hat{k} = (x - x_p) \hat{i} + (y - y_p) \hat{j} - z' \hat{k} \quad (4.2.1.2)$$

$$\vec{R}^* = R^*_x \hat{i} + R^*_y \hat{j} + R^*_z \hat{k} = (x_s - x_p) \hat{i} + (y_s - y_p) \hat{j} - (z_s + z') \hat{k} \quad (4.2.1.3)$$

For this case, the vector potential function, $W(\vec{R}')$, of Eq. (4.2.6) can be found to be²⁰

$$W(\vec{R}') = \frac{\hat{R}' \times \vec{R}^*}{R'} \left[\frac{\exp\{ik[R' + |\vec{R}' - \vec{R}^*|]\}}{|\vec{R}' - \vec{R}^*| [|\vec{R}' - \vec{R}^*| + R' \cdot (\vec{R}' - \vec{R}^*)]} - \frac{\exp\{ikR^*\}}{R^{*2}(1 - \hat{R}' \cdot \hat{R}^*)} \right], \text{ for } \hat{R}' \cdot \hat{R}^* \neq 1 \quad (4.2.1.4)$$

and since $\hat{R}' \times \vec{R}^* = 0$ when $\hat{R}' \cdot \hat{R}^* = 1$,

$$W(\vec{R}') = 0, \text{ for } \hat{R}' \cdot \hat{R}^* = 1 \quad (4.2.1.5)$$

Equations (4.2.10), (4.2.1.4), and (4.2.1.5) can then be used in Eq. (4.2.13) to calculate the diffraction field amplitude for a spherical wave incident upon a diffracting aperture.

4.2.2 Gaussian laser beams

$U(r, z)$ of Eq. (4.1.2.1), Section 4.1.2, is the expression for the amplitude and phase of a propagating laser beam. In this case, the vector potential function, $W(\vec{R}')$, for use in Eq. (4.2.6) is very complex in form. An analytical determination of this was not attempted and numerical integration was used instead. For the Gaussian beam, by replacing $U(r, z)$ by $U(\tau r, \tau z)$, the new term in Eq. (4.2.6) is

$$\begin{aligned} \nabla U(\tau \vec{R}') = & U(\tau r, \tau z) \left[\frac{ik\tau x}{R(\tau z)} - \frac{2\tau x}{\omega^2(\tau z)} \right] \hat{i} \\ & + U(\tau r, \tau z) \left[\frac{ik\tau y}{R(\tau z)} - \frac{2\tau y}{\omega^2(\tau z)} \right] \hat{j} \\ & - U(\tau r, \tau z) \left[\frac{1}{R(\tau z)} - \frac{2(\tau r)^2}{\omega^2(\tau z)R(\tau z)} - i \left[k \left[1 - \frac{(\tau r)^2 [1 - (z_0/\tau z)^2]}{2R^2(\tau z)} \right] \right. \right. \\ & \left. \left. - \frac{z_0}{(\tau z)R(\tau z)} \right] \right] \hat{k} \end{aligned} \quad (4.2.2.1)$$

where $\omega(z)$, $R(z)$, and r of Eqs. (4.1.2.4) through (4.1.2.6) were replaced by $\omega(\tau z)$, $R(\tau z)$, and τr . Also, z_0 is as defined in Eq. (4.1.2.7), and

$$\begin{aligned}\tau x &= \tau R'_x - R_x^*, \quad \tau y = \tau R'_y - R_y^*, \quad \tau z = \tau R'_z - R_z^*, \\ (\tau r)^2 &= (\tau x - x_s)^2 + (\tau y - y_s)^2\end{aligned}\quad (4.2.2.2)$$

where the components of $\vec{R}$ and $\vec{R}^*$ were defined in Eqs. (4.2.1.2) and (4.2.1.3). Equation (4.2.2.1) can then be used in Eq. (4.2.6). This along with Eq. (4.2.10) can be used in Eq. (4.2.13) to calculate the diffraction field amplitude for a Gaussian beam diffracted by an aperture. This version of Eq. (4.2.6) cannot be numerically integrated accurately even when using 16 terms in the Gaussian quadrature. It therefore was divided into m sub-intervals of $(-1,1)$ orthogonality as

$$W(\vec{R}') = \hat{R} \times \sum_{i=1}^m \frac{\Delta \tau_i}{2} \int_{-1}^1 \exp\{ik\delta R'\} \nabla U(\delta \vec{R}') d\delta \quad (4.2.2.3)$$

where $\Delta \tau_i = \tau_{i+1} - \tau_i$, $\tau_i = (i-1)/m$, $\tau_{i+1} = i/m$, and $\delta = (2\tau - \tau_i - \tau_{i+1})/\Delta \tau_i$. Gaussian quadrature numerical integration was then performed on each of the m sub-intervals.

4.3 Computational Considerations

The choice of transform method, numerical integration, and the structure of the computer programming are all important for efficient and accurate utilization of the above finite element diffraction integrals. The important aspects of these are discussed below.

4.3.1 Choice of transform method

The above diffraction formulations will be briefly summarized here by assigning each a classification designation to enable easy future referral:

- I. General finite element area diffraction–integral, Eq. (4.1.10)
 - a. Spherical wave case, Eq. (4.1.1.1)
 - b. Gaussian beam case, Eq. (4.1.2.8)
- II. General finite element line diffraction–integral, Eqs. (4.2.6), (4.2.10), and (4.2.13)
 - a. Spherical wave case, Eqs. (4.2.6), (4.2.10), (4.2.13), (4.2.1.4), and (4.2.1.5)
 - b. Gaussian beam case, Eqs. (4.2.6), (4.2.10), (4.2.13), (4.2.2.1), and (4.2.2.3)

In general, the area diffraction–integrals are more powerful because of the complex aperture function included in the formulation. However, given a particular problem, if an aperture function is constant at the element level and a spherical wave is being considered, an increase in computational speed of about 50 times is typical when the line diffraction integral is used instead of the area integral in the related examples of Appendix B. When a Gaussian beam is incident upon an aperture, there is only a 50 percent increase in speed when using the line diffraction–integral instead of the area diffraction–integral. This is because two parameters of integration are necessary for each formulation for the Gaussian beam: one coordinate dimension plus the vector potential

integral within this dimension for the former, and two coordinate dimensions for the latter. The area diffraction-integral must be used for aperture functions which vary continuously in amplitude and/or phase through an element.

4.3.2 Numerical integration convergence and accuracy

Gaussian quadrature was used for numerical integration of all of the above finite element diffraction integral equations. These integrals have the following proportionalities with respect to integration time, t_e ,

$$\text{Class I.a., } t_e \propto M_g O_g^2 \quad (4.3.2.1)$$

$$\text{Class I.b., } t_e \propto M_g O_g^2 \quad (4.3.2.2)$$

$$\text{Class II.a., } t_e \propto M_e O_g \quad (4.3.2.3)$$

$$\text{Class II.b., } t_e \propto M_e O_g^m O_w \quad (4.3.2.4)$$

where M_g is the number of elements defining the aperture geometry and the aperture function, O_g is the number of terms used in the Gaussian quadrature for geometry-based area or line integrals, M_e is the number of elements used to define the aperture boundary or an aperture function which is constant at the element level but varies from element to element, m is the number of sub-intervals into which the vector potential integral, $\vec{W}(\vec{R}')$, is divided, and O_w is the order of integration used in the Gaussian quadrature for $\vec{W}(\vec{R}')$. Accurate solutions were obtained for the examples given below using $O_g = 4$ and/or $O_w = 4$. Convergence was checked by successively increasing M_g , M_e , and/or m and examining the diffraction field amplitude values to insure that they remained unchanged. In the related examples of Appendix B, the smallest values of these parameters were used which permitted this convergence. This approach yielded four to five decimal accuracy integration results. Typical execution times on a 16 MHz, 32-bit personal computer with a math co-processor is from tens to hundreds of minutes. Double

precision or 64-bit floating point numbers must be used due to the high accuracy with which phase variations must be determined in these calculations.

4.3.3 Computer programming for increased efficiency

The primary goal of developing the finite element based diffraction integrals was to provide powerful and general aperture geometry and aperture function capabilities, not to develop the most efficient computational algorithm for diffraction calculations. However, computational efficiency is still an important factor in computer implementation of these integrals. To this end, a few close observations of these equations reveal a couple of tactical programming approaches to increased computational efficiency.

In general, Eqs. (4.1.10) and (4.2.13) must be calculated for all elements of the aperture for each point, P . However, for each new location of the point P , the geometry of each of the elements and, of course, the geometry of the entire aperture, remain unchanged. Therefore, the numerical integration coefficients which depend only upon geometry, and not upon the ever changing position vector, $\vec{R}'$, need to be calculated only once for each of the elements. If these coefficients are stored for repeated retrieval and use, they do not have to be re-calculated for each new observation point, P . Doing this and the analogous operation for the vector potential integral of Eq. (4.2.2.3), in fact, results in a several-fold reduction in computer computation times. In this manner, no specific computation is repeated more than once except in the specialized case of geometric symmetry about the optic-axis.

The line diffraction integral of Eq. (4.2.13) presents further opportunities for including simple steps in computer programs which greatly increase the efficiency for many problems. Note that if the incident wave function is identical in form for two

adjacent finite elements, and if their aperture functions have the same value, computation of this integral is not necessary. This is because the common element edge $\hat{t}$ vectors point in opposite directions resulting in opposite signs and cancellation of the otherwise identical contributions to the diffraction field at the point P. Under these circumstances, this will result in having to calculate the contributions to $E_p(x',y')$ only for the element edges which are not shared with another element. Adding a routine to identify and eliminate these unnecessary integrations is a critical factor in achieving much of the computational speed advantage of the line diffraction integral of Eq. (4.2.13) over the area diffraction integral of Eq. (4.1.10).

5.0 CALCULATION OF THE DIFFRACTION FIELDS

This section describes the method of numerical integration of all of the diffraction integrals of Sections 2.0, 3.0, and 4.0, the calculation of the diffraction field intensities, and normalization of the diffraction field intensities. Some considerations and procedures for obtaining accurate results from the numerical integration are discussed which are very important, in fact critical, to the successful use of FESDIF. They should be studied carefully before and during any analysis using FESDIF in order to insure that accurate results are obtained.

5.1 Numerical Integration of Diffraction Integrals

The method of numerical integration used for the diffraction integrals was Legendre polynomial based Gaussian quadrature.²⁵ The circular aperture integrals of Section 2.0 were divided into r - ϕ direction blocks and numerical integration was performed upon each of these blocks. The number of such blocks in the r and ϕ directions is controlled through user Input Data Blocks in FESDIF, as described in Appendix A. In the case of the finite element based diffraction formulations of Sections 3.0 and 4.0, Gaussian quadrature is performed at the element level, either in two-dimensions for the area based integrals or in one-dimension along an element edge for the line integrals. FESDIF has the capability to select the number of terms used in the Gaussian quadrature to be 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, or 16. To insure convergence to an accurate solution, the following procedure should be followed:

1. Make sure that you have accurately described the geometry of your aperture. When using the bi-quadratic isoparametric finite elements, it is not automatic that your geometry will be accurately defined using the mesh generators in FESDIF. However, this requirement is usually very easy to meet.
2. Make sure that you have described any aperture functions accurately using the finite elements.
3. Once you have specified the number of blocks and/or the number of terms to be used in the Gaussian quadrature numerical integration, and you have obtained a solution using FESDIF, then re-run the problem. This re-run should usually double the number of blocks you use in each coordinate direction, double the number of elements you use in each coordinate direction, double the number of terms used in the Gaussian quadrature or

some combination of the above in which case you need only increase, but not double, each of these parameters. Compare these results with the results from the previous run and make sure that the solution has not changed significantly. Any significant changes can usually be detected visually in the diffraction field plots. Typically, FESDIF can easily achieve 4 or 5 decimal accuracy. As with any numerical algorithm, this procedure can be taken to such an extreme that the solution will "blow-up" due to numerical truncation error. Avoid such extremes and FESDIF will produce accurate solutions.

When calculating the diffraction field for high pathlength Fresnel numbers, ie larger than 20 to 30, the requirements for obtaining an accurate solution using FESDIF become very demanding. In this context, demanding means that the problem will take relatively large amounts of computing time and not that FESDIF cannot compute the solution. (When properly used, FESDIF is always capable of producing accurate solutions, except when hampered by numerical truncation problems. The latter is not a problem with FESDIF, but rather a problem with the finite accuracy of the floating point numbers of the computer used.) The reason for this is that the phase variations become very rapid in the diffraction integrals and very fine finite element meshes and a large number of Gaussian quadrature terms are required to obtain an accurate solution. As the pathlength Fresnel number becomes larger and larger, there is very little intensity variation across the diffraction field so that these cases are usually of less interest for the central part of the light cone. However, sometimes it is only the light scattering which occurs at the aperture edges which ends up outside the central light cone that is of primary interest. In such cases, the pathlength Fresnel number is not of primary interest but it is still a good indicator of the computational effort which will be

required and the degree of difficulty experienced in obtaining an accurate solution to a problem. Studying the example problems of Appendix B will help to provide a good starting point for a particular problem. Using the pathlength Fresnel number equations of Section 2.0 will help to anticipate these types of demanding problems.

5.2 Normalization of the Calculated Diffraction Fields

The diffraction field integrals of Sections 2.0, 3.0, and 4.0 allow calculation of the diffraction field amplitude only. In all cases, the amplitude is used to calculate the diffraction field intensity and then this is normalized in some manner. The normalized diffraction field intensity is given by the relationship

$$I_n = \frac{I}{I_o} = \frac{\frac{1}{2} E_p^* E_p}{I_o} \quad (5.2.1)$$

where $I = (1/2)E_p^* E_p$ is the diffraction field intensity at point P, E_p^* is the complex conjugate of the amplitude E_p , and I_o is the intensity of the diffraction field used for normalization. FESDIF has the capability to let the user specify the value of I_o to be used. Usually these values must first be calculated using FESDIF and then a point selected, such as a point for another run perhaps for a different configuration or different aperture function, and then used in a new run. Note that because some of the leading constants are left off in FESDIF, these values are not absolute so that results from different diffraction formulations should not be mixed. The normalization value I_o is otherwise determined by FESDIF internally. The following tabulation gives the value of I_o used in default mode by FESDIF.

1. Simplified diffraction routines, lens or no lens, full diffraction field: I_o is the maximum diffraction field intensity in the observation plane.
2. Simplified diffraction routines, no lens, axial diffraction field: I_o is the intensity of the incident wave or beam on-axis at the center of the aperture but assuming that the aperture was not in place.
3. Simplified diffraction routines, lens, axial diffraction field: I_o is the intensity of the diffraction field on-axis at the image plane.
4. All finite element diffraction integrals: I_o is the maximum intensity of the diffraction field in the observation plane.

6.0 SUMMARY

This is the technical document describing the generation of a highly accurate state-of-the-art PC based diffraction analysis computer code called FESDIF (Finite Element Scalar DIFFraction Theory). The entire code is based upon scalar diffraction theory and covers the near-field, Fresnel, and Fraunhofer diffraction regions. Its limitations come from the fundamental limits of scalar diffraction theory in the near-field region. FESDIF is intended to be used as a tool to aid in the design and analysis of optical instruments and systems. This code contains an extensive set of routines which will calculate the intensity field beyond a diffracting aperture due to passage of an incident monochromatic optical wave. The capability to handle lenses, which may be diffracting and focusing, have been included for circular apertures. Incident waves may be planar, spherical, or a Gaussian laser beam. By building a foundation for this diffraction theory in finite element methods, complex aperture geometries and aperture function capabilities have been incorporated into the code. Line integral versions of these finite element integrals have been developed which significantly increase computational efficiency for many applications. This manual provides technical documentation, a user's input manual, and a large compliment of example problems to aid in the use of the code.

7.0 ACKNOWLEDGEMENTS

The funding for writing the FESDIF code and writing this technical document was provided under the Optical Engineering Long-Term-Research-Initiative (LTRI) with FY-92 funding. The research and development of the diffraction theory and methods upon which FESDIF is based was funded part under the Exploratory Research and Development Program (ERDP), part under the Computational Mechanics LTRI, and part under the Optical Engineering Research LTRI. The research and development phase of this work spanned four years from FY-88 to FY-91. The results of this effort are seven refereed journals articles,¹⁻⁷ a paper presentation at the 15th Congress of the International Commission for Optics,²⁶ the FESDIF code, and this technical report.

8.0 REFERENCES

1. H. G. Kraus, "Huygens–Fresnel–Kirchhoff wavefront diffraction formulation – spherical waves," J. Opt. Soc. Am. A, 7(8), 1196–1205 (1989).
2. H. G. Kraus, "Huygens–Fresnel–Kirchhoff wavefront diffraction formulation – paraxial and exact Gaussian laser beams," J. Opt. Soc. Am. A, 7(1), 47–65 (1990).
3. H. G. Kraus, "Huygens–Fresnel–Kirchhoff wavefront diffraction formulations – spherical waves and Gaussian laser beams: discussion," J. Opt. Soc. Am. A, 9(7), 1132–1134 (1992).
4. H. G. Kraus, "Characteristic pathlength Fresnel number equations and "ideal" lens wavefront Kirchhoff formulation: analysis of focused spherical wave diffraction fields," Opt. Laser Technol., submitted for publication (1992).
5. H. G. Kraus, "Characteristic pathlength Fresnel number equations and "ideal" lens wavefront Kirchhoff formulation: analysis of focused Gaussian beam diffraction fields," Opt. Laser Technol., 24(2), 77–87 (1992).
6. H. G. Kraus, "Finite element Fourier and Abbe transform methods for generalization of aperture function and geometry in Fraunhofer diffraction theory," Opt. Eng., 30(8), 1191–1207 (1991).
7. H. G. Kraus, "Finite element area and line integral transforms for generalization of aperture function and geometry in Kirchhoff scalar diffraction theory," Opt. Eng., accepted for publication (June 1, 1992).
8. J. J. Stamnes, Waves in Focal Regions, Adam Hilger, Boston (1986).
9. E. Hecht, Optics, 2nd Ed., Addison–Wesley (1987).
10. J. W. Goodman, Introduction to Fourier Optics, McGraw–Hill, New York (1968).
11. P. Lorrian and D. R. Corson, Electromagnetic Fields and Waves, 2nd Ed., W. H. Freeman and Co. (1970).

12. M. Born and E. Wolf, Principles of Optics, 6th Ed., Pergamon Press (1980).
13. E. Wolf and E. W. Marchand, "Comparison of the Kirchhoff and the Rayleigh–Sommerfeld Theories of Diffraction at an Aperture," J. Opt. Soc. Am., 54(5), 587–594 (1964).
14. A. Yariv, Quantum Electronics, 2nd Ed., John Wiley and Sons, New York (1975).
15. O. C. Zienkiewicz, The Finite Element Method, McGraw–Hill (1971).
16. J. Komrska, "Simple derivation of formulas for Fraunhofer diffraction at polygonal apertures," J. Opt. Soc. Am., 72(10), 1382–1384 (1982).
17. J. A. Hudson, "Fresnel–Kirchhoff diffraction in optical systems: an approximate computational algorithm," Appl. Opt., 23(14), 2292–2295 (1984).
18. A. E. Siegman, Lasers, University Science Books (1986).
19. J. S. Asvestas, "Line integrals and physical optics. Part I. The transformation of the solid–angle surface integral to a line integral," J. Opt. Soc. Am. A, 2(6), 891–895 (1985).
20. J. S. Asvestas, "Line integrals and physical optics. Part II. The conversion of the Kirchhoff surface integral to a line integral," J. Opt. Soc. Am. A, 2(6), 896–902 (1985).
21. A. Rubinowicz, "Die Beugungswelle in der Kirchhoffschen Theorie der Beugungserscheinungen," Ann. Physik Lpz., 53(12), 257–278 (1917).
22. K. Miyamoto and E. Wolf, "Generalization of the Maggi–Rubinowicz theory of the boundary diffraction wave – Part I," J. Opt. Soc. Am., 52(6), 615–625 (1962).
23. K. Miyamoto and E. Wolf, "Generalization of the Maggi–Rubinowicz theory of the boundary diffraction wave -- Part II," J. Opt. Soc. Am., 52(6), 626–637 (1962).
24. C. R. Wylie, Jr., Advanced Engineering Mathematics, 3rd Ed., McGraw–Hill (1966).

25. B. Carnahan, H. A. Luther, and J. O. Wilkes, Applied Numerical Methods, John Wiley & Sons Inc. (1969).
26. H. G. Kraus, "Finite element Fourier and Abbe transform methods for calculation of Fraunhofer diffraction patterns of geometrically complex apertures," presented at the 15th Congress of the International Commission for Optics, Garmisch-Partenkirchen, Bavaria, Federal Republic of Germany, August 5-10, 1990.

APPENDIX A

FESDIF (Finite Element Scalar Diffraction Theory) CODE USER'S MANUAL

TABLE OF CONTENTS

	<u>Page</u>
A.1. GENERAL DESCRIPTION	A-2
A.2. INPUT DATA BLOCKS	A-11

A.1. GENERAL DESCRIPTION

The FESDIF code has a large compliment of diffraction routines which collectively form a broad and powerful diffraction calculation capability for analysis and design of optical systems and instruments. Because of the many options available, they must be reviewed so that a decision can be made as to which one will be used. The information below is designed to guide the user of FESDIF through the process of deciding which input blocks will be necessary in the input data file to analyze a particular kind of problem.

Outlined below are the diffraction field calculation subroutines which have been incorporated into the FESDIF code. After the name of the subroutine there is a short description about what the subroutine does and the corresponding theoretical formulation used. These are divided into three sets of routines.

Set 1 is for calculating very-near, Fresnel, and Fraunhofer or far-field diffraction fields for circular apertures only. Spherical waves and Gaussian beams are covered. The circular apertures may contain a lens or lens system as long as the effective "ideal lens" parameters can be defined for the problem of concern. No mesh generators are necessary as the circular aperture meshes are generated internally in the calculation subroutines.

Set 2 is for calculating the Fraunhofer or far-field diffraction patterns for apertures with arbitrary geometries and arbitrary aperture functions. Focusing systems may be analyzed in which case the diffraction field calculated is that which will occur at the image plane or focal plane of the instrument. Mesh generators are used to define

the aperture geometry and these meshes are in turn used to define the aperture function.

Set 3 is for calculating very-near, Fresnel, and Fraunhofer or far-field diffraction fields for apertures with arbitrary geometries and arbitrary aperture functions. Mesh generators are used to define the aperture geometry and these meshes are in turn used to define the aperture function.

The input to FESDIF consists of a series of ordered input data blocks as described in the INPUT DATA BLOCKS section this appendix. At the end of each of the three sets of subroutines given below there is a list of the input data blocks which are required or optional to be used in conjunction with the corresponding set of subroutines described.

SET 1: SIMPLIFIED DIFFRACTION FIELD CALCULATION SUBROUTINES – CIRCULAR APERTURES ONLY

A. Incident Spherical Waves

subroutine fredifg

- o Calculates transverse diffraction field intensity
- o Uniform intensity incident spherical wave (on-axis)
- o Circular aperture
- o Kirchhoff aperture plane formulation

subroutine fredifz

- o Calculates axial diffraction field intensity
- o Uniform incident spherical wave (on-axis)
- o Circular aperture
- o Kirchhoff aperture plane formulation

B. Incident Spherical Waves Spherically Focused by Lens

subroutine fredfls

- o Calculates transverse diffraction field intensity
- o Uniform intensity incident spherical wave (on-axis)
- o Circular aperture lens
- o Spherically focused by lens
- o Kirchhoff wavefront formulation

subroutine fredflz

- o Calculates axial diffraction field intensity
- o Uniform intensity incident spherical wave (on-axis)
- o Circular aperture lens
- o Spherically focused by lens
- o Kirchhoff wavefront formulation

C. Incident Gaussian Laser Beams

subroutine lasdifg

- o Calculates transverse diffraction field intensity
- o Paraxial Gaussian laser beam (on-axis)
- o Circular aperture
- o Kirchhoff aperture plane formulation

subroutine lasdifz

- o Calculates axial diffraction field intensity
- o Paraxial Gaussian laser beam (on-axis)
- o Circular aperture
- o Kirchhoff aperture plane formulation

D. Incident Gaussian Laser Beams Spherically Focused by Lens

subroutine lasdfls

- o Calculates transverse diffraction field intensity
- o Paraxial Gaussian laser beam (on-axis)
- o Circular aperture lens
- o Spherically focused by lens
- o Kirchhoff wavefront formulation

subroutine lasdfiz

- o Calculates diffraction field intensity
- o Paraxial Gaussian laser beam (on-axis)
- o Circular aperture lens
- o Spherically focused by lens
- o Kirchhoff wavefront formulation

The following INPUT DATA BLOCKS are necessary to run the routines of the SET 1:

- o TITLE
- o DIFFRACTION FIELD PLOT (Optional)
- o SIMPLIFIED DIFFRACTION FIELD CALCULATION
- o END OF DATA

SET 2: GENERAL FRAUNHOFER (FAR-FIELD) AND IMAGE PLANE
(FOCAL PLANE) – ARBITRARY APERTURE GEOMETRIES AND
APERTURE FUNCTIONS

- A. Incident Spherical Waves (other waves can be defined through use of the aperture function)

subroutine ftrns

- o Calculates Fraunhofer diffraction field or
- o Calculates image plane diffraction field
- o Arbitrary aperture geometry based upon finite elements
- o Arbitrary aperture function based upon finite elements
- o Finite element Fraunhofer transform diffraction area integral formulation

subroutine abtrns

- o Calculates Fraunhofer diffraction field or
- o Calculates image plane diffraction field
- o Arbitrary aperture geometry based upon finite elements
- o Restricted aperture function based upon finite elements
- o Finite element Abbe transform diffraction line integral formulation

The following INPUT DATA BLOCKS, including only one of the three MESH GENERATORS listed, are necessary to run the routines of the SET 2:

- o TITLE
- o AUTOMATIC MESH GENERATOR
- o CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR
- o SCREEN MESH GENERATOR
- o MESH PLOTS (Optional)

- o AMPLITUDE OF APERTURE FUNCTION
- o PHASE OF APERTURE FUNCTION
- o DIFFRACTION FIELD PLOTS (Optional)
- o FRAUNHOFER DIFFRACTION FIELD CALCULATION
- o END OF DATA

SET 3: GENERAL VERY NEAR-FIELD AND FRESNEL DIFFRACTION FIELD CALCULATIONS (INCLUDING THE FRAUNHOFER FIELD) – ARBITRARY APERTURE GEOMETRIES AND APERTURE FUNCTIONS

A. Incident Spherical Waves

subroutine kirap1

- o Calculates transverse diffraction field intensity
- o Incident uniform intensity spherical wave (on- or off-axis)
- o Arbitrary aperture geometry based upon finite elements
- o Arbitrary aperture function based upon finite elements
- o Finite element Kirchhoff transform diffraction area integral formulation

B. Incident Gaussian Beams

subroutine kirap2

- o Calculates transverse diffraction field intensity
- o Incident paraxial Gaussian laser beam (on- or off-axis)
- o Arbitrary aperture geometry based upon finite elements
- o Aperture function based upon finite elements
- o Finite element Kirchhoff transform diffraction area integral formulation

C. Incident Spherical Waves

subroutine asvst1

- o Calculates transverse diffraction field intensity
- o Incident uniform intensity spherical wave (on- or off-axis)
- o Arbitrary aperture geometry based upon finite elements
- o Restricted aperture function based upon finite elements
- o Finite element transform Asvestas diffraction line integral formulation

D. Incident Gaussian Laser Beams

subroutine asvst2

- o Calculates axial diffraction field intensity
- o Incident paraxial Gaussian laser beam (on- or off-axis)
- o Arbitrary aperture geometry based upon finite elements
- o Restricted aperture function based upon finite elements
- o Finite element Asvestas transform diffraction line integral formulation.

The following INPUT DATA BLOCKS, including only one of the MESH GENERATORS, are necessary to run the routines of this SET 3:

- o TITLE
- o AUTOMATIC MESH GENERATOR
- o CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR
- o SCREEN MESH GENERATOR
- o MESH PLOTS (Optional)
- o AMPLITUDE OF APERTURE FUNCTION
- o PHASE OF APERTURE FUNCTION
- o DIFFRACTION FIELD PLOTS (Optional)
- o FRESNEL DIFFRACTION FIELD CALCULATION
- o END OF DATA

A.2. INPUT DATA BLOCKS

The following input data blocks are used in FESDIF. The required data blocks for the various options of FESDIF were described in Section A.1 of this appendix. Begin each block by using the title as given for that block. End each block with a blank line as indicated.

TITLE (Required)

A. First Title

Col. 1-80 First title card

B. Second Title

Col. 1-80 Second title card

C. Block Terminator Line

Insert a blank line to end block

AUTOMATIC MESH GENERATOR (Optional)

This general mesh generator creates 9-node isoparametric elements so that care must be taken to generate the proper number of nodes to allow for this.

A. Mesh Generation Controls Cards Format(3I5,4F10)

Col. 1-5 Maximum value of I in mesh, ≥ 3 and odd

Col. 6-10 Maximum value of J in mesh, ≥ 3 and odd

Col. 11-15 Number of material blocks to be assigned

Col. 16-25 Curvature modification parameter C_I

Col. 26-35 Curvature modification parameter C_J

Col. 36-45 Coordinate parameter S_I

Col. 46-55 Coordinate parameter S_J

B. Blank Card

Insert blank line

C. Line Segment Cards Format(2(2I5,2F10.0),/,2I5,2F10.0,I5)

Any reasonable combination of internal and external line segments which represent circular arcs, straight lines, or points in the x,y plane can be used to generate a finite element mesh. The line segments are defined by the location of the end points. Circular line segments are defined by one intermediate point, or the center, in addition to the end points. The order of the line segment cards is immaterial. Note from the report that the I J plane is the transposed plane.

Card 1

Col. 1-5	I coordinate of 1st point
Col. 6-10	J coordinate of 1st point
Col. 11-20	x coordinate of 1st point
Col. 21-30	y coordinate of 1st point
Col. 31-35	I coordinate of 2nd point
Col. 36-40	J coordinate of 2nd point
Col. 41-50	x coordinate of 2nd point
Col. 51-60	y coordinate of 2nd point

Card 2

- Col. 1-5 I coordinate of 3rd point
- Col. 6-10 J coordinate of 3rd point
- Col. 11-20 x coordinate of 3rd point
- Col. 21-30 y coordinate of 3rd point
- Col. 31-35 Line segment type indicator. If the number in Col. 35 is:
- 0 Point – input 1st set of I, J, x, y only
 - 1 Straight line – input 1st and 2nd sets of I, J, x, y
 - 3 Circular arc with mid-point of arc specified – input 1st and 3rd sets of I, J, x, y as end points of arc, and 2nd set of I, J, x, y as mid-point on arc.
 - 4 Circular arc with center of radius of curvature specified – input 1st and 2nd sets of I, J, x, y as end points of arc, and 3rd set of x, y coordinates as center of radius of curvature.

Straight or curved line segments in the x, y plane must correspond to either a straight line, I or J constant along a line, or a stepped diagonal segment, $ABS(\Delta J) = ABS(\Delta I)$, in the I, J plane. On diagonal segments, I is incremented first and the J is incremented.

D. Line Segment Terminators

Insert two blank lines.

E. Function Block Assignment Format(5I5)

A line is needed for each block specified. Each line assigns a material definition number to a block of elements defined by the I, J coordinates.

- Col. 1-5 Function identification number
- Col. 6-10 Minimum I
- Col. 11-15 Maximum I - $\Delta I \geq 2$ and even
- Col. 16-20 Minimum J
- Col. 21-25 Maximum J - $\Delta J \geq 2$ and even

F. Block Terminator Line

Insert a blank line to end block.

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

A. Mesh Generator Option Format(I5)

- Col. 1-5 1, use circular mesh generator
- 2, use elliptical mesh generator
- 3, use polygonal mesh generator
- 4, use circular with secondary aperture spider support
 mesh generator

B. Circular Mesh Generator Data (Mesh Generator Option 1)

Format(4I5,3F10.0)

- Col. 1-5 Number of angular divisions for node generation
- Col. 6-10 Number of radial divisions for node generation
- Col. 11-15 Discontinuous ring indicator
- 0, nodes not superimposed at ring interface
- 1, nodes superimposed at ring interface
- Col. 16-20 Number of circles surrounding the central circle
- Col. 21-30 Outer radius of circles
- Col. 31-40 Radial gap between mesh rings
- Col. 41-50 Radius of centers of surroundings circles

C. Elliptical Mesh Generator Data (Mesh Generator Option 2)

Format(2I5,/,3F10.0,/,2F10.0)

First Line

- Col. 1-5 Number of nodes generated angularly, must be an even number ≥ 4 .
- Col. 6-10 Number of nodes generated radially, must be an odd number ≥ 3 .

Second Line

- Col. 1-10 Major radius for right half of ellipse (-90° to 90°)
- Col. 11-20 Major radius for left half of ellipse (90° to 270°)
- Col. 21-30 Minor radius for entire ellipse (left and right halves must match)

Third Line

- Col. 1-10 x-coordinate of center of ellipse
- col. 11-20 y-coordinate of center of ellipse

D. Polygonal Aperture Mesh Generator (Mesh Generator Option 3)

Format(3I5,5X,F10.0,I5,5X,2F10.0)

- Col. 1-5 Number of angular divisions for nodes
- Col. 6-10 Number of radial divisions for nodes
- Col. 11-15 Number of equal length sides to polygon – must be an even number
- Col. 21-30 Radius of polygon from center to vertice
- Col. 31-35 Number of surrounding polygons
- Col. 41-50 Radius of center of surrounding polygons
- Col. 51-60 Angle in degrees of the position of the center of the first polygon, measured counter-clock-wise, from the center of the central polygon.

E. Circular Mesh with Secondary Obstruction/Spider Support Generator

(Input Mesh Generator Option 4) Format(4I5,5F10.0)

- Col. 1-5 Number of nodes in angular direction to be used to make up each sector of the apertures. Each sector is composed of the region between the spider supports.
- Col. 6-10 Number of nodes in radial direction to be used for all sectors.
- Col. 11-15 Number of sectors to be used in each circular aperture.
- Col. 16-20 Number of surrounding apertures identical to the central aperture. If this value is negative, the central aperture is removed from the overall multiple aperture mesh.
- Col. 21-30 Outer radius of unobstructed portion of apertures.
- Col. 31-40 Obscuration ratio of central secondary obstruction.
- Col. 41-50 Radius of the spider supports. A very large value of this radius essentially means that the spider supports are straight in the radial direction outward from the center of each aperture.
- Col. 51-60 Spider support thickness, expressed as a fraction of the outside diameter of each of the apertures.
- Col. 61-70 Radius of location of the centers of the apertures surrounding and identical to the central aperture.

F. Block Terminator Line

Input a blank line to terminate block.

SCREEN MESH GENERATOR

A. Screen Type Option Format(I5)

Col. 1-5 1, square aperture with a screen over it.

 2, circular aperture with a screen over it

B. Square Screen Parameters (Screen Type Option 1) Format(2I5,4F10.0)

Col.1-5 Number of elements in x-direction

Col.6-10 Number of elements in the y-direction

Col. 11-20 Maximum x-dimension from center

Col. 21-30 Maximum y-dimension from center

Col. 31-40 X-direction size of elements

Col. 41-50 Y-direction size of elements

C. Circular Screen Input Data (Screen Type Option 2)

Format(2I5,3F10.0)

Col. 1-5 Number of elements in x-direction at maximum radius

Col. 6-10 Number of elements in y-direction at maximum radius

Col. 11-20 Maximum radial dimension of aperture

Col. 21-30 X-direction size of elements

Col. 31-40 Y-direction size of elements

D. Block Terminator Line

Insert a blank line to terminate this block.

MESH PLOTS (Optional)

A. Plot Control Line Format(2I5)

Col. 1-5 Mesh plotting parameter (full mesh)
0, for no plot
1 , for full mesh plot which fills plot space
(usually distorted in x-y space)
2, full mesh plot with equal x-y coordinate axis
scaling

Col. 6-10 Mesh subplot indicator
0, for no mesh subplots
1, 2, 3, 4, or 5 for the number of mesh subplots
desired

These mesh subplots will be either distorted or
undistorted according to the entry in Cols. 1-5.

B. Mesh Plot Title Format(A60)

Col. 1-60 Title for full mesh plot of input line A.

C. Mesh Subplot Title(s) Format(A60)

Col. 1-60 Title for first mesh subplot of input line A.

Repeat this line for each mesh subplot of Col. 6-10, input line A.

D. Mesh Subplot Boundary Definition(s) (Use only if entry line A, Col. 6-10 $\neq$ 0) Format(4F10.0)

Col. 1-10 Minimum x-coordinate for first mesh subplot

Col. 11-20 Maximum x-coordinate for first mesh subplot

Col. 21-30 Minimum y-coordinate for first mesh subplot

Col. 31-40 Maximum y-coordinate for first mesh subplot

Repeat this line for each mesh subplot of Col. 6-10, input line A.

E. Block Terminator Line

Insert a blank line to terminate this block.

AMPLITUDE OF APERTURE FUNCTION (Required only if FRAUNHOFER and FRESNEL DIFFRACTION FIELD CALCULATION input blocks are used.)

- A. **Aperture Amplitude Function Option** All aperture amplitude functions are to be of the form $\mathcal{A} = \mathcal{A}(x,y)$ Format(I5)

Col. 1-5 1, constant aperture amplitude = 1.0

2, Gaussian aperture amplitude, $\mathcal{A} = ae^{-(bx^2 + cy^2)}$, where
a, b, and c, are user specified constants, and where
this function is centered on the optic-axis

3, Bessel function aperture amplitude

4, nodewise aperture amplitude specification

- B. **Gaussian Function Amplitude Parameters** (Option = 2 only)

Format(3F10.0)

Col. 1-10 Constant, a, of Gaussian amplitude function

Col. 11-20 Constant, b, of x^2 in Gaussian amplitude function

Col. 21-30 Constant, c, of y^2 in Gaussian amplitude function

- C. **Bessel Function Amplitude Parameters** (Option = 3 only) Format(XF10.0)

Col. 1-10 This option not currently available

- D. **Nodewise Amplitude Specification** (Option = 4 only)

Format(3I5,5X,F10.0)

Col. 1-5 First node number

Col. 6-10 Last node number

Col. 11-15 Node number increment

Col. 21-30 Amplitude value to be assigned to this sequence of nodes

This input line must be repeated until all node amplitudes of the aperture mesh have been specified. If the node number increment above = 0, then only the first node number is assigned the amplitude value.

E. Block Terminator Line

Insert a blank line to terminate this block.

PHASE OF APERTURE FUNCTION (Required only if FRAUNHOFER and FRESNEL DIFFRACTION FIELD CALCULATION input blocks are used.)

- A. **Aperture Phase Function Option** All aperture phase functions are to be of the form $e^{i\phi(x,y)}$ Format(I5)

Col. 1-5 1, constant aperture phase = 1.0

2, Gaussian function aperture phase,

$$e^{-\phi(bx^2 + cy^2)}, \text{ where } b \text{ and } c \text{ are user}$$

specified constants, and where this function is centered on the optic-axis

3, Bessel function aperture phase

4, nodewise aperture phase specification

- B. **Constant Phase Value** (Option = 1 only) Format(F10.0)

Col. 1-10 Constant value of phase in aperture (default = 0.0)

- C. **Gaussian Function Phase Parameters** (Option = 2 only)

Format(2F10.0)

Col. 1-10 Constant b of Gaussian phase aperture function

Col. 11-20 Constant c of Gaussian phase aperture function

- D. **Bessel Function Phase Parameters** (Option = 3 only) Format(XF10.0)

Col. 1-10 This option not currently available

- E. **Nodewise Phase Specification** (Option = 4)

Format(3I5,5X,F10.0)

Col. 1-5 First node number

Col. 6-10 Last node number

Col. 11-15 Node number increment

Col. 21-30 Phase value to be assigned to this sequence of nodes

This input line must be repeated until all node phases of the

aperture mesh have been specified. If the node number increment above
= 0, then only the first node number is assigned the phase value.

F. Block Terminator Line

Insert a blank line to terminate this block

DIFFRACTION FIELD PLOTS (Optional)

A. Diffraction Field Plots Format(I5)

Col. 1-5 0, no plot

- 1, A combined 3-D normalized diffraction intensity topology and isophote contour plot is to be created. This option is available for all diffraction field calculations except the axial diffraction field options of the SIMPLIFIED DIFFRACTION FIELD CALCULATION block.
- 2, A radial normalized diffraction intensity plot will be created. This option is available only for the full-field diffraction calculations of the SIMPLIFIED DIFFRACTION FIELD CALCULATION block.
- 3, Do both Option 1 and Option 2. This is possible only for the full-field diffraction calculations of the SIMPLIFIED DIFFRACTION FIELD CALCULATION block.
- 4, An axial normalized diffraction intensity plot will be created. This option is available only for the axial diffraction field calculation options of the SIMPLIFIED DIFFRACTION FIELD CALCULATION block.

B. Isophote Contour Values (Options 1 and 3 only) Format(5F10.0/5F10.0)

First Line

Col. 1-10 First isophote contour value
Col. 11-20 Second isophote contour value
Col. 21-30 Third isophote contour value
Col. 31-40 Fourth isophote contour value
Col. 41-50 Fifth isophote contour value

Second Line

Similar to columns 1-50, but for the sixth through the tenth isophote contour values

C. Block Terminator Line

Insert a blank line to terminate this block.

SIMPLIFIED DIFFRACTION FIELD CALCULATION (Optional)

This block is used to request that the diffraction field be calculated for an on-axis spherical wave or Gaussian beam diffracted by a circular aperture. No aperture function is allowed in these simplified formulations.

A. Problem Specification Format(2F10.0,3I5,F10.7,I5,F10.0,I5)

- Col. 1–10 Distance from aperture plane to observation plane. For axial diffraction field calculations, input 0.0 and refer to input line B below.
- Col. 11–20 Wavelength of incident optical radiation
- Col. 21–25 Diffraction formulation used. All non-focused fields must use the Kirchhoff aperture plane formulation and all focused fields use the Kirchhoff wavefront formulation.
- 1, Kirchhoff aperture plane – used for all non-focused diffraction field calculations
- 2, Kirchhoff wavefront – used for all focused diffraction field calculations
- Col. 26–30 Number of terms to be used in the Gaussian quadrature numerical integration. This parameter must be equal to 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, or 16.
- Col. 31–35 Number of sub-aperture blocks in each of the radial and angular directions of the circular aperture to be used for the numerical integration when full diffraction fields are being calculated; number of sub-aperture blocks in the radial direction of the circular aperture to be used for the numerical integration when axial diffraction fields are being calculated.

- Col. 36-45 Intensity factor to be used for normalization of the diffraction field for full diffraction field calculations. If = 0.0, the maximum field value is used to normalize the diffraction field for focused or non-focused full diffraction field calculations. For non-focused axial diffraction fields, the diffraction intensities are automatically normalized to the incident wave intensity in the center of the circular aperture. For focused axial diffraction fields, the diffraction intensities are automatically normalized to the wave intensity at focus. For the latter two cases, input 0.0 here.
- Col. 46-50 Incident wave type
- 1, spherical wave
 - 2, paraxial Gaussian laser beam
- Col. 51-60 Gaussian laser beam waist
- Col. 61-65 Problem type
- 1, non-focused full diffraction field
 - 2, non-focused axial diffraction field
 - 3, focused full diffraction field
 - 4, focused axial diffraction field

B. Problem Specification (Cont.) Format(5F10.0,I5)

Col. 1-10 Distance from spherical wave source or distance from paraxial Gaussian laser beam waist to the aperture plane

Col. 11-20 Radius of circular aperture

Col. 21-30 Beginning z' for axial diffraction field calculations

Col. 31-40 Ending z' for axial diffraction field calculations. The range from the beginning z' to the ending z' must include the axial image point $z' = s_1$. The intensity at this axial image point is used for normalization of the diffraction field for the entire z' interval requested.

Col. 41-50 Lens focal length or "ideal" lens equivalent focal length for focused diffraction field calculations.

Col. 51-55 Focused diffraction field Fresnel number indicator for full diffraction field calculations only. This parameter is automatically determined for focused axial diffraction field calculations.

-1, the requested z' location for which the full diffraction field is to be calculated is inside the image location, $z' = s_1$.

1, the requested z' location for which the full diffraction field is to be calculated is outside the image location, $z' = s_1$.

C. Observation Plane Parameters Format(2I5,F10.0,I5)

- Col. 1-5 Number of uniformly spaced points in the radial or axial direction for which the diffraction field is to be calculated.
- Col. 6-10 Number of points to be used in each coordinate direction of the two-dimensional diffraction field plots (Option 1 of the DIFFRACTION FIELD PLOT block only). This must be an odd number ≤ 127 .
- Col. 11-20 For full diffraction field calculations only, this is the maximum observation plane dimension as measured from the optic axis either in the x-coordinate or the y-coordinate direction. The observation region is assumed to be square with this dimension being equal to one-half the length of each side of the region. This dimension is determined internally by FESDIF for all focused diffraction field calculations; in which case enter 0.0.
- Col. 21-25 Non-normalized amplitude values print indicator. Note that a summary of the normalized diffraction intensities will automatically be printed and is not controllable using this parameter.
- 0, do not print non-normalized amplitude values
- 1, print non-normalized amplitude values

D. Block Terminator Line

Insert a blank line to terminate this block.

FRAUNHOFER DIFFRACTION FIELD CALCULATION (Optional)

This block is used to request that the Fraunhofer diffraction field be calculated for the aperture mesh, aperture amplitude function, and aperture phase function specified above.

A. Problem Specification Format(2F10.0,2I5,F10.0)

- Col. 1-10 Distance from aperture to observation plane or focal length of lens which is assumed to be in the aperture.
- Col. 11-20 Wavelength of incident optical radiation
- Col. 21-25 Type of diffraction integral:
1, Fourier area transform integral
2, Abbe line transform integral
- Col. 26-30 Number of terms to be used in Gaussian quadrature numerical integration. This parameter must be equal to 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, or 16.
- Col. 31-40 I_n , the value to be used to normalize the diffraction field. If this value is = 0.0, the maximum value of the diffraction field intensity is searched for and used to normalize the entire diffraction field.

B. Observation Plane Parameters Format(I5,5X,F10.0,5X,I5,2F10.0)

- Col. 1-5 Number of points to be calculated in x and y directions, centered about the optical axis. This must be an odd number ≤ 127 .
- Col. 11-20 Maximum observation plane dimension as measured from the optic axis either in the x-coordinate or the y-coordinate direction. The observation region is assumed to be square with this dimension being equal to one half the length of each side of the region.

Col. 26-30 Non-normalized amplitude values print indicator. Note that a summary of the normalized diffraction intensities will automatically be printed and is not controllable using this paramter.

0, do not print non-normalized amplitude values

1, print non-normalized amplitude values

Col. 31-40 X-coordinate of center of observation field.

Col. 41-50 Y-coordinate of center of observation field.

C. Block Terminator Line

Insert a blank line to terminate this block.

FRESNEL DIFFRACTION FIELD CALCULATION (Optional)

This block is used to request that the near field or the Fresnel diffraction field be calculated for the aperture mesh, aperture amplitude function, and aperture phase function specified above.

A. Problem Specification Format(2F10.0,2I5,F10.0,I5,F10.0,2I5)

Col. 1-10	Distance from aperture to observation plane
Col. 11-20	Wavelength of incident optical radiation
Col. 21-25	Type of diffraction integral:
1, Kirchhoff area transform integral
2, Kirchhoff line transform integral
Col. 26-30	Number of terms to be used in Gaussian quadrature numerical integration. This parameter must be equal to 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, or 16.
Col. 31-40	I_n , the value to be used to normalize the diffraction field. If this value is < 0 , the maximum value of the diffraction field intensity is searched for and used to normalize the entire diffraction field.
Col. 41-45	Incident wave type
1, Spherical
2, Gaussian beam
Col. 46-55	If the wave incident upon the aperture is in the form of a Gaussian beam, this parameter is the beam waist, ω_0 .
Col. 56-60	Number of blocks to be used for integrating the $\vec{W}(\vec{R}')$ vector potential integral for Gaussian beams.

Col. 61-65 Number of terms to be used in the Gaussian quadrature to integrate the $\vec{W}(\vec{R}')$ vector potential integral. This parameter must be equal to 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, or 16.

B. Location of Spherical Wave Source or Gaussian Beam Waist

Format(3F10.0)

Col. 1-10 X-coordinate of source or beam waist location

Col. 11-20 Y-coordinate of source or beam waist location

Col. 21-30 Z-coordinate of source or beam waist location

C. Observation Plane Parameters Format(I5,5X,F10.0,5X,I5,2F10.0)

Col. 1-5 Number of points to be calculated in x and y directions, centered about the optical axis. This must be an odd number ≤ 127 .

Col. 11-20 Maximum observation plane dimension as measured from the optic-axis either in the x-coordinate or the y-coordinate direction. The observation region is assumed to be square with this dimension being equal to one-half the length of each side of the region.

Col. 26-30 Non-normalized amplitude values print indicator. Note that a summary of the normalized diffraction intensities will automatically be printed and is not controllable using this parameter.

0, do not print non-normalized amplitude values

1, print non-normalized amplitude values

Col. 31-40 X-coordinate of center of observation field.

Col. 41-50 Y-coordinate of center of observation field.

D. Block Terminator Line

Insert a blank line to terminate this block

END OF DATA

This line terminates the input to FESDIF.

APPENDIX B
FESDIF (Finite Element Scalar Diffraction Theory)
EXAMPLE PROBLEMS

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION AND REQUIREMENTS FOR USING THE FESDIF CODE	B-5
EXAMPLE 1 Fresnel Diffraction/Incident Spherical Wave/Circular Aperture/Full Diffraction Field	B-8
EXAMPLE 2 Fresnel Diffraction/Incident Spherical Wave/Circular Aperture/Axial Diffraction Field	B-12
EXAMPLE 3 Fresnel Diffraction/Focused Incident Spherical Wave/Circular Aperture Lens/Full Diffraction Field	B-15
EXAMPLE 4 Fresnel Diffraction/Focused Incident Spherical Wave/Circular Aperture Lens/Axial Diffraction Field	B-19
EXAMPLE 5 Fresnel Diffraction/Incident Gaussian Laser Beam/Circular Aperture/Full Diffraction Field	B-22
EXAMPLE 6 Fresnel Diffraction/Incident Gaussian Laser Beam/Circular Aperture/Axial Diffraction Field	B-26
EXAMPLE 7 Fresnel Diffraction/Focused Incident Gaussian Laser Beam/Circular Aperture Lens/Full Diffraction Field	B-29
EXAMPLE 8 Fresnel Diffraction/Focused Incident Gaussian Laser Beam/Circular Aperture Lens/Axial Diffraction Field	B-33
EXAMPLE 9 Fraunhofer Diffraction/Incident Plane Wave/Square Aperture/Full Diffraction Field	B-36

EXAMPLE 10	Fraunhofer Diffraction/Incident Plane Wave/Circular Aperture/Full Diffraction Field	B-40
EXAMPLE 11	Fraunhofer Diffraction/Incident Plane Wave/Elliptical Aperture/Full Diffraction Field	B-44
EXAMPLE 12	Fraunhofer Diffraction/Incident Plane Wave/Array of Circular Apertures/Full Diffraction Field	B-48
EXAMPLE 13	Fraunhofer Diffraction/Incident Plane Wave/Array of Polygons/Full Diffraction Field	B-52
EXAMPLE 14	Fraunhofer Diffraction/Incident Plane Wave/Array of Circular Apertures each with Secondary Circular Obstruction and Curved Spider Supports/Full Diffraction Field	B-56
EXAMPLE 15	Fraunhofer Diffraction/Incident Plane Wave/Square Screen Aperture/Full Diffraction Field	B-60
EXAMPLE 16	Fraunhofer Diffraction/Incident Plane Wave/Circular Screen Aperture/Full Diffraction Field	B-64
EXAMPLE 17	Fraunhofer Diffraction/Incident Plane Wave/Synthetic Circular Aperture Array/Full Diffraction Field	B-68
EXAMPLE 18	Fraunhofer Diffraction/Incident Plane Wave/Circular Aperture with Secondary Circular Obstruction, Spider Supports, and Gaussian Function Apodization/Full Diffraction Field	B-72
EXAMPLE 19	Fraunhofer Diffraction/Incident Plane Wave/Five Rings Circular Aperture with Discontinuous Aperture Function/Full Diffraction Field	B-76

EXAMPLE 20	Fraunhofer Diffraction/Incident Plane Wave/Five Annular Rings Aperture with Continuously Varying Aperture Function/Full Diffraction Field	B-80
EXAMPLE 21	Fraunhofer Diffraction/Incident Plane Wave/Triangular Aperture/Full Diffraction Field	B-85
EXAMPLE 22	Fresnel Diffraction/Incident Spherical Wave/Square Aperture/Fresnel Number = 3/Full Diffraction Field	B-89
EXAMPLE 23	Fresnel Diffraction/Incident Spherical Wave/Circular Aperture/Fresnel Number = 4/Full Diffraction Field	B-93
EXAMPLE 24	Fresnel Diffraction/Incident Spherical Wave/Elliptical Aperture/Major Axis Fresnel Number = 4, Minor Axis Fresnel Number = 2/Full Diffraction Field	B-97
EXAMPLE 25	Fresnel Diffraction/Incident Off-Axis Gaussian Laser Beam/Circular Aperture/Fresnel Number = 2/Full Diffraction Field	B-101
EXAMPLE 26	Fresnel Diffraction/Incident Spherical Wave/Polygonal Aperture/Fresnel Number = 3/Full Diffraction Field	B-105
EXAMPLE 27	Fraunhofer Diffraction/Incident Spherical Wave/Nine-Circle Synthetic Aperture Array each with Secondary Obstructions and Spider Supports/Full Diffraction Field	B-109
EXAMPLE 28	Fresnel Diffraction/Incident Spherical Wave/Five Rings Circular Aperture with Discontinuous Aperture Function/Fresnel Number = 5/Full Diffraction Field	B-113

EXAMPLE 29 Fresnel Diffraction/Incident Off-Axis Gaussian Laser
 Beam/Five Annular Rings Circular Aperture with
 Ring Continuous Aperture Function/Fresnel
 Number = 2/Full Diffraction Field

B-117

APPENDIX B REFERENCES

B-121

INTRODUCTION AND REQUIREMENTS FOR USING THE FESDIF CODE

This appendix contains a series of examples which covers the basic range of capabilities of FESDIF to calculate diffraction fields beyond two-dimensional planar apertures. While 29 examples have been included, numerous additional options are possible by combining the various options of this code. The powerful mesh generators incorporated into FESDIF allow virtually any aperture shape to be modeled. When using FESDIF, it is recommended that you use the preceding TABLE OF CONTENTS to identify an example which is closest to the problem you want to analyze, study this example, and use it as a basis for building the input data file for your analysis.

Use of each of the fourteen diffraction calculation subroutines in FESDIF is illustrated at least once in the 29 examples of this appendix. Below is a listing of the subroutine used for each example. Also listed are any alternative subroutines which could have been used to solve the example. The line integrals are always faster computationally than the area integrals. Thus it is preferable to use the finite element Abbe or Asvestas line integral transformations if possible. In some cases only one subroutine has the specifics, power, or generality to solve a particular problem and in these cases no alternative is possible.

<u>Example Number</u>	<u>Subroutine Used</u>	<u>Alternative Subroutine(s)</u>
1	fredifg	kirap1, asvst1
2	fredifz	_____
3	fredfls	_____
4	fredflz	_____

<u>Example Number</u>	<u>Subroutine Used</u>	<u>Alternative Subroutine(s)</u>
5	lasdifg	kirap2, asvst2
6	lasdifz	_____
7	lasdfls	_____
8	lasdflz	_____
9	abtrns	ftrns
10	abtrns	ftrns
11	abtrns	ftrns
12	abtrns	ftrns
13	abtrns	ftrns
14	abtrns	ftrns
15	abtrns	ftrns
16	abtrns	ftrns
17	abtrns	ftrns
18	ftrns	_____
19	abtrns	ftrns
20	ftrns	_____
21	abtrns	ftrns
22	kirap1	asvst1
23	kirap1	asvst1, fredifg
24	asvst1	kirap1
25	kirap2	asvst2
26	kirap1	asvst1
27	asvst1	kirap1
28	asvst1	kirap1
29	kirap2	_____

The FESDIF computer code is run interactively. It was written for the Lahey F77L-EM/32 FORTRAN 77 compiler, Version 4.01. FESDIF also makes use of the PLOT88 graphics package by Plotworks Inc. It is necessary to compile this program using the Lahey FORTRAN compiler. Also the PLOT88 FORTRAN graphics library must be linked in with the FORTRAN library. Included on disk in Appendix C is a copy of the FORTRAN source file of FESDIF called fesdif.for, and a copy of a typical file for compiling, linking, and running FESDIF called run3p.bat. The source file is about 275 KB in length. Compilation will generate a file named fesdif.obj of about 300 KB in length, a file fesdif.sld of about 80 KB in length, and an executable file named fesdif.exp about 3.5 MB in length.

When FESDIF is uploaded into the extended memory capability of the Lahey compiler, FESDIF will interactively que the user for the name of your Input Data Deck file and ask you to name your Output File. All information which is printed to the screen interactively while the program runs is at the same time copied to the Output File you have specified. FESDIF informs the user of the primary subroutines which are being called and executed as a problem is being run. For example, the first subroutine called, which happens to be one that is always called, is indicated by the message "*****SUBROUTINE ECHO*****." Calls to subsequent primary routines are indicated by analogous messages. The plot files are set-up to be sent to an HP LaserJet Series II or compatible printer.

EXAMPLE 1 Fresnel Diffraction/Incident Spherical Wave/Circular Aperture/Full Diffraction Field

This example is of a spherical wave impinging upon a circular aperture. It utilizes the simplified diffraction calculation routines. The source, of wavelength $0.6328 \mu\text{m}$, is 0.01 m from the aperture. The diffraction field was calculated at a distance of $z' = 2.4613 \text{ mm}$ for which the pathlength Fresnel number $= 2$. The aperture has a diameter of $100 \mu\text{m}$. The next three pages give the input data listing and the resulting radial intensity and intensity topology/isophote contour plots. This example is Case 4 of Table 4 of the theoretical investigation by Kraus.¹

EXAMPLE 1 INPUT DATA LISTING

						(Column Number)											
0	1	2	3	4	5	6	7	0	1	2	3	4	5	6	7	0	1
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890
TITLE																	
FESDIF example - spherical wave/circular aperture																	
Units - m																	

DIFFRACTION FIELD PLOT

3

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

SIMPLIFIED DIFFRACTION FIELD CALCULATION

2.46134D-3	.6328D-6	1	4	16	0.0	1	0.0	1
0.01D0	50.D-6							
201	81	80.D-6	1					

END OF DATA

0	1	2	3	4	5	6	7	0	1	2	3	4	5	6	7	0	1
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

FESDIF Radial Diffraction Intensity Plot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 2 Fresnel Diffraction/Incident Spherical
Wave/Circular Aperture/Axial Diffraction Field**

This example is of the calculation of an axial diffraction field intensity. The incident spherical wave is of wavelength $0.6328 \mu\text{m}$ and is 0.01 m from the aperture. The aperture is a circle having a radius of $50 \mu\text{m}$. The axial diffraction field is calculated from $z' = 0.40980 \text{ mm}$ to $z' = 2.46134 \text{ mm}$ beyond the diffracting aperture. This z' range covers the pathlength Fresnel number range from 10 to 2 as z' increases from the aperture plane. The next two pages give the input data listing and the resulting diffraction intensity along the optic-axis. Note that this intensity is normalized to the value of the incident wave at the aperture, but assuming that the aperture is not in place, ie, at $z' = 0.0 \text{ m}$. This example is an axial diffraction calculation for Case 4, Table 4 of the theoretical investigation by Kraus.¹

EXAMPLE 2 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

TITLE

FESDIF example - spherical wave/circular aperture/axial diff. field

Units - m

DIFFRACTION FIELD PLOT

4

SIMPLIFIED DIFFRACTION FIELD CALCULATION

0.0D0	.6328D-6	1	4	8	0.0D0	1	0.0D0	2
0.01D0	50.D-6	.40980D-3	2.4613D-3					
201	0	0.0D0	1					

END OF DATA

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

FESDIF Axial Diffraction Intensity Plot

EXAMPLE 3 Fresnel Diffraction/Focused Incident Spherical Wave/Circular Aperture Lens/Full Diffraction Field

This example is of the calculation of the diffraction field for a focused spherical wave of wavelength $0.6328 \mu\text{m}$. The lens performing the focusing is of radius 3.45 mm and has a focal length of 3.9 m . The diffraction field is calculated at a distance of $z' = 2.757 \text{ m}$ beyond the diffracting aperture for which the pathlength Fresnel number is $= 2$. The next three pages give the input data listing, and the resulting normalized radial intensity and intensity topology/isophote contour plots for this example. This example is Case 11 of Table 1 by Kraus.²

EXAMPLE 3 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890							

TITLE

FESDIF example- focused spherical wave/circular lens

Units - m

DIFFRACTION FIELD PLOT

3

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

SIMPLIFIED DIFFRACTION FIELD CALCULATION

2.75700000	.6328D-6	2	4	16	0.0	1	0.0	3
1.0D12	3.45D-3	0.0	0.0	3.9D0	-1			
201	81	0.0	1					

END OF DATA

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890

FESDIF Radial Diffraction Intensity Plot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 4 Fresnel Diffraction/Focused Incident Spherical
Wave/Circular Aperture Lens/Axial Diffraction Field**

This example is of the calculation of the axial intensity field for a focused spherical wave of wavelength $0.6328 \mu\text{m}$. The lens has a focal length of 3.9 m and a radius of 1.1 mm. The axial diffraction intensity is calculated for $z' = 0.4 \text{ m}$ to $z' = 4.4 \text{ m}$ which covers the range from a pathlength Fresnel number greater than 4 to a distance of 0.5 m beyond the focal point of this lens. The next two pages give the input data listing and the resulting axial intensity for this problem. Note that the axial diffraction intensity has been normalized to its value at the back focal point of $z' = 3.9 \text{ m}$ which in this case is also the image plane. This example demonstrates the phenomenon of focal shift in which the maximum axial intensity occurs inside the image plane (ie, at a smaller z' value) rather than at the image plane. This result is very evident when inspecting the axial intensity plot. This example is Case 1 of Table 2 of Kraus.²

EXAMPLE 4 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - focused spherical wave/circular lens

Units - m

DIFFRACTION FIELD PLOT

4

SIMPLIFIED DIFFRACTION FIELD CALCULATION

0.0D0	.6328D-6	2	4	4	0.0	1	0.0	4
1.0D12	1.1D-3	0.4D0	4.4D0	3.9D0	0			
201	81	0.0	1					

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

FESDIF Axial Diffraction Intensity Plot

EXAMPLE 5 Fresnel Diffraction/Incident Gaussian
Laser Beam/Circular Aperture/Full Diffraction Field

The diffraction field at $z' = 33.3466$ mm beyond a circular aperture due to a Gaussian laser beam diffracted by a circular aperture is calculated in this example. The pathlength Fresnel number $= 10$ for this z' value. The diffracting circular aperture has a radius of .45474 mm. The beam waist is 1.0 m from the aperture. The beam has a wavelength of $0.6328 \mu\text{m}$ and a beam waist of 0.4 mm. At the aperture this Gaussian beam is truncated at the $1/e = 0.367879$ intensity level. Therefore the intensity variation will show up in the resulting diffraction pattern as being modified from that for a Fresnel number $= 10$ due to a uniform intensity wave. The next three pages give the input data listing, and the radial and topology intensity/isophote plots for this example. This example is Case 1 of Table 8 by Kraus.³

EXAMPLE 5 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890							

TITLE

FESDIF example - Gaussian beam/circular aperture

Units - m

DIFFRACTION FIELD PLOT

3

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

SIMPLIFIED DIFFRACTION FIELD CALCULATION

33.3466D-3	.6328D-6	1	16	16	0.0	2	0.4D-3	1
1.0D0	.45474D-3		0.0	0.0		0.0	0	
501	81	0.0	1					

END OF DATA

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890

FESDIF Radial Diffraction Intensity Plot

FESDIF Intensity/Isophote Contour Plot

EXAMPLE 6 Fresnel Diffraction/Incident Gaussian
Laser Beam/Circular Aperture/Axial Diffraction Field

The axial diffraction field beyond a circular aperture due to an incident Gaussian laser beam is calculated in this example. The aperture has a diameter of $250\text{ }\mu\text{m}$. The beam is focused through a spatial filter such that a waist of $5.96\text{ }\mu\text{m}$ is formed. The diffracting aperture is 38.9714 mm from this waist. The beam has a wavelength of $0.6328\text{ }\mu\text{m}$. The diffraction field is calculated along the optic-axis from $z' = 2.5\text{ mm}$ to $z' = 10.5\text{ mm}$ which covers a range of pathlength Fresnel numbers from greater than 10 to less than 3 as z' increases. The next two pages give the input data listing and the resulting normalized axial diffraction field intensity for this example. Note that the axial diffraction field intensity has been normalized to the on-axis beam intensity at $z' = 0.0\text{ m}$ assuming that the aperture is not in place. Results of this example for integer Fresnel number locations along the optic-axis closely match the experimental results for the $250\text{ }\mu\text{m}$ diameter aperture by Struckhoff.⁴

EXAMPLE 6 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890							

TITLE

FESDIF exmaple - Gaussian beam/circular aperture/axial

Units - m

DIFFRACTION FIELD PLOT

4

SIMPLIFIED DIFFRACTION FIELD CALCULATION

0.0D0	.6328D-6	1	16	16	0.0D0	2	5.96D-6	2
38.97D-3	125.D-6	2.500D-3	10.500D-3		0.0D0		0	
1001	0	0.0D0	0					

END OF DATA

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890

FESDIF Axial Diffraction Intensity Plot

**EXAMPLE 7 Fresnel Diffraction/Focused Incident Gaussian
Laser Beam/Circular Aperture Lens/Full Diffraction Field**

This example is of the diffraction due to a Gaussian laser beam focused by a circular aperture lens. The lens has a focal length of 0.3 m and a radius of 1.4115 mm. The beam has a waist of 0.106 mm and a wavelength of 0.6328 μm . This waist is located at 1.308 m from the aperture. The diffraction field is calculated at $z' = 0.3$ m which, in this case, is inside the image plane. The image plane is located at 0.389075 m. Therefore $n_f = -1$. The pathlength Fresnel number for this z' value is 2.403. The input data listing, the normalized radial intensity diffraction plot, and the normalized intensity topology/isophote contour plot are given on the next three pages. This example is Case 9 of Table 1 by Kraus.⁵

EXAMPLE 7 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

TITLE

FESDIF example - Gaussian beam/circular aperture/focused

Units - m

DIFFRACTION FIELD PLOT

3

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

SIMPLIFIED DIFFRACTION FIELD CALCULATION

0.3	.6328D-6	2	16	16	0.0D0	2	0.106D-3	3
1.308D0	1.4115D-3	0.0D0	0.0D0	0.0D0	0.3D0	-1		
501	81	0.0D0	1					

END OF DATA

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

FESDIF Radial Diffraction Intensity Plot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 8 Fresnel Diffraction/Focused Incident Gaussian
Laser Beam/Circular Aperture Lens/Axial Diffraction Field**

This example is of the calculation of the axial diffraction field for a Gaussian beam truncated at the $1/e^{0.25}$ intensity level by a circular aperture focusing lens. The lens has a 0.8796 mm radius and a focal length of 0.3 m. The beam has a waist of 0.106 mm and a wavelength of 0.6328 μm . This waist is located at 1.308 m from the aperture. The axial intensity field was calculated from $z' = 0.150$ to $z' = 0.400$. This z' range extends from an inside pathlength Fresnel number of greater than 4 to beyond the image plane. The image plane for this example occurs at 0.389075 m. The next two pages give the input data listing and the resulting axial diffraction intensity field. Note that this axial diffraction field has been normalized to the intensity value at the image plane, $z' = 0.389075$ m. This example demonstrates the phenomenon of focal shift for which the maximum axial intensity occurs inside the focal plane (ie, at a smaller z' value) rather than at the focal plane. Inspection of the axial intensity diffraction plot readily shows that the maximum axial intensity occurs inside $z' = 0.389075$ m. This is one of the three beam truncation level cases of Figure 8 by Kraus.⁵

EXAMPLE 8 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example -- Gaussian beam/circular aperture/focused

Units - m

DIFFRACTION FIELD PLOT

4

SIMPLIFIED DIFFRACTION FIELD CALCULATION

0.0	.6328D-6	2	16	16	0.0D0	2	0.106D-3	4
1.308D0	0.8796D-3	0.150D0	0.400D0	0.3D0	0			
501	0	0.0D0	1					

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

FESDIF Axial Diffraction Intensity Plot

**EXAMPLE 9 Fraunhofer Diffraction/Incident Plane
Wave/Square Aperture/Full Diffraction Field**

This example is of diffraction by a square aperture 1.0 mm on a side. The diffraction field is calculated 10.0 m beyond the aperture. The incident wave is planar, of uniform intensity, and of wavelength $0.6328\ \mu\text{m}$. The next three pages give the input data listing, the finite element mesh of the square aperture, and the resulting normalized diffraction intensity topology/isophote contour plot for this example. The results accurately match the analytical results given in the text by Hecht.⁶ This example is Example 2 by Kraus⁷ except that the scale has been changed and a non-focusing diffraction field instead of a focusing field has been calculated.

EXAMPLE 9 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example problem - square aperture

Units - m

AUTOMESH

9	9	1	0.0D0	0.0D0	0.0D0	0.0D0
0						
1	1	-0.5D-3	-0.5D-3	9	1	0.5D-3 -0.5D-3
				1		
9	1	0.5D-3	-0.5D-3	9	9	0.5D-3 0.5D-3
				1		
9	9	0.5D-3	0.5D-3	1	9	-0.5D-3 0.5D-3
				1		
1	9	-0.5D-3	0.5D-3	1	1	-0.5D-3 -0.5D-3
				1		

1	1	9	1	9
---	---	---	---	---

MESH PLOTS

2	1
---	---

Aperture Mesh Plot

Test Mesh Subplot

-0.6D-3	0.6D-3	-0.6D-3	0.6D-3
---------	--------	---------	--------

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

1.0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	40.0D-3		1	

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

EXAMPLE 10 Fraunhofer Diffraction/Incident Plane Wave/Circular Aperture/Full Diffraction Field

This example is of the diffraction of a uniform intensity wave by a circular aperture. The aperture is 1.0 mm in diameter. The wavelength of the incident light is $0.6328\ \mu\text{m}$. The diffraction field is calculated 10.0 m beyond the diffracting aperture. The next three pages give the input data listing, a plot of the finite element mesh of the aperture, and the resulting normalized diffraction intensity topology/isophote contour plot for this example. Note in the mesh plot that twelve biquadratic isoparametric finite elements were required in the angular direction to accurately map the geometry of this aperture to four or five decimal places of accuracy. Failure to insure that the geometry of the aperture is accurately defined will result in errors in the computed values of the diffraction field which may be very difficult to detect for more complicated aperture geometries. An analogous statement may be made when aperture functions are employed, ie, always use enough elements to define accurately the function being defined. The result of this example accurately matches the analytical results given in the text by Hecht.⁶ This example is Example 2 by Kraus⁷ except that the scale has been changed and a non-focusing diffraction field instead of a focusing field has been calculated.

EXAMPLE 10 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
123456789012345678901234567890123456789012345678901234567890							

TITLE
FESDIF example - circular aperture
UNITS: m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

1							
24	9	0	0	0.5D-3			

MESH PLOTS

2	1						
Aperture Mesh Plot							
Test Mesh Subplot							
-0.6D-3	0.6D-3	-0.6D-3	0.6D-3				

AMPLITUDE OF APERTURE FUNCTION

1							
---	--	--	--	--	--	--	--

PHASE OF APERTURE FUNCTION

1	0.0						
---	-----	--	--	--	--	--	--

DIFFRACTION FIELD PLOT

1							
0.001	0.101	0.201	0.301	0.401			
0.501	0.601	0.701	0.801	0.901			

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.DO	.6328D-6	2	4	.0000D-13			
81	40.0D-3	1					

END OF DATA

0	1	2	3	4	5	6	7
123456789012345678901234567890123456789012345678901234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 11 Fraunhofer Diffraction/Incident Plane Wave/
Elliptical Aperture/Full Diffraction Field**

The aperture for this example is an ellipse having a major axis of 1.0 mm and a minor axis of 0.5 mm. The incident uniform intensity plane wave has a wavelength of 0.6328 μm . The diffraction field is calculated 10 m beyond the aperture plane. The next three pages give the input data listing, the aperture mesh plot, and the normalized intensity topology/isophote contour plot for this example. This example is Example 3 by Kraus⁷ except that the scale has been changed and a non-focusing diffraction field instead of a focusing field has been calculated.

EXAMPLE 11 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - elliptical aperture

UNITS: m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

2			
48	17		
0.5D-3	0.5D-3	0.25D-3	
0.0D0	0.0D0		

MESH PLOTS

2	1		
Aperture Mesh Plot			
Test Mesh Subplot			
-0.6D-3	0.6D-3	-0.3D-3	0.3D-3

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	40.0D-3		1	

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 12 Fraunhofer Diffraction/Incident Plane
Wave/Array of Circular Apertures/Full Diffraction Field**

This example is typical of what might be considered in a multiple-aperture telescope design. The aperture consists of an array of seven circular apertures, each 1.0 m in diameter. The apertures surrounding the central aperture are centered on a 1.0 m radius. The incident uniform intensity wave is planar and has a wavelength of 0.6328 μm . The focal length of the multiple-aperture telescope is 10 m. The next three pages give the input data listing, the multiple-aperture mesh plot, and the normalized intensity topology/isophote contour plot for this example. This is Example 4 by Kraus.⁷

EXAMPLE 12 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE
FESDIF example - array of circular apertures
UNITS: - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

1						
24	9	0	6	0.5D0	0.0D0	1.0D0

MESH PLOTS

2	1
Aperture Mesh Plot	
Test Mesh Subplot	
-1.6D0	1.6D0
-1.6D0	1.6D0

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER

10.D0	.6328D-6	2	4	.0000D-13
81	40.0D-6		1	

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 13 Fraunhofer Diffraction/Incident Plane Wave/
Array of Polygons/Full Diffraction Field**

This example is representative of a segmented mirror telescope design. The aperture consists of an array of seven adjacent hexagonal mirrors, each of which can be inscribed within a 1.0 m diameter circle. The uniform intensity incident wave is planar and has a wavelength of $0.6328 \mu\text{m}$. The focal length of the system of apertures is 10.0 m. The next three pages give the input data listing, the multiple-aperture mesh plot, and the normalized intensity topology/isophote contour plot for this example. This is Example 5 by Kraus.⁷

EXAMPLE 13 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - array of polygons

UNITS: - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

3							
24	9	6	0.5D0	6	8.66025D-1	30.D0	

MESH PLOTS

2	1				
Aperture Mesh Plot					
Test Mesh Subplot					
-1.5D0	1.5D0	-1.5D0	1.5D0		

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	40.0D-6	1		

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 14 Fraunhofer Diffraction/Incident Planar Wave/Array
of Circular Apertures each with Secondary Circular Obstruction
and Curved Spider Supports/Full Diffraction Field**

This example begins to illustrate the real power of these finite element based diffraction theory methods. The next page gives a listing of the input data listing for this example. The finite element aperture array mesh plot is shown on the second page. The outer diameter of each aperture of the array is equal to 1.0 m. The central obstruction ratio for each aperture is equal to 0.3. The secondary mirror spider support width is 0.02 times the individual aperture outer diameter. The spiders are equally spaced within each aperture at 120-deg angular increments and show as small gaps between elements in the angular direction around each aperture. Each spider support has an angular coverage of 60 degrees about its center of curvature. The radius associated with the curved spider supports is 0.25 m. Curved spider supports are designed to eliminate the diffraction spikes which otherwise result from the presence of spider supports.^{8,9} The focal length of this system of apertures is 10.0 m. The uniform intensity incident light was of wavelength 0.6328 μm . The third page shows the resulting normalized diffraction intensity topology/isophote contour plot for this example. This is Example 6 by Kraus.⁷

EXAMPLE 14 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - array of circles w/ 2ndry obstr. & spiders

UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

4							
27	9	3	6	0.5D0	0.3	0.25D0	0.02 1.0D0

MESH PLOTS

2	1		
Aperture Mesh Plot			
Test Mesh Subplot			
-1.6D0	1.6D0	-1.6D0	1.6D0

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	40.0D-6		1	

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 15 Fraunhofer Diffraction/Incident Plane Wave/Square
Screen Aperture/Full Diffraction Field**

This example illustrates the diffraction effects of having a screen put in front of a square aperture. The uniform intensity incident light was of wavelength $0.6328 \mu\text{m}$. The input data listing and the finite element mesh plot are given on the next two pages. This screen is represented by the 1.0 mm crossed lines, whereas the remaining unobstructed area of the aperture is represented by the squares which are 4.0 mm on each side. Note that each of these squares was defined using a single biquadratic element. This aperture was considered to be the objective of a focusing instrument which has a focal length of 10.0 m. The third page presents the normalized diffraction intensity topology/isophote results for this example. This is Example 7 by Kraus,⁷ but with an aperture size $1/20$ that used originally.

EXAMPLE 15 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE
FESDIF example - square screen aperture
UNITS - m

SCREEN MESH GENERATOR

1							
10	10	0.25D-1	0.25D-1	0.4D-2	0.4D-2		

MESH PLOTS

2	1						
Aperture Mesh Plot							
Test Mesh Subplot							
-0.3D-1	0.3D-1	-0.3D-1	0.3D-1				

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

1.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	80.0D-5	1		

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 16 Fraunhofer Diffraction/Incident Plane Wave/Circular
Screen Aperture/Full Diffraction Field**

This example studies the diffraction effects of having a screen in front of a circular aperture. A uniform intensity plane wave of wavelength $0.6328\ \mu\text{m}$ was considered to be incident upon this aperture. The next page gives the input data listing for this example. The finite element mesh of the aperture used for this example is on the second page. This screen is represented by the 1.0 mm crossed lines, whereas the remaining unobstructed area of the aperture is represented by the squares which are 4.0 mm on each side, except those elements which are truncated at the edge of the circular aperture. A single element is still capable of defining each truncated square, except at 45-, 135-, 225-, and 315-deg rotation from the positive x-axis. In these cases, the truncation by the edge of the outer circular aperture edge resulted in a five-sided region which had to be divided into two biquadratic elements to be defined accurately. This is done automatically when using the SCREEN MESH GENERATOR for a circular aperture. This aperture was considered to be the objective of a focusing instrument which has a focal length of 10.0 m. The normalized intensity topology/isophote contour plot is given on the third page. This is Example 8 by Kraus,⁷ but with an aperture size 1/20 that used originally.

EXAMPLE 16 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE
FESDIF example - circular screen aperture
UNITS - m

SCREEN MESH GENERATOR

2				
10	10	0.25D-1	0.4D-2	0.4D-2

MESH PLOTS

2	1			
Aperture Mesh Plot				
Test Mesh Subplot				
-0.3D-1	0.3D-1	-0.3D-1	0.3D-1	

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

1.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	80.0D-5	1		

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 17 Fraunhofer Diffraction/Incident Plane Wave/Synthetic
Circular Aperture Array/Full Diffraction Field**

Eight circular apertures, each 1.0 m in diameter are equally spaced in the angular direction with centers at a 2.0 m radius to form the synthetic aperture array of this example. The incident wave was considered have uniform intensity and a wavelength of $0.6328 \mu\text{m}$. The focal length of this multiple aperture system was taken as 10.0 m. The input data listing is on the next page and the finite element mesh plot for this multiple aperture system is given on the second page. The normalized diffraction intensity/isophote contour plot for this configuration is given on the third page. This is Example 9 by Kraus.⁷

EXAMPLE 17 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - synthetic circular aperture array

UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

4							
27	9	3	-8	0.5D0	0.0D0	1.0D4	0.0D0 2.0D0

MESH PLOTS

2	1
Aperture Mesh Plot	
Test Mesh Subplot	
-2.6D0	2.6D0 -2.6D0 2.6D0

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	40.0D-6	1		

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

Example 18 Fraunhofer Diffraction/Incident Plane Wave/Circular
Aperture with Secondary Circular Obstruction, Spider Supports,
and Gaussian Function Apodization/Full Diffraction Field

It is known that the diffraction spikes caused by secondary mirror spider supports can be mostly eliminated by curving them as was done in Example 14 of this Appendix B. This example attempts to accomplish the same elimination of the spider-support-induced diffraction spikes using Gaussian function amplitude apodization. The input data listing for this example is on the next page and following that is the finite element mesh plot of the aperture used. The aperture is 1.0 m in diameter and has a focal length of 10.0 m. The central obstruction, representing the secondary mirror of a folded optical path telescope, is 0.3 of the aperture diameter. There are four straight spiders supporting the secondary mirror, each 0.02 m in thickness. The Gaussian amplitude function has a value of 1.0 in the center portion of the aperture (which is obstructed by the secondary mirror) and a value of e^{-3} at the outer edge of the aperture. The incident uniform intensity wave is considered to be planar and have a wavelength of $0.6328 \mu\text{m}$. The third page is a plot of the resulting normalized intensity topology/isophote contour diffraction field for this example. Note that the diffraction spikes have virtually been eliminated by this apodization. However, a secondary circular diffraction ring does remain. This example is Example 10 by Kraus.⁷

EXAMPLE 18 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - circular aperture, 2ndry obstr, Gaussian apodization

UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

4							
36	9	4	0	0.5D0	0.3D0	1.0D3	0.02D0 0.0D-3

MESH PLOTS

2	1		
Aperture Mesh Plot			
Test Mesh Subplot			
-0.6D0	0.6D0	-0.6D0	0.6D0

AMPLITUDE OF APERTURE FUNCTION

2		
1.0D0	6.0D0	6.0D0

PHASE OF APERTURE FUNCTION

1	
0.0D0	

DIFFRACTION FIELD PLOT

1				
0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	1	4 .0000D-13
81	40.0D-6	1	

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

EXAMPLE 19 Fraunhofer Diffraction/Incident Plane Wave/Five Rings
Circular Aperture with Discontinuous Aperture
Function/Full Diffraction Field

The aperture for this example consists of five concentric rings, each 0.2 mm in radial thickness, which overall form a circular aperture of 1.0 mm in diameter. The next two pages give the input data listing and the finite element mesh of this aperture. The five rings of this aperture represented by the five rings in the finite element mesh have constant-aperture amplitudes of 1.0, 0.8, 0.6, 0.4, and 0.2, in sequence beginning with the innermost ring. A duplicate set of nodes exists at the radius common to any two rings of elements, thus permitting this discontinuous or step-changing amplitude function. The incident wave is uniform in intensity and of wavelength $0.6328 \mu\text{m}$. The diffraction field is calculated 10.0 m beyond the plane of this aperture. The third page gives the resulting normalized intensity topology/isophote contour plot for this example. This example is Example 11 by Kraus⁷ except that the scale has been changed and a non-focusing diffraction field instead of a focusing field has been calculated.

EXAMPLE 19 INPUT DATA LISTING

(Column Number)

```

0          1          2          3          4          5          6          7
123456789012345678901234567890123456789012345678901234567890
TITLE
FESDIF example - five rings circular aperture, discont. aper. func.
UNITS - m

```

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

```

1
24 15 1 0 0.5D-3 0.00D-3 0.0D-3

```

MESH PLOTS

```

2 1
Aperture Mesh Plot
Test Mesh Subplot
-0.6D-3 0.6D-3 -0.6D-3 0.6D-3

```

AMPLITUDE OF APERTURE FUNCTION

```

4
1 346 15 1.0
2 347 15 1.0
3 348 15 1.0
4 349 15 0.8
5 350 15 0.8
6 351 15 0.8
7 352 15 0.6
8 353 15 0.6
9 354 15 0.6
10 355 15 0.4
11 356 15 0.4
12 357 15 0.4
13 358 15 0.2
14 359 15 0.2
15 360 15 0.2

```

PHASE OF APERTURE FUNCTION

```

1
0.0D0

```

DIFFRACTION FIELD PLOT

```

1
0.001 0.101 0.201 0.301 0.401
0.501 0.601 0.701 0.801 0.901

```

FRAUNHOFER DIFFRACTION FIELD CALCULATIONS

```

10.D0 .6328D-6 2 4 .0000D-13
81 40.0D-3 1

```

END OF DATA

```

0          1          2          3          4          5          6          7
123456789012345678901234567890123456789012345678901234567890

```

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 20 Fraunhofer Diffraction/Incident Plane Wave/
Five Annular Rings Aperture with Continuously Varying Aperture
Function/Full Diffraction Field**

The aperture for this example consists of five annular rings, each 0.0667 mm in radial thickness with a 0.0333 mm gap between rings, forming an overall diameter of 1.0 mm. The next two pages give the input data listing and the finite element mesh of this aperture. The five rings of this aperture represented by the five rings in the finite element mesh have a linearly continuous phase variation of $2\pi/14$ across each gap between the rings. There is a $\pi/14$ phase shift across each gap between rings. The center of the central disk has zero phase shift so that the outer edge of the central ring has $2\pi/14$ phase shift. The second ring begins with $3\pi/14$ phase shift at its inner radius and ends with $5\pi/14$ phase shift at its outer radius. The remaining rings and gaps proceed similarly until the phase shift at the outer edge of the outer ring is π . The incident wave is planar, of uniform intensity, and of wavelength $0.6328 \mu\text{m}$. The diffraction field was calculated 10.0 m beyond this aperture. The resulting normalized intensity topology/isophote contour plot is given on the third page. Note that this intensity field is representative of a Fresnel diffraction pattern with a pathlength Fresnel number greater than one. In this case, the phase plate function introduces a $\lambda/2$ phase shift in this difference, while the radial extent of the aperture introduces an additional $(a^2/\lambda R)(\lambda/2) = 0.0395(\lambda/2)$ phase shift which results in a pathlength Fresnel number of 1.0395. In other words, this diffraction pattern is representative of that which would exist for this aperture in the Fresnel diffraction region (ie, closer than 10.0 m) if no phase variation were present in the aperture. This example is Example 12 by

Kraus⁷ except that the scale has been changed and a non-focusing diffraction field instead of a focusing field has been calculated.

EXAMPLE 20 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

TITLE
FESDIF example - five annular rings aperture w/ cont. var. aper. func.
UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

1							
24	15	1	0	0.5D-3	.33333D-4	0.0D-3	

MESH PLOTS

2	1						
Aperture Mesh Plot							
Test Mesh Subplot							
-0.6D-3	0.6D-3	-0.6D-3	0.6D-3				

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

4				
1	346	15	0.00000000	
2	347	15	0.22439947	
3	348	15	0.44879895	
4	349	15	0.67319842	
5	350	15	0.89759790	
6	351	15	1.12199737	
7	352	15	1.34639685	
8	353	15	1.57079632	
9	354	15	1.79519580	
10	355	15	2.01959528	
11	356	15	2.24399475	
12	357	15	2.46839422	
13	358	15	2.69279370	
14	359	15	2.91719317	
15	360	15	3.14159265	

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	1	4	.0000D-13
81	40.0D-3	1		

END OF DATA

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 21 Fraunhofer Diffraction/Incident Plane Wave/
Triangular Aperture/Full Diffraction Field**

The aperture for this example is simply an equilateral triangle 1.0 mm on a side. This example was included to demonstrate that non-circular based apertures are also well within the capability of FESDIF. The input data listing and the finite element plot of this aperture are given on the next two pages. The incident uniform intensity plane wave is $0.6328 \mu\text{m}$ in wavelength. The diffraction field was calculated 10.0 m beyond the diffracting aperture. The third page is a plot of the normalized intensity topology/isophote contour diffraction results for this example.

EXAMPLE 21 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE
FESDIF example - triangular aperture
UNITS - m

AUTOMESH

3	3	1					
0							
1	1	-0.5D-3	-.28868D-3	3	1	0.5D-3	-.28868D-3
				1			
3	1	0.5D-3	-.28868D-3	3	3	0.0D-0	.57735D-3
				1			
3	3	0.0D-0	.57735D-3	1	3	-.5001D-3	-.28868D-3
				1			
1	3	-.5001D-3	-.28868D-3	1	1	-0.5D-3	-.28868D-3
				1			

1	1	3	1	3
---	---	---	---	---

MESH PLOTS

2	1
Aperutre Mesh Plot	
Test Mesh Subplot	
-0.6D-3	0.6D-3
-0.6D-3	0.6D-3

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRAUNHOFER DIFFRACTION FIELD CALCULATION

10.D0	.6328D-6	2	4	.0000D-13
81	40.0D-3		1	

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 22 Fresnel Diffraction/Incident Spherical
Wave/Square Aperture/Fresnel Number = 3/Full Diffraction Field**

The aperture for this example is a square 1.0 mm on a side. The source is a uniform intensity spherical wave source of wavelength $0.6328 \mu\text{m}$ centered 10.0 m from the aperture. The input data listing and the finite element mesh plot for this example are on the next two pages. The diffraction field shown on the third page represents a pathlength Fresnel number = 3 which occurs at $z' = 131.44673 \text{ mm}$ beyond the aperture. These results have been compared to the computational results by Kathuria¹¹ with excellent agreement. This is Example 2 by Kraus.¹⁰

EXAMPLE 22 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - spherical wave, square aperture, Fr = 3

UNITS - m

AUTOMESH

33	33	1	0.0	0.0	0.0	0.0
0						
1	1	-0.5D-3	-0.5D-3	33	1	0.5D-3 -0.5D-3
				1		
33	1	0.5D-3	-0.5D-3	33	33	0.5D-3 0.5D-3
				1		
33	33	0.5D-3	0.5D-3	1	33	-0.5D-3 0.5D-3
				1		
1	33	-0.5D-3	0.5D-3	1	1	-0.5D-3 -0.5D-3
				1		

1 1 33 1 33

MESH PLOTS

2 1

Square Aperture Mesh

Square Aperture Submesh

-0.6D-3 0.6D-3 -0.6D-3 0.6D-3

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRESNEL DIFFRACTION FIELD CALCULATION

.13344673	.6328D-6	1	4	.0000D-13	1	0.0D0	0	0
0.0D0	0.0D0	10.D0						
81	1.0D-3	1	0.0D0	0.0D0				

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Square Aperture Submesh

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 23 Fresnel Diffraction/Incident Spherical
Wave/Circular Aperture/Fresnel Number = 4/Full Diffraction Field**

This example is of a diffracting aperture 1.0 mm in diameter. A uniform intensity spherical wave source of wavelength $0.6328 \mu\text{m}$ centered 10.0 m from the aperture was used. The diffraction field was calculated for a pathlength Fresnel number = 4 which can be found to occur at $z' = 99.75197 \text{ mm}$ from the aperture plane. The next two pages give the input data listing for this problem and a plot of the finite element mesh of this aperture. The third page shows the normalized intensity topology/isophote contour plot of the resulting diffraction field. This is Example 1 by Kraus.¹⁰

EXAMPLE 23 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

TITLE

FESDIF example - spherical wave, circular aperture, Fr = 4

UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

1					
96	17	0	0	0.5D-3	

MESH PLOTS

2	1				
Aperture Mesh Plot					
Test Mesh Subplot					
-0.6D-3	0.6D-3	-0.6D-3	0.6D-3		

AMPLITUDE OF APERTURE FUNCTION

1	
0.0D0	

PHASE OF APERTURE FUNCTION

1	
0.0D0	

DIFFRACTION FIELD PLOT

1					
0.001	0.101	0.201	0.301	0.401	
0.501	0.601	0.701	0.801	0.901	

FRESNEL DIFFRACTION FIELD CALCULATION

.099751975	.6328D-6	1	4	.0000D-13	1	0.0D0	0	0
0.0D0	0.0D0	10.D0						
81	1.0D-3	1	0.0D0	0.0D0				

END OF DATA

0	1	2	3	4	5	6	7
12345678901	2345678901	2345678901	2345678901	2345678901	2345678901	2345678901	234567890

Test Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

EXAMPLE 24 Fresnel Diffraction/Incident Spherical
Wave/Elliptical Aperture/Major Axis Fresnel Number = 4,
Minor Axis Fresnel Number = 2/Full Diffraction Field

This example is of an elliptical aperture of major axis equal to 1.0 mm and minor axis equal to 0.7071 mm. The next two pages give the input data listing and the finite element mesh plot of this aperture. The source was a spherical wave of uniform intensity and wavelength $0.6328 \mu\text{m}$ located 10.0 m from the aperture. The diffraction intensities were calculated at a distance of $z' = 99.75197$ mm from the aperture at which point the pathlength Fresnel numbers for the minor and major axes are 2 and 4, respectively. The third page shows the normalized intensity topology/isophote contour plot of this calculated diffraction field. This example is similar to several of the elliptical aperture computational and experimental results presented by Kathuria.¹² This is Example 3 by Kraus.¹⁰

EXAMPLE 24 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE
FESDIF example - spherical wave, elliptical aperture, Fr=4, Fr'=2
UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

2	48	17		
0.3536D-3	0.3536D-3	0.50D-3		
0.0D0	0.0D0			

MESH PLOTS

2	1			
Elliptical Aperture Mesh Plot				
Elliptical Aperture Mesh Subplot				
-0.45D-3	0.45D-3	-0.60D-3	0.60D-3	

AMPLITUDE OF APERTURE FUNCTION

1	
0.0D0	

PHASE OF APERTURE FUNCTION

1	
0.0D0	

DIFFRACTION FIELD PLOT

1				
0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRESNEL DIFFRACTION FIELD CALCULATION

.099751974	.6328D-6	2	4	.0000D-13	1	0.0D0	0	0
0.0D0	0.0D0	10.D0						
81	1.0D-3	1	0.0D0	0.0D0				

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Elliptical Aperture Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

EXAMPLE 25 Fresnel Diffraction/Incident Off-Axis Gaussian

Laser Beam/Circular Aperture/Fresnel Number = 2/Full Diffraction Field

A paraxial Gaussian laser beam propagating parallel to the optic-axis and centered at $x_s = y_s = 0.3$ mm off-axis was used for this example. The aperture was circular with a diameter of 0.2 mm. The input data listing and aperture mesh plot for this example are on the next two pages. The beam radius was 0.4 mm with the beam waist located 1.0 m from the aperture. The wavelength used for the beam was 0.6328 μm . The third page is the normalized intensity/isohpote contour plot of the diffraction field which occurs at $z' = 7.93985$ mm beyond the aperture and corresponds to a pathlength Fresnel number of 2. This pathlength Fresnel number value is that which would be present if the beam were centered with respect to the aperture. This is Example 4 by Kraus.¹⁰

EXAMPLE 25 INPUT DATA LISTING

(Column Number)

```

0          1          2          3          4          5          6          7
1234567890123456789012345678901234567890123456789012345678901234567890
TITLE
FESDIF example - off-axis Gaussian laser beam, circular aperture, Fr=2
UNITS - m

```

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

1
48 17 0 0 0.1D-3

MESH PLOTS

2	1		
Circular Aperture	Mesh Plot		
Circular Aperture	Submesh Plot		
-0.12D-3	0.12D-3	-0.12D-3	0.12D-3

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.000

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRESNEL DIFFRACTION FIELD CALCULATION

.007939854	.6328D-6	1	4	.0000D-13	2	0.4D-3	0	0
0.3D-3	0.3D-3		1.0D0					
81	0.2D-3		1	0.0D0		0.0D0		

END OF DATA

[illegible]

Circular Aperture Submesh Plot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 26 Fresnel Diffraction/Incident Spherical
Wave/Polygonal Aperture/Fresnel Number = 3/Full Diffraction Field**

Segmented mirror apertures for telescopes result in primary objective shapes which are polygonal. This example is one such aperture. The input data listing and the aperture mesh plot for this example are given on the next two pages. The outer boundary of each of the hexagonal segments could be inscribed inside a circle of radius 0.5 mm. The absolute size of this aperture is unimportant whereas the capability to handle this type of geometry using finite elements is important. The incident wave was of uniform intensity, of wavelength $0.6328 \mu\text{m}$, and located 10.0 m from the aperture. The diffraction field was calculated for a distance of $z' = 1.1852086$ m from the aperture which corresponds to a pathlength Fresnel number of 3. The third page shows the resulting diffraction field plot for this example. This is Example 5 by Kraus.¹⁰

EXAMPLE 26 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

TITLE

FESDIF example - spherical wave, polygonal aperture, Fr = 3

UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

3							
24	9	6	0.5D-3	6	8.66025D-4	30.D0	

MESH PLOT

2	1						
Aperture Mesh Plot							
Aperture Mesh Subplot							
-1.5D-3	1.5D-3	-1.5D-3	1.5D-3				

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

1

0.0D0

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRESNEL DIFFRACTION FIELD CALCULATION

1.18520860	.6328D-6	1	4	.0000D-13	1	0.0D0	0	0
0.D0	0.0D0	10.0D0						
81	2.0D-3	1		0.0D0		0.0D0		

END OF DATA

0	1	2	3	4	5	6	7
1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

Aperture Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

**EXAMPLE 27 Fraunhofer Diffraction/Incident Spherical
Wave/Nine-Circle Synthetic Aperture Array each with Secondary
Obstructions and Spider Supports/Full Diffraction Field**

This multiple aperture array consists of nine circular apertures. The input data listing and the mesh plot for these apertures is given on the next two pages. The nine apertures are centered on a radius of 6.725 mm. Each aperture has a diameter of 2.1 mm and has a central obstruction of 5 percent of the single aperture diameter. Each central obstruction is supported by 3 straight spider supports having a thickness of 3 percent of the single circular aperture diameter. This aperture array is characteristic in shape, but 1000 times smaller than, the nine circular aperture telescope array presented by Massie et al.¹³ The incident wave was spherical with wavelength $0.6328 \mu\text{m}$ and located 1000.0 m from the aperture. The diffraction field plot corresponding to a distance of 1000.0 m from the aperture, at which distance the diffraction is far-field or Fraunhofer, is shown on the third page. Note that for Fraunhofer diffraction, the size of the point image diffraction field is directly proportional to the focal length and inversely proportional to the aperture diameter (see the discussion of circular aperture resolution in Ref. 6). therefore, if the dimensions of the aperture were made 1000 times those shown in the mesh plot of the second page, and the overall focal length of this nine-aperture array was 1.0 m, the size of the diffraction field would be $2 \mu\text{m}$ square instead of 2.0 m square. This is Example 6 by Kraus.¹⁰

EXAMPLE 27 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890							

TITLE
FESDIF example - 9-circle synth. aper. array, 2ndry obstr., spiders
UNITS - m

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

4							
27	9	3	-9	1.05D-3	0.05D0	1.0D3	3.D-2 6.725D-3

MESH PLOTS

2	1		
Aperture Mesh Plot			
Aperture Mesh Subplot			
-9.0D-3	9.0D-3	-9.0D-3	9.0D-3

AMPLITUDE OF APERTURE FUNCTION

1	
---	--

PHASE OF APERTURE FUNCTION

1	
0.0D0	

DIFFRACTION FIELD PLOT

1					
0.001	0.101	0.201	0.301	0.401	
0.501	0.601	0.701	0.801	0.901	

FRESNEL DIFFRACTION FIELD CALCULATION

1.D3	.6328D-6	2	4	.0000D-13	1	0.0D0	0	0
0.0D0	0.0D0	1.0D3						
81	1.0D0	1	0.0D0	0.0D0				

END OF DATA

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890

Aperture Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

EXAMPLE 28 Fresnel Diffraction/Incident Spherical Wave/Five
Rings Circular Aperture with Discontinuous Aperture
Function/Fresnel Number = 5/Full Diffraction Field

The aperture for this example consists of five concentric annular rings. The outer diameter is 1.0 mm. The input data listing and the finite element mesh plot for this example are given on the next two pages. An aperture function is used in this example in which its amplitude is stepwise constant at 1.0, 0.8, 0.6, 0.4, and 0.2 for the rings beginning with the inner-most ring. In order to accomodate this step change in aperture function amplitude between rings, a duplicate set of element nodes is superimposed at the radial interface between rings. A spherical wave source located 10.0 m and having a wavelength of $0.6328 \mu\text{m}$ was used. It was desired to calculate the diffraction field at a distance corresponding to a pathlength Fresnel number of 5. This occurs at a distance of $z' = 79.01391 \text{ mm}$ from the aperture. The resulting diffraction field plot is given on the third page. This is Example 7 by Kraus.¹⁰

EXAMPLE 28 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890							

TITLE
FESDIF example - five annular rings cir. aper., discount. aper. func.
UNITS - m Fr = 5

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

1						
48	15	1	0	0.5D-3	0.0D-3	0.0D-3

MESH PLOTS

2	1					
Aperture Mesh Plot						
Aperture Mesh Subplot						
-0.6D-3	0.6D-3	-0.6D-3		0.6D-3		

AMPLITUDE OF APERTURE FUNCTION

4			
1	706	15	1.0D0
2	707	15	1.0D0
3	708	15	1.0D0
4	709	15	0.8D0
5	710	15	0.8D0
6	711	15	0.8D0
7	712	15	0.6D0
8	713	15	0.6D0
9	714	15	0.6D0
10	715	15	0.4D0
11	716	15	0.4D0
12	717	15	0.4D0
13	718	15	0.2D0
14	719	15	0.2D0
15	720	15	0.2D0

PHASE OF APERTURE FUNCTION

1	
0.0D0	

DIFFRACTION FIELD PLOT

1					
0.001	0.101	0.201	0.301	0.401	
0.501	0.601	0.701	0.801	0.901	

FRESNEL DIFFRACTION FIELD CALCULATION

.079013906	.6328D-6	2	4	.0000D-13	1	0.0D0	0	0
0.0D0	0.0D0	10.0D0						
81	1.0D-3		1	0.0D0		0.0D0		

END OF DATA

0	1	2	3	4	5	6	7
1234567890123456789012345678901234567890123456789012345678901234567890

Aperture Mesh Subplot

FESDIF Intensity/Isophote Contour Plot

EXAMPLE 29 Fresnel Diffraction/Incident Off-Axis Gaussian

Laser Beam/Five Annular Rings Circular Aperture with

Ring Continuous Aperture Function/Fresnel

Number = 2/Full Diffraction Field

This example consists of five annular rings separated by gaps. The input data listing and the finite element plot of the aperture are given on the next two pages. The outer ring has a diameter of 1.0 mm and the ring obstruction to ring opening ratio is 0.5 for all rings. Here, the aperture function amplitude was held constant over the entire aperture while the phase was varied linearly by $2\pi/14$ across each ring, with a $\pi/14$ phase shift across each ring obstruction. From the center to the outer diameter of the aperture this results in a π phase change. A Gaussian beam with a beam radius of 0.4 mm with beam waist located at a distance of 0.1 m from the aperture was the source of illumination. In addition, this laser beam is propagating parallel to but displaced from the optic-axis at $x_s = -0.2$ mm, $y_s = 0.2$ mm. The diffraction field was calculated for a pathlength Fresnel number = 2, which occurs at the axial location of $z' = 0.203815709$ m. This z' value was calculated using the outer ring characteristic diameter. This pathlength Fresnel number assumes that the beam is centered upon the aperture, instead of being located off-axis. However, note that the total Fresnel number of this example is 3 because of the additional π or $\lambda/2$ phase shift of the aperture function. The resulting diffraction field is displayed in the plot of the third page. This is Example 8 by Kraus.¹⁰

EXAMPLE 29 INPUT DATA LISTING

(Column Number)

0	1	2	3	4	5	6	7
123456789012345678901234567890123456789012345678901234567890							

TITLE
FESDIF example - off-axis Gaussian laser beam, 5 annular rings aper.
UNITS - m Fr = 2

CIRCULAR, ELLIPTICAL, POLYGONAL, SECONDARY OBSTRUCTION MESH GENERATOR

1							
96	15	1	0	0.5D-3	.33333D-4	0.0D-3	

MESH PLOTS

2	1
Aperture	Mesh Plot
Aperture	Submesh Plot
-0.6D-3	0.6D-3 -0.6D-3 0.6D-3

AMPLITUDE OF APERTURE FUNCTION

1

PHASE OF APERTURE FUNCTION

4			
1	1426	15	0.00000000
2	1427	15	0.22439947
3	1428	15	0.44879895
4	1429	15	0.67319842
5	1430	15	0.89759790
6	1431	15	1.12199737
7	1432	15	1.34639685
8	1433	15	1.57079632
9	1434	15	1.79519580
10	1435	15	2.01959528
11	1436	15	2.24399475
12	1437	15	2.46839422
13	1438	15	2.69279370
14	1439	15	2.91719317
15	1440	15	3.14159265

DIFFRACTION FIELD PLOT

1

0.001	0.101	0.201	0.301	0.401
0.501	0.601	0.701	0.801	0.901

FRESNEL DIFFRACTION FIELD CALCULATION

.203815709	.6328D-6	1	4	.0000D-13	2	0.4D-3	0	0
-0.2D-3	0.2D-3	0.1D0						
81	1.0D-3	1	0.0D0	0.0D0				

END OF DATA

0	1	2	3	4	5	6	7
123456789012345678901234567890123456789012345678901234567890

Aperture Submesh Plot

FESDIF Intensity/Isophote Contour Plot

APPENDIX B REFERENCES

1. H. G. Kraus, "Huygens-Fresnel-Kirchhoff wavefront diffraction formulation – spherical waves," J. Opt. Soc. Am. A, 6(8), 1196–1205 (1989). See also: H. G. Kraus, "Huygens-Fresnel-Kirchhoff wavefront diffraction formulations for spherical waves and Gaussian laser beams: discussion," J. Opt. Soc. Am. A, 9(7), 1132–1134 (1992).
2. H. G. Kraus, "Characteristic pathlength Fresnel number equations and ideal lens wavefront Kirchhoff formulation: analysis of focused spherical wave diffraction fields," Opt. Laser Tech., submitted for publication (1992).
3. H. G. Kraus, "Huygens-Fresnel-Kirchhoff wavefront diffraction formulation – paraxial and exact Gaussian laser beams," J. Opt. Soc. Am. A, 7(1), 47–65 (1990). See also: H. G. Kraus, "Huygens-Fresnel-Kirchhoff wavefront diffraction formulations for spherical waves and Gaussian laser beams: discussion," J. Opt. Soc. Am. A, 9(7), 1132–1134 (1992).
4. A. D. Struckhoff, Fresnel Diffraction with Small Apertures, M. S. Thesis (See Data Set 13), Physics Dept., Montana State University (December 1991).
5. H. G. Kraus, "Characteristic pathlength Fresnel number equations and ideal lens wavefront Kirchhoff formulation: analysis of focused Gaussian beam diffraction fields," Opt. Laser Tech., 24(2), 77–87 (1992).
6. E. Hecht, Optics, 2nd Ed., Addison-Wesley, 1987.
7. H. G. Kraus, "Finite element Fourier and Abbe transform methods for generalization of aperture function and geometry in Fraunhofer diffraction theory," Opt. Eng., 30(8), 1191–1207 (1991).
8. J. L. Richter, "Spider diffraction: a comparison of curved and straight legs," Appl. Opt., 23(12), 1907–1913 (1984).

9. J. E. Harvey and C. Ftaclos, "Diffraction effects of secondary mirror spiders upon telescope image quality," Current Developments in Optical Engineering III, SPIE, Vol. 965, 7-17 (1988).
10. H. G. Kraus, "Finite element area and line integral transforms for generalization of aperture function and geometry in Kirchhoff scalar diffraction theory," Opt. Eng., accepted for publication (June 1992).
11. Y. P. Kathuria, "Computer modelling of three-dimensional Fresnel diffraction pattern at circular, rectangular, and square apertures," Opt. Appl., XIV(4), 509-514 (1984).
12. Y. P. Kathuria, "Fresnel and far-field diffraction due to an elliptical aperture," J. Opt. Soc. Am. A, 2(6), 852-857 (1985).
13. N. A. Massie, et al, "Low-cost, high-resolution, single-structure array telescopes for imaging of low-Earth-orbit satellites," Appl. Opts., 31(4), 447-456 (1992).

APPENDIX C

FESDIF CODE SOURCE AND RUN FILES

- o SOURCE FILE:** **feddif.for**
- o COMPILE, LINK, UPLOAD, AND EXECUTE:** **run3p.bat**

(These files are on the disk below)

**DATE
FILMED**

3 / 22 / 93