DISCLAIMER

DOE/ER/13572--1

DE92 040894

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Progress Report

THE EFFECT OF ELECTRIC FIELDS UPON LIQUID EXTRACTION

D.O.E. Contract #

FG07-86ER13572

April 13, 1988

Thomas E. Carleson
Department of Chemical Engineering
University of Idaho
Moscow, Idaho

MASTER

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED

SUMMARY

A series of mass transfer studies were conducted for the extraction of solute from droplets falling in an electric field. The experiments were planned such that the dispersed phase resistance was controlling. In one series of experiments single drops were formed from a charged nozzle and allowed to fall through a continuous, dielectric phase. The drop size and velocity were correlated by means of a simple force balance. Drop mass transfer coefficients were calculated for the drop free fall period and were compared to predictions based upon literature correlations for an oscillating droplet in the absence of an electric field. Droplet size and velocity were approximately predicted ($\pm 50\%$) by a simple force balance whereas the mass transfer coefficient was approximately 25-250% higher than that predicted. Droplet extraction efficiencies increased about 20-30% in the presence of electric fields up to 2 kV/cm. For the same field, the drop diameter decreased 30 - 50% and the terminal velocity increased by up to 50%. The enhancements for the toluene-water system can be ascribed to increases in terminal velocity and decreases in drop diameter. The mass transfer model for freely falling drops proposed by Skelland and Wellek (Skelland, 1974) roughly predicts the moderate mass transfer efficiency increases (about 18% at 1 kV/cm) for the toluene water system but failed to predict the increases (about 25% at 0.5 kV/cm) for the heptane furfural system.

The second series of experiments involved the formation of a swarm of droplets in a three stage sieve tray column. The upper and lower stages were electrically grounded while the middle was connected to a high voltage direct current power supply. Drop size, velocity, and mass transfer measurements were made. For fields up to 2 kV/cm the drop size decreased by 45%, the terminal velocity increased slightly over 100% and the stage efficiencies for two of the three stages increased slightly under 20%.

In a separate series of experiments, the effect of the electric field upon mass transfer from drops exhibiting interfacial turbulence was evaluated. Upon the application of fields up to 4 kV/cm, the desorption efficiencies of water drops from which methyl isobutyl ketone was desorbing into air decreased by 26 - 50%. Similar effects upon the desorption efficiencies were found when a surfactant was added.

INTRODUCTION

Mass transfer between phases is enhanced by a number of factors. These include: increases in transfer surface area, increases in relative velocity between the contacting phases, increases in mixing between phases, the presence of interfacial turbulence due variations in concentration along the interface and this effect upon interfacial tension, increases in concentration driving forces, changes in transport properties - increase in diffusivity, decrease in kinematic viscosity, and increases in exposure time. A number of these factors can be affected by an electric field operating on an interface which is rupturing to form droplets of one phase in another. For systems where the dispersed phase is a conductor and the continuous a dielectric, formation of the dispersed phase from a nozzle

connected to one pole of the electric field can result in the formation of a charge upon the interface. The amount of charge on the interface is proportional to the applied field strength (Takamatsu, et al., 1982; Vu and Carleson, 1986; Carleson and Berg, 1983). The charged interface interacts with the applied field to result in a body force that acts to pull droplets from the interface. If this force is in the same direction as gravity, smaller droplets are formed as the electric field increases. These charged droplets, although they are smaller than in the absence of the field, have higher terminal velocities than those formed in the absence of the field (Vu and Carleson, 1986; Carleson and Berg, 1983; Harker and Ahmadzadeh, 1974).

The smaller, faster travelling drops can exhibit lower absorption efficiencies in the case of gas absorption due to the reduction in residence time (Carleson and Berg, 1983) or have higher extraction efficiencies due to the increase in droplet surface area or oscillation (Bailes, 1981) in liquid extraction. In order to estimate the effect of the field, the separate effects upon drop size, velocity, must be evaluated.

As a first approximation, simple force balances can be used to correlate the effect of the electric field upon drop size and velocity (Carleson and Berg, 1983; Vu and Carleson, 1986; Takamatsu, et al., 1981). These appear as simple expressions for the drop charge density:

$$q = \gamma \epsilon E_0 \quad (1)$$

the drop volume:

$$\frac{V_0 - V}{V^{2/3}} = \frac{K \kappa E_0^2}{\Delta \rho} \quad (2)$$

and the drop velocity:

$$\frac{\rho_c U_t^2}{8d} = \frac{\Delta \rho g}{6C_D} + \frac{K}{C_D} \frac{\kappa E_0^2}{d} \quad (3)$$

where: q is the drop surface charge density, γ is a geometric factor for the forming nozzle type (Takamatsu et al., 1981) and field aspect ratio (Yang and Carleson, 1988), ϵ is the permittivity of the continuous phase, κ is the relative dielectric constant of the continuous phase, E_0 is the applied field strength, V_0 is the drop volume in the absence of an applied field, V is the drop volume at a given field strength, K is a geometrical constant, $\Delta \rho$ is the density difference between the dispersed and continuous phase, ρ_c is the density of the continuous phase, U_t is the drop terminal velocity, d is the drop diameter, g is the gravitational constant, C_D is the drop drag coefficient. Drop charges are predicted to within +/- 25% of the experimental values while drop volume and velocity changes are underpredicted by about 50% (Vu and Carleson, 1986). This may be due to nonlinearities in the field not accounted for in the model (perhaps due to drop distortion). Other effects include insufficient column spacing

to allow the drops to attain their terminal velocities (Yang and Carleson, 1988).

In terms of mass transfer, Vu and Carleson (1986) predicted the changes in drop free fall mass transfer coefficients and extraction efficiencies as a function of field strength. These predictions were based upon the standard mass transfer correlations for a non-oscillating droplet (Skelland, 1974). Figure 1, which is a plot of the ratio of the drop free fall mass transfer coefficient for a given electric field strength divided by that for zero field, shows that the drop free fall dispersed phase mass transfer coefficient would only increase about 8% while the continuous phase transfer coefficient would increase by about 35% for a field of 5 kV/cm. Bailes (1981) reports an increase in the dispersed phase coefficient of 25%, or about three times that predicted in Figure 1. Bailes attributes this increase to the effects of the field upon drop oscillation and turbulence levels.

Figure 2 depicts the predicted effects of the electric field upon the extraction efficiency of a freely falling drop. A predicted 50% increase in the efficiency for the dispersed phase controlled resistance and a 90% increase for the continuous phase controlled resistance is seen. These results are comparable to some of those experimentally observed for the continuous phase transfer rate (50% increase observed by Harker and Ahmadzadeh, 1974) and the dispersed phase transfer efficiency (25% increase observed by Bailes, 1981, and Yamaguchi, et al., 1985) while they differ from others experimentally observed (120% increase observed by Bailes, 1977).

It appears that simple force balance models may be used to approximate (+/- 50%) the effect of the electric field upon drop size and velocity. For better predictions, better models of the electric field and drop distortion are required (Yang and Carleson, 1988). These predicted effects of the field upon the drop size and velocity can be used with standard mass transfer predictions to approximate the effect of the field upon the mass transfer. Predicted effects are comparable to some of those observed. However, some experimental results indicate much more dramatic effects. These results indicate that more work is required in single drop mass transfer. In addition, there is a dearth of experimental results with multiple drops - a system of more practical, engineering interest and there is evidence that alternating fields may enhance mass transfer better than direct current fields. These research areas - more experimental results with single drops and multiple drops and theoretical treatment of the effect of the electric field upon the mass transfer - are addressed in this progress summary.

EXPERIMENTAL EQUIPMENT AND PROCEDURES

Figure 3 depicts the column used for the single drop studies and Figure 4, that used for the multiple droplet studies. In the single drop studies methanol was transferred from a toluene continuous phase to a water dispersed phase. A second single drop study was conducted with heptane transferring from a continuous heptane phase into a furfural dispersed phase. In the single droplet study extractor, droplets were formed at a hypodermic needle (4 or 18 gauge) which was connected to a stainless steel

upper plate connected to the high voltage power supply. The lower electrically grounded plate held a funnel in which the droplets were collected. A high speed motion picture camera was used for the determination

analyzed for the presence of methanol in water or heptane in furfural by means of a gas chromatograph.

For the toluene (continuous phase) - methanol (transferring solute) - water (dispersed phase) single drop studies, the continuous and dispersed phase were mutually saturated with water and toluene respectively, while the continuous phase was saturated with methanol. For the heptane (continuous phase and transferring solute) and furfural (dispersed phase) system, the continuous phase was saturated with furfural. In this manner, the dispersed phase resistance was made controlling.

By performing experiments at a variety of column lengths and ensuring that the drop formation time was kept constant (by varying the field), the measured extraction efficiencies were plotted as a function of column length. By extrapolation of the extraction efficiency to zero column length, one is able to estimate the extraction efficiencies due to the end effects of drop formation and coalescence. These end effects were factored out of the overall efficiencies to allow determination of the extraction efficiency during droplet free fall.

For the multiple droplet studies, a series of three sieve trays were used as depicted in Figure 4. Each tray was perforated with 46 1/8 inch diameter holes on a triangular pitch of approximately 3 - 4 hole diameters. The plate occupied about 83% of the column cross sectional area. The column diameter was 9.525 cm. A tray spacing of 4 inches was used. The upper and lower plates were connected to electrical ground while the middle plate was connected to the high voltage power supply. Sample ports were located at each tray.

The system evaluated was toluene (continuous phase) - methanol (transferring solute) - water (dispersed phase). To ensure that the dispersed phase controlled the resistance, the continuous phase was saturated with the transferring solute. Gas chromatography was used to determine the concentration of methanol in water.

In the third study, the effect of the electric field upon drop mass transfer in the presence of interfacial turbulence was evaluated. A single drop column similar to that depicted in Figure 3 was used. This column served to generate charged water drops saturated with methyl isobutyl ketone. The drops were allowed to fall through air into which the methyl isobutyl ketone (MIK) transferred. A VCR camera was used to evaluate the effect of the field upon drop turbulence.

Three field strengths were evaluated. To maintain a constant drop diameter as the field increased, three hypodermic needles were used (18, 20, and 22 gauge). The drops fell through a distance of 5 or 10 centimeters before collection in a glass funnel and analysis. A spectrophotometer was used to analyze for the amount of MIK left in the drops.

RESULTS

Figure 5 depicts the drop volume reduction due to the electric field plotted in accordance with equation 2. Depicted on this plot are data from the single and multiple droplets experiments with toluene-methanol-water and heptane-furfural. Note that straight line behavior is approximated in accordance with equation 2. Note, however, that the slope of the lines vary with plate spacing (4, 6, 8, and 10 cm), higher slopes are observed at higher plate spacings. The field in this figure is the nominal field, not adjusted for the plate-to-plate aspect ratio. Larger plate spacings have larger aspect (length to width) ratios which produce non-linearities in the field. This causes high fields near the plates and low fields toward the center of the column. The higher fields would result in a variation of drop volume with field strength larger than that predicted. This trend is seen in the experimental variation in drop volume with electric field. This phenomena can change the slope by as much as 20% (Yang and Carleson, 1988) which agrees with the observed results. There appears to also be some effect of the nature of the dispersed phase. Figure 5a (data depicted in Figure 5 over a narrower range of fields) indicates that the variation in drop volume with field (especially above 0.4 kV/cm) is stronger for drops of furfural formed in heptane (H-F) than for drops of water formed in toluene (T-W-M). The interfacial tension between heptane and furfural is about 1/10 of that between water and toluene so smaller, more deformed drops are formed of furfural in the absence of an applied field. Drop deformation would produce a higher charge upon the drop as it forms and would result in a higher electric body force, consequently a larger variation in drop volume with field. Drop volume appears more sensitive to the field for multiple droplets of water in toluene as well. In this case, however, the droplet forms from orifices in the high voltage plate rather than from a nozzle. This may result in drop charges higher than those for drops released from a nozzle. Smaller, faster falling drops would result.

Figure 6 depicts the electric field effect upon the drop velocity for drops of water in toluene. The data is plotted in accordance with equation 3. The data plots approximately linearly in accordance with the predictions from the simple force balance. Based upon the data, the experimentally calculated drag coefficient was found to be around one. The Reynolds numbers for the drops were around 1000. Standard drag coefficient curves would indicate drag coefficients much less than one. It was observed that the drops are oscillating as they fall, which would result in larger drag coefficients. Another reason for the higher drag coefficients is that the drops are accelerating during a significant portion of their fall. This is true for the shorter column spacings when the travel distances are less than about 5 -10 drop diameters (3 - 5 centimeters).

The drop velocity for the sieve tray column work varied approximately linearly with field strength from around 10 cm/sec at zero field to 23 cm/sec at a field strength of approximately 2 kV/cm. These changes are comparable to but slightly higher than those observed for single drops.

The above results indicate that the drop velocity increases by about 50 - 100% upon the imposition of a field of 2 kV/cm. The corresponding reduction in drop diameter is about 32% (single drops) to 54% (multiple drops) which would result in a drop surface area/volume increase of about 46% to 117%, respectively. The effect of the field upon the drop velocity

apparently is comparable or outweighs the effect upon drop surface area/volume ratio.

The changes in drop surface area and velocity are reflected in the mass transfer process as an increase in the drop extraction efficiency. Figure 7, 8, and 9 show the drop overall extraction efficiency as a function of field strength and plate spacing for the systems toluene-water-methanol (single drops), heptane-furfural (single drops), and toluene-water-methanol (multiple drops), respectively. The overall extraction efficiency increased a maximum of 15% for the toluene-water system, 51% for the heptane-furfural system, and 24% for the second stage of the sieve tray toluene-water system. The extraction in the third stage of the sieve tray column decreased with field strength, perhaps due to saturation of the drops leaving the second stage. The plate-to-plate spacing in the sieve tray column was 10 cm and the liquid height upon the tray was 2.5 cm.

Figure 10 shows that the application of an electric field will increase the column throughput by about 26%. The charged drop velocities increase with field strength to result in an increase in the dispersed phase flow rate or throughput. Figure 11 depicts the overall mass transfer coefficients for the multistage column stages 1 and 2. Increases in mass transfer coefficients of about 70% are seen at a field of 2 kV/cm.

These results can be compared to those for single drops in the toluene-methanol-water (T-W-M) and heptane-furfural (H-F) systems depicted in Figure 12, a plot of the efficiency ratio (extraction efficiency at a given field strength divided by that at zero field). These results indicate that the single drop extraction efficiencies (T-W-M, H-F) are slightly more sensitive to the field than that for multiple droplets (stage 1 and 2). The mass transfer coefficient for drop free fall (obtained by eliminating end effects as discussed in the procedures section) is depicted in Figure 13 for the heptane-furfural (H-F) and the toluene-water-methanol (T-W-M) systems. A 100% increase in the H-F coefficient at 0.5 kV/cm and an 80% increase in the T-W-M coefficient at 1.2 kV/cm are seen. Figure 14 shows the ratio of the observed transfer coefficients to the predicted based upon an empirical equation (Skelland, 1974) for oscillating, uncharged drops. The experimental values are about 220% above the predicted values. Figure 15 depicts a similar plot for the ratio of the experimental extraction efficiencies to those predicted based upon the oscillating drop correlation. Observed efficiencies are almost 80% greater than those predicted at the higher field strengths. This may be due to drop distortion and oscillation due to high effective fields from the nonlinear field produced at large plate spacings.

The effect of an electric field upon mass transfer from drops exhibiting interfacial turbulence is depicted in Figure 16 (Carleson and Fuller, 1987). From this figure (based upon experiments in which the drops size was maintained constant in order to maintain constant end effects), it appears that the desorption efficiency decreases with field strength. For drops forming and falling short distances in air, most of the mass transfer occurs during drop formation, when the drop liquid is circulating. A decrease in drop desorption efficiency for a constant drop size indicates that circulation is reduced, due to interface stabilization from the surface charge produced by the field. Comparable reductions in the desorption efficiencies were seen when surfactant was added to the

dispersed phase. These results agreed with predictions based upon surface charge distribution and resultant stress as well as Marangoni stresses (Carleson and Fuller, 1987).

DISCUSSION OF RESULTS

Figures 5, 5a, and 6 show approximately linear behavior, in accordance with simple force balance results presented in equations 1 through 3 (Vu and Carleson, 1986; Yang and Carleson, 1988). Differences in the slope may be due to nonlinear field behavior at large column spacing and different drop charging at orifices relative to nozzles (multiple drops). Further work is merited in the determination and modelling of drop charges and volumes formed at orifices in the high voltage plate. In addition, drop distortion for fluids with low interfacial tension may also lead to larger slopes.

Increases in drop extraction efficiencies of 20 - 25% observed for the dispersed phase controlled resistance in single and multiple drops (Figure 12) at 2 kV/cm is about twice that predicted (10% increase) based upon mass transfer correlations for an uncharged drop (Figure 2). Transfer coefficient ratios predicted in the same manner (Figure 1) indicate an increase of less than 5% while observed values increase between 70 and 100% (Figure 13) for fields up to 2 kV/cm. An oscillating drop mass transfer correlation can be used to model the low field (less than 0.6 kV/cm) mass transfer coefficients fairly well (Figure 14) but does poorly for higher fields. It may be that drop oscillation may also increase with the field to an extent not well correlated by the standard mass transfer correlations in the literature. Photographs of the drops at high fields indicate more oscillation. The abrupt decrease in drop diameter (Figure 5a) and increase in extraction efficiency (Figure 12) for the heptane-furfural system (a low interfacial tension system) at 0.4 kV/cm may correspond to an increase in drop distortion and oscillation. These changes are apparently not well modelled by the standard transfer correlations.

Although large increases in the mass transfer coefficient are observed these result in only moderate increases in the transfer efficiencies. Apparently the increases in drop velocity with field result in decreased residence times which partially moderate the increases in extraction efficiency due to increased surface area and mass transfer coefficients. Similar results would be expected for the continuous phase controlled resistance. In view of this, it appears that direct current fields may result in only moderate (up to 30 - 50%) increases in the extraction efficiency. For more dramatic increases other mechanisms must be sought.

It is possible to investigate the effect of drop oscillation upon the mass transfer process by inducing forced oscillations by means of an alternating field superimposed upon the direct current field. Recent studies (Kaji, 1978, 1980; Wham and Byers, 1987; Scott and Byers, 1988) show such forced oscillation may enhance the heat transfer coefficient as much as 135% (Kaji, 1980). It appears, however, based upon the above results and those of others (Yang and Carleson, 1988), that standard mass transfer correlations for oscillating drops would not be able to explain these results. Further work, experimental as well as theoretical, is merited in this area. Charged drops undergoing forced oscillations would

be expected to exhibit dramatic increases in mass transfer rates compared with uncharged or charged drops in direct current fields. These considerations also encourage new research in this area.

Preliminary results indicate that the charge induced by an electric field upon a curved interface may help stabilize such an interface against interfacial turbulence. In this case, the result of an electric field upon mass transfer would be to reduce the transfer rate if interfacial turbulence is the main mechanism for transport across the interface.

REFERENCES

- Bailes, P.J., "Electrostatic Extraction for Metals and Non-metal", Proceedings of the 1977 International Solvent Extraction Conference, 233(1977).
- Bailes, P.J., "Solvent Extraction in an Electrostatic Field", Ind. Eng. Chem. Process Des. Dev., 20, 564(1981).
- Carleson, T.E., and J. Berg, "The Effect of Electric Fields on the Absorption of Pure Sulfur Dioxide by Water Drops", Chem. Eng. Science, 38, No. 6, 871(1983).
- Carleson, T.E., and E. Fuller, "The Effect of Electrical Charge upon Mass Transfer from Droplets Exhibiting Interfacial Turbulence", Chemical Engineering Communications, 57, No. 1-6, 277(1987).
- Harker, J.H., and J. Ahmadzadeh, "The Effect of Electric Fields on Mass Transfer from Falling Drops", J. Heat and Mass Transfer, 17, 1219(1974).
- Kaji, N., Y.H. Mori, Y. Tochitani, K. Komotori, "Direct contact Heat Transfer to Drops in an Intermittent Electric Field", Proc. 6th Intl. Heat Transfer Conf., 3, 165(1978).
- Kaji, N., Y.H. Mori, Y. Tochitani, K. Komotori, "Augmentation of Direct Contact Heat Transfer to Drops with an Intermittent Electric Field", J. Heat Transfer, 102, 32(1980).
- Scott, T.C., and C.H. Byers, "A Model for Mass Transfer in Oscillating-Circulating Liquid Drops", Chem. Eng. Comm., in press, (1988).
- Takamatsu, T., M. Yamaguchi, T. Katayama, "Formation of Single Charged Drops in Liquid Media under a Uniform Electric Field", J. Chem. Eng. Japan, 15, No. 5, 349(1982).
- Vu, N., and T.E. Carleson, "Electric Field Effects on Drop Size and Terminal Velocity in Liquid-Liquid Systems", J. AIChE, 32, No. 10, 1739(1986).
- Wham, R.M., and C.H. Byers, "Mass Transfer from Single Droplets in Imposed Electric Fields", Sep. Sci. Tech., 22, No. 2-3, 447(1987).
- Yamaguchi, M., T. Takamatsu, F. Yoshida, T. Katayama, "An Experimental Study of Mass Transfer Rate in the Dispersed Phase for Single Charged Drops in a Dielectric Liquid under a Uniform Electric Field", J. Chem. Eng. Japan, 18, No. 4, 325(1985).
- Yang, W., and T.E. Carleson, "Several Effects of Electric Fields on Liquid Extraction", submitted for publication in Proceedings of 1987 IEEE Industry Applications Society 22nd Annual Meeting, Atlanta, Ga., 1987.

Figure 1

Transfer Coef. Ratio vs Field Strength

Figure 2

Efficiency Ratio vs Field Strength

Figure 3

Experimental Apparatus

Figure 4

Figure 5

Reduced Volume versus Reduced Field

Figure 5a

Reduced Volume versus Reduced Field

Figure 6

Reduced Velocity versus Reduced Field

Figure 7, Overall Extraction Efficiency

Toluene Water Methanol - Single Drops

Figure 8, Overall Extraction Efficiency
Heptane Furfural - Single Drops

Figure 9, Overall Stage Efficiency

Toluene Water Methanol - Multiple Drops

Figure 10
Column Throughput

Figure 11

Transfer Coef. versus Field Strength

Figure 12

Efficiency Ratio

Figure 13

Transfer Coef. versus Field Strength

Figure 14

Figure 15

Eff. Ratio (Actual/Pred.) versus Field

Figure 16
Desorption Efficiency versus Field

END

**DATE
FILMED**

12 / 1 / 92