NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

SRS BASELINE HYDROGEOLOGIC INVESTIGATION - SUMMARY REPORT (U)

Prepared by:

**H. W. Bledsoe
R. K. Aadland
K. A. Sargent**

November 1990

**Approved by: D. B. Moore
Environmental Sciences Section
Savannah River Laboratory**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER SITE
AIKEN, SC 29808**

**RECEIVED
FEB 22 1993
OSTI**

Prepared for the U. S. Department of Energy under Contract No. DE-AC09-89SR18035

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DB Moore
D. B. Moore, Section Manager
Authorized Derivative Classifier

WSRC-RP-90-1010

**SRS BASELINE HYDROGEOLOGIC INVESTIGATION -
SUMMARY REPORT (U)**

Prepared by:

H. W. Bledsoe¹
R. K. Aadland¹
K. A. Sargent²

November 1990

¹ Environmental Sciences Section
Savannah River Laboratory
Westinghouse Savannah River Company
Aiken, SC 29808

² Department of Geology
Furman University
Greenville, SC 29613

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER SITE
AIKEN, SC 29808

Prepared for the U.S. Department of Energy under Contract No. DE-AC09-89SR18035

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *cls*

TABLE OF CONTENTS

EXECUTIVE SUMMARY.....	1
INTRODUCTION.....	2
SUMMARY.....	2
Phase I Program.....	2
Phase II Program.....	9
Phase III Program.....	9
SC WATER RESOURCES COMMISSION PROGRAM.....	12
HYDROGEOLOGY.....	12
Stratigraphic Sequence at SRS.....	12
Hydrostratigraphy.....	23
Hydrostratigraphic Cross Sections.....	30
Low Permeability Layers.....	32
Water Levels.....	32
CONCLUSIONS.....	34
REFERENCES.....	39
Appendix A. Graphic Geologic Logs	
Appendix B. Well Cluster Profiles	
Appendix C. Hydrographs of Select Wells	
Appendix D. Summary of Laboratory Tests	
Appendix E. Grain Size Distribution for Undisturbed Samples	
Appendix F. Grain Size Distribution within Screen Zones	
Appendix G. Well Completion Diagrams	

LIST OF ILLUSTRATIONS

Figures

1	Location of SRS Baseline Observation Well Network.....	3
2	Location of Phase I Well Clusters.....	8
3	Location of Phase II Well Clusters.....	10
4	Location of Phase III Well Clusters.....	11
5	South Carolina Water Resources Commission Offsite Drilling Program.....	13
6	Proposed Stratigraphic Column for SRS	16
7	Stratigraphic Column used in Baseline Investigation..	18
8	Generalized Correlation between Stratigraphic and Hydrostratigraphic Units.....	26
9	Location of Hydrostratigraphic Cross Sections.....	31
10	Potentiometric Surface Map for Aquifer Unit IIA (Congaree Formation).....	35
11	Potentiometric Surface Map for Aquifer Unit IA (Black/Middendorf Formation).....	36
12	Potentiometric Surface Map for Aquifer Unit IB (Peedee/Black Creek Formation).....	37
13	Head Difference Map between Aquifer Units IB and IIA.	38

Plates (Plates are in Pocket)

1	Hydrostratigraphic Cross Section A - A'
2	Hydrostratigraphic Cross Section B - B'
3	Hydrostratigraphic Cross Section C - C'
4	Hydrostratigraphic Cross Section D - D'
5	Hydrostratigraphic Cross Section E - E'

LIST OF TABLES

1	Summary of SRS Baseline Observation Well Network.....	4
2	Summary of South Carolina Water Resources Commission Offsite Drilling Program.....	14
3	Summary of South Carolina Hydrostratigraphic Nomen- clature Subcommittee Proposed Classification System..	24

EXECUTIVE SUMMARY

The hydrogeology of the Savannah River Site was investigated by analyzing more than 16,000 feet of core collected from the Mesozoic-Cenozoic age Coastal Plain sedimentary sequence and installing 129 observation wells at 18 widely spaced well cluster locations. The field portion of the program began in 1983 and was completed in 1987. The results of this investigation, combined with existing data from both on and off the plant site, have been used to better define the hydrostratigraphy and to develop an updated nomenclature system that will be compatible with the system being developed by the South Carolina Hydrostratigraphic Nomenclature Subcommittee.

Based on the results of this investigation, the coastal plain sequence consists basically of two Confining Systems and two Aquifer Systems. These Systems can be subdivided into Confining Units and Aquifer Units, which in turn may be further subdivided into Confining Zones and Aquifer Zones. The relationship of the hydrostratigraphy to the coastal plain stratigraphic sequence is discussed in detail. Additionally a series of cross sections have been developed illustrating the hydrogeologic framework at the site. From the water level data collected, potentiometric surface maps for the major aquifer units have been constructed. These maps provide information on flow directions and gradients. This observation well network also provides the basic data needed to define areas of the plant where a hydraulic head reversal exists between the aquifer unit found in Tertiary age sediments (Congaree Formation) and the underlying aquifer unit within sediments of Cretaceous age (Peedee/Black Creek Formations). An updated head difference map has been prepared and is included as part of this report.

INTRODUCTION

Work on the Savannah River Site (SRS) Baseline Hydrogeologic Investigation began in 1983 when it was determined that the knowledge of the plant hydrogeologic systems needed to be expanded and improved in response to changing stratigraphic and hydrostratigraphic terminology and increased involvement by regulatory agencies (Bledsoe, 1984). Additionally, site-wide data were needed to determine flow paths, gradients, and velocities associated with the different aquifers underlying the plant site. The program was divided into three phases in order to allow the results of one phase to be evaluated and necessary changes and improvements incorporated into the following phases.

The program included the coring of more than 16,000 feet of unconsolidated coastal plain sediments and the installation of 129 observation wells completed in the different aquifer units at 18 widely spaced cluster sites (P-13 through P-30). The results of the different phases were reported in DPST-84-833, DPST-86-674, and DPST-86-627 (Bledsoe, 1984b; 1987; and 1988). The locations of the 18 cluster sites are shown on Figure 1. Table 1 is a listing of all wells within the Baseline Observation Well Network. Where possible, existing wells were incorporated in the location and design of cluster sites.

This report summarizes the results of all three phases and includes modified graphic logs, lithologic descriptions of the different geologic formations, profiles of each cluster site, hydrostratigraphic cross sections, hydrographs of selected wells within each cluster for the first full year of uninterrupted water level measurements, potentiometric maps developed from data collected from all clusters, completion diagrams for each well, and a summary of laboratory tests. Additionally, the proposed new classification of hydrostratigraphic units at SRS (Aadland and Bledsoe, 1990) has been incorporated.

SUMMARY

Phase I

The Phase I program consisted of core drilling, geophysical logging, physical testing of selected sediment samples, and construction of 20 observation wells located at three cluster sites (P-13, P-14, and P-15), Figure 2. Drilling activities began in December 1983 and were completed in May 1984. This was the first time that standard wireline rock coring techniques had been used to collect continuous geologic cores of the unconsolidated to semiconsolidated coastal plain sediments underlying the plant. An exploratory corehole was drilled at each cluster site from the ground surface to the

Figure 1. Location of SRS Baseline Hydrogeologic Observation Well Network

Table 1. SRS Baseline Observation Well Network

WELL NO.	SRS COORDINATES		GROUND SURFACE	APPROXIMATE ELEVATION SCREENED INTERVAL	HYDROSTRATIGRAPHIC INTERVAL
P-13D	35600	60000	253.0	229 to 207	Water Table
P-13C	35600	60000	252.8	43 to 33	Aquifer Unit IIB
P-13B	35600	60000	252.5	3 to -7	Aquifer Unit IIA
P-13A	35600	60000	252.4	-58 to -68	Aquifer Unit IIA
P-13TD	35600	60000	253.1	-177 to -187	Aquifer Unit IB
P-13TC	35600	60000	252.8	-377 to -387	Aquifer Unit IB
P-13TB	35600	60000	252.5	-498 to -508	Aquifer Unit IA
P-13TA	35600	60000	252.1	-657 to -678	Aquifer Unit IA
IDB-1C#	72388	76401	293.9	213 to 193	Water Table
P-14C	72420	76424	293.3	148 to 138	Aquifer Unit IIB
IDB-1B#	72396	76407	293.8	98 to 93	Aquifer Unit IIA
IDB-1A#	72403	76413	293.9	-50 to -55	Aquifer Unit IB
P-14TC	72433	76432	293.0	-197 to -207	Aquifer Unit IB
P-14TB	72454	76426	293.1	-262 to -272	Aquifer Unit IB
P-14TA	72445	76440	292.9	-524 to -547	Aquifer Unit IA
P-15D	47350	51130	252.7	239 to 218	Water Table
P-15C	47294	51408	252.7	103 to 93	Aquifer Unit IIB
P-15B	47023	51532	252.6	58 to 48	Aquifer Unit IIA
P-15A	46755	51376	252.6	-87 to -97	Aquifer Unit IIA
P-15TD	46738	51054	252.6	-197 to -207	Aquifer Unit IB
P-15TC	47382	51271	252.5	-357 to -367	Confining Unit IA-IB
P-15TB	47305	50976	252.5	-457 to -467	Aquifer Unit IA
P-15TA	47008	50864	252.6	-618 to -638	Aquifer Unit IA
P-16D	98236	82312	261.2	231 to 211	Water Table
P-16B	98230	82298	261.0	191 to 181	Aquifer Unit I/IIC
P-16A	98219	82271	259.6	131 to 120	Aquifer Unit I/IIC
P-16TD	98205	82276	259.8	40 to 30	Confining Unit I/IIB-I/IIC
P-16TC	98211	82290	260.4	-120 to -130	Aquifer Unit I/IIB
P-16TB	98216	82304	260.7	-184 to -194	Aquifer Unit I/IIA
P-16TA	98222	82318	261.3	-349 to -359	Aquifer Unit I/IIA
P-17D	63185	109795	332.2	287 to 267	Water Table
P-17C	63191	109810	332.0	202 to 192	Aquifer Unit IIB
P-17B	63196	109824	332.0	132 to 122	Aquifer Unit IIA
P-17A	63201	109837	331.6	42 to 32	Aquifer Unit IIA
P-17TD	63215	109833	332.0	-68 to -78	Confining System I-II
P-17TC	63210	109819	332.2	-278 to -288	Aquifer Unit IB
P-17TB	63205	109805	332.3	-358 to -368	Aquifer Unit IA
P-17TA	63199	109791	332.6	-517 to -527	Aquifer Unit IA

EXISTING WELL

NOTE: P-13 COORDINATES ONLY APPROXIMATE

Table 1, contd

WELL NO.	SRS COORDINATES		GROUND SURFACE	APPROXIMATE ELEVATION SCREENED INTERVAL	HYDROSTRATIGRAPHIC INTERVAL
P-18D	67553	47667	296.3	226 to 206	Water Table
P-18B	67579	47681	295.9	76 to 66	Aquifer Unit IIA
P-18A	67593	47688	295.9	21 to 11	Confining System I-II
P-18TD	67618	47678	295.6	-180 to -190	Aquifer Unit IB
P-18TC	67606	47670	296.3	-258 to -268	Aquifer Unit IB
P-18TB	67593	47661	296.2	-370 to -380	Aquifer Unit IA
P-18TA	67579	47653	296.3	-534 to -554	Aquifer Unit IA
P-19D	55302	60049	297.3	272 to 252	Water Table
P-19C	55322	60056	297.7	125 to 115	Aquifer Unit IIB
P-19B	55336	60051	297.7	78 to 58	Aquifer Unit IIA
P-19A	55347	60031	297.4	-28 to -38	Aquifer Unit IIA
P-19TD	55342	60017	296.8	-128 to -138	Confining System I-II
P-19TC	55328	60022	297.1	-230 to -240	Aquifer Unit IB
P-19TB	55310	60029	297.0	-316 to -326	Confining Unit IA-IB
P-19TA	55296	60035	296.8	-458 to -469	Aquifer Unit IA
P-10A#	55280	60049	296.7	-544 to -554	Aquifer Unit IA
P-20D	56075	76785	287.1	244 to 224	Water Table
P-20C	56068	76814	287.3	147 to 137	Aquifer Unit IIB
P-20B	56082	76817	287.6	48 to 28	Aquifer Unit IIA
P-20TD	56094	76768	287.4	-148 to -158	Aquifer Unit IB
P-21D	24661	40736	206.6	147 to 127	Water Table
P-21B	24642	40758	207.5	-72 to -82	Aquifer Unit IIA
P-21A	24650	40780	207.3	-145 to -155	Confining System I-II
P-21TD	24667	40769	206.7	-268 to -278	Aquifer Unit IB
P-21TC	24671	40754	206.6	-461 to -471	Aquifer Unit IB
P-21TB	24675	40739	206.5	-599 to -609	Aquifer Unit IA
P-5A#	24649	40617	206.4	-767 to -777	Aquifer Unit IA
P-22D	20608	73559	215.0	175 to 155	Water Table
P-22C	20610	73545	215.2	89 to 79	Confining Unit IIA-IIB
P-22B	20612	73530	215.6	-24 to -34	Aquifer Unit IB
P-22A	20615	73515	215.7	-134 to -144	Confining System I-II
P-22TD	20601	73511	215.7	-309 to -319	Aquifer Unit IB
P-22TC	20598	73526	215.6	-416 to -426	Aquifer Unit IB
P-22TB	20595	73541	215.2	-555 to -565	Aquifer Unit IA
P-22TA	20593	73555	215.0	-715 to -735	Aquifer Unit IA

EXISTING WELL

Table 1, Contd

WELL NO.	SRS COORDINATES		GROUND SURFACE	APPROXIMATE ELEVATION SCREENED INTERVAL	HYDROSTRATIGRAPHIC INTERVAL
P-23D	48074	30943	181.6	149 to 129	Water Table
P-23B	48101	30925	181.1	49 to 44	Aquifer Unit IIA
P-23A	48115	30915	180.6	-26 to -36	Confining System I-II
P-23TE	48117	30895	179.9	-152 to -162	Confining System I-II
P-23TD	48105	30903	180.0	-232 to -242	Aquifer Unit IB
P-23TC	48086	30900	179.9	-397 to -407	Aquifer Unit IB
P-23TB	48076	30923	180.8	-506 to -516	Aquifer Unit IA
P-23TA	48063	30931	180.6	-616 to -636	Aquifer Unit IA
P-24D	43099	66580	313.1	268 to 248	Water Table
P-24C	43113	66576	313.2	183 to 153	Aquifer Unit IIB
P-24B	43128	66573	313.3	94 to 84	Aquifer Unit IIA
P-24A	43142	66570	313.1	9 to -2	Aquifer Unit IIA
P-24TD	43139	66555	313.2	-176 to -187	Aquifer Unit IB
P-24TC	43125	66558	313.3	-271 to -282	Aquifer Unit IB
P-24TB	43110	66562	313.4	-482 to -492	Aquifer Unit IA
P-24TA	43096	66565	313.1	-638 to -659	Aquifer Unit IA
P-25D	52492	42246	264.7	225 to 205	Water Table
P-25C	52506	42244	264.9	110 to 100	Aquifer Unit IIB
P-25B	52521	42242	265.2	90 to 80	Aquifer Unit IIA
P-25A	52536	42240	265.5	-34 to -44	Confining System I-II
P-25TE	52553	42254	265.4	-134 to -145	Confining System I-II
P-25TD	52538	42255	265.3	-194 to -205	Aquifer Unit IB
P-25TC	52523	42257	265.2	-309 to -320	Aquifer Unit IB
P-25TB	52508	42259	265.1	-454 to -465	Aquifer Unit IA
P-25TA	52494	42261	264.7	-583 to -605	Aquifer Unit IA
P-26D	71969	18042	151.2	121 to 101	Water Table
P-26B	71996	18051	151.4	82 to 71	Confining Unit IIA-IIB
P-26A	72010	18056	151.2	31 to 21	Aquifer Unit IIA
P-26TD	72002	18068	151.0	-89 to -99	Aquifer Unit IB
P-26TC	71988	18063	151.2	-223 to -234	Aquifer Unit IB
P-26TB	71973	18057	151.3	-373 to -384	Aquifer Unit IA
P-26TA	71959	18052	151.5	-528 to -538	Aquifer Unit IA
P-27D	70377	64009	274.0	219 to 199	Water Table
P-27C	70392	64005	273.8	144 to 139	Aquifer Unit IIB
P-27B	70406	64000	273.8	94 to 74	Aquifer Unit IIA
P-27TE	70440	64006	273.6	-106 to -116	Confining System I-II
P-27TD	70425	64010	273.6	-206 to -216	Aquifer Unit IB
P-27TC	70411	64015	273.6	-286 to -296	Aquifer Unit IB
P-27TB	70397	64019	273.5	-406 to -416	Aquifer Unit IA
P-27TA	70382	64023	273.6	-533 to -543	Aquifer Unit IA

Table 1, Contd

WELL NO.	SRS COORDINATES		GROUND SURFACE	APPROXIMATE ELEVATION SCREENED INTERVAL	HYDROSTRATIGRAPHIC INTERVAL
FC-2F#	79283	55423	286.3	212 to 207	Water Table
FC-2E#	79276	55424	286.9	194 to 189	Aquifer Unit IIB
FC-2D#	79267	55423	287.2	164 to 159	Confining Unit IIA-IIB
FC-2C#	79260	55424	287.5	135 to 130	Aquifer Unit IIA
FC-2B#	79251	55424	287.8	84 to 79	Aquifer Unit IIA
FC-2A#	79244	55424	288.1	57 to 53	Confining System I-II
P-28A	79275	55488	282.6	-47 to -58	Confining System I-II
P-28TE	79296	55515	280.2	-123 to -135	Aquifer Unit IB
P-28TD	79294	55500	281.2	-213 to -223	Aquifer Unit IB
P-28TC	79291	55486	281.6	-272 to -283	Confining Unit IA-IB
P-28TB	79289	55471	282.2	-336 to -358	Aquifer Unit IA
P-28TA	79284	55441	284.9	-462 to -495	Aquifer Unit IA
P-29D	86495	42787	265.8	173 to 153	Water Table
P-29C	86485	42777	266.2	136 to 126	Aquifer Unit IIA
P-29B	86476	42764	266.0	87 to 77	Aquifer Unit IIA
P-29A	86467	42752	266.0	-38 to -49	Confining System I-II
P-29TD	86456	42762	265.6	-142 to -164	Aquifer Unit IB
P-29TC	86464	42773	265.7	-223 to -244	Confining Unit IA-IB
P-29TA	86483	42796	265.6	-403 to -424	Aquifer Unit IA
P-30D	98954	57095	354.1	279 to 259	Water Table
P-30C	98969	57100	354.0	205 to 195	Aquifer Unit I/IIB
P-30B	98983	57104	354.0	135 to 125	Aquifer Unit I/IIB
P-30A	98998	57109	354.0	85 to 75	Aquifer Unit I/IIB
P-30TD	98991	57122	354.0	15 to 4	Aquifer Unit I/IIB
P-30TC	98976	57118	354.1	-95 to -106	Aquifer Unit I/IIB
P-30TB	98962	57113	354.2	-214 to -236	Aquifer Unit I/IIA
P-30TA	98933	57105	354.4	-329 to -351	Aquifer Unit I/IIA

EXISTING WELL

approximate contact with the basement complex. Coreholes ranged in depth from approximately 845 feet at site P-14 to 1066 feet at both sites P-13 and P-15. Approximately 3,000 feet of coring was attempted with a resulting recovery rate of about 40%. Although not a very high recovery rate in terms of coring consolidated formations, 40% was considered to be quite good for the loose sediments penetrated. Recovery in the dense clays generally average between 90 and 100 per cent. The advantage of this technique is that the complete core barrel does not have to be removed from the borehole in order to retrieve the sample; only the inner barrel is removed by a wireline device. A great deal of experience was gained on the use of wireline core barrels from this program. The results of the Phase I program were reported in DPST-84-833 (Bledsoe, 1984b).

Phase II

The Phase II program consisted of continuous geologic coring, geophysical logging, physical testing of selected sediment samples, and construction of 56 observation wells at 8 widely spaced cluster sites (P-16 through P-23), Figure 3. Coreholes ranged in depth from approximately 450 feet at site P-20 to greater than 1200 feet at site P-22. In all, approximately 6350 feet of core was recovered from the approximately 7145 feet of coring attempted, for an overall recovery rate of about 90%. This was more than a twofold improvement over the Phase I drilling. Field activities for the Phase II program began in February 1985 and were completed in January 1986. Details of the Phase II program are summarized in DPST-86-674 (Bledsoe, 1987).

Phase III

The Phase III program consisted of continuous geologic coring, geophysical logging, physical testing of selected sediment samples, and the construction of 53 observation wells at 7 widely spaced cluster sites (P-24 through P-30), Figure 4. Coreholes ranged in depth from approximately 685 feet at site P-26 to 1070 feet at site P-24. In all, more than 6100 feet of coring was attempted with an overall recovery of about 85% (5185 ft). Sediment samples were also collected during the Phase III drilling in support of the Microbiology of the Deep Subsurface Program coordinated by the Department of Energy Office of Health and Environmental Research (OHER). This effort required samples be collected under sterile conditions in order to minimize or prevent contamination from the drilling operation and sample handling. Field activities for the Phase III program began in April 1986 and were completed in July 1987. Details of the Phase III investigation are presented in DPST-88-627 (Bledsoe, 1988).

Figure 3. Location of Phase II Well Clusters

Figure 4. Location of Phase III Well Clusters

SC WATER RESOURCES COMMISSION PROGRAM

The South Carolina Water Resources Commission (SCWRC) in cooperation with the Savannah River Operations Office-DOE and the Savannah River Laboratory began an offsite drilling program in 1986 to obtain detailed geologic and hydrologic information for the area surrounding the SRS. This program was designed as an extension and complement to the SRS Baseline Hydrogeologic Investigation. To date, various stages of work have been completed at 5 of the proposed 10 sites. The location of the proposed 10 well cluster sites, relative to the general SRS site, are presented on Figure 5. Sites where drilling has been conducted are also noted on Figure 5. Work on Phase I of the SCWRC program included sites C-2 and C-6 (Logan, 1987). Phase II included work at cluster sites C-3 and C-5 (Kuntz and Griffin, 1988). Phase III of the program was a cooperative effort with the Microbiology of the Deep Subsurface Program, which included work at cluster site C-10 (Kuntz, et al., 1989). A summary of the wells installed and documented to date is provided on Table 2. Data from the SCWRC program will be correlated with the Baseline data as it becomes available for a more complete delineation of the regional groundwater system.

HYDROGEOLOGY

Stratigraphic Sequence at SRS

The Coastal Plain sequence underlying the SRS forms a seaward dipping wedge of unconsolidated to semiconsolidated fluvial, deltaic, and marine sediments ranging in age from Late Cretaceous to Recent. The sequence thickens from approximately 650 feet at the northern edge of the SRS to 1200 feet at the southern edge. The sediments were deposited over both the Precambrian-Paleozoic aged crystalline basement complex which consists of metamorphic gneiss and schists with intrusive and extrusive igneous rocks and the indurated coarse to fine grained sediments of Triassic age deposited in the fault-bounded Dunbarton Basin, which underlies the southern third of the site.

Revision of the stratigraphic nomenclature of the Coastal Plain sequence is currently being undertaken by the Environmental Sciences Section of SRL. The currently favored stratigraphic nomenclature for the site is presented on Figure 6. Modifications to the nomenclature since the Baseline Reports were published include dividing the Coastal Plain sequence into four Groups; in ascending order, the Lumbee Group, Black Mingo Group, Orangeburg Group, and the Barnwell Group. In addition the revised nomenclature refers to the Ellenton Formation as the Ellenton Member of the Rhems Formation; the McBean Formation as the Santee Formation of which the McBean

Figure 5. South Carolina Water Resources Commission Offsite Drilling Program

**Table 2. Summary of South Carolina Water Resources Commission
Offsite Drilling Program**

Well Number	Latitude Longitude	Elevation of Land Surface	Total Depth	Screened Interval	Stratigraphic Interval Screened
CLUSTER SITE C-2					
AIK-817	33 26 16 81 46 14	418.8	561	520-530	MIDDENDORF
AIK-818	33 26 16 81 46 16	418.2	425	410-420	L. BLACK CREEK
AIK-824	33 26 16 81 46 17	418.7	365	350-360	U. BLACK CREEK
AIK-825	33 26 16 81 46 16	418.9	230	216-226	PEEDEE
AIK-823	33 26 15 81 46 17	----	168	153-163	(Dry Hole)
CLUSTER SITE C-3					
AIK-826	33 32 30 81 29 05	295.2	541	485-495	MIDDENDORF
CLUSTER SITE C-5					
BRN-357	33 19 14 81 24 28	-----	1,085	NONE	(Abandoned)
BRN-358	33 19 14 81 24 28	265.6	847	832-842	MIDDENDORF
BRN-359	33 19 16 81 24 28	265.7	220	199-209	CONGAREE
BRN-360	33 19 15 81 24 28	264.1	139	125-134	DRY BRANCH

Table 2, contd

Well Number	Latitude Longitude	Elevation of Land Surface	Total Depth	Screened Interval	Stratigraphic Interval Screened
CLUSTER SITE C-6					
BRN-349	33 10 42 81 18 55	208.7	1,385	1030-1040	MIDDENDORF
BRN-356	33 10 43 81 18 56	208.6	929	914-924	L. BLACK CREEK
BRN-355	33 10 44 81 18 55	208.0	701	686-696	U. BLACK CREEK
BRN-353	33 10 43 81 18 54	207.6	590	573-583	PEEDEE
BRN-354	33 10 44 81 18 54	207.5	415	396-406	L. CONGAREE
BRN-352	33 10 44 81 18 53	207.1	295	278-288	U. CONGAREE
BRN-350	33 10 45 81 18 54	207.3	170	155-165	DRY BRANCH
BRN-351	33 10 43 81 18 53	207.2	95	80-90	TOBACCO ROAD
CLUSTER SITE C-10					
ALL-348	33 01 30 81 23 03	289.6	1,732	1575-1600	CAPE FEAR
ALL-347	33 01 30 81 23 03	290.0	1,435	1401-1421	MIDDENDORF

North American Stage	European Stage	Groups	Formations	
AgeUnknown	AgeUnknown	Barnwell Group	"Upland Unit"	
Jacksonian	Priabonian		Tobacco Road Sand	
			Dry Branch Formation	Irwinton Sand Mbr Twiggs Clay Mbr Griffins Landing Mbr
			Clinchfield Formation	
Claibornian	Bartonian	Orangeburg Group	Santee Limestone	McBean Member Caw Caw Member Warley Hill Member
	Lutetian		Congaree Formation	
Sabinian	Ypresian	BlackMingo Group	Four Mile Mbr Fishburne Fm	
	Thanetian		Snapp Mbr Williamsburg Fm	
Midwayan	Danian		Ellenton Member Rhens Formation	
Navarroan	Maestrichtian	Lumbee Group	Steel Creek Member Peedee Formation	
Taloran	Campanian		Black Creek Formation	
Austinian	Santonian		Middendorf Formation	
	— ? — Coniacian ? Turonian ?			Cape Fear Formation

Note: Modified from Aadland and Bledsoe (1990)

Figure 6. Proposed Stratigraphic Column for SRS

is a member. Other modifications to the nomenclature include the addition of the Four Mile Member of the Fishburne Formation and the Clinchfield Formation to the base of the Barnwell Group. Until the revision of the site stratigraphy is completed and documented, the nomenclature used in this report is that contained in the Phase III Baseline report dated 1988 modified to include the four stratigraphic groups, Figure 7.

The time-equivalent units of the four formations included in the **Lumbee Group** in the type area are present at SRS. They comprise, from the base upward, the Cape Fear, the Middendorf, the Black Creek, and the Peedee Formations. These Cretaceous age strata have been referred to as the "Tuscaloosa Formation" in previous reports and publications. The thickness of this Group varies from approximately 380 feet at the northwest boundary of the site to more than 740 feet at the southeast boundary. In general, Lumbee Group deposits are variably colored sands and clays but may become calcareous down dip from SRS. At the coast, the group is more than 1500 feet in thickness. The upper surface of the group generally dips to the southeast at approximately 21 feet/mile across SRS.

The basal **Cape Fear Formation** rests directly on the weathered and eroded surface of the basement complex. The formation consists of firm to indurated, poorly sorted, silty, clayey sands and sandy silts and clays. The sands range from fine to more typically coarse grained with granule and pebble zones common. The grains are angular to subangular with feldspar common in the sands and rock fragments common in the pebble zones. These characteristics are indicative of high energy environments close to the sediment source, i.e., a fluvial-continental environment on the upper delta plain. Some investigators favor a marine origin due to the presence of montmorillonite/bentonite clay in these sediments; this clay, however, could also result from volcanic ash deposition. The Cape Fear Formation is typically greenish-gray or grayish-green in color, although this color can only be observed on fresh surfaces due to the rapid oxidation of reduced iron minerals present in the clay fraction. The oxidation of these minerals results in a brownish color.

Only two coreholes, P-25 and P-30, penetrate the Cape Fear to the basement rocks underneath. At cluster P-30, which is in the northwest portion of SRS, 15 feet of Cape Fear was penetrated before encountering weathered gneissic bedrock. Cluster P-25, located at K Area, penetrated 176 feet of Cape Fear and bottomed in the Triassic sediments of the Dunbarton Basin. The top of the Cape Fear Formation has a gentle dip to the southeast of approximately 30 feet/mile.

Overlying the Cape Fear is the **Middendorf Formation**. It consists typically of angular, slightly silty, fine to very

FORMATION NAMES

TIME-STRATIGRAPHIC UNITS

Figure 7. Stratigraphic Column used in Baseline Investigation

coarse sands with pebble and granule zones common in the updip section and clay layers more common in the downdip section. A distinguishing characteristic of these sediments is the presence of angular milky quartz grains, especially in the coarser fractions. The sands are typically light gray to light brown in color although medium gray and brown colors do occur. At updip clusters P-29 and P-30, white, purple, and yellow colors are present. Clays are typically massive and free of sand and silt and are usually light colored although some thin clay layers can be gray to black. The uppermost clay unit at a few cluster locations is variegated red, gray, and white in color. This upper clay unit is present at most cluster locations. The Middendorf sediments underlying most of the SRS were deposited in an upper delta plain environment but grade into quieter lower delta plain environments towards the southeast boundary of the site. At the South Carolina Water Resources Commission cluster site C-6, located approximately 9 miles km southeast of SRS in Barnwell County, the Middendorf contains abundant lignite and iron sulfides.

The Middendorf Formation was penetrated at all cluster sites with the exception of P-20 which was terminated in the upper part of the Cretaceous section. Thickness of the formation ranges from approximately 102 feet at P-16 to 236 feet at P-18, where the bottom of the formation is lower in elevation than would normally be expected from the regional dip of the Cape Fear Formation. Generally the formation dips to the southeast at a gradient of about 26 feet/mile.

The **Black Creek Formation** overlies the Middendorf. In the northeastern part of the SRS these sediments were deposited in an upper delta plain environment where in the southeastern part of the site deposition occurred more often in lower delta plain environments. The sands of the Black Creek are typically silty and fine grained; generally finer grained than the Middendorf. They typically contain lignite, iron sulfides, and muscovite is especially abundant. The color of the sands is mostly medium to dark gray or brown. Thick sequences of clay and silt are also common, especially in the southeastern part of the site. The clays and silts are usually thin-bedded and dark brown or dark gray to black. The formation dips gently to the southeast at a gradient of approximately 22 feet/mile and varies in thickness from approximately 103 feet at P-30 to 216 feet at P-22. The unit was penetrated at all cluster sites with the exception of P-20 which terminated in a shallower zone.

The uppermost Cretaceous unit of the Lumbee Group is the **Peedee Formation**. These sediments were deposited in upper delta plain environments in the northwestern portion of SRS and in lower delta plain environments in the southeastern area of the site. The sediments are sub-angular, slightly clayey,

medium to coarse grained sands interspersed with thick bedded, light colored, clay units. A distinguishing characteristic of the sands is the presence of large mica grains and, to a lesser extent, the presence of garnet grains. Typically, a variegated red, white, tan, and gray thick clay unit is present at or near the top of the formation. At clusters P-25 and P-27, a clayey sand overlies this clay unit. At cluster P-16, the upper clay unit is absent.

The Peedee Formation was penetrated at all clusters except P-20 where the base of this formation was not reached. The Peedee varies in thickness from approximately 148 feet at cluster P-19 to 241 feet at cluster P-21. The formation dips gently to the southeast at approximately 20 feet/mile. The Peedee Formation caps the upper Cretaceous sequence. A major unconformity separates the Peedee from the overlying Tertiary sediments.

The **Black Mingo Group** which consists of the Ellenton Formation and the overlying Williamsburg Formation represents the initial sediments deposited during the Tertiary (Midwayan to Middle Sabinian stage). The group is about 70 feet thick at the northwestern site boundary, 160 feet thick near the southeast boundary, and thickens to about 700 feet at the coast. The **Ellenton Formation** consists of laminated, dark, lignitic clays, silts, and very fine sands deposited in tidal flat environments as well as dark to light, micaceous, clayey, medium to coarse sands deposited in fluvial channel environments. Iron sulfides are common and the water in these sediments can be high in sulfate content due to the oxidation of the sulfides.

At clusters P-16 and P-30, it is not possible to positively identify the Ellenton in the section. The stratigraphic position there is occupied by light-colored, micaceous, clayey sands and thin clays that are more typical of the Williamsburg Formation than the Ellenton. The absence of organic-rich and calcareous sediments at these locations precludes use of fossil dating methods to resolve this problem. Similarly at P-17, the sediments in the upper Ellenton and in all of the overlying Williamsburg Formation are more typical of the clean sands of the overlying Congaree Formation. Whether this is a facies change in the Black Mingo Group lithologies or erosion and downcutting into the Black Mingo Group units followed by infilling by Congaree sands is unresolved at this time. As at P-16 and P-30 the absence of fossil evidence precludes determining the precise stratigraphic relation between the Black Mingo sediments and the overlying Congaree sands. The Ellenton varies from a few feet in thickness at the northwestern edge of the site to about 100 feet at P-22. The dip of the upper surface of the unit is about 18 feet/mile.

The **Williamsburg Formation** consists of light colored clays and micaceous, clayey, medium to coarse sands deposited in fluvial environments indicative of the upper delta plain-lower delta plain interface. The Williamsburg is missing at clusters P-17, P-20, and P-26, and may be missing at cluster locations P-29 and P-30 depending on whether the Paleocene sediments are assigned to the Ellenton or Williamsburg. The formation is thickest at cluster P-23 where it is approximately 58 feet thick. Due to the discontinuous nature of the formation, the dip on the top of the Williamsburg is difficult to calculate, but appears to average about 16 feet/mile across the site.

The **Orangeburg Group** (Claibornian Stage) consists of the Middle Eocene Congaree Formation and the Upper Middle Eocene McBean Formation. The Group crops out at the lower elevations in many places on and near SRS. A pisolitic clay zone that is present at the base of the Claiborne sediments in South Carolina is similar to the clay zone at the base of the Claiborne deposits in the Gulf Coastal Plain. The sediments thicken from approximately 100 feet at the northwestern SRS boundary to about 160 feet near the southeastern boundary. Dip of the upper surface is about 12 feet/mile to the southeast the site. Downdip at the coast, the Orangeburg Group is about 325 feet thick.

Sediments of the **Congaree Formation** are typically sub-rounded, well-sorted, clean sands, fine to very coarse grained with granule and small pebble zones, indicative of beach front depositional environments. Thin, discontinuous clay layers are sometimes present near the middle and bottom of the formation. The sands are typically tan, yellow or light gray, but may be dark gray to black where the silt content is high and dark green where glauconite occurs. At the P-21 cluster site, the upper 35 feet are calcareous and glauconitic and may represent deeper water marine environments. The lower 28 feet of the formation at the P-22 location are glauconitic while at the P-23 cluster location there are two glauconitic zones. A very distinguishing characteristic of the Congaree Formation is the presence of sub-rounded, gray to milky quartz grains. While the occurrence of these grains is not useful in distinguishing the Congaree from the overlying McBean Formation, it is very useful for distinguishing the Congaree from the underlying Williamsburg Formation.

The thickness of the Congaree Formation varies from approximately 50 feet at cluster P-14 to 171 feet at cluster P-17 where the formation fills a channel cut deeply into the underlying Williamsburg and Ellenton Formations. The dip of the top of the Congaree is approximately 16 feet/mile.

The **McBean Formation** overlies the Congaree. One or more glauconitic clay horizons sometimes referred to as the "green clay" are often found at or near the base of the formation. The green clay horizon was not encountered at clusters P-16, P-29, and P-30. In some areas the interval contains carbonate bank deposits that can act as conduits for groundwater flow into the Congaree Formation below. Depending on the geographic location, this clay unit grades upward into either a very fine to medium, clean "beach" sand, a calcareous sand, a marl, or a limestone. Dissolution of the calcareous material in this formation by groundwater has in places produced vugs and solution channels. Typical colors of the McBean sediments are yellow, tan, white, and lime-green. At the northern end of the SRS, the McBean sediments are difficult to distinguish from sediments of the underlying Congaree and the overlying Barnwell Group.

The late Eocene **Barnwell Group** is subdivided into the Dry Branch and Tobacco Road Formations. The basal **Dry Branch Formation** was deposited under oxidizing, shallow marine conditions and consists of tan, red, or yellow laminated clays and both clayey and clean, fine to medium grained sands. This formation can be further subdivided into the Clinchfield Sand Member, Griffins Landing Limestone Member, Irwinton Sand Member, and the Twiggs Clay Member. For the purpose of this study, however, no attempt has been made to differentiate the formation into the various members. The Twiggs Clay Member is interbedded with the other members and can appear anywhere in the section. The Twiggs clay is correlative with the "tan clay" and consists of thin, laminated clays and clayey sand. The Clinchfield Sand Member occurs at the base of the Dry Branch Formation and can only be identified where the limestone deposits in the McBean Formation and the limestone deposits in the Dry Branch are present. The Irwinton Sand Member occurs at the top of the formation. A zone with characteristically flat, discoidal pebbles occurs at the base of the Irwinton Sand. The Griffins Landing Member consists of limestone and calcareous sands and is characterized by the abundance of the distinctive Ostrea gigantissima oyster fossils. The uppermost Eocene unit is the Tobacco Road Formation which consists of red, purple, white, and orange laminated or mottled clayey, very fine to fine sands and sandy clays. As with the Dry Branch Formation, the depositional environment of the Tobacco Road Formation was a shallow shelf; however, this formation is more representative of a deeper water facies, whereas the Dry Branch was deposited closer to the beach face.

Overlying and cutting into the sediments of the Barnwell Group is the **Upland Unit** consisting of clayey, poorly sorted, feldspathic, angular, pebbly, coarse sand and sandy pebble zones. Cross-bedding is evident in outcrop. These sediments represent fluvial channels cut into the late Eocene beds prob-

ably during Oligocene or Miocene times. Typical colors for these sediments are red and orange. Distinguishing characteristics of these sediments include cross-bedding laminations and the presence of white clay balls typically around 1/4 inch in diameter.

Hydrostratigraphy

Laney and Davidson (1986) recommended to the USGS Water Resources Division a preferred system for naming hydrogeologic units in USGS reports. These recommendations suggest that aquifers be named primarily on the bases of either lithologic terms (sand and gravel aquifer), rock-stratigraphic names (Middendorf aquifer), or geographic locations (Dublin aquifer system in Georgia). They further suggest that aquifer or aquifer systems not be derived from time-stratigraphic names (Cretaceous aquifer), relative position (upper sand aquifer), depositional environment (shallow marine aquifer), depth of occurrence (200-foot sand), alphanumeric designations (aquifer A1), or hydrologic condition (water table aquifer).

Recommended guidelines for the classification of hydrostratigraphic units in South Carolina are currently being developed for the state by the South Carolina Hydrostratigraphic Nomenclature Subcommittee. This subcommittee is represented by members from industry and federal and state agencies, including SRS. The preliminary draft classification system developed by the subcommittee (Burt, 1988) combines guidelines published by Laney and Davidson (1986) and the North American Stratigraphic Code (Seaber, 1986). A summary of the proposed classification system is presented on Table 3.

This recommended classification of hydrostratigraphic units is based solely on hydraulic properties of the sediments and rocks. These properties include, but are not limited to, hydraulic conductivity, porosity, and specific storage. Additionally, lithology should be considered only relative to hydraulic properties. The use of geographic names, independent of stratigraphic nomenclature, is desirable because hydrogeologic units can cross time and geologic formation boundaries. Ideally, alphanumeric designations should only be used when discussing layers in a numerical flow model; however, in the absence of accepted names for the hydrogeologic units, this type of terminology may offer the best alternative for the SRS, pending formal designations.

Aquifer and confining units are the fundamental units of the classification system. As defined by the Subcommittee, an **aquifer** is "a body of rock or sediments, on a mappable scale (>400 square miles), that is sufficiently permeable to conduct groundwater and to yield significant quantities to wells and springs", while a **confining unit** is "a body of rock or

**Table 3. Summary of South Carolina Hydrostratigraphic
Nomenclature Subcommittee Proposed
Classification System**

Rank	Proposed South Carolina Hydrostratigraphic Units (after Laney and Davidson, 1986)	Corresponding NASC Units (Seabar, 1986)
1	Aquifer/Confining System	Aquigroup
2	Aquifer/Confining Unit	Aquiformation
3	Aquifer/Confining Zone	Aquimember/Aquibed

Note: Modified from Burt (1988)
NASC = North American Stratigraphic Code

sediment, on a mappable scale, of significantly lower hydraulic conductivity than an adjacent aquifer that serves as an impediment to ground water flow to or from an aquifer". Both aquifer and confining units may be further subdivided into **zones** which have characteristic properties significantly different from the main unit. For example these properties may included differences in hydraulic conductivity, water chemistry or lithology.

On a regional basis, aquifer and confining units can be grouped into **systems**. A **confining system** may be composed of two or more coalescing confining units and aquifers that as a whole serve as an impediment to groundwater flow. An **aquifer system** may be composed of two or more coalescing aquifer and confining units that as a whole readily transmit groundwater.

At the SRS the terms "Lower Tuscaloosa Aquifer", "Upper Tuscaloosa Aquifer", "Congaree Aquifer", "McBean Aquifer", and "Barnwell Aquifer" have been used to describe the aquifer units beneath the site since the 1960's. "Mid Tuscaloosa clay", "lower Tuscaloosa clay", Ellenton Formation, and "green clay" have been used synonymously with confining units at the site. With the change in the stratigraphic nomenclature to include formational names previously not used, Figure 6, the hydrostratigraphic nomenclature used at SRS will also have to undergo changes to make site terminology more compatible with the usage of state and federal agencies. Agreement with the naming and designation of the SRS hydrostratigraphy to conform to a regional classification system will probably not be reached until additional work is completed by: 1) the South Carolina Water Resources Commission (SCWRC) as part of the offsite drilling program and the results correlated with SRS data, and 2) the South Carolina Hydrostratigraphic Nomenclature Subcommittee.

In the absence of accepted and agreed upon names for the hydrogeologic units, at this time, it is suggested that within the boundary of SRS, the coastal plain sequence be divided into four main hydrostratigraphic systems; from bottom to top, **Confining System I**, **Aquifer System I**, **Confining System I-II**, and **Aquifer System II** (Aadland and Bledsoe, 1990). However, northwest of Upper Three Runs Creek, in the northwest corner of the site, Aquifer Systems I and II coalesce forming a single system, **Aquifer System I/II**. (Note: confining intervals, either systems, units, or zones are designated by hyphenating the name of the overlying and underlying aquifer; while coalescing aquifer systems, units, or zones are designated with a "/" between the intervals).

A generalized correlation between the stratigraphic units and the hydrostratigraphic units is provided on Figure 8. It should be emphasized that this is a very general

COMPARISON OF HYDROSTRATIGRAPHIC UNITS USED AT SRS			
AGE	Geologic	Stratigraphic	Hydrostratigraphic
TERTIARY	Siple (1967)	SRP Baseline Hydrogeologic Study Bledsoe (1987&1988)	Proposed Aquifer Nomenclature Hadland and Bledsoe (1990)
	HAYTHORN AQUIFER	UPLAND UNIT	Aquifer Unit IIB
	BARNWELL AQUIFER	TOBACCO ROAD FORMATION	Aquifer Unit IIC
		DRY BRANCH FORMATION	CONFINING UNIT IIA-IIB
	MCNEAL AQUIFER	MCNEAL FM Green Clay	Aquifer Unit IIA
		COGAREE FORMATION	
	ELLESTON AQUITARD	WILLIAMSBURG FORMATION	CONFINING SYSTEM I-II
		ELLESTON FORMATION	
	UPPER TUSCALOOSA AQUIFER	PEDDER FORMATION	Aquifer Unit IB
	MID TUSCALOOSA CLAY AQUITARD	BLACK CREEK FORMATION	CONFINING UNIT IA-IB
CRETACEOUS	LOWER TUSCALOOSA AQUIFER	MIDDLEDORF FORMATION	Aquifer Unit IA
	BASAL CLAY AQUITARD	CAPE FEAR FORMATION	
			CONFINING SYSTEM I
TRIASSIC OF PALEOZOIC BASEMENT		PALEOZOIC - TRIASSIC BASEMENT HYDROLOGIC SYSTEM	

Note: Not to Scale

Figure 8. Generalized Correlation between Stratigraphic and Hydrostratigraphic Units

correlation and that the boundaries of the hydrogeologic units do not necessarily correspond to formational boundaries. Also, found within the different aquifer and confining units can be **zones** of relatively lower or higher permeability. These **zones** are not of sufficient thickness or lateral extent to be elevated to the status of **unit**; however, at specific sites, these zones may have significant impact on the local groundwater flow regime. Relatively undisturbed samples were collected from the potential confining layers for laboratory testing of physical properties. No undisturbed samples were collected from the aquifer sands. However, grain size distributions were determined from composite samples from the entire screened section for most of the wells installed. The grain size curves for these wells are presented in Appendix F. Single well pumping tests at selected wells in each of the 18 clusters are currently in progress as part of the Aquifer Characterization Study. These data will provide more definitive information on the individual hydrogeologic units than could be obtained from conducting laboratory tests on a single sample of the sediments.

Confining System I correlates generally with the Cape Fear Formation and represents the bottom of the Cretaceous section at SRS, Figure 8. The fine grained and clayey character of the Cape Fear Formation creates an effective confining unit separating the water-bearing units of the Cretaceous section from the water of poor quality found in the basement complex, which is composed of Paleozoic crystalline and Triassic age sediments. Off the plant site and downdip the sediments within the Cape Fear become more sandy and the unit is used for groundwater withdrawal. At the SCWRC well cluster C-10, located about 15 miles south of the plant (Figure 5), the deepest well is completed within sands of the Cape Fear.

Aquifer System I includes sediments of Cretaceous age. Over the main body of the SRS, Aquifer System I can be divided into two aquifers; from bottom to top they are designated Aquifer Units IA and IB, separated by Confining Unit IA-IB, Figure 8. The water producing zones within System I constitute the major aquifers beneath the SRS as well as the region immediately surrounding the site. Wells completed within Aquifer System I are capable of producing thousands of gallons per minute. This System includes:

Aquifer Unit IA overlies Confining System I and generally corresponds to the Middendorf Formation. However, sand zones in the lower 1/3 of the Black Creek Formation, which are in communication with the Middendorf sands are also placed within this aquifer unit. Collectively these units represent the "lower Tuscaloosa aquifer" as used in previous reports.

Confining Unit IA-IB overlies Aquifer Unit IA and consists of silty and clayey sediments found mainly within the middle 1/3 of the Black Creek Formation. The formation, which as a whole is more fine grained and less transmissive than the underlying and overlying formations, contains significant clay layers that can retard vertical flow. However, these layers do not appear to be laterally continuous over large distances and are generally concentrated in the middle third of the formation. This confining sequence generally corresponds to what was previously known as the "mid Tuscaloosa Clay" in earlier reports. Sand layers which occur in the formation are assigned to either the underlying Aquifer Unit IA or the overlying Aquifer Unit IB. However, because of the overall lithologic and physical character of the formation, the middle third of the Black Creek Formation can generally be considered a confining unit between the two major water producing units. This confining unit persists as a hydrologic barrier to vertical groundwater flow within Aquifer System I over most of the site; however, the unit thins and pinches out in the vicinity of the P-19 well cluster and is discontinuous north of this general location.

Aquifer Unit IB is persistent through out the SRS and includes sandy sediments found generally within the upper 1/3 of the Black Creek Formation and the sands of the overlying Peedee Formation that are hydraulically connected. This aquifer unit corresponds basically to the "upper Tuscaloosa aquifer" terminology of older reports.

Overlying Aquifer System I is a sequence of clay beds found mostly within the Paleocene age Williamsburg and Ellenton Formations. The thickness and lateral continuity of these beds together with clays found in formations immediately above or below form an effective confining unit separating the overlying Tertiary age sediments from the underlying Cretaceous sediments over most of the SRS. Because of the thickness and lateral continuity of these units, it is suggested that this sequence be classified as **Confining System I-II**. Both the Williamsburg and Ellenton Formations contain sand units that are capable of producing significant quantities of water; however, these are relatively thin and discontinuous and do not constitute what would be considered major aquifers. At the P-30 cluster site, the entire Paleocene sequence is basically a sand with little or no clay to form an effective confining unit. Therefore, at this location there is probably good vertical communication between the aquifers within the Tertiary and Cretaceous age formations.

Aquifer System II includes all hydrogeologic units within the Tertiary age sediments overlying Confining System I-II. Between Upper Three Runs Creek (UTRC) and the southern boundary of the plant, this system is divided into two Aquifer Units separated by a Confining Unit. From bottom to top they are designated as Aquifer Unit IIA, Confining Unit IIA-IIB, and Aquifer Unit IIB, Figure 8.

Aquifer Unit IIA includes sands in the Congaree Formation and formations immediately above and below. This unit forms an aquifer second in importance only to the aquifers within Aquifer System I. Wells completed within Aquifer Unit IIA are capable of producing hundreds of gallons per minute.

Confining Unit IIA-IIB separates Aquifer Unit IIA from the overlying hydrogeologic units. This confining unit corresponds to the "green clay" interval found at and near the base of the McBean Formation. The confining interval generally consists of one or more thin but persistent clay beds; however, south of the P-19 cluster both clay beds and continuous limestone and carbonate-rich clastic beds dominate the interval in the southern third of the site and beyond. Confining Unit IIA-IIB is second in importance only to the clays of Confining System I-II as a major aquitard. The unit is not as laterally continuous as Confining System I-II; however, where present (especially in the central and southern part of the plant) the unit supports a significant head drop (greater than 20 feet in areas) in wells completed above and below.

Aquifer Unit IIB groups all sediments above Confining Unit IIA into the same general unit. This unit includes the water table and depending on the topographic and physiographic location on the site may include, with increasing depth, one or more confined or semi-confined aquifer zones. The water table is generally found within the Barnwell Group (Tobacco Road and Dry Branch Formations). Individual sand zones within the McBean Formation may be quite transmissive. Because of the overall heterogeneity of the sediments assigned to Aquifer Unit IIB, the unit is not considered a significant aquifer on the plant site.

Generally northwest of Upper Three Runs Creek, in the northwest corner of the SRS, the thickness and continuity of Confining System I-II is reduced and Aquifer Systems I and II coalesce forming a single system, **Aquifer System I/II**. In this part of the plant site **Aquifer Unit I/IIA** becomes the hydrologic equivalent of Aquifer Unit IA and **Aquifer Unit I/IIB** becomes the equivalent of Aquifer Unit IB. As a result of the

erosion by local stream systems and the thin and sporadic character of the clay beds in Confining Unit IIA-IIB, Aquifer Units IIA and IIB coalesce to form **Aquifer Unit I/IIC**. These three aquifer units are separated from each other by two confining units, **Confining Unit I/IIA-I/IIB** and **Confining Unit I/IIB-I/IIC**, Figure 8.

Hydrostratigraphic Cross Sections

Hydrogeologic cross sections in both strike and dip directions are presented on Plates 1 through 5. The locations of the section lines are shown on Figure 9. These sections were developed from a detailed analysis of all pertinent geophysical, core, and hydrologic data available. Although limited to the confines of SRS for the purpose of this report, these cross sections incorporate data from the SCWRC offsite well clusters, where appropriate. The delineation and correlation of the hydrostratigraphic units shown on the cross sections, although based largely on lithology and the inferred different hydraulic characteristics associated with lithology (i.e. sands vs clays and silts), potentiometric head, laboratory test, and pumping test data have been incorporated in selecting hydrogeologic unit boundaries. Graphic logs of the coreholes drilled as part of the Baseline Study and used in the preparation of the cross sections are provided in Appendix A. As illustrated on the sections and discussed in detail above, the coastal plain sequence overlying Confining System I is divided into two Aquifer Systems (System I and II) separated by a Confining System (System I-II). What is also shown on the sections are areas where there are departures from the two Aquifer and one Confining System. Northeast of Upper Three Runs Creek, in the northwest corner of SRS, Aquifer Systems I and II coalesce forming a single system, Aquifer System I/II. This coalescing of Aquifer and Confining Systems and Units is illustrated on Plates 1, 4, and 5. Also, due to apparent erosion by the local stream system and the thin and sporadic character of the clay beds found in Confining Unit IIA-IIB, Aquifers IIA and IIB appear to be hydraulically interconnected northwest of Upper Three Runs Creek. Between Upper Three Runs Creek and the southern boundary of SRS, Confining Unit IIA-IIB, which is informally termed the "green clay" consists of both clay beds and continuous limestone and carbonate-rich clastic beds that dominate the stratigraphic sequence in the southern third of the site and beyond, Plates 1, 2, and 5. As more information becomes available from subsequent borings drilled on the SRS, these correlations may change to reflect a better understanding of the complex sedimentary sequence that underlies the plant site and the surrounding region.

Figure 9. Location of Hydrostratigraphic Cross Sections

Low Permeability Layers

The formations that form effective confining units of significance were described above. However, scattered throughout the entire coastal plain sequence are numerous discontinuous low permeability layers which serve as impediments to the flow of groundwater. The distribution of these layers, generally greater than two feet in thickness, at each cluster location, is shown on the individual cluster profiles, Figures B-1 through B-19, in Appendix B. The major clay layers have been correlated between cluster sites as illustrated on the hydrostratigraphic cross sections presented on Plates 1 through 5. The continuity of the clay layers as shown on the cross-sections help to define the boundaries of the major water producing units.

In order to obtain information on the water transmitting properties of these thin units as well as on the major confining units, undisturbed samples were collected from most of the major clay layers or apparent low permeability zones encountered at each cluster site. These samples were then analyzed in the laboratory for determination of horizontal and vertical permeability, porosity, dry unit weight, moisture content, and grain size distribution. These results are tabulated on Table D-1 of Appendix D. In addition, grain size distributions were determined for each of the samples and are provided in Appendix E. The measured hydraulic conductivity values presented on Table D-1 range from as high as 10^{-4} cm/sec to as low as 10^{-9} cm/sec within these layers; however, the values dominantly fall within the 10^{-7} cm/sec to 10^{-8} cm/sec range.

Water Levels

Water levels in wells at each cluster site are provided on Figures B-1 through B-19 of Appendix B. These figures also provide information on the vertical gradients present at each location. The well completion diagrams, which give the construction details for each well installed as part of the Baseline Investigation are provided in Appendix G. Figures C-1 through C-18, found in Appendix C, are hydrographs for selected wells in each cluster for the first full year (April 1987 to March 1988) of data collection following completion of all 18 cluster sites. These figures illustrate the changes in the water levels in the wells with time. The wells selected for the hydrographs generally provide information on Aquifer IIA (largely the Congaree Formation), in places aquifer zones within Confining System I-II (largely the Williamsburg/Ellenton Formations), Aquifer Unit IB (Peedee/Black Creek Formations), and Aquifer Unit IA (Black Creek/Middendorf Formations). The screen zone elevation and hydrostratigraphic unit in which each well is completed are presented on Table 1.

Based on the hydraulic head distribution in wells screened below the water table, the cluster sites can be grouped into 4 general categories: 1) sites where the heads in Aquifer System I (upper Cretaceous formations) are higher than in Aquifer Unit IIA (lower Tertiary Congaree), i.e. **head reversal**; 2) sites where the heads in Aquifer IIA (lower Tertiary Congaree) are higher than in Aquifer System I (upper Cretaceous formations), i.e. **no head reversal**; 3) sites where the heads in Aquifer Unit IIA (lower Tertiary Congaree) are higher than in Aquifer IB (Peedee/Black Creek), no head reversal, but the heads in Aquifer Unit IA (Black Creek/Middendorf) are higher than in Aquifer Unit IIA; and 4) sites where Aquifer Systems I and II coalesce to form one Aquifer System, Aquifer System I/II. The differing heads and spacial variability reflects the influence of natural recharge and discharge, pumping, and varying hydraulic properties within the different units and within the same hydrologic unit.

At each of the 9 sites that fall into **category 1**, there is a continuing decrease in hydraulic head with increasing depth down to Confining System I-II (Williamsburg/Ellenton Formations) below which the heads increase. Five of the nine sites (P-18, P-21, P-22, P-23, and P-26) not only show a head reversal across Confining System I-II but show an increase in head with increasing depth within Aquifer System I; i.e., the heads in Aquifer Unit IA (lower part of the Cretaceous) are higher than in Aquifer Unit IB (upper part of the Cretaceous), Figures B-6, B-9, B-10, B-11, and B-14, respectively. Three sites in category 1 (P-14, P-28/FC-2, and P-29) show that the heads in both Aquifer Units IA and IB are higher than in Aquifer Unit IIA (Congaree Formation), Figures B-2, B-16/B-17, and B-18. At the P-27 cluster, Figure B-15, there is only a very slight (< 1 foot) increase in head across Confining System I-II.

All of the five cluster sites (P-17, P-19, P-20, P-24, and P-25) which fall into **category 2** (no head reversal across Confining System I-II), show heads that are lower in Aquifer System I than found in Aquifer Unit IIA immediately above Confining System I-II, Figures B-5, B-7, B-8, B-12, and B-13, respectively.

There are two clusters which fall into **category 3**, P-13 and P-15. At these sites there is no head reversal across Confining System I-II; however, the heads in Aquifer Unit IA (Black Creek/Middendorf Formations) are higher than in Aquifer Unit IB (Peedee/Black Creek Formations) and are also higher than in Aquifer Unit IIA (Congaree Formation). At these locations the head reversal occurs across Confining Unit IA-IB. Data for these clusters are presented on Figures B-1 and B-3.

Two of the cluster sites are located in areas of the plant site where Aquifer Systems I and II coalesce and are not separated by the regional confining system (Confining System I-II) and are included as **category 4** sites. At the P-16 site, there is a head reversal across Confining Unit I/IIB-I/IIC, Figure B-4. However, at the P-30 site, there is a continuing decrease in head with increasing depth below the water table in each of the aquifer units, Figure B-19.

Using the water level data collected from the SRS Baseline Observation Well Network, potentiometric maps have been constructed for three aquifer units. These include Aquifer Unit IIA of Aquifer System II (Congaree Formation) and Aquifer Units IA and IB of Aquifer System I (Peedee/ Black Creek and Black Creek/Middendorf Formations), Figures 10, 11, and 12, respectively. In addition, a comparison of the heads within the two major aquifer systems, across the principal confining unit, is presented in the form of a head difference map on Figure 13.

CONCLUSIONS

The SRS Baseline Hydrogeologic Investigation has greatly improved the overall knowledge of the geology and hydrogeology of the SRS. Data from this program have been and continue to be used in support of other programs such as the development of a numerical groundwater flow model of the site (GeoTrans, 1989), Microbiology of the Deep Subsurface Program, Environmental Impact Statements, Safety Analysis Reports, design of new water supply wells, and the proposed collaborative study of groundwater flow beneath the Savannah River by the U.S. Geological Survey. The SRS Aquifer Characterization Study, which is a continuation of the Baseline Study, will collect water quality and geochemical data from the different aquifer units along with additional physical characteristics such as transmissivity and hydraulic conductivity. This effort will allow for a more definitive delineation of the different aquifer systems and units.

Hydrographs will be maintained for wells in the network. At sites close to areas of the plant where high groundwater withdrawals occur, fluctuation of the water levels in the producing zones is very evident (P-30, P-27, P-28, P-24, P-18, etc.). Data from the Baseline Network will allow changes and trends in the water levels within the major aquifer units to be documented and evaluated in greater detail than in the past and aid in overall water resource management of the site.

Figure 10. Potentiometric Surface Map for Aquifer Unit IIA
(Congaree Formation) July 1990

**Figure 11. Potentiometric Surface Map for Aquifer Unit IA
(Black Creek/Middendorf Formation) July 1990**

**Figure 12. Potentiometric Surface Map for Aquifer Unit IB
(Peedee/Black Creek Formation) July 1990**

NOTE: Positive (+) contours represent areas where the potentiometric surface for aquifers in Cretaceous age sediments is higher than in the overlying aquifer in Tertiary age sediments (Head Reversal).

Figure 13. Head Difference Map for Aquifer Units IB and IIA
July 1990

REFERENCES

- Aadland, R. K. and H. W. Bledsoe, 1990. **Classification of Hydrostratigraphic Units at Savannah River Site, South Carolina**, USDOE Report WSRC-RP-90-987, Savannah River Site, Aiken, SC.
- Bledsoe, H. W., 1988. **SRP Baseline Hydrogeologic Investigation - Phase III**, DPST-88-627, E. I. du Pont de Nemours and Company, Savannah River Laboratory, Aiken, SC.
- Bledsoe, H. W., 1987. **SRP Baseline Hydrogeologic Investigation - Phase II**, DPST-86-674, E. I. du Pont de Nemours and Company, Savannah River Laboratory, Aiken, SC.
- Bledsoe, H. W., 1984a. **Program Plan for SRP Baseline Hydrogeologic Investigation - Observation Well Network**, DPST-84-303, E. I. du Pont de Nemours and Company, Savannah River Laboratory, Aiken, SC.
- Bledsoe, H. W., 1984b. **SRP Baseline Hydrogeologic Investigation - Phase I**, DPST-84-833, E. I. du Pont de Nemours and Company, Savannah River Laboratory, Aiken, SC.
- Burt, R., 1988, **Proposed Criteria for Nomenclature-Draft**, South Carolina Hydrostratigraphic Subcommittee.
- E. I. du Pont de Nemours & Co., 1988. **Final Safety Analysis Defense Waste Processing Facility**, DPSTSA-200-10, Savannah River Laboratory, Aiken, SC, June 1988 Draft.
- GeoTrans, Inc., 1989. **A Numerical Model of the Hydrogeological System Underlying the Savannah River Plant**, Report submitted to Savannah River Laboratory, June 1989.
- Kuntz, G. B. and W. T. Griffin, 1988. **Hydrogeologic Investigation and Establishment of a Permanent Multi-Observational Well Network in Aiken, Allendale, and Barnwell Counties South Carolina--Phase II**, State of South Carolina Water Resources Commission, Open-File Report No. 28.
- Kuntz, G. B., W. T. Griffin, T. Greaney, and J. A. Gellici, 1989. **Hydrogeologic Investigation and Establishment of a Permanent Multi-Observational Well Network in Aiken, Allendale, and Barnwell Counties South Carolina--Phase III**, State of South Carolina Water Resources Commission, Open-File Report No. 32.
- Laney, R. L. and C. B. Davidson, 1986. **Aquifer-Nomenclature Guidelines**, U. S. Geological Survey Open-File Report 86-534.

Logan, W. R., 1987. **Geohydrologic Investigation and Establishment of a Permanent Multi-Observational Well Network in Aiken, Allendale, and Barnwell Counties South Carolina-Phase I**, State of South Carolina Water Resources Commission, Open-File Report No. 23.

Seaber, P. R., 1986. **Application for Amendment of North American Stratigraphic Code to Provide Procedures for Classifying and Naming Hydrostratigraphic Units**, unpublished.

APPENDIX A: GRAPHIC GEOLOGIC LOGS

GRAPHIC GEOLOGIC LOGS

As the basis for the lithologic and hydrologic interpretation at each cluster location, the deepest boring at each site was continuously cored and geophysically logged. The cores were analyzed and described in SRL's Core Laboratory using a binocular microscope. Certain characteristics of the sediments were recorded on one foot intervals, entered into a computer data base, and merged with the geophysical logs. These data were then integrated to produce the detailed graphic logs for each of the clusters as presented on Figures A-2 through A-19.

The geophysical parameters recorded on the graphic logs include natural gamma (N. Gamma), spontaneous potential (S.P.), short and long normal resistivity (16\64 Res.), single point resistivity (S. Point), and caliper (Cal.). The percentage of gravel, lignite, glauconite, and muscovite along with a sand percentage curve is also plotted on the graphic log. The sand curve gives the percentage of sand vs clay and silt content with 100% sand indicated to the left and 100% clay and silt to the right. Where carbonate material is present in the section, the percentage is indicated on the sand curve by a black pattern with 100% to the right. A plot of the modal and maximum grain sizes is also given with the thinner line indicating the maximum and the thicker line the modal grain size. Gaps in the data indicate an interval where core was missing.

The lithology column of the logs uses six basic patterns to convey the lithologic character of the sediments. These patterns are presented on Figure A-1. The locations of the screen zones for each well in the cluster are provided along the side of the lithologic column. It should be noted that the lithologies represented on the graphic logs may differ from that presented on the hydrostratigraphic cross-sections. Each was constructed at different times and for different purposes. For example, the muscovite-rich sand beds are delineated on the cross-sections but not necessarily on the graphic logs.

Figure A-1. Legend for Graphic Geologic Logs

Figure A-2. Graphic Geologic Log for P-13 Cluster.

Figure A-2, cont'd

Figure A-2, cont'd

Figure A-3. Graphic Geologic Log for P-14 Cluster.

Figure A-3, cont'd

Figure A-4. Graphic Geologic Log for P-15 Cluster.

Figure A-4, cont'd

Figure A-4, cont'd

Figure A-5. Graphic Geologic Log for P-16 Cluster.

Figure A-5, cont'd

Figure A-6. Graphic Geologic Log for P-17 Cluster.

Figure A-6, cont'd

Figure A-6, cont'd

Pebble (gravel) Coarse Fine Sand Clay Sand Carb. Gravel Lignite Glauconite Muscovite

Modal Size Carb. Gravel Lignite Glauconite Muscovite

Elev Depth Gamma 16'64 Res. Point Ca.

296 0 250 50 200 100 150 100 200 50 250 0 300 50 350 400

Feet CPS m.v. Ohm-M. Ohms In.

Figure A-7. Graphic Geologic Log for P-18 Cluster.

Figure A-7, cont'd

Figure A-8. Graphic Geologic Log for P-19 Cluster.

Figure A-8, cont'd

Figure A-8, cont'd

Pebble
Gravel
Coarse
Fine Sand
Clay
Sand %
Carb. %
Gravel %
Lignite %
Glauconite %
Muscovite %

P-20

Figure A-9. Graphic Geologic Log for P-20 Cluster.

Figure A-9, cont'd

Figure A-10. Graphic Geologic Log for P-21 Cluster.

Figure A-10, cont'd

Figure A-10, cont'd

Figure A-11. Graphic Geologic Log for P-22 Cluster.

Figure A-11, cont'd

Figure A-11, cont'd

Figure A-12. Graphic Geologic Log for P-23 Cluster.

Figure A-12, cont'd

Figure A-12, cont'd

Figure A-13. Graphic Geologic Log for P-24 Cluster.

Figure A-13, cont'd

Figure A-13, cont'd

P-25

Figure A-14. Graphic Geologic Log for P-25 Cluster.

Figure A-14, cont'd

Figure A-14, cont'd

Figure A-15. Graphic Geologic Log for P-26 Cluster.

Figure A-15, cont'd

Figure A-16. Graphic Geologic Log for P-27 Cluster.

Figure A-16, cont'd

Figure A-16, cont'd

Figure A-17. Graphic Geologic Log for P-28 Cluster.

Figure A-17, cont'd

Figure A-18. Graphic Geologic Log for P-29 Cluster.

Figure A-18, cont'd

Figure A-19. Graphic Geologic Log for P-30 Cluster.

Figure A-19, cont'd

APPENDIX B: WELL CLUSTER PROFILES

WELL CLUSTER PROFILES

Profiles have been prepared for each of the 18 cluster sites and are presented on the following figures. These profiles provide a visual comparison of the depth relationships of each well in the cluster. In addition to showing the screen setting for each well, the locations of the major confining units and low permeability zones are also identified along with the boundaries of the major aquifer units and the water level data collected during July 1990. The coastal plain sequence is delineated on the basis of hydrostratigraphy and not on the basis of geologic formation. The hydrostratigraphic nomenclature used is the classification system discussed in the report. The locations of the zones from which undisturbed samples were collected for laboratory testing are also provided. The results of these tests are summarized in Appendix D and the grain size distributions curves for the samples are provided in Appendix E.

P-13

Figure B-1. Profile of P-13 Well Cluster

Figure B-2. Profile of P-14 Well Cluster

P-15

Figure B-3. Profile of P-15 Well Cluster

P-16

Figure B-4. Profile of P-16 Well Cluster

P-17

D C B A TD TC TB TA

Figure B-5. Profile of P-17 Well Cluster

P-18

Figure B-6. Profile of P-18 Well Cluster

P-19

D C B A TD TC TB TA P-10A

Figure B-7. Profile of P-19 Well Cluster

P-20

D C B TD

Figure B-8. Profile of P-20 Well Cluster

P-21

D B A TD TC TB P-5A

Figure B-9. Profile of P-21 Well Cluster

P-22

Figure B-10. Profile of P-22 Well Cluster

P-23

Figure B-11. Profile of P-23 Well Cluster

P-24

Figure B-12. Profile of P-24 Well Cluster

P-25

Figure B-13. Profile of P-25 Well Cluster

B-15

P-27

Figure B-15. Profile of P-27 Well Cluster

B-17

FC-2

Figure B-17. Profile of FC-2 Well Cluster

P-29

Figure B-18. Profile of P-29 Well Cluster

P-30

Figure B-19. Profile of P-30 Well Cluster

APPENDIX C: HYDROGRAPHS FOR SELECTED WELLS

HYDROGRAPHS

Water level measurements were collected each month for a full year following completion of the SRS Baseline Observation Well Network. However, there was a break in the data collection beginning in March 1988 due to installation of instrumentation, installation of dedicated sampling pumps, collection of groundwater samples, and initiation of single well pumping test. During this time interval measurements were collected on a sporadic basis. Hydrographs have been prepared for wells completed in each of the major aquifer units at each cluster site for this full year (April 1987 to March 1988) of uninterrupted data collection. Monthly measurements on a regular basis have now resumed.

Figure C-1. Hydrographs for P-13 Cluster

Figure C-2. Hydrographs for P-14 Cluster

Figure C-3. Hydrographs for P-15 Cluster

Figure C-4. Hydrographs for P-16 Cluster

Figure C-5. Hydrographs for P-17 Cluster

Figure C-6. Hydrographs for P-18 Cluster

Figure C-7. Hydrographs for P-19 Cluster

Figure C-8. Hydrographs for P-20 Cluster

Figure C-9. Hydrographs for P-21 Cluster

Figure C-10. Hydrographs for P-22 Cluster

Figure C-11. Hydrographs for P-23 Cluster

Figure C-12. Hydrographs for P-24 Cluster

Figure C-13. Hydrographs for P-25 Cluster

Figure C-14. Hydrographs for P-26 Cluster

Figure C-15. Hydrographs for P-27 Cluster

Figure C-16. Hydrographs for P-28 Cluster

Figure C-17. Hydrographs for P-29 Cluster

Figure C-18. Hydrographs for P-30 Cluster

APPENDIX D: SUMMARY OF LABORATORY TESTS

SUMMARY OF LABORATORY TESTS

Undisturbed core samples from the low permeability units identified from the corehole drilled at each cluster location were collected during the drilling of the individual wells. These samples were collected utilizing either a Pitcher barrel or Shelby tube sampler. In all a total of 96 samples were collected for testing. Physical characteristics determined included dry unit weight, moisture content, specific gravity, total porosity, grain size distribution, and both vertical and horizontal hydraulic conductivity. All tests were conducted in accordance with applicable ASTM specifications. The results of these tests are summarized on Table D-1 and have been grouped according to hydrologic unit. The locations from which the samples were collected are also identified on the individual well cluster profiles in Appendix B, Figures B-1 through B-19. The grain size distribution analyses have not been included in this report. These data are available in the individual Baseline Reports (DPST-84-833, DPST-86-674, and DPST-88-627).

Table D-1. Summary of Laboratory Test Results by Hydrologic Unit

<u>Sample</u>	<u>Description</u>	<u>Dry Unit Weight (PCF)</u>	<u>Moisture Content(%)</u>	<u>Specific Gravity</u>	<u>Total Porosity</u>	<u>Hydraulic Conductivity (cm/sec)</u>
AQUIFER SYSTEM I						
Aquifer Unit IA (low permeability zones)						
P-24 779'-781'	Mottled gray and tan sandy clay	81.3	53.0	2.65	0.51	5.52 x 10 ⁻⁸ (V) ** (H)
P-26 554'-556'	Medium gray silty clay	105.0	21.0	2.63	0.36	3.62 x 10 ⁻⁸ (V) 5.85 x 10 ⁻⁸ (H)
P-29 631'-634'	Mottled gray and tan clayey sand	92.1	31.8	2.67	0.45	3.11 x 10 ⁻⁷ (R)
P-29 591'-593'	Gray clay, slightly cemented	125.5	11.6	2.64	0.24	2.76 x 10 ⁻⁸ (V) 1.89 x 10 ⁻⁸ (H)
P-26 442'-444'	Gray silty clay	104.0	21.8	2.63	0.37	2.63 x 10 ⁻⁸ (V) 3.12 x 10 ⁻⁸ (H)
Confining Unit IA-IB						
P-13 670'-672'	Gray very clayey sand	91.2	40.0	2.66	0.45	4.80 x 10 ⁻⁹ (V) 8.00 x 10 ⁻⁹ (H)
P-17 662'-664'	Light gray silty clay	112.9	23.2	2.63	0.31	2.70 x 10 ⁻⁷ (V) ** (H)
P-18 643'-645'	Hard greenish-gray silty sandy clay	110.0	16.5	2.61	0.33	2.40 x 10 ⁻⁸ (V) ** (H)
P-25 650'-653'	Silty reddish-brown soft clay	52.1	98.4	2.65	0.69	1.56 x 10 ⁻⁶ (V) 1.45 x 10 ⁻⁶ (H)
P-26 504'-506'	Medium gray silty clay	106.7	19.7	2.61	0.35	1.65 x 10 ⁻⁷ (R)
P-27 607'-610'	Mottled gray-brown and red silty clay	102.1	22.7	2.70	0.39	3.45 x 10 ⁻⁸ (V) 5.46 x 10 ⁻⁸ (H)
P-28 600'-602'	Cemented gray and tan clay	87.1	15.9	2.71	0.49	7.37 x 10 ⁻⁶ (V) ** (H)
P-15 670'-672'	Light gray very sandy clay	101.4	22.8	2.64	0.38	1.50 x 10 ⁻⁵ (V) 4.10 x 10 ⁻⁸ (H)
P-15 652'-654'	Gray very sandy clay	97.1	26.4	2.65	0.41	6.75 x 10 ⁻⁸ (V) 1.65 x 10 ⁻⁸ (H)
Aquifer Unit IB (low permeability zones)						
P-13 610'-612'	Dark gray sandy clay	85.4	42.1	2.62	0.48	1.80 x 10 ⁻⁷ (V) 6.50 x 10 ⁻⁶ (H)
P-14 530'-532'	Gray very sandy clay	?	25.7	2.65	0.39	1.80 x 10 ⁻⁴ (V) 1.30 x 10 ⁻⁴ (H)
P-14 510'-512'	Sandy, silty clay with organic lenses	110.5	16.4	2.64	0.33	1.50 x 10 ⁻⁴ (V) 1.30 x 10 ⁻⁴ (H)

Table D-1, cont'd

Sample	Description	Dry Unit Weight (PCF)	Moisture Content (%)	Specific Gravity	Total Porosity	Hydraulic Conductivity (cm/sec)
P-19 495'-497'	Orange and light brown clayey sand with gray clay, coarse sand and gravel inclusions	109.2	20.9	2.66	0.34	3.00×10^{-8} (V) 2.30×10^{-6} (H)
P-19 548'-550'	Gray clayey sand with vertical seam of clay	104.1	24.1	2.65	0.31	7.00×10^{-6} (V) 2.80×10^{-6} (H)
P-21 495'-497'	Gray micaceous silty clay	116.4	15.1	2.61	0.29	2.20×10^{-7} (V) 2.70×10^{-7} (H)
P-21 522'-524'	Gray clay with iron staining, hard	119.8	18.3	2.69	0.29	6.40×10^{-9} (V) 1.00×10^{-8} (H)
P-21 560'-562'	Red-brown silty clay	101.4	25.9	2.59	0.37	3.30×10^{-8} (V)
P-22 612'-614'	Light and dark gray layered clay and silt with mica	98.2	21.4	2.60	0.40	4.20×10^{-8} (V) 9.90×10^{-8} (H)
P-23 401'-403'	Hard gray clayey silt	100.3	20.9	2.65	0.39	4.10×10^{-8} (V) 8.70×10^{-8} (H)
P-24 546'-549'	Gray silty clay	109.6	20.4	2.66	0.34	3.38×10^{-8} (V) 3.98×10^{-8} (H)
P-24 546'-549'	Coarse slightly silty clayey sand	88.2	31.3	2.63	0.46	3.66×10^{-6} (V) ** (H)
P-25 440'-443'	Light gray silty clay	107.1	21.3	2.64	0.35	3.95×10^{-8} (V) 4.51×10^{-8} (H)
P-26 282'-285'	Mottled gray and red-brown silty clay	101.6	20.4	2.63	0.38	2.48×10^{-8} (V) 2.63×10^{-8} (H)
P-27 458'-461'	Light gray silty clay	99.8	22.8	2.60	0.39	4.37×10^{-8} (V) 4.84×10^{-8} (H)
P-28 464'-465'	Gray-green silty clayey sand with mica	108.6	18.0	2.69	0.35	3.83×10^{-7} (V) ** (H)
P-28 465'-467'	Gray-green silty clay	97.8	24.9	2.62	0.40	2.69×10^{-7} (V) 2.98×10^{-7} (H)
P-29 365'-368'	Gray and redish-brown silty clay	94.3	25.5	2.65	0.43	2.92×10^{-8} (V) 3.49×10^{-8} (H)

CONFINING SYSTEM I-II

P-13 395'-397'	Green very clayey sand	33.5	63.3	2.42	0.78	2.65×10^{-9} (V) ** (H)
P-13 370'-372'	Mottled red and black sandy clay	71.2	46.8	2.66	0.57	** (V) 5.10×10^{-7} (H)
P-14 240'-242'	Coarse to medium sand with trace of clay	91.8	35.4	2.65	0.44	2.60×10^{-7} (V) 8.20×10^{-8} (H)
P-15 440'-442'	Gray silty clay	89.9	30.5	2.50	0.43	1.20×10^{-9} (V) ** (H)

Table D-1, cont'd

Sample	Description	Dry Unit Weight (PCF)	Moisture Content (%)	Specific Gravity	Total Porosity	Hydraulic Conductivity (cm/sec)
P-15 417'-419'	Gray slightly silty clay	99.9	24.0	2.72	0.37	3.70×10^{-9} (V) 1.50×10^{-8} (H)
P-17 443'-445'	Light gray silty clay with sand seams	104.9	22.9	2.71	0.38	1.20×10^{-7} (V) 2.40×10^{-7} (H)
P-18 261'-263'	Orange and tan clayey coarse sand with clay pockets	121.6	12.3	2.66	0.27	1.40×10^{-5} (V) 3.10×10^{-5} (H)
P-18 410'-412'	Green-gray and brown silty clay, slightly sandy	102.5	21.2	2.69	0.39	3.20×10^{-8} (V) 3.70×10^{-8} (H)
P-19 355'-358'	Grayish-green sandy clay, hard	125.8	14.4	2.63	0.23	1.40×10^{-8} (V) 2.10×10^{-8} (H)
P-21 380'-382'	Dark gray to black shaley clay with fine sand seams	61.8	60.1	2.50	0.60	1.90×10^{-5} (V) 2.40×10^{-4} (H)
P-22 331'-333'	Light gray silty clay	88.5	32.2	2.65	3.00×10^{-8} (H) 0.46	5.00×10^{-8} (V) 4.30×10^{-8} (H)
P-22 390'-392'	Dark gray silty clay brittled and cemented	65.8	53.0	2.50	0.58	3.60×10^{-7} (V) ** (H)
P-23 185'-187'	Blue-gray silty clay	102.2	26.1	2.70	0.39	3.40×10^{-8} (V) 4.00×10^{-8} (H)
P-23 224'-226'	Gray slightly silty clay with pyrite	92.0	27.6	2.63	0.44	1.50×10^{-8} (V) 1.30×10^{-8} (H)
P-23 301'-303'	Blue-gray sandy clay	106.6	19.6	2.64	0.35	1.20×10^{-8} (V) 4.00×10^{-5} (H)
P-23 361'-363'	Gray and brown silty sandy clay	119.1	14.9	2.66	0.28	3.40×10^{-7} (V) 9.00×10^{-9} (H)
P-24 370'-373'	Cream colored silty micaceous fine sand	99.2	23.4	2.65	0.40	3.40×10^{-5} (V) ** (H)
P-24 373'-376'	Reddish-brown brittle silty clay	89.4	31.3	2.63	0.46	6.11×10^{-6} (V) ** (H)
P-24 473'-475'	Gray silty clay with ferrous staining	107.6	21.1	2.65	0.35	2.14×10^{-8} (V) 3.61×10^{-8} (H)
P-25 254'-257'	Gray clay layered with fine sand	89.9	33.3	2.71	0.47	1.82×10^{-8} (V) 1.14×10^{-4} (H)
P-25 281'-284'	Gray silty sand	95.0	24.2	2.67	0.43	4.14×10^{-5} (V) 3.77×10^{-5} (H)
P-26 152'-155'	Green and black silty clay with mica	77.8	40.2	2.57	0.52	2.77×10^{-6} (V) ** (H)
P-27 230'-233'	Medium gray clay with pyrite seams	114.7	23.7	2.74	0.33	6.30×10^{-8} (R)

Table D-1, cont'd

Sample	Description	Dry Unit Weight (PCF)	Moisture Content (%)	Specific Gravity	Total Porosity	Hydraulic Conductivity (cm/sec)
P-27 340'-343'	Light gray to orange clay	106.6	20.4	2.66	0.36	3.44×10^{-8} (V) 3.93×10^{-8} (H)
P-28 293'-299'	Gray silty clayey sand with mica	119.2	15.9	2.64	0.28	1.01×10^{-7} (V) 3.92×10^{-8} (H)
P-28 370'-377'	Gray silty clay	95.8	27.8	2.59	0.41	2.99×10^{-8} (V) 3.92×10^{-8} (H)
P-28 370'-373'	Gray and tan silty clay, hard	114.5	17.5	2.68	0.32	2.70×10^{-8} (V) 3.61×10^{-8} (H)
P-29 191'-194'	Light tan silty clay with sand seams	83.4	37.1	2.71	0.51	3.38×10^{-7} (V) 3.07×10^{-7} (H)
P-29 229'-232'	Gray silty clay with mica	107.7	17.2	2.64	0.35	6.02×10^{-8} (V) 6.16×10^{-8} (H)
AQUIFER SYSTEM II						
Aquifer Unit IIA (low permeability zones)						
P-13 330'-332'	Brown-green sandy clay	75.9	44.5	2.80	0.57	1.70×10^{-7} (V) 3.10×10^{-5} (H)
P-15 305'-307'	Red-brown clayey fine sand	87.6	34.3	2.66	0.47	5.30×10^{-7} (V) 1.67×10^{-5} (H)
P-15 257'-259'	Light brown clayey sand	86.2	34.2	2.66	0.48	1.20×10^{-5} (V) 6.50×10^{-6} (H)
P-15 359'-361'	Light gray silty sand	99.3	22.6	2.71	0.30	4.00×10^{-7} (V) 2.70×10^{-5} (H)
P-17 308'-310'	Green clay, hard and layered	85.4	38.5	2.73	0.50	4.50×10^{-9} (V) 3.60×10^{-8} (H)
P-19 282'-283'	Dark gray and tan clayey sand with gray clay seams	108.0	22.0	2.68	0.36	3.40×10^{-6} (V) 3.50×10^{-5} (H)
P-21 325'-327'	Gray fine silty sand	116.1	17.7	2.64	0.30	1.20×10^{-4} (V) 5.10×10^{-4} (H)
P-23 97'-99'	Dark gray silty clay, brittle	50.9	82.6	2.76	0.71	1.30×10^{-7} (V) ** (H)
Confining Unit IIA-IIB						
P-13 237'-239'	Brown-green clayey fine sand	106.3	19.6	2.69	0.37	5.60×10^{-5} (V) 5.30×10^{-5} (H)
P-14 168'-170'	Coarse to medium sand with trace of clay	104.3	17.3	2.65	0.37	4.50×10^{-5} (V) 2.40×10^{-7} (H)
P-16 415'-417'	Light gray clay with tan clayey sand seams	99.5	26.0	2.59	0.39	6.30×10^{-8} (V) 6.70×10^{-7} (H)
P-18 180'-182'	Orange clayey sand with clay seams	95.4	21.5	2.58	0.41	2.70×10^{-8} (V) 2.00×10^{-8} (H)

Table D-1, cont'd

Sample	Description	Dry Unit Weight (PCF)	Moisture Content (%)	Specific Gravity	Total Porosity	Hydraulic Conductivity (cm/sec)
P-19 190'-193'	Orange clayey sand with tan silty clay	101.6	21.5	2.66	0.39	1.20×10^{-8} (V) 2.80×10^{-6} (H)
P-20 210'-211'	Brown very silty sand with mica, well consolidated	92.2	28.4	2.66	0.45	9.10×10^{-7} (V) 1.10×10^{-6} (H)
P-21 160'-162'	Tan calcareous sandy silt	91.0	50.4	2.59	0.44	6.70×10^{-7} (V) 5.80×10^{-6} (H)
P-22 140'-142'	Tan calcareous clayey silty sand	91.9	35.8	2.70	0.46	1.30×10^{-7} (V) 6.60×10^{-8} (H)
P-25 166'-169'	Orange and gray sandy clay	102.7	22.7	2.66	0.38	7.91×10^{-8} (V) 1.11×10^{-4} (H)
P-28 132'-134'	Light tan silty, clayey sand	78.9	36.7	2.58	0.51	2.01×10^{-7} (V) 1.85×10^{-7} (H)
Aquifer Unit IIB (low permeability zones)						
P-14 135'-137'	Fine sandy clay with limestone fragments	107.0	21.4	2.64	0.35	2.00×10^{-4} (V) 1.70×10^{-4} (H)
P-15 171'-173'	Yellow-brown clayey fine sand	93.5	25.9	2.69	0.44	4.10×10^{-7} (V) 1.70×10^{-6} (H)
P-20 105'-107'	Gray and brown clayey sand with iron stains	66.1	58.3	2.82	0.63	3.40×10^{-8} (V) 1.10×10^{-7} (H)
P-22 61'-63'	Tan clayey sand	82.3	36.2	2.69	0.51	1.70×10^{-7} (V) 3.40×10^{-7} (H)
P-25 110'-113'	Tan and orange clayey sand with seams of coarse sand	90.1	33.1	2.66	0.46	4.19×10^{-5} (V) 8.74×10^{-4} (H)
P-27 95'-98'	Mottled tan and orange silty clay	106.6	20.4	2.66	0.36	3.44×10^{-8} (V) 3.93×10^{-8} (H)
AQUIFER SYSTEM I/II						
Aquifer Unit I/IIA (low permeability zones)						
P-30 615'-617'	Gray silty clay	119.9	12.4	2.65	0.28	1.01×10^{-7} (V) 1.23×10^{-7} (H)
Confining Unit I/IIA-I/IIB						
P-30 506'-509'	Brittle layered silty clay	111.8	17.5	2.68	0.33	4.51×10^{-8} (V) ** (H)
Aquifer Unit I/IIB (low permeability zones)						
P-30 215'-217'	Light gray silty clay with layers of iron mica	84.0	34.7	2.69	0.50	4.64×10^{-8} (V) 1.43×10^{-7} (H)

Table D-1, cont'd

<u>Sample</u>	<u>Description</u>	<u>Dry Unit Weight (PCF)</u>	<u>Moisture Content(%)</u>	<u>Specific Gravity</u>	<u>Total Porosity</u>	<u>Hydraulic Conductivity (cm/sec)</u>
Confining Unit I/IIB-I/IIC						
P-16 158'-161'	Tan and brown clayey sand with light tan silty clay layers	73.7	40.8	2.64	0.55	1.70×10^{-7} (V) 5.30×10^{-7} (H)
P-16 177'-179'	Orange and tan sandy silt	114.0**	27.8	2.65	0.31	2.20×10^{-5} (R)
P-16 179'-181'	Orange and tan sand with tan silty clay layers and inclusions	107.6	24.2	2.63	0.35	2.50×10^{-6} (V) 1.10×10^{-5} (H)
P-16 180'-182'	Dark gray micaceous clay, slightly cemented	86.3	33.1	2.56	0.46	1.90×10^{-7} (V) **
P-16 248'-255'	Gray and tan sandy clay (bag sample)	112.5**	28.5	2.58	0.30	7.10×10^{-8} (R)
P-16 255'-257'	White clayey silty sand with mica and iron staining	109.8	16.7	2.61	0.33	6.50×10^{-7} (V) 9.50×10^{-7} (H)
P-30 139'-141'	Light gray clay with pockets of ferrous granules and fine sand	72.6	44.5	2.68	0.57	7.91×10^{-8} (V) 9.54×10^{-8} (H)
P-30 105'-108'	Reddish-brown clayey sand	80.5	36.7	2.74	0.53	8.08×10^{-7} (V) 6.78×10^{-7} (H)
Aquifer Unit I/IIC (low permeability zones)						
P-16 65'-67	Tan slightly silty	103.0	11.2	2.65	0.38	1.90×10^{-3} (R)

(V) Vertical hydraulic conductivity

(H) Horizontal hydraulic conductivity

(R) Hydraulic conductivity measurement on remolded sample

** Conductivity measurement not possible due to sample condition

? Value not reported

**APPENDIX E: GRAIN SIZE DISTRIBUTION FOR
UNDISTURBED SAMPLES**

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

Number	Depth	Moisture Moisture	L.L.	P.L.	P.L.	Classification
P-13	395'-397.5'	63.3%	-	-	-	Green very clayey sand

Number	Depth	Natural Moisture	Classification			SILT or CLAY
			LL	P.L	P.L	
P-13	610'-612.5'	42.1%	-	-	-	Dark gray sandy clay

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

Number	Depth	Natural Moisture	L.L.	P.L.	P.L.	Classification
P-13	670'-672'	40.0%	-	-	-	Gray very clayey sand

NFS SERVICES, INC.
St. Petersburg, Florida

Aiken, South Carolina		Sieve and Hydrometer Analysis	
Number	Depth	Natural Moisture	Classification
P-14	135 - 137'		Fine sand, trace of clay
TB			with occasional limestone fragments to 3/8 inch

NFS SERVICES, INC.
St. Petersburg, Florida

NFS SERVICES, INC.
St. Petersburg, Florida

Aiken, South Carolina
Sieve and Hydrometer Analysis

Number	Depth	Moisture	LL	PL	P.I.	Classification
GM 2	240-242.5					Sandy, silty clay, gray
14 TB						

NFS SERVICES, INC.
St. Petersburg, Florida

GRAVEL		SAND		SILT or CLAY	
Number	Depth	Natural Moisture	L.L.	P.L.	P.I.
1478	510.0-512.5				
Classification					
Coarse to medium sand, trace of clay, light gray					
Aiken, South Carolina					
Sieve and Hydrometer Analysis					

NFS SERVICES, INC.
St. Petersburg, Florida

Number	Depth	Natural Moisture	L.L.	P.L.	P.L.	Classification
P-14	530'					Sand, trace of silt with parti-
-TB						cles of decayed wood and occa-
						sional small clay lenses

Aiken, South Carolina
Sieve and Hydrometer Analysis

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

Number	Depth	Moisture	LL	P.L.	P.L.	Classification
P-15	171'	26.5%	-	-	-	Yellow-brown clayey fine sand

Number	Depth	Water Content	Liquid Limit		Plastic Limit		Classification
			U.C.	P.L.	U.C.	P.L.	
P-15	257'	34.12	-	-	-	-	Light brown clayey sand

Number	Depth	Natural Moisture	LL	P.L	P.L	Classification
P-15	305'	35.8%	-	-	-	Red-brown clayey fine sand

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

GRAVEL		SAND		SILT or CLAY	
Coarse	Fine				

Number	Depth	Natural Moisture	L.L.	P.L.	P.L.	Classification
P-15	359'	22.6%	-	-	-	Light gray silty sand

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

Number	Depth	Classification			
		Natural Moisture	L.L.	P.L.	P.L.
P-15	652'	26.3%	-	-	-

FLORIDA TESTING LABORATORIES, INC.
St. Petersburg, Florida

Number	Depth	Moisture	L.L.	P.L.	P.L.	Classification
P-15	670'-672'	22.8%	-	-	-	Light gray very sandy clay

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-16	158-161'	Tan and brown clayey sand with light tan and tan silty clay layers	Hydrogeologic Study, Phase II PSI File No. 372-55001

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-16	158- 161'	Tan and brown clayey sand with light tan and tan silty clay layers	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-16	177- 179'	Orange and tan sandy silt	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-16		179- 181.5'	Orange and tan sand with light tan silty clay layers and inclusions	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

CLASSIFICATION		PROJECT	
WELL CLUSTER	DEPTH	Hydrogeologic Study, Phase II PSI File No. 372-55001	
P-16	248- 255'	Gray and light tan sandy clay, slightly silty	

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-16	255-257'	White clayey sand, slightly silty with mica and iron staining	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-16	415-417.5'	Light gray clay with tan clayey sand seams	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-17	180-182'	Dark gray clay with mica and slightly cemented	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-17	308-310'	Green clay, hard and layered	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

Professional Service Industries, Inc.

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-18	180-182'	Orange clayey sand with clay seams	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-18	261- 263'	Orange and tan clayey coarse sand with clay pockets	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-18	410-412	Greenish gray and brown silty clay, marbled and slightly sandy	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-19	190-192.9'	Orange clayey sand with light tan silty clay lenses	Hydrogeologic Study, Phase II PSI File No. 372-55001

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-19	190- 192.9'	Orange clayey sand with light tan silty clay lenses	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-19	282- 283'	Dark gray and tan clayey sand with occasional gray clay seams	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

CLASSIFICATION		PROJECT	
WELL CLUSTER	DEPTH	Hydrogeologic Study, Phase II PSI File No. 372-55001	
P-19	355- 358'	Grayish-green sandy clay, hard	

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-19	495-497'	Orange and light brown clayey sand with gray clay, coarse sand and gravel inclusions	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-19		548-550'	Gray clayey sand with verticle seam of gray clay	Hydrogeologic Study, Phase II PSI File No. 372-55001

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-20	105-107'	Gray and brown clayey sand with Fe stains	Hydrogeologic Study, Phase II PSI File No. 372-55001

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-20	210-211'	Brown very silty sand with mica; well consolidated	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER		CLASSIFICATION		PROJECT	
P-21	160-162'	Tan sandy silt		Hydrogeologic Study, Phase II	
				PSI File No. 372-55001	

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-21	325-327'	Gray fine silty sand	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-21	380-382'	Dark gray to black shaley clay with fine sand seams	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

Professional Service Industries, Inc.

CLASSIFICATION		PROJECT	
WELL CLUSTER	DEPTH	Hydrogeologic Study, Phase II PSI File No. 372-55001	
P-21	522- 524'	Hard gray clay with iron staining

CLASSIFICATION		PROJECT	
WELL CLUSTER	DEPTH	Hydrogeologic Study, Phase II PSI File No. 372-55001	
P-21	560- 562'	Reddish-brown silty clay	

Professional Service Industries, Inc.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-22		61-63'	Tan clayey sand	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-22	140-142'	Tan clayey sand, slightly silty with traces of limestone	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-22		331-333'		Light gray silty clay		Hydrogeologic Study, Phase II PSI File No. 372-55001	

Professional Service Industries, Inc.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-22		612-614'	Light and dark gray layered clay and silt with mica	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

Professional Service Industries, Inc.

WELL CLUSTER		PROJECT	
WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-23	185-187'	Blue-gray silty clay	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

Professional Service Industries, Inc.

CLASSIFICATION		PROJECT	
WELL CLUSTER	DEPTH	Hydrogeologic Study, Phase II PSI File No. 372-55001	
P-23	301'- 303'	Blue-gray sandy clay	

Professional Service Industries, Inc.

Professional Service Industries, Inc.

CLASSIFICATION		PROJECT	
WELL CLUSTER	DEPTH	Hydrogeologic Study, Phase II PSI File No. 372-55001	
P-23	401-403'	Hard gray clayey silt	

PROFESSIONAL SERVICE INDUSTRIES, INC.

U.S. STANDARD SIEVE OPENING IN INCHES

U.S. STANDARD SIEVE NUMBERS

HYDROMETER

PER CENT FINER BY WEIGHT

PER CENT COARSER BY WEIGHT

GRAIN SIZE IN MILLIMETERS

GRAVEL

COARSE

FINE

SAND

COARSE

MEDIUM

FINE

SILT OR CLAY

COBBLES

WELL CLUSTER

DEPTH

CLASSIFICATION

PROJECT

P24TB

373-376

REDDISH BROWN, SANDY CLAY

PHASE III HYDROGEOLOGIC INVESTIGATION

Grain Size (mm)	Sieve Number	Percent Finer (%)
0.075	No. 200	100
0.15	No. 100	100
0.3	No. 60	100
0.6	No. 30	100
1.18	No. 16	100
2.5	No. 6	100
5.0	No. 3	100
10.0	No. 1	100
20.0	No. 75	65
40.0	No. 40	10
75.0	No. 20	5
150.0	No. 10	5
300.0	No. 5	5
600.0	No. 2	5

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROJECT

PHASE III HYDROGEOLOGIC INVESTIGATION

CLASSIFICATION

GRAY SANDY CLAY, WITH SILT POCKETS

DEPTH

546-549

WELL CLUSTER

P24TB

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-24 TB	779'-781'	Mottled gray and tan, clayey, fine, sand	Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-25 TB	110'-113'		Orange and tan clayey, medium sand	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-25 TB	166'-169'	Orange and gray clayey fine sand	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-25 TB		254'-257'		Gray, silty, clay with sand seams		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-25 TB		281'-284'		Gray, silty, fine sand		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-25 TB		440'-443'	Light gray, silty clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION	PROJECT
P-25 TB		650'-653'		Reddish brown, sandy clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-26 TB	152'-155'	Blackish green, clayey silt	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-26 TB		282'-285'		Purplish red clay		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-26 TB	504'-506'	Gray clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-26 TB		554'-556'		Gray clay		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-27 TB		95'-98'	Grayish green sandy clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-27 TB	230' -233'	Light gray, clayey silt	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-27 TB		340'-343'	Light gray clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-27 TB		458'-461'	Light gray clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-27 TB		607'-610		Grayish brown clay		Phase III Hydrogeologic Investigation	

GRAIN SIZE DISTRIBUTION

Y-axis: PER CENT FINER BY WEIGHT (0 to 100)

X-axis: GRAIN SIZE IN MILLIMETERS (0.001 to 500)

Soil Classification: SAND

Grain Size (mm)	Percent Finer (%)
0.001	100
0.075	85
0.15	75
4.75	0

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-28 TB	132' - 134'	Light tan clayey fine sand	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-28 TB	293'-299	Gray, clayey, fine sand with mica	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-28 TB		370'-373'		Gray and tan sandy clay		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P 28 TB	370'-377'	Gray silty clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-28 TB		464'-465'	Gray green silty medium sand with mica	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-28 TB		465'-467'	Gray green silty clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-28 TB		600'-602'		Cemented gray and tan clay		Phase III Hydrogeologic Investigation	

The graph is a semi-logarithmic plot used for soil classification. The vertical axis (y-axis) represents the percentage of soil, ranging from 0 to 100. The horizontal axis (x-axis) represents grain size, with two scales: millimeters (mm) on the top and inches (in) on the bottom. The x-axis is logarithmic, with major ticks at 0.075, 0.15, 0.3, 0.6, 1.2, 2.5, 5, 10, 20, 40, 60, 100, 200, 400, and 600 mm. The y-axis is linear, ranging from 0 to 100. A curve is plotted, showing the distribution of soil particles. The curve starts at 100% finer for 0.075 mm and decreases as grain size increases, reaching 0% finer at 600 mm. The curve is labeled 'PER CENT FINER BY WEIGHT' on the left and 'PER CENT COARSER BY WEIGHT' on the right. The graph also includes scales for U.S. Standard Sieve Numbers (top left) and U.S. Standard Sieve Opening in Inches (bottom left). The hydrometer scale is on the right side of the graph.

GRAIN SIZE IN MILLIMETERS	GRAIN SIZE IN INCHES	PER CENT FINER BY WEIGHT	PER CENT COARSER BY WEIGHT
0.075	0.003	100	0
0.15	0.006	90	10
0.3	0.012	75	25
0.6	0.024	55	45
1.2	0.048	35	65
2.5	0.099	15	85
5	0.197	5	95
10	0.394	2	98
20	0.787	1	99
40	1.575	0.5	100
60	2.362	0.2	100
100	3.937	0	100
200	7.874	0	100
400	15.748	0	100
600	23.622	0	100

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-29 TB	191'-194	Light tan, sandy clay, with sand and silt seams.	Phase III Hydrogeologic Investigation

Sieve Size (mm)	Percentage Finer (%)
0.001	100
0.002	100
0.004	100
0.0075	100
0.015	100
0.03	100
0.06	100
0.10	100
0.15	100
0.25	100
0.425	65
0.6	65
0.85	65
1.18	65
1.75	65
2.5	65
3.55	65
5.0	65
7.5	65
10.6	65
15.0	65
20.0	65
28.0	65
37.5	65
50.0	65
75.0	65
100.0	65
150.0	65
200.0	65
250.0	65
300.0	65
350.0	65
400.0	65
450.0	65
500.0	65

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-29 TB	229' - 232'	Gray sandy clay, with mica	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-29 TB		365'-368'		Gray and reddish brown clay		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-29 TB	591'-593		Gray sandy clay	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

P-29 TB	631'-634'	Mottled gray and tan clayey fine sand	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-30 TB		105'-108'		Reddish brown, clayey, fine sand.		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P-30 TB		139'-141'		Light gray sandy clay with ferrous nodules and sand pockets.		Phase III Hydrogeologic Investigation	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P-30 TB		215'-217'	Light gray, silty clay.	Phase III Hydrogeologic Investigation

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-30 TB	506'-509'	Gray, silty clay	Phase III Hydrogeologic Investigation

Grain Size (mm)	Percent Finer (%)	Percent Coarser (%)
0.001	100	0
0.075	75	25
0.425	50	50
4.75	10	90
500	0	100

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P-30 TB	615'-617'	Gray, sandy clay.	Phase III Hydrogeologic Investigation

**APPENDIX F: GRAIN SIZE DISTRIBUTION WITHIN
SCREEN ZONES**

Professional Service Industries, Inc.

WELL NUMBER		DEPTH		PROJECT	
P-16 (TA)		610-620'		Hydrogeologic Study, Phase II PSI File No. 372-55001	

Professional Service Industries, Inc.

PROJECT

Hydrogeologic Study, Phase II
PSI File No. 372-55001

DEPTH

130-140'

WELL NUMBER

P-16 (A)

GRAIN SIZE DISTRIBUTION DATA

Grain Size (mm)	Sieve Number	Percent Finer (%)
0.075	20	70
0.15	10	75
0.3	60	80
0.6	30	85
1.18	16	90
2.5	6	95
4.75	30	100

Professional Service Industries, Inc.

Professional Service Industries, Inc.

Professional Service Industries, Inc.

PROJECT

Hydrogeologic Study, Phase II
PSI File No. 372-55001

DEPTH

290-300'

WELL NUMBER

P17- (A)

Professional Service Industries, Inc.

WELL NUMBER		DEPTH		PROJECT	
P-17 (B)		200-210'		Hydrogeologic Study, Phase II PSI File NO. 372-55001	

Professional Service Industries, Inc.

Professional Service Industries, Inc.

WELL NUMBER

DEPTH

PROJECT

P-18 (TB)

666-676'

Hydrogeologic Study, Phase II
PSI File No. 372-55001

PROJECT

Hydrogeologic Study, Phase II
PSI File No. 372-55001

DEPTH

554-564'

WELL NUMBER

P-18 (TC)

PROJECT

Hydrogeologic Study, Phase II
PSI File No. 372-55001

DEPTH

476-576'

WELL NUMBER

P-18 (TD)

Professional Service Industries, Inc.

WELL NUMBER		DEPTH		PROJECT	
P19 (A)		325-335'		Hydrogeologic Study, Phase II PSI File No. 372-55001	

Professional Service Industries, Inc.

WELL NUMBER		DEPTH		PROJECT	
P-19 (B)		220-240'		Hydrogeologic Study, Phase II PSI File No. 372-55001	

Professional Service Industries, Inc.

WELL NUMBER

DEPTH

PROJECT

P-19 (C)

173-183'

Hydrogeologic Study, Phase II
PSI File No. 372-55001

Professional Service Industries, Inc.

PROJECT	
Hydrogeologic Study, Phase II PSI File No. 372-55001	
WELL NUMBER	
P-20 (TD)	
DEPTH	
435-445'

PROJECT	
Hydrogeologic Study, Phase PSI File No. 372-55001	
DEPTH	
476-486'	
WELL NUMBER	
P-21 (TD)	

Professional Service Industries, Inc.

DEPTH		PROJECT	
WELL NUMBER			
P-21 (A)	352-362'	Hydrogeologic Study, Phase II PSI File No. 372-55001	

Professional Service Industries, Inc.

PROJECT

DEPTH

WELL NUMBER

Hydrogeologic Study, Phase II
PSI File No. 372-55001

280-290'

P-21 (B)

WELL NUMBER	DEPTH	PROJECT
P-22 (TA)	930-950'	Hydrogeologic Study, Phase II PSI File No. 372-55001

Professional Service Industries, Inc.

Professional Service Industries, Inc.

PROJECT

DEPTH

WELL NUMBER

Hydrogeologic Study, Phase II
PSI File No. 372-55001

350-360'

P-22 (A)

Professional Service Industries, Inc.

PROJECT	
Hydrogeologic Study, Phase II PSI File No. 372-55001	
DEPTH	
240-250'	
WELL NUMBER	
P-22 (B)

Professional Service Industries, Inc.

PROJECT	
Hydrogeologic Study, Phase II PSI File No. 372-55001	
DEPTH	
800-820'	
WELL NUMBER	
P-23 (TA)	

Professional Service Industries, Inc.

WELL NUMBER		DEPTH		PROJECT	
P-23 (TB)		690-700'		Hydrogeologic Study, Phase II PSI File No. 372-55001	

Professional Service Industries, Inc.

Professional Service Industries, Inc.

Professional Service Industries, Inc.

WELL NUMBER		DEPTH		PROJECT	
P-23 (A)		210-220'		Hydrogeologic Study, Phase II PSI File No. 372-55001	

Professional Service Industries, Inc.

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P24TA SAMPLE A SCREEN ZONE		950-970	LIGHT GRAY COARSE SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROJECT

PHASE III HYDROGEOLOGIC INVESTIGATION

CLASSIFICATION

LIGHT GRAY MEDIUM SAND

DEPTH

586-596

WELL CLUSTER

P24TC
SCREEN ZONE

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P24TD SCREEN ZONE		490-500		LIGHT GRAY SILTY MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P24A SCREEN ZONE	305-315		TAN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P24C SCREEN ZONE	130-150	ORANGISH YELLOW SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

COBBLES	GRAVEL		SAND			SILT OR CLAY
	COARSE	FINE	COARSE	MEDIUM	FINE	

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P24D SCREEN ZONE	45-65	MEDIUM YELLOW CLAYEY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P25TA SCREEN ZONE	850-870	LIGHT GRAY SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P25TB	SCREEN ZONE	720-730	WHITISH GRAY SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P25TC SCREEN ZONE		575-585		TANNISH GRAY SILTY MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P25TD SCREEN ZONE		460-470		WHITISH GRAY SILTY MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

PROFESSIONAL SERVICE INDUSTRIES, INC.

PER CENT FINER BY WEIGHT

PER CENT COARSER BY WEIGHT

U.S. STANDARD SIEVE OPENING IN INCHES

U.S. STANDARD SIEVE NUMBERS

HYDROMETER

GRAIN SIZE IN MILLIMETERS

COBBLES

GRAVEL

SAND

SILT OR CLAY

COARSE

FINE

COARSE

FINE

MEDIUM

FINE

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P25A SCREEN ZONE	300-310	GRAY SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P25B SCREEN ZONE	175-185	ORANGISH TAN MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P25C	SCREEN ZONE	155-165	ORANGISII BROWN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PER CENT FINER BY WEIGHT

HYDROMETER

U.S. STANDARD SIEVE NUMBERS

GRAIN SIZE IN MILLIMETERS

COBBLES GRAVEL SAND

COARSE FINE

PER CENT FINER BY WEIGHT

GRAIN SIZE (mm)	PER CENT FINER (%)
0.075	100
0.15	95
0.3	90
0.6	85
1.2	80
2.5	75
5.0	70
10	65
20	60
40	55
80	50
150	45
300	40
600	35
1200	30
2500	25
5000	20
10000	15
20000	10
40000	5
80000	2
150000	1
300000	0.5
600000	0.2
1200000	0.1
2500000	0.05
5000000	0.02
10000000	0.01
20000000	0.005
40000000	0.002
80000000	0.001

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P25D SCREEN ZONE	40-60	TANNISH BROWN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P26TA SCREEN ZONE	680-700	LIGHT GRAY SILTY MEDIUM SAND	Phase III Hydrogeologic Investigation

GRAIN SIZE DISTRIBUTION

PER CENT FINER BY WEIGHT (Left Y-Axis, 0 to 100)

PER CENT COARSER BY WEIGHT (Right Y-Axis, 0 to 100)

U.S. STANDARD SIEVE NUMBERS (Top X-Axis, 10 to 200)

GRAIN SIZE IN MILLIMETERS (Bottom X-Axis, 500 to 0.075)

COBBLES (Grain Size > 4.75 mm)

GRAVEL (Grain Size 4.75 mm to 75 mm)

SAND (Grain Size 75 mm to 0.075 mm)

SILT OR CLAY (Grain Size < 0.075 mm)

Grain Size (mm)	U.S. Standard Sieve Number	Percent Finer (%)
500	-	100
250	60	100
150	100	100
100	150	100
75	200	100
60	250	100
50	300	100
40	350	100
30	425	100
25	60	100
20	84	100
15	100	100
12.5	120	100
10	150	100
7.5	200	100
6	250	100
4.75	30	100
4	40	100
3.5	48	100
3	60	100
2.5	75	100
2	100	100
1.5	120	100
1.25	150	100
1	20	100
0.85	25	100
0.75	30	100
0.6	40	100
0.5	50	100
0.425	60	100
0.375	70	100
0.3	80	100
0.25	90	100
0.2	100	100
0.15	120	100
0.125	150	100
0.1	20	100
0.085	25	100
0.075	30	100
0.06	40	100
0.05	50	100
0.0425	60	100
0.0375	70	100
0.03	80	100
0.025	90	100
0.02	100	100
0.015	120	100
0.0125	150	100
0.01	20	100
0.0085	25	100
0.0075	30	100
0.006	40	100
0.005	50	100
0.00425	60	100
0.00375	70	100
0.003	80	100
0.0025	90	100
0.002	100	100
0.0015	120	100
0.00125	150	100
0.001	20	100
0.00085	25	100
0.00075	30	100
0.0006	40	100
0.0005	50	100
0.000425	60	100
0.000375	70	100
0.0003	80	100
0.00025	90	100
0.0002	100	100
0.00015	120	100
0.000125	150	100
0.0001	20	100
0.000085	25	100
0.000075	30	100
0.00006	40	100
0.00005	50	100
0.0000425	60	100
0.0000375	70	100
0.00003	80	100
0.000025	90	100
0.00002	100	100
0.000015	120	100
0.0000125	150	100
0.00001	20	100
0.0000085	25	100
0.0000075	30	100
0.000006	40	100
0.000005	50	100
0.00000425	60	100
0.00000375	70	100
0.000003	80	100
0.0000025	90	100
0.000002	100	100
0.0000015	120	100
0.00000125	150	100
0.000001	20	100
0.00000085	25	100
0.00000075	30	100
0.0000006	40	100
0.0000005		

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P26TB SCREEN ZONE	525-535	LIGHT GRAY SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P26TC SCREEN ZONE	375-385	TANNISH WHITE SILTY FINE SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

GRAIN SIZE DISTRIBUTION

PER CENT FINER BY WEIGHT

GRAIN SIZE IN MILLIMETERS

PER CENT COARSER BY WEIGHT

HYDROMETER

U.S. STANDARD SIEVE OPENING IN INCHES

U.S. STANDARD SIEVE NUMBERS

COBBLES **GRAVEL** **SAND** **SILT OR CLAY**

COARSE **FINE** **COARSE** **FINE**

Grain Size (mm)	U.S. Sieve No.	Percent Finer (%)
500	-	100
250	60	100
150	100	100
100	150	100
75	200	100
60	250	100
50	300	100
40	350	100
30	425	100
25	60	100
20	84	100
15	100	100
12.5	120	100
10	150	100
7.5	200	100
6	250	100
5	300	100
4.75	350	100
4.25	400	100
3.75	450	100
3.0	60	100
2.5	84	100
2.0	100	100
1.5	120	100
1.18	150	100
0.85	200	100
0.75	250	100
0.6	300	100
0.5	350	100
0.425	400	100
0.375	450	100
0.3	60	100
0.25	84	100
0.2	100	100
0.15	120	100
0.125	150	100
0.106	200	100
0.085	250	100
0.075	300	100
0.06	350	100
0.05	400	100
0.0425	450	100
0.0375	500	100
0.03	600	100
0.025	750	100
0.02	1000	100
0.015	1500	100
0.0125	2000	100
0.0106	2500	100
0.0085	3000	100
0.0075	3500	100
0.006	4000	100
0.005	4500	100
0.00425	5000	100
0.00375	5500	100
0.003	6000	100
0.0025	7500	100
0.002	10000	100
0.0015	15000	100
0.00125	20000	100
0.00106	25000	100
0.00085	30000	100
0.00075	35000	100
0.0006	40000	100
0.0005	45000	100
0.000425	50000	100
0.000375	55000	100
0.0003	60000	100
0.00025	75000	100
0.0002	100000	100
0.00015	150000	100
0.000125	200000	100
0.000106	250000	100
0.000085	300000	100
0.000075	350000	100
0.00006	400000	100
0.00005	450000	100
0.0000425	500000	100
0.0000375	550000	100
0.00003	600000	100
0.000025	750000	100
0.00002	1000000	100
0.000015	1500000	100
0.0000125	2000000	100
0.0000106	2500000	100
0.0000085	3000000	100
0.0000075	3500000	100
0.000006	4000000	100
0.000005	4500000	100
0.00000425	5000000	100
0.00000375	5500000	100
0.000003	6000000	100
0.0000025	7500000	100
0.000002	10000000	100
0.0000015	15000000	100
0.00000125	2000	

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P26TC SCREEN ZONE	375-385	TANNISH WHITE SILTY FINE SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P26A SCREEN ZONE		120-130	GREENISH GRAY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P26B	SCREEN ZONE	70-80	ORANGISH TAN MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P26D SCREEN ZONE	35-55	ORANGISH BROWN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P27TA SCREEN ZONE	815-825	LIGHT TANNISH GRAY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P27TB SCREEN ZONE SAMPLE A	680-690	LIGHT GRAYISH TAN MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P27TC SCREEN ZONE		560-570		GRAY MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P27TD	SCREEN ZONE	480-490	LIGHT GRAY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P27TE SCREEN ZONE		380-390		LIGHT GRAY SILTY MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P27B SCREEN ZONE	180-200	DARK TANNISH YELLOW MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

COBBLES	GRAVEL		SAND		SILT OR CLAY
	COARSE	FINE	MEDIUM	FINE	

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P27C SCREEN ZONE	130-135	ORANGISH BROWN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P27D	SCREEN ZONE	55-75		DARK ORANGISH BROWN MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P28TA SCREEN ZONE		750-780		TANNISH YELLOW SILTY MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P28TB SCREEN ZONE		620-640	MEDIUM TAN MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PER CENT FINER BY WEIGHT

PER CENT COARSER BY WEIGHT

HYDROMETER

U.S. STANDARD SIEVE OPENING IN INCHES

U.S. STANDARD SIEVE NUMBERS

GRAIN SIZE IN MILLIMETERS

COBBLES

GRAVEL

COARSE

FINE

SAND

MEDIUM

FINE

SILT OR CLAY

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P28TC SCREEN ZONE	560-570	MEDIUM GRAY SILTY FINE SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P28TD SCREEN ZONE	495-505	DARK GRAY SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P28TE SCREEN ZONE		405-415	LIGHT GRAY SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

[illegible]

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P29TD SCREEN ZONE	410-430	LIGHT TAN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P29A	SCREEN ZONE	305-315	TANNISH ORANGE SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P29B	SCREEN ZONE	180-190	GRAYISH TAN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P29C SCREEN ZONE	130-140	GRAYISH TAN SILTY FINE SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P29D SCREEN ZONE	93-113	GRAYISH BROWN SILTY FINE SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P30TA SCREEN ZONE	695-705		LIGHT GRAYISH TAN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

COBBLES	GRAVEL		SAND		SILT OR CLAY
	COARSE	FINE	MEDIUM	FINE	

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P30TB SCREEN ZONE	570-590	LIGHT GRAY SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH		CLASSIFICATION		PROJECT	
P30TC SCREEN ZONE	450-460			BROWNISH ORANGE SILTY MEDIUM SAND		PHASE III HYDROGEOLOGIC INVESTIGATION	

COBBLES	GRAVEL		SAND		SILT OR CLAY
	COARSE	FINE	MEDIUM	FINE	

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P30TD SCREEN ZONE	340-350	LIGHT GRAY SILTY MEDIUM SAND	HYDROGEOLOGIC INVESTIGATION PHASE III

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P30A SCREEN ZONE		270-280	LIGHT PURPLISH GRAY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P30B SCREEN ZONE	220-230	PURPLISH BROWN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

GRAIN SIZE DISTRIBUTION CURVE

Grain Size (mm)	Percent Finer (%)
0.075	100
0.15	100
0.3	100
0.6	100
1.18	100
2.5	100
5.0	100
7.5	100
15	100
30	100
60	100
100	100
200	100
425	100
600	100
850	100
1180	100
1600	100
2200	100
3000	100
4250	100
6000	100
8500	100
11800	100
16000	100
22000	100
30000	100
42500	100
60000	100
85000	100
118000	100
160000	100
220000	100
300000	100
425000	100
600000	100
850000	100
1180000	100
1600000	100
2200000	100
3000000	100
4250000	100
6000000	100
8500000	100
11800000	100
16000000	100
22000000	100
30000000	100
42500000	100
60000000	100
85000000	100
118000000	100
160000000	100
220000000	100
300000000	100
425000000	100
600000000	100
850000000	100
1180000000	100
1600000000	100
2200000000	100
3000000000	100
4250000000	100
6000000000	100
8500000000	100
11800000000	100
16000000000	100
22000000000	100
30000000000	100
42500000000	100
60000000000	100
85000000000	100
118000000000	100
160000000000	100
220000000000	100
300000000000	100
425000000000	100
600000000000	100
850000000000	100
1180000000000	100
1600000000000	100
2200000000000	100
3000000000000	100
4250000000000	100
6000000000000	100
8500000000000	100
11800000000000	100
16000000000000	100
22000000000000	100
30000000000000	100
42500000000000	100
60000000000000	100
85000000000000	100
118000000000000	100
160000000000000	100
220000000000000	100
300000000000000	100
425000000000000	100
600000000000000	100
850000000000000	100
1180000000000000	100
1600000000000000	100
2200000000000000	100
3000000000000000	100
4250000000000000	100
6000000000000000	100
8500000000000000	100
11800000000000000	100
16000000000000000	100
22000000000000000	100
30000000000000000	100
42500000000000000	100
60000000000000000	100
85000000000000000	100
118000000000000000	100
160000000000000000	100
220000000000000000	100
300000000000000000	100
425000000000000000	100
600000000000000000	100
850000000000000000	100
1180000000000000000	100
1600000000000000000	100
2200000000000000000	100
3000000000000000000	100
4250000000000000000	100
6000000000000000000	100
8500000000000000000	100
11800000000000000000	100
16000000000000000000	100
22000000000000000000	100
30000000000000000000	100
42500000000000000000	100
60000000000000000000	100
85000000000000000000	100
118000000000000000000	100
16000000000	

WELL CLUSTER	DEPTH	CLASSIFICATION	PROJECT
P30C SCREEN ZONE	150-160	LIGHT ORANGE MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

PROFESSIONAL SERVICE INDUSTRIES, INC.

WELL CLUSTER		DEPTH	CLASSIFICATION	PROJECT
P30D	SCREEN ZONE	80-100	ORANGISH BROWN SILTY MEDIUM SAND	PHASE III HYDROGEOLOGIC INVESTIGATION

APPENDIX G: WELL COMPLETION DIAGRAMS

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13TA

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13TB

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13TC

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13TD

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13A

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13D

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13C

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-13D

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-14TA

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-14TB

Traghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-14TC

raghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-14C

raghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-157A

raghty & Miller, inc.

WELL COMPLETION DIAGRAM P-15TB

raghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-15TC

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-15TD

raghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-15A

Scragsby & Miller, Inc.

WELL COMPLETION DIAGRAM P-15B

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-15C

Geraghty & Miller, Inc.

WELL COMPLETION DIAGRAM P-15D

WELL NO.: P-16 TB

DATE INSTALLED: 4/24/85

(Not to Scale)

WELL NO.: B-14 TB

DATE INSTALLED: 5/1/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-16 TC

DATE INSTALLED: 5/3/85

(Not to Scale)

WELL NO.: P-16 TD

DATE INSTALLED: 4/13/85

(Not to Scale)

WELL NO.: B-16 A

DATE INSTALLED: 4/19/85

(Not to Scale)

WELL NO.: P-16 B

DATE INSTALLED: 6/17/85

(Not to Scale)

WELL NO.: P-16 D

DATE INSTALLED: 5/20/85

(Not to Scale)

WELL NO.: P-17 TA

DATE INSTALLED: 8-2-85

WELL DIAGRAM

(Not to Scale)

WELL NO.: B-17 TB

DATE INSTALLED: 3/15/95

(Not to Scale)

WELL NO.: P-17 TC

DATE INSTALLED: 3/16/85

(Not to Scale)

WELL NO.: B-17 TD

DATE INSTALLED: 3/18/95

(Not to Scale)

WELL NO.: B-17 A

DATE INSTALLED: 2/19/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-17 B

DATE INSTALLED: 8/13/85

(Not to Scale)

WELL NO.: P-17 C

DATE INSTALLED: 3/20/85

(Not to Scale)

WELL NO.: P-17 D

DATE INSTALLED: 9/26/85

(Not to Scale)

WELL NO.: P-12 TA

DATE INSTALLED: 6/13/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-18 TB

DATE INSTALLED: 6/25/85

(Not to Scale)

WELL NO.: P-18 TC

DATE INSTALLED: 7/9/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-13 TD

DATE INSTALLED: 7/11/85

(Not to Scale)

WELL NO.: P-18 A

DATE INSTALLED: 9/23/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-18 B

DATE INSTALLED: 3/18/85

(Not to Scale)

WELL NO.: P-18 C

DATE INSTALLED: 9/16/85

(Not to Scale)

WELL NO.: B-19 TA

DATE INSTALLED: 1/26/85

(Not to Scale)

WELL NO.: P-19 TB

DATE INSTALLED: 5/10/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-12 TC

DATE INSTALLED: 5/30/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: B-19 TD

DATE INSTALLED: 5/31/95

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-19 A

DATE INSTALLED: 5/23/85

(Not to Scale)

WELL NO.: P-19 B

DATE INSTALLED: 3/22/85

(Not to Scale)

WELL NO.: P-19 C

DATE INSTALLED: 3/20/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-19 D

DATE INSTALLED: 6/2/85

(Not to Scale)

WELL NO.: B-20 TD

DATE INSTALLED: 3/15/95

WELL DIAGRAM

(Not to Scale)

WELL NO.: B-22 B

DATE INSTALLED: 7/24/85

(Not to Scale)

DATE INSTALLED: 9/29/85

WELL NO.: P-20 D

DATE INSTALLED: 7/2/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-21 TB

DATE INSTALLED: 5/16/85

WELL DIAGRAM

(Not to Scale)

DATE INSTALLED: 6/11/95

WELL NO.: P-21 TD

DATE INSTALLED: 5/13/95

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-21 A

DATE INSTALLED: 6/18/85

(Not to Scale)

WELL NO.: 1-22 B

DATE INSTALLED: 6/20/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: B-21 D

DATE INSTALLED: 6/21/95

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-22 TA

DATE INSTALLED: 7/3/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-22 TB

DATE INSTALLED: 3/13/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: B-22 TC

DATE INSTALLED: 7/31/25

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-22 TD

DATE INSTALLED: 7/25/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: B-22 A

DATE INSTALLED: 7/23/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-22 B

DATE INSTALLED: 7/18/85

(Not to Scale)

WELL NO.: P-22 C

DATE INSTALLED: 7/17/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-22 D

DATE INSTALLED: 7/17/85

(Not to Scale)

WELL NO.: P-23 TA

DATE INSTALLED: 4/15/85

(Not to Scale)

WELL NO.: P-23 TB

DATE INSTALLED: 2/29/35

WELL DIAGRAM

(Not to Scale)

WELL NO.: B-23 TC

DATE INSTALLED: 9/6/85

(Not to Scale)

WELL NO.: P-23 TD

DATE INSTALLED: 3/28/85

(Not to Scale)

WELL NO.: P-23 TS

DATE INSTALLED: 3/29/85

(Not to Scale)

WELL NO.: P-23 A

DATE INSTALLED: 9/10/85

WELL DIAGRAM

(Not to Scale)

WELL NO.: P-23 B

DATE INSTALLED: 2/11/95

(Not to Scale)

WELL NO.: P-23 D

DATE INSTALLED: 9/13/85

(Not to Scale)

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO.P-24 TA

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8-4-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-24 TB

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8-4 -86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-24 TC

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8-4-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-24 TD
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 8-4-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-24 A

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8-4-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-24 B

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8 - 19-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P- 24C
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 8-4 -86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-24D

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8-18-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-25 TA

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 5-12-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-357B

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 5-24-86

not to scale

OBSERVATION WELL DIAGRAM
WELL NO. P- 25 TC
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 7-15-86

(not to scale)

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-25TE
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 7-11-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-25 A

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 7-10-86

Not to scale

OBSERVATION WELL DIAGRAM

WELL NO. P- 25 B

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 7-11-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 25C

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 7-7 -66

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 25D

SAVANNAH RIVER PLANT, S. C.

DATE INSTALLED 7-7-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-26 TA

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8-22-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-26 TB
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-23-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P- 26 TC
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-26-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 16 TD

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-18-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-26 A
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-16-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 26B

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-12-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-26D

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 8-12-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 27 TA

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-7-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-27 TB

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-16-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P- 27TC
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9 - 4 - 86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-27 TD

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-9 -66

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-27 TE

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-11-66

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-27B

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-5 -86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-27C

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-19-81

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 27D

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-18-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-28TA

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 7-8 -86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-28 TS
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 10-2-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 28TC

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-7-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P- 28 TD
SAVANNAH RIVER PLANT. S.C.
DATE INSTALLED 10-9-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-28 TE

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-14-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-28A

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-27-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-29TA
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-22-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-29TC

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-16-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO.P- 29 TD

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-21-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-29A

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-21-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-298

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-29-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-29C

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-9-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 29D

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 10-8-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P- 30 TA
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 6-18-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-30 TB
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-26-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-30 TC
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-22-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P- 30 TD

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-22-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-30A

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-18-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-30B
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-19-86

(not to scale)

OBSERVATION WELL DIAGRAM

WELL NO. P-30C

SAVANNAH RIVER PLANT, S.C.

DATE INSTALLED 9-22-86

(not to scale)

OBSERVATION WELL DIAGRAM
WELL NO. P-30D
SAVANNAH RIVER PLANT, S.C.
DATE INSTALLED 9-19-86

REGIONAL

P-28

ELEV 204'

2.4 MILES

SCALE IS EXAGGERATED IN
THIS AREA FOR CLARITY

P-27

ELEV 270'

GAMMA RES. 3. POINT

GAMMA	RES.	S. POINT
-------	------	----------

R THREE
CREEK

ADLIFER

**AQUIFER
ZONE IID**

AQUIFER

ACQUIFERUS

五、

THE EISENBERG

**AQUIFER
ZONE 1A**

AQUIFER ZONE 1A

NAL HYDROSTRATIGRAPHIC CROSS-SECTION

-SECTION A-A'

2.9 MILES

SCALE IS EXAGGERATED IN
THIS AREA FOR CLARITY

P-24

ELEV 313'

RES. S. POINT

P-22

ELEV 215'

4.9 MILES

SCALE IS EXAGGERATED IN
THIS AREA FOR CLARITY

GAMMA RES.

A'

LEGEND:

REGIONAL UNCONFORMITY

PLANT NORTH
TRUE NORTH

AQUIFE
ZONE I

PLANT
NORTH
TRUE
NORTH

VERTICAL 0 50 100 FEET

PLATE 1

DWG NO. R00042

UNITED STATES DEPARTMENT OF ENERGY

SAVANNAH RIVER SITE

AREA SRS REGIONAL	ENR NO. 866467	PROJECT NO. SRS REGIONAL HYDROSTRATIGRAPHIC CLASSIFICATION
----------------------	-------------------	--

TITLE
**REGIONAL
HYDROSTRATIGRAPHIC
CROSS-SECTION A-A'**

DRAFTED BY T. MICKLEY/S. VICK	DATE
PREPARED BY R. AADLAND	DATE
GEOLOGY BY R. AADLAND	DATE
	DATE

WEST-EAST HYDROGEOLOGIC

5.5 MILES

2.6 MILES

2.4 MILES

GEOLOGIC CROSS-SECTION B - B'

PBF-1
 ELEV. 212'
 GAMMA RES. S. POINT

B'

LEGEND:

- SAND LOCALLY CONGLOMERATE
- CLAYEY/SILTY SAND
- MICACEOUS SAND
- CLAY, SILTY CLAY
- CALCAREOUS MUD
- LIMESTONE
- CLAYEY MICRITIC LIMESTONE
- CALCAREOUS SAND
- REGIONAL UNCONFORMITY

SCALE
 VERTICAL 0 50 100

B'

LEGEND:

SCALE

VERTICAL 0 50 100 FEET

-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
-900
-950
-1000
-1050
-1100
-1150

SCALE
VERTICAL 0 50

PLATE 2

UNITED STATES DEPARTMENT OF ENERGY		
SAVANNAH RIVER		
AREA	ENR NO.	PROJ.
SRS REGION	866467	
TITLE		
HYDROGEOLOGIC CROSS-SECTION B - B'		

Fig. 9

SCALE
VERTICAL 0 50 100 FEET

PLATE 2

SWR NO. R08843

UNITED STATES DEPARTMENT OF ENERGY

SAVANNAH RIVER SITE

AREA SRS REGION	SWR NO. 866467	PROJECT NO. SRS REGIONAL HYDROSTRATIGRAPHIC CLASSIFICATION
TITLE HYDROGEOLOGIC CROSS-SECTION B - B'		
DRAFTED BY S.F. VICK		DATE
PREPARED BY ROLF K. AADLAND		DATE
REVIEWED BY ROLF K. AADLAND		DATE
		DATE

Fig. 9

REGION

CROSS-SECTION C-C'

LEGEND:

- SAND LOCALLY CONGLOMERATIC
- CLAYEY/SILTY SAND
- MICACEOUS SAND
- CLAY, SILTY CLAY
- CALCAREOUS MUD
- LIMESTONE
- CLAYEY MICRITIC LIMESTONE
- CALCAREOUS SAND
- CONFINING UNIT

PLANT NORTH
TRUE NORTH

SCALE
VERTICAL 0 50 100 FEET

PLATE 3

ROB44

UNITED STATES DEPARTMENT OF ENERGY

SAVANNAH RIVER SITE

-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850

PLANT NORTH
TRUE NORTH

SCALE
VERTICAL 0 50 100 FEET

PLATE 3

DWG NO. RO8844

UNITED STATES DEPARTMENT OF ENERGY

SAVANNAH RIVER SITE

AREA SRS REGION	DWG NO. 866467	PROJECT NO. SRS REGIONAL HYDROSTRATIGRAPHIC CLASSIFICATION
TITLE REGIONAL HYDROSTRATIGRAPHIC CROSS-SECTION C-C'		DRAFTED BY T. MICKLEY DATE PREPARED BY R. AADLAND DATE CHECKED BY R. AADLAND DATE DATE

SOUTHWEST - NORTHEAST RE

REGIONAL HYDROSTRATIGRAPHIC CROSS-

-SECTION D-D'

LEGEND:

SCALE

VERTICAL 0 50 100 FEET

-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
-900
-950
-1000
-1050
-1100

**AQUIFER SYSTEMS
BOUNDARY**

300
350
400
450
500
550
600
650
700
750
800
850
900
950
1000
1050
1100

CLINT JEFF
NORTH SOUTH

PLATE 4

UNITED STATES DEPARTMENT OF ENERGY

SAVANNAH RIVER

AREA	ERR NO.	PROJECT
SRS REGION	866467	

TITLE
**SOUTHWEST-NORTHEAST
REGIONAL
HYDROSTRATIGRAPHIC
CROSS-SECTION D-D'**

VER

-300
 -350
 -400
 -450
 -500
 -550
 -600
 -650
 -700
 -750
 -800
 -850
 -900
 -950
 -1000
 -1050
 -1100

CLIMATE DATA

SCALE

VERTICAL 0 50 100 FEET

PLATE 4

DWG NO.

RO8845

UNITED STATES DEPARTMENT OF ENERGY

SAVANNAH RIVER SITE

AREA

SRS REGION

ENR NO.

866467

PROJECT NO.

SRS REGIONAL
HYDROSTRATIGRAPHIC CLASSIFICATION

TITLE

SOUTHWEST-NORTHEAST
 REGIONAL
 HYDORSTRATIGRAPHIC
 CROSS-SECTION D-D'

DRAFTED BY

T. MICKLEY

DATE

PREPARED BY

R. AADLAND

DATE

GEOLOGY BY

R. AADLAND

DATE

DATE

REGIONAL HYDROSTRATIGRAPHIC CORRELATION

IKEN CO.

10.0 MILES

P-16

ELEV 281'

JOHNSON
FORK

QANDA 18°RES. S. POINT

LEGEND

-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
-900
-950
-1000
-1050
-1100
-1150

PLATE 5

DES. NO. **RO2846**

UNITED STATES DEPARTMENT OF ENERGY			
SAVANNAH RIVER SITE			
AREA SRS REGIONAL	ENR NO. 866467	PROJECT NO. SRS REGIONAL HYDROSTRATIGRAPHIC CLASSIFICATION	
TITLE REGIONAL HYDROSTRATIGRAPHIC CROSS-SECTION E-E'		DRAFTED BY T. WICKLEY	DATE
		PREPARED BY R. AADLAND	DATE
		REVIEWED BY R. AADLAND	DATE
			DATE

END

DATE
FILMED

5 / 20 / 93