DOE/PC/79816--9

DOE/PC/79816--9

DE93 006473

**Slurry Phase Fischer-Tropsch Synthesis:
Cobalt Plus a Water-Gas Shift Catalyst**

Report for

April 1, 1990 to June 30, 1990

Report No.: DOE/PC79816-9

Contract No.: DE-AC22-87PC79816

by

Ian C. Yates

and

Charles N. Satterfield

for

U.S. Department of Energy

Pittsburgh Energy Technology Center

P.O. Box 10940-MS 902-L

Pittsburgh, PA 15236

Attention: Dr. V.U.S. Rao, Project Manager

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Summary

Experiments to study cobalt-catalyzed reactions of light 1-alkenes added to synthesis gas feed have been performed. Data have been collected at 220°C, 0.45 to 1.48 MPa and a synthesis gas flow rate between 0.015 and 0.030 NI/(gcat·min) with H₂/CO of 1.45 to 2.25. C₂H₄, C₃H₆, and C₄H₈ were added to the synthesis gas feed in concentrations ranging from 0.5 to 1.2 mole% of total feed. For each material balance in which 1-alkenes were added, a material balance was performed at similar process conditions without 1-alkenes added. This use of "base case" process conditions should make data analysis and interpretation easier. Material balances without added 1-alkenes were also repeated to allow verification of catalyst selectivity stability. A total of 49 material balances were performed during a single run which lasted over 2,500 hours-on-stream. The hydrocarbon data have now been completely analyzed and are reported herewith.

Data correlations are still being made. One set of preliminary conclusions are that C₃/C₁ ratios are increased by ethene addition, C₄/C₁ ratios are increased by propene addition, and C₅/C₁ ratios are increased by 1-butene addition. Thus, it appears that 1-alkenes may incorporate into growing chains on the surface of the catalyst. Further evidence for incorporation can be seen by comparing the selectivity to the n-alcohol one carbon number higher than the added 1-alkene. The yield of this n-alcohol increases when alkenes are present. The sensitivity of hydrocarbon distribution to process variables seems to be greater on cobalt than on iron catalysts.

Introduction

We have reported previously on the activity and selectivity of a Co/MgO/kieselguhr catalyst. The selectivity to desired high molecular weight products increased with decreasing H_2/CO ratio and increased with decreasing space velocity. Figure 1 shows the C_1 fraction increasing and the C_{10}^+ fraction decreasing with increasing space velocity. On Figure 1, the data points have been labelled with the *in situ* ethene to ethane ratio that was observed during normal synthesis. The ethene to ethane ratio decreases with increasing space velocity. Thus, the cause of this selectivity trend cannot be definitively established, on the basis of these experiments. We therefore wanted to study the reactions of 1-alkene in the cobalt Fischer-Tropsch synthesis by adding them directly to the feed. By understanding the role of important secondary reaction, we can potentially learn how to optimize the yield to desired high molecular weight products.

As further evidence for the importance of secondary reactions on cobalt, we have observed that the sensitivity of the hydrocarbon distribution to process variables seems to be greater on cobalt catalysts than that encountered with iron catalysts. This implies that secondary reactions, such as chain incorporation, as well as 1-alkene hydrogenation and isomerization, may be important in determining the final product distribution.

The objective of this part of our work is to develop a more fundamental understanding of the role of 1-alkenes in the hydrocarbon chain growth process on cobalt-based catalysts. In particular, we are concerned with the effects of process variables on the hydrocarbon product distribution and the secondary reactions of 1-alkenes.

The published literature contains very little information on reactions of added 1-alkenes during the Fischer-Tropsch synthesis on cobalt. Most alkene addition studies on cobalt were performed in conjunction with a more extensive study of feed additions to iron catalysts; as a result, cobalt catalysts were studied at only a few different process conditions. Although the consensus appears to be that 1-alkenes are incorporated into growing chains on the cobalt catalyst surface, there is little agreement as to the extent to which incorporation affects the product distribution. Further, no studies exist which cover a wide range of process conditions. Our study will attempt to quantify the effect of 1-alkene incorporation and correlate the effect of 1-alkene incorporation on the hydrocarbon product distribution with process variables.

Experimental

The experiments were performed in a continuous, mechanically-stirred, one-liter autoclave. The slurry reactor and ancillary equipment are described in detail elsewhere (Huff and Satterfield, 1982). The reactor and its contents are well-mixed and the reactor has been shown to operate free of heat and mass transfer limitations (Huff, 1982; Huff and Satterfield, 1982; Huff and Satterfield, 1984b).

The reactor was initially charged with 400 g of n-octacosane. The n-octacosane had been previously recrystallized in tetrahydrofuran (>99.9% purity) to remove a bromine impurity.

The cobalt catalyst used is a Co/MgO on SiO₂. This catalyst was prepared for us by an outside laboratory and is of the approximate composition of the cobalt catalysts used

at Ruhrchemie (Storch et al., 1951). The nominal composition of the catalyst, as reported to us by its manufacturer, is 21.4 wt.% Co (as Co), 3.9 wt.% Mg (as Mg), and the remainder diatomaceous earth.

Supplied as an extrudate, the catalyst was ground and sieved to 52 to 92 μm (170 to 270 ASTM Mesh). Following sieving, 17 grams of the catalyst were placed in an external reduction vessel. The catalyst was held in this reduction unit with a 7 μm frit while hydrogen (prepurified, MedTech Gases, Inc.) was brought on-stream at a flow of 1.36 NI/min (approximately 10,000 V/V/hr). At this flow rate, the pressure in the vessel as 0.79 MPa. The temperature of the reduction tube was increased steadily from 25°C to 330°C over 4 hours while the inlet flow rate was held constant. During this period the pressure in the reaction vessel increased to 0.97 MPa. The reduction unit was then held at 330°C for 1.5 hours. The unit was then pressured with helium and rapidly cooled. The unit with the catalyst was weighed, and comparison with the initial weight indicated that the catalyst lost 18 wt.% during reduction. The reduced catalyst was added to the one-liter autoclave reactor which contained molten n-octacosane under helium.

After reduction, the catalyst was allowed to achieve stable activity and selectivity and then process variables were manipulated to provide data over a broad range. Table 1 shows the process conditions for the material balances performed during 1-alkene additions. Data were obtained at 220°C, 0.45 to 1.48 MPa and a synthesis gas flow rate between 0.015 and 0.030 NI/(gcat·min) with a H₂/CO ratio of 1.45 to 2.25. The CO used in these experiments was CP grade (Granite State Oxygen, Inc., Matheson Gases, Inc., and MedTech Gases, Inc.) and the H₂ was prepurified grade (MedTech Gases, Inc.). 1-alkenes were premixed with

the CP grade CO and analyzed by Matheson Gases, Inc. Analyses were verified by GC to range from 1.8 to 2.2 mol.% 1-alkene in CO.

Three light 1-alkenes were added to the synthesis gas feed separately; they were C_2H_4 , C_3H_6 , and C_4H_8 which were added in quantities to comprise from 0.5 to 1.2 mole% of total feed. At these feed rates, the added 1-alkenes are present in concentrations ranging from 2 to 10 times the normal. 15 material balances were performed adding C_2H_4 , 6 adding C_3H_6 , and 8 adding C_4H_8 . These light 1-alkenes were chosen because they are not condensed to any significant extent in either the hot or cold traps. Thus, analysis of these light 1-alkenes is very accurate, and will allow us to close material balances on the added component or at the added component carbon number.

Products, liquid hydrocarbons and water, are condensed in two traps, one kept at 85°C and reactor pressure, the other at 1°C and 0.34 MPa. Material balances which were included in the analysis were required to close between 97 and 103% on oxygen, which was chosen as the material balance closure criteria because carbon and hydrogen accumulate in the reactor (Huff, 1982; Donnelly et al., 1988).

Products were analyzed with three gas chromatographs, as described by Huff et al. (1983). A Hewlett-Packard 5880 with a dimethyl silicone capillary column and flame ionization detector (FID) was used for hydrocarbon analyses of non-condensable gases and the organic phases from the hot and cold traps. Aqueous liquid samples from the hot and cold traps, and non-condensed water and oxygenated hydrocarbons were analyzed with a Hewlett-Packard 5710 using a glass column packed with 60/80 mesh Tenax and a thermal conductivity detector (TCD). A Carle/Hach refinery gas analyzer Series S AGC 111-H was

used for the analysis of non-condensable gases, particularly H_2 , CO , and CO_2 . Tie components, CO_2 , CH_4 , and C_2 and C_3 compounds, were used to match the analyses from the three gas chromatographs and provide complete product distributions for each material balance.

Material balances were performed over periods of 6 to 24 hours, with at least 10 hours allowed between material balances to ensure steady-state operation. When the reactor temperature or pressure was changed, at least 48 hours were allowed between material balances. For each material balance in which 1-alkenes were added a material balance was performed at similar process conditions without 1-alkenes added. This use of "base case" process conditions should make data analysis and interpretation easier, as it facilitates simple comparison of hydrocarbon selectivity with and without alkene addition. Material balances without added 1-alkenes were also repeated to allow verification of catalyst selectivity stability. A total of 49 material balances were performed during a single run which lasted over 2,500 hours-on-stream. The data from the material balances is presented in Appendix A.

Results and Discussion

The added alkene concentration was varied from approximately 0.5 to 1.5 mol% of total feed. The majority of the data were collected at a reactor temperature of 220°C .

The data on ethene additions are most complete, with the data on propene and 1-butene taken mostly to see how trends observed with ethene are general for higher alkenes.

Comparing C_3/C_1 ratios of ethene addition material balances to base-case indicates

ethene incorporates (see Appendix A). Analogous analyses for propene and 1-butene also indicate that they may also incorporate, but to a lesser extent. Figure 2a shows a Schulz-Flory plot of without 1-alkene additions and Figure 2b shows the same process conditions, but with ethene added to the feed. Evidence of alkene incorporation can be seen by examining the relative yield of the n-alcohol one carbon number above the added 1-alkene. This yield of this alcohol can be seen to be higher than the material balance without added alkene by visual examination of the Schulz-Flory plots in Figures 2a and 2b. The relative yield of all compounds one carbon number above is probably increased when 1-alkenes are added, but alcohols are most easily seen because they are produced in such low quantities and therefore differences between material balances can be readily observed.

Conclusions

C_3/C_1 ratios are increased by ethene addition, C_4/C_1 ratios are increased by propene addition, and C_5/C_1 ratios are increased by 1-butene addition. Thus, it appears that 1-alkenes may incorporate into growing chains on the surface of the catalyst. Further evidence for incorporation can be seen by comparing the selectivity to the n-alcohol one carbon number higher than the added 1-alkene. The yield of this n-alcohol increases when alkenes are present.

Future work will focus first on accurately quantifying the extent to which 1-alkenes incorporate and second on determination of the effect of process variables on the extent of incorporation.

Literature Cited

Donnelly, T.J.; Yates, I.C.; Satterfield, C.N., Energy and Fuels, **2**, 734, (1988).

Huff, G.A., Jr., "The Fischer-Tropsch Synthesis in a Slurry Reactor", Sc.D. Thesis, Massachusetts Institute of Technology, Cambridge, MA (1982).

Huff, G.A., Jr., and Satterfield, C.N., Ind. Eng. Chem. Fund., **21**, 479 (1982).

Huff, G.A., Jr., Satterfield, C.N., and Wolf, M.H., Ind. Eng. Chem. Fund., **22**, 258 (1983).

Storch, H.H.; Golumbic, N.; Anderson, R.B., The Fischer-Tropsch And Related Syntheses, Wiley (1959).

TABLE 1

MB	T	P	H ₂ /CO in	H ₂ +CO	ADDED	ADDED	BASE
[#]	[C]	[MPa]	[molar]	FLOW	COMPONENT	FLOW	MB
				[l/min]		[l/min]	[#]
3	240	0.79	2.02	1.143	-----	-----	-----
4	240	0.79	1.85	0.256	C ₂ H ₄	0.00181	-----
5	240	0.79	2.05	0.253	C ₂ H ₄	0.00168	-----
6	240	0.79	1.25	0.253	C ₂ H ₄	0.00227	-----
7	240	0.79	1.33	0.262	C ₂ H ₄	0.00227	-----
8	220	0.79	1.74	0.278	-----	-----	-----
9	220	0.79	1.76	0.283	C ₂ H ₄	0.00207	8
10	220	0.79	2.21	0.506	-----	-----	-----
11	220	0.79	2.21	0.518	C ₂ H ₄	0.00326	10
12	220	0.79	1.45	0.492	-----	-----	-----
13	220	0.79	1.45	0.490	C ₂ H ₄	0.00404	12
14	220	0.79	1.73	0.505	-----	-----	-----
15	220	0.79	1.73	0.509	C ₂ H ₄	0.00377	14
16	220	0.79	1.58	0.297	-----	-----	-----
17	220	0.79	1.58	0.299	C ₂ H ₄	0.00234	16
18	220	0.79	1.76	0.310	-----	-----	-----
19	220	0.79	1.76	0.297	C ₄ H ₈	0.00217	18 or 8
20	220	1.48	1.85	0.305	-----	-----	-----
21	220	1.48	1.85	0.305	C ₄ H ₈	0.00216	20
22	220	1.48	1.61	0.491	-----	-----	-----
23	220	1.48	1.61	0.486	C ₄ H ₈	0.00376	22
24	220	1.48	1.61	0.482	C ₂ H ₄	0.00373	22
25	220	1.48	1.92	0.481	-----	-----	-----
26	220	1.48	1.92	0.480	C ₂ H ₄	0.00332	25
27	220	1.48	1.91	0.496	C ₄ H ₈	0.00344	25
28	220	1.48	2.15	0.501	-----	-----	-----
29	220	1.48	2.15	0.504	C ₂ H ₄	0.00323	28
30	220	1.48	2.15	0.517	C ₄ H ₈	0.00332	28
31	220	1.48	2.15	0.494	C ₃ H ₆	0.00317	28
32	220	1.48	1.92	0.480	C ₃ H ₆	0.00332	25
33	220	1.48	1.63	0.472	C ₃ H ₆	0.00363	22
34	220	0.45	1.61	0.486	-----	-----	-----
35	220	0.45	1.63	0.501	C ₂ H ₄	0.00385	34
36	220	0.45	1.65	0.494	C ₃ H ₆	0.00377	34
37	220	0.45	1.91	0.491	-----	-----	-----
38	220	0.45	1.70	0.495	C ₂ H ₄	0.00370	37
39	220	0.45	1.73	0.498	C ₃ H ₆	0.00368	37
40	220	0.45	2.25	0.500	-----	-----	-----
41	220	0.45	2.25	0.500	C ₂ H ₄	0.00311	40
42	220	0.45	2.25	0.493	C ₃ H ₆	0.00306	40
43	220	0.45	2.30	0.514	C ₄ H ₈	0.00315	40
44	220	0.45	1.77	0.492	C ₄ H ₈	0.00359	37
45	220	0.45	1.63	0.486	C ₄ H ₈	0.00373	34
46	220	0.79	1.61	0.292	-----	-----	16 or 47
47	220	0.79	1.62	0.292	-----	-----	16 or 46
48	220	0.79	2.21	0.522	-----	-----	10 or 49
49	220	0.79	2.21	0.522	-----	-----	10 or 48

Figure 1. Decrease in desired products with increasing H_2/CO and ethene to ethane ratio. No 1-alkene added.

Figure 2a. Schulz Flory diagram from no addition synthesis.

C7.8: 220 C, 0.79 MPa, H₂/COin=1.74, H₂+COin=0.278 l/min.

**Figure 2b. Schulz-Flory diagram from ethene addition
same operating conditions as Figure 2a.**

C7.9: 220 C, 0.79 MPa, H₂/CO_{in}=1.76, H₂+CO_{in}=0.283 l/min.

APPENDIX A

Complete Activity and Hydrocarbon Data for 1-Alkene Addition Experiments

MOLES H2/MIN	0.2693E-01
MOLES CO/MIN	0.1367E-01
MOLES CO2/MIN	0.2942E-04
MOLES H2O/MIN	0.2876E-02

MOLES H2/MIN	0.2333E-02
MOLES CO/MIN	0.1367E-02
MOLES CO2/MIN	0.1887E-03
MOLES H2O/MIN	0.2128E-02

RUN: C7.6

DATE:

SAMPLE#:

TIME (MIN): 540.0

TEMP(C)= 240.0 PRESS(ATM ABS)=: 7.71559 L/M IN= 0.256 FEED RATIO= 1.250

FT MOLES OUT/MIN= 0.3732E-03 OCTACOSANE MOLES OUT/MIN= 0.1809E-05

FEED ADDITION L/MIN= 0.002 C2 H4 O0

AVE.MOLWT= 55.47 USAGE RATIO= 1.742 RATE CO+H2 (MILLIMOLES/MIN)= 5.420

XH2= 56.47 XCO= 40.53 XCO+H2= 47.46

PERCENT OXYGENATES= 1.644

PERCENT METHANE= 8.507

PERCENT OLEFINS= 29.258

BALANCES

C= 88.25 H= 95.74 O= 98.51 TOTWT= 94.15

PRESSURES(ATM ABS)

H2= 2.70880 CO= 2.98512 H2O= 1.57920 CO2= 0.08664

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	29.49	0.00	0.00	0.00	0.00	0.75	0.00	0.000	30.24
2	21.37	5.08	0.00	0.00	0.00	0.36	0.02	0.000	26.83
3	1.98	6.36	0.00	0.00	0.00	0.73	0.02	0.000	9.09
4	1.70	3.89	0.65	0.03	0.00	0.04	0.01	0.000	6.32
5	1.50	2.68	0.50	0.31	0.00	0.01	0.00	0.000	5.00
6	1.36	1.58	0.45	0.31	0.00	0.00	0.00	0.000	3.70
7	1.47	0.88	0.41	0.18	0.00	0.00	0.00	0.000	2.94
8	1.51	0.56	0.39	0.22	0.00	0.00	0.00	0.000	2.68
9	1.54	0.39	0.36	0.28	0.00	0.00	0.00	0.000	2.57
10	1.46	0.27	0.33	0.27	0.00	0.00	0.00	0.000	2.32
11	1.46	0.18	0.12	0.26	0.00	0.00	0.00	0.000	2.03
12	1.28	0.13	0.08	0.22	0.00	0.00	0.00	0.000	1.70
13	1.07	0.08	0.06	0.21	0.00	0.00	0.00	0.000	1.42
14	0.81	0.05	0.04	0.18	0.00	0.00	0.00	0.000	1.08
15	0.56	0.03	0.04	0.10	0.00	0.00	0.00	0.000	0.73
16	0.37	0.01	0.01	0.08	0.00	0.00	0.00	0.000	0.48
17	0.25	0.01	0.01	0.04	0.00	0.00	0.00	0.000	0.31
18	0.17	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.20
19	0.11	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.14
20	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.09
21	0.04	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.05
22	0.03	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.03
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.48	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.2855E-02

MOLES CO/MIN 0.3146E-02

MOLES CO2/MIN 0.9131E-04

MOLES H2O/MIN 0.1664E-02

SAMPLE#:

AVE.MOLWT= 49.36 USAGE RATIO= 1.334 RATE CO+H2 (MILLIMOLES/MIN)= 2.706

PERCENT OLEFINS= 29.788

H2= 4.40344 CO= 2.34271 H2O= 0.77690 CO2= 0.01027

MOLES H2/MIN	0.6330E-02
MOLES CO/MIN	0.3368E-02
MOLES CO2/MIN	0.1477E-04
MOLES H2O/MIN	0.1117E-02

SAMPLE#:

AVE.MOLWT= 44.70 USAGE RATIO= 1.601 RATE CO+H2 (MILLIMOLES/MIN)= 2.539

PERCENT OLEFINS= 29.951

H2= 4.48381 CO= 2.52047 H2O= 0.57677 CO2= 0.01137

MOLES H2/MIN	0.6457E-02
MOLES CO/MIN	0.3630E-02
MOLES CO2/MIN	0.1638E-04
MOLES H2O/MIN	0.8306E-03

RUN: C7.10

DATE:

SAMPLE#:

TIME (MIN): 1525.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.80077 L/M IN= 0.506 FEED RATIO= 2.210

FT MOLES OUT/MIN= 0.2845E-03 OCTACOSANE MOLES OUT/MIN= 0.3154E-06

AVE.MOLWT= 46.32 USAGE RATIO= 1.377 RATE CO+H2 (MILLIMOLES/MIN)= 2.600

XH2= 9.69 XCO= 15.55 XCO+H2= 11.52

PERCENT OXYGENATES= 5.758

PERCENT METHANE= 16.702

PERCENT OLEFINS= 30.686

BALANCES

C= 97.21 H= 102.97 O= 97.29 TOTWT= 98.04

PRESSURES(ATM ABS)

H2= 5.18264 CO= 2.19286 H2O= 0.31503 CO2= 0.00509

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	48.35	0.00	0.00	0.00	0.00	7.20	0.00	0.000	55.55
2	4.28	1.49	0.00	0.00	0.00	0.49	0.00	0.000	6.25
3	2.33	7.40	0.00	0.00	0.00	0.13	0.00	0.000	9.86
4	2.15	4.64	0.34	0.04	0.00	0.05	0.00	0.000	7.21
5	1.71	2.97	0.24	0.20	0.00	0.03	0.00	0.000	5.14
6	1.22	1.65	0.20	0.22	0.00	0.00	0.00	0.000	3.29
7	1.07	0.98	0.18	0.11	0.00	0.00	0.00	0.000	2.34
8	1.03	0.67	0.18	0.10	0.00	0.00	0.00	0.000	1.98
9	0.89	0.41	0.16	0.12	0.00	0.00	0.00	0.000	1.58
10	0.77	0.23	0.07	0.11	0.00	0.00	0.00	0.000	1.18
11	0.73	0.14	0.05	0.10	0.00	0.00	0.00	0.000	1.02
12	0.63	0.08	0.04	0.10	0.00	0.00	0.00	0.000	0.85
13	0.55	0.05	0.03	0.08	0.00	0.00	0.00	0.000	0.71
14	0.51	0.03	0.02	0.08	0.00	0.00	0.00	0.000	0.63
15	0.49	0.01	0.01	0.08	0.00	0.00	0.00	0.000	0.59
16	0.45	0.01	0.01	0.08	0.00	0.00	0.00	0.000	0.55
17	0.37	0.00	0.01	0.06	0.00	0.00	0.00	0.000	0.45
18	0.27	0.00	0.00	0.05	0.00	0.00	0.00	0.000	0.32
19	0.17	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.21
20	0.11	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.13
21	0.06	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.07
22	0.04	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.04
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1404E-01

MOLES CO/MIN 0.5939E-02

MOLES CO2/MIN 0.1379E-04

MOLES H2O/MIN 0.8532E-03

RUN: C7.12

DATE:

SAMPLE#:

TIME (MIN): 855.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.79946 L/M IN= 0.492 FEED RATIO= 1.450

FT MOLES OUT/MIN= 0.2119E-03 OCTACOSANE MOLES OUT/MIN= 0.4467E-06

AVE.MOLWT= 54.26 USAGE RATIO= 1.808 RATE CO+H2 (MILLIMOLES/MIN)= 2.208

XH2= 10.94 XCO= 8.78 XCO+H2= 10.06

PERCENT OXYGENATES= 3.728

PERCENT METHANE= 13.105

PERCENT OLEFINS= 32.442

BALANCES

C= 100.12 H= 103.79 O= 102.33 TOTWT= 101.61

PRESSURES(ATM ABS)

H2= 4.31205 CO= 3.04619 H2O= 0.35767 CO2= 0.00441

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	44.45	0.00	0.00	0.00	0.00	4.49	0.00	0.000	48.94
2	3.79	2.00	0.00	0.00	0.00	0.71	0.00	0.000	6.50
3	2.14	7.89	0.00	0.00	0.00	0.28	0.00	0.000	10.30
4	1.94	5.06	0.33	0.04	0.00	0.07	0.00	0.000	7.44
5	1.49	3.34	0.24	0.22	0.00	0.05	0.00	0.000	5.35
6	1.15	2.06	0.21	0.22	0.00	0.00	0.00	0.000	3.64
7	0.99	1.32	0.17	0.15	0.00	0.00	0.00	0.000	2.63
8	1.08	0.96	0.19	0.14	0.00	0.00	0.00	0.000	2.36
9	1.30	0.72	0.22	0.17	0.00	0.00	0.00	0.000	2.40
10	1.30	0.47	0.19	0.17	0.00	0.00	0.00	0.000	2.12
11	1.20	0.28	0.08	0.15	0.00	0.00	0.00	0.000	1.71
12	0.95	0.15	0.06	0.13	0.00	0.00	0.00	0.000	1.29
13	0.79	0.08	0.04	0.11	0.00	0.00	0.00	0.000	1.03
14	0.67	0.04	0.03	0.09	0.00	0.00	0.00	0.000	0.84
15	0.61	0.02	0.02	0.09	0.00	0.00	0.00	0.000	0.74
16	0.60	0.01	0.01	0.08	0.00	0.00	0.00	0.000	0.70
17	0.55	0.01	0.01	0.08	0.00	0.00	0.00	0.000	0.64
18	0.43	0.00	0.00	0.07	0.00	0.00	0.00	0.000	0.51
19	0.30	0.00	0.00	0.05	0.00	0.00	0.00	0.000	0.35
20	0.19	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.22
21	0.11	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.13
22	0.06	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.07
23	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
24	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.21	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1157E-01

MOLES CO/MIN 0.8173E-02

MOLES CO2/MIN 0.1184E-04

MOLES H2O/MIN 0.9596E-03

RUN: C7.14

DATE:

SAMPLE#:

TIME (MIN): 1625.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.82183 L/M IN= 0.505 FEED RATIO= 1.730

FT MOLES OUT/MIN= 0.2069E-03 OCTACOSANE MOLES OUT/MIN= 0.4163E-06

AVE.MOLWT= 45.67 USAGE RATIO= 2.175 RATE CO+H2 (MILLIMOLES/MIN)= 2.018

XH2= 9.68 XCO= 7.70 XCO+H2= 8.96

PERCENT OXYGENATES= 3.760

PERCENT METHANE= 17.947

PERCENT OLEFINS= 32.077

BALANCES

C= 101.07 H= 99.22 O= 100.00 TOTWT= 100.32

PRESSURES(ATM ABS)

H2= 4.74378 CO= 2.80218 H2O= 0.16910 CO2= 0.03049

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	51.22	0.00	0.00	0.00	0.00	4.04	0.00	0.000	55.27
2	4.40	1.81	0.00	0.00	0.00	0.41	0.01	0.000	6.63
3	2.45	7.90	0.00	0.00	0.00	0.25	0.00	0.000	10.60
4	2.15	4.73	0.39	0.05	0.00	0.08	0.00	0.000	7.39
5	1.56	2.91	0.28	0.22	0.00	0.02	0.00	0.000	4.99
6	1.16	1.67	0.22	0.18	0.00	0.00	0.00	0.000	3.24
7	0.92	0.96	0.17	0.10	0.00	0.00	0.00	0.000	2.16
8	0.80	0.61	0.15	0.08	0.00	0.00	0.00	0.000	1.64
9	0.76	0.42	0.15	0.09	0.00	0.00	0.00	0.000	1.41
10	0.68	0.27	0.10	0.08	0.00	0.00	0.00	0.000	1.13
11	0.64	0.16	0.05	0.08	0.00	0.00	0.00	0.000	0.93
12	0.51	0.09	0.04	0.07	0.00	0.00	0.00	0.000	0.70
13	0.45	0.06	0.03	0.07	0.00	0.00	0.00	0.000	0.60
14	0.41	0.03	0.02	0.06	0.00	0.00	0.00	0.000	0.53
15	0.39	0.02	0.01	0.06	0.00	0.00	0.00	0.000	0.48
16	0.41	0.01	0.01	0.06	0.00	0.00	0.00	0.000	0.48
17	0.42	0.01	0.00	0.06	0.00	0.00	0.00	0.000	0.49
18	0.38	0.00	0.00	0.06	0.00	0.00	0.00	0.000	0.45
19	0.29	0.00	0.00	0.04	0.00	0.00	0.00	0.000	0.34
20	0.20	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.23
21	0.12	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.14
22	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
23	0.04	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.05
24	0.02	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.03
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.20	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1290E-01

MOLES CO/MIN 0.7617E-02

MOLES CO2/MIN 0.8289E-04

MOLES H2O/MIN 0.4597E-03

RUN: C7.15

DATE:

SAMPLE#:

TIME (MIN): 1345.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.80998 L/M IN= 0.509 FEED RATIO= 1.730

FT MOLES OUT/MIN= 0.3690E-03 OCTACOSANE MOLES OUT/MIN= 0.4164E-06

FEED ADDITION L/MIN= 0.004 C2 H4 O0

AVE.MOLWT= 38.16 USAGE RATIO= 1.295 RATE CO+H2 (MILLIMOLES/MIN)= 1.930

XH2= 9.98 XCO= 13.33 XCO+H2= 8.50

PERCENT OXYGENATES= 7.081

PERCENT METHANE= 10.527

PERCENT OLEFINS= 33.523

BALANCES

C= 97.65 H= 101.93 O= 97.35 TOTWT= 97.97

PRESSURES(ATM ABS)

H2= 4.77490 CO= 2.70306 H2O= 0.19556 CO2= 0.00354

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	25.11	0.00	0.00	0.00	0.00	4.11	0.00	0.000	29.22
2	29.94	17.88	0.00	0.00	0.00	0.28	0.01	0.000	48.10
3	1.46	4.87	0.00	0.00	0.00	2.02	0.00	0.000	8.36
4	1.18	2.74	0.24	0.02	0.00	0.05	0.00	0.000	4.22
5	0.83	1.63	0.16	0.14	0.00	0.01	0.00	0.000	2.78
6	0.61	0.93	0.13	0.11	0.00	0.00	0.00	0.000	1.78
7	0.48	0.53	0.10	0.05	0.00	0.00	0.00	0.000	1.16
8	0.37	0.29	0.08	0.03	0.00	0.00	0.00	0.000	0.78
9	0.31	0.17	0.07	0.04	0.00	0.00	0.00	0.000	0.59
10	0.28	0.10	0.05	0.04	0.00	0.00	0.00	0.000	0.47
11	0.27	0.06	0.02	0.03	0.00	0.00	0.00	0.000	0.38
12	0.24	0.04	0.02	0.03	0.00	0.00	0.00	0.000	0.32
13	0.20	0.02	0.01	0.03	0.00	0.00	0.00	0.000	0.26
14	0.18	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.23
15	0.17	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.22
16	0.18	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.21
17	0.20	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.23
18	0.19	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.22
19	0.15	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.18
20	0.11	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.12
21	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
22	0.04	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.04
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1327E-01

MOLES CO/MIN 0.7511E-02

MOLES CO2/MIN 0.9832E-05

MOLES H2O/MIN 0.5434E-03

MOLES H2/MIN	0.7069E-02
MOLES CO/MIN	0.4540E-02
MOLES CO2/MIN	0.6071E-05
MOLES H2O/MIN	0.3981E-03

RUN: C7.18

DATE:

SAMPLE#:

TIME (MIN): 1740.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.54164 L/M IN= 0.310 FEED RATIO= 1.760

FT MOLES OUT/MIN= 0.1881E-03 OCTACOSANE MOLES OUT/MIN= 0.3364E-06

AVE.MOLWT= 44.69 USAGE RATIO= 2.124 RATE CO+H2 (MILLIMOLES/MIN)= 1.561

XH2= 12.04 XCO= 9.97 XCO+H2= 11.29

PERCENT OXYGENATES= 3.807

PERCENT METHANE= 18.659

PERCENT OLEFINS= 29.150

BALANCES

C= 101.43 H= 101.52 O= 99.65 TOTWT= 100.53

PRESSURES(ATM ABS)

H2= 4.52558 CO= 2.63166 H2O= 0.27301 CO2= 0.00147

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	52.12	0.00	0.00	0.00	0.00	3.90	0.00	0.000	56.02
2	4.79	1.28	0.00	0.00	0.00	0.59	0.00	0.000	6.66
3	2.81	7.37	0.00	0.00	0.00	0.18	0.00	0.000	10.36
4	2.37	4.14	0.53	0.05	0.00	0.06	0.00	0.000	7.15
5	1.78	2.47	0.39	0.19	0.00	0.03	0.00	0.000	4.86
6	1.34	1.33	0.32	0.17	0.00	0.00	0.00	0.000	3.16
7	1.07	0.72	0.25	0.08	0.00	0.00	0.00	0.000	2.11
8	0.94	0.43	0.22	0.09	0.00	0.00	0.00	0.000	1.67
9	0.88	0.28	0.20	0.12	0.00	0.00	0.00	0.000	1.48
10	0.81	0.18	0.16	0.13	0.00	0.00	0.00	0.000	1.27
11	0.76	0.13	0.05	0.12	0.00	0.00	0.00	0.000	1.06
12	0.62	0.08	0.04	0.09	0.00	0.00	0.00	0.000	0.83
13	0.52	0.05	0.03	0.09	0.00	0.00	0.00	0.000	0.68
14	0.43	0.03	0.02	0.08	0.00	0.00	0.00	0.000	0.55
15	0.35	0.02	0.01	0.06	0.00	0.00	0.00	0.000	0.44
16	0.29	0.01	0.01	0.05	0.00	0.00	0.00	0.000	0.36
17	0.26	0.00	0.00	0.04	0.00	0.00	0.00	0.000	0.31
18	0.25	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.27
19	0.22	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.25
20	0.17	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.19
21	0.11	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.12
22	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
23	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
24	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.18	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.7758E-02

MOLES CO/MIN 0.4511E-02

MOLES CO2/MIN 0.2513E-05

MOLES H2O/MIN 0.4680E-03

RUN: C7.19

DATE:

SAMPLE#:

TIME (MIN): 1425.0

TEMP(C)= 220.0 PRESS(ATM ABS)= 7.82314 L/M IN= 0.297 FEED RATIO= 1.760

FT MOLES OUT/MIN= 0.2496E-03 OCTACOSANE MOLES OUT/MIN= 0.1808E-06

FEED ADDITION L/MIN= 0.002 C4 HB OO

AVE.MOLWT= 47.03 USAGE RATIO= 1.200 RATE CO+H2 (MILLIMOLES/MIN)= 1.010

XH2= 10.91 XCO= 16.00 XCO+H2= 7.62

PERCENT OXYGENATES= 3.581

PERCENT METHANE= 11.043

PERCENT OLEFINS= 53.612

BALANCES

C= 99.61 H= 104.52 O= 100.00 TOTWT= 100.35

PRESSURES(ATM ABS)

H2= 4.77346 CO= 2.64363 H2O= 0.25122 CO2= 0.00350

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	32.46	0.00	0.00	0.00	0.00	4.24	0.00	0.000	36.70
2	3.08	1.02	0.00	0.00	0.00	0.32	0.00	0.000	4.42
3	1.75	4.96	0.00	0.00	0.00	0.11	0.00	0.000	6.83
4	7.23	29.27	4.50	0.08	0.00	0.04	0.00	0.000	41.12
5	1.01	1.54	0.26	0.13	0.00	0.09	0.00	0.000	3.03
6	0.68	0.76	0.21	0.10	0.00	0.00	0.00	0.000	1.75
7	0.53	0.38	0.14	0.08	0.00	0.00	0.00	0.000	1.12
8	0.48	0.21	0.12	0.08	0.00	0.00	0.00	0.000	0.88
9	0.48	0.14	0.11	0.08	0.00	0.00	0.00	0.000	0.82
10	0.47	0.09	0.09	0.08	0.00	0.00	0.00	0.000	0.72
11	0.44	0.06	0.03	0.07	0.00	0.00	0.00	0.000	0.60
12	0.35	0.04	0.02	0.05	0.00	0.00	0.00	0.000	0.47
13	0.27	0.02	0.01	0.05	0.00	0.00	0.00	0.000	0.35
14	0.21	0.01	0.01	0.04	0.00	0.00	0.00	0.000	0.27
15	0.16	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.20
16	0.13	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.16
17	0.11	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.13
18	0.10	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.12
19	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.10
20	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
21	0.05	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.05
22	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.7878E-02

MOLES CO/MIN 0.4363E-02

MOLES CO2/MIN 0.5773E-05

MOLES H2O/MIN 0.4146E-03

RUN: C7.20 DATE: SAMPLE#:
 TIME (MIN): 1470.0
 TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.69462 L/M IN= 0.305 FEED RATIO= 1.850
 FT MOLES OUT/MIN= 0.2830E-03 OCTACOSANE MOLES OUT/MIN= 0.1209E-06
 AVE.MOLWT= 36.66 USAGE RATIO= 1.678 RATE CO+H2 (MILLIMOLES/MIN)= 2.530

XH2= 17.95 XCO= 19.79 XCO+H2= 18.59

PERCENT OXYGENATES= 5.912 PERCENT METHANE= 23.797
 PERCENT OLEFINS= 28.610

BALANCES

C= 94.89 H= 101.60 O= 97.84 TOTWT= 97.16
 PRESSURES(ATM ABS)
 H2= 8.74803 CO= 4.62242 H2O= 0.96847 CO2= 0.01397

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	54.52	0.00	0.00	0.00	0.00	4.36	0.00	0.000	58.88
2	5.90	0.96	0.00	0.00	0.00	0.91	0.00	0.000	7.77
3	3.73	7.56	0.00	0.00	0.00	0.33	0.00	0.000	11.62
4	2.88	4.03	0.54	0.04	0.00	0.15	0.00	0.000	7.64
5	2.65	2.07	0.33	0.19	0.00	0.06	0.00	0.000	5.29
6	1.28	0.99	0.24	0.15	0.00	0.00	0.00	0.000	2.66
7	0.84	0.45	0.15	0.06	0.00	0.00	0.00	0.000	1.50
8	0.63	0.21	0.11	0.06	0.00	0.00	0.00	0.000	1.00
9	0.60	0.13	0.09	0.06	0.00	0.00	0.00	0.000	0.88
10	0.53	0.08	0.07	0.06	0.00	0.00	0.00	0.000	0.75
11	0.45	0.05	0.04	0.09	0.00	0.00	0.00	0.000	0.63
12	0.28	0.04	0.01	0.03	0.00	0.00	0.00	0.000	0.36
13	0.19	0.02	0.01	0.04	0.00	0.00	0.00	0.000	0.25
14	0.14	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.19
15	0.11	0.01	0.00	0.02	0.00	0.00	0.00	0.000	0.13
16	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.10
17	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
18	0.06	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.07
19	0.05	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.06
20	0.04	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.05
21	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
22	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
23	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.7248E-02
 MOLES CO/MIN 0.3830E-02
 MOLES CO2/MIN 0.1158E-04
 MOLES H2O/MIN 0.8024E-03

RUN: C7.21 DATE: SAMPLE#:
 TIME (MIN): 1395.0
 TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.48514 L/M IN= 0.316 FEED RATIO= 1.710
 FT MOLES OUT/MIN= 0.3277E-03 OCTACOSANE MOLES OUT/MIN= 0.8549E-08
 FEED ADDITION L/MIN= 0.002 C4 H8 CO
 AVE.MOLWT= 47.05 USAGE RATIO= 2.006 RATE CO+H2 (MILLIMOLES/MIN)= 3.094

XH2= 27.97 XCO= 23.84 XCO+H2= 21.94

PERCENT OXYGENATES= 2.911 PERCENT METHANE= 12.562
 PERCENT OLEFINS= 45.693

BALANCES

C= 95.19 H= 95.07 O= 100.09 TOTWT= 97.58
 PRESSURES(ATM ABS)
 H2= 7.95659 CO= 5.08032 H2O= 1.04511 CO2= 0.01492

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	36.94	0.00	0.00	0.00	0.00	2.27	0.00	0.000	39.21
2	4.21	0.81	0.00	0.00	0.00	0.69	0.01	0.000	5.72
3	2.27	5.53	0.00	0.00	0.00	0.25	0.00	0.000	8.06
4	7.41	20.91	4.47	0.08	0.00	0.09	0.00	0.000	32.97
5	1.35	1.74	0.28	0.19	0.00	0.11	0.00	0.000	3.66
6	0.91	0.91	0.20	0.17	0.00	0.00	0.00	0.000	2.19
7	0.72	0.48	0.14	0.12	0.00	0.00	0.00	0.000	1.46
8	0.64	0.28	0.12	0.10	0.00	0.00	0.00	0.000	1.14
9	0.65	0.19	0.12	0.07	0.00	0.00	0.00	0.000	1.03
10	0.72	0.12	0.08	0.08	0.00	0.00	0.00	0.000	1.00
11	0.72	0.10	0.04	0.07	0.00	0.00	0.00	0.000	0.94
12	0.63	0.07	0.03	0.05	0.00	0.00	0.00	0.000	0.79
13	0.52	0.04	0.02	0.07	0.00	0.00	0.00	0.000	0.65
14	0.37	0.02	0.02	0.06	0.00	0.00	0.00	0.000	0.47
15	0.24	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.29
16	0.14	0.00	0.01	0.02	0.00	0.00	0.00	0.000	0.18
17	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.10
18	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.06
19	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
20	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
21	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
22	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
23	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
24	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.6716E-02
 MOLES CO/MIN 0.4288E-02
 MOLES CO2/MIN 0.1259E-04
 MOLES H2O/MIN 0.8822E-03

RUN: C7.22

DATE:

SAMPLE#:

TIME (MIN): 1665.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.54926 L/M IN= 0.491 FEED RATIO= 1.610

FT MOLES OUT/MIN= 0.2758E-03 OCTACOSANE MOLES OUT/MIN= 0.0000E+00

AVE.MOLWT= 41.26 USAGE RATIO= 2.775 RATE CO+H2 (MILLIMOLES/MIN)= 2.792

XH2= 15.19 XCO= 8.81 XCO+H2= 12.74

PERCENT OXYGENATES= 3.923

PERCENT METHANE= 20.454

PERCENT OLEFINS= 32.411

BALANCES

C= 100.60 H= 98.02 O= 101.35 TOTWT= 100.72

PRESSURES(ATM ABS)

H2= 8.25025 CO= 5.50950 H2O= 0.57605 CO2= 0.01491

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	52.74	0.00	0.00	0.00	0.00	2.69	0.00	0.000	55.43
2	5.73	1.81	0.00	0.00	0.00	0.91	0.00	0.000	8.45
3	2.95	8.09	0.00	0.00	0.00	0.33	0.00	0.000	11.36
4	2.29	4.50	0.45	0.05	0.00	0.13	0.00	0.000	7.42
5	1.67	2.57	0.28	0.24	0.00	0.05	0.00	0.000	4.82
6	1.13	1.44	0.22	0.20	0.00	0.00	0.00	0.000	2.99
7	0.88	0.81	0.17	0.14	0.00	0.00	0.00	0.000	2.00
8	0.74	0.48	0.15	0.12	0.00	0.00	0.00	0.000	1.50
9	0.47	0.18	0.08	0.11	0.00	0.00	0.00	0.000	0.84
10	0.50	0.15	0.09	0.06	0.00	0.00	0.00	0.000	0.81
11	0.60	0.12	0.04	0.06	0.00	0.00	0.00	0.000	0.82
12	0.61	0.09	0.04	0.07	0.00	0.00	0.00	0.000	0.81
13	0.61	0.07	0.04	0.08	0.00	0.00	0.00	0.000	0.80
14	0.53	0.04	0.03	0.08	0.00	0.00	0.00	0.000	0.68
15	0.42	0.02	0.03	0.08	0.00	0.00	0.00	0.000	0.55
16	0.28	0.01	0.02	0.05	0.00	0.00	0.00	0.000	0.36
17	0.15	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.18
18	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.09
19	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.05
20	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
21	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
22	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
23	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
24	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1146E-01

MOLES CO/MIN 0.7654E-02

MOLES CO2/MIN 0.2072E-04

MOLES H2O/MIN 0.8002E-03

RUN: C7.23

DATE:

SAMPLE#:

TIME (MIN): 1490.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.53742 L/M IN= 0.486 FEED RATIO= 1.610

FT MOLES OUT/MIN= 0.5998E-03 OCTACOSANE MOLES OUT/MIN= 0.2521E-06

FEED ADDITION L/MIN= 0.004 C4 H8 O0

AVE.MOLWT= 44.90 USAGE RATIO= 1.534 RATE CO+H2 (MILLIMOLES/MIN)= 3.992

XH2= 22.78 XCO= 23.90 XCO+H2= 18.41

PERCENT OXYGENATES= 2.013

PERCENT METHANE= 14.041

PERCENT OLEFINS= 49.673

BALANCES

C= 97.44 H= 100.69 O= 96.79 TOTWT= 97.46

PRESSURES(ATM ABS)

H2= 8.12468 CO= 5.11914 H2O= 0.79817 CO2= 0.04619

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	39.41	0.00	0.00	0.00	0.00	1.46	0.00	0.000	40.86
2	4.62	1.01	0.00	0.00	0.00	0.49	0.00	0.000	6.12
3	2.04	5.27	0.00	0.00	0.00	0.18	0.00	0.000	7.48
4	6.11	23.64	4.06	0.09	0.00	0.05	0.00	0.000	33.95
5	0.98	1.44	0.26	0.23	0.00	0.08	0.00	0.000	2.99
6	0.63	0.76	0.17	0.19	0.00	0.00	0.00	0.000	1.74
7	0.52	0.44	0.09	0.14	0.00	0.00	0.00	0.000	1.20
8	0.50	0.30	0.11	0.12	0.00	0.00	0.00	0.000	1.02
9	0.53	0.23	0.11	0.10	0.00	0.00	0.00	0.000	0.96
10	0.52	0.16	0.08	0.08	0.00	0.00	0.00	0.000	0.85
11	0.50	0.11	0.03	0.06	0.00	0.00	0.00	0.000	0.70
12	0.39	0.06	0.02	0.05	0.00	0.00	0.00	0.000	0.52
13	0.30	0.04	0.02	0.04	0.00	0.00	0.00	0.000	0.39
14	0.24	0.02	0.01	0.04	0.00	0.00	0.00	0.000	0.31
15	0.19	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.24
16	0.15	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.19
17	0.12	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.14
18	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.10
19	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
20	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.06
21	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
22	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
23	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1085E-01

MOLES CO/MIN 0.6838E-02

MOLES CO2/MIN 0.6170E-04

MOLES H2O/MIN 0.1066E-02

RUN: C7.24

DATE:

SAMPLE#:

TIME (MIN): 1460.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.48250 L/M IN= 0.482 FEED RATIO= 1.610

FT MOLES OUT/MIN= 0.5745E-03 OCTACOSANE MOLES OUT/MIN= 0.2375E-06

FEED ADDITION L/MIN= 0.002 C2 H4 O0

AVE.MOLWT= 35.61 USAGE RATIO= 1.760 RATE CO+H2 (MILLIMOLES/MIN)= 4.119

XH2= 21.44 XCO= 19.61 XCO+H2= 19.15

PERCENT OXYGENATES= 4.565

PERCENT METHANE= 19.000

PERCENT OLEFINS= 26.896

BALANCES

C= 97.35 H= 100.28 O= 97.41 TOTWT= 97.68

PRESSURES(ATM ABS)

H2= 8.02706 CO= 5.15146 H2O= 0.82070 CO2= 0.04762

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	42.29	0.00	0.00	0.00	0.00	1.93	0.00	0.000	44.22
2	25.31	5.36	0.00	0.00	0.00	0.59	0.01	0.000	31.27
3	2.25	5.90	0.00	0.00	0.00	1.07	0.00	0.000	9.22
4	1.72	2.95	0.48	0.05	0.00	0.07	0.00	0.000	5.28
5	0.99	1.44	0.23	0.29	0.00	0.04	0.00	0.000	2.99
6	0.62	0.76	0.15	0.17	0.00	0.00	0.00	0.000	1.70
7	0.48	0.40	0.10	0.11	0.00	0.00	0.00	0.000	1.09
8	0.38	0.24	0.08	0.08	0.00	0.00	0.00	0.000	0.76
9	0.35	0.15	0.06	0.06	0.00	0.00	0.00	0.000	0.62
10	0.33	0.10	0.05	0.05	0.00	0.00	0.00	0.000	0.52
11	0.32	0.07	0.02	0.04	0.00	0.00	0.00	0.000	0.44
12	0.27	0.04	0.02	0.04	0.00	0.00	0.00	0.000	0.37
13	0.25	0.03	0.01	0.04	0.00	0.00	0.00	0.000	0.33
14	0.22	0.02	0.01	0.04	0.00	0.00	0.00	0.000	0.28
15	0.19	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.24
16	0.15	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.19
17	0.12	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.14
18	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.11
19	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
20	0.05	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.06
21	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
22	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
23	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1059E-01

MOLES CO/MIN 0.6796E-02

MOLES CO2/MIN 0.6282E-04

MOLES H2O/MIN 0.1083E-02

SAMPLE#:

AVE.MOLWT= 36.83 USAGE RATIO= 1.871 RATE CO+H2 (MILLIMOLES/MIN)= 4.053

$$X_{H_2} = 20.97 \quad X_{CO} = 21.52 \quad X_{CO+H_2} = 18.93$$

PERCENT METHANE= 18.593

PERCENT OLEFINS= 22.753

BALANCES

C= 96.63 H= 98.72 O= 97.71 TOTWT= 97.41

PRESSURES (ATM ABS)

H2= 8.67189 CO= 4.57209 H2O= 0.79124 CO2= 0.04184

MOLE BASIS PERCENT OF FT PRODUCTS

[illegible]

MOLES H2O/MIN	0.1037E-02
---------------	------------

RUN: C7.27

DATE:

SAMPLE#:

TIME (MIN): 1400.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.42496 L/M IN= 0.496 FEED RATIO= 1.910

FT MOLES OUT/MIN= 0.4597E-03 OCTACOSANE MOLES OUT/MIN= 0.1629E-06

FEED ADDITION L/MIN= 0.004 C4 H8 CO

AVE.MOLWT= 46.03 USAGE RATIO= 2.388 RATE CO+H2 (MILLIMOLES/MIN)= 3.383

XH2= 21.32 XCO= 17.05 XCO+H2= 15.29

PERCENT OXYGENATES= 1.857

PERCENT METHANE= 12.596

PERCENT OLEFINS= 51.517

BALANCES

C= 101.10 H= 95.37 O= 101.15 TOTWT= 100.43

PRESSURES(ATM ABS)

H2= 8.58416 CO= 4.91599 H2O= 0.57084 CO2= 0.02283

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	36.24	0.00	0.00	0.00	0.00	1.15	0.00	0.000	37.39
2	4.22	0.95	0.00	0.00	0.00	0.61	0.00	0.000	5.77
3	2.20	4.68	0.00	0.00	0.00	0.18	0.00	0.000	7.07
4	7.28	28.58	3.57	0.09	0.00	0.08	0.00	0.000	39.59
5	0.99	1.42	0.19	0.17	0.00	0.04	0.00	0.000	2.81
6	0.66	0.75	0.12	0.13	0.00	0.00	0.00	0.000	1.66
7	0.46	0.38	0.08	0.10	0.00	0.00	0.00	0.000	1.02
8	0.37	0.21	0.06	0.05	0.00	0.00	0.00	0.000	0.70
9	0.30	0.11	0.04	0.04	0.00	0.00	0.00	0.000	0.49
10	0.33	0.10	0.04	0.04	0.00	0.00	0.00	0.000	0.51
11	0.37	0.07	0.02	0.03	0.00	0.00	0.00	0.000	0.48
12	0.35	0.04	0.02	0.04	0.00	0.00	0.00	0.000	0.45
13	0.33	0.03	0.01	0.03	0.00	0.00	0.00	0.000	0.41
14	0.31	0.02	0.01	0.04	0.00	0.00	0.00	0.000	0.38
15	0.27	0.01	0.01	0.04	0.00	0.00	0.00	0.000	0.33
16	0.22	0.01	0.00	0.04	0.00	0.00	0.00	0.000	0.27
17	0.17	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.21
18	0.13	0.01	0.00	0.02	0.00	0.00	0.00	0.000	0.15
19	0.10	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.11
20	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
21	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.05
22	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1192E-01

MOLES CO/MIN 0.6826E-02

MOLES CO2/MIN 0.3170E-04

MOLES H2O/MIN 0.7926E-03

RUN: C7.28 DATE: SAMPLE#:
 TIME (MIN): 1500.0
 TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.47856 L/M IN= 0.501 FEED RATIO= 2.150
 FT MOLES OUT/MIN= 0.3861E-03 OCTACOSANE MOLES OUT/MIN= 0.2017E-06
 AVE.MOLWT= 38.29 USAGE RATIO= 1.745 RATE CO+H2 (MILLIMOLES/MIN)= 3.177

XH2= 13.24 XCO= 16.31 XCO+H2= 14.21

PERCENT OXYGENATES= 2.853 PERCENT METHANE= 24.060
 PERCENT OLEFINS= 26.803

BALANCES

C= 98.20 H= 101.38 O= 97.53 TOTWT= 98.29
 PRESSURES(ATM ABS)
 H2= 9.34843 CO= 4.19410 H2O= 0.64059 CO2= 0.02260

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	57.58	0.00	0.00	0.00	0.00	2.07	0.00	0.000	59.65
2	6.84	1.25	0.00	0.00	0.00	0.71	0.00	0.000	8.80
3	3.61	6.59	0.00	0.00	0.00	0.11	0.00	0.000	10.31
4	2.44	3.67	0.54	0.06	0.00	0.05	0.00	0.000	6.76
5	1.67	1.86	0.26	0.23	0.00	0.01	0.00	0.000	4.03
6	1.06	1.02	0.17	0.20	0.00	0.00	0.00	0.000	2.45
7	0.80	0.56	0.11	0.10	0.00	0.00	0.00	0.000	1.58
8	0.65	0.34	0.09	0.04	0.00	0.00	0.00	0.000	1.11
9	0.56	0.21	0.08	0.05	0.00	0.00	0.00	0.000	0.91
10	0.54	0.13	0.04	0.05	0.00	0.00	0.00	0.000	0.76
11	0.50	0.08	0.03	0.04	0.00	0.00	0.00	0.000	0.65
12	0.45	0.06	0.02	0.03	0.00	0.00	0.00	0.000	0.55
13	0.40	0.03	0.02	0.05	0.00	0.00	0.00	0.000	0.50
14	0.36	0.02	0.01	0.04	0.00	0.00	0.00	0.000	0.44
15	0.32	0.01	0.01	0.04	0.00	0.00	0.00	0.000	0.38
16	0.27	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.31
17	0.22	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.25
18	0.16	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.18
19	0.12	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.14
20	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.10
21	0.06	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.07
22	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1324E-01
 MOLES CO/MIN 0.5939E-02
 MOLES CO2/MIN 0.3199E-04
 MOLES H2O/MIN 0.9070E-03

MOLES H2/MIN	0.1321E-01
MOLES CO/MIN	0.6050E-02
MOLES CO2/MIN	0.3367E-04
MOLES H2O/MIN	0.9319E-03

RUN: C7.30 DATE: SAMPLE#:
 TIME (MIN): 1500.0
 TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.41312 L/M IN= 0.517 FEED RATIO= 2.150
 FT MOLES OUT/MIN= 0.4507E-03 OCTACOSANE MOLES OUT/MIN= 0.2836E-06
 FEED ADDITION L/MIN= 0.003 C4 H8 O0
 AVE.MOLWT= 47.06 USAGE RATIO= 2.005 RATE CO+H2 (MILLIMOLES/MIN)= 3.254
 XH2= 17.86 XCO= 19.15 XCO+H2= 14.11

PERCENT OXYGENATES= 2.736 PERCENT METHANE= 12.138
 PERCENT OLEFINS= 47.445

BALANCES

C= 99.72 H= 98.26 O= 100.65 TOTWT= 99.97
 PRESSURES(ATM ABS)
 H2= 9.12620 CO= 4.35125 H2O= 0.60548 CO2= 0.02341

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	35.70	0.00	0.00	0.00	0.00	2.28	0.00	0.000	37.98
2	4.96	0.85	0.00	0.00	0.00	0.60	0.00	0.000	6.41
3	2.23	4.38	0.00	0.00	0.00	0.20	0.00	0.000	6.81
4	7.51	26.30	3.48	0.09	0.00	0.07	0.00	0.000	37.46
5	1.04	1.35	0.19	0.19	0.00	0.12	0.00	0.000	2.90
6	0.71	0.74	0.12	0.14	0.00	0.00	0.00	0.000	1.72
7	0.50	0.40	0.08	0.08	0.00	0.00	0.00	0.000	1.08
8	0.45	0.24	0.06	0.07	0.00	0.00	0.00	0.000	0.83
9	0.43	0.10	0.06	0.04	0.00	0.00	0.00	0.000	0.69
10	0.43	0.10	0.03	0.03	0.00	0.00	0.00	0.000	0.59
11	0.42	0.07	0.02	0.03	0.00	0.00	0.00	0.000	0.54
12	0.41	0.05	0.02	0.03	0.00	0.00	0.00	0.000	0.51
13	0.39	0.03	0.01	0.04	0.00	0.00	0.00	0.000	0.47
14	0.36	0.02	0.01	0.04	0.00	0.00	0.00	0.000	0.43
15	0.33	0.01	0.01	0.04	0.00	0.00	0.00	0.000	0.38
16	0.28	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.32
17	0.23	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.26
18	0.18	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.19
19	0.13	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.14
20	0.10	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.11
21	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.07
22	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1342E-01
 MOLES CO/MIN 0.6396E-02
 MOLES CO2/MIN 0.3441E-04
 MOLES H2O/MIN 0.8901E-03

RUN: C7.31

DATE:

SAMPLE#

TIME (MIN): 1465.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 14.42364 L/M IN= 0.494 FEED RATIO= 2.150

FT MOLES OUT/MIN= 0.4758E-03 OCTACOSANE MOLES OUT/MIN= 0.2512E-06

FEED ADDITION L/MIN= 0.003 C3 H6 O0

AVE.MOLWT= 40.04 USAGE RATIO= 1.557 RATE CO+H2 (MILLIMOLES/MIN)= 2.925

XH2= 14.79 XCO= 20.42 XCO+H2= 13.27

PERCENT OXYGENATES= 2.760

PERCENT METHANE= 15.505

PERCENT OLEFINS= 44.187

BALANCES

C= 97.53 H= 101.28 O= 98.30 TOTWT= 98.40

PRESSURES(ATM ABS)

H2= 9.28235 CO= 4.16445 H2O= 0.61932 CO2= 0.02266

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	38.80	0.00	0.00	0.00	0.00	2.02	0.00	0.000	40.83
2	4.43	0.80	0.00	0.00	0.00	0.50	0.00	0.000	5.74
3	8.46	30.69	0.00	0.00	0.00	0.16	0.00	0.000	39.31
4	1.60	2.30	0.30	0.04	0.00	0.15	0.00	0.000	4.38
5	1.03	1.20	0.15	0.17	0.00	0.02	0.00	0.000	2.57
6	0.66	0.62	0.09	0.13	0.00	0.00	0.00	0.000	1.50
7	0.48	0.47	0.06	0.08	0.00	0.00	0.00	0.000	1.09
8	0.40	0.20	0.05	0.04	0.00	0.00	0.00	0.000	0.70
9	0.38	0.13	0.05	0.02	0.00	0.00	0.00	0.000	0.58
10	0.38	0.09	0.03	0.03	0.00	0.00	0.00	0.000	0.52
11	0.37	0.06	0.02	0.02	0.00	0.00	0.00	0.000	0.47
12	0.34	0.04	0.01	0.03	0.00	0.00	0.00	0.000	0.42
13	0.30	0.02	0.01	0.03	0.00	0.00	0.00	0.000	0.37
14	0.27	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.32
15	0.24	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.28
16	0.21	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.23
17	0.18	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.19
18	0.14	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.16
19	0.11	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.12
20	0.08	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.08
21	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.06
22	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
23	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
24	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
25	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
26	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
28	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1319E-01

MOLES CO/MIN 0.5920E-02

MOLES CO2/MIN 0.3221E-04

MOLES H2O/MIN 0.8804E-03

MOLES H2/MIN	0.1204E-01
MOLES CO/MIN	0.6363E-02
MOLES CO2/MIN	0.1990E-04
MOLES H2O/MIN	0.8026E-03

SAMPLE#:

AVE.MOLWT= 43.33 USAGE RATIO= 1.107 RATE CO+H2 (MILLIMOLES/MIN)= 2.221

$$\text{XH}_2 = 12.41 \quad \text{XCO} = 18.27 \quad \text{XCO} + \text{H}_2 = 10.55$$

PERCENT METHANE= 10.810

PERCENT OLEFINS= 53.440

BALANCES

C= 96.32 H= 103.49 O= 97.01 TOTWT= 97.42

PRESSURES (ATM ABS)

H2= 8.52117 CO= 4.99312 H2O= 0.52692 CO2= 0.02229

MOLE BASIS PERCENT OF FT PRODUCTS

[illegible]

MOLES H2O/MIN	0.7344E-03
---------------	------------

SAMPLE: #

AVE. MOLWT= 42.40 USAGE RATIO= 1.917 RATE CO+H2 (MILLIMOLES/MIN)= 1.549

PERCENT OLEFINS= 37.682

H2= 2.60973 CO= 1.64235 H2O= 0.08999 CO2= 0.00278

MOLES H2/MIN	0.1236E-01
MOLES CO/MIN	0.7777E-02
MOLES CO2/MIN	0.1317E-04
MOLES H2O/MIN	0.4261E-03

MOLES H2/MIN	0.1211E-01
MOLES CO/MIN	0.7740E-02
MOLES CO2/MIN	0.1835E-04
MOLES H2O/MIN	0.6397E-03

RUN: C7.36 DATE: SAMPLE#:
 TIME (MIN): 1425.0
 TEMP(C)= 220.0 PRESS(ATM ABS)=: 4.41552 L/M IN= 0.494 FEED RATIO= 1.650
 FT MOLES OUT/MIN= 0.3834E-03 OCTACOSANE MOLES OUT/MIN= 0.6191E-06
 FEED ADDITION L/MIN= 0.004 C3 H6 O0
 AVE.MOLWT= 44.60 USAGE RATIO= 1.496 RATE CO+H2 (MILLIMOLES/MIN)= 2.136

XH2= 13.35 XCO= 14.72 XCO+H2= 9.69

PERCENT OXYGENATES= 2.072 PERCENT METHANE= 7.652
 PERCENT OLEFINS= 65.823

BALANCES

C= 98.89 H= 99.23 O= 96.66 TOTWT= 97.82

PRESSURES(ATM ABS)

H2= 2.62873 CO= 1.60621 H2O= 0.09566 CO2= 0.00321

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	21.33	0.00	0.00	0.00	0.00	2.56	0.00	0.000	23.89
2	1.02	1.92	0.00	0.00	0.00	0.11	0.00	0.000	3.04
3	4.93	55.80	0.00	0.00	0.00	0.04	0.00	0.000	60.76
4	0.76	2.10	0.18	0.00	0.00	0.04	0.00	0.000	3.08
5	0.56	1.37	0.13	0.06	0.00	0.01	0.00	0.000	2.12
6	0.43	0.84	0.11	0.08	0.00	0.00	0.00	0.000	1.46
7	0.41	0.58	0.11	0.09	0.00	0.00	0.00	0.000	1.19
8	0.37	0.39	0.10	0.04	0.00	0.00	0.00	0.000	0.91
9	0.29	0.19	0.08	0.04	0.00	0.00	0.00	0.000	0.60
10	0.25	0.13	0.08	0.02	0.00	0.00	0.00	0.000	0.48
11	0.24	0.08	0.02	0.02	0.00	0.00	0.00	0.000	0.35
12	0.19	0.04	0.01	0.02	0.00	0.00	0.00	0.000	0.26
13	0.11	0.02	0.01	0.02	0.00	0.00	0.00	0.000	0.16
14	0.11	0.01	0.01	0.01	0.00	0.00	0.00	0.000	0.14
15	0.11	0.01	0.01	0.01	0.00	0.00	0.00	0.000	0.14
16	0.13	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.15
17	0.17	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.19
18	0.20	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.22
19	0.21	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.23
20	0.19	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.20
21	0.15	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.16
22	0.10	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.11
23	0.06	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.07
24	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
25	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
26	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
27	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
28	0.16	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1235E-01
 MOLES CO/MIN 0.7549E-02
 MOLES CO2/MIN 0.1507E-04
 MOLES H2O/MIN 0.4496E-03

SAMPLE#:

AVE.MOLWT= 46.94 USAGE RATIO= 1.741 RATE CO+H2 (MILLIMOLES/MIN)= 1.685

$$\text{XH}_2 = 7.44 \quad \text{XCO} = 8.17 \quad \text{XCO} + \text{H}_2 = 7.69$$

PERCENT METHANE= 18.235

PERCENT OLEFINS= 33.152

C= 98.66 H= 99.85 O= 97.59 TOTWT= 98.27

H2= 2.81209 CO= 1.46077 H2O= 0.08600 CO2= 0.00251

[illegible]

MOLES H2O/MIN	0.4070E-03
---------------	------------

SAMPLE#:

AVE.MOLWT= 36.08 USAGE RATIO= 1.786 RATE CO+H2 (MILLIMOLES/MIN)= 1.968

PERCENT OLEFINS= 39.279

H2= 2.59154 CO= 1.56131 H2O= 0.08731 CO2= 0.01607

MOLES H2/MIN	0.1255E-01
MOLES CO/MIN	0.7563E-02
MOLES CO2/MIN	0.7784E-04
MOLES H2O/MIN	0.4229E-03

SAMPLE#:

AVE. MOLWT= 38.67 USAGE RATIO= 1.537 RATE CO+H2 (MILLIMOLES/MIN)= 2.104

PERCENT OLEFINS= 42.381

H2= 2.64654 CO= 1.54118 H2O= 0.07965 CO2= 0.00317

MOLES H2/MIN	0.1271E-01
MOLES CO/MIN	0.7403E-02
MOLES CO2/MIN	0.1523E-04
MOLES H2O/MIN	0.3826E-03

RUN: C7.40

DATE:

SAMPLE#:

TIME (MIN): 1450.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 4.40631 L/M IN= 0.500 FEED RATIO= 2.250

FT MOLES OUT/MIN= 0.1861E-03 OCTACOSANE MOLES OUT/MIN= 0.7943E-06

AVE.MOLWT= 43.74 USAGE RATIO= 1.576 RATE CO+H2 (MILLIMOLES/MIN)= 1.702

XH2= 6.74 XCO= 9.63 XCO+H2= 7.63

PERCENT OXYGENATES= 3.970

PERCENT METHANE= 19.770

PERCENT OLEFINS= 30.722

BALANCES

C= 98.55 H= 100.95 O= 97.69 TOTWT= 98.46

PRESSURES(ATM ABS)

H2= 2.98314 CO= 1.28483 H2O= 0.09721 CO2= 0.00242

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	54.04	0.00	0.00	0.00	0.00	4.76	0.00	0.000	58.81
2	4.41	1.64	0.00	0.00	0.00	0.29	0.00	0.000	6.34
3	2.33	6.73	0.00	0.00	0.00	0.10	0.00	0.000	9.16
4	2.02	4.02	0.54	0.03	0.00	0.02	0.00	0.000	6.64
5	1.68	2.72	0.40	0.17	0.00	0.00	0.00	0.000	4.97
6	1.32	1.65	0.34	0.24	0.00	0.00	0.00	0.000	3.56
7	1.05	0.95	0.26	0.12	0.00	0.00	0.00	0.000	2.38
8	0.75	0.57	0.19	0.09	0.00	0.00	0.00	0.000	1.59
9	0.56	0.35	0.14	0.10	0.00	0.00	0.00	0.000	1.15
10	0.45	0.20	0.09	0.06	0.00	0.00	0.00	0.000	0.80
11	0.41	0.10	0.04	0.05	0.00	0.00	0.00	0.000	0.60
12	0.38	0.06	0.03	0.05	0.00	0.00	0.00	0.000	0.52
13	0.29	0.03	0.02	0.04	0.00	0.00	0.00	0.000	0.39
14	0.26	0.02	0.02	0.04	0.00	0.00	0.00	0.000	0.34
15	0.24	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.30
16	0.22	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.27
17	0.22	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.26
18	0.26	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.29
19	0.33	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.35
20	0.35	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.37
21	0.30	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.32
22	0.21	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.24
23	0.14	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.15
24	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.09
25	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.05
26	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
27	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
28	0.43	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1440E-01

MOLES CO/MIN 0.6203E-02

MOLES CO2/MIN 0.1170E-04

MOLES H2O/MIN 0.4693E-03

SAMPLE#:

AVE.MOLWT= 37.92 USAGE RATIO= 1.824 RATE CO+H2 (MILLIMOLES/MIN)= 2.247

PERCENT OLEFINS= 32.339

H2= 2.91114 CO= 1.28254 H2O= 0.10211 CO2= 0.00984

MOLES H2/MIN	0.1393E-01
MOLES CO/MIN	0.6135E-02
MOLES CO2/MIN	0.4705E-04
MOLES H2O/MIN	0.4885E-03

MOLES H2/MIN	0.1397E-01
MOLES CO/MIN	0.6189E-02
MOLES CO2/MIN	0.4700E-04
MOLES H2O/MIN	0.3643E-03

RUN: C7.43

DATE:

SAMPLE#:

TIME (MIN): 3005.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 4.56877 L/M IN= 0.514 FEED RATIO= 2.300

FT MOLES OUT/MIN= 0.5656E-03 OCTACOSANE MOLES OUT/MIN= 0.8924E-06

FEED ADDITION L/MIN= 0.003 C4 H8 O0

AVE.MOLWT= 48.25 USAGE RATIO= 1.267 RATE CO+H2 (MILLIMOLES/MIN)= 1.627

XH2= 9.17 XCO= 16.64 XCO+H2= 7.10

PERCENT OXYGENATES= 6.448

PERCENT METHANE= 7.848

PERCENT OLEFINS= 61.131

BALANCES

C= 107.97 H= 106.59 O= 97.68 TOTWT= 102.89

PRESSURES(ATM ABS)

H2= 3.07596 CO= 1.28235 H2O= 0.09402 CO2= 0.00055

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	23.67	0.00	0.00	0.00	0.00	9.42	0.00	0.000	33.08
2	1.91	0.75	0.00	0.00	0.00	0.09	0.00	0.000	2.76
3	1.01	3.04	0.00	0.00	0.00	0.03	0.00	0.000	4.08
4	7.67	39.05	4.60	0.06	0.00	0.01	0.00	0.000	51.38
5	0.80	1.38	0.21	0.10	0.00	0.04	0.00	0.000	2.53
6	0.64	0.83	0.18	0.11	0.00	0.00	0.00	0.000	1.77
7	0.51	0.46	0.14	0.06	0.00	0.00	0.00	0.000	1.18
8	0.41	0.24	0.11	0.04	0.00	0.00	0.00	0.000	0.80
9	0.33	0.13	0.09	0.04	0.00	0.00	0.00	0.000	0.59
10	0.24	0.07	0.04	0.02	0.00	0.00	0.00	0.000	0.37
11	0.19	0.03	0.02	0.02	0.00	0.00	0.00	0.000	0.26
12	0.15	0.02	0.01	0.01	0.00	0.00	0.00	0.000	0.18
13	0.10	0.01	0.01	0.01	0.00	0.00	0.00	0.000	0.13
14	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.11
15	0.09	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.10
16	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.09
17	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
18	0.06	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.07
19	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.07
20	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.09
21	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.09
22	0.07	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
23	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.05
24	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
25	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
26	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
27	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
28	0.16	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1504E-01

MOLES CO/MIN 0.6269E-02

MOLES CO2/MIN 0.2668E-05

MOLES H2O/MIN 0.4596E-03

SAMPLE#:

AVE. MOLWT= 53.09 USAGE RATIO= 1.536 RATE CO+H2 (MILLIMOLES/MIN)= 1.301

PERCENT OLEFINS= 61.576

H2= 2.80324 CO= 1.60778 H2O= 0.08291 CO2= 0.00344

MOLES H2/MIN	0.1312E-01
MOLES CO/MIN	0.7527E-02
MOLES CO2/MIN	0.1609E-04
MOLES H2O/MIN	0.3882E-03

BALANCES
C= 104.00 H= 102.85 O= 97.95 TOTWT= 100.89
PRESSURES (ATM ABS)
H2= 2.69457 CO= 1.67485 H2O= 0.07659 CO2= 0.00057

[illegible]

MOLES H2/MIN	0.1239E-01
MOLES CO/MIN	0.7699E-02
MOLES CO2/MIN	0.2637E-05
MOLES H2O/MIN	0.3521E-03

RUN: C7.46

DATE:

SAMPLE#:

TIME (MIN): 1365.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.82972 L/M IN= 0.292 FEED RATIO= 1.610

FT MOLES OUT/MIN= 0.1752E-03 OCTACOSANE MOLES OUT/MIN= 0.4609E-06

AVE.MOLWT= 42.25 USAGE RATIO= 1.894 RATE CO+H2 (MILLIMOLES/MIN)= 1.561

XH2= 12.72 XCO= 10.81 XCO+H2= 11.99

PERCENT OXYGENATES= 9.656

PERCENT METHANE= 18.008

PERCENT OLEFINS= 30.471

BALANCES

C= 99.21 H= 100.62 O= 98.96 TOTWT= 99.23

PRESSURES(ATM ABS)

H2= 4.54171 CO= 2.88259 H2O= 0.28142 CO2= 0.01026

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	47.55	0.00	0.00	0.00	0.00	11.33	0.00	0.000	58.88
2	4.96	1.38	0.00	0.00	0.00	0.61	0.00	0.000	6.94
3	2.51	6.94	0.00	0.00	0.00	0.21	0.00	0.000	9.65
4	2.13	4.17	0.54	0.03	0.00	0.05	0.00	0.000	6.92
5	1.74	2.57	0.37	0.16	0.00	0.02	0.00	0.000	4.86
6	1.30	1.55	0.31	0.24	0.00	0.00	0.00	0.000	3.40
7	1.01	0.89	0.23	0.12	0.00	0.00	0.00	0.000	2.25
8	0.66	0.48	0.16	0.10	0.00	0.00	0.00	0.000	1.41
9	0.55	0.28	0.14	0.10	0.00	0.00	0.00	0.000	1.07
10	0.50	0.14	0.06	0.08	0.00	0.00	0.00	0.000	0.77
11	0.49	0.10	0.05	0.06	0.00	0.00	0.00	0.000	0.69
12	0.47	0.06	0.03	0.07	0.00	0.00	0.00	0.000	0.63
13	0.37	0.03	0.02	0.05	0.00	0.00	0.00	0.000	0.47
14	0.30	0.02	0.02	0.05	0.00	0.00	0.00	0.000	0.38
15	0.24	0.01	0.01	0.04	0.00	0.00	0.00	0.000	0.30
16	0.19	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.24
17	0.16	0.01	0.00	0.02	0.00	0.00	0.00	0.000	0.19
18	0.13	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.15
19	0.12	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.14
20	0.14	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.15
21	0.14	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.16
22	0.12	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.13
23	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.09
24	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.06
25	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.04
26	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
27	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
28	0.26	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.7014E-02

MOLES CO/MIN 0.4452E-02

MOLES CO2/MIN 0.1585E-04

MOLES H2O/MIN 0.4346E-03

RUN: C7.47

DATE:

SAMPLE#:

TIME (MIN): 1380.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.83367 L/M IN= 0.292 FEED RATIO= 1.610

FT MOLES OUT/MIN= 0.1775E-03 OCTACOSANE MOLES OUT/MIN= 0.4059E-06

AVE.MDLWT= 45.74 USAGE RATIO= 2.232 RATE CO+H2 (MILLIMOLES/MIN)= 1.783

XH2= 15.32 XCO= 11.05 XCO+H2= 13.68

PERCENT OXYGENATES= 6.768

PERCENT METHANE= 17.141

PERCENT OLEFINS= 28.851

BALANCES

C= 100.10 H= 98.78 O= 98.65 TOTWT= 99.22

PRESSURES(ATM ABS)

H2= 4.48916 CO= 2.92890 H2O= 0.28780 CO2= 0.01042

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	49.00	0.00	0.00	0.00	0.00	8.27	0.00	0.000	57.27
2	5.25	1.45	0.00	0.00	0.00	0.59	0.00	0.000	7.29
3	2.65	3.75	0.00	0.00	0.00	0.21	0.00	0.000	6.62
4	2.19	4.25	0.57	0.03	0.00	0.05	0.00	0.000	7.10
5	1.91	2.73	0.39	0.22	0.00	0.02	0.00	0.000	5.27
6	1.41	1.67	0.34	0.18	0.00	0.00	0.00	0.000	3.59
7	1.22	1.02	0.23	0.13	0.00	0.00	0.00	0.000	2.65
8	1.14	0.66	0.26	0.11	0.00	0.00	0.00	0.000	2.16
9	1.01	0.41	0.23	0.11	0.00	0.00	0.00	0.000	1.76
10	0.88	0.25	0.18	0.07	0.00	0.00	0.00	0.000	1.37
11	0.79	0.15	0.07	0.07	0.00	0.00	0.00	0.000	1.08
12	0.65	0.08	0.05	0.06	0.00	0.00	0.00	0.000	0.84
13	0.51	0.05	0.03	0.06	0.00	0.00	0.00	0.000	0.65
14	0.42	0.03	0.02	0.05	0.00	0.00	0.00	0.000	0.51
15	0.33	0.02	0.01	0.04	0.00	0.00	0.00	0.000	0.40
16	0.25	0.01	0.01	0.04	0.00	0.00	0.00	0.000	0.30
17	0.19	0.01	0.00	0.03	0.00	0.00	0.00	0.000	0.22
18	0.14	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.16
19	0.13	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.14
20	0.14	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.15
21	0.14	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.15
22	0.11	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.12
23	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
24	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.05
25	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
26	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
27	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
28	0.23	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.6805E-02

MOLES CO/MIN 0.4440E-02

MOLES CO2/MIN 0.1579E-04

MOLES H2O/MIN 0.4363E-03

SAMPLE#:

AVE. MOLWT= 41.35 USAGE RATIO= 1.965 RATE CO+H2 (MILLIMOLES/MIN)= 2.158

PERCENT OLEFINS= 27.933

H2= 5.22601 CO= 2.33577 H2O= 0.18090 CO2= 0.00527

MOLES H2/MIN	0.1460E-01
MOLES CO/MIN	0.6527E-02
MOLES CO2/MIN	0.1474E-04
MOLES H2O/MIN	0.5055E-03

RUN: C7.49

DATE:

SAMPLE#:

TIME (MIN): 1560.0

TEMP(C)= 220.0 PRESS(ATM ABS)=: 7.81262 L/M IN= 0.522 FEED RATIO= 2.210

FT MOLES OUT/MIN= 0.1940E-03 OCTACOSANE MOLES OUT/MIN= 0.4495E-06

AVE.MOLWT= 40.97 USAGE RATIO= 1.535 RATE CO+H2 (MILLIMOLES/MIN)= 1.892

XH2= 7.14 XCO= 10.29 XCO+H2= 8.12

PERCENT OXYGENATES= 7.169

PERCENT METHANE= 20.830

PERCENT OLEFINS= 25.305

BALANCES

C= 97.18 H= 100.44 O= 97.51 TOTWT= 97.79

PRESSURES (ATM ABS)

H2= 5.25754 CO= 2.29842 H2O= 0.18219 CO2= 0.00580

MOLE BASIS PERCENT OF FT PRODUCTS

C#	PARA	AOLE	BOLE	ISOM	ACID	NALC	CRBO	AROM	TOT
1	53.34	0.00	0.00	0.00	0.00	8.10	0.00	0.000	61.44
2	4.78	1.47	0.00	0.00	0.00	0.52	0.00	0.000	6.77
3	2.52	6.25	0.00	0.00	0.00	0.13	0.00	0.000	8.89
4	3.50	2.12	0.38	0.03	0.00	0.03	0.00	0.000	6.07
5	2.34	1.74	0.28	0.14	0.00	0.01	0.00	0.000	4.51
6	1.27	1.50	0.23	0.15	0.00	0.00	0.00	0.000	3.15
7	0.85	0.82	0.14	0.10	0.00	0.00	0.00	0.000	1.92
8	0.60	0.52	0.11	0.11	0.00	0.00	0.00	0.000	1.34
9	0.53	0.29	0.09	0.08	0.00	0.00	0.00	0.000	1.00
10	0.46	0.13	0.08	0.05	0.00	0.00	0.00	0.000	0.72
11	0.50	0.10	0.04	0.05	0.00	0.00	0.00	0.000	0.69
12	0.47	0.06	0.03	0.05	0.00	0.00	0.00	0.000	0.61
13	0.40	0.03	0.02	0.05	0.00	0.00	0.00	0.000	0.50
14	0.37	0.02	0.01	0.05	0.00	0.00	0.00	0.000	0.45
15	0.34	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.39
16	0.29	0.01	0.01	0.03	0.00	0.00	0.00	0.000	0.34
17	0.23	0.00	0.00	0.03	0.00	0.00	0.00	0.000	0.27
18	0.18	0.00	0.00	0.02	0.00	0.00	0.00	0.000	0.20
19	0.14	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.16
20	0.13	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.14
21	0.12	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.13
22	0.11	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.11
23	0.08	0.00	0.00	0.01	0.00	0.00	0.00	0.000	0.08
24	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.05
25	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.03
26	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.02
27	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.01
28	0.23	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00

MOLES H2/MIN 0.1489E-01

MOLES CO/MIN 0.6509E-02

MOLES CO2/MIN 0.1643E-04

MOLES H2O/MIN 0.5159E-03

END

**DATE
FILMED**

3 / 22 / 93