0006440

1 OF 1

.00000025
.000000225
.0000002
.000000175

sample-3-380 °c

CONTINUOUS-MIXTURE KINETICS OF COAL THERMOLYSIS IN SUPERCRITICAL FLUID

Reported by Ming Wang

Continuous-Mixture Kinetics. Models of continuous-mixture kinetics take advantage of the complex, multicomponent nature of reaction systems, such as polymer, coal, and petroleum processes. One considers that the many components form a continuum of a certain property, e.g., molecular weight. Based on early work of Aris and Gavalas (1966), Syamlal and Wittmann (1990) provided guidelines for lumping a large number of reactions. Prasad et al. (1986) simulated the rate processes during the liquefaction of coal. The number of carbon atoms and the number of oxygen atoms served as continuous variables. Both primary and subsequent thermal cracking were considered. The product MWD was lumped into groups representing solubility fractions, e.g., preasphaltenes, asphaltenes, and oils. Every cracking reaction was supposed to yield two product species (two-fragment reaction), whose molecular weights summed to the molecular weight of the reactant molecule. The theory admitted no single product species, for example, produced by the rupture of a bond in a polymeric reactant molecule unattached at one end. The two-fragment reaction required the adoption of a stoichiometric term. First-order rate expressions were assumed, i.e., the rate was proportional to the concentration density of reactants. According to Prasad et al. (1986) several different forms for the dependence of the rate constant on molecular weight provided similar results, such that progressively slower reactions occurred as molecules became smaller. Lastly, the coal was assumed to be composed of large molecules of identical molecular weight.

The model we develop builds on these earlier approaches, and introduces the following features:

- new rate expressions that describe both single- and two-fragment reactions.
- representation of the initial composition of coal by molecular-weight distributions of chemical functional groups that can be leached from the coal matrix by bond rupture.
- application to a semi-batch reactor.

Coal Structure. The detailed structure of coal is complex, and varies with rank and source of the coal. Coal is commonly believed to have a polymeric molecular network composed of cross-linked monomeric units (Solomon et al., 1992; Green et al, 1982). The monomeric units are aromatic, multi-ring units with attached aliphatic or heterocyclic substituent groups (Darivakis et al., 1990). The linkages between monomeric units are methylene, ethylene, and ether bridges. Our data for the molecular weight distribution (MWD), as well as Syamlal and Wittmann (1985), show that multiple, overlapping peaks may appear in the product distribution. Oil shale extraction likewise yields multipeak MWDs (Tahiri et al., 1988). We consider that each peak represents one group of reactive monomeric units in the coal network. Following Darivakis et al. (1990), we assume that the distribution of each group of reactive monomeric units is described by a gamma distribution.

$$c_{oi}(x) = m_{oi} y^{(\alpha_i-1)} \exp(-y) / [\beta_i \Gamma(\alpha_i)] \quad (1)$$

with

$$y = \frac{x - x_{oi}}{\beta_i} \quad (2)$$

Since the gamma distribution is defined for $y > 0$, we have $c_{oi}(x < x_{oi}) = 0$.

Mechanism. The thermolytic depolymerization of coal is considered to occur by chemical bonds rupturing to release product species. The rate of depolymerization and release of solubilized products will depend on the rate of bond rupture, which allows the monomeric units to migrate away from the coal particle. Darivakis et al. (1990) applied probability theory to postulate a coal depolymerization process based on rupture of network bonds. The study, which focused on the MWD of pyrolysis products, did not consider rate expressions for the coal reactions. The gamma distribution, a limiting form of the binomial distribution, successfully described the experimental data. As rate processes were not considered, the theory cannot predict time evolution of the MWD.

The present rate theory of coal depolymerization expands upon the concepts presented by Darivakis et al. (1990). We likewise hypothesize that bond rupture within

the coal network produces product species that are carried away from the reaction zone before secondary reactions can occur. Two types of reactions are considered, one producing a single product species and the other producing two product species. The thermolytic depolymerization of coal is considered to occur by chemical bonds rupturing to release product species. Since fewer bonds are ruptured simultaneously, the single-fragment process is expected to dominate over the two-fragment process. The above two types of reactions are considered in the continuous-mixture kinetics proposed below. The kinetics may be visualized as:

In the above mechanism, each group is a mixture of reactive components, which has different average molecular weight and reactivity. As mentioned before, each group can be described by a gamma distribution. We consider that continuous distributions of molecular weight, x , represent the coal and its extraction products as the coal is depolymerized or cracked into smaller molecules. The time-dependent concentration densities of a particular group of reactive component species and product species, denoted by the subscript i , are $c_i(x,t)$ and $p_i(x,t)$. We define rate constants for one- and two-fragment reactions as, k_i and $k_{ic}(x)$, respectively.

Group 1 (Single-Fragment Reaction)

Only single-fragment reaction occurs for this group of stable two- and three-ring aromatics. We consider that continuous distributions of molecular weight, x , represent the coal and its extraction products as the coal is depolymerized or cracked into smaller product species. The time-dependent concentration densities of a particular group of reactant species and product species, denoted by the subscript i , are $c_i(x,t)$ and $p_i(x,t)$,

where $i = 1, 2, 3$. We define rate constants k_i for single-fragment reactions. Then the first-order rate of reaction of coal is

$$\frac{\partial c_i(x,t)}{\partial t} = -k_i c_i(x,t) \quad (3)$$

with initial condition

$$c_i(x,t=0) = c_{oi}(x) \quad (4)$$

The solution is

$$c_i(x,t) = c_{oi} \exp[-k_i t] \quad (5)$$

Consider that the concentration density of reaction product species originating from $c_{oi}(x)$ in the differential reactor is $p_i(x,t)$. The average residence time based on the reactor volume of the fixed bed of coal is τ , and the bed void fraction is ϵ . The mass balance equation for the gradientless, continuous-flow reactor is written

$$\epsilon \tau \frac{\partial p_i(x,t)}{\partial t} + p_i(x,t) = k_i c_i(x,t) / Q \quad (6)$$

where Q is the volumetric flow rate. The initial condition is

$$p_i(x,t=0) = 0 \quad (7)$$

For our experimental condition, τ is very small and the accumulation term in Eq.6 is negligible relative to the other terms. Thus Eq.6 is simplified to

$$p_i(x,t) = k_i c_i(x,t) / Q \quad (8)$$

Combining Eq.5 and Eq.8 leads to the following solution

$$q_i(x,t) = k_i c_{oi}(x) \exp(-k_i t) / Q \quad (9)$$

Groups 2 and 3

For groups 2 and 3, composed of four-ring and larger aromatics, two types of reactions occur in the coal particle, single- and two-fragment reactions. Following the notation of Aris and Gavalas (1966) we define $A(x)$ to be a continuous distribution of coal products. The two-fragment reaction can be written as:

Denote the concentration density of $A(x)$ by $c_i(x,t)$. Let the rate kernel for cracking of $A(x)$ be $k_{ic}(x)$ and define $v(x,x')$ as the fraction of $A(x')$ that cracks to $A(x)$. All cracking reactions are assumed to be first-order with respect to reacting species. Reaction 10 describes the formation of product species $A(x)$ as well as $A(x'-x)$. The symmetry implies that

$$v(x,x') = v(x'-x,x') \quad (11)$$

If the product species of cracking reaction are distributed in the molecular weight range of x_{01} to x' , the fact that $v(x,x')$ is a fraction requires that

$$\int_{x_{01}}^{x'} v(x,x') dx = 1 \quad (12)$$

According to our experimental results for extract MWDs, the molecular weight x_{01} , the lower limit of extract molecular weight, is 115.

A possible form of the stoichiometric distribution was proposed originally by Syamlal et al. (1986),

$$v(x,x') = Bx(x'-x) \quad (13)$$

where B is fixed by constraint Eqs. 11 and 12; thus

$$B = \frac{6}{x'^3 - x_{01}^2(3x - 2x_{01})} \quad (14)$$

Then the stoichiometric distribution is

$$v(x,x') = \frac{6x(x'-x)}{x^3 - x_{01}^2(3x - 2x_{01})} \quad (15)$$

which is different from that of Syamlal et al. (1986), who took $x_{01}=0$.

The rate kernel used in this model is chosen to increase linearly with MW,

$$k_{ic}(x) = \kappa_{ic} \frac{x - x_{01}}{\beta_1} \quad (16)$$

so that $k_{ic}(x < x_{01}) = 0$.

The rate equation in the coal particle can be written as:

$$\frac{\partial c_i(x,t)}{\partial t} = -(k_i + k_{ic}(x))c_i(x,t) \quad (17)$$

with initial condition

$$c_i(x,t=0) = c_{oi}(x) \quad (18)$$

The rate of generation of product species $A(x)$ is

$$r(x,t) = \int_x^\infty k_{ic}(x')c_i(x',t)v(x,x')dx' + k_i c_i(x,t) \quad (19)$$

On the right side of Eq.19, the first term accounts for the rate of production by two-fragment reactions, and the second term accounts for the rate of production by single-fragment reactions. The mass balance for the flow reactor is

$$\epsilon \tau \frac{\partial p_i(x,t)}{\partial t} + p_i(x,t) = \frac{1}{Q} \left[\int_x^\infty k_{ic}(x')c_i(x',t)v(x,x')dx' + k_i c_i(x,t) \right] \quad (20)$$

where the initial condition is

$$p_i(x,t=0) = 0 \quad (21)$$

The accumulation term can be neglected in our reactor. Thus Eq.20 is simplified as

$$p_i(x,t) = \frac{1}{Q} \left[\int_x^\infty k_{ic}(x') c_i(x',t) v(x,x') dx' + k_{ii} c_i(x,t) \right] \quad (22)$$

Eqs. 17 and 18 can be solved and the solution is

$$c_i(x,t) = c_{oi}(x) \exp[-(k_i + k_{ic}(x))t] \quad (23)$$

The lumped rate expressions for the extractable compound and the extract product concentration densities are also defined as

$$C_i(t) = \int_0^\infty c_i(x,t) dx \quad (24)$$

$$P_i(t) = \int_0^\infty p_i(x,t) dx \quad (25)$$

Now combining Eqs. 15,16,22, and 23 leads to the concentration density $p_i(x,t)$ for components 2 and 3. The total concentration density of product species is the summation of $p_1(x,t)$, $p_2(x,t)$, and $p_3(x,t)$. Thus,

$$p(x,t) = p_1(x,t) + p_2(x,t) + p_3(x,t) \quad (27)$$

The simulations were performed with TK Solver, which is a software package made by Universal Technical Systems, Inc. (1992). The results for 653 K and 673 K are shown in Figures attached . The fitting parameters are listed in Tables 1 and 2.

References

Aris, R., and G. R. Gavalas, "On the Theory of Reactions in Continuous Mixtures," *Phil. Trans. R. Soc. London*, **A260**, 351 (1966).

- Darivakis, G. S., W. A. Peters, and J. B. Howard, "Rationalization for the Molecular Weight Distributions of Coal Pyrolysis Liquids," AIChE J. **36**, 1189(1990).
- Green, T., J. Kovac, D. Brenner, and J. W. Larsen, "The Macromolecular Structure of Coals," Coal Structure, R. A. Meyers, ed., Academic Press, 199(1982).
- Prasad, G. N., J. B. Agnew, and T. Sridhar, "Modeling of Coal Liquefaction Kinetics Based on Reactions in Continuous Mixtures. Part I: Theory," AIChE J. **32**, 1277 (1986)
- Solomon, P. R., M. A. Serio, and E. M. Suuberg, "Coal Pyrolysis: Experiments, Kinetics Rates and Mechanism," Prog. Energy Combust. Sci. **18**, 132(1992).
- Syamlal, M., and C. V. Wittmann, "Continuous Reaction Mixture Model for Coal Liquefaction Kinetics," Ind. Eng. Chem. Fundam. **24**, 82 (1985).
- Tahiri, M., C. M. Sliepcevich, and R. G. Mallinson, "Kinetics and Mechanism of Moroccan Oil Shale Solubilization in Toluene," Energy & Fuels **2**, 93 (1988).
- Universal Technical Systems, Inc., "TK Solver, Introduction Manual", (1992).

Table 1. Parameter Values for the Continuous-Mixture Model

Temperature (K)	613	633	653	673
$k_i \text{ s}^{-1}$	1.3×10^{-4}	2.2×10^{-4}	3.0×10^{-4}	3.7×10^{-4}
α	2	2	2	2
β_1	20	20	20	20
β_2	62	62	60	55
β_3	120	120	115	110
x_{01}	115	115	115	115
x_{02}	170	160	170	170
x_{03}	270	277	275	280
m_{01}	0.0033	0.0080	0.010	0.013
m_{02}	0.0257	0.058	0.061	0.077
m_{03}	0.037	0.034	0.039	0.050
c_0	0.066	0.100	0.11	0.14

where $c_0 = m_{01} + m_{02} + m_{03}$

Table 2. Rate constants at different temperatures

Temperature (K)	613	633	653	673
$k_1 \text{ s}^{-1}$	1.3×10^{-4}	2.2×10^{-4}	3.0×10^{-4}	3.7×10^{-4}
$k_2 \text{ s}^{-1}$	1.3×10^{-4}	2.2×10^{-4}	3.0×10^{-4}	3.7×10^{-4}
$k_{2c} \text{ s}^{-1}$	$*3 \times 10^{-7}$	$*1.7 \times 10^{-6}$	5.3×10^{-6}	1.6×10^{-5}
$k_3 \text{ s}^{-1}$	1.3×10^{-4}	2.2×10^{-4}	3.0×10^{-4}	3.7×10^{-4}
$k_{3c} \text{ s}^{-1}$	$*5.3 \times 10^{-7}$	$*1.6 \times 10^{-6}$	4.5×10^{-6}	1.2×10^{-5}

* estimated from the values of 653K and 673K

Figure 1. The initial concentrations vs. temperature

11/7/92

11/7/92

sample-2-380 °C

sample-3-380 °C

11/7/92

sample-4-380 °C

11/18/74

sample-5-380 °C

11/6/92

sample-1-400 °C

11/6/92

sample-2-400 °C

11/6/92

sample-3-400 °C

11/6/72

sample-4-400°C

11/6/92

sample-5-400°C

END

DATE
FILMED
319193