CONF 930160--6

COMBINED TRU-Sr EXTRACTION/RECOVERY PROCESS

RECEIVED BY
MAIL ROOM

E. PHILIP HORWITZ
Chemistry Division
(708) 252-3653

and
RALPH A. LEONARD
Chemical Technology Division
(708) 252-3229
Argonne National Laboratory
Argonne, IL 60439-4831

ANL/CHM/CP--78502

DE93 006415

Objective

The purpose of this task is to further develop and test a new solvent extraction/recover process that is designed to extract and selectively partition U, TRUs (Np, Pu, Am), ⁹⁰Sr and ⁹⁹Tc from dissolved sludge waste obtained from Hanford storage tanks. The objectives of the process are to minimize the amount of waste that must be vitrified and to reduce the cost of chemical pretreatment. The new process is a combination of TRUEX and the recently developed SREX (strontium extraction) process.

Process Approach and Solvent Formulation

Our earlier studies have shown the feasibility of combining a transuranic (TRU) selective extractant, octyl(phenyl)-N,N-diisobutylcarbamoylmethylphosphine oxide (CMPO), and a strontium selective extractant, 4, 4' (5') bis-tertiarybutylcyclohexano-18-crown-6 (DtBuCH18C6 or CE), into a single process solvent formulation with the aid of a phase modifier, tri-n-butyl phosphate (TBP). Both CMPO and DtBuCH18C6 (CE) are neutral extractants. These earlier studies showed that when dissolved into TBP, CMPO and CE have the same efficiency for Am and Sr, respectively (as measured by the distribution ratio, D_{Am} and D_{Sr}), whether present individually or in a mixture.

However, major problem that frequently arises when extractants are mixed is the formation of a second heavy organic phase (i.e., third phase formation) when the solvent is loaded with the metal ions. Both CMPO and DtBuCH18C6 require the presence of a phase modifier, e.g., TBP, if a hydrocarbon is used as the diluent. Table 1 shows the influence of carbon chain length on the loading of uranyl nitrate in a 0.2 M CMPO - 0.2 M DtBuCH18C6 solution. The data in Table 1 show the maximum concentration of uranyl nitrate that can be extracted into the organic solvent mixture without the formation of a third phase. Uranyl nitrate was chosen to induce third phase formation because uranium, together with bismuth, will be the major extractable constituent in the sludge from the Hanford storage tanks. (NorparTM-12 is a normal paraffinic hydrocarbon whereas IsoparTM-L and -M are isoparaffinic hydrocarbons.)

TABLE 1
Maximum loading of process solvent
(process solvent 0.2 M CMPO - 0.2 M DtBuCH18C6)
(aqueous phase 3 M HNO₃ - uranyl nitrate, 25 °C)

Diluent	No. of Carbons	Flash Point	[U] _{org} , M**
1.2 M TBP - Dodecane	12.0	71	0.021
1.2 M TBP - Norpar 12	11.5	69	0.038
1.2 M TBP - Isopar L	12.0	61	0.140
1.2 M DA[AP] - Isopar L	12.0	61	» 0.20
1.2 M TBP - Isopar M	13.5	80	0.029
1.2 M DA[AP] - Isopar M	13.5	80	0.20

** Maximum concentration of uranium in the process solvent without third phase formation

* Work supported by the U. S. Department of Energy under contract number W-31-109-ENG-38.

The submitted manuscript has been authored by a contractor of the U. S. Government under contract No. W-31-109-ENG-38. Accordingly, the U. S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for U. S. Government purposes.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

The data show that to minimize third phase formation while simultaneously utilizing a diluent with a reasonably high flash point (for safety), isoparaffinic hydrocarbons are more effective than normal paraffinic hydrocarbons. However, 1.2 M TBP in Isopar™-M forms a third phase above 0.029 M [U]_{org}, which significantly reduces the efficiency of the extraction stages because a high ratio of organic to aqueous phase (O/A) will be required to maintain [U]_{org} below 0.03 M concentration. As can be seen in Table 1, substitution of diamyl amylphosphonate, DA[AP], for TBP significantly reduces third phase formation in the CMPO-DtBuCH18C6 system.

Figure 1 shows the influence of aqueous HNO₃ concentration on the extraction of Sr, Tc, and Am as measured by their distribution ratios using the DtBuCH18C6-CMPO-DA[AP]-Isopar™-M system. The distribution ratios of Sr, Tc, and Am using the same formulation in Isopar™-L are similar. (These mixed extractant systems in either Isopar M or L are referred to hereafter as the combined process solvent.) The measurements were made at room temperature (24 °C). Strontium is efficiently extracted above 2 M HNO₃ and Am, as is characteristic of TRUEX chemistry, is efficiently extracted over a wide range (0.5 to 6 M) of HNO₃ concentrations. On the other hand, technetium is more effectively extracted at < 1 M HNO₃, but D_{Tc} is still high enough in 2 to 3 M HNO₃, which is the most likely concentration of acid in the dissolved sludge waste, to achieve the necessary decontamination of Tc. (Most of the Tc is found in the alkaline supernatant in the waste tanks and not in the sludge.) The influence of macro concentrations of U and Bi on D_{Sr}, Tc, Am is of equal importance to the data in Figure 1. Figure 2 shows that macro quantities of U and Bi are very similar in their influence on the extraction of Sr, Tc, and Am. As expected, D_{Sr} is not significantly affected by either Bi or U because neither is extracted to any degree by DtBuCH18C6. Americium extractability is decreased by macro concentrations of U and Bi due to their extractability by CMPO. However, the diminution in D_{Am} with increasing concentration of U and Bi is much less than expected based on UO₂(NO₃)₂•2CMPO and Bi(NO₃)₃•3CMPO stoichiometries. The explanation lies in the fact that DA[AP] probably replaces one of the CMPO molecules coordinated to U and Bi, resulting in much less rapid consumption of CMPO. Technetium extraction is increased by increasing concentrations of U and Bi due to complexation between TcO₄¹⁻ and UO₂²⁺ and Bi³⁺.

An important feature of the combined TRU-Sr extraction process is the partitioning of Sr and TRUs from U and Tc. This selective partitioning can be readily achieved using a new stripping agent, tetrahydrofuran-2,3,4,5-tetracarboxylic acid, abbreviated THFTCA. Table 2 shows the D_s for Am, Pu(IV), and U(VI) as a function of HNO₃ concentration in the presence of 0.5 M THFTCA. Data for Sr is not shown because D_{Sr} is sufficiently low below 0.2 M HNO₃ that no complexation by THFTCA is required. After stripping Sr and TRUs, U and Tc are readily stripped from the combined process solvent using 0.25 M Na₂CO₃.

Fig. 1 Distribution ratios of Sr, Am, and Tc vs. HNO₃ concentration for combined process solvent*

Fig. 2 The influence of loading on the extraction of Sr, Am, and Tc using combined process solvent*
Aqueous phase = 3.0 M HNO₃

(* 0.2 M DtBuCH18C6 - 0.2 M CMPO - 1.2 M DA[AP] in Isopar™-L or M)

TABLE 2
Influence of acidity on the distribution ratios of
Am(III), Pu(IV), and U(VI) with 0.5 M THFTCA*

HNO ₃ M	D		
	Am(III)	Pu(IV)	U(VI)
0.0	3.0×10^{-3}	4.5×10^{-2}	8.9
0.025	4.2×10^{-3}	5.1×10^{-2}	9.2
0.05	6.5×10^{-3}	5.9×10^{-2}	9.5
0.10	1.2×10^{-2}	7.6×10^{-2}	1.2×10^1
0.20	4.7×10^{-2}	1.0×10^{-1}	2.0×10^1

* Organic phase was the combined process solvent

Flowsheet for Combined TRUEX-SREX Process

Figure 3 shows the proposed flowsheet for processing dissolved sludge waste using the new combined process solvent and the new stripping agent, THFTCA. The feed will contain significant concentrations of oxalic acid (e.g., 0.2 M) to aid in dissolution of the sludge and to act as a hold-back complexant for Fe(III) and Zr (IV). Some reducing agent is also needed in the feed to ensure that Np(V) is reduced to Np(IV). The first scrub section (stages 9 and 10) uses Al³⁺ to keep oxalate and fluoride out of the strip. A second scrub section (stages 11 to 13) reduces the HNO₃ in the process solvent entering the strip so that the THFTCA will be an effective stripping agent. However, HNO₃ in the process solvent should not be lowered to such a level that Sr is significantly removed in the scrub section. Stages 14 to 21 consists of a combination strip-scrub section in order to backextract Sr and the TRUs and minimize the THFTCA entering the carbonate wash section. (The distribution ratio of THFTCA is 0.6). There are only two product streams, namely, Sr and TRUs (Am, Pu, Np)

Fig. 3 Flowsheet for extraction of Sr, Tc, TRU, and U from dissolved high-level sludge waste using the combined TRUEX-SREX Extraction/Recovery Process, parentheses designate relative flows.

(* 0.2 M DtBuCH18C6 - 0.2 M CMPO - 1.2 M DA[AP] - Isopar™-L or M)

and U and Tc. The lanthanide fission products and any Bi will follow the TRUs. Figures 4 and 5 show the calculated concentration profiles of Sr and Am throughout the extraction, scrub, and stripping stages using the Generic TRUEX Model. The decontamination factors of $>10^4$, >20 , and $>10^4$ achieved for ^{90}Sr , ^{99}Tc , and ^{241}Am , respectively, are well in excess of those required for the raffinate to meet the specifications for Class A low-level waste, with respect to these three nuclides.

Process Benefits

A combined TRU-Sr process has several advantages over individual processes carried out in tandem. For example, the combined process would require less equipment and therefore less space and would require the handling of only one process stream. However, the more complex process solvent formulation is a disadvantage. Nevertheless, the increasing demands for removal of a larger number of radionuclides in a single process can be achieved by combining different extractants of the same type.

Fig. 4 Calculated concentration profiles for Sr in combined TRUEX-SREX Flowsheet shown in Fig 3.

Fig. 5 Calculated concentration profiles for Am in combined TRUEX-SREX Flowsheet shown in Fig 3.

Acknowledgements

Co-workers in this program are: Mark L. Dietz and Herbert Diamond of the Chemistry Division, ANL, and Robin D. Rogers, Department of Chemistry, Northern Illinois University, DeKalb, Illinois.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

DATE
FILMED
3/19/93