Quarterly Report 3/1/92

DE93 007474

TITLE: Novel Technique for Coal Pyrolysis and Hydrogenation Product Analysis

PI: Lisa D. Pfefferle, Associate Professor

RESEARCH ASSOCIATE: German Bermudez

STUDENT(S) AND THE DEGREE FOR WHICH THEY ARE REGISTERED:
James Boyle, Ph.D.

INSTITUTION/ORGANIZATION: Yale University, Department of Chemical Engineering, P.O. Box 2159 Yale Station, New Haven, CT 06520.
Phone number of PI: (203) 432-2460

GRANT NO.: DE-FG22-89PC89767

OBJECTIVE: The overall objective of this study is to establish vacuum ultraviolet photoionization-MS and VUV pulsed EI-MS as useful tools for a simpler and more accurate direct mass spectrometric measurement of a broad range of hydrocarbon compounds in complex mixtures for ultimate application to the study of the kinetics of coal hydrogenation and pyrolysis processes. The VUV-MS technique allows ionization of a broad range of species with minimal fragmentation. Many compounds of interest can be detected with the initial wavelength used (118 nm), but additional compound selectivity is achievable by tuning the wavelength of the photo-ionization source in the VUV. Other techniques for discrimination of molecular isomers are also being investigated to allow for compound selectivity.

WORK DONE AND CONCLUSIONS: This report covers the second to the last quarter of the last year of the three-year grant period. In the final project year, we are focusing on the pyrolysis and oxidative pyrolysis of benzene and benzene acetylene mixtures (along with the pyrolysis of other C5-C12 compounds) in order to develop the VUV-MS technique for compounds more representative of those in coal pyrolysis applications. In the first quarters of the current project year, we have carried out the pyrolysis of mixtures of these compounds without oxygen in a microflow reactor. The acetylene/benzene mixtures were used to gain a better understanding of the mechanisms of molecular growth in such systems specifically to look at the kinetics of aryl-aryl reactions as opposed to small molecule addition to phenyl radicals. Sarofim and coworkers at MIT have recently demonstrated the importance of these reactions in coal processing environments. In the past, the growth mechanism for the formation of mid-sized PAH has been postulated to involve primarily successive acetylene additions to phenyl-type radicals, our work confirms this as an important mechanism especially for smaller PAH but also investigates conditions where biaryl formation can play an important role in higher hydrocarbon formation. Two different temperature regimes are considered: below 1000 K, where reactivity is dominated by molecular processes, and above 1000 K, where radical chain mechanisms become the dominant pathway. These experiments were carried out at a large range of total pressures and with different diluents.

Figures 1a and b show mass spectra for the pyrolysis of benzene^(a) and a benzene acetylene mixture^(b) at various temperatures from 1100 - 1300K, a total pressure of 40 Torr and 20 ms mean residence time. In these experiments Ar is the diluent. For the

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

acetylene/benzene mixture for these conditions, the phenylacetylene/biphenyl ratio remains approximately constant over the entire temperature range. At the highest temperature, mass 178 (anthracene and biphenylacetylene) production becomes significant. For the pure benzene case (shown at 0.5 times the intensity of the mixture case) the total benzene conversion is about the same as for the mixture case at equivalent conditions but the biphenyl product is the dominant higher hydrocarbon species at about twice the selectivity of the mixture case. This indicates that for the conditions shown the acetylene does not accelerate the production of phenyl radicals from benzene but simply provides an alternate pathway for their consumption. Also mass 168 was detected as a minor high mass species which was not observed in significant quantities in the mixture case.

A quadrupole mass analyzer with electron ionization was set up in the ionization chamber of the VUV-MS to allow the analysis of molecular species whose ionization potentials are above our present VUV capabilities and to provide another direct measurement to quantify the VUV-MS data.

SIGNIFICANCE TO FOSSIL ENERGY PROGRAM: This research is innovative, offering a relatively new technique with significantly improved performance for the mass detection of $> C_1$ hydrocarbons in mixtures. This technique would facilitate the scientific investigation of coal upgrading processes such as pyrolysis and hydrogenation by allowing accurate direct analysis of both stable and intermediate reaction products. The on-line, non-destructive nature of the VUV-MS technique facilitates data collection and analysis, allowing more experiments to be run with greater analysis accuracy, greatly improving the database and allowing more confident prediction of reaction pathways.

PLANS FOR THE COMING PERIOD:

In the final project quarter we plan to carry out the benzene pyrolysis experiments in the presence of oxygen. In a coal pyrolysis environment some oxygen will be present. In addition we plan to summarize our calibration strategies and theoretical bases to provide a rationale approach for others who will use the technique for hydrocarbon analyses in complex mixtures. We will also suggest changes to the instrument design to make it a more general tool capable of isomeric discrimination and to facilitate quantitative analysis.

HIGHLIGHT ACCOMPLISHMENTS

1. Pyrolysis of mixtures of acetylene and benzene have been carried out and the mechanisms for higher hydrocarbon formation elucidated. The presence of C_5H_5 radical has been semi-quantitatively determined showing the power of this technique for quantifying mechanistically important radical species.
2. Work is continuing on the development of theoretically based tools for determining relative detection efficiency.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Figure 1a:

Benzene Pyrolysis

In Ar gas. Total pressure 52 torr. $\tau = 20$ msec

Figure 1b:

Acetylene/Benzene Pyrolysis

In Ar gas. Total pressure 40 Torr. $t = 20$ msec

END

**DATE
FILMED**

3 / 15 / 93