Final Technical Report on the Project:
"Laser Acceleration and Nonlinear Beam Dynamics"

DOE Grant FDP DOE DE-FG03-90ER40565

Claudio Pellegrini

DOE/ER/40565--1

DE92 018703

UCLA Physics Department
405 Hilgard Avenue
Los Angeles, CA 90024-1547

1. Introduction

This research contract covers the period April 1990, September 1991. The work to be done under the contract was theoretical research in the areas of nonlinear beam dynamics and laser acceleration. In this final report we will discuss the motivation for this work and the results obtained.

The exploration of the structure of matter at smaller and smaller distances follows two paths: the first is the construction of higher energy accelerators, like SSC, LEP and the future linear colliders for electron and positrons. These very high energy colliders will permit a direct investigation of the structure of matters at extremely short distances, directly at the scale of elementary particles; they will also allow to produce very massive particles, like the Higgs boson. The second path is the study, at lower energies, of the violation of symmetry principles, or detailed tests of the validity of the Standard Model. Examples of this second approach are the study of CP violation in the K-meson or B-meson systems, and the related proposal for a K-factory, a B-factory or a Phi-factory. In the second case the most important parameter is the luminosity of the collider, which has to be increased much above the present state of the art, by one or two order of magnitudes.

There are particular particle beam physics problems which are encountered for accelerators designed to advance the frontiers on either one of these two paths. For a very large accelerator, like the SSC, the issues are mainly, but not uniquely, related to questions of dynamic aperture, single particle nonlinear dynamics, and machine control and reliability. For systems like the B- or Phi-factory, needing an extremely large luminosity, we must also be concerned about high intensity effects, collective instabilities, beam-beam interaction, design of low beta insertions, and the technology of RF and vacuum systems. For linear colliders the main problems are the production

and acceleration of beams with extremely large six-dimensional phase space density, and the development of high gradient linear accelerators to contain the dimension and the cost of the system within reasonable limits.

The developments of these new systems, or the continuing improvements of existing ones with regard to higher luminosities and energies, requires a better understanding of the physics of particle beams, the complex phenomena introduced by the interactions of beams between themselves and with their environment, as well as the nonlinear dynamics of particle beams.

During the period 1990-91 we have been studying two problems relevant to these development. The first is how to increase the luminosity in a B- or Phi-factory. We have studied the scaling law of luminosity with beam and collider parameters [1]. The most commonly followed approach is to increase the luminosity by increasing the stored electron and positron beam current. The disadvantage of this strategy is that it leads to problems with multibunch instabilities, RF systems, and vacuum systems.

Our approach is to study the possibility of obtaining a large luminosity by increasing the beam density at the interaction point; this requires a stronger focusing system and a short bunch length. The strong focusing needed to reduce the transverse spot size by a factor of ten or larger is within the present capability. The short bunch length can be obtained by designing the storage ring as a "Quasi Isochronous Ring", i.e. a ring with a small momentum compaction, in which the particle revolution frequency is nearly independent of the particle energy. In this situation the beam dynamics becomes essentially nonlinear and it is important to study the stability of single particles under these circumstances. The results obtained will be discussed in section 2, and can be partly found in reference 1 to 4.

The second problem that we have studied is the production of high brightness electron beams using a photoinjector. This is the most promising approach to obtain the beam densities needed in a linear collider, at least for the electron case. Although positrons might still need a damping ring, there is already considerable saving in using a photoinjector to produce the electron beam.

2. Quasi Isochronous Ring

The idea of a Quasi Isochronous Ring (QIR) as a way to high luminosity electron-positron collider arose during the Blois workshop on B-factories [1]. After an initial study showed this to be an interesting alternative design for a high luminosity collider, we started a more systematic study of the system. Since the longitudinal linear focusing force is reduced when the momentum compaction is made small, the nonlinear terms become very important in a QIR. In reality when discussing a ring with a small momentum compaction one must be careful to realize that the momentum compaction is a nonlinear function of the energy deviation and of the transverse oscillation amplitude. To reduce the bunch length one has to make the linear term of

the momentum compaction near to zero, i.e. about hundred times smaller than present values. The higher order nonlinear term can then become large compared to the linear term. In this situation the stability region for synchrotron oscillation can be totally different from that of a "standard" storage ring.

The stable space phase area in a normal storage ring is determined by the RF characteristics and the linear term of the momentum compaction. The work done under this contract, reference 2 and 3, shows that when the linear term is made small one can reach a situation where the stable phase space area is determined by the ratio of the linear and quadratic term in the momentum compaction expansion in power of the energy deviation. This new stability condition has been named the alpha-bucket, as opposed to the RF bucket.

To have a stable phase space area large enough to provide a long beam lifetime one has to establish a strict control over the nonlinear terms of the momentum compaction. As shown in reference 2 and 3, this can be partly accomplished by using non linear magnetic lenses, like sextupoles.

An example of QIR has been developed in full for a Phi-factory [4]. In addition to the analytical studies described above we have also applied a symplectic tracking program to the study of the nonlinear beam dynamics, essentially confirming the results of the analytical theory.

IN addition to a continuation of our theoretical studies, we are now considering the possibility of an experimental test of this concept on an existing storage ring. A positive result would be interesting not only for its applications to electron-positron colliders, but also for synchrotron radiation sources, where it would provide the novel possibility of producing picosecond long radiation pulses. These would be very interesting in applications like the study of reaction dynamics, where a short, picosecond range, pulse duration is critical.

3. High Brightness Electron Beams

In the area of laser acceleration we have continued the study of an IFEL, and have also studied the production of high brightness electron beams, using high field photoinjectors. During this period we have completed the design of a photoinjector[5], to be build at UCLA, and based on a similar system developed recently at Brookhaven. The main characteristics expected for the beam are given in Table 1.

Table 1: Expected characteristics from the UCLA Photoinjector

Beam Energy, MeV	20
Normalized Transverse emittance, rms, mm mrad	5
Peak Current, A	200
Relative energy spread, rms	0.2%
Pulse duration, rms, ps	1.6

The photoinjector has been designed to produce a larger peak current than the Brookhaven system. This is achieved by using solenoidal focusing instead of quadrupolar focusing at the gun exit. The solenoidal field extends also inside the gun, modifying the electron trajectory there. The field on the cathode is kept zero using a back up solenoid symmetrically positioned respect to the cathode plane.

The beam characteristics have been evaluated with numerical simulations using Parmela. More recently we have been starting to use also Mask.

We have completed a detailed engineering design of the system, and we have started the process of acquisition and fabrication. We have also prepared the laboratory space for the installation of the system.

The goal of this program is to study the physics of production of high brightness beams, the associated instrumentation, and the technological problems associated with the operation of such a system. We have also started the study of the use of this electron source for experimental work in the area of beam plasma interaction, beam focusing and wakefield acceleration.

References

1. C. Pellegrini and D. S. Robin, Isochronous Storage Rings and High Luminosity Electron-Positron Colliders, in Proc. of the Workshop on CP Violation and Beauty Factories and Related Issues in Physics, D. B. Cline and A. Fridman eds., Annals of the New York Acad. of Sciences, Vol. 619, 1991.
2. C. Pellegrini and D.S.Robin, Nuclear Instr. and Methods, A301, 27-36, 1991.

3. C. Pellegrini, D. Robin and M. Cornacchia, Conceptual Design of a High Luminosity 510 MeV Collider, in Proc. IEEE Particle Accelerator Conference, p. 2853, 1991.
4. D. S. Robin, Quasi Isochronous Storage Rings Colliders, Ph. D. Thesis, UCLA 1991
5. C. Pellegrini et al., Photocathode driven linac at UCLA for FEL and Plasma Wakefield acceleration experiments, in Proc. IEEE Particle Accelerator Conference, p. 2967, 1991.

**DATE
FILMED**
8/27/92