DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DEVELOPMENT AND DEMONSTRATION OF A TELEOPERATED MODULAR ROBOT SYSTEM

Progress Reports

January 1992 - December 1992

Sabri Tosunoglu and Delbert Tesar
Department of Mechanical Engineering
University of Texas at Austin
Austin, TX 78712

December 18, 1992

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY
UNDER GRANT NUMBER DE-FG02-86NE37966

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DOE/NE/37966--T1
DE9-005721

**DOE/NE ROBOTICS PROGRAM
BI-MONTHLY PROGRESS REPORT
UNIVERSITY OF TEXAS AT AUSTIN**

Sabri Tosunoglu and Delbert Tesar

January 21, 1992

Significant Accomplishments

Report on Real-Time Control Software

The recent work carried out on the development of real-time controllers has been gathered in a report. This work concentrates on the development of efficient algorithms and real-time advanced control software for robotic manipulators. In his report, real-time software is developed for three separate advanced controllers.

The first of the three control software developments was a computed-torque controller which was implemented on the CESARm Manipulator at Oak Ridge National Laboratory. This example of an actual implementation proves that a computed-torque controller can be implemented on a highly complex seven degree-of-freedom manipulator in real-time. However, there were several problems associated with its implementation, including a compliant drive train, a slow loop rate, and the presence of unmodelled dynamics. Nonetheless, the application was shown to be feasible. With relatively minor changes, and more importantly, more time to properly tune the controller parameters, improved results may be obtained. Comparisons are also made to simulation results, some of which were not close to resembling the experimental results. This indicates that the simulations may be subject to error in predicting a controller's performance.

The second software development was a robust controller for compliant manipulators. A version for a general, six degree-of-freedom manipulator with compliant joints was implemented on an Analogic AP-500 array processor in order to achieve real-time status. Specifically, the code executes in 3.71 milliseconds, which is fast enough to obtain a

satisfactory loop rate for actual implementation. The problem remains, however, as to how to obtain the required feedback information on the magnitude of the joint deflections. Either a separate deflection model may be developed to predict these deflections, or sensory feedback may be provided by additional position sensors mounted on the output shafts of the actuators.

Finally, the report describes a model-reference adaptive controller which was written to control a spatial three degree-of-freedom manipulator. Simulations of this manipulator were performed based on the assumption that the manipulator carries a large, unknown payload. The controller adaptively estimates on-line the ten parameters associated with unknown payload. Results of these simulations show that compared to the computed-torque method, the algorithm improves trajectory tracking. As predicted theoretically, convergence of the unknown parameters is obtained, although convergence to their actual values is not necessarily guaranteed. Actual implementation of this algorithm on the testbed is planned to verify the simulation results.

A copy of this report is transmitted to ORNL.

Actuator Module Electronics

In order to improve the control strategies of the actuator module, measurement of the current sent to each phase of the motor is necessary. This is accomplished by using the current sensing circuit, analog-to-digital converters, and software to read this information. Currently, the code developed for this purpose runs without any problems.

Additionally, two circuits were built to measure positions from the two resolvers independently. These circuits measure peak of the sine and cosine winding voltages of the resolver. The circuits are isolated from the commutation circuit of the motor, and are built to detect the quadrant and the direction of movement. Through the analog-to-digital converters, the computer reads the sine and cosine winding peaks and the phase information to determine the position, which is later displayed. The measurement of position from one resolver is kept independent of the other.

Hydraulic Drives for Joint Actuation

In addition to the electric drives, another possible way of actuation is the use of hydraulics. The Texas team has carried out a brief survey on the use of hydraulic systems which is briefly summarized below.

Hydraulic motors can deliver very high torques (more than 1000 ft-lbs) and are suitable where hydraulic power is available and torque requirements are high. The axial and rotary piston motors have high start-up torques but have losses associated with friction between the piston and the seal, and friction between the piston and the valve seat. The rolling vane type motors are capable of running smoothly to speeds as low as 10 rpm, and have high power per unit weight. The gear motors usually have high power to weight ratio but have very low start-up torque.

Control of the hydraulic motors is achieved by sending analog voltage to proportional valves which control the flow. In some other designs, this is accomplished by PWM control using solenoid valves. Proportional valves tend to be expensive and have high pressure drop resulting in loss of energy and heat generation. PWM control is done by turning the solenoid valves on and off at frequency of 50 Hz and by controlling the duration the solenoid valve remains on. Both of these control methods can be accurate up to 0.001 inch with position feedback. The modeling of the hydraulic machines should include valve characteristics, compressibility and stick-slip friction and other nonlinearities to predict the performance of machines accurately.

Design Procedure for Lightweight Stiff Actuator Module

A design method which can be applied to the present actuator module has been developed. This method calculates the loading and deflection by separating each element. Therefore the general boundary conditions must be solved when using this method. To check the validity of the new method a simple problem is chosen (shown below) and compared with the F.E.M. solutions.

In the example problem considered, P_1 , P_3 , P_4 and P_5 are unknown boundary stresses. Elements 1, 3 and 5 are attached to a fixed frame; however, it is free to move in the x direction.

The stress function for each element are written in following form:

$$s_x = a_{i1} x^2 + a_{i2} x + a_{i3}$$

$$s_y = a_{i1} y^2 + a_{i4} y + a_{i5}$$

$$t_{xy} = -2a_{i1}xy - a_{i2}y - a_{i3}x - a_{i6}$$

where a_{ij} are constants and the subscript i represents the element number.

Applying boundary conditions and solving for common sides, the unknowns are reduced to a_{11} , P_1 , P_3 , P_4 and P_5 . If P_4 is 100 lb, then the final results after applying deflection conditions are $P_1 = 25.4$ lb, $P_3 = 49.2$ lb, $P_5 = 25.4$ lb.

The displacements of the right sides of elements 2, 4 and 6 are compared with the F.E.M. solutions.

Element Number	F.E.M. Solution	New Method
2	0.487 E-06 in	0.13 E-06 in
4	0.419 E-05 in	0.51 E-05 in
6	0.487 E-06 in	0.13 E-06 in

As seen in the above table, there are some discrepancies since the grids are too rough in this example (for the sake of simplicity). Therefore, the future work will concentrate on the generalization of this method, and possibly will use symbolic computation algorithms.

Gimbal Module

An optimal architecture for the parallel 6-DOF controller has been defined. The optimal architecture for the controller was found by analyzing the singularities and limitations of the controller geometry. This particular architecture will serve as a base line for the gimbal module to facilitate initial estimation of gimbal specifications.

Although the exact dimensions of the controller are yet to be determined, a relatively large-scale set of parameters were assumed which will ensure a conservative estimate of the specifications. Generally, a ratio of 3:1 for base to platform size and 2.5:1 for upper to lower link lengths results in a large contiguous workspace. Specifically, we have chosen for a base line design a 10 in diameter base with a 3 in diameter platform with 20 in upper links and 8 in lower links.

The specifications for the gimbal are derived from the controller architecture and performance specifications. In a fully degraded mode, the controller must be able to reflect a range of forces up to 10 pounds in a response time of less than 0.1 sec. Some of the gimbal specifications include:

Continuous Stall Torque

25 in-lbs

Intermittent Torque	65 in-lbs
Peak Stall Torque	130 in-lbs

The gimbal module will be constructed from off-the-shelf components. The ongoing selection is based on making precision and smooth performance the dominating criteria and considering size and weight as secondary.

Currently, we are looking at precision gear drives with a ratio of 10:1 to facilitate a stiff and responsive drive train that is backdrivable with minimal inertial effects. Our aim is to find a set of gears that is on par with the Japanese Robotics Industry that has a backlash rating of less than 1 arc-min.

Report on Geometric Stability and Force Control

A report detailing the work completed on the effects of robot design on geometric stability and fault tolerance issues was recently prepared.

First, the important role of robot geometry (configuration) is emphasized for stability in force control. A region of stable operation is determined according to the robot configuration and the force-controlled direction. Intelligent configuration control by redundant manipulators improves this stability factor. However, considering general spatial manipulators, difficulty still remains in assuring geometric stability with serial type robotic manipulators.

The abundance of potential input locations in parallel mechanisms, as well as in general closed-chain mechanisms, allows redundant actuation mode, which provides the key to resolving the geometric stability problem. Antagonistic actuation incorporated with nonlinear system geometry creates an effective stiffness, analogous to that of a wound metal spring. Proper coordination of system actuators generates a desired system stiffness, while taking care of the geometric stability factor in force control tasks. Conditions for full stiffness generation are derived from an analysis of a second-order geometric property, which is central to stiffness generation.

Stiffness modulation capability is applied to the generation of actively adjustable nonlinear springs. Initially, a planar parallel mechanism is employed to simulate the spring behavior by redundant actuation. The proposed methodology resolves many of the current shortcomings of passive- and feedback-based RCC technology, and forms a general architecture for active spring design.

Modulation of impedance properties in biomechanical systems is also investigated. Musculoskeletal structures of biomechanical systems exhibit highly kinematically dependent characteristics, and possess excess numbers of muscles. As an illustrative example, impedance modulation of the human arm is studied. Investigation of musculoskeletal structures of biomechanical systems deliver the following lessons; intelligent mechanical structures allow for high level intelligent control strategy.

Fault tolerance is one of the benefits acquired from kinematic and force redundancies. Two levels of a fault-tolerant architecture are presented in terms of a spherical shoulder module. The first level involves a dual prime mover, and the second level involves a parallel structure with redundant actuation. A redundantly actuated shoulder module with four legs exhibits marked improvement in force transmission capability, compared to a fully functional three-legged shoulder module. Incorporation of dual prime mover is shown to greatly enhance a system's fault tolerance capability.

A variety of redundant actuation concepts are expected to be implemented in the design and the control of general linkage systems to enhance overall operational performances of general advanced mechanical systems.

Reports and Major Correspondence Issued

The University of Texas group published the following reports:

"Development and Demonstration of General, Real-Time Software for Robotic Manipulators," by R. Giddings.

"Analysis of Redundantly Actuated Mechanisms with Applications to Design and Control of Advanced Robotic Systems," by B. J. Yi.

A copy of these reports will be transmitted to ORNL.

Important Meetings

Sabri Tosunoglu, John Borgman, Richard Hooper, Mars Chu, Robert Smithson, Joe Geisinger, and Edward Hernandez attended the Student Conference held at Oak Ridge, Tennessee, January 16-18, 1992.

Major Problems

None.

**DOE/NE ROBOTICS PROGRAM
BI-MONTHLY PROGRESS REPORT
UNIVERSITY OF TEXAS AT AUSTIN**

Sabri Tosunoglu and Delbert Tesar

March 20, 1992

Significant Accomplishments

Gimbal Module

The torque output specifications for the actuators to be used on the gimbal module prototype were decided as follows:

Continuous Stall Torque:	27 lb-in
Peak Stall Torque:	220 lb-in

A motor and gearhead survey was conducted in January. The most significant criteria for the motor was the torque output, torque ripple, friction, rotor inertia, motor dimensions and cost. For the gearhead, the emphasis was on low backlash, high efficiency, low cogging, the dimensions and cost. Other decisions regarding the gimbal design are summarized below:

- The prototype gimbal module actuators would consist of a clutch, a gearhead, a brake, the motor and a position/velocity sensor package.
- In order to facilitate fitting these components into the prototype, the size restrictions on the gimbal module prototype have been relaxed considerably. A more compact design for the final version of the gimbal module can be engineered after conducting functional performance testing on the prototype.
- The best motor for the actuator is the Inland Brushless Motor, RBEH 1501 with the following specifications:

Stall torque:	3.4 lb-in
Peak torque:	27.6 lb-in
Diameter:	2.8 in
Length:	1.9 in
Cost:	\$845 each

- The best gearhead was the MPC Single Plane Planetary Gearhead, 18S-9. This gearhead, which has 3 arc min of backlash, a 9:1 gear ratio and 90% efficiency has a body length of only 0.8 in.

Recently however, it has been learned that the verbal quote of \$1500 for the MPC gearhead was incorrect and that the actual cost is \$3450 a piece. Additionally, the lead time for this item is 24 weeks. The cost and lead time for the MPC gearhead was decided to be too large for further consideration. The selection of an alternate gearhead with similar specifications is currently under consideration.

Comparison of Actuators

A report on the application of hydraulic and electric drives for robot actuation has been completed. The high power densities of the hydraulic actuators are discussed with the consideration on various problems associated with the use of hydraulic actuators. The control methods for the application of hydraulic actuators and the static and dynamic response that can be expected from the application are also discussed.

This report also addresses various characteristics of different electric actuators and the application of these actuators in robotics. Emphasis is made on important factors to be considered when choosing between conventional dc motors, brushless dc motors and high torque stepping motors. The report discusses possible optimization criteria that can be applied to the electric motors with respect to their design in armature and magnetic materials, application of immersion cooling, convective cooling, and feasibility of supercooling.

Progress on Four-Legged Platform Design

Structurally parallel mechanisms have been employed in robot design due to their many attractive advantages compared to commonly used serial-type manipulators. The abundance of potential input locations in structurally parallel mechanisms allows the implementation of redundant actuation, which may be utilized for optimal load distribution, beneficial internal load generation, and fault-tolerance.

A redundantly actuated Stewart platform-type manipulator has been studied as an illustrative example. This mechanism has four legs which connect the lower platform to the upper platform, and each leg (chain) consists of two active axes in the base gimbal mechanism, a passive revolute joint in the elbow, and a spherical joint in the distal location. Therefore, this mechanism has two force redundancies, compared to typical Stewart-platform with six active inputs. The first goal is to find out a set of optimal kinematic dimensions of this mechanism. These optimal dimensions are obtained based on the evaluation of the work-space, global dexterity measure, and global force transmission ratio.

As the first step in designing this mechanism, three types of manipulator architectures have been considered. The first type possesses equal link lengths and platforms (upper and lower) radii, the second type possesses equal link length with different radii, and the third type possesses equal radii with different link lengths. It is found from a kinematic analysis that the first type possesses the largest work-space, the best dexterity, and the smallest maximum force transmission requirement.

Later, an optimal ratio between the radius and link length is searched. It is observed that there exist some tradeoffs between the good dexterity, and the work-space and force transmission. However, considering the dexterity as the most important aspect in robot

design, 1 to 1 ratio is found to be the optimal ratio, and also, for this optimal ratio, the mechanism possesses allowable work-space and force transmission ratio.

The distribution of redundant actuation is reconsidered in terms of the input locations. The first type possesses two actuators in each base, the second type possesses one in the first axis of each base and another one in the elbow, the third type possesses one in the second axis of each base and another one in the elbow. It is shown from a kinematic analysis view point that the first type possesses the best dexterity, the second type possesses the smallest maximum force transmission requirement, but the third type is not recommended because it does not produce some of the operational moment components due to a singular configuration in the actuation site.

In addition, a full-actuation case (three actuators for each chain; two for the base and one for the elbow) is considered. This study illustrates that more actuation generally enhances the force transmission capability, but that more actuation does not always enhance the dexterity due to the kinematically increased interaction among the activated inputs. It is concluded that redundant actuation itself provides the designer with the intelligence in robot operation, and that the distribution of redundant actuation provides the designer with flexibility in robot design.

Reports and Major Correspondence Issued

None.

Important Meetings

Douglas Carroll and Gary Stimmell of GE Nuclear Energy, San Jose visited the University of Texas on February 4 and 5.

Major Problems

None.

**DOE/NE ROBOTICS PROGRAM
BI-MONTHLY PROGRESS REPORT
UNIVERSITY OF TEXAS AT AUSTIN**

Sabri Tosunoglu and Delbert Tesar

May 20, 1992

Significant Accomplishments

**Maintenance of ALMR RVACS:
Deployment of Robots**

In order to deploy the mobile platform, robotic arm, crawlers and camera systems to the RVACS plenum area, the Texas team developed three design alternatives:

1. Open Environment Robot Deployment Unit (OERDU)
2. Removable and Permanent Structure Robot Deployment Unit (RPSRDU)
3. Removable Structure Robot Deployment Unit (RSRDU)

Although the Open Environment Robot Deployment Unit would be a simple way to deploy the robots, it reduces RVACS system integrity during maintenance. The Removable and Permanent Structure proposes to use two enclosures for deployment which was later judged to be too complicated. The third alternative proposes to contain all robotic systems in one unit. This unit will be positioned on the ISI access hatch by a crane and deployment will be carried out remotely. The team recommended the third alternative (RSRDU) for plenum area robot deployment purposes.

Deployment of stack crawlers may be accomplished by a crane or a scissor-lift mechanism as listed below:

1. Crane and Cherry-Picker Configuration
 - (a) Control Unit in Refueling Enclosure
 - (b) On-Board Control Unit

2. Deployment by a Scissor-Lift Mechanism

- (a) Control Unit in Refueling Enclosure
- (b) On-Board Control Unit

Considering the size and weight of the crawler installation mechanism developed by the University of Florida, scissors-lift mechanism will be more suitable than the cherry-picker configuration. Also, on-board control of the crawler seems to be simpler than having the controller in the refueling enclosure.

Maintenance of ALMR RVACS: Manipulator Design

A demountable, general-purpose manipulator arm will be installed on the mobile platform to collect smear samples, loosen the dirt by a wire brush, carry out vacuuming, assist in inspection, handle the tether system, and other maintenance tasks in the hot and cold plenum areas.

Initial specifications for this arm were decided by the RVACS Design Team as follows:

- Degrees of Freedom: 6 or 7
- Maximum Reach: 40 in (between 35–45 in)
- Load Capacity: 30–40 lb (max peak), 15–20 lb (continuous)
- End-Effector Accuracy: 5 mm (0.2 in)
- Total Manipulator Weight: 200–300 lb
- Platform Weight: 400 lb (without the manipulator)
- Temperature: 160°F air, 100–200°F surface
- Radiation: 100 mR in Shielded Areas, 500 R at CV Surface

The above specifications imply the following manipulator characteristics:

- High Payload-to-Weight Ratio
- Compact Arm with Small Footprint
- Easily Demountable (specified by GE)
- Tolerant to Heat

- Tolerant to Radiation
- Easy Decontamination

In this case, manipulator design alternatives were listed as

1. Design of a New Manipulator
2. Utilization of an Existing Manipulator
3. Modification of an Existing Manipulator for RVACS Requirements

A fairly extensive survey of the existing commercial manipulators revealed that it may be impossible to find an arm which satisfies the above specifications. However, instead of designing a new robot, the Texas team will evaluate the possibility of modifying an existing arm for RVACS specifications. This may require shielding, use of radiation-hardened components, minor modifications in the arm dimensions, etc. (GE will provide detailed information on the nature of radiation and the energy levels of gamma rays in July 1992.)

The manipulator system will have autonomous as well as teleoperated mode of operations. The manual controller will provide force feedback to the operator for more precise control of the manipulator.

Gimbal Module

Previously an actuator design incorporating a 10:1 ratio gearhead was presented. The length of the actuator was over 11 inches, which later raised some concern. A concept for a direct drive actuator was proposed as a space saving alternative.

A survey of electric motors revealed that the Inland RBEH 3001-A50 was suitable as a replacement. The cost of the motor is equivalent to the combined cost of the previous motor and gearhead. The axial length of the direct drive actuator is over two inches shorter than the geared actuator, and three pounds lighter. A direct drive actuator has other advantages such as zero backlash and less compliance.

The Inland motor has a peak stall torque of 249 lb-in and a continuous stall torque of 45 lb-in. This meets the peak torque requirement and is double the continuous torque

specification. The motor meets or exceeds other motor specifications such as inertia, torque capacity, friction, etc.

Without the gearhead, the direct drive actuator's resolution is not limited by backlash. In an attempt to take advantage of this characteristic and determine the highest feasible resolution, several sensor technologies were surveyed.

An Inductisyn or a similar capacitive rotary position sensor by Farrand Controls can determine angles to 4 arc seconds. The sensors are incremental and require a second sensor for coarse resolution. A major disadvantage is their price which is about five thousand dollars for a sensor and transducer package.

Cannon makes an absolute optical encoder that provides an accuracy of .5 arc min. Unfortunately this device costs \$1,600 which also makes it prohibitive. Next year the company plans to market an absolute encoder with a resolution of 1 arc min for approximately \$500. We will continue to monitor this for possible inclusion in the final design.

We have decided to purchase a single speed resolver recommended by Inland that provides a 5 arc min resolution. Its cost is approximately \$500.

We have initiated a purchase order for the Inland motor, RBEH 3001-A50, with some modifications. Inland will mount the selected brake within a housing on the back of the motor. Behind the brake, Inland will mount and properly phase the resolver to the motor. The total cost per motor with brake and resolver is \$3,431. A clutch for the actuator is being purchased from Electroid, Inc. for \$228.

The motor will be delivered 10–12 weeks after Inland receives the purchasing order. We expect to receive the motor by the end of August.

Reports and Major Correspondence Issued

University of Texas RVACS Design Team published a status report for the May 7–8 Meetings at ORNL. This document, entitled “Robotic Systems for ALMR RVACS: Deployment and Manipulation,” was authored by S. Tosunoglu, B. J. Yi, R. Bryngelson, A. Hernandez-Luna, G. Buckner, B. McNatt, V. Menon, C. Pencis, K. Shin, Y. Ting, and P. Varatharajan.

Important Meetings

On May 7–8, 1992, Rob Bryngelson, Bryan McNatt and Sabri Tosunoglu attended the RVACS Design Team Meeting at ORNL.

Major Problems

None.

**DOE/NE ROBOTICS PROGRAM
QUARTERLY PROGRESS REPORT
UNIVERSITY OF TEXAS AT AUSTIN**

Sabri Tosunoglu and Delbert Tesar

July 20, 1992

Significant Accomplishments

Cooling System Testbed for RVACS Environment

In order to test the effectiveness of vortex tubes to cool actuators, other electronic equipment and sensors in 160°F (RVACS) to 350°F (Reactor Vessel) temperatures, a testbed design is underway at the University of Texas. This testbed will have a heater unit to provide high ambient temperatures, a unit to be cooled, and a vortex tube with attachment to compressed air supply. Although details of the set-up is currently being designed, the following equipment was recently ordered to the Vortec Corporation:

Model	Item
770	Panel Guard System (delivers 1,500 BTUH while consuming 25 CFM at 100 psig)
218	Experimental Outfit
208R	Pressure Regulator 3/8 inch NPT (up to 50 CFM)
701S-36A	Auto Drain Filter Separator 1/4 inch NPT (up to 50 CFM)
1408	Compressed Air Hose 8 ft long, 250 psig, 1/4 inch NPTM

Gimbal Design

Over the past two months, the conceptual design for the gimbal has been completed. As reported previously, this is a two-degree-of-freedom module that kinematically resembles a knuckle. According to the final conceptual design, the housing of this module will consist of a square tube box with four circular tubes mounted to the vertical sides. The actuators

will be fitted to a tube end cap and then passed down the tubes and recessed into the box. The end caps will then be bolted to the tubes.

The goal for the gimbal is to aesthetically house the four actuators with the tightest reasonable footprint. Several different designs were considered; however, because of the governing parameters presented, the four-tube scheme was selected. This particular design incorporated the use of "off-the-shelf" materials to simplify machining and assembly.

The main factor that affected our decision was the size of the gimbal and the ease of assembly. Having the smallest possible footprint for the gimbal is critical to the performance of the fault tolerant testbed. The smaller the footprint, the less torque output needed from the driving actuators. By assembling the gimbal from outside towards the inside, the housing can tightly pack the components, possibly up to the point of component interference. This will in effect minimize the amount of free air space within the gimbal delivering the smallest module footprint.

Since Inland Motors has decided to place housings over some of the components, and we have not yet received the finalized actuator drawings from them, only conceptual drawings of the gimbal design have been completed. Several factors will need to be addressed when the final dimensions are released. For instance, those dimensions will determine the critical actuator components that can interfere with other module components. The size of the tubes and their connection will most probably be affected by the final actuator dimensions.

Module Coupling Design

A new coupling design is being developed for quick assembly and disassembly of robotic modules. This design involves left- and right-hand threaded collars to attach or detach modules. The new coupling design offers high preloading and accurate relative positioning of modules with low stress concentrations. Theoretically, this design appears to be one order of magnitude stiffer than the coupling used by the Robotics Research Corp. Detailed design drawings are currently being developed. It is expected that a prototype will be built and tested after the design is finalized.

Actuator Module Tests

The experimentation of the actuator module has considerably progressed. Tests have been performed on both sides of the actuator and are summarized below:

Calibration of Actuator

- Both actuator sides are operating from two separate amplifiers. However, since each side possesses different resistance characteristics and gain factors, it was impossible to have perfect synchronous motion between the two sides in both the positive and negative rotation directions.
- The position drift for both sides were adjusted such that motion is insignificant when a zero command signal was inputted.
- Precision Temperature Sensors LM335A from National Semiconductor are used as thermal sensors for the actuator cooling shell. They were calibrated at hot and cold temperatures, and provide about $\pm 1^{\circ}\text{C}$ accuracy.
- Voltage constants, which provide a ratio of armature voltage to armature speed, were obtained for both sides of the actuator. Both sides possessed similar results with a constant of 10.0 V/kRPM.
- Torque constants were not obtainable at this time due to lack of sufficient equipment. These tests will be performed later.

Experiments for Current Actuator State

- Resolver accuracy tests were performed by using a calibrated scale strapped to the circumference of the planet carriers. The carriers were rotated at 1/2 inch increments, and the associated position was measured from the resolver into the computer. The results produced a cyclic error between 0.0° to 10.0° . These errors are cyclic for a full rotation and can be attributed to variations in the resolver position circuits. These circuits are being analyzed to determine whether the accuracy can be improved.

- Bandwidth tests were initially performed with a spectrum analyzer. The results showed bandwidths between 2 to 2.5 Hz. It is expected that these results will greatly improve during the next phase of experimentations when the gear trains are removed for testing.
- Friction tests were divided into three types and performed for the positive and negative directions on each side:
 - Zero mode - where the command voltage is ramped up and then zeroed when the actuator side broken free of stiction (static friction).
 - Steady mode - where the command voltage is ramped up and remained at a constant magnitude whenever the actuator side broke stiction.
 - Up/Down mode - where the command voltage is ramped up, then ramped down after the break point (from stiction), and then remained constant at the catch point (from kinetic friction).

Several problems occurred with these tests which varied the data. First, the current limits have been set low. This is primarily to ensure safe conditions, since the system is still unknown and it is undesirable to overheat the motors. Furthermore, the mesh between the central gears and the planet gears produces different characteristics (such as friction and backlash) at different orientations of the gear train. Thus, a series of ten data sets was taken for each friction test. However, since the constant torque test has not been performed, frictional torque could not be obtained at the moment.

- Five temperature sensors were installed upon the motor cooling shell. They span from one end to the other (equally spaced). Their circuitry has been developed and integrated into the control system. These sensors are used primarily for safety purposes to monitor and ensure that the motors do not overheat.
- Stiffness and backlash tests were performed on each side individually and as a total system. These data are still being post-processed. Initial indications show the overall system backlash to be approximately 25-35 arc-min and the overall system stiffness to be approximately 650,000 in-lbs/rad.

The project is currently initiating the second experimentation phase. The actuator sides are being disassembled into motor and gear subassemblies. In this phase, similar tests will be conducted and compared to the previous tests. The most difficult and time-consuming portion of these tests will involve the gear trains. We desire to conduct a series of tests (backlash, stiffness, friction) consisting of the following setups:

- Multiple number of planets: 2, 3, 4, 6, 9, 12
- Multiple planet sets per number of planets. For example, when testing with 2 planets, different 2 set of planets can be used.
- Multiple orientations per planet set. For example, when testing with 2 planets, the planet carrier can be oriented at various rotations.

In fact, a very large number of combinations can be derived, but only a selected few will be used for a represented range of results. These tests require constant assembling, maintenance, and disassembling of the gear trains that will delay the completion of the experimentation stage. Fortunately though, the majority of the motor subassembly tests can be conducted simultaneously with the gear subassembly tests without delay.

Reports and Major Correspondence Issued

S. Tosunoglu submitted a paper titled "Design, Modeling and Control Techniques to Improve Robot Precision" to the Turkish Electrical Engineering Magazine, *Elektrik Muhendisligi Dergisi*, for publication in Turkish in July 1992.

Important Meetings

Walter Kwant of GE Nuclear Energy, San Jose visited the University of Texas Robotics Program on Friday, July 3.

Major Problems

None.

**DOE/NE ROBOTICS PROGRAM
QUARTERLY PROGRESS REPORT
UNIVERSITY OF TEXAS AT AUSTIN**

Sabri Tosunoglu and Delbert Tesar

October 20, 1992

Significant Accomplishments

Manual Controller Interface to the VME System

In order to improve the update rate of the existing and future manual controllers, the MicroVAX workstation is being replaced with a VME-OS/9 system. In this system, VME's open architecture makes incremental growth possible, and the OS/9 provides a real-time operating system. Previously, the VME has been interfaced with the shoulder manual controller. Recently, the VME is interfaced with the Silicon Graphics workstation. This set-up eliminates the MicroVAX usage, and allows the control of a robot via the manual controller on the Silicon Graphics using the previously developed robot animation package.

Code earlier developed on the MicroVAX has been rewritten for the VME system. Also, drivers have been developed to read encoder-supplied information associated with each actuator. These readings are then mapped into the end-effector domain of the shoulder module.

As reported previously, the shoulder system contains a Lord force/torque sensor to record the forces input by the operator. Interface of this sensor to the VME has also been completed. This will allow the implementation of power steering option so that the forces felt at the hand on the controller (due to friction and stiction at the gears) to be read and overcome with the use of the three base actuators.

Additionally, in order to read from the tachometers installed on the shoulder actuators, an additional data acquisition board, DATEL DVME-613C board, has been recently purchased. The tachometer readings will allow the implementation of more sophisticated

controllers in the future. Once this real-time controller system with the VME as its central processor is fully developed, it will be used to control other robot modules and manual controllers currently being developed.

Design of a 7-Degree-of-Freedom Modular Robot

Design specifications for a seven-degree-of-freedom (DOF) modular robot has been set as follows:

- 7-DOF made up of three modules
- 3-1-3 configuration
 - 3-DOF shoulder
 - 1-DOF elbow
 - 3-DOF wrist
- 6 ft maximum reach
- 50 lb payload capacity
- 30 in/sec end-effector speed
- less than 400 lb total weight
- brushless DC motors

Although currently this robot is not intended to be used directly in the Advanced Liquid Metal Reactor (ALMR) developed by General Electric, the above specifications closely match the manipulator characteristics recommended by the Texas team for the ALMR Reactor Vessel Auxiliary Cooling System (RVACS).

Since each of the three modules (shoulder, elbow, wrist) is being designed in three scales, other robots with different arm properties can also be constructed. The above represents the maximum arm length, payload, speed, etc. envisioned for the most capable manipulator configuration.

Consistent with the above outlined goals, structural design in the following modules are currently in progress:

- Shoulder and wrist joints: These three-DOF modules each have two in-line revolutes and one elbow revolute. Although similar in design, the wrist uses a split mid-joint actuator to yield a larger workspace for the payload. Each in-line joint has 360 degree motion capability whereas the elbow joint has a minimum of 240 degree motion range.
- Elbow joint: This one-DOF module is installed between the shoulder and the wrist and is being developed in three scales. Kinematic design of this joint has previously been studied by the Texas group. Currently its structural design is being addressed.
- Links: Standard links will be established and scaled in shape and length for different robot configurations. Standard joint, link, power and communication interfaces are also being addressed.
- In-line actuator: Although a prototype for the elbow actuator has been previously constructed within the group, an in-line actuator has not been studied. Currently, scaled design of an in-line actuator is being developed. Basic properties of this actuator are listed as follows:
 - Single motor
 - Single gear-train: Nested internal gear with Ferguson paradox
 - On-board electronics
 - Standardized modular connections

ALMR Cooling System Components Purchased

The Texas team is developing a cooling system testbed to test the performance of vortex tubes in such systems. If found successful, the goal is to integrate vortex tube-based cooling systems into the designs of heat-sensitive components that will be used in the Advanced Liquid Metal Reactor—ALMR.

Recently, the following testbed components were received from the Vortec Corp:

- Panel guard system vortex tube which delivers 1,500 BTUH consuming 25 CFM (cubic feet per minute) at 100 psig pressure

- Experimental outfit which includes generators with various properties to adjust the mass and temperature of the cold output air, muffler, and connectors
- Pressure regulator
- Auto drain filter separator
- Compressed air hose

In addition, the remaining components were ordered and received since the last reporting period:

- 11 E-series Chromel-Constantan Thermocouples rated to 900°F, 60 inch in length with stripped end leads (Omega Engineering, Inc. WTE-10-S-60)
- Thermal bonding resins (Omega Engineering, Inc. OB-200-2)
- 2 Thermistors (Omega Engineering, Inc. AD-590-JF)
- 1 Farberware Turbo Convection Oven (Model T-4850)
- Lab-PC Data Acquisition Board for thermocouple/PC interface with the following characteristics: 12-bit A/D converter, two 12-bit double-buffered D/A converters, 24 digital I/O lines, configured as three 8-bit ports, and 3 independent 16-bit counter/timers (National Instruments, Inc. Lab-PC 776333-01)
- I/O Connector Block (National Instruments, Inc. 776164-02)
- 1 In-line Flowmeter (Omega Engineering, Inc. FL-505)

A 100 psi compressed air line has been extended to the Robotics Laboratory to feed the vortex tubes during experimentations.

Kinematic Design of the Four-Legged Manual Controller

As reported previously, four gimbal modules designed by the Texas team will be used to actuate the legs of a four-legged platform. Much like the shoulder, this platform will be used as a manual controller. However, this controller will have six degrees of freedom instead of the three offered by the shoulder.

Before the structural design of such a platform begins, a kinematic analysis of this mechanism was carried out. The first goal was to improve the useful workspace by

adjusting kinematic system parameters. Initially, three types of four-legged mechanisms were considered. The type with equal link and platform radii was found to have the best transmission characteristics between the system input and outputs. Next, a set of optimal dimensions was sought based on normalized system dimensions. In this case, one-to-one ratio between the link length and the platform radii was found to represent the optimal solution. Also, the distribution of redundant actuation was considered in terms of input locations.

Force analysis of the four-legged platform was also formulated. Similar to most three-dimensional, parallel mechanisms, it has been observed that this system too has compatibility problems in terms of the available force equilibrium equations and the number of unknown force components. In this case, there were two more unknowns than the number of equations for each chain. Therefore, two compatibility relations were required for each chain to completely track the force distribution within the system. System force transmission characteristics for different architectures as well as in cases of partial failures will be investigated next.

Reports and Major Correspondence Issued

Yung Ting, Sabri Tosunoglu, and Delbert Tesar submitted a paper titled "A Control Structure for Fault-Tolerant Operation of Robotic Manipulators," for presentation at the 1993 IEEE International Conference on Robotics and Automation to be held in Atlanta, Georgia.

Important Meetings

Michael Unseren of ORNL has visited the University of Texas Robotics Group on October 5 and 6. Since Dr. Unseren's research interests are close to the ongoing work at Texas, we had interesting sessions and discussed possible cooperation in various areas.

Major Problems

None.

END

DATE
FILMED
3 / 5 / 93