~~OFFICIAL USE ONLY~~

K/D--5720-Draft

DE93 007041

ANALYSIS OF THE APRIL 18, 1986
UF₆ RELEASE TEST

R. A. Just

Date of Issue: October 1986

Oak Ridge Gaseous Diffusion Plant
Oak Ridge, Tennessee 37831
operated by
Martin Marietta Energy Systems, Inc.
for the
U. S. DEPARTMENT OF ENERGY
under Contract No. DE-AC05-84OR21400

~~OFFICIAL USE ONLY~~

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

	<u>Page</u>
1. Introduction	1
2. Meteorological Properties	5
3. Ratio of Uranium and Fluorine Concentrations	10
4. Concentration Measurements Using Integrated Samplers	11
4.1 Downwind Variation in Uranium and Fluorine Concentrations	25
4.2 Estimation of Crosswind Dispersion Coefficients	25
4.3 Error Analysis of Concentration Measurements	31
5. Measurements Using Sequential Samplers	42
5.1 Estimation of Experimental Error	48
5.2 Variation in Concentration as a Function of Time	52
5.3 Estimation of Vertical Dispersion Coefficients	52
6. Comparison of Concentration Measurements Using Continuous and Sequential Samplers	59
7. Estimation of Deposition Rates	65
8. Particle Size Distribution Data	75
9. Considerations for Future UF ₆ Release Tests	75
10. Suggested Revisions for Future UF ₆ Release Tests	80
11. Comparison of Test Data with Predictions of UF ₆ Dispersion Model	81
11.1 Simulation of the UF ₆ Release	82
11.2 Comparison of Experimental and Predicted Maximum Concentrations	83
11.3 Comparison of Experimental and Predicted Concentration Surface Patterns	83
11.4 Comparison of Experimental and Predicted Estimates of the Dispersion Coefficients	87
11.5 Comparison of Experimental and Predicted Estimates of the Centerline Elevation	87
11.6 Summary of Comparison of Test Data with Predictions of UF ₆ Dispersion Model	87
12. Summary and Conclusions	92
References	94
Appendix	

List of Figures

<u>No.</u>	<u>Title</u>	<u>Page</u>
1	Uranium Concentration (mg/m ³) at Distances of 10, 20, 40, and 100 m	16
2	Fluorine Concentrations (mg/m ³) at Distances of 10, 20, 40, and 100 m	17
3	Uranium Concentrations (mg/m ³) at Distances of 500, 1000, and 2200 m	18
4	Fluorine Concentrations (mg/m ³) at Distances of 500, 1000, and 2200 m	19
5	Values of $(114/238) \times (\text{Concentration U})/(\text{Concentration F})$ at Distances of 10, 20, 40, and 100 m	20
6	Values of $(114/238) \times (\text{Concentration U})/(\text{Concentration F})$ at Distances of 500, 1000, and 2200 m	21
7	Distribution of Normalized Concentration Ratio over the Range 0.5 to 3 Using Integrated Samplers	22
8	Distribution of Normalized Concentration Ratio over the Range of 0.02 to 0.5 using Integrated Samplers	23
9	Variation of Normalized Concentration Ratio as a Function of Uranium Concentration	24
10	Downwind Variation in Maximum Measured Concentrations	27
11	Downwind Variation in Maximum Adjusted Concentrations	37
12	Distribution of Normalized Concentration Ratio over the Range 0.5 to 3 using Sequential Samplers	50
13	Variation of Normalized Concentration Ratio as a Function of Uranium Concentration Measured by Sequential Samplers	51
14	Estimated Values of Deposition Velocity of Uranium Using Unadjusted Concentration Estimates	70
15	Estimated Values of Deposition Velocity of Fluorine Using Unadjusted Concentration Estimates	71
16	Estimates Values of Deposition Velocity of Uranium Using Adjusted Concentration Estimates	72

<u>No.</u>	<u>Title</u>	<u>Page</u>
17	Estimated Values of Deposition Velocity of Fluorine Using Adjusted Concentration Estimates	73
18	Uranium Particle Size Distribution Data	78
19	Fluorine Particle Size Distribution Data	79

List of Tables

<u>No.</u>	<u>Title</u>	<u>Page</u>
1	Locations of Uranium and Fluorine Concentration Measurements Using the Integrated Samplers	2
2	Locations of Uranium and Fluorine Concentration Measurements Using the Sequential Samplers	3
3	Locations of Particle Size Distribution Measurements	3
4	Locations of Deposition Measurements	4
5	Meteorological Properties - Wind Velocity and Direction	6
6	Meteorological Properties - Temperature, Pressure, and Relative Humidity Data	7
7	Meteorological Conditions Defining Pasquill Turbulence Types	8
8	Classification of Atmospheric Stability by Horizontal Wind Fluctuations (σ_θ)	9
9	Uranium and Fluorine Concentration Measurements at an Elevation of 1 m	13
10A	Maximum Measured Uranium Concentrations	26
10B	Maximum Measured Fluorine Concentrations	26
11	Evaluation of Crosswind Concentration Profile Information	28
12	Summary of Crosswind Concentration Information	30
13	Adjusted Uranium and Fluorine Concentration Measurements	33
14A	Maximum Measured Adjusted Uranium Concentrations	36
14B	Maximum Measured Adjusted Fluorine Concentrations	36
15	Evaluation of Adjusted Crosswind Concentration Profile Information	38
16	Summary of Adjusted Crosswind Concentration Information	40

<u>No.</u>	<u>Title</u>	<u>Page</u>
17	Estimation of Experimental Error in Concentration Measurements	41
18	Sample Intervals of Sequential Samplers	42
19	Uranium and Fluorine Concentration Measurements Using Sequential Samplers	43
20	Adjusted Sequential Uranium and Fluorine Concentration Measurements	53
21	Summary of Sequential Uranium and Fluorine Concentration Measurements	58
22	Evaluation of Vertical Uranium Concentration Profile Information	60
23	Evaluation of Vertical Fluorine Concentration Profile Information	61
24	Evaluation of Adjusted Vertical Uranium Concentration Profile Information	62
25	Evaluation of Adjusted Vertical Fluorine Concentration Profile Information	63
26	Summary of σ_z Information	64
27	Comparison of Uranium and Fluorine Concentration Measurements Using the Continuous and the Sequential Samplers	66
28	Comparison of Adjusted Uranium and Fluorine Concentration Measurements Using the Continuous and the Sequential Samplers	67
29	Uranium and Fluorine Deposition Measurements Using Unadjusted Concentration Estimates	68
30	Adjusted Uranium and Fluorine Deposition Measurements Using Adjusted Concentration Estimates	69
31	Summary of Deposition Velocity Data	74
32	Particle Size Information	76
33	Estimates of Accuracy for Dispersion Calculations	82

<u>No.</u>	<u>Title</u>	<u>Page</u>
34	Comparison of Experimental and Predicted Maximum Uranium Concentrations at an Elevation of 1 m	84
35	Comparison of Experimental and Predicted Maximum Fluorine Concentrations at an Elevation of 1 m	85
36	Comparison of Experimental and Predicted Concentrations Using Unadjusted Data	86
37	Comparison of Experimental and Predicted Concentrations Using Adjusted Data	87
38	Comparison of Predicted and Estimated Values of σ_y	88
39	Comparison of Predicted and Estimated Values of σ_z	88
40	Comparison of Predicted and Estimated Values of the Centerline Elevation	88

1. Introduction

On April 18, 1986 a controlled uranium hexafluoride (UF_6) release test was conducted at a CESTA (a French government agency) test site near Bordeaux, France. During the test, 45.8 kg of UF_6 vapor were released, over a time interval of 605 s from a 3.15-m high, 0.05-m diameter pipe at a rate of 75.7 kg/s. The exit velocity was 3.46 m/s, and the average exit temperature was 108°C. Information collected during the release test included: meteorological data, measurements of uranium and fluorine concentrations, deposition data, and particle size distribution data.

Meteorological properties measured included the wind velocity at 10 m, the standard deviation in the wind velocity at 10 m, the wind direction at 10 m, the standard deviation in the wind direction at 10 m, the wind velocity at 30 m, the standard deviation in the wind velocity at 30 m, the wind direction at 30 m, the standard deviation in the wind direction at 30 m, the ambient temperature, the relative humidity, and the ambient pressure.

Uranium and fluorine concentration measurements were made using two types of samplers: (1) the integrated or continuous samplers which were used to determine average values of uranium and fluorine concentrations at selected locations and (2) the sequential samplers which were used to determine average values of uranium and fluorine concentrations as a function of time. Parameters measured included: the distance from the source, the azimuth, the volume of the sample, the duration of the sample, the volumetric flow rate, the quantity uranium collected, the quantity fluorine collected, and the sampler type (bubbler or filter). From this information uranium and fluorine concentrations were estimated at the locations indicated in Tables 1 and 2.

Particle size distribution measurements included the distance from the source, the azimuth, the quantity of uranium and fluorine collected in each of nine particle size ranges, and the collection duration. The locations of the particle size measurements are indicated in Table 3.

Deposition measurements at the locations indicated in Table 4, included the distance from the source, the azimuth, the quantity of uranium and fluorine collected, and the collection duration. From this information and

Table 1. Locations of Uranium and Fluorine Concentration Measurements Using the Integrated Samplers

Distance (m)	Azimuth Locations					
10	360 ^a 300	350 290	340 280	330 270	320 ^b 255 ^a	310
20	342 306 270	336 300	330 ^b 294	324 288	318 282	312 276
40	336 300	330 294	324 288	318 282	312 276	306 ^b
100	327 ^a 309 291 270	324 306 288	321 ^a 303 285	318 ^a 300 282	315 297 279	312 294 276
500	312 ^a	306	300	294 ^a	288 ^a	
1000	312 ^a	306	300	294 ^b	288 ^b	
2200	315 ^a	300	285 ^a			

^aUranium concentration data are not available.

^bNeither uranium nor fluorine concentration data are available.

Table 2. Locations of Uranium and Fluorine Concentration Measurements Using the Sequential Samplers

Distance (m)	Azimuth	Elevations (m)
20	292.5	1,3,8
20	315	1,3,8
20	337.5	1,3,8
40	292.5	1,3,8
40	315	1,3,8,15
40	337.5	1,3,8

Table 3. Locations of Particle Size Distribution Measurements

Distance (m)	Azimuth
20	315
40	315
40	292.5
100	315
100	292.5

Table 4. Locations of Deposition Measurements

Distance (m)	Azimuth Locations					
10	340 ^a 280 ^a	330 270 ^a	320	310	300	290
20	330 294	324 ^a 288	318 282 ^a	312 276	306	300
40	324 288	318 282 ^a	312	306	300	294
100	318 ^b 300	315 ^b 297	312 294 ^b	309	306	303
500	312 ^a	306	300	294	288 ^c	

^aFluorine deposition data not available.

^bUranium deposition data not available.

^cNeither uranium nor fluorine deposition data available.

the concentration measurements, the uranium and fluorine deposition velocities were estimated.

The U.S. Department of Energy has sponsored the development of a UF₆ dispersion model for simulating postulated accidental releases of UF₆. The UF₆ dispersion model was developed by using a knowledge of the physical processes involved and engineering judgment to extend the state-of-the-art of existing dispersion models to simulate UF₆ dispersion. This model is the only known dispersion model that simulates the unique aspects of UF₆ dispersion which include the effects of chemical reactions; positive, neutral, or negative buoyancy; phase changes; elevated or ground-hovering behavior; and significant density variations. The data collected during the April 18 UF₆ release test at the CESTA test site are the only known information on UF₆ releases that can be used to evaluate the accuracy of the UF₆ dispersion model.

In this report the data collected during the April 18 release test will be evaluated and compared with the predictions of the UF₆ dispersion model. It should be noted in reading this report that the error analysis has not yet been received from the French working group. After this information is received and evaluated, the conclusions presented in this report will be reevaluated.

2. Meteorological Properties

Meteorological information collected during the test is presented in Tables 5 and 6. Although an attempt was made to measure the vertical temperature gradient, experimental difficulties resulted in loss of this information.

The wind direction measurements at elevations of 10 and 30 m appear to be inconsistent. The consistent difference of -9 to -15.6 seems to indicate that they are not aligned correctly. However, the wind direction sensors were checked prior to and after the release. Their accuracy is about 1 to 2°. Therefore, the wind direction measurements indicate a very high level of wind shear.

Criteria for evaluating atmospheric stability are presented in Tables 7 and 8. The 6.8 m/s wind velocity at 10 m would yield a "neutral" or Class D stability. Prior to using the stability criteria¹ presented in

Table 5. Meteorological Properties - Wind Velocity and Direction

Time of Day	Velocity at 10 m (m/s)	Standard Deviation (m/s)	Direction at 10 m	Standard Deviation at 10 m	Velocity at 30 m (m/s)	Standard Deviation (m/s)	Direction at 30 m	Standard Deviation at 30 m	Change in Wind Direction ^b
15:28	7.9	0.22	304.4	3.3	10.2	0.22	319.7	3.7	-15.3
15:30	5.9	0.14	309.5	3.9	7.4	0.19	324.7	4.3	-15.2
15:32	7.5	0.25	315.0	4.0	9.3	0.21	327.8	4.3	-12.8
15:34	7.3	0.24	308.5	3.6	8.9	0.22	323.1	4.0	-14.6
15:36	6.8	0.23	311.8	3.9	7.8	0.20	325.0	4.3	-13.2
15:38	5.9	0.15	312.3	3.8	7.0	0.20	321.8	4.0	-9.5
15:40	8.0	0.24	308.6	3.5	9.0	0.22	322.2	4.0	-13.6
15:42	6.6	0.15	311.5	3.7	7.1	0.12	326.8	4.2	-15.3
15:44	6.6	0.15	309.4	3.7	7.8	0.15	322.9	4.0	-13.5
15:46	5.6	0.15	302.8	3.4	6.8	0.15	318.5	3.9	-15.7
15:48	6.2	0.12	313.8	3.9	6.7	0.15	322.8	4.1	-9.0
15:50	8.2	0.24	315.5	3.9	9.8	0.21	325.5	4.1	-10.0
15:52	6.5	0.17	309.7	3.8	8.1	0.11	322.4	4.1	-12.7
15:54	7.8	0.19	310.0	3.6	8.8	0.14	321.9	3.9	-11.9
15:56	6.5	0.26	301.4	3.4	7.6	0.15	312.4	3.7	-11.0
15:58	6.8	0.39	307.0	3.5	10.1	0.34	317.5	3.6	-10.5
Minimum	5.6	0.12	301.4	3.3	6.7	0.11	312.4	3.6	-15.7
Maximum	8.2	0.39	315.5	4.0	10.2	0.34	327.8	4.3	-9.0
Mean	6.9	0.21	309.5	3.7	8.3	0.19	322.2	4.0	-12.7

^aWhere P is obtained from the assumed power law relation for the velocity profile: $V = V_0(z/z_0)^P$.

^b(Wind direction at 10 m) - (wind direction at 30 m).

Table 6. Meteorological Properties -
Temperature, Pressure, and Relative Humidity Data

Time of Day	Temperature (°C)	Temperature Difference (°C)	Pressure (Bars)	Relative Humidity (%)
15:28	8.4	Bad Data	1.014	100
15:30	8.5	Bad Data	1.014	100
15:32	8.7	Bad Data	1.014	100
15:34	8.7	Bad Data	1.014	100
15:36	8.7	Bad Data	1.014	100
15:38	9.1	Bad Data	1.014	100
15:40	9.2	Bad Data	1.014	100
15:42	9.2	Bad Data	1.014	100
15:44	9.5	Bad Data	1.014	100
15:46	9.9	Bad Data	1.014	100
15:48	10.2	Bad Data	1.014	100
15:50	10.6	Bad Data	1.014	100
15:52	10.9	Bad Data	1.014	100
15:54	11.3	Bad Data	1.014	100
15:56	11.6	Bad Data	1.014	100
15:58	11.4	Bad Data	1.013	100
Minimum	8.4	Bad Data	1.014	100
Maximum	11.6	Bad Data	1.014	100
Mean	9.7	Bad Data	1.014	100

Table 7. Meteorological Conditions Defining
Pasquill Turbulence Types^a

Surface Wind Speed (m/s)	Daytime Insolation ^b			Nighttime Conditions ^{b,c}	
	Strong	Moderate	Slight	Thin Overcast or > 4/8 Low Cloud	< 3/8 Cloudiness
< 2	A	A-B	B		
2	A-B	B	C	E	F
4	B	B-C	C	D	E
6	C	C-D	D	D	D
> 6	C	D	D	D	D

^aFrom F. A. Gifford (Ref. 2).

^bA - Extremely unstable conditions

B - Moderately unstable conditions

C - Slightly unstable conditions

D - Neutral conditions (applicable to heavy overcast day or night)

E - Slightly stable conditions

F - Moderately stable conditions

^cThe degree of cloudiness is defined as that fraction of the sky above the local apparent horizon that is covered by clouds.

Table 8. Classification of Atmospheric Stability by
Horizontal Wind Fluctuations (σ_θ)

Stability Classification ^a	Pasquill Categories	σ_θ ^b (degrees)
Extremely unstable	A	$\sigma_\theta > 22.5$
Moderately unstable	B	$22.5 > \sigma_\theta > 17.5$
Slightly unstable	C	$17.5 > \sigma_\theta > 12.5$
Neutral	D	$12.5 > \sigma_\theta > 7.5$
Slightly stable	E	$7.5 > \sigma_\theta > 3.8$
Moderately stable	F	$3.8 > \sigma_\theta > 2.1$
Extremely stable	G	$2.1 > \sigma_\theta$

^aFrom U.S. Nuclear Regulatory Commission.¹

^bStandard deviation of horizontal wind direction
fluctuation over a period of 15 min to 1 h.

Table 8, the measured standard deviation in the wind direction must be converted from an averaging time of 2 min to an averaging time of 15 min. Gifford² has developed an empirical rule for correcting the dispersion coefficients (σ) for different averaging times,

$$\sigma = \sigma' (T/T')^{0.2},$$

where T and T' are the averaging times used in evaluating σ and σ' , respectively. For T = 15 min and T' = 2 min, $\sigma = 1.5 \sigma'$. Therefore, the standard deviation in the wind direction at 10 m is estimated as 1.5 times 3.7° or 5.6°. The stability class information presented in Table 8 indicates a "slightly stable" or Class E stability. This application of the information contained in Table 8 is somewhat uncertain because of the uncertainty in correcting for a 2-min averaging time. Therefore, a Class D or "neutral" stability class will be assumed.

The information presented in Tables 5 and 6 indicates that the average ambient conditions during the UF₆ release were: temperature of 8.8°C, pressure of 1.013 bar, 100% relative humidity, mean wind direction at 10 m of 311, a wind velocity of 6.9 m/s at 10 m, and the exponent p in the power law velocity profile is approximately 0.17. It should be noted that a value of 0.17 for p is reasonably consistent with the 0.15 estimate reported by Irwin.³

3. Ratio of Uranium and Fluorine Concentrations

After release into the ambient air, UF₆ will react with the moisture (H₂O) present in the air to form the hydrolysis products uranyl fluoride (UO₂F₂) and hydrogen fluoride (HF). The reaction equation for the hydrolysis of UF₆ is,

After all the UF₆ had reacted with the ambient moisture, one-third of the fluorine was present in UO₂F₂ particles, and two-thirds of the fluorine was present as HF. Noting that the molecular weights of uranium and fluorine are approximately 238, and 19, respectively, indicates that 6 x 19 or 114 kg of fluorine will be released for every 238 kg of uranium. Therefore, at the release point, the value of (114/238) x (concentration U)/(concentration F) will be exactly 1. If uranium and fluorine have the same

dispersion and deposition characteristics, $(114/238)$ times the ratio of the uranium and fluorine concentrations should be exactly 1 beyond the release point.

If the value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ is not exactly 1, then either (1) uranium and fluorine disperse at different rates, or (2) the rates of uranium and fluorine deposition are different, or (3) experimental error results in incorrect estimates of the concentrations, or (4) a combination of the above reasons. Therefore, the value $(114/238)$ times the ratio of the uranium and fluorine concentrations is useful in comparing the dispersion properties of uranium and fluorine and in detecting potential errors in the data.

The value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ can range from 0, the value when no uranium is present, to 3 when no HF is present. A value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ greater than 3 indicates experimental error in measuring the uranium and/or the fluorine concentration.

4. Concentration Measurements Using Integrated Samplers

Measurements made using the integrated or continuous samplers included the distance from the source, azimuth, volume of sample, duration of the sample, volumetric flow rate, quantity uranium collected, and quantity fluorine collected. Two types of samplers were used: bubblers and filter. The samplers that use filters have one filter for measuring uranium and two filters for measuring fluorine.

A 20-min sample was initiated 5 min before the start of the release (i.e., at H-5 min) at distances of 10, 20, 40, and 100 m. Collection was initiated at H = 0 min for distances of 500, 1000 and 2200 m, where material was collected for 30 min.

Uranium and fluorine concentrations estimates obtained using the data from the integrated samplers are based on the assumption that the duration of the plume was equal to the release duration of 605 s. In reality, the actual plume duration will increase as a function of downwind distance as the plume disperses in the upwind and downwind directions. However, only a small error is introduced in assuming a plume duration of 605 s. The

uranium and fluorine concentrations estimates are presented in Table 9 and on Figs. 1 through 4.

Values of the normalized concentration ratio, $(114/238) \times (\text{concentration U})/(\text{concentration F})$, are shown on Figs. 5 and 6. Examination of Figs. 5 and 6 indicates that the value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ tends to decrease as the concentrations decrease (i.e., in both the downwind and crosswind directions). The distribution in the $(114/238) \times (\text{concentration U})/(\text{concentration F})$ values is shown on Figs. 7 and 8.

The relationship between the estimated uranium concentrations and the value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ values is shown on Fig. 9. Examination of the data presented on Figs. 7, 8, and 9 indicates that the distribution of the $(114/238) \times (\text{concentration U})/(\text{concentration F})$ values is not randomly distributed around 1. Random error in the measurements would result in the a mean value of 1.0, with the values being randomly distributed about the mean. As will be discussed in Section 4.3, it is believed that experimental errors resulted in low estimates of UO_2F_2 concentrations, which yielded values much less than 1 of the quantity $(114/238) \times (\text{concentration U})/(\text{concentration F})$.

At distances of 10, 20, and 40 m many of the values of the quantity $(114/238) \times (\text{concentration U})/(\text{concentration F})$ are significantly greater than 1.0 (approximately 2). It is probable that the unexpectedly high values of the normalized concentration ratio results from experimental error. A value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ significantly greater than 1 may imply a low estimate of the HF concentration. A low estimate of HF could have resulted from a chemical reaction between HF and either the collection apparatus or the chemical analysis equipment.

Anomalies in the concentration measurements occur at four locations: (1) at a radial distance of 20 m, the uranium and fluorine concentration measurements at azimuths 300 and 306 do not monotonically decrease with the crosswind distance and (2) at a radial distance of 100 m, the uranium and fluorine concentration measurements at azimuths 300 and 303 do not monotonically decrease with the crosswind distance.

Table 9. Uranium and Fluorine Concentration Measurements at an Elevation of 1 m

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Volumetric Flow Rate (m ³ /s)	Quantity Uranium (mg)	Quantity Fluorine (mg)	Sampler Type
360	10		0.0590		2.8 x 10 ⁻⁵		0.001	Bubbler
350	10	0.1771	0.0590	1.44	2.8 x 10 ⁻⁵	0.003	0.001	Bubbler
340	10	0.2361	0.1181	0.96	2.8 x 10 ⁻⁵	0.004	0.002	Bubbler
330	10	178.0992	41.9126	2.04	2.8 x 10 ⁻⁵	3.017	0.710	Bubbler
320	10							
310	10	437.3394	80.9917	2.59	2.8 x 10 ⁻⁵	7.417	1.372	Bubbler
300a	10	434.0614	96.1039	2.16	2.8 x 10 ⁻⁵	7.353	1.628	Bubbler
290	10	170.9563	43.0933	1.90	2.8 x 10 ⁻⁵	2.896	0.730	Bubbler
280	10	32.9988	12.0425	1.31	2.8 x 10 ⁻⁵	0.559	0.204	Bubbler
270	10	9.3861	2.3613	1.90	2.8 x 10 ⁻⁵	0.159	0.040	Bubbler
255	10		0.0590		2.8 x 10 ⁻⁵		0.001	Bubbler
342	20	0.1181	0.6494	0.09	2.8 x 10 ⁻⁵	0.002	0.011	Bubbler
336	20	2.4793	0.6494	1.83	2.8 x 10 ⁻⁵	0.042	0.011	Bubbler
330	20							
324	20	93.3294	24.4392	1.83	2.8 x 10 ⁻⁵	1.581	0.414	Bubbler
318	20	218.2409	45.6907	2.29	2.8 x 10 ⁻⁵	3.697	0.774	Bubbler
312	20	262.1606	61.0980	2.06	2.8 x 10 ⁻⁵	4.441	1.035	Bubbler
306	20	91.7946	23.7898	1.85	2.8 x 10 ⁻⁵	1.555	0.403	Bubbler
300	20	213.8725	42.9752	2.38	2.8 x 10 ⁻⁵	3.623	0.728	Bubbler
294	20	75.5608	22.7863	1.59	2.8 x 10 ⁻⁵	1.280	0.386	Bubbler
288	20	46.3400	11.0980	2.00	2.8 x 10 ⁻⁵	0.785	0.188	Bubbler
282	20	10.8619	2.5384	2.05	2.8 x 10 ⁻⁵	0.184	0.043	Bubbler
276	20	1.5939	0.4132	1.85	2.8 x 10 ⁻⁵	0.027	0.007	Bubbler
270	20	1.4758	0.5903	1.20	2.8 x 10 ⁻⁵	0.025	0.010	Bubbler

^aAnomaly in the concentration measurements: the uranium and fluorine concentration measurements do not monotonically decrease with the crosswind distance.

Table 9 (continued)

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Volumetric Flow Rate (m ³ /s)	Quantity Uranium (mg)	Quantity Fluorine (mg)	Sampler Type
336	40	0.3542	1.4758	0.11	2.8 x 10 ⁻⁵	0.006	0.025	Bubbler
330	40	3.4238	2.1842	0.75	2.8 x 10 ⁻⁵	0.058	0.037	Bubbler
324	40	3.8371	1.5939	1.15	2.8 x 10 ⁻⁵	0.065	0.027	Bubbler
318	40	28.7485	8.5596	1.61	2.8 x 10 ⁻⁵	0.487	0.145	Bubbler
312 ^a	40	46.2810	11.3341	1.96	2.8 x 10 ⁻⁵	0.784	0.192	Bubbler
306	40							
300 ^a	40	92.5620	21.6647	2.05	2.8 x 10 ⁻⁵	1.568	0.367	Bubbler
294	40	29.1617	6.7296	2.08	2.8 x 10 ⁻⁵	0.494	0.114	Bubbler
288	40	16.4109	5.3129	1.48	2.8 x 10 ⁻⁵	0.278	0.090	Bubbler
282	40	3.7190	1.2987	1.37	2.8 x 10 ⁻⁵	0.063	0.022	Bubbler
276	40	0.8264	0.5313	0.75	2.8 x 10 ⁻⁵	0.014	0.009	Bubbler
327	100		0.0542		2.44 x 10 ⁻⁴		0.008	Filter
324	100		0.0883	0.02	3.93 x 10 ⁻⁴	0.001	0.021	Filter
321	100	0.0042	0.2805		2.77 x 10 ⁻⁴		0.047	Filter
318	100		0.7320		1.40 x 10 ⁻⁴		0.062	Filter
315	100	0.0244	0.4593		4.75 x 10 ⁻⁴	0.007	0.132	Filter
312	100	0.1222	0.7933	0.07	7.98 x 10 ⁻⁴	0.059	0.383	Filter
309	100	0.1181	2.9339	0.02	2.80 x 10 ⁻⁴	0.020	0.497	Filter
306	100	1.2193	3.5098	0.17	3.24 x 10 ⁻⁴	0.239	0.688	Filter
303 ^a	100	0.2130	2.8758	0.04	4.19 x 10 ⁻⁴	0.054	0.729	Filter
300	100	0.3624	2.1030	0.08	4.15 x 10 ⁻⁴	0.091	0.528	Filter
297	100	0.0830	1.2589	0.03	7.97 x 10 ⁻⁴	0.040	0.607	Filter
294	100	0.0116	1.1912	0.005	4.26 x 10 ⁻⁴	0.003	0.307	Filter
291	100	0.0175	0.6971	0.01	3.77 x 10 ⁻⁴	0.004	0.159	Filter
288	100	0.0133	0.5310	0.01	2.49 x 10 ⁻⁴	0.002	0.080	Filter
285	100	0.0262	0.3400	0.04	3.16 x 10 ⁻⁴	0.005	0.065	Filter
282	100	0.0157	0.1338	0.06	4.20 x 10 ⁻⁴	0.004	0.034	Filter
279	100	0.0033	0.0457	0.03	5.06 x 10 ⁻⁴	0.001	0.014	Filter
276	100	0.0026	0.0291	0.04	6.24 x 10 ⁻⁴	0.001	0.011	Filter
270	100	0.0029	0.0231	0.06	5.72 x 10 ⁻⁴	0.001	0.008	Filter
312	500		0.1043		2.06 x 10 ⁻⁴		0.013	Filter
306	500	0.0222	0.4770	0.02	1.49 x 10 ⁻⁴	0.002	0.043	Filter
300	500	0.0146	0.3859	0.02	2.27 x 10 ⁻⁴	0.002	0.053	Filter
294	500		0.0988		1.84 x 10 ⁻⁴		0.011	Filter
288	500		0.0113		7.30 x 10 ⁻⁴		0.005	Filter

^aAnomaly in the concentration measurements: the uranium and fluorine concentration measurements do not monotonically decrease with the crosswind distance.

Table 9 (continued)

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Volumetric Flow Rate (m ³ /s)	Quantity Uranium (mg)	Quantity Fluorine (mg)	Sampler Type
312	1000		0.0200		4.96 x 10 ⁻⁴		0.006	Filter
306	1000	0.0014	0.0493	0.01	5.70 x 10 ⁻⁴	0.001	0.017	Filter
300	1000	0.0027	0.0272	0.05	3.64 x 10 ⁻⁴	0.001	0.006	Filter
294	1000							
288	1000							
315	2200		0.0100		9.90 x 10 ⁻⁴		0.006	Filter
300	2200	0.0022	0.0242	0.04	7.50 x 10 ⁻⁴	0.001	0.011	Filter
285	2200		0.0083		6.00 x 10 ⁻⁴		0.003	Filter

Fig. 1. Uranium Concentration (mg/m^3) at Distances of 10, 20, 40, and 100 m

Fig. 2. Fluorine Concentrations (mg/m^3) at Distances of 10, 20, 40, and 100 m

Fig. 3. Uranium Concentrations (mg/m³) at Distances of 500, 1000, and 2200 m

Fig. 4. Fluorine Concentrations (mg/m^3) at Distances of 500, 1000, and 2200 m

Fig. 5. Values of $(114/238) \times (\text{Concentration } U)/(\text{Concentration } F)$ at Distances of 10, 20, 40, and 100 m

Fig. 6. Values of $(114/238) \times (\text{Concentration } U) / (\text{Concentration } F)$ at Distances of 500, 1000, and 2200 m

Fig. 7. Distribution of Normalized Concentration Ratio over the Range 0.5 to 3 Using Integrated Samplers

Fig. 8. Distribution of Normalized Concentration Ratio over the Range of 0.02 to 0.5 using Integrated Samplers

Fig. 9. Variation of Normalized Concentration Ratio as a Function of Uranium Concentration

4.1 Downwind Variation in Uranium and Fluorine Concentrations

The downwind variation in the maximum measured uranium and fluorine concentrations is indicated in Table 10 and on Fig. 10. The maximum concentration information indicates that uranium and fluorine have essentially the same dispersion characteristics between 10 and 40 m. Between 100 and 500 m, the uranium concentrations decrease much more rapidly than do the fluorine concentrations. There are only two known physical mechanisms for this trend: (1) either the uranium disperses faster than the fluorine or (2) uranium has a much higher deposition rate. As will be discussed in Section 7, the deposition rates of both uranium and fluorine were very small during this release. Therefore, the only known mechanism that would cause the maximum uranium concentrations to decrease much more rapidly than the maximum fluorine concentrations between 100 and 500 m is for uranium to disperse at a faster rate. The relative dispersion rates of uranium and fluorine can be compared by computing dispersion coefficients in the crosswind direction based upon the uranium and fluorine concentration profiles.

4.2 Estimation of Crosswind Dispersion Coefficients

The concentration information shown in Table 9 can be used to estimate dispersion coefficients in the crosswind direction if a Gaussian concentration profile is assumed. If a Gaussian concentration profile exists, then

$$C(x,y,z) = C(x,0,z) \times e^{[-0.5y^2/(\sigma_y)^2]},$$

where

$C(x,y,z)$ = concentration at location (x,y,z) ,

$C(x,0,z)$ = centerline concentration,

y = crosswind distance, and

σ_y = dispersion coefficient in the crosswind distance.

Table 11 presents estimated values of σ_y based on the measured uranium and fluorine concentrations at distances of 10, 20, 40, 100, and 500 m. There was insufficient data to "reliably" estimate the σ_y values at distances of 1000 and 2200 m.

Table 10A. Maximum Measured Uranium Concentrations

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	U Concentration/				U Concentration/			
			at 10 m	at 20 m	at 40 m	at 100 m	at 10 m	at 20 m	at 40 m	at 500 m
300 ^a	10	434	1	1.7	4.7	356				19,564
312	20	262	0.60	1	2.8	215				11,816
300	40	93	0.21	0.35	1	76				4,172
306	100	1.22	0.0028	0.0047	0.013	1				55
306	500	0.022	0.000051	0.000085	0.00024	0.018				1

^aThe highest measured uranium concentration at a distance of 10 m was 437.8 g/m³ at an azimuth of 310. Because the uranium concentrations at azimuths of 310 and 300 differ by less than 1% and because the fluorine concentration at an azimuth of 310 is 19% greater than the uranium concentration at an azimuth of 300, an azimuth of 300 will be assumed to be the centerline of the plume at a distance of 10 m.

Table 10B. Maximum Measured Fluorine Concentrations

Azimuth	Distance (m)	Fluorine Concentration (mg/m ³)	F Concentration/				F Concentration/			
			at 10 m	at 20 m	at 40 m	at 100 m	at 10 m	at 20 m	at 40 m	at 500 m
300	10	96	1	1.6	4.4	27				201
312	20	61	0.64	1	2.8	17				128
300	40	22	0.23	0.35	1	6.2				45
306	100	3.5	0.037	0.057	0.16	1				7.4
306	500	0.48	0.0050	0.0078	0.022	0.14				1

Fig. 10. Downwind Variation in Maximum Measured Concentrations

Table 11. Evaluation of Crosswind Concentration Profile Information^a

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	Upwind Distance (m)	Crosswind Distance (m)	U Concentration σ_y from (m)	F Concentration σ_y from (m)	$(\sigma_y)_U/(\sigma_y)_F$
360	10		0.0590	15.00	8.66		2.25	
350	10	0.1771	0.0590	9.13	7.66	1.94	1.99	0.97
340	10	0.2361	0.1181	5.39	6.43	1.66	1.76	0.94
330	10	178.0992	41.9126	2.89	5.00	3.75	3.88	0.97
320	10							
310	10	437.8394	80.9917	0.31	1.74		2.97	
300 ^b	10	434.0614	96.1039	0	0			
290	10	170.9563	43.0933	0.31	1.74	1.27	1.37	0.93
280	10	32.9988	12.0425	1.24	3.42	1.51	1.68	0.90
270	10	9.3861	2.3613	2.89	5.00	1.81	1.84	0.98
255	10		0.0590	7.07	7.07		1.84	
342	20	0.1181	0.6494	5.77	10.00	2.55	3.32	0.77
336	20	2.4793	0.6494	3.62	8.13	2.66	2.70	0.99
330	20							
324	20	93.3294	24.4392	0.88	4.16	2.89	3.07	0.94
318	20	218.2409	45.6907	0.22	2.09	3.45	2.74	1.26
312	20	262.1606	61.0980	0	0			
306	20	91.7946	23.7898	0.22	2.09	1.44	1.52	0.95
300	20	213.8725	42.9752	0.88	4.16	6.52	4.96	1.31
294	20	75.5608	22.7863	2.01	6.18	3.92	4.40	0.89
288	20	46.3400	11.0980	3.62	8.13	4.37	4.40	0.99
282	20	10.8619	2.5384	5.77	10.00	3.96	3.96	1.00
276	20	1.5939	0.4132	8.54	11.76	3.68	3.72	0.99
270	20	1.4758	0.5903	12.05	13.38	4.16	4.39	0.95

^aThe crosswind and upwind distances are calculated assuming that the plume centerline at each radial distance corresponds to the location of maximum measured concentration.

^bThe highest measured uranium concentration at a distance of 10 m was 437.8 g/m³ at an azimuth of 310. Because the uranium concentrations at azimuths of 310 and 300 differ by less than 1% and because the fluorine concentration at an azimuth of 310 is 19% greater than the uranium concentration at an azimuth of 300, an azimuth of 300 will be assumed to be the centerline of the plume at a distance of 10 m.

Table 11 (continued)

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	Upwind Distance (m)	Crosswind Distance (m)	U Concentration (m)	F Concentration (m)	$(\sigma_y)U/(\sigma_y)F$
336	40	0.3542	1.4758	17.08	23.51	7.05	10.14	0.69
330	40	3.4238	2.1842	11.55	20.00	7.79	9.34	0.83
324	40	3.8371	1.5939	7.24	16.27	6.45	7.12	0.91
318	40	28.7485	8.5596	4.02	12.36	8.08	9.07	0.89
312	40	46.2810	11.3341	1.77	8.32	7.06	7.31	0.97
306	40							
300	40	92.5620	21.6647	0	0			
294	40	29.1617	6.7296	0.44	4.18	2.75	2.73	1.01
288	40	16.4109	5.3129	1.77	8.32	4.47	4.96	0.90
282	40	3.7190	1.2987	4.02	12.36	4.88	5.21	0.94
276	40	0.8264	0.5313	7.24	16.27	5.30	5.97	0.89
327	100							
324	100		0.0542	13.76	35.84		12.41	
321	100	0.0042	0.0883	10.04	30.90	9.18	11.39	0.81
318	100		0.2805	6.94	25.88		11.51	
315	100		0.7320	4.42	20.79		11.74	
312	100	0.0244	0.4593	2.48	15.64	5.59	7.76	0.72
309	100	0.1222	0.7933	1.10	10.45	4.87	6.06	0.80
306	100	0.1181	2.9339	0.27	5.23	2.42	8.74	0.28
303	100	1.2193	3.5098	0	0			
300	100	0.2130	2.8758	0.27	5.23	2.80	8.29	0.34
297	100	0.3624	2.1030	1.10	10.45	6.71	10.33	0.65
294	100	0.0830	1.2589	2.48	15.64	6.75	10.92	0.62
291	100	0.0116	1.1912	4.42	20.79	6.82	14.14	0.48
288	100	0.0175	0.6971	6.94	25.88	8.89	14.39	0.62
285	100	0.0133	0.5310	10.04	30.90	10.28	15.90	0.65
282	100	0.0262	0.3400	13.76	35.84	12.93	16.59	0.78
279	100	0.0157	0.1338	18.11	40.67	13.79	15.91	0.87
276	100	0.0033	0.0457	23.13	45.40	13.19	15.41	0.86
270	100	0.0026	0.0291	28.87	50.00	14.28	16.15	0.88
	100	0.0029	0.0231	42.71	58.78	16.90	18.55	0.91
312	500		0.1043	5.49	52.26		29.97	
306	500	0.0222	0.4770	0	0			
300	500	0.0146	0.3859	5.49	52.26	56.96	80.28	0.71
294	500		0.0988	22.10	103.96		58.59	
288	500		0.0113	50.20	154.51		56.49	

In computing the σ_y values presented in Table 11, the location of the maximum concentration was assumed to coincide with the plume centerline, and then the crosswind distance was evaluated. Because of the finite number of samplers, the location corresponding to the maximum measured concentration may not have been the location of the highest concentration.

It should also be noted that the sampler locations are on radial arcs, rather than on straight lines in the crosswind direction. Consequently, the samplers at a given radial distance from the source are at different downwind distances. The values of the crosswind dispersion coefficient, σ_y , will be overestimated because uranium and fluorine concentrations decrease with the downwind distance.

The σ_y information is summarized in Table 12. Beyond 40 m, the estimated values of σ_y obtained from the uranium concentrations are significantly lower than the values of σ_y obtained from the fluorine concentration data. As will be discussed in Section 7, the particle size distribution data indicate that the particles formed from a UF_6 release are approximately 1 to 6 μm in diameter.

Table 12. Summary of Crosswind Concentration Information

Downwind Distance (m)	Mean σ_y from U (m)	Mean σ_y from F (m)	Ratio of Mean σ_y Values	Mean Ratio of σ_y Values
10	1.99	2.17	0.91	0.95
20	3.60	3.56	1.01	1.00
40	5.98	6.87	0.87	0.89
100	9.03	11.74	0.77	0.64
500	56.96	56.33	1.01	0.71

As indicated in Section 4.1, between 100 and 500 m the uranium concentrations decrease much more rapidly than do the fluorine concentrations. It is not possible for the values of σ_y obtained from the uranium concentrations to be lower than the values of σ_y obtained from the fluorine concentration data, if the variation in maximum concentration values is as indicated.

4.3 Error Analysis of Concentration Measurements

As indicated in Section 4.1, the maximum concentration information indicates that uranium and fluorine have similar dispersion characteristics between 10 and 40 m. However, between 100 and 500 m the uranium concentrations decrease much more rapidly than do the fluorine concentrations. As noted in Section 4.2, the estimated values of σ_y obtained from the uranium concentrations are consistently lower than the values of σ_y obtained from the fluorine concentration data.

Because the deposition rates of both uranium and fluorine during this release were very small, there is a contradiction between the observed variation in maximum downwind concentrations and the relative magnitudes in the uranium and fluorine σ_y values.

Experimental error could account for both the observed variation in maximum downwind concentrations and the relative magnitudes in the uranium and fluorine σ_y values. The particle size measurements (see Section 7) indicate that the hydrolysis product, UO_2F_2 , was present in the form of small particles on the order of 1 to 6 μm in diameter. Although some of the HF could have been in the liquid state, the majority of the hydrogen fluoride was believed to be in the gaseous state. If an experimental problem resulted in a low estimate of the amount of UO_2F_2 present, then the "unexplainable" variation in maximum downwind concentrations and the relative magnitudes in the uranium and fluorine σ_y values can be explained. Let,

C_U = measured uranium concentration,

C_F = measured fluorine concentration, and

$$R = (114/238)C_U/C_F.$$

Then the amount of measured fluorine present in the UO_2F_2 is $(38/238)C_U$, and the amount of measured fluorine present in HF is $C_F - (38/238)C_U$. If the amount of UO_2F_2 is underestimated by a factor of "n," then the value of $n(114/238)(C_U)/[C_F + (n - 1)(38/238)C_U]$ should equal 1.0. Rearranging $n(114/238)(C_U)/[C_F + (n - 1)(38/238)C_U] = 1$, yields $n = (1.5/R) - 0.5$. Therefore, the adjusted estimate of the uranium concentration, is then $C_U[(1.5/R) - 0.5]$, and the adjusted estimate of the fluorine concentration is $[C_F + (n - 1)(38/238)C_U]$.

Adjusted values of the measured uranium and fluorine concentrations are presented in Tables 13 and 14 and on Fig. 11. Estimates of σ_y using the adjusted concentration values are presented in Tables 15 and 16.

If the experimental errors in measuring the uranium concentrations and the errors in measuring the fluorine concentrations result in overestimation of both quantities, then it is not possible to estimate the error from the concentration data. However, if it is assumed that the dispersion characteristics of uranium and fluorine are identical and if at a given location the experimental error in measuring the uranium concentrations is assumed equal to -1 times the error in measuring the fluorine concentration, an estimate of the error can be obtained.

Assume $(114/238) \times (\text{concentration U})/(\text{concentration F})$ equals 1.0 and let

$$R1 = (114/238) \times (\text{concentration U})/(\text{concentration F}),$$

$$R2 = 1/R1,$$

RMAX = maximum of $R1$ or $R2$, and

$$RMAX = (1 + \epsilon)/(1 - \epsilon).$$

Then the value of RMAX indicates the factor by which one of the concentration measurements may be in error and the value of ϵ indicates the magnitude of the error if both concentration measurements have an error of ϵ .

The information presented in Table 17 indicates that, if the experimental errors in measuring the uranium and fluorine concentrations are equal in magnitude at a given location, then the error in the concentration measurements is typically 25 to 35% at downwind distance of 10, 20 or 40 m. Beyond 40 m, the ϵ values indicate much larger errors. As indicated above, it is believed that experimental difficulties resulted in significant errors in estimating the UO_2F_2 concentrations at distance beyond 40 m.

If only one of the uranium and fluorine concentrations measurements are in error, then the error in the concentration measurements (i.e., the value of RMAX) is typically a factor of 2 to 3 at downwind distance of 10, 20 or 40 m. Beyond 40 m, the RMAX values indicate much larger errors.

Table 13. Adjusted Uranium and Fluorine Concentration Measurements

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
360	10		0.0590		1			0.0590
350	10	0.1771	0.0590	1.4370	1	1	0.1771	0.0590
340	10	0.2361	0.1181	0.9580	1	1	0.2361	0.1181
330	10	178.0992	41.9126	2.04	1	1	178.0992	41.9126
320	10							
310	10	437.8394	80.9917	2.5894	1	1	437.8394	30.9917
300 ^a	10	434.0614	96.1039	2.1634	1	1	434.0614	96.1039
290	10	170.9563	43.0933	1.9002	1	1	170.9563	43.0933
280	10	32.9988	12.0425	1.3125	1	1	32.9988	12.0425
270	10	9.3861	2.3613	1.9040	1	1	9.3861	2.3613
255	10		0.0590		1		0.0590	
342	20	0.1181	0.6494	0.0871	16.7	1.5	1.9745	0.9458
336	20	2.4793	0.6494	1.8289	1	1	2.4793	0.6494
330	20							
324	20	93.3294	24.4392	1.8292	1	1	93.3294	24.4392
318	20	218.2409	45.6907	2.2879	1	1	218.2409	45.6907
312	20	262.1606	61.0980	2.0553	1	1	262.1606	61.0980
306	20	91.7946	23.7898	1.8482	1	1	91.7946	23.7898
300	20	213.8725	42.9752	2.3838	1	1	213.8725	42.9752
294	20	75.5608	22.7863	1.5884	1	1	75.5608	22.7863
288	20	46.3400	11.0980	2.0000	1	1	46.3400	11.0980
282	20	10.8619	2.5384	2.0496	1	1	10.8619	2.5384
276	20	1.5939	0.4132	1.8475	1	1	1.5939	0.4132
270	20	1.4758	0.5903	1.1975	1	1	1.4758	0.5903

^aAnomaly in the uranium and fluorine concentration measurements. The uranium and fluorine concentration measurements do not monotonically decrease with the crosswind distance.

Table 13 (continued)

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
336	40	0.3542	1.4758	0.1150	12.5	1.4	4.4445	2.1289
330	40	3.4238	2.1842	0.7509	1.5	1.1	5.1280	2.4563
324	40	3.8371	1.5939	1.1531	1	1	3.8371	1.5339
318	40	28.7485	8.5596	1.6088	1	1	28.7485	8.5596
312 ^a	40	46.2810	11.3341	1.9559	1	1	46.2810	11.3341
306	40							
300 ^a	40	92.5620	21.6647	2.0465	1	1	92.5620	21.6647
294	40	29.1617	6.7296	2.0756	1	1	29.1617	6.7296
288	40	16.4109	5.3129	1.4796	1	1	16.4109	5.3129
282	40	3.7190	1.2987	1.3717	1	1	3.7190	1.2987
276	40	0.8264	0.5313	0.7451	1	1	0.8264	0.5313
327	100		0.0542		1		0.0542	
324	100	0.0042	0.0883	0.0228	65.3	1.5	0.2745	0.1315
321	100		0.2805		1		0.2805	
318	100		0.7320		1		0.7320	
315	100	0.0244	0.4593		1	1	0.0244	0.4593
312	100	0.1222	0.7933				2.4232	1.1607
309	100	0.1181	2.9339	0.0193	77.3	1.5	9.1287	4.3726
306	100	1.2193	3.5098	0.1664	8.5	1.4	10.3817	4.9728
303 ^a	100	0.2130	2.8758	0.0355	41.8	1.5	8.8993	4.2627
300	100	0.3624	2.1030	0.0826	17.7	1.5	6.4044	3.0676
297	100	0.0830	1.2589	0.0316	47.0	1.5	3.9007	1.8684
294	100	0.0116	1.1912	0.0047	320.0	1.5	3.7244	1.7840
291	100	0.0175	0.6971	0.0121	124.0	1.5	2.1743	1.0415
288	100	0.0133	0.5310	0.0120	124.8	1.5	1.6564	0.7934
285	100	0.0262	0.3400	0.0368	40.2	1.5	1.6516	0.5037
282	100	0.0157	0.1338	0.0564	26.1	1.5	0.4112	0.1969
279	100	0.0033	0.0457	0.0342	43.3	1.5	0.1416	0.0678
276	100	0.0026	0.0291	0.0435	33.9	1.5	0.0899	0.0431
270	100	0.0029	0.0231	0.0599	24.6	1.5	0.0709	0.0340

^aAnomaly in the uranium and fluorine concentration measurements. The uranium and fluorine concentration measurements do not monotonically decrease with the crosswind distance.

Table 13 (continued)

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
312	500		0.1043		1			0.1043
306	500	0.0222	0.4770	0.0223	66.8	1.5	1.4827	0.7102
300	500	0.0146	0.3859	0.0181	82.5	1.5	1.2013	0.5754
294	500		0.0988		1			0.0988
288	500		0.0112		1			0.0113
312	1000		0.0200		1			0.0200
306	1000	0.0014	0.0493	0.0141	106.0	1.5	0.1537	0.0736
300	1000	0.0027	0.0272	0.0479	30.8	1.5	0.0840	0.0402
294	1000							
288	1000							
315	2200		0.0100		1			0.0100
300	2200	0.0022	0.0242	0.0435	33.9	1.5	0.0748	0.0358
285	2200		0.0083		1			0.0083

Table 14A. Maximum Measured Adjusted Uranium Concentrations

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)		U Concentration/ U Concentration at 10 m		U Concentration/ U Concentration at 20 m		U Concentration/ U Concentration at 40 m		U Concentration/ U Concentration at 100 m		U Concentration/ U Concentration at 500 m	
		U Concentration	(mg/m ³)	U Concentration	U Concentration	U Concentration	U Concentration	U Concentration	U Concentration	U Concentration	U Concentration	U Concentration	U Concentration
300 ^a	10	434		1		1.7		4.7		42		293	
312	20	262		0.60		1		2.8		25		177	
300	40	93		0.21		0.35		1		9		62	
306	100	10.38		0.040		0.04		0.11		1		7.0	
306	500	1.483		0.016		0.006		0.016		0.14		1	

^aThe highest measured uranium concentration at a distance of 10 m was 437.8 g/m³ at an azimuth of 310. Because the uranium concentrations at azimuths of 310 and 300 differ by less than 1% and because the fluorine concentration at an azimuth of 310 is 19% greater than the uranium concentration at an azimuth of 300, an azimuth of 300 will be assumed to be the centerline of the plume at a distance of 10 m.

Table 14B. Maximum Measured Adjusted Fluorine Concentrations

Azimuth	Distance (m)	Fluorine Concentration (mg/m ³)		F Concentration/ F Concentration at 10 m		F Concentration/ F Concentration at 20 m		F Concentration/ F Concentration at 40 m		F Concentration/ F Concentration at 100 m		F Concentration/ F Concentration at 500 m	
		F Concentration	(mg/m ³)	F Concentration	F Concentration	F Concentration	F Concentration	F Concentration	F Concentration	F Concentration	F Concentration	F Concentration	F Concentration
300	10	96		1		1.6		4.4		19		135	
312	20	61		0.64		1		2.8		12		86	
300	40	22		0.23		0.35		1		4.4		31	
306	100	5.0		0.052		0.081		0.23		1		7	
306	500	0.71		0.0074		0.0116		0.033		0.14		1

Fig. 11. Downwind Variation in Maximum Adjusted Concentrations

Table 15. Evaluation of Adjusted Crosswind Concentration Profile Information^a

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	Upwind Distance (m)	Crosswind Distance (m)	U Concentration (m)	σ_y from F Concentration (m)	σ_y from $(\sigma_y)_U/(\sigma_y)_F$ (m)
360	10		0.0590	15.00	8.66		2.25	
350	10	0.1771	0.0590	9.13	7.66	1.94	1.99	0.97
340	10	0.2361	0.1181	5.39	6.43	1.66	1.76	0.94
330	10	178.0992	41.9126	2.89	5.00	3.75	3.88	0.97
320	10							
310	10	437.8394	80.9917	0.31	1.74		2.97	
300 ^b	10	434.0614	96.1039	0	0			
290	10	170.9563	43.0933	0.31	1.74	1.27	1.37	0.93
280	10	32.9988	12.0425	1.24	3.42	1.51	1.68	0.90
270	10	9.3861	2.3613	2.89	5.00	1.81	1.84	0.98
255	10							
342	20	1.9745	0.9458	5.77	10.00	3.20	3.46	0.92
336	20	2.4793	0.6494	3.62	8.13	2.66	2.70	0.99
330	20							
324	20	93.3294	24.4392	0.88	4.16	2.89	3.07	0.94
318	20	218.2409	45.6907	0.22	2.09	3.45	2.74	1.26
312	20	262.1606	61.0980	0	0			
306	20	91.7946	23.7898	0.22	2.09	1.44	1.52	0.95
300	20	213.8725	42.9752	0.88	4.16	6.52	4.96	1.31
294	20	75.5608	22.7863	2.01	6.18	3.92	4.40	0.89
288	20	46.3400	11.0980	3.62	8.13	4.37	4.40	0.99
282	20	10.8619	2.5384	5.77	10.00	3.96	3.96	1.00
276	20	1.5939	0.4132	8.54	11.76	3.68	3.72	0.99
270	20	1.4758	0.6734	12.05	13.38	4.16	4.46	0.95

^aThe crosswind and upwind distances are calculated assuming that the plume centerline at each radial distance corresponds to the location of maximum measured concentration.

^bThe highest measured uranium concentration at a distance of 10 m was 437.8 g/m³ at an azimuth of 310. Because the uranium concentrations at azimuths of 310 and 300 differ by less than 1% and because the fluorine concentration at an azimuth of 310 is 19% greater than the uranium concentration at an azimuth of 300, an azimuth of 300 will be assumed to be the centerline of the plume at a distance of 10 m.

Table 15 (continued)

Azimuth	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	Upwind Distance (m)	Crosswind Distance (m)	U Concentration (m)	F Concentration (m)	σ_y from $(\sigma_y)_U/(\sigma_y)_F$
336	40	4.4445	2.1289	17.08	23.51	9.54	10.91	0.87
330	40	5.1280	2.4563	11.55	20.00	8.31	9.58	0.87
324	40	3.8371	1.5939	7.24	16.27	6.45	7.12	0.91
318	40	28.7485	8.5596	4.02	12.36	8.08	9.07	0.89
312	40	46.2810	11.3341	1.77	8.32	7.06	7.31	0.97
306	40							
300	40	92.5620	21.6647	0	0			
294	40	29.1617	6.7296	0.44	4.18	2.75	2.73	1.01
288	40	16.4109	5.3129	1.77	8.32	4.47	4.96	0.90
282	40	3.7190	1.2987	4.02	12.36	4.88	5.21	0.94
276	40	0.8264	0.5313	7.24	16.27	5.30	5.97	0.89
327	100		0.0542	13.76	35.84		11.92	
324	100	0.2745	0.1315	10.04	30.90	11.46	11.46	1.00
321	100		0.2805	6.94	25.88		10.79	
318	100		0.7320	4.42	20.79		10.62	
315	100	0.0244	0.4593	2.48	15.64	4.50	7.17	0.63
312	100	2.4232	1.1607	1.10	10.45	6.13	6.13	1.00
309	100	9.1287	4.3726	0.27	5.23	10.32	10.32	1.00
306	100	10.3817	4.9728	0	0			
303	100	8.8993	4.2627	0.27	5.23	9.43	9.43	1.00
300	100	6.4044	3.0676	1.10	10.45	10.63	10.63	1.00
297	100	3.9007	1.8684	2.48	15.64	11.18	11.18	1.00
294	100	3.7244	1.7840	4.42	20.79	14.52	14.52	1.00
291	100	2.1743	1.0415	6.94	25.88	14.64	14.64	1.00
288	100	1.6564	0.7934	10.04	30.90	16.13	16.13	1.00
285	100	1.0516	0.5037	13.76	35.84	16.75	16.75	1.00
282	100	0.4112	0.1969	18.11	40.67	16.01	16.01	1.00
279	100	0.1416	0.0678	23.13	45.40	15.49	15.49	1.00
276	100	0.0899	0.0431	28.87	50.00	16.22	16.22	
270	100	0.0709	0.0340	42.71	58.78	18.61	18.61	1.00
312	500		0.1043	5.49	52.26		26.68	
306	500	1.4827	0.7102	0	0			
300	500	1.2013	0.5754	5.49	52.26	80.55	80.55	1.00
294	500		0.0988	22.10	103.96		52.34	
288	500		0.0113	50.20	154.51		53.70	

Table 16. Summary of Adjusted Crosswind
Concentration Information

Downwind Distance (m)	σ_y from U (m)	σ_y from F (m)	Ratio of Mean σ_y Values	Mean Ratio of σ_y Values
10	1.99	1.97	1.01	0.95
20	3.66	3.58	1.02	1.02
40	6.32	6.99	0.90	0.91
100	12.80	11.85	1.08	0.91
500	80.55	53.32	1.51	1.00

Table 17. Estimation of Experimental Error in Concentration Measurements^a

	R1	RMAX	ϵ
Downwind Distance, 10 m			
Average	1.79	1.8	0.26
Minimum	0.96	1.0	0.021
Maximum	2.59	2.6	0.44
Downwind Distance, 20 m			
Average	1.8	2.7	0.35
Minimum	0.087	1.2	0.09
Maximum	2.4	11	0.84
Downwind Distance, 40 m			
Average	1.3	2.3	0.28
Minimum	0.11	1.2	0.071
Maximum	2.1	8.7	0.79
Downwind Distance, 100 m			
Average	0.05	45	0.91
Minimum	0.005	6	0.71
Maximum	0.17	210	0.99
Downwind Distance, 500 m			
Average	0.020	50	0.96
Minimum	0.018	45	0.96
Maximum	0.022	55	0.96
Downwind Distance, 1000 m			
Average	0.031	46	0.94
Minimum	0.014	21	0.91
Maximum	0.048	71	0.97
Downwind Distance, 2200 m			
Average	0.044	23	0.92
Minimum	0.044	23	0.92
Maximum	0.044	23	0.92
Downwind Distances, 10, 20, 40, 100, 500, and 2200 m			
Average	0.65	31	0.68
Minimum	0.005	1	0.021
Maximum	2.59	210	0.99

$$^a R1 = (114/238) \times (\text{concentration } U) / (\text{concentration } F)$$

$$RMAX = \text{maximum of } R1 \text{ or } 1/R1$$

$$RMAX = (1 + \epsilon) / (1 - \epsilon)$$

5. Measurements Using Sequential Samplers

Measurements made using the sequential samplers included the distance from the source, the azimuth, the elevation, the duration of the sample, the volumetric flow rate, the quantity uranium collected, and the quantity fluorine collected. Filter samplers were used to collect uranium and fluorine.

The sequential samplers began collecting material when the release was initiated (i.e., at $H = 0$ min). Each sampler assembly consisted of 8 samplers. Sampler 0 collected material for 14 min, and samplers 1 through 7 collected material sequentially for 2-min intervals as indicated in Table 18.

Table 18. Sample Intervals of Sequential Samplers

Sampler No.	Start Time (min)	End Time (min)
0	H	H + 14
1	H	H + 2
2	H + 2	H + 4
3	H + 4	H + 6
4	H + 6	H + 8
5	H + 8	H + 10
6	H + 10	H + 12
7	H + 12	H + 14

Estimates of uranium and fluorine concentrations, which were obtained using the data from the sequential samplers, are presented in Table 19. It should be noted that the concentration estimates represent mean concentrations over the sample interval. If the plume residence time at a given location is less than the sample interval, then the average plume concentrations may differ significantly from the estimated concentrations.

The plume residence time at a sampler location is a function of the time for the plume to travel downwind to the sampler location. The travel time to 20 m is approximately 3.6 s, and the travel time to 40 m is approximately 7 s. Because there is only a small error in neglecting the

Table 19. Uranium and Fluorine Concentration Measurements Using Sequential Samplers^a

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Conc. (mg/m ³)		Fluorine Conc. (mg/m ³)		F Conc. / U Conc.		[(U Conc.)/(U Mean)] / [(F Conc.)/(F Mean)]		Flow Rate (l/min)	Duration (min)	Quantity Uranium (mg)	Quantity Fluorine (mg)	
				Conc.	Mean	Conc.	Mean	F Conc.	U Conc.	Conc. F	Conc. U/					
0	292.5	1	20	63.71	1.00	30.47	1.00	1.00	1.00	1.00	1.00	5.72	14	5.102	2.440	
1	292.5	1	20	178.80	2.81	77.90	2.56	1.10	1.10	1.10	1.10	5.00	2	1.788	0.779	
2	292.5	1	20	69.00	1.08	36.00	1.18	0.92	0.92	0.92	0.92	5.00	2	0.690	0.360	
3	292.5	1	20	49.10	0.77	23.40	0.77	1.01	1.01	1.00	1.00	5.00	2	0.491	0.234	
4	292.5	1	20	117.40	1.84	60.60	1.99	0.93	0.93	0.93	0.93	5.00	2	1.174	0.606	
5	292.5	1	20	117.40	1.84	60.50	1.99	0.93	0.93	0.93	0.93	5.00	2	1.174	0.605	
6	292.5	1	20	19.20	0.30	56.00	1.84	0.16	0.16	Anomaly	Anomaly	5.00	2	0.192	0.560	
7	292.5	1	20	4.80	0.08	12.40	0.41	0.19	0.19	Anomaly	Anomaly	5.00	2	0.048	0.124	
Average of Samplers 1-7				79.39	1.25	46.69	1.53	0.81	0.75							
0	292.5	3	20	43.52	1.00	19.18	1.00	1.09	1.09	1.00	1.00	5.92	14	3.607	1.590	
1	292.5	3	20	129.70	2.98	53.10	2.77	1.17	1.17	1.08	1.08	5.00	2	1.297	0.531	
2	292.5	3	20	56.50	1.30	23.40	1.22	1.16	1.16	1.06	1.06	5.00	2	0.565	0.234	
3	292.5	3	20	58.30	1.34	21.80	1.14	1.28	1.28	1.18	1.18	5.00	2	0.583	0.218	
4	292.5	3	20	103.20	2.37	43.40	2.26	1.14	1.14	1.05	1.05	5.00	2	1.032	0.434	
5	292.5	3	20	92.00	2.11	40.80	2.13	1.08	1.08	0.99	0.99	5.00	2	0.920	0.408	
6	292.5	3	20	26.50	0.61	9.00	0.47	1.41	1.41	1.30	1.30	5.00	2	0.265	0.090	
7	292.5	3	20	4.50	0.10	2.90	0.15	0.74	0.74	0.68	0.68	5.00	2	0.045	0.029	
Average of Samplers 1-7				67.24	1.55	27.77	1.45	1.16	1.05							
0	292.5	8	20	3.60	1.00	1.35	1.00	1.28	1.28	1.00	1.00	5.84	14	0.294	0.110	
1	292.5	8	20	9.90	2.75	4.20	3.12	1.13	1.13	0.88	0.88	5.00	2	0.099	0.042	
2	292.5	8	20	1.20	0.33	1.00	0.74	0.57	0.57	Anomaly	Anomaly	5.00	2	0.012	0.010	
3	292.5	8	20	1.40	0.39	1.00	0.74	0.67	0.67	0.52	0.52	5.00	2	0.014	0.010	
4	292.5	8	20	7.30	2.03	3.30	2.45	1.06	1.06	0.83	0.83	5.00	2	0.073	0.033	
5	292.5	8	20	8.40	2.34	3.40	2.53	1.18	1.18	0.92	0.92	5.00	2	0.084	0.034	
6	292.5	8	20	0.40	0.11	0.60	0.45	0.32	0.32	Anomaly	Anomaly	5.00	2	0.004	0.006	
7	292.5	8	20	0.40	0.11	0.50	0.37	0.38	0.38	Anomaly	Anomaly	5.00	2	0.004	0.005	
Average of Samplers 1-7				4.14	1.15	2.00	1.49	0.99	0.59							

^aAn anomaly is indicated if the ratio of (uranium concentration)/(mean uranium concentration) to (fluorine concentration)/(mean fluorine concentration) is less than 0.5 or greater than 2.

Table 19 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Conc. (mg/m ³)	U Conc. Mean	Fluorine Conc. (mg/m ³)	F Conc. Mean	Conc. U/ Conc. F	[(U Conc.)/(U Mean)]/ [(F Conc.)/(F Mean)]	Flow Rate (l/min)	Duration (min)	Quantity Uranium (mg)	Quantity Fluorine (mg)
0	315	1	20	237.15	1.00	104.96	1.00	1.08	1.00	5.73	14	19.024	8.420
1	315	1	20	199.20	0.84	80.80	0.77	1.18	1.09	5.00	2	1.992	0.808
2	315	1	20	377.40	1.59	159.00	1.51	1.14	1.05	5.00	2	3.774	1.590
3	315	1	20	330.00	1.39	157.00	1.50	1.01	0.93	5.00	2	3.300	1.570
4	315	1	20	312.70	1.32	134.00	1.28	1.12	1.03	5.00	2	3.127	1.340
5	315	1	20	296.00	1.25	107.00	1.02	1.33	1.22	5.00	2	2.960	1.070
6	315	1	20	51.60	0.22	17.20	0.16	1.44	1.33	5.00	2	0.516	0.172
7	315	1	20	7.50	0.03	3.70	0.04	0.97	0.90	5.00	2	0.075	0.037
Average of Samplers 1-7				224.91	0.95	94.10	0.90	1.14	1.08				
0	315	3	20	90.64	1.00	58.28	1.00	0.74	1.00	5.54	14	7.030	4.520
1	315	3	20	105.50	1.16	32.30	0.55	1.56	2.10	Anomaly	2	1.055	0.323
2	315	3	20	175.00	1.93	66.50	1.14	1.26	1.69	5.00	2	1.750	0.665
3	315	3	20	160.60	1.77	64.70	1.11	1.19	1.60	5.00	2	1.606	0.647
4	315	3	20	165.00	1.82	68.20	1.17	1.16	1.56	5.00	2	1.650	0.682
5	315	3	20	215.90	2.38	90.50	1.55	1.14	1.53	5.00	2	2.159	0.905
6	315	3	20	17.10	0.19	7.80	0.13	1.05	1.41	5.00	2	0.171	0.078
7	315	3	20	7.60	0.08	5.70	0.10	0.64	0.86	5.00	2	0.076	0.057
Average of Samplers 1-7				120.96	1.33	47.96	0.82	1.21	1.53				
0	315	8	20	6.00	1.00	2.40	1.00	1.20	1.00	5.44	14	0.457	0.183
1	315	8	20	2.10	0.35	1.10	0.46	0.91	0.76	5.00	2	0.021	0.011
2	315	8	20	7.50	1.25	2.60	1.08	1.38	1.16	5.00	2	0.075	0.026
3	315	8	20	3.00	0.50	1.40	0.58	1.03	0.86	5.00	2	0.030	0.014
4	315	8	20	22.50	3.75	4.00	1.66	2.69	2.25	Anomaly	2	0.225	0.040
5	315	8	20	9.30	1.55	3.70	1.54	1.20	1.01	5.00	2	0.093	0.037
6	315	8	20	2.00	0.33	1.10	0.46	0.87	0.73	5.00	2	0.020	0.011
7	315	8	20	1.50	0.25	1.00	0.42	0.72	0.60	5.00	2	0.015	0.010
Average of Samplers 1-7 0.5 or greater than 2.				6.84	1.14	2.13	0.89	1.54	1.05				

Table 19 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Conc. (mg/m ³)		Fluorine Conc. (mg/m ³)		F Conc./U Conc. (114/238)		[(U Conc.)/(U Mean)]/[(F Conc.)/(F Mean)]		Flow Rate (l/min)	Duration (min)	Quantity (mg)	
				U Conc. Mean	U Conc.	Fluorine Conc. Mean	Fluorine Conc.	Mean F Conc.	Conc. U/Conc. F					Uranium	Fluorine
0	337.5	1	20	3.51	1.00	2.03	1.00	1.00	0.83	1.00	1.56	5.59	14	0.275	0.159
1	337.5	1	20	4.60	1.31	1.70	0.84	1.30	1.30	1.56	1.56	5.00	2	0.046	0.017
2	337.5	1	20	2.30	0.65	1.10	0.54	1.00	1.00	1.21	1.21	5.00	2	0.023	0.011
3	337.5	1	20	6.10	1.74	1.60	0.79	1.83	1.83	2.20	Anomaly	5.00	2	0.061	0.016
4	337.5	1	20	11.90	3.39	3.00	1.48	1.90	1.90	2.29	Anomaly	5.00	2	0.119	0.030
5	337.5	1	20	0.80	0.23	1.10	0.54	0.35	0.35	0.42	Anomaly	5.00	2	0.008	0.011
6	337.5	1	20	0.10	0.03	0.70	0.34	0.07	0.07	0.08	Anomaly	5.00	2	0.001	0.007
7	337.5	1	20			0.60	0.30					5.00	2	0.001	0.006
Average of Samplers 1-7				4.30	1.22	1.40	0.75	1.47	1.47	1.30					
0	337.5	3	20	0.97	1.00	0.41	1.00	1.00	1.12	1.00	0.68	5.01	14	0.068	0.029
1	337.5	3	20	5.90	6.09	3.70	8.95	0.76	0.76	1.00	0.68	5.00	2	0.059	0.037
2	337.5	3	20	0.40	0.41	0.50	1.21	0.38	0.38	0.34	Anomaly	5.00	2	0.004	0.005
3	337.5	3	20	0.70	0.72	0.50	1.21	0.67	0.67	0.60	0.60	5.00	2	0.007	0.005
4	337.5	3	20	3.40	3.51	1.20	2.90	1.36	1.36	1.21	1.21	5.00	2	0.034	0.012
5	337.5	3	20	0.20	0.21	0.40	0.97	0.24	0.24	0.21	Anomaly	5.00	2	0.002	0.004
6	337.5	3	20	0.04	0.04	0.50	1.21	0.04	0.04	0.03	Anomaly	5.00	2	0.0004	0.005
7	337.5	3	20	0.04	0.04	0.30	0.73	0.06	0.06	0.06	Anomaly	5.00	2	0.0004	0.003
Average of Samplers 1-7				1.53	1.57	1.01	2.45	0.72	0.72	0.45					
0	337.5	8	20	0.56	1.00	0.31	1.00	1.00	0.86	1.00	1.00	5.46	14	0.043	0.024
1	337.5	8	20	0.06	0.11	0.30	0.96	0.10	0.10	0.11	Anomaly	5.00	2	0.001	0.003
2	337.5	8	20	0.03	0.05	0.30	0.96	0.05	0.05	0.06	Anomaly	5.00	2	0.0003	0.003
3	337.5	8	20	0.03	0.05	0.30	0.96	0.05	0.05	0.06	Anomaly	5.00	2	0.0003	0.003
4	337.5	8	20	2.30	4.09	0.70	2.23	1.57	1.57	1.83	Anomaly	5.00	2	0.023	0.007
5	337.5	8	20	0.03	0.05	0.40	1.27	0.04	0.04	0.04	Anomaly	5.00	2	0.0003	0.004
6	337.5	8	20	0.01	0.02	0.30	0.96	0.02	0.02	0.02	Anomaly	5.00	2	0.0001	0.003
7	337.5	8	20	0.05	0.09	0.40	1.27	0.06	0.06	0.07	Anomaly	5.00	2	0.001	0.004
Average of Samplers 1-7				0.36	0.64	0.39	1.23	0.45	0.45	0.31					

Table 19 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium		Fluorine		F Conc./ (114/238)		[(U Conc.)/(U Mean)]/ [(F Conc.)/(F Mean)]	Flow Rate (l/min)	Duration (min)	Quantity	
				Conc. (mg/m ³)	Mean U Conc.	Conc. (mg/m ³)	Mean F Conc.	Conc. U/ Conc. F	Uranium (mg)				Fluorine (mg)	
0	292.5	1	40	25.37	1.00	9.49	1.00	1.28	1.00	5.76	14	2.046	0.765	
1	292.5	1	40											
2	292.5	1	40	61.80	2.44	21.90	2.31	1.35	1.06	5.00	2	0.618	0.219	
3	292.5	1	40	14.40	0.57	7.40	0.78	0.93	0.73	5.00	2	0.144	0.074	
4	292.5	1	40	37.00	1.46	13.90	1.47	1.28	1.00	5.00	2	0.370	0.139	
5	292.5	1	40	37.00	1.46	14.90	1.57	1.19	0.93	5.00	2	0.370	0.149	
6	292.5	1	40	4.80	0.19	3.50	0.37	0.66	0.51	5.00	2	0.048	0.035	
7	292.5	1	40	1.90	0.07	2.10	0.22	0.43	0.34	Anomaly	2	0.019	0.021	
Average of Samplers 1-7				26.15	1.03	10.62	1.12	1.18	0.76					
0	292.5	3	40	17.79	1.00	7.86	1.00	1.08	1.00	5.69	14	1.417	0.626	
1	292.5	3	40	54.70	3.08	18.80	2.39	1.39	1.29	5.00	2	0.547	0.188	
2	292.5	3	40	23.10	1.30	8.20	1.04	1.35	1.24	5.00	2	0.231	0.082	
3	292.5	3	40	13.50	0.76	5.50	0.70	1.18	1.08	5.00	2	0.135	0.055	
4	292.5	3	40	27.10	1.52	9.70	1.23	1.34	1.23	5.00	2	0.271	0.097	
5	292.5	3	40	19.00	1.07	7.80	0.99	1.17	1.08	5.00	2	0.190	0.078	
6	292.5	3	40	12.40	0.70	4.90	0.62	1.21	1.12	5.00	2	0.124	0.049	
7	292.5	3	40	13.60	0.76	5.10	0.65	1.28	1.18	5.00	2	0.136	0.051	
Average of Samplers 1-7				23.34	1.31	8.57	1.09	1.30	1.17					
0	292.5	8	40	5.33	1.00	1.82	1.00	1.41	1.00	6.02	14	0.449	0.153	
1	292.5	8	40	25.50	4.79	7.00	3.86	1.74	1.24	5.00	2	0.255	0.070	
2	292.5	8	40	2.40	0.45	1.80	0.99	0.64	Anomaly	5.00	2	0.024	0.018	
3	292.5	8	40	4.00	0.75	2.90	1.60	0.66	0.47	Anomaly	2	0.040	0.029	
4	292.5	8	40	9.50	1.78	4.00	2.20	1.14	0.81	5.00	2	0.095	0.040	
5	292.5	8	40	4.20	0.79	2.90	1.60	0.69	0.49	Anomaly	2	0.042	0.029	
6	292.5	8	40	0.70	0.13	1.40	0.77	0.24	0.17	Anomaly	2	0.007	0.014	
7	292.5	8	40	0.40	0.08	0.90	0.50	0.21	0.15	Anomaly	2	0.004	0.009	
Average of Samplers 1-7				6.67	1.25	2.99	1.64	1.07	0.54					

Table 19 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium		Fluorine		(114/238)		[(U Conc.)/(U Mean)]/[(F Conc.)/(F Mean)]	Flow Rate (l/min)	Duration (min)	Quantity	
				Conc. ₂ (mg/m ³)	Mean U Conc.	Conc. (mg/m ³)	Mean F Conc.	Conc. U/ Conc. F	Uranium (mg)				Fluorine (mg)	
0	315	1	40	62.27	1.00	30.43	1.00	0.98	1.00	6.08	14	5.300	2.590	
1	315	1	40	51.50	0.83	17.90	0.59	1.38	1.41	5.00	2	0.515	0.179	
2	315	1	40	109.60	1.76	44.30	1.46	1.19	1.21	5.00	2	1.096	0.443	
3	315	1	40	116.80	1.88	48.70	1.60	1.15	1.17	5.00	2	1.168	0.487	
4	315	1	40	78.80	1.27	30.00	0.99	1.26	1.28	5.00	2	0.788	0.300	
5	315	1	40	78.20	1.26	30.30	1.00	1.24	1.26	5.00	2	0.782	0.303	
6	315	1	40	13.50	0.22	7.40	0.24	0.87	0.89	5.00	2	0.135	0.074	
7	315	1	40	2.30	0.04	2.80	0.09	0.39	0.40	Anomaly	2	0.023	0.028	
Average of Samplers 1-7				64.39	1.03	25.91	0.85	1.19	1.09					
0	315	3	40	43.63	1.00	20.22	1.00	1.03	1.00	5.37	14	3.280	1.520	
1	315	3	40	35.70	0.82	1.00	0.05	17.10	16.54	Anomaly	2	0.357	0.010	
2	315	3	40	83.10	1.90	27.00	1.34	1.47	1.43	5.00	2	0.831	0.270	
3	315	3	40	80.80	1.85	26.00	1.29	1.49	1.44	5.00	2	0.808	0.260	
4	315	3	40	63.10	1.45	21.60	1.07	1.40	1.35	5.00	2	0.631	0.216	
5	315	3	40	87.40	2.00	27.90	1.38	1.50	1.45	5.00	2	0.874	0.279	
6	315	3	40	8.10	0.19	5.20	0.26	0.75	0.72	5.00	2	0.081	0.052	
7	315	3	40	2.00	0.05	2.30	0.11	0.42	0.40	Anomaly	2	0.020	0.023	
Average of Samplers 1-7				51.46	1.18	15.86	0.78	1.55	3.33					
0	315	8	40	6.44	1.00	2.44	1.00	1.28	1.00	5.06	14	0.456	0.170	
1	315	8	40	2.80	0.43	1.30	0.54	1.03	0.80	5.00	2	0.028	0.013	
2	315	8	40	8.20	1.27	3.80	1.58	1.03	0.80	5.00	2	0.082	0.038	
3	315	8	40	5.80	0.90	2.20	0.92	1.26	0.98	5.00	2	0.058	0.022	
4	315	8	40	21.40	3.32	5.90	2.46	1.74	1.35	5.00	2	0.214	0.059	
5	315	8	40	13.80	2.14	8.00	3.33	0.83	0.64	5.00	2	0.138	0.080	
6	315	8	40	1.20	0.19	0.70	0.82	0.82	0.64	5.00	2	0.012	0.007	
7	315	8	40	1.40	0.22	2.50	1.04	0.27	0.21	5.00	2	0.014	0.025	
Average of Samplers 1-7				7.80	1.21	3.49	1.45	1.07	0.78	Anomaly				
0	315	15	40	0.06		0.04		0.80	0.80	5.59	14	0.005	0.003	
0	337.5	1	40	0.50		0.18		1.37	1.37	5.67	14	0.040	0.014	
0	337.5	3	40	0.34		0.17		0.96	0.96	5.86	14	0.028	0.014	
0	337.5	8	40	0.50		0.22		1.07	1.07	5.47	14	0.038	0.017	

travel time, the travel time was neglected in developing the concentration estimates presented in Table 19.

Because $(114/238)$ times (concentration U)/(concentration F) is greater than 3, which is not possible, an anomaly in the concentration measurements occurs at a radial distance of 40 m, a height of 3 m, and an azimuth of 315. An anomaly is also indicated if the ratio of [(uranium concentration)/(mean uranium concentration)] to [(fluorine concentration)/(mean fluorine concentration)] is believed to be in "error" by a factor of 2 (i.e., if it is either less than 0.5 or greater than 2).

5.1 Estimation of Experimental Error

Experimental error may result from either uncertainties associated with the hardware or from uncertainties associated with the chemical analyses. The uncertainty associated with the hardware is approximately 6.5%. Quantification of the uncertainty in the chemical analyses follows.

Examination of the data in Table 19 indicates that at 14 locations data were available for sampler 0 and for samplers 1 through 7. If there were no experimental error, the uranium and fluorine concentrations obtained from the sampler 0 data should exactly equal the uranium and fluorine concentrations obtained from the data for samplers 1 through 7. The concentration estimates shown in Table 19 indicate a mean average error in the uranium and fluorine concentrations of 26 and 52%, respectively.

If the experimental errors in measuring the uranium concentrations and the errors in measuring the fluorine concentrations result in overestimates of both quantities, then it is not possible to estimate the error from the concentration data. However, if it is assumed that the dispersion characteristics of uranium and fluorine are identical and if at a given location the experimental error in measuring the uranium concentrations is assumed equal to -1 times the error in measuring the fluorine concentration, an estimate of the error can be obtained.

Let,

$$R1 = (114/238) \times (\text{concentration U})/(\text{concentration F}),$$

$$R2 = 1/R1, \text{ and}$$

$$R = \text{maximum of } R1 \text{ and } R2.$$

Then,

$$R = (1 + \epsilon)/(1 - \epsilon)$$

and

$$\epsilon = (R - 1)/(R + 1).$$

The mean, maximum, and minimum values of the quantity $(114/238) \times (\text{concentration U})/(\text{concentration F})$ were 1.11, 0.02, and 17.1, respectively. The mean value of ϵ was estimated to be 22%.

If it is assumed that the dispersion characteristics of uranium and fluorine are identical and if at a given location the experimental error in measuring the uranium concentration or the error in measuring the fluorine concentration is exactly zero, then an additional estimate of the error can be obtained by equating ϵ' to R . The mean value of ϵ' was estimated to be 322%. Therefore, it is concluded that the errors in the data may result in the concentration estimates being in error by a factor of 3.22.

As noted in Section 3.1, a value of the quantity $(114/238) \times (\text{concentration U})/(\text{concentration F})$ greater than 3 indicates experimental error in measuring the uranium and/or the fluorine concentration. Values of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ are shown on Fig. 12. The relationship between the estimated uranium concentrations and the value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ values is shown on Fig 13.

Examination of the data presented on Figs. 12 and 13 indicates that the distribution of the $(114/238) \times (\text{concentration U})/(\text{concentration F})$ values appears to be randomly distributed around 1, except at low uranium concentrations. Random error in the measurements would result in the a mean value of 1.0, with the values being randomly distributed about the mean. As noted in Section 4.3, it is believed that experimental error resulted in a low estimate of the amount of UO_2F_2 present, which yielded values of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ less than 1. The adjusted uranium concentration was estimated to be $C_U[(1.5/R) - 0.5]$, and the adjusted fluorine concentration estimate was $[C_F - (n - 1)(38/238)C_U]$.

Fig. 12. Distribution of Normalized Concentration Ratio over the Range 0.5 to 3 using Sequential Samplers

Fig. 13. Variation of Normalized Concentration Ratio as a Function of Uranium Concentration Measured by Sequential Samplers

Where, C_U is the measured uranium concentration and C_F is the measured fluorine concentration.

Adjusted estimates of uranium and fluorine concentrations, which were obtained using the data from the sequential samplers, are presented in Table 20. A summary of uranium and fluorine concentrations obtained using the data from the sequential samplers is shown in Table 21.

5.2 Variation in Concentration as a Function of Time

The UF_6 release was initiated at the same time that samplers 0 and 1 were initiated, and the release was terminated 5 s after sampling was initiated with sampler 6. Plume residence time at a sampler location is a function of the time for the plume to travel downwind to the sampler location. The travel time to 20 m is approximately 3.6 s, and the travel time to 40 m is approximately 7 s. Therefore, it would be expected that the concentration measurements for samplers 0 and 1 would be slightly underestimated if the travel time was neglected. The concentration measurements at each location for sampler 6 would be approximately 10% of the average concentration for samplers 1 through 5, and the concentration measurements for sampler 7 would be zero. It would also be expected that at each location the concentrations measured by sampler 0 would be approximately 10/14 times the average concentrations of samplers 1 through 5.

The concentration data taken with the sequential samplers show significant concentrations during the time intervals 10 to 12 min and 12 to 14 min. This result is surprising; the concentration should have dropped to zero shortly after the release was terminated. After the valve was closed to terminate the release, the release ended within a few seconds.

5.3 Estimation of Vertical Dispersion Coefficients

The concentration information shown in Tables 19 and 20 can be used to estimate dispersion coefficients in the vertical direction if a Gaussian concentration profile is assumed. If a Gaussian concentration profile exists, then

Table 20. Adjusted Sequential Uranium and Fluorine Concentration Measurements

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
0	292.5	1	20	63.71	30.47	1.00	1	1	63.71	30.47
1	292.5	1	20	178.80	77.90	1.10	1	1	178.80	77.90
2	292.5	1	20	69.00	36.00	0.92	1.13	1.04	78.24	37.47
3	292.5	1	20	49.10	23.40	1.01	1	1	49.10	23.40
4	292.5	1	20	117.40	60.60	0.93	1.12	1.04	131.07	62.78
5	292.5	1	20	117.40	60.50	0.93	1.11	1.04	130.76	62.63
6	292.5	1	20	19.20	56.00	0.16	8.63	1.42	165.77	79.40
7	292.5	1	20	4.8	12.40	0.19	7.59	1.41	36.43	17.45
Average of Samplers 1-7				79.39	46.69	0.81			110.02	51.58
0	292.5	3	20	43.52	19.18	1.09	1	1	43.52	19.18
1	292.5	3	20	129.70	53.10	1.17	1	1	129.70	53.10
2	292.5	3	20	56.50	23.40	1.16	1	1	56.50	23.40
3	292.5	3	20	58.30	21.80	1.28	1	1	58.30	21.80
4	292.5	3	20	103.20	43.40	1.14	1	1	103.20	43.40
5	292.5	3	20	92.00	40.80	1.08	1	1	92.00	40.80
6	292.5	3	20	26.50	9.00	1.41	1	1	26.50	9.00
7	292.5	3	20	4.50	2.90	0.74	1.52	1.13	6.83	3.27
Average of Samplers 1-7				67.24	27.77	1.16			67.58	27.82
0	292.5	8	20	3.60	1.35	1.28	1	1	3.60	1.35
1	292.5	8	20	9.90	4.20	1.13	1	1	9.90	4.20
2	292.5	8	20	1.20	1.00	0.57	2.11	1.21	2.53	1.21
3	292.5	8	20	1.40	1.00	0.67	1.74	1.16	2.43	1.16
4	292.5	8	20	7.30	3.30	1.06	1	1	7.30	3.30
5	292.5	8	20	8.40	3.40	1.18	1	1	8.40	3.40
6	292.5	8	20	0.40	0.60	0.32	4.20	1.34	1.68	0.80
7	292.5	8	20	0.40	0.50	0.38	3.41	1.31	1.37	0.65
Average of Samplers 1-7				4.14	2.00	0.99			4.80	2.11

Table 20 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
0	315	1	20	237.15	104.96	1.08	1	1	237.15	104.96
1	315	1	20	199.20	80.80	1.18	1	1	199.20	80.80
2	315	1	20	377.40	159.00	1.14	1	1	377.40	159.00
3	315	1	20	330.00	157.00	1.01	1	1	330.00	157.00
4	315	1	20	312.70	134.00	1.12	1	1	312.70	134.00
5	315	1	20	296.00	107.00	1.33	1	1	296.00	107.00
6	315	1	20	51.60	17.20	1.44	1	1	51.60	17.20
7	315	1	20	7.50	3.70	0.97	1.04	1.01	7.84	3.75
Average of Samplers 1-7				224.91	94.10	1.14			224.96	94.11
0	315	3	20	90.64	58.28	0.74	1.51	1.13	137.18	65.71
1	315	3	20	105.50	32.30	1.56	1	1	105.50	32.30
2	315	3	20	175.00	61.0	1.26	1	1	175.00	66.50
3	315	3	20	160.60	64.70	1.19	1	1	160.60	64.70
4	315	3	20	165.00	68.20	1.16	1	1	165.00	68.20
5	315	3	20	215.90	90.50	1.14	1	1	215.90	90.50
6	315	3	20	17.10	7.80	1.05	1	1	17.10	7.80
7	315	3	20	7.60	5.70	0.64	1.85	1.18	14.05	6.73
Average of Samplers 1-7				120.96	47.96	1.21			121.88	48.10
0	315	8	20	6.00	2.40	1.20	1	1	6.00	2.40
1	315	8	20	2.10	1.10	0.91	1.14	1.04	2.39	1.15
2	315	8	20	7.50	2.60	1.38	1	1	7.50	2.60
3	315	8	20	3.00	1.40	1.03	1	1	3.00	1.40
4	315	8	20	22.50	4.00	2.69	1	1	22.50	4.00
5	315	8	20	9.30	3.70	1.20	1	1	9.30	3.70
6	315	8	20	2.00	1.10	0.87	1.22	1.06	2.44	1.17
7	315	8	20	1.50	1.00	0.72	1.59	1.14	2.38	1.14
Average of Samplers 1-7				6.84	2.13	1.54			7.07	2.17

Table 20 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
0	337.5	1	20	3.51	2.03	0.83	1.31	1.09	4.61	2.21
1	337.5	1	20	4.60	1.70	1.30	1	1	4.60	1.70
2	337.5	1	20	2.30	1.10	1.00	1	1	2.30	1.10
3	337.5	1	20	6.10	1.60	1.83	1	1	6.10	1.60
4	337.5	1	20	11.90	3.00	1.90	1	1	11.90	3.00
5	337.5	1	20	0.80	1.10	0.35	3.81	1.33	3.04	1.46
6	337.5	1	20	0.10	0.70	0.07	21.42	1.47	2.14	1.03
7	337.5	1	20	4.30	0.60	0.00			5.01	0.60
Average of Samplers 1-7										
0	337.5	3	20	0.97	0.41	1.12	1	1	0.97	0.41
1	337.5	3	20	5.90	3.70	0.76	1.46	1.12	8.64	4.14
2	337.5	3	20	0.40	0.50	0.38	3.41	1.31	1.37	0.65
3	337.5	3	20	0.70	0.50	0.67	1.74	1.16	1.22	0.58
4	337.5	3	20	3.40	1.20	1.36	1	1	3.40	1.20
5	337.5	3	20	0.20	0.40	0.24	5.76	1.38	1.15	0.55
6	337.5	3	20	0.04	0.50	0.04	38.64	1.48	1.55	0.74
7	337.5	3	20	0.04	0.30	0.06	22.99	1.47	0.92	0.44
Average of Samplers 1-7										
0	337.5	8	20	0.56	0.31	0.86	1.25	1.07	0.70	0.34
1	337.5	8	20	0.06	0.30	0.10	15.16	1.45	0.91	0.44
2	337.5	8	20	0.03	0.30	0.05	30.82	1.48	0.92	0.44
3	337.5	8	20	0.03	0.30	0.05	30.82	1.48	0.92	0.44
4	337.5	8	20	2.30	0.70	1.57	1	1	2.30	0.70
5	337.5	8	20	0.03	0.40	0.04	41.25	1.48	1.24	0.59
6	337.5	8	20	0.01	0.30	0.02	93.45	1.49	0.93	0.45
7	337.5	8	20	0.05	0.40	0.06	24.55	1.47	1.23	0.59
Average of Samplers 1-7										
				0.36	0.39	0.45			1.21	0.52

Table 20 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/Concentration F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
0	292.5	1	40	25.37	9.49	1.28	1	1	25.37	9.49
1	292.5	1	40							
2	292.5	1	40	61.80	21.90	1.35	1	1	61.80	21.90
3	292.5	1	40	14.40	7.40	0.93	1.11	1.03	15.97	7.65
4	292.5	1	40	37.00	13.90	1.28	1	1	37.00	13.90
5	292.5	1	40	37.00	14.90	1.19	1	1	37.00	14.90
6	292.5	1	40	4.80	3.50	0.66	1.78	1.17	8.56	4.10
7	292.5	1	40	1.90	2.10	0.43	2.96	1.28	5.63	2.69
Average of Samplers 1-7				26.15	10.62	1.18			27.66	10.86
0	292.5	3	40	17.79	7.86	1.08	1	1	17.79	7.86
1	292.5	3	40	54.70	18.80	1.39	1	1	54.70	18.80
2	292.5	3	40	23.10	8.20	1.35	1	1	23.10	8.20
3	292.5	3	40	13.50	5.50	1.18	1	1	13.50	5.50
4	292.5	3	40	27.10	9.70	1.34	1	1	27.10	9.70
5	292.5	3	40	19.00	7.80	1.17	1	1	19.00	7.80
6	292.5	3	40	12.40	4.90	1.21	1	1	12.40	4.90
7	292.5	3	40	13.60	5.10	1.28	1	1	13.60	5.10
Average of Samplers 1-7				23.34	8.57	1.30			23.34	8.57
0	292.5	8	40	5.33	1.82	1.41	1	1	5.33	1.82
1	292.5	8	40	25.50	7.00	1.74	1	1	25.50	7.00
2	292.5	8	40	2.40	1.80	0.64	1.85	1.18	4.44	2.13
3	292.5	8	40	4.00	2.90	0.66	1.77	1.17	7.08	3.39
4	292.5	8	40	9.50	4.00	1.14	1	1	9.50	4.00
5	292.5	8	40	4.20	2.90	0.69	1.66	1.15	6.98	3.34
6	292.5	8	40	0.70	1.40	0.24	5.76	1.38	4.03	1.93
7	292.5	8	40	0.40	0.90	0.21	6.55	1.39	2.62	1.25
Average of Samplers 1-7				6.67	2.99	1.07			8.59	3.29

Table 20 (continued)

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/ Concentration F	Uranium Adjustment Factor	Fluorine Adjustment Factor	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
0	315	1	40	62.27	30.43	0.98	1.03	1.01	64.15	30.73
1	315	1	40	51.50	17.90	1.38	1	1	51.50	17.90
2	315	1	40	109.60	44.30	1.19	1	1	109.60	44.30
3	315	1	40	116.80	48.70	1.15	1	1	116.80	48.70
4	315	1	40	78.80	30.00	1.26	1	1	78.80	30.00
5	315	1	40	78.20	30.30	1.24	1	1	78.20	30.30
6	315	1	40	13.50	7.40	0.87	1.22	1.06	16.42	7.87
7	315	1	40	2.30	2.80	0.39	3.31	1.30	7.62	3.65
Average of Samplers 1-7				64.39	25.91	1.19			65.56	26.10
0	315	3	40	43.63	20.22	1.03	1	1	43.63	20.22
1	315	3	40	35.70	1.00	17.10	1	1	35.70	1.00
2	315	3	40	83.10	27.00	1.47	1	1	83.10	27.00
3	315	3	40	80.80	26.00	1.49	1	1	80.80	26.00
4	315	3	40	63.10	21.60	1.40	1	1	63.10	21.60
5	315	3	40	87.40	27.90	1.50	1	1	87.40	27.90
6	315	3	40	8.10	5.20	0.75	1.51	1.13	12.23	5.86
7	315	3	40	2.00	2.30	0.42	3.10	1.29	6.20	2.97
Average of Samplers 1-7				51.46	15.86	1.55			52.65	16.05
0	315	8	40	6.44	2.40	1.28	1	1	2.40	1.28
1	315	8	40	2.80	1.30	1.03	1	1	2.80	1.30
2	315	8	40	8.20	3.80	1.03	1	1	8.20	3.80
3	315	8	40	5.80	2.20	1.26	1	1	5.80	2.20
4	315	8	40	21.40	5.90	1.74	1	1	21.40	5.90
5	315	8	40	13.80	2.14	8.0	0.83	1.32	18.15	8.69
6	315	8	40	1.20	0.70	0.82	1.33	1.09	1.59	0.76
7	315	8	40	1.40	2.50	0.27	5.09	1.37	7.13	3.41
Average of Samplers 1-7				7.80	3.49	1.07			9.30	3.72
0	315	15	40	0.06	0.04	0.80	1.38	1.10	0.09	0.04
0	337.5	1	40	0.50	0.18	1.37	1	1	0.50	0.18
0	337.5	3	40	0.34	0.17	0.96	1.07	1.02	0.36	0.17
0	337.5	8	40	0.50	0.22	1.07	1	1	0.50	0.22

Table 21. Summary of Sequential Uranium and Fluorine Concentration Measurements

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/Concentration F	Adjusted Uranium Concentration (mg/m ³)	Adjusted Fluorine Concentration (mg/m ³)
0	292.5	1	20	63.71	30.47	1.00	63.71	30.47
Average of Samplers 1-7				80.01	46.69	0.82	109.71	51.43
0	292.5	3	20	43.52	19.18	1.09	43.52	19.18
Average of Samplers 1-7				67.24	27.77	1.16	67.58	27.82
0	292.5	8	20	3.60	1.35	1.28	3.60	1.35
Average of Samplers 1-7				4.14	2.00	0.99	4.80	2.11
0	315	1	20	237.15	104.96	1.08	237.15	104.96
Average of Samplers 1-7				224.91	94.10	1.14	224.96	94.11
0	315	3	20	90.64	58.28	0.74	137.18	65.71
Average of Samplers 1-7				120.96	47.96	1.21	121.88	48.10
0	315	8	20	6.00	2.40	1.20	6.00	2.40
Average of Samplers 1-7				6.84	2.13	1.54	7.07	2.17
0	337.5	1	20	3.51	2.03	0.83	4.61	2.21
Average of Samplers 1-7				4.30	1.40	1.47	5.01	1.50
0	337.5	3	20	0.97	0.41	1.12	0.97	0.41
Average of Samplers 1-7				1.53	1.01	0.72	2.61	1.19
0	337.5	8	20	0.56	0.31	0.86	0.70	0.34
Average of Samplers 1-7				0.36	0.39	0.45	1.21	0.52
0	292.5	1	40	25.37	9.49	1.28	25.37	9.49
Average of Samplers 1-7				26.15	10.62	1.18	27.66	10.86
0	292.5	3	40	17.79	7.86	1.08	17.79	7.86
Average of Samplers 1-7				23.34	8.57	1.30	23.34	8.57
0	292.5	8	40	5.33	1.82	1.41	5.33	1.82
Average of Samplers 1-7				6.67	2.99	1.07	8.59	3.29
0	315	1	40	62.27	30.43	0.98	64.15	30.73
Average of Samplers 1-7				64.39	25.91	1.19	65.56	26.10
0	315	3	40	43.63	20.22	1.03	43.63	20.22
Average of Samplers 1-7				51.46	15.86	1.55	52.65	16.05
0	315	8	40	6.44	2.40	1.28	6.44	2.40
Average of Samplers 1-7				7.80	3.49	1.07	9.30	3.72
0	315	15	40	0.06	0.04	0.80	0.09	0.04
0	337.5	1	40	0.50	0.18	1.37	0.50	0.18
0	337.5	3	40	0.34	0.17	0.96	0.36	0.17
0	337.5	8	40	0.50	0.22	1.07	0.50	0.22

$$C(x,y,z) = C(x,y) \times \{e^{[-0.5 \times (h - z)^2/(\sigma_z)^2]} + e^{[-0.5 \times (h + z)^2/(\sigma_z)^2]}\},$$

where

$C(x,y,z)$ = concentration at location (x,y,z) ,

$C(x,y)$ = centerline concentration at elevation z ,

h = vertical distance from the plume centerline, and

σ_z = dispersion coefficient in the vertical direction.

Tables 22 through 25 present estimated values of the vertical dispersion coefficient, σ_z , and the plume centerline elevation, h . It should be noted that solutions for σ_z and h could not be found at all locations. A summary of the data in Tables 22 through 25 is provided in Table 26.

Examination of the data shown in Table 26 indicates that the σ_z values obtained from uranium and fluorine concentrations are in reasonably good agreement. The data seem to indicate a centerline height of 2.4 to 2.6 m at a downwind distance of 20 m and a centerline height of 2.4 to 3.3 m at a downwind distance of 40 m. The value of σ_z is apparently 2.4 m at a distance of 20 m and 2.6 to 3.2 m at a distance of 40 m.

The σ_z values obtained from uranium concentrations are lower than the values of σ_z obtained from fluorine concentrations. It is not known whether the relatively low σ_z values obtained from uranium concentrations are a result of a low estimate of UO_2F_2 concentrations or whether HF disperses more rapidly than UO_2F_2 .

6. Comparison of Concentration Measurements Using Continuous and Sequential Samplers

The sequential concentrations were determined using an assumed sample duration of 14 min, while the continuous concentrations were determined using a sample duration equal to the release duration of 605 s. Therefore, if there were no experimental error, the ratio of the sequential concentration to the continuous concentration should be approximately 1.33 ($60 \times 14/605$).

It is possible to compare the concentration measurements obtained using the continuous and the sequential samplers at five locations. A comparison

Table 22. Evaluation of Vertical Uranium Concentration Profile Information

Sampler No.	Azimuth	Distance (m)	Uranium Concentration			Uranium Concentration		(U Conc. at 3m)/ (U Conc. at 1m)	Uranium Concentration		(U Conc. at 8m)/ (U Conc. at 1m)	Centerline Height (m)	σ_z (m)
			at 1 m (mg/m ³)	at 3 m (mg/m ³)	at 8 m (mg/m ³)	at 1 m (mg/m ³)	at 3 m (mg/m ³)		at 1 m (mg/m ³)	at 3 m (mg/m ³)			
0	292.5	20	63.71	43.52	3.60	0.6831	0.0564		0.6831	0.0564		1.77	2.81
1	292.5	20	178.80	129.70	9.90	0.7254	0.0554		0.7254	0.0554		2.15	2.10
2	292.5	20	69.00	56.50	1.20	0.8188	0.0174		0.8188	0.0174		2.70	1.94
3	292.5	20	49.10	58.30	1.40	1.1874	0.0285		1.1874	0.0285		2.45	2.43
4	292.5	20	117.40	103.20	7.30	0.8790	0.0622		0.8790	0.0622		2.14	2.74
5	292.5	20	117.40	92.00	8.40	0.7836	0.0716		0.7836	0.0716		2.78	1.80
6	292.5	20	19.20	26.50	0.40	1.3802	0.0208		1.3802	0.0208		2.65	2.46
7	292.5	20	4.80	4.50	0.40	0.9375	0.0833		0.9375	0.0833			
0	315	20	237.15	90.64	6.00	0.3822	0.0253		0.3822	0.0253			
1	315	20	199.20	105.50	2.10	0.5296	0.0105		0.5296	0.0105			
2	315	20	377.40	175.00	7.50	0.4637	0.0199		0.4637	0.0199			
3	315	20	330.00	160.60	3.00	0.4867	0.0091		0.4867	0.0091			
4	315	20	312.70	165.00	22.50	0.5277	0.0720		0.5277	0.0720			
5	315	20	296.00	215.90	9.30	0.7294	0.0314		0.7294	0.0314		1.91	2.44
6	315	20	51.60	17.10	2.00	0.3314	0.0388		0.3314	0.0388		3.14	2.77
7	315	20	7.50	7.60	1.50	1.0133	0.2000		1.0133	0.2000			
0	337.5	20	3.51	0.97	0.56	0.2759	0.1601		0.2759	0.1601		2.64	1.77
1	337.5	20	4.60	5.90	0.06	1.2826	0.0130		1.2826	0.0130			
2	337.5	20	2.30	0.40	0.03	0.1739	0.0130		0.1739	0.0130			
3	337.5	20	6.10	0.70	0.03	0.1148	0.0049		0.1148	0.0049			
4	337.5	20	11.90	3.40	2.30	0.2857	0.1933		0.2857	0.1933			
5	337.5	20	0.80	0.20	0.03	0.2500	0.0375		0.2500	0.0375			
6	337.5	20	0.10	0.04	0.01	0.4000	0.1000		0.4000	0.1000			
7	337.5	20											
0	292.5	40	25.37	17.79	5.33	0.7011	0.2100		0.7011	0.2100		3.19	3.29
1	292.5	40	61.80	23.10	2.40	0.3738	0.0388		0.3738	0.0388			
2	292.5	40	14.40	13.50	4.00	0.9375	0.2778		0.9375	0.2778			
3	292.5	40	37.00	27.10	9.50	0.7324	0.2568		0.7324	0.2568			
4	292.5	40	37.00	19.00	4.20	0.5135	0.1135		0.5135	0.1135		3.67	1.79
5	292.5	40	4.80	12.40	0.70	2.5833	0.1458		2.5833	0.1458		4.05	1.44
6	292.5	40	1.90	13.60	0.40	7.1579	0.2105		7.1579	0.2105			
7	292.5	40											
0	315	40	62.27	43.63	6.44	0.7007	0.1034		0.7007	0.1034		1.00	3.13
1	315	40	51.50	35.70	2.80	0.6932	0.0544		0.6932	0.0544		1.96	2.89
2	315	40	109.60	83.10	8.20	0.7548	0.0748		0.7548	0.0748		1.32	2.96
3	315	40	116.80	80.80	5.80	0.6918	0.0497		0.6918	0.0497			
4	315	40	78.80	63.10	21.40	0.8008	0.2716		0.8008	0.2716		3.20	2.53
5	315	40	78.20	87.40	13.80	1.1176	0.1765		1.1176	0.1765			
6	315	40	13.50	8.10	1.20	0.6000	0.0889		0.6000	0.0889			
7	315	40	2.30	2.00	1.40	0.5696	0.6087		0.5696	0.6087			

Table 23. Evaluation of Vertical Fluorine Concentration Profile Information

Sampler No.	Azimuth	Distance (m)	Fluorine Concentration		Fluorine Concentration at 8 m (mg/m ³)	(F Conc. at 3m)/ (F Conc. at 1m)	(F Conc. at 8m)/ (F Conc. at 1m)	Centerline Height (m)	σ _z (m)
			at 1 m (mg/m ³)	at 3 m (mg/m ³)					
0	292.5	20	30.47	19.18	1.35	0.6296	0.0442		
1	292.5	20	77.90	53.10	4.20	0.6816	0.0539	1.31	2.68
2	292.5	20	36.00	23.40	1.00	0.6500	0.0278	2.48	2.23
3	292.5	20	23.40	21.80	1.00	0.9316	0.0427	1.67	2.85
4	292.5	20	60.60	43.40	3.30	0.7162	0.0545		
5	292.5	20	60.50	40.80	3.40	0.6744	0.0562		
6	292.5	20	56.00	9.00	0.60	0.1607	0.0107		
7	292.5	20	12.40	2.90	0.50	0.2339	0.0403		
0	315	20	104.96	58.28	2.40	0.5552	0.0229		
1	315	20	80.80	32.30	1.10	0.3998	0.0136		
2	315	20	159.00	66.50	2.60	0.4182	0.0164		
3	315	20	157.00	64.70	1.40	0.4121	0.0089		
4	315	20	134.00	68.20	4.00	0.5090	0.0299		
5	315	20	107.00	90.50	3.70	0.8458	0.0346	2.28	2.27
6	315	20	17.20	7.80	1.10	0.4535	0.0640		
7	315	20	3.70	5.70	1.00	1.5405	0.2703	3.68	2.30
0	337.5	20	2.03	0.41	0.31	0.2035	0.1545		
1	337.5	20	1.70	3.70	0.30	2.1765	0.1765	3.66	1.92
2	337.5	20	1.10	0.50	0.30	0.4545	0.2727		
3	337.5	20	1.60	0.50	0.30	0.3125	0.1875		
4	337.5	20	3.00	1.20	0.70	0.4000	0.2333		
5	337.5	20	1.10	0.40	0.40	0.3636	0.3636		
6	337.5	20	0.70	0.50	0.30	0.7143	0.4286		
7	337.5	20							
0	292.5	40	9.49	7.86	1.82	0.8284	0.1914	2.30	3.62
1	292.5	40							
2	292.5	40	21.90	8.20	1.80	0.3744	0.0822		
3	292.5	40	7.40	5.50	2.90	0.7432	0.3919		
4	292.5	40	13.90	9.70	4.00	0.6978	0.2878		
5	292.5	40	14.90	7.80	2.90	0.5235	0.1946		
6	292.5	40	3.50	4.90	1.40	1.4000	0.4000	3.89	2.56
7	292.5	40	2.10	5.10	0.90	2.4286	0.4286	4.08	2.03
0	315	40	30.43	20.22	2.40	0.6645	0.0789		
1	315	40	17.90	1.00	1.30	0.0559	0.0726		
2	315	40	44.30	27.00	3.80	0.6095	0.0858		
3	315	40	48.70	26.00	2.20	0.5339	0.0452		
4	315	40	30.00	21.60	5.90	0.7200	0.1967		
5	315	40	30.30	27.90	8.00	0.9208	0.2640	2.85	2.88
6	315	40	7.40	5.20	0.70	0.7027	0.0946		
7	315	40	2.80	2.30	2.50	0.8214	0.8929		

Table 24. Evaluation of Adjusted Vertical Uranium Concentration Profile Information

Sampler No.	Azimuth	Distance (m)	Uranium Concentration			Uranium Concentration at 8 m		(U Conc. at 3m)/ (U Conc. at 1m)		Centerline Height (m)	σ_z (m)
			at 1 m (mg/m ³)	at 3 m (mg/m ³)	at 8 m (mg/m ³)	at 3 m (mg/m ³)	at 8 m (mg/m ³)				
0	292.5	20	63.71	43.52	3.60	0.6831	0.0564			1.77	2.81
1	292.5	20	178.80	129.70	9.90	0.7254	0.0554			1.88	2.47
2	292.5	20	78.24	56.50	2.53	0.7222	0.0324			2.82	2.06
3	292.5	20	49.10	58.30	2.43	1.1874	0.0495			2.16	2.57
4	292.5	20	131.07	103.20	7.30	0.7873	0.0557				
5	292.5	20	130.76	92.00	8.40	0.7036	0.0642				
6	292.5	20	165.77	26.50	1.68	0.1599	0.0101				
7	292.5	20	36.43	6.83	1.37	0.1875	0.0375				
0	315	20	237.15	137.18	6.00	0.5785	0.0253				
1	315	20	199.20	105.50	2.39	0.5296	0.0120				
2	315	20	377.40	175.00	7.50	0.4637	0.0199				
3	315	20	330.00	160.60	3.00	0.4867	0.0091				
4	315	20	312.70	165.00	22.50	0.5277	0.0720				
5	315	20	296.00	215.90	9.30	0.7294	0.0314			1.91	2.44
6	315	20	51.60	17.10	2.44	0.3314	0.0474				
7	315	20	7.84	14.05	2.38	1.7928	0.3039			3.81	2.18
0	337.5	20	4.61	0.97	0.70	0.2105	0.1524				
1	337.5	20	4.60	8.64	0.91	1.8776	0.1977				
2	337.5	20	2.30	1.37	0.92	0.5938	0.4019			3.63	2.04
3	337.5	20	6.10	1.22	0.92	0.1993	0.1516				
4	337.5	20	11.90	3.40	2.30	0.2857	0.1933				
5	337.5	20	3.04	1.15	1.24	0.3786	0.4065				
6	337.5	20	2.14	1.55	0.93	0.7216	0.4362				
7	337.5	20									
0	292.5	40	25.37	17.79	5.33	0.7011	0.2100				
1	292.5	40	61.80	23.10	4.44	0.3738	0.0718				
2	292.5	40	15.97	13.50	7.08	0.8451	0.4433				
3	292.5	40	37.00	27.10	9.50	0.7324	0.2568				
4	292.5	40	37.00	19.00	6.98	0.5135	0.1887				
5	292.5	40	8.56	12.40	4.03	1.4485	0.4713			4.03	2.59
6	292.5	40	5.63	13.60	2.62	2.4172	0.4654			4.12	2.05
7	292.5	40									
0	315	40	64.15	43.63	6.44	0.6801	0.1003				
1	315	40	51.50	35.70	2.80	0.6932	0.0544			1.00	3.13
2	315	40	109.60	83.10	8.20	0.7582	0.0748			1.96	2.89
3	315	40	116.80	80.80	5.80	0.6918	0.0497			1.32	2.96
4	315	40	78.80	63.10	21.40	0.8008	0.2716				
5	315	40	78.20	87.40	18.15	1.1176	0.2321			3.35	2.66
6	315	40	16.42	12.23	1.59	0.7449	0.0969			1.08	3.51
7	315	40	7.62	6.20	7.13	0.8142	0.9358				

Table 25. Evaluation of Adjusted Vertical Fluorine Concentration Profile Information

Sampler No.	Azimuth	Distance (m)	Fluorine		Fluorine		Fluorine		Centerline Height (m)	Height (m)	oz (m)
			Concentration (mg/m ³)	at 1 m (mg/m ³)	Concentration (mg/m ³)	at 3 m (mg/m ³)	Concentration (mg/m ³)	at 8 m (mg/m ³)	(F Conc. at 3m)/ (F Conc. at 1m)	(F Conc. at 8m)/ (F Conc. at 1m)	
0	292.5	20	30.47	19.18	1.35	0.6296	0.0442				
1	292.5	20	77.90	53.10	4.20	0.6816	0.0539				
2	292.5	20	37.47	23.40	1.21	0.6324	0.0324			2.51	2.28
3	292.5	20	23.40	21.80	1.16	0.9316	0.0498			1.08	3.09
4	292.5	20	62.78	43.40	3.30	0.6913	0.0526				
5	292.5	20	62.63	40.80	3.40	0.6514	0.0543				
6	292.5	20	79.40	9.00	0.80	0.1133	0.0101				
7	292.5	20	17.45	3.27	0.65	0.1875	0.0375				
0	315	20	104.96	65.71	2.40	0.6260	0.0229		1.05	2.70	
1	315	20	80.80	32.30	1.15	0.3998	0.0142				
2	315	20	159.00	66.50	2.60	0.4182	0.0164				
3	315	20	157.00	64.70	1.40	0.4121	0.0089				
4	315	20	134.00	68.20	4.00	0.5090	0.0299				
5	315	20	107.00	90.50	3.70	0.8458	0.0346		2.28	2.27	
6	315	20	17.20	7.80	1.17	0.4535	0.0681				
7	315	20	3.75	6.73	1.14	1.7928	0.3039		3.81	2.18	
0	337.5	20	2.21	0.41	0.34	0.1874	0.1524				
1	337.5	20	1.70	4.14	0.44	2.4335	0.2563		3.85	1.92	
2	337.5	20	1.10	0.65	0.44	0.5947	0.4026				
3	337.5	20	1.60	0.58	0.44	0.3640	0.2768				
4	337.5	20	3.00	1.20	0.70	0.4000	0.2333				
5	337.5	20	1.46	0.55	0.59	0.3786	0.4065				
6	337.5	20	1.03	0.74	0.45	0.7216	0.4362				
7	337.5	20									
0	292.5	40	9.49	7.86	1.82	0.8284	0.1914		2.30	3.62	
1	292.5	40									
2	292.5	40	21.90	8.20	2.13	0.3744	0.0970				
3	292.5	40	7.65	5.50	3.39	0.7188	0.4433				
4	292.5	40	13.90	9.70	4.00	0.6978	0.2878				
5	292.5	40	14.90	7.80	3.34	0.5235	0.2244				
6	292.5	40	4.10	4.90	1.93	1.1950	0.4713		3.98	2.96	
7	292.5	40	2.69	5.10	1.25	1.8924	0.4654		4.08	2.26	
0	315	40	30.73	20.22	2.40	0.6579	0.0781				
1	315	40	17.90	1.00	1.30	0.0559	0.0726				
2	315	40	44.30	27.00	3.80	0.6095	0.0858				
3	315	40	48.70	26.00	2.20	0.5339	0.0452				
4	315	40	30.00	21.60	5.90	0.7200	0.1967				
5	315	40	30.30	27.90	8.69	0.9208	0.2870		3.15	3.43	
6	315	40	7.87	5.86	0.76	0.7449	0.0969		1.08	3.51	
7	315	40	3.65	2.97	3.41	0.8142	0.9358				

Table 26. Summary of σ_z Information

Downwind Distance (m)	Concentration Data Used	Centerline Elevation (m)	Mean σ_z (m)
20	Unadjusted Uranium	2.4	2.3
20	Unadjusted Fluorine	2.5	2.4
20	Adjusted Uranium	2.6	2.4
20	Adjusted Fluorine	2.4	2.4
40	Unadjusted Uranium	2.6	2.6
40	Unadjusted Fluorine	3.3	2.8
40	Adjusted Uranium	2.4	2.8
40	Adjusted Fluorine	2.9	3.2

of uranium and fluorine concentration measurements using the continuous and the sequential samplers is presented in Tables 27 and 28. The data in Tables 27 and 28 indicate that the concentration measurements may only be accurate within a factor of 2 to 3 (if the correct release duration is used in evaluating the concentrations).

7. Estimation of Deposition Rates

As a UF_6 plume is transported downwind, UO_2F_2 particles and HF vapor are removed from the plume as a result of depletion mechanisms. UO_2F_2 particles are deposited on vegetation and on the ground, and HF vapor is removed from the plume as a result of chemical reaction with the vegetation and the ground.

A deposition velocity model is generally accepted for deposition of gases and small particles although published values of deposition velocities show wide variations. A deposition velocity model assumes the rate of deposition is directly proportional to the pollutant concentration.

Let,

V_d = deposition velocity,

M = mass collected,

A = area of collector (147 cm^2),

C = pollutant concentration, and

T = collection duration (605 s),

then

$$V_d = M / [(A)(T)(C)] .$$

The above equation was used to develop the deposition velocity estimates shown in Tables 29 and 30 and on Figs. 14 through 17. Examination of the estimates of V_d indicates a multi-order of magnitude uncertainty in the correct value of the deposition rates.

The deposition velocity estimates were then used to develop best guess estimates (see Table 31) by discarding V_d estimates that were greater than the mean value plus two standard deviations. The best guess estimates of uranium and fluorine deposition velocities are 0.03 and 0.6 cm/s, respectively.

Table 27. Comparison of Uranium and Fluorine Concentration Measurements Using the Continuous and the Sequential Samplers

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium		Fluorine Concentration (mg/m ³)	(114/238)		(U Concentration)/ (F Concentration) ^a	
				Concentration (mg/m ³)	Concentration (mg/m ³)		Concentration F	Concentration U	Continuous Concentration ^a	Continuous Concentration ^a
0	292.5	1	20	63.71	30.47	1.00	0.67	0.47	0.67	0.47
Av. 1-7	292.5	1	20	79.39	46.69	0.82	1.23	1.48	1.23	1.48
Continuous	294	1	20	75.56	22.79	1.59				
Interpolated	292.5	1	20	68.26	19.86	1.65				
Continuous	288	1	20	46.34	11.10	2.00				
0	315	1	20	237.15	104.96	1.08	0.71	0.80	0.71	0.80
Av. 1-7	315	1	20	224.91	94.10	1.14	0.62	1.49	0.62	1.49
Continuous	318	1	20	218.24	45.69	2.29				
Interpolated	315	1	20	240.20	53.39	2.15				
Continuous	312	1	20	262.16	61.10	2.06				
0	337.5	1	20	3.51	2.03	0.83	1.34	1.05	1.34	1.05
Av. 1-7	337.5	1	20	4.30	1.40	1.47	1.25	1.56	1.25	1.56
Continuous	342	1	20	0.12	0.65	0.09				
Interpolated	337.5	1	20	1.89	0.65	1.39				
Continuous	336	1	20	2.48	0.65	1.83				
0	315	1	40	62.27	30.43	0.98	1.20	0.85	1.20	0.85
Av. 1-7	315	1	40	64.39	25.91	1.19	1.00	2.18	1.00	2.18
Continuous	318	1	40	28.75	8.56	1.61				
Interpolated	315	1	40	37.51	9.95	1.81				
Continuous	312	1	40	46.28	11.33	1.96				
0	337.5	1	40	0.50	0.18	1.37	0.11	0.10	0.11	0.10
Interpolated	337.5	1	40	-0.41	1.30	-0.15				
Continuous	336	1	40	0.35	1.48	0.11				
Continuous	330	1	40	3.42	2.18	0.75				

^aThe sequential concentrations are based on a sampling duration of 14 min, while the integrated concentrations are based on a 605-s duration. Therefore, the ratio of the sequential concentration to the integrated concentration is multiplied by 605/(60 x 14).

Table 28. Comparison of Adjusted Uranium and Fluorine Concentration Measurements Using the Continuous and the Sequential Samplers

Sampler No.	Azimuth	Elevation (m)	Distance (m)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)	(114/238) Concentration U/F		(U Concentration)/ (F Concentration) ^a	
						Continuous	U Concentration ^a	Continuous	F Concentration ^a
0	292.5	1	20	63.71	30.47	1.00	0.67	0.43	
Av. 1-7	292.5	1	20	110.02	51.58	1.02	1.71	1.63	
Continuous	294	1	20	75.56	22.79	1.59			
Interpolated	292.5	1	20	68.26	19.86	1.65			
Continuous	288	1	20	46.34	11.10	2.00			
0	315	1	20	237.15	104.96	1.08	0.71	0.80	
Av. 1-7	315	1	20	224.96	94.11	1.15	0.62	1.49	
Continuous	318	1	20	218.24	45.69	2.29			
Interpolated	315	1	20	240.20	53.39	2.15			
Continuous	312	1	20	262.16	61.10	2.06			
0	337.5	1	20	4.61	2.21	1.00	2.44	3.40	
Av. 1-7	337.5	1	20	5.01	1.50	1.60	2.65	2.31	
Continuous	342	1	20	0.12	0.65	0.09			
Interpolated	337.5	1	20	1.89	0.65	1.39			
Continuous	336	1	20	2.48	0.65	1.83			
0	315	1	40	64.15	30.73	1.00	1.23	0.85	
Av. 1-7	315	1	40	65.56	26.10	1.20	1.02	2.20	
Continuous	318	1	40	28.75	8.56	1.61			
Interpolated	315	1	40	37.51	9.95	1.81			
Continuous	312	1	40	46.28	11.33	1.96			
0	337.5	1	40	0.50	0.18	1.37	0.12	0.08	
Interpolated	337.5	1	40	4.27	2.05	1.00			
Continuous	336	1	40	4.44	2.13	1.00			
Continuous	330	1	40	5.13	2.46	1.00			

^aThe sequential concentrations are based on a sampling duration of 14 min, while the integrated concentrations are based on a 605-s duration. Therefore, the ratio of the sequential concentration to the integrated concentration is multiplied by 605/(60 x 14).

Table 29. Uranium and Fluorine Deposition Measurements
Using Unadjusted Concentration Estimates

Azimuth	Distance (m)	Uranium Deposition Velocity (cm/s)	Fluorine Deposition Velocity (cm/s)	Quantity Uranium (mg)	Quantity Fluorine (mg)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)
340	10	0.4286		0.009		0.2361	0.1181
330	10	0.0134	0.3109	0.212	1.159	178.0992	41.9126
320	10			0.722	2.529		
310	10	0.0364	0.6079	1.418	4.379	437.8394	80.9917
300	10	0.0307	0.4293	1.184	3.669	434.0614	96.1039
290	10	0.0351	0.1425	0.534	0.546	170.9563	43.0933
280	10	0.0065		0.019		32.9988	12.0425
270	10	0.0216		0.018		9.3861	2.3613
330	20			0.004			
324	20	0.0171	0.3543	0.142	0.770	93.3294	24.4392
318	20	0.0253	0.4206	0.492	1.709	218.2409	45.6907
312	20	0.0381	0.4010	0.888	2.179	262.1606	61.0980
306	20	0.1684	1.4458	1.375	3.059	91.7946	23.7898
300	20	0.0496	0.5178	0.944	1.979	213.8725	42.9752
294	20	0.0674	0.4648	0.453	0.942	75.5608	22.7863
288	20	0.0311	0.4610	0.128	0.455	46.3400	11.0980
282	20	0.0466		0.045		10.8619	2.5384
276	20	0.0423		0.006		1.5939	0.4132
324	40	0.0062	1.1570	0.002	0.164	3.8371	1.5939
318	40	0.0008	0.4926	0.002	0.375	28.7485	8.5596
312	40	0.0326	0.8651	0.134	0.872	46.2810	11.3341
306	40			0.230	0.913		
300	40	0.0208	0.4370	0.171	0.842	92.5620	21.6647
294	40	0.0081	0.7669	0.021	0.459	29.1617	6.7296
288	40	0.0014	0.6519	0.002	0.308	16.4109	5.3129
282	40	0.0060		0.002		3.7190	1.2987
318	100		0.2919		0.019		0.7320
315	100		0.8568		0.035	0.0244	0.4593
312	100	0.0920	1.4883	0.001	0.105	0.1222	0.7933
309	100	0.1905	0.5672	0.002	0.148	0.1181	2.9339
306	100	0.1844	1.0668	0.020	0.333	1.2193	3.5098
303	100	1.7419	0.9227	0.033	0.236	0.2130	2.8758
300	100	0.2792	1.1014	0.009	0.206	0.3624	2.1030
297	100	0.1355	1.7775	0.001	0.199	0.0830	1.2589
294	100		0.7835		0.083	0.0116	1.1912
312	500			0.003			0.1043
306	500	0.5068	0.0471	0.001	0.002	0.0222	0.4770
300	500	0.7721	0.1457	0.001	0.005	0.0146	0.3859
294	500		0.4552		0.004		0.0988
288	500						

Table 30. Adjusted Uranium and Fluorine Deposition Measurements
Using Adjusted Concentration Estimates

Azimuth	Distance (m)	Uranium Deposition Velocity (cm/s)	Fluorine Deposition Velocity (cm/s)	Quantity Uranium (mg)	Quantity Fluorine (mg)	Uranium Concentration (mg/m ³)	Fluorine Concentration (mg/m ³)
340	10	0.4286		0.009		0.2361	0.1181
330	10	0.0134	0.3109	0.212	1.159	173.0992	41.9126
320	10			0.722	2.529		
310	10	0.0364	0.6079	1.418	4.379	437.8394	80.9917
300	10	0.0307	0.4293	1.184	3.669	434.0614	96.1039
290	10	0.0351	0.1425	0.534	0.546	170.9563	43.0933
280	10	0.0065		0.019		32.9988	12.0425
270	10	0.0216		0.018		9.3861	2.3613
330	20			0.004			
324	20	0.0171	0.3543	0.142	0.770	93.3294	24.4392
318	20	0.0253	0.4206	0.492	1.709	218.2409	45.6907
312	20	0.0381	0.4010	0.888	2.179	262.1606	61.0980
306	20	0.1684	1.4458	1.375	3.059	91.7946	23.7898
300	20	0.0496	0.5178	0.944	1.979	213.8725	42.9752
294	20	0.0674	0.4648	0.453	0.942	75.5608	22.7863
288	20	0.0311	0.4610	0.128	0.455	46.3400	11.0980
282	20	0.0466		0.045		10.8619	2.5384
276	20	0.0423		0.006		1.5939	0.4132
324	40	0.0062	1.1570	0.002	0.164	3.8371	1.5939
318	40	0.0008	0.4926	0.002	0.375	28.7485	8.5596
312	40	0.0326	0.8651	0.134	0.872	46.2810	11.3341
306	40			0.230	0.913		
300	40	0.0208	0.4370	0.171	0.842	92.5620	21.6647
294	40	0.0081	0.7669	0.021	0.459	29.1617	6.7296
288	40	0.0014	0.6519	0.002	0.308	16.4109	5.3129
282	40	0.0060		0.002		3.7190	1.2987
318	100		0.2919		0.019		0.7320
315	100		0.8568		0.035	0.0244	0.4593
312	100	0.0046	1.0172	0.001	0.105	2.4232	1.1607
309	100	0.0025	0.3806	0.002	0.148	9.1287	4.3726
306	100	0.0217	0.7530	0.020	0.333	10.3817	4.9728
303	100	0.0417	0.6225	0.033	0.236	8.8993	4.2627
300	100	0.0158	0.7551	0.009	0.206	6.4044	3.0676
297	100	0.0029	1.1976	0.001	0.199	3.9007	1.8684
294	100		0.5231		0.083	3.7244	1.7840
312	500			0.003			0.1043
306	500	0.0076	0.0317	0.001	0.002	1.4827	0.7102
300	500	0.0094	0.0977	0.001	0.005	1.2013	0.5754
294	500		0.4552		0.004		0.0988
288	500

Fig. 14. Estimated Values of Deposition Velocity of Uranium Using Unadjusted Concentration Estimates

Fig. 15. Estimated Values of Deposition Velocity of Fluorine Using Unadjusted Concentration Estimates

Fig. 16. Estimated Values of Deposition Velocity of Uranium Using Adjusted Concentration Estimates

Fig. 17. Estimated Values of Deposition Velocity of Fluorine Using Adjusted Concentration Estimates

Table 31. Summary of Deposition Velocity Data

	Concentration Data Used	Uranium Deposition Velocity (cm/s)	Fluorine Deposition Velocity (cm/s)
Minimum	Unadjusted	0.0008	0.0471
Mean	Unadjusted	0.1625	0.6700
Maximum	Unadjusted	1.7419	1.7775
Standard Deviation	Unadjusted	0.3349	0.4152
Minimum	Adjusted	0.0008	0.0317
Mean	Adjusted	0.0400	0.5831
Maximum	Adjusted	0.4286	1.4458
Standard Deviation	Adjusted	0.0773	0.3240
Minimum	Unadjusted ^a	0.0008	0.0471
Mean	Unadjusted ^a	0.1098	0.6305
Maximum	Unadjusted ^a	0.7721	1.4883
Standard Deviation	Unadjusted ^a	0.1731	0.3649
Minimum	Adjusted ^a	0.0008	0.0317
Mean	Adjusted ^a	0.0270	0.5522
Maximum	Adjusted ^a	0.1684	1.1976
Standard Deviation	Adjusted ^a	0.0312	0.2850

^aCalculated after discarding deposition velocity estimates that were greater than the mean value plus 2 standard deviations.

8. Particle Size Distribution Data

Particle size distribution measurements were made at five locations. At each location the quantity of uranium and fluorine present in nine size distribution ranges was measured. The particle size distribution information is presented in Table 32 and on Figs. 18 and 19.

Examination of Fig. 18 indicates that the uranium particle size distribution had a typical "bell shaped" curve. The uranium particles were approximately 1 to 5 μm in diameter with a mean particle size of 2 to 3 μm .

Examination of Fig. 19 indicates that the fluorine particle size distribution did not have a typical bell shaped curve, it is bimodal. The fluorine particles were approximately 1 to 5 μm in diameter with a mean particle size of 2 to 3 μm .

It is not currently known whether the bimodal nature of the fluorine particle size distribution indicates the measurement of HF vapor as part of the fluorine measurement or whether fluorine (HF) is also present in particles that do not contain uranium or if HF is associated with the UO_2F_2 particles.

9. Considerations for Future UF_6 Release Tests

The observed variation in maximum downwind concentrations and the relative magnitudes in the uranium and fluorine dispersion coefficients are not consistent. It was noted that, if an experimental problem resulted in low estimates of the amount of UO_2F_2 present, then the "unexplainable" variation in maximum downwind concentrations and the relative magnitudes in the uranium and fluorine σ_y values can be explained.

At some locations, the concentration data taken with the sequential samplers showed significant concentrations during the time intervals 10 to 12 min and 12 to 14 min. The cause of this anomaly is not known.

It is recommended that future release tests attempt to resolve these questions.

Table 32. Particle Size Information

Azimuth	Distance (m)	Particle Size (μm)	Quantity	% U	Quantity	% F	(114/238)
			U (mg)	in Size Range	F (mg)	in Size Range	Mass U/ Mass F
315	20	> 9	0.321	0.39	1.920	11.34	0.08
		5.8 to 9	0.953	1.17	1.040	6.14	0.44
		4.7 to 5.8	3.300	4.05	1.040	6.14	1.52
		3.3 to 4.7	20.690	25.41	3.440	20.32	2.88
		2.1 to 3.3	39.330	48.29	6.200	36.62	3.04
		1.1 to 2.1	15.350	18.85	2.400	14.18	3.06
		0.7 to 1.1	1.440	1.77	0.480	2.84	1.44
		0.4 to 0.7	0.050	0.06	0.233	1.38	0.10
		0 to 0.4	0.004	0.005	0.176	1.04	0.01
		Total	81.438		16.929		2.30
315	40	> 9	0.066	0.31	0.900	8.66	0.04
		5.8 to 9	0.281	1.34	0.460	4.43	0.29
		4.7 to 5.8	0.537	2.56	0.390	3.75	0.66
		3.3 to 4.7	4.019	19.17	2.020	19.43	0.95
		2.1 to 3.3	8.065	38.48	3.860	37.14	1.00
		1.1 to 2.1	6.980	33.30	2.560	24.63	1.31
		0.7 to 1.1	0.990	4.72	0.160	1.54	2.96
		0.4 to 0.7	0.021	0.10	0.033	0.32	0.30
		0 to 0.4	0.001	0.005	0.011	0.11	0.04
		Total	20.960		10.394		0.97
292.5	40	> 9	0.059	0.47	0.330	14.05	0.09
		5.8 to 9	0.205	1.63	0.131	5.58	0.75
		4.7 to 5.8	0.152	1.21	0.012	0.51	6.07
		3.3 to 4.7	1.730	13.74	0.280	11.92	2.96
		2.1 to 3.3	5.600	44.49	0.820	34.91	3.27
		1.1 to 2.1	4.510	35.83	0.690	29.37	3.13
		0.7 to 1.1	0.295	2.34	0.070	2.98	2.02
		0.4 to 0.7	0.011	0.09	0.007	0.30	0.75
		0 to 0.4	0.025	0.20	0.009	0.38	1.33
		Total	12.587		2.349		2.57

Table 32 (continued)

Azimuth	Distance (m)	Particle Size (μ m)	Quantity U (mg)	% U in Size Range	Quantity F (mg)	% F in Size Range	(114/238) Mass U/ Mass F
315	100	> 9	0.002	0.24	0.070	18.47	0.01
		5.8 to 9	0.007	0.84	0.027	7.12	0.12
		4.7 to 5.8	0.003	0.36	0.017	4.49	0.08
		3.3 to 4.7	0.048	5.78	0.044	11.61	0.52
		2.1 to 3.3	0.405	48.80	0.117	30.87	1.66
		1.1 to 2.1	0.357	43.01	0.083	21.90	2.06
		0.7 to 1.1	0.006	0.72	0.011	2.90	0.26
		0.4 to 0.7	0.001	0.12	0.005	1.32	0.10
		0 to 0.4	0.001	0.12	0.005	1.32	0.10
		Total	0.830		0.379		1.05
292.5	100	> 9	0.003	0.29	0.056	14.93	0.03
		5.8 to 9	0.023	2.20	0.020	5.33	0.55
		4.7 to 5.8	0.012	1.15	0.013	3.47	0.44
		3.3 to 4.7	0.093	8.91	0.053	14.13	0.84
		2.1 to 3.3	0.525	50.29	0.125	33.33	2.01
		1.1 to 2.1	0.372	35.63	0.084	22.40	2.12
		0.7 to 1.1	0.013	1.25	0.013	3.47	0.48
		0.4 to 0.7	0.002	0.19	0.007	1.87	0.14
		0 to 0.4	0.001	0.10	0.004	1.07	0.12
		Total	1.044		0.375		1.33

Fig. 18. Uranium Particle Size Distribution Data

Fig. 19. Fluorine Particle Size Distribution Data

10. Suggested Revisions for Future UF₆ Release Tests

In order to accurately estimate the error associated with the bubbler and filter integrated samplers, it would be desirable to locate two filter samplers at one location and two bubbler samplers at another location.

The error in the concentration measurements could be reduced by locating the samplers closer to the release point. It would be desirable to move the samplers located at 500, 1000, and 2200 m closer to the release point, perhaps to 200, 300, and 500 m.

More accurate concentration measurements could be obtained by moving some of the filter samplers to locations where low concentrations are expected (i.e., not only on the outer radii but also on the crosswind periphery of the plume).

During the first release test, it was conjectured that a low value of $(114/238) \times (\text{concentration U})/(\text{concentration F})$ implied a significant error in the concentration measurements. This assumption can be checked by locating both a bubbler and a filter integrated sampler at a location where low concentrations are expected. The filter sampler should be able to detect lower concentrations than the bubbler sampler because the filter sampler has a higher air intake rate. It may also be desirable to conduct a laboratory experiment in which the samplers are exposed to a known concentration of HF.

The cameras were not able to record the plume near the release point during the first release test. Therefore, it would be desirable to locate cameras to observe the area near the release point.

During the first release test, a significant wake from the oven containing the UF₆ cylinder was observed. Although the wake probably was enhanced by the high wind velocities, it would be desirable to minimize the wake during future releases. Smoke tests could be used to determine if the wake is significant for lower wind velocities. If the wake is found to be significant, it may be possible to move the release outside the wake region by adding a short horizontal section of pipe upstream from the release section.

The wind direction measurements at elevations of 10 and 30 m appeared to be inconsistent during the first release. The consistent difference of -9

to -15.6 seems to indicate that they were not aligned correctly. The alignment should be checked prior to future release tests.

In addition to the 2-min average values of the standard deviation in the wind velocity and direction, it would be desirable to calculate standard deviation values over the release. It would also be desirable to measure the solar flux and the ground surface temperature.

11. Comparison of Test Data with Predictions of UF₆ Dispersion Model

Even for known source and ambient conditions, the results of the UF₆ dispersion model may have uncertainties that arise either from inherent limitations of Gaussian dispersion models or as a result of uncertainties in characterizing the unique aspects of UF₆ dispersion. Table 33 shows estimates of the accuracy of dispersion calculations. For actual applications for which steady meteorological conditions are reasonably well known, the expected accuracy of the best dispersion models available is at best approximately a factor of 2. In less favorable conditions, for example, if the plume is not neutrally buoyant or if there are other exceptional circumstances such as building wake effects or rough terrain, the accuracy may be as poor as a factor of 10. Because the simulation of a UF₆ release requires the simulation of a dense, chemically reacting plume, the simulation should be considered as an "exceptional circumstance." Therefore, if the estimates shown in Table 33 are correct, then the accuracy of a UF₆ simulation "...may be as poor as a factor of 10, or more." Data obtained from the UF₆ release were used to develop estimates of uranium and fluorine concentrations, the downwind variation in maximum measured uranium and fluorine concentrations, crosswind dispersion coefficients (σ_y), vertical dispersion coefficients (σ_z), and the plume centerline elevation. These estimates can be used to develop a preliminary assessment of the accuracy of the UF₆ dispersion model.

Table 33. Estimates of Accuracy for Dispersion Calculations^a

Circumstances	Accuracy
Point Sources	
Ideal conditions: near field (<1 km), short averaging times (min to h), flat terrain, steady meteorology, surface source	10 to 20%
Same as above, except for elevated sources	20 to 40%
Real world applications: meteorological parameters reasonably well known and steady with no exceptional circumstances	Factor of 2
Exceptional circumstances: wakes; buoyant plumes; varied surfaces, such as forests, cities, shorelines, rough terrain; extreme stable and unstable conditions; distances > 10 to 20 km	Poorer than factor of 2; may be as poor as a factor of 10, or more
Urban Area Sources	
Ideal source and meteorological input data and conditions	10 to 20%
Real world applications with no exceptional circumstances	Factor of 2

11.1 Simulation of the UF₆ Release

The UF₆ source was simulated by assuming that during the test, 108°C UF₆ vapor was released over 605 s from a 3.15-m high, 0.05-m diameter pipe. Simulation of the UF₆ release requires that the ambient environment be characterized. The simulation assumed an ambient temperature of 9.74°C, a pressure of 1 atm, 100% relative humidity, a mean wind direction at 10 m of 309.5, a wind velocity of 6.9 m/s at 10 m, and a neutral (Class D) stability class.

The wind speed was specified by a velocity profile defined as,

$$V = 6.88 \text{ m/s if } z < 1.8 \text{ m ,}$$

$$V = 6.88(z/10)^{0.15} \text{ m/s if } 1.8 < z < 198 \text{ m ,}$$

$$V = 6.88(198/10)^{0.15} \text{ m/s if } z > 198 \text{ m ,}$$

where z is the height above ground level.

11.2 Comparison of Experimental and Predicted Maximum Concentrations

Concentration measurements were used to develop the comparison of the maximum measured and predicted uranium and fluorine concentrations shown in Tables 34 and 35. Using the adjusted concentrations as best guess estimates, it is concluded that the UF_6 dispersion model underestimated the uranium and fluorine concentrations at radial distances of 10 and 20 m and the model overestimated concentrations beyond 20 m.

Visual observations indicated that there was a wake from the oven which contained the UF_6 cylinder. Increased turbulence generated by the wake could result in higher uranium and fluorine concentrations near the release point and lower concentrations away from the release point.

The comparison of the maximum measured and predicted uranium and fluorine concentrations indicates that the predicted and the adjusted experimental maximum concentrations typically agree within a factor of 5. It should be noted that the factor of 5 agreement is better than the predicted "... poor as a factor of 10, or more" accuracy estimate obtained from Table 33.

11.3 Comparison of Experimental and Predicted Concentration Surface Patterns

Experimental data collected from the UF_6 test can be compared with predicted data by use of the spatial comparison technique developed by W. S. Lewellyn.⁵ Lewellyn's approach provides a quantitative measure of the spatial comparison between observed and calculated surface patterns.

The spatial comparison yields a measure of how much the calculated pattern must be shifted in space to cover all of the observed values. For this purpose define the area A centered at an arbitrary observation point x_0 . This $A(x_0, \Delta\theta)$ is completely defined by its position in polar

Table 34. Comparison of Experimental and Predicted Maximum Uranium Concentrations at an Elevation of 1 m

Radial Distance (m)	Maximum Measured Uranium Concentration at a 1 m Elevation (mg/m ³)	Maximum Adjusted Uranium Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Uranium Concentration at Ground Level (mg/m ³)	Maximum Predicted Uranium Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Uranium Concentration at a 2 m Elevation (mg/m ³)	Maximum Predicted Uranium Concentration at a 3 m Elevation (mg/m ³)
10	434	434	1.9×10^{-6}	0.051	63	1800
20	262	262	5.5	43	260	610
40	93	93	82	100	140	170
100	1.2	10	46	46	45	42
500	0.022	1.5	3.2	3.2	3.2	3.1
1000 ^a	0.0027	0.15	0.98	0.98	0.98	0.98
2000 ^a	0.0022	0.075	0.27	0.27	0.27	0.27

^aThe data for radial distances of 1000 and 2000 m are provided for information only. The small number of concentration measurements at 1000 and 2000 m would probably result in the maximum plume concentration not being measured.

Table 35. Comparison of Experimental and Predicted Maximum Fluorine Concentrations at an Elevation of 1 m

Radial Distance (m)	Maximum Measured Fluorine Concentration at a 1 m Elevation (mg/m ³)	Maximum Adjusted Fluorine Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Fluorine Concentration at Ground Level (mg/m ³)	Maximum Predicted Fluorine Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Fluorine Concentration at a 2 m Elevation (mg/m ³)	Maximum Predicted Fluorine Concentration at a 3 m Elevation (mg/m ³)
10	96	96	9.2×10^{-7}	0.024	30	880
20	61	61	2.6	20	120	290
40	22	22	39	48	67	83
100	3.5	5	22	22	21	20
500	0.48	0.71	1.5	1.5	1.5	1.5
1000 ^a	0.049	0.074	0.45	0.45	0.45	0.45
2000 ^a	0.024	0.036	0.12	0.12	0.12	0.12

^aThe data for radial distances of 1000 and 2000 m are provided for information only. The small number of concentration measurements at 1000 and 2000 m would probably result in the maximum plume concentration not being measured.

coordinates (r_0, θ_0) centered on the emission point and an angular displacement $\Delta\theta$. The area is bounded by $|\theta - \theta_0| < \Delta\theta$ and $|r - r_0| < r_0\Delta\theta$.

The measured concentration (C_{EXPER}) is compared with the predicted maximum (C_{MAX}) and minimum (C_{MIN}) concentrations within the area segment $A(x_0, \Delta\theta)$. If the calculated concentrations are within a factor N of the observed value within the area $A(x_1, \Delta\theta)$ and if $C_{\text{MIN}} \leq C_{\text{EXPER}} \leq C_{\text{MAX}}$, then $N = 1.0$. If $C_{\text{EXPER}} < C_{\text{MIN}}$, then $N = C_{\text{MIN}}/C_{\text{EXPER}}$, and if $C_{\text{EXPER}} > C_{\text{MAX}}$, then $N = C_{\text{EXPER}}/C_{\text{MAX}}$. Thus, the model prediction gets credit for agreeing with the observation at x_1 if the observed value lies within a factor N of the range of predicted values over the area $A(x_1, \Delta\theta)$.

Define $f_N(\Delta\theta)$ as the fraction of the test points which yield calculated concentrations within a ratio N of the observed value within the area defined by the sector $\Delta\theta$. The function f_N is clearly a monotonically increasing function of both N and $\Delta\theta$ because, if the observation is within a factor N , it is also within any factor greater than N ; also, if the observation is counted within an area defined by $\Delta\theta$, it must also be counted within any extended area. So $f_N(\Delta\theta)$ increases to one as N or $\Delta\theta$ increase. When $\Delta\theta = 0$, we obtain the usual scatter diagram information, i.e., $f_N(0)$ gives the fraction of observations which are predicted within a factor of N (note that $N = 1$ implies exact equality so that $f_1(0)$ is almost certainly zero).

If vertical concentration gradients are significant, it seems reasonable to extend Lewellyn's approach to three dimensions. This can be accomplished by extending the area segment $A(x_0, \Delta\theta)$ to a volume segment $V(x_0, \Delta\theta)$ by projecting $A(x_0, \Delta\theta)$ vertically $\pm r_0\Delta\theta$. Volume segment $V(x_0, \Delta\theta)$ is bounded by $|\theta - \theta_0| < \Delta\theta$, $|r - r_0| < r_0\Delta\theta$, and $|z - r_0\Delta\theta| \leq z + r_0\Delta\theta$.

The methodology described above has been used to compare the experimental estimates of uranium and fluorine concentrations with predictions from the UF_6 plume code. The comparison used the concentration measurements obtained from the integrated samplers, as well as the measurements obtained from the 14-min sequential samplers. It should be noted that the 14-min duration was assumed for the sequential sampler concentrations and a 605-s duration for the integrated sampler. As noted previously, it is not known what the actual release duration was.

Results of the comparison of observed and predicted concentration patterns are presented in Tables 36 and 37. The comparison indicates that the experimental and predicted uranium and fluorine concentrations are in good agreement.

11.4 Comparison of Experimental and Predicted Estimates of the Dispersion Coefficients

A comparison of predicted and estimated values of the crosswind dispersion coefficient, σ_y , and the vertical dispersion coefficient, σ_z , is presented in Tables 38 and 39. The dispersion coefficient estimates indicate that the default values for Class D stability used by the UF₆ plume code underestimated σ_y and σ_z for this release.

The UF₆ plume code uses curve fits of the standard Pasquill-Gifford curves for estimating σ_y and σ_z . Because the Pasquill-Gifford values represent typical values for a given stability class, no definitive conclusion can be drawn from the comparison of the dispersion coefficients. However, it should be noted that a low estimate of the dispersion coefficients is consistent with the high estimate of the maximum concentrations.

11.5 Comparison of Experimental and Predicted Estimates of the Centerline Elevation

The results of a comparison of predicted and experimental estimates of the centerline elevation of the plume are shown in Table 40. The data presented in Table 40 indicate that the model underestimated the plume rise. As mentioned previously, a significant wake from the oven containing the UF₆ cylinder was observed. A lower plume rise could result from the plume being pulled down by the wake.

11.6 Summary of Comparison of Test Data with Predictions of UF₆ Dispersion Model

The comparison of the test data with the predictions of the UF₆ dispersion model indicated that: (1) the UF₆ dispersion model

Table 36. Comparison of Experimental and Predicted Concentrations
Using Unadjusted Data

Type of Segment	$\Delta\theta$ (°)	Factor	Fraction of Experimental and Predicted Uranium and Fluorine Concentration Data that Agree within Stated Factor	
			Uranium Concentrations	Fluorine Concentrations
			(%)	(%)
Area	0	1	0	0
Area	0	2	7	11
Area	0	5	17	25
Area	0	10	21	37
Area	5	1	49	48
Area	5	2	53	57
Area	5	5	60	64
Area	5	10	64	67
Area	10	1	87	80
Area	10	2	87	83
Area	10	5	91	88
Area	10	10	93	89
Area	15	1	96	93
Area	15	2	96	94
Area	15	5	97	95
Area	15	10	100	96
Volume	0	1	0	0
Volume	0	2	7	11
Volume	0	5	17	25
Volume	0	10	21	37
Volume	5	1	21	31
Volume	5	2	30	36
Volume	5	5	41	53
Volume	5	10	47	56
Volume	10	1	47	53
Volume	10	2	54	62
Volume	10	5	64	68
Volume	10	10	71	72
Volume	15	1	63	70
Volume	15	2	71	75
Volume	15	5	80	81
Volume	15	10	86	84

Table 37. Comparison of Experimental and Predicted Concentrations Using Adjusted Data

Type of Segment	$\Delta\theta$ (°)	Factor	Fraction of Experimental and Predicted Uranium and Fluorine Concentration Data that Agree within Stated Factor	
			Uranium	Fluorine
			Concentrations (%)	Concentrations (%)
Area	0	1	0	0
Area	0	2	13	12
Area	0	5	27	26
Area	0	10	31	36
Area	5	1	49	49
Area	5	2	56	58
Area	5	5	60	63
Area	5	10	64	67
Area	10	1	80	79
Area	10	2	83	83
Area	10	5	89	88
Area	10	10	90	88
Area	15	1	94	91
Area	15	2	96	94
Area	15	5	97	95
Area	15	10	99	96
Volume	0	1	0	0
Volume	0	2	13	12
Volume	0	5	27	26
Volume	0	10	31	36
Volume	5	1	29	32
Volume	5	2	34	36
Volume	5	5	46	53
Volume	5	10	53	56
Volume	10	1	44	52
Volume	10	2	53	62
Volume	10	5	64	68
Volume	10	10	70	70
Volume	15	1	61	69
Volume	15	2	70	75
Volume	15	5	80	81
Volume	15	10	84	84

007041

2 OF 2

Table 38. Comparison of Predicted and Estimated Values of σ_y

Downwind Distance (m)	Predicted σ_y (m)	σ_y from Unadjusted U Concentration (m)	σ_y from Unadjusted F Concentration (m)	σ_y from Adjusted U Concentration (m)	σ_y from Adjusted F Concentration (m)
10	1.1	2.0	2.2	2.0	2.0
20	2.0	3.6	3.6	3.7	3.6
40	3.8	6.0	6.9	6.3	7.0
100	8.8	9.0	11.7	12.8	11.8
500	36.8	57.0	56.3	80.5	53.3

Table 39. Comparison of Predicted and Estimated Values of σ_z

Downwind Distance (m)	Predicted σ_z (m)	σ_z from Unadjusted U Concentration (m)	σ_z from Unadjusted F Concentration (m)	σ_z from Adjusted U Concentration (m)	σ_z from Adjusted F Concentration (m)
20	1.0	2.3	2.4	2.4	2.4
40	2.0	2.6	2.8	2.8	3.2

Table 40. Comparison of Predicted and Estimated Values of the Centerline Elevation

Downwind Distance (m)	Predicted Centerline Elevation (m)	Centerline Elevation from Unadjusted U Concentration (m)	Centerline Elevation from Unadjusted F Concentration (m)	Centerline Elevation from Adjusted U Concentration (m)	Centerline Elevation from Adjusted F Concentration (m)
20	3.42	2.4	2.5	2.6	2.4
40	3.46	2.6	3.3	2.4	2.9

underestimated near-field concentrations and overestimated concentrations beyond 20 m, (2) the predicted and the adjusted experimental maximum concentrations typically agree within a factor of 5, (3) the experimental and predicted uranium and fluorine concentrations patterns are in good agreement, (4) the Class D stability dispersion coefficient values underestimated σ_y and σ_z , and (5) the plume rise was underestimated. It was noted that the wake from the oven which contained the UF₆ cylinder could result in higher pollutant concentrations near the release point and lower concentrations away from the release point.

The primary figure of merit in assessing the accuracy the UF₆ dispersion model as applied to the safety analysis of postulated accidental UF₆ releases is the ability to predict maximum downwind pollutant concentrations. If the model can predict maximum downwind pollutant concentrations, it is possible to estimate the maximum hazard level at a given downwind distance. Because the predicted and the adjusted experimental maximum concentrations typically agree within a factor of 5 and because the experimental and predicted uranium and fluorine concentrations patterns are in good agreement, it is concluded that the model predictions and experimental data were in good agreement.

Although the model predictions and the experimental data were determined to be in good agreement for this release, it should not be concluded that the model has been substantiated. Rather it should be concluded that a favorable comparison between the model and the test data from a single release was obtained. The favorable comparison should be interpreted as an indication that the model appears to yield a reasonable simulation under the conditions of the first release test. It should be noted that experimental difficulties prevented the measurement of plume rise and growth data near the release point required to check the accuracy of the dispersion model.

Because the dispersion coefficient estimates indicated that the default dispersion coefficient values for Class D stability used by the UF₆ plume code underestimated σ_y and σ_z for this release, it was decided to repeat the analysis assuming a Class C stability. (The dispersion coefficients applicable to Class C stability simulate a faster rate of dispersion than the dispersion coefficients applicable to Class D stability.) A comparison

of the test data and the results of a UF_6 plume simulation in a Class C environment is provided in the appendix. Examination of the information in the appendix indicates that the test data agree better with the simulation in a Class C stability than the simulation in a Class D environment.

12. Summary and Conclusions

On April 18, 1986, a controlled UF_6 release test was conducted at a CESTA test site near Bordeaux, France. During the test, 45.8 kg of UF_6 vapor were released over approximately 10 min. Information collected during the release test included: meteorological data, measurements of uranium and fluorine concentrations, deposition data, and particle size distribution data. The test data have been analyzed, and experimental difficulties associated with the first release test were identified.

The observed variation in maximum downwind concentrations and the relative magnitudes in the uranium and fluorine dispersion coefficients were not consistent. It was noted that, if an experimental problem resulted in low estimates of the amount of UO_2F_2 present, then the "unexplainable" variation in maximum downwind concentrations and the relative magnitudes in the uranium and fluorine σ_y values can be explained. Adjusted estimates of uranium and fluorine concentrations were obtained by assuming that $(114/238) \times (\text{concentration U})/(\text{concentration F})$ equals 1.

At some locations, the concentration data taken with the sequential samplers showed significant concentrations during the time intervals 10 to 12 min and 12 to 14 min. It was conjectured that either the UF_6 continued to leave the exhaust section for a period of time after the valve was closed or the sampling interval was not 2 min.

The test data have been compared to the UF_6 dispersion model developed by the U.S. Department of Energy for simulating postulated accidental releases of UF_6 . The comparison of the maximum measured and predicted uranium and fluorine concentrations indicated that the measured and predicted maximum concentrations typically agree within a factor of 5. Results of the comparison of observed and predicted concentration patterns indicate that the experimental and predicted uranium and fluorine concentrations are in good agreement. It was concluded that the

experimental and predicted uranium and fluorine concentrations are in good to excellent agreement.

References

1. U. S. Nuclear Regulatory Commission, "On-Site Meteorological Programs," Regulatory Guide 1.23, 1972.
2. F. A. Gifford, Jr., "An Outline of Theories of Diffusion in the Lower Layer of the Atmosphere," Chapter 3 in "Meteorology and Atomic Energy," D. H. Slade (ed.), U.S. AEC Report TID-24190, July 1968.
3. J. S. Irwin, "A Theoretical Variation of the Wind Profile Power-Law Exponent as a Function of Surface Roughness and Stability," Atmospheric Environment, Vol. 13, pp. 191-194, 1979.
4. R. L. Drake, D. J. McNaughton, and C. Hiang, "Mathematical Models for Atmospheric Pollutants. Appendix D: Available Air Quality Models," EA-1131, Appendix D, Electric Power Research Institute, August 1979.
5. W. S. Lewellyn, R. I. Sykes, and D. Oliver, "The Evaluation of MATHEW/ADPIC as a Real-Time Dispersion Model," NUREG/CR-2199, December 1981.

Appendix

SIMULATION OF UF_6 RELEASE IN A SLIGHTLY UNSTABLE ENVIRONMENT

The simulation of the UF₆ release described in Section 11.1 assumed a Class D or neutral stability class. The simulation of the UF₆ release has been repeated assuming a slightly unstable or Class C stability class, instead of a neutral stability class. The only modifications to the simulation described in Section 11.1 were the use of dispersion coefficients that correspond to a Class C stability class and a modification of the velocity profile. The velocity profile was defined as,

$$V = 6.88 \text{ m/s if } z < 1.8 \text{ m,}$$

$$V = 6.88(z/10)^{0.10} \text{ m/s if } 1.8 < z < 198 \text{ m,}$$

$$V = 6.88(198/10)^{0.10} \text{ m/s if } z > 198 \text{ m,}$$

where z is the height above ground level.

Concentration measurements were used to develop the comparison of the maximum measured and predicted uranium and fluorine concentrations shown in Tables A.1 and A.2. Using the adjusted concentrations as best guess estimates, it is concluded that the UF₆ dispersion model underestimated the uranium and fluorine concentrations at radial distances of 10 and 20 m and the model overestimated concentrations beyond 20 m.

Visual observations indicated that there was a wake from the oven which contained the UF₆ cylinder. Increased turbulence generated by the wake could result in higher uranium and fluorine concentrations near the release point and lower concentrations away from the release point.

The comparison of the maximum measured and predicted uranium and fluorine concentrations indicates that the predicted and the adjusted experimental maximum concentrations typically agree within a factor of 3.

The spatial comparison methodology described in Section 11.3 has been used to compare the experimental estimates of uranium and fluorine concentrations with predictions from the UF₆ plume code. Results of the comparison of observed and predicted concentration patterns are presented in Tables A.3 and A.4. The comparison indicates that the experimental and predicted uranium and fluorine concentrations are in good agreement.

A comparison of predicted and estimated values of the crosswind dispersion coefficient, σ_y , and the vertical dispersion coefficient, σ_z , is presented in Tables A.5 and A.6. The dispersion coefficient estimates indicate that the default values for Class C stability used by the UF₆ plume code underestimated σ_y and σ_z for this release.

Table A.1 Comparison of Experimental and Predicted Maximum Uranium Concentrations at an Elevation of 1 m

Radial Distance (m)	Maximum Measured Uranium Concentration at a 1 m Elevation (mg/m ³)	Maximum Adjusted Uranium Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Uranium Concentration at Ground Level (mg/m ³)	Maximum Predicted Uranium Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Uranium Concentration at a 2 m Elevation (mg/m ³)	Maximum Predicted Uranium Concentration at a 3 m Elevation (mg/m ³)
10	434	434	0.41	19	340	1200
20	260	260	58	110	250	360
40	93	93	98	100	110	110
100	1.2	10	31	31	30	29
500	0.022	1.5	1.58	1.6	1.6	1.6
1000a	0.0027	0.15	0.42	0.42	0.42	0.42
2000a	0.0022	0.075	0.093	0.093	0.093	0.093

aThe data for radial distances of 1000 and 2000 m are provided for information only. The small number of concentration measurements at 1000 and 2000 m would probably result in the maximum plume concentration not being measured.

Table A.2 Comparison of Experimental and Predicted Maximum Fluorine Concentrations at an Elevation of 1 m

Radial Distance (m)	Measured Fluorine Concentration at a 1 m Elevation (mg/m ³)	Maximum Adjusted Fluorine Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Fluorine Concentration at Ground Level (mg/m ³)	Maximum Predicted Fluorine Concentration at a 1 m Elevation (mg/m ³)	Maximum Predicted Fluorine Concentration at a 2 m Elevation (mg/m ³)	Maximum Predicted Fluorine Concentration at a 3 m Elevation (mg/m ³)
10	96	96	0.20	8.9	160	590
20	61	61	28	54	120	170
40	22	22	47	48	51	52
100	3.5	5	15	15	14	14
500	0.48	0.71	0.73	0.73	0.73	0.73
1000a	0.049	0.074	0.19	0.19	0.19	0.19
2000a	0.024	0.036	0.043	0.043	0.043	0.043

aThe data for radial distances of 1000 and 2000 m are provided for information only. The small number of concentration measurements at 1000 and 2000 m would probably result in the maximum plume concentration not being measured.

Table A.3 Comparison of Experimental and Predicted Concentrations Using Unadjusted Data

Type of Segment	$\Delta\theta$ (°)	Factor	Fraction of Experimental and Predicted Concentration Data that Agree within Stated Factor	
			Uranium Concentrations (%)	Fluorine Concentrations (%)
Volume	0	1	0	0
Volume	0	2	13	14
Volume	0	5	39	37
Volume	0	10	50	53
Volume	5	1	56	60
Volume	5	2	66	68
Volume	5	5	76	79
Volume	5	10	81	83
Volume	10	1	90	89
Volume	10	2	91	90
Volume	10	5	96	91
Volume	10	10	96	93
Volume	15	1	96	95
Volume	15	2	99	96
Volume	15	5	99	96
Volume	15	10	100	98
Area	0	1	0	0
Area	0	2	13	14
Area	0	5	39	37
Area	0	10	50	53
Area	5	1	31	36
Area	5	2	46	53
Area	5	5	64	67
Area	5	10	67	72
Area	10	1	63	73
Area	10	2	76	79
Area	10	5	80	84
Area	10	10	86	90
Area	15	1	80	84
Area	15	2	84	86
Area	15	5	90	94
Area	15	10	97	95

Table A.4 Comparison of Experimental and Predicted Concentrations Using Adjusted Data

Type of Segment	$\Delta\theta$ (°)	Factor	Fraction of Experimental and Predicted Concentration Data that Agree within Stated Factor	
			Uranium Concentrations (%)	Fluorine Concentrations (%)
Volume	0	1	0	0
Volume	0	2	13	14
Volume	0	5	39	37
Volume	0	10	50	53
Volume	5	1	56	60
Volume	5	2	66	68
Volume	5	5	76	79
Volume	5	10	81	83
Volume	10	1	90	89
Volume	10	2	91	90
Volume	10	5	96	91
Volume	10	10	96	93
Volume	15	1	96	95
Volume	15	2	99	96
Volume	15	5	99	96
Volume	15	10	100	98
Area	0	1	0	0
Area	0	2	13	14
Area	0	5	39	37
Area	0	10	50	53
Area	5	1	31	36
Area	5	2	46	53
Area	5	5	64	67
Area	5	10	67	72
Area	10	1	63	73
Area	10	2	76	79
Area	10	5	80	84
Area	10	10	86	90
Area	15	1	80	84
Area	15	2	84	86
Area	15	5	90	94
Area	15	10	97	95

Table A.5 Comparison of Predicted and Estimated Values of the Centerline Elevation

Downwind Distance (m)	Predicted Centerline Elevation (m)	Centerline Elevation from Unadjusted U Concentration (m)	Centerline Elevation from Unadjusted F Concentration (m)	Centerline Elevation from Adjusted U Concentration (m)	Centerline Elevation from Adjusted F Concentration (m)
20	3.32	2.4	2.5	2.6	2.4
40	3.34	2.6	3.3	2.4	2.9

Table A.6 Comparison of Predicted and Estimated Values of σ_y

Downwind Distance (m)	Predicted σ_y (m)	σ_y from Unadjusted U Concentration (m)	σ_y from Unadjusted F Concentration (m)	σ_y from Adjusted U Concentration (m)	σ_y from Adjusted F Concentration (m)
10	1.3	2.0	2.2	2.0	2.0
20	2.4	3.6	3.6	3.7	3.6
40	4.6	6.0	6.9	6.3	7.0
100	10.9	9.0	11.7	12.8	11.8
500	48.4	57.0	56.3	80.5	53.3

A.7

The UF6 plume code uses curve fits of the standard Pasquill-Gifford curves for estimating σ_y and σ_z . Because the Pasquill-Gifford values represent typical values for a given stability class, no definitive conclusion can be drawn from the comparison of the dispersion coefficients. However, it should be noted that a low estimate of the dispersion coefficients is consistent with the high estimate of the maximum concentrations.

The results of a comparison of predicted and experimental estimates of the centerline elevation of the plume are shown in Table A.7. The data presented in Table A.7 indicate that the model underestimated the plume rise. As mentioned previously, a significant wake from the oven containing the UF6 cylinder was observed. A lower plume rise could result from the plume being pulled down by the wake.

Table A.7 Comparison of Predicted and Estimated Values of σ_z

Downwind Distance (m)	Predicted σ_z (m)	σ_z from Unadjusted	σ_z from Unadjusted	σ_z from Adjusted	σ_z from Adjusted
		U Concentration (m)	F Concentration (m)	U Concentration (m)	F Concentration (m)
20	1.5	2.3	2.4	2.4	2.4
40	2.7	2.6	2.8	2.8	3.2

END

DATE
FILMED
5128193