DOE/PC/92111--T1

DE93 009707

DOE/PC/92111-T1

FEB 12 1993

Report No. FE-MIT-92111-1

**Conversion of Light Hydrocarbon Gases to Metal Carbides for
Production of Liquid Fuels and Chemicals**

**Quarterly Technical Status Report for the Period October 1-December 31, 1992
DOE/PETC-MIT Contract No. DE-AC22-92PC92111**

**Alexander F. Diaz, Anthony J. Modestino,
Jack B. Howard, and William A. Peters
Energy Laboratory and Dept. of Chemical Engineering
MIT, Cambridge, MA 02139**

RECEIVED
MAR 24 1993
OSTI

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, makes warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Submitted to the United States Department of Energy
Pittsburgh Energy Technology Center
Attention: Arun C. Bose

MASTER

Date Submitted: February 1993

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

U.S. DOE Patent Clearance is not required prior to the publication of this document.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

1. Background and Objectives

Previous work at MIT indicates that essentially stoichiometric, rather than catalytic, reactions with alkaline earth metal oxides offer technical and economic promise as an innovative approach for converting light hydrocarbon gases (e.g., natural gas) to premium products such as liquid hydrocarbon fuels and chemicals. In this approach, light hydrocarbon gases would be reacted with relatively low cost alkaline earth metal oxides, such as CaO or MgO, in high temperature or thermal plasma reactors to achieve very high (i.e., approaching 100%) gas conversions to H₂, CO and the corresponding alkaline earth metal carbides. These carbides would be stored, transported, and hydrolyzed to acetylene or methyl acetylene, which would in turn be upgraded to a wide range of valuable chemicals and premium grade liquid hydrocarbon fuels. Research is needed to provide key information for further technical and economic assessment of this approach. In particular there is need:

- 1) To determine if, in analogy to the high methane conversion and selectivity of CaC₂, H₂, and CO, previously demonstrated at MIT by reacting methane with CaO in an electrical discharge reactor, high yields, selectivities, and methane conversions to Mg₂C₃, H₂ and CO can be achieved by reacting methane and MgO in a thermal plasma.
- 2) For methane reactions with CaO and MgO, to define preferred ranges of plasma operating conditions, that provide desired yields, selectivity, and conversion rates to CaC₂ or Mg₂C₃, H₂ and CO, and which would be suitable for industrial practice.
- 3) To determine the applicability of this approach to converting other major components of natural gas such as ethane, propane, and butane.
- 4) To determine if, as is implied by thermodynamics, methane can be converted to CaC₂ and Mg₂C₃, by thermal reactions with CaO and MgO, respectively, without the need for electric arc discharge, i.e., plasma processing.
- 5) To establish better understanding of the underlying chemical and physical processes by which this approach gives desired conversion/selectivity and kinetics behavior.

The objectives of this project are to obtain answers to these questions by carrying out research as the following two tasks:

Task 1: Industrial Chemistry and Applied Kinetics of Light Hydrocarbon Gas Conversion to Metal Carbides, H₂ and CO

Task 2: Mechanistic Foundations For Converting Light Hydrocarbon Gases to Metal Carbides, H₂ and CO

2. Progress on Task 1: Industrial Chemistry and Applied Kinetics of Light Hydrocarbon Gas Conversion to Metal Carbides, H₂ and CO

2.1 Reactor Design Criteria

The initial step taken to assess the technical feasibility of producing Mg_2C_3 , H_2 and CO from CH_4 and MgO under thermal plasma conditions was to form a design basis for an electric arc discharge reactor. We revisited the work of Kim [1] with CaO in a thermal plasma reactor to define such a basis. Our preliminary design basis is presented in Table 1.

Table 1. Preliminary Design Basis

Gas	Methane
Gas Flowrate, L/min @ 70°F (21°C) and 1 atm	10 - 100
Powder Feedrate, g/min (0.2 to 1.5 x Stoichiometric Feedrate)	
CaO	1.5 - 116.1
MgO	1.3 - 100.2
Calcinated Dolomite (40 wt% MgO, 55 wt% CaO)	1.5 - 108.8
Particle Size, microns	1 - 100

2.2 Investigation of Equipment Construction and Purchase Options

Kim built a d.c rotating-arc reactor, with the head assembly based on a design of AVCO Systems Division, and fitted the head in a cooling chamber from which he collected samples with a quench probe. Power was supplied to the arc reactor with a 40 kW Miller welding power supply.

We had initially planned on purchasing a commercially available plasma gun system, rather than devoting significant efforts to the design, construction, and systematic testing of a "home-made" unit. Significant time savings would come with procuring a turn-key unit, which would provide the equivalent of Kim's arc generator assembly, as well as a power supply (with a built-in high frequency oscillator), controls and interlocks, and a powder feeder unit. Additional benefits of this approach are expected to include a ready-to-go system with a typical vendor's guarantee, and presumably, an initial system checkout by the vendor at our site.

Last December 2, three of us visited a manufacturer of commercial plasma spraying equipment in Westborough, Massachusetts, Bay State Abrasives Division of Abrasives Industries, Inc., which was formerly a division of AVCO. We witnessed a demonstration of its commercial 40 kW and 60 kW plasma gun systems with argon as the plasma-forming gas. The possible operation of a commercial plasma gun system with methane to meet current project objectives was discussed. Bay State Abrasives would not, however, guarantee stable operation of their gun with methane. They were, however, willing to

conduct an exploratory test but at an estimated cost that could reach about a quarter of the total system cost. We do not consider this an attractive proposition, as we could very well purchase the entire system and do the testing ourselves. Should their gun prove to be unsuitable to our experimental needs, at worst, we would be unable to use the gun, which is less than ten percent of the total system cost. The power supply unit, control console and powder feeder would still be of use, no matter what plasma gun design we use.

We also found out, in the course of the discussions, that much of the technology employed for the design of many commercial plasma spray gun systems is as much as 25-30 years old.

After completing our visit to Bay State Abrasives, we had four options:

- 1) Purchase a Bay State Abrasives or similar commercial plasma spray gun system and determine its suitability to our experimental needs ourselves. At worst, the plasma gun would need to be replaced but the power supply unit, control console and powder feeder would be still be usable.
- 2) Construct a 1993 version of Kim's arc generator assembly (plasma gun) and buy the other components of a commercial unit (power supply unit, control console and powder feeder).
- 3) Revitalize an old plasma gun system at the Department of Chemical Engineering that dates back to the 1960's. This may have essentially the same features as the Bay State Abrasives' thirty-year-old design. The system has an AIRCO power supply unit, rated by the manufacturer up to 83 kW, a control console and a plasma gun. This system, however, has not been used routinely for about 12 years and has not been operated over 20 kW. In addition, it does not have the capability for powder injection. Therefore, provisions for powder feeding would need to be included.
- 4) Locate other manufacturers of commercial plasma gun systems.

We have decided to explore Option 3 simultaneously with Option 4. We think that going in this direction will be the least costly and will enable us to assess our experimental equipment needs better. With Option 3, some level of effort may be required to revive the old unit. Should the old plasma gun turn out to be unusable and if the other system components are in good shape, we would also consider, as a next step, a variant of Option 2, wherein we would purchase a commercial plasma gun and try it with the existing power supply and control console.

Under Option 4, Mr. Diaz contacted another manufacturer of commercial plasma gun systems, Hobart Tafa Technologies in Concord, New Hampshire. From preliminary discussions with them, the same conclusions reached with the Bay State Abrasives seem to apply. In fact, Hobart Tafa has just acquired sales distributorship of the Bay State Abrasives system.

Mr. Diaz also spoke with Dr. Val Krukonis, a former AVCO employee with whom Kim consulted for the design of his arc generator assembly. Dr. Krukonis provided valuable insights on possible problems in designing our own plasma gun.

2.3 Locating the New Reactor

We have decided to set up our experimental apparatus in a laboratory on the first floor of the Chemical Engineering Building. The choice of location was influenced mainly by two factors: the availability of utilities (electrical power supply and cooling water) and heat dissipation from the power supply unit. The first factor is a major concern since the installation of a power supply line would entail significant additional costs to the project. The laboratory where we intend to put up our reactor already has a three-phase power supply line rated up to 60 kVA. The cooling water supply, however, may not be adequate and needs to be investigated more closely. Having the reactor on the first floor, which has a higher ceiling than other floors, also addresses the concern on heat dissipation from the power supply. We are planning to build a duct from the outlet of the exhaust of the power supply unit's cooling fan to direct the hot air upwards. We expect, however, the noise generated by the power supply to be a potential problem, wherever we set up the reactor.

2.4 Further Issues in Reactor Design and Operation.

Kim examined six experimental parameters:

- 1) Power Input: 10 - 26 kW
- 2) Methane Flowrate: 16 - 48 L/min
- 3) Lime Feedrate: 1.5 - 38 g/min (0.12 - 1.4 times stoichiometric lime feedrates based on carbon in the methane)
- 4) CaO Particle Size: -8, -44, -74 microns
- 5) Residence Time: use of various anodes of different lengths
- 6) Quench Distance (probe to anode nozzle exit) : 5" or 15"

We intend to examine most or all of these parameters in our experiments with MgO but over possibly different ranges appropriate to MgO. Kim was limited in his investigations by the instability of the arc in his reactor. Specifically, he found that the arc was unstable whenever the arc voltage was more than half the maximum open circuit voltage of his power supply. He was unable to get enough data points for the higher gas flowrates of 44 - 48 L/min because these flowrates led to increased convective cooling of the arc, which, in turn, resulted in an increase in the electric field strength. We would like to investigate regions of higher methane gas flowrates up to possibly 100 L/min and, therefore, higher solid flowrates. Consequently, we would try to design our arc generator assembly accordingly or, should we go for a commercial unit, ensure first that the system will have stable operation under these conditions. In addition to investigating MgO and CaO separately, we also plan to run experiments with calcined dolomite.

Kim examined the effect of residence times by using different anode lengths. Options for changing residence time under consideration for our reactor include changing the cathode-anode separation and the use of anodes of different sizes as well as varying the gas flowrate and power input proportionately.

We also need to design and have fabricated a product quenching and collection system. We expect this to consist of a movable, cooled cylindrical collection probe that can be mounted in a separate chamber directly attached to the plasma gun and designed so that the distance of separation between the end tip of the plasma "flame" and the entrance to the collector can be varied in a controlled manner. The time necessary to quench the products (and unreacted feed) from the plasma reactor depends on the temperature and enthalpy content of the reactor effluent, the final temperature desired, and the rates at which enthalpy can be removed from the effluent stream. The length of the cooling zone, which will

consist of the region between the plasma tip and the entrance to the collector, will then depend on the exit gas flowrate and the necessary quench time.

To test the feasibility of using the old unit under Option 3, we are planning to proceed with the fabrication of a cooling chamber on which the plasma gun will be mounted. This will be a carbon steel schedule 40 cylinder with 7" inside diameter and 18" in length. This is 6" shorter than Kim's chamber to allow for future installation of an additional section with optical access ports. We also intend to use a 30" quench probe for sample collection, the parts of which are already available and ready for assembly.

2.5 Literature Reviews

We are also conducting a literature review of relevant work. In particular, we are looking into analytical methods for identification and quantification of samples to be collected in our experiments, i.e. quantitative determination of MgC_2 , Mg_2C_3 and CaC_2 in samples that may contain the first two or even all three of these carbides.

3. Progress on Task 2. Mechanistic Foundations for Converting Light Hydrocarbon Gases to Metal Carbides, H_2 and CO

Our main activity was reviewing the literature (see also Section 2.5).

4. Future Plans

By the end of the next reporting period, we expect to have a preliminary checkout of the old AVCO plasma gun system under Option 3 and to be able to better assess our experimental equipment needs and options.

5. References

1. Kim, C.S., "Formation of CaC_2 from CaO and 'Nascent' Carbon Species in a Rotating-Arc Reactor", Sc.D. Thesis, Dept. of Chemical Engineering, MIT, Cambridge, MA (1977).

END

DATE
FILMED
4/9/93