PNL-SA--20155

DE93 007841

RECEIVED

FEB 18 1993

OSTI

MOISTURE CONTENT AND RECHARGE ESTIMATES
AT THE YAKIMA BARRICADE BOREHOLE

E. M. Murphy
J. E. Szescody
S. J. Phillips

December 1991

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Moisture Content and Recharge Estimates at the Yakima Barricade Borehole

The DOE Deep Microbiology Program recently drilled a borehole near the Yakima Barricade, west of the 200 Areas. The area is vegetated by mature sagebrush. The borehole was drilled by cable tool and approximately every 1.5 m, sediment samples were collected in a bucket by the drill site geologist. Sediment samples for moisture content were sealed quickly. "Samples of opportunity" were collected for the HSPA program (Hanford Site Performance Assessment), Isotope Recharge task. *It should be noted that, although many QA Level II procedures were incorporated into the drilling and sampling, the Deep Microbiology Program is officially designated QA Level III, and therefore, the recharge values that we report here should only be used for planning purposes.*

A series of graphs are shown in the attached figure that illustrate the moisture content and chloride profiles in the Hanford Formation at the Yakima Barricade Borehole. The gravimetric moisture content generally ranges between 0.01 and 0.08 in the first 70 m of sediment (only the first 30 m are shown in the figure), values that are typically found at the Hanford Site. The stratigraphy of this borehole is also attached. The first 1.5 m of the soil profile is Warden silt loam (designated eolian), followed by over 50 m of Hanford Formation. The Hanford Formation is composed of unconsolidated sands, silts, and gravels that were carried into the area by glacial flood waters during the close of the last Ice Age. Below the Hanford Formation is the Ringold Formation composed of semiconsolidated sediments. The water table is located at a depth of approximately 100 m.

The chloride ion profile shows an accumulation of meteoric chloride in the first 5-6 m that probably occurred over the last 13,000 years. Site geologists have verified that the last flood event occurred 13,000 years ago. The location of this borehole is well below the elevation of the high water mark associated with this last flood event. Based on the low chloride content, sediments below this chloride peak have probably not been exposed to meteoric water over that time period. Therefore, glacial flood waters are still responsible for water drainage in the major portion of the unsaturated zone in this area. Because the geology of this site is well-defined, the cumulative chloride versus cumulative water content graphs in the attached figure were used to calculate the long-term input of atmospheric chloride as opposed to age dating the profile segments. Since a cable tool was used, the majority of samples were not recovered intact, and therefore, actual bulk densities are not available. At least one interval in the first 30 m was cored and bulk density will be measured on this core. Values of bulk density typically encountered in the Hanford Formation range from 1.27 to 1.97 g/cm³ (Bjornstad 1990). Although individual bulk densities, could be estimated for each lithology based on the detailed geologic log, we have used the reported range of bulk density as a first approximation. The age-dating calculation requires the additional assumption of piston flow. Cumulative chloride is calculated as

$$\sum_i (\theta_{v_i} \times Cl_{sw_i}) d_i$$

(1)

where θ_{v_i} = volumetric water content at depth i (m³/m³)

Cl_{sw_i} = chloride content in the soil water at depth i (g/m³)

d_i = sample interval length at depth i (m)

Cumulative water content is calculated as

$$\sum_i (\theta_{v_i} \times d_i)$$

(2)

The volumetric water content is equal to the gravimetric water content times the bulk density. Plots of cumulative chloride content versus cumulative water content will give a straight line, unless there has been a change in precipitation, chloride input, and/or recharge, in which case the line will curve. The curve is a series of straight-line segments that represent periods of constant conditions. The date represented by the end points of each straight-line segment, or the travel time to soil depth interval, can be estimated by

$$t = \sum_i \left(\frac{\rho_B M_i d_i}{Cl_o P} \right) \quad (3)$$

where ρ_B is the dry bulk density, M the chloride concentration (in mg chloride/kg soil), d is the interval length, Cl_o the atmospheric input of chloride, and P the annual precipitation (Phillips et al. 1988). The term $\rho_B M_i d_i$ is essentially the same as Cl_{sw} , the cumulative chloride content of the water in the unsaturated zone at that point.

Assuming that $t = 13,000$ years and $P = 0.16$ m/y, the value for Cl_o ranges from 0.24 to 0.38 mg/L for the assumed bulk densities of 1.27 and 1.97 g/cm³ respectively. The higher value for Cl_o , 0.38 mg/L, is very similar to the value reported by Phillips et al. (1988) for New Mexico. The chloride concentration in rainfall at Hanford is generally reported to be below 0.1 mg/L (the ion chromatograph detection limit) suggesting that the major portion of chloride input occurs as dry fallout. The suggestion that dry fallout is much more significant than wet fallout is consistent with findings by the Hanford Environmental Dose Reconstruction project.

A second method will be employed in the Isotope Recharge task to estimate Cl_o . In this method, the calculated natural ³⁶Cl fallout (calculated atmospheric production of ³⁶Cl for this latitude) is divided by the measured ³⁶Cl/Cl ratio:

$$Cl_o = \frac{{}^{36}Cl}{{}^{36}Cl/Cl} \quad (4)$$

To obtain an average, long-term Cl_o input, the meteoric ³⁶Cl/Cl ratio (that is rainwater) and the pre-bomb ³⁶Cl/Cl ratio in the soil, well below the ³⁶Cl peak caused by atmospheric bomb testing, are measured (Phillips et al. 1988; Scanlon et al. 1990).

Net recharge can be determined by applying a mass-balance argument on the chloride ion, where the difference between the chloride concentration of the soil water and the atmospheric input concentration is due to evapotranspirative enrichment. Although this approach typically does not require the assumption of piston flow, since we calculated Cl_o by equation (3), we are indirectly assuming piston flow. Recharge is determined by the relationship

$$R = \left(\frac{Cl_o}{Cl_{sw}} \right) * P \quad (5)$$

where R = recharge (cm/y), Cl_o = average chloride concentration in local precipitation (mg/L) and dry fallout, Cl_{sw} = average chloride concentration (mg/L) in the soil water, and P = average annual precipitation (cm/y). The average Cl^- value (Cl_{sw}) at the peak concentration was ~4000 mg/L. If precipitation is assumed to be 0.16 m/y and we use Cl_o calculated above (0.24 to 0.38 mg/L), then the estimated, long-term recharge would range from 0.0096 to 0.0152 mm/y in this soil profile.

References:

Bjornstad, B. N. 1990. *Geohydrology of the 218-W-5 Burial Ground, 200-West Area, Hanford Site*. PNL-7336, Pacific Northwest Laboratory, Richland, Washington.

Phillips, F., J. Mattick, T. Duval, D. Elmore, and P. Kubik. 1988. "Chlorine-36 and Tritium from Nuclear Weapons Fallout as Tracers for Long-Term Liquid and Vapor Movement in Desert Soils." *Water Resour. Res.* 24(11):1877-1891.

Scanlon, B. R., P. W. Kubik, P. Sharma, B. C. Richter, and H. E. Gove. 1990. "Bomb Chlorine-36 Analyses in the Characterization of Unsaturated Flow at a Proposed Radioactive Waste Disposal Facility, Chihuahuan Desert, Texas." Presented at the 5th International Conference on Accelerator Mass Spectrometry, Paris, France, April 1990.

**Moisture Content and Chloride Profile
Hanford Site - Yakima Barricade Borehole
(September - October 1990)**

Interpretation of Cumulative Chloride Profile

YAKIMA BARRICADE BOREHOLE

(prepared by Bruce Bjornstad)

END

DATE
FILMED

5 / 7 / 93