165/637-83
LA-9391-PR
Progress Report

(1)
I-3911

Sh. 637

Los Alamos National Laboratory is operated by the University of California for the United States Department of Energy under contract W-7405-ENG-36.

DO NOT MICROFILM
COVER

MASTER

Environmental and Radiological-Safety Studies

*Interaction of $^{238}\text{PuO}_2$ Heat Sources with
Terrestrial and Aquatic Environments
January 1—March 31, 1982*

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

The four most recent reports in this series, unclassified, are LA-8932-PR, LA-8996-PR, LA-9070-PR, and LA-9248-PR.

This work was supported by the US Department of Energy, Office of Coordination and Special Projects, Space and Terrestrial Division.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

LA-9391-PR
Progress Report

UC-33a
Issued: June 1982

LA--9391-PR

DE82 016389

Environmental and Radiological-Safety Studies

**Interaction of $^{238}\text{PuO}_2$ Heat Sources with
Terrestrial and Aquatic Environments
January 1—March 31, 1982**

G. M. Matlack
J. H. Patterson

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy or completeness or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service, by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

DISTRIBUTION STATEMENT 1

ENVIRONMENTAL AND RADIOLOGICAL SAFETY STUDIES

Interaction of $^{238}\text{PuO}_2$ Heat Sources with Terrestrial and Aquatic Environments

January 1 - March 31, 1982

by

G. M. Matlack and J. H. Patterson

ABSTRACT

Although existing radioisotope thermoelectric generator designs have proved more than adequately safe, more information is continually sought about the heat sources to improve their safety. The work here includes studies of the effects on the heat sources of terrestrial and aquatic environments and also of the effects of the heat sources on various simulated environments. This progress report presents recent data from environmental chamber and aquatic experiments and gives the present status of the experiments.

No reference to results cited in this report should be published without the explicit permission of the person in charge of this work.

I. INTRODUCTION

The containers for $^{238}\text{PuO}_2$ heat sources in radioisotope thermoelectric generators are designed with large safety factors to ensure that they will withstand reentry from orbit and impact with the earth and safely contain the nuclear fuel until it is recovered. Existing designs have proved more than adequately safe, but the Space and Terrestrial Division of the Department of Energy Office of Coordination and Special Projects continually seeks more information about the heat sources to improve their safety. The work discussed here includes studies of the effects on the heat source of terrestrial and aquatic environments to obtain data for design of even safer systems and also information on the dispersal and environmental effects of the heat source fuels. This report includes data from environmental chamber experiments that simulate terrestrial conditions, soil-column experiments to measure sorption of plutonium by soils, and several aquatic experiments.

II. TERRESTRIAL ENVIRONMENTS

A. MHFT-12

The two experiments with chunks and fine particles from the impact-tested PPO sphere MHFT-12 were terminated last spring after 7 yr. A topical report will be written next quarter.

B. MHFT-27

Experiments were continued in two test chambers with fragments of the impact-tested PPO sphere MHFT-27 under arid winter conditions of 3 to 28°C and 21 to 87% RH. Chamber 10 contains 221 g of PPO pieces >6 mm in diameter on sandy soil. The rainwater that percolated through the soil after each of three monthly rains contained from 1.0 to 1.3 μCi plutonium, compared with the 0.05 to 0.14 μCi released during the previous quarter under arid summer conditions. This is the largest plutonium release observed during operation of this chamber and is consistent with previous observations that releases during winter are larger than those during summer. The average collection rate in the dehumidifier

condensate was 1.1 $\mu\text{Ci}/\text{wk}$, 40% more than in the previous quarter.

In chamber 7, in which 32 g of PPO MHFT-27 pieces <6 mm in diameter were under the same test conditions as in chamber 10, the percolated water contained 0.5 to 1.1 μCi , much more than the 0.06 μCi for the previous quarter. The average collection rate in the dehumidifier condensate was 0.92 $\mu\text{Ci}/\text{wk}$, up by a factor of 15 from the 0.06 $\mu\text{Ci}/\text{wk}$ rate of the last quarter.

C. MHFT-50

Fragments from an impact-tested PPO sphere, MHFT-50, and the top inch of loam soil had been removed from two test chambers after a 5-yr exposure to humid climate, and the experiments were continued for 1 yr to simulate a superficially cleaned area. The soil in each chamber is in two concentric compartments; the PPO was formerly in the inner compartment. The initial quantities had been 186 g of pieces larger than 2 mm in diameter in chamber 8 and 68 g of finer material in chamber 6. These experiments were terminated last quarter. A topical report will be issued.

D. ET-1-1

On February 27, 1981, we placed a 15-W cylinder of GROG fuel, designated ET-1-1, on a pedestal in chamber 12. The pedestal is located above a tray containing compartmented quadrants of sand, silt loam, loam, and humus. Rainwater striking the pedestal area drains directly, without flowing through the soils, to the dehumidifier condensate bottle. Thus, mainly spalled plutonium is present in the rainwater that percolates through each soil. The chamber was operated this quarter under humid summer conditions. The average plutonium contents of the percolated waters from weekly rains were 3 nCi for sand, 4 nCi for silt loam, 3 nCi for loam, 1 nCi for humus, compared to 2 nCi for sand, 8 nCi for silt loam, 9 nCi for loam, and 3 nCi for humus during the previous quarter under winter conditions. The average dehumidifier condensates contained 2.6 $\mu\text{Ci}/\text{wk}$, slightly higher than the 2.4 $\mu\text{Ci}/\text{wk}$ observed during the winter quarter. Most of this plutonium is from surface particles loosened by radioactive recoil and washed from the fuel source by rain. It appears that recoil processes contribute more significantly to plutonium release than does thermal spalling.

E. Microbiological Experiments

In May 1981, we placed a 15-W GROG fuel pellet, ET-3-5, on humus soil that had been inoculated with *Streptomyces pilosus* microorganism in chamber 11. This common soil organism produces Desferal, an organic chemical that is reported to complex plutonium. The objective is to determine whether this organism changes the amount of plutonium found in percolated rainwaters. The chamber is kept at 26°C and high humidity, and one weekly rain in five contains nutrients that support the growth of this microorganism. The percolated water from the rains this quarter contained an average of 6 nCi of plutonium, significantly less than the usual contents of several hundred nanocuries from other chambers with fuel pellets on the soil. Either the plutonium is being retained by Desferal or the fuel particles carried by the percolating rainwater are solubilized by Desferal and held by ion exchange action in the soil. It is also possible that the humus soil has a higher ion exchange capacity for plutonium than other soils.

III. AQUATIC EXPERIMENTS

A. Sealed-Glass-Chamber Experiments

A 15-W, bare, GROG fuel pellet has been in each of four sealed-glass chambers for 25 months for experiments designed to furnish material-balance data that are more complete than are obtainable from aquarium experiments. Two chambers contain simulated sea water at different temperatures of 10 and 35°C; the other two contain fresh water at the same temperatures. Table I gives the average of weekly measured plutonium release rates during this and the previous quarter. The release rate in warm fresh water is higher than was measured last quarter. The rates in the other three are essentially unchanged.

Table I. Plutonium Release Rates from Bare Pellets in Sea Water and Fresh Water in Sealed-Glass Chambers

Measurement Period	Average Release Rate (nCi/m ² -s)			
	Fresh Water		Sea Water	
	10°C	35°C	10°C	35°C
This quarter	1420	316	71	14
Prior quarter	1930	250	60	8

These data agree with previous data showing releases to be highest in cold fresh water and lowest in warm sea water. The causes for these differences are not understood at this time.

B. Aquarium Experiments

A new experiment was started last quarter with a Radioactive Heat Unit (RHU). The graphite-iridium-clad assembly was placed in an aquarium containing simulated sea water at 10°C. No significant plutonium levels have been detected in the water for 130 days.

Plutonium release data for six experiments using HPZ-designated sources over periods of 1 to 7 yr are summarized in Table II. These experiments are nearing completion, and four of the fuel sources have been removed. Measurements of the plutonium contents in these four aquariums will continue for 3 months to establish the decrease rate. To date, the release rates are decreasing in the aquariums where the sources were removed.

Sample HPZ-186-2 is the heat source used in the sea cucumber experiment. All three sea cucumbers have died. The decreasing release rate is probably caused by plutonium deposition on underwater algae.

The last four experiments shown in Table II were started in March 1981, using GROG heat sources. The objective is to determine the effects of sea water and fresh water immersion on fuel stability. The release rates are highest in cold fresh water and lowest in warm sea water, consistent with earlier experiments. This is the first time the effect of warm fresh water has been studied in aquariums.

C. Soil-Column Experiments

Of six soil-column experiments, three (designated 7, 8, and 9) use columns that are 14 cm high and 2.5 cm in diameter, each filled with silt loam soil. Each column contains 3 mg of $^{238}\text{PuO}_2$ particles. The approximate particle sizes are 50 μm for column 7, 12 μm for column 8, and 7 μm for column 9. All particles are on top of the soil column. Distilled water flows through the columns at 0.4 to 0.8 $\mu\text{l/s}$. The columns have now operated 61 months. The total plutonium contents of the effluents are 50, 63, and 69 ng, respectively, for columns 7, 8, and 9. These results substantiate that smaller particles release more plutonium than larger particles. The total percentage released is less than 0.002%. These experiments have been terminated.

In the other three columns, the sorption of soluble plutonium by sandy soils was being measured. The feed solution to the columns contained 15 $\mu\text{g/l}$ of ^{238}Pu in distilled water and flowed at a rate of 2 $\mu\text{l/s}$. After 575 days, about 99.5% of 1280 μg plutonium remained on the columns. This was less than the 99.9% retained by the silt loam soils. At about 600 days, a sudden breakthrough occurred where the plutonium increased by a factor of about 10. The breakthrough occurred with about 1.5 mg of plutonium on each column. This was never observed with loam soil columns that were fed soluble plutonium, even after 5 yr of operation, and represents the limited ion-exchange capacity of a sandy soil compared to loam soils.

Table II. Plutonium Release Rates from PPO in Aquatic Environments

Sample	Power (W)	Elapsed Days	Water	°C	Release (nCi/m ² -s)	Change from Last Quarter (%)
HPZ-60-2 ^a	2.5	2907	fresh	10	98	+400
HPZ-59-4 ^a	25	2650	sea	10	0.6	-40
HPZ-174	18	1595	sea	10	18	+360
HPZ-186-4 ^a	19	1591	sea (tidal)	10	5	-75
HPZ-186-2	15	608	sea	10	1.2	-8
ET-1-5	15	350	sea	10	122	+18
ET-2-2	15	350	fresh	10	160	+3
ET-2-4	15	350	fresh	37	72	+4
ET-2-6	15	350	sea	37	0.4	-40

^aSource removed from aquarium last quarter.