Technical Progress Report Number 2

DOE Contract Number DE-FG22-89PC89768

For the Period

December 1, 1989 - February 28, 1990

Submitted by
Aerosol Physics Research Group
Department of Physics
The Florida State University
Tallahassee, FL 32306-3016

Principal Investigator

Dr. W. Neil Shelton
Professor of Physics
(904) 644-6552

Report Editor

Wright C. Finney
Associate in Research
(904) 644-2878

MASTER

WCF

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

"US/DOE Patent Clearance is not required prior to the publication of this document."

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Technical Progress Report No. 2

(December 1, 1989 - February 28, 1990)

TABLE OF CONTENTS

	<u>Page</u>
A. INTRODUCTION AND SUMMARY.....	1
B. CONTRACT PROGRESS DURING QUARTER TWO.....	7
1. Task A - Precharger Modification.....	7
a. BG-2 Vacuum Station.....	7
b. MINACC Electron Beam Accelerator.....	10
2. Task B - Installation of Charge vs. Radius Apparatus.....	12
a. Description of Charge vs. Radius Apparatus..	12
b. Accomplishments during the Quarter.....	16
3. Tasks D-H - Preparations for Experiments.....	21
a. High Concentration Aerosol Generation.....	21
b. Data Acquisition and Analysis System.....	24
C. Visitors to the Laboratory.....	28
1. Dr. W.K. Rhim, Jet Propulsion Laboratory, Pasadena, California.....	28
D. PUBLICATIONS, PRESENTATIONS, AND PARTICIPATIONS.....	29
1. "Combined Removal of SO ₂ , NO _x , and Fly Ash from Flue Gas Using Pulsed Streamer Corona",.....	30
E. PERSONNEL.....	38
1. Retirement of Professor R.H. Davis.....	38
2. Current Personnel Listing.....	39

Removed

Figure Captions

- Figure 1. Top View of the Mk. III-B Electron Beam Precharging Module showing the Ionization and Charging Zones.
- Figure 2. Top View of the BG-2 Vacuum Station, the 100 keV Electron Beam Accelerator, and the Mk. III E-Beam Precharging Module.
- Figure 3. Schematic Diagram of the 100 keV Electron Beam Accelerator (MINACC).
- Figure 4. The FSU Two-Stage Electron Beam Precipitator (EBP) Wind Tunnel.
- Figure 5. The FSU Particle Charge vs. Radius (Q/A) Monitoring Apparatus, showing the Laser, Video Recording System, and the Particle Charge Measurement Cell.
- Figure 6. Vector Diagram of Various Inputs of the Particle Charge vs. Radius (Q/A) Monitoring Apparatus; E = Electric Field, G = Gas Flow, O = Viewing Direction, I = Laser Illumination. Diagram A: Fixed Experimental Vectors
Diagram B: Current Q/A Cell Design.
- Figure 7. Vector Diagram of the Proposed Q/A Cell Re-Design; E = Electric Field, G = Gas Flow, O = Viewing Direction, I = Laser Illumination.
- Figure 8. Schematic Diagram of the Fluidized Bed Aerosol Generator (FBAG) which resuspends Fly Ash and Hydrated Alumina (Hydral).
- Figure 9. The Microprocessor-based Data Acquisition and Analysis System serving the Electron Beam Precipitator.
- Figure 10. Circuit Layout of the Micromac (μ -Mac) Analog to Digital Converter showing the connections to the Precipitator Plate Electrodes and the Host Computer.

A. INTRODUCTION AND SUMMARY

Quarter Two of the Pulsed Electron Beam Precharger contract was primarily spent readying the various subsystems of the Electron Beam Precipitator (EBP) wind tunnel for experiments which are scheduled to commence during Quarter 3 or 4. Effort was devoted towards finishing all of the modifications and repairs to the precharging module, accelerator, and vacuum station. Upgrading the charge vs. radius apparatus proved to be a time-intensive task. Pulsed power supply testing which commenced this quarter will be reported on in the next Technical Progress Report. In preparation for operation of the E-Beam Precipitator wind tunnel, both the high concentration aerosol generator and the data acquisition system were overhauled. The laboratory was visited by Dr. W. K. Rhim of the Jet Propulsion Lab, and Dr. Robert H. Davis, long-time principal investigator of the Aerosol Physics Group, retired during the term.

Modifications to the precharging module (Figure 1) itself are for the most part complete. A 12 in. long x 6 in. high aluminum anode plate electrode resides along the outer wall of the 6 in. high x 8 in. wide polyvinyl chloride (PVC) inner precharging module. Opposite the plate anode is the precharging module annex which contains the electron beam accelerator. Mounted on the window housing is a circular grounded electrode of about 4 in. diameter. An electric field is applied between the large anode plate electrode and a "cathode" electrode composed of the aforementioned circular accelerator electrode and two smaller "wing" electrodes mounted to the precharging module wall adjacent to the annex. Particle charging occurs within the main body of the precharging module while the ionization zone is retained within the annex.

Progress was made toward re-commissioning back to reliable working order the 100 keV MINACC electron beam source and the BG-2 vacuum station serving the accelerator. Both devices had been used sparingly during the almost six-month long contract lapse period and were in need of repair and refurbishment. An assessment of the state of the MINACC and the BG-2 was made early in the term, and an ongoing effort to improve these systems continued this quarter.

The BG-2 vacuum station underwent an overhaul partially to correct several faults. Initially, the fore pump shaft seal was replaced, the diffusion pump was disassembled, cleaned, and new silicone oil was added, and the pneumatic test valve was repaired. After about one month of running, several water leaks developed in the diffusion pump cooling coils which required another vacuum station disassembly for a complete coil replacement. The BG-2 now seems to be functioning properly and it has attained an ultimate vacuum of about 5×10^{-6} torr which is satisfactory for the

Figure 1. Top View of the Mk. III-B Electron Beam Precharging Module showing the Ionization and Charging Zones.

requirements of the accelerator.

Window blowouts became an increasingly frequent problem when testing the 100 keV MINACC electron beam source with the overhauled BG-2 vacuum station. A visible buildup of brown, oxidized material was being deposited on the 0.0005 in. thick "Kapton" plastic film window. Excessive heating led to eventual failure of the window, necessitating time-consuming changeout procedures. The source of the oxidized material was thought to be the inside surface of the PVC accelerator containment tubes. Replacement of the damaged beam tube sections has, for the present, solved the window deposit and blowout problem. The beam focusing electrodes were also realigned, and a new hot cathode electron emitting filament was installed. Section B-1 contains a thorough description of the work accomplished on the BG-2 vacuum station and the MINACC E-beam source.

A unique charge vs. radius (Q/A) measurement device was earlier designed and constructed at FSU to be a semi-automated particle mass and charge data acquisition and retrieval system similar in function to a Millikan oil drop apparatus. Data obtained from this instrument showed that, in the high particle loading E-beam precharging runs using hydrated aluminum (Hydral) test dust, experimental particle charge was half of the predicted charge at that particular electric field and ion current density level. Normally, charge and radius measurements of this type must be made manually with the operator measuring the various particle parameters directly. The FSU system, however, can be operated remotely, and the data is recorded on videotape for real-time or future analysis.

Extended use of the Q/A measurement system during the last contract has pointed up several areas for improvement. Problems encountered included the instability of the mounting bracket on the laser mirror, a non-secure attachment of the remote control motor to the microscope objective focusing knob, a buildup of a visibility-obscuring film on all four sides of the charge measurement cell, and poor particle illumination in the cell. Applying a viscous lubricant to the mounting bracket and using silicone rubber cement on the focusing knob couple readily solved the first two problems listed above. The film deposit on the cell windows can be removed manually with a cotton swab, but other methods that do not interrupt the experiment, such as an air jet blast, are being investigated.

The latter problem, namely that of insufficient particle illumination in the charging cell, required a more thorough effort to remedy. A simple vector formalism was constructed to analyze the geometry of the cell. Gas flow direction, incidence of light origin and reflection, electric field orientation, and viewing (or video recording) position were all taken into account in proposing a new geometric arrangement. Instead of a vertical orientation below the cell, the laser was re-oriented to a horizontal position coincident with the viewing direction using a beam splitter.

Unfortunately, the glare from the front and back glass windows in the measurement cell "blinded" the video camera, precluding any permanent re-orientation of the laser beam. Other options to increase the particle illumination and decrease the particle deposition are being considered, which are discussed in Section B-2.

A major stumbling block for any program attempting to duplicate a fly ash-entrained gas stream in the laboratory has been the availability of a suitable dust feeder. Aerosol generation devices of many kinds have been developed by various companies and also at a number of research labs with varying degrees of success. Most of the dust feeders available commercially are very expensive, in the \$5000 - \$10,000 range. Although one of the lesser cost devices was purchased by the Aerosol Physics Group about 8 years ago, this feeder eventually proved to be unsuitable for evenly feeding the quantity and type of dust that is now used for the high particle loading E-beam precipitator study, namely hydrated alumina, or "Hydral".

During the present quarter, a redesigned fluidized bed aerosol generation (FBAG) system was completed and put on-line. Constructed principally out of a 2.5 ft. long, 3.5 in. inside diameter plexiglass tube, polyvinyl chloride (PVC) access hatch assemblies were fitted to the top and bottom ends. Two ports, one to allow dust to exit the tube and one to connect with the screw feeder via a hose, were installed in the upper access hatch. Into the lower access hatch was installed a compressed gas inlet to provide the fluidization mechanism. A dust feeding port leading to a screw feeder is located in the side wall of the tube just above the gas distribution plate.

The bed itself is composed of a semi-porous gas distribution plate tightly suspended within the tube with an o-ring seal. Across an aluminum ring is stretched a piece of wire cloth which is permeable to air but impermeable to dust or glass beads. A 0.5 cm. thick layer of solid glass spheres of between 100 and 200 μ m in. diameter rests on the porous screen. When sufficient compressed air flows through the screen, constant energetic collisions of the glass beads in the layer occurs; this action is known as fluidization.

Operation of the now functional fluidized bed is as follows. Fly ash or hydrated alumina bulk dust is loaded into the hopper of an AccuRate flexible hopper screw feeder. Dust is fed into the FBAG side port at a point where maximum fluidization of the glass beads is occurring. Deagglomeration of the dust clumps and clusters is insured by the violent bead motion. Compressed air pumped through the gas distribution plate keeps the fluidization process going, as well as providing the lift and gas flow to carry the resuspended dust particles out the top of the FBAG tube and into the EBP wind tunnel. Testing of the fluidized bed aerosol generator revealed an optimum gas flow rate of 7 cfm.

Data acquisition and analysis for the Electron Beam Precipitator have been handled by a ten-year old assemblage of equipment including an early microcomputer, a multichannel analyzer, and an analog-to-digital converter. A group of monitoring sensors feed signals into these three devices, completing the system. Particle size and number information and gas velocity and temperature readings are sent directly to the microcomputer, while the precharger and collector current signals are first routed through the Micromac (μ -Mac) A/D converter before going to the microcomputer. The Micromac measures and stores input data in continuously updated random access memory. Twelve total channels consisting of four channels per A/D converter measure voltage drops across precision resistors in order to obtain current readings for the 12 collector plates.

Sparkover between the high voltage wires and collector plates occasionally caused a malfunction in the Micromac circuitry despite the presence of an extensive array of spark protection devices and a comprehensive grounding network. At the end of the last set of experimental runs completing the previous contract, an episode of collector sparking caused a fault in the Micromac. Following an extended trouble shooting session this term, one A/D converter was replaced and calibrated using a separate computer terminal. In addition, the spark protection circuit was re-vamped in order to guard more effectively against the frequent high energy sparks which occur in the collector under normal operating conditions. The importance of protecting all of the integrated circuitry throughout the data acquisition, power supply, and vacuum station subsystems cannot be overemphasized. Section B-3 provides more detailed information on the preparations for experiments which are now centered on the aerosol generation system and the data acquisition system.

The Aerosol Physics Laboratory at FSU was visited this quarter by Dr. W.K. Rhim of the Jet Propulsion Laboratory, Pasadena, CA. Mutually beneficial discussions were held on the application of small electron beam sources in charging particles and larger solid granules. A tour of the laboratory and a decision to continue to explore joint research possibilities completed the day-long contact, which is outlined in Section C.

Publication activity for the term centered on the paper entitled "Combined Removal of SO_2 , NO_x , and Fly Ash from Flue Gas Using Pulsed Streamer Corona", by J. S. Clements, A. Q. Mizuno, W. C. Finney, and R. H. Davis. The paper was published in the IEEE Transactions on Industry Applications, Volume IA - 25, No. 1, pp. 62-69, January/February, 1989, and it is reprinted in Section D.

A major change in the composition of the Aerosol Physics Group occurred during Quarter Two. Principal Investigator Prof. Robert H. Davis retired from the Department of Physics at FSU and, as such, from the project after 32 1/2 years of service. Prof. W. Neil Shelton has agreed to take over the role of P.I. for the remainder of the contract. The current complement of personnel is listed in Section E.

CONCISE STATEMENT OF WORK PROPOSED

- Task A: Modification of precharger for pulsed and DC energization of anode.
- Task B: Installation of the Q/A measurement system.
- Task C: Modification and installation of pulsed power supply to provide both pulsed and DC energization of the precharger anode.
- Task D: Measurement of the removal efficiency for monodisperse simulated fly ash particles for two energization frequencies and several pulse heights.
- Task E: Measurement of particle charge for monodisperse particles for DC only and DC plus pulsed operation.
- Task F: Optimization of pulse energization schedule for maximum removal efficiency of test aerosol particles.
- Task G: Practical assessment of results for monodisperse test particles.
- Task H: Measurement of the removal efficiency for polydisperse test particles for two energization frequencies and several pulse heights.

B. CONTRACT PROGRESS DURING QUARTER TWO

1. Task A: Precharger Modification

a. BG-2 Vacuum Station

At the beginning of this term, one of the main objectives was to evaluate the BG-2 vacuum station (Figure 2) and to restore it to a reasonably reliable state of operation. This station provides the necessary vacuum to the 100 keV MINACC electron beam accelerator utilized in the electron beam precharging experiments. As this vacuum system had not been run appreciably in approximately 6 months, getting it back its previous level of dependability proved to be quite a task.

As a first step, the BG-2 was powered up and run through the normal start-up procedures. As a result, it was found that: 1) the fore pump connected to the outlet of the diffusion pump was leaking oil; 2) the "test valve" separating the inlet of the diffusion pump from the accelerator was sticking and would not open on its own; and 3) the ultimate vacuum attained after pumping on the accelerator for one day was on the order of 1×10^{-5} torr; which is the maximum pressure at which the electron beam source can operate effectively.

Upon examination of the fore pump, we found that it only needed a shaft seal. When a new seal was installed, the oil leak problem was solved. However, after much consultation with other vacuum technicians in the department, it was decided that a complete overhaul of the BG-2 vacuum station was in order. This entailed cleaning and changing the oil in the diffusion pump, overhauling the test valve, and replacing a four inch O-ring seal between the diffusion pump baffle and the test valve which had deteriorated.

When this work was completed, the vacuum station operated quite satisfactorily for approximately 6 weeks. Unfortunately, a cooling water leak soon developed in the upper cooling coils on the body of the diffusion pump. This particular leak was temporarily closed, but because the copper cooling coils were quite old and eroded, other more serious leaks soon developed. The vacuum station was dismantled again, and the diffusion pump re-wrapped with new tubing.

At present, it is felt that no more serious problems are likely to occur in the BG-2 vacuum system. Although several of the major components are at least 20 years old, regular maintenance and periodic upgrading should keep the station functional for the pulsed electron beam precharger experiments. It is now operating quite predictably and has attained an ultimate vacuum on the order

Figure 2. Top View of the BG-2 Vacuum Station, the 100 keV Electron Beam Accelerator, and the Mk. III E-Beam Precharging Module.

of 5×10^{-6} torr, which is significantly below the maximum allowable pressure for the MINACC.

b. MINACC Electron Beam Accelerator

The initial problems with the BG-2 vacuum station were eventually sorted out, and a program of testing and calibrating the 100 keV electron beam accelerator (Figure 3) began. After several successful test runs, accelerator window blowouts became an all too frequent occurrence. The accelerator window separates the interior components of the electron beam source (which must remain at high vacuum) from the particle-laden gas flowing through the precharger (which is at atmospheric pressure). Sudden loss of vacuum integrity in the accelerator generally causes a burnout of the hot cathode filament, resulting in a time-consuming disassembly of the E-beam source.

The window of the E-beam is a 0.0005 in. thick, 2.0 in. diameter sheet of DuPont "Kapton" plastic film clamped between two halves of the ground potential electrode on the downstream end of the accelerator. The geometry of this electrode forms a 1.0 in. diameter accelerator port through which the E-beam passes out into air. Kapton film of this thickness poses a negligible attenuation to 90 keV electrons. In the past, the life of this window, when properly mounted and under sufficient vacuum, was found to be several months.

After much investigation and two more window replacements, it was determined that the abnormally frequent window blowouts were due to excessive oxidation of the interior surfaces of the accelerator housing, which were made out of polyvinyl chloride (PVC) pipe. The impingement of the electron beam on the inside of the beam tube led to the liberation of oxidized molecules into the accelerator, which caused excessive beam scattering. In addition, the liberated molecules themselves were accelerated down the beam tube by the potential voltage drop, finally impacting the Kapton window. After sufficient accelerator run time, these particles formed an attenuating film on the window which caused excessive window heating, finally resulting in failure of the window. Resolution of this problem necessitated constructing new PVC beam tube sections to replace the existing ones, cleaning the interior accelerating electrodes, and replacing both the window film and the hot cathode filament electron source.

These steps effectively ended the formation of any window deposits and have restored the accelerator to a reliable state of operation. At this time we have completed the re-calibration and testing of the 100 keV MINACC electron beam accelerator, which is now ready for use in the pulsed E-beam particle precharging experiments.

Figure 3. Schematic Diagram of the 100 keV Electron Beam Accelerator (MINACC).

2. Task B. - Installation of Charge vs. Radius Apparatus

a. Description of Charge vs. Radius Apparatus

A device which had been used in earlier free electron particle charging studies, namely the charge vs. radius (Q/A) measurement system, has been applied to particle charging studies in the Electron Beam Precipitator wind tunnel (Figure 4). A sampling tube located just downstream from the end of the precharging module delivered a charged aerosol to the Q/A system. Experimentally determined particle charge levels were then compared with the theoretical values previously determined, and with values commonly found in corona wire ESPs.

The charge-to-radius measurement system (Figure 5) is a research apparatus originally invented in Japan and later fully developed at FSU. It is designed to determine the mass and charge of fine aerosol particles of the order of one micrometer diameter. This task is accomplished by observing the physical behavior of such particles in a controlled environment with known conditions. These conditions are:

1. A gaseous medium with minimal turbulence.
2. The action of gravity on a small particle of known density.
3. An oscillating uniform electric field with known frequency and voltage.

Since the behavior of a particle in such a well-defined environment can be predicted with well known physical laws and principles, it is also possible to reverse the process in order to determine information about the particle by applying those same physical laws to an unknown particle after monitoring its experimentally determined behavior.

The charge to radius measurement system consists of three subsystems: 1. the gas flow subsystem, 2. the electrical subsystem, and 3. the optical subsystem. Combining these three systems enables the desired measurement cell environment to be produced and the particles' behavior within this environment to be monitored.

The gas flow subsystem transports aerosol particles from the wind tunnel into the particle measurement cell, isolates them there for observation, and then passes them out the exhaust. An input and an output tube connect the apparatus to the aerosol source and to the exhaust vent, respectively. Two solenoid valves, the Q/A measurement cell, and a small pump constitute the subsystem proper. The two solenoid valves are located in one flow line, one before and one after the measurement cell. With both valves open the aerosol can flow easily through the entire gas flow subsystem, allowing the old aerosol sample to be cleared from the measurement cell and a new sample to be brought in. Closing the valves seals the aerosol particles in the cell at that time, stopping the gas currents and turbulence within the measurement cell. The pump is

F.S.U. ELECTRON BEAM PRECIPITATOR TEST SYSTEM

Figure 4. The FSU Two-Stage Electron Beam Precipitator (EBP) Wind Tunnel.

Figure 5. The FSU Particle Charge vs. Radius (Q/A) Monitoring Apparatus, showing the Laser, Video Recording System, and the Particle Charge Measurement Cell.

provided to facilitate gas flow throughout the tubing and cell.

The electrical subsystem produces the required oscillating electric field within the particle measurement cell. Two opposing metal plate electrodes are mounted vertically to the insulated walls of the Q/A measurement cell on either side of a clear observation window. A variable frequency AC power supply is connected to the two electrodes between which test particles are allowed to either oscillate or free-fall. In practice, the voltage and frequency applied across the electrodes is set to a known constant value for the duration of the experiment.

The optical subsystem allows the behavior of the test aerosol particles within the particle measurement cell to be observed and recorded. A microscope objective in place of a normal lens is mounted on a high resolution closed circuit video camera. This objective lens is focused upon the center of the glass walled Q/A measurement cell through which the aerosol flows. Particles trapped in the measurement cell are illuminated from below through a window mounted on the bottom of the chamber. A 0.8 mW He-Ne laser provides a well-defined, intensely lighted region between the cell electrodes. Particle oscillation and free-fall behavior are videographed through the microscope objective and displayed on the TV monitor screen. The signal is simultaneously recorded for later detailed analysis using the video tape recorder.

The raw data produced from these charge vs. radius experiments consists of a tape recording of a number of small white dumbbell-shaped "lines" falling downward. These lines are produced by the reflected laser light bouncing off the rapidly oscillating particles within the measurement cell. By measuring the length of these lines and the distance they fall in a given number of video frames of known duration, it is possible to determine the charge and the radius of the particle. Calculations of charge-to-radius (Q/A) ratios were done on either a microcomputer based spreadsheet program, or a BASIC computer program written specifically for this purpose.

b. Accomplishments During the Quarter

At the beginning of this contract period the entire charge vs. radius (Q/A) system was disassembled and the components of each subsystem were cleaned and refurbished in order to prepare for future experiments. Of special importance was the disassembly and cleaning of the Q/A measurement cell which had accumulated a thin film deposit on the observation window during the earlier high loading experiments. As was noted in the previous Technical Progress Report, this dust deposit was one of several deficiencies with the Q/A system in its current design incarnation. These problems are:

1) Poor particle illumination due to the small diameter of the laser beam relative to the cell width. Only those particles exactly within the beam boundary are illuminated sufficiently for measurement, but the beam diameter is too small to illuminate the entire measurement cell interior. Consequently, particles under study do not remain within the beam long enough to be easily measured.

2) Instability of the 90° laser mirror. The mirror's rotating stand is too easily jarred by outside forces, resulting in the laser beam becoming misaligned with the cell if the optics bench is disturbed.

3) The build-up of a particle film on all four sides of the measurement cell, especially on the front observation window, although the AC electric field plates are also affected. This coating severely restricts or prevents observation of particle behavior in the cell. The effect of the film on the AC field plates is unknown. This condition is a problem primarily in the high particle loading runs.

4) Inadequate coupling of the focusing motor to the microscope focusing knob. The original method of attaching the low speed motor to the focusing knob of the Q/A microscope by the use of set screws worked for only a short while before the set screws began to strip the threads of their mounting holes, thus slipping on the focusing knob. Eventually the set screws failed completely; a new method of attachment is needed. Two of the above problems were solved fairly easily.

The instability problem with the laser mirror was easily solved by disassembling it and greasing the rotating mechanism with silicone vacuum grease. This mucilaginous substance prevented the slippage caused by the pump and solenoid valve vibration. The motor was taken off of its mount and a new mount constructed for greater stability. The motor-focus knob coupler has yet to be reattached, but it is believed that a few dabs of silicone rubber cement between the coupler and the knob will provide the needed connection and yet still be removable if necessary.

The particle film deposit and the laser illumination problems proved to be far more intractable. The film deposit can be removed by disconnecting the gas input line and inserting a cotton swab into the cell and wiping the front observation window. Unfortunately, this solution requires a break in the experimental run and is not conducive to remote operation. The possibility of using an air jet to blast the window clean has been considered. The laser illumination problem is a difficult one which requires a re-analysis of the fundamental design of the Q/A measurement cell.

The Q/A cell must operate as an isolated gaseous chamber with certain geometric design requirements. These design requirements can best be illustrated using a vector formalism. The mass determination of a particle is produced by measuring the downward fall of that particle. This can be represented as a downward pointing vector $\underline{G}$. The particle charge is determined by suspending the particle in an oscillating electric field which must be perpendicular to the $\underline{G}$ vector; represented by an $\underline{E}$ vector. The particle must be observed from a direction perpendicular to both the $\underline{E}$ and $\underline{G}$ vectors; represented by an $\underline{Q}$ vector. These three vectors are fixed by the nature of the experiment and cannot be moved relative to one another (Figure 6-A).

Other aspects of the experiment can be represented as vectors also, but these are not required to be in any specific orientation relative to the fixed vectors, although some directions may be preferable. These are the direction of gas flow, both entering and exiting the cell, $\underline{GF}_{in}$ and $\underline{GF}_{out}$; respectively; the direction of the illumination beam $\underline{I}$, and the proposed window cleaning gas jet direction $\underline{WC}$.

The current vector design of the Q/A measurement cell is as follows (Figure 6-B). The particle-laden gas is brought in through the top of the cell and expelled from the bottom rear of the cell after making a 90 degree turn. Cell illumination is provided from an upwardly aimed laser source entering through a microscope cover side in the bottom of the cell. Test particles are therefore illuminated from below.

An alternative cell design (Figure 7) which might solve some of the current problems consists of the following changes: 1) switching the illumination direction from up through the cell bottom to concentrically in line with the observation direction by the use of a beam splitter. This change will illuminate the side of the particles facing the camera rather than the old method of illuminating the lower surface of the particle from below. The resulting increase in illumination (direct backscattered light, rather than 90° scattering) should more than compensate for the loss of light available for the camera due to viewing through the beam splitter. 2) The addition of a gas jet opening opposite the observation window to blast clean the observation window. 3) Shifting the gas flow exit from the bottom rear of the cell to the bottom, in order to remove one 90 degree gas turn and any resulting

Diagram 1: Fixed Experimental Vectors

Diagram 2: Current q/a Cell Design

Figure 6. Vector Diagram of Various Inputs of the Particle Charge vs. Radius (Q/A) Monitoring Apparatus; E = Electric Field, G = Gas Flow, O = Viewing Direction, I = Laser Illumination. Diagram A: Fixed Experimental Vectors
Diagram B: Current Q/A Cell Design.

Diagram 3: Proposed q/a Cell Design

Figure 7. Vector Diagram of the Proposed Q/A Cell Re-Design; E = Electric Field, G = Gas Flow, O = Viewing Direction, I = Laser Illumination.

turbulence that bend may cause.

The proposed design would require the construction of an entirely new particle measurement cell as well as several modifications to the optics subsystems. Before undertaking this non-trivial task it was decided to investigate the feasibility of the proposed changes. An air jet is expected to blast a thin coat of Hydral dust or fly ash off of the inner surface of the observation window. To test the ability of a quick blast of air to accomplish this task, a microscope slide was lightly coated with a wet Hydral solution and allowed to dry. Applying a blast of air from a hand-held air jet did not clear the window as was hoped. This result brought the utility of an air jet into doubt and the concept was at least temporarily shelved.

The possibility of changing the direction of cell illumination was tested by the construction of a separate microscope slide mount, and the repositioning of the rotating laser mirror beneath the microscope slide. This new mount allowed the positioning of a microscope slide in between the video camera and the measurement cell at any desired angle relative to the camera's line of sight. By tilting the slide at a forty-five degree angle relative to both the camera's line of sight and the reflected laser beam, the slide became partially reflective to the laser beam while maintaining partial transparency to the camera. Unfortunately, when this system was tested the glare off both the front and back of the measurement cell was so great that the camera optics were "blinded", and no video picture was obtainable. Therefore, this modification was also abandoned and the original illumination system was restored.

3. Tasks D.- H. - Preparations for Experiments

a. High Concentration Aerosol Generation

The main focus of attention this quarter has been centered around the completion of a redesigned fluidized bed aerosol generation (FBAG) system. The FBAG was constructed out of a vertical plexiglass tube which is 4 in. in outside diameter and approximately 2 1/2 ft. in length (Figure 8). Wall thickness of this tubing is 1/4 in., thereby making the inner diameter 3 1/2 in. The end caps of the fluidized bed tube were composed of two 4 in. clean-out female fittings otherwise known as "grease traps". This fitting consists of a 4 in. PVC pipe coupling on one side mated to a threaded female adaptor on the opposite side, into which a 4 in. threaded PVC plug is inserted. A small adaptor between the PVC pipe fitting and the tubing completed the assembly; this machined adaptor was necessary in order to allow the pipe to properly seat against the tubing. The PVC plug was used to allow easy access to the fluidized bed interior while providing an airtight seal to allow the fluidized bed to function properly.

The next step in the process was to modify the upper access hatch of the fluidized bed to allow the de-agglomerated dust to exit the chamber. Furthermore, the FBAG and the dust screw feeder had to be equally pressurized. In order to accomplish this requirement, an additional port was needed in the upper access hatch so that an air equalization hose from the dust hopper could be attached to the fluidized bed. Meanwhile, a fitting was installed into the bottom of the lower access hatch which allowed the connection of a compressed gas supply providing the fluidization mechanism.

A connection between the screw feeder and the side of the fluidized bed plexiglass tube was fabricated in order to feed dust to the region directly above the porous disk. A 1 in. PVC coupling and a 1 in. PVC threaded male adaptor were connected to the plexiglass tubing using a hole having 1 in. pipe thread. This port was located approximately 6 in. above the lower access hatch. The connector assembly was then glued to a 1 in. long piece of PVC pipe, which was then attached to the dust feeder on the adjacent end.

Feeding a steady stream of dust to the fluidized bed was an AccuRate series 300 dry material feeder. This dust feeder uses a flexible vinyl hopper and a rotating screw gear type of delivery method. A variable speed motor connected to the screw shaft allows the AccuRate deliver between .000003 and 4.16 cubic feet of dry material per hour. The configuration of the screw feeder is such that the screw gear extends through the 1 in. diameter PVC inlet pipe past the plexiglass tubing wall and into the interior of the fluidized beds where it directly deposits the dust into the glass bead bed material. Here, the dust is resuspended by a stream of

Figure 8. Schematic Diagram of the Fluidized Bed Aerosol Generator (FBAG) which resuspends Fly Ash and Hydrated Alumina (Hydral).

compressed gas filtering up through the gas distribution plate, de-agglomerated by the glass beads, and carried out the top of the closed plexiglass tube and into the wind tunnel.

The bed material, which is composed of Potters Industries Inc. Cat. #2227, US Screen Number 100-200 solid glass spheres, is supported by a semi-porous, rigid gas distribution plate. This plate was constructed according to the description in Technical Progress Report No. 1. An aluminum ring having an o-ring around its circumference was fitted snugly up against the inside of the plexiglass tube. Attached to the ring covering the open area was a woven wire screen composed of a patented product called Betamesh 30. Betamesh 30 is a Dutch weave wire cloth that is designed to allow higher gas flow rates, while retaining a larger portion of solids. This insures maximum air flow while preventing the bed material or dust from falling down through the screen. The gas distribution plate is located approximately 5 1/2 in. above the lower access door and approximately 1/2 in. below the dust inlet port.

After construction of the fluidized bed aerosol generation system and the screw feeder connection were completed, a test was performed to determine the flow rate needed to agitate the bed material and effectively resuspend hydrated alumina (Hydral) dust. After careful consideration it was determined that a flow rate of 7 cu. ft./min., which is approximately 12 % of the total volume of gas flow in the Electron Beam Precipitator wind tunnel, would provide maximum de-agglomeration without excessive waste of the compressed gas supply.

b. Data Acquisition and Analysis System

The Analog Devices, Inc., Micromac (μ -Mac) is an independent, microcomputer-based data measurement system (Figure 9) that can be connected to either a terminal or a host computer. It is used mainly in the collection and transmission of data acquired from the Electron Beam Precipitator (EBP) wind tunnel. An on-board microcomputer measures and stores input data in random access memory which is continuously updated at a rate of 15 readings per second. Several analog to digital converters as well as a main processing unit that receives and executes commands comprise the architecture of the device. The Micromac has twelve channels of input, or four channels per A/D converter, and each A/D converter unit can be configured to measure either voltage, current or temperature.

In the present application, the Micromac is used to measure the voltage drops across precision resistors connected to each of the electrode plates in the particle collecting section of the EBP. This information is then sent to the host computer for analysis and storage on magnetic media. A separate program which converts the voltage reading to current is run on the host computer (an old Z-80 microprocessor). Commands from this program are sent to the Micromac, thus automating the system to read data at different intervals of time.

Originally installed in 1982, the Micromac and the host computer have functioned satisfactorily for a wide range of collector operating conditions. An extensive network of spark protection devices and heavy grounding strips were installed in order to minimize the effect of infrequent but periodic collector wire-plate sparkover. An electrically shielded bunker housed the Micromac and the precision resistors to reduce the possibility of damage. Occasionally, however, during particularly energetic episodes of collector flashover, some unavoidable circuit failures would occur.

During a hiatus in the experimental run schedule, a problem developed with the Micromac. Four of the channels serving the collector read a constant zero on the host computer. The Micromac was tested and it was found that one of the three on-board analog to digital converters had malfunctioned. Since the converters are not repairable on-site, an order for a replacement part was sent and the new A/D converter circuit arrived from Analog Devices after five weeks. After the A/D converter was replaced, tests using a terminal only were carried out to ascertain that the system was operating normally. The Micromac was then configured to operate with the host computer and the system was tested again. A few problems determined by this configuration resulted in a delay of about two weeks before the repaired system produced adequate results. These problems were related to the spark protection devices that act on the input signal before it is sent to the

MICROCOMPUTER DATA ACQUISITION SYSTEM

Figure 9. The Microprocessor-based Data Acquisition and Analysis System serving the Electron Beam Precipitator.

Micromac.

A schematic of the wiring layout of the Micromac, the host computer, and the collector electrodes are shown in Figure 10. The inputs from the collector electrode plates go through a series of two spark protection circuits that are designed to shunt a high voltage pulse to ground in the event that an arc is sustained between a high voltage wire and an electrode plate in the collector. Data is then sent to the Micromac which is directly hooked up to a host computer situated in a remote location away from the collector. The communication line between the Micromac and the host computer consists of a 20 mA current loop instead of an RS232C interface. The reason for this is that a considerable distance (75 ft.) separates the Micromac and host computer, and signal attenuation would occur through such a long communications line. The communications line must travel to get to the host computer. The RS232C interface is recommended only for distances up to 50 ft.

FIGURE 1

Figure 10. Circuit Layout of the Micromac (μ -Mac) Analog to Digital Converter showing the connections to the Precipitator Plate Electrodes and the Host Computer.

C: VISITORS TO THE LABORATORY

1. Dr. W.K. Rhim, Jet Propulsion Laboratory, Pasadena, CA.

The Aerosol Physics Group at Florida State University was visited by Dr. Won-Kyu Rhim of the Modular Containerless Processing Facility, Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA, on February 12-13, 1990. His primary interest in visiting FSU was in learning more about various uses of small electron beam sources. The 100 keV maximum energy MINACC electron beam accelerator which was designed and constructed entirely at FSU became Dr. Rhim's principal focus during his visit. His group at JPL is interested in charging high temperature material samples for electrostatic levitation and containment in a microgravity environment. Since the Aerosol Physics Group has expertise in small, low energy (< 100 keV) electron guns, a lively discussion concerning various accelerator configurations ensued between the two parties. A tour of the Electron Beam Precipitator laboratory was followed by an in-depth description of the particle charging research currently being conducted at FSU. A continuing dialogue between the two parties concerning electron beam technology is planned.

D: PUBLICATIONS, PRESENTATIONS, AND PARTICIPATIONS

1. "Combined Removal of SO₂, NO_x, and Fly Ash from Flue Gas Using Pulsed Streamer Corona".

The paper entitled "Combined Removal of SO₂, NO_x, and Fly Ash from Flue Gas Using Pulsed Streamer Corona", authored by J. Sidney Clements, Akira Q. Mizuno, Wright C. Finney, and R. H. Davis, was recently published in the IEEE Transactions on Industry Applications, Volume IA-25, No. 1, pp. 62-69, January/February, 1989. The paper was originally presented at the Industry Applications Society Annual Meeting held in Denver, CO, in September of 1986. The paper details a technology using positive pulsed streamer corona in a module similar to an electrostatic precipitator for the simultaneous removal of the gaseous pollutants SO₂, and NO_x, and the particulate effluent fly ash.

pp 30-37 removed -

E: PERSONNEL**1. Retirement of Professor R. H. Davis.**

A major change in the complement of personnel associated with the Aerosol Physics Group occurred during the second quarter of the contract period. Professor Robert H. Davis, Principal Investigator of the present contract entitled: "Pulsed Electron Beam Precharger," retired somewhat unexpectedly in December, 1989. Dr. Davis was the funded and head of first the Electron Beam Precipitator Project and, later, the Aerosol Physics Group at FSU. This work, beginning in 1978, has been funded by an almost interrupted sequence of contracts of between two and three year's duration, interspersed by several relatively short lapse periods. The loss of such a central figure in the project will no doubt influence the contract research in some ways, but plans have been formulated to reduce as much as possible the impact of Dr. Davis' retirement.

Taking the place of R. H. Davis as Principal Investigator for the remainder of the current contract will be Professor W. Neil Shelton of the Department of Physics at FSU. Dr. Shelton's experience in Atomic and Molecular Physics and Collision Phenomena should serve him well in his role as project head. The following sub-section lists the other members and their roles presently with the Aerosol Physics Group.

2. CURRENT PERSONNEL LISTING

Scientific Investigators

1. Dr. Robert H. Davis	Principal Investigator
2. Dr. W. Neil Shelton	Principal Investigator-Designate
3. Mr. Wright C. Finney	Associate in Research

Graduate Student Assistants

1. TBA

Undergraduate Student Assistants

1. David Eibeck
2. Arnnie Gibson
3. Chris Oswald
4. Misho Sarwar

Part-time Secretaries

1. Natalie Duguid
2. Cheryl Brown
3. Amy Maxey

END

**DATE
FILMED**

8 / 17 / 92