E66

An Investigation of the Role of Water on Retrograde/Condensation Reactions and Enhanced Liquefaction Yields

Francis P. Miknis

January 1993

Quarterly Progress Report for the Period October 1, 1992 - December 31, 1992

Work Performed Under DOE Contract, DE-AC22-91PC91043

By

**Western Research Institute
Laramie, Wyoming**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

BACKGROUND

The overall objectives of this work are to conduct research that will provide the basis for an improved liquefaction process, and to facilitate our understanding of those processes that occur when coals are initially dissolved. Changes in coal structure that occur during coal drying and steam pretreatments will be measured in order to determine what effect water has on retrograde/condensation reactions, and to determine the mechanism by which water enhances coal reactivity toward liquefaction. Different methods for coal drying will be investigated to determine if drying can be accomplished without destroying coal reactivity toward liquefaction, thereby making coal drying a relatively economical and efficient method for coal pretreatment. Coal drying methods will include conventional thermal drying, microwave drying, and chemical drying at low temperature. State-of-the-art solid-state nuclear magnetic resonance (NMR) techniques using combined rotation and multiple pulse spectroscopy (CRAMPS) and cross polarization with magic-angle spinning (CP/MAS) will be employed: (1) to measure changes in coal structure brought about by the different methods of drying and by low temperature oxidation, and (2) to obtain direct measurements of changes in the aromatic hydrogen-to-carbon ratio of the solid/semisolid material formed or remaining during pretreatment and the initial stages of liquefaction. The aromatic hydrogen-to-carbon ratios are difficult, if not impossible, to measure without the use of solid-state NMR, and as a result this ratio will be used to monitor the retrograde/condensation reactions that take place during coal liquefaction in the presence and absence of steam and various inert gases.

RESULTS

The objectives for this quarter were to begin coal drying experiments using thermal, microwave, and chemical methods. The initial coal drying experiments are being conducted on an Eagle Butte coal from the Powder River Basin near Gillette,

Wyoming and a Usibelli coal from Alaska. Both coals are subbituminous rank. Some microwave drying experiments were also conducted on a subbituminous coal from the Caballo Rojo mine in Wyoming. A stirred microautoclave reactor system that was acquired during the previous quarter was installed and tested. Work on each of the subtasks is described in separate paragraphs.

Coal Preparation

A master batch sample (~500 g) of Caballo Rojo subbituminous coal was prepared for use in the microwave coal drying experiments. The sample was prepared by grinding and screening to -20, +100 mesh particle size. This sample was placed in a wide mouth jar and placed in an oven with a beaker of water, and allowed to equilibrate at 40RC for 24 hrs. The sample was then removed from the oven and placed in a humidifier until aliquots were taken for the different drying tests.

Thermal Drying

Samples of the Eagle Butte subbituminous coal were heated to different final temperatures in order to determine at what temperature, significant structural changes begin to occur that might affect the liquefaction behavior. These heating experiments are referred to as ballistic heating experiments. The ballistic heating experiments were performed with a small, vertically aligned furnace. The furnace has a 12-centimeter long heated section which accepts a 1.4-centimeter i.d. quartz liner. A stainless steel screen provides support for the coal and a steel wool pack heats the nitrogen sweep gas which is introduced at the bottom of the quartz liner. In a typical experiment, the furnace is preheated to about 10RC above the desired final coal temperature. A 2-gram coal sample is then poured into the quartz liner and a thermocouple is inserted into the coal sample bed. When this thermocouple reaches the desired temperature, the quartz liner is removed from the furnace and allowed to cool. Nitrogen flow is maintained at all times. When the sample temperature is below 50RC the coal is poured into a sample vial, capped with

nitrogen, and sealed. Heatup times with this system are typically from 15 to 20 minutes.

Samples of the Eagle Butte coal were ballistically heated to final temperatures of 100, 150, 200, and 250 RC. Solid-state ^{13}C NMR measurements were made on the heated samples, and are shown in Figure 1 for the starting coal, and coal heated to 150, and 250 RC. The spectra indicate that under this method of heating, there are no significant changes in carbon functionality up to temperatures of 250 RC, except for some deterioration in resolution of branched aromatic carbons (~140 ppm), phenolic carbons (~155 ppm), and carboxyl carbons (~180 ppm).

Microwave Drying

Microwave drying is an alternative thermal method of drying coals. However, the mechanism of drying with microwaves is different from that of simply heating the coal. In order for a substance to absorb microwaves and become heated, it must have a permanent dipole moment. Therefore, the functional groups that are the most efficient absorbers of microwaves are those that are highly polar, such as the -OH group in water.

When a substance containing water molecules is exposed to microwaves of the proper frequency (2,450 MHz) the water molecules attempt to align and realign with the alternating electric field of the microwaves. This causes friction at the molecular level, which becomes manifested as heat. Because the water in coals can be distributed on the surface, in pores, or as part of the coal structure as in a gel, depending on rank, microwaves might be used to provide some selectivity for coal drying without appreciably affecting the overall coal structure and liquefaction behavior of the coal.

The objective of the microwave drying subtask is to determine whether microwave drying alters the structure and composition of the coal, and hence its behavior toward liquefaction. This work was prompted by earlier work of Silver and Frazee

(1) that showed that drying coal with microwaves beyond ~75% moisture removal actually had a detrimental effect on the reactivity toward liquefaction. However, there has not been a systematic study of changes in coal structure induced by microwave drying.

A number of microwave drying experiments using the Eagle Butte and Caballo Rojo subbituminous coals were conducted during the quarter. The microwave drying tests were conducting in the following manner: ~ 2 grams of coal were placed in 25 mL beakers, and the beakers placed at the center of the microwave oven. Samples were exposed to microwave radiation for different periods of time and at different power levels, after which the samples were removed from the oven and a thermocouple inserted into the coal bed to determine an average temperature.

At full power (600 watts), 75 % or greater of the moisture was removed in ~2 min., and removal of the remaining moisture caused the temperatures to increase rapidly (Figure 2). Because of the rapid moisture removal at full power, different levels of microwave power were used in order to obtain a more complete drying curve. At power levels of 300 watts, 25 -75 % moisture could be removed for irradiation times of up to 15 min.

The general features of the coal drying curves using microwave radiation are shown in Figure 2. In general, there is a very rapid temperature rise after ~10 % of the moisture is removed. This is followed by removal of the bulk of the moisture (10-80%) at temperatures close to the boiling point of water, which is ~ 93RC at the 7,200 ft elevation in Laramie, WY. The rapid increase in temperature after >75% of the moisture is removed seems to be a general characteristic of microwave heating of subbituminous coals. This behavior was also observed by Silver and Frazee (1), who also noted a decreased reactivity toward liquefaction for greater than 75% moisture removal. We speculate that beyond this level of moisture removal, the additional moisture that is removed is an integral part of the gel or pore structure of the coal. These water molecules have a more difficult time aligning and realigning with the radiation field, and thus would cause heating to higher temperature, and possible

disruption of part of the coal matrix enabling some retrograde reactions to take place that diminish the reactivity toward liquefaction.

The total microwave energy experienced by a coal sample appears to be important to the removal of moisture from the coal. As shown in Figure 3, the amount of moisture removed is a relatively smooth function of the total microwave energy applied. The total energy was obtained by multiplying the calibrated microwave power level in Watts by the total coal exposure time in seconds. The results, in total kilojoules of energy, are the abscissa in Figure 3. The moisture removed was determined in each case by comparing the sample weight lost in the microwave with a thermally dried standard sample.

Chemical Drying

No work was done on this subtask during the quarter because of lack of available personnel. Work will resume next quarter.

Coal Liquefaction Experiments

Shakedown experiments are being performed with the microautoclave system using undried western subbituminous coal and tetralin. The initial goals of these experiments have been to evaluate the performance of the system and to test and establish operating procedures. Example results from one of the shakedown experiments are shown in Table 1. A 1:1 mixture of Caballo Rojo coal and tetralin was heated for one hour at 400 RC in a helium atmosphere. The initial helium charge pressure was 1000 psig. After cooldown, product gases were collected in 5 liter containers and analyzed by gas chromatography. The gas analysis results are also shown in Table 1. The trace of argon in the analysis is a remnant of a volume calibration performed immediately prior to the experiment. Liquid and solid products were removed from the reactor by a combination of decanting and dichloromethane wash. The material balance for run CLF3, as shown in Table 1 was 98.8 wt%.

Table 1. Experiment conditions and material balance for CLF3.

Run Conditions		Material Charged	
Run Number	CLF3	Coal	19.9
Temperature	400 C	Tetralin	20.1 g
Duration	60 minutes	Material Recovered	
Coal Type	Caballo Rojo		
Solvent	Tetralin		
Charge Gas	Helium		
Charge Pressure	1000 psig		
		Paste	37.4 g
		Spindle Wash	0.5 g
		Gas	1.6 g
		Total Material Recovered 98.8 wt%	

Gas composition, wt%

Hydrogen	0.0
Nitrogen	11.4
Argon	1.5
Carbon Monoxide	5.6
Methane	5.9
Carbon Dioxide	60.8
Ethene	1.2
Ethane	4.2
Water in gas	2.9
Hydrogen Sulfide	0.0
Carbonyl Sulfide	0.0
Propane	5.1
iso Butane	0.4
normal Butane	1.0

Miscellaneous

Abstracts of papers were submitted for presentation at the American Chemical Society national spring in Denver, Colorado March 28-April 3, 1993 and the

International Conference on Coal Science, Banff, Alberta September 12-18, 1993. A preprint was prepared for the ACS meeting in Denver.

REFERENCES

Silver, H.F., and W.S. Frazee, 1985, Integrated Two-Stage Coal Liquefaction Studies, Laramie, WY, August 1985, Final Report, EPRI project RP2147-3.

Figure 1. CP/MAS ^{13}C NMR spectra of ballistically-heated Eagle Butte subbituminous coal.

Figure 2. Coal temperature as a function of moisture removal for microwave drying.

Figure 3. Coal temperature as a function of microwave energy.

END

DATE
FILMED

5 / 10 / 93