Revised OSTI

AUG 13 1992

K/ETO-93

MARTIN MARIETTA

Gas-Phase Chemical Reactivity
of CFC-114 and
Potential Replacements
Part IV: Reactivity of $c\text{-C}_4\text{F}_8$
with F_2 and UF_6

L.D.Trowbridge
E.C.Angel

Enrichment Technical Operations Division

July 1992

MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

K/ETO--93

DE92 019277

Enrichment Technical Operations

GAS-PHASE CHEMICAL REACTIVITY
OF CFC-114 AND POTENTIAL REPLACEMENTS

PART IV:
REACTIVITY OF $c\text{-C}_4\text{F}_8$ WITH F_2 AND UF_6

L.D.Trowbridge
E.C.Angel

Date Published -- July 1992

Prepared by the
URANIUM ENRICHMENT ORGANIZATION
Oak Ridge, Tennessee 37831-7266
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S.DEPARTMENT OF ENERGY
under Contract No. DE-AC05-76OR00001

MASTER

12
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

TABLE OF CONTENTS	iii
ABSTRACT	v
INTRODUCTION	1
EXPERIMENTAL	2
RESULTS AND DISCUSSION	6
Data and Data Analysis	6
F ₂ Experiments	9
UF ₆ Experiments	30
Summary of Results	32
Discussion	32
CONCLUSIONS	35
APPENDIX A - IR Calibration	36
APPENDIX B - Estimated Magnitude of Systematic Errors	39
ACKNOWLEDGEMENTS	41
BIBLIOGRAPHY	42

ABSTRACT

The DOE gaseous diffusion plant complex makes extensive use of CFC-114 as a primary coolant. As this material is on the Montreal Protocol list of materials scheduled for production curtailment, a substitute must be found. In addition to physical cooling properties, the gaseous diffusion application imposes the unique requirement of chemical inertness to fluorinating agents. A series of studies has therefore been undertaken to evaluate the gas-phase chemical reactivity of potential alternate coolants. This report examines the reactivity of perfluorocyclobutane ($c\text{-C}_4\text{F}_8$) with UF_6 and F_2 at selected reference conditions (approximately 10 Torr partial pressure of each reactant at 150°C). At the reference conditions, a very slight degree of reactivity was observed with F_2 , but much less than the observed reactivity of the reference coolant, CFC-114. No reaction was observed with UF_6 . A limited number of experiments was conducted at higher temperature, providing a first estimate of the rate of increase of reaction rate with increased temperature.

INTRODUCTION

Evidence supporting the theory that chlorofluorocarbons (CFCs) contribute to reduction of ozone in the stratosphere has prompted a significant national and international response over the last several years, most notably the September 1987 signing of the Montreal Protocol¹ and its adoption the following year by the major CFC producing and consuming nations of the world. More recently, this phase-out schedule has been accelerated. The planned reduction in production of CFCs in turn has significant implications for the operation of the Department of Energy's gaseous diffusion uranium enrichment complex in the United States, since one of the regulated materials, CFC-114, is the primary coolant for the gaseous diffusion plants.

The CFC manufacturers' response to the evolving concerns with CFCs has been vigorous. The major manufacturers were, even prior to the regulation of these substances, developing substitutes for the restricted materials in widest use. Most such potential substitutes are compounds termed HCFCs (hydrochlorofluorocarbons) and HFCs (hydrofluorocarbons). These compound classes are chemically similar to CFCs or PFCs (perfluorocarbons, or fully fluorinated hydrocarbons), but differ in that they contain one or more hydrogen atoms in place of halogens. The addition of hydrogen makes these compounds somewhat more susceptible to reaction with hydroxyl radicals in the lower atmosphere, thus leading to their earlier removal, shorter atmospheric lifetime, and diminished ozone depletion potential relative to CFCs. These are the classes of compounds likely to be available in quantity on the commercial market in a few years as CFCs are phased out.

Unfortunately, the gaseous diffusion complex imposes requirements on its coolant that are not generally found in commercial cooling applications. Most notable is that the coolant must possess a reasonable degree of chemical compatibility with UF_6 . One of the compatibility issues that must be addressed in choosing a replacement coolant is the effect of coolant leakage into the UF_6 stream in the cascade. UF_6 is a fairly potent fluorinating agent, so the possibility of gas-phase or gas-surface reactions of UF_6 and a substitute coolant must be considered. In addition, gaseous diffusion equipment is routinely subject to off-stream cleanup treatments with the more potent fluorinating agents F_2 and ClF_3 , so the reactivity of coolant with these materials must also be minimal.

Because of this unique reactivity requirement, Martin Marietta Energy Sys-

tems, which operates the two US DOE diffusion plants, has initiated contacts with potential producers of substitute coolants. Candidate materials which could be produced in the quantities needed have been proposed, and small quantities have been supplied to Martin Marietta for evaluation. This report is the fourth in a series^{2,3,4} which discusses results of screening tests performed on these candidates. The results discussed here pertain to cycloperfluorobutane (c-C₄F₈), also known as FC-c318. Its structure is as follows:

These screening tests are intended to examine the gas-phase reactivity of candidate coolants with UF₆ and F₂. These are "screening" tests in the sense that the experiments are designed to compare relative behavior under a fixed set of conditions similar to those that might pertain in operating diffusion plant equipment. The range of conditions chosen are not generally extensive enough to definitively deduce reaction kinetics and mechanisms, although some small progress in this regard will be reported below.

The report series of which this document is a part is divided into sections specific to each material tested. The first report in the series² discussed in some detail the experimental apparatus, procedures, and data analysis, as well as the results for the reference coolant, CFC-114. The second report in the series³ discussed results on HCFC-124, which proved to be significantly more reactive than CFC-114, and the third report⁴ covered reactivity of normal perfluorobutane (n-C₄F₁₀), which proved to be much less reactive than CFC-114.

EXPERIMENTAL

The experimental system is described in more detail in Reference 2. Briefly, it consists of a loop of monel tubing around which the gases are driven by a metal bellows pump. The majority of the volume of this loop is contained in a 5.1 cm diameter nickel reaction tube situated in a muffle furnace. In most of the experiments reported in this document, the reaction tube was packed with sintered nickel filter material similar to gaseous diffusion barrier. A few

experiments were also performed with this high surface area packing material removed. The circulating gas also passes through an infrared gas cell situated in a Nicolet 5DXB Fourier Transform Infrared Spectrometer (FTIR). The FTIR is used to automatically collect and store spectra of the gas at intervals during the course of an experiment. A modification to the experimental system as described in reference 2 is the addition of a third capacitance manometer to the loop. This pressure transducer is located in the immediate vicinity of the IR cell, thus allowing (nearly) direct reading of the IR cell pressure. Previously, pressure readings in the IR cell, required for quantitative interpretation of IR spectra, had been interpolated from measurements at the other transducers.

Prior to an experiment, the system is evacuated to about 10^{-5} Torr and the tube furnace brought to operating temperature. The reactant gases are mixed sequentially: the first about 10 Torr of one reactant, then 80 additional Torr of Argon, and finally 10 additional Torr of the second reactant are introduced into the circulating loop. In UF_6 experiments, UF_6 is the first gas added to the loop (to avoid condensation problems at 100 Torr); in F_2 experiments, C_4F_8 was added first to minimize material use in the gas addition manifold. The addition of the second reactant is taken as time "zero", and infrared spectra are collected beginning at that time. Table 1 lists the experimental parameters for the experiments discussed in this report.

Reactant mixing is accomplished by the shearing action of continuously pumping the gas around the flow loop. The time constant for mixing (i.e. stabilization of concentrations to their final values) was on the order of 12 minutes in blank runs (i.e. runs in which the oxidizer was not present). The cause of this delay appears to be that addition of a gas to the system compresses the gas mixture already in the loop into dead-end regions remote from the inlet point (e.g. volumes contained in the pressure instrumentation or the bodies of pump-out valves). Gas circulation rapidly mixes the gases in the loop (i.e. within a few tens of seconds), but the unmixed gases in dead end lines must mix by diffusion. Though kept to a minimum, the dead end sections of the loop are between 5 and 20 cm in length. The concentration equilibration rate observed is consistent with the expected time constant for diffusion of these gases at 100 Torr for such dimensions.

The implication of these observations is that changes in apparent concentration occurring early in an experiment should not necessarily be taken as due to reaction unless there is other confirming evidence (e.g. similar reaction

rates later in the experiment or the appearance of corresponding quantities of reaction products at similar rates).

Table 1: Experimental Parameters for c-C₄F₈ Reactivity Experiments

Exp. # ^a	Temp °C	P _{ox.} ^a Torr	P ₃₁₈ Torr	P _{oven} Torr	P _{IR-cell} Torr	Cyl #
F150A	148	8.9 ^b	7.4	99.5	88.3 ^c	19
F150B	149	8.8 ^b	9.1	99.6	88.4 ^c	2
F150C	150	9.3 ^b	9.2	100.0	88.5	11
F150D	151	8.6 ^b	10.0	98.6	87.6	8
F150E	148	9.6 ^b	9.4	100.3	89.1	5
F150F	151	9.4 ^b	10.1	99.9	88.8	14
F150G ^d	149	9.2 ^b	9.9	100.9	89.8	11
F200A	200	10.0 ^b	9.1	100.4	88.9	11
F250A	250	9.4 ^b	9.2	99.9	88.3	11
F250B ^d	250	9.1 ^b	10.2	100.0	88.9	11
U150A	150	9.4	8.5	100.8	94.8 ^c	19
U150B	149	8.9	9.8	100.5	90.4 ^c	2
U150C	150	7.8	9.7	101.0	90.4	11
U150D	150	8.0	10.6	101.1	90.8	8
U150E	150	7.9	14.4	106.0	95.8	5
U150F	151	8.5	11.0	101.2	91.1	14
U250A	248	8.6	9.9	100.4	90.3	11

^a Oxidizer used in experiments beginning with "F" and "U" was F₂ and UF₆ respectively.

^b F₂ partial pressure was estimated by system pressure change on addition of F₂.

^c System pressure at IR cell (P_{IR-cell}) interpolated, as the manometer at the cell was not operational in these experiments.

^d Experiment run without high-surface area sintered nickel filter in oven.

General: Unless otherwise indicated, partial pressures (UF₆ and C₄F₈) are calculated from IR spectra, and represent the partial pressure in the IR cell; the overall system pressures are measured by capacitance manometer near the listed location

The UF_6 used in these experiments was derived from subsamples of natural assay feed of the (now shut-down) Oak Ridge Gaseous Diffusion Plant. The fluorine was purchased from Air Products, and had a nominal purity of 98.5%.

Six samples of $\text{c-C}_4\text{F}_8$ were obtained for this series of experiments. We have locally designated the samples as 2, 5, 8, 11, 14, and 19, based on cylinder label numbers. Selected impurities originally in these samples, per the manufacturer's gas chromatography analyses, are listed in Table 2. The major impurities are related fluorocarbons. Sample 19 did not have extensive GC analysis, but was indicated to be 96% pure.

Table 2 - $\text{c-C}_4\text{F}_8$ Sample impurities per manufacturer, as determined by GC. Quantities are in mole percent.

Designation	2	5	8	11	14	19
Constituent						
c318	96.4	96.1	88.0	99.9	98.3	96.0
31-10	0.01	0.02	3.2	ND	0.02	NA
other PFCs	0.2	0.3	1.9	ND	ND	NA
1216	0.7	0.03	0.9	0.03	ND	NA
1318	2.6	3.5		0.02	1.7	NA

Notes

1. Component designations are as follows:

c318 = perfluorocyclobutane : $\text{c-C}_4\text{F}_8$

31-10 = perfluorobutane (both normal and iso) : C_4F_{10}

other PFCs: fully fluorinated saturated linear or cyclic fluorocarbons, other than C_4F_{10}

1216 = hexafluoropropene : $\text{CF}_3\text{CF}=\text{CF}_2$

1318 = cis- or trans- perfluorobutene : $\text{CF}_3\text{CF}=\text{CFCF}_3$

2. "ND" means "none detected"; "NA" means analysis "not available"

(We do not have an extensive GC analysis for Sample 19)

This section has given only a fairly abbreviated description of the experimental apparatus and procedures. The reader is referred to Reference 2 for a more complete description.

RESULTS AND DISCUSSION

Data and Data Analysis: The raw data for these experiments consist of a series of infrared spectra taken at intervals throughout the course of an experiment. Figures 1 and 2 show examples of such spectra. In Figure 1 the initial and final spectra for one of the $F_2 + C_4F_8$ experiments (designated F150F) are shown. Figure 2 illustrates the results of spectral subtraction. The initial spectrum has been appropriately attenuated to exactly cancel the remaining $c-C_4F_8$ in the final spectrum; subtraction of the attenuated initial spectrum from the final spectrum yields the "spectral subtraction" plot in Figure 2. Also plotted is a reference spectrum of $n-C_4F_{10}$. These two spectra match quite well.

At least one experiment was performed on each sample with each oxidizer under the previously defined conditions. In each experiment, reaction products (if any) were identified primarily by means of spectral subtraction and comparison to reference spectra. This operation was performed on the final spectrum of each series. Spectral subtraction was accomplished by means of software inherent to the Nicolet 5DXB system.

Spectral subtraction is a rather labor-intensive operation; a more automated procedure was used to extract quantitative information on the major gas constituents from the complete time series of spectra. In this procedure, characteristic absorbance bands were chosen to represent each identifiable reactant or product. The absorbances for characteristic bands of interest were read using the built-in "peak-pick" routine in the Nicolet 5DXB. In addition, absorbance values for nearby spectrum baseline regions (i.e. adjacent areas of minimal absorbance) were also read. Spectrum baselines can shift during the course of an experiment due to optical changes in the window material (adsorption or reaction on the infrared window; scattering by dust or defects on the window; refraction due to window distortion). When the absorbance changes which one seeks to observe are small, correction for small baseline changes is important.

The net absorbances ($A - A_{base}$) for the monitored bands are listed in Tables 3 through 19. The identity and partial pressures of components observed by spectral subtraction in the final spectrum of the series are listed for all experiments in Table 20. Partial pressures of the reactants listed as "initial" are from the spectrum that was taken as soon as possible after gas mixing is expected to be complete (i.e. at approximately one half hour). The absorb-

Figure 1 - IR spectra from beginning (top curve) and end (bottom curve) for Experiment # F150F (F₂ + c-C₄F₈)

Figure 2 - Bottom curve: Spectral subtraction of initial $c\text{-C}_4\text{F}_8$ spectra from final spectrum in Experiment #F150F
Top curve: Reference spectrum of $n\text{-C}_4\text{F}_{10}$

ance shown is scaled to a 1 cm path length; the IR cell used actually had a pathlength of approximately 2 cm (the pathlength varied by a few mm with window distortion).

Using the Beer's Law-based calibration factors listed in Appendix A, absorbance can be converted into partial pressure. Figures 3 through 19 show such results for these experiments. These figures show partial pressure of C_4F_8 and of UF_6 where appropriate. F_2 is not infrared active: its concentration thus could not be followed in these experiments.

F_2 Experiments

The F_2 experimental data are shown in Tables 3 through 12 and plotted in Figures 3 through 12. Note that in several cases the plots' vertical axes are considerably magnified to reveal the slight partial pressure decline that occurred in these experiments.

Table 3: $A-A_{base}$ (absorbance/cm pathlength)
for $F_2 + c-C_4F_8$, Sample 19
Expt # F150A, $T = 148^\circ C$

Time <u>hrs</u>	C_4F_8 <u>$962cm^{-1}$</u>
0.00	0.407
0.03	0.402
0.41	0.412
3.97	0.412
9.98	0.403
16.00	0.395

Table 4: $A - A_{\text{base}}$ (absorbance/cm pathlength)
for $F_2 + \text{c-C}_4F_8$, Sample # 2,
Expt # F150B, $T = 149^\circ\text{C}$.

Time hrs	C_4F_8 962cm^{-1}	$\text{n-C}_4\text{F}_{10}$ 1152cm^{-1}
0.00	0.501	N/D
0.03	0.500	N/D
1.00	0.509	N/D
5.50	0.505	0.013
8.50	0.498	0.016
13.00	0.485	0.022
17.50	0.473	0.027

Table 5: $A - A_{\text{base}}$ (absorbance/cm pathlength)
for $F_2 + \text{c-C}_4F_8$, Sample # 11,
Expt # F150C, $T = 150^\circ\text{C}$

Time hrs	C_4F_8 962cm^{-1}	$\text{n-C}_4\text{F}_{10}$ 1152cm^{-1}
0.00	0.495	N/D
0.03	0.499	N/D
0.19	0.505	N/D
0.45	0.516	N/D
1.70	0.510	N/D
2.70	0.501	N/D
7.70	0.500	0.010
11.70	0.493	0.012
64.60	0.412	0.035

Table 6: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{F}_2 + \text{c-C}_4\text{F}_8$, Sample #8,
Expt # F150D, $T = 151^\circ\text{C}$

Time hrs	C_4F_8 569cm^{-1}	$\text{n-C}_4\text{F}_{10}$ 1152cm^{-1}
0.00	0.077	0.010
0.03	0.077	0.014
0.50	0.076	0.015
2.40	0.075	0.017
5.40	0.070	0.020
8.40	0.071	0.022
20.40	0.065	0.028

Table 7: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{F}_2 + \text{c-C}_4\text{F}_8$, Sample #14,
Expt # F150E, $T = 148^\circ\text{C}$

Time hrs	C_4F_8 569cm^{-1}	$\text{n-C}_4\text{F}_{10}$ 1152cm^{-1}
0.00	0.070	N/A
0.03	0.071	N/A
0.50	0.072	N/A
0.90	0.071	N/A
5.70	0.067	0.017
11.70	0.063	0.020
16.20	0.062	0.023
19.00	0.062	0.026

Table 8: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $F_2 + c-C_4F_8$, Sample #11,
Expt # F150F, $T = 151^\circ\text{C}$

Time <u>hrs</u>	C_4F_8 <u>569cm^{-1}</u>	$n-C_4F_{10}$ <u>1152cm^{-1}</u>
0.00	0.0749	N/D
0.03	0.0754	N/D
0.50	0.0769	N/D
0.80	0.0747	N/D
2.50	0.0730	0.0152
11.50	0.0627	0.0215
17.50	0.0568	0.0291

Table 9: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $F_2 + c-C_4F_8$, Sample #11 - without filter
Expt # F150G, $T = 149^\circ\text{C}$

Time <u>hrs</u>	C_4F_8 <u>569cm^{-1}</u>
0.00	0.0765
0.03	0.0741
0.50	0.0734
0.95	0.0751
5.40	0.0743
9.95	0.0728
14.40	0.0711
20.40	0.0694

Table 10: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $F_2 + c-C_4F_8$, Sample #11,
Expt # F200A, $T = 200^\circ\text{C}$

<u>Time</u> <u>hrs</u>	<u>C_4F_8</u> <u>962cm^{-1}</u>	<u>$n-C_4F_{10}$</u> <u>1152cm^{-1}</u>
0.00	0.509	N/D
0.03	0.498	N/D
0.40	0.508	N/D
0.90	0.501	N/D
3.00	0.475	0.020
5.00	0.446	0.032
7.00	0.415	0.043
9.00	0.380	0.053
11.00	0.353	0.064

Table 11: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $F_2 + c-C_4F_8$, Sample # 11,
Expt # F250A, $T = 250^\circ\text{C}$

<u>Time</u> <u>hrs</u>	<u>C_4F_8</u> <u>962cm^{-1}</u>	<u>$n-C_4F_{10}$</u> <u>1152cm^{-1}</u>
0.00	0.510	N/D
0.03	0.509	N/D
0.10	0.510	N/D
0.21	0.511	0.010
0.36	0.502	0.014
1.54	0.422	0.045
5.54	0.242	0.110
9.54	0.204	0.124
13.54	0.204	0.124
16.54	0.203	0.124
19.55	0.204	0.124

Table 12: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{F}_2 + \text{c-C}_4\text{F}_8$, Sample # 11 - **without filter**
Expt # F250B, $T = 250^\circ\text{C}$

<u>Time</u> <u>hrs</u>	C_4F_8 <u>569cm^{-1}</u>	$\text{n-C}_4\text{F}_{10}$ <u>1152 cm^{-1}</u>
0.00	0.0779	N/D
0.03	0.0780	N/D
0.50	0.0777	N/D
2.40	0.0757	0.0193
5.40	0.0654	0.0386
11.40	0.0525	0.0681
14.40	0.0479	0.0787
20.40	0.0426	0.0949

Table 13: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{UF}_6 + \text{c-C}_4\text{F}_8$, Sample 19,
Expt # U150A, $T = 150^\circ\text{C}$

<u>Time</u> <u>hrs</u>	C_4F_8 <u>962cm^{-1}</u>	UF_6 <u>631 cm^{-1}</u>
0.00	N/A	0.605
0.03	0.502	0.588
0.50	0.473	0.597
1.03	0.463	0.597
7.62	0.451	0.566
16.21	0.453	0.564
23.80	0.457	0.568

Table 14: $A - A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{UF}_6 + \text{c-C}_4\text{F}_8$, Sample #2,
Expt # U150B, $T = 149^\circ\text{C}$

Time <u>hrs</u>	C_4F_8 <u>962cm^{-1}</u>	UF_6 <u>631cm^{-1}</u>
1.00	0.545	0.565
7.00	0.539	0.558
13.00	0.544	0.566
19.00	0.544	0.556

Table 15: $A - A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{UF}_6 + \text{c-C}_4\text{F}_8$, Sample #11,
Expt # U150C, $T = 149^\circ\text{C}$

Time <u>hrs</u>	C_4F_8 <u>962cm^{-1}</u>	UF_6 <u>631cm^{-1}</u>
0.000	N/A	0.509
0.030	0.591	0.503
0.500	0.541	0.496
0.910	0.526	0.489
5.500	0.522	0.469
10.000	0.526	0.463
20.700	0.526	0.453

Table 16: $A - A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{UF}_6 + \text{c-C}_4\text{F}_8$, Sample #8,
Expt # U150D, $T = 152^\circ\text{C}$

Time hrs	C_4F_8 962 cm^{-1}	UF_6 631 cm^{-1}
0.00	N/A	0.557
0.03	0.614	0.520
0.50	0.567	0.504
0.90	0.565	0.504
2.60	0.553	0.501
7.10	0.547	0.469
10.10	0.555	0.468
22.10	0.551	0.449

Table 17: $A - A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{UF}_6 + \text{c-C}_4\text{F}_8$, Sample #5,
Expt # U150E, $T = 149^\circ\text{C}$

Time hrs	C_4F_8 569 cm^{-1}	UF_6 631 cm^{-1}
0.00	N/A	0.548
0.03	0.119	0.531
0.50	0.109	0.498
2.40	0.105	0.480
6.90	0.103	0.448
14.40	0.104	0.442
20.40	0.103	0.424
26.30	0.106	0.422

Table 18: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{UF}_6 + \text{c-C}_4\text{F}_8$, Sample #14,
Expt # U150F, $T = 151^\circ\text{C}$

Time hrs	C_4F_8 569 cm^{-1}	UF_6 631 cm^{-1}
0.00	N/A	0.5691
0.03	0.0906	0.5546
0.50	0.0838	0.5393
2.40	0.0811	0.5354
8.40	0.0813	0.5141
11.40	0.0802	0.5121
17.40	0.0791	0.5007
23.40	0.0824	0.4993

Table 19: $A-A_{\text{base}}$ (absorbance/cm pathlength)
for $\text{UF}_6 + \text{c-C}_4\text{F}_8$, Sample #11,
Expt # U250A, $T = 248^\circ\text{C}$

Time hrs	C_4F_8 1239 cm^{-1}	UF_6 631 cm^{-1}
0.00	N/A	0.596
0.03	0.322	0.552
0.5	0.298	0.547
3.8	0.287	0.514
8.3	0.287	0.507
12.8	0.287	0.485
20.1	0.288	0.476

Figure 3: Partial pressures for Experiment F150A, C4F8 + F2 at 148C

Figure 4: Partial pressures for Experiment F150B, C4F8 + F2 at 149C

Figure 5: Partial pressures for Experiment F150C, C4F8 + F2 at 150C

Figure 6: Partial pressures for Experiment F150D, C4F8 + F2 at 151C

Figure 7: Partial pressures for Experiment F150E, C4F8 + F2 at 148C

Figure 8: Partial pressures for Experiment F150F, C4F8 + F2 at 151C

Figure 9: Partial pressures for Experiment F150G, C4F8 + F2 at 149C

Figure 10: Partial pressures for Experiment F200A, C4F8 + F2 at 200C

Figure 11: Partial pressures for Experiment F250A, C4F8 + F2 at 250C

Figure 12: Partial pressures for Experiment F250B, C4F8 + F2 at 250C

Figure 13: Partial pressures for Experiment U150A, C4F8 + UF6 at 150C

Figure 14: Partial pressures for Experiment U150B, C4F8 + UF6 at 149C

Figure 15: Partial pressures for Experiment U150C, C4F8 + UF6 at 149C

Figure 16: Partial pressures for Experiment U150D, C4F8 + UF6 at 152C

Figure 17: Partial pressures for Experiment U150E, C4F8 + UF6 at 149C

Figure 18: Partial pressures for Experiment U150F, C4F8 + UF6 at 151C

Figure 19: Partial pressures for Experiment U250A, C4F8 + UF6 at 248C

At least one experiment was run on each sample of $c\text{-C}_4\text{F}_8$ received, although there is no reason to think that any difference would be observed in the rates measured with one or the other, so long as the effect of differing impurity levels is properly considered. In sample #8, for example, (Figure 6), much of the $n\text{-C}_4\text{F}_{10}$ observed can plausibly be attributed to C_4F_{10} initially present as an impurity, and to the reaction of F_2 with *cis*- and *trans*-2-perfluorobutene ($2\text{-C}_4\text{F}_8$), also present in moderate concentration initially. Reaction of fluorine with unsaturated fluorocarbons in general, and 2-perfluorobutene in particular, is expected to be very rapid⁵ at the experimental conditions employed here, yielding primarily the saturated analogous perfluorocarbon. Sample 19 was found to be slightly diluted in its vapor phase with an infrared inactive, non-condensable (at 77°K) gas (i.e. probably air or nitrogen), accounting for its initial concentration being significantly lower than the target partial pressure of 10 Torr.

At higher temperatures (Figures 10 to 12), the reaction rate can be seen to accelerate significantly. At the highest temperatures, the reaction rate eventually slows or stops, most likely as a result of exhaustion of F_2 .

Table 20 System and partial pressures (Torr) in the tube furnace; "initial" = ca. 30 minutes from start of run; "final" = last spectrum; generally ca. 24 hrs.

Expt	Total initial	Oxidizer initial	Oxidizer final	c-C ₄ F ₈ initial	c-C ₄ F ₈ final	n-C ₄ F ₁₀ final	CF ₄ final	C ₂ F ₆ final	C ₃ F ₈ final
F150A*	99.50	10.00	NA	8.33	7.98	0.66	0.73	< 0.10	< 0.18
F150B	99.60	9.90	NA	10.29	9.56	1.2	0.22	< 0.03	< 0.05
F150C	100.02	10.55	NA	10.44	8.34	1.8	< 0.11	< 0.04	< 0.05
F150D	98.64	9.70	NA	11.28	9.66	1.55**	0.33	0.07?	0.12?
F150E	100.30	10.83	NA	10.62	9.10	1.41	0.16	0.04?	0.04?
F150F	99.90	10.58	NA	11.36	8.40	1.62	< 0.08	< 0.05	< 0.11
F150G	100.93	10.28	NA	11.08	10.24	0.56	< 0.05	< 0.02	< 0.05
F200A	100.36	11.30	NA	10.28	7.15	3.37	< 0.07	0.05?	< 0.12
F250A	99.90	10.63	NA	10.37	4.13	6.87	< 0.16	< 0.22	< 0.27
F250B	99.96	10.25	NA	11.48	6.29	5.24	< 0.15	< 0.02	< 0.07
U150A	100.80	10.48	9.96	9.43	9.10	< 0.11	< 0.06	< 0.05	< 0.13
U150B	100.50	9.92	9.75	10.88	10.83	< 0.022	< 0.01	< 0.02	< 0.02
U150C	101.00	8.74	8.00	10.83	10.52	< 0.015	< 0.01	< 0.01	< 0.02
U150D	101.05	8.84	7.89	11.74	11.22	0.14	< 0.04	< 0.02	< 0.01
U150E	105.95	8.70	7.37	15.88	15.35	0.13	< 0.04	< 0.02	< 0.02
U150F	101.24	9.46	8.76	12.24	12.04	< 0.03	< 0.01	< 0.03	< 0.05
U250A	100.44	9.60	8.37	10.98	10.64	< 0.011	< 0.006	< 0.007	< 0.012

Notes: NA = data not available; ? = provisional identification; < = calculated detection limit; nothing actually observed.

* F150A: unk. FC (1224 cm⁻¹) ca. 0.1 Torr

** F150D showed an *initial* partial pressure of C₄F₁₀ of ca 0.8 Torr (likely due to 2-C₄F₈)

Two experiments (F150G and F250B) were run with the sintered nickel filter removed from the tube furnace in order to gain an insight into the effect of surface area on reaction rate. The rates calculated in both cases are lower (by a factor of 2 to 3) from the corresponding with-filter rates. The 150°C experiment can be compared to the several with-filter runs. The non-filter rate lies at the lower limit of the range of with-filter reaction rates. There appears to be a weak effect of surface area on reaction rate, but the statistical difference in rate is not definitive on this point. It should be noted, however, that a reduction in rate of similar magnitude was observed in low-surface area experiments for the reaction of HCFC-124 and F₂.³

Common features of the F₂ experiments were as follows:

- (1) There appeared to be a slight reaction under the reference experimental conditions, based on observation of decline in the absorbance of C₄F₈ spectral peaks and the appearance of reaction products.
- (2) The reaction rate increased with temperature.
- (3) The reaction rate decreased slightly for experiments with the high surface area nickel filter removed from the tube furnace.
- (4) Reaction products were observed in quantities comparable to the loss of C₄F₈. One might expect, if reaction took place, to produce either n-C₄F₁₀ as a result of ring-opening, or fully halogenated fragments of C₄F₈ (e.g. C₃F₈, C₂F₆, and CF₄). The predominant product appeared to be n-C₄F₁₀, but in some experiments, smaller quantities of the lower-carbon-number PFCs were also seen.

Table 21 lists reaction rate constants, *k*, derived from the experimental data using first order kinetics, that is, by fitting to the equation

$$[C_4F_8]_t = [C_4F_8]_0 e^{-kt}$$

where [C₄F₈] is the C₄F₈ concentration at the time designated by the subscript, and *t* is time. These fits were performed discarding data points earlier than one half hour into the experiment (to allow system mixing to stabilize concentrations). The fit results indicate that C₄F₈ reacts slowly with F₂ at

150°C. The rate constant increased with temperature per the equation:

$$k(\text{sec}^{-1}) = 2.95 e^{-6049/T(\text{K})}$$

This equation was derived by fitting all rate constants except those from the low-surface area experiments (F150G and F250B). It must be pointed out that since only a very limited number of higher temperature experiments were performed, the above equation contains considerable uncertainty. The measured rates at 150°C span the range 0.9 to $4.8 \times 10^{-6} \text{ sec}^{-1}$. The lower measured values approach the limit of detection of reactant loss using this experimental system, and would be regarded as doubtful were it not for the confirming observations of reaction products via spectral subtraction. At 150°C, the average rate constant is $1.8 \times 10^{-6} \text{ sec}^{-1}$ (interpreting this as a first order reaction in C_4F_8), lower by more than an order of magnitude than the rate of F_2 with CFC-114².

Table 21: First Order Rate Constants for F_2 experiments

<u>Experiment</u>	<u>Rate constant k</u> <u>(units: 10^{-6} sec^{-1})</u>	<u>Temp</u> <u>(°C)</u>
F150A	0.96 ± 0.03	148
F150B	1.52 ± 0.05	149
F150C	0.94 ± 0.04	150
F150D	2.1 ± 0.4	151
F150E	2.4 ± 0.2	148
F150F	4.8 ± 0.2	151
F150G**	1.16 ± 0.07	149
F200A	9.5 ± 0.4	200
F250A	$25. \pm 8.$	250
F250B**	9.0 ± 0.6	250
CFC-114 + F_2^*	43.	150
CFC-114 + F_2^*	29.	150

Note: uncertainty figures are one standard deviation, as computed from statistical fit of data.

* from Reference 2

** Experiments done without high surface area sintered nickel filter

The fact that we compute the rate constants per first order kinetics in C_4F_8 should not be taken as an indication that this is the appropriate kinetic scheme for this reaction. Several kinetic schemes were attempted in addition to the first order kinetics used here (e.g. rate proportional to $[C_4F_8] \times [F_2]$; rate proportional to $[C_4F_8] \times [F_2]^{1/2}$), with no scheme clearly providing a superior fit to the experimental data. We report the rates as first order in $[C_4F_8]$ for simplicity only. Since only a limited number of experiments were run under a relatively limited set of conditions, and since one of the reactants (F_2) was not directly observable, we cannot with confidence deduce the reaction kinetics from our data.

UF₆ Experiments

The results of the UF₆ experiments are depicted in Figures 13 through 19 and listed in Tables 13 through 19. In all these experiments, after any initial apparent changes in partial pressure (e.g., due to gas mixing), *c*-C₄F₈ remained constant within experimental error. Furthermore, no evidence of likely reaction products of *c*-C₄F₈ fluorination were seen except in two experiments, U150D and U150E. In these two experiments, a trace of *n*-C₄F₁₀ appeared. Those two experiments utilized samples # 5 and # 8, which contained the largest fractions of 2-C₄F₈ (i.e. FC-1318), which is likely to be significantly reactive with UF₆. It should be noted that the spectral subtraction method used here, in comparing the initial and final spectra, shows quantitative *changes* in the mixture, and not absolute concentrations of constituents. Furthermore, the products of very rapid reactions (i.e. those that go to completion in a fraction of the time it takes to complete the first spectrum) will be indistinguishable from an initially present impurity. This distinction is only important for samples which contain significant quantities of reactive impurities. Both these samples began with moderate concentrations of both C₄F₁₀ and 2-C₄F₈. The excess C₄F₁₀ that appeared is best explained as due to reaction of UF₆ with 2-C₄F₈ and *not* reaction of *c*-C₄F₈.

Common features of the UF₆ + C₄F₈ experiments were:

- (1) After the initial mixing period allowed stabilization of concentrations, no obvious change in concentration of C₄F₈ was observed.
- (2) In most experiments, a moderate consumption of UF₆ appeared to occur. This is unfortunately common, and is assumed to be associated with slow reaction of UF₆ with materials of construction (including the

AgCl infrared cell windows) or residual impurities in the system. Reaction with reactive impurities in the coolant may also contribute. This loss is of the same order of magnitude as seen in blank UF_6 runs, such as that reported in Reference 2.

(3) The only reaction product observed by spectral subtraction was $n\text{-C}_4\text{F}_{10}$, which likely was produced by reaction of the unsaturated $2\text{-C}_4\text{F}_8$ initially present as an impurity in the $c\text{-C}_4\text{F}_8$ sample.

Table 22: Rate constants for $\text{UF}_6 + c\text{-C}_4\text{F}_8$ experiments (assuming 1st order kinetics)

Experiment	C_4F_8 loss (units : 10^{-7} sec^{-1})	UF_6 loss (units : 10^{-7} sec^{-1})	Temp ($^{\circ}\text{C}$)
U150A	1.3 ± 2.1	5.3 ± 3.6	150
U150B	0.07 ± 1.25	1.7 ± 1.8	149
U150C	0.36 ± 0.75	9.5 ± 2.8	149
U150D	2.9 ± 2.0	$16. \pm 3.$	152
U150E	2.6 ± 2.6	$17. \pm 3.$	149
U150F	2.2 ± 3.0	9.9 ± 1.5	151
U250A	3.1 ± 3.0	$18. \pm 4.$	248

Conclusion: No C_4F_8 reaction observed

$\text{CFC-114} + \text{UF}_6^* \leq 2.2 \times 10^{-7}$ 150

Note: uncertainty figures are one standard deviation, computed from statistical fit of data. Experimental uncertainty is estimated at $5 \times 10^{-8} \text{ sec}^{-1}$.

* From Reference 2. As in this work, no actual reaction with UF_6 was observed; this is the upper limit on the rate constant.

While no C_4F_8 loss was observed, the same reaction rate formalism can be applied to the data as was done for the $\text{F}_2 + \text{C}_4\text{F}_8$ experiments, above. The resulting rate constants are listed in Table 22. The average C_4F_8 first order rate constant calculated from the 150°C experiments is $1.5 \times 10^{-7} \text{ sec}^{-1}$. In general, the rate constants are of the same order of magnitude as their stand-

ard deviations. In other words, these results reflect a rate for loss of $c\text{-C}_4\text{F}_8$ of essentially zero within experimental uncertainty up to 250°C .

Summary of Results

As is obvious from the data, F_2 is more reactive toward C_4F_8 than is UF_6 .

For F_2 , the reaction rate at 150°C averages $1.8 \times 10^{-6} \text{ sec}^{-1}$ (vs. $4 \times 10^{-5} \text{ sec}^{-1}$ for CFC-114). Only a small fraction of the C_4F_8 reacted, ranging from about 6 to 15%. The reaction products, to the extent that they are definitely identified, are all perfluorocarbons. These, like $c\text{-C}_4\text{F}_8$, will have no ozone depletion impact upon eventual escape to the atmosphere, and presumably will have similar greenhouse warming impact to the parent C_4F_8 .

In the UF_6 experiments, no obvious pattern emerges other than that the C_4F_8 concentration didn't change significantly. We can conclude that at normal cascade conditions, $c\text{-C}_4\text{F}_8$ leaking into the UF_6 stream will ultimately emerge from the plant as $c\text{-C}_4\text{F}_8$.

The experimental system, by design, had a considerable surface (ca $83,000 \text{ cm}^2$ - see reference 2) of potentially active surface. Our reaction may have occurred primarily on this NiF_2 surface rather than in the gas phase. Further work will be necessary to determine the actual kinetics of the reaction in our system, although that is not a necessity for judging the general behavior of this compound on inleakage into a gaseous diffusion cascade.

Discussion:

The published literature contains a few references to work on gas-phase reaction kinetics of fluorine and $c\text{-C}_4\text{F}_8$. Three papers by E.A. Fletcher and co-workers^{6,7,8} concern flame reactions of F_2 and ClF_3 with the saturated gaseous fluorocarbons C_2F_6 , C_3F_8 , and $c\text{-C}_4\text{F}_8$. These studies operated in temperature regimes far from those of our present study (flame temperatures ranged from 1300 to 3500°K), and are not of quantitative relevance to our work, though they may prove useful in comparing the flammability or explosivity of fluorocarbon coolants to that of CFC-114. From this literature, it is evident that $c\text{-C}_4\text{F}_8$ and F_2 will form explosive mixtures, as does CFC-114.

One general result of Fletcher's may be relevant to our studies. He observed

that of the compounds studied, the reactivity, as measured by the maximum flame temperature and the relative reaction rates in competitive experiments, increased in the following order: $C_2F_6 < C_3F_8 < c-C_4F_8$. The explanation offered was that reaction began by attack of a C-F bond, and that primary C-F bonds (i.e. one in a CF_3 group) were more stable than secondary C-F bonds (i.e. ones in a CF_2 group). Other explanations could account for this ordering: the C-C bond energy likely decreases in the order of increasing reactivity above. In any case, this order of reactivity may well also apply at the relatively low temperatures of concern in the gaseous diffusion cascade, although such a conclusion is speculative without information on the mechanism of reaction at low temperature.

Rogers⁵ studied the reaction of F_2 with 2- C_4F_8 (i.e. perfluoro-2-butene, $CF_3CF_2=CF_2CF_3$). He established a rate equation and mechanism for the addition of F_2 to the double bond. The proposed mechanism was one of direct attack of F_2 on the double bond, followed by a chain of radical reaction steps. The rate is very much higher (4 to 8 orders of magnitude) than any of the rates discussed in this or previous work in this series, and is relevant only to the extent of confirming that unsaturated fluorocarbon impurities will be very reactive in F_2 (and presumably also UF_6), and will therefore saturate readily in such an environment, which, indeed, we observed for the relatively impure samples containing a small fraction of 2- C_4F_8 .

The literature study of most relevance to our work is that of Levy and Kennedy⁹. They investigated the reactions of $c-C_4F_8$, $c-C_6F_{12}$, C_3F_8 , and CF_3OF with F_2 . The last three fluorocarbons showed no evidence of reaction at 100 Torr in 900 Torr of F_2 at 750°K (477°C). Cyclo C_4F_8 was more reactive: its kinetics were studied at temperatures between 309°C and 450°C and partial pressures between 4 and 200 Torr. The reaction was found to follow the equation:

$$-d[c-C_4F_8]/dt = k [F_2]^{1/2} [c-C_4F_8]$$

where

$$k = 10^{8.55} \exp(-39.8 \text{ kcal/mole/RT}) \text{ Torr}^{-1/2} \text{ sec}^{-1}$$

The proposed mechanism was

The products found were (in descending order of importance) $\text{n-C}_4\text{F}_{10}$, CF_4 , C_2F_6 , and C_3F_8 . The reaction was found to be homogeneous (i.e. gas-phase), although there was evidence of the onset of a higher-rate heterogeneous (i.e. gas-surface) reaction at the lower end of the temperature range studied. Except to work out methods to avoid the heterogeneous reaction component, Levy did not attempt to study it further. Since most of our experiments were intentionally performed with a considerable surface of fluorine-passivated, sintered nickel filter in the heated reactor, (a condition relevant to the gaseous diffusion environment), it would not be surprising for our rates to be dominated by a gas-surface component.

Levy's reaction mechanism, as shown above, involves atomic fluorine produced by thermal dissociation of molecular F_2 . The form of the kinetic equation (rate proportional to $[\text{F}_2]^{1/2}$) suggests that the fluorine dissociation (and recombination) is fast relative to the subsequent reaction of atomic F with the fluorocarbon. The reaction of $\text{c-C}_4\text{F}_8$ with UF_6 could follow a similar route via the well-characterized thermal dissociation reaction:

Since the $\text{UF}_5\text{-F}$ dissociation requires significantly more energy than that of F_2 (ca. 68 kcal/mole for UF_6 vs. ca. 39 kcal/mole for F_2), the equilibrium concentration of atomic F, and thus the net $\text{UF}_6 + \text{C}_4\text{F}_8$ reaction rate, will be lower. The rate could in principle be calculated from available information, but would involve a number of serious complications (buildup of UF_5 ; desublimation of UF_5 ; heterogeneous recombination of F with UF_5), making any result highly speculative.

Levy's rate equation for $\text{F}_2 + \text{c-C}_4\text{F}_8$, extrapolated to 150°C and adjusted to 10 Torr reactant concentration (so as to express the rate constants in identical units), is 4 to 5 orders of magnitude *lower* than the rate we measured for $\text{F}_2 + \text{c-C}_4\text{F}_8$ at 150°C . This left open the possibility of an alternate lower temperature mechanism (likely heterogeneous) with weaker temperature dependence. To resolve this question, we extended our experimental program to

higher temperatures and ran a few experiments without the sintered nickel filter packing material in our high temperature reactor. As previously stated, the lower-surface area experiments seemed to have a slightly lower rate, but followed the same general temperature behavior with a significantly lower apparent activation energy, ca. 12 kcal/mole, than Levy's value of 39 kcal/mole.

CONCLUSIONS

Conclusions that can be drawn from the work to date are:

1. At temperatures comparable to (actually, slightly higher than) those pertaining in the GDP cascades, namely 150°C or about 300°F, $c\text{-C}_4\text{F}_8$ is slightly reactive with F_2 , and reacts primarily by ring opening, i.e. C-C bond breakage and fluorination to form $n\text{-C}_4\text{F}_{10}$. This rate is significantly lower than the rate of the similar reaction of CFC-114 with F_2 , implying that C_4F_8 would not pose any increased reactivity concern on inleakage to the diffusion cascade.
2. No reaction of $c\text{-C}_4\text{F}_8$ with UF_6 was observed at conditions otherwise similar to the F_2 experiments.

This document reports results of the fourth set in a series of experiments intended to screen out excessively reactive alternate coolant candidates. Unfortunately, we do not have an objective criterion for rendering this decision, but rather only the subjective criterion that reactivity significantly greater than that of CFC-114 is undesirable. On the basis of this subjective criterion, however, $c\text{-C}_4\text{F}_8$ appears acceptable as an alternative to CFC-114.

The experiments reported here were performed primarily at constant conditions designed to emulate, and slightly accelerate, cascade conditions, similar to earlier screening experiments in this series. Due to the limited range of conditions, however, we have not attempted to elucidate the reaction kinetics of these systems, except in a fairly *ad hoc* sense. More in-depth studies are planned to characterize the reaction rate, and hopefully mechanism, by conducting experiments over a range of temperatures, reagent concentrations, and surface conditions for a few substitute candidates, and to run experiments at sufficiently high temperature to detect reaction with UF_6 .

APPENDIX A - IR Calibration

Partial pressures of infrared-active gases are determined from IR spectra using Beer's Law:

$$P = S A / l$$

where P = partial pressure, l is the IR path length through the gas sample, S is the specific absorbance for the peak in question, and A is the absorbance of that peak. A is automatically calculated by the Nicolet 5DXB spectrometer, but is defined as

$$A = \log_{10} (I/I_0)$$

where I is the IR intensity at the peak in question with the gas sample present, and I_0 is the IR intensity at that frequency with no sample present. An "absorbance unit," (or AU) is dimensionless, and is the absorbance that diminishes the IR intensity by a factor of 10. In the literature, absorbance is sometimes calculated as a natural log, rather than a base 10 log, often without clarification of that point. S , the specific absorbance value for a peak of interest, is determined by IR calibration for gases of primary importance, and taken from literature spectra for species less critical to this study.

IR calibration in the series of experiments covered in this and previous reports^{2,3,4} was normally accomplished by a serial dilution method, as described in Reference 2. The calibration data for sample 11 are shown in Table A-1. This sample had the highest purity (99.94%); its IR calibration is used throughout this report to estimate partial pressure of $c\text{-C}_4\text{F}_8$. During calibration (and also during experiments), the IR cell temperature is approximately 25°C, regardless of the oven temperature. The partial pressures shown in the table are read from a capacitance manometer installed approximately 10 cm from the IR cell. The raw data show the absorbance read in the IR cell after spectrum baseline correction. When fit to a first order equation (per Beer's law), these data give the specific absorbance values for the three IR peaks shown in Table A-1.

The gas circulation during an experiment results in variation in the total gas pressure from place to place within the system, as determined by the flow rate and resistance of system components to gas flow. The actual pressure in the IR cell is, during experimental operation at approximately 2000 sccm flow

rate, within 1% of that measured at the cell's manometer; the pressure in the tube furnace is (as measured by another capacitance manometer in the vicinity of the furnace) 111 to 113% that at the IR cell manometer. For purposes of computing partial pressure in the tube furnace, the partial pressure calculated from IR absorbance in the IR cell is scaled up by the ratio of the capacitance manometer readings (the 111 to 113% figures just quoted).

Table A-1: Infrared Absorbance calibration for $\text{c-C}_4\text{F}_8$ at 592, 962, and 1239 cm^{-1} . Calibration used cylinder #11 (99.94% purity) and a 2.0 cm path length. The sample's purity (99.94%) was used to adjust the computed specific absorbance.

Freq.	(cm^{-1})	569	962	1239
Sp.Abs.	(Torr-cm/AU)	131.35	17.93	33.17
$\sigma(\text{Sp.Abs.})$	(")	1.49	0.27	0.09
Cell pressure		Net Absorbance		
	(Torr)			
19.30	(Torr)	0.2916	2.3981*	1.1708
14.29	(")	0.2191	1.5724	0.8725
6.69	(")	0.1022	0.7114	0.4130
3.23	(")	0.0474	0.3433	0.2026

* this absorbance value is near saturation and was discarded. The 962 cm^{-1} peak was fit from the remaining three points.

Our IR calibration for UF_6 was published in Reference 2. Other IR calibrations derived from the scientific literature and from local unpublished sources, scaled for a 1.0 cm path length, are listed in Table A-2.

Table A-2: Infrared Absorbance calibration for other gases, scaled to a 1 cm path length

<u>Gas</u>	<u>cm⁻¹</u>	<u>Torr•cm/AU</u>	<u>Ref</u>
n-C ₄ F ₁₀	1313	36.4	4
	1254	9.6	
	1239	20.7	
	1152	48.8	
	901	53.7	
	732	76.3	
C ₃ F ₈	1007	23.2	10,11
	1154	29.5	
	1210	38.7	
	1261	10.7	
	1350	49.8	
C ₂ F ₆	714	98.5	12
	1116	18.1	
	1250	6.3	
CF ₄	1284	5.4	12
UF ₆	631	15.8	2

APPENDIX B - Estimated Magnitude of Systematic Errors

A number of factors contribute to possible systematic errors in partial pressure measurements. The overall effect of most of these errors will be to shift *all* values reported here by a few percent. This will not affect the reaction rates reported for $F_2 + C_4F_8$, as these were essentially computed from the ratio of the partial pressure at a given time to the partial pressure at time zero.

IR Window warpage: Most of the experiments reported in this document were carried out using an IR gas cell with nominal path length of 2.16 cm. This cell used AgCl windows, which, in vacuum service, are subject to distortion. This distortion often, but not always, has the effect of bowing the windows inward, thereby reducing the path length by a few mm. Micrometer measurements on the IR cell used in these experiments after various periods of service indicate that a typical path length in our experiments was actually about 2.0 ± 0.2 cm. As measurements were not taken of the path length in every experiment, we have assumed an IR path length of 2 cm throughout this report for the "2.16 cm" cell, except in those cases where a specific measurement was made. The resulting absolute concentrations may thus be in error by about 5 percent, but the relative changes within a given experiment should not be significantly affected by this source of uncertainty.

IR Calibration: The partial pressures reported in the text of this report are the best estimate of those pressures occurring in the tube furnace. These pressures are estimated by taking the partial pressure in the IR cell as calculated from the infrared absorbance, then multiplying by approximately 113% for F_2 experiments and 111% for UF_6 experiments. The precise multiple is determined by the pressure ratio between two capacitance manometers, one located downstream of the IR cell and the other immediately upstream of the tube furnace. This ratio varied from the quoted average values from experiment to experiment and within an experiment by about 0.3% (other than the 2% difference between UF_6 and F_2 experiments, due probably to viscosity differences between UF_6 and F_2).

Oven temperature profile: Another source of systematic error derives from the non-uniform temperature of the reaction system. The quoted temperature of the system for a given run is taken from the measured temperature in the center of the tube furnace. Temperature of the system declines from this value as one moves toward the ends of the furnace, and outside the furnace,

the temperature quickly declines to near room temperature. The reaction rates calculated from data implicitly assume that the entire volume of gas is at the quoted temperature, whereas only a fraction of it is at any one time. Much, but not all, of the system volume is contained within the tube furnace, but this temperature non-uniformity could conceivably bias the reaction rates measured in this report (and all previous reports) low by a significant amount. To further confound matters, while a significant fraction of the system's volume is outside the hot region of the tube furnace, very little of the total surface area of the system is outside that area, at least for those experiments in which the high-surface area nickel filter material was present.

At the specified reference conditions of flow and temperature, whatever systematic error in average system temperature might arise from these concerns will apply approximately equally to all experiments. The relative reactivities of the various materials considered to date should be correctly given. An improvement in the system configuration is, however, called for before extensive kinetic studies are conducted in the next phase of the CFC replacement effort.

Overall, these systematic errors, if uncorrelated, suggest an overall systematic error of about $\pm 11\%$ for partial pressure measurements. To reiterate, these errors to a large degree apply to all data points within a given experiment, and to a lesser degree will apply to all experiments. The systematic error in average temperature (or, viewing it from a different point of view, the error in measured rate constant) due to the system's non-uniform temperature is difficult to estimate definitively. Based simply on temperature profile and system component volumes, the calculated rates might be low by a factor of two to four; if surface effects are important, however, as is suggested by comparison of Rogers' work⁵ to ours, the bias would be much less.

ACKNOWLEDGEMENTS

The authors would like to thank Dr. David Harkins for his review and comments on this report.

BIBLIOGRAPHY

- 1 *Montreal Protocol on Substances that Deplete the Ozone Layer*, U.N.E.P., 1987.
- 2 L.D.Trowbridge, E.C.Angel, and W.D.Bostick, *Gas-Phase Chemical Reactivity of Potential CFC-114 Replacements -- Part I: CFC-114 Reactivity with F_2 and UF_6* , K/ETO-34, Martin-Marietta Energy Systems, Enrichment Technical Operations, Oak Ridge, TN, Aug 90.
- 3 L.D.Trowbridge, E.C.Angel, and W.D.Bostick, *Gas-Phase Chemical Reactivity of Potential CFC-114 Replacements -- Part II: HCFC-124 Reactivity with F_2 and UF_6* , K/ETO-49, Martin-Marietta Energy Systems, Enrichment Technical Operations, Oak Ridge, TN, Mar 91.
- 4 L.D.Trowbridge, E.C.Angel, *Gas-Phase Chemical Reactivity of Potential CFC-114 Replacements -- Part III: $n-C_4F_{10}$ Reactivity with F_2 and UF_6* , K/ETO-66, Martin-Marietta Energy Systems, Enrichment Technical Operations, Oak Ridge, TN, July 91.
- 5 A.S.Rogers, *J. Phys. Chem.*, **69**(1), p 254 (1965).
- 6 E.A.Fletcher and J. Hinderman, *Combust. & Flame*, **51**, p 193 (1983).
- 7 E.A.Fletcher and D.B.Kittelson, *Combust. & Flame*, **12**, p 119 (1968).
- 8 E.A.Fletcher and E.A.Ambs, *Combust. & Flame*, **8**, p 275 (1964).
- 9 J.B.Levy and R.C.Kennedy, *J. Amer. Chem. Soc.*, **96**(15), p 4791 (1974)
- 10 H. Bürger and B. Pawelke, *Spectrochimica Acta*, **35A**, p 525 (1979).
- 11 W.F.Edgell et al., *J.A.C.S.* **72**, p 4856 (1950).
- 12 L.D.Trowbridge, unpublished work, 1982

DISTRIBUTION

Oak Ridge K-25 Site

E.C.Angel
D.P.Armstrong
E.J.Barber
G.B.Boroughs
W.D.Bostick
D.A.Harkins
R.L.Higgins
J.A.Hoffmeister
D.L.Mason
J.F.Preston
A.S.Quist (3)*
R.L.Ritter
L.D.Trowbridge (13)
D.L.Weishaar
Appl. Techn. Library
K-25 Plant Records

Oak Ridge National Laboratory

V.D.Baxter
P.D.Fairchild
M.P.Farrell
J.R.Sand

Paducah Gaseous Diffusion Plant

P.B.Kreitz
M.G.Otey
S.F.Seltzer
P.D.Wooldridge
Technical Library

Portsmouth Gaseous Diffusion Plant

J.G.Crawford
J.E.Ratliff
A.J.Saraceno
Technical Library

DOE/OR

M.A.Million
J.W.Parks

DOE/HQ

O.L.Ewing (3)

Lawrence Livermore National Laboratory

B.L.Anderson

University of Tennessee, Knoxville

J.L.Adcock

* 2 copies intended for OSTI

END

**DATE
FILMED
9/25/92**