NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

DOE/ID/12797-2

DOE/ID/12797--2

DE93 011113

DOE HiPHES PROGRAM - PHASE II

TASK 1 REPORT

CONTRACT NO. DE-FC07-88ID12797

**EVALUATION OF HiPHES CONVECTIVE
REFORMER DESIGN ALTERNATIVES**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**FINAL ISSUE
AUGUST, 1991**

**STONE & WEBSTER ENGINEERING CORPORATION
BOSTON, MASSACHUSETTS**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

<u>SECTION</u>	<u>TITLE</u>	<u>PAGE</u>
1	EXECUTIVE SUMMARY	1
1.1	Task 1 Approach	2
1.2	Task 1 Results	3
1.3	Task 1 Recommendations	4
2	DESIGN CONSIDERATIONS	6
2.1	Heat Transfer	7
2.2	Space Velocity	15
2.3	Mechanical and Structural Considerations	17
3	RECOMMENDATIONS	28
	REFERENCES	
APPENDIX A	Development Team Meeting Attendees (2/21/91)	
APPENDIX B	Design Cases	
APPENDIX C	Sample Calculations	

LIST OF TABLES

<u>TABLE NO.</u>	<u>TITLE</u>
2.1-1	Reformer Size Comparisons
2.1-2	Extended Surfaces-No Filler Columns Used
2.1-3	Extended Surfaces-Filler Columns Used
2.1-4	Extended Surfaces-Close Packing
2.1-5	Staged Reformer Simulation Summary
2.2-1	Space Velocity Comparisons
2.2-2	Space Velocity Reduction-Tube Loadings
2.2-3	Space Velocity Reduction-Tube Diameter
2.3-1	Estimated Costs of Hydrogen Loss

LIST OF FIGURES

<u>FIGURE NO.</u>	<u>TITLE</u>
1.1-1	Phase I Designs
2.1-1	Flow Path Arrangements-Counterflow
2.1-2	Flow Path Arrangements-Crossflow
2.1-3	Tube Length vs. Loading
2.1-4	Tube Length vs. Diameter-Annulus
2.1-5	Tube Length vs. Diameter-Tube
2.1-6	Tube Area vs. Loading
2.1-7	Tube Length vs. Flue Gas Temperature-Annulus
2.1-8	Tube Length vs. Flue Gas Temperature-Tube
2.1-9	Tube Arrangements
2.1-10	Two Stage Reforming
2.3-1	O-Ring Seal
2.3-2	Solar Bonded Joint
2.3-3	B&W Glass Seal Joint
2.3-4	Suggested Tube Sheet Design-Scheme I
2.3-5	Suggested Tube Sheet Design-Scheme II

SECTION 1

EXECUTIVE SUMMARY

In Phase I Stone & Webster presented three potential design configurations for a ceramic-tubed steam-methane reformer.¹ These were the Tube-Within-a-Tube (TWIT) design, the Once-Through design, and the Monolith design (Figure 1.1-1). Although the TWIT design configuration appeared to be the most viable, the inclusion of a more detailed examination of design alternatives for the HiPHES reformer was deemed appropriate for the Phase II program. Of particular concern was the length of the ceramic tubes required for the TWIT design.

To assist in this evaluation, Stone & Webster established a Development Team consisting of specialists in the areas of heat transfer, ceramic materials, exchanger design, vessel design, and potential users. Stone & Webster reviewed the critical areas of concern for a ceramic convective reformer, evaluated competing design configurations, and presented the results to the Development Team. This report presents Stone & Webster's evaluations and the comments and recommendations of the Development Team.

This effort comprised the majority of Task 1 of Phase II of Stone & Webster's HiPHES project. The design review was executed in parallel with the material coupon screening tests at BP America. The goal of both tasks was to confirm the materials selection and reformer design configuration so that the conditions for the tube and joint tests to be conducted at Oak Ridge National Laboratory (ORNL) could be specified. The ORNL tests are intended to evaluate the reformer design configuration and materials of construction used for the reformer design in Phase II, and to be used in the demonstration unit in Phase III.

The Task 1 (Evaluation of Alternative Reformer Designs) effort has identified a preferred design configuration for the proposed ceramic reformer. Additional engineering and material evaluation work is necessary before an operating prototype can be designed.

1.1 Task 1 Approach

The critical areas of concern, potential design alternatives, and Stone & Webster's recommendations were presented to the Development Team members on February 21, 1991.* Interaction between ceramic vendors and Stone & Webster Development Team members continued for several weeks to consolidate critical design information identified at the meeting. Stone & Webster has incorporated input and feedback from the Development Team members and DOE in its recommended design configuration.

Stone & Webster's evaluations focused on three broad areas critical to the reformer's design: heat transfer, space velocity, and mechanical and structural issues such as joints and seals. The evaluations sought design modifications that reduce the required length of ceramic tubes to less than the 40 ft length required by the original TWIT design in Phase I. This goal was a major concern since, with the exception of Carborundum, none of the participating ceramic tube manufacturers can envision modifying their manufacturing process to produce continuous 40 ft tubes. The ultimate goal was to reduce the number of multiple short tubes and ceramic/ceramic joints required per tube length as well as the absolute length of the tubes.

Stone & Webster evaluated several reformer arrangements as part of the first task in Phase II of its HiPHES project. These arrangements included a once-through design, several flow-path variations of the bayonet-style arrangement, a two stage reformer and a fluidized bed arrangement. The bayonet (Tube-Within-a-Tube) style arrangement was, again, selected as the most suitable for the HiPHES reformer. By adjusting process variables, such as flue gas temperatures, tube lengths can be reduced to below 20 ft. However, these short tube designs also exhibit high space velocity and high ceramic/metal joint temperatures, both of which are undesirable.

Based on discussions at the Development Team meeting held February 21, 1991, Stone & Webster also investigated the advantages of fins on the outside diameter (OD) of the ceramic tubes. This study showed that tube spacing has a greater influence on heat

* A list of meeting attendees is attached as Appendix A.

transfer rates and tube lengths than does the increased surface area from the addition of fins to the tubes. Consequently, finning of the ceramic tubes was only advantageous (in terms of tube length) if solid columns of ceramic materials were installed in the void spaces among the tubes to reduce the void space. This design added considerably to the cost of the HiPHES reformer, for a nominal gain, and was therefore less desirable than a bare tube design.

Stone & Webster also evaluated the benefits of a two-stage reformer design wherein the reforming reaction zone is divided into a low temperature reformer and high temperature reformer and the use of a fluidized bed of solids to transfer the heat to the reactor zone. These arrangements, however, did not prove advantageous in comparison to the other competing designs.

1.2 Task 1 Results

This report presents several potential ceramic reformer design options. The design options that require tube lengths under 37 ft have space velocities above $12,000 \text{ hr}^{-1}$. Space velocity represents the relationship between feed gas volume per hour and catalyst volume. Although typical space velocity values range between 5,000 and 9,000 hr^{-1} , values above $12,000 \text{ hr}^{-1}$ may be acceptable for the HiPHES reformer because of the higher temperatures and smaller catalyst size.² Additional experimental confirmation of this point during this phase of the program would be desirable.

Next to reducing tube length, which is a function of heat transfer rates, the areas of most concern in the design of the ceramic reformer are the joints between the ceramic tubes and metal header, and the ceramic/ceramic joints. A related concern is the design of the metal header that will distribute feed gas into the ceramic tubes. Stone & Webster developed preliminary header and ceramic/metal joint designs and presented them to the Development Team at the review meeting on February 21. The proposed joint designs, unlike joint designs developed by Coors, Solar, and Babcock & Wilcox (B&W), assumed a ceramic tube sleeve over metal tube connection.

Based on the importance of joints and header design to the HiPHES reformer, Stone & Webster has initiated discussions with Solar, B&W, and Coors to address the HiPHES

reformer's specific requirements.

Thermal, mechanical, and vibrational stresses on the ceramic tube material in the HiPHES reformer are not expected to exceed the strength limits of the ceramic materials under consideration. Based on the proposed bare tube bayonet reformer design presented in this report and ceramic strength data developed at atmosphere pressure by ORNL, the calculated loads on the ceramic tubes are not expected to exceed 20% of the failure load.

Fabrication and maintenance of the ceramic reformer will be relatively expensive because of the tube installation's high labor costs and lower tolerance to construction mishandling. Continued efforts are required to improve ceramic/metal joint and ceramic/ceramic joint technologies as well as ceramic tube strength and fracture toughness so that fabrication requirements can be relaxed.

1.3 Task 1 Recommendations

The results of the ceramic HiPHES reformer design review study presented herein reconfirm the bayonet-style arrangement as the most appropriate at this time. In addition, this study includes that the 2-stage reformer design, fluidized bed heating, and finning of the OD of the ceramic tube are not advantageous in comparison to a bare tube design. Operating conditions can be adjusted to reduce tube lengths, but catalyst volume requirements (space velocity) may limit tube lengths to no less than 30 ft. Tubes as short as 20 ft are achievable if ceramic/metal joint temperatures can be increased to 1500°F and if space velocities above 25,000 hr⁻¹ are found to be acceptable.

Current work by Solar Turbines and others may result in reliable ceramic/metal seals operating at 1500°F. However, no data are available on high space velocity reforming conditions. The major catalyst suppliers are reported to be developing new high activity catalysts that may be capable of working at high space velocities, but until actual data are available, space velocity limitations may keep tube lengths at 30 ft or greater.

The design of the ceramic reformer to be demonstrated in Phase III will not be finalized until after the ORNL and Penn State material and component testing as well as BP America catalyst testing are complete. At that time designs for the ceramic tube to metal header and ceramic/ceramic joints can be finalized. The catalyst tests will explore

the catalyst's temperature limitations and the reformer's space velocity limitations thus setting suitable ceramic tube length, diameter and feed gas loading. Stone & Webster believes that this level of additional information is required before a prototype ceramic reformer can be demonstrated.

SECTION 2

DESIGN CONSIDERATIONS

The design of the proposed TWIT ceramic reformer in Phase I was partially dictated by limits in the use of structural ceramic components. The bayonet style arrangement, proposed for the Phase I TWIT design is a common feature of high temperature ceramic heat exchangers^{3,4} since it requires only one ceramic/metal joint per tube and allows free expansion of the ceramic tube. The TWIT reformer design was also limited by the ceramic tube to metal tubesheet joint temperature of approximately 1000°F. These and other constraints, however, resulted in ceramic tube lengths on the order of 40 ft, which are beyond the capabilities of most ceramic tube manufacturers, without the use of multiple tube sections and ceramic/ceramic joints.

The proposed 40 ft length for ceramic tubes in the ceramic convective TWIT reformer presents other concerns in addition to the capability of manufacturers to produce quality tubes of this length. Among these are:

- Need for more ceramic/ceramic joints per reformer (assuming only 6-8 ft tube lengths are available).
- Mechanical, vibrational, and thermal stresses extended over greater length.
- Reformer fabrication and maintenance procedures.

Each of these concerns and other design issues relevant to ceramic heat exchanger design were reviewed by Stone & Webster. Evaluations focused on heat transfer options, space velocity limitations, and mechanical and structural issues. In the initial stage of the evaluation, Stone & Webster sized more than 70 reformer designs based on a variety of flow path arrangements and operating variables. Summaries of the design cases are included in Appendix B. These design cases were evaluated in terms of tube length and space velocity and the most favorable were selected for further review and development. This section

discusses the configuration options for the ceramic reformer that could be used to reduce tube length, space velocity limits on the reformer design, and mechanical and structural considerations.

2.1 Heat Transfer

The reaction between steam and methane over a reforming catalyst is highly endothermic and therefore supplying heat to the reactants is a critical issue in the design of any reformer. Since the level of conversion in the reforming reaction is defined by thermodynamic conditions, the size of the reformer is determined by heat transfer considerations. This section discusses the various design options for providing the heat of reaction to the steam and methane mixture. These options include radiant vs. convective heat transfer, flue gas and feed gas flow path arrangements, and extended surfaces. This section also includes brief discussions of the 2-stage reformer, pressurized fluidized bed ceramic reformer and heat transfer correlations.

2.1.1 Radiant vs. Convective Heat Transfer

There are two basic heat transfer options to supplying the heat of reaction in the design of a ceramic reformer: radiant or convective. The same options also exist for metal-tubed reformers. Radiant reformers are currently more common in industry and are distinguished by their large fireboxes and high heat fluxes on their radiant tubes. A convective reformer relies on a hot pressurized flue gas stream, in a compact, tubular reactor shape, to provide the necessary heat of reaction via convective heat transfer only.

Convective reforming is still a developing technology in the sense that few commercial units have been built. In general, the chemical industry believes that the benefits of smaller units and lower capital costs associated with convective reforming will be realized in the future, but that these benefits are currently insufficient to outweigh the performance reliability of radiant reformers gained over decades of operation.

Despite its limited commercial application in steam reformers to date, convective heat transfer is the preferred approach for the ceramic reformer. The use of ceramics improves the advantages of convective reforming over radiant reforming because ceramics

permit higher reforming temperatures, and therefore greater conversion rates.^{1,5} The improved performance of a ceramic convective reformer should make it more readily acceptable than a conventional "low temperature" metal-based convective reformer. In addition, a radiant ceramic-tubed reformer would be very difficult to design because of the excessively high temperature at the ceramic tube/firebox roof interface. (The radiant firebox operates at essentially isothermal conditions of about 2000°F.)

2.1.2 Flow Path Arrangement

The concern over ceramic/metal joint temperatures is one facet of the problem associated with the large difference in thermal expansion between metals and ceramics. Most ceramic heat exchanger designs have addressed this problem by incorporating a bayonet heat exchanger arrangement.^{1,3,4} This approach simplifies ceramic/metal interfaces in two ways. First, it requires only one ceramic/metal joint per tube, and second, this joint does not have to account for longitudinal expansion of the tube because the tube is free on the opposite end.

For a bayonet-style reformer, there are several potential flow path arrangements available. Figure 2.1-1 shows the four possible convective reformer arrangements where the hot flue gas flow is parallel to the outer tube. The arrangements shown in Figures 2.1-1C and 2.1-1D do not provide a temperature profile in the catalyst bed suitable for the reforming reaction (i.e. a temperature rise to 1900°F). In the Figure 2.1-1D arrangement, the "cold" steam/hydrocarbon feed in the annulus would act as an insulator and severely limit the reforming reaction in the catalyst-packed inner tube. In the Figure 2.1-1C arrangement, hot steam and hydrocarbon would enter the catalyst bed at its highest temperature, partially converted to synthesis gas, and cool as it flowed up the catalyst bed in the annulus. This arrangement would cause severe coking problems because of the high hydrocarbon content at high temperature and provide unreliable conversion.

The flow path arrangements shown in Figures 2.1-1A and 2.1-1B exhibit suitable heat transfer characteristics for convective reforming. Heat transfer calculations indicate that the flow path arrangement shown in Figure 2.1-1A results in tube lengths which are on the order of 25% shorter than the tube lengths required for the Figure 2.1-1B arrangements. The

HiPHES TWIT reformer proposed in Phase I used the Figure 2.1-1A flow path arrangement.

Another potential reformer arrangement that was not proposed in any of the Phase I designs because of concerns for the ceramic tube/metal header connection temperature is the crossflow arrangement. The possible flow path arrangements for a crossflow reformer would require multiple passes that are not represented in Figure 2.1-2. Figure 2.1-2 describes only the layout of a single pass. The crossflow arrangement was proposed by both Solar and B&W in their respective HiPHES Phase I proposals.

With a crossflow flue gas arrangement and multiple passes, only two of the possible four reformer flow path configurations are suitable. The arrangements in Figures 2.1-2C and 2.1-2D, like the similar counterflow arrangements in Figure 2.1-1, are unsuitable because of coking concerns and unreliable conversion in the case of 2.1-2C, and because the insulating annulus would inhibit the reforming reaction in 2.1-2D. Heat transfer calculations indicate that the flow path arrangements shown in Figures 2.1-2A and 2.1-2B could be used as convective reformers. In general, however, the crossflow arrangements are not as preferred as the counterflow arrangements because of the additional heat transfer surface required. A crossflow ceramic reformer would require from 2,600 to 4,900 tubes (albeit on the order of 10 ft long) as compared to 650 for a comparable counterflow type.

While the bayonet-style ceramic reformer arrangement addresses the metal/ceramic thermal expansion difference problem, it is not the only solution. A single-tube-pass ceramic reformer with ceramic to metal connections at both ends of the ceramic tube is possible if o-ring seals are used at one end. The o-ring seals allow expansion and contraction of the ceramic tube. A single-tube-pass or Once-Through design would require a quench section between the reaction zone and the o-ring since o-ring seals have a low temperature requirement (400-500°F).

From a heat transfer perspective, there are few distinguishing characteristics between the bayonet arrangement and the single-tube pass arrangement that would make one preferred over the other. All arrangements, with the exception of the flow path arrangements shown in Figures 2.1-1C, 2.1-1D, 2.1-2C and 2.1-2D, will transfer sufficient heat from a hot flue gas to achieve desired conversions. The only major heat transfer-related

distinguishing feature is the amount of heat transfer surface area required for each arrangement. Table 2.1-1 provides a summary of the performance of each reformer arrangement.

In Table 2.1-1 the Counterflow/Annulus and Crossflow/Annulus arrangements correspond to the reformer flow path arrangements shown in Figures 2.1-1A and 2.1-2A, respectively. The Counterflow/Tube and Crossflow/Tube arrangements correspond to Figures 2.1-1B and 2.1-2B, respectively. The Total Area includes the outside diameter heat transfer surface for both the inside and outside tubes for the four bayonet style flow path arrangements and the outside diameter heat transfer surface only for the Once-Through flow path arrangement. As Table 2.1-1 shows, the total heat transfer surface required for the two crossflow arrangements is greater than the corresponding surface area for the counterflow arrangements. Although the tube length for each of the crossflow arrangements is only 10 feet, from 4 to more than 7 times the number of tubes are required as for the counterflow arrangements. In addition the ceramic/metal joint temperatures for the crossflow arrangements will be more than 2000°F. Therefore the counterflow arrangement is preferred over the crossflow arrangement for the ceramic reformer application. Similarly, the counterflow bayonet-style arrangement is preferred over the Once-Through arrangement. The Once-Through reformer design requires additional tube length to cool the synthesis gas down to 500°F so that an o-ring seal can be used at the synthesis gas exit header.

The convective reformer comparisons presented in Table 2.1-1 are based on identical values for feed flowrate and temperature, flue gas flowrate and temperature, and tube diameters and spacing. These and other variables can be adjusted to improve the heat transfer capabilities of a particular design.

The most common method of increasing the heat transfer in any convective heat exchanger is to increase the superficial velocity of one or both fluids. This can be achieved by increasing the flowrate per tube (changing the number of tubes) or by decreasing the cross-sectional flow area (tube diameters, tube spacing). Figures 2.1-3 through 2.1-8 show the effect of various factors on tube length and total reformer surface area for the 2 counterflow reformer configurations.

Figures 2.1-3 through 2.1-6 plot tube length as a function of the feed gas superficial

velocity (lb/hr/ft²). In Figure 2.1-3 the amount of feed gas per tube is varied while maintaining the relative tube diameters. In Figures 2.1-4 and 2.1-5 the feed gas per tube is constant (300 lb/hr/tube) while the diameter of the inside tube is varied. Figure 2.1-3 seems to indicate that tube lengths can be reduced by reducing the superficial velocity. This is the case only because the number of tubes is increasing. If the total heat transfer surface is plotted against feed gas superficial velocity for the cases represented in Figures 2.1-3 through 2.1-5, the resulting plot (Figure 2.1-6) shows more agreement (i.e. heat transfer surface decreasing with increasing feed gas superficial velocity).

As Figures 2.1-7 and 2.1-8 show, the factors that have the most influence on tube length are the flue gas exit temperature and the related superficial velocity of the flue gas. If the flue gas rate is increased and the flue gas exit temperature is allowed to increase, then a substantial decrease in tube length can be achieved. The two constraints on this approach are the ceramic tube to metal header joint temperature limits and the space velocity of the process gas inside the tube (discussed in Section 2.2). A ceramic/metal (c/m) joint that can survive in temperatures up to 1500°F would be required to allow for this option; current upper limits are about 1050°F although Solar Turbines now claim to have a c/m joint capable of surviving at 1500°F. Stone & Webster is currently pursuing this option with Solar Turbines.

Extended Surfaces

Increasing the superficial velocities of the reactants, synthesis gas, or flue gas decreases the required total tube heat transfer surface area (i.e. tube length) by increasing the overall heat transfer coefficient. The relationship between the amount of heat transferred and length of tube is expressed as:

$$Q = U \times A \times \text{LMTD}$$

where:

Q = Heat transferred across tube wall,
U = Overall heat transfer coefficient,

A = Tube surface area, and
LMTD = Log mean temperature difference driving force.

The tube surface area, A , is the product of the tube's circumference and its length. Therefore for a fixed heat duty, tube diameter, and temperature difference driving force, the length of the tube can be decreased if the overall heat transfer coefficient, U , is increased.

Another approach to decreasing the tube length without having to increase U is to increase the tube surface area, A , per length of tube by adding fins. Stone & Webster investigated the use of fins on the outside of the ceramic tube since this was the controlling heat transfer surface.

All four of the ceramic material suppliers participating in Phase II are capable of producing finned ceramic tubes. Fin configurations range from 4 to 20 longitudinal fins per tube, 1/8" to 1/4" in height. The fins can be produced in semi-circular or rectangular shapes. Stone & Webster limited the evaluation of finned tubes to rectangular (uniform thickness) fins, and varied the number of fins per tube and height of the fins.

The effect on tube length of the distance between the fin tips on adjacent tubes was examined for 1/4" spacing (Figure 2.1-9) and close packing (intermeshed). As shown in Table 2.1-2, 1/4" spacing resulted in increased tube lengths as compared to the bare tube cases because of the increased cross sectional area of flue gas flow path and subsequent decrease in flue gas superficial velocity and heat transfer coefficient. To adjust for this, the triangular shaped void spaces between the tubes were assumed to be filled by solid ceramic filler columns for the length of the reformer (Figure 2.1-9). This reduces the flue gas flow path area and increases the heat transfer coefficient. The tube lengths for finned tube cases with the filler columns are shown in Table 2.1-3.

When the tube pitch was not increased for finned tube cases with 1/8" fins (with from 10 to 30 fins per tube), tube lengths decreased 9% to 24%, respectively, as compared to bare tube cases. Tube lengths for these cases are shown in Table 2.1-4. As Table 2.1-4 shows, if the ceramic tube manufacturers could produce ceramic tubes with twenty 1/8" fins per tube and if the tubes could be packed with minimal clearance between fins on adjacent tubes (intermeshed fins), then a tube length of about 26.5 ft could be achieved. The other

extreme case scenario is 10 fins per tube with a 1/4" spacing. In this case the tube length is about 36 ft as shown in Table 2.1-2 (Case 5B1'), which is 4 ft greater than the bare tube case (Case 2A' in Table 2.1-4), with a slightly lower flue gas outlet temperature.

Therefore, either tight tube spacing (Case 5A2' in Table 2.1-4) or filler columns (Case 6B2' in Table 2.1-3), both with a flue gas outlet temperature of about 1140°F, will be required to realize the benefits of finned tubes. The optimum arrangement must be determined by an economic evaluation of the cost of manufacture and installation of finned tubes and filler columns. Both approaches are expected to be considerably more complicated and expensive than using bare tubes.

2.1.3 Two-Stage Reformer

Stone & Webster also examined a two-stage reformer design. In this arrangement the first reformer is a low temperature reactor with metal tubes and the second reformer is a high temperature reactor with ceramic tubes. A bayonet style reformer was assumed to be used in both reformers. A simplified diagram of the 2-stage reformer is shown in Figure 2.1-10. The expected advantages of such an arrangement included shorter ceramic tube lengths and the potential for retrofit applications.

The 2-stage reformer cases that were simulated are summarized in Table 2.1-5. Three different maximum reaction temperatures were used in simulating the metal tubed reformer. The maximum reaction temperatures in the low temperature metal reformers for Cases 2STG1, 2STG2, 2STG3, 2STG4 and 2STG5 are 1300, 1400, 1500, 1500 and 1500°F respectively. The ceramic reformer flue gas outlet temperature assumed for all cases except Case 2STG5 is 1300°F and for Case 2STG5 is 1500°F.

Assuming the same feed and product conditions (lb/hr/tube, temperature, pressure, etc), the length of the ceramic tubes in a single-stage reformer is only slightly longer than the length in a 2-stage reformer (approximately 2-3 ft longer). For example, a ceramic tube length of 16 ft was calculated for Case 2STG5. The single-stage reformer operating under identical conditions requires a tube length of 18 ft. But one must note that both of these cases assumed flue gas temperatures that exceed currently viable levels.

The additional cost of an extra reformer vessel (the metal tube length for Case 2

STG 5 is 76 ft) and associated equipment plus the complications of controls, increased pressure drop, and increased maintenance do not justify the reduction of 2 to 3 ft of ceramic tube length. Stone & Webster, therefore, will not pursue this design concept further.

2.1.4 Pressurized Fluidized Bed Ceramic Reformer

In response to a suggestion by Gary Peterson of DOE of the Development Team meeting in February, 1991 Stone & Webster investigated the effect of a pressurized fluidized bed (PFB) heat source on the ceramic reformer tube length. Preliminary calculations indicated that tube lengths and space velocities could be reduced simultaneously with a PFB application. The tube lengths achievable with a PFB application are similar to the lengths achievable with conventional convective heating and high five gas exit temperatures. These high five gas exit temperatures are still lower than the 2300°F isothermal bed temperature assumed for the PFB calculations. Space velocity was reduced by assuming 4.0" OD tubes as compared to 3.5" OD tubes. Reduced space velocity may not prove to be of major concern if high efficiency reforming catalysts is available.

Stone & Webster believes that a PFB ceramic reformer offers a potential approach to reducing tube lengths if conventional convective arrangements do not prove successful. A PFB approach also represents a potential second generation ceramic reformer. However, Stone & Webster does not believe that the marginal reduction in tube length that could be achieved with a PFB warrants serious consideration at this time. There are several unknowns associated with a PFB reformer that would require extensive research and development. These unknowns include abrasion and wear of ceramic tubes by fluidized particles, fluidization rates, bed particle size, solids handling, seals and joints, and tube spacing. Stone & Webster will therefore not pressure a PFB approach.

2.1.5 Heat Transfer Correlations

All of the calculations used to generate the graphs in Figures 2.1-3 through 2.1-8 used typical Nusselt-type equations with corrections for heat transfer through packed beds and/or heat transfer through an annulus as required. All correlations used in the heat transfer calculations are included in Appendix C. Since all calculations used identical correlations,

comparative evaluation of the results is consistent. However, more refined or specialized correlations may be necessary to accurately size the convective reformers. Of particular concern are correlations for heat transfer through packed annuli.

Stone & Webster conducted a literature search for experimental and theoretical reviews of heat transfer in a packed annulus with chemical reaction. None were found that matched the prescribed conditions exactly, however those that were most similar are being investigated further.

2.2 Space Velocity

The catalytic steam plus methane reaction in the convective reformer is endothermic. Maximum conversion rates are defined by thermodynamic relationships. Therefore, supplying the heat of reaction is an essential feature of the reformer design. In general, the size of the reformer is determined largely by heat transfer considerations and not reaction rates, i.e. feed rates and catalyst volumes.

The relationship between gas feed rate and catalyst volume is often expressed in terms of "Theoretical H_2 Space Velocity" (TH_2SV). This is defined as the volume of H_2 (hydrogen) produced at equilibrium conversion per hour per volume of catalyst. It is often more meaningful, however, to use a space velocity (SV) based on the total volume of feed gas at standard conditions. Based upon this definition, space velocities for tubular radiant reformers,⁶ the most common type in use today, range from 1,000 to 8,000 hr^{-1} . Operating experiences outside of this range is limited because of the predominance of radiant reformers. The SV is an empirical relationship between the feed gas and catalyst volume and is unique for specific reactor geometries and feed gas loadings. It is not representative of catalyst activity or active surface area, but is used only as a general guideline for sizing reformer reactors.

The space velocity, therefore, sets limits on the acceptable reformer tube sizes and feed gas loadings. Table 2.2-1 shows the relationship between feed gas flow rate and space velocity for various configurations of the convective reformer. As shown in Table 2.2-1, most of the ceramic reformer configurations exhibit relatively high space velocities (i.e. low

catalyst volume per volume of gas) as compared to radiant reformers. These high space velocity values do not indicate that the reactions will not reach equilibrium, although they are out of the range of conventional reformer space velocities. However, the proposed HiPHES ceramic reformer will operate at more severe conditions than conventional radiant reformers. Thus, higher reforming temperature and smaller catalyst size in the proposed ceramic reformer will increase catalyst activity. With higher catalyst activity, SV values on the order of $10,000 \text{ hr}^{-1}$ to $12,000 \text{ hr}^{-1}$ may be reasonable according to catalyst suppliers². Actual data on the conversion of methane and steam at the proposed conditions are necessary to confirm the viability of the proposed designs. Without data at these more severe conditions, the reformer should be designed within the conservative SV range.

There are two straightforward methods to decrease the SV without drastically increasing reformer tube lengths if lower SV values are required. The first approach is to increase the number of tubes per reformer, while holding the feed gas flow constant thereby decreasing the feed gas per tube (and per volume of catalyst). Table 2.2-2 shows the relationship between the pounds per hour of feed per tube, number of tubes, length of tubes, and SV. As Table 2.2-2 shows, adjusting the feed gas loading per tube downward (from 600 to 200 lb/hr/tube) reduces SV as well as tube length, but at the expense of a greater number of tubes.

The second approach to decreasing space velocity is to increase the packed annular space between the inner and outer tubes by increasing the OD/ID of the outer tube or decreasing the OD of the inner tube. Table 2.2-3 shows the effect of varying the relative tube diameters on SV and tube length. If lower space velocities are required, then larger outside tube ODs up to 4.00 in. can be used with little detriment to tube length. The most significant effect would be on the reformer reactor vessel diameter, which would increase by about 15 percent.

In summary, the SV values calculated for the bare tube and finned tube design cases are greater than reformer space velocities based upon tubular radiant reformers. These higher values may be acceptable because of the higher catalyst activity associated with higher reforming temperatures and smaller catalyst size. Catalyst activity tests at the proposed conditions are required to confirm the acceptability of higher SV values. If lower

SV values are required, then the reformer tube sizes can be altered without significantly affecting tube lengths.

2.3 Mechanical and Structural Considerations

Stone & Webster has developed more than 70 design cases, for a ceramic high pressure steam/methane reformer, based solely upon heat transfer considerations. Many of these are impractical for economic reasons (i.e. large number of tubes or multiple reactor vessels as compared to less extreme alternatives), excessive manufacturing limits (i.e. 70 ft tubes), or extremely high space velocity values. The bare tube design case selected for further development has not been eliminated for economic, tube length, or space velocity reasons. Whether a ceramic reformer can be built based on this design ultimately depends on non-process or mechanical and structural considerations.

A major impediment to the fabrication of a ceramic reformer not addressed in this report is the availability of a suitable ceramic material for use in a high pressure reforming service. This very important aspect of the HiPHES reformer demonstration program is being addressed separately.

The other mechanical and structural considerations that must be addressed and resolved before rigorous design of the ceramic reformer can begin include ceramic-to-metal joints and seals, ceramic-to-ceramic joints and seals, feed header design including feed gas distribution, ceramic tube stress minimization, and flue gas distribution. In addition to these specific design concerns, general issues such as field vs. shop fabrication, ease of maintenance, tube transportation, and catalyst loading and replacement must be addressed and incorporated into the design basis.

This section discusses the relevant mechanical and structural considerations and the potential approaches to resolving each. Much of the research and development work being applied to these issues is still ongoing. A decision on the best approach towards resolving the mechanical and structural details will probably not be reached until after the Phase II tube and joint testing is completed.

2.3.1 Joints

Implicit in the goals of the DOE's High Pressure Heat Exchanger System (HiPHES) program is the development of pressure-containing joints and seals between ceramic components and between ceramic and metal parts. Historically, one of the major obstacles to development of ceramic heat exchangers has been the interface between metals and ceramics. Most of the difficulty in this area is associated with the difference in thermal expansion between metals and ceramics. The proposed ceramic reformer has added to the difficulty by requiring that the joints and seals, depending on their position along the tube length, be capable of containing various hydrocarbon mixtures at 300 psia against a pressurized flue gas at 150 psia. The varying composition and potential corrosiveness of the high pressure process stream (from methane and steam to a mixture of hydrogen, carbon monoxide and steam) adds to the complexity of the joining of ceramics to ceramics and ceramics to metal in different degrees depending upon the type and design of joint. The joint tests proposed for Phase II will investigate corrosive attack of the joints, at appropriate temperatures, by the feed gas (ceramic/metal joint) and reactants (ceramic/ceramic joint). A simulated flue gas mixture will also be exposed to the outside of the joints.

Greater demands are placed on joint technology in the ceramic reformer than in most other ceramic heat exchanger applications where only near ambient pressures are encountered. The ceramic reformer requires reliable seals for all joints, because of the desire to minimize the loss of valuable hydrogen plus carbon monoxide product, although a "perfect seal" is not required.

The initial HiPHES reformers will probably require both ceramic-to-metal and ceramic-to-ceramic joints. Various joining and sealing techniques are available for both types of joints. Ceramic/metal joints are available in several designs. The basic types of joints include brazed joints, o-ring joints, mechanical joints, glass and cemented joints (bonded joints), and various metal/ceramic composite material joints. All of these designs address the thermal expansion difference in some way and are potential candidates for the HiPHES ceramic reformer with the possible exception of brazed joints. Although brazing of ceramic to metal components has been demonstrated in the past,⁷ it may be too costly to use for the proposed ceramic reforming tubes because of the number of tubes involved and

excessive manhours required for each joint.

This section discusses the seal requirements for ceramic joints, the anticipated strength requirements and describes the types of ceramic/metal joints available. The decision as to what joint will be used in the design will be determined after the Phase II joint tests are complete. All joints described herein are expected to be tested.

Seal Requirements

Like a ceramic air heater, the ceramic reformer can tolerate some joint leakage. However, whereas in the air heater leakage might mean a loss in working fluid and a slight reduction in power production, in the reformer a leak could produce a flame and cause a hot spot to develop on an adjacent tube. To minimize this potential problem, the excess air in the flue gas will be kept to a minimum. A leak also represents a loss of valuable hydrogen and CO product and will impact on project economics.

At the Development Team meeting held February 21, 1991, the ceramic material suppliers noted that the amount of leakage a joint could tolerate was a required design specification for joint design. In order to develop a specification for allowable leakage rates at the joints, Stone & Webster reviewed the associated safety issues and economic costs of leakage.

Stone & Webster used criteria developed for the design of nuclear reactor containment buildings to evaluate the safety limits for ceramic tube and joint leaks. The Lower Explosive Limit (LEL) for hydrogen in air (21 vol% oxygen) is 4 volume percent. Nuclear design criteria limit the amount of hydrogen and oxygen not only below the LEL limit but also below the flammability limits. The flammability limit used is a combination of 4 volume percent hydrogen and 6 volume percent oxygen. For design purposes, either the hydrogen, methane or oxygen must be limited to 2.5 volume percent (max). This was the limit used by Stone & Webster to evaluate seal leakage rates.

The maximum allowable seal leakage rate was set as the rate which would result in a 2.5 volume percent methane content in the flue gas. Under steady state operating conditions, a seal leakage rate of 20% will result in a 2.5 volume percent methane content. A 20% leakage rate is equal to approximately 60 lb/hr/tube of steam and methane. At the

process conditions near the ceramic-to-metal joint, this rate corresponds to a minimum clearance between the outside diameter of the ceramic tube and the seal of 1.5×10^{-4} in. or approximately 4 microns.

There are, however, economic incentives to reduce the maximum allowable seal leakage rate below 20%. As Table 2.3.1 shows, a 20% leakage rate corresponds to an annual loss of more than \$5.9 million. This loss reduces pretax ROI by 22% and below the ROI for a high efficiency metal-tubed radiant reformer. Therefore, seals must be designed to limit the leakage rate to below the safety limit if the ceramic reformer is to be a viable option.

The economic allowable seal leakage rate will be determined from a comparison of the present value of the savings achievable from improving the seal and the cost of the seal improvements. If currently available seal technologies limit leakage to below 20%, then seal improvements would only be required to optimize process economics. The optimum seal would then be determined by equaling the present value of the savings and cost of the seal improvements.

Joint Strength

Ceramic joint strength is also of greater concern for certain ceramic reformer designs than for other ceramic heat exchangers because of the potentially greater mechanical loads placed on the joints. Greater static loads are imposed because of the longer tube lengths required for some designs.

The calculated weight of one of the 32 ft ceramic tubes required for the bare tube design case is 115 lbs. The pressure differential between the tube side and shell acting on the base of the ceramic tube adds an additional 1,000 lbs of force. The stress on a ceramic/metal joint supporting this tube can obviously be reduced by supporting the tube at its base as has been proposed. The weight of the catalyst inside the tube has not been included because this can be supported by the inner metal tube.

Joint flexibility is also of concern. Because of the inability of ceramics to dissipate stress, stresses are concentrated at defects and points of constraint, such as joints. Ceramic joints must be designed to be as compliant as possible so as to prevent failure of the ceramic

due to stress concentrations at the joint. This concern is of particular significance for the ceramic reformer designs because of the longer tubes required that introduce the potential for greater bending moments that might locate themselves at ceramic/ceramic or ceramic/metal joints.

For design purposes Stone & Webster would assume that the vibrational forces acting on the joint equal 50% of the static forces. The total of all static and dynamic forces on a 32 ft ceramic tube would be approximately 1,675 lbs. The design load on the joint would normally be set at 4 times this figure of 6,700 lbs.

Types of Joints

The temperature to which a ceramic/metal joint is exposed during service is a key factor governing the type of joint that can be used. As an example, if the temperature of the joint does not exceed 400°F, then elastomeric type o-rings can be used as long as the elastomer is not attacked by the gases to which they will be exposed during service in the reformer. These o-ring type joints can be effective in acting to seal joints having a differential pressure of several hundred psi (Figure 2.3-1). This type of joint also allows the tube to expand and contract along its length with changes in temperature during operation.

For temperatures up to about 1000 - 1200°F, ceramic/metal joints can be designed using spring loaded mechanical devices, ceramic fiber paper seals, grafoil, and metal o-rings or gaskets that are spiral wound stainless steel reinforced with a high temperature, nonasbestos material. These mechanical spring-loaded joints between ceramic tubes and a metal header have already been demonstrated.⁸ The major problem with these types of joints are their questionable reliability to seal when differential pressures of 100 psi or more exist across the joints. In addition, the grafoil seals will have to be tested in the reformer environment to be sure that they will not react with the gases present.

The most promising joints for use in the ceramic reformer are the cemented joints and the metal/ceramic composite joints. Solar Turbines has been successfully applying a bonding (cement) technique for commercial applications for more than 4 years and has proposed this process for use in its HiPHES program.⁴ Babcock & Wilcox has also tested various bonding glasses that also appear promising in maintaining a pressure seal.³

Bonded or cemented joints may be used for both ceramic/ceramic and ceramic/metal connections. The major benefit of bonded joints is the ability to use filler material that can provide a compliant seal. A compliant seal system is preferred since it reduces stress concentrations from thermal expansion mismatches, vibrations, and static loadings. Potential classes of joining materials include glasses, glass ceramics, ceramics, and Si-based braze fillers.

Glass fillers are only useful at low temperatures, however they do allow the greatest relative movement of the materials being joined. Glass ceramics have improved mechanical properties and chemical durability as compared to the parent glass. Ceramics have ideal filler characteristics because of their high temperature strength and corrosion resistance. Their disadvantages include more restrictive movement and poorer thermal expansion match with metals. Silicon based binary-alloy braze fillers have been used by Solar to bond SiC-SiC joints.⁴ This filler has the potential for much improved performance and application in ceramic/metal joints.

An example of Solar's application of this joining approach for ceramic/metal "bonded" joints for service between 1000 - 2000°F is shown in Figure 2.3-2. This sketch describes a joint between a ceramic tube, in this case a SiC tube, and a metal header. The tube is bonded to a threaded metal connector. The "bond" as shown in Figure 2.3-2 is an $\text{Al}_2\text{O}_3\text{-SiO}_2$ material, Kaocrete 32C. The tube-bond-metal connector are made as a separate module and then threaded into the metal header as shown. The Kaocrete is slip-cast into the annulus between the tube and threaded connector after a glass seal ring, or washer, is placed in the annulus between the tube and threaded connector. The composition of the glass seal ring is designed to soften in the temperature range that the joint will see during service, thus increasing the effectiveness of the joint under pressure.

After slip casting, the Kaocrete 32C the bond material is allowed to cool for 24 hours at room temperature. Then the bond is further cured for 12 hours at 400°F. The cured bond is then held in place by a SiC ceramic retaining ring that is brazed to the top of the tube surface. This retaining ring acts to hold the bond in place when the pressure on one side of the joint is significantly greater than the other side.

An example of the use of glass fillers is B&W's current work on the development of

a "compliant" seal system for containing high pressures that prevents leakage and reduces stress concentration due to thermal gradients, expansion mismatches, vibration, or mechanical loading. Figure 2.3-3 is a schematic sketch showing a glass sealed joint between a ceramic tube and a metal header. B&W's work indicates that a glass seal containing 75 wt% frit mixed with 25 wt% ceramic fibers will function better than a fiber-free glass under a differential pressure across the seal. This is because the fiber reduces the tendency of the glass to be extruded out of the joint under pressure.

2.3.2 Stresses

Stresses on the ceramic tubes and joints can be classified into thermal stresses, vibrational stresses, and other mechanical stresses. Previous and ongoing testing at ORNL has shown that the 4 ceramic materials under consideration for use in the ceramic reformer should have sufficient resistance to creep at the anticipated total stress level of about 5,000 psi that is expected to be encountered during normal operation at 2300°F. It was noted at the February 21 Development Team meeting that the ORNL creep tests at 70% of the average fracture strength at 2300°F were at a considerably greater stress load than the expected 5000 psi stresses during normal operation. Irv Federer of ORNL has indicated that high stress loads are required during the creep tests to obtain useful results in a reasonable amount of time. If only 20% of the average fracture strength were used, then time to failure would be on the order of "centuries" for alpha silicon carbide⁹. Therefore, performing creep tests on the silicon carbide materials at high stress levels is the preferred approach so that creep failure data can be obtained in reasonable time. The results from the high stress level creep tests can be extrapolated to lower stress levels to determine how long it would take for a specific silicon carbide material to fail by creep at 5000 psi loads.

Thermal Stresses

Thermal stresses on the ceramic tubes during steady state operation are expected to be concentrated near the bottom of the ceramic tubes and will also be of concern during start-up and shutdown of the reactor. Under normal operating conditions, thermal stress

across the ceramic tube wall was calculated as approximately 4000 psi for the bare tube design case. This stress level is equivalent to a temperature gradient of 50°F across the tube wall. If hot spots develop on a ceramic tube then the resulting thermal stresses could easily exceed the normal values (4000 psi).

Mechanical stress concentration at ceramic/ceramic joints near the bottom of the tubes might exacerbate thermal stresses. One advantage of the bayonet-style arrangement is that the ceramic/metal joints can be isolated at the cold end of the reformer where thermal stresses are of lesser significance. Another advantage of the bayonet arrangement is that ceramic/ceramic joints (if required) along the length of the tube are not as restricted (compared to a double tube sheet design) since the tubes are free to expand and therefore mechanical stresses would not be expected to concentrate there.

The most critical time for thermal stress effects will be during start-up and shutdown. Accordingly, the reformer design must address the capability of gradual heating and cooling of the reactor. Most of these precautions can be implemented through procedures and will not impact on the physical design of the reformer itself.

Mechanical Stresses

Mechanical stresses on the ceramic tubes and joints in the proposed ceramic reformer will include hoop stresses, static loads from the weight of the tubes and pressure differences across the tube base in bayonet-style arrangements, and dynamic loads from process upsets, start-up/shutdown and flow-induced vibrations.

Hoop stress on the ceramic tubes will be on the order of 2500 psi for the bare tube design. The average failure load for the 4 ceramic materials under consideration based on data collected at ORNL is 40 ksi. The combined thermal and hoop stresses are approximately 20% of this value.

The static load from the weight of one bare ceramic tube plus pressure effects is approximately 1115 lbs. Joint strength data are available only for the Solar glass-bonded joint.⁴ At room temperature, joint strength was measured to be greater than 9000 lbs. The strength at higher temperatures is expected to be much less, but is above the expected state load on the ceramic tube alone. If required, static load on the ceramic/metal and

ceramic/ceramic joints could be readily reduced. In the preferred design case, catalyst would be supported by the inner metal tube in the bayonet-style arrangement. Shorter tube lengths will also obviously reduce the loads. In addition, a spring loaded support plate could be placed beneath the tubes to relieve stress on the ceramic/ceramic and ceramic/metal joints.

Dynamic stresses caused by flow-induced vibrations, process upsets, and start-up and shutdown operations are of most concern at the joint sites since these stresses will tend to concentrate at these constraint points. As discussed previously, the best solution to these stresses next to minimizing them is to fabricate compliant joints that are capable of accommodating any movement caused by these stresses. Control of the cause of these stresses include close process control and monitoring during operation and start-up/shutdown.

Vibrations

Vibration-induced stresses on the ceramic tubes in the convective ceramic reformer are a critical design concern. High flue gas velocities increase the potential of vibration damage. As usual, because of the inelasticity of ceramics, vibration-induced stresses will most likely be concentrated in the joints or other constraint sites.

The four basic mechanisms of tube vibration are: fluid-elastic coupling, pressure fluctuation, vortex shedding, and acoustic coupling.¹⁰ Fluid-elastic coupling is caused by the whirling motion of the fluid flowing over the outside of the tubes. If the fluid velocity exceeds a "critical" velocity then the vibration becomes self-excited and grows in amplitude. Pressure fluctuation can be caused by turbulent pressure fluctuations that develop in the wake of a cylinder or are carried to the cylinder from upstream such as from a process upset. Vibration damage is possible if the natural frequency of the tubes is within the energy spectrum of the wave.

Vortex shedding and acoustic coupling are limited to crossflow arrangements. Vortex shedding vibration damage occurs when the shell side fluid vortex-shedding frequency coincides with a natural frequency of the tubes. If this occurs, then large resonant vibration amplitudes may result. In metal-tubed exchangers, an acoustic resonance develops when the

standing waves in the shell, perpendicular to the tubes, are in phase with the vortex shedding. Control of vibration damage is most easily achieved by vibration damping. The catalyst packing inside the tubes will provide a large amount of damping, which can be increased by using tube spacers to support the tubes at regular intervals. The problem with spacers is that, since they constrain movement of the ceramic tubes, tube stresses will tend to concentrate there.

Other vibration damage control options include maintaining shell-side fluid velocities below the "critical" velocity and minimizing pressure fluctuations during startup, shutdown and process upsets.

2.3.3 Fabrication and Maintenance

In addition to ceramic materials of construction, ceramic joints, and tube stress minimization, another major concern for design of a ceramic reformer is the fabrication and maintenance of the reformer vessel. This includes the tubesheet and flue gas plenum designs, catalyst loading, tube installation, replacement and transportation. This section discusses the relevant design issues affecting these areas and potential alternatives. Resolution of these issues and a final design of the reformer vessel can not be completed until after more review and component testing.

Feed/Flue Gas Distribution

One of the key concerns in designing a ceramic convective reformer is proper distribution of the feed and flue gases. Improper distribution of the feed could cause hot spots along a tube wall if flow to a tube is reduced significantly or restricted. Improper distribution of the flue gases could cause cold spots and affect conversion or permit hot flue gas to reach the tubesheet and ceramic/metal joints through a chimney effect.

The bayonet-style arrangement facilitates flue gas distribution because the bottom end of the reformer is open and unencumbered by a tubesheet. This arrangement facilitates an even distribution of the hot flue gas among the suspended ceramic tubes. To assure an even distribution of the flue gases at the top of the reformer shell, evenly-spaced multiple exit ports would be provided.

The challenge of obtaining an even distribution of the methane/steam feed among a large number of tubes is helped by the significant pressure drop across each tube. This pressure drop will have to be equalized across each tube. Two potential designs for a feed header tubesheet are shown in Figures 2.3-4 and 2.3-5. A honeycombed lattice structure provides strength to the tubesheet. Swaging of the tubes would provide greater strength to the tubesheet and accommodate joint requirements.

Tube Transport, Installation and Replacement

Transporting 30 ft ceramic tubes to the site will not be a trivial task, although not without precedent. The ceramic material suppliers indicated at the February 21 Development Team meeting that tubes of comparable length to the proposed reformer tubes have been transported without problems. Special precautions would be required, or the tubes might have to be transported in shorter lengths and joined at the site.

Another option is the shop fabrication of the tubesheet and ceramic tube bundle. The entire assembly could be carefully packed and transported.

Replacement of the tubes presents a challenge similar to that of field assembly of the tube bundle. In field fabrication, the ceramic tubes can be installed before insertion of the inner metal tubes and catalyst loading. This can be accomplished in an orderly pattern. If a ceramic tube must be replaced after the reformer has been assembled and is operational, the entire tube assembly can not be disassembled. Provision will have to be made to isolate the faulty tube.

SECTION 3

RECOMMENDATIONS

The results of the HiPHES reactor alternative designs evaluation indicate that the ceramic reformer to be demonstrated in Phase III will require 30 ft long bare ceramic tubes. The strongest impediment to using even shorter tubes is the uncertainty of the high space velocities associated with shorter tube lengths. If space velocities on the order of $25,000 \text{ hr}^{-1}$ prove to be acceptable, then the shorter tube length designs can be pursued. However, without the development of a new line of high activity catalysts, it is unlikely that these high space velocity values will result in the desired equilibriums. Therefore, current testing and engineering efforts should focus on the 30 ft tube length design.

The countercurrent bayonet-style heat exchanger flow path arrangement is the preferred design for the ceramic reformer. With the catalyst in the annular space, tube length minimized and the total heat transfer surface area is less than the Once-Through design and crossflow bayonet arrangements.

Stone & Webster has identified several key items that will require special attention during Phase II testing and engineering. These include the importance of achieving a high operating temperature (higher than 1050°F) for the ceramic/metal joint which allows the development of shorter tube lengths. In addition, this Task 1 study work has identified the importance of the catalyst testing program to identify the maximum achievable space velocity values under the proposed maximum operating conditions in the ceramic reformer.

Input from the ceramic tube manufacturers indicates that the integrity of ceramic/ceramic joints will probably prove to be sufficient in the Phase II testing program. The most critical area will be the ceramic/metal joints. Stone & Webster has begun discussions with Solar Turbines, B&W, Airesearch and Coors Ceramics about their development of ceramic/metal joints, and their supplying sample joints for our test program at ORNL.

Stone & Webster will continue to develop the reformer vessel design, concentrating on the tubesheet and flue gas plenum arrangements. The designs will be guided by the desire to assure good mixing of the flue gas and even distribution of the feed, as well as

concerns about tube installation, replacement and catalyst loading. Many of these issues will not be finalized until the engineering of the demonstration test unit begins (Task 4) and after component testing is complete. (Task 2)

REFERENCES

1. Stone & Webster Engineering Corporation, "Development of a High Pressure heat Exchange System (HiPHES) for Reforming of Methane - Final Report, Phase I," DOE Contract No. FC07-88ID12730, 1990.
2. Private correspondence with Ron Huber of United Catalyst.
3. Parks, W.P., Jr., "Research and Development of a Ceramic Fiber Composite Heat Exchanger - Final Report, Phase II," DOE Contract No. AC07-84ID12536, 1989.
4. Harkins, Bruce and Michael Ward, "High Pressure Heat Exchange Systems - Final Report, Phase I," DOE Contract No. FC07-88ID12799, 1990.
5. Williams, Joseph J., R. A. Rosenberg, L. J. McDonough, "High Temperature Ceramic-Tubed Reformer," presented at AIChE Spring 1990 National Meeting.
6. "Feedstock Purification & Manufacture of Synthesis Gases, Hydrogen, Ammonia, Methanol," United Catalysts Inc., 1990.
7. Ward, M.E., A. D. Russell, and W.W. Liang, "Ceramic Recuperator Design for an Aluminum Reclamation Furnace," F. Foster and J Patten, ed., The American Ceramic Society, Inc., Columbia, OH, Vol. 14, 1985.
8. "Externally Fired Combined Cycle (EFCC) - Phase I Report," Stone & Webster Engineering Corp. and Hague International, 1989.
9. Private Correspondence with Irv Federer and Jim Keiser of ORNL, March 5, 1991.
10. Perry, Robert H. and Don W. Green, "Chemical Engineers Handbook," 6th Edition, McGraw-Hill Book Co., 1984, p. 11-5.

FIGURE 1.1-1 **PHASE I DESIGNS**

TUBE WITHIN A TUBE

ONCE-THROUGH

MONOLITH

FIGURE 2.1-1

FLOW PATH ARRANGEMENTS- COUNTERFLOW

FIGURE 2.1-2

FLOW PATH ARRANGEMENTS - CROSSFLOW

FIGURE 2.1-3 **TUBE LENGTH vs. LOADING**

FIGURE 2.1-4 **TUBE LENGTH vs. DIAMETER**

FIGURE 2.1-5
TUBE LENGTH vs. DIAMETER

FIGURE 2.1-6
TUBE AREA vs. LOADING

FIGURE 2.1-7
TUBE LENGTH vs. FLUE GAS TEMPERATURE

FIGURE 2.1-8
TUBE LENGTH vs. FLUE GAS TEMPERATURE

FIGURE 2.1-9 **TUBE ARRANGEMENTS**

Bare Tubes
1/4" Spacing

Finned Tubes
1/2" Spacing
Filler Columns

Finned Tubes
1/2" Spacing

Finned Tubes
1/4" Spacing
Intermeshed

FIGURE 2.1-10
TWO STAGE REFORMING

FIGURE 2.3-1 O-RING SEAL

FIGURE 2.3-2
SOLAR BONDED JOINT

FIGURE 2.3-3
B&W GLASS SEAL JOINT

FIGURE 2.3-4

Suggested Tube Sheet Design-Scheme I

FIGURE 2.3-5

Suggested Tube Sheet Design-Scheme II

TABLE 2.1-1

REFORMER SIZE COMPARISONS

Arrangement	Passes	Tubes/Pass	Total Area	Tube Length
Counter/ Annulus 2.1-1A	1	650	31,700 ft ²	37 ft
Counter/ Tube 2.1-1B	1	650	67,490	66
Cross/ Annulus 2.1-2A	3	870	34,180	10
Cross/ Tube 2.1-2B	3	1635	77,095	10
Once-Through	1	650	44,730	75

TABLE 2.1-2**EXTENDED SURFACES - NO FILLER COLUMNS USED**

<u>Case</u>	<u>Fins/ Tube</u>	<u>OTOD*</u>	<u>ITOD**</u>	<u>Fin Height</u>	<u>Pitch</u>	<u>Tube Length</u>	<u>FG Temp</u>
5B10	12	3.5 in	1.25 in	0.125 in	4.0 in	48.7 ft	1041F
5B20	21	3.5	1.25	0.125	4.00	44.6	1039
5B30	30	3.5	1.25	0.125	4.00	41.5	1032
5C10	12	3.5	1.25	0.50	4.75	63.7	1035
5C20	21	3.5	1.25	0.50	4.75	48.5	1047
5C30	30	3.5	1.25	0.50	4.75	39.5	1042
5D10	12	3.5	1.25	1.00	5.75	80.9	1049
5D20	21	3.5	1.25	1.00	5.75	55.8	1046
5D30	30	3.5	1.25	1.00	5.75	43.4	1048
5E10	12	4.0	1.50	0.50	5.25	64.8	1051
5E20	21	4.0	1.50	0.50	5.25	50.5	1043
5E30	30	4.0	1.50	0.50	5.25	41.4	1047
5B1'	12	3.5	1.25	0.125	4.00	35.8	1139
5B2'	21	3.5	1.25	0.125	4.00	35.3	1147

* Outer Tube Outside Diameter

** Inner Tube Outside Diameter

TABLE 2.1 - 3**EXTENDED SURFACES - FILLER COLUMNS USED**

<u>Case</u>	<u>Fins/ Tube</u>	<u>OTOD*</u>	<u>ITOD**</u>	<u>Fin Height</u>	<u>Pitch</u>	<u>Tube Length</u>	<u>FG Temp</u>
6B10	12	3.5 in	1.25 in	0.125 in	4.0 in	36.6 ft	1031F
6B20	21	3.5	1.25	0.125	4.00	32.9	1042
6B30	30	3.5	1.25	0.125	4.00	29.5	1035
6C10	12	3.5	1.25	0.50	4.75	55.4	1038
6C20	21	3.5	1.25	0.50	4.75	42.5	1034
6C30	30	3.5	1.25	0.50	4.75	34.8	1036
6D10	12	3.5	1.25	1.00	5.75	74.9	1038
6D20	21	3.5	1.25	1.00	5.75	51.9	1035
6D30	30	3.5	1.25	1.00	5.75	40.7	1035
6E10	12	4.0	1.50	0.50	5.25	57.3	1035
6E20	21	4.0	1.50	0.50	5.25	44.3	1035
6E30	30	4.0	1.50	0.50	5.25	36.8	1035
6B1'	12	3.5	1.25	0.125	4.00	28.7	1147
6B2'	21	3.5	1.25	0.125	4.00	26.9	1141

* Outer Tube Outside Diameter

** Inner Tube Outside Diameter

TABLE 2.1 - 4**EXTENDED SURFACES - CLOSE PACKING**

<u>Case</u>	<u>Fins/ Tube</u>	<u>OTOD*</u>	<u>ITOD**</u>	<u>Fin Height</u>	<u>Pitch, in</u>	<u>FG Temp</u>	<u>Length ft</u>
4A	0	3.50 in	1.25 in	-	3.75	1040	37.8
5A10	12	3.50	1.25	0.125	3.75	1041	34.5
5A20	21	3.50	1.25	0.125	3.75	1039	31.9
5A30	30	3.50	1.25	0.125	3.75	1032	28.8
2A'	0	3.5	1.25	-	3.75	1121	31.7
5A1'	12	3.50	1.25	0.125	3.75	1137	28.3
5A2'	21	3.50	1.25	0.125	3.75	1138	26.3

* Outer Tube Outside Diameter

** Inner Tube Outside Diameter

TABLE 2.1 - 5
STAGED REFORMER SIMULATION SUMMARY

CASE	2STG1		2STG2		2STG3		2STG4		2STG5	
Max Reforming Temperature, F	1300	1900	1400	1900	1500	1900	1500	1900	1500	1900
Length, ft	15.5	33.7	40.9	30.7	44.3	30.9	73.7	25.7	76.5	16.3
Feed Temperature, F	750	1060	750	925	750	970	750	850	750	850
Flue Gas Temperature Out, F	1126	1300	886	1300	949	1300	872	1300	847	1500
Syngas Temperature Out, F	1060	1322	925	1337	970	1368	850	1358	850	1512
Auxiliary Fuel, mol/h	244.5	0.0	213.5	0.0	259.2	0.0	234.2	0.0	166.9	0.0

TABLE 2.2 - 1

SPACE VELOCITY COMPARISONS, CONVECTIVE REFORMER

<u>Case</u>	<u>OTOD*</u>	<u>ITOD**</u>	<u>Pitch</u>	<u>FG Temp</u>	<u>Lb/Hr/ Tube</u>	<u>Tube Length</u>	<u>Space Vel.</u>
2D	3.5 in	1.5 in	3.75 in	1500F	300	18.1 ft	24,745
2C	3.50	1.50	3.75	1350	300	21.7	20,618
2B	3.50	1.50	3.75	1260	300	24.6	18,189
6B1'	3.50	1.25	4.00	1147	300	28.7	13,527
2A'	3.50	1.25	3.75	1121	300	31.7	12,246
1A	3.50	1.50	3.75	1038	200	33.0	9,028
4B	3.50	1.50	3.75	1040	300	36.1	14,985
BAS	3.50	1.50	3.75	1040	300	37.2	12,002
E							
4D	3.75	1.75	4.00	1040	300	37.5	10,730
4A	3.50	1.25	3.75	1040	300	37.8	10,270

* Outer Tube Outside Diameter

** Inner Tube Outside Diameter

TABLE 2.2 - 2

SPACE VELOCITY REDUCTION - TUBE LOADINGS

<u>Case</u>	<u>OTOD*</u>	<u>ITOD**</u>	<u>Lb/Hr/ Tube</u>	<u>Number Tubes</u>	<u>Tube Length</u>	<u>Space Velocity</u>
1A	3.50 in	1.50 in	200	975	33.0 ft	9,708
BASE	3.50	1.50	300	650	37.2	12,912
1B	3.50	1.50	500	390	44.4	18,057
1C	3.50	1.50	600	325	47.5	20,255

* Outer Tube Outside Diameter

** Inner Tube Outside Diameter

TABLE 2.2 - 3

SPACE VELOCITY REDUCTION - TUBE DIAMETER

<u>Case</u>	<u>OTOD*</u>	<u>ITOD**</u>	<u>Pitch In.</u>	<u>Fins/ Tube</u>	<u>Lb/Hr/ Tube</u>	<u>Tube Length</u>	<u>Space Vel.</u>
2A'	3.5 in	1.25 in	3.75	0	300	31.7 ft	12,246
6B1'	3.50	1.25	4.00	10	300	28.7	13,527
2A!!	4.00	1.25	4.25	0	300	33.1	7,742
6B1!!	4.00	1.25	4.5	10	300	29.2	8,760

* Outer Tube Outside Diameter

** Inner Tube Outside Diameter

TABLE 2.3 - 1

ESTIMATED COSTS OF HYDROGEN LOSS*

PERCENT LOSS	1%	5%	20%
METHANE LOSS, LB/H	446	2230	8920
METHANE LOSS, LB/YR	3,906,960	19,537,800	78,139,200
STEAM LOSS, LB/H	1,506	7,531	30,120
STEAM LOSS, LB/YR	13,192,560	65,962,800	263,851,200
HOURLY LOSS, \$/H	34	169	680
ANNUAL LOSS, \$/Y	296,526	1,483,155	5,930,520
DECREASE IN ROI	1.2%	5.5%	22.0%

* Methane cost is \$62.45/1,000 lbs. Steam cost is \$3.98/1,000 lbs.

APPENDIX A

S&W HIPHES DEVELOPMENT TEAM **MEETING 2/21/91 AT S&W BOSTON**

<u>NAME</u>	<u>COMPANY</u>	<u>PHONE</u>
Joe Williams	Stone & Webster	(617) 589-7197
Bob Rosenberg	Stone & Webster	(617) 589-8651
Lane McDonough	Stone & Webster	(617) 589-8066
Don Kluberdanz	Stone & Webster	(713) 492-3003
Kathy Creighton	Stone & Webster	(617) 589-7475
Scott Richlen	DOE-Washington	(202) 586-2078
Gary R. Peterson	DOE-Idaho	(208) 526-0708
Blaine W. Brown	EG&G-Idaho	(208) 526-9292
Chris Stala	GRI	(312) 399-8233
Pamela DeBellis	Coors	(303) 277-4880
Glenn White	DuPont	(302) 892-1413
Aspi Patel	Lanxide	(302) 456-6558
Ken Green	Norton Company	(508) 795-5513
Jim Keiser	ORNL	(615) 574-4453
Irv Federer	ORNL	(615) 574-5131
John Haggerty	M.I.T.	(617) 253-2129
Chris Singh	Holtec	(609) 424-0999
Don Johnson	Norton Company	(508) 395-5930

(APPENDIX B)
DETAILS OF EVALUATION CASES

APPENDIX B

DESIGN CASES

Explanation of case designations.

Numerical Codes

- Case 1 series varied feed gas loading
- Case 2 series varied five gas temperature and rate
- Case 3 series not used
- Case 4 series varied tube diameter
- Case 5 series was finned tube cases w/o filler columns
- Case 6 series was finned tube cases with filler columns

R-Code

The R-codes designate reverse feed gas flow, i.e. catalyst in the inner tube and feed gas entering through the annulus. These cases correspond to the flow path arrangement shown in Figure 2.1-1B. All other cases shown correspond to flow path arrangement shown in 2.1-1A.

BASE and R-BASE

The BASE case corresponds to flow path arrangement shown in Figure 2.1-1A. The R-BASE case corresponds to Figure 2.1-1B.

Letter Codes

The letters A, B, C, D and E designate the various options within the numerical series.

Punctuation Codes and Double Letters

Punctuation marks such as " ' " and " ! " and double letters were used to distinguish cases within a numerical series which were variants of the regular progression. For example, the Case 2 series flue gas outlet temperatures. Case 2A has a flue gas outlet temperature of 1,120°F and Case 2B has a temperature of 1,260°F. Both have inside tube OD's of 1.50". Case 2A has a flue gas outlet temperature of 1,121°F, but an inside tube OD of 1.25".

Finned Tube Codes

The number of fins per tube in the Case 5 and Case 6 series are designated after the letter. For example, Case 5A20 has 20 fins per tube and Case 6B10 has 10 fins per tube.

APPENDIX B - CASE SUMMARIES

CASE	LB/HR/ TUBE	FG TEMP (F)	ITOD (in)	OTOD (in)	PITCH (in)	NO. FINS	TUBE LENGTH (Ft)	DELTA P (PSI)	SPACE VEL. (1/Hr)	LB/SEC/FT ²		FIN		FLUE GAS RATE(#/Hr)	NO. TUBES
										ANN	SHELL	HT(in)	FILLER		
BASE	300	1037	1.50	3.50	3.75	0	37.2	37	12,000	2.26	15.4	-	-	620,600	650
RBASE	300	1262	2.50	3.50	3.75	0	66.0	170	6,770	5.56	17.9	-	-	719,400	650
1A	200	1038	1.50	3.50	3.75	0	33.0	15	9,030	1.51	10.3	-	-	620,900	980
1B	500	1037	1.50	3.50	3.75	0	44.4	20	25,160	3.77	25.6	-	-	619,600	390
1C	600	1035	1.50	3.50	3.75	0	47.5	30	28,210	4.53	30.7	-	-	618,500	325
R1A	200	1263	2.50	3.50	3.75	0	61.7	58	4,820	3.71	11.9	-	-	717,900	980
R1B	400	1269	2.50	3.50	3.75	0	73.8	255	8,060	7.41		-	-		490
2A	300	1120	1.50	3.50	3.75	0	31.0	31	14,410	2.26	16.9	-	-	679,900	650
2A'	300	1121	1.25	3.50	3.75	0	31.7	31	12,250	2.06	16.9	-	-	681,800	650
2A!	300	1120	1.25	3.50	3.75	0	30.5	30	12,750	2.06	17.0	-	-	685,500	650
2AB	300	1138	1.25	3.50	3.75	0	32.5	32	11,960	2.06	16.6	-	-	668,700	650
2AC	300	1198	1.25	3.50	3.75	0	29.8	30	13,040	2.06	17.3	-	-	698,800	650
2B	300	1260	1.50	3.50	3.75	0	24.6	26	18,200	2.26	19.6	-	-	789,000	650
2C	300	1349	1.50	3.50	3.75	0	21.7	23	20,620	2.26	21.6	-	-	871,300	650
2D	300	1498	1.50	3.50	3.75	0	18.1	19	24,740	2.26	25.8	-	-	1,039,000	650
R2A	300	1187	2.50	3.50	3.75	0	71.3	187	6,260	5.56	16.4	-	-	663,000	650
R2B	300	1352	2.50	3.50	3.75	0	60.9	154	7,330	5.56	19.8	-	-	797,100	650
R2C	300	1516	2.50	3.50	3.75	0	53.6	134	8,330	5.56	24.1	-	-	972,100	650
4A	300	1039	1.25	3.50	3.75	0	37.8	36	10,270	2.06	15.5	-	-	623,800	650
4B	300	1040	1.75	3.50	3.75	0	36.1	38	14,990	2.57	15.5	-	-	624,000	650
4C	300	1036	1.50	3.75	4.00	0	38.2	29	9,090	1.84	14.1	-	-	623,400	650
4D	300	1036	1.75	3.75	4.00	0	37.5	30	10,730	2.04	14.1	-	-	623,400	650
4E	300	1036	1.50	4.00	4.25	0	38.1	18	6,080	1.29	13.1	-	-	634,900	650

PENDIX B - CASE SUMMARIES

CASE	LB/HR/ TUBE	FG TEMP (F)	ITOD (in)	OTOD (in)	PITCH (in)	NO. FINS	TUBE LENGTH (Ft)	DELTA P (PSI)	SPACE VEL. (1/Hr)	LB/SEC/FT ²		FIN		FLUE GAS RATE(#/Hr)	NO. TUBES
										ANN	SHELL	HT(in)	FILLER		
R4A	300	1264	2.75	3.50	3.75	0	45.8	72	7,750	10.63	17.7	-	-	712,100	650
R4B	300	1263	3.00	3.75	4.00	0	45.6	51	6,340	9.78	16.1	-	-	711,100	650
R4C	300	1263	3.25	4.00	4.25	0	45.5	38	5,280	9.06	14.7	-	-	711,100	650
R4D	300	1263	3.50	4.25	4.50	0	45.5	28	4,450	8.43	13.5	-	-	711,100	650
R4DA	400	1260	3.50	4.25	4.50	0	48.8	56	5,540	11.25	18.0	-	-	711,100	490
R4DB	500	1260	3.50	4.25	4.50	0	51.3	97	6,580	14.06	22.5	-	-	711,100	390
VBASE	300	1036	1.50	3.50	3.75	4	35.6	35	12,550	2.26		3/16	No		650
IN4A	300	1036	1.25	3.50	3.75	4	36.3	35	10,700	2.06		3/16	No		650
IN4B	300	1036	1.75	3.50	3.75	4	34.8	37	15,560	2.57		3/16	No		650
IN4C	300	1036	1.50	3.75	4.00	4	36.6	28	9,510	1.84		3/16	No		650
5A10	300	1041	1.25	3.50	3.75	12	34.5	33	11,280	2.06	16.8	1/8	No	632,600	650
5A20	300	1039	1.25	3.50	3.75	21	31.9	31	12,170	2.06	18.1	1/8	No	638,400	650
5A30	300	1032	1.25	3.50	3.75	30	28.8	28	13,480	2.06	20.0	1/8	No	652,900	650
5A10'	300	1137	1.25	3.50	3.75	12	28.3	28	13,710	2.06	18.6	1/8	No	701,700	650
5A20'	300	1138	1.25	3.50	3.75	21	26.3	26	14,800	2.06	20.2	1/8	No	709,500	650
5E10	300	1035	1.25	3.50	4.00	12	48.7	47	7,980	2.06	9.3	1/8	No	604,400	650
5E20	300	1036	1.25	3.50	4.00	21	44.6	43	8,710	2.06	9.8	1/8	No	611,000	650
5B10'	300	1139	1.25	3.50	4.00	12	35.8	35	10,860	2.06	10.9	1/8	No	681,300	650
5B20'	300	1147	1.25	3.50	4.00	21	35.3	35	11,000	2.06	11.0	1/8	No	686,600	650
5C10	300	1045	1.25	3.50	4.75	12	63.7	61	6,100	2.06	4.0	1/2	No	593,300	650
5C20	300	1041	1.25	3.50	4.75	21	48.5	47	8,020	2.06	4.4	1/2	No	608,000	650
5C30	300	1042	1.25	3.50	4.75	30	39.5	38	9,840	2.06	4.8	1/2	No	622,400	650
5C40	300	1051	1.25	3.50	4.75	39	33.3	32	11,680	2.06	5.4	1/2	No	641,300	650

PENDIX B - CASE SUMMARIES

CASE	LB/HR/ TUBE	FG TEMP (F)	ITOD (In)	OTOD (In)	PITCH (In)	NO. FINS	TUBE LENGTH (Ft)	DELTA P (PSI)	SPACE VEL. (1/Hr)	LB/SEC/FT ²		FIN		FLUE GAS RATE(#/Hr)	NO. TUBES
										ANN	SHELL	HT(In)	FILLER		
5D10	300	1049	1.25	3.50	5.75	12	80.9	78	4,800	2.06	2.0	1	No	583,600	650
5D20	300	1046	1.25	3.50	5.75	21	55.8	54	6,970	2.06	2.3	1	No	601,900	650
5D30	300	1048	1.25	3.50	5.75	30	43.4	42	8,960	2.06	2.5	1	No	619,800	650
5D40	300	1049	1.25	3.50	5.75	39	36.2	35	10,730	2.06	2.8	1	No	633,200	650
5E10	300	1051	1.50	4.00	5.25	12	64.8	38	4,330	1.53	3.5	1/2	No	599,900	650
5E20	300	1043	1.50	4.00	5.25	21	50.5	30	5,550	1.53	3.8	1/2	No	612,300	650
5E30	300	1047	1.50	4.00	5.25	30	41.4	24	6,770	1.53	4.2	1/2	No	628,200	650
5E40	300	1049	1.50	4.00	5.25	39	35.6	21	7,860	1.53	4.6	1/2	No	642,200	650
6A10	300	1036	1.25	3.50	3.75	12	28.3	27	13,730	2.06	25.7	1/8	Yes	656,400	650
6A20	300	1042	1.25	3.50	3.75	21	25.9	25	14,990	2.06	29.0	1/8	Yes	667,300	650
6A30	300	1037	1.25	3.50	3.75	30	23.9	23	16,260	2.06	33.0	1/8	Yes	675,500	650
6A40	300	1034	1.25	3.50	3.75	39	22.6	22	17,200	2.06	37.9	1/8	Yes	679,000	650
6A10'	300	1146	1.25	3.50	3.75	12	24.0	24	16,220	2.06	28.3	1/8	Yes	722,200	650
6A20'	300	1145	1.25	3.50	3.75	21	21.5	21	18,100	2.06	32.3	1/8	Yes	742,800	650
6B10	300	1031	1.25	3.50	4.00	12	36.6	35	10,610	2.06	17.3	1/8	Yes	622,500	650
6B20	300	1041	1.25	3.50	4.00	21	32.9	32	11,820	2.06	19.0	1/8	Yes	636,900	650
6B30	300	1034	1.25	3.50	4.00	30	29.5	29	13,150	2.06	21.1	1/8	Yes	651,500	650
6B10'	300	1147	1.25	3.50	4.00	12	28.7	28	13,530	2.06	19.6	1/8	Yes	706,400	650
6B20'	300	1141	1.25	3.50	4.00	21	26.9	26	14,460	2.06	21.2	1/8	Yes	709,500	650
6C10	300	1038	1.25	3.50	4.75	12	55.4	53	7,010	2.06	5.3	1/2	Yes	598,100	650
6C20	300	1034	1.25	3.50	4.75	21	42.5	41	9,150	2.06	6.0	1/2	Yes	613,900	650
6C30	300	1036	1.25	3.50	4.75	30	34.8	33	11,170	2.06	6.9	1/2	Yes	629,700	650
6D10	300	1038	1.25	3.50	5.75	12	74.9	72	5,190	2.06	2.5	1	Yes	582,400	650
6D20	300	1035	1.25	3.50	5.75	21	51.9	50	7,480	2.06	2.8	1	Yes	601,000	650
6D30	300	1036	1.25	3.50	5.75	30	40.7	39	9,540	2.06	3.2	1	Yes	618,200	650

APPENDIX B - CASE SUMMARIES

CASE	LB/HR/ TUBE	FG TEMP (F)	ITOD (In)	OTOD (In)	PITCH (In)	NO. FINS	TUBE LENGTH (Ft)	DELTA P (PSI)	SPACE VEL. (1/Hr)	LB/SEC/FT^2		FIN		FLUE GAS RATE(#/Hr)	NO. TUBES
										ANN	SHELL	HT(In)	FILLER		
6E10	300	1035	1.50	4.00	5.25	12	57.3	34	4,890	1.53	4.7	1/2	Yes	599,500	650
6E20	300	1036	1.50	4.00	5.25	21	44.3	26	6,330	1.53	5.2	1/2	Yes	618,200	650
6E30	300	1036	1.50	4.00	5.25	30	36.8	22	7,620	1.53	5.9	1/2	Yes	632,600	650

APPENDIX C
SAMPLE CALCULATIONS

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No 1 of 1
Preliminary _____
Item _____

1	Client	<u>DOB</u>	Location	<u>Idaho</u>	Est. No.	<u>NOTED MAY 1991</u>	J.O. No.	<u>18525.20</u>
2	Subject	<u>Calculations TOC</u>					<u>McDonough</u>	
3		<u>Task 1 Report - Appendix C</u>			Checked		By	
4	Based on				Revised		By	

Calculation Summary Table of Contents

<u>Description</u>	<u>Pages</u>
Heat Transfer Calculations	1 of 1
Equivalent Diameters for Catalyst	2 of 2
Pressure Drop Through Catalyst	5 of 5
Finned Tubes for H ₂ /PHOS Refractor	2 of 2
Incorporating Finned Tube Heat Transfer	2 of 2
Base Tube Design	5 of 5
Computer Output	5
Temperature Profile	1
Heat Flux Plot	1

Client	DOG	Location	Flsks	Est. No.	ION 18506.20
Subject	Heat Transfer Coeff. Summaries.	NOTED	1/1/91	1991	McDonough
	For Tank 1 Report.	Checked		By	
Based on		Revised	8/1/91	By	LT/1

Heat transfer coefficient for shell side

$$1) H_O = 0.024 * (k/d_{eq}) * Re^{.8} * \left(\frac{cp * \mu}{k}\right)^{.44} \quad (\text{Revised 8/1/91})$$

Heat transfer coefficient for Annulus

Annulus / shell

$$2) H_{out} = 0.26 * (k/d_p) * (2d_r/d_{eqo})^{.2} * Re_A^{.75} * \left(\frac{cp * \mu}{k}\right)^{.4}$$

$$3) d_{eqo} = \frac{(ID \text{ outer tube})^2 - (OD \text{ inner tube})^2}{ID \text{ outer tube}}$$

Annulus / Inner Tube

$$4) H_{in} = 0.26 * (k/d_p) * (2d_r/d_{eqI})^{.2} * Re_A^{.75} * \left(\frac{cp * \mu}{k}\right)^{.4}$$

$$5) d_{eqI} = \frac{(ID \text{ outer tube})^2 - (OD \text{ inner tube})^2}{OD \text{ inner tube}}$$

Heat transfer coefficient for inner tube

$$6) H_I = 0.023 * (k/d) * Re^{.8} * \left(\frac{cp * \mu}{k}\right)^{.3} \quad (\text{Revised 8/1/91})$$

Where:

- k = thermal conductivity of stream
- d_{eq} = equivalent diameter of shell
- Re = Reynolds number of stream
- cp = heat capacity of stream
- μ = viscosity of stream
- d_p = equivalent diameter of catalyst
- Re_A = Reynolds number of stream in packed annulus
- d = ID of inner tube.

1 Client DOB Location Idaho Est. No. _____ IO No. 18508.20
2 Subject Equipment Diameter for catalyst Date 11/11/91 By LJM
3 _____ Checked _____ By _____
4 Based on _____ Revised _____ By _____

Particle Diameter for Non-spherical Particles

From Perry's p. 5-54.

$$D_p = \frac{6(1-E)}{\phi_s S}$$

where: E = void fraction
 ϕ_s = shape factor = 0.3 for Raschig rings
 S = specific area.

S is defined as area of particle surface per unit volume of bed = $S_0(1-E)$

S_0 is defined as area of particle surface per unit volume of solids

$$\text{Therefore } D_p = \frac{6(1-E)}{\phi_s S_0(1-E)} = \frac{6}{\phi_s S_0} = \frac{20}{S_0} \text{ for Raschig rings}$$

$$S_0 = \frac{\text{Surface area of Raschig Ring}}{\text{Unit Volume of Raschig Ring}}$$

Surface area = $2 \times \text{Area of top} + \text{Area of outside cylinder surface} + \text{Area of inside surface}$

$$= 2\left(\frac{\pi D_o^2}{4} - \frac{\pi D_i^2}{4}\right) + \pi D_o L + \pi D_i L$$

$$= \pi \left[\frac{1}{2}(D_o^2 - D_i^2) + L(D_o + D_i) \right]$$

$$= \pi \left[\frac{1}{2}(D_o - D_i)(D_o + D_i) + L(D_o + D_i) \right]$$

$$= \pi (D_o + D_i) \left[\frac{1}{2}(D_o - D_i) + L \right]$$

Volume of Raschig Ring

2 choices: a) Volume of material which constitutes ring
OR
b) Volume occupied by ring.

a) Volume = Volume of cylinder with diameter D_o - volume of cylinder with diameter D_i

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No. 2 of 2
Preliminary _____
Item _____

1	Client	<u>DOB</u>	Location	<u>Indhs</u>	Est. No.		I.O. No.	<u>18538,20</u>
2	Subject	<u>Ea. Drain</u>			Date	<u>1/11/91</u>	By	<u>LJA</u>
3					Checked		By	
4	Based on				Revised		By	

a. Volume = $L \left(\frac{\pi D_o^2}{4} - \frac{\pi D_i^2}{4} \right) = \frac{\pi L}{4} (D_o + D_i)(D_o - D_i)$

$S_o = \frac{4\pi(D_o + D_i) \left[\frac{1}{2}(D_o - D_i) + L \right]}{\pi L(D_o + D_i)(D_o - D_i)} = \frac{2(D_o - D_i) + 4L}{L(D_o - D_i)}$

$S_o = 2/L + 4/(D_o - D_i)$

for $5/16" \times 5/16" \times 1/8"$ Raschig Rings:

$S_o = 2/(0.3125) + 4/(0.4375) = 27.72$

$D_r = 20/27.72 = 0.7212$

b. Volume = $L \pi D_o^2 / 4$

$S_o = \frac{4\pi(D_o + D_i) [2(D_o - D_i) + L]}{\pi D_o^2 L}$

for $5/16" \times 5/16" \times 1/8"$ Raschig Rings:

$\frac{4(0.4375)(0.375 + 0.3125)}{(0.3125)^2} = 39.42$

$D_r = 20/39.42 = 0.5073$

1	Client <u>DOF</u>	Location <u>Idaho</u>	Est. No.	J.O. No. <u>18528-20</u>
2	Subject <u>Pressure Drop thru catalyst bed</u>	Date <u>1/14/51</u>	By <u>CJM</u>	
3		Checked	By	
4	Based on	Revised	By	

Leva Correlation Particle Diameter

D_p is defined as diameter of sphere having same volume as the actual particle.

$$f_m = \frac{9 D_p \Delta P \epsilon^3}{2 L \rho u^2 (1-\epsilon)^{3-n} \lambda^{3-n}} \quad \Delta P = \frac{2 f_m \rho u^2 L (1-\epsilon)^{3-n} \lambda^{3-n}}{D_p^3 \epsilon^3 \rho}$$

$$\lambda = 5.205 \frac{S_p}{V_p^{2/3}} = \frac{S_p}{\pi D_p^2} ?$$

$$\begin{aligned} \text{Volume of particle, } V_p &= 0.3125 \frac{\pi}{4} (0.3125^2 - 0.125^2) \\ &= 0.0201 \text{ in}^3 = \frac{1}{6} \pi D_p^3 \end{aligned}$$

$$D_p = 0.3375 \text{ in}$$

$$\begin{aligned} S_p &= 2 \frac{\pi}{4} (0.3125^2 - 0.125^2) + \pi (0.3125)(0.3125) + \pi (0.125)(0.3125) \\ &= 0.5584 \text{ in}^2 \end{aligned}$$

$$\lambda = 5.205 \frac{0.5584}{0.0201^{2/3}} = 39.31$$

$$\lambda = \frac{0.5584}{\pi (0.3375)^2} = 1.5604$$

$$Re = \frac{D_p u}{\mu} = \frac{(0.3375/12)(8149)}{0.102} = 2,250$$

$$f_m = 1.2 \quad n = 1.98 \quad \epsilon = 0.72$$

$$\begin{aligned} \Delta P &= \frac{2(1.2)(8149)^2 50 (1-0.72)^{3-1.98} (1.5604)^{3-1.98}}{(0.3375/12)^4 4.173 \times 10^8 (0.72)^3 0.183} \\ &= 4,271.6 \text{ } \frac{\text{lb}}{\text{ft}^2} = 30 \text{ psi} \end{aligned}$$

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No. 2 of 5
Preliminary _____
Item _____

Client DOF DP Location Idaho Est. No. _____ J.O. No. 18520, 20
Subject _____ Date 1/14/91 By _____
Checked _____ By _____
Revised _____ By _____
Based on _____

~~$$f_m = a + b e^{cx}$$~~

~~$$f_m = 10^{\Delta(10^{\Delta(-0.4305 * \log(R_e) + 0.3886)})}$$~~

$$\log R_e = \log(R_e)$$

$$F_m = 2.0127 - 1.3370 * \log R_e + 0.29822 * (\log R_e)^2 - 2.1658 E-2 * (\log R_e)^3$$

$$F_m = 10^{F_m}$$

$$\eta_{Factor} = 1.0607 - 1.2903 * \log R_e + 1.9951 * (\log R_e)^2 - 0.86667 * (\log R_e)^3 + 0.15588 * (\log R_e)^4 - 1.0341 E-2 * (\log R_e)^5$$

$$9008 \quad \overset{0.6}{V_P} = 0.25 * \pi * L_P * (ODP^2 - HD^2)$$

$$9008 \quad DP = (6 * V_P / \pi)^{1/3}$$

$$9008 \quad SP = 0.5 * \pi * (ODP^2 - HD^2) + \pi * L_P * ODP + \pi * L_P * HD$$

$$9009 \quad \lambda_{ADA} = SP / \pi / DP^2$$

$$Re = DP * G / \text{Visc}$$

$$\log Re = \log(Re) / \log(10)$$

$$E = 0.5357 * DP / 80600^2 + 0.4850$$

$$\lambda_{ADA} = SP / \pi / DP^2$$

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No. 3 of 5
Preliminary _____
Item _____

1	Client	<u>Dob</u>	Location	<u>Flah</u>	Est. No.		J.O. No.	<u>18526.0</u>
2	Subject	<u>DP</u>			Date	<u>1/14/91</u>	By	<u>LTm</u>
3					Checked		By	
4	Based on				Revised		By	

$$DOLP = 3.3282 E^{-11} * F_m * G^2 * (1-E)^{(3-n)} * (L_{max})^{\frac{1}{3-n}}$$

$$/ DP / E^3 / RO$$

4015

Friction Factor Correlation

$$y = 2.0127 - 1.3370x + 0.29822x^2 - 2.1658e-2x^3 \quad R^2 = 0.998$$

Friction Factor Correlation

Polynomial Fit of "n" Factor Data

$$y = 1.0007 - 1.2903x + 1.9951x^2 - 0.86067x^3 + 0.15588x^4 - 1.0341e-2x^5 \quad R^2 = 0.999$$

"n" Factor Plot for Leva

Client	DOE	Location	Est. No	IO No	18524.20
Subject	Finned Tubes for HiPHOS Return	Date	2/26/91	By	LSM
		Checked		By	
Based on	Kern pp. 515-523	Revised		By	

Longitudinal Fins of Uniform Thickness

Kern provides a derivation of an equivalent heat transfer coefficient for the inside tube surface area based upon a fin efficiency, Ω :

$$h_{fi} = (\Omega A_f + A_o) h_c / A_i$$

Where:

h_{fi} = Equivalent heat transfer coefficient based upon inside surface

Ω = Fin efficiency

A_f = Area of fins

A_o = Area of bare tube on outside of tube

h_c = Heat transfer coefficient on outside of tube

A_i = Inside area of tube.

The fin efficiency is defined as:

$$\Omega = \frac{\tanh mb}{mb}$$

Where:

$$m = \left(\frac{h_c P}{k a_x} \right)^{1/2}$$

b = Height of fin

And,

P = Perimeter of fin

k = Thermal conductivity of fin

a_x = Cross-sectional area of fin.

Weighted Fin Efficiency Curve

We can generate an efficiency curve for the certain Return tube from information supplied by Coors.

According to Pam DeBollis of Coors, Coors can make continuous fins of $3/16$ " height at 90° separation (4 fins per tube). Assume for now that fins are as wide as they are tall.

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No 2 of 2
Preliminary _____
Item _____

1 Client DOE Location _____ Est No _____ I.O. No 18538.20
2 Subject Finned tubes Date 2/26/91 By LJM
3 _____ Checked _____ By _____
4 Based on Kern and Cooper Info Revised _____ By _____

Calculate Efficiency Curves for 3.5" OD and 4.0" OD tubes.

$$A_f = 4 \times 2 \times 0.1875 \times 12 / 144 = 0.125 \text{ ft}^2 / \text{lin ft}$$

$$A_o = (3.5\pi - 4 \times 0.1875) \times 12 / 144 = 0.8538 \text{ ft}^2 / \text{lin ft}$$

$$A_i = (3.0\pi \times 12) / 144 = 0.7854 \text{ ft}^2 / \text{lin ft}$$

$$b = 0.1875 / 12 = 0.0156 \text{ ft}$$

$$h = 60 \text{ W/m}^2 \cdot \text{K} @ 1200 \text{ F} = 103.8 \text{ Btu/hr ft}^2 \cdot \text{F}$$

$$a_x = 4 \times 0.1875 \times 12 / 144 = 0.0625 \text{ ft}^2 / \text{lin ft}$$

$$P = 2 \times 4 \times 12 / \pi = 8 \text{ ft} / \text{lin ft}$$

$$m = \left(\frac{h_f P}{k_x} \right)^{1/4} = h_f^{1/4} \left(\frac{8}{103.8 \times 0.0625} \right)^{1/4} = 1.110 h_f^{1/4}$$

h_f	$1.110 h_f^{1/4}$	mb	$\tanh$	Ω	h_{fi}
56.0	8.306	0.1296	0.1289	0.9946	69.7
56.5	8.344	0.1302	0.1295	0.9946	70.4
57.0	8.380	0.1307	0.1300	0.9946	71.0
57.5	8.417	0.1313	0.1306	0.9947	71.6
58.0	8.454	0.1319	0.1311	0.9939	72.2
59.0	8.526	0.1330	0.1322	0.9940	73.5
59.5	8.562	0.1336	0.1328	0.9940	74.1
60.0	8.598	0.1341	0.1333	0.9940	74.7
60.5	8.634	0.1347	0.1339	0.9941	75.3
61.0	8.669	0.1352	0.1344	0.9941	76.0
61.5	8.705	0.1358	0.1350	0.9941	76.1
62.0	8.740	0.1363	0.1355	0.9941	76.7
62.5	8.775	0.1369	0.1361	0.9942	77.8

Results in a 14% increase in the overall heat transfer coefficient.

1	Client	DOE	Location	Est. No	J.O. No	18518.20
2	Subject	Incorporation of Finned tube heat transfer into TWIST sizing		Date	2/26/91	By: LJM
3				Checked		By:
4	Based on	KERN derivations.		Revised		By:

Longitudinal Fins of Uniform Thickness

Must modify outside heat transfer coefficient to an equivalent inside coefficient h_{fi} :

$$h_{fi} = (\Omega A_f + A_o) h_{fo} / A_i$$

Where:

Ω = Fin efficiency

A_f = Area of fins

A_o = Base tube outside area not covered by fin

h_{fo} = Outside heat transfer coefficient

A_i = Inside tube area

And,

$$\Omega = \frac{\tanh mb}{mb} \quad \text{where:}$$

$$m = \left(\frac{h_{fo} P}{k_{ax} a_x} \right)^{1/2}$$

$$ax = w$$

b = fin height

P = fin perimeter

k = Thermal conductivity of fin

a_x = Cross-sectional area of fin

Must adjust following definitions in Program code:

FLOWA - subarea area of fins (may be significant)

AOUT - Inside area of ceramic tube, not outside area.

FLOWA =

AOUT =

1	Client <u>DOB</u>	Location _____	Est. No _____	J.O. No <u>18538.20</u>
2	Subject <u>Incorporation of Finned tube heat transfer into THERM Sizing</u>	Date <u>2/16/91</u>	By <u>CTH</u>	
3		Checked _____	By _____	
4	Based on _____	Revised _____	By _____	

New Variables:

HFI - Equivalent inside tube heat transfer coefficient

OMEGA - Fin efficiency

AREAFIN - Area of fins per linear foot of tube

AREATUBE - Area of outside tube not covered by fins per foot of tube

AREAINTUBE - Area of inside tube per linear foot

PERIM - Perimeter of fin per linear foot of tube, inches

bFIN - Fin height, inches

AX - Cross-sectional area of fins per linear foot of tube

NFIN - Number of fins per tube

W - width of fin, inches

New Relationships:

$$AX = NFIN * 12 * W / 144 \quad (Ft^2)$$

$$PERIM = NFIN * (2 * 12 + 2 * W) / 12 = NFIN * (12 + W) / 6$$

$$AREAINTUBE = \pi * IDOT \quad (\text{make sure IDOT is in feet!})$$

$$AREATUBE = \pi * ODOT - AX$$

$$AREAFIN = NFIN * 2 * b * 12 / 144 \quad (Ft^2)$$

$$m = (HOJU * PERIM / KCER / AX)^{0.5}$$

$$OMEGA = \tanh(m * b) / (m * b)$$

$$HFI = HOJU / AREAINTUBE * (OMEGA * AREAFIN + AREATUBE)$$

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No. 1 OF 5
Preliminary _____
Item _____

1 Client DOB Location _____ Est. No. _____ I.O. No. 18534.20
2 Subject Ceramic Tube Wall Temperature Date 3/13/91 By LJM
3 for Base Tube Design Case. Checked _____ By _____
4 Based on Coke / Kluhndanz Cases. Revised _____ By _____

Maximum Temperature Difference

<u>L</u>	<u>T_{FG}</u>	<u>T_w</u>	<u>T_{amb}</u>	<u>ΔT_{FG-amb}</u>
31.7	2400	2128	1900	500
30.8	2356	2072	1832	524
30.0	2311	2030	1785	526
28.8	2255	1975	1720	535
29.0	2255	1970	1720	536
27.9	2199	1930	1670	529
26.4	2122	1875	1600	522
24.9	2046	1820	1555	491
23.0	1954	1757	1490	464
21.0	1862	1700	1440	422

CALCULATION SHEET

1	Client	<u>DOE</u>	Location	Est. No.	J.O. No. <u>18538.20</u>
2	Subject	<u>Ceramic Tube Wall Temperature And</u>	Date	<u>3/13/91</u>	By <u>LJA</u>
3		<u>Stresses</u>	Checked		By
4	Based on		Revised		By

Max Temperature difference is at 28.8 Ft.

$$\Delta T_{T_{\text{gas}} - T_{\text{ann}}} = 536^\circ\text{F}$$

Average Tube wall temp. = 1970 F at this point.

$$T_{\text{TC}} = 2248^\circ\text{F}$$

$$T_{\text{ann}} = 1912^\circ\text{F}$$

Corresponds to maximum heat flux from shell to annulus.

Heat Flux = 22,530 BTU/hr ft² of outside surface

$$h_o = 67.03$$

$$h_i = 228.45$$

$$k = 13.25 \text{ BTU/hr-ft-F}$$

PRELIMINARY

Assume $\Delta T_{\text{wall}} = 30^\circ\text{F}$

$$\text{Tube outside wall } T = 1970 + 30/2 = 1,985^\circ\text{F}$$

$$R_{\text{wall}} = 0.25'/12/13.25 = 0.0016 \frac{\text{ft}^2\text{-hr}\cdot^\circ\text{F}}{\text{BTU}}$$

$$U_{\text{tube}} = 1/(1/67.03 + 1/228.45) = 51.82 = 0.0193 \frac{\text{ft}^2\text{-hr}\cdot^\circ\text{F}}{\text{BTU}}$$

$$\Delta T_{\text{wall}} = 536 * (\frac{0.0016}{0.0193}) = 44.44^\circ\text{F}$$

Adjust guess of $\Delta T_{\text{wall}} = 50^\circ\text{F}$

$$\text{Tube OD wall } T = 1970 + 50/2 = 1,995^\circ\text{F}$$

Effect of Radiation

$$\text{For } T_{\text{wall}} = 1,995^\circ\text{F} \quad \begin{aligned} \epsilon_{\text{H}_2\text{O}} &= 0.083 \\ \epsilon_{\text{CO}_2} &= 0.056 \end{aligned}$$

$$\text{For } T_{\text{gas}} = 2248^\circ\text{F} \quad \begin{aligned} \epsilon_{\text{H}_2\text{O}} &= 0.077 \\ \epsilon_{\text{CO}_2} &= 0.049 \end{aligned}$$

$$q_{\text{H}_2\text{O}} = 0.171 * 0.85 \left(0.077 \left(\frac{2248+1995}{100} \right)^4 - 0.083 \left(\frac{1995+1995}{100} \right)^4 \right)$$

$$= 1,636 \text{ BTU/hr ft}^2$$

$$q_{\text{CO}_2} = 0.171 * 0.85 \left(0.049 \left(\frac{2248+1995}{100} \right)^4 - 0.056 \left(\frac{1995+1995}{100} \right)^4 \right)$$

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No 3 of 5
Preliminary _____
Item _____

1	Client <u>DOB</u>	Location _____	Est. No. _____	J.O. No. <u>14524.20</u>
2	Subject <u>Stress Calculations</u>	Date <u>3/13/91</u>	By <u>CSA</u>	
3		Checked _____	By _____	
4	Based on _____	Revised _____	By _____	

$$\begin{aligned} \text{Convective Flux} &= 536 * 47.85 = 25,648 \text{ Btu/hr-ft}^2 \\ \text{Radiant Flux} &= 1,636 + 873 = 2,509 \\ &= 28,157 \text{ Btu/hr-ft}^2 \end{aligned}$$

$$\Delta T_{\text{wall}} = 28,157 * .0016 \frac{\text{ft}^2 \cdot \text{hr} \cdot ^\circ\text{F}}{\text{Btu}} = 45^\circ\text{F}$$

SAY 50°F

Thermal Stress Calculation per Kulkarni / Croke

$$\text{Outside: } \sigma_c = \frac{E \alpha \Delta T}{(1-\mu)} \left(\frac{2r_o + r_i}{3(r_o + r_i)} \right)$$

$$\text{Inside } \sigma_o = \frac{E \alpha \Delta T}{(1-\mu)} \left(\frac{r_o + 2r_i}{3(r_o + r_i)} \right)$$

$$\sigma_i = \frac{-(61 \times 10^6)(2.20 \times 10^{-6})(-50)}{1 - 0.15} \left(\frac{2(1.75) + 1.5}{3(1.75 + 1.5)} \right)$$

$$= 4,030 \text{ psi}$$

$$\sigma_o = \frac{(61 \times 10^6)(2.20 \times 10^{-6})(50)}{0.85} \left(\frac{1.75 + 3.0}{3(3.25)} \right)$$

$$= 3,845 \text{ psi}$$

hoop Stress

$$\sigma = (350 \frac{\text{lb}}{\text{in}^2}) \left(\frac{3.5 \text{ in}}{2} \right) \left(\frac{1}{.25 \text{ in}} \right) = 2,450 \text{ psi}$$

CHECK

PRELIMINARY

CNT
70 LB/FT³

▲ 5010.10

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No. 4 of 5
Preliminary
Item

1	Client	DOB	Location	Est. No.	J.O. No.
2	Subject	Tube Stress Calc.		Date 3/13/91	By CTH
3		Base Tube Design Case		Checked	By
4	Based on			Revised	By

Weight of Tubes

Ceramic density = 200 LB/FT³ per 9/19 telcon with
Bob Rule of BP America.

$$\text{Tube volume per foot} = 1 \text{ FT} \times \pi/4 \left(\left(\frac{3.5}{12} \right)^2 - \left(\frac{3.0}{12} \right)^2 \right) \\ = 0.0177 \text{ FT}^3/\text{FT}$$

$$\text{Weight per foot} = 200 \text{ LB/FT}^3 \times 0.0177 \text{ FT}^3/\text{FT} = 3.55 \text{ LB/FT}$$

$$\text{Assume 32' tubes : Weight/tube} = 32 \times 3.55 = \boxed{115 \text{ LB/tube}}$$

Based upon Triangular pitch, will either fit
622 or 712 tubes into the reformer shell.

Assume 622 tubes and ~315 LB/m/tube

$$\text{Total weight of ceramic tubes} = 622 \times 115 = \boxed{71,530 \text{ LB}}$$

Weight of Catalyst

$$\text{Annular space} = \pi/4 \left[\left(\frac{3}{12} \right)^2 - \left(\frac{1.25}{12} \right)^2 \right] = 0.0406 \text{ FT}^2$$

$$\text{Catalyst volume/tube} = 32 \text{ FT} \times 0.0406 = 1.30 \text{ FT}^3/\text{tube}$$

Catalyst bulk density = 70 LB/FT³ per telcon between
K. Craigston & R. Hildebrand.

$$\text{Catalyst weight/tube} = 1.30 \text{ FT}^3/\text{tube} \times 70 \text{ LB/FT}^3 = \boxed{91 \text{ LB/tube}}$$

$$\text{Total catalyst weight} = 91 \text{ LB/tube} \times 622 \text{ tubes} = \boxed{56,602 \text{ LB}}$$

PRELIMINARY

STONE & WEBSTER ENGINEERING CORPORATION
CALCULATION SHEET

Page No 5 of 5
Preliminary _____
Item _____

1 Client DOB Location _____ Est. No. _____ I.O. No. 18558.20
2 Subject Tube Stress Calc. Date 3/14/91 By CTM
3 Bone Tube Design Case Checked _____ By _____
4 Based on _____ Revised _____ By _____

Weight of meter Tube

1.25' OD x 1.60' ID meter tube.

Assume Length = 32' + 6' (For Feed Header) = 38' Total.

Volume of meter/tube = $38 \times \frac{\pi}{4} \left(\left(\frac{1.25}{12} \right)^2 - \left(\frac{1.60}{12} \right)^2 \right) = 0.1166 \text{ ft}^3$

Meter Density = 758 #/ft^3

Weight/tube = $758 \times 0.1166 = 88.5 \text{ #/tube}$

Total weight of tubes = $622 \times 88.5 = 55,047 \text{ LBS}$

Load on meter Tube Joint

Assume catalyst is supported by a metal collar at base of meter tube.

Total weight per meter tube = $88.5 + 91 = 179.5 \text{ LB/tube}$

Total weight supported by meter tube header = $622 \times 179.5 =$

111,649 LBS

Load on meter tube weld:

X-section of weld = $\frac{\pi}{4} (1.25^2 - 1) = 0.442 \text{ in}^2$

Load/weld = $179.5 \text{ LB} / 0.442 = 410 \text{ PSI}$

PRELIMINARY

File Name: A:TWIT2A'.dat. Case: TWIT2A'
03-12-1991 14:52:06

Input Summary

	Feed	Fuel
Temp (F) =	750	100
Pres (psia) =	350	135
Moles H2 =	0	3081
Moles CO =	0	43
Moles CO2 =	0	79
Moles CH4 =	2789	447
Moles C2H6 =	0	0
Moles C3H8 =	0	0
Moles H2O =	8367	1
Moles N2 =	0	0

Tube Outlet Temp (F) = 1900
Tube Outlet Pres (psia) = 300
Tube Within a Tube Case ? 1
Inner Tube ID (in) = 1
Inner Tube OD (in) = 1.25
Outer Tube ID (in) = 3
Outer Tube OD (in) = 3.5
Pitch (in) = 3.75
Syngas mass flow rate per tube (#/hr/tube) = 300
Mixed Combustion Temp = 2400
Mixed Combustion Pres. = 135
Furnace Effluent Temp (F) = 1124
Furnace Cross Sectional Flow Area (ft2/tube) = .01776
Reactor Excess Air (%) = 5
Thermal Conductivity of Inner Pipe (Btu/lb-ft-F) = 13
Material Code (1=CRY,2=LAN,3=CAR,4=COORS,DEFAULT=1) = 1
Number of segments for reactor design = 10
Max. iterations = 5
Turbine = GE
Type = *5322 RB
Air Rate (#/sec) = 250
Compressor Air Pres (psia) = 126
Compressor Air Temp (F) = 570
% Bypass Air = 10%
% Air to Reformer = 27.5%
Turbine Inlet Pres (psia) = 125
Turbine Outlet Temp (F) = 955
Turbine Outlet Pres (psia) = 15

PRELIMINARY

FIXED STREAM DATA

Stream #	1	T= 750	P=350.0	DP= 0
Stream #	2	T=1900	P=300.0	DP=50
Stream #	3	T=1144	P=270.0	DP=30
Stream #	4	T= 100	P=135.0	DP= 0
Stream #	5	T= 597	P=135.0	DP= 0
Stream #	6	T= 980	P=135.0	DP= 0
Stream #	7	T=2400	P=135.0	DP= 0
Stream #	8	T=1124	P=135.0	DP= 0
Stream #	9	T= 0	P=135.0	DP= 0
Stream #	11	T= 368	P=135.0	DP= 0
Stream #	12	T= 393	P=131.0	DP= 4
Stream #	13	T= 275	P=127.0	DP= 4
Stream #	14	T= 292	P=135.0	DP= 0
Stream #	16	T= 980	P=139.0	DP= 4
Stream #	18	T= 750	P=350.0	DP= 0
Stream #	28	T= 570	P=126.0	DP= 0
Stream #	29	T= 60	P= 15.0	DP= 0
Stream #	32	T= 240	P= 0.0	DP= 0

PRELIMINARY

PRELIMINARY

pg 3 of 7

TUBE SEGMENT 10

Hout= 66.92799 Hin= 232.2196 K ,BTU/FT-H-F; 13.00695
ANNULUS= 1785.0 to 1900.0 F SHELL= 2399.5 to 2311.1 F FLUX= 21895 BTU/FT2
Utube= 42.7 BTU/HR-FT²-F DUTY= 21.9 MM BTU DELTA T= 512.8 LENGTH= 1.734
ANNULUS/SHELL DP= 2.59 / 0.15 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 2072

TWIT SEGMENT 10

Hout= 194.9201 Hin= 166.2535
ANNULUS= 1785.0 to 1900.0 F TWIT= 1900.0 to 1890.5 F FLUX= 3654 BTU/FT2
Utwit= 69.3 BTU/HR-FT²-F DUTY= 1.4 MM BTU DELTA T= 52.8 LENGTH= 1.734
ANNULUS/TWIT DP= 2.59 / 0.07 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1878.0

TUBE SEGMENT 9

Hout= 67.02618 Hin= 228.4473 K ,BTU/FT-H-F; 13.24928
ANNULUS= 1670.0 to 1785.0 F SHELL= 2311.1 to 2199.2 F FLUX= 22530 BTU/FT2
Utube= 42.7 BTU/HR-FT²-F DUTY= 27.5 MM BTU DELTA T= 527.6 LENGTH= 2.106
ANNULUS/SHELL DP= 2.94 / 0.17 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1975

TWIT SEGMENT 9

Hout= 191.7537 Hin= 165.9814
ANNULUS= 1670.0 to 1785.0 F TWIT= 1890.5 to 1858.5 F FLUX= 10115 BTU/FT2
Utwit= 68.8 BTU/HR-FT²-F DUTY= 4.7 MM BTU DELTA T= 147.0 LENGTH= 2.106
ANNULUS/TWIT DP= 2.94 / 0.09 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1829.5

TUBE SEGMENT 8

Hout= 66.9884 Hin= 222.3582 K ,BTU/FT-H-F; 13.50261
ANNULUS= 1555.0 to 1670.0 F SHELL= 2199.2 to 2045.6 F FLUX= 21693 BTU/FT2
Utube= 42.5 BTU/HR-FT²-F DUTY= 37.4 MM BTU DELTA T= 509.9 LENGTH= 2.954
ANNULUS/SHELL DP= 3.79 / 0.23 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1875

TWIT SEGMENT 8

Hout= 186.6427 Hin= 165.3504
ANNULUS= 1555.0 to 1670.0 F TWIT= 1858.5 to 1794.2 F FLUX= 14545 BTU/FT2
Utwit= 68.0 BTU/HR-FT²-F DUTY= 9.4 MM BTU DELTA T= 213.9 LENGTH= 2.954
ANNULUS/TWIT DP= 3.79 / 0.12 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1770.6

TUBE SEGMENT 7

Hout= 66.68625 Hin= 213.0136 K ,BTU/FT-H-F; 13.76696
ANNULUS= 1440.0 to 1555.0 F SHELL= 2045.6 to 1861.9 F FLUX= 19220 BTU/FT2
Utube= 42.1 BTU/HR-FT²-F DUTY= 44.2 MM BTU DELTA T= 456.3 LENGTH= 3.928
ANNULUS/SHELL DP= 4.51 / 0.28 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1757

TWIT SEGMENT 7

Hout= 178.799 Hin= 164.2894
ANNULUS= 1440.0 to 1555.0 F TWIT= 1794.2 to 1696.6 F FLUX= 16539 BTU/FT2
Utwit= 66.7 BTU/HR-FT²-F DUTY= 14.1 MM BTU DELTA T= 247.9 LENGTH= 3.928
ANNULUS/TWIT DP= 4.51 / 0.15 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1693.6

PRELIMINARY

AS 4 of 7

File Name: A:TWIT2A'.dat. Case: TWIT2A'
03-12-1991 14:52:42

TUBE SEGMENT 6

Hout= 66.05441 Hin= 200.7002 K ,BTU/FT-H-F; 14.04231
ANNULUS= 1325.0 to 1440.0 F SHELL= 1861.9 to 1681.0 F FLUX= 16103 BTU/FT2
Utube= 41.4 BTU/HR-FT^2-F DUTY= 42.9 MM BTU DELTA T= 389.0 LENGTH= 4.443
ANNULUS/SHELL DP= 4.47 / 0.29 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1618

TWIT SEGMENT 6

Hout= 168.4634 Hin= 162.9211
ANNULUS= 1325.0 to 1440.0 F TWIT= 1696.6 to 1585.8 F FLUX= 16803 BTU/FT2
Utwt= 65.0 BTU/HR-FT^2-F DUTY= 15.8 MM BTU DELTA T= 258.7 LENGTH= 4.443
ANNULUS/TWIT DP= 4.47 / 0.16 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1593.4

TUBE SEGMENT 5

Hout= 65.19568 Hin= 186.6529 K ,BTU/FT-H-F; 14.32866
ANNULUS= 1210.0 to 1325.0 F SHELL= 1681.0 to 1527.5 F FLUX= 13619 BTU/FT2
Utube= 40.4 BTU/HR-FT^2-F DUTY= 35.8 MM BTU DELTA T= 336.8 LENGTH= 4.346
ANNULUS/SHELL DP= 3.79 / 0.26 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1472

TWIT SEGMENT 5

Hout= 156.6724 Hin= 161.4807
ANNULUS= 1210.0 to 1325.0 F TWIT= 1585.8 to 1478.4 F FLUX= 16631 BTU/FT2
Utwt= 62.8 BTU/HR-FT^2-F DUTY= 15.2 MM BTU DELTA T= 264.6 LENGTH= 4.346
ANNULUS/TWIT DP= 3.79 / 0.15 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1482.8

TUBE SEGMENT 4

Hout= 64.28342 Hin= 172.1231 K ,BTU/FT-H-F; 14.62603
ANNULUS= 1095.0 to 1210.0 F SHELL= 1527.5 to 1404.8 F FLUX= 12344 BTU/FT2
Utube= 39.4 BTU/HR-FT^2-F DUTY= 28.2 MM BTU DELTA T= 313.6 LENGTH= 3.840
ANNULUS/SHELL DP= 2.91 / 0.21 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1335

TWIT SEGMENT 4

Hout= 144.4764 Hin= 160.1089
ANNULUS= 1095.0 to 1210.0 F TWIT= 1478.4 to 1380.2 F FLUX= 16761 BTU/FT2
Utwt= 60.5 BTU/HR-FT^2-F DUTY= 13.8 MM BTU DELTA T= 276.8 LENGTH= 3.840
ANNULUS/TWIT DP= 2.91 / 0.12 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1373.7

TUBE SEGMENT 3

Hout= 63.42006 Hin= 157.9739 K ,BTU/FT-H-F; 14.9344
ANNULUS= 980.0 to 1095.0 F SHELL= 1404.8 to 1305.9 F FLUX= 12147 BTU/FT2
Utube= 38.2 BTU/HR-FT^2-F DUTY= 22.5 MM BTU DELTA T= 317.8 LENGTH= 3.082
ANNULUS/SHELL DP= 2.04 / 0.16 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1213

TWIT SEGMENT 3

Hout= 132.5999 Hin= 158.8851
ANNULUS= 980.0 to 1095.0 F TWIT= 1380.2 to 1297.7 F FLUX= 17531 BTU/FT2
Utwt= 58.2 BTU/HR-FT^2-F DUTY= 11.5 MM BTU DELTA T= 301.5 LENGTH= 3.082
ANNULUS/TWIT DP= 2.04 / 0.09 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1269.9

PRELIMINARY

pg 5 of 7

File Name: A:TWIT2A'.dat. Case: TWIT2A'
03-12-1991 14:52:46

TUBE SEGMENT 2

Hout= 62.63605 Hin= 144.6941 K ,BTU/FT-H-F; 15.25377
ANNULUS= 865.0 to 980.0 F SHELL= 1305.9 to 1224.9 F FLUX= 12711 BTU/FT2
Utube= 37.1 BTU/HR-FT²-F DUTY= 18.2 MM BTU DELTA T= 342.9 LENGTH= 2.370
ANNULUS/SHELL DP= 1.39 / 0.12 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1102

TWIT SEGMENT 2

Hout= 121.4531 Hin= 157.8434
ANNULUS= 865.0 to 980.0 F TWIT= 1297.7 to 1228.8 F FLUX= 18992 BTU/FT2
Utwt= 55.7 BTU/HR-FT²-F DUTY= 9.5 MM BTU DELTA T= 340.7 LENGTH= 2.370
ANNULUS/TWIT DP= 1.39 / 0.07 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1177.3

TUBE SEGMENT 1

Hout= 61.75129 Hin= 129.0259 K ,BTU/FT-H-F; 15.58416
ANNULUS= 750.0 to 865.0 F SHELL= 1224.9 to 1121.1 F FLUX= 12998 BTU/FT2
Utube= 35.6 BTU/HR-FT²-F DUTY= 23.0 MM BTU DELTA T= 365.5 LENGTH= 2.919
ANNULUS/SHELL DP= 1.51 / 0.14 PSI; TUBE ID= 3.00 IN.; TUBE CERAMIC TEMP= 1014

TWIT SEGMENT 1

Hout= 108.3016 Hin= 156.7342
ANNULUS= 750.0 to 865.0 F TWIT= 1228.8 to 1139.9 F FLUX= 19839 BTU/FT2
Utwt= 52.6 BTU/HR-FT²-F DUTY= 12.1 MM BTU DELTA T= 376.9 LENGTH= 2.919
ANNULUS/TWIT DP= 1.51 / 0.08 PSI; TWIT ID= 1.00 IN.; TWIT METAL TEMP= 1102.2

TOTAL LENGTH = 31.7 FT
TOTAL TUBE/SHELL PRESSURE DROP = 31.1 / 2.01 PSI
FLUE GAS FLOW = 681785 LB/HR
Gshell = 16.9 #/ft2 -sec
Gtwit = 15.29 #/ft2 -sec
Gannulus = 2.06 #/ft2 -sec
AVG INSIDE HEAT FLUX = 15731 BTU/HR-FT²
AVG OUTSIDE HEAT FLUX = 15921 BTU/HR-FT²
SUPERFICIAL VELOCITY = 388562 FT/H H2 SUPERFICIAL VELOCITY = 12246 HR⁻¹

PRELIMINARY

Base Taka
Design

	$\frac{OF}{1121}$	$\frac{OF}{750}$	$\frac{OF}{1140}$	$\frac{OF}{1140}$	$\frac{OF}{1140}$	$\frac{OF}{1140}$
						0
		1014		19,839	12,998	
	1225	965	1229			0.09
		1102		18,992	12,711	
	1306	980	1298			0.17
		1213		17,531	12,147	
23.35	1405	1095	1380			0.26
		1335		16,761	12,344	
19.51	1528	1210	1478			0.38
		1472		16,631	13,619	
	1681	1325	1586			0.52
		1618		16,803	16,102	
10.75	1862	1440	1677			0.66
		1757		16,539	19,220	
	2046	1555	1774			0.78
		1875		19,545	21,693	
5.0	2197	1620	1858			0.88
		1975		10,115	22,530	
	2311	1805	1891			0.94
	$H_0 = 66.93$ $H_{10} = 232.22$ $k = 1201$	2072	$H_0 = 179.71$ $H_{10} = 166.45$	3,654	21,895	
	2400	1900				1.00

3/12/92

pg 6 of 7

3/12/91

pg 7 of 7

Heat Flux and Temperature Profiles

Tube within a Tube Design

300 #/hr/tube

3.5" OD Ceramic Tube on 3.75" Δ Center

1.25" OD Inner Metal Tube

5/16" Catalyst

1125 F Fire Gas Exit Temp.

Tube Length = 32'

$THSV = 12,250 \text{ hr}^{-1}$

END

**DATE
FILMED**

5 / 3 / 93