8-82
12

I-6148

(2)

Lh. 946

ornl

ORNL-5791

OAK
RIDGE
NATIONAL
LABORATORY

ORNL--5791

DE83 001719

**Experimental and Calculational
Analyses of Actinide Samples
Irradiated in EBR-II**

D. Gilai
M. L. Williams
J. H. Cooper
W. R. Laing
R. L. Walker
S. Raman
P. H. Stelson

OPERATED BY
UNION CARBIDE CORPORATION
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
NTIS price codes—Printed Copy: A05; Microfiche A01

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability for responsibility for the accuracy, completeness, or usefulness of any information, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute an endorsement, recommendation, or approval by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL-5791
Dist. Category
UC-79d

Contract No. W-7405-eng-26

**EXPERIMENTAL AND CALCULATIONAL ANALYSES
OF ACTINIDE SAMPLES IRRADIATED
IN EBR-II**

MASTER

D. Gilai*
M. L. Williams

Engineering Physics Division

J. H. Cooper
W. R. Laing
R. L. Walker

Analytical Chemistry Division

S. Raman
P. H. Stelson

Physics Division

Date Published - October 1982

This Work was Sponsored by
U.S. Department of Energy
Division of Basic Energy Sciences

*Nuclear Research Center Negev, P.O. Box 9001, Beer-Sheva, ISRAEL

OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37830
operated by
UNION CARBIDE CORPORATION
for the
DEPARTMENT OF ENERGY

TABLE OF CONTENTS

ABSTRACT	v
ACKNOWLEDGMENTS	vii
I. INTRODUCTION	1
II. DESCRIPTION OF THE EXPERIMENTAL ENVIRONMENT	5
III. THE EXPERIMENTAL DETERMINATION OF THE SAMPLES COMPOSITION ...	9
IV. THE CALCULATIONAL ANALYSIS OF IRRADIATED SAMPLES	17
V. COMPARISON OF CALCULATIONAL AND EXPERIMENTAL RESULTS	37
VI. SENSITIVITY ANALYSIS OF INPUT PARAMETERS AND THEIR IMPACT ON CALCULATED RESPONSES	55
VII. SUMMARY AND CONCLUSIONS	71
VIII. REFERENCES	77
APPENDIX A. IRRADIATION HISTORY OF THE ACTINIDE SAMPLES IN EBR-II .	79
APPENDIX B. PROCEDURE FOR THE DISSOLUTION OF EBR-II IRRADIATED NICKEL CAPSULES CONTAINING PuO ₂	83

ABSTRACT

Higher actinides influence the characteristics of spent and recycled fuel and dominate the long-term hazards of the reactor waste. Reactor irradiation experiments provide useful benchmarks for testing the evaluated nuclear data for these actinides. During 1967-1970, several actinide samples were irradiated in the Idaho EBR-II fast reactor. These samples have now been analyzed, employing mass and alpha spectrometry, to determine the heavy element products. A simple spherical model for the EBR-II core and a recent version of the ORIGEN code with ENDF/B-V data were employed to calculate the exposure products. A detailed comparison between the experimental and calculated results has been made. For samples irradiated at locations near the core center, agreement within 10% was obtained for the major isotopes and their first daughters, and within 20% for the nuclides up the chain. A sensitivity analysis showed that the assumed flux should be increased by 10%. The lessons learned from the present study were incorporated into the planning of a future irradiation study to be carried out in the UK Prototype Fast Reactor at Dounreay.

ACKNOWLEDGEMENTS

The experiment involving irradiation of actinide samples in EBR-II was initiated by the scientific personnel at the Argonne National Laboratory. Their primary objective was to determine accurately the fission yields of various potential burnup monitors for application to fast reactors. A secondary objective was the study of heavy element transformations of the actinides. Beyond accomplishing the irradiations and the analysis of a single ^{239}Pu sample, this experiment was discontinued, for various reasons, at ANL. When requested, the irradiated samples were readily made available to us along with background information. We acknowledge deeply the assistance received from R. R. Heinrich, J. J. Hines, R. P. Larsen, D. Meneghetti, R. J. Meyer, R. D. Oldham, R. J. Popek and J. P. Unik, all from ANL. Some samples were shared with W. J. Maeck at Idaho. We thank J. E. Bigelow, J. A. Carter, J. W. T. Dabbs, M. C. G. Hall, C. R. Weisbin and J. R. White, all from ORNL, for their interest in this work and for several helpful comments and criticisms. We also thank S. Whetstone of the U.S. Department of Energy for his interest and encouragement.

I. INTRODUCTION

In performing fast reactor fuel cycle analysis, burnup calculations are done to determine not only the time-dependent reactor operating conditions and performance, but also many factors which may influence spent fuel reprocessing/fabrication and waste disposal. Calculations of reactor core performance (e.g., reactivity swing, breeding, etc.) depends largely on the accuracy of the cross sections for the "common" uranium and plutonium isotopes (^{238}U , ^{235}U ; ^{239}Pu , ^{240}Pu , ^{241}Pu). However, many of the factors which affect the ex-core portion of the fuel cycle depend on knowledge of the buildup of less common nuclides, such as ^{238}Pu and the Am and Cm isotopes. These nuclides influence the characteristics of the spent and recycled fuel through their contributions to neutron heating and source strength and dominate the long-term hazard of the reactor waste. The calculated production of these nuclides depends on the more "exotic" nuclear data of the trans-plutonium actinides, which until recently has been poorly represented on the ENDF/B data files. The latest release of ENDF/B, version V, supposedly has much improved data for the higher actinides; however, the new data have never actually been tested against actual fast reactor experiments.

Reactor irradiation experiments can provide an integral comparison of measurement versus calculation and hence are useful as benchmarks for data testing. While this type of information is available for several thermal reactor cores, very little experimental information exists on the transmutation of actinides irradiated in fast reactors. Until the advent of the Fast Flux Test Facility (FFTF), the Experimental Breeder

Reactor (EBR-II) was the only fast reactor available in the U.S. for such experiments, and its spectrum is somewhat harder than the spectrum in proposed commercial LMFBR's. A joint U.S. and United Kingdom program is currently under way to irradiate many actinide samples in the English Prototype Fast Reactor (PFR). The actinide samples are to be provided by the U.S. and will include such nuclides as ^{231}Pa , ^{241}Am , ^{243}Am , ^{243}Cm , ^{244}Cm , and ^{245}Cm , as well as the more common thorium, uranium, and plutonium isotopes. Pure samples of these isotopes are very valuable and therefore prior to the proposed PFR irradiation, a similar irradiation experiment done in EBR-II has been analyzed to obtain experience and to reveal any pitfalls in performing fast reactor experiments, which hopefully could be avoided in the PFR experiment.

During the years 1967-1970 several actinide samples ranging from ^{232}Th to ^{241}Pu were irradiated in the Idaho Experimental Breeder Reactor EBR-II. The actinides examined in this experiment, and their exposure products, are of importance for physical analysis and economical evaluation of the in-core portion of fast breeder reactor fuel cycles. The original goal of our efforts was to test methods and nuclear data used in fast reactor core calculations; however, the goal was extended to also provide recommended procedures for the future PFR experiment. The purpose of this report therefore is to present results of, as well as to review critically, the calculational and experimental procedures used to determine the exposure products in the irradiated samples.

The burnup or buildup of actinides in a sample may be derived from the difference between the sample's isotopic compositions before and after irradiation, the former being measured not directly for the sample itself but for an identical unirradiated control sample.

Analyses of one of the irradiated (as well as the unirradiated) EBR samples began soon after they had been discharged from the reactor, by the Chemistry Division at ANL; however, all other samples remained untouched until 1978 when ORNL started a program to complete the analysis. This work was finished in early 1981.

In the next chapter a description of the experimental environment as it concerns the present study is given. A description of the experimental techniques used for sample analysis and a detailed description of the calculational model are given in Chapters III and IV respectively. The experimental and calculational results are compared in Chapter V. This chapter also discusses the adequacy of the calculational procedures employed in the study. Since discrepancies between calculation and experiment were found for some samples, a series of sensitivity calculations were performed in order to reveal possible sources of errors. The results of these calculations are given in Chapter VI. Concluding remarks and recommendations for future experiments are given in Chapter VII.

4

II. DESCRIPTION OF THE EXPERIMENTAL ENVIRONMENT

The EBR-II reactor configuration at the time of this experiment consisted of a driver core of highly enriched (~50%) uranium, surrounded by a depleted ^{238}U blanket. The fuel was arranged in a hexagonal array of 91 subassemblies of which 16 locations were reserved for experimental purposes.¹ The lattice pitch was 5.89 cm and the core height varied between 34.3 and 36.1 cm. The experimental actinide samples were stacked in two sealed tubes. The first tube, containing 12 samples, was placed in the driver core and the second, containing 8 samples, was placed below the first one in the axial blanket. The ordering of the samples in the tubes is given in Figure 1.

in reactor	^{232}Th (21)	in blanket	^{241}Pu (11)
	^{238}U (81)		^{235}U (52)
	^{239}Pu (92)		^{238}U (82)
	^{233}U (31)		^{237}Np (71)
	^{235}U (53)		^{239}Pu (91)
	^{239}Pu (93)		^{240}Pu (01)
	^{235}U (51)		^{233}U (33)
	^{239}Pu (94)		^{232}Th (23)
	^{233}U (32)		
	^{240}Pu (02)		
	^{241}Pu (14)		
	^{237}Np (72)		

Figure 1. Samples Placement in EBR-II

Each of the 20 samples had an identity number shown in Figure 1. These numbers were given at the early stage of the experiment and are used in the present report for compatibility with other reports.

The sample materials, usually about 100 mg in weight, were loosely packed oxide powders sealed in cylindrical nickel containers.² The outer diameter of each container was 0.912 cm and their wall thickness was 0.185 cm. Each cylinder was 2.87 cm high so that the total length of 12 stacked containers was equivalent to a core height of 34.3 cm. To protect against hazards which might be caused by a failure of the containers, the reactor and the blanket samples were separately assembled into two sealed nickel capsules, which were designed to keep fission products from entering the coolant. These capsules also contained small amounts of NaK for better heat removal.

Due to its nature as an experimental reactor, the EBR-II core was continuously changing during the irradiation period. These changes should be taken into consideration since they could affect the burnup history of the samples by causing flux levels and spectra to vary from loading to loading. However, it was observed³ that the relative fluence distribution along a core radius remained almost constant from run to run from which it was inferred that the relative flux distribution also remained nearly constant. Another observation was that the measured values of (σ_c/σ_f) for many isotopes do not change during many EBR runs,⁴ which leads to the conclusion that the flux spectrum is nearly constant too. Therefore it has been assumed that a single representative model of the reactor at a characteristic time

will be sufficient for all calculations; i.e., the only time-dependent variable which has to be considered is the power level of the reactor. This parameter was provided by ANL and was used in the depletion calculations described later. The majority of this information may be found in Ref. 5.

§

III. THE EXPERIMENTAL DETERMINATION OF THE SAMPLES COMPOSITION

A. INTRODUCTION

Mass spectrometry has been used to measure the isotopic distribution and total quantity of uranium and plutonium in irradiated samples from the EBR-II reactor. Tracers of U-233, U-236, and Pu-242 were used for quantitative analysis by isotope dilution. Neptunium and actinide products formed by nuclear reactions were measured by alpha spectrometry. Burn-up calculations have been made to compare with the results obtained from these measurements.

B. EXPERIMENTAL

1. INSTRUMENTAL

The mass spectrometer measurements were made using a 2-stage, 30-cm radius thermal emission mass spectrometer of ORNL design.⁶ High vacuum is achieved by ion pumping, with normal operating pressures $< 4 \times 10^{-5}$ Pa. A pulse-counting detection system, comprised of an RCA 6810 electron multiplier as the detector, an ORTEC discriminator, an ORTEC scaler, and an ARL preamplifier, is used for higher sensitivity. This system, which operates under the control of a Digital Equipment Corporation PDP-11/10 computer, scans the mass range by adjusting the high voltage source. Only peak tops are scanned, and it is possible to sweep each peak top a preselectable number of times for each scan across the mass region. For the analysis of plutonium and uranium, a background correction is made to all masses.

Measurements made on nuclides such as Np-237, Pu-239, and Pa-231 were done using gas-flow, alpha counters and pulse height analysis systems common to radiochemical laboratories.

2. SAMPLE DISSOLUTION

The first step in the analysis of irradiated targets is to prepare a clean area for sample dissolution. A hot cell was cleared of all unneeded equipment and cleaned thoroughly. Both detergents and acid washes were used with remote scrubbing and pressure washers.

New quartz reflux flasks and water-cooled condensers were placed in the cell. Each compact was weighed using an analytical balance with 0.1 mg sensitivity and placed in the quartz flask. Nitric acid was used to dissolve the targets according to the procedure in Appendix B. An addition of a small amount of hydrofluoric acid aided the dissolution of samples containing thorium or plutonium. After dissolution was complete (4-24 hours) the solution was transferred to a new volumetric flask, made to volume, and weighed to ± 0.1 mg. Aliquots were removed from this solution for the measurement of individual elements or isotopes. Duplicate blanks were carried through the entire process with each set of samples.

3. SAMPLE PREPARATION

A weight basis was employed for all aliquanting and dilutions to improve the precision and accuracy of the analyses. A simplified resin bead sample preparation procedure for plutonium and uranium isotopic composition has been developed at ORNL⁷ and used for this work. In this method, several anion resin beads are introduced into a solution of the sample in 8 M HNO₃ to absorb Pu, U, or Th. A single bead

is removed and transferred to a rhenium V-shaped filament for mass analysis. The amount of each element on a single bead is several nanograms, which is adequate for a sequential analysis of plutonium and uranium or thorium. For this work, only zone-refined rhenium was used for making filaments, and they were cleaned after manufacture by baking at 2000 C for 30 minutes.

Where alpha counting was the choice for quantitative analysis, solvent extraction techniques were employed to prepare purified samples. Methylisobutyl ketone was used to extract Np-237 and Pu-238 and diisobutyl carbinol was used for extraction of Pa-231.

C. RESULTS

The primary target isotopes used in this experiment were U-233, U-235, U-238, Pu-239, Pu-240, and Pu-241. The results for the initial, unirradiated isotopic compositions are given in Table 3.1. Isotopic data for the starting fuel were taken from an ANL report² and confirmed by recent ORNL measurements made on archive samples. There is very good agreement between the two sets of data. No correction for decay of Pu isotopes was made on ORNL data; however, if one uses 16 years since ANL analysis for this calculation, plutonium isotopic results agree well. For this experiment, this approximation was sufficient for confirmation.

The results for the primary target nuclides are given in Tables 3.2 and 3.3. The quantity of fuel loaded into targets and the quantity measured by isotope dilution after irradiation are shown. Precisions quoted for all isotopic measurements are given under the individual

Table 3.1 Unirradiated Uranium and Plutonium Isotopic Compositions

Major Isotope	Isotope	Composition (%) ANL ^a	Composition (%) ORNL ^b $\pm$ S.D.
U-233	233	98.51	98.518 $\pm$ 0.003
	234	1.06	1.051 $\pm$ 0.003
	235	0.012	0.019 $\pm$ 0.001
	236	-	<0.001
	238	0.414	0.412 $\pm$ 0.006
U-235	234	0.90	0.908 $\pm$ 0.001
	235	93.16	93.250 $\pm$ 0.015
	236	0.438	0.436 $\pm$ 0.002
	238	5.50	5.406 $\pm$ 0.013
U-238	234	-	0.0010 $\pm$ 0.0001
	235	0.037	0.045 $\pm$ 0.001
	236	-	0.0018 $\pm$ 0.0002
	238	99.96	99.952 $\pm$ 0.001
Pu-239 ^c	239	95.17	No archive sample available.
	240	4.59	
	241	0.218	
	242	0.019	
Pu-240	238	-	0.0024 $\pm$ 0.0001
	239	0.77	0.825 $\pm$ 0.004
	240	98.58	98.798 $\pm$ 0.005
	241	0.54	0.253 $\pm$ 0.002
	242	0.11	0.121 $\pm$ 0.001
Pu-241	238	-	0.0152 $\pm$ 0.0002
	239	1.03	2.094 $\pm$ 0.009
	240	3.66	7.539 $\pm$ 0.009
	241	94.04	87.853 $\pm$ 0.009
	242	1.27	2.499 $\pm$ 0.002

^aData from ANL report (ANL-RCV-4084); no precision given; date of analysis not well documented, but would be before 1966. See Ref. 2.

^bORNL measurements - July, 1980, on archive samples. Plutonium data not corrected for decay.

^cThe isotopic composition for this archive sample was supplied by J. J. Hines (ANL). The values listed here supersede those listed in Ref. 2.

Table 3.2 Isotopic Composition of Uranium in Irradiated Samples

Major ^a Isotope	wt. of U, mg		Isotope Composition of U (%)				
	Before Irradiation	After Irradiation	233	234	235	236	238
U-233(31)	100.07	82.74 ±0.13	96.827 ±0.006	2.552 ±0.002	0.076 ±0.001	0.0014 ±0.001	0.544 ±0.004
U-233(32)	134.48	113.4 ±1.0	96.96 ±0.01	2.50 ±0.001	0.060 ±0.001	0.007 ±0.001	0.47 ±0.01
U-233(33)	57.81	48.76 ±0.24	96.222 ±0.022	3.080 ±0.022	0.194 ±0.004	0.005 ±0.001	0.500 ±0.014
U-235(53) ^b	88.19	79.3 ±0.5	-	0.89 ±0.01	90.51 ±0.02	2.69 ±0.01	5.92 ±0.02
U-238(81) ^c	91.58	90.30 ±0.4	-	0.0007 ±0.0002	0.035 ±0.001	0.0014 ±0.0002	99.963 ±0.001
U-238(82)	87.85	84.07 ±0.42	-	0.0018 ±0.0002	0.033 ±0.001	0.0015 ±0.0002	99.963 ±0.001
Th-232(21) ^d	0.00	0.58 ±0.04	98.60 ±0.1	0.90 ±0.1	0.17 ±0.03	-	0.41 ±0.05

^aCapsule number in parentheses.

^bMore uncertainty surrounding these data. Sample was dissolved at ANL or Idaho Falls; solutions sent to ORNL for analysis. All others received in capsules and dissolved at ORNL.

^cPu composition for this sample is listed in Table 5.4.

^dInitial weight of Th before irradiation was 32.81 mg.

Table 3.3 Isotopic Composition of Plutonium in Irradiated Samples

Major ^a Isotope	Wt. of Pu, mg		Isotopic Composition of Pu (%)				
	Before Irradiation	After Irradiation	238	239	240	241	242
Np-237(72) ^c	0.0	.056 ±.0017	100.00				
Pu-239(94)	105.74	89.93 ±1.00	0.016 ±0.002	93.247 ±0.016	6.476 ±0.016	0.234 ±0.003	0.026 ±0.001
Pu-239(91)	71.35	66.56 ±0.34	0.022 ±0.001	90.588 ±0.002	8.771 ±0.002	0.577 ±0.003	0.041 ±0.001
Pu-239(92) ^b	82.99	82.00 ±0.2	0.019 ±0.002	93.148 ±0.015	6.555 ±0.015	0.251 ±0.002	0.026 ±0.001
Pu-240(02)	51.44	47.54 ±0.12	0.012 ±0.001	0.753 ±0.004	97.768 ±0.004	1.324 ±0.005	0.143 ±0.002
Pu-241(14) ^b	32.84	15.64 ±0.20	1.94 ±0.01	2.00 ±0.01	7.25 ±0.05	83.78 ±0.05	5.03 ±0.04
Pu-241(11)	26.31	10.13 ±0.02	3.245 ±0.008	1.903 ±0.015	6.776 ±0.024	81.185 ±0.025	6.891 ±0.015

^aCapsule number in parentheses.

^bMore uncertainty surrounding these data. Samples were dissolved at ANL or Idaho Falls; solutions sent to ORNL for analysis. All others received in capsules and dissolved at ORNL.

^cInitial weight of Np before irradiation was 1.0 mg.

results; they are standard deviation values which represent internal precision. The accuracy of the measurements is expected to be better than one percent except in cases indicated by the footnote b in Tables 3.1 and 3.2.

16

IV. THE CALCULATIONAL ANALYSIS OF IRRADIATED SAMPLES

A. SEPARATION INTO SPACE- AND TIME-DEPENDENT PROBLEMS

A complete calculational analysis of the irradiation process requires a solution of the coupled neutron-nuclide equations in space, energy, and time. However, for long irradiation periods and frequent changes in core composition, such an approach becomes too elaborate and expensive for this type of experiment. A frequently used approximation is to assume space-time separability by splitting the equations into two sets, one being time independent and the other being space independent. Such an approach is applicable for the analysis of EBR-II since as stated above, its flux distribution and spectrum (but not flux level) remained essentially constant during the whole period of irradiation. The calculation of the exposure products at the end of irradiation was therefore performed in two steps. In the first step, the flux spatial shape and spectrum were calculated for a representative EBR-II model.⁸ The flux spectrum was then used to collapse a multigroup cross section set into a one-group library. In the second step, the one-group cross sections, along with the flux level history of the EBR-II, were utilized in a series of depletion calculations which provided the amounts of exposure products in each sample. A detailed description of this approach will follow next.

B. THE SPACE-DEPENDENT PROBLEM: DETERMINATION OF FLUX SPECTRUM AND ONE-GROUP CROSS SECTIONS

During the period in which the actinide samples were irradiated in EBR-II, the reactor was started up and shut down more than 60 times.

In most of the shutdown periods, fresh fuel subassemblies were loaded or spent fuel subassemblies were discharged while some others were shuffled for experimental purposes. The core configuration was therefore continuously changing, so that it is difficult to determine a "typical" configuration out of the many different core loadings. Yet, since our purpose is to check the adequacy of a simple model for burn-up analysis, we will focus the analysis on a model, which although containing few details about the fine structure of the core composition, may still be regarded as a representative model for many core loadings. This model is described in Ref. 8 and is basically a one-dimensional spherical reactor, divided in three different concentric zones: an inner driver core, a reflector, and a blanket. The material composition in each zone is assumed to be homogeneous so that there are no irregularities other than the differences between the three zones in the model. The effects of localized heterogeneities on the flux are usually small for fast reactors because of the long mean free path of high energy neutrons. The materials comprising each zone and their atom densities are listed in Table 4.1.

In order to judge how adequate this simplified model is, and to justify several assumptions made later, a picture of the simplified model overlapping the real reactor configuration is given in Fig. 2. This picture shows that the inner core of EBR-II may hardly be described as a sphere because its diameter-to-height ratio is far away from 1.0. Since only the center zones of both models do overlap, it is difficult to locate the sample positions in the simplified model, especially for those near the inner core boundary.

Fig. 2: The EBR-II spherical model compared to the real geometry of EBR-II

Table 4.1 Composition of simplified EBR-II Model

Material	Concentration (atoms/cm ³ *10 ²⁴)		
	25.2 cm Radius Core	10 cm thick Reflector	35 cm thick Blanket
²³⁵ U	6.3·10 ⁻³	-	6.0·10 ⁻⁵
²³⁸ U	6.0·10 ⁻³	-	2.9·10 ⁻²
²³⁹ Pu	1.0·10 ⁻⁵	-	3.0·10 ⁻⁵
Fe	1.2·10 ⁻²	4.5·10 ⁻²	1.2·10 ⁻²
Ni	1.5·10 ⁻³	6.1·10 ⁻³	1.5·10 ⁻³
Cr	3.0·10 ⁻³	1.4·10 ⁻²	3.0·10 ⁻³
Na	1.1·10 ⁻²	4.0·10 ⁻³	4.0·10 ⁻³
Mo	7.0·10 ⁻⁴	-	-

The exact location of the samples however, is for two reasons most important: firstly because the location of the sample determines the flux level to which its nuclides are exposed, and secondly because the flux spectrum varies from point to point. It is important to use the flux spectrum pertaining to the location of the sample in order to obtain appropriately collapsed cross sections for the subsequent depletion calculations. To overcome the above mentioned difficulty, spatial flux distributions were taken from earlier two-dimensional calculations provided by ANL instead of from the simplified model calculations, which was used merely to obtain flux spectra for different sample locations. To that end the inner core was divided into three subzones, each representing a part of the core in which only small flux spectra variations are expected. The radii of these subzones were chosen somewhat arbitrarily and are also shown in Figure 2.

At the time the samples were first introduced into the reactor they were located at row 2, which is one lattice pitch off center. Later on (from run 34A) they were moved to row 4, where they remained until their final discharge (with exception of short periods in which they were entirely withdrawn from the reactor). From Figure 1 it can be seen that the change in the position of the samples subassembly causes each sample to move into the next subzone of the driver core, a fact which has to be taken in consideration when choosing the appropriate spectrum-averaged cross sections for subsequent depletion calculations.

From EBR-II reports it can be learned that besides the changes in core loading from run to run, which may be regarded as minor changes, several major changes also took place. The most important change is the transition from MARK-I to MARK-1A type driver fuel. During this time the reactor axial blanket was also changed from depleted uranium to stainless steel. MARK-1A subassemblies were used during most of the period in which the samples resided in core; therefore the depleted uranium in the blanket zone of the simplified model was replaced by stainless steel (identical with the reflector). In order to check the adequacy of both configurations, two models have been calculated, one with depleted uranium in the core outer region and the other with stainless steel.

The calculations were performed with the modular AMPX9 code system, from which the modules AJAX, BONAMI, XSDRN, and MALOCS were utilized. Cross sections were taken from the 174-group VITAMIN-E library which is based on the recently released ENDF/B-V. One of the goals of this

study is to check this library against the former ENDF/B-IV library since at the time there was little experience with fast reactor calculations utilizing ENDF/B-V.

The calculational procedure starts with a resonance self-shielding calculation for the mixtures in the core and the blanket. Assuming the materials in each region were homogenously mixed, the resonance self-shielding calculation was performed by the Bondarenko method with the BONAMI module. As might have been expected, the self-shielding effect was negligibly small because the EBR-II has such a hard spectrum that most of the neutrons never reach the resonance region. To demonstrate this fact, shielded and unshielded one-group cross sections collapsed from the VITAMIN-E library are given in Table 4.2. The collapse was performed in two steps: first using a typical ZPR spectrum, the 174-group cross sections were collapsed into a 15-group data set; then using the EBR-II spectrum obtained from ANL, the 15-group cross sections were further collapsed into a one-group data set.

Table 4.2 A Comparison Between Resonance Self-shielded and Unshielded One-Group Cross Sections (in barns)

Nuclide	σ_c		σ_f	
	Unshielded	Shielded	Unshielded	Shielded
^{235}U	.2444	.2443	1.3407	1.3403
^{238}U	.1397	.1383	.0799	.0799
^{239}Pu	.1535	.1533	1.6559	1.6557

Following the self-shielding calculations, the flux distributions for the two previously mentioned EBR-II models were computed with the one-dimensional discrete ordinate transport code XSDRN-PM. In the present calculations an $S_8 - P_3$ approximation was used and as many as 49 intervals were used for the spatial distribution. The same code was also utilized to collapse the cross sections from 174 groups to one group in each of the subregions of the two driver cores. It should be noted that only the cross sections for the most important isotopes have been selected for collapsing in this way. For all other isotopes a generic one-group library for LMFBF calculations was used in subsequent depletion calculations.

In Table 4.3, one-group cross sections for capture, fission, and $(n,2n)$ reactions are given for the 3 subregions of the uranium blanketed driver core. Similar cross sections for the stainless steel blanketed core are given in Table 4.4, however, with a slight difference. Since cross sections in zones 1 and 2 are almost the same, Table 4.4 does not contain cross sections for zone 1. On the other hand, since the spectrum in the stainless steel is much softer than in the core, it is expected that the spectrum at the core outer boundary will also be softer. For this reason an additional subzone, which is the last interval of the driver core, was added to Table 4.4 designated as zone 3'. Note that this zone is a part of zone 3 and that the cross sections for zone 3 are averaged over a core section also containing zone 3'.

Table 4.3 1-Group Cross Sections Collapsed from the 174-Group
V-E Library Using a Simplified EBR-II Spherical
Model with a Depleted Uranium Blanket

Isotope	Zone	σ_c	σ_f	$\sigma_{n,2nd}$
232Th	1	.1801	2.290	3.673-3
	2	.1858	2.220-2	not calculated
	3	.2127	1.920	2.998-3
233U	1	.1353	2.071	1.331-3
	2	.1395	2.087	1.291-3
	3	.1570	2.162	1.099-3
234U	1	.2814	6.894-1	3.051-4
	2	.2891	6.714-1	3.497-4
	3	.3286	6.095-1	3.392-4
235U	1	.2226	1.320	1.897-3
	2	.2325	1.334	1.840-3
	3	.2716	1.393	1.567-3
238U	1	.1279	1.042-1	3.705-3
	2	.1326	1.010-1	3.593-3
	3	.1501	8.770-2	3.060-3
239Pu	1	.1369	1.669	7.939-4
	2	.1460	1.669	7.700-4
	3	.1895	1.680	6.558-4
240Pu	1	.1937	7.333-1	3.497-4
	2	.2035	7.149-1	3.392-4
	3	.2505	6.501-1	2.889-4
241Pu	1	.1893	1.746	5.188-3
	2	.1968	1.765	5.032-3
	3	.2291	2.080	4.286-3

Even though these ($n,2n$) cross sections are small, there exist serious deficiencies and inconsistencies amongst them. In particular, we suggest that the cross section for ^{234}U is much too small. Both cross sections collapsed from ENDF/B-IV. All others are from ENDF/B-V.

Table 4.4 1-Group Cross Sections Collapsed from the 174-Group
V-E Library Using a Simplified EBR-II Spherical
Model with a Stainless Steel Blanket

Isotope	Zone	σ_c	σ_f	$\sigma_{n,2n}^a$
^{233}U	2	.1409	2.093	1.280-3
	3	.1763	2.271	1.098-3
	3'	.2264	2.539	8.932-4
^{234}U	2	.2930	6.694-1	3.552-4
	3	.4366	6.089-1	3.046-4
	3'	.6887	5.553-1	2.479-4
^{235}U	2	.2344	1.3368	1.825-3
	3	.2938	1.436	1.564-3
	3'	.3676	1.569	1.273-3
^{238}U	2	.1333	1.003-1	3.564-3
	3	.1569	8.758-2	3.055-3
	3'	.1843	7.480-2	2.486-3
^{239}Pu	2	.1490	1.671	7.636-4
	3	.2426	1.742	6.548-4
	3'	.3831	1.876	5.238-4
^{240}Pu	2	.2077	7.127-1	3.364-4
	3	.4453	6.498-1	2.885-4
	3'	1.0107	5.934-1	2.347-4
^{241}Pu	2	.1994	1.771	4.991-3
	3	.2718	1.970	4.279-3
	3'	.3791	2.277	3.482-3

^aEven though these (n,2n) cross sections are small, there exist serious deficiencies and inconsistencies amongst them. In particular, we suggest that the cross section for ^{234}U is much too small.

Upon examining the data in Tables 4.3 and 4.4, one notices first that there are only slight differences between cross sections in zones 1 and 2 of both models (this is true also for the cross sections of zone 1 in the stainless steel blanketed reactor not given in Table 4.4). Consequently it was concluded that one-group cross sections are insensitive to the composition of the blanket and to the location in the core over a region which spreads far away from the core center. Since many of the samples were located in this region, we may be fairly confident about the spectrum-averaged cross sections used in the depletion calculations for these samples. However, the rapid increase in the capture cross sections of zone 3 in both models and the high cross sections obtained at the core-reflector interface of the core with the stainless steel blanket indicate sensitivity to modeling approximations in cross sections for samples at these locations. The effect of the reactor location on the flux spectrum is shown in Fig. 3, where flux spectra at the core center and at the core outer boundary are plotted. From this figure it can be seen that the spectrum at the core center is harder than the spectrum at the outer boundary. This is the reason for the capture cross section increase at off-center areas as shown in Tables 4.3 and 4.4.

Figure 3. Calculated Flux Spectra at the Core Center and the Core Outer Boundary of EBR-II

As already mentioned, one goal of this study was to test results based on ENDF/B-V cross sections against results which were derived using ENDF/B-IV. To that end the EBR-II model with the depleted uranium blanket was calculated with an older 174-group library based on ENDF/B-IV and one-group cross sections were processed the same way as previously. In the next two tables, capture and absorption cross sections obtained with both libraries are compared. As may be seen, ENDF/B-V cross sections usually differ by less than 2.5% from the ENDF/B-IV values with an exception for ^{232}Th and ^{240}Pu (capture and absorption) and ^{234}U (absorption only). The differences in the thorium cross sections are thought to result from a known error in the ENDF/B-V file, so that for this nuclide, ENDF/B-IV cross sections are preferred. Differences in the other cross sections presumably reflect improvements arising from new measurements and/or evaluations.

Table 4.5. Comparison Between ENDF/B-IV and V
Capture Cross Sections

Isotope	Zone	ENDF/B-IV σ_c	ENDF/B-V σ_c	Relative Change (%)
^{232}Th	1	.1801	.1599	-11.2
	2	.1858	not calculated	
	3	.2127	.1779	-16.4
^{233}U	1	.1374	.1353	-1.5
	2	.1415	.1395	-1.4
	3	.1581	.1570	-0.7
^{234}U	1	.2821	.2813	-0.2
	2	.2893	.2891	-0.1
	3	.3253	.3286	1.0
^{235}U	1	.2283	.2226	-2.5
	2	.2383	.2325	-2.4
	3	.2784	.2716	-2.4
^{238}U	1	.1310	.1279	-2.4
	2	.1357	.1326	-2.3
	3	.1537	.1501	-2.3
^{239}Pu	1	.1403	.1369	-2.3
	2	.1494	.1460	-2.3
	3	.1927	.1895	-1.7
^{240}Pu	1	.1757	.1937	10.2
	2	.1846	.2035	10.2
	3	.2278	.2505	10.0
^{241}Pu	1	.1918	.1893	-1.3
	2	.1993	.1968	-1.3
	3	.2318	.2291	-1.2

Table 4.6. Comparison Between ENDF/B-IV and V
Absorption Cross Sections

Isotope	Zone	ENDF/B-IV σ_a	ENDF/B-V σ_a	Relative Change (%)
^{232}Th	1	0.2030	0.1839	-9.4
	2	0.2080	not calculated	
	3	0.2319	0.1983	-14.5
^{233}U	1	2.1639	2.2062	2.0
	2	2.1872	2.2266	1.8
	3	2.2882	2.3191	1.4
^{234}U	1	0.9037	0.9707	7.4
	2	0.8946	0.9604	7.4
	3	0.8731	0.9381	7.4
^{235}U	1	1.5597	1.5424	-1.1
	2	1.5843	1.5662	-1.1
	3	1.6878	1.6642	-1.4
^{238}U	1	0.2314	0.2321	0.2
	2	0.2331	0.2336	0.2
	3	0.2383	0.2378	-0.2
^{239}Pu	1	1.7961	1.8055	0.5
	2	1.8052	1.8147	0.5
	3	1.8601	1.8949	1.9
^{240}Pu	1	0.8767	0.9270	5.7
	2	0.8681	0.9184	5.8
	3	0.8489	0.9006	6.1
^{241}Pu	1	1.9451	1.9352	-0.5
	2	1.9705	1.9621	-0.4
	3	2.0858	2.0801	-0.3

C. THE TIME-DEPENDENT PROBLEM: BUILDUP AND DECAY OF TRANSMUTATION PRODUCTS

Having obtained appropriate space-dependent cross sections for each sample location, the time-dependent transmutation process by which nuclides are generated and destroyed may be described by the following matrix equation:¹⁰

$$\frac{dN(\underline{X}_0, t)}{dt} = [\underline{M}(\sigma(\underline{X}_0))\phi(\underline{X}_0, t) + \underline{\lambda}] N(\underline{X}_0, t) , \quad (1)$$

where $\underline{M}(\sigma(\underline{X}_0))$ is a time-independent matrix which contains all (one-group) cross sections that contribute to the transmutation of nuclides at position $\underline{X}_0$, $\underline{\lambda}$ is a matrix of radioactive decay constants, including α , β^- , and β^+ decays as well as appropriate branching ratios, and $\phi(\underline{X}_0, t)$ is the total energy-integrated flux at the reactor location $\underline{X}_0$. We have chosen to write Eq. (1) in a somewhat unconventional way in order to emphasize some aspects of the approach used in the present study. First, the space-time separation becomes apparent in view of the fact that the cross section matrix $\underline{M}(\sigma(\underline{X}_0))$ is considered to be time-independent. Further the flux at point $\underline{X}_0$ is usually a complex function which depends on the core composition, burnup level, control rod position and reactor power. However, as was already stated, we assume that the flux may be separated in space and time so that we may write:

$$\phi(\underline{X}, t) = \phi_0(\underline{X}) \cdot x(t) . \quad (2)$$

We may further express the spatial term $\phi_0(\underline{X})$ as a fraction of the maximum flux:

$$\phi_o(x) = \phi_o(\text{max}) \cdot \psi(x) , \quad (3)$$

where $\psi(x)$ may be regarded as a shape function of the flux, independent of time and flux level.

Inserting Eqs. (2) and (3) into (1), we obtain for the nuclides at position x_o :

$$\frac{dN(x_o, t)}{dt} = [\phi_o(\text{max}) \sigma(x_o) \psi(x_o) \chi(t) + \lambda] N(x_o, t) . \quad (4)$$

Under the assumption that the flux is separable in time and space, Eqs. (1) and (4) are equivalent. The advantage of Eq. (4) is that it expresses the space and time dependence of the flux in easily measurable quantities. The value for $\phi_o(\text{max})$ was measured in EBR-II and was found to be $2.5 \cdot 10^{15}/\text{cm}^2\text{s}$ at core center when the reactor was operating at 50MW. The shape function may be either measured or calculated, and the time function $\chi(t)$ may be obtained from the recorded power history of the reactor, since by constant core characteristics, the time dependence of the flux at any location is proportional to the power output of the reactor. It should be noted however, that when the core suffers substantial burnup, this statement is no longer valid because in that case higher fluxes are required in order to maintain the reactor power at a constant level. However, since burnups of only 1-2% were recorded¹¹ for representative subassemblies, power and flux may be assumed proportional over the entire considered irradiation period.

The irradiation of the samples began on December 6, 1965 when run number 24 was started, and ended on September 10, 1970 with the shut-down of run 45B. During this time the reactor was shut down many

times. However, although a full record of the power schedule was provided by ANL, the history of the samples during this period was not well documented, a fact which caused some confusion in preliminary calculation. For that reason a full description of the irradiation history of the samples is given in Appendix A, indicating primarily two major events: first, the subassembly which contained the samples was removed from its original location at row 2 (one lattice position off center) to row 4 before starting run 34A; and secondly, there were several runs when the samples were entirely withdrawn from the reactor. These two events significantly affected the total fluence to which the samples were exposed and were taken into account in the subsequent depletion calculations.

To complete the description of the irradiation history, the flux level at each sample's location must be given. Once a flux distribution for any power level is given, it may be used to obtain a shape function from which fluxes at any location may be calculated. As already stated, such a distribution, factorized in axial and radial functions, was provided by ANL. Thus an overall shape function could be determined as a product of the axial and radial shape functions, each normalized to 1.0 at the reactor center. The radial distribution showed that at row 2 the total flux was 0.99 of the flux at core center, whereas at row 4 it dropped to 0.85. The axial shape factor for the different samples is given in Table 4.7. However, since the flux distributions provided by ANL extend over the driver core only, shape factors for the samples in the lower axial blanket may not be given, and therefore calculations were not performed for those samples. In Table 4.7 the slight asymmetry between top and bottom should be noted.

Table 4.7. Axial Shape Factors for Samples in Driver Core

Sample Position	Sample ID	Major Isotope	Axial Shape Factor
1	21	^{232}Th	.73
2	81	^{238}U	.81
3	92	^{239}U	.88
4	31	^{233}U	.94
5	53	^{235}U	.97
6	93	^{239}U	1.00
7	51	^{235}U	1.00
8	94	^{239}Pu	.97
9	32	^{233}U	.95
10	02	^{240}Pu	.89
11	14	^{241}Pu	.82
12	72	^{237}Np	.74

To perform the time-dependent depletion calculations, the code ORIGEN¹⁰ was utilized. Given a set of initial values for the nuclides of interest and a set of one-group cross sections, this code traces the process of formation and destruction of these nuclides for any given flux history. Initial values and flux history are provided as input to the code whereas the cross-section and decay constant matrices are usually taken from standard libraries. An option provided in ORIGEN, however, allows cross sections to be input and therefore those generated by the simplified EBR-II model calculations were used to replace the standard ORIGEN library. The library was altered from sample to sample according to their position in the reactor.

A special option in ORIGIN enables the calculation of transmutation processes after shutdown. This option was used to extend the calculations over the postirradiation period till the time the samples were finally analyzed, a period of 8-10 years in most cases. The addition of this period to the calculations is important not only for the unstable nuclides, but also for stable ones which may gain appreciable amounts during this period from the decay of other nuclides. As an example, 10 years after withdrawal from the reactor the ^{238}Pu content in a ^{240}Pu sample has increased by about 25% because of the α decay of ^{242}Am .

Calculational results will be given in the next section and compared to experimentally determined values.

36

V. COMPARISON OF CALCULATIONAL AND EXPERIMENTAL RESULTS

In this chapter we will finally turn to the actual calculational and experimental results. Out of the 12 samples which have been irradiated in the driver core, 10 were "completely analyzed," by which we mean that compositions of both the irradiated and unirradiated samples were measured. The two remaining samples were not measured because duplicate samples were available.

The calculations were performed using cross sections and fluxes as described above. However, in order to check the a priori validity of our EBR-II simplified model, some basic parameters related to this model were compared with measured ones. Agreement between these parameters will help to eliminate sources of uncertainties in case discrepancies between measured and calculated exposure products occur. We will therefore concentrate first on a comparison between measured and calculated EBR-II parameters; then we will discuss the results obtained for the irradiated samples.

A. COMPARISON BETWEEN CALCULATED AND MEASURED PARAMETERS OF EBR-II

We have shown above that the flux in the central part of the EBR-II model is essentially asymptotic and is insensitive to changes to the outer core environment. For this reason, calculated and measured data are expected to agree best for the innermost subzone of the driver core. The most obvious way to check this agreement is to compare calculated and experimental flux spectra; yet a measured flux spectrum unfortunately was not available. Instead we compared the calculated

174-group flux spectrum with a spectrum computed by ANL from a two-dimensional model which is believed to represent the reactor configuration more accurately than our 1-dimensional spherical model. The ANL calculations were carried out with the 2-D transport code DOT, utilizing a 22 group cross-section library based on an early ENDF/B file. In order to compare flux spectra, the 174-group spectrum was condensed into a 15-group spectrum with a group structure corresponding to that of the ANL spectrum. It was found, however, that 11 groups might be sufficient for the comparison of both spectra because for the low energy groups ($E < 0.68$ eV) the flux is negligible. Both spectra are given in Table 5.1 from which it can be seen that for most important groups the values agree to about 10%. Differences of this magnitude can be caused by the difference in cross sections used by ORNL and ANL. It is especially significant that the ENDF/B-V fission spectrum used by ORNL is considerably harder than the older spectrum used by ANL.

Table 5.1. ANL and ORNL 14-Group Flux Spectra for EBR-II

Group	Upper Energy(MeV)	ANL Flux Spectrum	ORNL Flux Spectrum	Relative Change(%)
1	10.000	0.074	0.111	50.0
2	2.231	0.087	0.095	9.2
3	1.353	0.120	0.132	10.0
4	8.209-1	0.341	0.328	-3.8
5	3.020-1	0.245	0.214	-12.7
6	1.111-1	0.098	0.086	-12.2
7	4.087-2	0.027	0.027	0.0
8	1.503-2	6.0-3	5.768-3	-3.9
9	5.531-3	7.0-4	5.257-4	-24.9
10	3.355-3	2.0-4	1.526-4	-23.7
11	2.035-3	4.0-4	3.104-4	-22.7

A further parameter which might be considered is the central capture-to-fission ratio, which is the ratio of the spectrum-averaged one-group capture cross section to the average fission cross section at the core center. Experimental as well as calculational values for various isotopes were reported in Ref. 4 and are compared with data obtained from Table 4.3. This is shown in Table 5.2, which shows a fairly good agreement between ratios calculated with the EBR model and those determined experimentally. Deviations between ORNL and ANL values are of the order of a few percent only, except for the ANL calculated value for ^{242}Pu , which seems to be unreasonable.

Table 5.2. Experimental vs. Calculated Capture-to-Fission Ratios for Various Isotopes

Nuclide	ANL			ORNL	
	Measured	Calculated	C/E	Calculated	/E
^{233}U	.073	.069	.945	.065	.890
^{235}U	.180	.161	.894	.169	.939
^{239}Pu	.085	.080	.941	.082	.965
^{240}Pu	.305	.277	.908	.264	.866
^{242}Pu	.469	.208	.443	.419*	.893

* From standard ORIGEN Library.

The results in Table 5.2 establish the expected agreement between experimental and calculated parameters of EBR-II at the core center and verify the adequacy of the spherical model. It might,

however, be also interesting to examine some space-dependent characteristic of the reactor in order to assess the validity of the computed space-dependent spectra. To that end we examined the spatial distributions of capture-to-fission ratios of various isotopes which have been irradiated in EBR-II.¹² This experiment took place in the early days of EBR-II (prior to the actinide samples experiment) when the core was fueled with MARK-I type subassemblies in seven rows only and had no reflector. Such a reactor setup may be represented by a spherical model better than any other configuration since there are only two compositions to be considered: the driver core and the depleted uranium blanket. In the experiments reported, many samples were placed at various distances from the vertical axis, in or next to the horizontal midplane of the core. Assuming azimuthal symmetry of the reactor, the radial direction in the horizontal midplane may be adequately represented by the only coordinate of the spherical model, so that a good agreement between calculation and model might be expected in spite of all limitations of the calculational model.

In Figure 4, calculational and experimental results for four isotopes irradiated at various locations are shown. The experimental data were taken from Ref. 12, whereas our calculational results are from a two-region spherical model of EBR-II with an inner core divided in 5 subzones. The calculated capture-to-fission ratios of each subzone shown in Figure 4 are volume averaged, but the overall agreement between experimental and calculational results is still

Fig. 4. Capture-to-Fission Ratio Distribution in Horizontal Midplane of EBR-II.

surprisingly good, even at locations deep in the blanket. We may therefore conclude that when correctly interpreted, simple models may give very acceptable results. However, since the actinide samples were arranged in a vertical direction, successful application of a simple spherical model for their analysis is not assured.

The overall conclusion of this section is that the simplified spherical model will produce acceptable results for samples irradiated near the horizontal midplane of the reactor, but for samples located near the axial blanket, calculational results are expected to be less accurate, due both to inaccuracies in the spectrum calculation and to uncertainties in determining an "equivalent" location for the shape factor.

B. CALCULATED AND MEASURED EXPOSURE PRODUCTS IN THE ACTINIDE SAMPLES

In this section, calculated and measured values for the exposure products in the actinide samples will be given. The calculations are based on the spherical three-zone model composed of a driver core surrounded by a reflector and a "blanket," both made of stainless steel. This model was chosen because it is believed to correspond best to the reactor composition in the vertical direction during the major part of the irradiation period. When the actinide samples were introduced into the reactor, MARK-IA type fuel subassemblies having stainless steel axial blankets were being used.

To start the calculation, the initial composition of the samples must be known. These were determined experimentally using control samples with compositions identical to those of the irradiated samples.

Most of these samples, however, have been analyzed at about the same time as the irradiated ones; therefore the actual composition at the initial time of irradiation must be calculated backwards for isotopes with relatively short half lives. Such a calculation was especially necessary for ^{241}Pu , which has a half life of 14.3 years.

The initial composition for the various samples, corrected to the initial time of irradiation, are given in Table 5.3. With the exception of the ^{239}Pu samples, the data in Table 5.3 results from measurements made at ORNL at about mid-1980. The relative abundance of the isotopes in the ^{239}Pu sample (#93) was measured by ANL in 1974 and is valid also for the two other ^{239}Pu samples (#92 and 94). Two samples are not indicated: the ^{232}Th sample of 32.81 mg and the ^{237}Np sample of 1.0 mg. These two samples are assumed to be nearly 100% pure.

Table 5.3. Initial Composition of Actinide Samples
Irradiated in EBR-II (in mg)

SAMPLE NUCLIDE	#81	#31 ^a	#53	#94 ^b	#02	#14
	^{238}U	^{233}U	^{235}U	^{239}Pu	^{240}Pu	^{241}Pu
^{233}U		9.859+1				
^{234}U	9.160-4	1.052	7.968-1			
^{235}U	4.120-2	1.929-2	8.218+1			
^{236}U	1.650-3	9.639-4	3.858-1			
^{238}U	9.154+1	4.125-1	4.825			
^{238}Pu					1.023-3	2.660-3
^{239}Pu				1.006+2	4.240-1	3.727-1
^{240}Pu				4.857	5.083+1	1.335
^{241}Pu				3.460-1	2.504-1	3.069+1
^{242}Pu				2.010-2	6.224-2	4.387-1

^aFor ^{233}U sample #32 multiply all values by 1.344.

^bFor ^{239}Pu sample #93 multiply all values by 1.295.

In Table 5.4 measured quantities of the exposure products in 10 samples are given. Four of these samples, namely ^{233}U (#32), ^{235}U (#53), ^{239}Pu (#93) and ^{241}Pu (#14), were measured by ANL; the other ones were measured at ORNL.

Now we turn to the calculated values. Using the initial compositions from Table 5.3 and appropriate cross sections and flux levels, the exposure products in each sample were calculated with the ORIGEN code. These calculations span a period of nearly 15 years, including the irradiation period as well as the out-of-core decay period. Calculations were performed for 7 samples only: each pair of the ^{233}U and ^{239}Pu samples required one calculation only since the samples of the same type had, up to a constant factor, the same initial composition. The slight differences in the flux factor may be accounted for accurately by a linear adjustment, although the burnup process is a strictly nonlinear function of the flux level. For the ^{237}Np sample, a hand calculation was sufficient to obtain values for the two measured nuclides of this sample. Calculated results for all samples are given in Table 5.5 .

With the results of Tables 5.4 and 5.5 one may compare the calculation against the experiment. One way to carry out such a comparison is simply to calculate the ratios of the calculated to the experimentally obtained quantities (C/E) of the end products. One, of course, desires these ratios to be as close as possible to 1.0, but even so, this might not necessarily indicate a good correlation between calculation and experiment. The reason for that lies in the fact that the

Table 5.4. Measured Exposure Products (in mg) of Actinide Samples Irradiated in EBR-II Core

NUCLIDE	Sample # and Major Nuclide									
	21 232Th	81 238U	31 233U	32 233U	53a 235U	93b 239Pu	94 239Pu	02 240Pu	14 241Pu	72 237Np
233U	5.720-1		8.012+1	1.100+2						
234U	5.200-3	9.000-4	2.112	2.835	7.058-1					
235U	9.900-4	3.070-2	6.300-2	6.800-2	7.171+1					
236U		9.000-4	8.300-4	7.938-3	2.133					
238U		9.027+1	4.500-1	5.300-1	4.695					
231Pa	5.500-3									9.000-1
237Np										5.600-2
238Pu							1.440-2	5.700-3	3.034-1	
239Pu		1.198				1.110+2	8.386+1	3.580-1	3.128-1	
240Pu		1.250-2				7.790	5.820	4.644+1	1.134	
241Pu		4.850-5				3.520-1	2.100-1	6.290-1	1.310+1	
242Pu		4.200-5				3.450-2	2.340-2	6.790-2	7.867-1	
241Am							1.290-1	4.700-1		

a 235U sample #51 was not analyzed.
b 239Pu sample #92 was not analyzed.

Table 5.5. Calculated Exposure Products of Actinide Samples Irradiated in EBR-II Core (in mg)

NUCLIDE	Sample # and Major Nuclide									
	21 232Th	81 238U	31 233U	32a 233U	53 235U	93b 239Pu	94 239Pu	02 240Pu	14 241Pu	72 237Np
233U	3.58-1		8.11+1	1.10+2						
234U	2.68-3	8.87-4	2.01	2.73	7.43-1					
235U	2.70-5	3.66-2	5.38-2	7.31-2	7.15+1					
236U		2.60-3	1.66-3	2.26-3	1.94					
238U		9.02+1	4.04-1	5.49-1	4.72					
231Pa	6.21-3									
237Np										9.33-1
238Pu							4.64-3	2.55-3	9.95-2	3.28-2
239Pu		9.80-1				1.14+2	8.54+1	3.68-1	2.96-1	
240Pu		8.99-3				7.65	5.73	4.71+1	1.24	
241Pu		6.07-5				.365	2.06-1	5.79-1	1.35+1	
242Pu						3.35-2	2.51-2	6.84-2	9.44-1	
241Am							1.78-1	3.94-1		

aAdjusted from sample 31 data.
bAdjusted from sample 94 data.

calculated end product of an isotope becomes insensitive to the input parameters if substantial amounts of this isotope were present initially. This statement is especially true for the major isotope in each sample, but may also be true for other nuclides initially present as impurities as well. In Table 5.6 we have listed the C/E ratios for the end products based on Tables 5.4 and 5.5. From this table it may be easily verified that there is a high correlation between nuclides with appreciable initial contents and the closeness of their C/E value to 1.0. For this reason it appears that we should check not only the C/E ratios for the end products, but also the ratios for the net change in each nuclide, namely the difference between its final and initial charge. This ratio will be a better measure for the quality of the burnup calculation, no matter what quantities were initially loaded in the reactor. The C/E ratios for these ratio quantities are listed in Table 5.7. This table actually provides the essence of the whole study and we shall devote the remainder of the section to analyze its implications.

There are two ways to analyze the results in Table 5.7. One is to examine each sample separately, the other is to examine individual nuclides, regardless of which sample they appear in. We shall start with the first approach, and then turn to the other method.

By examining the results for the individual samples we notice that for most samples the major isotope and its first daughter can be computed with an accuracy of 90% or better. Two exceptions are the ^{232}Th and ^{237}Np . These samples show disagreements of over 30% between

Table 5.6. C/E Ratios for the End Products of the Actinide Samples

NUCLIDE	Sample # and Major Nuclide									
	21 232Th	81 238U	31 233U	32 233U	53 235U	93 239Pu	94 239Pu	02 240Pu	14 241Pu	72 237Np
233U	0.626		1.012	1.000						
237U	0.515	0.986	0.952	0.963	1.053					
235U		1.192	0.854	1.075	0.996					
236U				0.285	0.910					
238U		0.999	0.898	1.030	1.005					
231Pa	1.129									
237Np										1.037
238Pu							0.322	0.447	0.328	0.590
239Pu		0.819				1.027	1.018	1.028	0.946	
240Pu		0.720				0.982	0.985	1.014	1.093	
241Pu		1.25				1.038	0.981	0.919	1.031	
242Pu						0.952	1.073	1.007	1.200	
241Am							1.380	0.838		

TABLE 5.7. C/E Ratios for Nuclide Rate of Changes

NUCLIDE	Sample # and Major Nuclide									
	21 232Th	81 238U	31 233U	32 233U	53 235U	93 239Pu	94 239Pu	02 240Pu	14 241Pu	72 237Np
233Pu	0.626		0.947	1.000	0.592					
234U	0.515	1.813	1.904	0.926	0.592					
235U		0.438	0.789	1.121	1.026					
236U				0.145	0.890					
238U		0.947	-0.227 ^a	0.221	-0.808					
231Pa	1.129									0.670
237Np										0.59
238Pu							0.322	0.327	0.322	
239Pu		0.818				1.031	0.908	0.849	1.280	
240Pu		0.720				0.907	0.907	0.845	0.473	
241Pu		1.225				1.341	1.029	0.868	0.977	
242Pu						0.882	1.515	1.088	1.452	
241Am							1.380	0.838		

^aNegative values mean that the calculated and measured changes have opposite directions:

measurements and calculation. The fact that these two samples were located most closely to the core outer boundary raises the suspicion that a common reason might be responsible for the disagreement, e.g., too low flux levels or too low cross sections or both. A too low flux level may result from an underestimation of the flux drop near the core boundary, whereas too low cross sections may arise from too hard a spectrum. Whatever the reasons might be, the unsatisfactory results for these two samples definitely demonstrate the need for a well-defined experimentation in order to enable accurate calculations.

Starting with the major isotope of a sample and going up the mass chain, we notice that the major isotope in each sample and its first successor usually were calculated with similar accuracies. This is no surprise since any error in calculating the burnup of the major isotope will be directly transferred to the buildup of its first successor. Proceeding up the chain, however, we notice increasing deviation of the C/E values from 1.0. This may be attributed to two effects. First, each error made in the calculation of a nuclide is transferred to all its progeny; thus a nuclide high up the chain suffers from an accumulation of all errors made to its precursors. The second reason is that the further up the chain, the less are the absolute amounts of the individual nuclides, so that in many cases the measured quantities of these nuclides become less accurate.

Many samples have also small amounts of impurity isotopes down the mass chain from the major isotope. Their contributions to the final products of interest is in most cases negligible, and we need not worry about their accuracy.

The order in which the samples appear in Table 5.7 corresponds more or less to their axial arrangement in the reactor. This was done to emphasize the effect of the sample locations on the accuracy with which the exposure products may be computed. It is easily seen that the worst results are obtained for the two outermost samples, the thorium and neptunium, as already discussed above. Moving one location towards the center, we arrive at the ^{238}U and the ^{241}Pu samples at the top and bottom, respectively. Here, the accuracy is significantly higher, but still not quite satisfactory. As a matter of fact we would like very much to be able to calculate the buildup of ^{239}Pu from (n,γ) -capture in ^{238}U within 5%, which is about the current accuracy requirements for the breeding ratio calculation in SUPER-PHENIX,¹³ since this reaction has an important impact on fast breeder physics and economics. Unfortunately, the ^{238}U sample was placed at a location where the reaction rate is very sensitive to the reactor configuration, so that only moderate accuracy may be expected for this sample when our simple reactor model is used. This is also the reason for the low accuracy obtained for other peripheral samples.

Arriving at the central samples, we notice a great improvement in the C/E values. As a rule for samples irradiated at locations near the core center, agreement within 10% is obtained for the major isotopes and for their first daughter, and within 20% for the next nuclide up the chain. Results for nuclides higher up the chain are less predictable.

Now we shall look at Table 5.7 horizontally, examining individual nuclides, while varying the samples in which they occur. Starting with ^{238}U , we notice that the only case where this isotope was satisfactorily measured was for the ^{238}U sample itself. One should, however, keep in mind that ^{238}U is present in all U samples because total elimination of this

isotope is practically impossible. Small amounts of ^{238}U are usually also present in the measuring devices, which probably accounts for the observed discrepancies for this nuclide.

Difficulties in measuring ^{238}Pu may also be one reason for the surprisingly low accuracy obtained for the ^{238}Pu in three Pu samples: the measured values are always much higher than the computed values. Another reason seems to be the limited accuracy to which the ^{238}Pu precursors can be computed. Recall that ^{238}Pu may be produced by two different channels: either by (n,2n) reaction on ^{239}Pu or by α decay of ^{242}Cm . The ^{238}Pu produced in the ^{239}Pu sample comes mainly from the first reaction, whereas the second channel is responsible for the buildup of ^{238}Pu in the ^{241}Pu and in the ^{240}Pu sample. The data uncertainties for $^{241}\text{Pu}(\beta)$, $^{241}\text{Am}(n,\gamma)$, $^{242}\text{Am}(\beta)$, and $^{242}\text{Cm}(\alpha)$ are large and might therefore be the primary reason for the poor ^{238}Pu results.

Examination of the other Pu nuclides reveals fair accuracy in most cases. It should be noted also that many calculated values are correlated -- an error in the calculation for one isotope affects other isotopes as well. We shall return to this point in the next chapter.

Finally, we note that the results for ^{241}Am are fairly good, considering the fact that Am is located relatively high up the depletion chain. This result is actually a consequence of the fact that ^{241}Am is a direct decay product of ^{241}Pu , which implies that the ^{241}Am concentration depends mainly on the accuracy to which the ^{241}Pu concentration is known.

Summarizing this section, we have found reasonable agreement between calculation and experiment for most samples located near the core center.

As the samples approach the axial blanket, problems start to appear due to a breakdown in the accuracy of the spherical reactor model. Other C/E discrepancies (e.g., for ^{238}Pu) are probably related to errors in the experimental measurements, especially for those nuclides whose concentrations are very small.

54

VI. SENSITIVITY ANALYSIS OF INPUT PARAMETERS AND THEIR IMPACT ON CALCULATED RESPONSES

A. GENERAL REMARKS

Table 5.7 of the previous chapter reveals some discrepancies between experiments and calculations which are intolerably large. For example, the discrepancy between the calculated and measured amounts of ^{239}Pu in the ^{238}U sample and the ^{238}Pu amount in all Pu samples indicates that some problem exists in these analyses, possibly arising from input data. The difficulty is determining what data in the complex chain of calculations and experiments contributes most to the discrepancies between the measured and calculated results. To answer this question, sensitivity theory seems to be most appropriate.

A full sensitivity analysis of the experiments described in the previous chapters is far beyond the scope of this chapter. We shall limit the following discussion to a few selected questions only, which we find to be of general importance. Also, we seek conclusions which might be helpful in subsequent experiments, e.g., the irradiation of actinide samples in the UK Prototype Fast Reactor (PFR).

Sensitivity analyses seek to answer the following question: How much will the "response" of a system be changed if a certain input parameter is changed by an arbitrary (small) quantity? The information from sensitivity calculations can therefore be used to ascertain the input parameters which have the largest impact on the calculated results. This is useful in judging whether the uncertainties in the input parameters are large enough to account for the differences between measurements and calculations, or whether the differences can be only attributed to uncertainties in the experimental measurements. In the following, examples for both possibilities will be given.

The input parameters for the calculations may be categorized into three classes, according to their overall impact on the system responses, which correspond here to the exposure products. These three are:

a) initial charges and impurities, b) flux levels, and c) flux-weighted cross sections and decay constants. In the following sections these three types of parameters will be discussed, but first we shall recall the most important aspects of sensitivity analysis for depletion calculations.

The time-dependent equation for the exposure products in a sample irradiated at position $\underline{X}_0$ is given in Chapter IV.C and will be repeated for convenience:

$$\frac{dN(\underline{X}_0, t)}{dt} = \left[\phi \left(\max \right) \underline{M} \left(\sigma(\underline{X}_0) \right) \psi(\underline{X}_0) \theta(t) + \underline{\lambda} \right] N(\underline{X}_0, t), \quad (5)$$

with the initial conditions

$$N(\underline{X}_0, t_0) = \underline{N}_0. \quad (6)$$

Equations (5) and (6) may be written in a compact form, as follows:

$$\frac{dN}{dt} = \underline{B}(t)N(t) + \underline{N}_0\delta(t-t_0). \quad (7)$$

We consider now the final concentration of a selected nuclide in a sample at $\underline{X}_0$ as our "system response," designated by R , where

$$R = N(\underline{X}_0, t_f), \quad (8)$$

and ask for the change ΔR in this response due to a given (small) perturbation in one of the system input parameters appearing in $\underline{B}$ or $\underline{N}_0$ of (7).

To answer this question we define the adjoint equation to (7) as:

$$\frac{d\underline{N}^+}{dt} = -\underline{B}^+(t)\underline{N}^+(t) + \underline{S}^+\delta(t-t_f), \quad (9)$$

where

$$\underline{B}^+ = \underline{B}^T.$$

In our special case the adjoint source $\underline{S}^+$ (which is equivalent to a final condition) is given by:

$$S_j^+ = \begin{cases} 1 & j = i \\ 0 & j \neq i \end{cases}, \quad (10)$$

i being the index of the response nuclide of interest. The change in the reactor response due to a variation $\Delta \underline{B}$ of $\underline{B}$ may now be given, accurate to first order, by

$$\Delta R_B = \int_{t_0}^{t_f} dt \underline{N}^+(t) \Delta \underline{B} \underline{N}(t) \quad (11)$$

and the change due to a variation in the initial condition is given exactly by

$$\Delta R_I = \int_{t_0}^{t_f} dt \underline{N}^+(t) \Delta \underline{N}_0 \delta(t-t_0), \quad (12)$$

which, because of the δ function at t_0 , reduces to

$$\Delta R_I = \underline{N}^+(t_0) \Delta \underline{N}_0. \quad (13)$$

Each of the expressions in (11) and (13) assume that changes in data characterizing the samples have negligible effect on the flux seen by the sample, due to the small sample size. The discussion in the following sections is based on the expressions in (11) and (13).

B. SENSITIVITIES TO INITIAL CONCENTRATION AND IMPURITIES

Using Eq. (13) we define a relative sensitivity coefficient for the final amount of nuclide i to the initial amount of nuclide j in a sample as follows:

$$S_{i,j} = \frac{\Delta R_i / R_i}{\Delta N_{j,0} / N_{j,0}} = \frac{N_{j,0}}{R_i} \frac{N_i^+(t_0) \Delta N_{j,0}}{\Delta N_{j,0}} = \frac{N_{j,0}}{R_i} N_j^+(t_0) . \quad (14)$$

This coefficient expresses the percentage change of the final amount of nuclide i , when the initial amount of nuclide j is increased by 1%.

The definition of the relative sensitivity coefficient for initial concentration is a priori restricted to nuclides which are known to exist in the initial charge. However, it may happen that some unknown impurities are also included in the sample, and they too may impact the final concentrations of the nuclides. In that case, a "relative change" becomes meaningless and we must revert to the original Eq. (13), which is an exact expression for the change in the response due to a change in the vector of initial concentrations.

In Table 6.1 sensitivities to initial concentrations are given for several nuclides in selected samples. The response nuclides listed were chosen because they have unsatisfactory C/E values for their burnup during irradiation. Also listed are the initial weights of the contributing nuclides. The conclusion from this table is that the major isotope of a

sample is not necessarily the major contributor to the final quantity of interest. For instance, the production of ^{241}Am in the ^{239}Pu sample is mainly due to the presence of ^{241}Pu in the initial sample, although this isotope comprises only about 0.3% of the total initial weight. A similar situation, although not as extreme, may be found for the production of ^{235}U in the ^{233}U sample, where ^{234}U (about 1% of the initial weight) contributes 44% of the final ^{235}U quantity. For ^{238}Pu production the situation is more involved because this isotope may be produced either by (n,2n) reactions in ^{239}Pu or by α decay of ^{242}Cm . The production from the former route is usually limited because of the small (n,2n) cross sections; therefore, the presence of any isotope which leads to the formation of ^{242}Cm may appreciably affect the ^{238}Pu production. For this reason, only 68% of the ^{238}Pu produced in the ^{239}Pu sample is attributed to the major isotope; the rest is due to the 0.3% of ^{241}Pu in the initial charge. The fraction of the ^{238}Pu production due to ^{241}Pu is even higher in the ^{240}Pu sample, where 25% of the final ^{238}Pu quantity originates from the initial impurity of 0.5% ^{241}Pu .

To conclude this section it should be emphasized that an accurate determination of the initial composition of all the nuclides in an irradiated sample is a primary condition for a successful evaluation of the experiment by calculational models. However, although final amounts are usually very sensitive to the initial compositions of the samples, it seems unlikely that the discrepancies between calculations and measurements may be attributed entirely to inaccurate measurements. Unfortunately, the uncertainty of the measurements could not be verified,

Table 6.1: Sensitivity Coefficients for Several Initial Nuclides

Sample	Initial Nuclide		Response Type	Nuclide C/E	Sensitivity Coeff.
	Type	Weight(mg)			
$^{238}\text{U}(\#81)$	^{238}U	9.129+1	^{239}Pu	.818	.996
	^{233}U	1.325+2	^{235}U	1.121	.246
$^{233}\text{U}(\#32)$	^{234}U	1.413	^{235}U	1.121	.442
	^{235}U	2.553-2	^{235}U	1.121	.309
	^{239}Pu	1.006+2	^{238}Pu	0.322	.679
$^{239}\text{Pu}(\#94)$	^{241}Pu	3.461-1	^{238}Pu	0.322	.287
	^{239}Pu	1.006+2	^{241}Am	1.380	.025
	^{240}Pu	4.857	^{241}Am	1.380	.190
	^{241}Pu	3.461-1	^{241}Am	1.380	.770
	^{238}Pu	2.660-3	^{238}Pu	0.327	.250
$^{240}\text{Pu}(\#02)$	^{240}Pu	5.083+1	^{238}Pu	0.327	.490
	^{241}Pu	2.504-1	^{238}Pu	0.327	.255
	^{240}Pu	5.083+1	^{241}Am	0.838	.725
	^{241}Pu	2.504-1	^{241}Am	0.838	.280
$^{241}\text{Pu}(\#14)$	^{241}Pu	3.069+1	^{238}Pu	0.322	.987

but it is believed not to exceed 5%, which is not large enough to account for the observed discrepancies. This statement, however, does not exclude the possibility of existing impurities which were not measured. Such impurities might significantly contribute to the production rate of some nuclides of interest, or may unexpectedly appear in the irradiated sample as "exposure" products. Experimentalists should therefore always be aware of the eventual high importance of small impurities which, in case they cannot be eliminated, should at least be accurately characterized.

C. SENSITIVITIES TO CROSS SECTIONS AND FLUX LEVELS

In the previous section we eliminated the possibility that inaccurate measurements of the initial composition of the samples could entirely account for discrepancies between measurements and calculations. Therefore, we will examine now the impact of uncertainties of the other parameters, namely, the cross sections and flux levels on the computed results. Of particular interest are any systematic errors which can be eliminated by adjusting various input data. In order to make this point clear, let us extract from the burnup matrix in Eq. (5) that part which is related to neutronic reactions only, by defining:

$$\underline{B}_N = \phi(\max) \underline{M}(\sigma(\underline{X}_0)) \psi(\underline{X}_0) \theta(t) . \quad (15)$$

Recalling the meaning of the four terms on the right-hand side of Eq. (15), we observe that the uncertainty in $\underline{B}_N$ is mainly due to insufficient knowledge of the proper cross sections which enter the matrix $\underline{M}$ and to

the appropriate flux level at $\underline{X}_0, \phi(\max)\psi(\underline{X}_0)$, since the time dependence of the flux normalization is thought to be accurately known. Performing the total differential of the final amounts, we may write:

$$\Delta N_i(t_f) = \frac{\partial N_i}{\partial \sigma_{\underline{j}}} \Delta \sigma_{\underline{j}} + \frac{\partial N_i}{\partial \phi} \Delta \phi, \quad (16)$$

where ϕ is a short notation for $\phi(\max)\psi(\underline{X}_0)$. Equation (16) is a formal expression only which might be replaced by a perturbation expression of the form (11), using the definition in (15):

$$\frac{\partial N_i}{\partial \sigma_{\underline{j}}} \Delta \sigma_{\underline{j}} = \phi \int_{t_0}^{t_f} \underline{N}^+(t) \Delta \sigma_{\underline{j}} \chi(t) \underline{N}(t) dt \quad (17a)$$

and

$$\frac{\partial N_i}{\partial \phi} \Delta \phi = \Delta \phi \int_{t_0}^{t_f} \underline{N}^+(t) \sigma_{\underline{j}} \chi(t) \underline{N}(t) dt. \quad (17b)$$

Combining both parts of (17) we obtain:

$$\Delta N_i(t_f) = \int_{t_0}^{t_f} \underline{N}^+(t) [\phi \Delta \sigma_{\underline{j}} + \Delta \phi \sigma_{\underline{j}}] \underline{N}(t) dt. \quad (18)$$

This is the basic perturbation expression for examining the effects of uncertainties in input parameters. Our approach will be based on the assumption that systematic discrepancies between measurements and calculations arise from possible errors in one of these parameters.

The most common way to use Eq. (18) is to insert in its right-hand side the uncertainty values for the cross sections and the flux in order to obtain the variation of the response $N_i(t_f)$. Such a procedure might enable us to decide whether the uncertainties to the input parameters are sufficient to account for the discrepancies between measurements and calculations, but it would be effective only for a single response. This is the so-called "forward sensitivity problem." In our case, however, the number of responses is large, since each nuclide in each sample acts as a response, so that a given set of uncertainties has to account for all discrepancies associated with that set. This is especially important for the flux uncertainty because if we allow a variation in $\phi(\max)$, the final nuclide concentrations in all samples are expected to vary. Even if we assume a change in the flux level only at a certain location X_0 (changing the flux distribution locally), all nuclides in the sample at that location will obtain different final values, which may not necessarily be closer to the measured ones. For that reason we have chosen another approach known as the "inverse sensitivity problem," which will be described next. In this approach we focus first on the nuclides within a single sample and then we shall try to apply our findings to other samples. The sample chosen was ^{239}Pu #94 which was located nearest to the core center and therefore is expected to yield the best results. However, as may be seen from Table 5.7, discrepancies of 10-15% were found for the three first nuclides up the chain, even in this sample. We shall now try to analyze the source for these discrepancies.

In the ^{239}Pu sample analysis we concentrate on three nuclides only, assuming the discrepancies for the rest are beyond the uncertainty limits of the input parameters. These nuclides are ^{239}Pu , ^{240}Pu and ^{241}Pu , for which three equations of the form (18) may be written. In this equation we consider $\Delta\text{Ni}(t_f)$ to be known quantities; namely, the differences between measured and calculated values, whereas the flux and cross-section variations are thought of as "variables." If there were only three unknown parameters, we could uniquely solve those three equations for the three unknowns, obtaining values for the changes to the input parameters which are required in order to exactly match the measured and calculated responses. Such a case, however, does not permit any degree of freedom for treating data uncertainties. In reality there are more than three parameters involved in this chain, thus allowing a high degree of freedom in choosing appropriate changes to the input parameters. In order to determine these changes we have used an optimization technique¹⁴ based on minimization of an appropriate quadratic loss function obtained from a Bayesian inference approach. This method takes into account the uncertainties of each individual parameter and measurement. The result of this adjustment procedure is given in the following table as "best" estimates for the cross sections and flux amplitude for the ^{239}Pu sample. The nominal values which appear in Table 6.2 are those which were originally used to calculate the final products in the ^{239}Pu sample. The uncertainty of the flux was intentionally chosen to be large in order not to constrain the results too much in advance. The remaining uncertainties were taken from Ref. 15. These, however, are uncertainties in the basic nuclear data used to obtain the one-group cross sections (ENDF/B-V) and do not

Table 6.2 Modification of Cross Sections and Flux Level
for ^{239}Pu Sample #94

Parameter	Nominal Values	Uncertainty (%)	Best Estimate	% Change
ϕ	1.000	15.0	1.069	8.9
σ_c^9 ^a	.149	7.0	0.157	5.4
σ_f^9	1.671	5.0	1.688	1.0
σ_c^0	.208	10.0	.170	-18.3
σ_f^0	.713	5.0	.708	- .07
σ_a^1	1.974	4.0	.201	1.8

^aThe indices 9, 0, and 1 pertain to ^{239}Pu , ^{240}Pu and ^{241}Pu , respectively.

include a component arising from uncertainties in the flux spectra. Hence, the values in Table 6.2 are actually lower bounds of the uncertainties. From Table 6.2 we see that with the exception of one parameter, all changes are within the specified uncertainty limits. The only exception is for the capture cross section of ^{240}Pu , but even here the change is within two standard deviations, which is still acceptable. It should also be noted that ^{240}Pu capture cross sections from ENDF/B-V are 10% higher than those from ENDF/B-IV (Table 4.8), which is larger than the other deviations. The most interesting result from Table 6.2, however, is that the best estimate for the flux is about 9% higher than the nominal value. In fact, the flux level for each sample was never determined experimentally

so that the nominal flux values should indeed have high uncertainties. This is also in accordance with previously detected discrepancies between power levels of EBR-II measured by different methods.¹⁶ In Ref. 16 it was pointed out that the power level (which is proportional to the flux level) at which EBR-II was operated might be as much as $9 \pm 2\%$ lower than a nominal value of 62.5 MW. This nominal power level is by more than 25% higher than power levels used in the present study, which are mainly based on data from Ref. 5. Therefore, it seems very reasonable to raise the flux level in our calculation by nearly 9%.

In order to verify the usefulness of the suggested adjustments to the flux level and cross sections, we applied the new values to two other samples. The first was the ^{240}Pu sample (#02) which uses the same cross sections as the ^{239}Pu sample, and the second was the ^{238}U sample (#81) which uses different cross sections, based on the softer spectra near the core boundary. For the first sample we used the adjusted cross sections and flux level, and for the second sample the cross sections and flux level were both changed by the percentage changes given in Table 6.2. Results for these two samples compared with the original results are given in Table 6.3. This table shows improved results for most of the nuclides, with the exception of ^{238}U and ^{241}Pu . The increased disagreement for ^{238}U is caused by the increase in the flux only, since no changes were made to the uranium cross section (only Pu cross sections were modified); however, there is still an uncertainty in the ^{238}U absorption cross section which could account for the discrepancy. Also recall that a contamination problem is thought to exist for the ^{238}U measurements. The increased

Table 6.3 Comparison Between C/E Values Obtained
from Nominal and Adjusted Data

Nuclide	^{240}Pu (#81)		^{238}U (#02)	
	Nominal	Best Estimate	Nominal	Best Estimate
^{238}U	-	-	1.282 ^a	1.588 ^b
^{238}Pu	.322	.333	-	-
^{239}Pu	.849	.939	.818	.885
^{240}Pu	.850	.872	.720	.888
^{241}Pu	.881	.739	1.225	1.349
^{242}Pu	1.088	1.035	-	-

^a ± 0.3 ; ^b ± 0.37 .

disagreement for ^{241}Pu in the ^{240}Pu sample is, of course, due to the significant decrease of the ^{240}Pu capture cross section, which shows that the required change in this cross section was probably overestimated by the optimization program.

It was not intended in this section to develop a completely consistent set of adjusted cross sections in order to re-evaluate the calculated exposure products; it was merely meant to reveal systematic discrepancies. As a result of the study we feel that there is a strong incentive to increase the assumed flux level by nearly 10%. The results for other samples that have not been mentioned in this section also show that better C/E values may be obtained for the major nuclide and its first processor by merely increasing the flux level by 5-10%, whereas further cross-section adjustments may probably be required in order to reduce the C/E deviations

of other nuclides from 1.0.

The cross-section uncertainties given in Table 6.2 arise only from basic data uncertainties. Other uncertainties arise from the flux-weighting spectrum used in collapsing the data, especially near the core-blanket interface since the change in blanket composition was not accounted for in the calculations. To estimate this effect, one-group cross sections from Tables 4.3 and 4.4, which were derived from flux calculations using two different EBR-II models, are compared in Table 6.4. These models assumed a depleted uranium blanket and a stainless steel blanket, respectively, and the cross sections that are compared are taken from regions near the core boundary where their sensitivities to blanket composition are at a maximum. The cross sections of the first column are regarded as reference cross sections in order to define the relative changes between the different data. The changes in the collapsed data can be viewed as an upper bound to the uncertainty arising from the flux spectrum, since the two limiting cases have been considered at the location of maximum sensitivity. In the sense that this table bounds the uncertainties in one-group data, practically all cross sections have "uncertainties" which are high enough to account for most discrepancies between the measured and calculated values. It should, however, be noted that these estimated uncertainties are probably unrealistically high and also are correlated since each cross-section set in Table 6.2 was derived from a common model; i.e., if it is assumed that a certain cross section should be changed due to spectra adjustments, the whole set of cross sections should be changed simultaneously.

**Table 6.4 The Range of Variation of One-Group Capture Cross
Sections Due to Different Weighting Spectra**

Nuclide	Table 4.3 Region 3	Table 4.4 Region 3	Relative Change (%)	Table 4.4 Region 3'	Relative Change (%)
^{233}U	.1570	.1763	12.3	.2264	44.2
^{234}U	.3286	.4366	32.9	.6887	109.6
^{235}U	.2716	.2938	8.2	.3676	35.3
^{238}U	.1501	.1569	4.5	.1843	22.8
^{239}Pu	.1895	.2426	28.0	.3831	102.2
^{240}Pu	.2505	.4453	77.8	1.0107	303.5
^{241}Pu	.2291	.2718	18.6	.3791	65.5

We have not considered here the uncertainties of the fission cross sections. The sensitivity of the results to these data are usually a factor of 2 lower than for the capture cross sections. They significantly affect only the disappearance of the major nuclides, while their importance for the transformation process is, in general, negligible.

10

VII. SUMMARY AND CONCLUSIONS

This report presents a comparison of experimental versus calculated results for the burnup of actinide samples irradiated in EBR II during 1967-1970. The experimental analysis consisted of mass spectrometer and alpha counting measurements to determine the exposure products in the irradiated samples. The calculational analysis employed a spherical model of the EBR configuration to obtain space-dependent flux spectra for multi-group averaging of the latest ENDF/B-V data. The spatial shape of the flux distribution was obtained from earlier ANL reports. Burnup calculations were performed for each sample with the ORIGEN code.

Table 7.1 presents an overall summary of our results. In many cases the agreement between the measured and calculated postirradiation composition of the samples is quite satisfactory. The differences between the measured and calculated values can be attributed to at least three different possibilities: (a) the values taken for the cross sections, (b) the assessment of the total neutron flux and its energy composition, and (c) characterization of the initial isotopic composition of the samples, especially those nuclides with low abundance.

These several possibilities are illustrated by the results for ^{238}Pu observed in the irradiated ^{239}Pu (#94) sample. The observed amount of ^{238}Pu is almost 3 times larger than the calculated amount. One possibility for this difference is that the amount of ^{238}Pu in the original sample is not known (we assumed it was zero). Secondly, the

Table 7.1 Summary of Experimental and Calculated Isotopic Composition of Irradiated Actinide Samples

Sample	Nuclide	Experimental Initial Weight (mg)	Experimental Final Weight (mg)	Calculated Final Weight (mg)
Th232 (#21)	Th232	32.81		
	U233		0.57	0.36
	U234		0.005	0.003
	U235		0.001	<0.0001
	Pa231		0.005	0.006
U235 (#81)	U234	0.0009	0.0009	0.0009
	U235	0.041	0.031	0.037
	U236	0.0017	0.0009	0.0026
	U238	91.54	90.27	90.2
	Pu239		1.20	0.98
	Pu240		0.013	0.009
	Pu241		0.00055	0.00006
	Pu242		0.00004	
U233 (#31)	U233	92.6	80.1	81.1
	U234	1.05	2.11	2.01
	U235	0.019	0.063	0.054
	U236	<0.001	0.001	0.002
	U238	0.41	0.45	0.40
U235 (#53)	U234	0.80	0.71	0.74
	U235	82.2	71.7	71.5
	U236	0.39	2.13	1.94
	U238	4.83	4.70	4.72
Pu239 (#93)	Pu239	130.3	111.0	114.0
	Pu240	6.29	7.79	7.65
	Pu241	0.45	0.35	0.37
	Pu242	0.026	0.034	0.034
Pu239 (#94)	Pu238		0.014	0.005
	Pu239	100.6	83.9	85.4
	Pu240	4.86	5.82	5.73
	Pu241	0.35	0.21	0.21
	Pu242	0.020	0.023	0.025
	Am241		0.13	0.18
U233 (#32)	U233	132.5	110.0	110.0
	U234	1.41	2.84	2.73
	U235	0.026	0.068	0.073
	U236	<0.001	0.002	0.002
	U238	0.55	0.53	0.55
Pu240 (#14)	Pu238	0.001	0.006	0.003
	Pu239	0.42	0.36	0.37
	Pu240	50.8	46.4	47.1
	Pu241	0.25	0.63	0.58
	Pu242	0.062	0.068	0.068
	Am241		0.47	0.39
Pu241 (#02)	Pu238	0.003	0.30	0.10
	Pu239	0.37	0.31	0.30
	Pu240	1.34	1.13	1.24
	Pu241	30.7	13.1	13.5
	Pu242	0.44	0.79	0.94
Np237 (#72)	Np237	1.00	0.90	0.93
	Pu238		0.06	0.03

important process for the production of ^{238}Pu in the ^{239}Pu sample is the (n,2n) process. This process depends on the flux of high energy neutrons. As illustrated in Table 5.1, the relative amount of flux in the region above 2 MeV differs by 50 percent in the ANL and ORNL flux spectra. The ANL flux spectra would have predicted even less ^{238}Pu . In this particular case of ^{238}Pu production in the ^{239}Pu sample, we strongly suspect that the observed difference is caused by assuming cross-section values for the ^{239}Pu (n,2n) process which are too small. This cross section has not been measured; it was drawn in from general systematics.

It was found that the spherical reactor model gave reasonable results near the core center but was inadequate near the blanket regions. It is estimated that an uncertainty of around 20% should be assigned to the calculated results due to a combination of methods and data uncertainties. Sensitivity analysis indicates that small amounts of impurities in the samples can strongly influence the measured results for those materials which are produced in minute quantities, and therefore the initial sample composition is another source of uncertainty.

It is disappointing that this large an uncertainty must be assigned to the results, but this fact illustrates the importance of having a well planned and documented experimental program in which pre-analysis calculations play an important role. The present EBR-II experiment was somewhat lacking in this regard because the original

experiment was designed by ANL for other purposes, and it was then difficult for ORNL to resurrect all the necessary information after ten years had elapsed.

A comparison was made of the 1-group effective EBR cross sections based ENDF/B-IV and V data. Averaged over the hard EBR-II spectrum at the core center, the cross sections for ^{235}U fission, ^{238}U capture, and ^{239}Pu changed by -0.9, 2.3, and -0.77%, respectively, going from ENDF/B-IV to V.

The buildup of most transmutation products in the Pu samples was computed to within 15% using ENDF/B-V data. The production of ^{239}Pu in the ^{238}U sample was underestimated by 20%, possibly due to the close proximity of this sample to the axial blanket where the flux spectrum was poorly represented. A simple least-squares adjustment of the input data to the burnup calculation was performed on the ^{239}Pu sample to reduce the C/E values. A systematic adjustment of 5-10% in the EBR flux normalization was indicated, which could imply that earlier EBR measurements underestimated the power level. Unfortunately, no reliable information could be obtained on the buildup of americium and curium due to large experimental uncertainties in measuring the small quantities of these materials. The future PFR experiment should provide much better data on the higher actinide cross sections.

As noted in Section I, a primary goal of the present study was to gain experience for a future irradiation study to be performed in the United Kingdom's PFR. Several important lessons have been learned from problems encountered in the EBR-II analysis, which are to be corrected for the PFR program. These are the following:

(a) Results are sensitive to small amounts of impurities in the initial actinide specimens. The PFR samples should be made as pure as possible, and any isotopic impurities should be accurately characterized using mass spectrometry.

(b) Heavy metal impurities in the Ni capsule material influenced the mass spectrometer measurements. A capsule made of a material such as high purity vanadium should be used in the PFR experiment.

(c) Experiment analysis must be done in a very clean environment to avoid contamination from other experiments. It is recommended that new glove boxes be used for PFR analysis.

(d) The effect of capsule perturbation on the flux should be examined and corrected for.

(e) The effect of thermal reactions on the sample burnup should be identified and corrected for.

(f) Accurate documentation of reactor operating history and power level is imperative; a reasonable estimate for the uncertainty in the absolute reactor power level (flux normalization) should be obtained.

(g) The axial and radial flux shapes should be obtained with 3-D diffusion theory; any time dependence in the relative shapes and spectra should be identified.

(h) Dosimeters should be strategically placed to aid in determining flux spectra and shape. It is recommended that a least squares adjustment be done on the 3-D diffusion theory calculations to minimize differences between measured and computed dosimeter values. The

resulting flux spectra, axial and radial shape factors, and normalization should then be used as in the present EBR-II analysis.

(i) Time-dependent sensitivity analysis was shown in the present study to be a useful tool for understanding discrepancies. It is recommended that a similar type of analysis be performed for the PFR experiment.

VIII. REFERENCES

1. J. T. Madell, R. E. Jarka, "Analysis of Experimental Sub-assemblies in EBR-II," Argonne National Laboratory, ANL-7410 (1969).
2. R. J. Meyer, R. P. Larsen, "Experiment Description and Hazards Evaluation for ANL-MET-CEN Irradiation Capsule for EBR-II Subassembly X018," Argonne National Laboratory, ANL-RCV-4084, (1966).
3. H. A. Larson, P. Walker, D. Meneghetti, "EBR-II Burnup and Fluence History I," Part 2, Argonne National Laboratory, ANL/ECRO-085 (1974).
4. D. Meneghetti, R. H. Rempert, "Calculational Analysis of Tests of EBR-II Capture-to-Fission Ratios," Argonne National Laboratory, ANL-7942 (1972).
5. J. C. Case, "Core Loading Diagram for EBR-II Runs 4 Through 38, April 1965-Mid-December 1969," Argonne National Laboratory, ANL/EBR-7 (1969).
6. D. H. Smith, ed., "Mass Spectrometry in the Analytical Chemistry Division of ORNL," ORNL/TM-6485.
7. R. L. Walker, R. E. Eby, C. A. Pritchard, J. A. Carter, "Simultaneous Plutonium and Uranium Isotope Analysis from a Single Resin Bed - A Simplified Chemical Technique for Assaying Spent Reactor Fuels," Analytical Letters (8 & 9), 563-574 (1974).
8. D. A. Kucera, J. T. Madell, "Analysis and Development of Neutron Cross Sections for EBR-II Studies," Argonne National Laboratory, ANL-7410 (1969).
9. N. M. Greene, W. E. Ford, III, J. L. Lucius, J. E. White, L. M. Petrie, R. Q. Wright, "AMPX: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Libraries from ENDF/B," ORNL/TM-3706, also PSR-63.
10. M. J. Bell, "ORIGEN-The ORNL Isotope Generation and Depletion Code," ORNL-6428. (1973).
11. D. Meneghetti, E. R. Ebersole, P. Walker, "Analysis of Burnups in EBR-II Driver Fuel Elements," Nuclear Technology, Vol. 25, (Feb. 1975).

12. R. R. Heinrich, J. Williams, A. A. Madson, N. D. Dudley, "Integral Measurements in EBR-II of Capture Rates, Fission Rates and Alpha for ^{233}U , ^{235}U , ^{238}U , ^{239}Pu , ^{240}Pu , and ^{242}Pu ," Argonne National Laboratory, ANL-7791 (1971).
13. P. Hammer, in "Proceedings of the Conference: 1980 Advances in Reactor Physics and Shielding," p. 450 ff., Sun Valley, Idaho, September 14-29, 1980.
14. J. Barhen, J. J. Wagschal, "NOGA, A Nonlinear Optimization and Generalized Adjustments Code for Uncertainty Analysis of Transient Systems," ORNL/TM-7544 (1981).
15. M. L. Williams, "Perturbation and Sensitivity Theory for Reactor Burnup Analysis," ORNL/TM 7096 (1979).
16. G. H. Golden et al., "Correlation and Interpretation of Data Relative to EBR-II Power Level" in Proc. Am. Nucl. Soc. Topical Meeting on Irradiation Experimentation in Fast Reactors, Jackson Lake Lodge, WY (Ept. 1974).

APPENDIX A

IRRADIATION HISTORY OF THE ACTINIDE SAMPLES IN EBR-II

<u>Run No.</u>	<u>Date Started</u>	<u>Date Ended</u>	<u>Oper. Days</u>	<u>Total Energy Output (MWd)</u>	<u>Avg. Power (MW)</u>	<u>Samples Location</u>	<u>Shut-down Period (Days)</u>
24	12/6/66	12/31/66	25	630	25.20	Row 2	107
25A	4/17/67	6/19/67	63	641	10.17	" 2	2
25B	6/21/67	6/27/67	6	150	25.00	" 2	2
25C	6/29/67	7/20/67	21	723	34.43	" 2	1
25D	7/21/67	7/22/67	1	34	34.00	Out	1
25E	7/23/67	8/18/67	26	13	0.50	Row 2	35
26A	9/22/67	9/29/67	7	87	12.43	" 2	12
26B	10/11/67	11/20/67	40	1029	25.73	" 2	2
26C	11/22/67	12/12/67	21	619	29.48	" 2	52
27A	2/2/68	2/29/68	27	283	10.48	" 2	3
27B	3/1/68	3/5/68	4	177	44.25	" 2	2
27C	3/7/68	3/11/68	4	62	15.50	" 2	19
27D	3/30/68	4/5/68	7	286	40.86	" 2	1
27E	4/7/68	4/11/68	4	90	22.50	" 2	2
27F	4/13/68	4/16/68	3	68	22.67	" 2	1
27G	4/17/68	4/19/68	2	49	24.50	" 2	6
27H	4/25/68	5/2/68	7	206	29.43	" 2	1
27I	5/3/68	5/6/68	3	96	32.00	" 2	3
28A	5/9/68	5/13/68	4	154	38.50	" 2	2
28B	5/15/68	5/27/68	12	303	25.25	" 2	2
28C	5/29/68	6/15/68	17	669	39.35	" 2	11

<u>Run No.</u>	<u>Date Started</u>	<u>Date Ended</u>	<u>Oper. Days</u>	<u>Total Energy Output (MMd)</u>	<u>Avg. Power (MW)</u>	<u>Samples Location</u>	<u>Shut-down Period (Days)</u>
29A	6/26/68	7/5/68	9	188	20.89	Row 2	4
29B	7/9/68	7/11/68	2	24	12.00	" 2	4
29C	7/15/68	7/22/68	7	205	29.29	" 2	3
29D	7/25/68	8/16/78	22	710	32.27	" 2	5
30A	8/21/68	9/5/68	15	652	43.47	" 2	2
30B	9/7/68	9/11/68	4	166	41.50	" 2	0
30C	9/11/68	9/15/68	4	52	13.00	" 2	2
30D	9/17/68	9/21/68	4	79	19.75	2	1
30E	9/22/68	9/25/68	3	79	26.33	" 2	5
31A	9/30/68	10/4/68	4	89	22.25	" 2	7
31B	10/11/68	10/18/68	7	15.9	22.71	" 2	1
31C	10/19/68	10/22/68	3	84	28.00	" 2	4
31D	10/26/68	11/3/68	8	372	46.50	" 2	1
31E	11/4/68	11/4/68	-	-	-	Out	1
31F	11/5/68	11/14/68	9	413	45.89	"	1
31G	11/15/68	11/17/68	2	111	55.50	Row 2	10
32A	11/27/68	12/17/68	20	852	42.60	" 2	1
32B	12/18/68	12/24/68	6	249	41.50	" 2	1
32C	12/25/68	12/27/68	2	72	36.00	" 2	1
32D	12/28/68	1/2/69	5	224	44.8	" 2	54
33A	2/25/69	3/29/69	32	600	18.75	Out	9
33B	4/7/69	4/22/69	15	576	38.40	"	3
34A	4/25/69	5/13/69	18	822	45.67	Row 4	1

<u>Run No.</u>	<u>Date Started</u>	<u>Date Ended</u>	<u>Oper. Days</u>	<u>Total Energy Output (MWd)</u>	<u>Avg. Power (MW)</u>	<u>Samples Location</u>	<u>Shut-down Period (Days)</u>
34B	5/14/69	5/21/69	7	310	44.29	Row 4	1
35	5/29/69	6/26/69	28	1202	42.93	" 4	8
36A-38A	6/30/69	9/28/69	75	3166	42.21	Out	19
38B	10/3/69	10/16/69	13	600	46.15	Row 4	5
39A	12/16/69	1/10/70	25	771	30.84	" 4	61
39B	1/14/70	1/19/70	5	185	37.00	" 4	4
39C	1/19/70	1/28/70	9	415	46.11	" 4	0
40A	1/31/70	2/10/70	10	443	44.3	" 4	3
40B	2/10/70	3/1/70	19	924	48.63	" 4	0
41A	3/5/70	3/25/70	20	961	48.05	" 4	4
41B	3/27/70	4/1/70	5	157	31.40	" 4	2
42A	4/18/70	5/18/70	30	1344	44.80	" 4	17
43A	5/26/70	6/23/70	28	1350	48.21	" 4	8
44A	6/26/70	7/15/70	19	900	47.37	" 4	3
44B	7/25/70	8/4/70	10	451	45.10	" 4	10
45A	8/9/70	8/23/70	14	645	46.07	" 4	5
45B	8/26/70	9/10/70	15	705	47.00	" 4	-

82

APPENDIX B

PROCEDURE FOR THE DISSOLUTION OF EBR-1' IRRADIATED

NICKEL CAPSULES CONTAINING PuO_2 Acid Dissolution

1. Clean outside of nickel capsule by immersing it in 6 N HNO_3 until a fresh nickel surface is exposed.
2. Rinse nickel capsule with distilled water.
3. Place nickel capsule in a 250-ml round bottom quartz flask which has an outer 24/40 $\frac{1}{2}$ joint.
4. Place quartz flask in a heating mantel which is regulated by a Variac.
5. Connect a quartz water-cooled condenser. The jacket length is about 20 cm. The condenser has an inner 24/40 $\frac{1}{2}$ joint for connection to the flask.
6. Add 50 ml 9 N HBr -0.1 N HF which contains 10 mg chloroplatinic acid (Note 1) to the quartz flask.
7. Turn on the heating mantel and adjust the Variac setting to 80.
8. Heat the solution while under reflux until the dissolution of the nickel capsule is complete (3-5 hours).
9. Turn off the heating mantel and allow the solution in the quartz flask to cool to room temperature.
10. Add 10 ml 9 N HBr -0.1 N HF which contains 100- μ l of bromine to the quartz flask.
11. Turn on the heating mantel and adjust the Variac setting to 80.
12. Heat the solution while under reflux for 2 hours.
13. Turn off the heating mantel and allow the solution in the quartz flask to cool to room temperature.
14. Place the quartz flask in an ice bath.

15. Pass hydrogen bromide gas into the solution at a rate of approximately 3-4 bubbles per second via a 0.5 mm i.d. quartz tube which is long enough to pass through the condenser and into the solution (Note 2).
16. Place the quartz flask back in the heating mantel.
17. Raise the quartz tube out of the solution in the flask.
18. Wash the quartz tube with 10 ml 12 N HBr-0.5 N HF (Note 3) and collect the washings in the quartz flask.
19. Remove the quartz tube from the condenser.
20. Turn on the heating mantel and adjust the Variac setting to 80.
21. Heat the solution while under reflux for 8 hours.
22. Turn off the heating mantel and allow the solution to cool to room temperature.
23. Transfer approximately half the solution to a 50-ml quartz centrifuge tube.
24. Centrifuge for 15 minutes.
25. Transfer the supernate to a pre-weighed (Note 4) quartz Erlenmeyer flask.
26. Transfer the remaining solution in the round bottom quartz flask to the 50-ml quartz centrifuge tube.
27. Centrifuge for 15 minutes.
28. Transfer the supernate to the pre-weighed quartz Erlenmeyer flask.
29. Wash the round bottom quartz flask with 15-20 ml of distilled water and transfer this washing to the quartz centrifuge tube.
30. Wash the round bottom quartz flask with another 15-20 ml of distilled water and transfer this washing to the quartz centrifuge tube.
31. Centrifuge for 15 minutes.
32. Transfer the supernate to the pre-weighed quartz Erlenmeyer flask.
33. Wash the precipitate in the quartz centrifuge tube with 10 ml distilled water.
34. Centrifuge for 15 minutes.

35. Transfer the supernate to the quartz Erlenmeyer flask.
36. Carefully add 10 ml aqua regia (4 parts HCl + 1 part HNO₃) to the residue in the quartz centrifuge tube.
37. Place the quartz centrifuge tube in a hot water bath (80-90°C) and heat 4 to 8 hours.
38. Carefully add 9 N HBr dropwise to the solution in the quartz centrifuge tube until all the nitrate present is destroyed. (Note 4)
39. Remove the quartz centrifuge tube from the hot water bath and allow the solution to cool to room temperature.
40. Centrifuge for 15 minutes.
41. Transfer supernate to the quartz Erlenmeyer flask.
42. Wash the precipitate in the quartz centrifuge tube with 10 ml distilled water.
43. Centrifuge for 15 minutes.
44. Transfer supernate to the quartz Erlenmeyer flask.
45. Repeat steps 42, 43, and 44.

Pyrosulfate Fusion

1. To the residue in the quartz centrifuge tube, add 0.5 ml conc. H₂SO₄.
2. Place quartz tube halfway down into a tube furnace and heat to fumes of H₂SO₄. (Note 5)
3. Remove quartz tube from tube furnace and allow to cool to room temperature.
4. Add 1 gram anhydrous Na₂SO₄ to the quartz tube.
5. Place quartz tube halfway down into the tube furnace and adjust heat until the NaHSO₄ formed by the reaction of Na₂SO₄ has melted.
6. Heat the sample for 12 hours while applying enough heat to keep the salt molten.
7. Occasionally add 1-2 drops of conc. H₂SO₄ to the quartz tube. (Note 6)

8. Remove the quartz tube from the furnace and allow it to cool to room temperature.
9. Add 10 ml 1 N HNO_3 to the quartz tube.
10. Place the quartz tube in a hot water bath at 80-90°C and heat for several hours until the fusion melt dissolves.
11. Centrifuge for 15 minutes.
12. Remove a 10- μ l aliquot of the solution in the centrifuge tube and test for the presence of plutonium by hexone extraction and alpha counting. (Note 7)
13. Transfer the residue which remains from the NaHSO_4 fusion to a piece of filter paper.
14. Count residue with a portable alpha survey meter such as an Eberline Model PAC-4G. (Note 8)

Notes

1. The presence of 10 mg of chloroplatinic acid increases the dissolution rate of nickel in 9 N HBr by a factor of 3 to 4.
2. The HBr concentration of the solution will be increased to approximately 12 N. Under these conditions, NiBr_2 (brown in color) will precipitate. However, as the solution is heated in step 21 and the HBr concentration decreases, the precipitate will go into solution.
3. Prepare 12 N HBr by passing HBr gas into a solution of 9 N HBr in an ice bath.
4. Assume all the nitrate is destroyed when further additions of 9 N HBr do not cause bromine evolution.
5. Fuming with H_2SO_4 insures that all H_2O has been driven off.
6. The excess H_2SO_4 present from the occasional dropwise addition of H_2SO_4 will reflux and wash down the sides of the quartz tube.
7. Less than 0.001% of the plutonium in the samples was found in the solution resulting from the NaHSO_4 fusion.
8. When little or no alpha activity can be detected in the residue from the dissolution, discard the residue. If significant alpha activity remains, repeat the fusion.