STANDARD INTERFACE FILE HANDBOOK

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

A. SHAPIRO AND H. C. HURIA¹

PUBLISHED OCTOBER 1992

UNIVERSITY OF CINCINNATI
NUCLEAR ENGINEERING PROGRAM
CINCINNATI, OH 45221

Prepared for the
U.S. Department of Energy
Assistant Secretary for Nuclear Energy
Under DOE Idaho Field Office
Contract DE-AC07-76ID01570

MASS 08

¹Presently with Commercial Nuclear Fuels Division, Westinghouse Electric Corporation, Monroeville, PA

ABSTRACT

This handbook documents many of the standard interface file formats that have been adopted by the U.S. Department of Energy to facilitate communications between and portability of, various large reactor physics and radiation transport software packages. The emphasis is on those files needed for use of the VENTURE/PC diffusion-depletion code system. File structures, contents and some practical advice on use of the various files are provided.

Table of Contents

Part I Description of Standard Interface Files

I. Introduction	I-1
II. Standard Interface Files	I-1
III. Las Alamos Interface File Processor, LASIP-III	I-7
III.1 Data Format for Input Processor	I-8
III.1.1 Comments	I-8
III.1.2 Numeric Data	I-8
III.1.3 Alphanumeric Data	I-9
III.1.4 Control Options	I-9
IV. Standard Interface Files Explained in This Handbook.	I-10
V. Cross Sections Files	I-11
V.1 ISOTXS-IV, Nuclide Ordered Microscopic Cross Section File	I-11
V.1.1 Example of ISOTXS File	I-24
V.1.2 Second Example of ISOTXS File	I-28
V.2 GRUPXS-IV, Group Ordered Microscopic Cross Section File	I-31
V.2.1 Example of GRUPXS File	I-43
V.3 CXSPRR Cross Section Processing File	I-46
V.3.1 Example of CXSPRR	I-57
V.3.2 Second Example of CXSPRR File	I-59
VI. GEODST Geometry File	I-61
VI.1 Example of GEODST File	I-71
VII. Nuclide and Concentration Assignment Files	I-74
VII.1 Nuclide Density and Cross section Referencing File, NDXSRF-IV	I-75
VII.1.1 Example of NDXSRF File	I-80
VII.2 Zone Atomic density File, ZNATDN-IV	I-82
VII.2.1 Example of ZNATDN File	I-85
VIII. Source Files	I-87
VIII.1 FIXSRC -Distributed and Surface Fixed Source File	I-87
VIII.1.1 Example of FIXSRC File	I-93
VIII.2 FISSOR, Fission Source File	I-95
VIII.2.1 Example of FISSOR File	I-98
VIII.3 DLAYXS, Delayed Neutron Source File	I-101
IX. SEARCH File	I-105
IX.1 Example of SEARCH File	I-113
X. Burnup Problems and the EXPOSE File	I-115
IX.1 Example of EXPOSE File	I-128

XI. Control Files and Standard Interface	
File CONTRL.	I-131
XI.1 Problem Information Record, PROINS	I-131
XI.1.1 Example of PROINS Record	I-133
XI.2 Driver Control File, DVRINS	I-135
XI.2.1 Example of Driver Information Record, DVRINS	I-137
XII. Output Files	I-139
XII.1 The Regular Total Point Flux File, RTFLUX.	I-139
XII.1.1 Example of RTFLUX File	I-143
XII.2 The Adjoint Total Point Flux File, ATFLUX.	I-146
XII.2.1 Example of Adjoint Flux File, ATFLUX.	I-149
XII.3 Regular Zone Flux File, RZFLUX	I-152
XII.3.1 Example of RZFLUX File	I-157
XII.4 PWDINT, Power Density by Interval File	I-161
XII.4.1 Example of Power Density File	I-164
References.	I-166

Part II. Alphabetical Listing of Standard Interface Files. II-1

Standard Interface File AAFLUX-IV, Adjoint Angular Flux . . .	II-2
Standard Interface File AAFLXM, Code dependent Computational- Ordered Angular Flux at Cell Edges for TWODANT Code . . .	II-5
Standard Interface File ACURNT-IV, Adjoint Currents	II-8
Standard Interface File ADJMAC, Code Dependent Macroscopic Multigroup Cross Section File Used in ONEDANT Solver Module for Adjoint Calculations	II-11
Standard Interface File ASGMAT, Code Dependent File Assigning Materials to Zones	II-15
Standard Interface File ATFLUX-IV, Adjoint Total Fluxes . . .	II-18
Standard Interface File BRKOXS-IV, Bondarenko Self Shielding Tables	II-20
Standard Interface File BXSLIB, Microscopic Neutron Cross Sections from Cards	II-24
Standard Interface File CFHIST, Record of Exposure History, Continuous Refueling Module	II-26
Standard Interface File CONTRL	II-31
BLANK Record	II-32
DTNINS Record, Neutronic Instructions	II-33
DVRINS Record, Module Driving Information	II-41
EXPINS Record, Exposure Module Instructions	II-42
PBLINS Record, Pebble Thermal Hydraulic Module Instructions	II-56
PERINS Record, Perturbation Module Instructions	II-61
PROINS Record, Problem Information	II-67
REFINS Record, Fuel Management Information	II-68
RODINS Record, Control Rod Positioning Instructions . . .	II-71
RRTINS Record, Reaction Rate Module instructions	II-74
XCPINS Record, Cross Section Processor Instructions . . .	II-78
Standard Interface File CXSPRR, Data for Cross Section Processor	II-80
Standard Interface File DLAYXS-IV, Microscopic group Delayed Neutron Precursor data	II-86
Standard Interface File EDITIT, Code Dependent File of Information Specific to the ONEDANT Edit Module	II-89
Standard Interface File EXPOHT, Record of Exposure History . .	II-94
Standard Interface File EXPOSE, Data for Exposure Calculations	II-100
Standard Interface File FISSOR, Fission Source by Interval and Distribution Function	II-108
Standard Interface File FISSRC, Code Dependant Fission Source for TWODANT Code	II-110
Standard Interface File FIXSRC-IV, Distributed and Surface Fixed Sources	II-112
Standard Interface File FPRINT, Code Dependent Input Data File for Print Module	II-116
Standard Interface File GEODST-IV, Geometry Description . .	II-119
Standard Interface File GRUPXS-IV, Microscopic Group Neutron Cross Sections	II-126
Standard Interface File ISOGXS-IV, Microscopic Group Gamma Cross sections	II-136

Standard Interface File ISOTXS-IV, Microscopic Group Neutron	
Cross sections	.II-142
Standard Interface File MACRXS, Code Dependent Macroscopic	
Cross Section File for Use in ONEDANT Solver Module .II-150	
Standard Interface File MASBAL, Mass Balance Information	II-154
Standard Interface File NDXSRF-IV, Nuclide Density, Data,	
Cross Section Referencing	.II-159
Standard Interface File PERTUB, Perturbation Data, Regular	
and Adjoint Flux Intervals	.II-162
Standard Interface File PTATDN, Point Nuclide Densities .	II-164
Standard Interface File PWDINT-IV Power Density by Interval	II-167
Standard Interface File QNATDN, Zone (Subzone) Nuclide	
Densities (Discharge)	.II-169
Standard Interface File RAFLUX-IV, Regular Angular Flux .	II-171
Standard Interface File RAFLXM, Code dependent Computational	
Ordered Angular Flux at Cell edges for TWODANT code .II-174	
Standard Interface File REFUEL, Fuel Management	
Specifications	.II-180
Standard Interface File RODSET, Control Rod Reference	
Positionong Data	.II-189
Standard Interface File RSTRTR, Code Block Dependent	
Restart Data Saved for Recovery	.II-197
Standard Interface File RTFLUX, Regular Total Fluxes . .	II-177
Standard Interface File RCURNT-IV, Regular Currents . . .	II-199
Standard Interface File RMFLUX-IV, Regular Moments flux .	II-202
Standard Interface File RZFLUX-IV, Regular Zone Flux by Group,	
Averaged Over each Zone	.II-204
Standard Interface File SEARCH-IV, Criticality search File	II-207
Standard Interface File SNCONS-IV, SN Constants	II-212
Standard Interface File SNXEDT, Code Dependent Microscopic	
Multigroup Cross Section File for Use in ONEDANT Edits	II-214
Standard Interface File SOLINP, Code dependent File of	
Information Specific to the ONEDANT Solver Module .	.II-218
Standard Interface File TRIGON, Triangular Geometry	
Description	.II-226
Standard Interface File WORTHS-IV, Reactivity Per CC By Fine	
Mesh interval	.II-231
Standard Interface File ZNATDN-IV, Zone Atomic Densities	II-234
Standard Interface File ZNPOWD, Zone Average and Peak	233
. . Power Density	II-236
Standard Interface File, ZNTEMP, Zone Temperature Data .	II-240

List Of Figures

Figure II.1	Standard Interface File Description Format	.4
Figure V.1	Specifications for ISOTXS File, Version IV. . . .	16
Figure V.1.1	Example of ISOTXS File	27
Figure V.1.2	Second Example of ISOTXS File	30
Figure V.2	Specification for GRUPXS File, Version IV. . . .	.35
Figure V.2.1	Example of GRUPXS File	45
Figure V.3	Calculational Modes of Cross Section Processor..	47
Figure V.3.1	Specification for Interface File CXSPRR. . . .	51
Figure V.3.2	Example of CXSPRR Interface File	58
Figure V.3.3	Second Example of CXSPRR File	60
Figure VI.1	Specifications for GEODST Geometry Interface File	64
Figure VI.1.1	Example of GEODST Geometry Standard File. . . .	73
Figure VII.1	Nuclide Density and Cross Section Referencing File, NDXSRF	77
Figure VII.1.1	Example of NDXSRF Interface File	81
Figure VII.2	Specifications for ZNATDN Interface File. . . .	83
Figure VII.2.1	Example of ZNADTN File	86
Figure VIII.1	Specifications fgor FIXSRC Interface File. . . .	.89
Figure VIII.1.1	Example of FIXSRC File	94
Figure VIII.2	Specifications for FISSOR Interface file. . . .	.96
Figure VIII.2.1	Example of FISSOR Interface File	99
Figure VIII.3	Specifications for DELAYXS Interface File. . . .	102
Figure IX.1	Specifications for Interface File SEARCH. . . .	.108
Figure IX.1.1	Example of SEARCH Interface File	115
Figure X.1	Specifications for Interface File EXPOSE. . . .	120
Figure X.1.1	Example of EXPOSE Interface File	130
Figure XI.1	Specification for PROINS Record in Interface File CONTRL	132
Figure XI.1.1	Example of PROINS Control Record	134
Figure XI.2	Specification for DVRINS Record in Interface File CONTRL	136
Figure XI.2.1	Example of DVRINS Record	138
Figure XII.1	Specification for Interface File RTFLUX. . . .	.140
Figure XII.1.1	Example of RTFLUX Interface File	144
Figure XII.2	Specifications for Interface File ATFLUX. . . .	147
Figure XII.2.1	Example of ATFLUX File	150
Figure XII.3	Specifications for Interface File RZFLUX. . . .	154
Figure XII.3.1	Example of RZFLUX File	158
Figure XII.4	Specifications for Interface file PWDINT. . . .	162
Figure XII.4.1	Example of PWDINT File	165

Part I. Description of Standard Interface Files.

I. Introduction

In order to improve the portability of large computer codes within the DOE complex, a Committee on Computer Code Coordination (CCCC) was formed to establish standardized procedures¹ for the development and use of DOE codes. The committee established that all calculational modules will use standardized files for input, and produce standardized files as output. This allowed computer codes developed at one installation to use as input, output data developed at other installations, and vice versa. It also allowed for the interchange of data developed by different codes at the same installation. This handbook documents many of the standard interface files developed and used in the DOE complex. Examples and detailed explanations are given for those standard interface files used for the multigroup, multidimensional diffusion-depletion code system, VENTURE. Reference 1 documents version IV of the standard interface files, which were revised late in 1976. In some cases, additional revisions were made later for the VENTURE code system. The specifications for all available standard interface files, including Version IV files with VENTURE updates, are listed in alphabetical order in Part II of this handbook.

Standard interface files are defined and discussed in paragraph II. The Los Alamos Standard Interface File Processor, version III, denoted as LASIP-III², is used to convert card image, ASCII and BCD input to standard interface files. The ASCII or BCD input to LASIP-III follows the specified structure of the binary standard interface file it generates. The LASIP-III Input Processor is discussed in paragraph III. Explanations and examples of files required for the VENTURE code system follows. These explanations are categorized into tasks, which include:

- cross section input and processing;
- geometry specifications;
- nuclide identification and mixing, nuclide density, and nuclide zone assignments;
- source files;
- search files;
- burnup;
- control records;
- and the files required for output.

II. Standard Interface File Structure.

A standard interface file is a binary sequential file with a specified structure and data content. The basic structure of standard interface files has been documented in accordance with the prescription developed by CCCC. It is given in reference 1, and is repeated here for convenience and continuity.

The standard interface file specifications is made up of sections which follow a prescribed order. These include: a file name section; a file identification section; a file structure section; a file control section; data record type 1; data record type 2 ,etc. In most cases. each section is associated with a record written on the file. A file record is defined as that information transferred in a single READ or WRITE statement.

Figure II.1 shows an example of the file description as printed from FORTRAN comment cards. Each record then begins in column 1 with the comment character, "C". Each file section is blocked. The file name section is blocked with asterisks in columns 2 through 72, horizontally, and with a minus sign in column 72, vertically. Other sections are blocked horizontally with minus signs in columns 2 through 72, as shown in Figure II.1. In some cases an asterisk appears in column 71, indicating a modification to the file. The characters in column 2 mean the following:

- F = File Name (Six Alphanumeric Characters)
- E = File Description
- N = Note
- R = Record Name
- C = Test on Presence of Record
- L = Record List
- W = Record Length Algorithm
- D = Definition
- S = File Structure
- B = Text Format on Read or Write

Only the Record List information, with the L identifier in column 2, are actually written on the file. The characters CEOF indicate "End of File", and are given in the first four columns of the final section.

Figure II.1 shows the File Name Section for a fictitious file called "FILNAM". Note the "F" in column 2 of the file name line. Additional notes and the creation date may be included in this section. Note the "N" in column 2 for notes.

The File Identification Section specifies the first record written on the file. This includes the file name, user identification information, and the file data version number. The record name has an "R" in column 2, and this record is named "File Identification". The name, user identification, and file version number make up this record, as shown on the line with the "L" in column 2. The CW or record length line includes the MULT parameter which is unity for long word machines, such as CDC mainframes, and has the value 2 for short word machines such as the IBM mainframe and PC (i.e., 8 bits per byte and 4 bytes per word). This parameter is required to keep track of record lengths. Names under the CCCC specifications are 6 letters in length. Long word machines can accomodate 6 letters in one word, but short word machines can only

accommodate 4 letters, so two words are required for each name on short word machines. The number of words for this record on a long word machine is four, one for the file name, two for the user identification, and one for the version number. On short word machines, two words are required for the file name. Also, four words are required for the user identification, i.e., 2 six letter statements, and one word for the version number, making a total of 7 words for this record on a short word machine. Definitions associated with this record are given on those lines containing a "D" in column 2. These definitions indicate that the file name and user identification are 6 letter words which can be read in A6 format. Again, all names under the CCCC specifications are 6 letters.

The file structure is given in the next block, and indicates the file sections associated with the file, and the conditions under which these sections are present. This information is given under the "RECORD TYPE" and "PRESENT IF" columns. This block is required only if the data is structured in loops extending beyond one record. These loops follow the rules associated with FORTRAN DO loops. The loop is shown bounded by asterisks in this block. There is no file record written for this block. The "S" in column 2 stands for file structure.

The File Control Section is next. This contains the second record written on the file, and gives the lengths of the file records, and the control flags associated with the file. This record is usually the "1D Data Record", and is associated with control parameters which are file-wide, i.e., they apply to the file as a whole. The "R" in column 2 is associated with the name of the record, in this case "File Control". The "L" in column 2 is the record list as written, the "W" is the number of words in the record, and the "D" lines are definitions of the parameters in the record.

The remaining records are associated with data, and describe the data written on the file. The data associated with each record is categorized by type, starting with data type 1, then data type 2, etc., extending to the end of the file. The first of these records is the "2D Record", the second is the "3D Record", etc. The line with the "C" in column 2 is the test for the presence of the record. These data records are present if the control flags associated with them, and given in the File Control Record, have the values required to include the record. The records illustrated have a DO Loop shown with the executable line "READ(N), *LIST AS ABOVE*", which means these records are repeated in accordance with the DO Loop. The "W" line gives the number of words in the record, and the "D" lines define the parameters in the record.

```

C*****
C          CREATED 11/14/75
C
CF          FILNAM
CE          BRIEF DESCRIPTION OF TYPE OF DATA IN FILE
C
C
CN          ADDITIONAL NOTE ON THE FILE CONTENTS MAY BE
CN          INCLUDED HERE
C
C*****
C-----
CR          FILE IDENTIFICATION
C
CL          HNAME,(HUSE(I),I=1,2),IVERS
C
CW          1 + 3*MULT = NUMBER OF WORDS
C
C
CD          HNAME          HOLLERITH FILENAME -FILNAM- (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE DATA - VERSION NUMBER
CD          MULT            DOUBLE PRECISION PARAMETER
CD                          1 - A6 WORD IS SINGLE WORD
C                          2 - A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C-----
CS          FILE STRUCTURE
CS
CS          RECORD TYPE          PRESENT IF
CS          =====
CS          FILE IDENTIFICATION  ALWAYS
CS          FILE CONTROL         ALWAYS
CS          DATA TYPE 1         NFLAG1.EQ.1
CS          ***** (REPEAT TO NLOOP1)
CS          * DATA TYPE 2       NFLAG2.EQ.1
CS          * DATA TYPE 3       NFLAG3.EQ.1
CS          *****
C
C-----

```

FIGURE II.1. STANDARD INTERFACE FILE DESCRIPTION FORMAT

```

C-----
CR      FILE CONTROL    (1D RECORD)
C
CL      NWDS1,NWDS2,NWDS3,NFLAG1,NFLAG2,NFLAG3,NLOOP1,NLOOP2,NLOOP3
C
CW      9 = NUMBER OF WORDS
C
CD      NWDS1           NUMBER OF WORDS OF DATA TYPE 1 IN A RECORD
CD      NWDS2           NUMBER OF WORDS OF DATA TYPE 2 IN A RECORD
CD      NWDS3           NUMBER OF WORDS OF DATA TYPE 3 IN A RECORD
CD      NFLAG1          CONTROL FLAG FOR DATA TYPE 1
CD                        0 = DATA TYPE 1 NOT PRESENT
CD                        1 = DATA TYPE 1 PRESENT
CD      NFLAG2          CONTROL FLAG FOR DATA TYPE 2
CD                        0 = DATA TYPE 2 NOT PRESENT
CD                        1 = DATA TYPE 2 PRESENT
CD      NFLAG3          CONTROL FLAG FOR DATA TYPE 3
CD                        0 = DATA TYPE 3 NOT PRESENT
CD                        1 = DATA TYPE 3 PRESENT
CD      NLOOP1          NUMBER OF RECORDS OF DATA TYPE 1
CD      NLOOP2          NUMBER OF RECORDS OF DATA TYPE 2
CD      NLOOP3          NUMBER OF RECORDS OF DATA TYPE 3
C
C-----

C-----
CR      DATA TYPE 1    (2D RECORD)
C
CC      PRESENT IF NFLAG1.EQ.1
C
CL      (ARRAY1(I),I=1,NWDS1)---NOTE STRUCTURE BELOW---
C
CW      NWDS1
C
C      DO 1 J=1,NLOOP1
C      1 READ(N) *LIST AS ABOVE*
C
CD      ARRAY1(I)        ARRAY CONTAINING DATA TYPE 1 WORDS
C
C-----

```

FIGURE II.1. standard interface file DESCRIPTION FORMAT (cont.)


```

C-----
CR          DATA TYPE 2    (3D RECORD)          -
C                                                  -
CC          PRESENT IF NFLAG2.EQ.1              -
C                                                  -
CL      (ARRAY2(I),I=1,NWDS2)                   -
C                                                  -
CW      NWDS2                                    -
C                                                  -
C      DO 1 J=1,NLOOP2                          -
C  1 READ(N) *LIST AS ABOVE*                    -
C                                                  -
CD      ARRAY2(I)          ARRAY CONTAINING DATA TYPE 2 WORDS -
C                                                  -
C-----

C-----
CR          DATA TYPE 3    (4D RECORD)          -
C                                                  -
CC          PRESENT IF NFLAG3.EQ.3              -
C                                                  -
C                                                  -
CL      (ARRAY3(I),I=1,NWDS3)                   -
C                                                  -
CW      NWDS3                                    -
C                                                  -
C      DO 1 J=1,NLOOP3                          -
C  1 READ(N) *LIST AS ABOVE*                    -
C                                                  -
CD      ARRAY3(I)          ARRAY CONTAINING DATA TYPE 3 WORDS -
C                                                  -
C-----

CEOF

```

FIGURE II.1. STANDARD INTERFACE FILE DESCRIPTION FORMAT (cont.)

III. Las Alamos Standard Interface File Processor, LASIP-III.²

The LASIP-III Input Processor will henceforth be denoted simply as the "Input Processor". The primary function of the Input Processor is to create interface files entirely from card, or BCD, or ASCII input. The card input follows a structure similar to the structure associated with the interface files specifications, and uses free format. Blanks are recommended between data entries, but other than that the data can reside anywhere on a record or card.

The first data record of the Input Processor is a file identification record, which is considered a file control card. It is the "nV FILEID" card, where n is an integer, and FILEID is the name of the standard interface file to be written or overwritten by the subsequent data cards. If n=0, the latest version number of the file named "FILEID" will be rewritten with the data to follow. If no file exists, it is created with version number 1. This is the usual situation. If n is greater than zero, but not 99, an old "FILEID" file with version number n is overlaid with the data to follow, and the new file has the same version number as the old file, but it is placed on a new logical unit. If n=99, a new file version of "FILEID" is created. If there are two 0V control cards with the same name, an existing old file will always be rewritten with the first set of data, while the second set creates a new file with a next higher version number. Data and comments following the filename on this card are ignored. The FILEID card substitutes for the file identification record of the standard interface file specifications, and is the first listed record of the file. The user identification is automatically applied by the Input Processor as "LASIP - III"

A FILEID card is the first card read by the input processor. Processing of the file associated with this card is continued until a new FILEID is encountered, in which case the new file is processed, or a STOP card is read, in which case the Input Processor is exited.

Data is input through "mD" cards, which follow the file identification card. These cards are associated with the data type cards of the interface file named FILEID. The data may be integer, floating point or Hollerith, but must satisfy the data specifications for the specific file. If the list for record type m is repeated, mD must precede each repetition.

The Input Processor is terminated when a card containing STOP as the first entry is encountered. The STOP card must be followed by an END card, signifying the end of data input for the Input Processor.

There is an additional control card which can be inserted anywhere in the input data, but preferably before an OV card. This is the FLAG card with the form

FLAG IUNIT IPRINT ISTART IEND

The word FLAG identifies a special instruction to the Input Processor. IUNIT identifies a new unit from which the Input Processor is to immediately obtain data, unless it is zero, in which case processing continues on the original unit. Processing continues on the new unit until a STOP instruction or end of file is processed, after which the Input Processor is returned to the original unit. If IPRINT is zero, all card images will be printed; if it is one, no card images will be printed; and if IPRINT is two, the cards between and including ISTART and IEND will be printed.

III.1 Data Format for Input Processor.

III.1.1 Comments.

The slash (/) may be used to terminate a data record, after which comments can be inserted. Such trailing comments on a data record will appear in the output. Comments may also be enclosed between dollar signs (\$), and inserted freely between data entries on a record. These comments will not be written on the binary files generated by the Input Processor.

III.1.2 Numeric Data.

Numeric data is either integer or single precision floating point numbers. Exponents are input for floating point numbers with a sign or E immediately following the number to be exponentiated. The following forms are equivalent real numbers equaling the floating point number 10:

1E1
1+1
1.0E+01
1.0E 01
1.0D 01

The last number indicates that double precision is treated as single precision on input.

III.1.3 Alphanumeric Data

Hollerith or alphanumeric input is specified in three ways:

1. by enclosing the data in asterisks or,
2. by using the nH Hollerith specification, or
3. by beginning a single word entry, containing no more than six characters, with a letter.

Hollerith data are stored as six characters per word, where each word is stored as REAL*8, or as a double precision number on short word machines. All character data are left adjusted, with the unfilled spaces filled with blanks.

Imbedded blanks (), commas (,), slashes (/), dollar signs (\$), plus signs (+), and minus signs (-), are allowed only in methods 1 and 2. Imbedded asterisks (*) or apostrophes are allowed only in method 2.

III.1.4 Control Options.

There are several control options which can be applied to the data to facilitate input. These include the Repeat Option, the Skip Option, the Interpolation Option, and the Section Repeat Option. The Repeat Option is an unsigned integer immediately followed by the letter "R". Applying this option repeats the previously entered data by the unsigned integer. Thus, 3R in the input stream repeats the previous data entry 3 times. The Skip Option is an unsigned integer followed by the letter "S". The Skip Option is used only when overlaying an existing file. The unsigned integer number of data locations are skipped before the next entry is input. Thus, 3S in the input stream means to skip the next 3 locations associated with the file being revised. The Interpolation Option allows for linear interpolation between two real numbers. Thus "nI", with n an integer, means to interpolate between the previous entry and the entry to follow, with n equally spaced points. For example:

1.0 3I 5.0 = 1.0 2.0 3.0 4.0 5.0

A section is a group of data entries enclosed in parentheses. The Section Repeat Option has the form (data entries) nR, where n is the number of times to repeat the entries enclosed in parentheses. Section repeats may be nested. Thus,

(1(5.0 2I 20.0) 2R WORD1) 2R

is equivalent to

(1 5.0 10.0 15.0 20.0 5.0 10.0 15.0 20.0 WORD1) 2R

If Hollerith words are repeated, the Section Repeat Option must be used. For example,

(*PU238B*) 2R = *PU238B* *PU238B*.

Many examples of the use of the Input Processor format are given in the ensuing file descriptions and explanations.

IV. Standard Interface Files Explained in This Handbook.

Some of the standard interface files used by VENTURE/PC and their function are given in alphabetical order as follows:

ATFLUX - Adjoint total point flux
CONTRL - Computation module control records
CXSPRR - Cross section processing data
DLAYXS - Delayed neutron data
EXPOSE - Exposure data
FISSOR - Fission source
FIXSRC - Fixed source
GEODST - Geometry description
GRUPXS - Group ordered microscopic cross sections
ISOTXS - Nuclide ordered microscopic cross sections
NDXSRF - Nuclide referencing
PWDINT - Point power density
RTFLUX - Regular total point flux
RZFLUX - Regular total zone flux
SEARCH - Criticality search data
ZNATDN - Nuclide Concentration

These particular files will be explained, in most cases with examples, in this handbook. The files will be explained by function. The cross section files, ISOTXS and GRUPXS will be explained first, along with the cross section processing file CXSPRR. Then the geometry file, GEODST, will be described and illustrated. This will be followed by the files associated with setting up the nuclides used in the problem. These include the nuclide referencing file NDXSRF, and the zone atomic density file ZNATDN. The source files will then be explained as a group. These include the fixed source specification file FIXSRC, the fission source file FISSOR, and the delayed neutron file DELAYXS. The file associated with nuclide concentration and/or dimension searches, SEARCH, will then be discussed. The standard interface file associated with burnup or exposure, EXPOSE will then be described and illustrated. The CONTRL file, which contains records for controlling the path taken by a calculation, and the specified conditions for the problem, will be discussed. Finally, the output files ATFLUX, RTFLUX, PWDINT, and RZFLUX will be shown.

V. Cross Section Files

Cross section data for neutronics problems are supplied in the cross section standard interface files ISOTXS and GRUPXS. In addition, cross section processing is provided through the standard interface file CXSPRR.

V.1 ISOTXS-IV Nuclide Ordered Microscopic Cross Section File.

The ISOTXS file provides microscopic cross sections ordered by isotope. All of the microscopic cross sections for the first designated isotope in a problem are listed, followed by the microscopic cross sections for the second isotope, etc. This is the format in which cross section generators produce cross section sets from basic cross section data. As a consequence, most cross sections are input to CCCC standard codes in ISOTXS format. The specifications for ISOTXS standard interface file, version IV are shown in Figure V.1.

The ISOTXS file contains the following sections in addition to the File Name Section:

- File Structure Section
- File Identification Section
- 1D Record - File Control Section
- 2D Record - File-Wide Data
- 3D Record - File Wide Fission Spectrum Data, when applicable
- 4D Record - Isotope Control and Group Independent Data
- 5D Record - Principal Isotopic Cross Sections
- 6D Record - Isotopic Fission Spectrum data, when applicable
- 7D Record - Scattering Matrix Data

As indicated in the File Name section of ISOTXS-IV, Figure V.1, version IV was established in November, 1976. The File Structure section indicates that the File Identification, the File Control (1D Record) parameters, and the File Data (2D Record), are always given. If a file wide fission spectrum matrix is required it is given in the 3D Record. The parameter ICHIST in the File Control Record specifies whether or not the same fission spectrum is to be used for all isotopes. As shown in the File Structure section, the isotope control and group independent data, (4D Record), the Principal Cross Sections (5D Record), the isotopic fission spectrum data if applicable (6D Record), and the scattering matrices (7D Record) are then repeated for each isotope. The parameter ICHI in the 4D Record controls the use of separate fission spectra for each isotope. If more than one scattering matrix applies to a given isotope, it is repeated within the isotope loop, as indicated in the file structure section.

The File Identification section contains the first record written on the file. This record includes the file name, i.e., ISOTXS, the user identification, and the file version number. In binary, the file name and user identification are written as REAL*8, since they are 6 letters in length, and require double precision words on short word machines such as the IBM PC. In ASCII or text formatted input (the CB line), the FORMAT is shown as "OV ISOTXS", followed by a 12 letter user identification enclosed in asteriks, followed by a version number in I6 format. When using the LASIP-III Input Processor, the user identification and version number is applied automatically, and is not required to be input.

The File Control section is written as the 1D record. It contains 8 integers which provide control information for the entire file. This includes the number of energy groups, NGROUP, the number of isotopes NISO, the maximum number of upscatter groups, MAXUP, the maximum number of downscatter groups, MAXDN, the maximum scattering order, MAXORD, the file wide fission spectrum flag, ICHIST, the maximum number of scattering blocks, NSCMAX, and the subblocks per scattering block, NSBLOK. The use of subblocks has heretofore been used for the higher order Legendre component scattering matrices, but has for the most part been discontinued (reference 1). Thus, the subblocks per scattering block is most often input as unity. The parameter ICHIST is the file wide fission spectrum flag. If it is input as 0, there is no file wide spectrum. If ICHIST is unity, there is a file wide fission spectrum vector, which implies a single spectrum for all fissionable isotopes. If ICHIST is greater than 1, a file wide fission spectrum matrix is employed which is detailed in the 3D Record.

The file wide data is given in the 2D Record. The first entry of this record is the file identification written in binary as 12 6 character words, the format for which is (HSETID(I), I=1,12). Then the isotope names are given, one for each isotope in the file, (HISONM(I), I=1,NISO). As are all names, these are also 6 character words, which are typed as REAL*8 double precision words on short word machines. If ICHIST in the 1D Record is unity, the file wide fission spectrum vector is given next, (CHI(J), J=1,NGROUP). The average velocities for each group, (VEL(J), J=1,NGROUP), and the maximum energies for each group, (EMAX(J), J=1,NGROUP), are given next. The lowest energy bound is then given, EMIN, followed by the number of records which must be skipped to read data for each isotope, (LOCA(I), I=1,NISO).

If the parameter ICHIST in the 1D record was set greater than unity, a file wide fission matrix is input in the 3D record. The first array of the record is written in the following manner: ((CHI(K,J), K=1, ICHIST), J=1, NGROUP). Here, CHI(K,J) is the fraction of neutrons emitted into group J as a result of fission using spectrum K. Thus, the number of spectra available is equal to ICHIST. An additional array, (ISSPEC(I), I=1, NGROUP), is part of this record. This parameter identifies the fission spectrum to be

used for each group. Thus, if ISSPEC(I)=K, spectrum K is used to calculate the emission spectrum from fission in group I.

The isotope control and group independent data are given in the 4D record. Most of the entries are reasonably self explanatory. Many of these entries may not affect or be applicable to a given problem, and can be put in as zero's. The first three entries are associated with identifying the nuclide or isotope. HABSID is the Hollerith absolute isotope label, which remains the same throughout the file. HIDENT identifies the library from which the data came, e.g., ENDF/B, and HMAT is the isotope identification, which might be, for example, the ENDF/B material number. These are followed by EFISS, the thermal energy yield per fission in watt-sec/fission, and ECAPT, the thermal energy yield per capture in watt-sec per capture. The isotopic temperature, TEMP, associated with the cross section file is given in degrees Kelvin. This is followed by SIGPOT, the average effective potential scattering in the resonance range in barns/atom. The density of the isotope in the mixture in which the isotope cross sections were generated, ADENS, is given next in atoms/(barn-cm). The isotope classification, KBR, follows. If KBR is zero, the classification is undefined. Additional classifications are: fissile; fertile; other actinide; fission product; structure; coolant; and control. These classifications are given by assigning numbers one through seven, in order, to KBR. The isotope fission spectrum flag, ICHI, follows. If isotopic fission spectra (in contrast to file wide spectra) are used, the parameter ICHI must be set to unity or greater. An isotopic fission spectrum vector is used with ICHI set to unity, while a fission spectrum matrix is used for ICHI greater than one. The matrix is defined in the 6D record. The next parameter is the cross section fission flag, IFIS. If IFIS is zero, there is no fission data in the principal cross section record, while if IFIS is unity, fission data are present in the principal cross section record. The next 5 entries are associated with charged particle out and (N,2N) cross sections. These include IALF, the (N,ALPHA) cross section flag, INP, the (N,P) cross section flag, IN2N, the (N,2N) flag, IND, the (N,D) flag, and INT, the (N,T) flag. The number of moments for the total cross section, LTOT, is entered next, followed by LTRN, the number of moments in the transport cross section. Scattering matrix parameters are included in the 4D record. The parameter IDSCT(N), given next, designates the type of scattering matrix for block N, which may be selected as total, elastic, inelastic, or (N,2N) matrices. In addition, provision is made in the integer assigned to IDSCT(N) to establish the Legendre expansion order of the first matrix in block N. The parameter LORD(N) which follows, establishes the number of scattering orders in block N. The combination of IDSCT(N) and LORD(N) establish the scattering matrices of all Legendre expansion components needed for the particular isotope assigned to block N. The parameter JBAND(J,N) defines the number of groups that scatter into group J in scattering block N. Self scatter is included in JBAND(J,N). The parameter IJJ(J,N) fixes the

position of the with-in group scattering cross section for group J, for the isotope in block N. The format for the 4D Record is then:

```
HABSID,HIDENT,HMAT,AMASS,EFISS,ECAPT,TEMP,SIGPOT,ADENS,KBR,ICHI,
1IFIS,IALF,INP,IN2N,IND,INT,LTOT,LTRN,ISTRPD,
2(IDSCT(N),N=1,NSCMAX),(LORD(N),N=1,NSCMAX),
3((JBAND(J,N),J=1,NGROUP),N=1,NSCMAX),
4((IJJ(J,N),J=1,NGROUP),N=1,NSCMAX)
```

Here, NSCMAX is the maximum number of blocks of scattering data.

The principal microscopic isotopic cross sections are detailed in the 5D record. These include the transport, total, capture, and fission cross sections. In addition, fission spectral data, charged particle out, and (N,2N) cross section are given. The first entry, ((STRPL(J,L),J=1,NGROUP),L=1,LTRN), is the P_L weighted transport cross section, with LTRN being the number of moments for the transport cross section. The first element is the current or P_1 weighted transport cross section. The (2L+1) factor used in Legendre expansions is not included in the transport cross sections. The next entry is the P_L weighted total cross section, (STOTPL(J,L),J=1,NGROUP),L=1,LTOT), where LTOT is the number of moments used for the total cross section. The first element in this array is the flux or P_0 weighted total cross section. Again, the (2L+1) factor is not included. (SNGAM(J),J=1,NGROUP), the (N,GAMMA) cross sections are given next. If IFIS is greater than zero, fission cross sections are present and are given by (SFIS(J),J=1,NGROUP). Again, if IFIS is greater than zero, the total neutron yield per fission, (SNUTOT(J),J=1,NGROUP), is entered. If ICHI is set to unity, the isotope fission spectrum, (CHISO(J),J=1,NGROUP), is given. The (N,ALPHA) cross sections, (SNALF(J),J=1,NGROUP) are given next, followed by (SNP(J),J=1,NGROUP), (SN2N(J),J=1,NGROUP), (SND(J),J=1,NGROUP), (SNT(J),J=1,NGROUP), the (N,P), (N,2N), (N,D), and (N,T) cross sections, respectively. These are present if the flags associated with these cross sections in the 4D Record were set greater than zero. The final array for this record is ((STRPD(J,I),J=1,NGROUP),I=1,ISTRPD), the coordinate dependent transport cross sections, wher I denotes the coordinate direction, and ISTRPD is the number of coordinate directions stipulated in the 4D Record.

The 6D record is used for isotopic fission spectrum matrices. It applies only when the parameter ICHI, of the 4D record, is greater than unity. The entries for this record are: ((CHIISO(K,J),K=1,ICHI),J=1,NGROUP), (ISOPEC(I),I=1,NGROUP). Here, CHIISO(K,J) is the fraction of neutrons emitted into group J as a result of fission in any group, using spectrum K. ISOPEC(I) denotes the spectrum used to calculate the fission in group I. If ISOPEC(I)=K, then spectrum K will be used for group I.

The scattering blocks are given in the 7D record. The scattering cross sections are stored by group, with each group having JBAND values, i.e., the number of groups which scatter into the stored group plus self scatter. Within a group, the upscatter groups are given first, with the furthest upscatter group from the given group stored first, followed by the next furthest group from the given group stored next, etc. The self scatter follows the upscatter groups, which is then followed by the downscatter groups, with the furthest removed down scatter group stored last. As an example, suppose there are 5 groups, with the total scattering cross section matrix to be given. Then, only one scattering block is involved. Additional scattering blocks would be required if elastic, inelastic, and (N,2N) scattering cross sections were given separately. Say the scattering bandwidth is 5, with two downscatter groups and two upscatter groups maximum. The scattering block would be listed as

$$\begin{array}{l}
 \sigma_{s,0}^{3-1}; \sigma_{s,0}^{2-1}; \sigma_{s,0}^{1-1}; 0; 0 \\
 \sigma_{s,0}^{4-2}; \sigma_{s,0}^{3-2}; \sigma_{s,0}^{2-2}; \sigma_{s,0}^{1-2}; 0 \\
 \sigma_{s,0}^{5-3}; \sigma_{s,0}^{4-3}; \sigma_{s,0}^{3-3}; \sigma_{s,0}^{2-3}; \sigma_{s,0}^{1-3} \\
 0; \sigma_{s,0}^{5-4}; \sigma_{s,0}^{4-4}; \sigma_{s,0}^{3-4}; \sigma_{s,0}^{2-4} \\
 0; 0; \sigma_{s,0}^{5-5}; \sigma_{s,0}^{4-5}; \sigma_{s,0}^{3-5}
 \end{array}$$

If P_1 , P_2 , etc. scattering components are to be given, they follow in the order shown, except the subscript on the scattering cross section is changed from 0 to 1 or 2 etc. In the past, higher order Legendre components were considered to be subblocks of the P_0 scattering matrix. Now, IDSCT(N) specifies the type (i.e., total, elastic, inelastic, or (N,2N)) of scattering matrix, and the order of the first matrix in the block, while LORD(N) specifies the number of Legendre orders in each block. Subblocks are generally no longer used and are not recommended (reference 1). Thus, blocks are defined through IDSCT(N) and LORD(N), and NSBLOK is set to unity. The scattering cross sections are stored in the array SCAT(K,L), where K refers to the record number and L to the Legendre component. The record number K, increases by group, with the first cross section in a group associated with the highest group upscattering into the group, and the last cross section in a group to the highest group downscattered to. In the example shown above, S(1,1) is the group three to group one upscatter cross section, S(3,1) is the within group scattering cross section for group 1, S(5,1) is the group one to three downscatter cross section, etc. Since there are no higher order Legendre components for this example, the second index of S(K,L) remains at 1.


```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME, (HUSE(I), I=1, 2), IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CB          FORMAT(11H OV ISOTXS ,   1H*,
CB          12A6, 1H*, I6)
C
CD          HNAME          HOLLERITH FILE NAME - ISOTXS - (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
CD          MULT           DOUBLE PRECISION PARAMETER
CD                          1 - A6 WORD IS A SINGLE WORD
CD                          2 - A6 WORD IS A DOUBLE PRECISION WORD
C
C-----

C-----
CR          FILE CONTROL      (1D RECORD)
C
CL          NGROUP, NISO, MAXUP, MAXDN, MAXORD, ICHIST, NSCMAX, NSBLOK
C
CW          8=NUMBER OF WORDS
C
CB          FORMAT(4H 1D , 8I6)
C
CD          NGROUP          NUMBER OF ENERGY GROUPS IN FILE
CD          NISO            NUMBER OF ISOTOPES IN FILE
CD          MAXUP           MAXIMUM NUMBER OF UPSCATTER GROUPS
CD          MAXDN           MAXIMUM NUMBER OF DOWNSCATTER GROUPS
CD          MAXORD          MAXIMUM SCATTERING ORDER (MAXIMUM VALUE OF
CD                          LEGENDRE EXPANSION INDEX USED IN FILE).
CD          ICHIST          FILE WIDE FISSION SPECTRUM FLAG
CD                          ICHIST.EQ.0,      NO FILE-WIDE SPECTRUM
CD                          ICHIST.EQ.1      FILE-WIDE CHI VECTOR
CD                          ICHIST.GT.1      FILE WIDE CHI MATRIX
CD          NSCMAX          MAXIMUM NUMBER OF BLOCKS OF SCATTERING DATA
CD          NSBLOK          SUBBLOCKING CONTROL FOR SCATTER MATRICES. THE
CD                          SCATTERING DATA ARE SUBBLOCKED INTO NSBLOK
CD                          RECORDS (SUBBLOCKS) PER SCATTERING BLOCK.
C
C-----

```

FIGURE V.1 SPECIFICATIONS FOR ISOTXS FILE, VERSION IV (CON'T).

```

C-----
CR          FILE DATA      (2D RECORD)
C
CL      (HSETID(I),I=1,12),(HISONM(I),I=1,NISO),
CL      1(CHI(J),J=1,NGROUP),(VEL(J),J=1,NGROUP),
CL      2(EMAX(J),J=1,NGROUP),EMIN,(LOCA9I),I=1,NISO)
C
CW      (NISO+12)*MULT+1+NISO
CW      +NGROUP*(2+ICHIST*(2/(ICHIST+1)))=NUMBER OF WORDS
C
CB      FORMAT(4H 2D ,1H*,11A6,1H*/          HSETID,HISONM
CB      11H*,A6,1H*,9(1X,A6)/(10(1X,A6)))
CB      FORMAT(6E12.5)                      CHI (PRESENT IF ICHIST.EQ.1)
CB      FORMAT(6E12.5)                      VEL,EMAX,EMIN
CB      FORMAT(12I6)                        LOCA
C
CD      HSETID(I)      HOLLERITH IDENTIFICATION OF FILE (A6)
CD      HISONM(I)      HOLLEREITH ISOTOPE LABEL FOR ISOTOPE I (A6)
CD      CHI(J)         FILE-WIDE FISSION SPECTRUM (pRESENT IF ICHIST.EQ.1)
CD      VEL(J)         MEAN NEUTRON VELOCITY IN GROUP J (CM/SEC)
CD      EMAX(J)        MAXIMUM ENERGY BOUND OF GROUP J (EV)
CD      EMIN          MINIMUM ENERGY BOUND OF SET (EV)
CD      LOCA(I)        NUMBER OF RECORDS TO BE SKIPPED TO READ DATA FOR
CD                      ISOTOPE I.  LOCA(I)=0.
C
C-----

C-----
CR          FILE-WIDE CHI DATA      (3D RECORD)
C
CC      PRESENT IF ICHIST.GT.1
C
CL      ((CHI(K,J),K=1,ICHIST),J=1,NGROUP),(ISSPEC(I),I=1,NGROUP)
C
CW      NGROUP*(ICHIST+1)=NUMBER OF WORDS
C
CB      FORMAT(4H 3D , 5E12.5/(6E12.5))      CHI
CB      FORMAT(12I6)                        ISSPEC
C
CD      CHI(K,J)      FRACTION OF NEUTRONS EMITTED INTO GROUP J AS A
CD                      RESULT OF FISSION IN ANY GROUP, USING SPECTRUM K-
CD      ISSPEC(I)     ISSPEC(I)=K IMPLIES THAT SPECTRUM K IS USED
CD                      TO CALCULATE EMISSION SPECTRUM FROM FISSION
CD                      IN GROUP I
C
C-----

```

FIGURE V.1 SPECIFICATIONS FOR ISOTXS FILE, VERSION IV (CON'T).

```

C-----
CR      ISOTOPE CONTROL AND GROUP INDEPENDENT DATA  (4D RECORD)  -
C      -
CL      HABSID,HIDENT,HMAT,AMASS,EFISS,ECAPT,TEMP,SIGPOT,ADENS,KBR,ICHI.  -
CL      1IFIS,IALF,INP,IN2N,IND,INT,LTOT,LTRN,ISTRPD,  -
CL      2(IDSCT(N),N=1,NSCMAX),(LORD(N),N=1,NSCMAX,  -
CL      3((JBAND(J,N),J=1,NGROUP),N=1,NSCMAX),  -
CL      4((IJJ(J,N),J=1,NGROUP),N=1,NSCMAX)  -
C      -
CW      3*MULT+17+NSCMAX*(2*NGROUP+2)=NUMBER OF WORDS  -
C      -
CB      FORMAT(H 4D ,3(1X,A6)/ 6E12.5/  -
CB      1(12I6)  -
C      -
CD      HABSID          HOLLERITH ABSOLUTE ISOTOPE LABEL - SAME FOR ALL  -
CD                        VERSIONS OF THE SAME ISOTOPE IN FILE (A6)  -
CD      HIDENT          IDENTIFIER OF LIBRARY FROM WHICH BASIC DATA  -
CD                        CAME (E.G. ENDF/B) (A6)  -
CD      HMAT            ISOTOPE IDENTIFICATION (E.G. ENDF/B MAT NO.) (A6)  -
CD      AMASS           GRAM ATOMIC WEIGHT  -
CD      EFISS           TOTAL THERMAL ENERGY YIELD/FISSION (W.SEC/FISS)  -
CD      ECAPT           TOTAL THERMAL ENERGY YIELD/CAPTURE (W.SEC/FISS)  -
CD      TEMP            ISOTOPE TEMPERATURE (DEGREES KELVIN)  -
CD      SIGPOT          AVERAGE EFFECTIVE POTENTIAL SCATTERING IN  -
CD                        RESONANCE RANGE (BARNS/ATOM)  -
CD      ADENS           DENSITY OF ISOTOPE IN MIXTURE IN WHICH ISOTOPE  -
CD                        CROSS SECTIONS WERE GENERATED (A/BARN-CM)  -
CD      KBR             ISOTOPE CLASSIFICATION  -
CD                        0=UNDEFINED  -
CD                        1=FISSILE  -
CD                        2=FERTILE  -
CD                        3=OTHER ACTINIDE  -
CD                        4=FISSION PRODUCT  -
CD                        5=STRUCTURE  -
CD                        6=COOLANT  -
CD                        7=CONTROL  -
CD      ICHI            ISOTOPE FISSION SPECTRUM FLAG  -
CD                        ICHI.EQ.0,      USE FILE-WIDE CHI  -
CD                        ICHI.EQ.1,      ISOTOPE CHI VECTOR  -
CD                        ICHI.GT.1,      ISOTOPE CHI MATRIX  -
CD      IFIS            (N,F) CROSS SECTION FLAG  -
CD                        IFIS=0,  NO FISSION DATA IN PRINCIPAL CROSS  -
CD                        SECTION RECORD  -
CD                        =1,  FISSION DATA PRESENT IN PRINCIPAL  -
CD                        CROSS SECTION RECORD  -

```

FIGURE V.1 SPECIFICATIONS FOR ISOTXS FILE, VERSION IV (CON'T).

CD	IALF	(N.ALPHA) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS IFIS	-
CD	INP	(N.P) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS IFIS	-
CD	IN2N	(N,2N) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS IFIS	-
CD	IND	(N,D) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS IFIS	-
CD	INT	(N,T) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS IFIS	-
CD	LTOT	NUMBER OF MOMENTS OF TOTAL CROSS PROVIDED	-
CD		IN PRINCIPAL CROSS SECTIONS RECORD	-
CD	LTRN	NUMBER OF MOMENTS OF TRANSPORT CROSS SECTION	-
CD		PROVIDED IN PRINCIPAL CROSS SECTIONS RECORD	-
CD	ISTRPD	NUMBER OF COORDINATE DIRECTIONS FOR WHICH	-
CD		COORDINATE DEPENDENT TRANSPORT CROSS SECTIONS	-
CD		ARE GIVEN. IF ISTRPD=0, NO COORDINATE DEPENDENT	-
CD		TRANSPORT CROSS SECTIONS ARE GIVEN.	-
CD	IDSCT(N)	SCATTERING MATRIX TYPE IDENTIFICATION FOR	-
CD		SCATTERING BLOCK N. SIGNIFICANT ONLY IF	-
CD		LORD(N).GT.0	-
CD		IDSCT(N)=000 + NN, TOTAL SCATTERING, (SUM OF	-
CD		ELASTIC, INELASTIC, AND (N,2N) SCATTERING	-
CD		MATRIX TERMS).	-
CD		-100 + NN, ELASTIC SCATTERING	-
CD		-200 + NN, INELASTIC SCATTERING	-
CD		-300 + NN, (N,2N) SCATTERING, ----SEE	-
CD		NOTE BELOW ----	-
CD		WHERE NN IS THE LEGENDRE EXPANSION INDEX OF THE	-
CD		FIRST MATRIX IN BLOCK N	-
CD	LORD(N)	NUMBER OF SCATTERING ORDERS IN BLOCK N. IF	-
CD		LORD(N)=0, THIS BLOCK IS NOT PRESENT FOR THIS	-
CD		ISOTOPE. IF NN IS THE VALUE TAKEN FROM	-
CD		IDSCT(N), THEN THE MATRICES IN THIS BLOCK	-
CD		HAVE LEGENDRE EXPANSION INDICES OF NN, NN+1,	-
CD		NN+2, ..., NN+LORD(N)-1	-
CD	JBAND(J,N)	NUMBER OF GROUPS THAT SCATTER INTO GROUP J,	-
CD		INCLUDING SELF-SCATTER, IN SCATTERING BLOCK N.	-
CD		IF JBAND(J,N).NE.0 THEN IJJ(J,N) MUST SATISFY	-
CD		THE RELATION 1.LE.IJJ(J,N).LE.JBAND(J,N)	-
CD	IJJ(J,N)	POSITION OF IN-GROUP SCATTERING CROSS SECTION IN	-
CD		SCATTERING DATA FOR GROUP J, SCATTERING BLOCK	-
CD		N, COUNTED FROM THE FIRST WORD OF GROUP J DATA.	-
CD		IF JBAND(J,N).NE.0 THEN IJJ(J,N) MUST SATISFY	-
CD		THE RELATION 1.LE.IJJ(J,N).LE.JBAND(J,N)	-

FIGURE V.1 SPECIFICATIONS FOR ISOTXS FILE, VERSION IV (CON'T).

```

C
CN      NOTE - FOR (N,2N) SCATTER, THE MATRIX CONTAINS TERMS.
CN      SCAT(J TO G), WHICH ARE EMISSION (PRODUCTION)-
CN      BASED, I.E., ARE DEFINED SUCH THAT MACROSCOPIC
CN      SCAT(J TO G) TIMES THE FLUX IN GROUP J GIVES
CN      THE RATE OF EMISSION (PRODUCTION) OF NEUTRONS
CN      INTO GROUP G.
C
C-----

C-----
CR      PRINCIPAL CROSS SECTIONS      (5D RECORD)
C
CL      ((STRPL(J,L),J=1,NGROUP),L=1,LTRN),
CL      1((STOTPL(J,L),J=1,NGROUP),L=1,LTOT),(SNGAM(J),J=1,NGROUP),
CL      2(SFIS(J),J=1,NGROUP),(SNUTOT(J),J=1,NGROUP),
CL      3(CHISO(J),J=1,NGROUP),(SNALF(J),J=1,NGROUP),
CL      4(SNP(J),J=1,NGROUP),(SN2N(J),J=1,NGROUP),
CL      5(SND(J),J=1,NGROUP),(SNT(J),J=1,NGROUP),
CL      6(STRPD(J,I),J=1,NGROUP),I=1,ISTRPD)
C
CW      (1+LTRN+LTOT+IALF+INP+IN2N+IND+INT+ISTRPD+2*IFIS+
CW      ICHI*(2/(ICHI+1)))*NGROUP=NUMBER OF WORDS
C
CB      FORMAT(4H 5D ,      5E12.5/(6E12.5) LENGTH OF LIST AS ABOVE
C
CD      STRPL(J,L)      PL WEIGHTED TRANSPORT CROSS SECTION
CD                        THE FIRST ELEMENT OF ARRAY STRPL IS THE
CD                        CURRENT (P1) WEIGHTED TRANSPORT CROSS SECTION
CD                        THE LEGENDRE EXPANSION COEFFICIENT FACTOR (2L+1)
CD                        IS NOT INCLUDED IN STRPL(J,L).
CD      STOTPL(J,L)      PL WEIGHTED TOTAL CROSS SECTION
CD                        THE FIRST ELEMENT OF ARRAY STOTPL IS THE
CD                        FLUX (P0) WEIGHTED TOTAL CROSS SECTION
CD                        THE LEGENDRE EXPANSION COEFFICIENT FACTOR (2L+1)
CD                        IS NOT INCLUDED ON STOTPL(J,L).
CD      SNGAM(J)          (N,GAMMA)
CD      SFIS(J)           (N,F)
CD      SNUTOT(J)          TOTAL NEUTRON YIELD/FISSION (PRESENT IF IFIS.GT.0)
CD      CHISO(J)           ISOTOPE CHI (PRESENT IF ICHI.EQ.1)
CD      SNALF(J)           (N,ALPHA) (PRESENT IF IALF.GT.0)
CD      SNP(J)             (N,P) (PRESENT IF INP.GT.0)
CD      SN2N(J)            (N,2N) (PRESENT IF IN2N.GT.0) ----SEE
CD                        NOTE BELOW----
CD      SND(J)             (N,D) (PRESENT IF IND.GT.0)
CD      SNT(J)             (N,T) (PRESENT IF INT.GT.0)
CD      STRPD(J,I)         COORDINATE DIRECTION I TRANSPORT CROSS SECTION
CD                        (PRESENT IF ISTRPD.GT.0)

```

FIGURE V.1 SPECIFICATIONS FOR ISOTXS FILE, VERSION IV (CON'T).


```

C
CN      NOTE - THE PRINCIPAL (N.2N) CROSS SECTION SN2N(J) -
CN      IS DEFINED AS THE (N.2N) REACTION CROSS SECTION, -
CN      I.E., SUCH THAT MACROSCOPIC SN2N(J) TIMES THE -
CN      FLUX IN GROUP J GIVES THE RATE AT WHICH (N.2N) -
CN      REACTIONS OCCUR IN GROUP J. tHUS, FOR (N.2,) -
CN      SCATTERING,  $SN2N(J) = 0.5 * (SUM OF SCAT(J TO G)$  -
CN      SUMMED OVER ALL G). -
C
C-----

C-----
CR      ISOTOPE CHI DATA      (6D RECORD)
C
CC      PRESENT IF ICHI.GT.1
C
CL      ((CHIISO(K,J),K=1,ICHI),J=1,NGROUP),(ISOPEC(I),I=1,NGROUP)
C
CW      NGROUP*(ICHI+1)=NUMBER OF WORDS
C
CB      FORMAT(4H 6D , 5E12.5/((6E12.5)) CHIISO
CB      FORMAT(12I6)          ISOPEC
C
CD      CHIISO(K,J)  FRACTION OF NEUTRONS EMITTED INTO GROUP J AS A
CD                   RESULT OF FISSION IN ANY GROUP, USING SPECTRUM K
CD      ISOPEC(I)    ISOPEC(I)=K IMPLIES THAT SPECTRUM K IS USED
CD                   TO CALCULATE EMISSION SPECTRUM FROM FISSION
CD                   IN GROUP I
C
C
C-----

C-----
CR      SCATTERING SUB-BLOCK    (7D RECORD)
C
CC      PRESENT IF LORD(N).GT.0
CL      ((SCAT(K,L),K=1,KMAX),L=1,LORDN)
C
CC      KMAX=SUM OVER J OF JBAND(J,N) WITHIN THE J-GROUP RANGE OF THIS
CC      SUB-BLOCK. IF M IS THE INDEX OF THE SUB-BLOCK, THE J-GROUP
CC      RANGE CONTAINED WITHIN THIS SUB-BLOCK IS
CC      JL=(M-1)*(NGROUP-1)/NSBLOCK+1 TO JU=MINO(NGROUP,JUP),
CC      WHERE JUP=M*((NGROUP-1)/NSBLOK+1).
C
CC      LORDN=LORD(N)
CC      N IS THE INDEX FOR THE LOOP OVER NSCMAX. (SEE FILE STRUCTIRE)

```

FIGURE V.1 SPECIFICATIONS FOR ISOTXS FILE, VERSION IV (CON'T).

```

C
CD      SCAT(K,L)      SCATTERING MATRIX OF SCATTERING ORDER L. FOR
CD                        REACTION TYPE IDENTIFIED BY IDSCT(N) FOR THIS
CD                        BLOCK. JBAND(J,N) VALUES FOR SCATTERING INTO
CD                        GROUP J ARE STORED AT LOCATIONS K=SUM FROM 1
CD                        TO (J-1) OF JBAND(J,N) PLUS 1 TO K-1+JBAND(J,N).
CD                        THE SUM IS ZERO WHEN J=1. J-TO-J SCATTER IS
CD                        THE IJJ(J,N)-TH ENTRY IN THE RANGE JBAND(J,N).
CD                        VALUES ARE STORED IN THE ORDER (J+JUP),
CD                        (J+JUP-1),..., (J+1), J, (J-1), ..., (J-JDN),
CD                        WHERE JUP=IJJ(J,N)-1 AND JDN=JBAND(J,N)-IJJ(J,N)-
C
C-----

```

FIGURE V.1 SPECIFICATIONS FOR ISOTXS FILE, VERSION IV (CON'T).

V.1.1 Example of ISOTXS File.

The first example of an ISOTXS file is shown as Figure V.1.1. This file was input through the LASIP-III Input Processor, which reads files in ASCII or BCD in free format, and produces the corresponding sequential binary standard interface file.

The first line of this file substitutes for the file identification when utilizing the Input Processor. The "0V" before the name ISOTXS indicates that subsequent data is to form a new version of the file. If an "NV" were used here instead, the file for version number "N" would be overlaid with the subsequent data. The user identification is automatically applied by the Input Processor as "LASIP - III".

The second line is the 1D record . All data records are preceded by the number associated with the record when inputting in ASCII through the Input Processor. This record indicates the following (see Figure 2): The number of groups in the file is 3; the number of isotopes, 3; no upscatter; the maximum number of downscatter groups is 1; the maximum order of scatter, 0; a file wide fission spectrum vector is to be used; the maximum number of scattering blocks is 1; the subblocks per scattering block is 1, i.e., the same as the scattering block.

The 2D record follows: The file identification is "CITATION MACROS TO MICROS"; the isotope labels are "ZONE1", "ZONE2", and "ZONE3"; the fission spectrum vector for the three groups is 0.6, 0.4, and 0; the average velocity of each of the three groups is not used and set to 0; the maximum energy bound of each of the three groups is not required and set to 0, as is the lowest energy for the cross section set; the number of records to be skipped to start reading data for the first isotope is 0, for the second isotope, 3, and for the final isotope, 6.

Problems have arisen in the past in applying the Input Processor methods to alphanumeric records such as those included in the 2D and 4D data of an ISOTXS interface file. The first record under 2D, HSETID(I), is the Hollerith identification of the file. The specified method for titles and identification records is to include them between asterisks written in columns one and 72. The second record under 2D data includes isotope labels, written in A6 format. Suppose Uranium-235, Plutonium-239 and Sodium are included. The record may be written as follows:

```

*U235-A* *PU239 * *NA      *      (method 1, preferred)
6HU235-A 5HPU239 2HNA      (method 2)
U235A PU239 NA      (method 3)

```

Note that U235-A is not permitted under method 3 because of the imbedded minus (-) sign.

Alternatives are:

```

*U235-APU239 NA      *      (method 1)
14HU235-APU239 NA      (method 2)

```

Thus, although the specified text format for the isotope names in the 2D Record, shown as the "CB" line in Figure 2, is (1X,A6), the Input Processor will not accept minus signs (-), plus signs (+), blanks, commas, dollar signs, asterisks or apostrophe's within these names if written as A6. The best method is to include these names within asterisks as shown in the example file of Figure 3.

There is no 3D record, since a fission spectrum matrix was not specified in the File Control (1D) record.

The 4D record containing the isotope control and group independent data for the isotope labeled "ZONE1" follows: In this case "ZONE1" is used for the isotope label, the library identifier, and the material number. The atomic weight is not used and is set to zero. The watt-sec per fission is set to unity, (note: VENTURE assigns the value 3.2×10^{-11} when the watt-sec per fission is input as unity), and the watt-sec per capture is set to zero. The isotopic temperature, potential resonance integral, and the density of the isotope in the mixture in which the isotopic cross sections were generated were also set to zero, since they are not required for the problem. The isotope classification was set to "undefined", or 0. The isotope fission spectrum flag was set to 1, indicating that an isotopic chi vector is used. The fission cross section flag is 1, indicating that fission data is present in the principal cross section record for this isotope. Five zero's follow, indicating that the charged particle out cross sections are not given in the principal cross section record. The number of moments for the total and transport cross sections is one each. No coordinate dependent transport cross sections are given. The scattering matrix type applies to the total scattering cross section, only (there is only one scattering block). The number of scattering orders is one, and is P_0 . The number of groups that scatter into group 1 is 1, group 2 is 2, and group 3 is 2. These include self scatter. The position of the self scattering cross section is the first for each group (i.e., there is no upscatter).

The 5D record contains the principal cross sections for the first isotope labeled ZONE1. This includes the three transport cross sections for each group, the total cross sections for each group, the capture cross sections, the fission cross sections, the fission yields, and the isotopic chi data.

There is no 6D record, since there is no isotopic fission spectrum matrix.

The 7D record contains the scattering matrix for the ZONE1 isotope. There is no self scattering or scattering down in group 1, i.e., these cross sections have the value zero. There is self scattering in group 2, but no downscattering, and self scattering in group 3 occurs. In the File Control (1D) record, only 1 downscatter group was specified.

The 4D, 5D and 7D records are repeated for the remaining two isotopes. Neither of these isotopes are fissile, as indicated by the zero for the eleventh and twelfth entries in the 4D record. Therefore, there are no fission cross sections in the 5D record, no fission yield data, and no fission spectrum data. There are three transport cross sections, three total cross sections, and three capture cross sections, one for each of the three groups, and no other cross section data in the 5D record. The scattering matrices for these isotopes are similar to that of the first isotope, i.e., the self scatter and scattering down from group 1 are zero, as is the scattering down from group 2. Only the self scatter in groups two and three are non-zero.

```

OV ISOTXS
1D  3  3  0  1  0  1  1  1
2D/
*CITATION MACROS TO MICROS
*ZONE1* *ZONE2* *ZONE3* 0.6 0.4 0.0 0.0 3R 0.0 4R 0 3 6
4D (*ZONE1) 3R 0.0 1.0 0.0 4R 0 1 1 0 5R 1 1 0
  0  1  1 2 2  1 1 1
5D 1.987677-1 3.833180-1 9.962149-1 0.0 3R
  0.0 2.864-2 1.132-1 0.0 8.0-14 1.0-12
  0.0 9.4375+10 1.088+11 0.6 0.4 0.0
7D 0.0 0.0 4.378-2 0.0 4.295-2
4D (*ZONE2*) 3R 0.0 6R 0 8R 1 1 0
  0  1  1 2 2  1 1 1
5D 1.8205-1 2.745745-1 3.333333-1 0.0 3R
  1.3-2 8.0-3 0.0
7D 0.0 0.0 4.3-3 0.0 2.5-3
4D (*ZONE3*) 3R 0.0 6R 0 8R 1 1 0
  0  1  1 2 2  1 1 1
5D 2.438403-1 3.261500-1 5.048977-1 0.0 3R
  0.0 2.9-3 7.16-3
7D 0.0 0.0 2.016-2 0.0 1.392-2

```

*

Figure V.1.1 Example of ISOTXS File.

V.1.2 Second Example of ISOTXS File

A second example of an ISOTXS file is shown in Figure V.1.2. This file follows the text format specified in the file specifications, i.e., the format given on the lines which begin with "CB". Although this file can be read by the Input Processor, it was not explicitly written for the Input Processor. It is a formatted file, and not written as free format, as is the case with data supplied to the Input Processor.

The file identification is given as "0V ISOTXS", the user identification is enclosed in asterisks and specified as *ANISN XS*, in 2A6 format between the asterisks. The version number is "1" in I6 format.

The 1D Record indicates 4 energy groups, 2 isotopes, no upscatter, downscatter to the next adjacent group, a maximum scattering order of zero, a file wide chi vector is to be used, and there is one scattering block and one subblock.

The 2D Record identifies the file as "diffusion sample problem from egg-pbs-6821". The file identification is continued on the next line with 6 letters between asterisks. In this case the letters are blanks. The isotope labels in (1X,A6) format are "A1" and "A2". This is followed by the 4 group fission spectrum vector, on the next line. All mean velocities are not required and set to unity, and the 4 group maximum energies are not applicable and set to zero. The lowest energy bound in the data is also set to zero. No records are to be skipped to read the data for the first isotope, while three records should be skipped to read the data for the second isotope, i.e., the following 4D, 5D, and 7D records.

There is no 3D Record since ICHIST in the 1D Record was not greater than unity.

The 4D Record for the first isotope indicates an absolute label of "A1", an identifier as "ANISN", and a material number specified as "A1". The gram atomic weight is taken as zero. The yield per fission is 0.32×10^{-10} watt-sec, indicating that A1 is a fissionable isotope. The energy yield from capture, the isotope temperature, the average potential scattering cross section in the resonance range, and the density of the isotopes in the mixture in which the cross sections were generated, were all set to zero. The isotope classification was set to "undefined" or zero. The isotope fission flag was input as zero, indicating a file wide fission spectrum is to be used. The parameter IFIS is set to unity, indicating that fission data is present in the principal cross section record. The (n,alpha), (n,p), (n,2n), (n,D), and (n,T) cross sections were input as zero. There is one total cross section moment, and one transport cross section moment. No coordinate dependent transport cross sections are given. The scattering matrix

is for the total scattering cross section. There is one scattering order in the scattering block. The number of groups that scatter into group 1 is 1, i.e., the self scatter. The number of groups that scatter into groups 2, 3, and 4, including self scatter, are two each, since the maximum number of downscatter groups is 1. The position of the in-group scattering cross section in each of the four groups is one, since there is no upscatter.

The 5D Record gives the principal cross sections. The transport cross section for each of the four groups is given first, followed by the four total cross sections, which in this case is the same as the transport cross sections. (In some instances, the transport cross section is used in place of the total cross section to account for linear anisotropic scattering). These are followed by four capture gamma cross sections, one for each group, four fission cross sections, and four fission yields, which is 2.437 neutrons per fission for each group.

There is no 6D Record, since there is no isotopic fission spectrum matrix.

The 7D Record contains the scattering block, which includes the following 7 values:

$$\sigma_{s,0}^{1-1}, \sigma_{s,0}^{1-2}, \sigma_{s,0}^{2-2}, \sigma_{s,0}^{2-3}, \sigma_{s,0}^{3-3}, \sigma_{s,0}^{3-4}, \sigma_{s,0}^{4-4}$$

These values are consistent with the JBAND values given in the 4D Record.

Similar data is repeated for the second isotope, "A2". Although the data for this isotope indicated fission cross sections were present, the fission cross sections were input as zero's.


```

OV ISOTXS * ANISN      XS*      1
1D      4      2      0      1      0      1      1      1
2D *diffusion sample problem from egg-pbs-6821
*      *      A1      A2
7.37600E-01 2.62200E-01 2.00000E-04 0.00000E-01
1.00000E+00 1.00000E+00 1.00000E+00 1.00000E+00 0.00000E-01 0.00000E-01
0.00000E-01 0.00000E-01 0.00000E-01
      0      3
4D      A1      ANISN      A1
0.00000E+00 0.32000E-10 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
      0      0      1      0      0      0      0      0      1      1      0      0
      1      1      2      2      2      1      1      1      1
5D 1.36110E-01 2.71620E-01 3.09670E-01 8.85350E-01 1.36110E-01
2.71620E-01 3.09670E-01 8.85350E-01 2.99134E-04 2.86477E-04 8.35442E-03
7.79390E-02 3.99467E-04 4.73123E-04 7.20558E-03 9.76611E-02 2.43700E+00
2.43700E+00 2.43700E+00 2.43700E+00
7D 7.71700E-02 2.04420E-01 5.82400E-02 2.36590E-01 6.64420E-02
7.09750E-01 5.75180E-02
4D      A2      ANISN      A2
0.00000E+00 0.32000E-10 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
      0      0      1      0      0      0      0      0      1      0      0      0
      1      1      2      2      2      1      1      1      1
5D 2.05250E-01 5.03520E-01 6.66666E-01 9.66740E-01 2.05250E-01
5.03520E-01 6.66666E-01 9.66740E-01 7.30000E-03 1.00000E-04 1.00000E-04
3.50000E-03 0.00000E-01 0.00000E-01 0.00000E-01 0.00000E-01 2.43700E+00
2.43700E+00 2.43700E+00 2.43700E+00
7D 1.43250E-01 4.58920E-01 6.93000E-02 6.30160E-01 4.45000E-02
9.63240E-01 3.64000E-02

```

Figure V.1.2 Second Example of ISOTXS File

V.2 GRUPXS-IV Group Ordered Microscopic Cross Section File

The GRUPXS standard interface file provides a group library ordered by group, rather than isotope, for use in multigroup analysis. All of the isotopic cross sections in a given problem are listed for group one, and then repeated for each succeeding group. Thus, unlike the ISOTXS file, sums are taken over isotopes for each group, instead of over groups for each isotope. The records in the file pertaining to a specified group are repeated for each group. In addition to the File Name, File Structure and File Identification sections, the following data are included:

- 1D Record - File Control data
- 2D Record - File Data
- 3D Record - File wide Fission Spectrum Matrix data
- 4D Record - Isotope Control and Group Independent data
- 5D Record - Principal Cross Sections for a given group
- 6D Record - Isotopic Fission Spectra Matrix data
- 7D Record - Scattering Control Record
- 8D Record - Scattering Block Data for a given group

The specifications for the GRUPXS file are shown in Figure V.2.

As indicated in the File Name section, the latest revision of the GRUPXS file, i.e., version IV, occurred 11/30/76. The File Structure section shows that the File Identification, File Control, i.e., the 1D Record, and the File Data, i.e., the 2D Record, are always present. The file wide fission spectrum data depends on the parameter ICHIST, which must be greater than unity for such information to be given. The Isotope Control and Group Independent Data, the 4D Record, is always present. The Principal Cross Sections are given in the 5D Record, which is repeated for each group. If isotopic fission spectral data are specified, it is given next in the 6D record, and repeated over all necessary isotopes. The scattering control data followed by the scattering matrices, are then repeated over all groups.

The File Identification is the first record written on the file, and includes the file name, user identification, and version number.

The File Control or 1D Record records the following data: the number of groups, NGROUP; the number of isotopes, NISO; the maximum number of upscatter groups, MAXUP; the maximum number of downscatter groups, MAXDN; the maximum scattering order, MAXORD; the file wide fission spectrum flag, ICHIST; the length of the principal cross section records, NPSCS; the number of coordinate directions for which the transport cross sections are given, NSTRPD; the number of isotopes for which there are isotopic fission spectrum data, NCHIN; the number of spectra associated with isotopic fission, NICH1; the maximum number of scattering blocks,

NSCMAX; the number of records per scattering block, NSBLOK; and two reserved parameters.

The File Data or 2D Record includes: the title of the cross section set, (HSETID(I), I=1,12); the isotope labels, (HISONM(I), I=1,NISO); the fission spectrum flag for each group of data, (CHI(J), J=1,NGROUP); the average velocity for each group, (VEL(J), J=1,NGROUP); the maximum energy for each group, (EMAX(J), J=1,NGROUP), and the minimum energy for the cross section set, EMIN.

If file wide fission spectral data was specified in the 1D record, it is given in the 3D record. The spectrum used for each group is specified in this data. The format for this record is ((CHI(K,J), K=1, ICHIST), J=1, NGROUP), (ISSPEC(I), I=1, NGROUP). Here, CHI(K,J) is the fraction of neutrons emitted in group J, when using spectrum K. The number of spectra available is given by ICHIST. When ISSPEC(I)=K, the emission spectrum used for group I is spectrum K.

The Isotope Control and Group Independent Data are given in the 4D Record. This record first sets the isotope label, for each isotope in the set, (HABSID(I), I=1,NISO). The identifier for each isotope is then given, which could be the ENDF number, (HIDENT(I), I=1,NISO). The material reference for each isotope is then given, (HMAT(I), I=1,NISO), followed by the gram atomic weight of each isotope, (AMASS(I), I=1,NISO). The thermal energy yield per fission is then given for each isotope, (EFISS(I), I=1,NISO), followed by the thermal energy yield per capture, (ECAPT(I), I=1,NISO). A set of reserved parameters for each isotope is then provided, (XN(I), I=1,NISO). The temperature, (TEMP(I), I=1,NISO), the average effective potential scattering in the resonance range in barns per atom, (SIGPOT(I), I=1,NISO), and the density of the isotope in the mixture in which the cross sections were generated, (ADENS(I), I=1,NISO), are then given for each isotope. The isotopic classification for each isotope is then supplied, (KBR(I), I=1,NISO). These classifications include: Undefined; Fissile; Fertile; Other Actinide; Fission Product; Structure; Coolant; and Control. The scattering matrix type identification is then given for each scattering block, (IDSCT(N), N=1, NSCMAX). These types include total, elastic, inelastic, and (N,2N) scattering. The next parameter defines the number of scattering orders in scattering block N, (LORD(N), N=1, NSCMAX). The isotopic fission spectrum flag, (ICHI(I), I=1,NISO) is then supplied. The charged particle out and (N,2N) cross sections, IALF, INP, IN2N, IND, and INT are then given. The record is completed with two reserved parameters, IX and IY.

The principal cross sections are provided in the 5D Record. These cross sections are given for all the isotopes in a group. The 5D record must then be repeated for the number of groups specified in the 1D Record. The transport cross sections for each isotope

and each order, ((STRPL(I,L),I=1,NISO),L=1,MAXT) are listed first. Here, MAXT is MAXORD+1, so if higher Legendre components are used, they are then listed for each isotope. Next, the total cross section is listed in a similar manner, ((STOTPL(I,L),I=1,NISO),L=1,MAXT). No other cross sections listed in the 5D record have higher order Legendre components. The capture cross sections, (SNGAM(I),I=1,NISO), fission cross sections, ((SFIS(I),I=1,NISO), and neutron yield per fission, (SNUTOT(I),I=1,NISO), are then listed for each isotope. This is followed by the isotope fission spectrum vector for each isotope in the group, (CHISO(I),I=1,NISO). The charged particle out and (N,2N) cross sections are listed next, (SNALF(I),I=1,NISO), (SNP(I),I=1,NISO), (SN2N(I),I=1,NISO), (SND(I),I=1,NISO), (SNT(I),I=1,NISO). If coordinate direction transport cross sections are used, they are then listed for each isotope, for each direction, ((STRPD(I,J),I=1,NISO),J=1,NSTRPD).

If an isotopic fission spectrum matrix is specified, it is listed in the 6D Record. The format is ((CHISI(K,J),K=1,ICHI(I)),J=1,NGROUP), (ISOPEC(I),I=1,NGROUP), where CHISI(K,J) is the fraction of neutrons emitted in group J as a result of fission in any group using spectrum K, and ISOPEC(I)=K indicates that spectrum K is used to calculate the emission spectrum from fission in group I.

The Scattering Control Record is listed in the 7D Record. This includes the scattering bandwidth for each isotope and each scattering order, ((JBAND(I,N),I=1,NISO),N=1,NSCMAX), and the position of the self scattering cross section for each isotope and scattering order, ((IJJ(I,N),I=1,NISO),N=1,NSCMAX).

The 8D Record contains the scattering matrices. This includes the scattering from other groups into the group being listed, for all the isotopes in succession. For example, suppose that group 3 is being listed with two upscatter and two downscatter groups. The listing would appear as follows:

$$\begin{array}{ccccc}
\sigma_{s,0,1}^{5-3} & \sigma_{s,0,1}^{4-3} & \sigma_{s,0,1}^{3-3} & \sigma_{s,0,1}^{3-4} & \sigma_{s,0,1}^{3-5} \\
\sigma_{s,0,2}^{5-3} & \sigma_{s,0,2}^{4-3} & \sigma_{s,0,2}^{3-3} & \sigma_{s,0,2}^{3-4} & \sigma_{s,0,2}^{3-5} \\
\sigma_{s,0,3}^{5-3} & \sigma_{s,0,3}^{4-3} & \sigma_{s,0,3}^{3-3} & \sigma_{s,0,3}^{3-4} & \sigma_{s,0,3}^{3-5}
\end{array}$$

The matrix shown is for three isotopes, with no higher order Legendre moments. The first subscript identifies the cross section as scattering, the second subscript identifies the scattering order, and the third subscript identifies the isotope. If higher scattering orders were included, the matrix would be repeated for each order. For P_1 scattering, for example, the matrix would be repeated with the second subscript set to unity. The format is ((SCAT(K,L),K=1,KMAX),L=1,LORDN), where KMAX is the sum of the isotopic bandwidths.

```

C*****
C          REVISED 11/30/76
C
CF          GRUPXS-IV
CE          MICROSCOPIC GROUP NEUTRON CROSS SECTIONS
C
CN          THIS FILE PROVIDES A BASIC BROAD GROUP
C          LIBRARY, ORDERED BY GROUP
C
C*****

C-----
CS          FILE STRUCTURE
CS
CS          RECORD TYPE          PRESENT IF
CS          RECORD TYPE          PRESENT IF
CS          FILE IDENTIFICATION    ALWAYS
CS          FILE CONTROL            ALWAYS
CS          FILE DATA              ALWAYS
CS          SET CHI DATA           ICHIST.GT.1
CS          ISOTOPE CONTROL AND GROUP
CS          INDEPENDENT DATA      ALWAYS
CS          ***** (REPEAT OVER ALL ENERGY GROUPS)
CS          *      PRINCIPAL CROSS SECTIONS    ALWAYS
CS          *****
CS          ***** (REPEAT OVER NISO ISOTOPES) NCHIN.GT.0
CS          *      ISOTOPE CHI DATA           ICHI(I).GT.1
CS          *****
CS          ***** (REPEAT OVER ALL ENERGY GROUPS)
CS          *      SCATTERING CONTROL          ALWAYS
CS          *      ***** (REPEAT TO NSCMAX SCATTERING BLOCKS)
CF          * * ***** (REPEAT FROM 1 TO NSBLOK)
CS          * * * SCATTERING SUB-BLOCK        LORD(N).GT.0
CS          *****
C
C-----

```

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV.

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2).IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - GRUPXS - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                      1 - A6 WORD IS SINGLE WORD
CD                      2 - A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR      FILE CONTROL          (1D RECORD)
C
CL      NGROUP,NISO,MAXUP,MAXDN,MAXORD,ICHIST,NPSCS,NSTRPD,NCHIN,NICHI,
CL      NSCMAX,NSBLOK,NRG,NRH
C
CW      14 = NUMBER OF WORDS
C
CD      NGROUP         NUMBER OF ENERGY GROUPS IN SET
CD      NISO           NUMBER OF ISOTOPES IN SET
CD      MAXUP          MAXIMUM NUMBER OF UPSCATTER GROUPS
CD      MAXDN          MAXIMUM NUMBER OF DOWNSCATTER GROUPS
CD      MAXORD         MAXIMUM SCATTERING ORDER (MAXIMUM VALUE OF
CD                      LEGENDRE EXPANSION INDEX USED IN FILE)
CD      ICHIST         SET FISSION SPECTRUM FLAG
CD                      1 - SET FISSION SPECTRUM VECTOR
CD                      .GT.1- NUMBER OF SPECTRA FOR RANGES IN
CD                      INCIDENT ENERGY DEPENDENT CHI
CD      NPSCS          LENGTH OF THE PRINCIPAL CROSS SECTION RECORDS
CD      NSTRPD         NUMBER OF COORDINATE DIRECTIONS FOR WHICH
CD                      TRANSPORT CROSS SECTIONS ARE GIVEN, .LE.3
CD      NCHIN          NUMBER OF ISOTOPES FOR WHICH THERE ARE INCIDENT
CD                      ENERGY DEPENDENT CHI DATA
CD      NICHI          NUMBER OF INCIDENT ENERGY SPECTRA FOR ISOTOPE CHI-
CD                      DATA (MAXIMUM)
CD      NSCMAX         MAXIMUM NUMBER OF BLOCKS OF SCATTERING DATA
CD                      FOR EACH GROUP SCATTERED INTO - CAN BE THE
CD                      NUMBER OF TYPES OF SCATTERING FOR WHICH THERE-
CD                      ARE DATA.
CD      NSBLOK         BLOCKING CONTROL FOR SCATTERING MATRICES. THE
CD                      SCATTERING DATA ARE BLOCKED INTO NSBLOK
CD                      RECORDS PER SCATTERING BLOCK.

```

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV. (CON'T.)

```

CD      NRG      RESERVED      -
CD      NRH      RESERVED      -
C      -
C-----
C-----
CR      FILE DATA      (2D RECORD)      -
C      -
CL      (HSETID(I),I=1,12),(HISONM(I),I=1,NISO),      -
CL      (CHI(J),J=1,NGROUP),(VEL(J),J=1,NGROUP),      -
CL      (EMAX(J),J=1,NGROUP),EMIN      -
C      -
CW      3*NGROUP+MULT*(NISO+12)+1=NUMBER OF WORDS      -
C      -
CD      HSETID(I)      HOLLERITH IDENTIFICATION OF SET (A6)      -
CD      HISONM(I)      HOLLERITH ISOTOPE LABEL FOR ISOTOPE I (A6)      -
CD      CHI(J)      SET FISSION SPECTRUM      -
CD      VEL(J)      MEAN NEUTRON VELOCITY IN GROUP J (CM/SEC)      -
CD      EMAX(J)      MAXIMUM ENERGY BOUND OF GROUP J (EV)      -
CD      EMIN      MINIMUM ENERGY BOUND OF SET (EV)      -
C      -
C-----
C-----
CR      SET CHI DATA      (3D RECORD)      -
C      -
CC      PRESENT IF ICHIST.GT.1      -
C      -
CL      ((CHII(K,J),K=1,ICHIST),J=1,NGROUP),(ISSPEC(I),I=1,NGROUP)      -
C      -
CW      NGROUP*(ICHIST+1)=NUMBER OF WORDS      -
C      -
CD      CHII(K,J)      FRACTION OF NEUTRONS EMITTED IN GROUP J AS A      -
CD      RESULT OF FISSION IN ANY GROUP USING SPECTRUM K      -
CD      ISSPEC(I)      ISSPEC(I)=K IMPLIES THAT SPECTRUM K IS USED TO      -
CD      CALCULATE EMISSION SPECTRUM FROM FISSION IN      -
CD      GROUP I      -
C      -
C-----

```

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV. (CON'T.)


```

C-----
CR      ISOTOPE CONTROL AND GROUP INDEPENDENT DATA   (4D RECORD)   -
C
CL      (HABSID(I),I=1,NISO),(HIDENT(I),I=1,NISO),(HMAT(I),I=1,NISO). -
CL      (AMASS(I),I=1,NISO). -
CL      (EFISS(I),I=1,NISO),(ECAPT(I),I=1,NISO),(XN9I),I=1,NISO), -
CL      (TEMP(I),I=1,NISO),(SIGPOT(I),I=1,NISO),(ADENS(I),I=1,NISO), -
CL      (KBR(I),I=1,NISO),(IDSCT(N),N=1,NSCMAX),(LORD(N),N=1,NSCMAX), -
CL      (ICHI(I),I=1,NISO),IALF,INP,IN2N,IND,INT,IX,IY -
C
CW      NISO*(3*MULT+9)+2*NSCMAX+7=NUMBER OF WORDS -
C
CD      HABSID(I)      HOLLERITH ABSOLUTE ISOTOPE LABEL (A6) -
CD      HIDENT         IDENTIFIER, USUALLY ENDF NUMBER (A6) -
CD      HMAT(I)        MATERIAL REFERENCE FOR IDENTIFICATION (A6) -
CD      AMASS(I)       GRAM ATOMIC WEIGHT -
CD      EFISS(I)       TOTAL THERMAL ENERGY YIELD/FISSION (W.SEC/FISS) -
CD      ECAPT(I)       THERMAL ENERGY YIELD PER CAPTURE (W.SEC/CAP) -
CD      XN(I)          RESERVED -
CD      TEMP(I)        ISOTOPE TEMPERATURE (DEGREES KELVIN) -
CD      SIGPOT(I)      AVERAGE EFFECTIVE POTENTIAL SCATTERING IN -
CD                      RESONANCE RANGE (BARNS/ATOM) -
CD      ADENS(I)       DENSITY OF ISOTOPE IN MIXTURE IN WHICH ISOTOPE -
CD                      CROSS SECTIONS WERE GENERATED (A/BARN/CC) -
CD      KBR(I)         ISOTOPE CLASSIFICATION -
CD                      0=UNDEFINED -
CD                      1=FISSILE -
CD                      2=FERTILE -
CD                      3=OTHER ACTINIDE -
CD                      4=FISSION PRODUCT -
CD                      5=STRUCTURE -
CD                      6=COOLANT -
CD                      7=CONTROL -
CD      IDSCT(N)       SCATTERING MATRIX TYPE IDENTIFICATION FOR -
CD                      SCATTERING BLOCK N. SIGNIFICANT ONLY IF -
CD                      LORD(N).GT.0 -
CD                      IDSCT(N)=000+NN, TOTAL SCATTERING (SUM OF -
CD                      ELASTIC, INELASTIC, AND (N,2N) SCATTERING) -
CD                      =100 + NN, ELASTIC SCATTERING -
CD                      =200 + NN, INELASTIC SCATTERING -
CD                      =300 + NN, (N,2N) SCATTERING,----SEE -
CD                      NOTE BELOW---- -
CD                      WHERE NN IS EXPANSION ORDER OF BLOCK N DATA, -
CD                      DATA ORDERED BY INCREASING EXPANSION ORDER -
CD                      FOR EACH OF THE TYPES IN THE ABOVE ORDER -

```

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV. (CON'T.)

CD	LORD(N)	NUMBER OF SCATTERING ORDERS IN BLOCK N. IF	-
CD		LORD(N)=0. THIS BLOCK IS NOT PRESENT FOR THIS	-
CD		ISOTOPE BLOCK. IF NN IS THE VALUE TAKEN FROM	-
CD		IDSCT(N). THEN THE MATRICES IN THIS BLOCK	-
CD		HAVE LEGENDRE EXPANSION INDICES OF NN,NN+1,	-
CD		,LORD(N)	-
CD	ICHI(I)	ISOTOPE FISSION SPECTRUM FLAG	-
CD		0 - USE SET CHI	-
CD		1 - ISOTOPE CHI VECTOR	-
CD		.GT.1 - NUMBER OF SPECTRA FOR RANGES IN INCIDENT	-
CD		ENERGY DEPENDENT CHI	-
CD	IALF	(N,ALPHA) CROSS SECTION FLAG	-
CD		IALF=1, (N,ALPHA) DATA IN THE FILE	-
CD		IALF=0, NO (N,ALPHA) DATA IN THE FILE	-
CD	INP	(N,P) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	IN2N	(N,2N) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	IND	(N,D) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	INT	(N,T) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	IX	RESERVED	-
CD	IY	RESERVED	-
C			-
CN		NOTE - FOR (N,2N) SCATTER, THE MATRIX CONTAINS	-
CN		TERMS, SS(G TO J), WHICH ARE EMISSION	-
CN		(PRODUCTION) - BASED, I.E., ARE DEFINED SUCH	-
CN		THAT MACROSCOPIC SS(G TO J) TIMES THE FLUX IN	-
CN		GROUP G GIVES THE RATE OF EMISSION (PRODUCTION)-	-
CN		OF NEUTRONS INTO GROUP J.	-
C			-
C			-

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV. (CON'T.)

```

C-----
CR          PRINCIPAL CROSS SECTIONS      (5D RECORD)      -
C                                                    -
CL          ((STRPL(I,L),I=1,NISO),L=1,MAXT).              -
CL          ((STOTPL(I,L),I=1,NISO),L=1,MAXT),(SNGAM(I),I=1,NISO). -
CL          (SFIS(I),I=1,NISO),(SNUTOT(I),I=1,NISO),        -
CL          (CHISO(I),I=1,NISO),(SNALF9I,I=1,NISO),          -
CL          (SNP(I),I=1,NISO),(SN2N(I),I=1,NISO),            -
CL          (SND(I),I=1,NISO),(SNT(I),I=1,NISO),             -
CL          ((STRPD(I,J),I=1,NISO),J=1,NSTRPD)              -
C                                                    -
CW          NPSCS=NISO*(2*MAXT+4+IALF+INP+IN2N+IND+INT+NSTRPD)=NUMBER -
CW          OF WORDS                                         -
C                                                    -
CD          STRPL(I,L)    PL WEIGHTED TRANSPORT CROSS SECTIONS -
CD                        THE LEGENDRE EXPANSION COEFFICIENT FACTOR (2L+1)-
CD                        IS NOT INCLUDED IN STOTPL(I,L)      -
CD          SNGAM(I)      (N,GAMMA) CROSS SECTION            -
CD          SFIS(I)       (N,FISSION) CROSS SECTION          -
CD          SNUTOT(I)     TOTAL NEUTRON YIELD/FISSION         -
CD          CHISO(I)      ISOTOPE CHI VECTOR                  -
CD          SNALF(I)      (N,ALPHA)          (PRESENT IF IALF.GT.0) -
CD          SNP(I)        (N,P)              (PRESENT IF INP.GT.0) -
CD          SN2N(I)       (N,2N)             (PRESENT IF IN2N.FTO) ----SEE -
CD                        NOTE BELOW                          -
CD          SND(I)        (N,D)              (PRESENT IF IND.GT.0) -
CD          SNT(I)        (N,T)              (PRESENT IF INT.GT.0) -
CD          STRPD(I,J)    COORDINATE DIRECTION J DEPENDENT TRANSPORT CROSS -
CD                        SECTION (PRESENT IF NSTRPD.GT.0)     -
CD          MAXT          MAXORD+1              -
C                                                    -
CN                        NOTE - THE PRINCIPAL (N,2N) CROSS SECTION SN2N FOR -
CN                        A GIVEN GROUP IS THE (N,2N) REACTION CROSS -
CN                        SECTION FOR THAT GROUP, I.E., SUCH THAT -
CN                        MACROSCOPIC SN2N FOR A GIVEN GROUP TIMES THE -
CN                        GROUP FLUX GIVES THE RATE AT WHICH (N,2N) -
CN                        REACTIONS OCCUR IN THAT GROUP        -
C                                                    -
C-----

```

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV. (CON'T.)

```

C-----
CR      ISOTOPE CHI DATA    (6D RECORD)      -
C                                           -
CC      PRESENT IF NCHIN.GT.0AND ICHI(I).GT.1  -
C                                           -
CL      ((CHISI(K,J),K=1,ICHII),J=1,NGROUP),(ISOPEC(I),I=1,NGROUP) -
C                                           -
CW      NGROUP*(ICHII + 1)=NUMBER OF WORDS    -
C                                           -
CD      ICHII                =ICHI(I)         -
CD      CHISI(K,J)           FRACTION OF NEUTRONS EMITTED IN GROUP J AS A RESULT-
CD                               OF FISSION IN ANY GROUP USING SPECTRUM K      -
CD      ISOPEC(I)            ISOPEC(I)=K IMPLIES THAT SPECTRUM K IS USED TO  -
CD                               CALCULATE EMISSION SPECTRUM FROM FISSION IN  -
C                               GROUP I                                         -
C                                           -
C-----

C-----
CR      SCATTERING CONTROL    (7D RECORD)      -
C                                           -
CC      PRESENT IF LORD(N).GT.0               -
C                                           -
CL      ((SCAT(K,L),K=1,KMAX),L=1,LORDN)      -
C                                           -
CC      KMAX=SUM OVER I OF JBAND(I,N) WITHIN THE I - ISOTOPE RANGE OF THIS-
CC      SUB-BLOCK. IF M IS THE INDEX OF THE SUB-BLOCK, THE I - ISOTOPE -
CC      RANGE CONTAINED WITHIN THIS SUB-BLOCK IS                               -
CC      IL=(M-1)*((NISO-1)/NSBLOK + 1) TO IU=MINO(NISO,IUP),                  -
CC      WHERE IUP=M*((NISO-1)/NSBLOK + 1).                                     -
C                                           -
CC      LORDN = LORD(N)                                                         -
CC      N IS THE INDEX FOR THE LOOP OVER NSCMAX (SEE FILE STRUCTURE)          -
C                                           -
CW      KMAX*LORDN=NUMBER OF WORDS                                             -

```

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV. (CON'T.)

```

C
CD   SCAT(K,L)      SCATTERING MATRIX OF SCATTERING ORDER L. FOR
CD                   REACTION TYPE IDENTIFIED BY IDSCT(N) FOR THIS
CD                   BLOCK. JBAND(I) VALUES FOR SCATTERING INTO
CD                   GROUP J ARE STORED AT LOCATIONS K=SUM FROM 1
CD                   TO (I-1) OF JBAND (I) PLUS 1 TO K-1+JBAND(I).
CD                   THE SUM IS ZERO WHEN I=1. J-TO-J SCATTER IS
CD                   THE IJJ(I)-TH ENTRY IN THE RANGE JBAND(I).
CD                   VALUES ARE STORED IN THE ORDER (J+JUP),
CD                   (J+JUP-1),..., (J+1), J, (J-1),..., (J-JDN),
CD                   WHERE JUP=IJJ(I)-1 AND JDN=JBAND(I)-IJJ(I)
C
CN                   BLOCKING OVER ISOTOPES FOR EACH ORDER IS
CN                   NECESSARY IF THE DATA IS TO BE PROCESSED ONCE
CN                   SEQUENTIALLY AND THE MACROSCOPIC DATA STORED
CN                   ONE ORDER AT A TIME. IN THIS EVENT, EITHER
CN                   VALUES OF LORD(N) MUST BE LIMITED TO 1 OR
CN                   NSBLOK BE 1.
C
C-----
CEOF

```

FIGURE V.2 SPECIFICATIONS FOR GRUPXS FILE, VERSION IV. (CON'T.)

V.2.1 Example of GRUPXS File.

An example of a GRUPXS file for input to the Las Alamos Input Processor, LASIP - III, is shown in Figure V.2.1. The 1D Record indicates the following: the number of groups is 2; the number of isotopes, 3; no upscattering; the maximum number of downscatter groups is 1; the maximum scattering order is 0; a fission spectrum vector is used; the length of the principal cross section records is 18; the number of coordinate directions for which transport cross sections are given is 0, i.e., the transport cross section is not given as a function of direction; there are no isotopes with incident energy dependent chi data; there are no incident energy spectra for chi data; the maximum number of blocks of scattering data is one; there is one record per scattering block; the two reserved parameters are zero.

The 2D Record indicates that the cross section set identification is "TWO GROUP MACROS FOR THREE ZONES". The isotope labels are "FUEL", "ABS", and "MOD". The chi vector is unity for the first group, and zero for the second group. The average velocities for both groups are set to 1. The maximum group energies, and the minimum problem energy are all set to 0.

There is no 3D Record, since a fission spectrum matrix was not specified.

The 4D Record indicates the following: The isotope labels are "FUEL", "ABS", and "MOD", and these same names are used for the isotope identifier and material reference identification. The next 21 entries are set to zero. Thus, the entries between and including AMASS(I) and ADENS(I), for the three isotopes, are zero. The isotope identification for the three isotopes are set to zero. The scattering matrix type, IDSCT(N), is unity, indicating a total scattering matrix (i.e., including elastic, inelastic, and (N,2N) scattering), and no higher Legendre moments. The number of scattering orders is 1, and the remaining parameters in the record are zero, indicating no scattering out or (N,2N) cross sections.

The principal cross sections are given in the 5D Record. The first group cross sections are given in the first 5D Record. These include the three transport cross sections for each isotope, the total cross sections which are input as zero, the three capture cross sections, the three fission cross sections, the neutron yield per fission for the three isotopes, and the isotope chi vector which is zero. The 5D Record is then repeated for the second group.

There is no 6D Record, since there are no isotopic chi matrices.

The 7D and 8D Records associated with the scattering matrix are then repeated for each group. The first 7D Record indicates that the scattering band into group 1 for all three isotopes is

unity, and the position of the self scatter cross section is 1 for all three isotopes or cross section sets. The first 8D Record indicates that the self scatter cross section for each isotope in group 1 is zero. It should be noted that the scattering bandwidth includes self scatter. Thus, a scattering band of unity implies no up or down scatter. The second 7D Record applies to group 2. The band width for the first cross section set is 2, for the second 1 and for the third 2. Since there is no upscattering, this implies that the fuel scatters down to group 2, the absorber does not, and the moderator also has downscattering from group 1. Since there is no upscattering, the position of the self scatter cross section for each isotope is unity. The second 8D Record assigns a zero self scattering cross section to the fuel, a fuel downscattering cross section from group 1 as 0.01596 barns, a zero self scattering in the absorber, and a zero self scattering in the moderator, with a downscattering cross section from group 1 as 0.02838 barns.

```

OV GRUPXS
1D 2 3 0 1 0 1 18 0 0 0 1 1 0 0
2D/
* TWO GROUP MACROS FOR THREE ZONES
*FUEL * *ABS * *MOD *
1.0 0.0 1.0 2R 0.0 3R
4D (*FUEL * *ABS * *MOD *) 3R 0.0 21R 0 3R
0 1 0 10R
5D .2321263 .3052503 .2157497 0.0 3R
.0068635 .003185 .000444 .003645 0.0 2R
2.0 0.0 2R 0.0 3R
5D .8617718 .950480 1.066325 0.0 3R
.02525 .4021 .008736 .07655 0.0 2R
2.0 0.0 2R 0.0 3R
7D 1 1 1 1 1 1
8D 0.0 0.0 0.0
7D 2 1 2 1 1 1
8D 0.0 0.01596 0.0 0.0 0.02838
STOP
END

```

Figure V.2.1 Example of GRUPXS file.

V.3 CXSPRR Cross Section Processing File.

The CXSPRR file provides data for a Cross Section Processor which completes various cross section processing functions. The CXSPRR file is used to convert microscopic CITATION cross section sets to ISOTXS, to update an ISOTXS file, to merge two ISOTXS files, to produce mixture ISOTXS files, and to convert the resultant ISOTXS file to a GRUPXS file. The CXSPRR file is not required if an existing ISOTXS file is to be directly converted to a GRUPXS file. The control record XCPINS, which provides control information to the Cross Section Processor, is all that is required to convert an unaltered ISOTXS file to a GRUPXS file. The Citation cross section set must be generated on logical unit 8 by a separate processor, before it can be converted to ISOTXS. The functions completed by the Cross Section Processor are described in Figure V.3³. The GRUPXS format is required by multigroup diffusion codes, such as the VENTURE code. The XCPINS record contains some integer parameters referred to by the CXSPRR file. These integer parameters are:

- IX(3) Option on the processing of the input cross section file:
 - 0 - No processing required.
 - 1 - Create a new nuclide ordered file ISOTXS from the given file whose format is controlled by IX(5).
- IX(4) Option to generate a new group ordered file (GRUPXS) from a nuclide ordered file (ISOTXS):
 - 0 - No
 - 1 - Yes.
- IX(5) Format of the input cross sections.
 - 0 - Nuclide ordered (ISOTXS)
 - 1 - CITATION cross section sets
 - 2 - Merge two nuclide ordered (ISOTXS) files. The file control parameters NGROUP, MAXORD, ICHIST, NSCMAX, NBLOK, must be the same for both files.
- IX(11) Option to prepare isotope mixtures after completion of the processing as indicated by IX(3) and IX(5). A new nuclide ordered ISOTXS file will be written:
 - 0 - No
 - 1 - Yes (requires additional input data)
- IX(23) Option to edit ISOTXS file
 - 0 - No
 - 1 - Yes
- IX(24) Option to edit GRUPXS file
 - 0 - No
 - 1 - Yes

Note: Ver. n refers to the current latest version at that stage of processing.

Figure V.3 Calculational Modes of Cross section Processor
(from ref.3)

The CXSPRR file is shown in Figure V.3.1. In addition to the File Name, File Structure, and File Identification Sections the file includes the following:

- 1D Record - File Control
- 2D Record - Citation Cross Section Set Numbers
- 3D Record - Neutron Energy Spectrum
- 4D Record - Multipliers for Transport Cross Sections
- 5D Record - Isotope Data
- 6D Record - Isotope Names in Mixture
- 7D Record - Isotope Densities in Mixture
- 8D Record - Mixture Data

The File Structure indicates that the 1D File Control Record is always present. The 2D Record is present if the parameter NOP(1) is greater than zero. The 3D Record requires that the parameter NOP(3) be greater than zero, and the 4D Record will be present if NOP(4) is greater than zero. If NOP(5) is greater than zero, the 5D Record is repeated NOP(5) times. The 6D and 7D Records are repeated in succession NOP(6) times, and the 8D Record is then repeated NOP(6) times.

The File Control Record is the 1D Record. Twenty four intergers are input in the format (NOP(I), I=1,24). NOP(1) is the number of CITATION cross section sets to process. NOP(2) is the scattering blocking factor for a nuclide ordered file created from a CITATION cross section set. If NOP(2) is zero, the number of scattering blocks, NSBLOK, is one. If NOP(2) is equal to N, and N equals the number of groups, the number of scattering blocks equals N, i.e., one scattering block per group. NOP(3) provides an option for inputting a neutron energy spectrum. If NOP(3) is set to zero, no spectrum is to be given. If NOP(3) is set to N, the number of energy groups, an input spectrum will be given. NOP(4) provides an option for creating a direction dependent transport cross section; if 0, no direction dependent cross section is to be created, and if 1, a direction dependent transport cross section will be created. NOP(5) provides an option for overriding isotopic data. If NOP(5) is zero, no overriding of data will be done, but if set to N, N records of data will be overridden. NOP(6) is the number of mixtures required, if this option was selected with IX(11). NOP(7) is the maximum number of isotopes in any mixture. NOP(8) and NOP(9) are reserved. NOP(10) provides an option for the use of override data. If NOP(10) is 0, the override data corresponds with the order of isotopes in the file, while if 1, the isotopes are selected by a unique isotope label. NOP(11) through NOP(23) are reserved locations. NOP(24) is an option to edit during CITATION cross section processing. If set to zero, no editing will be done, and if set to unity, editing will be done.

The 2D Record provides CITATION cross section set numbers, in ascending order. It is present if NOP(1) is greater than zero. The format is (ISET(I), I=1,NOP1), where NOP1 is NOP(1).

The 3D Record provides a weighting spectrum for mixing calculations. It is present if NOP(3) is greater than zero. The format is (WGT(I), I=1,NOP3), where NOP3 is equal to NOP(3).

The 4D Record provides multipliers for each coordinate direction to produce coordinate dependent transport cross sections. The format is (TRMOD(I),I=1,3), and this record is present when NOP(4) is greater than zero.

The 5D Record is applicable when NOP(5) is greater than zero, and provides NOP(5) records of isotopic override data. When NOP(10) equals zero, the order of the override data corresponds, one-to-one, with the order of the isotopes in the input cross section file. This input may be used when IX(3) is set to unity to create a new cross section file. If HISONM, the isotope name, is set to "DELETE", the data for this isotope is not written on the new cross section file. If HISONM is not equal to "DELETE", the data for this isotope will be copied to the new nuclide ordered file. Non-blank, or non-zero data will replace the data on the new file. If after reading NOP(5) records, there are isotopes remaining on the original cross section file, they will be deleted on the new file. If NOP(10) is set to unity, the overridden data on an ISOTXS file is selected by isotope name. The order of the isotopes is not specified, since the unique label (HISONM) is used to identify isotopes copied to the new file. Non-blank or non-zero input values will be placed on the new file. The unique label cannot be changed when using this option. The input record includes HISONM, HABSID, HMAT, AMASS, EFISS, ECAPT, KBR, and 3 reserved locations (IOP(I),I=1,3). HISONM is the unique isotope label, HABSID is the absolute isotope label, HMAT is a reference isotope label, AMASS is the gram atomic weight of the isotope, EFISS is the thermal energy yield per fission, watt-sec/fission, ECAPT is the thermal energy yield per capture, w-sec/capture, and KBR is the isotope classification (i.e., fuel, moderator, coolant, structure, etc.).

The 6D Record provides the isotope names making up a mixture, when NOP(6) is greater than zero. This record and the following 7D Record appear in pairs, and includes NOP(6) pairs. The format for this record is (HISONX(I),I=1,NOP7), where NOP7 is equal to NOP(7). HISONX is the unique name of the isotope to be included in the mixture, with blank names ignored. Any isotope included in the mixture will be deleted from the new file.

The 7D Record provides the isotopic densities in a mixture. The format is (RDENS(I),I=1,NOP7).

The 8D Record provides mixture data when NOP(6) is greater than zero. There must be NOP(6) such records. The data includes: HISONM, the unique mixture label; HABSID, the absolute mixture label; HMAT, the reference mixture label; AMASS, the gram atomic weight; EFISS, the thermal energy yield per fission, watt-sec/fission; ECAPT, the thermal energy yield per capture, w-sec/capture; KBR, the mixture classification; and three reserved locations. Non-blank data should be supplied for labels, and non-zero data for KBR. AMASS, EFISS, and ECAPT are calculated for mixtures, but may be replaced by non-zero entries.

```

C*****
C          PREPARED 10/18/73
CF          CXSPRR
C
CE          DATA FOR CROSS SECTION PROCESSOR
C
CN          SEE INTERFACE FILE CONTRL, RECORD XCPINS, FOR REFERENCES
CN          TO ARRAY IX
C
C*****

C-----
CS          FILE STRUCTURE
CS
CS          RECORD TYPE          PRESENT IF
CS          -----
CS          FILE IDENTIFICATION    ALWAYS
CS          1D FILE CONTROL          ALWAYS
CS          2D CITATION SET NUMBERS  NOP(1).GT.0
CS          3D NEUTRON ENERGY SPECTRUM  NOP(3).GT.0
CS          4D TRANSPORT MULTIPLIERS      Hx  NOP(4).GT.0
CS
CS          ***** (REPEAT FROM 1 TO NOP(5))
CS          *      5D ISOTOPE DATA          NOP(5).GT.0
CS          *****
CS
CS          ***** (REPEAT FROM 1 TO NOP(6))
CS          *      6D ISOTOPE NAMES IN MIXTURE  NOP(6).GT.0
CS          *      7D ISOTOPE DENSITIES IN MIXTURE  NOP(6).GT.0
CS          *****
CS
CS          ***** (REPEAT FROM 1 TO NOP(6))
CS          *      8D MIXTURE DATA
CS          *****
C
C-----

```

Figure V.3.1 Specifications for Interface File CXSPRR

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME. (HUSE(I),I=1,2).IVERS
C
CW      3*MULT + 1 = NUMBER OF WORDS
C
CD      HNAME      HOLLERITH FILE NAME - CXSPRR - (A6)
CD      HUSE       HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS      FILE VERSION NUMBER
CD      MULT       DOUBLE PRECISION PARAMETER Hx
CD                1 - A6 WORD IS SINGLE WORD
CD                2 - A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR      1D      FILE CONTROL
C
CL      (NOP(I),I=1,24)
C
CW      24
C
CD      NOP(1)     NUMBER OF CITATION CROSS SECTION SETS TO PROCESS
CD                (IF NOP(1).EQ.0 AND IX(3).EQ.1 AND IX(5).EQ.1,
CD                SET ONE WILL BE PROCESSED)
CD      NOP(2)     SCATTERING BLOCKING FACTOR FOR NUCLIDE-ORDERED
CD                FILE CREATED FROM CITATION CROSS SECTIONS
CD                0 - NSBLOK = 1
CD                N - NSBLOK = N, IF (NGROUP/N)*N.EQ.NGROUP
CD                OTHERWISE NSBLOK = 1
CD      NOP(3)     OPTION TO INPUT A NEUTRON ENERGY SPECTRUM
CD                0 - NO
CD                1 - YES
CD      NOP(4)     OPTION TO CREATE PSEUDO DIRECTION DEPENDENT
CD                TRANSPORT DATA
CD                0 - NO
CD                1 - YES
CD      NOP(5)     OPTION TO INPUT OVERRIDE DATA FOR ISOTOPES
CD                0 - NO
CD                1 - YES
CD      NOP(6)     NUMBER OF MIXTURES (REQUIRED IF IX(11).EQ.1)
CD      NOP(7)     MAXIMUM NUMBER OF ISOTOPES IN ANY MIXTURE
CD                (REQUIRED IF IX(11).EQ.1)
CD      NOP(8-9)   RESERVED

```

Figure V.3.1 Specifications for Interface File CXSPRR (CON'T.)

```

CD      NOP(10)          OPTION ON USE OF OVERRIDE DATA FOR ISOTOPES      -
CD                               WHEN NOP(5).GT.0 (APPLICABLE ONLY WHEN      -
CD                               IX(3).EQ.1 AND IX(5).EQ.0)                  -
CD                               0 - DATA CORRESPONDS WITH THE ORDER OF      -
CD                               ISOTOPES IN THE FILE                        -
CD                               1 - DATA IDENTIFIES ISOTOPES TO BE SELECTED -
CD                               BY UNIQUE ISOTOPE LABEL                    -
CD
CD      NOP(11-23)       RESERVED                                          -
CD      NOP(24)          OPTION TO EDIT DURING CREATION CROSS SECTION      -
CD                               PROCESSING                                -
CD                               0 - NO                                     -
CD                               1 - YES                                    -
C
C-----
C-----
CR      2D      CITATION CROSS SECTION SET NUMBERS                        -
C
CC                               PRESENT IF NOP(1).GT.0                    -
C
CL      (ISET(I),I=1,NOP1)                                                -
C
CW      NOP1 = NOP(1)                                                      -
C
CD      ISET          SET NUMBERS IN ASCENDING ORDER OF APPEARANCE        -
CD                               IN LIBRARY                                -
C
C-----
C-----
CR      3D      NEUTRON ENERGY SPECTRUM                                  -
C
CC                               PRESENT IF NOP(3).GT.0                    -
C
CL      (WGT(I),I=1,NOP3)                                                -
C
CW      NOP3 = NOP(3)                                                      -
C
CD      WGT          SPECTRUM FOR WEIGHTING IN MIXTURE CALCULATION        -
C
C-----

```

Figure V.3.1 Specifications for Interface File CXSPRR (CON'T.)


```

C-----
CR      4D      MULTIPLIERS FOR TRANSPORT CROSS SECTION -
C                                             -
CC              PRESENT IF NOP(4).GT.0 -
C                                             -
CL      (TRMOD(I).I=1.3) -
C                                             -
CW      3 -
C                                             -
CD      TRMOD      MULTIPLIER FOR EACH COORDINATE DIRECTION -
CD              STRPD(I)=TRMOD*STRPL(1) FOR EACH ENERGY -
C                                             -
C-----

C-----
CR      5D      ISOTOPE DATA -
C                                             -
CC              PRESENT IF NOP(5).GT.0 -
CC              THERE MUST BE NOP(5) RECORDS -
C                                             -
CN              WHEN NOP(10).EQ.0, -
CN              THIS DATA MAY BE USED WHEN IX(3).EQ.1 TO CONTROL THE -
CN              PROCESSING OF THE INPUT CROSS SECTIONS. THE ORDER -
CN              OF THESE RECORDS MUST BE ONE-TO-ONE WITH THE ORDER -
CN              OF THE ISOTOPES IN THE INPUT CROSS SECTIONS. FOR EACH -
CN              ISOTOPE READ FROM THE INPUT CROSS SECTIONS, ONE RECORD -
CN              IS READ FROM THIS DATA. -
CN                                             -
CN              A) IF HISONM.EQ.6HDELETE, THE DATA FOR THIS ISOTOPE -
CN              IS NOT WRITTEN ON THE NEW NUCLIDE ORDERED FILE. -
CN              B) IF HISONM.NE.DELETE, THE DATA FOR THIS ISOTOPE -
CN              WILL BE COPIED TO THE NEW NUCLIDE ORDERED FILE -
CN              (NON-BLANK OR NON-ZERO DATA WILL REPLACE THE -
CN              DATA ON THE NEW FILE) -
CN              C) IF AFTER READING NOP(5) RECORDS, THERE ARE ISOTOPES -
CN              REMAINING IN THE INPUT CROSS SECTIONS, THOSE -
CN              REMAINING WILL BE DELETED FROM THE NEW FILE. -
CN                                             -
CN                                             -
CN              WHEN NOP(10).EQ.1, -
CN              THIS DATA MAY BE USED WHEN IX(3).EQ.1 AND IX(5).EQ.0 TO -
CN              CONTROL THE CONTENT OF THE NEW ISOTXS FILE. THE ORDER -
CN              OF THE RECORDS IS NOT SPECIFIED SINCE THE UNIQUE LABEL -
CN              (HISONM) IS USED TO IDENTIFY ISOTOPES TO BE COPIED TO -
CN              THE NEW FILE. NON-BLANK OR NON-ZERO VALUES FOR THE -
CN              REST OF THE DATA WILL BE PUT ON THE NEW FILE. -
CN              THE UNIQUE LABEL CANNOT BE CHANGED WHEN USING THIS OPTION. -

```

Figure V.3.1 Specifications for Interface File CXSPRR (CON'T.)

```

CN
CN      IF THIS DATA IS NOT PRESENT. ALL ISOTOPES ON THE INPUT
CN      CROSS SECTIONS WILL BE COPIED TO THE NEW FILE
C
CL      HISONM,HABSID,HMAT,AMASS,EFISS,ECAPT,KBR,(IOP(I),I=1,3)
C
CW      3*MULT + 7
C
CD      HISONM      HOLLERITH ISOTOPE LABEL (UNIQUE)      (A6)
CD      HABSID      HOLLERITH ISOTOPE LABEL (ABSOLUTE)    (A6)
CD      HMAT        HOLLERITH ISOTOPE LABEL (REFERENCE)   (A6)
CD      AMASS       GRAM ATOMIC WEIGHT
CD      EFISS       TOTAL THERMAL ENERGY YIELD/FISSION  (W.SEC/FISS)
CD      ECAPT       TOTAL THERMAL ENERGY YIELD PER CAPTURE (N,GAMMA)
CD                  (W.SEC/CAPT)
CD      KBR         ISOTOPE CLASSIFICATION
CD      IOP         RESERVED
C-----

C-----
CR      6D          ISOTOPE NAMES IN MIXTURES
C
CC              PRESENT IF NOP(6).GT.0
CC              THIS RECORD AND THE RECORD FOLLOWING APPEAR IN PAIRS
CC              THERE MUST BE NOP(6) PAIRS
C
CL      (HISONX(I),I=1,NOP7)
C
CW      MULT*NOP7=MULT*NOP(7)
C
CD      HISONX      UNIQUE NAME OF ISOTOPE TO BE INCLUDED IN MIXTURE
CD                  (BLANK NAMES ARE IGNORED)
C
CN              ANY ISOTOPE INCLUDED IN A MIXTURE WILL BE DELETED FROM THE
CN              NEW FILE
C-----

C-----
CR      7D          ISOTOPE DENSITIES IN MIXTURE
C
CC              PRESENT IF NOP(6).GT.0
C
CL      (RDENS(I),I=1,NOP7)
C
CW      NOP7=NOP(7)
C
CD      RDENS       DENSITY OF ISOTOPE TO BE INCLUDED IN MIXTURE
C-----

```

Figure V.3.1 Specifications for Interface File CXSPRR (CON'T.)

```

C-----
CR      8D      MIXTURE DATA
C
CC              PRESENT IF NOP(6).GT.0
CC              THERE MUST BE NOP(6) RECORDS
C
CL      HISONM,HABSID,HMAT,AMASS,EFISS,ECAPT,KBR,(IOP(I),I=1,3)
C
CD      HISONM      HOLLERITH MIXTURE LABEL (UNIQUE) (A6)
CD      HABSID      HOLLERITH MIXTURE LABEL (ABSOLUTE) (A6)
CD      HMAT        HOLLERITH MIXTURE LABEL (REFERENCE)
CD      AMASS        GRAM ATOMIC WEIGHT
CD      EFISS        TOTAL THERMAL ENERGY YIELD/FISSION (W.SEC/FISS)
CD      ECAPT        TOTAL THERMAL ENERGY YIELD/CAPTURE (N,GAMMA)
CD                      (W.SEC/CAPT)
CD      KBR          MIXTURE CLASSIFICATION
CD      IOP          RESERVED
C
CN              NON-BLANK DATA SHOULD BE SUPPLIED FOR LABELS
CN              AND NON-ZERO DATA FOR KBR
CN              AMASS, EFISS, AND ECAPT ARE CALCULATED FOR MIXTURE, BUT
CN Hx          MAY BE REPLACED BY NON-ZERO ENTRIES
C
C-----

C*****
C
CEOF          CXSPRR
C
C*****

```

Figure V.3.1 Specifications for Interface File CXSPRR (CON'T.)

V.3.1 Example of CXSPRR

An example of a CXSPRR file is shown in Figure V.3.2. In this example, the only non-zero entry in the 1D Record is NOP(5), which indicates that 2 records of override data will be used. The two records are shown in the 5D Record, indicating the unique isotope label for the first record overwrite is ZONE 1, and for the second record, ZONE 2. All remaining data in the 5D Record are zero's.

```

CXSPRR
1D/
0 0 0 0 2 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0
5D/
ZONE 1 0.000000E+00 0.000000E+00 0.000000E+00 0 0 0 0
ZONE 2 0.000000E+00 0.000000E+00 0.000000E+00 0 0 0 0

```

Figure V.3.2 Example of CXSPRR Interface File

V.3.2 Second Example of CXSPRR File

A second example of a CXSPRR file and its accompanying XCPINS File is shown in Figure V.3.3. The XCPINS file, as are all control files, is made up of 100 floating point numbers, and 100 integers. As shown in Figure 10, the 100 floating point numbers are all zero. The third integer, IX(3) is unity, indicating that an ISOTXS file should be created from a given microscopic cross section file. The fourth integer, IX(4) is also unity, which requires that a GRUPXS file is to be developed from an ISOTXS file. The fifth integer, IX(5) is also unity, indicating that the microscopic cross sections input are in CITATION format. Thus the control file XCPINS, requires that the Cross Section Processor convert a CITATION microscopic cross section set to an ISOTXS file, and then convert the ISOTXS file to a GRUPXS file.

The 1D Record of the CXSPRR file indicates that NOP(5) is 7, so that 7 records of data are to be overridden. These 7 records are all 5D Records, and the only change is to rename the 7 isotopes and to set the unique, absolute and reference labels of each isotope equal to each other. Thus, the only change made in the CITATION microscopic cross section set is the renaming.

```

OV CONTRL
1D XCPINS 0.0 100R 0 0 1 1 1 0 0 0 0 0 0
          0 11R 1 1 0 76R
OV CXSPRR
1D/
0 0 0 0 7 0 0 0 0 0 0 13R 0
5D *COMP1 * *COMP1 * *COMP1 * 0.0 0.0 0.0 0 0 0 0
5D *COMP2 * *COMP2 * *COMP2 * 0.0 0.0 0.0 0 0 0 0
5D *COMP3 * *COMP3 * *COMP3 * 0.0 0.0 0.0 0 0 0 0
5D *COMP4 * *COMP4 * *COMP4 * 0.0 0.0 0.0 0 0 0 0
5D *COMP5 * *COMP5 * *COMP5 * 0.0 0.0 0.0 0 0 0 0
5D *COMP19* *COMP19* *COMP19* 0.0 0.0 0.0 0 0 0 0
5D *COMP20* *COMP20* *COMP20* 0.0 0.0 0.0 0 0 0 0

```

Figure V.3.3 Second Example of CXSPRR File

VI. GEODST Geometry File.

The GEODST file provides the geometry description for a problem. It is listed as Figure VI.1. This file contains the following sections:

File Identification

- 1D Record - File Specifications
- 2D Record - One Dimensional Coarse Mesh Interval Boundaries and Fine Mesh Intervals
- 3D Record - Two Dimensional Coarse Mesh Interval Boundaries and Fine Mesh Intervals
- 4D Record - Three Dimensional Coarse Mesh Interval Boundaries and Fine Mesh Intervals
- 5D Record - Geometry Data
- 6D Record - Region Assignments to Coarse Mesh Intervals
- 7D Record - Region Assignments to Fine Mesh Intervals

The major function of the GEODST interface file is to assign the geometry, i.e., slab, sphere, R-Z, R-THETA-Z, etc., the mesh spacing, and the boundary conditions. The mesh spacing is given as a coarse mesh within which equally spaced fine mesh intervals are inserted. Providing the mesh spacing in this way has certain advantages, as for example, in applying the coarse mesh rebalancing technique for accelerating convergence. The coarse mesh is used for rebalancing.

The File Specification Record includes the following: the geometry of the problem, IGEOM, which can be selected from a total of eighteen different listed geometries, such as slab, cylinder, sphere, etc.; the number of zones, NZONE, or neutronically homogeneous volumes in the problem; the number of regions, NREG, which are volumes contained within zones; the number of zone classifications, NZCL; the number of first dimension coarse mesh intervals, NCINTI; the number of second dimension coarse mesh intervals, NCINTJ; the number of third dimension coarse mesh intervals, NCINTK; the number of fine mesh intervals for each dimension, NINTI, NINTJ, NINTK; the boundary condition for the first boundary on the first dimension, IMB1, is then given; the boundary condition for the last boundary on the first dimension, IMB2; the boundary conditions on the remaining boundaries, JMB1, JMB2, KMB1, KMB2; the number of buckling specifications for the problem, NBS; the number of constants used to define external boundary conditions, NBCS; the number of constants used to define internal boundary conditions, NIBCS; the number of zones which are black absorbers, NZWBB; a triangular/hexagonal geometry option, NTRIAG; region assignments, NRASS; orientation of first fine mesh interval in triangular geometries, NTHPT; and finally, one reserved parameter, NGOP.

The constants used to define external boundary conditions are explained by the following boundary equation:

$$\vec{n} \cdot \nabla \phi_g(\vec{R}) / \phi_g(\vec{R}) = -C/D$$

Here, C is a constant, and D is the diffusion coefficient. The flux is defined on the boundary R. For an extrapolated boundary, C/D is one over the extrapolation distance. For a large extrapolated boundary, the extrapolation distance is 0.71 times the transport mean free path. The diffusion coefficient is 1/3 of the transport mean free path. Therefore, the extrapolation distance is 2.13 times the diffusion coefficient, and C would equal the inverse of 2.13, or 0.469.

The 2D Record defines the one dimensional mesh intervals, both coarse and fine. This record applies to slab, infinite cylinder and spherical geometry, only. The coarse mesh boundaries are listed, and the number of equally spaced fine mesh intervals per coarse mesh interval are given. The format for this record is: (XMESH(I), I=1, NCBNDI), (IFINTS(I), I=1, NCINTI), where, XMESH(I) are the coarse mesh boundaries for the first dimension, NCBNDI=NCINTI+1, and IFINT(I) is the number of equally spaced fine mesh intervals for each first dimension coarse mesh interval.

The two dimensional mesh boundaries are given in the 3D record. This includes the coarse mesh boundaries in each of the two dimensions, and the number of equally spaced fine mesh intervals in each coarse mesh interval. The format for this record is: (XMESH(I), I=1, NCBNDI), (YMESH(J), J=1, NCBNDJ), (IFINTS(I), I=1, NCINTI), and (JFINTS(J), J=1, NCINTJ). The meaning of these quantities is the same as that of the 2D Record with the addition of the second dimension.

The 4D Record contains the listing for the three dimensional coarse mesh boundaries, and the number of equally spaced fine mesh intervals in each coarse mesh interval. The format, which follows naturally from the 2D and 3D Records is: (XMESH(I), I=1, NCBNDI), (YMESH(J), J=1, NCBNDJ), (ZMESH(K), K=1, NCBNDK), (IFINTS(I), I=1, NCINTI), (JFINTS(J), J=1, NCINTJ), (KFINTS(K), K=1, NCINTK).

The geometry data is given in the 5D Record. This includes the region volumes, (VOLR(N),N=1,NREG), buckling values, (BSQ(N),N=1,NBS), boundary constants, (BNDC(N),N=1,NBCS), internal black boundary constants, (BNCI(N),N=1,NIBCS), zone numbers with black absorber conditions, (NZHBB(N),N=1,NZWBB), zone classifications, (NZC(N),N=1,NZONE), and zone number assigned to each region, (NZNR(N),N=1,NREG).

The 6D record assigns regions to coarse mesh intervals. In three dimensions, these assignments are made for a plane, and then repeated over each plane in the third dimension. The format is: ((MR(I,J),I=1,NCINTI),J=1,NCINTJ).

The 7D Record assigns regions to fine mesh intervals, when this type of region assignment is specified. The assignments are made in a manner similar to that of the 6D Record. The format is: ((MR(I,J),I=1,NINTI),J=1,NINTJ).

```

C*****
C              REVISED 11/30/76
C
CF              GEODST - IV
C
CE              GEOMETRY DESCRIPTION
C
C*****

C-----
CR              FILE IDENTIFICATION  (0V RECORD)
C
CL      HNAME, (HUSE(I), I=1, 2), IVERS
C
CW      1+3*MULT
C
CD      HNAME          HOLLERITH FILE NAME - GEODST - (A6)
CD      HUSE           HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS A SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR              FILE SPECIFICATIONS  (1D RECORD)
C
CL      IGOM, NZONE, NREG, NZCL, NCINTI, NCINTJ, NCINTK, NINTI, NINTJ, NINTK, IMB1,
CL      IMB2, JMB1, JMB2, KMB1, KMB2, NBS, NBCS, NIBCS, NZWBB, NTRIAG, NRASS, NTHPT,
CL      (NGOP(I), I=1, 4)
C
CW      27
C
CD      IGOM           GEOMETRY  0- POINT (FUNDAMENTAL MODE)
CD                      1- SLAB
CD                      2- CYLINDER
CD                      3- SPHERE
CD                      6- X-Y
CD                      7- R-Z
CD                      8- THETA-R
CD                      9- UNIFORM TRIANGULAR
CD                      10- HEXAGONAL (1 MESH POINT IN EACH
CD                          HEXAGONAL ELEMENT)
CD                      11- R-THETA

```

Figure VI.1 Specifications for GEODST Geometry Interface File

CD		12- R-THETA-Z	-
CD		13- R-THETA-ALPHA	-
CD		14- X-Y-Z	-
CD		15- THETA-R-Z	-
CD		16- THETA-R-ALPHA	-
CD		17- UNIFORM TRIANGULAR-Z	-
CD		18- HEXAGON-Z (MESH POINTS AS IN 10	-
CD		ABOVE	-
CD	NZONE	NUMBER OF ZONES (EACH HOMOGENEOUS IN NEUTRONICS	-
CD		PROBLEM - A ZONE CONTAINS ONE OR MORE REGIONS)	-
CD	NREG	NUMBER OF REGIONS	-
CD	NZCL	NUMBER OF ZONE CLASSIFICATIONS (EDIT PURPOSES)	-
CD	NCINTI	NUMBER OF FIRST DIMENSION COARSE MESH INTERVALS	-
CD	NCINTJ	NUMBER OF SECOND DIMENSION COARSE COARSE MESH	-
CD		INTERVALS. NCINTJ.EQ.1 FOR ONE DIMENSIONAL	-
CD		CASE.	-
CD	NCINTK	NUMBER OF THIRD DIMENSION COARSE MESH INTERVALS	-
		NCINTK.EQ.1 FOR ONE AND TWO DIMENSION CASES	-
CD	NINTI	NUMBER OF FIRST DIMENSION FINE MESH INTERVALS	-
CD	NINTJ	NUMBER OF SECOND DIMENSION FINE MESH INTERVALS	-
CD		NINTJ.EQ.1 FOR ONE DIMENSIONAL CASE.	-
CD	NINTK	NUMBER OF THIRD DIMENSION FINE MESH INTERVALS	-
CD		NINTK.EQ.1 FOR ONE AND TWO DIMENSION CASES.	-
CD	IMB1	FIRST BOUNDARY OF FIRST DIMENSION	-
CD		0 - ZERO FLUX (DIFFUSION)	-
CD		1 - REFLECTED	-
CD		2 - EXTRAPOLATED (DIFFUSION - DEL PHI/PHI	-
CD		= -C/D WHERE C IS GIVEN AS BNDC BELOW	-
CD		AND D IS THE GROUP DIFFUSION CONSTANT.	-
CD		TRANSPORT - NO RETURN).	-
CD		3 - REPEATING (PERIODIC) WITH OPPOSITE FACE	-
CD		4 - REPEATING (PERIODIC) WITH NEXT ADJACENT	-
CD		FACE.	-
CD		5 - INVERTED REPEATING ALONG THIS FACE.	-
CD		(180 DEGREE ROTATION)	-
CD		6 - ISOTROPIC RETURN (TRANSPORT)	-
C			-
CC		NOTE FOR REPEATING CONDITIONS (3,4,5) - LET I1 DENOTE FIRST-	-
CC		BOUNDARY ON FIRST DIMENSION, I2 THE SECOND BOUNDARY ON THE	-
CC		FIRST DIMENSION, J1 THE FIRST BOUNDARY ON THE SECOND	-
CC		DIMENSION, ETC. THEN THESE REPEATING BOUNDARY CONDITIONS	-
CC		ONLY APPLY TO BOUNDARIES I1, I2, J1, AND J2, GOING IN ORDER-	-
CC		OF I1, J1, I2, J2. THE FIRST BOUNDARY WHICH IS INVOLVED	-
CC		CARRIES THE DESIGNATOR DEFINING THE REPEATING CONDITION.	-

Figure VI.1 Specifications for GEODST Geometry Interface File (Con't)

C			-
CD	IMB2	LAST BOUNDARY ON FIRST DIMENSION	-
CD	JMB1	FIRST BOUNDARY ON SECOND DIMENSION	-
CD	JMB2	LAST BOUNDARY ON SECOND DIMENSION	-
CD	KMB1	FIRST BOUNDARY ON THIRD DIMENSION	-
CD	KMB2	LAST BOUNDARY ON THIRD DIMENSION	-
CD	NBS	NUMBER OF BUCKLING SPECIFICATIONS	-
CD		0 - NONE	-
CD		1 - SINGLE VALUE APPLIES EVERYWHERE	-
CD		.EQ.NZONE - ZONE DEPENDENT	-
CD		M*NZONE - DATA IS GIVEN OVER ALL ZONES FOR	-
CD		THE FIRST ENERGY GROUP, THEN FOR THE	-
CD		NEXT GROUP, TO END OF LIST. IF	-
CD		M.LT.NGROUP THEN THE M-TH GROUP DATA	-
CD		APPLIES TO ALL ADDITIONAL GROUPS.	-
CD		(2.LE.M.LE.NGROUP)	-
CD	NBCS	NUMBER OF CONSTANTS FOR EXTERNAL BOUNDARIES	-
CD		0 - NONE	-
CD		1 - SINGLE VALUE USED EVERYWHERE	-
CD		2 - INDIVIDUAL VALUE GIVEN FOR EACH	-
CD		EXTERNAL BOUNDARY. THE ORDERING OF THE	-
CD		VALUES IS THE SAME AS THE ORDERING OF	-
CD		THE BOUNDARY CONDITIONS.	-
CD		6*M - SIX VALUES GIVEN FOR FIRST ENERGY	-
CD		GROUP (ORDERED AS DESCRIBED ABOVE).	-
CD		THEN 6 FOR THE NEXT GROUP, TO END OF	-
CD		LIST. (2.LE.M.LE.NGROUP).	-
CD		IF M.LT.NGROUP THEN THE M-TH GROUP DATA	-
CD		APPLIES TO ALL REMAINING GROUPS.	-
CD	NIBCS	NUMBER OF CONSTANTS FOR INTERNAL BOUNDARIES	-
CD		0 - NONE	-
CD		1 - SINGLE VALUE USED EVERYWHERE	-
CD		.GT.1 - VALUES ARE GIVEN BY ENERGY GROUP	-
CD		WITH NON-BLACK CONDITION INDICATED BY	-
CD		ZERO ENTRY - LAST VALUE APPLIES TO	-
CD		ADDITIONAL GROUPS.	-
CD	NZWBB	NUMBER OF ZONES WHICH ARE BLACK ABSORBERS	-

Figure VI.1 Specifications for GEODST Geometry Interface File (Con't)

CD	NTRIAG	TRIANGULAR/HEXAGONAL GEOMETRY OPTION	-
CD		0 - REGION OF SOLUTION IS A RHOMBUS IN	-
CD		WHICH THE 1ST AND 2ND DIMENSION AXES	-
CD		INTERSECT AT AN ANGLE OF 120 DEGREES.	-
CD		1 - REGION OF SOLUTION IS A RHOMBUS IN	-
CD		WHICH THE 1ST AND 2ND DIMENSION AXES	-
CD		INTERSECT AT AN ANGLE OF 60 DEGREES.	-
CD		2 - REGION OF SOLUTION IS A RECTANGLE. THE	-
CD		BOUNDARIES I1 AND I2 BISECT MESH	-
CD		TRIANGLES. SEE NTHPT BELOW.	-
CD		(IGOM=9, 17 ONLY)	-
CD		3 - REGION OF SOLUTION IS AN EQUILATERAL,	-
CD		60 DEGREE TRIANGLE, (IGOM=9, 17 ONLY)	-
CD		4 - REGION OF SOLUTION IS A 30-60 DEGREE	-
CD		RIGHT TRIANGLE IN WHICH THE 1ST AND 2ND	-
CD		DIMENSION AXES INTERSECT AT THE 30	-
CD		DEGREE ANGLE. (IGOM=9, 17 ONLY)	-
CD		5 - REGION OF SOLUTION IS A RHOMBUS IN	-
CD		WHICH THE 1ST AND 2ND DIMENSION AXES	-
CD		INTERSECT AT AN ANGLE OF 30 DEGREES.	-
CD		(IGOM=9, 17 ONLY)	-
CD	NRASS	REGION ASSIGNMENTS	-
CD		0- TO COARSE MESH	-
CD		1- TO FINE MESH	-
CD	NTHPT	ORIENTATION OF FIRST FINE MESH INTERVAL IN	-
CD		TRIANGULAR GEOMETRIES. NTRIAG = 2 ONLY.	-
CD		1- TRIANGLE(1,1) POINTS AWAY FROM FIRST	-
CD		DIMENSION AXIS, I.E., NO INTERNAL MESH	-
CD		LINE INTERSECTS THE ORIGIN.	-
CD		2- TRIANGLE(1,1) POINTS TOWARD THE FIRST	-
CD		DIMENSION AXIS, I.E., AN INTERNAL MESH	-
CD		LINE INTERSECTS THE ORIGIN.	-
CD	NGOP	RESERVED	-
C			-
C			-

Figure VI.1 Specifications for GEODST Geometry Interface File (Con't)

```

C-----
CR      ONE DIMENSIONAL COARSE MESH INTERVAL BOUNDARIES AND FINE
CR      MESH INTERVALS (2D RECORD)
C
CC      PRESENT IF IGOM.GT.0 AND IGOM.LE.3
C
CL      (XMESH(I),I=1,NCBNDI).(IFINTS(I),I=1,NCINTI)
C
CW      NCBNDI*MULT+NCINTI
C
CD      XMESH          COARSE MESH BOUNDARIES, FIRST DIMENSION
CD      IFINTS         NUMBER OF EQUALLY SPACED FINE MESH INTERVALS
CD                      PER COARSE MESH INTERVAL, FIRST DIMENSION
CD      NCBNDI         NCINTI+1, NUMBER OF FIRST DIMENSION COARSE
CD                      MESH BOUNDARIES
C
CC      UNITS ARE CM FOR LINEAR DIMENSIONS AND RADIANS FOR ANGULAR
C      DIMENSIONS
C-----

C-----
CR      TWO DIMENSIONAL COARSE MESH INTERVAL BOUNDARIES AND FINE
CR      MESH INTERVALS (3D RECORD)
C
CC      PRESENT IF IGOM.GT.6 AND IGOM.LE.11
C
CL      (XMESH(I),I=1,NCBNDI),(YMESH(J),J=1,NCBNDJ),
CL      1(IFINTS(I),I=1,NCINTI),(JFINTS(J),J=1,NCINTJ)
C
CW      (NCBNDI+NCBNDJ)*MULT+NCINTI+NCINTJ
C
CD      YMESH          COARSE MESH BOUNDARIES, SECOND DIMENSION
CD      JFINTS         NUMBER OF EQUALLY SPACED FINE MESH INTERVALS
CD                      PER COARSE MESH INTERVAL, SECOND DIMENSION
CD      NCBNDJ         NCINTJ+1, NUMBER OF SECOND DIMENSION COARSE
CD                      MESH BOUNDARIES
C
CC      FOR UNIFORM-TRIANGULAR-MESH GEOMETRY (IGOM = 9) THE
CC      LENGTH (L) OF THE SIDE OF A MESH TRIANGLE MUST BE GIVEN
CC      BY THE EXPRESSION
CC      L = 2.*(XMESH(2)-XMESH(1))/IFINTS(1).
CC      FOR UNIFORM-HEXAGONAL-MESH GEOMETRY (IGOM = 10) THE
CC      FLAT-TO-FLAT DISTANCE (FTF) ACROSS A MESH HEXAGON MUST
CC      BE GIVEN BY THE EXPRESSION
CC      FTF = (XMESH(2)-XMESH(1))/IFINTS(1)
C
C-----

```

Figure VI.1 Specifications for GEODST Geometry Interface File (Con't)

```

C-----
CR      THREE DIMENSIONAL COARSE MESH INTERVAL BOUNDARIES AND FINE -
CR      MESH INTERVALS (4D RECORD), -
C -
CC      PRESENT IF IGOM.GE.12 -
C -
CL      (XMESH(I),I=1,NCBNDI).(YMESH(J),J=1,NCBNDJ), -
CL      1(ZMESH(K),K=1,NCBNDK),(IFINTS(I),I=1,NCINTI), -
CL      2(JFINTS(J),J=1,NCINTJ),(KFINTS(K),K=1,NCINTK) -
C -
CW      (NCBNDI+NCBNDJ+NCBNDK)*MULT+NCINTI+NCINTJ+NCINTK -
C -
CD      ZMESH          COARSE MESH BOUNDARIES, THIRD DIMENSION -
CD      KFINTS          NUMBER OF EQUALLY SPACED FINE MESH INTERVALS -
CD                        PER COARSE MESH INTERVAL, THIRD DIMENSION -
CD      NCBNDK          NCINTK+1, NUMBER OF THIRD DIMENSION COARSE MESH- -
CD                        BOUNDARIES -
C -
CC      FOR UNIFORM-TRIANGULAR-MESH GEOMETRY (IGOM =17) THE -
CC      LENGTH (L) OF THE SIDE OF A MESH TRIANGLE MUST BE GIVEN -
CC      BY THE EXPRESSION -
CC      L = 2.*(XMESH(2)-XMESH(1))/IFINTS(1). -
CC      FOR UNIFORM-HEXAGONAL-MESH GEOMETRY (IGOM = 18) THE -
CC      FLAT-TO-FLAT DISTANCE (FTF) ACROSS A MESH HEXAGON MUST -
CC      BE GIVEN BY THE EXPRESSION -
C      FTF = (XMESH(2)-XMESH(1))/IFINTS(1) -
C -
C-----

C-----
CR      GEOMETRY DATA (5D RECORD) -
C -
CC      PRESENT IF IGOM.GT.0 OR NBS.GT.0 -
C -
CL      (VOLR(N),N=1,NREG),(BSQ(N),N=1,NBS),(BNDK(N),N=1,NBCS), -
CL      (BNCI(N),N=1,NIBCS),((NZHBB(N),N=1,NZWBB),(NZC(N),N=1,NZONE), -
CL      (NZNR(N),N=1,NREG) -
C -
CW      2*NREG+NBS+NBCS+NIBCS+NZWBB+NZONE -
C -
CD      VOLR          REGION VOLUMES (CC) -
CD      BSQ           BUCKLING (B**2) VALUES (CM**-2) -
CD      BNDK          BOUNDARY CONSTANTS ((DEL PHI)/PHI = -C/D) -
CD      BNCI          INTERNAL BLACK BOUNDARY CONSTANTS -
CD      NZHBB         ZONE NUMBERS WITH BLACK ABSORBER CONDITIONS -
CD      NZC           ZONE CLASSIFICATIONS -
CD      NZNR          ZONE NUMBER ASSIGNED TO EACH REGION -
C -
C-----

```

Figure VI.1 Specifications for GEODST Geometry Interface File (Con't)


```

C-----
CR      REGION ASSIGNMENTS TO COARSE MESH INTERVALS  (6D RECORD)  -
C                                           -
CC      PRESENT IF IGOM.GT.0 AND NRASS.EQ.0                      -
C                                           -
CL      ((MR(I,J),I=1,NCINTI),J=1,NCINTJ)---NOTE STRUCTURE BELOW--- -
C                                           -
CW      NCINTI*NCINTJ                                           -
C                                           -
CS      DO 1 K=1,NCINTK                                          -
CS      1 READ(N)  *LIST AS ABOVE*                               -
C                                           -
CD      MR              REGION NUMBERS ASSIGNED TO COARSE MESH  -
CD                        INTERVALS                               -
C                                           -
C-----

C-----
CR      REGION ASSIGNMENTS TO FINE MESH INTERVALS  (7D RECORD)  -
C                                           -
CC      PRESENT IF IGOM.GT.0 AND NRASS.EQ.1                      -
C                                           -
CL      ((MR(I,J),I=1,NINTI),J=1,NINTJ)----NOTE STRUCTURE BELOW---- -
C                                           -
CW      NCINTI*NCINTJ                                           -
C                                           -
CS      DO 1 K=1,NINTK                                          -
CS      1 READ(N)  *LIST AS ABOVE*                               -
C                                           -
CD      MR              REGION NUMBERS ASSIGNED TO FINE MESH INTERVALS-
C                                           -
C-----

CEOF

```

Figure VI.1 Specifications for GEODST Geometry Interface File (Con't)

VI.1 Example of GEODST File.

An example of a GEODST file is shown in Figure VI.1.1. The 1D Record indicates the following: the geometry of the problem is Theta-R; the number of zones is three; the number of regions is 16; the number of zone classifications is one; the number of first dimension coarse mesh intervals is 4; the number of second dimension coarse mesh intervals is 4; the number of third dimension coarse mesh intervals is set to unity for a two dimensional problem; there are 24 first dimension fine mesh intervals, and 20 second dimension fine mesh intervals; the number of third dimension fine mesh intervals is set to unity for a three dimensional problem; the first boundary of the first dimension is periodic, i.e., 3, as is the last boundary of the first dimension; the first boundary of the second dimension is reflected, while the last boundary of the second dimension is extrapolated; the boundaries on the third dimension are set to unity, i.e. reflected, making this dimension in essence, infinite; the number of buckling specifications is one, a single value everywhere; there are six constants given for the external boundaries; there are three constants given for internal boundaries; there is one black absorber zone; the next input parameter associated with triangular-hexagonal geometries does not apply and is input as zero; coarse mesh regions assignments are made; again, a triangular mesh parameter is not applicable and is set to zero; the remaining parameters are reserved and set to zero.

There is no 2D Record, since the problem is two dimensional.

The 3D Record assigns mesh intervals. The four coarse mesh interval boundaries for the first dimension are given, followed by the four coarse mesh boundaries of the second dimension. Five values are required to establish the four interval boundaries for each dimension. In this problem, both dimension interval boundaries start at zero. The equally spaced fine mesh intervals in each coarse mesh interval are then given. Four values are required for the first dimension, and four for the second dimension.

There is no 4D Record, since the problem is not three dimensional.

The 5D Record provides geometry data. The 16 region volumes are given first. A single buckling value of 0.001 is used. The first three boundary constants are zero, the fourth is 0.4692, and the last two are zero. The first two internal black boundary constants are zero, while the last is 0.4692. The region number containing the black absorber is 2. The three zone classifications are unity. The zone numbers assigned to the first four regions are 1, the next region 2, the next 1, followed by 2, the next 5 are 1, followed by the next 4 assigned to zone 3.

The 6D Record assigns regions to coarse mesh intervals. Since there are 4 intervals in each of two dimensions, there is a total of 16 regions. The first four theta regions at the initial radius location are assigned regions 1 through 4 consecutively. The next four theta regions at the second radial location are assigned 5 through 8, etc.

There is no 7D Record, since region assignments are not made to fine mesh intervals.

```

OV GEODST
1D 8 3 16 1 4 4 1 24 20 1 3 3 1 2 1 1 1 6 3 1 0 0
    0 0 0 0 0
3D/
0.00000E+00 1.70796E-01 1.57080E+00 1.74159E+00 3.14159E+00
0.00000E+00 3.00000E+01 3.50000E+01 4.50000E+01 7.00000E+01
4 8 4 8 6 4 4 6
5D/
7.68583E+01 6.30000E+02 7.68583E+01 6.30000E+02 2.77544E+01
2.27500E+02 2.77544E+01 2.27500E+02 6.83185E+01 5.60000E+02
6.83185E+01 5.60000E+02 2.45520E+02 2.01250E+03 2.45520E+02
2.01250E+03
1.00000E-03
0.00000E+00 0.00000E+00 0.00000E+00 4.69200E-01 0.00000E+00
0.00000E+00
0.00000E+00 0.00000E+00 4.69200E-01
2 1 1 1 1 4R 2 1 2 1 5R 3 4R
6D/ MR COARSE MESH PLANE NO.1
1 2 3 4
5 6 7 8
9 10 11 12
13 14 15 16

```

Figure VI.1.1.1 Example of GEODST Geometry Standard File.

VII. Nuclide and Concentration Assignment Files.

In any neutronics problem, nuclides must be identified, mixture compositions must be established, and nuclide densities must be given. This information is required to establish number densities for the calculation of microscopic cross sections. The two standard interface files which provide this information are NDXSRF and ZNATDN. NDXSRF assigns nuclides to mixtures, assigns mixtures to zones and subzones, and provides zone volumes and volume fractions. ZNATDN provides the atomic densities of the nuclides in each zone.

As given in reference 3, macroscopic cross sections are calculated as follows, using subscripts "a" for absorption, "f" for fission, "tr" for transport, "s" for scattering, "g" and "k" for energy groups, "z" for zone and "n" for nuclide:

$$\Sigma_{a,g,z} = \sum_n N_{n,z} \sigma_{a,n,g}$$

$$\Sigma_{f,g,z} = \sum_n N_{n,z} \sigma_{f,n,g}$$

$$v \Sigma_{f,g,z} = \sum_n N_{n,z} v_{n,g} \sigma_{f,n,g}$$

$$\Sigma_{tr,g,z} = \sum_n N_{n,z} \sigma_{tr,n,g}$$

$$\Sigma_{s,g \rightarrow k} = \sum_n N_{n,z} \sigma_{s,n,g \rightarrow k}$$

In these equations, $N_{n,z}$ is the number density of nuclide n in zone z. This is calculated as follows:

$$N_{n,z} = M_{n,z} q_z + \sum_{sz} M_{n,sz} \frac{V_{sz}}{V_z}$$

Here, $M_{n,z}$ is the concentration of nuclide n in zone z, q_z is the volume fraction, $M_{n,sz}$ is a subzone concentration, and V_{sz} and V_z are the subzone and zone volumes respectively. The zone concentration is set to zero when the zone is broken into subzones. The volume fractions and zone concentrations should be selected to produce the correct number density, and do not necessarily have to correspond to reality. If $M_{n,z}$ is the true concentration of nuclide n in zone z with no subzones, then the volume fraction should be selected as unity. If macroscopic cross sections are utilized, the number

density should be unity, so both $M_{n,z}$ and q_z should be set to unity in a zone without subzones, etc.

VII.1 Nuclide Density and Cross Section Referencing File, NDXSRF-IV

The Nuclide Density and Cross Section Referencing File, NDXSRF, is shown in Figure VII.1. This file provides the nuclide assignments to mixtures, and the mixtures assigned to zones and subzones. It also provides the necessary volume fractions required to establish macroscopic cross sections. The records, in addition to the file identification record, for this file are:

- 1D Record - Specifications
- 2D Record - Nuclide Referencing Data
- 3D Record - Nuclide Zone Assignment Data

The 1D Record is the File Specifications Record, and includes 6 integers. The first, NON, is the number of nuclides in the cross section set. The second is the number of mixtures (nuclide sets), and is labeled NSN. The third parameter is the maximum number of nuclides in any set or mixture, NNS. The fourth specification is the number of different nuclides in the data, and is called NAN. Usually NAN is the same as NON, although there may be instances where the same nuclide is counted more than once in the cross section set, in which case $NAN < NON$. This may occur, e.g., if oxygen is listed twice in the cross section set, once for UO_2 and once for H_2O . Next, the number of zones, NZONE, is given, followed by the number of subzones, NSZ.

The 2D Record provides the nuclide referencing data. First, the unique reference nuclide name in the order they appear in the library are given for each nuclide, (HNNAME(N), $N=1, NON$). This is followed by an absolute nuclide reference name for each nuclide in library order, (HNAME(N), $N=1, NON$). The unique and absolute names are often the same, but they don't have to be. There are then some reserved locations, one for each nuclide, (WPF(N), $N=1, NON$). This is followed by the atomic weight for each nuclide, (ATWT(J), $J=1, NAN$). The nuclide classification, (NCLN(N), $N=1, NON$), e.g., fissile, fertile, coolant, etc., is then given for each nuclide. The reference data then provides the number of nuclides in each set or mixture, ((NDXS(K,L), $K=1, 4$), $L=1, NSN$). Here, when K is set to 1, NDXS(1,L) is the number of nuclides in set L. If K is 2, 3, or 4, the location is reserved. Thus, for each mixture there are four entries for reference data, three of which are reserved and should be set to zero. Next, the nuclides are assigned to each set or mixture. The number of a nuclide used for this assignment, is the order number for that nuclide in the name list (HNNAME(N), and follows the format ((NOS(I,L), $I=1, NNS$), $L=1, NSN$). The next input also assigns nuclides to mixtures, but the numbers used for the assignment are serial, except for an isotope not in the mixture, which takes the value zero. The format for this record is ((NOR(N,L), $N=1, NON$), $L=1, NSN$).

Mixture or nuclide set zone assignments are made in the 3D Record. Since volumes and volume fractions are required to establish macroscopic mixture cross sections, volume fractions are also given in this record. First, the volume of each zone is given (VOLZ(N), N=1, NZONE). Next, the volume fractions of each zone is given (VFPA(N), N=1, NZONE). This is followed by the volumes of any subzones (VLSA(M), M=1, NSZ). The mixtures or nuclide sets are then assigned to zones (NSPA(N), N=1, NZONE). A zero in this list indicates the zone has subzones. The mixtures or nuclide sets are then assigned to subzones (NSSA(M), M=1, NSZ). The final listing is the zone containing the subzone, for each subzone (NZSZ(M), M=1, NSZ).

```

C*****
C                      REVISED 11/30/76
C
CF          NDXSRF - IV
C
CE          NUCLIDE DENSITY. DATA, CROSS SECTION REFERENCING
C
C*****

C-----
CR          FILE IDENTIFICATION
CL  HNAME,(HUSE(I),I=1,2),IVERS
C
CW  1+3*MULT=NUMBER OF WORDS
C
CD  HNAME          HOLLERITH FILE NAME - NDXSRF - (A6)
CD  HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD  IVERS          FILE VERSION NUMBER
CD  MULT           DOUBLE PRECISION PARAMETER
CD                1 - A6 WORD IS SINGLE WORD
CD                2 - A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          SPECIFICATIONS          (1D RECORD)
C
CL  NON,NSN,NNS,NAN,NZONE,NSZ
C
CW  6 = NUMBER OF WORDS
C
CD  NON            NUMBER OF NUCLIDES IN CROSS SECTION DATA
CD  NSN            NUMBER OF NUCLIDE SETS IDENTIFIED
CD  NNS            MAXIMUM NUMBER OF NUCLIDES IN ANY SET
CD  NAN            NUMBER OF DIFFERENT NUCLIDES IN DATA
CD  NZONE          NUMBER OF ZONES
CD  NSZ            NUMBER OF SUBZONES (SUBASSEMBLIES)
C
C-----

```

Figure VII.1 Nuclide Density and Cross Section Referencing File, NDXSRF


```

C-----
C      NUCLIDE REFERENCING DATA      (2D RECORD)      -
C      -
CL      (HNNAME(N),N=1,NON),(HNAME(N),N=1,NON),(WPF(N),N=1,NON). -
CL      (ATWT(J),J=1,NAN),(NCLN(N),N=1,NON),((NDXS(K,L),K=1,4),L=1,NSN), -
CL      ((NOS(I,L),I=1,NNS),L=1,NSN),((NOR(N,L),N=1,NON),L=1,NSN) -
C      -
CW      NAN+2*NON*(1+MULT)+NSN*(4+NNS+NON)=NUMBER OF WORDS -
C      -
CD      HNNAME(N)          UNIQUE REFERENCE NUCLIDE NAME, IN LIBRARY ORDER -
CD      (A6) ALPHANUMERIC -
CD      HNAME(N)          ABSOLUTE NUCLIDE REFERENCE, IN LIBRARY ORDER -
CD      (A6) ALPHANUMERIC -
CD      WPF(N)            RESERVED -
CD      ATWT(N)            ATOMIC WEIGHT -
CD      NCLN(N)            NUCLIDE CLASSIFICATION -
CD      1 - FISSILE -
CD      2 - FERTILE -
CD      3 - OTHER CLASSIFICATION -
CD      4 - FISSION PRODUCT -
CD      5 - STRUCTURAL -
CD      6 - COOLANT -
CD      7 - CONTROL ROD -
CD      GREATER THAN 7, UNDEFINED -
CD      NDXS(K,L)          REFERENCE DATA FOR SET L -
CD      K = 1, NUMBER OF NUCLIDES IN SET -
CD      K = 2, RESERVED -
CD      K = 3, RESERVED -
CD      K = 4, RESERVED -
CD      NOS(I,L)          ORDER NUMBER OF NUCLIDE IN CROSS SECTION DATA -
CD      (IN HNAME LIST) OF NUCLIDE ORDERED I IN -
CD      SET L -
CD      NOR(N,L)          ORDER NUMBER OF NUCLIDE IN SET L GIVEN ORDER -
CD      NUMBER N IN CROSS SECTION DATA -
C      -
C-----

```

Figure VII.1. Nuclide Density and Cross Section Referencing File. NDXSRF (con't.)

```

C-----
CR      NUCLIDE CONCENTRATION ASSIGNMENT DATA  (3D RECORD)      -
C                                             -
CL      (VOLZ(N),N=1,NZONE),(VFPA(N),N=1,NZONE),(VLSA(M),M=1,NSZ). -
CL      (NSPA(N),N=1,NZONE),(NSSA(M),M=1,NSZ),(NZSZ(M),M=1,NSZ) -
C                                             -
CW      3*(NZONE+NSZ)=NUMBER OF WORDS -
C                                             -
CD      VOLZ(N)          VOLUMES OF ZONES, CC -
CD      VFPA(N)          VOLUME FRACTIONS FOR PRIMARY ZONE ASSIGNMENTS -
CD      VLSA             VOLUMES OF SUBZONES -
CD      NSPA(N)          NUCLIDE SET REFERENCE, PRIMARY ZONE ASSIGNMENT -
CD                        (MAY BE ZERO ONLY IF THERE ARE SUBZONES) -
CD      NSSA(M)          NUCLIDE SET REFERENCE ASSIGNMENT TO SUBZONES -
CD      NZSZ(M)          ZONE CONTAINING SUBZONE -
C                                             -
CN      NOTE THAT TO CALCULATE MACROSCOPIC CROSS SECTIONS FOR A ZONE, -
CN      IT IS NECESSARY TO CONSIDER THE CONCENTRATION OF EACH NUCLIDE -
CN      IN THE PRIMARY SET ASSIGNMENT (UNLESS A ZERO IN NSPA INDICATES -
CN      THERE ARE NONE) TIMES THE VOLUME FRACTION, AND THE CONCENTRATION -
CN      OF EACH NUCLIDE IN EACH SUBZONE ASSIGNED TO THE ZONE TIMES THE -
CN      RATIO OF THE SUBZONE VOLUME TO THE ZONE VOLUME. -
C                                             -
C-----
CEOF

```

Figure VII.1. Nuclide Density and Cross Section Referencing File, NDXSRF
(con't.)

VII.1.1 Example of NDXSRF File.

An example of a NDXSRF standard interface file is shown in Figure VII.1.1. The 1D Record indicates there are 15 nuclides in the cross section data. The number of mixtures or nuclide sets is 4, and the maximum number of nuclides in a mixture or set is 14. The number of different nuclides in the data is 15, the number of zones 8, and the number of subzones 4.

The 2D Record shows that the nuclides in the data set are: O-16; Na-23; Cr-N; Mn-55; Fe-N; Ni-N; Mo-N; Ta-181; U-235; U-238; Pu-239; Pu-240; Pu-241; Pu-242; and 2 saturated fission products. The same names are repeated for the absolute nuclide reference. The next 15 zero's are in reserve for possible later use. The 15 atomic weights associated with the nuclide list are given next. The nuclide classifications follow: O-16 is not classified, since it has a zero classification; Na-23 is classified as a coolant material; The next 5 nuclides are classified as structure; Tantalum is classified as a control rod material; U-235 is fissile, U-238, fertile; Pu-239, fissile; Pu-240, fertile; Pu-241, fissile; Pu-242, other actinide; and SSFP is a fission product. The number of nuclides in each mixture are assigned next. There are 14 nuclides in the first three mixtures, and 7 nuclides in the next mixture. For each entry in this record, three additional zeros are given as reserved data. The nuclide numbers, assigned in the order listed, are then given for each mixture or nuclide set. The first mixture excludes the ninth nuclide listed, i.e., U-235, but includes all others. The next two mixtures exclude the fourteenth nuclide listed, i.e., Pu-242. The final mixture does not include oxygen, but includes sodium, the structural materials, the control material tantalum, and that's all. Seven zero's are therefore inserted in the final mixture, to bring the nuclide number to 14, which is the maximum for any set or mixture.

The 3D Record begins with the volumes of the eight zones. The volume fractions of each zone is then given. Zone 2 has a volume fraction of zero entered, since this zone has subzones associated with it. The volumes of the four subzones are then given. The mixtures or nuclide sets are then assigned to zones. Mixture 1 is assigned to the first zone. The second zone has a zero zone assignment, since this zone has subzones. The next four zones are assigned nuclide set number 3, while the final two zones are assigned nuclide set 4. The four subzones are assigned mixture 2, while the four subzones are assigned to zone 2.

```

OV NDXSRF
1D/
  15 4 14 15 8 4
2D/
  (*O-16 * *NA-23 * *CR-N * *MN-55 * *FE-N * *NI-N * *MO-N *
  *TA-181* *U-235 * *U-238 * *PU-239* *PU-240* *PU-241* *PU-242*
  *SSFF * ) 2R/
0.0 15R/
15.862 22.786 52.01 54.466 55.845 58.705 95.066 179.39 233.025
236.006 236.999 237.990 238.978 240.145 161.0 /
0 6 5 5R 7 1 2 1 2 1 3 4 /
(14 0 3R) 3R 7 0 3R /
1 2 3 4 5 6 7 8 10 11 12 13 14 15/
(1 2 3 4 5 7 8 9 10 11 12 13 15) 2R /
2 3 4 5 6 7 8 0 7R /
1 2 3 4 5 6 7 8 0 9 10 11 12 13 14 /
(1 2 3 4 5 6 7 8 9 10 11 12 13 0 14 ) 2R /
0 1 2 3 4 5 6 7 0 7R/
3D /
266983.6 223505.7 187884.9 157288.2 296002.6 208306.6 498851.2
445948.4 /
1.0 0.0 1.0 6R /
55876.42 4R /
1 0 3 4R 4 4 /
2 4R /
2 4R /

```

Figure VII.1.1 Example of NDXSRF Interface File.

VII.2 Zone Atomic Density File - ZNATDN-IV

The ZNATDN File assigns atomic densities of all nuclides to geometric zones. The specifications for this file are shown in Figure VII.2. The data records follow the File Identification Record. They include:

- 1D Record - Specifications
- 2D Record - Zone Atomic Densities (of Nuclides)

The 1D Record lists 5 file specifications. These include: the real time in days, TIME; the cycle number, NCY; the number of zones plus the number of subzones, NTZSZ; the maximum number of nuclides in any set, NNS; the number of blocks of atom density data, NBLKAD.

The 2D Record lists the atomic densities with the format ((ADEN(N,J), N=1,NNS),J=JL,JU), for nuclide N, and zone or subzone J. The densities are given in order for each zone, followed in order for each subzone. The data is repeated for each block of atom density data. The lower zone index, JL, and the upper zone index, JU, then depend on the block index, as shown in the 2D record specifications. If there were only a single block of atom density data, JL would equal 1, and JU would equal NTZSZ.

```

C*****
C              REVISED 11/30/76
C
CF          ZNATDN-IV
CE          ZONE ATOMIC DENSITIES (OF NUCLIDES)
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL  HNAME,(HUSE(I),I=1,2),IVERS
C
CW  1+3*MULT=NUMBER OF WORDS
C
CD  HNAME          HOLLERITH FILE NAME - ZNATDN - (A6)
CD  HUSE(I)        HOLLERITH USER IDENTIFICATION - (A6)
CD  IVERS          FILE VERSION NUMBER
CD  MULT           DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          SPECIFICATIONS          (1D RECORD)
C
CL  TIME,NCY,NTZSZ,NNS,NBLKAD
C
CW  5=NUMBER OF WORDS
C
CD  TIME          REFERENCE REAL TIME, DAYS
CD  NCY           REFERENCE CYCLE NUMBER
CD  NTZSZ         NUMBER OF ZONES PLUS NUMBER OF SUBZONES
CD  NNS           MAXIMUM NUMBER OF NUCLIDES IN ANY SET
CD  NBLKAD        NUMBER OF BLOCKS OF ATOM DENSITY DATA
C
C-----

```

Figure VII.2 Specifications for ZNATDN Interface File

```

C-----
CR          ZONE ATOMIC DENSITIES (OF NUCLIDES)      (2D RECORD)      -
C                                                    -
CL      ((ADEN(N,J),N=1,NNS),J=JL,JU)-----SEE STRUCTURE BELOW----- -
C                                                    -
CW      NNS*(JL - JU + 1) = NUMBER OF WORDS          -
C                                                    -
CC      DO 1 M=1,NBLKAD                               -
CC 1 READ(N) *LIST AS ABOVE*                          -
C                                                    -
CC          WITH M AS THE BLOCK INDEX, JL=(M-1)*((NTZSZ-1)/NBLKAD+1)+1 -
CC          AND JU=MINO(NTZSZ,JUP) WITH JUP=M*((NTZSZ-1)/NBLKAD + 1) -
C                                                    -
CD      ADEN(N,J)          ATOMIC DENSITY OF NUCLIDE ORDERED N IN THE -
CD                               ASSOCIATED SET GIVEN IN ORDER FOR EACH ZONE -
C                                                    -
C-----

```

CEOF

Figure VII.2 Specifications for ZNATDN Interface Data File (cont'd.)

VII.2.1 Example of ZNATDN File.

An example of a Zone Atomic Density File is shown in Figure VII.2.1. The 1D Record specifies that the reference time and reference cycle are both zero, the number of zones plus subzones are 12, the maximum number of nuclides is 14, and the number of blocks of data is 1.

The 2D Record lists the atomic densities. The first 14 entries are the nuclide densities for zone 1. The next 14 entries, which are all zero, are the nuclide densities for zone 2, and so on, until the nuclide densities for all 12 zones and subzones are listed. The densities of zone 2 are zero, since this zone has subzones. The subzone densities follow the zone densities, and are the final four sets of 14 nuclide density entries.


```

OV ZNATDN
1D /
0.0 0 12 14 1
2D /
1.804800E-02 8.218598E-03 2.945900E-03 4.325500E-04 1.134900E-02
2.078700E-03 6.186498E-04 5.261999E-05 7.179096E-03 9.960700E-04
2.896199E-04 2.796900E-05 7.217899E-06 5.223998E-04
0.0 14R 1.804800E-02 /
8.218598E-03 2.945900E-03 4.325500E-04 1.134900E-02 2.078700E-03
5.186498E-04 5.261999E-05 2.124799E-05 8.596398E-03 1.841500E-04
6.197200E-06 9.999999E-16 4.515100E-05 1.804800E-02 8.218598E-03
2.945900E-03 4.325500E-04 1.134900E-02 2.078700E-03 5.186498E-04
5.261999E-05 2.124799E-05 8.596398E-03 1.841500E-04 6.197200E-06
9.999999E-16 4.515100E-05 1.804800E-02 8.218598E-03 2.945900E-03
4.325500E-04 1.134900E-02 2.078700E-03 5.186498E-04 5.261999E-05
2.124799E-05 8.596398E-03 1.841500E-04 6.197200E-06 9.999999E-16
4.515100E-05 1.804800E-02 8.218598E-03 2.945900E-03 4.325500E-04
1.134900E-02 2.078700E-03 5.186498E-04 5.261999E-05 2.124799E-05
8.596398E-03 1.841500E-04 6.197200E-06 9.999999E-16 4.515100E-05
4.359999E-03 1.149600E-02 1.699000E-03 4.428800E-02 8.111998E-03
2.024000E-03 9.999999E-16 /
0.0 7R 4.439998E-03 1.149600E-02 1.688000E-03
4.428800E-02 8.111998E-03 2.024000E-03 9.999999E-16
0.0 7R 1.804800E-02 /
8.218598E-03 2.945900E-03 4.325500E-04 1.134900E-02 2.078700E-03
5.186498E-04 5.261999E-05 2.124799E-05 8.596398E-03 1.841500E-04
6.197200E-06 9.999999E-16 4.515100E-05 1.804800E-02 8.218598E-03
2.945900E-03 4.325500E-04 1.134900E-02 2.078700E-03 5.186498E-04
5.261999E-05 2.124799E-05 8.596398E-03 1.841500E-04 6.197200E-06
9.999999E-16 4.515100E-05 1.804800E-02 8.218598E-03 2.945900E-03
4.325500E-04 1.134900E-02 2.078700E-03 5.186498E-04 5.261999E-05
2.124799E-05 8.596398E-03 1.841500E-04 6.197200E-06 9.999999E-16
4.515100E-05 1.804800E-02 8.218598E-03 2.945900E-03 4.325500E-04
1.134900E-02 2.078700E-03 5.186498E-04 5.261999E-05 2.124799E-05
8.596398E-03 1.841500E-04 6.197200E-06 9.999999E-16 4.515100E-05

```

Figure VII.2.1 Example of ZNATDN File.

VIII. Source Files.

Several files are used to define the source under various problem conditions. The file FIXSRC defines a fixed source for problems with external sources. The file FISSOR defines a fission source. In addition, for problems requiring delayed neutron sources, the file DLAYXS is used.

VIII.1 FIXSRC - Distributed and Surface Fixed Source File.

The FIXSRC file provides the necessary input to establish a fixed source, either distributed or surface. The specifications for this file are given in Figure VIII.1. This file includes the following data records:

- 1D Record - Specifications
- 2D Record - One-Dimensional Distributed Fixed Source
- 3D Record - Multi-Dimensional Distributed Fixed Source
- 4D Record - First Dimension Surface Source Pointers
- 5D Record - First Dimension Surface Sources
- 6D Record - Second Dimension Surface Source Pointers
- 7D Record - Second Dimension Surface Sources
- 8D Record - Third Dimension Surface Source Pointers
- 9D Record - Third Dimension Surface Sources

The file specifications are given in the 1D Record. This includes: the type of source, diffusion or discrete ordinates (SN), ITYPE; the number of dimensions, NDIM; the number of groups, NGROUP; the number of first dimension fine mesh intervals, NINTI; the number of second dimension fine mesh intervals, NINTJ; the number of third dimension fine mesh intervals, NINTK; IDIST, the distributed source flag; NDCOMP is the number of surface source components; NEDGI is the number of first dimension boundary sources; NEDGJ is the number of second dimension boundary sources; and, NEDGK, is the number of third dimension boundary sources. If IDIST is 0, there is no distributed source, if 1, the distributed source is given by point, if 2, the distributed source is given by zone, if 3, an additional record is added to the data if the distributed source is given by point, and if 4, an additional record is added to the data if the distributed source is given by zone.

The 2D Record pertains to the one dimensional distributed fixed source. The format is ((QDIST(L,I),L=1,NDCOMP),I=1,NINTI). It is given for each zone, L, and for each interval, I. QDIST(L,I) is the distributed source times the point volume in cc. The listing repeats QDIST(L,I) for each group in succession.

The multidimensional distributed fixed source values are given in the 3D Record. The format is ((QDIST(I,J),I=1,NINTI),J=1,NINTJ), where QDIST(I,J) is the distributed source times the volume at the (I,J) interval. The listing is repeated for the third dimension

intervals, if the problem is three dimensional, then repeated for each zone, and finally repeated for each energy group.

The 4D, 5D, 6D, 7D, 8D, and 9D records all apply to surface source pointers and values. They do not apply to the VENTURE code.

The 10D Record provides the distributed source by zone and group. The format is ((ZSOR(L,N),L=1,NDCOMP),N=1,NGROUP), where NDCOMP is the number of zones, and NGROUP, the number of groups. This source is not multiplied by the zone volume prior to input.

The 11D Record is an additional record which provides the multiplication factor. It includes 20 words, the last 19 of which are dummies. The first word input is the effective multiplication factor. The format is (R(N),N=1,20), with R(1) being the multiplication factor.

```

C*****
C          REVISED 07/23/75 - REVISED 04/01/80
C
CF          FIXSRC-IV
CE          DISTRIBUTED AND SURFACE FIXED SOURCES
C
C*****

C-----
CR          FILE IDENTIFICATION
C          HNAME,(HUSE(I),I=1,2),IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CD          HNAME          HOLLERITH FILE NAME - FIXSRC - (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
CD          MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          SPECIFICATIONS      (1D RECORD)
C
CL          ITYPE,NDIM,NGROUP,NINTI,NINTJ,NINTK,IDISTS,NDCOMP,NSCOMP,NEDGI,
CL          NEDGJ,NEDGK
C
CW          12=NUMBER OF WORDS
C
CD          ITYPE          TYPE SOURCE.  0=DIFFUSION
CD                      1=SN
CD          NDIM           NUMBER OF DIMENSIONS
CD          NGROUP         NUMBER OF GROUPS
CD          NINTI          NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD          NINTJ          NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD          NINTK          NUMBER OF THIRD DIMENSION FINE MESH INTERVALS
C
CN          FOR MESHPOINT EDGE LOCATIONS, NINTI, NINTJ, AND NINTK ARE *-
CN          INTERPRETED AS THE NUMBER OF POINTS (ONE MORE THAN THE *-
CN          NUMBER OF INTERVALS). *-
CN          FOR SPECIAL TRIANGULAR GEOMETRIES, NINTI IS THE NUMBER OF *-
CN          POINTS ON EACH PLANE, AND NINTJ IS SET TO 1. *-
C

```

Figure VIII.1 Specifications for FIXSRC Interface File

```

CD      IDISTS          DISTRIBUTED SOURCE FLAG.          -
CD                                     0= NO DISTRIBUTED SOURCE GIVEN.      -
CD                                     1= DISTRIBUTED SOURCE IS GIVEN BY POINT  *-
CD                                     2= DISTRIBUTED SOURCE IS GIVEN BY ZONE  *-
CD                                     3= SAME AS 1 BUT AN ADDITIONAL RECORD IS  -
CD                                     PRESENT AT END OF DATA                *-
CD                                     4= SAME AS 2 BUT AN ADDITIONAL RECORD IS  *-
CD                                     PRESENT AT END OF DATA                *-
CD      NDCOMP          NUMBER OF DISTRIBUTED SOURCE COMPONENTS          -
CD                                     = NUMBER OF ZONES IF IDISTS IS 2 OR 4    *-
CD      NSCOMP          NUMBER OF SURFACE SOURCE COMPONENTS (0)          *-
CD      NEDGI           NUMBER OF FIRST DIMENSION BOUNDARY SOURCES (0) *-
CD      NEDGJ           NUMBER OF SECOND DIMENSION BOUNDARY SOURCES (0) *-
CD      NEDGK           NUMBER OF THIRD DIMENSION BOUNDARY SOURCES (0) *-
C-----

```

```

C-----
CR          ONE DIMENSIONAL DISTRIBUTED FIXED SOURCE  (2D RECORD)          -
C                                     -
CC          PRESENT IF NDIM.EQ.1 AND IDISTS IS 1 OR 3                      *-
C                                     -
CL          ((QDIST(L,I),L=1,NDCOMP),I=1,NINTI)---NOTE STRUCTURE BELOW--- -
C                                     -
CW          NDCOMP*NINTI=NUMBER OF WORDS                                  -
C                                     -
C          DO 1 J=1,NGROUP                                                -
C          1 READ(N) *LIST AS ABOVE*                                       -
C                                     -
CD          QDIST(L,I)           DISTRIBUTED SOURCE TIMES POINT VOLUME (CC) *-
CD                                     BY COMPONENT, INTERVAL, AND GROUP      *-
C                                     -
C-----

```

```

C-----
CR          MULT-DIMENSIONAL DISTRIBUTED FIXED SOURCE  (3D RECORD)          -
C                                     -
CC          PRESENT IF NDIM.GE.2 AND IDISTS IS 1 OR 3                      *-
C                                     -
CL          ((QDIST(I,J),I=1,NINTI),J=1,NINTJ)---NOTE STRUCTURE BELOW--- -
C                                     -
CW          NINTI*NINTJ=NUMBER OF WORDS                                  -
C                                     -
CS          DO 1 N = 1,NGROUP                                              -
CS          DO 1 L = 1,NDCOMP                                              -
CS          DO 1 K=1,NINTK                                                -
CS          1 READ(N) *LIST AS ABOVE*                                       -
C                                     -
CD          QDIST(I,J)           AS DEFINED ABOVE.                        -
C                                     -
C-----

```

Fig. 8 VIII.1 Specifications for FIXSRC Interface File (con't.)

C-----		
CR	FIRST DIMENSION SURFACE SOURCE POINTERS (4D RECORD)	-
C		-
CC	PRESENT IF NEDGI.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C-----		
C-----		
CR	FIRST DIMENSION SURFACE SOURCES (5D RECORD)	-
C		-
CC	PRESENT IF NEDGI.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C-----		
C-----		
CR	SECOND DIMENSION SURFACE SOURCE POINTERS (6D RECORD)	-
C		-
CC	PRESENT IF NDIM.GE.2 AND NEDGJ.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C-----		
C-----		
CR	SECOND DIMENSION SURFACE SOURCES (7D RECORD)	-
C		-
CC	PRESENT IF NDIM.GE.2 AND NEDGJ.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C-----		
C-----		
CR	THIRD DIMENSION SURFACE SOURCE POINTERS (8D RECORD)	-
C		-
CC	PRESENT IF NDIM.EQ.3 AND NEDGK.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C-----		
C-----		
CR	THIRD DIMENSION SURFACE SOURCES (9D RECORD)	-
C		-
CC	PRESENT IF NDIM.EQ.3 AND NEDGK.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C-----		

Figure VIII.1 Specifications for FIXSRC Interface File (con't.)

```

C-----
CR          SOURCE BY ZONE AND GROUP  (10D RECORD)          *-
C                                                    *-
CC          PRESENT IF IDISTS IS 2 OR 4                    *-
C                                                    *-
CL          ((ZSOR(L,N).L=1.NDCOMP).N=1.NGROUP)            *-
C                                                    *-
CW          NDCOMP*NGROUP=NUMBER OF WORDS                  *-
C                                                    *-
CD          ZSOR(L,N)          SOURCE BY ZONE AND GROUP - NOT MULTIPLIED *-
CD                                BY ZONE VOLUME            *-
C                                                    *-
C-----

C-----
C          ADDITIONAL RECORD IF IDISTS IS 3 OR 4  (11D RECORD)  *-
C                                                    *-
CL          (R(N),N=1,20)                                    *-
C                                                    *-
CW          20=NUMBER OF WORDS                              *-
C                                                    *-
CD          R(1)          KEFFECTIVE                        *-
C                                                    *-
C-----

C*****
C                                                    -
CEOF          FIXSRC                                         -
C                                                    -
C*****

```

Figure VIII.1 Specifications for FIXSRC Interface File (con't.)

VIII.1.1 Example of FIXSRC File.

An example of a FIXSRC file is shown in Figure VIII.1.1. The 1D Record indicates the following: The type of problem is diffusion; the number of dimensions is two; the number of groups is five; the number of first dimension fine mesh intervals is 17; the number of second dimension fine mesh intervals is 10; the number of third dimension fine mesh intervals is one, since the problem is two dimensional; the distributed source flag indicates that the distributed source is given by zone, but an additional record is present at the end of the data; the number of zones is eight; there are no surface sources or boundary sources.

The next record given is the 10D Record, which provides the source by zone and group. Since there are eight zones and 5 groups, there are 40 data entries for this record. The first 8 entries are the distributed source for the 8 zones in group one, and the next eight entries are for group 2, etc.

The final record is the 11D Record, which is the additional record referenced earlier. This record contains 20 entries, the first of which is the effective multiplication factor, which is given as 1.273779. The remaining 19 entries are not specified, and are input as zero's.


```

FIXSRC
0
1D /
0 2 5 17 10 1 4 8 0 0 0 0
10D /
1.80371E-17 1.27542E-17 1.27542E-17 1.27542E-17 1.27542E-17 1.27542E-17
0.00000E+00 0.00000E+00 -2.00076E-17 3.69489E-17 3.69489E-17 3.69489E-17
3.69489E-17 3.69489E-17 0.00000E+00 0.00000E+00 3.41975E-17 1.17895E-16
1.17895E-16 1.17895E-16 1.17895E-16 1.17895E-16 0.00000E+00 0.00000E+00
5.86164E-17 2.35631E-16 2.35631E-16 2.35631E-16 2.35631E-16 2.35631E-17
0.00000E+00 0.00000E+00 -1.29345E-16 2.93994E-16 2.93994E-16 2.93994E-16
2.93994E-16 2.93994E-16 0.00000E+00 0.00000E+00
11D /
1.27378E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00

```

Figure VIII.1.1 Example of FIXSRC File.

VIII.2 FISSOR, Fission Source File

The FISSOR File description is shown in Figure VIII.2. The function of this file is to provide the fission source distribution as a function of zone, interval and group.

The 1D Record contains 9 parameters. The first is the reference real time in days, i.e., the actual time in days during a fueling cycle that is to be used as the starting time in the analysis. The second parameter is the power level in thermal watts. The effective multiplication factor is input next. Next, the number of first dimension fine mesh intervals, followed by the second and third dimension intervals are given. The reference count or cycle number is then given. This is followed by the number of energy groups and the number of cycles.

The 2D Record provides the fission source distribution as a function of zone and groups. The format for this distribution is: $((CHIN(N,K), N=1, NZ), K=1, NG)$, where $CHIN(N,K)$ is the source of neutrons in group K and zone N, NZ is the number of zones, and NG is the number of groups.

The 3D Record gives the fission source values in neutrons/cc/sec for each interval in the analysis. The format used is: $((PFS(I,J), J=1, IM), I=1, JM)$, where IM is the number of first dimension fine mesh intervals, and JM is the number of second dimension fine mesh intervals. This information is repeated for each third dimension fine mesh interval, in order.

```

C*****
C              REVISED  04/01/80
C
CF          FISSOR
C
CE          FISSION SOURCE BY INTERVAL AND DISTRIBUTION FUNCTION
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2),IVERS
C
CW      3*MULT + 1
C
CD      HNAME          HOLLERITH FILE NAME - FISSOR - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
C
CN      MULT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----

C-----
CR          FILE REFERENCE IDENTIFICATION
C
CL      TIME, POWER, KEFF, IM, JM, KM, NCT, NG, NZ
C
CW      9
CD      TIME           REFERENCE REAL TIME, DAYS
CD      POWER          POWER LEVEL FOR ACTUAL NEUTRONICS PROBLEM.
CD                      WATTS THERMAL
CD      KEFF           MULTIPLICATION FACTOR
CD      IM             NUMBER OF FIRST DIMENSION FINE INTERVALS
CD      JM             NUMBER OF SECOND DIMENSION FINE INTERVALS
C
CN                      FOR SPECIAL TRIANGULAR GEOMETRIES, IM IS THE NUMBER OF *-
CN                      TRIANGLES ON EACH PLANE AND JM IS NOT DEFINED (SET TO 1)*-
C
CD      KM             NUMBER OF THIRD DIMENSION FINE INTERVALS
CD      NCY            REFERENCE COUNT (CYCLE NUMBER)
CD      NG            NUMBER OF ENERGY GROUPS
CD      NZ            NUMBER OF ZONES
C
C-----

```

Figure VIII.2 Specifications for FISSOR interface File

```

C-----
CR          FISSION SOURCE DISTRIBUTION FUNCTION  (2D RECORD)      -
C                                                    -
CL      ((CHIM(M,K),M=1,NZ),K=1,MG)                               -
C                                                    -
CW      NG*NZ                                                       -
C                                                    -
CD      CHIM(M,K)   SOURCE OF NEUTRONS IN GROUP K, ZONE M         -
C                                                    -
C-----

C-----
CR          FISSION SOURCE VALUES  (3D RECORD)                    -
C                                                    -
CL      ((PFS(I,J),I=1,IM),J=1,JM)-----NOTE STRUCTURE BELOW-----
C                                                    -
CW      IM*JM                                                       -
C                                                    -
CS      DO 1 K=1,KM                                                -
CS  1 READ(N)  *LIST AS ABOVE*                                     -
C                                                    -
CD      PFS(I,J)          FISSION SOURCE BY INTERVAL, NEUTRONS/SEC/CC
C                                                    -
C-----

C*****
C
CEOF      FISSOR
C
C*****

```

Figure VIII.2 Specifications for FISSOR interface File. (con't.)

VIII.2.1 Example of FISSOR File

An example of a FISSOR file is shown in Figure VIII.2.1 . The 1D record indicates the reference real time starts at zero, the power level is zero, the multiplication factor is 1.0207, the number of first, second, and third dimension intervals are 12, 12, and 1, respectively, the cycle number is zero, the number of energy groups are 2, and the number of zones is 78.

The 2D record indicates that the fission source is in the first group of each of the 78 zones, and there is no fission source in the second group.

The 3D Record provides the fission source for each of the 12 by 12 intervals, with the first dimension given first for each second dimension interval. The record indicators are not present in this file, but have been inserted for illustration purposes.

[illegible]

I-99

3D/

0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	6.42955E-03	6.85951E-03	6.44432E-03	6.03675E-03
5.17880E-03	5.68771E-03	5.62503E-03	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	7.65683E-03	6.90019E-03	6.28684E-03	2.12749E-03
2.09773E-03	5.37053E-03	5.68772E-03	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	7.07769E-03	6.20973E-03	5.80581E-03	5.41659E-03
5.28349E-03	2.09774E-03	5.17881E-03	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	6.78090E-03	2.21721E-03	5.58876E-03	5.46273E-03
5.41658E-03	2.12750E-03	6.03676E-03	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	7.03042E-03	6.16365E-03	5.81589E-03	5.58876E-03
5.80580E-03	6.28684E-03	6.44434E-03	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	7.51145E-03	6.70438E-03	6.16363E-03	2.21720E-03
6.20971E-03	6.90018E-03	6.85951E-03	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	7.03927E-03	7.51144E-03	7.03039E-03	6.78087E-03
7.07766E-03	7.65681E-03	6.42955E-03	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00

Figure VIII.2.1 Example of Fissor Interface File (con't.)

VIII.3 Delayed Neutron Source - DLAYXS File.

Delayed neutrons are provided for, when necessary, by the DLAYXS File. This file contains the following data sections, in addition to a File Structure Section and File Identification Section:

- 1D Record - File Control
- 2D Record - File Data, Decay Constants, and Emission Spectra
- 3D Record - Delayed Neutron Precursor Yield data

The specifications for the DELAYXS file is given in Figure VIII.3. The file structure section indicates that the File Control, i.e., the 1D Record, and the File Data, Decay Constants, and Emission Spectra data, i.e. the 2D Record, are always present. The Delayed Neutron Precursor and Yield data, the 3D Record, is then repeated for each isotope in the delayed neutron set.

The 1D or File Control Record contains 4 integers. This include NGROUP, the number of neutron energy groups in the set, NISOD, the number of isotopes in the delayed neutron set, NFAM, the number of delayed neutron families in the set, and IDUM, a dummy required to make a four word record.

The 2D Record contains file data, decay constants, and emission spectra data. The first entry is the absolute isotope label, (HABSID(I), I=1, NISOD). Then, the delayed neutron precursor decay constant for the various delayed groups or families, (FLAM(N), N=1, NFAM), is given. The fraction of the delayed neutrons emitted into neutron energy group J from precursor family N, ((CHID(J,N), J=1, NGROUP), N=1, NFAM) is then input. The maximum energy bound for each group, (EMAX(J), J=1, NGROUP), is the next entry of the record. The minimum energy bound for the set, EMIN, is then supplied. This is followed by (NKFAM(I), I=1, NISOD), the number of families to which fission in isotope I contributes delayed neutron precursors. The number of records to be skipped to read data for isotope I, (LOCA(I), I=1, NISOD), is the final entry of this record, with LOCA(1) equal to zero as is expected.

The 3D Record contains delayed neutron precursor yield data. The first array of entries is (SNUDEL(J,K), J=1, NGROUP), K=1, NKFAMI), where SNUDEL(J,K) is the number of delayed neutron precursors produced in family number NKFAM(K) per fission in group J. Here NKFAMI is the same as NKFAM(I). The final entry is (NUMFAM(K), K=1, NKFAMI), where NUMFAM(K) is the family number (or precursor number) of the K'th yield vector in array SNUDEL(J,K). The K'th yield vector represent the precursor yields of the K'th precursor family.


```

C*****
C          REVISED 11/30/
CF          DLAYXS-IV
CE          MICROSCOPIC GROUP DELAYED NEUTRON PRECURSOR DATA
C
CN          THIS FILE PROVIDES PRECURSOR YIELDS.
CN          EMISSION SPECTRA, AND DECAY CONSTANTS
CN          ORDERED BY ISOTOPE. ISOTOPES ARE IDENTIFIED
CN          BY ABSOLUTE ISOTOPE LABELS FOR RELATION TO
CN          ISOTOPES IN EITHER FILE ISOTXS OR GRUPXS.
CN          FORMATS GIVEN ARE FOR FILE EXCHANGE PURPOSES
CN          ONLY.
C
C*****

C-----
CS          FILE STRUCTURE
CS
CS          RECORD TYPE                PRESENT IF
CS          =====
CS          FILE IDENTIFICATION        ALWAYS
CS          FILE CONTROL                ALWAYS
CS          FILE DATA, DECAY CONSTANTS, AND
CS          EMISSION SPECTRA          ALWAYS
CS          ***** (REPEAT TO NISOD)
CS          *      DELAYED NEUTRON PRECURSOR
CS          *      YIELD DATA          ALWAYS
CS          *****
C
C-----

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME, (HUSE(I), I=1,2), IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CB          FORMAT(11H 0V DLAYXS ,1H*,2A6,1H*,I6)
C
CD          HNAME          HOLLERITH FILE NAME - DLAYXS -
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
CD          MULT            DOUBLE PRECISION PARAMETER
CD                          1- A6 WORD IS SINGLE WORD
CD                          2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

Figure VIII.3 Specifications for DELAYXS Interface File

```

C-----
CR      FILE CONTROL   (1D RECORD)
C
CL      NGROUP.NISOD.NFAM.IDUM
C
CW      4=NUMBER OF WORDS
C
CB      FORMAT(4H 1D ,4I6)
C
CD      NGROUP          NUMBER OF NEUTRON ENERGY GROUPS IN SET
CD      NISOD           NUMBER OF ISOTOPES IN DELAYED NEUTRON SET
CD      NFAM            NUMBER OF DELAYED NEUTRON FAMILIES IN SET
CD      IDUM            DUMMY TO MAKE UP FOUR WORD RECORD.
C
C-----

C-----
CR      FILE DATA, DECAY CONSTANTS, AND EMISSION SPECTRA
C
C      (2D RECORDS)
C
CL      (HABSID(I0,I=1,NISOD),(FLAM(N),N=1,NFAM),((CHID(J,N),J=1,NGROUP),
CL      N=1,NFAM),(EMAX(J),J=1,NGROUP),EMIN,(NKFAM(I),I=1,NISOD),
CL      (LOCA(I),I=1,NISOD)
C
CW      (2+MULT)*NISOD+(NGROUP+1)*(NFAM+1)=NUMBER OF WORDS
C
CB      FORMAT(4H 2D ,9(1X,A6)/          HABSID
CB      1 (10(1X,A6)))
CB      FORMAT (6E12.5)                  FLAM,CHID,EMAX,EMIN
CB      FORMAT(12I6)                     NKFAM,LOCA
C
CD      HABSID(I)      HOLLERITH ABSOLUTE ISOTOPE LABEL FOR ISOTOPE I (A6)
CD      FLAM(N)        DELAYED NEUTRON PRECURSOR DECAY CONSTANT
CD                      FOR FAMILY N
CD      CHID(J,N)      FRACTION OF DELAYED NEUTRONS EMITTED INTO NEUTRON
CD                      ENERGY GROUP J FROM PRECURSIR FAMILY N
CD      EMAX(J)        MAXIMUM ENERGY BOUND OF GROUP J (EV)
CD      EMIN           MAXIMUM ENERGY BOUND OF SET (EV)
CD      NKFAM(I)       NUMBER OF FAMILIES TO WHICH FISSION IN ISOTOPE I
CD                      CONTRIBUTES DELAYED NEUTRON PRECURSORS
CD      LOCA(I)        NUMBER OF RECORDS TO BE SKIPPED TO READ DATA FOR
CD                      ISOTOPE (I0. LOCA(1)=0
C
C-----

```

Figure VIII.3 Specifications for DELAYXS Interface File (con't.)

```

C-----
CR      DELAYED NEUTRON PRECURSOR YIELD DATA  (3L RECORD)      -
C                                           -
CL      (SNUDEL(J,K).J=1,NGROUP).K=1,NKFAMI).(NUMFAM(K).K=1,NKFAMI) -
C                                           -
CC      NKFAMI=NKFAM(I)                                           -
C                                           -
CW      (NGROUP+1)*NKFAMI=NUMBER OF WORDS                         -
C                                           -
CB      FORMAT(4H 3D ,      5E12.5/(6E12.5)) SNUDEL              -
CB      FORMAT(12I6)                      NUMFAM                  -
C                                           -
CD      SNUDEL(J,K)      NUMBER OF DELAYED NEUTRON PRECURSORS PRODUCED IN -
CD                        FAMILY NUMBER NUMFAM(K) PER FISSION IN -
CD                        GROUP J                                   -
CD      NUMFAM(K)        FAMILY NUMBER OF THE K-TH YIELD VECTOR IN -
CD                        ARRAY SNUDEL(J,K)                       -
C                                           -
C-----
CEOF

```

Figure VIII.3 Specifications for DELAYXS Interface File (con't.)

IX. SEARCH File

The SEARCH file provides information required to make criticality searches. Searches can be made on dimensions, time eigenvalue, buckling, and on nuclide concentrations, to provide a desired eigenvalue. The specifications for the SEARCH file are shown in Figure IX.1

The SEARCH file is made up of the following data sections, in addition to the file identification section:

- 1D Record - Individual data Set Identifier
- 2D Record - File Specifications
- 3D Record - Coarse Mesh Modifiers for Dimension Search
- 4D Record - Nuclides for Proportional Search and Special Search
- 5D Record - Nuclides for Search Involving Weighted Eigenvalue Adjustments to Initial concentrations

The 1D Record provides identifying data for a given data set. The record consists of two integers, and a reserved integer array of 18 entries. The first integer, NSHID, is a positive identifying integer. This, and the following records are repeated until this integer, NSHID, is given as a negative integer. The next entry, NREC, is the number of data records to skip in order to start on the next set of data which begins with a new identifier, i.e., a new NSHID. The next 18 records, (NSP(I), I=1,18), are reserved for integer inputs.

The 2D Record consists of specifications common to the file. The first entry in this record is the desired multiplication factor, EFFK. The next entry is the slope of the multiplication factor, DKEFF. The third entry is the convergence criterion to be met by the multiplication factor, EPSK. The next entry is the convergence criterion to be met by the primary search variable, EPSEI. CMOD follows, and is the modifier to be applied to nuclide concentration searches, when proportional adjustments to nuclide concentrations are selected as the type of search. The next 5 entries, (SRCH(I), I=1,5), are reserved for future use. The type of search, ISRCH, is next. The following types may be selected: not defined; buckling search; alpha search; dimension search; nuclide concentration search by proportional adjustments of selected initial concentrations; and nuclide concentration search by adding weighted eigenvalue adjustments to selected initial concentrations. The next parameter is an integer ISZOP, defining whether concentration searches should be made by zone or subzone. This is followed by the integer NMAXNP, which is the maximum number of trial eigenvalues allowed in a search. A zero NMAXNP, specifies that a direct search should be done. A direct search catches the search problem as an eigenvalue problem, with the eigenvalue used as a multiplier on the search variable. In a direct search, the

eigenvalue, k_{eff} , remains constant. Then, the number of first dimension coarse mesh intervals, NCINTI, is given, followed by the same for the second and third dimensions, NCINTJ, and NCINTK. If a concentration search was selected, the number of isotopes or nuclides involved in the search, NISOSR, is input next. The number of specification sets, if a concentration search is selected, NSETS, is input next. A choice of eigenvalue ranges, NEIRNG, is given next. The search is terminated if this range is violated during the search. An option to terminate the search iterations is input next. The parameter is ITEND, and the choices are: no restraint; terminate if convergence criteria are not met; terminate only if problem is not converging. The next input parameter is a terminate option on a nuclide concentration search, ICEND. The options are: terminate if any concentration becomes negative; terminate if any concentration is negative at the end of the search; allow negative concentrations. The last 19 inputs, (NRCH(I), I=1,19), are reserved integers.

The 3D Record is used for a dimension search only (i.e., ISRCH=5). Three arrays are given: The first dimension coarse mesh modifiers, (SRHD(I), I=1,NCINTI); the second dimension coarse mesh modifiers, (SRHDJ(J), J=1, NCINTJ); and the third dimension coarse mesh modifiers, (SRHDK, K=1,NCINTK).

The 4D Record is associated with a concentration search, where concentrations are made proportionately on selected initial concentrations (ISRCH=7). The first input is (NSHZ1(I), I=1,NSETS), where NSETS was given in the 2D Record as the number of specification sets in the concentration search. NSHZ1(I) is the first number of a consecutive set of zones if ISZOP=0, or a consecutive set of subzones if ISZOP=1. The parameter ISZOP is given in the 2D Record and defines whether the concentration search is done for zones or subzones. The second array listed is (NSHZ2(I), I=1,NSETS), and is the last number of a consecutive set of zones or subzones. Then the reference names of the nuclides whose concentrations are to be adjusted proportionately are given as (HNNAMS(N,I), N=1,NISOSR, I=1,NSETS). NISOSR is the number of isotopes involved in the concentration search, as given in the 2D Record. The final array is (HNSHN(J), J=1,10), which are search nuclide references, or names. They are used in the following prescription for conducting a concentration search by adjusting the concentrations proportionately: HNNAMES concentrations are adjusted according to $C2 = C1 * EI$, where EI is the eigenvalue, and C1 is the initial concentration, and C2 is the concentration after the adjustment. Then, HNSHN(J) concentrations can be adjusted according to $C2 = C1 + C1 * (1.0 - EI) * CMOD$, where CMOD is given in Record 2D.

The 5D Record adjusts nuclide concentrations by weighted eigenvalue adjustments on initial concentrations, if this option was chosen. The first set of entries, (NSHZ1(I), I=1,NSETS), are the

first numbers of a consecutive set of zones or subzones containing the nuclides whose concentrations are to be adjusted. The next set of numbers, (NSHZ2(I),I=1,NSETS), are the last numbers of the consecutive sets of zones or subzones. The names of the nuclides whose concentrations are to be adjusted are given next, in the format ((HNAMS(N,I),N=1,NISOSR),I=1,NSETS), as in the 4D Record. The concentration modifiers, ((CHDZN(N,I),N=1,NISOSR),I=1,NSETS), are then listed. The modification uses the formula $C2 = C1 + EI * CHZDN$, where $C1$ is the initial concentration, $C2$ is the new concentration, EI is the eigenvalue, and $CHZDN$ is the concentration modifier. The 5D Record completes the SEARCH file.

```

C*****
C              REVISED 7/22/75 - REVISED 04/01/80
C
CF          SEARCH - III
C
CE          CRITICALITY SEARCH FILE
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL      HNAME.(HUSE(I),I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - SEARCH - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                   1- A6 WORD IS SINGLE WORD
CD                   2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          INDIVIDUAL DATA SET IDENTIFIER (1D RECORD)
C
CL      NSHID,NREC,(NSO(I),I=1,18)
C
CW      20=NUMBER OF WORDS
C
CD      NSHID          POSITIVE INTEGER IDENTIFYING A SET OF SEARCH
CD                   DATA, THIS AND FOLLOWING RECORDS REPEATED
CD                   UNTIL NEGATIVE NSHID TERMINATES FILE
CD      NREC           NUMBER OF RECORDS TO SKIP TO POSITION ON NEXT
CD                   INDIVIDUAL DATA SET IDENTIFIER RECORD
CD      NSP(I)         RESERVED
C
C-----

C-----
CR          FILE SPECIFICATIONS          (2D RECORD)
C
CL      EFFK,DKEFF,EP SK,EPSEI,CMOD,(SRCH(I),I=1,5),ISRCH,ISZOP,NMAXNP,
CL      NCINTI,NCINTJ,NCINTK,NISOSR,NSETS,NEIRNG,ITEND,ICEND,
CL      NRCH(I),I=1,19)

```

Figure IX.1 Specifications for Innterface File SEARCH.

C			-
CW	40=NUMBER OF WORDS		-
C			-
CD	EFFK	DESIRED MULTIPLICATION FACTOR	-
CD	DKEFF	MULTIPLICATION FACTOR SLOPE	-
CD	EPSK	CONVERGENCE CRITERION TO BE MET BY EFFK	-
CD	EPSEI	CONVERGENCE CRITERION TO BE MET BY PRIMARY	-
CD		VARIABLE	-
CD	CMOD	MODIFIER APPLIED TO NUCLIDE CONCENTRATIONS	-
CD		VARIED SPECIALLY (ISRCH=7 BELOW), MAY BE	-
CD		.LT.0	-
CD	SRCH(I)	RESERVED	-
CD	ISRCH	TYPE OF SEARCH	-
CD		0- NOT DEFINED	-
CD		1- BUCKLING SEARCH	-
CD		2- ALPHA SEARCH	-
CD		5- DIMENSION SEARCH	-
CD		7- NUCLIDE CONCENTRATION SEARCH BY	-
CD		PROPORTIONAL ADJUSTMENTS OF SELECTED	-
CD		INITIAL CONCENTRATIONS	-
CD	ISZOP	SUBZONE OPTION FOR ISRCH = 7 OR 9	-
CD		0- SEARCH DATA IS BY ZONE	-
CD		1- SEARCH DATA IS BY SUBZONE	-
CD	NMAXNP	MAXIMUM NUMBER OF NEUTRONICS PROBLEMS OR	-
CD		TRIAL EIGENVALUES ALLOWED IN A SEARCH.	-
CD		A ZERO HERE SPECIFIES A DIRECT SEARCH.	-
CD	NCINTI	NUMBER OF FIRST DIMENSION COARSE MESH	-
CD		INTERVALS.	-
CD	NCINTJ	NUMBER OF SECOND DIMENSION COARSE MESH	-
CD		INTERVALS.	-
CD	NCINTK	NUMBER OF THIRD DIMENSION COARSE MESH	-
CD		INTERVALS.	-
CD	NISOSR	NUMBER OF ISOTOPES OR NUCLIDES INVOLVED IN	-
CD		CONCENTRATION SEARCH (ISRCH=7 OR 9)	-
CD	NSETS	NUMBER OF SPECIFICATION SETS IN CONCENTRATION-	-
CD		SEARCH (ISRCH = 7 OR 9)	-
CD	NEIRNG	EIGENVALUE (EI) RANGE RESTRICTIONS. SEARCH	-
CD		TERMINATED IF SPECIFIED RANGE IS VIOLATED.	-
CD		-1 EI.LT.0	-
CD		0- NO RESTRICTION ON EI	-
CD		1- EI.GT.0 AND .LT. 1	-
CD		2- EI.GT.1	-

Figure IX.1 Specifications for Interface File SEARCH (con't.)


```

CD      ITEND          TERMINATION OPTION ON ITERATIVE PROCESS.      -
CD                      SEARCH IS LIMITED BY NMAXNP. NUMBER OF OUTER-
CD                      ITERATIONS. OR OTHER PARAMETER. THEN          -
CD                      0- NO RESTRAINT                                -
CD                      1- TERMINATE IF CONVERGENCE CRITERIA ARE      -
CD                      NOT MET                                        -
CD                      2- IF CONVERGENCE CRITERIA ARE NOT MET,      -
CD                      TERMINATE ONLY IF PROBLEM IS NOT              -
CD                      CONVERGING.                                    -
CD      ICEND          TERMINATION OPTIONS ON NUCLIDE CONCENTRATIONS-
CD                      0- TERMINATE IF ANY NUCLIDE CONCENTRATION    -
CD                      BECOMES NEGATIVE AT ANY STAGE OF THE         -
CD                      CALCULATION.                                  -
CD                      1- TERMINATE IF ANY NUCLIDE CONCENTRATION    -
CD                      IS NEGATIVE AT THE END OF THE SEARCH        -
CD                      2- ALLOW NEGATIVE NUCLIDE CONCENTRATIONS    -
CD      NRCH(1)        .GT.0 - INDICATES THAT MACROSCOPIC CROSS    *-
CD                      SECTIONS ARE TO BE RECALCULATED DURING      *-
CD                      A DIRECT SEARCH                              *-
CD      NRCH(2)        .GT.0 - INDICATES SECONDARY SEARCH          *-
CD                      SPECIFICATIONS (REFERENCE SET) ARE TO BE    *-
CD                      USED IF THE SPECIFIED CONSTRAINTS ON THE    *-
CD                      SEARCH EIGENVALUE ARE NOT SATISFIED USING   *-
CD                      THE PRIMARY SEARCH DATA                    *-
CD      NRCH(3-19)     RESERVED                                      *-
C
C-----
C-----
CR          COARSE MESH MODIFIERS FOR DIMENSION SEARCH            -
CR          (3D RECORD)                                           -
C
CC          PRESENT ID# ISRCH.EQ.5                                -
C
CL          (SRHDI(I),I=1,NCINTI),(SRHDJ(J),J=1,NCINTJ),SRHDK(K),K=1,NCINTK) -
C
CW          NCINTI+NCINTJ+NCINTK=NUMBER OF WORDS                  -
C
CD          SRHDI(I)      FIRST DIMENSION COARSE MESH MODIFIERS    -
CD          SRHDJ(J)      SECOND DIMENSION COARSE MESH MODIFIERS   -
CD          SRHDK(K)      THIRD DIMENSION COARSE MESH MODIFIERS    -
C
C-----

```

Figure IX.1 Specifications for Interface File SEARCH (con't.)

```

C-----
CR          NUCLIDES FOR PROPORTIONAL SEARCH AND SPECIAL SEARCH          -
CR          (4D RECORD)                                                  -
C                                                                 -
CC          PRESENT IF ISRCH.EQ.7                                         -
C                                                                 -
CL          (NSHZ1(I),I=1,NSETS),(NSHZ2(I),I=1,NSETS).                  -
CL          ((HNNAMS(N,I),N=1,NISOSR),I=1,NSETS),(HNSHN(J),J=1,10)      -
C                                                                 -
CW          2*NSETS+MULT*(NISOSR*NSETS+10)=NUMBER OF WORDS              -
C                                                                 -
CD          NSHZ1(I)              FIRST NUMBER OF A CONSECUTIVE SET OF ZONES -
CD                                IF ISZOP.EQ.0, OR OF A CONSECUTIVE SET OF  -
CD                                SUBZONES IF ISZOP.EQ.1                    -
CD          NSHZ2(I)              LAST NUMBER OF A SET OF ZONES OR SUBZONES -
CD          HNNAMS(N,I)           REFERENCE NAMES OF NUCLIDES WHOSE        -
CD                                CONCENTRATIONS ARE TO BE ADJUSTED         -
CD                                PROPORTIONATELY IN ABOVE ZONES (A6)      -
CD          HNSHN(J)              SEARCH NUCLIDE REFERENCE USED AS NOTED BELOW -
CD                                (A6)                                       -
C                                                                 -
CC                                HNNAMS CONCENTRATIONS ADJUSTED ACCORDING TO -
CC                                 $C2 = C1*EI$  AND HNSHN CONCENTRATIONS ADJUSTED -
CC                                ACCORDING TO  $C2 = C1 + C1*(1.0-EI)*CMOD$  WHERE -
CC                                EI IS THE EIGENVALUE.                      -
CC                                C1 IS THE INITIAL CONCENTRATION, AND      -
CC                                C2 IS THE FINAL OR INTERMEDIATE VALUE OF  -
CC                                THE CONCENTRATION                         -
C                                                                 -
C-----

```

Figure IX.1 Specifications for Interface File SEARCH (con't.)

```

C-----
CR      NUCLIDES FOR SEARCH INVOLVING WEIGHTED EIGENVALUE      -
CR      ADJUSTMENTS TO INITIAL CONCENTRATIONS                -
CR      (5D RECORD)                                           -
C                                           -
CC      PRESENT IF ISRCH.EQ.9                                  -
C                                           -
CL      (NSHZ1(I),I=1,NSETS),(NSHZ2(I),I=1,NSETS),           -
CL      ((HNNAMS(N,I),N=1,NISOSR),I=1,NSETS),                -
CL      ((CHZDN(N,I),N=1,NISOSR),I=1,NSETS)                   -
C                                           -
CW      NSETS*(2+NISOSR*(1+MULT))=NUMBER OF WORDS            -
C                                           -
CD      NSHZ1(I0          FIRST NUMBER OF A CONSECUTIVE SET OF ZONES -
CD                        IF ISZOP.EQ.0, OR OF A CONSECUTIVE SET OF -
CD                        SUBZONES IF ISZOP.EQ.1                -
CD      NSHZ2(I)          LAST NUMBER OF A SET OF ZONES OR SUBZONES -
CD      HNNAMS(N,I)       REFERENCE NAMES OF NUCLIDES WHOSE      -
CD                        CONCENTRATIONS ARE TO BE ADJUSTED (A6) -
CD      CHZDN(N,I)        CONCENTRATION MODIFIERS                -
C                                           -
CC                        CONCENTRATIONS ADJUSTED ACCORDING TO   -
CC                        C2 = C1+EI*CHZDN WHERE EI,C1, AND C2 ARE -
CC                        AS DEFINED UNDER ISRC:I .EQ. 7         -
C                                           -
C-----

```

Figure IX.1 Specifications for Interface File SEAFCH (con't.)

IX.1 Example of SEARCH

An example of a search file is shown in Figure IX.1.1. The 1D Record shows that the first set of search data is identified with the number 7. Two records must be skipped after the 1D record to reach the next identifying number for the next set of data.

The first line of the 2D Record shows that the desired multiplication factor is 1.01, the multiplication factor slope is 0.0, the convergence criterion for the multiplication factor is 0.00005, the convergence criterion on the primary variable is 0.001, there is no modifier applied to nuclide concentrations, and 5 reserved locations are set to zero. The second line indicates that the type of search is a nuclide concentration search with weighted eigenvalue adjustments, search data is to be done by zone, a direct search is to be implemented, the number of coarse mesh intervals is not used and is set to zero for three dimensions, the number of nuclides involved in the concentration search is 3, the number of sets to be modified is 1, the eigenvalue range is greater than unity, there is no termination restraint on the iteration process, the problem should be terminated if any nuclide concentration becomes negative, and all other entries in the 2D Record are reserved and set to zero, except one which is set to 8.

There is no 3D Record since dimension searches have not been stipulated.

There is no 4D Record, since a proportional search on nuclide concentrations has not been specified.

The 5D Record indicates that the first number of a consecutive set of zones is 1, while the last number of the set of zones is 2. The reference names of nuclides whose concentrations are to be adjusted are U-238, PU-240, and PU-239. The concentration modifiers are 0.0001, 0.0002, and 0.0003, respectively.

The second set of search data begins with a new 1D Record, with an identifying number of 8, with two records skipped after the 1D Record to start another set of search data. This is the input associated with a secondary search, if the primary search fails to converge on the desired values.

The 2D Record shows that the desired eigenvalue is 1.01, the eigenvalue slope is 0.0, the convergence criterion for the eigenvalue is 0.00005, the convergence criterion on the search variable is 0.001, there is no modifier applied to nuclide concentrations, and 5 reserved locations are set to zero. A dimension search is specified, the search is to be done by zone, rather than subzone, the maximum number of trial eigenvalues allowed is 7, the number of first dimension coarse mesh intervals is 6, second dimension, 3, and third dimension 1. There are no

nuclides involved in a concentration search for this set of data, and the number of specification sets is zero, since a concentration search is not specified. The eigenvalue range is greater than unity. There is no termination restraint on the number of iterations, and the problem will terminate if any nuclide concentration becomes negative. The remaining reserved locations are set to zero.

Since this set of data is associated with a dimension search, the 3D record follows. The first dimension coarse mesh modifiers, one for each interval, are: 1.0; 1.0; 1.0; 1.0; 0.0; and 0.0. The second dimension modifiers are 0.0, 0.0, and 0.5, while the third dimension modifier is set to zero.

The next 1D Record is negative, and indicates the end of the search data.

```

OV SEARCH
1D /
  7  2  0 18R /
2D /
  1.01  0.0  0.00005  0.001  0.0 6R /
  9  0  0  0 3R  3  1  2  0  0  0  8  0 17R /
5D /
  1  2 /
*U-238 * *PU-240* *PU-239* /
  0.0001  0.0002  0.0003
1D /
  8  2  0 18R /
2D /
  1.01  0.0  0.00005  0.001  0.0 6R /
  5  0  7  6  3  1  0  0  2  0  0  0  0  0 18R /
3D /
  1.0  1.0  1.0  1.0  0.0  0.0 /
  0.0  0.0  0.5 /
  0.0
1D /
  -10  0 19R /
STOP
END

```

Figure IX.1.1 example of SEARCH Interface File.

X. Burnup Problems and the EXPOSE File.

The EXPOSE file is used by the BURNER¹ code to provide the basic data required for solving the chain equations in burnup analysis. It identifies the nuclides associated with the problem, including the fissioning nuclides and the fission products. It also provides decay, yield, energy and coupling data. The EXPOSE file is shown as Figure X.1 This file includes the following data sections:

- 1D Record - File Reference Information
- 2D Record - Title and Nuclide Names
- 3D Record - Reference Data
- 4D Record - Decay Data
- 5D Record - Fission Product Yield Data
- 6D Record - Chain Data for Matrix Exponential or Average Generation Rate
- 7D Record - Chain Data Supplemental Explicit
- 8D Record - Chain Data, Complete Basic data to Apply Explicit Solution
- 9D Record - Decay Energy Release Data
- 10D Record - Secondary Energy release From Fission
- 11D Data - Energy release from capture

The 1D Record provides file reference information, which requires 20 integers. These include: the file reference number (zero is acceptable), NEXP1; the number of nuclides involved in burnup, NISOE; an option to use absolute nuclide names or user defined names, NAMOPT; the number of incident neutron energy ranges for yield data, NYER; the number of energy ranges for gamma rays, NGER; the number of fissile nuclides which yield fission products, NFSLR; the number of fission products which have a yield, NFPR; the number of nuclides which decay, NDCYR; three reserved data locations, NEXP9, NEXP10, NEXP11; the number of matrix exponential data entries, NMATEX; the number of data entries in the supplementing table of explicit chain data, LSEXCH; the number of entries in the basic table of explicit chain data, LBEXCH; a reserved data location, NEXP15; an option indicating that beta particle and gamma ray data associated with the decay process will be included, NOEDCT; an option indicating that beta particle and gamma ray data associated with the fission process will be included, NOEFIS; an option indicating that beta particle and gamma ray data for the capture process is included, NOECAP; two reserved locations, NEXP19, NEXP20.

The 2D Record provides the title and the nuclide names. All further references to nuclides are by the order number given in this record. The first entry is the title, (HTL(J), J=1, 12) in (12A6) or equivalent format. Then the nuclides are named, (HNUC(I), I=1, NISOE), with each name totaling 6 letters. The order in which the naming is done should be the order in which the nuclides appear in the chain. Dominating chains, such as uranium to plutonium, and

iodine to xenon, should be named first. Fission product decay chains should be named last.

The 3D Record provides additional reference data. The neutron energies associated with different fission yields are broken up into energy ranges. The first set of entries in the 3D Record includes the lowest energies of each of these ranges, in decreasing order, (YER(N), N=1, NYER). The last entry is typically zero, and a single entry is usually zero. Then, the mean or effective energy of gamma rays are listed in decreasing order (GER(J), J=1, NGER). The units are in eV per gamma ray. The order number assigned to fissile nuclides for reference follows, (IFSLR(K), K=1, NFSLR). The order number of fission products (those nuclides for which fission yield data are given) for future reference is listed next ((IFPR(L), L=1, NFPR). Finally, the reference order number for nuclides which decay are given (IDCYR(I), I=1, NDCYR).

The 4D Record provides decay data. In particular, the total decay constant for nuclide ordered I in the reference set IDCYR(I) are listed, (ALMDA(I), I=1, NDCYR). The units are in inverse seconds.

The 5D Record provides fission product yield data. The fission product, the fissile nuclide, and the energy range for inducing fission must all be identified. The format used is (((YFFP(K,L,N), K=1, NFSLR), L=1, NFPR), N=1, NYER), for the yield of fission product IFPR(L) from the fissioning of nuclide IFSLR(K), in the neutron energy range N. The units for the yield are atoms per second per fission per second.

The 6D Record provides data for the Matrix Exponential or Average Generation Rate methods. The input format is given as: ((MATXE(J,I), J=1,3), I=1, NMAXTE), where NMAXTE was given in the 1D Record as the number of Matrix Exponential data entries. The first entry in this array, MAXTE(1,I) is the source nuclide. The second entry, MAXTE(2,I), is the product nuclide, while the third entry, MAXTE(3,I), specifies the transformation process. The options on the transformation process include: not allowed, 0; decay, 1; (N,Gamma), 2; (N,Alpha) 3; (N,P), 4; (N,2N), 5; (N,D), 6; (N,T) 7; fission, 8 (not to be used for products with yield data); total Capture (absorption less fission), 9. Partial rates of product generation can be considered. This can be done by expressing the decay fraction in parts per million. For example, the fraction 0.5 is expressed in parts per million as 500000. The number associated with the transformation process listed above is then added to the parts per million to establish the number to use for the transformation process. The example given in the 6D record is as follows. Suppose the partial capture routes of Pm-147 are to Pm-148, at a fraction of 0.53, and to Pm-148M at a fraction of 0.47, the appropriate entries to indicate (N, Gamma) reaction products are 53002 for Pm-148, and 47002 for Pm-148M.

The 7D Record provides supplemental chain data for an explicit chain, which may be specified in problems using the Matrix Exponential method. The entries include the parent nuclide, followed by the transmutation process as given in the 6D Record, followed by the product nucleus. These entries are then followed by the next transmutation process, and the next nucleus in the chain. The entry format is: (NSXCH(I), I=1,LSEXCH), where LSEXCH is specified in the 1D Record as the number of entries in the supplemental explicit table. An entry of zero is used to indicate the chain is completed. Two successive zeros indicate the end of the data for this record.

The 8D Record provides a complete list of data for the explicit solution method. As in the 7D Record, the first entry is the first nuclide in the first chain, followed by the transmutation process, followed by the product nuclide, followed by the next transmutation process, followed by the next nuclide in the chain, etc. A chain ends with a zero entry, and then the next chain begins. A zero following the zero of the end of the chain, signifies the end of data. A nuclide cannot be repeated in a given chain, but can be produced in multiple ways through branching. If a nuclide is produced in two independent manners, the second generation is denoted by a minus sign in front of the nuclide reference number. The example shown in the record description is as follows: 1 02 2 02 3 01 4 02 5 0 1 02 2 01 6 02 -4 02 -5 0 0. The numbers with preceding zeros are transmutation processes. Nuclides 4 and 5 are produced in two independent manners. This is indicated by minus signs in front of them for the second generation process. The format used for this record is as follows: (NBXCH(I), I=1, LBEXCH), where LBEXCH is given in the 1D Record as the number of entries in the basic table of explicit chain data.

The 9D Record provides decay energy release data. The format for this record is: ((EGAMA(I,J), I=1,NDCYR),J=1,NGER), (EBETA(I), I=1,NDCYR), (EDCY(I), I=1,NDCYR). Here, EGAMA(I,J) is the energy released as gamma rays in energy range J, per atomic decay of parent nuclide IDCYR(I). IDCYR(I) was defined in the 3D record as reference order number of nuclide I which decays. NDCYR was defined in the 1D Record as the number of nuclides which decay, while NGER was defined as the number of energy releases for gamma rays. The units for energy are eV. EBETA(I) is the energy released as beta particles per atomic decay of the parent, in eV, while EDCY(I) is the total energy released per atomic decay of the parent nuclide in eV.

The 10D Record provides the secondary energy release from fission. Again, the energy release is broken into gamma ray release and beta particle release. The format for this record is: ((EFGAM(I,J), I=1,NFSLR), J=1,NGER), (EFBAT(I), I=1,NFSLR). Here EFGAM(I,J) is the amount of energy released per atomic fission of nuclide IFSLR(I) in the form of gamma rays in energy range J. The units are, again, eV. NFSLR was defined in the 1D Record as the

number of nuclides which yield fission products, and NGER as the number of energy ranges for gamma rays. EFBAT(I) is the energy release as beta particles per fission, in eV.

The 11D Record provides the energy release from capture. Gamma ray and beta particle energy release are again differentiated. The format is: ((ECGAM(I,J), I=1,NISOF), J=1, NGER), for the first entry, and (ECBAT(I), I=1,NISOE) for the second entry. the parameter ECGAM(I,J) is the amount of energy released in the form of gamma rays per atomic capture in nuclide I, in the energy range J, in eV. NISOE is the number of nuclides, as defined in the 1D Record. NGER is the number of energy ranges for gamma rays. ECBAT(I) is the energy released as beta particles per atomic capture in nuclide I. The energy is given in eV.

```

C*****
C          REFERENCE 02/01/79  ORNL-5180
C
CF          EXPOSE
C
CE          DATA FOR EXPOSURE CALCULATIONS
C
CN          THE BASIC DATA REQUIRED FOR SOLVING THE CHAIN
CN          EQUATIONS IDENTIFIES NUCLIDES, FISSIONING
CN          NUCLIDES, FISSION PRODUCTS, AND GIVES DECAY. YIELD. ENERGY.
CN          AND COUPLING DATA
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME, (HUSE(I), I=1,2), IVERS
C
CW          3*MULT + 1
C
CD          HNAME          FILE NAME (A6) 'EXPOSE'
CD          HUSE           USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CN          MULT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINE
C
C-----

```

Figure X.1 Specifications for Interface File EXPOSE

```

C-----
CR      1D      FILE REFERENCE INFORMATION
C
CL      NEXP1,NISOE,NAMOPT,NYER,NGER,NFSLR,NFPR,NDCYR,NEXP9,NEXP10.
CL      NEXP11,NMATXE,LSEXCH,LBEXCH,NEXP15,NOEDCY,NOEFIS,NOECAP.
CL      NEXP19,NEXP20
C
CW              20
C
CN      UNDEFINED DATA IS RESERVED FOR FUTURE USE
C
CD      NEXP1          DOCUMENTING FILE REFERENCE NUMBER
CD      NISOE          REFERENCE NUMBER OF NUCLIDES
CD                        MUST BE NON-ZERO
CD      NAMOPT        OPTION ON NUCLIDE NAMES
CD                        IF 0 - THEY ARE ABSOLUTE NAMES
CD                        IF 1 - THEY ARE USER LABELS
C
CN                        IN FILE ISOTXS, ABSOLUTE LABELS ARE
CN                        HABSID, WHILE USER LABELS ARE HISONM
C
CN                        UNIQUE NAMES ARE REQUIRED HERE
CD      NYER          NUMBER OF ENERGY RANGES FOR YIELD DATA
CD                        (GENERALLY NON-ZERO)
CD      NGER          NUMBER OF ENERGY RANGES FOR GAMMA RAYS
CD      NFSLR         NUMBER OF IDENTIFIED FISSION NUCLIDE WHICH YIELD
CD                        FISSION PRODUCTS
CD      NFPR          NUMBER FISSION PRODUCTS HAVING YIELD
CD      NDCYR         NUMBER OF NUCLIDES WHICH DECAY
CD      NEXP9         RESERVED
CD      NEXP10        RESERVED
CD      NEXP11        RESERVED
CD      NMATXE        OPTION IF .GT.0 INDICATING THE NUMBER
CD                        OF MATRIX EXPONENTIAL DATA ENTRIES
CD      LSEXCH        OPTION IF .GT.0 INDICATING THE NUMBER
CD                        OF ENTRIES IN THE SUPPLEMENTING TABLE OF EXPLICIT
CD                        CHAIN DATA (USED WITH MATRIX DATA)
CD      LBEXCH        OPTION IF .GT.0 INDICATING THE NUMBER
CD                        OF ENTRIES IN THE BASIC TABLE OF EXPLICIT
CD                        CHAIN DATA (USED ONLY ALONE)
CD      NEXP15        RESERVED
CD      NOEDCY        OPTION INDICATING DATA FOR THE DECAY PROCESS
CD                        IS INCLUDED FOR GAMMA RAYS AND BETA PARTICLES
CD      NOEFIS        OPTION INDICATING DATA FOR THE FISSION PROCESS
CD                        IS INCLUDED FOR GAMMA RAYS AND BETA PARTICLES
CD      NOECAP        OPTION INDICATING DATA FOR THE CAPTURE PROCESS
CD                        IS INCLUDED FOR GAMMA RAYS AND BETA PARTICLES
CD      NEXP19        RESERVED
CD      NEXP20        RESERVED
C
C-----

```

Figure X.1 Specifications for Interface File EXPOSE

```

C-----
CR      2D      TITLE AND NUCLIDE NAMES      -
C                                           -
CC      ALWAYS PRESENT                      -
C                                           -
CN      HEREFTER ALL REFERENCES TO NUCLIDES IN THIS FILE ARE -
CN      BY THE ORDER NUMBER IN THIS TABLE OF NAMES      -
C                                           -
CL      (HTL(J),J=1,12),(HNUC(I),I=1,NISOE)      -
C                                           -
CW      MULT*(12+NISOE)                    -
C                                           -
CD      HTL      DOCUMENTING TITLE (12A6)      -
CD      HNUC(I)   NAME OF NUCLIDE ORDERED I (A6) SEE NAMOPT OPTION -
C                                           -
CN      ALL NUCLIDES TO BE TREATED (EXPOSURE CALCULATED) MUST BE -
CN      NAMED IN THIS LIST (NORMALLY EXCLUDE COOLANT, STRUCTURE). -
C                                           -
CN      WHEN THE AVERAGE GENERATION RATE METHOD IS USED, THESE -
CN      SPECIFICATIONS ARE PROCESSED IN THE ORDER IN THIS LIST, SO-
CN      THEY SHOULD BE ORDERED ALONG CHAINS, DOMINATING ROUTES -
CN      FIRST (EXAMPLE,  U....PU, I..XE, XE..CS), FISSION -
CN      PRODUCTS LAST.                      -
C                                           -
CN      NUCLIDES SPECIFIED HERE BUT ABSENT IN THE SYSTEM OF COURSE-
CN      ARE NOT TREATED - IMPACTS ARE DOCUMENTED ELSEWHERE      -
C                                           -
C-----

```

Figure X.1 Specifications for Interface File EXPOSE (con't.)

```

C-----
CR      3D      REFERENCE DATA
C
CC      PRESENT IF NYER+NGER+NFSLR+NFPR+NDCYR.GT.0
C
CL      (YER(N).N=1,NYER).(CER(J).J=1,NGER).(IFSLR(K).K=1,NFSLR).
CL      (IFPR(L).L=1,NFPR).(IDCYR(I).I=1,NDCYR)
C
CW      NYER+NGER+NFSLR+NFPR+NDCYR
C
CD      YER      LOWER ENERGY OF RANGE OF INCIDENT
CD      NEUTRON ENERGY (EV), DECREASING ORDER
CD      (LAST NUMBER TYPICALLY ZERO, SINGLE VALUE USUALLY 0)
CD      GER      MEAN OR EFFECTIVE ENERGY OF EACH RANGE
CD      OF DATA FOR GAMMA RAY ENERGY DATA, ORDERED BY
CD      DECREASING ENERGY, FOR DOCUMENTATION (EV PER PART.)
CD      IFSLR     REFERENCE ORDER NUMBER OF IDENTIFIED
CD      NUCLIDES WHICH FISSION
CD      IFPR      REFERENCE ORDER NUMBER OF FISSION PRODUCTS
CD      (NUCLIDES FOR WHICH FISSION YIELD DATA IS GIVEN)
CD      IDCYR     REFERENCE ORDER NUMBER OF NUCLIDES WHICH DECAY
C
C-----

C-----
CR      4D      DECAY DATA
C
CC      PRESENT IF NDCYR.GT.0
C
CL      (ALMDA(I).I=1,NDCYR)
C
CW      NDCYR
C
CD      ALMDA     TOTAL DECAY CONSTANT FOR NUCLIDE ORDERED I IN THE
CD      REFERENCE SET IDCYR(I) (SEC-1)
C
C-----

```

Figure X.1 Specifications for Interface File EXPOSE (con't.)

```

C-----
CR      5D      FISSION PRODUCT YIELD DATA      -
C                                           -
CC              PRESENT IF NFSLR*NFPR*NYER.GT.0      -
C                                           -
CL      (((YFFP(K,L,N).K=1,NFSLR).L=1,NFPR).N=1,NYER)      -
C                                           -
CW              NFSLR*NFPR*NYER      -
C                                           -
CD      YFFP(K,L,N)  YIELD OF FISSION PRODUCT IFPR(L) FROM      -
CD                      FISSION OF NUCLIDE IFSLR(K) DUE TO FISSIONING      -
CD                      NEUTRON IN ENERGY RANGE N      -
CD                      (ATOMS PER SECOND PER FISSION PER SECOND)      -
C-----

C-----
CR      6D      CHAIN DATA FOR MATRIX EXPONENTIAL OR AVERAGE GENERATION RATE-
C                                           -
CC              PRESENT IF NMATXE.GT.0      -
C                                           -
CL      ((MATXE(J,I),J=1,3),I=1,NMATXE)      -
C                                           -
CW              3*NMATXE      -
C                                           -
CD      MATXE(1,I)    SOURCE NUCLIDE      -
CD      MATXE(2,I)    PRODUCT NUCLIDE      -
CD      MATXE(3,I)    SPECIFIES THE TRANSMUTATION PROCESS,      -
CD                      0- NOT ALLOWED      -
CD                      1- DECAY      -
CD                      2- (N,GAMMA), USUAL CAPTURE UP THE CHAIN      -
CD                      3- (N,ALPHA)      -
CD                      4- (N,P)      -
CD                      5- (N,2N), DOWN THE CHAIN      -
CD                      6- (N,D)      -
CD                      7- (N,T)      -
CD                      8- FISSION (DO NOT SPECIFY FOR A FISSION PRODUCT -
CD                          FOR WHICH YIELD DATA IS GIVEN. THIS IS TREATED-
CD                          DIRECTLY)      -
CD                      9- TOTAL CAPTURE, TOTAL ABSORPTION LESS FISSION      -
C

```

Figure X.1 Specifications for Interface File EXPOSE (con't.)

CN PARTIAL RATES OF PRODUCT GENERATION CAN BE CONSIDERED. THE -
 CN PARTS PER MILLION IS EXPRESSED AS AN INTEGER (500000 IS THE -
 CN FRACTION 0.5). ROUNDED TO THE NEAREST TEN (LAST DIGIT ZERO). -
 CN ADDED TO THE NUMBER FROM THE ABOVE TABLE TO SPECIFY THE -
 CN TRANSMUTATION PROCESS. FOR EXAMPLE, IF THE PARTIAL CAPTURE -
 CN ROUTES OF PM-147 TO PM-148 AND TO PM-148M ARE BOTH TO BE -
 CN CONSIDERED, THE FIRST AT FRACTION 0.53, THE APPROPRIATE -
 CN ENTRIES TO INDICATE (N,GAMMA) REACTION PRODUCTS ARE 530002 -
 CN FOR THE PRODUCT PM-148 AND 470002 FOR PM148M. LESS THAN -
 CN A TOTAL FRACTION OF UNITY MAY BE SPECIFIED, BUT TAKE CARE. -
 C -
 C-----

C-----
 CR 7D CHAIN DATA, SUPPLEMENTAL EXPLICIT -
 C -
 CC PRESENT IF LSEXCH.GT.0 -
 C -
 CL (NXSCH(I), I=1, LSEXCH) -
 C -
 CW LSEXCH -
 C -
 CD NSXCH ENTRY IN THE SUPPLEMENTAL EXPLICIT CHAIN -
 CD DATA TABLE (SEE DESCRIPTION BELOW) -
 C -
 C-----

C-----
 CR 8D CHAIN DATA, COMPLETE BASIC DATA TO APPLY EXPLICIT SOLUTION -
 C -
 CC PRESENT IF LBEXCH.GT.0 -
 C -
 CL (NBXCH(I), I=1, LBEXCH) -
 C -
 CW LBEXCH -
 C -
 CD NBXCH ENTRY IN THE BASIC EXPLICIT CHAIN DATA TABLE, -
 CD OUTLINED HERE -
 C -
 CN THE FIRST ENTRY IS THE FIRST NUCLIDE IN THE FIRST -
 CN CHAIN. THE NEXT ENTRY IS THE TRANSMUTATION PROCESS FOR -
 CN GENERATION OF THE PRODUCT (SEE THE VALUES OF MATXE(3,I) IN -
 CN THE TABLE ABOVE). THE NEXT ENTRY IN THE LIST IS THE FIRST -
 CN PRODUCT IN THE FIRST CHAIN. THUS FOR N NUCLIDES IN A CHAIN, -
 CN THERE ARE 2*(N-1)+1 ENTRIES FOR THE CHAIN. THEN THERE IS A -
 CN ZERO ENTRY. DATA FOLLOWS FOR THE NEXT CHAIN. A FINAL -
 CN EXTRA ZERO IS PLACED AT THE END AFTER THE LAST CHAIN WHICH -
 CN FLAGS THE END OF CHAINS. TWO ZERO ENTRIES AT THE END. -
 CN ENTER ACTINIDE CHAINS FIRST. -
 CN

Figure X.1 Specifications for Interface File EXPOSE (con't.)


```

C
CN      REPEAT OF A NUCLIDE REFERENCE IN A CHAIN IS NOT ALLOWED.
CN      GIVEN A FIRST APPEARANCE IN ONE CHAIN, SUBSEQUENT ENTRIES OF
CN      A NUCLIDE REFERENCE INDICATE OTHER GENERATION ROUTES WHICH
CN      CONTRIBUTE INDEPENDENTLY. CARE MUST BE TAKEN TO SUPPLY
CN      REASONABLE SPECIFICATIONS. ONLY THE ACTUAL CHAINS SHOWN
CN      WILL BE TREATED, SO FULL SPECIFICATIONS REQUIRING REPEATS
CN      ARE REQUIRED. AND ONLY LIMITED BRANCHING IS ALLOWED.
CN      THE CONTRIBUTIONS ALONG A ROUTE THROUGH THE CHAINS ARE ONLY
CN      THOSE FOR THE NUCLIDES ACTUALLY GIVEN FOR THAT CHAIN.
CN      AS AN EXAMPLE. THE TABLE
CN      1 +02 2 +02 3 +01 4 +02 5 0 1 +02 2 +01 6 +02 -4 +02 -5 0 0
CN      ALLOWS TWO ROUTES TO BE TREATED FOR GENERATION OF NUCLIDES
CN      REFERENCED 4 AND 5. THE -4 AND -5 IN THE SECOND CHAIN
CN      INDICATE THESE CONTRIBUTIONS ARE ADDITIONAL.
C
CN      ONLY NUCLIDES GIVEN IN THESE CHAINS WILL BE TREATED
CN      (EXPOSED)
C
C-----

C-----
CR      9D      DECAY ENERGY RELEASE DATA
C
CC      PRESENT IF NOEDCY.GT.0.AND.NDCYR*NGER+2).GT.0
C
CL      ((EGAMA(I,J),I=1,NDCIR),J=1,NGER),(EBETA(I),I=1,NDCYR).
CL      (EDCY(I),I=1,NDCYR)
C
CW      NDCYR*(NGER+2)
C
CD      EGAMA(I,J)  THE AMOUNT OF ENERGY RELEASED PER ATOMIC
CD                  DECAY OF PARENT NUCLIDE IDCYR(I)
CD                  AS GAMMA RAYS IN ENERGY RANGE J (EV)
CD      EBETA(I)   THE AMOUNT OF ENERGY RELEASED PER
CD                  ATOMIC DECAY OF PARENT NUCLIDE IDCYR(I)
CD                  AS BETA PARTICLES (EV)
CD      EDCY(I)    THE AMOUNT OF ENERGY RELEASED PER ATOMIC DECAY OF
CD                  PARENT NUCLIDE IDCYR(I), (EV)
C
C-----

```

Figure X.1 Specifications for Interface File EXPOSE (con't.)

```

C-----
CR      10D      SECONDARY ENERGY FROM FISSION -
C -
CC          PRESENT IF NOEFIS.GT.0.AND.NFSLR*(NGER+1).GT.0 -
C -
CL      ((EFGAM(I,J),I=1,NFSLR),J=1,NGER),(EFBAT(I),I=1,NFSLR) -
C -
CW          NFSLR*(NGER+1) -
C -
CD      EFGAM(I,J)      THE AMOUNT OF ENERGY RELEASED PER -
CD                        ATOMIC FISSION OF NUCLIDE IFSLR(I) -
CD                        AS GAMMA RAYS IN ENERGY RANGE J (EV) -
CD      EFBAT(I)        THE AMOUNT OF ENERGY RELEASED PER ATOMIC -
CD                        FISSION OF NUCLIDE IFSLR(I) AS BETA PARTICLES (EV)-
C -
C-----

C-----
CR      11D      ENERGY RELEASE PER CAPTURE -
C -
CC          PRESENT IF NOECAP.GT.0.AND.NISOE*(NGER+1).GT.0 -
C -
CL      ((ECGAM(I,J),I=1,NISOE),J=1,NGER),(ECBAT(I),I=1,NISOE) -
C -
CW          NISOE*(NGER+1) -
CD      ECGAM(I,J)      THE AMOUNT OF ENERGY RELEASED PER -
CD                        ATOMIC CAPTURE OF NUCLIDE I AS GAMMA RAYS -
CD                        IN ENERGY RANGE J (EV) -
CD      ECBAT(I)        THE AMOUNT OF ENERGY RELEASED PER ATOMIC -
CD                        CAPTURE OF NUCLIDE I AS BETA PARTICLES (EV) -
C -
C-----

C*****
C
CEOF
C
C*****

```

Figure X.1 Specifications for Interface File EXPOSE (con't.)

X.1 Example of EXPOSE File.

An example of an EXPOSE file is shown in Figure X.1.1. The input is through the Input Processor, so the file identification is given as "OV EXPOSE". The 1D record follows. It shows that the documenting file reference number is set to zero, the number of nuclides is 14, the nuclide names will be absolute, the number of energy ranges for yield data is 1, the number of energy ranges for gamma rays is 0, the number of fissile nuclides is 7, the number of fission products assigned a yield is 5, the number of nuclides which decay is 5, three zero's for reserved data, the number of matrix exponential data entries is 10, the number of explicit entries in the supplemental table is 3, and the number of entries in the basic table for explicit chain data is 33. The remaining 6 entries are either reserved or apply to decay data, and are all set to zero.

The 2D Record provides the title for the problem. and a listing of the nuclides applicable to the analysis. These include: U235, U236, U238, PU239, PU240, PU241, PU242, XE135, PM147, SM149, NSFP, SSFP, PM148M, and PM148. The list includes non saturated fission products (NSFP), and saturated fission products (SSFP). Note the spaces between the asterisks since alphanumeric names are required to be 6 letters (or spaces) in length.

The 3D Record shows the lowest energy for the incident neutrons is zero, and there is only one such energy. Since there are no energy ranges for gamma rays, there is no GER(J) array. The reference order numbers for the identified nuclides which fission are: 1,2,3,4,5,6 and 7. That includes the uranium and plutonium isotopes listed in the 2D Record. The reference order numbers for fission products, i.e., those nuclides with yield data, are: 8, 9, 10, 11, and 12. That includes Xenon, Promethium, Samarium, and the fission products. The reference order numbers for the nuclides which decay are: 6, 8, 9, 13, and 14. This includes PU242, PM147, SM149, PM148M, and PM148.

The 4D Record gives the decay constants for the 5 decaying nuclides. The decay constant for PU242 is 1.689-9; for PM147, 2.093-5; 8.289-5 for SM149; 1.976-7 for PM148M; and 1.488-6 for PM148. All decay constants are given in inverse seconds.

The 5D Record gives the yields for the fission products. There are 7 yields each for the 5 fission products, one yield for each fissile nuclide. The yields are listed for each fission product in the order that the fission products are listed.

The 6D Record gives the chain data for the Matrix Exponential Method. The first chain listed is 3 4 2, indicating the parent nuclide is the third one listed, i.e., U238, the product nucleus is the fourth one listed, PU239, and the transition process is

(N, Gamma), as specified by the 2 entry. The second set is 4 5 2, converting PU239 to PU240 by neutron capture. The next set is 5 6 and 2, converting PU240 to PU241 by neutron capture. This is followed by 6 7 2, converting PU241 to PU242 by neutron capture. Then 1 2 2 is listed, converting U235 to U236 by neutron capture. This is followed by 9 13 9000002, which converts PM147 to PM 148M in 90% of the neutron capture reactions in PM147. The next set is 13 10 and 2, wher PM148M is converted to SM149 by neutron capture. Then 9 14 100002 is given, for the remaining 10 % of the conversions of FM147, resulting in PM148 by neutron capture. The next chain is defined by 14 10 2, converting PM148 to SM149 by neutron capture. The final chain is 12 11 2, converting saturated fission products to nonsaturated fission products by neutron capture.

The 7D Record provides supplemental explicit chain data. The sequence of numbers is 8 0 0, meaning that XE135, isotope number 8, is treated explicitly. It is converted to an unlisted isotope, probably XE136, however. The first 0 indicates an end to the chain, while the second following zero indicates an end to the record.

The 8D Record gives the basic data for the Explicit Method. The first number of a sequence of three numbers represents the nuclide to be transformed. the second number the transformation process, and the third number the product nucleus. The first set , 3 2 4 indicates that U238 is converted to PU239 by neutron capture. The second grouping, 4 2 5 indicates that PU239 is converted to PU240 by capture. The third set, 5 2 6 produces PU241 from PU240 by capture, and the final set in this chain, 6 2 7 results in PU242 from capture in PU241. The final zero indicates an end to this chain. The second chain, 1 2 2, indicates that U235 is converted to U2326 by neutron capture. The third chain implies that the ninth isotope is converted to the 13'th isotope in 90% of the captures. This converts PM147 to PM148M. Then, the 13'th nuclide is converted to the 10'th by capture. That is, Pm148M converts to SM149 by capture. This chain is then ended with a zero. The next chain shows that in 10% of the captures, the ninth isotope, PM147, is converted by capture to the 14'th nuclide, PM148. Then PM148 is converted by capture to SM149. The minus sign in front of the 10'th nuclide, SM149, implies that this generation route is a second route, and not the principal route. A zero ends this chain. The XE135 chain is next, but since it is converted to an unnamed an unreferenced isotope, this chain is immediately ended with a zero as the second entry. The final chain 12 2 11, converts the saturated fission products to unsaturated ones through neutron capture. The double zero then ends this data record.

Since there is no decay data, that completes the EXPOSE file for this problem.

```

OV EXPOSE
1D 0 14 0 1 0 7 5 5 0 0 0 10 3 33 0 0 0 0 0
2D /
* DEPLETION TEST CASE - SIMILAR TO A CITATION TEST CASE *
*U235 * *U236 * *U238 * *PU239 * *PU240 * *PU241 * *PU242 * *XE135 *
*PM147 * *SM149 * *NSFP * *SSFP * *PM148M* *PM148 *
3D 0.0 /
  1 2 3 4 5 6 7 /
  8 9 10 11 12 /
  6 8 9 13 14
4D 1.689-9 2.093-5 8.289-9 1.976-7 1.488-6 /DECAY CONSTANTS
5D 0.0715 0.06 0.06 0.0715 0.06 0.0715 0.06 / XE135 YIELD
  0.027 0.03 0.03 0.027 0.03 0.027 0.03 / PM147 YIELD
  0.013 0.02 0.02 0.013 0.02 0.013 0.02 / SM149 YIELD
  1.5011 1.5466 1.5466 1.5011 1.5466 1.5011 1.5466 /NSFP YIELD
  0.0134 7R / SSFP YIELD
6D / MATRIX EXPONENTIAL OR AVERAGE GENERATION RATE
  3 4 2 4 5 2 5 6 2 6 7 2 1 2 2 /
  9 13 900002 13 10 2 9 14 100002 14 10 2 12 11 2 /
7D / SUPPLEMENTAL EXPLICIT CHAINS
  8 0 0 /
8D / BASIC EXPLICIT CHAINS
  3 2 4 2 5 2 6 2 7 0 /
  1 2 2 0 /
  9 900002 13 2 10 0 /
  9 100002 14 2 -10 0 /
  8 0 /
  12 2 11 0 0 /

```

Figure X.1.1 Example of EXPOSE Interface File

XI. Control Files and Standard Interface File "CONTRL".

Control files are used by calculational modules such as VENTURE and BURNER to select the control options associated with the calculational module. They are, therefore, code dependent. They can, however, be inserted into the input stream through the Input Processor, since they are considered to be part of the standard interface file named "CONTRL". Each calculational module has a record on this file which controls the calculation for that module. Each of these records consists of the name of the record, 100 floating point numbers or characters written as REAL*8, and 100 integers. The floating point numbers or characters are designated as XX(I), and the integers as IX(I). Two examples will be shown. These are the PROINS record, or Problem Information Record, and DVRINS, a record which provides Driving Information. Both records are required for the VENTURE code system. There are many other control records associated with the VENTURE code system. Some of the more important ones are XCPINS, for controlling the Cross Section Processor, DTNINS for providing neutronics instructions to the VENTURE neutronics module, and EXPINS for supplying instructions to the exposure module. All of these files end in "INS" which, although not documented, must abbreviate the word "instructions", or "information".

Since each of these specifications refer to a single record, each record is a 1D Record.

XI.1 Problem Information Record, PROINS.

The specifications for the PROINS record is shown in Figure XI.1. All control records must begin with the name of the record, for unambiguous identification. The first 24 floating point or character locations are associated with the problem title. The title is written in A6 format. The next two character locations are used for the user label, again written in A6 format. The remaining floating point locations are reserved, as are all of the 100 integer locations.

C	-----		-
CR	PROBLEM INFORMATION		-
C			-
CL	PROINS, (XX(I),I=1,100),(IX(I),I=1,100)		-
C			-
CW	101*MULT + 100		-
C			-
CD	PROINS	PROBLEM INFORMATION DATA IDENTIFIER (6HPROINS)	-
C			-
CD	XX(1-24)	PROBLEM OR CASE TITLE (A6)	-
C			-
CD	XX(25)	USER LABEL (JOBNAME) FOR INTERFACE DATA FILES (A6)	-
C			-
CD	XX(26)	USER LABEL (DATE) FOR INTERFACE DATA FILES (A6)	-
C			-
CD	XX(27-100)	RESERVED	-
C			-
CD	IX(1-100)	RESERVED	-
C			-
C	-----		-

Figure XI.1 Specifications for PROINS Record in Interface File CONTRL

XI.1.1 Example of PROINS Record.

An example of the PROINS Record as read by the Input Processor is shown in Figure XI.1.1. To identify the file containing this record, the input starts with the "OV CONTRL" line, as required by all standard interface files processed by the Input Processor. All the control records are assumed to be "1D" records, since they are all a single record. The name of the record, however, must follow the "1D" specification, as shown in Figure XI.1.1, so the record will be unambiguously identified. Since the title occupies 24 A6 locations, or 144 bytes of data, it consumes two 72 column lines. The preferable way to handle characters with the Input Processor is to enclose them in asterisks. The two title lines are, therefore, enclosed in asterisks placed in columns 1 and 72. The two user label locations are shown as two 6 character blanks enclosed in asterisks on the next line. Since the title and user label occupy 26 data locations, there are 74 remaining character or floating point locations. As shown in the example, these are input as "0.0". In addition, 100 integers are input as "0".


```
OV CONTRL
1D PROINS
* TWO DIMENSIONAL. NON SEPARABLE WATER REACTOR PROBLEM      *
* TWO DIMENSIONAL. NON SEPARABLE WATER REACTOR PROBLEM      *
*      * *      * 0.0    74R 0    100R
```

FIGURE XI.1.1 EXAMPLE OF PROINS CONTROL RECORD

XI.2 Driver Control File. DVRINS.

The file which provides information associated with the VENTURE code system driver is shown in Figure XI.2. After the name of the file, DVRINS, the 100 floating point locations are reserved. The first integer input is the memory locations in words (remember, there are four bytes to a word in a short word machine). The next two integer locations are reserved. The fourth integer is the maximum block size for direct access data files. If this entry is non-zero, the automated procedure used in the VENTURE code to establish maximum direct access block sizes is overridden. The next entry is the total CPU time allowed for the problem (this entry is not applicable to the PC version of VENTURE). The next entry is reserved. The eleventh data input for this record is a flag for using the separate modules in the VENTURE code block as stand alone codes or as a driven modular system. The PC version of VENTURE must be run in the modular driven mode, i.e., IX(11) is zero. The remaining entries for this record are reserved.

```

C-----
CR      MODULE DRIVING INFORMATION -
C      -
CL      DVRINS, (XX(I),I=1,100), (IX(I),I=1,100) -
C      -
CW      101*MULT + 100 -
C      -
CD      DVRINS      MODULE DRIVING INFORMATION IDENTIFIER (6HDVRINS) -
C      -
CD      XX(1-100)    RESERVED -
C      -
CD      IX(1)        PRIMARY MEMORY ALLOCATION, WORDS -
C      -
CD      IX(2)        RESERVED -
C      -
CD      IX(3)        RESERVED -
C      -
CD      IX(4)        MAXIMUM BLOCK SIZE FOR DIRECT ACCESS DATA FILES, IN-
CD                      WORDS. BEST VALUE DEPENDING ON SEVERAL THINGS -
CD                      INCLUDING DISK TRACK LENGTH. OVERRIDE THE -
CD                      AUTOMATED PROCEDURE ASSIGNMENT IF NON-ZERO -
C      -
CD      IX(5)        TOTAL PROCESSOR TIME ALLOWED FOR THE RUN, MINUTES -
C      -
CD      IX(6-10)     RESERVED -
C      -
CD      IX(11)       STAND-ALONE FLAG -
CD                      0- MODULES ARE ACCESSED IN A TRUE MODULAR SENSE-
CD                      1- MODULES ARE ACCESSED AS IF EACH IS A -
CD                      STAND-ALONE CODE (NOT RECOMMEND) -
C      -
CD      IX(12-100)   RESERVED -
C      -
C-----

```

Figure XI.2 Specifications for DVRINS Record in Interface File CONTRL

XI.2.1 Example of Driver Information Record, DVRINS.

An example of a DVRINS record as giuven to the Input Processor is shown in Figure XI.2.1. After the CONTRL file and the identification of the record (i.e., the 1D Record), the record indicates 0.0 for all the floating point numbers. The memory allocation for the problem as 36000 words, with all other entries in the record set to zero.

```
OV CONTRL
1D DVRINS 0.0 100R
 36000 0 0 0 0 0 0 0 0 0 0 0 0 89R
```

Figure XI.2.1 Example of DVRINS Record

XII. Output Files.

The output files associated with VENTURE include RTFLUX, the regular total point flux, ATFLUX, the adjoint total point flux, RZFLUX, the regular zone flux, and PWDINT, the point power density. These will be described in order.

XII.1 The Regular Total Point Flux File, RTFLUX.

The file specifications for RTFLUX are shown in Figure XII.1. When the MULT parameter is 2, as is the case with short word machines, the fluxes are given in double precision.

The data records associated with this file are as follows:

- 1D Record - Specifications
- 2D Record - One Dimensional Regular Total Flux
- 3D Record - Multi-Dimensional Regular Total Flux

The 1D Record includes the file specifications, which contains 8 integers. These are: the number of dimensions, NDIM; the number of energy groups, NGROUP; the number of first dimension fine mesh intervals, NINTI; the number of second dimension fine mesh intervals, NINTJ; the number of third dimension fine mesh intervals, NINTK; ITER, the outer iteration number at which the flux file is written; the effective multiplication factor, EFFK; and, the power in watts to which the flux is normalized.

The 2D Record contains the one dimensional flux by interval and group, and is applicable if NDIM is unity. The format for this record is: ((FREG(I,J),I=1,NINTI),J=1,NGROUP).

The 3D Record contains the multi-dimensional regular flux, and is applicable when the number of dimensions, NDIM, is greater than unity. This flux is written for the first two dimensions for each group, and then repeated for the third dimension, and then for the group. Thus, first a plane of fluxes is written for a group, and the plane is repeated for each third dimension interval (If greater than unity), and then the procedure is repeated over the number of groups. The format is ((FREG(I,J),I=1,NINTI),J=1,NINTJ). The structure followed is:

```
DO 1 L=1,NGROUP
DO 1 K=1,NINTK
1 READ(N) *LIST AS ABOVE*
```

```

C*****
C          REVISED 07/23/75 - REVISED 04/01/80
C
CF          RTFLUX
C
CE          REGULAR TOTAL FLUXES
C
C*****

```

ORDER OF GROUPS IS ACCORDING TO DECREASING
ENERGY. NOTE THAT DOUBLE PRECISION FLUXES ARE
GIVEN WHEN MULT.EQ.2

```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME, (HUSE(I), I=1, 2), IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CD          HNAME          HOLLERITH FILE NAME - RTFLUX - (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CD          MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS A SINGLE WORD
CD                      2- A6 WORD IS A DOUBLE PRECISION WORD
C
C-----

```

Figure XII.1 Specifications for Interface File RTFLUX

```

C-----
CR          SPECIFICATIONS      (1D RECORD)      -
C                                                  -
CL  NDIM,NGROUP,NINTI,NINTJ,NINTK,ITER,EFFK,POWER -
C                                                  -
CW  8=NUMBER OF WORDS                    -
C                                                  -
CD  NDIM          NUMBER OF DIMENSIONS          -
CD  NGROUP        NUMBER OF ENERGY GROUPS      -
CD  NINTI         NUMBER OF FIRST DIMENSION FINE MESH INTERVALS -
CD  NINTJ         NUMBER OF SECOND DIMENSION FINE MESH INTERVALS -
CD  NINTK         NUMBER OF THIRD DIMENSION FINE MESH INTERVALS, -
CD               NINTK.EQ.1 IF NDIM.LE.2          -
C                                                  -
CN          FOR MESHPOINT EDGE LOCATIONS, NINTI,NINTJ, AND NINTK ARE *-
CN          INTERPRETED AS THE NUMBER OF POINTS (ONE MORE THAN THE *-
CN          NUMBER OF INTERVALS)                  *-
CN          FOR SPECIAL TRIANGULAR GEOMETRIES, NINTI IS THE NUMBER OF *-
CN          POINTS ON EACH PLANE, AND NINTJ IS SET TO 1.          *-
C                                                  -
CD  ITER          OUTER ITERATION NUMBER AT WHICH FLUX WAS WRITTEN -
CD               MADE NEGATIVE FOR MESH EDGE POINTS             *-
CD  EFFK          EFFECTIVE MULTIPLICATION FACTOR              -
CD               SET TO ZERO IF FIXED SOURCE PROBLEM            *-
CD  POWER         POWER IN WATTS TO WHICH FLUX IS NORMALIZED    -
C                                                  -
C-----

C-----
CR          ONE DIMENSIONAL REGULAR TOTAL FLUX  (2D RECORD)      -
C                                                  -
CC          PRESENT IF NDIM.EQ.1                    -
C                                                  -
CL  ((FREG(I,J),I=1,NINTI),J=1,NGROUP)              -
C                                                  -
CW  NINTI*NGROUP*MULT=NUMBER OF WORDS                -
C                                                  -
CD  FREG(I,J)     ONE DIMENSIONAL REGULAR TOTAL FLUX BY INTERVAL -
CD               AND GROUP                                     -
C                                                  -
C-----

```

Figure XII.1 Specifications for Interface File RTFLUX (con't.)


```

C-----
CR          MULTI-DIMENSIONAL REGULAR TOTAL FLUX  (3D RECORD)      -
C                                                  -
CC          PRESENT IF NDIM.GE.2                                -
C                                                  -
CL  ((FREG(I,J).I=1.NINTI).J=1.NINTJ)-----NOTE STRUCTURE BELOW -
C                                                  -
CW  NINTI*NINTJ*MULT=NUMBER OF WORDS                            -
C                                                  -
CS  DO 1 L=1,NGROUP                                             -
CS  DO 1 K=1,NINTK                                             -
CS  1 READ(N)  *LIST AS ABOVE*                                  -
C                                                  -
CD  FREG(I,J)    MULTIDIMENSIONAL REGULAR TOTAL FLUX           -
CD                      BY INTERVAL FOR EACH GROUP             -
C                                                  -
C-----

C*****
C
CEOF          RTFLUX
C
C*****

```

Figure XII.1 Specifications for Interface File RTFLUX (con't.)

XII.1.1 Example of RTFLUX File.

An example of an RTFLUX file written in ASCII by VENTURE is shown in Figure XII.1.1. The first record is the file identification record indicating: the name of the file, RTFLUX; the user identification was left blank; and the file version was number 1.

The 1D Record indicates 2 dimensions, 2 groups, a 12x12 geometrical mesh, 1 third dimension since the problem is two dimensional, the outer iteration number at which the flux was written was number 10, the effective multiplication factor was 1.0207, and the power in watts to which the flux was normalized was not not input and was written as zero.

There is no 2D Record since the problem is multidimensional.

The 3D Record provides the flux values. The first 12 values are for the first dimension, at the first row of the second dimension, in the first group. The next 12 values vary the first dimension along the second row, etc. After the 12x12 values are given for the first group, the values are repeated for the second group.

Since this is an output file, the 1D and 3D Record identifiers are not on the file, but were included here for ease of explanation and understanding.

```

RTFLUX    1
1D/
  2    2   12   12    1   10 1.02070E+00 0.00000E+00
3D/
1.87935E-01 1.88192E-01 1.89182E-01 1.89494E-01 1.87958E-01 1.85182E-01
1.82149E-01 1.78281E-01 1.72966E-01 1.70189E-01 1.69352E-01 1.68825E-01
1.88807E-01 1.89192E-01 1.90449E-01 1.90795E-01 1.89210E-01 1.86354E-01
1.83339E-01 1.79486E-01 1.74004E-01 1.70948E-01 1.69963E-01 1.69352E-01
1.90190E-01 1.90871E-01 1.92552E-01 1.92935E-01 1.91267E-01 1.88272E-01
1.85292E-01 1.81474E-01 1.75724E-01 1.72250E-01 1.70948E-01 1.70189E-01
1.94518E-01 1.95578E-01 1.99413E-01 1.99855E-01 1.97856E-01 1.94288E-01
1.91505E-01 1.87911E-01 1.81152E-01 1.75725E-01 1.74004E-01 1.72966E-01
2.00457E-01 2.01602E-01 2.05767E-01 2.06784E-01 2.04323E-01 1.98274E-01
1.94429E-01 1.92167E-01 1.87911E-01 1.81475E-01 1.79487E-01 1.78282E-01
2.03981E-01 2.05098E-01 2.09066E-01 2.09995E-01 2.08688E-01 2.04940E-01
2.00492E-01 1.94430E-01 1.91506E-01 1.85294E-01 1.83341E-01 1.82151E-01
2.05985E-01 2.07056E-01 2.10756E-01 2.10226E-01 2.11267E-01 2.08932E-01
2.04940E-01 1.98274E-01 1.94288E-01 1.88273E-01 1.86355E-01 1.85183E-01
2.07517E-01 2.08654E-01 2.12697E-01 2.14149E-01 2.13705E-01 2.11267E-01
2.08688E-01 2.04323E-01 1.97857E-01 1.91268E-01 1.89211E-01 1.87959E-01
2.07481E-01 2.08662E-01 2.12950E-01 2.15109E-01 2.14148E-01 2.10225E-01
2.09994E-01 2.06784E-01 1.99855E-01 1.92935E-01 1.90796E-01 1.89494E-01
2.05035E-01 2.06122E-01 2.09983E-01 2.12950E-01 2.12696E-01 2.10754E-01
2.09065E-01 2.05766E-01 1.99413E-01 1.92552E-01 1.90449E-01 1.89182E-01
2.03076E-01 2.03871E-01 2.06122E-01 2.08661E-01 2.08652E-01 2.07054E-01
2.05096E-01 2.01601E-01 1.95578E-01 1.90871E-01 1.89192E-01 1.88192E-01
2.02533E-01 2.03076E-01 2.05035E-01 2.07480E-01 2.07515E-01 2.05983E-01
2.03980E-01 2.00455E-01 1.94517E-01 1.90189E-01 1.88807E-01 1.87934E-01
1.05775E-01 1.04490E-01 1.00050E-01 9.41563E-02 8.91831E-02 8.52435E-02
8.47257E-02 9.10433E-02 1.03598E-01 1.12220E-01 1.15188E-01 1.17214E-01
1.02615E-01 1.00385E-01 9.52199E-02 8.93263E-02 8.43595E-02 8.03205E-02
7.96648E-02 8.61675E-02 9.92189E-02 1.08454E-01 1.12525E-01 1.15188E-01
9.80716E-02 9.42795E-02 8.88147E-02 8.29722E-02 7.80193E-02 7.38486E-02
7.29966E-02 7.97421E-02 9.34384E-02 1.02591E-01 1.08454E-01 1.12220E-01
8.75939E-02 8.40764E-02 7.59497E-02 7.06352E-02 6.57166E-02 6.09904E-02
5.91076E-02 6.64164E-02 8.20234E-02 9.34385E-02 9.92189E-02 1.03598E-01
7.70031E-02 7.34450E-02 6.55767E-02 5.78078E-02 5.17085E-02 4.19211E-02
4.15824E-02 5.30286E-02 6.64165E-02 7.97422E-02 8.61676E-02 9.10435E-02
7.09184E-02 6.73171E-02 5.94782E-02 5.05807E-02 4.65451E-02 4.28065E-02
4.17192E-02 4.15824E-02 5.91077E-02 7.29968E-02 7.96650E-02 8.47260E-02
6.82703E-02 6.45705E-02 5.63530E-02 4.28585E-02 4.41785E-02 4.30356E-02
4.28065E-02 4.19212E-02 6.09906E-02 7.38489E-02 8.03207E-02 8.52438E-02
7.02885E-02 6.66440E-02 5.87775E-02 4.98606E-02 4.63450E-02 4.41785E-02

```

Figure XII.1.1 Example of RTFLUX Interface File

4.65450E-02 5.17085E-02 6.57168E-02 7.80195E-02 8.43598E-02 8.91834E-02
7.51716E-02 7.15389E-02 6.36623E-02 5.53107E-02 4.98605E-02 4.28584E-02
5.05805E-02 5.78078E-02 7.06353E-02 8.29723E-02 8.93265E-02 9.41564E-02
8.31045E-02 7.96056E-02 7.21748E-02 6.36622E-02 5.87773E-02 5.63528E-02
5.94780E-02 6.55766E-02 7.59497E-02 8.88147E-02 9.52199E-02 1.00050E-01
8.87837E-02 8.52908E-02 7.96055E-02 7.15387E-02 6.66437E-02 6.45701E-02
6.73168E-02 7.34448E-02 8.40764E-02 9.42795E-02 1.00385E-01 1.04490E-01
9.09985E-02 8.87837E-02 8.31044E-02 7.51714E-02 7.02882E-02 6.82699E-02
7.09181E-02 7.70029E-02 8.75938E-02 9.80716E-02 1.02615E-01 1.05775E-01

Figure XII.1.1 Example of RTFLUX Interface File (con't.)

XII.2 The Adjoint Total Point Flux File, ATFLUX.

The file ATFLUX provides the adjoint flux for each interval and group. The specifications for this file are shown in Figure XII.2. When the MULT parameter is 2, as is the case with short word machines, the fluxes are given in double precision. The data records for this file are:

- 1D Record - Specifications
- 2D Record - One Dimensional Adjoint Total Flux
- 3D Record - Multi-Dimensional; Adjoint Total flux

The 1D Record consists of 8 numbers, which are: NDIM, the number of dimensions in the problem; NGROUP, the number of energy groups; NINTI, the number of first dimension fine mesh intervals; NINTJ, the number of second dimension fine mesh intervals; NINTK, the number of third dimension fine mesh intervals; ITER, the outer iteration number at which the flux was written; EFFK, the effective multiplication factor; and, ADUM, a reserved location.

The 2D Record gives the adjoint flux for one dimensional problems. The format is ((FADJ(I,J),I=1,NINTI),J=1,NGROUP), with FADJ(I,J) being the one dimensional adjoint flux by interval and group. This record is written when NDIM=1.

The 3D Record applies to multidimensional problems, i.e., when NDIM is greater than unity. The data for a given group are given for rows, until a plane is filled. For three dimensional problems, these planes are repeated. The data is then repeated over groups. The format is ((FADJ(I,J),I=1,NINTI),J=1,NINTJ), where FADJ(I,J) is the adjoint flux at row I and column J. The data has the following structure:

```
DO 1 L=1,NGROUP
DO 1 K=1,NINTK
1  READ(N)  *LIST AS ABOVE*
```

```

C*****
C              REVISED 07/23/75 - REVISED 04/01/80
C
CF          ATFLUX
CE          ADJOINT TOTAL FLUXES
C
C*****

```

ORDER OF GROUPS IS ACCORDING TO INCREASING
ENERGY. NOTE THAT DOUBLE PRECISION FLUXES ARE
GIVEN WHEN MULT.EQ.2

```

C-----
CR          FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2),IVERS
C
CW      1 + 3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - ATFLUX - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
C
CD      MULT            DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          SPECIFICATIONS      (1D RECORD)
C
CL      NDIM,NGROUP,NINTI,NINTJ,NINTK,ITER,EFFK,ADUM
C
CW      8=NUMBER OF WORDS
C
CD      NDIM            NUMBER OF DIMENSIONS
CD      NGROUP          NUMBER OF ENERGY GROUPS
CD      NINTI           NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD      NINTJ           NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD      NINTK           NUMBER OF THIRD DIMENSION FINE MESH INTERVALS,
CD                      NINTK.EQ.1 IF NDIM.LE.2
C
CN          FOR MESHPOINT EDGE LOCATIONS, NINTI, NINTJ, AND NINTK ARE *-
CN          INTERPRETED AS THE NUMBER OF POINTS (ONE MORE THAN THE *-
CN          NUMBER OF INTERVALS) *-
CN          FOR SPECIAL TRIANGULAR GEOMETRIES, NINTI IS THE NUMBER OF *-
CN          POINTS ON EACH PLANE, AND NINTJ IS SET TO 1. *-

```

Figure XII.2 Specifications for Interface File ATFLUX

```

C
CD  ITER          OUTER ITERATION NUMBER AT WHICH FLUX WAS WRITTEN      -
CD                                     MADE NEGATIVE FOR MESH EDGE POINTS  *-
CD                                     SET TO ZERO IF FIXED SOURCE ADJOINT FLUXES  *-
CD                                     (DOMINANT HARMONIC) HAVE BEEN CORRECTED FOR  *-
CD                                     FUNDAMENTAL CONTAMINATION              *-
CD  EFFK          EFFECTIVE MULTIPLICATION FACTOR                      -
CD  ADUM          ZERO FOR NON FIXED SOURCE PROBLEM                     *-
CD                                     SUM FIXED SOURCE IF FIXWD SOURCE PROBLEM  *-
C
C-----

C-----
CR          ONE DIMENSIONAL ADJOINT TOTAL FLUX    (2D RECORD)          -
C
CC          PRESENT IF NDIM.EQ.1                                       -
C
CL  ((FADJ(I,J),I=1,NINTI),J=1,NGROUP)                                -
C
CW  NINTI*NGROUP*MULT=NUMBER OF WORDS                                  -
C
CD  FADJ(I,J)      ONE DIMENSIONAL ADJOINT TOTAL FLUX BY INTERVAL      -
CD                  AND GROUP                                           -
C
C-----

C-----
CR          MULTI-DIMENSIONAL ADJOINT TOTAL FLUX    (3D RECORD)          -
C
CC          PRESENT IF NDIM.GE.2                                       -
C
CL  ((FADJ(I,J),I=1,NINTI),J=1,NINTJ)-----NOTE STRUCTURE BELOW----- -
C
CW  NINTI*NINTJ*MULT=NUMBER OF WORDS                                  -
C
CS  DO 1 L=1,NGROUP                                                    -
CS  DO 1 K=1,NINTK                                                      -
CS  1 READ(N)      *LIST AS ABOVE*                                     -
C
CD  FADJ(I,J)      MULTI-DIMENSIONAL ADJOIN TOTAL FLUX                 -
CD                  BY INTERVAL FOR EACH GROUP                         -
C
C-----

C*****
C
CEOF
C
C-----

```

Figure XII.2 Specifications for Interface File ATFLUX (con't.)

XII.2.1 Example of Adjoint Flux File, ATFLUX.

An example of an ATFLUX file is shown in Figure XII.2.1. The first record is the File Identification Record giving the name and version number of the file. This is followed by the 1D Record indicating 2 dimensions, 2 groups, 12 first dimension intervals, 12 second dimension intervals, 1 third dimension interval, the flux was written at outer iteration number 9, the eigenvalue is 1.0207, and the reserved variable was set to zero. The adjoint fluxes are then given. The first 12 values are the first dimension fluxes for the first row of the second dimension in group 1, the next 12 are for the second row of fluxes, etc. After the 12X12 values for the first group are given, the second group values are given. The data identifiers, 1D and 3D are not part of this output file, but have been inserted for ease of explanation and understanding.


```

ATFLUX
1D/
1 2 2 12 12 1 9 1.02070E+00 0.00000E+00
3D/
2.44017E-03 2.44249E-03 2.44777E-03 2.39525E-03 2.25888E-03 2.07056E-03
1.95954E-03 1.94857E-03 1.93859E-03 1.91541E-03 1.90723E-03 1.90156E-03
2.45200E-03 2.45764E-03 2.46631E-03 2.41492E-03 2.27568E-03 2.07791E-03
1.96476E-03 1.96011E-03 1.95203E-03 1.92619E-03 1.91477E-03 1.90723E-03
2.46916E-03 2.47964E-03 2.49081E-03 2.44088E-03 2.29798E-03 2.08724E-03
1.97125E-03 1.97543E-03 1.96989E-03 1.94268E-03 1.92619E-03 1.91541E-03
2.51313E-03 2.52348E-03 2.55102E-03 2.50605E-03 2.35299E-03 2.09758E-03
1.97293E-03 2.00994E-03 2.01299E-03 1.96989E-03 1.95202E-03 1.93859E-03
2.57257E-03 2.58513E-03 2.62321E-03 2.54710E-03 2.33545E-03 1.69987E-03
1.56261E-03 1.87071E-03 2.00994E-03 1.97542E-03 1.96011E-03 1.94856E-03
2.56994E-03 2.58085E-03 2.61104E-03 2.48294E-03 2.43484E-03 2.21495E-03
1.99108E-03 1.56260E-03 1.97292E-03 1.97124E-03 1.96475E-03 1.95953E-03
2.54451E-03 2.54905E-03 2.54637E-03 2.06865E-03 2.43652E-03 2.39556E-03
2.21494E-03 1.69987E-03 2.09756E-03 2.08723E-03 2.07790E-03 2.07055E-03
2.64594E-03 2.65722E-03 2.68848E-03 2.57646E-03 2.56675E-03 2.43652E-03
2.43483E-03 2.33544E-03 2.35298E-03 2.29797E-03 2.27567E-03 2.25886E-03
2.72291E-03 2.73621E-03 2.77632E-03 2.72797E-03 2.57645E-03 2.06865E-03
2.48293E-03 2.54709E-03 2.50603E-03 2.44087E-03 2.41491E-03 2.39523E-03
2.73437E-03 2.74673E-03 2.78219E-03 2.77632E-03 2.68847E-03 2.54636E-03
2.61102E-03 2.62319E-03 2.55100E-03 2.49079E-03 2.46630E-03 2.44775E-03
2.71633E-03 2.72712E-03 2.74672E-03 2.73620E-03 2.65721E-03 2.54904E-03
2.58083E-03 2.58512E-03 2.52347E-03 2.47963E-03 2.45763E-03 2.44248E-03
2.70939E-03 2.71632E-03 2.73437E-03 2.72291E-03 2.64593E-03 2.54450E-03
2.56992E-03 2.57255E-03 2.51311E-03 2.46914E-03 2.45199E-03 2.44016E-03
2.01510E-03 2.01388E-03 2.00864E-03 1.98957E-03 1.96119E-03 1.92932E-03
1.90400E-03 1.89014E-03 1.88499E-03 1.88484E-03 1.88484E-03 1.88486E-03
2.01394E-03 2.01245E-03 2.00664E-03 1.98772E-03 1.95963E-03 1.92808E-03
1.90298E-03 1.88928E-03 1.88441E-03 1.88462E-03 1.88475E-03 1.88484E-03
2.01215E-03 2.00993E-03 2.00321E-03 1.98458E-03 1.95699E-03 1.92602E-03
1.90128E-03 1.88780E-03 1.88336E-03 1.88421E-03 1.88462E-03 1.88484E-03
2.00725E-03 2.00426E-03 1.99365E-03 1.97613E-03 1.94956E-03 1.91952E-03
1.89542E-03 1.88279E-03 1.87998E-03 1.88336E-03 1.88440E-03 1.88499E-03
2.00823E-03 2.00523E-03 1.99529E-03 1.97403E-03 1.94712E-03 1.91562E-03
1.89321E-03 1.88341E-03 1.88279E-03 1.88779E-03 1.88927E-03 1.89013E-03
2.01303E-03 2.01003E-03 2.00004E-03 1.97799E-03 1.95488E-03 1.92944E-03
1.90783E-03 1.89321E-03 1.89542E-03 1.90127E-03 1.90297E-03 1.90399E-03
2.02231E-03 2.01933E-03 2.00911E-03 1.98535E-03 1.96787E-03 1.94772E-03
1.92943E-03 1.91561E-03 1.91951E-03 1.92601E-03 1.92807E-03 1.92930E-03
2.03921E-03 2.03612E-03 2.02613E-03 2.00582E-03 1.98677E-03 1.96787E-03

```

Figure XII.2.1 Example of ATFLUX File

1.95488E-03	1.94712E-03	1.94956E-03	1.95698E-03	1.95962E-03	1.96117E-03
2.05752E-03	2.05436E-03	2.04449E-03	2.02587E-03	2.00582E-03	1.98535E-03
1.97799E-03	1.97403E-03	1.97612E-03	1.98457E-03	1.98771E-03	1.98956E-03
2.07306E-03	2.07006E-03	2.06093E-03	2.04450E-03	2.02613E-03	2.00911E-03
2.00004E-03	1.99529E-03	1.99365E-03	2.00320E-03	2.00664E-03	2.00864E-03
2.07905E-03	2.07662E-03	2.07006E-03	2.05436E-03	2.03612E-03	2.01933E-03
2.01003E-03	2.00523E-03	2.00426E-03	2.00993E-03	2.01245E-03	2.01388E-03
2.08069E-03	2.07904E-03	2.07306E-03	2.05752E-03	2.03920E-03	2.02231E-03
2.01302E-03	2.00823E-03	2.00724E-03	2.01215E-03	2.01394E-03	2.01509E-03

Figure XII.2.1 Example of ATFLUX File (con't.)

XII.3 Regular Zone Flux File, RZFLUX (Modified).

The VENTURE specifications for the regular zone flux by group, averaged over each zone, is shown in Figure XII.3. This file has been locally modified by the developers of the VENTURE code system. As indicated in the file name section, an asterisk in column 72 indicates a local modification. The data records for this file include:

- 1D Record - File Reference Information
- 2D Record - Flux Values
- 3D Record - Additional Data, First of Two Records
- 4D Record - Additional Data, Second of Two Records
- 5D Record - Local Flux Record Reference Data
- 6D Record - Local Neutron Flux Values

The 1D Record contains 20 values. These are: TIME, the reference real time, in days; POWER, the thermal power level in watts; VOL, the volume over which the power was determined, in cc; EFFK, the multiplication factor; EIVS, the eigenvalue for a search problem; DKDS, the drivative of the eigenvalue for a search problem; TNL, the total neutron losses; TNA, the total neutron absorptions; TNSL, the total neutron surface leakage; TNBL, the total neutron buckling loss; TNBAL, the total neutron black absorber loss; TNCRA, the total neutron control rod absorptions; CF, the fraction of the core treated in the problem; CE, the conversion factor, or the ratio of thermal energy to fission plus capture energy; CR, additional data flag if greater than zero; CC, a reserved location; ITPS, the iterative process state; NZONE, the number of geometric zones; NGROUP, the number of neutron energy groups; and NPV, the number of blocks of local, fine-scale flux values. The iterative process state as determined by the value of ITPS includes the following possibilities: 0, for no iteration done; 1, for convergence satisfied; 2 implies not converged but converging; and 3 means not converged, and not converging. The energy released from fission and capture is available with the cross section set.

The 2D Record contains regular zone flux values. These fluxes are averaged over the zone. They are given for each group in a zone and repeated over zones. The format used is as follows: ((ZGF(K,M),K=1,NGROUP),M=1,NZONE), where ZGF(K,M) is the regular zone flux for group K at zone M.

The 3D Record shown is a local modification associated with the VENTURE code. This record is additional data, and is present only if the CR parameter is greater than zero. It contains two real arrays of 100 locations each, and 200 integer arrays. The format as shown is: (SHARE8(I),I=1,100),(SHARE(I),I=1,100),(LX(I),I=1,200). The SHARE8 array is double precision on short word machines, and represents neutronics data for reference. The SHARE array contains reference neutronics data, and the LX array provides neutronics

flags for reference. A strong familiarity with the VENTURE code is required to establish the definitive meaning of these output values.

The 4D array also includes additional nonstandard data, and is present when CR is greater than zero. The format for this record is: (INRS(I), I=1, NGROUP), (RHO(I), I=1, NGROUP), (BATA(I), I=1, NGROUP). INRS consists of neutronics iteration flags, and RHO and BATA contain neutronics iteration data.

The 5D and 6D arrays are repeated NPV times, where NPV is the number of blocks of local, fine-scale flux values, as given in the 1D Record. The 5D format contains four variables: (XFV(I), I=1, 10), NLP, NRZ, (IFV(J), J=1, 8). The first member of the XFV array, XFV(1), is the reference volume in cc. The second member, XFV(2), is the reference power level in watts. NLP is the number of locations for which the data is given, and NRZ is the reference zone number. The remaining entries for this record are not defined in the record.

The 6D array contains local neutron flux values. The format is: ((FLF(K,M), K=1, NGROUP, M=1, NLP). FLF is the local value of the neutron total flux, as associated with a sub-volume within the reference zone, NRZ.

```

C*****
C          REFERENCE 02/01/79  ORNL-5180
CF          RZFLUX
C
CE          REGULAR ZONE FLUX BY GROUP, AVERAGED OVER EACH ZONE
C
CN          AN ASTRISK IN COLUMN 71 INDICATES LOCAL MODIFICATION
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME,(HUSE(I),I=1,2),IVERS
C
CW          3*MULT + 1
C
CD          HNAME          FILE NAME (A6) 'RZFLUX'
CD          HUSE           USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CN          MULT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----

C-----
CR          1D          FILE REFERENCE INFORMATION
C
CL          TIME,POWER,VOL,EFFK,EIVS,DKDS,TNL,TNA,TNSL,TNBL,TNBAL,TNCRA,
CL          CF,CE,CR,CC,ITPS,NZONE,NGROUP,NPV
C
CW          20
C
CD          TIME          REFERENCE REAL TIME, DAYS
CD          POWER         POWER LEVEL FOR ACTUAL NEUTRONICS PROBLEM, WATTS
CD                      THERMAL
CD          VOL           VOLUME OVER WHICH POWER WAS DETERMINED, CC
CD          EFFK          MULTIPLICATION FACTOR
CD          EIVS          EIGENVALUE OF SEARCH OF SEARCH PROBLEM
CD          DKDS          DERIVATIVE OF SEARCH PROBLEM
CD          TNL           TOTAL NEUTRON LOSSES
CD          TNA           TOTAL NEUTRON ABSORPTIONS
CD          TNSL          TOTAL NEUTRON SURFACE LEAKAGE
CD          TNBL          TOTAL NEUTRON BUCKLING LOSS
CD          TNBAL         TOTAL NEUTRON BLACK ABSORBER LOSS
CD          TNCRA         TOTAL NEUTRON CONTROL ROD ABSORPTIONS

```

Figure XII.3 Specifications for interface File RZFLUX

CD	CF	FRACTION OF CORE TREATED IN PROBLEM	*-
CD	CE	CONVERSION FACTOR. RATIO OF THERMAL ENERGY TO	*-
CD		FISSION + CAPTURE ENERGY AVAILABLE WITH	*-
CD		THE CROSS SECTIONS	*-
CD	CR	ADDITIONAL DATA FLAG IF .GT.0 (TWO RECORDS)	*-
CD	CC	RESERVED	-
CD	ITPS	ITERATIVE PROCESS STATE	-
CD		=0. NO ITERATIONS DONE	-
CD		=1. CONVERGENCE SATISFIED	-
CD		=2. NOT CONVERGED, BUT CONVERGING	-
CD		=3. NOT CONVERGED, NOT CONVERGING	-
CD	NZONE	NUMBER OF GEOMETRIC ZONES	-
CD	NGROUP	NUMBER OF NEUTRON ENERGY GROUPS	-
CD	NPV	NUMBER OF BLOCKS OF LOCAL FINE SCALE FLUX VALUES	*-
C			-
C			-----
C			-----
CR	2D	FLUX VALUES	-
C			-
CL		((ZGF(K,M),K=1,NGROUP),N=1.NZONE)	-
C			-
CW		NGROUP*NZONE	-
C			-
CD	ZGF	REGULAR ZONE FLUX BY GROUP, AVERAGED OVER ZONE	-
CD		NEUTRONS/SEC-CM**2	-
C			-
C			-----
C			-----
CR	3D	ADDITIONAL DATA, FIRST OF TWO RECORDS	*-
C			*-
CC		PRESENT IF CR.GT.0	*-
C			*-
CL		(SHARE8(I),I=1,100),(SHARE(I),I=1,100),(LX(I),I=1,200)	*-
C			*-
CW		100*MULT + 300	*-
C			*-
CD	SHARE8	NEUTRONICS DATA FOR REFERENCE	*-
C		DOUBLE PRECISION ON A SHORT WORD MACHINE	*-
CD	SHARE	NEUTRONICS DATA FOR REFERENCE	*-
CD	LX	NEUTRONICS FLAGS FOR REFERENCE	*-
C			*-
C			-----

Figure XII.3 Specifications for interface File RZFLUX (con't.)

```

C-----
CR      4D      ADDITIONAL DATA, SECOND OF TWO RECORDS      *-
C                                           *-
CC              PRESENT IF CR.GT.0                          *-
C                                           *-
CL      (INRS(I),I=1,NGROUP).(RHGO(I),I=1,NGROUP).(BATA(I),I=1,NGROUP) *-
C                                           *-
CW              3*NGROUP                                     *-
C                                           *-
CD      INRS          NEUTRONICS ITERATION FLAGS            *-
CD      RHO           NEUTRONICS ITERATION DATA            *-
CD      BATA          NEUTRONICS ITERATION DATA            *-
C                                           *-
CN              NOTE NONSTANDARD DATA TYPE ORDER          *-
C                                           *-
C-----
                                *-
                                *-
                                *-
C-----
CR      5D      LOCAL FLUX RECORD REFERENCE DATA          *-
C                                           *-
CL      (XFV(I),I=1,10),NLP,NRZ,(IFV(J),J=1,8)              *-
C                                           *-
CW              20                                           *-
C                                           *-
CD      XFV(1)        REFERENCE VOLUME, CC                  *-
CD      XFV(2)        REFERENCE POWER LEVEL, WATTS          *-
CD      NLP           NUMBER OF LOCATIONS FOR WHICH DATA IS GIVEN *-
CD      NRZ           REFERENCE ZONE NUMBER                  *-
C                                           *-
C-----

C-----
CR      6D      LOCAL NEUTRON FLUX VALUES                  *-
C                                           *-
CL      ((FLF(K,M),K=1,NGROUP),M=1,NLP)                     *-
C                                           *-
CW              NGROUP*NLP                                   *-
C                                           *-
CD      FLF           LOCAL VALUE OF THE NEUTRON TOTAL FLUX, *-
CD                        AS ASSOCIATED WITH A SUB-VOLUME WITHIN THE *-
CD                        REFERENCE ZONE NRZ                  *-
C                                           *-
C-----

C*****
C
CEOF      RZFLUX
C
C*****

```

Figure XII.3 Specifications for interface File RZFLUX (con't.)

XII.3.1 Example of RZFLUX File.

An example of the modified version of an RZFLUX file is shown in Figure XII.3.1. The 1D file indicates that the TIME and POWER are not relevant to the problem. The total volume is 232.45 cc, and the multiplication factor is 1.0207. There are no search parameters. The total neutron loss is 0.979718, with the neutron absorptions accounting for the entire loss. There is no surface leakage, buckling, black absorber or control rod absorption loss. The entire core was treated in the problem. The conversion factor of thermal to fission energy is 3.2×10^{-11} . The additional data flag is unity, indicating that the additional data records are present. The reserved location is set to zero, convergence has been satisfied since ITPS is unity, there are 78 geometric zones, two groups, and the number of blocks of fine scale flux values is zero.

The 2D Record shows the zone averaged flux values. Since there are 78 zones and two groups, there are a total of 156 zone averaged flux values. The first two values are for zone 1, groups 1 and 2 respectively, the next two values for zone 2, etc.

The 3D and 4D Records containing additional data are primarily for code developers, who understand the meaning of the parameters given in these records.


```

RZFLUX      1
1D/
0.00000E+00 0.00000E+00 2.32450E+02 1.02070E+00 0.00000E+00 0.00000E+00
9.79718E-01 9.79718E-01 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
1.00000E+00 3.20000E-11 1.00000E+00 0.00000E+00 1 78 2 0
2D/
1.87935E-01 1.05775E-01 1.88192E-01 1.04490E-01 1.89182E-01 1.00050E-01
1.89494E-01 9.41563E-02 1.87958E-01 8.91833E-02 1.85183E-01 8.52437E-02
1.82150E-01 8.47258E-02 1.78281E-01 9.10434E-02 1.72966E-01 1.03598E-01
1.70189E-01 1.12220E-01 1.69352E-01 1.15188E-01 1.68825E-01 1.17214E-01
1.88807E-01 1.02615E-01 1.89192E-01 1.00385E-01 1.90449E-01 9.52199E-02
1.90795E-01 8.93264E-02 1.89211E-01 8.43596E-02 1.86354E-01 8.03206E-02
1.83340E-01 7.96649E-02 1.79487E-01 8.61675E-02 1.74004E-01 9.92189E-02
1.70948E-01 1.08454E-01 1.69963E-01 1.12525E-01 1.90190E-01 9.80716E-02
1.90871E-01 9.42795E-02 1.92552E-01 8.88147E-02 1.92935E-01 8.29722E-02
1.91267E-01 7.80194E-02 1.88272E-01 7.38487E-02 1.85293E-01 7.29967E-02
1.81474E-01 7.97421E-02 1.77641E-01 8.88730E-02 1.72250E-01 1.02591E-01
1.94518E-01 8.75938E-02 1.95578E-01 8.40764E-02 1.99413E-01 7.59497E-02
1.99855E-01 7.06353E-02 1.97856E-01 6.57167E-02 1.94288E-01 6.09905E-02
1.91506E-01 5.91076E-02 1.87911E-01 6.64164E-02 1.81152E-01 8.20234E-02
2.00456E-01 7.70030E-02 2.01602E-01 7.34449E-02 2.05766E-01 6.55766E-02
2.06784E-01 5.78078E-02 2.04323E-01 5.17085E-02 1.98274E-01 4.19212E-02
1.94429E-01 4.15824E-02 1.92167E-01 5.30286E-02 2.03981E-01 7.09183E-02
2.05097E-01 6.73170E-02 2.09065E-01 5.94781E-02 2.09995E-01 5.05806E-02
2.08688E-01 4.65450E-02 2.04940E-01 4.28065E-02 2.00492E-01 4.17192E-02
2.05984E-01 6.82701E-02 2.07055E-01 6.45703E-02 2.10755E-01 5.63529E-02
2.10226E-01 4.28585E-02 2.11267E-01 4.41785E-02 2.08932E-01 4.30356E-02
2.07516E-01 7.02883E-02 2.08653E-01 6.66438E-02 2.12697E-01 5.87774E-02
2.14148E-01 4.98606E-02 2.13705E-01 4.63450E-02 2.07481E-01 7.51715E-02
2.08661E-01 7.15388E-02 2.12950E-01 6.36622E-02 2.15109E-01 5.53107E-02
2.05035E-01 8.31044E-02 2.06122E-01 7.96056E-02 2.09983E-01 7.21748E-02
2.03076E-01 8.87837E-02 2.03871E-01 8.52908E-02 2.02533E-01 9.09985E-02

```

Figure XII.3.1 Example of RZFLUX File

3D/

```

9.79719E-01 5.68563E-14 5.93179E-17 1.72315E+13 1.75882E+13 0.00000E+00
0.00000E+00 0.00000E+00 9.79718E-01 1.00000E+00 0.00000E+00 0.00000E+00
9.79718E-01 5.93174E-17 1.72314E+13 1.75881E+13 0.00000E+00 0.00000E+00
9.79718E-01 3.22867E-01 3.45469E-01 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 1.00000E+01 0.00000E+00 2.05283E-01 1.00658E-01 3.30413E+00
-8.66462E-01 3.30413E+00 -8.66462E-01 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 3.86261E-01 0.00000E+00 5.68563E-14 1.75882E+13
1.75882E+13 1.75885E+13 1.75884E+13 3.68058E+11 3.68054E+11 1.00015E+00
9.99910E-01 0.00000E+00 3.86261E-01 0.00000E+00 0.00000E+00 7.72894E-01
1.02070E+00 8.46854E-01 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 2.34430E-01
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 1.02070E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 9.79719E-01 3.86261E-01 0.00000E+00 0.00000E+00
0.00000E+00 1.00012E+00 9.99875E-01 0.00000E+00
1.70507E+00 1.00000E+00 5.00000E-05 5.00000E-06 1.02070E+00 1.02070E+00
0.00000E+00 1.59456E+00 0.00000E+00 0.00000E+00 1.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 4.94672E-05 0.00000E+00 2.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
5.21500E+03 0.00000E+00 0.00000E+00 2.32450E+02 0.00000E+00 0.00000E+00
1.00000E+00 0.00000E+00 1.00000E+00 1.00000E-01 0.00000E+00 0.00000E+00
0.00000E+00 1.00000E+00 3.20000E-11 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 1.02069E+00
0.00000E+00 0.00000E+00 0.00000E+00 9.90000E+01 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 1.00000E+02 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
1.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 3.75216E-04 1.00000E+00 0.00000E+00 0.00000E+00
1.00000E+10 0.00000E+00 1.00000E+00 0.00000E+00

```

Figure XII.3.1 Example of RZFLUX File (con't.)

1	2	4	0	0	0	0	0	6
0	1	0	0	0	0	6	0	0
0	0	0	0	0	1	0	1	0
0	0	0	0	0	10	0	0	0
0	0	2	9	1	29	0	0	0
0	0	0	99	0	12	12	1	2
78	7	1	0	0	78	144	1	7
1	0	1	2	13	13	2	1	1
1	1	0	0	1	1	1	0	1
0	0	0	0	0	0	0	99	0
1	1	1	1	0	0	1	71	0
0	0	0	4	20	4	0	8	0
0	27	6	0	0	0	0	0	0
0	0	0	1	0	0	8	1	0
0	0	0	10	13	1	1	0	0
0	1	0	0	0	36000	0	0	0
0	0	0	0	0	0	0	0	0
0	0	1	0	2	1	0	0	0
0	0	0	0	1	0	0	9	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	1	1	1	0	0	0
0	0							

4D/
5 4 9.91285E-01 9.66283E-01 1.76720E+00 1.59048E+00

Figure XII.3.1 Example of RZFLUX File (con't.)

XII.4 Power Density by Interval, PWDINT File.

Power density is given for each interval in the PWDINT standard interface file. The records for this file is shown in Figure XII.4. The file contains two data records:

- 1D Record - Specifications
- 2D Record - Power Density Values

The 1D Record contains the file specifications, which includes eight values. These are: TIME, the reference real time in days; POWER, the power level for the neutronics problem, in thermal watts; VOL, the volume over which the power was determined, in cc; IM, the number of first dimension fine intervals; JM, the number of second dimension fine intervals; KM, the number of third dimension fine intervals; NCY, the cycle number; and NBLK, the blocking factor set to unity.

The 2D Record provides the power density values. The format is ((PWR(I,J),I=1,IM),J=1,JM), where PWR(I,J) is the power density for the interval (I,J) in the K'th plane. The manner in which the data is listed is given by the following DO Loop:

```
DO 1 K=1,KM
1  READ(N)  *LIST AS ABOVE*
```

That is, each plane of data is read in succession.

```

C*****
C              REVISED 07/23/75 - REVISED 04/01/80
C
CF          PWDINT
C
CE          POWER DENSITY BY INTERVAL
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2),IVERS
C
CW      1 + 3*MULT=NUMBER OF WORDS
C
CD      HNAME              HOLLERITH FILE NAME - PWDINT - (A6)
CD      HUSE(I)            HOLLERIYH USER IDENTIFICATION (A6)
CD      IVERS              FILE VERSION NUMBER
CD      MULT                DOUBLE PRECISION PARAMETER
CD                        1- A6 WORD IS SINGLE WORD
CD                        2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          SPECIFICATIONS (1D RECORD)
C
CL      TIME, POWER, VOL, IM, JM, KM, NCY, NBLK
C
CD      8=NUMBER OF WORDS
C
CD      TIME                REFERENCE REAL TIME, DAYS
CD      POWER                POWER LEVEL FOR ACTUAL NEUTRONICS PROBLEM,
CD                        WATTS THERMAL
CD      VOL                  VOLUME OVER WHICH POWER WAS DETERMINED,CC
CD      IM                   NUMBER OF FIRST DIMENSION FINE INTERVALS
CD      JM                   NUMBER OF SECOND DIMENSION FINE INTERVALS
C
CN          FOR SPECIAL TRIANGULAR GEOMETRIES, IM IS THE NUMBER OF
CN          TRIANGLES ON EACH PLANE AND JM IS NOT DEFINED (SET TO 1)
C
CD      KM                   NUMBER OF THIRD DIMENSION FINE INTERVALS
CD      NCY                  REFERENCE COUNT (CYCLE NUMBER)
CD      NBLK                 =1
C
C-----

```

Figure XII.4 Specifications For Interface File PWDINT

```

C-----
CR                POWER DENSITY VALUES  (2D RECORD)          -
C                                                         -
CL      ((PWR(I,J),I=1,IM),J=1,JM)-----NOTE STRUCTURE BELOW-----
C                                                         -
CW      IM*JM=NUMBER OF WORDS                                -
C                                                         -
CS      DO 1 K=1,KM                                          -
CS  1  READ(N)  *LIST AS ABOVE*                             -
C                                                         -
CD      PWR(I,J)                POWER DENSITY BY INTERVAL, WATTS/CC
C                                                         -
C-----

C*****
C
CEOF      PWDINT
C
C*****

```

Figure XII.4 Specifications For Interface File PWDINT (con't.)

XII.4.1 Example of Power Density File.

An example of a power density file is shown in Figure XII.4.1. The file identification record includes the name of the file, PWDINT, and the version number, which in this case is 1. There is no user identification information.

The 1D Record indicates the following: the reference real time is not applicable and has been set to zero; the power level here is set as zero; the volume is 232.45 cc; there are 12 first dimension and second dimension intervals; the number of third dimension intervals is unity, indicating a two dimensional problem; the cycle number is not applicable, and is zero, and the number of blocks has been set to 1.

The 2D Record gives the power density by interval. The first 12 numbers are the power density in watts/cc for the first dimension intervals, at the first second dimension interval. The next 12 values are for the first dimension intervals, at the next second dimension interval, etc. The record identifiers are not part of the file, but are shown for illustration purposes.

```

PWDINT  1
1D/
0.00000E+00 0.00000E+00 2.32450E+02 12 12 1 0 1
2D/
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 6.42955E-03 6.85951E-03 6.44432E-03 6.03675E-03
5.17880E-03 5.68771E-03 5.62503E-03 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 7.65683E-03 6.90019E-03 6.28684E-03 2.12749E-03
2.09773E-03 5.37053E-03 5.68772E-03 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 7.07769E-03 6.20973E-03 5.80581E-03 5.41659E-03
5.28349E-03 2.09774E-03 5.17881E-03 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 6.78090E-03 2.21721E-03 5.58876E-03 5.46273E-03
5.41658E-03 2.12750E-03 6.03676E-03 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 7.03042E-03 6.16365E-03 5.81589E-03 5.58876E-03
5.80580E-03 6.28684E-03 6.44434E-03 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 7.51145E-03 6.70438E-03 6.16363E-03 2.21720E-03
6.20971E-03 6.90018E-03 6.85951E-03 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 7.03927E-03 7.51144E-03 7.03039E-03 6.78087E-03
7.07766E-03 7.65681E-03 6.42955E-03 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00
0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00 0.00000E+00

```

Figure XII.4.1 Example of PWDINT File.

DRAFT

References

- 1) R. Douglas O'Dell, "Standard Interface Files and Procedures for Reactor Physics Codes, Version IV," LA-6941-MS, Los Alamos Scientific Laboratory, September, 1977
- 2) G.E. Boshier, R.D. Odell, W.M. Resnik, "LASIP-III, A Generalized Processor for Standard Interface Files," LA-6280-MS, Los Alamos Scientific laboratory, April, 1976
- 3) D.R. Vondy, T.B. Fowler, G.W. Cunningham, "VENTURE: A Code Block for Solving Multigroup Neutronics Problems Applying the Finite Difference Diffusion Theory Approximation to Neutron transport, Version II," ORNL-5026/R1, Oak Ridge National Laboratory, November, 1977
- 4) D.R. Vondy, and G.W. Cunningham, "Exposure Computational Code Module for Reactor Core Analysis: BURNER," ORNL-5180, Oak Ridge National Laboratory, August, 1977

Part II. Listings of Standard Interface Files

The specifications for the available standard interface files developed by the DOE for use in various codes are listed in alphabetical order in the following pages. The latest available version is listed, many of which are Version-IV files. Changes made to Version-IV files for application to the VENTURE code system³, are denoted with an asterisk in column 71 of the specification.

```

C *****
C                                     REVISED 11/30/76
C
C
CF      AAFLUX-IV
CE      ADJOINT ANGULAR FLUX
C
C *****

```

```

CD      ORDER OF GROUPS IS ACCORDING TO INCREASING
CD      ENERGY.  THE DIRECTION NUMBERS M=1,NDIR DENOTE
CD      DIRECTIONS WHICH ARE REFLECTED WITH RESPECT TO
CD      THE DIRECTIONS GIVEN IN THE SNCONS FILE.

```

```

C -----
CR      FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2),IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - AAFLUX - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT            DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C -----

```

```

C -----
CR      SPECIFICATIONS      (1D RECORD)
C
CL      NDIM,NGROUP,NINTI,NINTJ,NINTK,NDIR,EFFK,ADUM
C
CW      8=NUMBER OF WORDS
C
CD      NDIM           NUMBER OF DIMENSIONS
CD      NGROUP         NUMBER OF GROUPS
CD      NINTI          NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD      NINTJ          NUMBER OF SECOND DIMENSION FINE MESH INTERVALS.
CD                      NINTJ.EQ.1 IF NDIM.EQ.1
CD      NINTK          NUMBER OF THIRD DIMENSION FINE MESH INTERVALS.
CD                      NINTK.EQ.1 IF NDIM.LE.2
CD      NDIR           NUMBER OF DIRECTIONS
CD      EFFK           EFFECTIVE MULTIPLICATION FACTOR
CD      ADUM           RESERVED
C
C -----

```

```

C-----
CR      ADJOINT ANGULAR FLUXES AT FIRST DIMENSION BOUNDARIES
CR      (2D RECORD)
C
CL      ((AFADJI(M,I),M=1,NDIR),I=1,NBDRYI)----NOTE STRUCTURE BELOW----
C
CW      NDIR*NBDRYI=NUMBER OF WORDS
C
C      DO 1 L=1,NGROUP
C      DO 1 K=1,NINTK
C      DO 1 J=1,NINTJ
C      1 READ (N) *LIST AS ABOVE*
C
CD      AFADJI(M,I)      ADJOINT FIRST DIMENSION BOUNDARY ANGULAR FLUX
CD      NBDRYI           =NINTI+1, NUMBER OF FIRST DIMENSION FINE MESH
CD                        BOUNDARIES.
C
C-----

```

```

C-----
CR      ADJOINT ANGULAR FLUXES AT SECOND DIMENSION BOUNDARIES
CR      (3D RECORD)
C
CC      PRESENT IF NDIM.GE.2
C
CL      ((AFADJJ(M,I),M=1,NDIR),I=1,NINTI)----NOTE STRUCTURE BELOW----
C
CW      NDIR*NINTI=NUMBER OF WORDS
C
C      DO 1 L=1,NGROUP
C      DO 1 K=1,NINTK
C      DO 1 J=1,NBDRYJ
C      1 READ (N) *LIST AS ABOVE*
C
CD      AFADJJ(M,I)      ADJOINT SECOND DIMENSION BOUNDARY ANGULAR FLUX
CD      NBDRYJ           =NINTJ+1, NUMBER OF SECOND DIMENSION FINE MESH
CD                        BOUNDARIES.
C
C-----

```

```

C-----
CR      ADJOINT ANGULAR FLUXES AT THIRD DIMENSION BOUNDARIES
CR      (4D RECORD)
C
CC      PRESENT IF NDIM.EQ.3
C
CL      ((AFADJK(M,I),M=1,NDIR),I=1,NINTI)----NOTE STRUCTURE BELOW----
C
CW      NDIR*NINTI=NUMBER OF WORDS
C
C      DO 1 L=1,NGROUP
C      DO 1 K=1,NBDRYK
C      DO 1 J=1,NINTJ
C      1 READ (N) *LIST AS ABOVE*
C
CD      AFADJK(M,I)      ADJOINT THIRD DIMENSION BOUNDARY ANGULAR FLUX
CD      NBDRYK           =NINTK+1, NUMBER OF THIRD DIMENSION FINE MESH
CD                       BOUNDARIES.
C
C-----
CEOF

```

```

C*****
C                                     DATE 12/13/85
C
C
CF      AAFLXM
CE      CODE DEPENDENT COMPUTATIONAL-ORDERED ANGULAR FLUX AT CELL
CE      EDGES FOR TWODANT CODE
C
C*****

```

```

C-----
C
C
CN      THIS FILE PROVIDES THE EDGE ANGULAR FLUX AS ORDERED
CN      BY THE CODE
C
C
C-----

```

```

C-----
C
CD      ORDER OF GROUPS IS ACCORDING TO INCREASING
CD      ENERGY. NOTE THAT DOUBLE PRECISION FLUXES ARE
CD      GIVEN WHEN MULT=2
C
C-----

```

```

C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      -----                                -----
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                                ALWAYS
CS
CS      ***** (REPEAT FOR ALL GROUPS)
CS      *      (GROUP 1 IS FIRST)
CS      *      ***** (REPEAT FOR ALL DIRECTIONS)
CS      *      *      COMPUTATIONAL COSINES                ALWAYS
CS      *      *      VERTICAL-EDGE ANGULAR FLUX            ALWAYS
CS      *      *      HORIZONTAL-EDGE ANGULAR FLUX          ALWAYS
CS      *      *****
CS      *****
C
C-----

```

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C

```

CW 1+3*MULT=NUMBER OF WORDS
 C
 CD HNAME HOLLERITH FILE NAME - AAFLXM - (A6)
 CD HUSE(I) HOLLERITH USER IDENTIFICATION (A6)
 CD IVERS FILE VERSION NUMBER
 CD MULT DOUBLE PRECISION PARAMETER
 CD 1- A6 WORD IS SINGLE WORD
 CD 2- A6 WORD IS DOUBLE PRECISION WORD
 C
 C-----

C-----
 CR SPECIFICATIONS (1D RECORD)
 C
 CL NDIM,NGROUP,NINTI,NINTJ,NINTK,EFFK,POWER
 C
 CW 8 =NUMBER OF WORDS
 C
 CD NDIM NUMBER OF DIMENSIONS
 CD NGROUP NUMBER OF ENERGY GROUPS
 CD NINTI NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
 CD NINTJ NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
 CD NINTK NUMBER OF THIRD DIMENSION FINE MESH INTERVALS.
 CD NINTK.EQ.1 IF NDIM.LE.2
 CD EFFK EFFECTIVE MULTIPLICATION FACTOR
 CD POWER POWER IN WATTS TO WHICH FLUX IS NORMALIZED
 C
 C-----

C-----
 CR COMPUTATIONAL COSINES
 C
 CL XMU,XETA,WEIGHT,XM
 C
 CW 4*MULTI
 C
 CD XMU MU COSINE
 CD XETA ETA COSINE
 CD WEIGHT WEIGHT
 CD XM COMPRESSED COSINE TABLE INDEX
 C
 C-----

C-----
 CR VERTICAL EDGE ANGULAR FLUX
 C
 CL ((VEDGE(I,J),I=NBDRYI),J=1,NINTJ)
 C
 CW NBDRYI*NINTJ*MULTI=NUMBER OF WORDS
 C
 CD VEDGE(I,J) VERTICAL-EDGE-BOUNDARY ANGULAR FLUX
 C


```

C
CD      NBDRYI      NINTI+1 (NUMBER OF FIRST DIMENSION FINE MESH
CD      BOUNDARIES)
C
C-----

```

```

C-----
CR      HORIZONTAL EDGE ANGULAR FLUX
C
CL      ((HEDGE(I,J),I=1,NINTI),J=1,NBDRYJ)
C
CW      NINTI*NBDRYJ*MULTI=NUMBER OF WORDS
C
CD      HEDGE(I,J)   HORIZONTAL-EDGE-BOUNDARY ANGULAR FLUX
C
CD      NBDRYJ      NINTJ+1 (NUMBER OF SECOND DIMENSION FINE MESH
CD      BOUNDARIES)
C
C-----

```

CEOF

```

C*****
C                                     REVISED 11/30/76
C
C
CF      ACURNT-IV
CE      ADJOINT CURRENTS
C
C*****

```

```

CD      ORDER OF GROUPS IS ACCORDING TO INCREASING
CD      ENERGY.

```

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2),IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - ACURNT - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR      SPECIFICATIONS      (1D RECORD)
C
CL      NDIM,NGROUP,NINTI,NINTJ,NINTK,NBLOK
C
CW      6=NUMBER OF WORDS
C
CD      NDIM           NUMBER OF DIMENSIONS
CD      NGROUP         NUMBER OF GROUPS
CD      NINTI          NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD      NINTJ          NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD      NINTK          NUMBER OF THIRD DIMENSION FINE MESH INTERVALS.
CD                      NINTK.EQ.1 IF NDIM.LE.2
CD      NBLOK          DATA BLOCKING FACTOR
CD                      IF NDIM.EQ.1 THE GROUP VARIABLE IS BLOCKED
CD                      INTO NBLOK BLOCKS (SEE 2D RECORD BELOW)
CD                      IF NDIM.GE.2 THE 2ND DIMENSION VARIABLE IS
CD                      BLOCKED INTO NBLOK BLOCKS (SEE 3D RECORD)
C
C-----

```

```

C-----
CR      ONE DIMENSIONAL ADJOINT CURRENT      (2D RECORD)
C
CC      PRESENT IF NDIM.EQ.1
C
CL      ((ACURI(I,J),I=1,NBDRIYI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW      NBDRIYI*(JU-JL+1) = NUMBER OF WORDS
C
C      DO 1 M=1,NBLOK
C      1 READ(N)      *LIST AS ABOVE*
C
CC      WITH M AS THE BLOCK INDEX, JL=(M-1)*((NGROUP-1)/NBLOK+1)+1
CC      AND JU=MINO(NGROUP,JUP) WHERE JUP=M*((NGROUP-1)/NBLOK +1)
C
CD      ACURI(I,J)      ONE DIMENSIONAL ADJOINT CURRENT BY MESH POINT
CD                        BOUNDARY AND GROUP
CD      NBDRIYI          =NINTI+1, NUMBER OF FIRST DIMENSION FINE MESH
CD                        BOUNDARIES
C
C-----

```

```

C-----
CR      MULTI-DIMENSIONAL ADJOINT CURRENTS AT FIRST DIMENSION
CR      BOUNDARIES      (3D RECORD)
C
CC      PRESENT IF NDIM.GE.2
C
CL      ((ACURI(I,J),I=1,NBDRIYI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW      NBDRIYI*(JU-JL+1) = NUMBER OF WORDS
C
C      DO 1 L=1,NGROUP
C      DO 1 K=1,NINTK
C      DO 1 M=1,NBLOK
C      1 READ(N) *LIST AS ABOVE*
C
CC      WITH M AS THE BLOCK INDEX, JL=(M-1)*((NINTJ-1)/NBLOK +1)+1
CC      AND JU=MINO(NINTJ,JUP) WHERE JUP=M*((NINTJ-1)/NBLOK +1)
C
CD      ACURI(I,J)      ADJOINT FIRST DIMENSION BOUNDARY CURRENT
C
C-----

```

```

C-----
CR      MULTI-DIMENSIONAL ADJOINT CURRENTS AT SECOND DIMENSION
CR      BOUNDARIES          (4D RECORD)
C
CC      PRESENT IF NDIM.GE.2
C
CL      ((ACURJ(I,J),I=1,NINTI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW      NINTI*(JU - JL + 1) = NUMBER OF WORDS
C
C      DO 1 L=1,NGROUP
C      DO 1 K=1,NINTK
C      DO 1 M=1,NBLOK
C      1 READ(N) *'ST AS ABOVE*
C
CC      WITH M AS THE BLOCK INDEX, JL=(M-1)*((NBDRYJ-1)/NBLOK+1)+1
CC      AND JU=MINO(NBDRYJ,JUP) WHERE JUP=M*((NBDRYJ-1)/NBLOK+1)
C
CD      ACURJ(I,J)          ADJOINT SECOND DIMENSION BOUNDARY CURRENT
CD      NBDRYJ              =NINTJ+1, NUMBER OF SECOND DIMENSION FINE MESH
CD                          BOUNDARIES
C
C-----

```

```

C-----
CR      MULTI-DIMENSIONAL ADJOINT CURRENTS AT THIRD DIMENSION
CR      BOUNDARIES.        (5D RECORD)
C
CC      PRESENT IF NDIM.EQ.3
C
CL      ((ACURK(I,J),I=1,NINTI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW      NINTI*(JU - JL + 1) = NUMBER OF WORDS
C
C      DO 1 L=1,NGROUP
C      DO 1 K=1,NBDRYK
C      DO 1 M=1,NBLOK
C      1 READ(N) *LIST AS ABOVE*
C
CC      WITH M AS THE BLOCK INDEX, JL=(M-1)*((NINTJ-1)/NBLOK +1)+1
CC      AND JU=MINO(NINTJ,JUP) WHERE JUP=M*((NINTJ-1)/NBLOK +1)
C
CD      ACURK              ADJOINT THIRD DIMENSION BOUNDARY CURRENT
CD      NBDRYK              =NINTK+1, NUMBER OF THIRD DIMENSION FINE MESH
CD                          BOUNDARIES
C
C-----

```

CEOF

```

C*****
C                                     DATE 05/12/83
C
C
CF      ADJMAC
CE      CODE DEPENDENT MACROSCOPIC MULTIGROUP CROSS SECTION FILE
CE      USED IN ONEDANT SOLVER MODULE FOR ADJOINT CALCULATIONS
C
C
C*****
C
CN      THIS FILE PROVIDES A BASIC BROAD GROUP
CN      LIBRARY, ORDERED BY GROUP
C
C      ORDER OF GROUPS IS ACCORDING TO INCREASING ENERGY
C
C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                      PRESENT IF
CS      -----
CS      FILE IDENTIFICATION              ALWAYS
CS      FILE CONTROL                     ALWAYS
CS      FILE DATA                       ALWAYS
CS
CS      ***** (REPEAT FOR ALL GROUPS)
CS      *      PRINCIPAL CROSS SECTIONS    ALWAYS
CS      *      SCATTERING CONTROL DATA    NORD.NE.0
CS      *      SCATTERING MATRIX           NORD.NE.0
CS      *****
C
C-----
C
C
C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME      HOLLERITH FILE NAME - ADJMAC - (A6)
CD      HUSE(I)    HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS      FILE VERSION NUMBER
CD      MULT       DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C-----
CR      FILE CONTROL
C
CL      NGROUP, NMAT, NORD, NED, IDPF, LNG, MAXUP, MAXDN, NPRIN, I2LP1
C
CW      10=NUMBER OF WORDS

```

C		
CD	NGROUP	NUMBER OF ENERGY GROUPS IN FILE
CD	NMAT	NUMBER OF MATERIALS IN FILE
CD	NORD	NUMBER OF LEGENDRE SCATTERING ORDERS
CD	NED	NUMBER OF EXTRA EDIT CROSS SECTIONS (IN ADDITION
CD		TO THE BASIC PRINCIPAL CROSS SECTIONS)
CD	IDPF	0/1 NO/YES CROSS SECTION DATA ARE DOUBLE PRECISION
CD	LNG	NUMBER OF THE LAST NEUTRON GROUP (FOR COUPLED SETS)
CD	MAXUP	MAXIMUM NUMBER OF UPSCATTER GROUPS
CD	MAXDN	MAXIMUM NUMBER OF DOWNSCATTER GROUPS
CD	NPRIN	NUMBER OF PRINCIPAL CROSS SECTIONS
CD	I2LPI	0/1 = NO/YES 2L+1 TERM WAS INCLUDED IN LIBRARY

C

C

C

C

C

CR

FILE DATA

C

CL

((HMAT(I), I=1, NMAT), (HED(J), J=1, NEDT), (VEL(N), N=1, NGROUP),

CL

1(EMAX(N), N=1, NGROUP), EMIN

C

CW

NMAT+NEDT+2*NGROUP+1=NUMBER OF WORDS

C

CD

HMAT(I)

HOLLERITH MATERIAL LABEL FOR MATERIAL I (A6)

CD

HED(J)

HOLLERITH LABEL FOR J-TH CROSS SECTION POSITION(A6)

CD

VEL(N)

MEAN NEUTRON VELOCITY IN GROUP N (CM/SEC)

CD

EMAX(N)

MAXIMUM ENERGY BOUND OF GROUP N (EV)

CD

EMIN

MINIMUM ENERGY BOUND OF SET (EV)

CD

NEDT

NED+NPRIN

C

CN

THE FOUR BASIC PRINCIPAL CROSS SECTIONS

CN

ALWAYS PRESENT ARE:

CN

HED(1) = 3HCHI

CN

HED(2) = 6HNUSIGF

CN

HED(3) = 5HTOTAL

CN

HED(4) = 3HABS

CN

C

CN

ALSO PRESENT WHEN NPRIN=5 IS:

C

CN

HED(5) = 5HTRANS

C

C

C

CR

PRINCIPAL CROSS SECTIONS FOR GROUP N

C

CL

((C(I,J), I=1, NMAT), J=1, NEDT)

C

CW

NMAT*NEDT=NUMBER OF WORDS

C

CD

C(I,J)

PRINCIPAL CROSS SECTIONS

C

CN

BASIC PRINCIPAL CROSS SECTIONS ALWAYS PRESENT ARE:

```

CN
CN      J=1  FISSION SPECTRUM
CN      J=2  FISSION NU*FISSION CROSS SECTION
CN      J=3  TOTAL CROSS SECTION
CN      J=4  ABSORPTION CROSS SECTION
C
CN      ALSO PRESENT WHEN NPRIN=5 IS:
C
CN      J=5  TRANSPORT CROSS SECTION
C
C-----
C
C-----
CR      SCATTERING CONTROL BLOCK FOR GROUP N
C
CC      PRESENT IF NORD.GT.0
C
CL      ((NGPB(L,J),L=1,NORD),J=1,NMAT)
CL      ((IFSG(L,J),L=1,NORD),J=1,NMAT)
C
CW      2*NORD*NMAT=NUMBER OF WORDS
C
CD      NGPB(L,J)  NUMBER OF SOURCE GROUPS THAT CAN SCATTER INTO GROUP N-
CD      IFSG(L,J)  GROUP NUMBER OF THE FIRST SOURCE GROUP
CD      L          LEGENDRE ORDER NUMBER
CD      J          MATERIAL NUMBER
C
C-----
C-----
CR      SCATTERING SUB-BLOCK FOR GROUP N
C
CC      PRESENT IF NORD.GT.0
C
CL      (SCAT(I),I=1,NTAB)
C
CW      NTAB=NUMBER OF WORDS
C
CD      SCAT(I)    SCATTERING CROSS SECTION
C
CD      NTAB       TABLE LENGTH OF THE CROSS SECTIONS FOR SCATTERING
CD                  INTO GROUP N. THIS IS FOR ALL MATERIALS AND ALL
CD                  LEGENDRE ORDERS, THUS IT IS THE SUM OF NGPB(L,J)
CD                  OVER L FROM 1 TO NORD AND OVER J FROM 1 TO NMAT.
C
CN                  THE SCATTERING CROSS SECTIONS ARE PACKED IN BANDS.
CN                  ONE FOR EACH LEGENDRE ORDER AND MATERIAL. EACH BAND-
CN                  CONTAINS THE NGPB GROUPS WHICH SCATTER INTO GROUP
CN                  N. THE FIRST SOURCE GROUP NUMBER IS IFSG AND
CN                  THE LAST IS IFSG-NGPB+1. THE NORD BANDS FOR THE
CN                  FIRST MATERIAL APPEAR FIRST (P0, P1, ....) FOLLOWED-
CN                  BY THE NORD BANDS FOR THE SECOND, ETC.
C
CN                  HIGHER LEGENDRE ORDER SCATTERING CROSS SECTIONS
CN                  INCLUDE A 2*L+1 FACTOR WHERE L IS THE LEGENDRE

```

CN

ORDER.

C

C

CEOF


```

C*****
C                                     DATE 09/18/81
C
CF      ,SGMAT
CE      CODE DEPENDENT FILE ASSIGNING MATERIALS TO ZONES
C
C*****
C
CN      THIS FILE CONTAINS THE INFORMATION FROM THE INPUT
CN      ARRAYS ASSIGN= AND ASGMOD=
C
C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS      COMPATABILITY CODE                        ALWAYS
CS      MATERIAL NAMES                            ALWAYS
CS      ZONE NAMES                                ALWAYS
CS      NUMBER OF MATERIALS PER ZONE              MPZTOT.NE.0
CS      MATERIAL LIST FOR ALL ZONES              MPZTOT.NE.0
CS      MATERIAL CONCENTRATIONS                  MPZTOT.NE.0
CS      MATERIAL CONCENTRATION FACTORS           MPZTOT.NE.0
CS      CONCENTRATION MODIFIER                   MPZTOT.NE.0
C
C-----
C
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - ASGMAT - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C
CR      FILE CONTROL
C
CL      MT, NZONE, MPZTOT
C
CW      3=NUMBER OF WORDS
C
CD      1  MT          NUMBER OF MATERIALS
CD      2  NZONE       NUMBER OF ZONES

```

```

CD   3  MPZTOT   IN-SOLVER MIXING TABLE LENGTH
C
C-----
C
C-----
CR           COMPATABILITY CODE WORDS
C
CL   CODE1, CODE2
C
CW   2=NUMBER OF WORDS
C
CD   1  CODE1   DATE OF THE MACRXS FILE TO WHICH ASGMAT APPLIES
CD   2  CODE2   TIME OF THE MACRXS FILE TO WHICH ASGMAT APPLIES
C
C-----
C
C-----
CR           MATERIAL NAMES
C
CL   (MATNAM(I), I=1, MT)
C
CW   MT=NUMBER OF WORDS
C
CD   MATNAM(I) HOLLERITH NAME FOR THE I-TH MATERIAL
C
C-----
C
C-----
CR           ZONE NAMES
C
CL   (ZONNAM(I), I=1, NZONE)
C
CW   NZONE=NUMBER OF WORDS
C
CD   ZONNAM(I) HOLLERITH NAME FOR THE I-TH ZONE
C
C-----
C
C-----
CR           NUMBER OF MATERIALS PER ZONE
C
CC   PRESENT IF MPZTOT.NE.0
C
CL   (NUMZON(I), I=1, NZONE)
C
CW   NZONE=NUMBER OF WORDS
C
CD   NUMZON(I) NUMBER OF MATERIALS IN THE I-TH ZONE
C
C-----
C
C-----
CR           MATERIAL LIST FOR ALL ZONES
C

```

```

CC      PRESENT IF MPZTOT.NE.0
C
CL      (MATLST(I),I=1,MPZTOT)
C
CW      MPZTOT=NUMBER OF WORDS
C
CD      MATLST      PACKED LIST OF MATERIAL NUMBERS. MATERIALS FOR ZONE 1-
CD                      FOLLOWED BY THOSE FOR ZONE 2, THEN ZONE3, ETC.
C
C-----
C
C-----
CR      MATERIAL CONCENTRATIONS
C
CC      PRESENT IF MPZTOT.NE.0
C
CL      (CONC(I),I=1,MPZTOT)
C
CW      MPZTOT=NUMBER OF WORDS
C
CD      CONC(I)      CONCENTRATION OF THE I-TH MATERIAL IN THE MATLST
CD                      ARRAY
C
C-----
C
C-----
CR      MATERIAL CONCENTRATION FACTORS
C
CC      PRESENT IF MPZTOT.NE.0
C
CL      (C1(I),I=1,MPZTOT)
C
CW      MPZTOT=NUMBER OF WORDS
C
CD      C1(I)      CONCENTRATION FACTOR FOR THE I-TH MATERIAL IN THE
CD                      MATLST ARRAY
C
C-----
C
C-----
CR      CONCENTRATION MODIFIER
C
CC      PRESENT IF MPZTOT.NE.0
C
CL      CMOD
C
CW      1=NUMBER OF WORDS
C
CD      CMOD      INPUT VALUE OF THE CONCENTRATION MODIFIER
C
C-----
CEOF

```

```

C*****
C              REVISED 07/23/75 - REVISED 04/01/80
C
CF          ATFLUX
CE          ADJOINT TOTAL FLUXES
C
C*****

```

ORDER OF GROUPS IS ACCORDING TO INCREASING
ENERGY. NOTE THAT DOUBLE PRECISION FLUXES ARE
GIVEN WHEN MULT.EQ.2

```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME.(HUSE(I),I=1,2),IVERS
C
CW          1 + 3*MULT=NUMBER OF WORDS
C
CD          HNAME          HOLLERITH FILE NAME - ATFLUX - (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CD          MULT            DOUBLE PRECISION PARAMETER
CD                          1- A6 WORD IS SINGLE WORD
CD                          2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          SPECIFICATIONS      (1D RECORD)
C
CL          .NDIM,NGROUP,NINTI,NINTJ,NINTK,ITER,EFFK,ADUM
C
CW          8=NUMBER OF WORDS
C
CD          NDIM            NUMBER OF DIMENSIONS
CD          NGROUP          NUMBER OF ENERGY GROUPS
CD          NINTI           NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD          NINTJ           NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD          NINTK           NUMBER OF THIRD DIMENSION FINE MESH INTERVALS.
CD                          NINTK.EQ.1 IF NDIM.LE.2
C
CN          FOR MESHPOINT EDGE LOCATIONS, NINTI, NINTJ, AND NINTK ARE
CN          INTERPRETED AS THE NUMBER OF POINTS (ONE MORE THAN THE
CN          NUMBER OF INTERVALS)
CN          FOR SPECIAL TRIANGULAR GEOMETRIES, NINTI IS THE NUMBER OF
CN          POINTS ON EACH PLANE, AND NINTJ IS SET TO 1.

```

```

C
CD  ITER          OUTER ITERATION NUMBER AT WHICH FLUX WAS WRITTEN
CD                MADE NEGATIVE FOR MESH EDGE POINTS
CD                SET TO ZERO IF FIXED SOURCE ADJOINT FLUXES
CD                (DOMINANT HARMONIC) HAVE BEEN CORRECTED FOR
CD                FUNDAMENTAL CONTAMINATION
CD  EFFK          EFFECTIVE MULTIPLICATION FACTOR
CD  ADUM          ZERO FOR NON FIXED SOURCE PROBLEM
CD                SUM FIXED SOURCE IF FIXED SOURCE PROBLEM
C
C-----
C-----
CR          ONE DIMENSIONAL ADJOINT TOTAL FLUX  (2D RECORD)
C
CC          PRESENT IF NDIM.EQ.1
C
CL  ((FADJ(I,J),I=1,NINTI),J=1,NGROUP)
C
CW  NINTI*NGROUP*MULT=NUMBER OF WORDS
C
CD  FADJ(I,J)     ONE DIMENSIONAL ADJOINT TOTAL FLUX BY INTERVAL
CD                AND GROUP
C
C-----
C-----
CR          MULTI-DIMENSIONAL ADJOINT TOTAL FLUX  (3D RECORD)
C
CC          PRESENT IF NDIM.GE.2
C
CL  ((FADJ(I,J),I=1,NINTI),J=1,NINTJ)-----NOTE STRUCTURE BELOW-----
C
CW  NINTI*NINTJ*MULT=NUMBER OF WORDS
C
CS  DO 1 L=1,NGROUP
CS  DO 1 K=1,NINTK
CS  1 READ(N)     *LIST AS ABOVE*
C
CD  FADJ(I,J)     MULTI-DIMENSIONAL ADJOIN TOTAL FLUX
CD                BY INTERVAL FOR EACH GROUP
C
C-----
C*****
C
CEOF
C
C-----

```

```

C*****
C                                     REVISED 11/30/76
C
CF      BRKOXS-IV
CE      BONDARENKO SELF-SHIELDING TABLES
C
CN      THIS FILE PROVIDES DATA NECESSARY FOR
CN      BONDARENKO TREATMENT IN ADDITION TO
CN      THOSE DATA IN FILE ISOTXS
CN      FORMATS GIVEN ARE FOR FILE EXCHANGE PURPOSES
CN      ONLY.
C
C*****

```

```

C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====                                =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS      FILE DATA                                ALWAYS
CS      ***** (REPEAT FROM 1 TO NISOSH)
CS      *      SELF-SHIELDING FACTORS              ALWAYS
CS      *
CS      *      CROSS SECTIONS                      ALWAYS
CS      *****
CS
C-----

```

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CB      FORMAT(11H OV BRKOXS ,1H*,2A6,1H*,I6)
C
CD      HNAME      HOLLERITH FILE NAME - BRKOXS - (A6)
CD      HUSE       HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS      FILE VERSION NUMBER
CD      MULT       DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          FILE CONTROL          (1D RECORD)
C
CL  NGROUP,NISOSH,NSIGPT,NTEMPT,NREACT,IBLK
C
CW  6 = NUMBER OF WORDS
C
CB  FORMAT(4H 1D ,6I6)
C
CD  NGROUP          NUMBER OF ENERGY GROUPS IN SET
CD  NISOSH          NUMBER OF ISOTOPES WITH SELF-SHIELDING FACTORS
CD  NSIGPT          TOTAL NUMBER OF VALUES OF VARIABLE X (SEE FILE DATA-
CD                   RECORD) WHICH ARE GIVEN. NSIGPT IS EQUAL TO
CD                   THE SUM FROM 1 TO NISOSH OF NTABP(I)
CD  NTEMPT          TOTAL NUMBER OF VALUES OF VARIABLE TB (SEE FILE
CD                   DATA RECORD) WHICH ARE GIVEN. NTEMPT IS EQUAL
CD                   TO THE SUM FROM 1 TO NISOSH OF NTABT(I)
CD  NREACT          NUMBER OF REACTION-TYPES FOR WHICH SELF-SHIELDING
CD                   FACTORS ARE GIVEN (IN PREVIOUS VERSIONS OF THIS
CD                   FILE NREACT HAS BEEN IMPLICITLY SET TO 5).
CD  IBLK            BLOCKING OPTION FLAG FOR SELF-SHIELDING FACTORS.
CD                   IBLK=0, FACTORS NOT BLOCKED BY REACTION-TYPE.
CD                   IBLK=1, FACTORS ARE BLOCKED BY REACTION-TYPE.
C-----

```

```

C-----
CR          FILE DATA            (2D RECORD)
C
CL  (HISONM(I),I=1,NISOSH),(X(K),K=1,NSIGPT),(TB(K),K=1,NTEMPT),
CL  1(EMAX(J),J=1,NGROUP),EMIN,(JBFL(I),I=1,NISOSH),
CL  2(JBFH(I),I=1,NISOSH),(NTABP(I),I=1,NISOSH),(NTABT(I),I=1,NISOSH)
C
CW  (4+MULT)*NISOSH+NSIGPT+NTEMPT+NGROUP+1=NUMBER OF WORDS
C
CB  FORMAT(4H 2D ,9(1X,A6)/          HISONM
CB  1(10(1X,A6)))
CB  FORMAT ( 6E12.5)                  X,TB,EMAX,EMIN
CB  FORMAT(12I6)                      JBFL,JBFH,NTABP,NTABT
C
CD  HISONM(I)      HOLLERITH ISOTOPE LABEL FOR ISOTOPE I (A6). THESE
CD                   LABELS MUST BE A SUBSET OF THOSE IN FILE ISOTXS
CD                   OR GRUPXS, IN THE CORRESPONDING ARRAY.
CD  X(K)           ARRAY OF LN(SIGPO)/LN(10) VALUES FOR ALL ISOTOPES,
CD                   WHERE SIGPO IS THE TOTAL CROSS SECTION OF THE
CD                   OTHER ISOTOPES IN THE MIXTURE IN BARNS PER ATOM
CD                   OF THIS ISOTOPE. FOR ISOTOPE I, THE NTABP(I)
CD                   VALUES OF X FOR WHICH SELF-SHIELDING FACTORS

```

CD ARE GIVEN ARE STORED STARTING AT LOCATION L=1+
 CD SUM FROM 1 TO I-1 OF NTABP(K).
 CD TB(K) ARRAY OF TEMPERATURES (DEGREES C) FOR ALL ISOTOPES.
 CD FOR ISOTOPE I, THE NTBT(I) VALUES OF TB FOR
 CD WHICH SELF-SHIELDING FACTORS ARE GIVEN ARE
 CD STORED AT LOCATION L=1+SUM FROM 1 TO I-1 OF
 CD NTABT(K).

CD EMAX(J) MAXIMUM ENERGY BOUND OF GROUP J (EV)
 CD EMIN MINIMUM ENERGY BOUND OF SET (EV)
 CD JBFL(I) LOWEST NUMBERED OR HIGHEST ENERGY GROUP FOR WHICH
 CD JBFH(I) SELF-SHIELDING FACTORS ARE GIVEN
 CD HIGHEST NUMBERED OR LOWEST ENERGY GROUP FOR WHICH
 CD NTABP(I) SELF-SHIELDING FACTORS ARE GIVEN
 CD NUMBER OF SIGPO VALUES FOR WHICH SELF-SHIELDING
 CD NTABT(I) FACTORS ARE GIVEN FOR ISOTOPE I.
 CD NUMBER OF TEMPERATURE VALUES FOR WHICH SELF-
 C SHIELDING FACTORS ARE GIVEN FOR ISOTOPE I.
 C

C-----
 CR SELF-SHIELDING FACTORS (3D RECORD)
 C
 CL (((FFACT(N,K,J,M),N=1,NBINT),K=1,NBTEM),J=JBFLI,JBFHI),M=ML,MU)
 CL ----- SEE DESCRIPTION BELOW -----
 C
 CC NBINT=NTABP(I)
 CC NBTEM=NTABT(I)
 CC JBFLI=JBFL(I)
 CC JBFHI=JBFH(I)
 CC FOR ML, MU SEE STRUCTURE BELOW
 C
 CW NBINT*NBTEM*(JBFHI-JBFLI+1)*(MU-ML+1) = NUMBER OF WORDS
 C
 CB FORMAT(4H 3D , 5E12.5/(6E12.5))
 C
 CC DO 1 L=1,NBLOK
 CC 1 READ(N) *LIST AS ABOVE*
 C
 CC IF IBLK=0, NBLOK=1, ML=1, MU=NREACT
 CC IF IBLK=1, NBLOK=NREACT, ML=MU=L, WHERE L IS THE BLOCK
 CC INDEX.
 C
 CD FFACT(N,K,J,M) SELF-SHIELDING FACTOR EVALUATED AT X(N) AND
 CD TB(K) FOR ENERGY GROUP J. THE M INDEX IS
 CD A DUMMY INDEX TO DENOTE THE REACTION-TYPE.


```

CD          THE FIRST FIVE REACTION-TYPES ARE, IN
CD          ORDER, TOTAL, CAPTURE, FISSION, TRANSPORT,
CD          AND ELASTIC.
C
CN          NOTE THAT IF IBLK=1, EACH REACTION-TYPE WILL CONSTITUTE
CN          A SEPARATE DATA BLOCK.
C
C-----

```

```

C-----
CR          CROSS SECTIONS   (4D RECORD)
C
CL          (XSPO(J),J=1,NGROUP),(XSIN(J),J=1,NGROUP),(XSE(J),J=1,NGROUP),
CL          1(XSMU(J),J=1,NGROUP),(XSED(J),J=1,NGROUP),(XSXI(J),J=1,NGROUP)
C
CW          6*NGROUP=NUMBER OF WORDS
C
CB          FORMAT(4H 4D , 5E12.5/(6E12.5))
C
CD          XSPO(J)          POTENTIAL SCATTERING CROSS SECTION (BARNs)
CD          XSIN             INELASTIC CROSS SECTION (BARNs)
CD          XSE(J)           ELASTIC CROSS SECTION (BARNs)
CD          XSMU(J)          AVERAGE COSINE OF ELASTIC SCATTERING ANGLE
CD          XSED(J)          ELASTIC DOWN-SCATTERING TO ADJACENT GROUP
CD          XSXI(J)          AVERAGE ELASTIC SCATTERING LETHARGY INCREMENT
C
C-----

```

CEOF

```

C*****
C                                     DATE 09/22/88
C
C
CF      BXSLIB
CE      MICROSCOPIC GROUP NEUTRON CROSS SECTIONS FROM CARDS
C
CN      THIS FILE CONTAINS IN BINARY FORM THE
CN      BLOCK III ONEDANT INPUT TOGETHER WITH THE
CN      CROSS SECTIONS FROM THE ORIGINAL CARD LIBRARY.
CN      THE FILE ALSO MAY CONTAIN ISOTOPE/ATOMIC WEIGHT-
CN      PAIRS FROM THE BLOCK IV ONEDANT INPUT
C
C*****
C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS      FILE DATA                                ALWAYS
CS
CS      ***** (REPEAT FOR ALL ISOTOPES)
CS      * ***** (REPEAT FOR ALL LEGENDRE ORDERS)
CS      * *      CROSS SECTION SET                ALWAYS
CS      * *****
CS      *****
CS      ISOTOPE LABEL/ATOMIC WEIGHT PAIR    NISOAW.GT.0
C
C-----
C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
C
CD      HNAME      HOLLERITH FILE NAME - BXSLIB - (A6)
CD      HUSE(I)    HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS      FILE VERSION NUMBER
CD      MULT       DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C-----
CR      FILE CONTROL
C
CL      NGROUP, NISO, IHM, IHT, IHS, MAXT, NISOAW, NXSREC, I2LP1
C
CW      9=NUMBER OF WORDS
C
C

```

CD	NGROUP	NUMBER OF ENERGY GROUPS IN FILE	-
CD	NISO	NUMBER OF ISOTOPES IN FILE	-
CD	IHM	TABLE LENGTH (NUMBER OF CROSS SECTIONS FOR	-
CD		ONE ISOTOPE, FOR ONE GROUP, AND FOR ONE LEGENDRE	-
CD		ORDER	-
CD	IHT	TOTAL CROSS SECTION POSITION IN THE TABLE	-
CD	IHS	SELF SCATTER CROSS SECTION POSITION	-
CD	MAXT	MAXIMUM NUMBER OF LEGENDRE MOMENTS	-
CD	NISOAW	NUMBER OF ISOTOPE LABEL/ATOMIC WEIGHT PAIR	-
CD	NXSREC	TOTAL NUMBER OF CROSS SECTION SETS	-
CD	I2LP1	0/1 - NO/YES SCATTERING CROSS SECTIONS CONTAIN	-
CD		2L+1 FACTOR	-
C			-
C			-
C			-
CR	FILE DATA		-
C			-
CL	(HSETID(I), I=1, 12), (HISONM(I), I=1, NISO), (EDNAME(I), I=1, IHT-3),		-
CL	1(CHI(J), J=1, NGROUP), (VEL(J), J=1, NGROUP),		-
CL	2(EMAX(J), J=1, NGROUP), EMIN, (NSPI(I), I=1, NISO)		-
C			-
CW	(NISO+12+IHT-3)*MULT+(3*NGROUP+1)*MULT+NISO=NUMBER OF WORDS		-
C			-
C			-
CD	HSETID(I)	HOLLERITH IDENTIFICATION OF FILE (A6)	-
CD	HISONM(I)	HOLLERITH ISOTOPE LABEL FOR ISOTOPE I (A6)	-
CD	EDNAME(I)	HOLLERITH NAME FOR EDIT POSITIONS	-
CD		PRECEDING SIGMA ABSORPTION FOR POSITION I (A6)	-
CD	CHI(J)	FILE-WIDE FISSION SPECTRUM(ZEROES IN ONEDANT)	-
CD	VEL(J)	MEAN NEUTRON VELOCITY IN GROUP J (CM/SEC)	-
CD	EMAX(J)	MAXIMUM ENERGY BOUND OF GROUP J (EV)	-
CD	EMIN	MINIMUM ENERGY BOUND OF SET (EV)	-
CD	NSPI(I)	NUMBER OF LEGENDRE ORDERS FOR ISOTOPE I	-
C			-
C			-
C			-
CR	CROSS SECTION SET FOR ISOTOPE I AND LEGENDRE ORDER M		-
C			-
CL	((C(I, J), I=1, IHM), J=1, NGROUP)		-
C			-
CW	IHM*NGROUP*MULT=NUMBER OF WORDS		-
C			-
C			-
C			-
CR	HOLLERITH ISOTOPE LABEL/ATOMIC WEIGHT PAIR SET		-
C			-
CC	PRESENT IF NISOAW.GT.0		-
C			-
CL	(ATWTP(I), I=1, 2*NISOAW)		-
C			-
CW	2*NISOAW*MULT=NUMBER OF WORDS		-
C			-
C			-
C			-
CEOF			-

SPECIFICATIONS FOR INTERFACE FILE CPHIST

```

C.....
C          REFERENCE 05/01/79
C
C  CPHIST
C
C  RECORD OF EXPOSURE HISTORY (CONTINUOUS FUELING MODEL)
C.....

```

```

C-----
C  FILE STRUCTURE
C-----
C          RECORD TYPE          PRESENT IF
C          -----
C          FILE IDENTIFICATION  ALWAYS
C          10 FILE REFERENCE INFORMATION  ALWAYS
C          ***** (REPEAT FROM 1 TO IHIST)
C          * 20 GENERAL INFORMATION  ALWAYS
C          * 30 TOTAL FUELANCE  NPLUT = 1
C          * 40 FUELANCE RANGE 1  NPLC1 = 1
C          * 50 FUELANCE RANGE 2  NPLJ2 = 1
C          * 60 FISSIONS  NFR1 = 1
C          * 90 EXPOSURE  NFR2 = 1
C          * 100 ENERGY  NRR3 = 1
C          * 110 UNDEFINED  NRR4 = 1
C          *****
C-----

```

```

C-----
C  FILE IDENTIFICATION
C-----
C          RNAME, (HUSE (I), I=1,2), IVERS
C
C          3*MULT = 1
C
C          RNAME  FILE NAME (A6) 'CPHIST'
C          HUSE  USER IDENTIFICATION (A6)
C          IVERS  FILE VERSION NUMBER
C
C          MULT  1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C-----

```

```

C-----
C  10  FILE REFERENCE INFORMATION
C-----
C          IXP1, IXP2, IXP3, IPL1, IPL2, IHIST, IZONE, ISL,
C          NPLUT, NPLC1, NPLJ2, IXP12, IXP13, NRR1, NRR2, NRR3,
C          NRR4, IXP18, IXP19, IXP20, NRT1, NRT2, KRT1, KRT2,
C          NPD1, NPD2, NPD3, NPD4, IXP29, IXP30
C
C          30
C-----

```

(CONT)

C			
CD	EXPH1	END OF EXPOSURE TIME (DAYS) FROM LAST SET OF DATA	-
CD	EXPH2	RESERVED	-
CD	EXPH3	RESERVED	-
CD	EFLU1	CUTOFF ENERGY (eV) FOR FIRST FLUENCE	-
CD	EFLU2	CUTOFF ENERGY (eV) FOR SECOND FLUENCE	-
CD	INIST	NUMBER OF SETS OF DATA	-
CD	ISONE	NUMBER OF ZONES	-
CD	ISZ	NUMBER OF SUBZONES	-
CD	NFLU1	OPTION FOR TOTAL FLUENCE	-
CD		0 - NOT PRESENT	-
CD		1 - PRESENT	-
CD	NFLU1	OPTION FOR FLUENCE IN FIRST RANGE	-
CD		0 - NOT PRESENT	-
CD		1 - PRESENT	-
C			-
CN		WHEN NFLU1 = 1, EFLU1 MUST BE GREATER THAN 0 AND	-
CN		LIE IN THE ENERGY RANGE SPECIFIED IN THE	-
CN		CROSS SECTION DATA	-
C			-
CD	NFLU2	OPTION FOR FLUENCE IN SECOND RANGE	-
CD		0 - NOT PRESENT	-
CD		1 - PRESENT	-
C			-
CN		WHEN NFLU2 = 1, EFLU2 MUST BE GREATER THAN 0 AND	-
CN		LIE IN THE ENERGY RANGE SPECIFIED IN THE	-
CN		CROSS SECTION DATA	-
C			-
CD	IXPH12	RESERVED	-
CD	IXPH13	RESERVED	-
CD	NRR1	OPTION FOR FISSIONS	-
CD		0 - NOT PRESENT	-
CD		1 - PRESENT	-
CD	NRR2	OPTION FOR EXPOSURE	-
CD		0 - NOT PRESENT	-
CD		1 - PRESENT	-
CD	NRR3	OPTION FOR ENERGY	-
CD		0 - NOT PRESENT	-
CD		1 - PRESENT	-
CD	NRR4	OPTION FOR UNDEFINED	-
CD		0 - NOT PRESENT	-
CD		1 - PRESENT	-
CD	IXPH18	RESERVED	-
CD	IXPH19	RESERVED	-
CD	IXPH20	INDICATOR NORMALLY = 0, BUT IS SET = 1 IF	-
CD		A DISCONTINUITY EXISTS IN EXPOSURE TIMES	-
CD	NRT1	NUMBER OF ZONE PATHS	-
CD	NRTS2	NUMBER OF SUBZONE PATHS	-
C			-
CN		NRT1 + NRTS2 MUST BE LESS THAN OR EQUAL TO 70	-
C			-
CD	NRT2	NUMBER OF ZONES ALONG EACH ZONE PATH	-
CD	NRTS2	NUMBER OF SUBZONES ALONG EACH SUBZONE PATH	-

(CONT)

```

C3  NPDZ1      ZONE NUMBER CONTAINING FIRST ZONE PATH FEED
C3  NPDZ2      ZONE NUMBER CONTAINING LAST ZONE PATH FEED
C3  NPDZ2      MATERIAL COMPOSITION
C
C3  NPDZ2 = NPDZ1
C3  OR
C3  NPDZ2 = NPDZ1 + NRTZ - 1
C
C3  NPDZS1     ZONE NUMBER CONTAINING FIRST SUBZONE PATH FEED
C3  NPDZS2     ZONE NUMBER CONTAINING LAST SUBZONE PATH FEED
C3  NPDZS2     MATERIAL COMPOSITION
C
C3  NPDZS2 = NPDZS1
C3  OR
C3  NPDZS2 = NPDZS1 + NRTSZ - 1
C
C3  IIPH29     RESERVED
C3  IIPH30     RESERVED
C

```

```

C-----
C3  20  GENERAL INFORMATION
C
C3  (EPHT(2), IS=1, 40), (TPHT(NRT), NRT=1, NRTT)
C
C3  40 + NRTT = 40 + (NRTZ + NRTSZ)
C
C3  EPHT(1)    END OF EXPOSURE TIME (DAYS)
C3  EPHT(2)    START OF EXPOSURE TIME (DAYS)
C3  EPHT(3)    FRACTION OF COPE TREATED IN PROBLEM
C3  EPHT(4)    CONVERSION FACTOR, RATIO OF THERMAL ENERGY TO
C3  FISSIION + CAPTURE ENERGY (FROM CROSS SECTIONS)
C3  EPHT(5-43) RESERVED
C3  TPHT       EXPOSURE TIME BY ZONE AND SUBZONE PATH
C3  (DAYS PER ZONE (SUBZONE))
C

```

```

C-----
C3  30  TOTAL FLUENCE
C
C3  PRESENT IF NPLUT = 1
C
C3  (PLUT(N), NN=1, ITZSZ), (PLUTD(NRT), NRT=1, NRTT)
C
C3  ITZSZ + NRTT = (IZONE + ISZ) + (NRTZ + NRTSZ)
C
C3  PLUT       TOTAL FLUENCE BY ZONE AND SUBZONE (NEUTRONS/CM**2)
C3  ACCUMULATED ALONG PATHS
C3  PLUTD      DISCHARGE TOTAL FLUENCE BY ZONE AND SUBZONE PATH
C3  (NEUTRONS/CM**2)
C

```

(CONT)

```

C-----
CR  8D  FLUENCE TO FIRST CUTOFF ENERGY 2FL01
C
CC      PRESENT IF 2FL01 = 1
C
CL      (FL01(NH),NH=1,ITZSZ), (FL01D(NRT),NRT=1,NRTT)
C
CW      ITZSZ + NRTT = (IZONE + ISZ) + (NRTZ + NRTSZ)
C
CD  FL01      FLUENCE IN FIRST RANGE BY ZONE AND SUBZONE
CD              (NEUTRONS/CM**2) ACCUMULATED ALONG PATHS
CD  FL01D     DISCHARGE FLUENCE IN FIRST RANGE BY ZONE AND
CD              SUBZONE PATH (NEUTRONS/CM**2)
C-----

```

```

C-----
CR  9D  FLUENCE TO SECOND CUTOFF ENERGY 2FL02
C
CC      PRESENT IF 2FL02 = 1
C
CL      (FL02(NH),NH=1,ITZSZ), (FL02D(NRT),NRT=1,NRTT)
C
CW      ITZSZ + NRTT = (IZONE + ISZ) + (NRTZ + NRTSZ)
C
CD  FL02      FLUENCE IN SECOND RANGE BY ZONE AND SUBZONE
CD              (NEUTRONS/CM**2) ACCUMULATED ALONG PATHS
CD  FL02D     DISCHARGE FLUENCE IN SECOND RANGE BY ZONE AND
CD              SUBZONE PATH (NEUTRONS/CM**2)
C-----

```

```

C-----
CR  6D  RESERVED
C-----

```

```

C-----
CR  7D  RESERVED
C-----

```

```

C-----
CR  8D  FISSIONS
C
CC      PRESENT IF NRR1 = 1
C
CL      (RR1(NH),NH=1,ITZSZ), (RR1D(NRT),NRT=1,NRTT)
C
CW      ITZSZ + NRTT = (IZONE + ISZ) + (NRTZ + NRTSZ)
C
CD  RR1      FISSIONS BY ZONE AND SUBZONE
CD              (FISSIONS/CM**3) ACCUMULATED ALONG PATHS
CD  RR1D     DISCHARGE FISSIONS BY ZONE AND SUBZONE PATH
CD              (FISSIONS/CM**3)
C-----

```

(CONT)

```

C-----
CR  90  EXPOSURE
C
CC      PRESENT IF NRR2 = 1
C
CL      (PR2(NR),NR=1,ITZSZ), (RR2D(NRT),NRT=1,NRTT)
C
CV      ITZSZ + NRTT = (IZONE + ISZ) + (NRTT + NRTSZ)
C
CD  RR2      EXPOSURE BY ZONE AND SUBZONE
CD              (MEGAWATT(THERMAL)-DAYS/CG) ACCUMULATED ALONG
CD              PATHS
CD  RR2D     DISCHARGE EXPOSURE BY ZONE AND SUBZONE PATH
CD              (MEGAWATT(THERMAL)-DAYS/CG)
C-----

```

```

C-----
CR  100  ENERGY
C
CC      PRESENT IF NRR3 = 1
C
CL      (PR3(NR),NR=1,ITZSZ), (RR3D(NRT),NRT=1,NRTT)
C
CV      ITZSZ + NRTT = (IZONE + ISZ) + (NRTT + NRTSZ)
C
CD  RR3      ENERGY BY ZONE AND SUBZONE
CD              (MEGAWATT(THERMAL)-DAYS/CH=3) ACCUMULATED ALONG
CD              PATHS
CD  RR3D     DISCHARGE ENERGY BY ZONE AND SUBZONE PATH
CD              (MEGAWATT(THERMAL)-DAYS/CH=3)
C-----

```

```

C-----
CR  110  UNDEFINED
C
CC      PRESENT IF NRR4 = 1
C
CL      (RR4(NR),NR=1,ITZSZ), (RR4D(NRT),NRT=1,NRTT)
C
CV      ITZSZ + NRTT = (IZONE + ISZ) + (NRTT + NRTSZ)
C
CD  RR4      UNDEFINED BY ZONE AND SUBZONE
CD  RR4D     UNDEFINED BY ZONE AND SUBZONE PATH
C-----

```

```

C-----
CZOP  CPHIST
C-----

```


FIGURE 204-1. SPECIAL DATA FILE SPECIFICATIONS

```

C-----
CN      DATE 3-15-77
C
C
C
C
CZ      CODE-BLOCK-DEPENDENT DATA UNDER CONTROL OF THE DRIVER
C-----

CS      A FILE IDENTIFICATION RECORD ALWAYS FIRST
CS      THE FOLLOWING ARE CONTROL DATA RECORDS, ONE FOR EACH CODE
CS      DATA BLOCK, LENGTH 101*MULT+100 WORDS, 201 LONG, 302 SHORT
CS
CS      RECORD NAME      CODE BLOCK (MODULE)      REQUIREMENT
CS      -----
CS      PROINS           (PROBLEM INFORMATION)      ALWAYS FIRST
CS      DVRINS           (MODULE DRIVING INFORMATION) ALWAYS
CS      ICPINS           CROSS SECTION PROCESSOR      AS NEEDED
CS      DTNINS           NEUTRONICS (VENTURE)         AS NEEDED
CS      RTNINS           REACTION RATE               AS NEEDED
CS      BLANK            (CLOSURE)                   ALWAYS LAST
CS      SUCH OF THE DATA IN THE INDIVIDUAL INSTRUCTION RECORDS IS
CS      NOT DEFINED, IT BEING RESERVED FOR FUTURE USE AND DEFINITION
C
C-----
CR      FILE IDENTIFICATION
C
C
CL      HNAME, (H0SZ(I), I=1,2), IVERS
C
CW      3*MULT + 1
C
CD      HNAME           FILE NAME (A6) 'CONTEL'
CD      H0SZ            USER IDENTIFICATION (A6)
CD      IVERS           FILE VERSION NUMBER
C
CN      MULT            1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----
C-----
CR      PROBLEM INFORMATION
C
C
CL      PROINS, (IX(I), I=1,100), (IX(I), I=1,100)
C
CW      101*MULT + 100
C
CD      PROINS          PROBLEM INFORMATION DATA IDENTIFIER (6*PROINS)
CD      IX(1-24)        PROBLEM OR CASE TITLE (A6)
CD      IX(25)          USER LABEL (JOBNAME) FOR INTERFACE DATA FILES (A6)
CD      IX(26)          USER LABEL (DATE) FOR INTERFACE DATA FILES (A6)
C
C-----

```

(CONT)

SPECIFICATIONS FOR BLANK RECORD IN INTERFACE FILE CONTROL

```

C-----
CR      CLOSURE
C
CL      BLANK1, (IX(I),I=1,100), (IX(I),I=1,100)
C
CF      101*MULT + 100
C
CD      BLANK1      END OF FILE IDENTIFIER (6H      ) OR (6HBLANK )
C-----
C.....
C
CENDP      CONTROL
C
C.....

```

SPECIFICATIONS FOR DTWINS RECORD IN INTERFACE FILE CONTROL

```

C-----
C      NEUTRONICS INSTRUCTIONS
C
C      DTWINS. (XX(I),I=1,100), (XX(I),I=1,100)
C
C      101=HULT * 100
C
C      DTWINS      NEUTRONICS CONTROL IDENTIFIER, A(6)
C      XX(1)      REFERENCE REAL TIME, DAYS
C      XX(2)      MACHINE TIME ALLOWED FOR SOLUTION, MIN
C                  (ITERATION TERMINATED IF TIME EXCEEDED)
C      XX(3)      CYCLE TIME IN MINUTES TO WRITE RESTART DATA
C                  NOT DONE IF 0, ALWAYS DONE AT END IF NON-ZERO
C
C      NOTE THAT VARIABLES NOT DEFINED ARE RESERVED FOR LATER USE
C
C      XX(4)      POWER LEVEL OF REACTOR, WATTS THERMAL
C                  IF 0, NORMALIZATION IS TO ONE SOURCE NEUTRON
C                  (WATT-SEC/PISS DEFAULTED TO 3.2E-11 IF ZERO)
C      XX(5)      ENERGY CONVERSION FACTOR, FISSION TO THERMAL
C      XX(6)      FRACTION OF REACTOR TREATED
C      XX(7)      SPECIFIED MULTIPLICATION FACTOR FOR SEARCH IF
C                  NON-ZERO
C      XX(8)      SPECIFIED OVERRELAXATION COEFFICIENT IF NON-ZERO
C      XX(9)      ESTIMATE OF THE EIGENVALUE FOR CHEBYSHEV
C                  ACCELERATION ON OUTER ITERATIONS
C      XX(10)     ESTIMATE OF THE LOWER LIMIT OF THE SPECTRUM OF
C                  EIGENVALUES FOR CHEBYSHEV ACCELERATION
C      XX(11)     CONVERGENCE CRITERIA ON INTEGRAL QUANTITIES
C                  MAXIMUM RELATIVE CHANGE ON OUTER ITERATION
C      XX(12)     CONVERGENCE CRITERIA ON LOCAL OR POINT VARIABLES-
C                  MAXIMUM RELATIVE POINT FLUX CHANGE ON OUTER
C                  ITERATION (.00005)
C      XX(13)     CONSTANT BUCKLING VALUE WHICH OVERRIDES THE DATA
C                  IN GEODST FILE IF NON-ZERO
C      XX(14)     RESERVED
C      XX(15)     RESERVED
C      XX(16)     RESERVED
C      XX(17)     RESERVED
C      XX(18)     RESERVED
C      XX(19)     LIMITING VALUE OF ANY DIFFUSION COEFFICIENT
C                  IF NOT ZERO - DEFAULT 100.0
C      XX(20)     PARAMETER FOR HIGHER ORDER VALE SOLUTION
C                  1/6 = 0.1666666 - TAYLOR SERIES
C                  7/16 = 0.194444 - LINEAR FLUX
C                  1/4 = 0.25 - LINEAR FINITE ELEMENT
C                  IF MADE NEGATIVE, THE HIGHER ORDER APPROXIMATION-
C                  IS NOT APPLIED TO THE SOURCE

```

(CONT)

CS	II(21)	THE ZONE AND GROUP DIFFUSION COEFFICIENTS	-
CS		THROUGH ZONE II(83) (SEE BELOW) WILL BE	-
CS		MULTIPLIED BY THIS NUMBER IF NOT ZERO	-
CS	II(22)	THIS NUMBER WILL BE ADDED TO THE ZONE AND	-
CS		GROUP DIFFUSION COEFFICIENTS THROUGH ZONE	-
CS		II(83) AFTER II(21) IS APPLIED IF NOT ZERO.	-
CS	II(23)	XENON+IODINE YIELD FRACTION FOR EQUILIBRIUM	-
CS		XENON - IF II(69) GT 0	-
CS	II(24)	'Q' FACTOR FOR POWER WEIGHTED REGULAR TIMES	-
CS		ADJOINT FLOX	-
CS	II(25)	REFERENCE TEMPERATURE (DEGREES C) OF THE	-
CS		NEXT-TO-LATEST VERSION 'GROUPS' CROSS SECTION	-
CS		INTERFACE FILE	-
CS	II(26)	REFERENCE TEMPERATURE (DEGREES C) OF THE	-
CS		LATEST VERSION 'GROUPS' CROSS SECTION INTERFACE	-
CS		FILE	-
CS	II(27)	CORRELATION PARAMETER FOR THE ARCTANGENT	-
CS		DEPENDENCE OF CROSS SECTIONS ON ZONE	-
CS		TEMPERATURES (LINEAR CORRELATION IF 0.0)	-
CS	II(29)	FACTOR APPLIED TO SPACE INTERPOLATION SLOPE	-
CS		FOR SPACE-ENERGY REBALANCE. IF ZERO, NO	-
CS		SPACE INTERPOLATION IS DONE	-
CS	II(29)	FACTOR APPLIED TO THE FINAL REBALANCE FACTORS	-
CS		FOR SPACE-ENERGY REBALANCE - DEFAULT 1.0	-
CS	II(30)	XENON DECAY CONSTANT FOR EQUILIBRIUM XENON -	-
CS		IF II(69) GT 0	-
CS	II(31) - II(100)	RESERVED	-
CS			-
CS	II(1)	INDICATOR THAT THE CODE BLOCK HAS INPUT DATA	-
CS		NOT CONTAINED IN THE STANDARD INTERFACE FILES-	-
CS		OTHER THAN THIS BLOCK OF DATA IF .GT.0	-
CS	II(2)	RESTART OPTIONS- RESTART USING DATA FROM AN	-
CS		OLD CASE IF .GT. 0, REQUIRES SPECIAL RESTART	-
CS		DATA FILE	-
CS	II(3)	REFERENCE COUNT ON PROBLEMS (CYCLE NUMBER)	-
CS	II(4)	FORMULATION OPTIONS	-
CS			-
CS		VENTURE, MESH CENTERED FINITE-DIFFERENCE	-
CS		1 - DIFFUSION THEORY (FUNDAMENTAL)	-
CS		2 - SIMPLE P1 APPROXIMATELY (FUNDAMENTAL)	-
CS		-1 - DIFFUSION THEORY SOLUTION FOR THE DOMINANT-	-
CS		ALLOWED FIRST HARMONIC REQUIRING THE	-
CS		FUNDAMENTAL REGULAR AND ADJOINT FLOX FILES-	-
CS		'RTFLOX' AND 'ATFLOX'. THE FIRST ITERATE	-
CS		SOURCE DISTRIBUTION WILL BE SKEWED TO	-
CS		EXCITE ALL SPACIAL FLOX HARMONICS SO	-
CS		THAT THE DOMINANT WILL SURFACE.	-
CS		-2 - SAME AS -1 BUT THE FIRST ITERATE SOURCE	-
CS		WILL NOT BE SKEWED. USUALLY FOR THIS	-
CS		OPTION THE 'RTFLOX' FILE MUST EITHER BE A	-
CS		UNIFORM FLOX DISTRIBUTION (IN WHICH CASE	-
CS		THE SOLUTION MAY OR MAY NOT BE FOR THE	-

(CONT)

DOMINANT HARMONIC) OR AN INITIAL ESTIMATE -
OF THE DOMINANT HARMONIC FLUX DISTRIBUTION -
(FOR EXAMPLE, A COSINE FROM -1 TO +1 -
ALONG A COORDINATE WHILE PERHAPS UNIFORM -
IN OTHER DIRECTIONS) THAT WILL CAUSE THE -
DESIRED HARMONIC TO SURFACE. THIS MAY -
ESPECIALLY BE USEFUL TO ACCELERATE -
CONVERGENCE WHEN TWO OF THE SPATIAL -
HARMONIC EIGENVALUES ARE NEARLY EQUAL. -
SPECIAL DOMINANT HARMONIC SOLUTION (R2) -
ADJUSTING THE TOTAL LOSS TERM TO ACCOUNT -
FOR THE AZIMUTHAL HARMONIC -

```

-1 - DIFFUSION THEORY (FUNDAMENTAL)
-1 - DIFFUSION THEORY (DOMINANT HARMONIC)
-2 - SAME AS -1 BUT THE FIRST ITERATE SOURCE
    WILL NOT BE SKIPPED
  3 - HIGHER ORDER (FUNDAMENTAL) - SEE IX(20)
-3 - HIGHER ORDER (DOMINANT HARMONIC)
-4 - SAME AS -3 BUT THE FIRST ITERATE SOURCE
    WILL NOT BE SKIPPED

```

```

1 - FINITE DIFFERENCE
2 - LINEAR FINITE DIFFERENCE (8, 10 NEIGHBORS)
3 - EXTENDED TAYLOR SERIES (8, 10 NEIGHBORS)
4 - LINEAR FINITE ELEMENT (8, 10 NEIGHBORS)
5 - SIMPLE TAYLOR SERIES (8, 10 NEIGHBORS)
6 - USUAL FINITE DIFFERENCE (4, 6 NEIGHBORS)
7 - COMPROMISE (8, 10 NEIGHBORS)
8 - COMPROMISE (4, 6 NEIGHBORS)
9 - COMPENSATED DIFFERENCE (4, 6 NEIGHBORS)

```

```

0- DETERMINE SOURCE MULTIPLICATION FACTOR
1- SEARCH PROBLEM (FILE OF SEARCH DATA IS
   REQUIRED, SEE OPTION IX(10))
2- FIXED SOURCE PROBLEM
3- ADJOINT PROBLEM ONLY
4- BUCKLING SEARCH
5- PUNCH MODE ALPHA CALCULATION, 1/V SIZE

```

- 0 - NO ADJOINT PROBLEM TO BE DONE
- 1 - EIGENVALUE TYPE PROBLEM
(NORMALLY FOLLOWING A FORWARD PROBLEM)
- 2 - FIXED SOURCE TYPE PROBLEM

RESERVED

TT-35

```

CD      IX(8)      OPTION TO FORCE DATA HANDLING MODE (FOR TESTING) -
CD      -1        OPTION TO TERMINATE IF MEMORY ALLOCATION -
CD                  IS TOO SMALL FOR EFFICIENT EXECUTION (THE -
CD                  SPACE PROBLEM CANNOT BE STORED IN TWO- -
CD                  DIMENSIONS OR ENOUGH PLANES OF DATA CAN -
CD                  NOT BE STORED TO AVOID EXCESS TRANSFER -
CD                  IN THREE-DIMENSIONS) -
CD      0-        AUTOMATED TO MINIMIZE INPUT/OUTPUT -
CD      1-        BASE PROBLEM CORE CONTAINED -
CD      2-        SPACE PROBLEM AT EACH ENERGY CONTAINED -
CD      3-        ONE ROW CONTAINED IN CORE -
CD      4-        ONE OR MORE SPACE PLANES CONTAINED IN CORE -
CD      5-        MULTIPLE ROWS STORED FOR TWO DIMENSIONAL -
CD      6-        MULTI-LEVEL DATA TRANSFER -
CD      IX(9)      OPTIONS ON FLUX INITIALIZATION -
CD      -1        SET ALL FLUX VALUES EQUAL -
CD      0        AUTOMATED PROCEDURE -
CD      1        POINT ENERGY MODEL, COSINE IN SPACE -
CD      2        USE LATEST VERSION OF AVAILABLE SCALAR -
CD                  FLUX FILE -
CD      3        USE NEXT-TO-LATEST VERSION OF AVAILABLE -
CD                  SCALAR FLUX FILE -
CD      IX(10)     IDENTIFIES SEARCH DATA IN SEARCH FILE, IX(5)=1 -
CD      IX(11)     IDENTIFIES SECONDARY SEARCH DATA IN SEARCH FILE -
CD                  TO BE USED IF CONSTRAINTS FOR FIRST SET ARE -
CD                  NOT SATISFIED, AND SECOND SEARCH IS TO BE DONE -
CD      IX(12)     SPECIFIES THAT A 2-D (OR 1-D) PROBLEM IS TO BE -
CD                  SOLVED FOR THIS PLANE (OR ROW) OF A 3-D -
CD                  (OR 2-D) DESCRIPTION IF NON-ZERO -
CD      IX(13)     ORDER IN THE CROSS SECTION FILE OF THE DIRECTION- -
CD                  DEPENDENT TRANSPORT CROSS SECTION TO BE USED -
CD                  FOR THE FIRST COORDINATE DIRECTION (USUALLY 0) -
CD      IX(14)     DITTO, SECOND COORDINATE DIRECTION -
CD      IX(15)     DITTO, THIRD COORDINATE DIRECTION -
CD      IX(16)     INSTRUCTION NORMALLY EXERCISED BY CONTROL MODULE -
CD                  TO INFORM THE NEUTRONICS MODULE TO RECOVER -
CD                  DATA FOR INITIALIZATION FROM FILES RZPLUX AND -
CD                  RTPLUX -
CD      IX(17)     FORCE KEFF. CALC. BY SOURCE RATIO IF GT 0 -
CD      IX(18)     FISSION SOURCE DISTRIBUTION FUNCTION OPTION -
CD      0-        SET VALUES TO BE USED (SAME IN EACH ZONE) -
CD      1-        REGION DEPENDENT VALUES TO BE USED -
CD      IX(19)     FISSION SOURCE DISTRIBUTION NORMALIZATION OPTION -
CD      0-        LEAVE UNNORMALIZED -
CD      1-        NORMALIZE EACH SET TO SUM TO UNITY -
CD      IX(20)     CONSTRAINT ON OUTER ITERATIONS (MAX ALLOWED) -
CD                  (SET BY THE CODE IF NOT SPECIFIED) -
CD                  IF SET = 969 INITIAL DATA PROCESSING IS DONE -
CD                  FOR CHECKING INTERFACE DATA FILES, MEMORY -
CD                  REQUIREMENTS, ETC. AND NO CALCULATIONS -
CD                  ARE DONE - EXCEPT IF IX(9) IS GREATER -
CD                  THAN 1, THE RESIDUES PASS IS MADE TO -
CD                  CALCULATE RESPECTIVE ONLY -

```

(CONT)

CD	IX (21)	INNER ITERATION OPTION	-
CD		0- USE AUTOMATED PROCEDURE (RECOMMENDED)	-
CD		1- REFERENCE NUMBER OF INNERS = 1	-
CD		SET BY THE CODE IF NOT SPECIFIED	-
CD		(IF 1 .LT. 5 .LT. 8, CHEBYSHEV ACCELERATION-	-
CD		WILL NOT BE DONE ON OUTER ITERATIONS	-
CD		AS THE AUTOMATED PROCEDURE)	-
CD	IX (22)	OPTION TO REGULATE OVERRELAXATION FACTORS BY	-
CD		L1 NORM FOR ZERO SOURCE PROBLEM, SPECIAL INNER	-
CD		ITERATIONS ARE DONE (MAKE LARGE TO OVERRIDE	-
CD		THE AUTOMATED PROCEDURE WHICH EMPLOYS THIS)	-
CD	IX (23)	INITIALIZATION OPTIONS FOR PROCEDURES, CHOICE OF	-
CD		OVERRELAXATION COEFFICIENTS AND ITERATIONS	-
CD		-2 DONT DO ONE-DIMENSIONAL CALCULATION	-
CD		FOR INITIALIZATION	-
CD		-1 DONT USE 1-D OVERRELAXATION COEFFICIENTS	-
CD		0- USE AUTOMATED PROCEDURE, SOLVES 1-D PROBLEM-	-
CD		CHEBYSHEV COEFFICIENTS ON OUTER ITERATIONS	-
CD		IF THE NUMBER OF INNERS IS .LT. 5	-
CD		EXCEPT WHEN CHEBYSHEV FLUX ON OUTERS	-
CD		1- SAME AS 0 BUT DO NOT CHEBYSHEV	-
CD		OVERRELAXATION COEFFICIENTS	-
CD		2- FIX THE NUMBER OF INNER ITERATIONS	-
CD		3- FIX NUMBER OF INNERS, NO CHEBYSHEV	-
CD		4- FIXED INNERS AND INITIAL COEFFICIENTS	-
CD		5- FIXED INNERS AND COEFFICIENTS, NO CHEBYSHEV	-
CD		6- SAME AS 4 BUT DONT USE 1-D COEFFICIENTS	-
CD		7- SAME AS 5 BUT DONT USE 1-D COEFFICIENTS	-
CD	IX (24)	INNER ITERATION SWEEP ORDER	-
CD		-1 NORMAL ORDERED	-
CD		0 AUTOMATED (SIGNA-1 IF AVAILABLE, USUALLY)	-
CD		1 SIGNA-1 ORDERED IF AVAILABLE	-
CD	IX (25)	OUTER ITERATION CHEBYSHEV ACCELERATION OPTIONS	-
CD		.LT. 0 START AT THIS ITERATION	-
CD		0- USE AUTOMATED PROCEDURE	-
CD		1- APPLY ONLY AFTER THE FIRST EXTRAPOLATION	-
CD		2- APPLY CONTINUOUSLY FROM THE START	-
CD		3- DONT APPLY THE PROCESS	-
CD		.GT. 100- THE PROCESS IS STARTED AT ITERATION	-
CD		IX (25) -100 USING AN L1 NORM EIGENVALUE	-
CD	IX (26)	ASYMPTOTIC OUTER ITERATION EXTRAPOLATION OPTIONS	-
CD		-1 SINGLE ERROR MODE ONLY	-
CD		0- USE AUTOMATED PROCEDURE	-
CD		1- SINGLE ERROR MODE USING DATA FOR ALTERNATE	-
CD		ITERATIONS	-
CD		2- NOT ALLOWED	-
CD		3- WE ARE TRYING TO FIGURE OUT WHAT THIS DOES	-

(CONT)

CS	IX(27)	FORCED DELAY IN ASYMPTOTIC EXTRAPOLATION	-
CS		N- NOT ALLOWED FOR THIS MANY OUTER ITERATIONS-	-
CS		(IF NEGATIVE, A FORCED PROCEDURE MAY BE	-
CS		EXECUTED EARLIER)	-
C			-
CW		EDITS GENERALLY ARE NOT DONE WHEN FLAG IS ZERO	-
C			-
CS	IX(28)	OPTION FOR CONDENSED EDIT (TERMINAL) IF .GT. 1	-
CS	IX(29)	OPTION TO EDIT THE PRINCIPAL MACROSCOPIC	-
CS		CROSS SECTIONS BY ZONE	-
CS	IX(30)	OPTION TO EDIT THE MACROSCOPIC SCATTERING	-
CS		CROSS SECTIONS BY ZONE	-
CS	IX(31)	OPTIONS ON ITERATION DATA EDITS	-
CS		0- NO EDITS DURING ITERATION	-
CS		1- OR 1- PRIMARY OUTER ITERATION DATA ONLY	-
CS		2- GETS DETAILS EDITED FOR TESTING	-
CS		3- REQUESTS EXTENDED EDIT FOR DEBUGGING	-
CS	IX(32)	OPTION TO EDIT OVERALL NEUTRON BALANCE BY GROUP	-
CS	IX(33)	OPTION TO EDIT NEUTRON BALANCE BY ZONE	-
CS	IX(34)	RESERVED	-
CS	IX(35)	OPTION TO EDIT SCALAR NEUTRON FLUX BY POINT	-
CS	IX(36)	RESERVED	-
CS	IX(37)	OPTION TO EDIT ZONE-AVERAGE FLUX BY GROUP	-
CS		IF .GT. 1, ALSO EDIT THE ZONE, GROUP ADJOINT FLUX-	-
CS	IX(38)	OPTION TO EDIT POWER DENSITY MAP BY INTERVAL	-
CS	IX(39)	OPTION TO EDIT POWER DENSITY TRAVERSES THRU PEAK-	-
CS	IX(40)	OPTION TO EDIT NEUTRON DENSITY MAP (1/V FLUX	-
CS		WEIGHTING)	-
CS	IX(41)	OPTION TO EDIT NEUTRON DENSITY TRAVERSES	-
CS	IX(42)	OPTION TO EDIT SCALAR ADJOINT FLUX	-
CS	IX(43)	MAXIMUM ZONE NUMBER FOR WHICH IX(21) AND IX(22)	-
CS		ARE TO BE APPLIED TO THE ZONE AND GROUP	-
CS		DIFFUSION COEFFICIENTS IF NOT ZERO	-
CS	IX(44)	OPTION TO EDIT ATOMIC DENSITIES WHEN SEARCHING	-
CS		0- NO EDIT	-
CS		1- MINIMUM EDIT AT END	-
CS		2- MAXIMUM EDIT DURING CALCULATION	-
CS	IX(45)	PERTURBATION OPTIONS - IF NEGATIVE, FILES BFLUX-	-
CS		AND APLUX ARE SUPPLIED AND NO NEUTRONICS	-
CS		CALCULATION IS DONE - OTHERWISE THE REGULAR	-
CS		AND/OR ADJOINT SOLUTION IS OBTAINED AS	-
CS		SPECIFIED ABOVE AND EITHER FLUX FILE NOT	-
CS		GENERATED MUST BE SUPPLIED	-
CS		0- NO PERTURBATION CALCULATION	-
CS		1- CALCULATE AND EDIT BASIC REGULAR-ADJOINT	-
CS		FLUX INTEGRALS EXCEPT TRANSPORT	-
CS		2- ALSO CALCULATE AND EDIT TRANSPORT INTEGRALS-	-
CS		(REQUIRED FOR COMPLETE PERTURBATION EFFECT)	-
CS		3- ALSO EDIT MACROSCOPIC ABSORPTION CROSS	-
CS		SECTION SPACE POINT IMPORTANCE MAP	-
CS		4- ALSO EDIT MACROSCOPIC PRODUCTION CROSS	-
CS		SECTION SPACE POINT IMPORTANCE MAP	-
CS		PLUS ABS-PROD MAP	-
CS		5- ALSO EDIT 1/V SPACE POINT IMPORTANCE MAP	-

(CONT)

CD	IX(46)	EDIT RESULTS FOR A 100 PERCENT CHANGE IN MACRO	-
CD		CROSS SECTIONS, ONLY IF IX(45).NE.0	-
CD	IX(47)	OPTION TO WRITE POINT FLUX VALUES FOR EXPOSURE	-
CD		(EXERCISED ONLY IF IX(53) .GT. 0)	-
CD		.GT. 0 WRITE DATA FOR POINTS IN THIS ZONE	-
CD		-1 WRITE ONLY THE SPECTRUM FOR THE POINT WHERE	-
CD		THE POWER DENSITY IS A MAXIMUM INITIALLY	-
CD		-2 WRITE DATA FOR THE POINTS IN THE ZONE WHERE	-
CD		THE POWER DENSITY IS A MAXIMUM INITIALLY	-
CD		-3 WRITE ONLY THE SPECTRUM FOR THE POINT WHERE	-
CD		THE FIRST GROUP FLUX IS A MAXIMUM INITIALLY	-
CD		-4 WRITE DATA FOR THE POINTS IN THE ZONE WHERE	-
CD		THE FIRST GROUP FLUX IS A MAXIMUM INITIALLY	-
CD		.LT.-4 WRITE SPECTRUM FOR THIS MESH POINT	-
CD	IX(48)	ANOTHER ZONE NUMBER FOR WHICH THE POINT FLUX	-
CD		VALUES ARE TO BE WRITTEN FOR EXPOSURE IF .GT.	-
CD	IX(49)	OPTION TO EDIT THE DIRECT CONTRIBUTION TO CHANGE-	-
CD		IN CONVERSION RATIO FROM UNIT CHANGE IN FERTILE	-
CD		CAPTURE AND FISSION ABSORPTION (MACROSCOPIC)	-
CD	IX(50)	OPTION TO WRITE SCALAR ADJOINT FLUX FILE AS	-
CD		THE PRODUCT OF THE REGULAR AND ADJOINT FLUX	-
CD		0- NO	-
CD		1- REWRITE THE LATEST VERSION OF AN OLD FILE-	-
CD		(IF THERE IS NONE, WRITE A NEW ONE)	-
CD		2- WRITE NEW FILE	-
C			-
CN		OPTIONS ABOVE ARE TYPICAL FOR EACH FILE COVERED BELOW	-
C			-
CD	IX(51)	OPTION TO WRITE THE POINT SCALAR FLUX FILE	-
CD	IX(52)	OPTION TO WRITE THE POINT FISSION SOURCE FILE	-
CD	IX(53)	OPTION TO WRITE ZONE-AVERAGE SCALAR FLUX FILE	-
CD	IX(54)	OPTION TO WRITE POINT POWER DENSITY FILE	-
CD	IX(55)	WRITE THE CONVERSION RATIO ADJOINT IMPORTANCE	-
CD		FIXED SOURCE FILE (ALWAYS ADDS A FILE OR TWO)	-
CD		.GT.0- WRITE COMBINED FILE (HAS NEGATIVE DATA)	-
CD		.LT.0- WRITE TWO FILES, ALL POSITIVE	-
CD	IX(56)	OPTION TO WRITE THE ZONE POWER DENSITY FILE	-
CD	IX(57)	OPTION TO WRITE THE ADJOINT ZONE AVERAGE FLUX	-
CD		FILE A2FLUX	-
CD	IX(58)	OPTION TO WRITE SCALAR ADJOINT FLUX FILE	-
CD		APPLICABLE ONLY IF AN ADJOINT PROBLEM WAS DONE-	-
CD	IX(59)	OPTION TO WRITE PERTURBATION INTEGRALS ON FILE	-
CD		PERTURB. IX(45) MUST BE NON-ZERO. TRANSPORT	-
CD		INTEGRALS ARE INCLUDED IF ABS(IX(45)) GT 2.	-
CD	IX(60)	OPTION TO WRITE SPECIAL FORMATTED DATA FILE	-
CD		(LOGICAL 4) AT THE END OF A CASE - SEE SECTION-	-
CD		OF THE VENTURE REPORT	-
CD	IX(61)	A PLANE NUMBER AT WHICH ZONE AND GROUP BUCKLINGS-	-
CD		ARE TO BE CALCULATED	-
CD	IX(62)	A SECOND PLANE NUMBER FOR THE BUCKLING CALCULATI-	-

(CONT)

CD	IX(63)	OPTION TO WRITE A POINTWISE FIXED SOURCE FILE	-
CD		AS (DB*=2) TIMES FLUX	-
CD	IX(64)	WRITE A POINT POWER DENSITY ADJOINT IMPORTANCE	-
CD		FIXED SOURCE FILE (ALWAYS ADDS A FILE)	-
CD		1 POINT WHERE POWER DENSITY IS MAX	-
CD		-M POINT IN ZONE ABS(M) WHERE POWER DENSITY	-
CD		IS MAX	-
CD		2 POINT GIVEN BY IX(65-67) BELOW	-
CD	IX(65)	COLUMN NUMBER FOR IX(64)=2	-
CD	IX(66)	ROW NUMBER FOR IX(64)=2	-
CD	IX(67)	PLANE NUMBER FOR IX(64)=2	-
CD	IX(68)	RESERVED	-
CD	IX(69)	IF GT 0 EQUILIBRIUM XENON WILL BE ACCOUNTED FOR	-
CD		AND THIS IS THE ORDER NUMBER OF XENON IN THE	-
CD		NUCLIDE LIST (SET 1) IN SECTION 013 DVENTH	-
CD	IX(70)	FORCE DATA TRANSFER IN INITIALIZATION (TO TEST PROCEDURES)	-
CD	IX(71)	RESERVED	-
CD	IX(72)	RESERVED	-
CD	IX(73)	OVERRIDE DEFAULT OF FILES TO MEMORY (TO TEST PROCEDURES)	-
CD	IX(74)	SPACE-ENERGY REBALANCE WILL BE DONE OCCASIONALLY IF GT 0	-
CD	IX(75)	THE NUMBER OF BOLCKS ALONG ROWS (LEFT-RIGHT)	-
CD		FOR REBALANCE - IX(74) .GT. 0	-
CD	IX(76)	THE NUMBER OF BOLCKS ALONG COLS (TOP-BOTTOM)	-
CD		FOR REBALANCE - IX(74) .GT. 0	-
CD	IX(77)	THE NUMBER OF BOLCKS ALONG PLANES (FORE-AFT)	-
CD		FOR REBALANCE - IX(74) .GT. 0	-
CD	IX(78)-		-
CD	IX(79)	RESERVED	-
CD	IX(80)	OPTION TO ACCOUNT FOR THE DEPENDENCE OF THE CROSS SECTIONS	-
CD		ON THE LOCAL TEMPERATURE, REQUIRES TWO 'GRUPIS' FILES,	-
CD		A 'ZNTEMP' FILE, AND REFERENCE TEMPERATURES [SEE XX(25),	-
CD		XX(26), AND XX(27)]	-
CD		0 - NO	-
CD		1 - YES	-
CD	IX(81)	EDIT ZONE ASSIGNMENTS TO MESH INTERVALS	-
CD		0 - NO	-
CD		1 - YES	-
CD	IX(82)-		-
CD	IX(100)	RESERVED	-
C			-

C-----

SPECIFICATIONS FOR DVRINS RECORD IN INTERFACE FILE CONTROL

C	-----		
CR		MODULE DRIVING INFORMATION	-
C			-
CL	DVRINS, (IX(I),I=1,100), (IX(I),I=1,100)		-
C			-
CV	101*HULT + 100		-
C			-
CD	DVRINS	MODULE DRIVING INFORMATION IDENTIFIER (6HDVRINS)	-
C			-
CD	IX(1-100)	RESERVED	-
C			-
CD	IX(1)	PRIMARY MEMORY ALLOCATION, WORDS	-
C			-
CD	IX(2)	RESERVED	-
C			-
CD	IX(3)	RESERVED	-
C			-
CD	IX(4)	MAXIMUM BLOCK SIZE FOR DIRECT ACCESS DATA FILES, WORDS, BEST VALUE DEPENDS ON SEVERAL THINGS INCLUDING DISK TRAIL LENGTH, OVERRIDE THE AUTOMATED PROCEDURE ASSIGNMENT IF NON-ZERO	-
C			-
CD	IX(5)	TOTAL PROCESSOR TIME ALLOWED FOR THE RUN, MINUTES	-
C			-
CD	IX(6-10)	RESERVED	-
C			-
CD	IX(11)	STAND-ALONE FLAG - 0 - MODULES ARE ACCESSED IN A TRUE MODULAR SENSE- 1 - MODULES ARE ACCESSED AS IF EACH IS A STAND-ALONE CODE (NOT RECOMMENDED)	-
C			-
CD	IX(12-100)	RESERVED	-
C			-
C	-----		-

(CONT)

TABLE 04-1 INTERFACE FILE SPECIFICATIONS
SPECIFICATIONS FOR EXPINS RECORD IN INTERFACE FILE CONTROL

C	-----	
CH	EXPOSURE MODULE INSTRUCTIONS	
C		
CL	EXPINS, (XX(I), I=1, 100), (IX(I), I=1, 100)	
C		
CH	101*MULT + 100	
C		
CD	EXPINS EXPOSURE MODULE DATA IDENTIFIER (6HEXPINS)	
C		
CH*	OPTION NOT IMPLEMENTED	
CH**	OPTION NOT RECOMMENDED	
C		
CD	XX (1) EXPOSURE TIME STEP (DAYS)	
CD**	(A NEGATIVE TIME IS USED FOR SPECIAL SITUATIONS)	
C		
CD	XX (2) SHUTDOWN TIME STEP AFTER EXPOSURE (DAYS AT ZERO	
CD	FLUX)	
C		
CD	XX (3) THE RATIO OF EACH SHUTDOWN SUBSTEP TIME INTERVAL	
CD	TO THAT OF THE PREVIOUS SUBSTEP (APPLICABLE	
CD	ONLY IF IX (7) .GT. 1)	
CD	(DEFAULT TO 1.0)	
C		
CD	XX (4) RESERVED	
C		
CD	XX (5) RESERVED	
C		
CD	XX (6) RELATIVE POWER LEVEL (ALL REACTION RATES ARE	
CD	MULTIPLIED BY THIS FACTOR IF NONZERO - PROPER	
CD	NORMALIZATION OF THE FLUX LEVEL BY THE NEUTRONICS	
CD	CODE TO EFFECT SOME POWER LEVEL IS PRESUMED)	
C		
CD	XX (7) RESERVED	
C		
CD	XX (8) RESERVED	
C		
CD	XX (9) RESERVED	
C		
CD	XX (10) WEIGHTING FACTOR FOR USE WITH TWO FLUX INTERFACE	
CD	FILES (IF IX (13) .EQ. -2)	
C		
CD	PHI(USED) = PHI(LV) + XX(10)*(PHI(NTLV) - PHI(LV))	
CD	WHERE PHI(LV) IS LATEST VERSION (IN TIME) FLUX	
CD	WHERE PHI(NTLV) IS NEXT-TO-LATEST VERSION (IN	
CD	TIME) FLUX	
CD	(DEFAULT TO 0.5)	
C		
CD	XX (11) FLUENCE LOWER BOUND FOR FIRST ENERGY RANGE (EV)	
C		
CD	XX (12) FLUENCE LOWER BOUND FOR SECOND ENERGY RANGE (EV)	

(CONT)

CD	XX(13)	CONVERGENCE LEVEL FOR MATRIX EXPONENTIAL METHOD (DEFAULT TO 1.0E-9)	-
CD			-
CD	XX(14)	LIMITING VALUE OF DIAGONAL TERM FOR MATRIX EXPONENTIAL METHOD (EACH SUBSTEP IS SUBDIVIDED INTO AS MANY TIME INCREMENTS AS NEEDED TO REDUCE THE LARGEST DIAGONAL TERM TO THIS LEVEL) (DEFAULT TO 12.0)	-
CD			-
CD	XX(15)	MATRIX EXPONENTIAL TRANSFORM, FRACTION OF LARGEST DIAGONAL TERM (DEFAULT TO 0.5)	-
CD			-
CD	XX(16)	MINIMUM NUCLIDE DENSITY ALLOWED (DEFAULT TO 1.0E-50)	-
CD			-
CD	XX(17)	MAGNITUDE OF DIAGONAL TERM USED AS CRITERIA FOR APPLYING THE EQUILIBRIUM APPROXIMATION TO A NUCLIDE WITH THE MATRIX EXPONENTIAL METHOD (DEFAULT TO 10.0*XX(14))	-
CD			-
CD	XX(18)	WEIGHTING FACTOR FOR EXPOSURE NUCLIDE DENSITIES WRITTEN ON INTERFACE FILE (IF XX(31) .NE. 0) 'ZEATON' FOR ZONE CALCULATION 'PTATON' FOR POINT CALCULATION $N(WRITTEN) = N(Z) + XX(18) * (N(S) - N(Z))$ WHERE N(Z) ARE DENSITIES AT END OF EXPOSURE WHERE N(S) ARE DENSITIES AT START OF EXPOSURE (DEFAULT TO 0.5)	-
CD			-
CD	XX(19)	AVERAGE GENERATION RATE WEIGHTING FACTOR FOR SOURCE TERM PRECURSOR DENSITY IS $XX(19) * N(T) + (1.0 - XX(19)) * N(T+DT)$ (DEFAULT TO 0.5)	-
CD			-
CD	XX(20)	CONVERGENCE CRITERIA ON POWER LEVEL FOR CONTINUOUS FUELING MODEL TO DISCONTINUE POWER LEVEL INITIALIZATION PASSES (APPLICABLE IF IX(51) .GT. 0 AND/OR IX(52) .GT. 0 AND IX(61) .GT. 1) (DEFAULT TO 0.005)	-
CD			-
CD	XX(21)	RESERVED	-
CD			-
CD	XX(22)	RESERVED	-
CD			-
CD	XX(23)	RESERVED	-

(CONT)

IX (24)	RESERVED
IX (25)	REFERENCE TEMPERATURE (DEGREES C) OF THE FIRST-TO-LATEST VERSION 'GROUPS' CROSS SECTION INTERFACE FILE
IX (26)	REFERENCE TEMPERATURE (DEGREES C) OF THE LATEST VERSION 'GROUPS' CROSS SECTION INTERFACE FILE
IX (27)	CORRELATION PARAMETER FOR THE RECTANGENT DEPENDENCE OF CROSS SECTIONS ON ZONE TEMPERATURES (LINEAR CORRELATION IF 0.0)
IX (28)	RESERVED
IX (29)	RESERVED
IX (30)	RESERVED
IX (31-100)	CORE RESIDENCE TIME (DAYS) FOR EACH ZONE PATH FOLLOWED BY THE CORE RESIDENCE TIME (DAYS) FOR EACH SUBZONE PATH (IF ANY) - SEE IX (51) (DEFAULT TO IX (1))

USUAL VALUES OF SOME OF THE PARAMETERS ARE SHOWN HERE IN ()

IX (1)	RESERVED
IX (2)	CONDENSED EDIT OPTION 0- YES 1- NO
IX (3)	DEBUG EDIT OPTION (0) 0- NO SPECIAL EDITS 1- CROSS REFERENCE TABLES, EXPOSURE DATA, CHECK AND EDIT DATA FROM 'EXPOSE' INTERFACE FILE, AND EDIT INTERFACE FILE PARAMETERS 2- HIGHER LEVEL DATA EDIT 3- PLUS STARTING NUCLIDE DENSITIES 4- PLUS INTERMEDIATE LEVEL DATA 5- PLUS STARTING REACTION RATES 6- PLUS ALL EDIT OPTIONS ARE TURNED ON 7- PLUS MATRIX EXPONENTIAL AND AVERAGE GENERATION RATE DEBUG EDITS 8- PLUS ADDITIONAL MATRIX EXPONENTIAL DEBUG EDITS

NOTE- USE OF 6, 7, OR 8 WILL PRODUCE REAMS OF PAPER

(CONT)

CD	IX (4)	RESERVED
C		
CD	IX (5)	OPTION ON BASIC CHAIN EQUATION SOLUTION METHOD
CD		(CONSISTENT CHAIN DATA MUST BE PRESENT ON
CD		INTERFACE FILE 'EXPOSE')
CD		0- MATRIX EXPONENTIAL
CD		1- EXPLICIT CHAIN
CD		2- AVERAGE GENERATION RATE
C		
CD		(IF IX(5) .EQ. 0 AND WHATIE('EXPOSE') .EQ. 0 AND
CD		LEPICH('EXPOSE') .GT. 0, DEFAULT TO 1)
C		
CD	IX (6)	NUMBER OF SUBSTEP EXPOSURE INTERVALS
CD		IX(6) .GT. 1 IS NORMALLY USED ONLY WHEN THE FLUX
CD		LEVEL IS TO BE ADJUSTED (SEE IX(12))
CD		(DEFAULT TO 1 IF IX(1) .NE. 0.0)
C		
CD		EXPOSURE NOT CALCULATED IF IX(1) .EQ. 0.0
C		
CD		FOR CONTINUOUS FUELING MODEL SET IX(6) .EQ. 1
C		
CD	IX (7)	NUMBER OF SUBSTEP SHUTDOWN INTERVALS
CD		IX(7) .GT. 1 IS NORMALLY USED ONLY TO PRODUCE
CD		EDITS AT POINTS ALONG SHUTDOWN STEP
CD		(DEFAULT TO 1 IF IX(2) .GT. 0.0)
C		
CD		SHUTDOWNS NOT CALCULATED IF IX(2) .LE. 0.0
C		
CD	IX (8)	OPTION ON VERSION OF NUCLIDE DENSITIES AT START
CD		'ZNATDN' FOR ZONE CALCULATION
CD		'PTATDN' FOR POINT CALCULATION (IF NOT AVAILABLE
CD		DENSITIES WILL BE EXTRACTED FROM INITIAL ZONE
CD		DENSITIES)
CD		-1- USE VERSION WITH THE SAME TIME AS THE ZONE
CD		FLUX FILE
CD		0- USE LATEST VERSION (USUAL)
CD		1- USE NEXT-TO-LATEST VERSION IF IT EXISTS
C		
CD	IX (9)	OPTION TO ACCOUNT FOR THE DEPENDENCE OF THE
CD		CROSS SECTIONS ON THE LOCAL TEMPERATURE, REQUIRES
CD		TWO 'GROUPS' FILES, A 'ZNTEMP' FILE, AND REFERENCE
CD		TEMPERATURES (SEE IX(25), IX(26), AND IX(27))
CD		0- NO
CD		1- YES
C		
CD	IX (10)	RESERVED
C		
CD	IX (11)	NUMBER OF SUBDIVISIONS OF EACH SUBSTEP FOR THE
CD		AVERAGE GENERATION RATE METHOD (IF ZERO, THE
CD		CHOICE IS AUTOMATED)
C		

(CONT)

IX (21) SPECIAL NUCLEIDE DENSITY EDIT OPTION FOR A SINGLE ZONE PROBLEM
-1- COLUMN EDIT IN OPE15.6 FORMAT
0- NORMAL EDIT
1- COLUMN EDIT IN 1PE15.6 FORMAT

IX (22) RESERVED

IX (23) RESERVED

IX (24) RESERVED

IX (25) OPTION ON WRITING INTERFACE FILE 'EXPORT'
(FLUENCE AND REACTION RATE TYPE DATA)
0- DO NOT WRITE
1- YES - SAVE LATEST AND NEXT-TO-LATEST DATA
2- YES - SAVE ALL DATA
3- YES - SAVE LATEST DATA ONLY
4- YES - START OVER AGAIN

IF .GT. 0, NO EDIT
IF .LT. 0, EDITS OF CUMULATIVE DATA BY ZONE AND SUBZONE

OPTIONS IX(26), IX(27), IX(11), AND IX(12) APPLY ONLY WHEN 'EXPORT' FILE IS INITIALLY WRITTEN
IF THE FILE EXISTS THE OPTIONS SPECIFIED OF THE FILE ARE USED

IX (26) FLUENCE DATA TO BE SAVED ON 'EXPORT' FILE
0- NONE
1- TOTAL FLUENCE (AND FIRST AND SECOND FLUENCE RANGES IF XI(11) AND XI(12) ARE PROPERLY DEFINED)

IX (27) REACTION RATE TYPE DATA TO BE SAVED ON 'EXPORT' FILE
0- NONE
1- FISSIONS AND EXPOSURE
2- PLUS ENERGY
3- PLUS UNDEFINED

IX (28) OPTION TO EDIT EXPOSURE STEP AVERAGE ZONE(SUBZONE) POWER DENSITIES
0- NO
1- YES

03	IX(29)	OPTION TO WRITE INTERFACE FILE 'INPCWD' WITH EXPOSURE STEP AVERAGE ZONE(SUBZONE) POWER DENSITIES 0- DO NOT WRITE 1- REPLACE THE LATEST VERSION OF AN OLD FILE, IF NONE EXISTS WRITE NEW FILE 2- WRITE NEW FILE	- - - - - - -
03	IX(30)	OPTION ON NUCLIDE DENSITY FILE WRITING 'ZNATDN' FOR ZONE CALCULATION 'PTATDN' FOR POINT CALCULATION 0- WRITE OVER LATEST EXISTING FILE WITH END OF EXPOSURE DENSITIES 1- WRITE NEW FILE WITH END OF EXPOSURE DENSITIES 2- WRITE OVER LATEST EXISTING FILE WITH END OF SHUTDOWN DENSITIES 3- WRITE NEW FILE WITH END OF SHUTDOWN DENSITIES 4- WRITE OVER LATEST EXISTING FILE WITH END OF EXPOSURE DENSITIES AND WRITE NEW FILE WITH END OF SHUTDOWN DENSITIES 5- WRITE NEW FILE WITH END OF EXPOSURE DENSITIES AND WRITE NEW FILE WITH END OF SHUTDOWN DENSITIES	- - - - - - - - - - - - -
03	IX(31)	OPTION TO WRITE WEIGHTED AVERAGE EXPOSURE DENSITIES (SEE IX(18)) 'ZBATCH' FOR ZONE CALCULATION 'PTATCH' FOR POINT CALCULATION -1- REPORT NORMAL END OF EXPOSURE TIME 0- NO 1- REPORT WEIGHTED TIME	- - - - - - -
03	IX(32)	OPTION TO CHECK AND EDIT DATA FROM INTERFACE FILE 'EXPOSE' 0- NO 1- YES	- - - -
03	IX(33)	OPTION TO EDIT INITIAL ZONE(SUBZONE) SPECIFIC REACTION RATES 0- NO 1- YES	- - - -
03	IX(34)	OPTION TO EDIT INITIAL ZONE(SUBZONE) SPECIFIC REACTION RATE FOR FISSION IN YIELD DATA ENERGY RANGES 0- NO 1- YES	- - - - -
03	IX(35)	OPTION TO EDIT INITIAL ZONE(SUBZONE) NUCLIDE DENSITIES 0- NO 1- YES	- - - -

(CONT)

CD	IX (36)	OPTION TO FORCE CALCULATION INTO I/O MODE (NORMALLY
CD		DETERMINED BY CODE BASED ON MEMORY AVAILABLE)
CD		0- NO (AUTOMATED)
CD		1- YES
C		
CD	IX (37)	OPTION TO INCREASE STORAGE FOR COUPLING TERMS
CD		FOR MATRIX EXPONENTIAL METHOD (IN THE EVENT
CD		STOP 4321 OCCURS)
CD		(DEFAULT - NUMBER OF NUCLIDES IN EXPOSURE DATA)
C		
CD==	IX (38)	OPTION TO SOLVE THE TRANSPOSE OF THE MATRIX FOR
CD==		THE MATRIX EXPONENTIAL METHOD (THIS IS A SPECIAL
CD==		FEATURE - NOT APPLICABLE TO A REACTOR CALCULATION)
CD==		0- NO
CD==		1- YES
C		
CD	IX (39)	MATRIX EXPONENTIAL EQUILIBRIUM OPTION
CD		0- DEFAULT, SAME AS 1
CD		1- APPLY EQUILIBRIUM ASSUMPTION TO HIGH LOSS
CD		NUCLIDES
CD		2- DO NOT APPLY EQUILIBRIUM ASSUMPTION (REQUIRED
CD		FOR HIGH ACCURACY (BENCHMARKING) BUT IS
CD		EXPENSIVE IN TERMS OF RUNNING TIME)
C		
CD	IX (40)	MATRIX EXPONENTIAL FORMULATION OPTION
CD		0- DEFAULT, SAME AS 4
CD		1- NO TRANSFORMATION, ONE TERM
CD		2- TRANSFORMATION, ONE TERM
CD		3- NO TRANSFORMATION, TWO TERM
CD		4- TRANSFORMATION, TWO TERM
C		
CD	IX (41)	MATRIX EXPONENTIAL REFERENCE NUMBER OF TERMS
CD		IN EXPANSION
CD		(DEFAULT TO 60)
C		
CD	IX (42)	NUMBER OF SUBDIVISIONS OF EACH SUBSTEP FOR THE
CD		MATRIX EXPONENTIAL METHOD (IF ZERO, THE CHOICE
CD		IS AUTOMATED)
C		
CD	IX (43)	UPPER BOUND ON NUMBER OF SUBDIVISIONS OF EACH
CD		SUBSTEP FOR THE MATRIX EXPONENTIAL METHOD.
CD		(IF IX (39) .EQ. 2 AND THE NUMBER OF SUBDIVISIONS
C		COMPUTED BY THE CODE EXCEEDS IX (43) THEN THE
CD		EQUILIBRIUM ASSUMPTION WILL BE USED)
CD		(DEFAULT TO 10000)
C		
CD	IX (44)	RESERVED
C		

(CONT)

CD	IX(45)	EXPLICIT CHAIN MISSING NUCLIDE OPTION (0)	-
CD		0- TREAT SUBCHAINS	-
CD		1- TREAT FIRST SUBCHAIN ONLY	-
CD		2- SKIP CHAIN	-
C			-
CD	IX(46)	RESERVED	-
C			-
CD	IX(47)	RESERVED	-
C			-
CD	IX(48)	RESERVED	-
C			-
CD	IX(49)	OPTION TO ALLOW EXPOSURE WITH ZERO FLUX AND/OR	-
CD		ZERO ZONE VOLUME	-
CD		0- DO NOT TREAT THE ZONE (SUBZONE)	-
CD		1- ALLOW (FOR TREATING OUT-OF-CORE DECAY IN	-
CD		FALSE ZONES (SUBZONES))	-
C			-
CD	IX(50)	RESERVED	-
C			-
CD	IX(51)	FALSE ZONE NUMBER CONTAINING FEED MATERIAL	-
CD		COMPOSITION FOR ZONE PATHS (OR THE FIRST IN A	-
CD		SEQUENCE OF FALSE ZONE NUMBERS IF IX(57) .EQ. 1)	-
C			-
CH		IF IX(51) .GT. 0 AND/OR IX(52) .GT. 0 THE STEADY STATE,	-
CH		CONTINUOUS FUELING MODEL IS TO BE APPLIED.	-
C			-
CH		THIS ZONE IS THE FEED BOX (OR THE FIRST OF A SET OF BOXES)	-
CH		WHERE FEED MATERIAL FOR EACH FLOW PATH ORIGINATES.	-
CH		THESE ARE FALSE ZONES WHICH MUST BE WITHIN THE DATA	-
CH		DESCRIPTION OF THE PROBLEM, THAT ARE NOT ASSIGNED	-
CH		TO GEOMETRIC LOCATIONS FOR THE NEUTRONICS CALCULATION (THE	-
CH		FLUX WILL NOT BE CALCULATED), AND HAVE ASSIGNED NUMBERS	-
CH		LESS THAN THE MAXIMUM ZONE NUMBER IN THE PROBLEM IF	-
CH		THE 'DOWITE' SPECIAL INPUT PROCESSOR IS USED.	-
CH		THE NUCLIDE DENSITIES ALONG A FLOW PATH CALCULATED IN	-
CH		THIS MODEL DEPEND ONLY ON THE FEED MATERIAL, THE	-
CH		NEUTRON FLUX, AND THE RESIDENCE TIME, SO ALL MATERIALS	-
CH		IN THESE ZONES INCLUDING STRUCTURE, MODERATOR, ETC.	-
CH		MUST BE GIVEN IN THE FEED BOX ZONE (ZONES). IF THE	-
CH		DENSITIES OF THE NUCLIDES REPRESENTING STRUCTURAL	-
CH		MATERIAL WERE NOT SPECIFIED FOR THE FEED BOX (OR BOXES),	-
CH		NONE WOULD APPEAR IN THE REACTOR AFTER THE EXPOSURE	-
CH		CALCULATION EVEN THOUGH VALUES WERE ASSIGNED INITIALLY.	-
CH		FOR SOME SIMPLE SITUATIONS IT IS POSSIBLE TO SEPARATE	-
CH		OUT SELECTED MATERIALS USING THE SUBZONE REPRESENTATION	-
CH		(THOSE MATERIALS ACCOUNTED FOR WOULD NOT BE ASSIGNED	-
CH		CONCENTRATIONS IN THE FEED BOX(ES)). IT IS DESIRABLE	-
CH		TO CARRY AT LEAST ONE NON-DEPLETING NUCLIDE CONCENTRATION	-
CH		ALONG THE PATHS TO PROVIDE A MASS BALANCE CHECK.	-
CH		MATERIAL ENTERING A ZONE IS THAT LEAVING THE PREVIOUS	-
CH		ZONE ALONG A PATH, WHILE THE AVERAGE BETWEEN ENTERING	-
CH		AND LEAVING NUCLIDE DENSITIES IN EACH ZONE ARE WRITTEN	-
CH		IN THE NEW NUCLIDE DENSITY FILE 'ZNATDN' FOR USE BY	-
CH		THE NEUTRONICS CODE TO ESTIMATE THE FLUX DISTRIBUTION.	-

(CONT)

THE SPECIAL INPUT DATA FOR THIS MODEL ARE THE RESIDENCE
 TIMES ALONG FLOW PATHS (IX(31) UP TO IX(100)),
 IX(20), IX(49), IX(51), IX(52), IX(53), IX(54), IX(55),
 IX(56), IX(57), IX(58), IX(59), IX(60), IX(61),
 AND IX(62). THE EXPOSURE TIME IX(1) MUST BE
 SPECIFIED - IT WILL BE USED FOR RECORD KEEPING AND IT
 WILL BE USED FOR EXPOSURE OF ANY ZONES NOT IN THE FLOW
 PATHS, EXCLUDING THE FEED BOX ZONE(S), AS MIGHT BE USED
 TO REPRESENT A FIXED BLANKET, AND THE FINAL NUCLIDE
 DENSITIES IN THESE ZONES WILL BE PLACED IN THE NEW
 NUCLIDE DENSITY FILE (WHICH REQUIRES ACTION TO BE TAKEN
 TO PREVENT CONTINUING BUILDUP FROM EXPOSURE IN AN
 ITERATION PROCESS.
 QUITE GENERALLY AN ITERATION PROCESS IS NECESSARY
 (NEUTRONICS, EXPOSURE) TO ESTABLISH A NEUTRON FLUX
 DISTRIBUTION WHICH DEPENDS ON THE NUCLIDE DENSITIES
 AFTER EXPOSURE, THE COMPOSITION IN THE FEED BOX(ES) MUST
 BE ALTERED TO EFFECT A CRITICAL STATE, AND THE ITERATIVE
 PROCESS MUST CONVERGE TO A SOLUTION FOR RELIABLE
 ANALYSIS. IF THE FEED BOX COMPOSITIONS ARE NOT ALTERED,
 A PSEUDO STEADY STATE CONDITION RESULTS FOR A REACTOR
 WHICH IS NOT JUST CRITICAL. A CAPABILITY EXISTS TO
 EFFECT THE CRITICAL STATE BY APPLYING THE CRITICALITY
 SEARCH OPTION WHEN THE NEUTRONICS PROBLEM IS SOLVED.
 MATERIALS IN THE REACTOR MUST BE CHANGED AS WELL AS THE
 CONTENTS OF THE FEED BOXES. AFTER EXPOSURE THE REACTOR
 CONTENTS DEPEND ON THE FEED, SO THE FEED MUST BE
 DETERMINED (CHANGING ONLY THE FEED DURING A
 NEUTRONICS CALCULATION WILL NOT CHANGE THE CURRENT
 ESTIMATE OF THE REACTOR CONTENTS SINCE THE FEED BOX
 LIES OUTSIDE OF THE REACTOR AND THE NEUTRONICS SEARCH
 PROBLEM COULD NOT CONVERGE).
 MORE THAN ONE PASS MAY BE MADE THROUGH THE REACTOR.
 HOLD-UP OUT-OF-CORE MAY BE ALLOWED WITH FALSE ZONES
 NOT IN THE ACTUAL GEOMETRY (IX(49) MUST BE SET .EQ. 1).
 NOTE THAT THE ASSIGNMENT OF ZONES AND SUBZONES TO THE
 GEOMETRY MUST START WITH 1 FOR LOCATIONS RECEIVING
 FEED AND INDEX UP ALONG FLOW PATHS.
 ONLY ONE EXPOSURE SUBSTEP MAY BE REQUESTED FOR THIS
 OPTION.

CONSTRAINTS ON INPUT:

IX(31) .LE. NUMBER OF ZONES
 IX(51)+IX(53)-1 .LE. NUMBER OF ZONES IF IX(57) .EQ. 1-
 IX(52) .LE. NUMBER OF ZONES
 IX(52)+IX(54)-1 .LE. NUMBER OF ZONES IF IX(58) .EQ. 1-
 IX(55)+IX(53) .LE. MIN(IX(51),IX(52)+1)
 IX(56)+IX(54) .LE. NUMBER OF SUBZONES
 IX(53)+IX(54) .LE. 70
 STOP WILL OCCUR IF CONSTRAINTS ARE EXCEEDED

(CONT)

IX(52)	FALSE ZONE NUMBER CONTAINING FEED MATERIAL COMPOSITION FOR SUBZONE PATHS (OR THE FIRST IN A SEQUENCE OF FALSE ZONE NUMBERS IF IX(58) .2Q. 1)
IX(53)	NUMBER OF ZONE PATHS THROUGH THE REACTOR THE FIRST ZONE IN THE FIRST ZONE PATH IS ZONE NUMBER 1, AND THE PATH FOLLOWS UP THE NUMBERS
IX(54)	NUMBER OF SUBZONE PATHS THROUGH THE REACTOR THE FIRST SUBZONE IN THE FIRST SUBZONE PATH IS SUBZONE NUMBER 1, AND THE PATH FOLLOWS UP THE NUMBERS
IX(55)	NUMBER OF ZONES ALONG EACH ZONE PATH
IX(56)	NUMBER OF SUBZONES ALONG EACH SUBZONE PATH
IX(57)	OPTION ON ZONE FEED MATERIAL 0- USE ZONE IX(51) AS FEED FOR ALL ZONE PATHS 1- USE ZONES IX(51) THROUGH IX(51)+IX(53)-1 AS FEED FOR EACH ZONE PATH (A DIFFERENT ZONE FOR EACH ZONE PATH)
IX(58)	OPTION ON SUBZONE FEED MATERIAL 0- USE ZONE IX(52) AS FEED FOR ALL SUBZONE PATHS 1- USE ZONES IX(52) THROUGH IX(52)+IX(54)-1 AS FEED FOR EACH SUBZONE PATH (A DIFFERENT ZONE FOR EACH SUBZONE PATH)
IX(59)	RESERVED
IX(60)	RESERVED
IX(61)	NUMBER OF PASSES TO ESTABLISH POWER LEVEL REPORTED BY THE NEUTRONICS CALCULATION (DEFAULT TO 1)

THE CALCULATION IS DONE THIS MANY TIMES (OR UNTIL THE
CONVERGENCE CRITERIA (SEE IX(20)) IS SATISFIED) WITH
THE FLUX LEVEL ADJUSTED AFTER EACH PASS WHICH IMPROVES
THE POWER LEVEL AND MAY ACCELERATE THE CONVERGENCE RATE
OF A USUAL FEED SEARCH ITERATION PROCEDURE.

(CONT)

CD*	IX (62)	OPTION TO WRITE INTERFACE FILE 'QHATDN' WITH	-
CD*		DISCHARGE DENSITIES (FOR CONTINUOUS FUELING MODEL	-
CD*		ONLY)	-
CD*		0- DO NOT WRITE	-
CD*		1- REPLACE THE LATEST VERSION OF AN OLD FILE,	-
CD*		IF NONE EXISTS WRITE NEW FILE	-
CD*		2- WRITE NEW FILE	-
C			-
CD	IX (63)	RESERVED	-
C			-
CD	IX (64)	RESERVED	-
C			-
CD	IX (65)	RESERVED	-
C			-
CD	IX (66)	RESERVED	-
C			-
CD	IX (67)	RESERVED	-
C			-
CD	IX (68)	RESERVED	-
C			-
CD	IX (69)	RESERVED	-
C			-
CD	IX (70)	RESERVED	-
C			-
CD	IX (71)	RESERVED	-
C			-
CD	IX (72)	RESERVED	-
C			-
CD	IX (73)	OPTION TO PERFORM AUXILIARY POINT CALCULATION	-
CD		OVER SELECTED ZONES	-
CD		0- NO	-
CD		1- YES - THE ZONE NUMBERS SPECIFIED IN	-
CD		IX (84)-IX (93), MAXIMUM OF 10, ARE TREATED IF	-
CD		THE POINT NUCLIDE DENSITY FILE 'PTATDN' DOES	-
CD		NOT EXIST; IF THIS FILE EXISTS THE REFERENCE	-
CD		DATA IN THE FILE IS USED TO CONTINUE THE	-
CD		CALCULATION FOR THE SAME ZONES TREATED	-
CD		PREVIOUSLY. FILE 'GEODST' IS ACCESSED FOR	-
CD		IDENTIFYING LOCATIONS OF POINTS IN THE ZONES	-
CD		AND POINT FLUX VALUES ARE OBTAINED FROM FILE	-
CD		'RTFLUX'.	-
CD		2- YES - THE REFERENCE DATA IS INITIALLY TAKEN	-
CD		FROM THE FILE 'RTFLUX' (MODIFIED) AND THE	-
CD		POINT FLUX VALUES ARE ALWAYS USED FROM THIS	-
CD		FILE (AS MADE AVAILABLE FROM A COMPATIBLE	-
CD		NEUTRONICS CODE). IF THE POINTS DO NOT	-
CD		AGREE WITH AN EXISTING 'PTATDN' FILE THE	-
CD		CALCULATION WILL NOT BE DONE.	-
C			-

(CONT)

IS AN ATTEMPT TO PARALLEL THE ZONE CALCULATION
OPTIONS IX(6), IX(10), IX(18), IX(8), IX(12),
IX(13), IX(30), AND IX(31) APPLY TO BOTH ZONE
AND POINT CALCULATIONS

THE PROCEDURE SHOULD MAINTAIN A SET OF POINT DENSITIES CONSISTENT WITH THE ZONE DENSITIES BUT CAN NOT ACCOUNT FOR EXTERNAL CHANGES IN THE ZONE DENSITIES (FROM A NEUTRONICS SEARCH, OR AFTER REFUELLING, OR REPOSITIONING, FOR EXAMPLE.)

NOT DONE IF IX(51) .GT. 0 OR IX(52) .GT. 0

IX (74) OPTION ON POINT EUCLIDE DENSITY EDITS (EXPOSURE)

- 0- NONE
- 1- END OF EXPOSURE STEP
- 2- END OF EACH EXPOSURE SUBSTEP

```

IX (75)      OPTION ON POINT EUCLIDE DENSITY EDITS (SHUTDOWN)
              0- NONE
              1- END OF SHUTDOWN STEP
              2- END OF EACH SHUTDOWN SUBSTEP

```

IX (76) OPTION TO EDIT INITIAL POINT SPECIFIC REACTION
 RATES
 0- NO
 1- YES

IX (77) OPTION TO EDIT INITIAL POINT SPECIFIC REACTION
RATE FOR FISSION IN YIELD DATA ENERGY RANGES
0- NO
1- YES.

IX (78) OPTION TO EDIT INITIAL POINT EUCLIDE DENSITIES
 0- NO
 1- YES

IX (79) DEBUG EDIT OPTION FOR POINT CALCULATION
(IN ADDITION TO THOSE REQUESTED WITH IX (3))
0- NONE
1- MINIMAL EDITS
2- PLUS FLUX INFORMATION
3- PLUS VOLUME INFORMATION

2,3 MAY INCREASE STORAGE REQUIREMENTS FOR
IX (73) .2Q. 1

IX (80) RESERVE

IX (81) RESERVE

(CONT)

CD	IX (82)	RESERVED	-
C			-
CD	IX (83)	RESERVED	-
C			-
CD	IX (84-93)	UP TO 10 ZONE NUMBERS SPECIFYING THE LOCATIONS WHERE-	-
CD		THE POINT CALCULATION IS TO BE DONE	-
CD		(IF IX (73) .EQ. 1)	-
CD		IF THERE ARE LESS THAN 10 ENTRIES , THE FIRST 0	-
CD		TERMINATES THE LIST OF ZONE NUMBERS	-
C			-
CD	IX (94-100)	RESERVED	-
C			-
C	-----		-

(CONT)

SPECIFICATIONS FOR PBLINS RECORD IN INTERFACE FILE CONTROL

```

C-----
C      PEBBLE THERMAL HYDRAULICS MODULE INSTRUCTIONS, FILE 'CONTROL'
C
C      (THERMAL PEBBLE BED IN RZ OF Z GEOMETRY)
C
C      DATE OF THESE USE INSTRUCTIONS, OCTOBER, 1980  --D VONDT, ORNL
C
C      PBLINS, (XX(Z),I=1,100), (IX(I),I=1,100)
C
C      101*MULT = 100
C
C      PBLINS  PEBBLE THERMAL HYDRAULICS DATA IDENTIFIER (6HPBLINS)
C
C      A * IS PLACED IN COLUMN 1 TO INDICATE THAT THAT DATA MUST
C      NORMALLY BE SUPPLIED -- READ NOTES AND CHECK OLD DECKS
C      FLAG TO INDICATE THAT DATA IS USUALLY REQUIRED FOR FLOW THRO
C      HOLES IN A SOLID MATRIX
C
C      XX(1)  VOID FRACTION IF TO BE CONSTANT
C              (DEFAULT VALUE 0.39 LACKING OTHER DATA - THE ZONE
C              FRACTIONS MAY BE USED AS SOLID FRACTIONS IF .02 <X< .98)
C      CDX    SPECIAL CONSIDERATIONS WITH FLOW THROUGH HOLES
C      CD*    XX(2)  INLET TEMPERATURE OF COOLANT, DEG C (DEFAULT 350.35)
C      CD*    XX(3)  INLET PRESSURE OF COOLANT, ATM (DEFAULT 40)
C      CD      XX(4)  COOLANT MASS FLOW RATE FOR REACTOR, KG/SEC,
C              NORMALLY CALCULATED GIVEN INLET AND OUTLET TEMPS
C      CD*    XX(5)  PEBBLE DIAMETER OR COOLANT HOLE DIAMETER, CM
C              THIS IS THE COOLANT FLOW CHARACTERISTIC DIAMETER
C      CD      XX(6)  REFERENCE HIGH ENERGY NEUTRON FLUX FLUENCE, 1/CM**2
C              APPLIED ONLY IF XX(3) < 0
C      CD      XX(7)  RECOVERABLE ENERGY FRACTION (DEFAULT 1.0)
C      CD      XX(8)  REACTOR POWER LEVEL DESIRED, W-TM, USUALLY NOT SET
C      CDX    XX(9)  EFFECTIVE DIAMETER OF UNIT CELL ABOUT FUEL (INSIDE
C              A SHELL OF MATERIAL OUTSIDE, LOCATION OF COOLANT FLOW), CM-
C              SET EQUAL TO XX(5) IF 0
C      CD*    XX(10) RADIUS OF THE ZONE PEBBLE HEAT OR HEAVY METAL CORE
C              (DEFAULT HALF OF PEBBLE DIAMETER - NO SHELL)
C      CD*    XX(11) RADIUS OF THE SUBZONE PEBBLE HEAT OR HEAVY METAL CORE
C              (DEFAULT HALF OF PEBBLE DIAMETER - NO SHELL)
C      CD      XX(12) OUTLET TEMPERATURE OF COOLANT, DEG C (DEFAULT 850.35 IF
C              XX(4)=0)
C              (NOT USED IF XX(4) IS NON-ZERO)
C      CD      XX(13) FLUENCE MULTIPLIER ON DATA AVAILABLE (DEFAULT 1.0)
C      CD      XX(14) RELATIVE PEBBLE GRAPHITE THERMAL CONDUCTIVITY, A
C              MULTIPLIER ON BUILT IN DATA (DEFAULT 1.0)
C      CD      XX(15) ITERATION CONVERGENCE CRITERIA, MAXIMUM RELATIVE ITERATE
C              CHANGE FOR TERMINATION (DEFAULT 0.00005)
C      CD      TH*  OPTION ON BLOCKED FLOW AREA FOLLOWS, USE WITH CAUTION
C      CD      XX(16) INSIDE RADIUS (MUST BE ZERO TO BE REALISTIC)
C      CD      XX(17) OUTSIDE RADIUS OF BLOCKAGE, CM

```

(CONT)

```

C3 XX(18)  DISTANCE BLOCKAGE STARTS FROM COOLANT INLET, CM -
C3 XX(19)  HEIGHT OF BLOCKAGE, CM -
C3 XX(20)  SOLID BLOCKAGE FRACTION (DEFAULT 0.85 — USE LARGE VALUES -
C3          WITH DISCRETIONS) -
C3          THE OPTION ON DEFINING CORE BOUNDARIES FOLLOWS -
C3          WITHOUT DATA, THE NON-ZERO POWER DENSITY EXTREMES DEFINE CORE -
C3 XX(21)  INSIDE RADIUS (IF NON-ZERO WILL REQUIRE ADDING THE -
C3          ANNULAR INTERNAL SOLID BOUNDARY PLANNED) -
C3 XX(22)  OUTSIDE RADIUS OF CORE, CM -
C3 XX(23)  DISTANCE FROM START OF GEOMETRY, TYPICALLY FROM TOP, CM -
C3 XX(24)  HEIGHT OF CORE, CM -
C3          -
C3          ADDITIONAL OPTIONS AND OVERRIDE DATA VALUES FOLLOW -
C3 XX(25)  LIMITING PROCESSOR TIME, SECONDS (DEFAULT 120) -
C3          -
C3          INITIAL ACCELERATION COEFFICIENTS ARE MADE PROBLEM DEPENDENT -
C3          AND MAY BE ALTERED DURING THE PROBLEM SOLUTION IF DEEMED TO BE -
C3          DESIRABLE BY THE AUTOMATED MONITORING PROCEDURES -
C3          -
C3          IT IS QUITE POSSIBLE THAT THE ROUGH ITERATIVE BEHAVIOR EARLY IN -
C3          THE HISTORY WILL CAUSE INITIAL COEFFICIENTS TO BE DECREASED -
C3          WHICH WOULD REQUIRE INPUT OF SOMEWHAT LARGER VALUES THAN THOSE -
C3          EXPECTED TO BE OPTIMUM ASYMPTOTICALLY -
C3          -
C3 XX(26)  STREAM FUNCTION OVERRELAXATION COEFFICIENT -
C3 XX(27)  BULK TEMPERATURE, DITTO, SEE FOLLOWING NOTE -
C3          THIS COEFFICIENT MAY BE OF GREATEST IMPORTANCE, AND AN EFFECTIVE -
C3          VALUE SHOULD BE SUPPLIED IF KNOWN (TEST PROVEN FOR AT LEAST A -
C3          SIMILAR PROBLEM). TYPICALLY THE VALUE IS MUCH LESS THAN 1. -
C3 XX(28)  SURFACE TEMPERATURE, DITTO -
C3          IT IS DIFFICULT TO SEE HOW A VALUE OTHER THAN UNITY WOULD BE -
C3          EFFECTIVE HERE -
C3 XX(29)  PRESSURE, DITTO -
C3 XX(30)  SPECIFIC HEAT VALUE (5193.) -
C3          -
C3          DATA FOR A SECOND AND THIRD CALCULATION FOLLOW (3 DATUM EACH) -
C3 XX(31)  NEW INLET COOLANT TEMPERATURE, DEG C (DEFAULT XX(2)) -
C3 XX(32)  NEW OUTLET COOLANT TEMPERATURE, DEG C (DEFAULT XX(12)) -
C3 XX(33)  RELATIVE POWER LEVEL FOR SUBSEQUENT CALCULATION -
C3 XX(34)  NEW INLET COOLANT TEMPERATURE, DEG C (DEFAULT XX(31)) -
C3 XX(35)  NEW OUTLET COOLANT TEMPERATURE, DEG C (DEFAULT XX(32)) -
C3 XX(36)  RELATIVE POWER LEVEL FOR THIRD CASE (DEFAULT (XX(33)) -
C3          (RELATIVE TO THAT FOR THE SECOND CASE) -
C3          -
C3 XX(37)  MOLECULAR WEIGHT (8.0026) -
C3 XX(38)  AZERO (0.0216) -
C3 XX(39)  AGAS (0.49849) -
C3 XX(40)  B (0.) -
C3 XX(41)  C (40.) -
C3 XX(42)  RGAS (0.08206) -

```

(CONT)

```

C3 XX(43) BZERO (0.014)
C3 XX(44) PCONA (17.)
C3 XX(45) PCONB (20.5)
C3 XX(46) PCONC (-15.17)
C3 XX(47) BETAK (0.95)
C3 XX(48) GAMMAK (2./3. SPHERE, PI/4. CYLINDER)
C3 XX(49) PC (3.674E-07)
C3 XX(50) PD (0.7)
C3 XX(51) PE (0.71)
C3 XX(52) PF (2.682E-03)
C3 XX(53) PG (0.0011379)
C3 XX(54) PH (1.4389E-4)
C3 XX(55) APRIC (4.1666) HYDRAULIC EQUATION, FIRST COEFFICIENT
C3X NOT USED IF XX(13) > 0
C3 XX(56) BPRIC (.1754)
C3X (1.0 IF XX(13) > 0)
C3 XX(57) P1 (2.2679E-07)
C3 XX(58) P2 (3.)
C3 XX(59) P3 (.1293)
C3 XX(60) P4 (.3292)
C3 XX(61) P5 (.277)
C3 XX(62) P6 (.2426)
C3 XX(63) P7 (.26)
C3 XX(64) P8 (.476)
C3 XX(65) P9 (.41)
C3 XX(66) P10 (1.176E-04)
C3 XX(67) P11 (311.)
C3 XX(68) FOR ONE-DIMENSIONAL CALCULATIONS, RADIAL PEAKING FACTOR
C3 FOR AUXILIARY CALCULATION (DEFAULT 1.2)
C3 XX(69) P12 (.005)
C3 XX(70) P13 (2.)
C XX(71) - XX(83) REFERENCE THERMAL CONDUCTIVITY DATA
C USED IF XX(71) NE. 0
C3 AT NO EXPOSURE, CORRESPONDING TO TEMPERATURES (K) --
C3 300. 350. 400. 500. 600. 700. 800. 900. 1000. 1100. 1200. 1300. 1600.
C3 REFERENCE POINT C(2) AT T = 350. IS 1.05 WATTS/CM-DEG DELTA T
C3 TO CONVERT GM-CAL TO WATT-SEC, MULTIPLY BY 4.186
C3 XX(84) P15 (0.1905)
C3 XX(85) P16 (2./3.)
C3 XX(86) ECVR (0.1409)
C3 XX(87) ECV1 (0.5409)
C3 XX(88)-XX(100) RESERVED
C
C3 XX(1) OPTION ON COOLANT FLOW
C3 -1 NO GRAVITY TERM
C3 0- DOWNWARD FLOW
C3 1- UPWARD FLOW
C

```

(CONT)

CN IT MAY BE USEFUL TO CONSIDER THAT AS THE PROBLEMS ARE DESCRIBED -
 CN FOR THE NEUTRONICS, FLOW IS FROM THE TOP TO THE BOTTOM -
 CN (LEFT TO RIGHT IF ONE DIMENSIONAL) -
 CN AND THE COOLANT FLOW MUST BE IN THIS DIRECTION, REASONABLE IT -
 CN SEEMS FOR DOWN FLOW OF COOLANT AND PEBBLES, BUT IF THE COOLANT IS -
 CN TO FLOW UP AND THE PEBBLES DOWN, THEN THE PROBLEM MUST BE SET UP -
 CN QUITE DIFFERENTLY (ZONE NUMBERS RUN UP INSTEAD OF DOWN) -
 C -
 CD IX(2) OPTION ON PRESSURE DROP AND FILM COEFFICIENT -
 CD 0- SERIAL -
 CD 1- US CORRELATIONS (OLD) -
 CD IX(3) OPTION ON FLUENCE, 0- DON'T READ DATA (SEE IX(6)) -
 CD 0,1- CPNIST FILE, CONTINUOUS FUELING -
 CN NOTE THAT THIS FLAG MUST BE SET FOR FIXED FUEL EXPOSURE -
 CD 2- EXPORT FILE, FIXED FUEL EXPOSURE -
 CD IX(4) FLUENCE SELECTION, 0,1- USE FIRST RANGE IF AVAILABLE -
 CD 2- USE SECOND RANGE IF AVAILABLE -
 CD 3- USE TOTAL IF IT IS AVAILABLE -
 CN IF DESIRED DATA IS NOT AVAILABLE, NO DATA IS USED -
 CD IX(5) MEMORY AVAILABLE FOR DATA IN 1000 WORDS -
 CD (DEFAULT 20000 ADDED TO RECORD 'DEVINS' CONSTANT -
 CD WHICH IS THE NUMBER SUPPLIED TO THE CONTROL MODULE) -
 CD UNDER VERTICAL MEMORY, ASSURE FULL CORE CONTAINED -
 CD AND ALLOCATE SPACE ACCORDINGLY -
 CD IX(6) THERMAL CONDUCTIVITY TREATMENT (FOR GROSS HEAT TRANSFER -
 CD ACROSS CORE), OPTIONS -
 CD 0- NO SOLID PHASE HEAT TRANSFER -
 CD 0- USE ZONE EXPOSURE DATA AND SURFACE TEMPERATURE -
 CD 1- USE SUBZONE EXPOSURE DATA AND SURFACE TEMPERATURE -
 CD 2- DITTO, BUT VOLUME FRACTION WEIGHT INSTEAD OF AVERAGE -
 CD 3- USE BUILT IN AXIAL FUNCTION -
 CD IX(7) DEBUG EDIT LEVEL (0,1,2,3) -
 CD IX(8) EDIT LEVEL OF RESULTS (-1,0,1,2) -
 CD EDIT LEVEL IS INDEXED UP IF RESULTS SEEM UNUSUAL -
 CD IX(9) HEAT REMOVAL OPTIONS -
 CD 0- NORMAL -
 CD 1- EXCLUDE SOLID CONDUCTION -
 CD IX(10) FUEL ELEMENT GEOMETRY (GRAPHITE, NOW USED ONLY FOR THE -
 CD TEMPERATURE CALCULATION IN THE ELEMENT AND AT THE -
 CD SURFACE, NOT FOR FLOW) -
 CD 0- SPHERICAL -
 CD 1- CYLINDRICAL (INFINITE LENGTH) -
 CD IX(11) ITERATION COUNT TERMINATION (DEFAULT ESTIMATED BY CODE) -
 CD -NO ITERATION IF <0 -
 CD IX(12) OPTION TO ELIMINATE RADIAL (GROSS) FLOW -
 CD 0- NORMAL (INCLUDE) -
 CD 1- EXCLUDE -
 CD 2- EXCLUDE, AND FIX THE AXIAL FLOW RATE PROPORTIONAL -
 CD TO THE AXIAL HEAT LOAD (IDEAL ORIFICING) -
 CD 3- SAME AS 2 BUT ORIFICE AT INLET INSTEAD OF OUTLET -
 CN NOTE THAT THE ABOVE NON-ZERO OPTIONS APPLY TO FIXED TRAVERSE -
 CN COOLANT FLOW REQUIRING ADJUSTMENT IN THE DEFAULT COEFFICIENTS -
 CD IX(13) OPTION FOR FLOW THROUGH HOLES IN SOLID IF > 0 -
 CD IX(14) ITERATION PROCEDURE OPTION, -
 CD -1- DO NOT INCREASE OVERRELAXATION COEFFICIENTS -
 CD 0- ADJUST OVERRELAXATION COEFFICIENTS DURING ITERATION -
 CD 1- DO NOT INCREASE NOR DECREASE COEFFICIENTS -

(CONT)

```

C9      IX(15)    EQUATION STEP ORDER,
C9      0- SIGMA-1 (ODD POINTS, THEN EVEN POINTS)
C9      1- NORMAL ORDERED (ONE POINT AFTER THE OTHER, 2 THEN 1)
C9      IX(16)    ASYMPTOTIC EXTRAPOLATION PROCEDURE OPTION,
C9      0- NORMAL (ALLOW)
C9      1- DO NOT ALLOW
C9      >1- MINIMUM CYCLE DELAY
C9      IX(17)    OPTION ON ASYMPTOTIC EXTRAPOLATION, DATA LEVEL
C9      0- STREAM FUNCTION, TEMPERATURES, PRESSURE
C9      1- STREAM FUNCTION, PRESSURE
C9      2- PRESSURE
C9      IX(18)    OPTION ON THE CALCULATION OF THE LOCAL VOID FRACTION
C9      (OVERRIDDEN BY IX(1), APPLICABLE ONLY WHEN THERE ARE SUBONES)
C9      0- SUMS ZONE AND SUBZONE VOLUME FRACTIONS
C9      1- USES ONLY ZONE VOLUME FRACTION
C9      2- SUMS ONLY SUBZONE VOLUME FRACTIONS
C9      IX(19)    INITIALIZATION OPTIONS
C9      -1 ONLY FOR SUBSEQUENT CASE THE SOLUTION IS KEPT
C9      0- AUTOMATED PROCEDURE (AXIAL FLUID HEATING)
C9      1- SOMETHING DIFFERENT FOR HE WHO HAS TRIED EVERYTHING
C9      IX(20)    WRITE ZONE TEMPERATURE FILE 'TEMP?' OPTIONS
C9      -1- NO
C9      0, 1- WRITE OVER EXISTING ONE IF ONE EXISTS
C9      OTHERWISE WRITE NEW ONE
C9      2- WRITE OVER NEXT TO LATEST VERSION IF IT EXISTS,
C9      OTHERWISE WRITE NEW ONE
C9      3- GENERATE NEW FILE
C9      IX(21)    SAVE DATA ON AN INTERFACE FILE FOR RECOVERY
C9      -1 SAVE DATA IF CONVERGENCE CRITERIA IS NOT SATISFIED
C9      0 DO NOT SAVE DATA
C9      1 SAVE THE THERMAL HYDRAULICS DATA FOR RECOVERY
C9      2 ALSO SAVE THE PEBBLE THERMAL CONDUCTIVITY DATA
C9      DATA IS SAVED FOR ONLY THE FIRST PROBLEM SOLVED IN A CODE ACCESS-
C9      IX(22)    RECOVER DATA FROM AN INTERFACE FILE TO CONTINUE ITERATION-
C9      OR TO INITIALIZE WITH (PROBLEM MUST BE SIMILAR)
C9      1- RECOVER ALL DATA (NO REPLACEMENT)
C9      2- DO NOT USE VOID FRACTION, POWER DENSITY, NOR
C9      EXPOSURE DATA FROM FILE (USE NEW DATA)
C9      IX(23)    OPTION TO RECOVER THE PEBBLE THERMAL CONDUCTIVITY DATA
C9      0- DO NOT
C9      1- RECOVER AND USE THE IRRADIATION TEMPERATURE AND
C9      NEUTRON FLUX EXPOSURE FUNCTION DATA
C9      (THIS OPTION REQUIRED TO OBTAIN ONLY EFFECTS OF
C9      SHORT TERM TEMPERATURE CHANGES)
C9      2- RECOVER AND USE DIRECTLY THE THERMAL CONDUCTIVITY
C9      PEBBLE THERMAL DATA MAY BE SAVED OR RECOVERED, BUT NOT BOTH.
C9      DEFAULT PROCEDURES GIVE PREFERENCE TO DATA RECOVERY OVER SAVING-
C9      (USED FIRST PROBLEM ONLY)
C9      IX(24)-IX(100) RESERVED
C9
C-----

```

(CONT)

SPECIFICATIONS FOR PERINS RECORD IN INTERFACE FILE CONTROL

PERTURBATION MODULE INSTRUCTIONS

PERINS, (IX(I), I=1,100), (IX(I), I=1,100)

101=MULT * 100

PERINS PERTURBATION MODULE DATA IDENTIFIER (6HPERINS)

NOTE- UNDEFINED DATA ARE RESERVED FOR FUTURE USE.

NOTE- THE VALUE OF ZERO IS A DEFAULT MEANING THAT THE OPTION TO PERFORM THE TASK IS NOT EXERCISED.

NOTE- THE INTERFACE FILES -GROUPIS- -GRODST- -GDISIP- -GSTAT- -ATPLUX- AND -ACTPLUX- ARE NEEDED.

IF THE FILE -DELAYIS- EXISTS, INFORMATION ABOUT THE DELAYED NEUTRON BEHAVIOR IS CALCULATED IN ADDITION TO THE OTHER PERTURBATION CALCULATIONS.

IX(1) - REFERENCE TEMPERATURE T1, DEGREES C (SEE IX(7) BELOW).

IX(2) - CHANGED TEMPERATURE T2, DEGREES C.

IX(3) - TEMPERATURE CORRELATING PARAMETER 'ALPHA'

IX(4)

IX(5)

IX(6)

IX(7) - 'ALPHA' FOR THE DELAYED NEUTRON SOURCE - DEFAULT -0.05.

IX(8) - 'ALPHA' FOR THE DELAYED NEUTRON SOURCE - DEFAULT -0.05.

IX(9)

IX(10)

IX(11)

IX(12)

IX(13) - CONSTANT BUCKLING, OVERRIDES DATA ON GRODST.

IX(14)

IX(15)

IX(16)

IX(17)

IX(18)

IX(19)

IX(20)

IX(21)

IX(22)

IX(23)

IX(24)

IX(25) - FRACTION CHANGE IN SACTO. CROSS SECTIONS FOR IX(2)=1.

(CONT)

THE FOLLOWING TABLE SHOWS THE INTERFACE FILES REQUIRED FOR
OPTIONS IX(1) AND IX(2), AND THE FILE VERSIONS USED TO OBTAIN THE
PERTURBATION (DELTA FACTOR = SIGM-SIGA). ADDITIONAL FILES ARE
ALSO REQUIRED.

IX(2)	IX(1) =	-1	0	1	2	3
0		EXCLUDED	W1, W2, S1, S2, X	W1, W2, S, X	W, S1, S2, X	W, S, X
1	SIGA	W, S, X	W1, S1, X W2, S2	W1, S, X W2	W, S1, X S2	W, S, X
2	SIGB	W1, S, X	W1, S1, X	W1, S, X	W1, S1, X	W1, S, X
	SIGB	W2, S, X	W2, S2, X	W2, S, X	W2, S2, X	W2, S, X
3	SIGA	W, S1, X	W1, S1, X	W1, S1, X	W, S1, X	W, S1, X
	SIGB	W, S2, X	W2, S2, X	W2, S2, X	W, S2, X	W, S2, X
4	SIGA	W1, S1, X	W1, S1, X	W1, S1, X	W1, S1, X	W1, S1, X
	SIGB	W2, S2, X	W2, S2, X	W2, S2, X	W2, S2, X	W2, S2, X
5	SIGA	W, S, X1	W1, S1, X1	W1, S, X1	W, S1, X1	W, S, X1
	SIGB	W, S, X2	W2, S2, X2	W2, S, X2	W, S2, X2	W, S, X2
6	SIGA	W1, S, X1	W1, S1, X1	W1, S, X1	W1, S1, X1	W1, S, X1
	SIGB	W2, S, X2	W2, S2, X2	W2, S, X2	W2, S2, X2	W2, S, X2
7	SIGA	W1, S1, X1	W1, S1, X1	W1, S1, X1	W1, S1, X1	W1, S1, X1
	SIGB	W2, S2, X2	W2, S2, X2	W2, S2, X2	W2, S2, X2	W2, S2, X2

VERBS - W1 = NEXT-TO-LATEST VERSION (UNPERTURBED) ZNATON FILE.
W2 = LATEST VERSION (PERTURBED) ZNATON FILE.
S1 = NEXT-TO-LATEST VERSION (UNPERTURBED) GROUPIS FILE.
S2 = LATEST VERSION (PERTURBED) GROUPIS FILE.
X1 = NEXT-TO-LATEST VERSION (UNPERTURBED) NOISEP FILE.
X2 = LATEST VERSION (PERTURBED) NOISEP FILE.
W, S, X = LATEST (MAY BE ONLY ONE) VERSION OF ZNATON,
GROUPIS, AND NOISEP FILES.

(CONT)

IF FILES DO NOT EXIST FOR IX(1) OPTIONS 0, 1, OR 2, IX(1) IS
 DEFAULTED TO 3 AND THE ATTEMPT IS MADE TO PROCEED USING A SINGLE
 EXISTING FILE AS NEXT-TO-LATEST VERSION UNLESS IX(6) GT 0.
 NOTE -- DIFFERENT GROUPS FILES MUST HAVE THE SAME GROUP STRUCTURE.
 THE FILES GEODST, REFLOX, AND ATFLUX MUST HAVE THE SAME
 NUMBER OF GROUPS AND THE SAME MESH.
 THE FILES GEODST AND NDKSRF MUST HAVE THE SAME NUMBER
 OF ZONES.
 THE FILES GROUPS AND NDKSRF MUST HAVE THE SAME TOTAL
 NUMBER OF NUCLIDES.
 THE FILES SWATON AND NDKSRF MUST HAVE THE SAME MAXIMUM
 NUMBER OF NUCLIDES IN ANY SET, AND THE SAME NUMBER OF
 ZONES PLUS SUB-ZONES.

IX(1) - OPTIONS FOR CALCULATING BASIC INTEGRALS.
 -1 - NO CALCULATION (PERTURB ALREADY EXISTS).
 0 - CALCULATE INTEGRALS USING FILES N1, S1.
 1 - CALCULATE INTEGRALS USING FILES N1, S2 (USUALLY NOT
 DONE).
 2 - CALCULATE INTEGRALS USING FILES N2, S1 (USUALLY NOT
 DONE).
 3 - CALCULATE INTEGRALS USING FILES N2, S2 (OR N, S).

IX(2) - OPTIONS FOR CALCULATING $(\Delta K)/K = (\text{PERTURBATION INTEGRALS}) / (\text{SIGN-SIGN})$.
 0 - ONLY CALCULATE BASIC INTEGRALS.
 1 - CHANGE MACROSCOPIC CROSS SECTIONS BY MULTIPLYING
 THEM BY IX(25).
 2 - CHANGE ONLY DENSITIES.
 3 - CHANGE ONLY CROSS SECTIONS.
 4 - CHANGE BOTH DENSITIES AND CROSS SECTIONS.
 5 - CHANGE ONLY REFERENCING.
 6 - CHANGE DENSITIES AND REFERENCING.
 7 - CHANGE DENSITIES, CROSS SECTIONS, AND REFERENCING.

IX(3) - PERTURBATION CALCULATION OPTIONS FOR IX(1) GE 0.
 -1 - DO NOT CALCULATE TRANSPORT INTEGRALS.
 0 - CALCULATE ALL INTEGRALS.
 1 - ALSO CALCULATE RESULTS FOR 100 PERCENT CHANGE IN
 MACROSCOPIC CROSS SECTIONS AND UNCERTAINTY
 (SENSITIVITY) RESULTS.
 6 - SAME AS 0 BUT NO EDITS ARE PRINTED.

IX(4) - EDIT OPTIONS FOR IMPORTANCE MAPPING FOR IX(1) GE 0.
 1 - ABSORPTION CROSS SECTION SPACE POINT IMPORTANCE MAP.
 2 - ALSO PRODUCTION AND PRODUCTION-ABSORPTION SPACE
 POINT IMPORTANCE MAPS.
 3 - ALSO $1/\nu$ SPACE POINT IMPORTANCE MAP.

(CONT)

C9 IX(5) - OPTION TO WRITE INTERFACE FILE PERTUS FOR IX(1) GE 0. -
 C9 0 - REPLACE OLD FILE, IF NONE EXISTS SET UP NEW ONE. -
 C9 1 - WRITE NEW FILE. -
 C9 IX(6) - OPTION TO DEFAULT FILES FOR IX(1) = 0, 1, OR 2. -
 C9 0 - DEFAULT IX(1) TO 3 IF FILES FOR IX(1) = 0, 1, OR 2 -
 C9 DO NOT EXIST. -
 C9 1 - STOP CALCULATION IF FILES DO NOT EXIST. -
 C9
 C9 IX(7) - OPTIONS TO CONSIDER A CORRELATION OF MACROSCOPIC -
 C9 CROSS SECTIONS ON ZONE TEMPERATURE IF GT 0, REQUIRES -
 C9 ZONE TEMPERATURE DATA IN INTERFACE FILE(S). -
 C9 0 - NO TEMPERATURE DEPENDENCE, SEE DISCUSSION ABOUT -
 C9 OPTIONS ABOVE. -
 C9 1 - SIGA = SIGAT1, AND -
 C9 SIGB = SIGBT1+P1*(SIGBT2-SIGBT1). -
 C9 2 - SIGA = SIGAT1+P1*(SIGAT2-SIGAT1), AND -
 C9 SIGB = SIGBT1+P1*(SIGBT2-SIGBT1). -
 C9 3 - SIGA = SIGAT1+P1*(SIGAT2-SIGAT1), AND -
 C9 SIGB = SIGBT1+P2*(SIGBT2-SIGBT1). -
 C9
 C9 WHERE -- SIGA = STATE A MACROS. -
 C9 SIGB = STATE B MACROS. -
 C9 SIGAT1 = MACROS CALCULATED USING FILE N1 (OR N) AND -
 C9 FILE S1 (REFERENCE TEMPERATURE) OR I1. -
 C9 SIGAT2 = MACROS CALCULATED USING FILE N1 (OR N) AND -
 C9 FILE S2 (CHANGED TEMPERATURE) OR I2. -
 C9 SIGBT1 = MACROS CALCULATED USING FILE N2 (OR N) AND -
 C9 FILE S1 (REFERENCE TEMPERATURE) OR I1. -
 C9 SIGBT2 = MACROS CALCULATED USING FILE N2 (OR N) AND -
 C9 FILE S2 (CHANGED TEMPERATURE) OR I2. -
 C9 A1 = (Z1-T1)/(T2-T1). -
 C9 A2 = (Z2-T1)/(T2-T1). -
 C9 T1 = REFERENCE TEMPERATURE (IX(1) ABOVE). -
 C9 T2 = CHANGED TEMPERATURE (IX(2) ABOVE). -
 C9 Z1 = ZONE DEPENDENT REFERENCE TEMPERATURES -
 C9 (FROM FILE ZTEMP). -
 C9 Z2 = ZONE DEPENDENT CHANGED TEMPERATURES -
 C9 (FROM FILE ZTEMP). -
 C9 IF ALPA= 0, P1=A1, -
 C9 OTHERWISE P1=TAN-1(ALPA=A1)/TAN-1(ALPA) -
 C9 IF ALPA= 0, P2=A2, -
 C9 OTHERWISE P2=TAN-1(ALPA=A2)/TAN-1(ALPA) -
 C9
 C9 NOTE -- FOR IX(7) = 0, ALL IX(1) AND IX(2) OPTIONS APPLY. -
 C9 FOR IX(7) GT 0, IX(1) OPTIONS -1, 0, OR 3 APPLY, AND -
 C9 IX(2) OPTIONS 3, 4, 5, 6, AND 7 APPLY. -
 C9

(CONT)

CD IX(8) - OPTION TO CALCULATE IMPORTANCE BY UNIQUE (USER) NUCLIDE
 CD NAME IN EACH ZONE.
 CD 0 - NO.
 CD 1 - CALCULATE $(\Delta K)/(K \cdot \Delta H)$ FOR NUCLIDES HAVING
 CD CLASSIFICATION 1, 2, AND 3 (ACTINIDES). DEFAULT TO ALL
 CD NUCLIDES IF NO 1, 2, OR 3 CLASSIFICATION.
 CD 2 - ALSO CALCULATE $(H \cdot \Delta K)/(K \cdot \Delta H)$.
 CD 3 - SAME AS 1 BUT FOR ALL NUCLIDES.
 CD 4 - SAME AS 2 BUT FOR ALL NUCLIDES.
 CD NOTE -- THE INATON, GROUPS, AND NDISRP FILES USED FOR THIS
 CD OPTION WILL BE THE ONES LAST USED AS REQUIRED BY OPTIONS
 CD IX(1), IX(2), AND IX(7).
 CD
 CD IX(9)
 CD
 CD IX(10) - OPTION TO USE LOCAL I/O ROUTINES IF GT 0.
 CD
 CD IX(11) - OPTION TO PREVENT FILES FROM DEFAULTING TO CORE IF GT 0.
 CD
 CD IX(12)
 CD
 CD IX(13) - 0 OR 1 = NORMAL REFLEX. 2 = FIRED SOURCE REFLEX.
 CD
 CD IX(14) - 0 OR 1 = NORMAL ATFLUX. 2 = FIRED SOURCE ATFLUX.
 CD IX(15) - EDIT MACROSCOPIC CROSS SECTIONS IF GT 0.
 CD
 CD IX(16) - EDIT MACROSCOPIC SCATTERING CROSS SECTIONS IF GT 0.
 CD
 CD IX(17)
 CD
 CD IX(18) - FISSION SOURCE DISTRIBUTION FUNCTION OPTION.
 CD 0 - SET VALUES TO BE USED (SAME IN EACH ZONE).
 CD 1 - REGION DEPENDENT VALUES TO BE USED.
 CD
 CD IX(19) - FISSION SOURCE DISTRIBUTION NORMALIZATION OPTION.
 CD 0 - LEAVE UNNORMALIZED.
 CD 1 - NORMALIZE EACH SET TO SUM TO UNITY.
 CD
 CD IX(20) - OPTION TO FORCE DATA HANDLING MODE.
 CD 1 - 1-ROW STORED MODE.
 CD 2 - SPACE STORED MODE.
 CD 3 - PLANE STORED MODE.
 CD
 CD IX(21) - ORDER IN THE CROSS SECTION FILE OF THE DIRECTION
 CD DEPENDENT TRANSPORT CROSS SECTION TO BE USED FOR THE
 CD FIRST COORDINATE DIRECTION (USUALLY 0).
 CD
 CD IX(22) - DITTO, SECOND COORDINATE DIRECTION.
 CD
 CD IX(23) - DITTO, THIRD COORDINATE DIRECTION.

(CONT)

```

C
CD IX(24) - FORCE DATA TRANSFER IN INITIALIZATION (FOR TESTING ONLY). -
C
CD IX(25) - DEBUG OUTPUT OPTION. -
C 0 - NO DEBUG EDIT. -
C 1 - EDIT NUCLEIDE IMPORTANCE (SEE IX(9)) BY REACTION -
C TYPE (SIGA, NUSIGP, SIGTR, DB**2, SIGR, AND SIGS) -
C AND FOR EACH ZONE CLASS. ALSO EDIT CONTENTS OF I/O -
C ISIGNA. -
C 2 - PLUS EDIT CONTENTS OF I/O ISIGS AND OTHER SIGNALS. -
C 3 - PLUS EDIT CONTENTS OF I/O 23 AND/OR 40. -
C-----

```

(CONT)

SPECIFICATIONS FOR PROINS RECORD IN INTERFACE FILE CONTROL

C	-----		
CR		PROBLEM INFORMATION	-
C			-
CL	PROINS, (IX(I),I=1,100), (IX(I),I=1,100)		-
C			-
CV	101=MULT * 100		-
C			-
CD	PROINS	PROBLEM INFORMATION DATA IDENTIFIER (6XPROINS)	-
C			-
CD	IX(1-25)	PROBLEM OR CASE TITLE (A6)	-
C			-
CD	IX(25)	USER LABEL (JOBNAME) FOR INTERFACE DATA FILES (A6)	-
C			-
CD	IX(26)	USER LABEL (DATE) FOR INTERFACE DATA FILES (A6)	-
C			-
CD	IX(27-100)	RESERVED	-
C			-
CD	IX(1-100)	RESERVED	-
C	-----		-

(CONT)

SPECIFICATIONS FOR REPINS RECORD IN INTERFACE FILE CONTROL

FUEL MANAGEMENT INFORMATION	
REPINS, (IX(I), I=1,100), (IX(I), I=1,100)	
101=HULT * 100	
REPINS	REQUIRED INFO IDENTIFIER = 'REPINS' (A6)
IX(1)	*** RESERVED ***
IX(2)	FRACTION OF THE WHOLE REACTOR TREATED (DEFAULT VALUE = 1.0)
IX(3)	ELECTRICAL POWER LEVEL OF THE REACTOR (WATTS) (DEFAULT VALUE = 0.0)
IX(4)	THERMAL CONVERSION FACTOR FOR THE REACTOR (ELECTRICAL POWER/THERMAL POWER)
IX(5)	RATE OF FUEL CONSUMPTION PER UNIT THERMAL ENERGY GENERATED (KG FISSILE/WATT-DAY) (DEFAULT VALUE=1.3E-9 KG/WATT-DAY ASSUMING 3.1E-11 WATTS/FISSION)
IX(7)	REFERENCE FUEL COST DISCOUNT RATE (DEFAULT VALUE = 0.10)
IX(8)	SECONDARY FUEL COST DISCOUNT RATE FOR AUXILIARY CALCULATIONS (DEFAULT VALUE = 0.15)
IX(20)	PROGRAMMABLE SIGNIFICANCE VALUE. 1. THIS VALUE IS THE FRACTIONAL VOLUME MISMATCH TO ALLOW BEFORE REPORTING ERRORS FOR FUEL MOVEMENT. FUEL MOVEMENT IS ALLOWED FROM ZONE 1 TO ZONE 2 IF, FOR VOLUMES V1 AND V2, ABS((V1-V2)/V1) .LE. MAXIMUM MISMATCH. 2. FOR ANY RECYCLE PROCESSING (TRANSFER TO SUPPLY FROM DISCHARGE, FABRICATION AND PROCESSING, OR TRANSITIONS), IF THE RELATIVE MASS BEFORE AND AFTER PROCESSING IS LESS THAN THE SIGNIFICANCE VALUE, THE MASS IS FORCED TO 0. (DEFAULT VALUE= 1.0E-04)
IX(1)	PRIMARY TASK ASSIGNMENT OPTIONS -1 INITIALIZATION OPTION TO START THE MASS BALANCE HISTORY. NO RECYCLING/FUEL MOVEMENT IS PERMITTED; THE MASS BALANCE HISTORY FILE IS CREATED FOR THE INITIAL REACTOR INVENTORY. IF INITIALIZATION IS NOT THE FIRST OPTION USED, THE MASS BALANCE HISTORY FILE IS CREATED BUT MASS BALANCES MAY NOT BE COMPLETE. 3 PERFORM NORMAL TASKS (NORMAL FUEL MOVEMENT WITH MASS BALANCE ACCOUNTING OR FUEL RELOCATION) (DEFAULT)

(CONT)

CO		1 REEVALUATE MASS BALANCE WITH OTHER	-
CO		TASKS AS IN A NEUTRONICS CONCENTRATION	-
CO		ADJUSTMENT. THIS OPTION IS NOT AVAILABLE.	-
CO		2 HISTORY END; OUTPUT MASS BALANCE	-
CO	IX(3)	DEBUG EDIT OPTION FOR PROGRAM MAINTENANCE	-
CO		0 NO SPECIAL EDITS (DEFAULT)	-
CO		1 FIRST LEVEL EDITS	-
CO		2 ELABORATE DEBUG EDIT	-
CO	IX(4)	ZNATON UPDATE OPTION	-
CO		0 REWRITE NEW DATA ON EXISTING FILE (DEFAULT)	-
CO		1 GENERATE A NEW FILE FOR EACH CYCLE	-
CO	IX(5)	ZONE ATOM DENSITY (ZNATDN) BACKUP FILE OPTION	-
CO		0 WRITE BACKUP FILE ZNATDN (DEFAULT)	-
CO		1 DO NOT WRITE BACKUP FILE ZNATDN	-
CO		-1 RECOVER ZONE ATOM DENSITY DATA FROM BACKUP	-
CO		FILE ZNATDN RATHER THAN FROM FILE ZNATON	-
CO	IX(6)	CONTINUOUS FUELING FILE OPTION	-
CO		0 READ ZONE CONCENTRATIONS FROM FILE ZNATON	-
CO		AND UPDATE ZONE CONCENTRATIONS IN FILE	-
CO		ZNATDN (DEFAULT)	-
CO		1 READ ZONE CONCENTRATIONS FROM FILE QNATDN	-
CO		AND UPDATE ZONE CONCENTRATIONS IN FILE	-
CO		ZNATDN	-
CO	IX(7)	MASS BALANCE FILE (HASBAL) DELETE OPTION	-
CO		0 RETAIN CURRENT VERSION OF HASBAL FILE ONLY;	-
CO		DELETE ALL OLDER VERSIONS (DEFAULT)	-
CO		1 RETAIN CURRENT VERSION OF HASBAL FILE AND	-
CO		PREVIOUS VERSION ONLY; DELETE ALL OLDER	-
CO		VERSIONS	-
CO			-
CO		NOTE: THIS OPTION IS NOT USED IF FUEL RELOCATION IS	-
CO		THE ONLY TASK PERFORMED SINCE NO MASS BALANCE	-
CO		ACCOUNTING IS PERFORMED.	-
CO			-
CO	IX(11)	FUEL COST CALCULATION OPTION	-
CO		0 NO FUEL COST CALCULATIONS	-
CO		1 OBTAIN LEVELIZED COST FOR ENTIRE HISTORY.	-
CO		WITH COST BREAKDOWN INTO COMPONENTS AT	-
CO		END OF HISTORY ONLY.	-
CO		(FABRICATION, PROCESSING, SHIPPING, ETC.)	-
CO		2 OBTAIN LEVELIZED COST FOR HISTORY WITH	-
CO		BREAKDOWN, COST BETWEEN SUCCESSIVE FUELINGS	-
CO		AND RUNNING LEVELIZED COST. (EACH CYCLE IS	-
CO		TREATED AS A COMPLETE HISTORY FOR REPORTING	-
CO		PURPOSES)	-
CO	IX(12)	PLANT LIFE OPTION	-
CO		<0 LIFE IN YEARS ESTIMATED PRECISELY (USE THE	-
CO		HISTORY TO THE TIME ESTIMATED, REGARDLESS	-
CO		OF ITS POINT IN THE CYCLE.)	-

(CONT)

SPECIFICATIONS FOR RODINS RECORD IN INTERPACE FILE CONTROL

```

C-----
C1      CONTROL ROD POSITIONING INSTRUCTIONS
C
C1      RODINS, (IX(I),I=1,100),(IX(I),I=1,100)
C
C1      101=MULT + 100
C
C1      RODINS      ROD POSITIONING MODULE DATA IDENTIFIER (6HRODINS).
C
C1      NOTE - THE INTERPACE FILES 'CONTROL' 'RODSET' 'NDISRP' 'ZNATCH'
C1      AND 'GEODST' ARE REQUIRED.
C
C1      XX(1)      REFERENCE HISTORY TIME (CYCLE TIME), DAYS, BETWEEN
C1      FEELINGS DURING WHICH A SUCCESSION OF CONTROL ROD
C1      POSITIONINGS ARE TO BE DONE (SEE IX(10)=0 BELOW) -
C1      USED FOR THE FIRST NSRPS SET (IX(8)=1).
C
C1      XX(2)      REFERENCE HISTORY TIME TO BE USED FOR ALL BUT THE
C1      FIRST NSRPS SET (IX(8).GT.1) - DEFAULTED TO XX(1)
C1      IF 0.
C
C1      IX(3)      EDIT OPTIONS.
C1      0- NO SPECIAL EDITS.
C1      1- ROD-FOLLOWER ZONE DENSITIES AFTER POSITIONING.
C1      2- PLUS SOME INFORMATION ABOUT ROD POSITIONING.
C1      3- PLUS MORE INFORMATION ABOUT ROD POSITIONING.
C1      4- PLUS CONTENTS OF THE COMMON DATA BLOCK.
C1      5- PLUS THE CONTENTS OF FILES 'NDISRP', 'ZNATCH',
C1      AND THIS RECORD 'RODINS' OF FILE 'CONTROL'.
C
C1      IX(8)      THE SET NUMBER OF THE ROD POSITIONING SPECIFICATIONS
C1      (OUT OF NSRPS SETS ON FILE 'RODSET') THAT IS TO BE
C1      USED THIS ACCESS. DEFAULTED TO 1 IF 0. (APPLICABLE
C1      FOR IX(10) =0, OR =L BELOW).
C
C1      IX(9)      ANOTHER SET NUMBER OF THE ROD POSITIONING
C1      SPECIFICATIONS THAT IS TO BE USED THIS ACCESS
C1      (IF.GT.0) AFTER USING THE IX(8) SET.
C
C1      IX(10)     OPTIONS ON ROD POSITIONING.
C1      -4- RECOVER ALL ROD AND FOLLOWER CONCENTRATIONS
C1      FROM THE NEXT-TO-LATEST VERSION OF THE ZONE
C1      DENSITY FILE 'ZNATCH' (SEE IX(11) AND IX(12)
C1      BELOW). IF NEXT-TO-LATEST VERSION DOES NOT
C1      EXIST, USE LATEST VERSION.
C1      -3- RECOVER ALL ROD AND FOLLOWER CONCENTRATIONS
C1      FROM THE LATEST VERSION OF FILE 'ZNATCH'.
C1      -2- INSERT RODS FULLY AS SPECIFIED BY OPTION NSZ
C1      IN THE FILE 'RODSET'.
C1      -1- WITHDRAW RODS FULLY AS SPECIFIED BY OPTION NSZ
C1      IN THE FILE 'RODSET'.

```

(CONT)

0- AUTOMATED PROCEDURE.
IF THE TIME $IX(1).GT.0$ ----- THE REFERENCE TIME INTO THE CYCLE (TR) IS OBTAINED FROM THE DENSITY FILE 'ZNATON'. THEN THE FRACTION OF EXPOSURE TIME IS $P=TR/IX(1)$. THE NEAREST $PEN(L)$ (ON 'RODSET' FILE) TO P IS FOUND, AND THE CORRESPONDING L IS THEN THE POINT IN THE HISTORY FOR ROD POSITIONING. I.E., THE SPECIFICATIONS $NZL(J,L)$ (ON 'RODSET' FILE) ARE USED TO POSITION THE RODS. NOTE THAT WITH THIS OPTION, IT IS POSSIBLE THAT SOME POINTS IN THE HISTORY MAY BE SKIPPED.
IF THE TIME $IX(1).EQ.0$ ----- ON THE FIRST ACCESS OF RODMOD, THE CONTROL RODS ARE POSITIONED AS SPECIFIED AT POINT 1 IN THE HISTORY ($NZL(J,L=1)$). THEN ON EACH SUBSEQUENT ACCESS FOR WHICH THE NUMBER $IX(10)=0$, THE POINT IN THE HISTORY L IS INCREMENTED BY 1. IF L EXCEEDS THE NUMBER OF POINTS GIVEN (NCDY ON 'RODSET') THE LAST POINT $L=NCDY$ IS REUSED. THIS OPTION ASSURES THAT THE RODS ARE POSITIONED AS SPECIFIED FOR ALL POINTS IN THE HISTORY, IN ORDER, WITH NO POINTS SKIPPED. IF THE CYCLE NUMBER FROM THE FILE 'ZNATON' IS GREATER THAN THE CYCLE NUMBER IN THE PREVIOUS RODMOD ACCESS, L IS RESET TO 1.
L- POSITION RODS AS SPECIFIED (AT THIS POINT L IN THE HISTORY) BY THE DATA ($NZL(J,L)$) IN THE FILE 'RODSET'.
TION TO INSERT SHUT-DOWN (SAFETY) RODS.
0- NO.
1- AFTER ANY OPTION $IX(10).NE.0$ (ABOVE) HAS BEEN APPLIED, INSERT SHUT-DOWN RODS USING SPECIAL DATA PRESENT IN THE FILE 'RODSET'. IF OPTION $IX(10)=0$, ONLY SHUT-DOWN RODS ARE INSERTED AND NO OTHER POSITIONING IS DONE. WHEN THIS OPTION IS SPECIFIED, AFTER ANY POSITIONING IS DONE ($IX(10).NE.0$) AND BEFORE INSERTION OF SHUT-DOWN RODS, A NEW VERSION OF THE ZONE DENSITY FILE 'ZNATON' IS WRITTEN. THIS IS DONE SO THAT RECOVERY OF THE CONCENTRATIONS PRIOR TO INSERTION OF THE SHUT-DOWN RODS MAY BE DONE ON THE NEXT OR ANY SUBSEQUENT ACCESS (SEE $IX(10)=-4$, OR -3 ABOVE).
NORMALLY IT IS NECESSARY TO SOLVE A NEUTRONICS PROBLEM BEFORE AND AFTER SUCH INSERTION WITHOUT OTHER ACTION (AS EXPOSURE) IN BETWEEN TO PRODUCE TWO VALUES OF THE MULTIPLICATION FACTOR GIVING ΔK FOR THE INSERTION.
2- SAME AS 1 BUT THE NEW VERSION OF 'ZNATON' IS WRITTEN BEFORE ANY POSITIONING ($IX(10).NE.0$) IS DONE.

TT-72

CD	IX(12)	OPTION ON SAVING THE ZONE DENSITY INTERFACE FILE	-
CD		'YNATDN', ONLY IF IX(11)=0.	-
CD		-1- NO.	-
CD		0- IF NO FILE EXISTS, CREATE IT WITH DENSITIES -	-
CD		A) AFTER FULL ROD INSERTION (IX(10)=-2)	-
CD		IF SPECIFIED, OR	-
CD		B) RECOVERED FROM LATEST 'YNATDN' FILE.	-
CD		IF A FILE EXISTS, NONE IS WRITTEN.	-
CD		1- WRITE IT AFTER FULL ROD INSERTION (IX(10)=-2).	-
CD		2- WRITE IT AFTER ANY ROD POSITIONING	-
CD		SPECIFICATION.	-
C			-
CD	IX(13)	OPTION ON DELETING THE LATEST VERSION OF THE ZONE	-
CD		DENSITY FILE 'YNATDN' AFTER APPLYING SPECIFICATIONS,	-
CD		PROVIDED IT WAS NOT CREATED THIS ACCESS.	-
CD		0- NO.	-
CD		1- DELETE THE LATEST VERSION OF 'YNATDN' BUT	-
CD		ONLY IF MORE THAN 1 VERSION EXISTS.	-
C			-
CD	IX(14)	BLACK ABSORBER OPTION FOR ROD ZONES.	-
CD		0- NO.	-
CD		1- YES (GENERALLY REQUIRED FOR THERMAL REACTORS	-
CD		WITH RODS REPRESENTED EXPLICITLY).	-
CD		NORMALLY THE LATEST VERSION OF 'GEOST' IS	-
CD		READ TO OBTAIN THE BLACK ABSORBER ZONES AND	-
CD		A NEW VERSION IS WRITTEN IF ONLY ONE EXISTS,	-
CD		OTHERWISE THE LATEST VERSION IS RE-WRITTEN.	-
CD		IF IX(10)=-4, THE NEXT-TO-LATEST VERSION OF	-
CD		'GEOST' IS READ TO OBTAIN THE BLACK ABSORBER	-
CD		ZONES.	-
CD		WHEN CONTROL ROD INTERCHANGES ARE APPLIED,	-
CD		BLACK ABSORBER CONDITIONS ARE MOVED WITH THE	-
CD		INTERCHANGES. SOME ROD ZONES MAY NOT BE BLACK	-
CD		AND NEVER BECOME BLACK IF ONLY THE ROD	-
CD		INTERCHANGE SPECIFICATIONS ARE USED (NO	-
CD		INSERTION SPECIFICATIONS). WHEN INSERTION	-
CD		SPECIFICATIONS ARE APPLIED, ALL ZONES	-
CD		CONTAINING CONTROL ROD ARE ASSIGNED THE BLACK	-
CD		ABSORBER CONDITION, LIMITING APPLICATION TO	-
CD		ONLY FULLY EXPLICIT CONTROL ROD	-
CD		REPRESENTATION.	-
C			-
C			-

(CONT)

SPECIFICATIONS FOR RETINS RECORD IN INTERFACE FILE CONTROL

REACTION RATE MODULE INSTRUCTIONS

REFERENCE 11/01/77 ORNL-5062/R1
MODIFIED 09/17/79

RETINS, (IX(I), I=1,100), (IX(I), I=1,100)

101*MULT * 100

RETINS REACTION RATE MODULE DATA IDENTIFIER (6HRETINS)

NOTE- UNDEFINED DATA ARE RESERVED FOR FUTURE USE.

NOTE- THE VALUE OF ZERO IS A DEFAULT MEANING THAT THE OPTION TO PERFORM THE TASK IS NOT EXERCISED. CONSIDERABLE DATA HANDLING MAY BE INVOLVED AND MUCH PAPER PRINTED, SO CARE SHOULD BE TAKEN TO OBTAIN ONLY THOSE RESULTS NEEDED.

NOTE- QUITE GENERALLY THE FILES -MOXSRT- AND -ZMATON- ARE NEEDED AND USUALLY -GROUPIS-

XX(1) DESIRED POWER LEVEL IF NON-ZERO (USUALLY NEW)

XX(2) RESERVED

XX(3) WEIGHTING FACTOR DISCUSSED BELOW

XX(4) WEIGHTING FACTOR DISCUSSED BELOW

XX(5-24) RESERVED

XX(25) REFERENCE TEMPERATURE (DEGREES C) OF THE NEXT-TO-LATEST VERSION 'GROUPIS' CROSS SECTION INTERFACE FILE

XX(26) REFERENCE TEMPERATURE (DEGREES C) OF THE LATEST VERSION 'GROUPIS' CROSS SECTION INTERFACE FILE

XX(27) CORRELATION PARAMETER FOR THE ARCTANGENT DEPENDENCE OF CROSS SECTIONS ON ZONE TEMPERATURES (LINEAR CORRELATION IF 0.0)

XX(28-30) RESERVED

XX(31-100) RESERVED - SEE XX(41)

IX(1) RESERVED

IX(2) CONDENSED EDIT OPTION
0- YES
1- NO

(CONT)

CD IX(3) OPTION TO EDIT PROGRAMMER INFORMATION FOR DEBUGGING -
 C
 CD IX(4) RESERVED -
 C
 CD IX(5) OPTION TO ACCOUNT FOR THE DEPENDENCE OF THE
 CD CROSS SECTIONS ON THE LOCAL TEMPERATURE, REQUIRES -
 CD TWO 'GROUPS' FILES, A 'ZNTENP' FILE, AND REFERENCE -
 CD TEMPERATURES (SEE IX(25), IX(26), AND IX(27)) -
 CD 0- NO -
 CD 1- YES -
 C
 CD IX(6) OPTION TO COMPUTE AND EDIT REACTION RATES,
 CD INVENTORIES, AND POWER PRODUCTION -
 CC NOTE- INDEPENDENT OF THE OPTIONS WHICH FOLLOW, SUMMARY TABLES
 CC ARE ALWAYS EDITED ON THIS OPTION -
 C
 CD IX(7) RESERVED -
 C
 CD IX(8) RESERVED -
 C
 CD IX(9) OPTION TO EDIT BY ZONE AND SUBZONE FOR EACH UNIQUE
 CD NUCLIDE NAME -
 CD 1 - YES (WILL BE DONE ONLY IF THERE ARE
 CD SUBZONES)
 CC NOTE- IN THIS EDIT, ZONE RESULTS EXCLUDE SUBZONE CONTRIBUTIONS -
 C
 CD IX(10) OPTION TO EDIT BY ZONE FOR EACH UNIQUE NUCLIDE NAME -
 CD NOTE - ZONES WILL INCLUDE SUBZONE CONTRIBUTIONS -
 C
 CD IX(11) OPTION TO EDIT BY ZONE CLASS FOR EACH UNIQUE
 CD NUCLIDE NAME -
 C
 CD IX(12) RESERVED -
 C
 CD IX(13) RESERVED -
 C
 CD IX(14) OPTION TO WEIGHT SUMMARY REACTION RATES BY NUCLIDE
 CD ENERGY GENERATION -
 CD 1- FISSION ENERGY ONLY -
 CD 2- FISSION PLUS CAPTURE ENERGY -
 C
 CD IX(15) OPTION FOR ADDITIONAL RESULTS WITH ALTERNATIVE
 CD WEIGHTINGS (SUMMARY TABLES ONLY) -
 CD 1- BY NET NEUTRON PRODUCTION (GENERATION MINUS
 CD ABSORPTION)
 CD 2- BY CAPTURE RATE IF FERTILE AND ABSORPTION
 CD RATE IF FISSILE -
 C
 CD IX(16) REPEAT THE CALCULATIONS OF REACTION RATES INDICATED
 CD ABOVE (IX(5).GT.0) USING FLUX, ADJOINT WEIGHTING-
 CD REQUIRING FILE -PERTUB-
 C

(CONT)

THE FOLLOWING ARE PRELIMINARY, NOT IMPLEMENTED	
IX(17-20)	RESERVED
IX(21)	OPTION TO EDIT REACTION RATE MAPS USING FILE -RTPLUX- .GT.0- SPECIFIES A PLANE OF A 3-D PROBLEM OR A ROW OF A 2-D PROBLEM -1- THE PLANE OR ROW IS TO CONTAIN THE LOCATION OF MAXIMUM POWER DENSITY
IX(22)	MAP PRINCIPAL REACTION RATES FOR FISSILE NUCLIDES 1- ABSORPTION 2- ABSORPTION AND PRODUCTION 3- CAPTURE AND FISSION 4- CAPTURE, FISSION AND PRODUCTION PER ABSORPTION
IX(23)	MAP PRINCIPAL REACTION RATES FOR FERTILE NUCLIDES 1- CAPTURE 2- ABSORPTION ONLY
IX(24)	MAP ABSORPTION RATES FOR NUCLIDES OF THIS CLASS
IX(25)	RESERVED
IX(26)	REPEAT THE MAPPING WITH WEIGHTING ON ADJOINT FLUX USING FILE -PERTUB
IX(27-30)	RESERVED
IX(31)	OPTION TO EDIT REACTIVITY COEFFICIENTS FOR UNIT CHANGES IN FISSILE NUCLIDE CONCENTRATIONS
IX(32)	OPTION TO EDIT REACTIVITY COEFFICIENTS FOR UNIT CHANGES IN FERTILE NUCLIDE CONCENTRATIONS
IX(33)	OPTION TO EDIT REACTIVITY COEFFICIENTS FOR UNIT CHANGES IN NUCLIDE CONCENTRATIONS OF THIS CLASS
IX(34-36)	RESERVED
IX(37)	OPTION TO PRODUCE DELAYED NEUTRON PROPERTIES WITH FLUX, ADJOINT WEIGHTING USING FILE -PERTUB- AND -DLATIS-
IX(38-40)	RESERVED

(CONT)

CD	IX(41)	OPTION TO COLLAPSE CROSS SECTIONS IN ENERGY, FILE
CD		-ISOTXS-TO-ISOTXS- USING THE ENERGY STRUCTURE
CD		GIVEN AS GROUP LOWER BOUNDS DESCENDING EV, DATA
CD		IN ARRAY IX STARTING AT IX(31) TERMINATING WITH
CD		A ZERO ENTRY FOR THE LAST GROUP
CD		1- PRODUCE MACROSCOPIC CROSS SECTIONS FOR PSEUDO-
CD		DENSITY UNITY FOR EACH ZONE, FLUX WEIGHTED
CD		2- PRODUCE ONE-TO-ONE NUCLIDE DATA ONLY FOR THE
CD		ONES HAVING NON-ZERO CONCENTRATIONS WITH FLUX-
CD		WEIGHTING USING FILE -RTFLUX-
CD		3- SAME AS 2 EXCEPT FLUX, ADJOINT WEIGHTING
CD		REQUIRING FILE -PERTUR-
C		
CD	IX(42-50)	RESERVED
C		
CD	IX(51)	OPTION TO GENERATE A DISTRIBUTED NEUTRON SOURCE FILE-
CD		-FIXSRC- USING FLUX FROM -RTFLUX-
CD		1- TOTAL PRODUCTIONS FROM FISSION MULTIPLIED BY
CD		IX(3) NORMALIZED TO A TOTAL OF IX(3)*IX(4)
CD		IF IX(4) IS NON ZERO, IX(3) SET TO UNITY IF 0-
CD		2- TOTAL DELAYED NEUTRON SOURCE USING FILE
CD		-DLAYXS-
CD		3- ASYMPTOTIC DELAYED NEUTRON SOURCE USING THE
CD		FAMILY OF LONGEST HALF LIFE (ASSUMES DISTINCT-
CD		ONE APPLIES) USING FILE -DLAYXS-
C		
CD	IX(52)	OPTION TO GENERATE A ZONE-GROUP DISTRIBUTED SOURCE
CD		FILE -FIXSRC- USING ZONE AVERAGE FLUX FILE
CD		-RTFLUX- (SEE OPTIONS IMMEDIATELY ABOVE)
C		
CD	IX(53-100)	RESERVED
C		
C		

(CONT)

SPECIFICATIONS FOR ICPINS RECORD IN INTERFACE FILE CONTROL

```

C-----
C2      CROSS SECTION PROCESSOR INSTRUCTIONS
C
C2      THIS DATA REQUIRED BY THE CROSS SECTION PROCESSOR
C
C2      ICPINS, (IX(I),I=1,100), (IX(I),I=1,100)
C
C2      101=MULT * 100
C
C2      ICPINS      CROSS SECTION PROCESSOR DATA IDENTIFIER (6HICPINS)
C
C2      IX(1-100)    RESERVED
C
C2      IX(1-2)      RESERVED
C
C2      IX(3)        OPTION ON INPUT CROSS SECTION FILE PROCESSING
C                      0 - NO PROCESSING REQUIRED
C                      1 - GENERATE NEW NUCLIDE-ORDERED FILE FROM
C                          THE FILE OR FILES HAVING FORMAT IX(5)
C                          (REQUIRE INTERFACE FILE CIPHER FOR
C                          ADDITIONAL INFORMATION)
C
C2      IX(4)        OPTION TO GENERATE A GROUP-ORDERED FILE FROM
C                      A NUCLIDE-ORDERED FILE
C                      0 - NO
C                      1 - YES
C
C2      IX(5)        FORMAT OF INPUT CROSS SECTIONS FOR IX(3) EQ 1
C                      0 - NUCLIDE-ORDERED FILE
C                      1 - CITATION CROSS SECTION SETS
C                      2 - MERGE TWO NUCLIDE-ORDERED FILES
C
C2      IX(6)        OPTION ON PRINCIPAL CROSS SECTION DATA
C                      FOR IX(4) EQ 1
C                      0 - RETAIN ALL DATA
C                      1 - REDEFINE (N,GAMMA) CROSS SECTION TO BE
C                          THE CAPTURE CROSS SECTION = (N,GAMMA) *
C                          (N,ALPHA) + (N,P) + (N,D) + (N,T) - (N,2N)
C
C2      IX(7)        OPTION ON SCATTERING DATA FOR IX(4) EQ 1
C                      0 - RETAIN ALL DATA
C                      1 - RETAIN THE TOTAL SCATTERING ONLY
C
C2      IX(8)        OPTION ON SCATTERING ORDER FOR IX(4) EQ 1
C                      0 - RETAIN ALL DATA
C                      N - RETAIN ORDERS UP TO (N-1) ONLY
C

```

(CONT)

CD	IX(9)	OPTION ON SCATTERING RECORD BLOCKING FACTOR	-
CD		FOR IX(4) EQ 1	-
CD		0 - NSBLK = 1	-
CD		N - NSBLK = N, IF (NISO/N)*N EQ NISO,	-
CD		OTHERWISE NSBLK = NISO	-
CD		WHERE NISO IS THE NUMBER OF NUCLIDES	-
C			-
CD	IX(10)	OPTION TO COMPUTE THE TOTAL SCATTERING MATRIX	-
CD		FROM THE COMPONENTS FOR IX(4) EQ 1	-
CD		TOTAL = ELASTIC + INELASTIC + N2N	-
CD		(THIS MUST BE DONE IF THE GROUPS FILE IS TO BE	-
CD		USED BY VENTURE AND THERE IS NO TOTAL	-
CD		SCATTERING DATA PRESENT)	-
CD		0 - NO	-
CD		1 - YES	-
CD		2 - YES AND MULTIPLY N2N SOURCE BY 2.0	-
C			-
CD	IX(11)	OPTION TO CREATE ISOTOPE MIXTURES AFTER PROCESSING	-
CD		SPECIFIED BY IX(3) AND IX(5), IF ANY	-
CD		0 - NO	-
CD		1 - YES (REQUIRES INTERFACE FILE CYSPEE FOR	-
CD		ADDITIONAL INFORMATION)	-
C			-
CD	IX(12-22)	RESERVED	-
C			-
CD	IX(23)	OPTION TO EDIT LATEST NUCLIDE-ORDERED FILE	-
CD		0 - NO	-
CD		1 - YES	-
C			-
CD	IX(24)	OPTION TO EDIT GROUP-ORDERED FILE	-
CD		0 - NO	-
CD		1 - YES	-
C			-
CD	IX(25-100)	RESERVED	-
C			-

(CONT)

```

C*****
C          PREPARED 10/18/73
CF      CXSPRR
C
CE      DATA FOR CROSS SECTION PROCESSOR
C
CN      SEE INTERFACE FILE CONTRL. RECORD XCPINS. FOR REFERENCES
CN      TO ARRAY IX
C
C*****

```

```

C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                PRESENT IF
CS
CS      FILE IDENTIFICATION          ALWAYS
CS      1D FILE CONTROL              ALWAYS
CS      2D CITATION SET NUMBERS      NOP(1).GT.0
CS      3D NEUTRON ENERGY SPECTRUM  NOP(3).GT.0
CS      4D TRANSPORT MULTIPLIERS      Hx  NOP(4).GT.0
CS
CS      ***** (REPEAT FROM 1 TO NOP(5))
CS      *      5D ISOTOPE DATA      NOP(5).GT.0
CS      *****
CS
CS      ***** (REPEAT FROM 1 TO NOP(6))
CS      *      6D ISOTOPE NAMES IN MIXTURE  NOP(6).GT.0
CS      *      7D ISOTOPE DENSITIES IN MIXTURE  NOP(6).GT.0
CS      *****
CS
CS      ***** (REPEAT FROM 1 TO NOP(6))
CS      *      8D MIXTURE DATA
CS      *****
C
C-----

```

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I),I=1,2),IVERS
C
CW      3*MULT + 1 = NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - CXSPRR - (A6)
CD      HUSE           HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER Hx
CD                        1 - A6 WORD IS SINGLE WORD
CD                        2 - A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR      1D      FILE CONTROL
C
CL      (NOP(I),I=1,24)
C
CW      24
C
CD      NOP(1)        NUMBER OF CITATION CROSS SECTION SETS TO PROCESS
CD                        (IF NOP(1).EQ.0 AND IX(3).EQ.1 AND IX(5).EQ.1,
CD                        SET ONE WILL BE PROCESSED)
CD      NOP(2)        SCATTERING BLOCKING FACTOR FOR NUCLIDE-ORDERED
CD                        FILE CREATED FROM CITATION CROSS SECTIONS
CD                        0 - NSBLOK = 1
CD                        N - NSBLOK = N, IF (NGROUP/N)*N.EQ.NGROUP
CD                        OTHERWISE NSBLOK = 1
CD      NOP(3)        OPTION TO INPUT A NEUTRON ENERGY SPECTRUM
CD                        0 - NO
CD                        1 - YES
CD      NOP(4)        OPTION TO CREATE PSEUDO DIRECTION DEPENDENT
CD                        TRANSPORT DATA
CD                        0 - NO
CD                        1 - YES
CD      NOP(5)        OPTION TO INPUT OVERRIDE DATA FOR ISOTOPES
CD                        0 - NO
CD                        1 - YES
CD      NOP(6)        NUMBER OF MIXTURES (REQUIRED IF IX(11).EQ.1)
CD      NOP(7)        MAXIMUM NUMBER OF ISOTOPES IN ANY MIXTURE
CD                        (REQUIRED IF IX(11).EQ.1)
CD      NOP(8-9)      RESERVED

```

```

CD      NOP(10)          OPTION ON USE OF OVERRIDE DATA FOR ISOTOPES
CD                               WHEN NOP(5).GT.0 (APPLICABLE ONLY WHEN
CD                               IX(3).EQ.1 AND IX(5).EQ.0)
CD                               0 - DATA CORRESPONDS WITH THE ORDER OF
CD                               ISOTOPES IN THE FILE
CD                               '1 - DATA IDENTIFIES ISOTOPES TO BE SELECTED
CD                               BY UNIQUE ISOTOPE LABEL
CD
CD      NOP(11-23)       RESERVED
CD      NOP(24)          OPTION TO EDIT DURING CREATION CROSS SECTION
CD                               PROCESSING
CD                               0 - NO
CD                               1 - YES
C
C-----
C-----
CR      2D      CITATION CROSS SECTION SET NUMBERS
C
CC                               PRESENT IF NOP(1).GT.0
C
CL      (ISET(I).I=1.NOP1)
C
CW      NOP1 = NOP(1)
C
CD      ISET            SET NUMBERS IN ASCENDING ORDER OF APPEARANCE
CD                               IN LIBRARY
C
C-----
C-----
CR      3D      NEUTRON ENERGY SPECTRUM
C
CC                               PRESENT IF NOP(3).GT.0
C
CL      (WGT(I).I=1.NOP3)
C
CW      NOP3 = NOP(3)
C
CD      WGT            SPECTRUM FOR WEIGHTING IN MIXTURE CALCULATION
C
C-----

```

```

C-----
CR      4D      MULTIPLIERS FOR TRANSPORT CROSS SECTION
C
CC      PRESENT IF NOP(4).GT.0
C
CL      (TRMOD(1).I-1.3)
C
CW      3
C
CD      TRMOD      MULTIPLIER FOR EACH COORDINATE DIRECTION
CD      STRPD(1)=TRMOD*STRPL(1) FOR EACH ENERGY
C
C-----

```

```

C-----
CR      5D      ISOTOPE DATA
C
CC      PRESENT IF NOP(5).GT.0
CC      THERE MUST BE NOP(5) RECORDS
C
CN      WHEN NOP(10).EQ.0.
CN      THIS DATA MAY BE USED WHEN IX(3).EQ.1 TO CONTROL THE
CN      PROCESSING OF THE INPUT CROSS SECTIONS. THE ORDER
CN      OF THESE RECORDS MUST BE ONE-TO-ONE WITH THE ORDER
CN      OF THE ISOTOPES IN THE INPUT CROSS SECTIONS. FOR EACH
CN      ISOTOPE READ FROM THE INPUT CROSS SECTIONS. ONE RECORD
CN      IS READ FROM THIS DATA.
CN
CN      A) IF HISONM.EQ.6HDELETE. THE DATA FOR THIS ISOTOPE
CN      IS NOT WRITTEN ON THE NEW NUCLIDE ORDERED FILE.
CN      B) IF HISONM.NE.DELETE. THE DATA FOR THIS ISOTOPE
CN      WILL BE COPIED TO THE NEW NUCLIDE ORDERED FILE
CN      (NON-BLANK OR NON-ZERO DATA WILL REPLACE THE
CN      DATA ON THE NEW FILE)
CN      C) IF AFTER READING NOP(5) RECORDS. THERE ARE ISOTOPES
CN      REMAINING IN THE INPUT CROSS SECTIONS. THOSE
CN      REMAINING WILL BE DELETED FROM THE NEW FILE.
CN
CN
CN      WHEN NOP(10).EQ.1.
CN      THIS DATA MAY BE USED WHEN IX(3).EQ.1 AND IX(5).EQ.0 TO
CN      CONTROL THE CONTENT OF THE NEW ISOTXS FILE. THE ORDER
CN      OF THE RECORDS IS NOT SPECIFIED SINCE THE UNIQUE LABEL
CN      (HISONM) IS USED TO IDENTIFY ISOTOPES TO BE COPIED TO
CN      THE NEW FILE. NON-BLANK OR NON-ZERO VALUES FOR THE
CN      REST OF THE DATA WILL BE PUT ON THE NEW FILE.
CN      THE UNIQUE LABEL CANNOT BE CHANGED WHEN USING THIS OPTION.
CN

```

```

CN
CN      IF THIS DATA IS NOT PRESENT. ALL ISOTOPES ON THE INPUT
CN      CROSS SECTIONS WILL BE COPIED TO THE NEW FILE
C
CL      HISONM,HABSID,HMAT,AMASS,EFISS,ECAPT,KBR,(IOP(I),I=1,3)
C
CW      3*MULT + 7
C
CD      HISONM      HOLLERITH ISOTOPE LABEL (UNIQUE)      (A6)
CD      HABSID      HOLLERITH ISOTOPE LABEL (ABSOLUTE)    (A6)
CD      HMAT        HOLLERITH ISOTOPE LABEL (REFERENCE)    (A6)
CD      AMASS       GRAM ATOMIC WEIGHT
CD      EFISS       TOTAL THERMAL ENERGY YIELD/FISSION   (W.SEC/FISS)
CD      ECAPT       TOTAL THERMAL ENERGY YIELD PER CAPTURE (N.GAMMA)
CD                  (W.SEC/CAPT)
CD      KBR         ISOTOPE CLASSIFICATION
CD      IOP         RESERVED
C-----
C-----
CR      6D          ISOTOPE NAMES IN MIXTURES
C
CC              PRESENT IF NOP(6).GT.0
CC              THIS RECORD AND THE RECORD FOLLOWING APPEAR IN PAIRS
CC              THERE MUST BE NOP(6) PAIRS
C
CL      (HISONX(I),I=1,NOP7)
C
CW      MULT*NOP7=MULT*NOP(7)
C
CD      HISONX      UNIQUE NAME OF ISOTOPE TO BE INCLUDED IN MIXTURE
CD                  (BLANK NAMES ARE IGNORED)
C
CN              ANY ISOTOPE INCLUDED IN A MIXTURE WILL BE DELETED FROM THE
CN              NEW FILE
C-----
C-----
CR      7D          ISOTOPE DENSITIES IN MIXTURE
C
CC              PRESENT IF NOP(6).GT.0
C
CL      (RDENS(I),I=1,NOP7)
C
CW      NOP7=NOP(7)
C
CD      RDENS       DENS.      ISOTOPE TO BE INCLUDED IN MIXTURE
C-----

```

```

C .....
CR      8D          MIXTURE DATA
C
CC          PRESENT IF NOP(6).GT.0
CC          THERE MUST BE NOP(6) RECORDS
C
CL      HISONM.HABSID.HMAT.AMASS.EFISS.ECAPT.KBR.(IOP(I),I=1,3)
C
CD      HISONM          HOLLERITH MIXTURE LABEL (UNIQUE) (A6)
CD      HABSID          HOLLERITH MIXTURE LABEL (ABSOLUTE) (A6)
CD      HMAT            HOLLERITH MIXTURE LABEL (REFERENCE)
CD      AMASS           GRAM ATOMIC WEIGHT
CD      EFISS           TOTAL THERMAL ENERGY YIELD/FISSION (W.SEC/FISS)
CD      ECAPT           TOTAL THERMAL ENERGY YIELD/CAPTURE (N.GAMMA)
CD                      (W.SEC/CAPT)
CD      KBR             MIXTURE CLASSIFICATION
CD      IOP             RESERVED
C
CN          NON-BLANK DATA SHOULD BE SUPPLIED FOR LABELS
CN          AND NON-ZERO DATA FOR KBR
CN          AMASS, EFISS, AND ECAPT ARE CALCULATED FOR MIXTURE, BUT
CN Hx      MAY BE REPLACED BY NON-ZERO ENTRIES
C
C .....

C*****
C
CEOF      CXSPRR
C
C*****

```

```

C*****
C          REVISED 11/30/76
CF      DLAYXS-IV
CE      MICROSCOPIC GROUP DELAYED NEUTRON PRECURSOR DATA
C
CN      THIS FILE PROVIDES PRECURSOR YIELDS,
CN      EMISSION SPECTRA, AND DECAY CONSTANTS
CN      ORDERED BY ISOTOPE. ISOTOPES ARE IDENTIFIED
CN      BY ABSOLUTE ISOTOPE LABELS FOR RELATION TO
CN      ISOTOPES IN EITHER FILE ISOTXS OR GRUPXS.
CN      FORMATS GIVEN ARE FOR FILE EXCHANGE PURPOSES
CN      ONLY.
C
C*****

```

```

C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      -----
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS      FILE DATA, DECAY CONSTANTS, AND
CS      EMISSION SPECTRA                          ALWAYS
CS      ***** (REPEAT TO NISOD)
CS      *      DELAYED NEUTRON PRECURSOR
CS      *      YIELD DATA                        ALWAYS
CS      *****
C
C-----

```

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME.(HUSE(I),I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CB      FORMAT(11H ON DLAYXS ,1H*,2A6,1H*,16)
C
CD      HNAME      HOLLERITH FILE NAME - DLAYXS -
CD      HUSE(I)    HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS      FILE VERSION NUMBER
CD      MULT        DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```



```

C-----
CR      FILE CONTROL   (1D RECORD)
C
CL      NGROUP,NISOD,NFAM,IDUM
C
CW      4=NUMBER OF WORDS
C
CB      FORMAT(4H 1D .4I6)
C
CD      NGROUP          NUMBER OF NEUTRON ENERGY GROUPS IN SET
CD      NISOD           NUMBER OF ISOTOPES IN DELAYED NEUTRON SET
CD      NFAM            NUMBER OF DELAYED NEUTRON FAMILIES IN SET
CD      IDUM            DUMY TO MAKE UP FOUR WORD RECORD.
C
C-----

C-----
CR      FILE DATA, DECAY CONSTANTS, AND EMISSION SPECTRA
C
C
C
CL      (HABSID(IO,I=1,NISOD).(FLAM(N),N=1,NFAM).((CHID(J,N),J=1,NGROUP),
CL      N=1,NFAM).(EMAX(J),J=1,NGROUP).EMIN.(NKFAM(I),I=1,NISOD).
CL      (LOCA(I),I=1,NISOD)
C
CW      (2+MULT)*NISOD+(NGROUP+1)*(NFAM+1)=NUMBER OF WORDS
C
CB      FORMAT(4H 2D .9(1X.A6))/          HABSID
CB      1 (10(1X.A6)))
CB      FORMAT (6E12.5)                    FLAM,CHID,EMAX,EMIN
CB      FORMAT(12I6)                       NKFAM,LOCA
C
CD      HABSID(I)      HOLLERITH ABSOLUTE ISOTOPE LABEL FOR ISOTOPE I (A6)
CD      FLAM(N)        DELAYED NEUTRON PRECURSOR DECAY CONSTANT
CD                      FOR FAMILY N
CD      CHID(J,N)      FRACTION OF DELAYED NEUTRONS EMITTED INTO NEUTRON
CD                      ENERGY GROUP J FROM PRECURSIR FAMILY N
CD      EMAX(J)        MAXIMUM ENERGY BOUND OF GROUP J (EV)
CD      EMIN           MAXIMUM ENERGY BOUND OF SET (EV)
CD      NKFAM(I)       NUMBER OF FAMILIES TO WHICH FISSION IN ISOTOPE I
CD                      CONTRIBUTES DELAYED NEUTRON PRECURSORS
CD      LOCA(I)        NUMBER OF RECORDS TO BE SKIPPED TO READ DATA FOR
CD                      ISOTOPE (IO. LOCA(1)=0
C
C-----

```

```

C-----
CR      DELAYED NEUTRON PRECURSOR YIELD DATA  (3D RECORD)
C
CL      (SNUDEL(J,K),J=1,NGROUP),K=1,NKFAMI), (NUMFAM(K),K=1,NKFAMI)
C
CC      NKFAMI=NKFAM(I)
C
CW      (NGROUP+1)*NKFAMI=NUMBER OF WORDS
C
CB      FORMAT(4H 3D , 5E12.5/(6E12.5)) SNUDEL
CB      FORMAT(12I6)                      NUMFAM
C
CD      SNUDEL(J,K)  NUMBER OF DELAYED NEUTRON PRECURSORS PRODUCED IN
CD                   FAMILY NUMBER NUMFAM(K) PER FISSION IN
CD                   GROUP J
CD      NUMFAM(K)    FAMILY NUMBER OF THE K-TH YIELD VECTOR IN
CD                   ARRAY SNUDEL(J,K)
C
C-----

```

CEOF

```

C*****
C                                     DATE 08/19/88
C
CF      EDITIT
CE      CODE DEPENDENT FILE OF INFORMATION SPECIFIC TO THE
CE      ONEDANT EDIT MODULE
C
C*****
C
CN      THIS FILE CONTAINS THE CARD INPUT INFORMATION
CN      FROM BLOCK VI
C
C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====                                =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      RAW CONTROLS AND DIMENSIONS                ALWAYS
CS      DEFAULTED CONTROLS AND DIMENSIONS          ALWAYS
CS      FINE GROUPS PER BROAD GROUP                ALWAYS
CS      ZONE NUMBERS                               NZNS.NE.0
CS      POINT NUMBERS                             NIPE.NE.0
CS      CROSS SECTION POSITIONS                    NPOS.NE.0
CS      ISOTOPE NUMBERS TO EDIT                     NISO.NE.0
CS      MATERIAL NUMBERS TO EDIT                    MACRO.NE.0
CS      CONSTITUENT NUMBERS TO EDIT                 NCONS.NE.0
CS      RESPONSE FUNCTION NAMES                     IDOSE.NE.0
CS      ***** (REPEAT FOR ALL RESPONSE FUNCTIONS)
CS      *      RESPONSE FUNCTION ENERGY VECTOR     IDOSE.NE.0
CS      *      RESPONSE FUNCTION SPATIAL VECTOR     IDOSE.NE.0
CS      *****
CS      CROSS SECTION SUMMING ARRAY -               IXSUM.NE.0
CS      RESPONSE FUNCTION SUMMING ARRAY             IRSUM.NE.0
CS      FINE MESH DENSITY FACTORS                   IDEN.NE.0
C
C-----
C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME      HOLLERITH FILE NAME - EDITIT - (A6)
CD      HUSE(I)    HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS      FILE VERSION NUMBER
CD      MULT       DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C-----

```

```

CR          RAW CONTROLS AND DIMENSIONS
C
CL      IEDOPT,PTED, NIPE, IKND, ZNED, NZNS,IXSUM,IRSUM, NPOS, NISO,
CL 1 NCONS, MACRO, IDOSE, IGRPED, LNG, NBG, IDEN, NGROUP, AJED,
CL 2 ITED, JTED, KTED, IRZFLX, IRZMFX
C
CW      25=NUMBER OF WORDS
C
CD 1 IEDOPT NOT USED
CD 2 PTED 0/1 - NO/YES DO POINT EDIT
CD 3 NIPE NUMBER OF POINTS TO EDIT
CD 4 BYVOLP 0/1 - NO/YES MULTIPLY REACTION RATES BY MESH VOLUME
CD 5 ZNED 0/1 - NO/YES DO ZONE EDIT
CD 6 NZNS NUMBER OF EDIT ZONES
CD 7 IXSUM LENGTH OF CROSS SECTION SUMMING TABLE
CD 8 IRSUM LENGTH OF RESPONSE FUNCTION SUMMING TABLE
CD 9 NPOS NUMBER OF CROSS SECTION POSITIONS TO EDIT
CD 10 NISO NUMBER OF ISOTOPES TO EDIT
CD
CD 11 NCONS NUMBER OF ISOTOPES TO EDIT AS CONSTITUENTS
CD 12 MACRO NUMBER OF MATERIALS TO EDIT
CD 13 IDOSE NUMBER OF RESPONSE FUNCTIONS TO EDIT
CD 14 IGRPED 0/1/2/3 - ENERGY GROUP PRINT OPTIONS
CD 15 LNG NUMBER OF THE LAST NEUTRON GROUP
CD 16 NBG NUMBER OF BROAD ENERGY GROUPS
CD 17 IDEN 0/1 - NO/YES THERE ARE FINE MESH DENSITY FACTORS
CD 18 NGROUP NUMBER OF FINE ENERGY GROUPS
CD 19 AJED 0/1 - NO/YES THIS IS AN ADJOINT EDIT
CD 20 ITED NUMBER OF FINE RADIAL MESH
CD 21 JTED NUMBER OF FINE AXIAL MESH
CD 22 KTED NUMBER OF FINE Z DIRECTION MESH
CD 23 IRZFLX WRITE CCCC RZFLUX FILE
CD 24 IRZMFX WRITE ZONE MOMENTS FILE
CD 25 NOT USED

```

CR DEFAULTED CONTROLS AND DIMENSIONS

```

C
CN      THIS RECORD IS THE SAME FORMAT AS THE RAW CONTROLS AND
CN      DIMENSION RECORD ABOVE, BUT IT CONTAINS THE DEFAULTED
CN      VALUES FOR EACH VARIABLE

```

CR FINE GROUPS PER GROAD GROUP

```

C
CL      (ICOLL(G),G=1,NBG)

```

```

C
CW      NBG=NUMBER OF WORDS

```

```

C
CD      ICOLL(G) NUMBER OF FINE GROUPS IN BROAD GROUP G

```

```

C
C-----
C
C-----
CR      ZONE NUMBERS
C
CC      PRESENT IF NZNS.GT.0
C
CL      (EDZONE(I),I=1,IT)
C
CW      IT=NUMBER OF WORDS
C
CD      EDZONE(I) EDIT ZONE NUMBER FOR THE I-TH FINE MESH
C
C-----
C
C-----
CR      POINTS TO EDIT
C
CC      PRESENT IF NIPE.GT.0
C
CL      (POINTS(I),I=1,NIPE)
C
CW      NIPE=NUMBER OF WORDS
C
CD      POINTS(I) NUMBER OF THE I-TH POINT TO EDIT
C
C-----
C
C-----
CR      CROSS SECTION POSITIONS TO EDIT
C
CC      PRESENT IF NPOS.GT.0
C
CL      (EDXS(I),I=1,NPOS)
C
CW      NPOS=NUMBER OF WORDS
C
CD      EDXS(I) POSITION NUMBER TO EDIT(IN NUMERIC FORM)
C
C-----
C
C-----
CR      ISOTOPE NUMBERS TO EDIT
C
CC      PRESENT IF NISO.GT.0
C
CL      (EDISOS(I),I=1,NISO)
C
CW      NISO=NUMBER OF WORDS
C
CD      EDISOS(I) ISOTOPE NUMBER TO EDIT(IN NUMERIC FORM)
C
C-----

```

```

C
C-----
CR      MATERIAL NUMBERS TO EDIT
C
CC      PRESENT IF MACRO.GT.0
C
CL      (EDMATS(I), I=1, MACRO)
C
CW      MACRO=NUMBER OF WORDS
C
CD      EDMATS(I) MATERIAL NUMBER TO EDIT(IN NUMERIC FORM)
C
C-----
C
C-----
CR      CONSTITUENT NUMBERS TO EDIT
C
CC      PRESENT IF NCONS.GT.0
C
CL      (EDCONS(I), I=1, NCONS)
C
CW      NCONS=NUMBER OF WORDS
C
CD      EDCONS(I) CONSTITUENT NUMBER TO EDIT(IN NUMERIC FORM)
C
C-----
C
C-----
CR      RESPONSE FUNCTION NAMES
C
CC      PRESENT IF IDOSE.GT.0
C
CL      (RSFNAM(I), I=1, IDOSE)
C
CW      IDOSE=NUMBER OF WORDS
C
CD      RSFNAM(I) HOLLERITH NAME FOR THE I-TH RESPONSE FUNCTION
C
C-----
C
C-----
CR      RESPONSE FUNCTION ENERGY VECTOR
C
CC      PRESENT IF IDOSE.GT.0
C
CL      (RSFE(I), I=1, NGROUP)
C
CW      NGROUP=NUMBER OF WORDS
C
CD      RSFE(I) RESPONSE FOR GROUP I
C
C-----
C
C-----

```

```

CR      RESPONSE FUNCTION SPATIAL VECTOR
C
CC      PRESENT IF IDOSE.GT.0
C
CL      (RSFX(I),I=1,IT)
C
CW      IT=NUMBER OF WORDS
C
CD      RSFX(I)  RESPONSE FUNCTION FOR FINE MESH I
C
C-----
C
C-----
CR      CROSS SECTION SUMMING ARRAY
C
CC      PRESENT IF IXSUM.GT.0
C
CL      (MICSUM(I),I=1,IXSUM)
C
CW      IXSUM=NUMBER OF WORDS
C
CD      MICSUM   INPUT SUMMING ARRAY IN NUMERIC FORM
C
C-----
C
C-----
CR      RESPONSE FUNCTION SUMMING ARRAY
C
CC      PRESENT IF IRSUM.GT.0
C
CL      (IRSUMS(I),I=1,IRSUM)
C
CW      IRSUM=NUMBER OF WORDS
C
CD      IRSUMS   INPUT SUMMING ARRAY IN NUMERIC FORM
C
C-----
C
C-----
CR      FINE MESH DENSITY ARRAY
C
CC      PRESENT IF IDEN.GT.0
C
CL      (XDF(I),I=1,IT)
C
CW      IT=NUMBER OF WORDS
C
CD      XDF(I) DENSITY FACTOR FOR THE I-TH FINE MESH
C
C-----
CEOF

```

SPECIFICATIONS FOR INTERFACE FILE EXPORT

```

C.....
C      REFERENCE 02/01/79 ORNL-5180
C      MODIFIED 05/01/79
C
C      EXPORT
C
C      RECORD OF EXPOSURE HISTORY
C
C      ORIGINAL SPECS MODIFIED TO INCLUDE SUBZONE FLUENCE
C.....

```

```

C-----
C      FILE STRUCTURE
C
C      RECORD TYPE                                PRESENT IF
C      -----
C      FILE IDENTIFICATION                        ALWAYS
C      10 FILE REFERENCE INFORMATION              ALWAYS
C      ***** (REPEAT FROM 1 TO INIST)
C      * 20 GENERAL INFORMATION                  ALWAYS
C      * 30 TOTAL FLUENCE                        NFLOT = 1
C      * 40 FLUENCE RANGE 1                      NFLOT1 = 1
C      * 50 FLUENCE RANGE 2                      NFLOT2 = 1
C      * 60 POSITIONS                            NR1 = 1
C      * 90 EXPOSURE                             NR2 = 1
C      * 100 ENERGY                             NR3 = 1
C      * 110 UNDEFINED                           NR4 = 1
C      *****
C
C-----

```

```

C-----
C      FILE IDENTIFICATION
C
C      HNAME, (HUSE(I), I=1, 2), IVERS
C
C      J=HOLT + 1
C
C      HNAME      FILE NAME (A6) 'EXPORT'
C      HUSE      USER IDENTIFICATION (A6)
C      IVERS      FILE VERSION NUMBER
C
C      HOLT      1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----

```

(CONT)


```

C-----
C 1D FILE REFERENCE INFORMATION
C
C EXPH1, EXPH2, EXPH3, EPLU1, EPLU2, IMIST, IZONE, ISZ,
C NPLU1, NPLU2, IXP12, IXP13, NRR1, NRR2, NRR3,
C NRR4, IXP18, IXP19, IXP20
C
C 2D
C
C EXPH1 END OF EXPOSURE TIME (DAYS) FROM LAST SET OF DATA
C EXPH2 RESERVED
C EXPH3 RESERVED
C EPLU1 CUTOFF ENERGY (EV) FOR FIRST FLUENCE
C EPLU2 CUTOFF ENERGY (EV) FOR SECOND FLUENCE
C IMIST NUMBER OF SETS OF DATA
C IZONE NUMBER OF ZONES
C ISZ NUMBER OF SUBZONES
C NPLU1 OPTION FOR TOTAL FLUENCE
C 0 - NOT PRESENT
C 1 - PRESENT
C NPLU2 OPTION FOR FLUENCE IN FIRST RANGE
C 0 - NOT PRESENT
C 1 - PRESENT
C
C WHEN NPLU1 = 1, EPLU1 MUST BE GREATER THAN 0 AND
C LIE IN THE ENERGY RANGE SPECIFIED IN THE
C CROSS SECTION DATA
C
C NPLU2 OPTION FOR FLUENCE IN SECOND RANGE
C 0 - NOT PRESENT
C 1 - PRESENT
C
C WHEN NPLU2 = 1, EPLU2 MUST BE GREATER THAN 0 AND
C LIE IN THE ENERGY RANGE SPECIFIED IN THE
C CROSS SECTION DATA
C
C IXP12 RESERVED
C IXP13 RESERVED
C NRR1 OPTION FOR FISSIONS
C 0 - NOT PRESENT
C 1 - PRESENT
C NRR2 OPTION FOR EXPOSURE
C 0 - NOT PRESENT
C 1 - PRESENT
C NRR3 OPTION FOR ENERGY
C 0 - NOT PRESENT
C 1 - PRESENT
C NRR4 OPTION FOR UNDEFINED
C 0 - NOT PRESENT
C 1 - PRESENT
C IXP18 RESERVED
C IXP19 RESERVED
C IXP20 INDICATOR NORMALLY = 0, BUT IS SET = 1 IF
C A DISCONTINUITY EXISTS IN EXPOSURE TIMES
C-----

```

(CONT)

CR	2D	GENERAL INFORMATION
CL	(EPHT(I), I=1,40)	
CM	80	
CD	EPHT(1)	END OF EXPOSURE TIME (DAYS)
CD	EPHT(2)	START OF EXPOSURE TIME (DAYS)
CD	EPHT(3)	FRACTION OF CORE TREATED IN PROBLEM
CD	EPHT(4)	CONVERSION FACTOR, RATIO OF THERMAL ENERGY TO FISSION + CAPTURE ENERGY (FROM CROSS SECTIONS)
CD	EPHT(5-10)	RESERVED
CD	EPHT(11)	CURRENT TOTAL SYSTEM FISSIONS (FISSIONS)
CM		DEFINED WHEN HRR1 = 1
CD	EPHT(12)	CURRENT TOTAL SYSTEM EXPOSURE (MEGAWATT(THERMAL)-DAYS/KG)
CM		DEFINED WHEN HRR2 = 1
CD	EPHT(13)	CURRENT TOTAL SYSTEM ENERGY (MEGAWATT(THERMAL)-DAYS)
CM		DEFINED WHEN HRR3 = 1
CD	EPHT(14)	CURRENT TOTAL SYSTEM UNDEFINED
CM		DEFINED WHEN HRR4 = 1
CD	EPHT(15-20)	RESERVED
CD	EPHT(21)	CUMULATIVE TOTAL SYSTEM FISSIONS (FISSIONS)
CM		DEFINED WHEN HRR1 = 1
CD	EPHT(22)	CUMULATIVE TOTAL SYSTEM EXPOSURE (MEGAWATT(THERMAL)-DAYS/KG)
CM		DEFINED WHEN HRR2 = 1
CD	EPHT(23)	CUMULATIVE TOTAL SYSTEM ENERGY (MEGAWATT(THERMAL)-DAYS)
CM		DEFINED WHEN HRR3 = 1
CD	EPHT(24)	CUMULATIVE TOTAL SYSTEM UNDEFINED
CM		DEFINED WHEN HRR4 = 1
CD	EPHT(25-40)	RESERVED

(CONT)

```

C-----
C 30 TOTAL FLUENCE
C
C  PRESENT IF NPLUT = 1
C
C  (PLUT (NM) ,NM=1,ITEST)
C
C  ITEST = IZONE + ISZ
C
C  PLUT      CUMULATIVE TOTAL FLUENCE BY ZONE AND SUBZONE
C            (NEUTRONS/CN**2)
C-----

```

```

C-----
C 40 FLUENCE TO FIRST CUTOFF ENERGY ZFLU1
C
C  PRESENT IF NPLU1 = 1
C
C  (ZFLU1 (NM) ,NM=1,ITEST)
C
C  ITEST = IZONE + ISZ
C
C  ZFLU1     CUMULATIVE FLUENCE IN FIRST RANGE BY ZONE
C            AND SUBZONE (NEUTRONS/CN**2)
C-----

```

```

C-----
C 50 FLUENCE TO SECOND CUTOFF ENERGY ZFLU2
C
C  PRESENT IF NPLU2 = 1
C
C  (ZFLU2 (NM) ,NM=1,ITEST)
C
C  ITEST = IZONE + ISZ
C
C  ZFLU2     CUMULATIVE FLUENCE IN SECOND RANGE BY ZONE
C            AND SUBZONE (NEUTRONS/CN**2)
C-----

```

(CONT)

C-----
 CR 60 RESERVED
 C-----

C-----
 CR 70 RESERVED
 C-----

C-----
 CR 80 FISSIONS
 C-----
 CC PRESENT IF NRR1 = 1
 C-----
 CL (RR1(NN), NN=1, ITZSZ)
 C-----
 CV ITZSZ = IZONE + ISZ
 C-----
 CD RR1 CUMULATIVE FISSIONS BY ZONE AND SUBZONE
 CD (FISSIONS/CM**3)
 C-----

C-----
 CR 90 EXPOSURE
 C-----
 CC PRESENT IF NRR2 = 1
 C-----
 CL (RR2(NN), NN=1, ITZSZ)
 C-----
 CV ITZSZ = IZONE + ISZ
 C-----
 CD RR2 CUMULATIVE EXPOSURE BY ZONE AND SUBZONE
 CD (MEGAWATT(THERMAL)-DAYS/KG)
 C-----

C-----
 CR 100 ENERGY
 C-----
 CC PRESENT IF NRR3 = 1
 C-----
 CL (RR3(NN), NN=1, ITZSZ)
 C-----
 CV ITZSZ = IZONE + ISZ
 C-----
 CD RR3 CUMULATIVE ENERGY BY ZONE AND SUBZONE
 CD (MEGAWATT(THERMAL)-DAYS/CM**3)
 C-----

(CONT)

```

C-----
C 110  UNDEFINED
C
C      PRESENT IF NRR4 = 1
C
C      (NRR4(1), NRR4(2), ITZSZ)
C
C      ITZSZ = IZOMF + ISZ
C
C  NRR4  UNDEFINED
C-----
C.....
C
C  EXPORT
C.....

```

```

C*****
C          REFERENCE 02/01/79  ORNL-5180
C
C          EXPOSE
C
C          DATA FOR EXPOSURE CALCULATIONS
C
C          THE BASIC DATA REQUIRED FOR SOLVING THE CHAIN
C          EQUATIONS IDENTIFIES NUCLIDES, FISSIONING
C          NUCLIDES, FISSION PRODUCTS, AND GIVES DECAY, YIELD, ENERGY,
C          AND COUPLING DATA
C
C*****

C-----
C          FILE IDENTIFICATION
C
C          HNAME.(HUSE(1), I=1,2) IVERS
C
C          3*MULT + 1
C
C          HNAME          FILE NAME (A6) 'EXPOSE'
C          HUSE           USER IDENTIFICATION (A6)
C          IVERS          FILE VERSION NUMBER
C
C          MULT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINE
C
C-----

```

```

C-----
CR      1D      FILE REFERENCE INFORMATION
C
CL      NEXP1,NISOE,NAMOPT,NYER,NGER,NFSLR,NFPR,NDCYR,NEXP9,NEXP10,
CL      NEXP11,NMATXE,LSEXCH,LBENCH,NEXP15,NOEDCY,NOEFIS,NOECAP,
CL      NEXP19,NEXP20
C
CW              20
C
CN      UNDEFINED DATA IS RESERVED FOR FUTURE USE
C
CD      NEXP1          DOCUMENTING FILE REFERENCE NUMBER
CD      NISOE          REFERENCE NUMBER OF NUCLIDES
CD                        MUST BE NON-ZERO
CD      NAMOPT         OPTION ON NUCLIDE NAMES
CD                        IF 0 - THEY ARE ABSOLUTE NAMES
CD                        IF 1 - THEY ARE USER LABELS
C
CN                        IN FILE ISOTXS, ABSOLUTE LABELS ARE
CN                        HABSID, WHILE USER LABELS ARE HISONM
C
CN                        UNIQUE NAMES ARE REQUIRED HERE
CD      NYER           NUMBER OF ENERGY RANGES FOR YIELD DATA
CD                        (GENERALLY NON-ZERO)
CD      NGER           NUMBER OF ENERGY RANGES FOR GAMMA RAYS
CD      NFSLR          NUMBER OF IDENTIFIED FISSION NUCLIDE WHICH YIELD
CD                        FISSION PRODUCTS
CD      NFPR           NUMBER FISSION PRODUCTS HAVING YIELD
CD      NDCYR          NUMBER OF NUCLIDES WHICH DECAY
CD      NEXP9          RESERVED
CD      NEXP10         RESERVED
CD      NEXP11         RESERVED
CD      NMATXE         OPTION IF .GT.0 INDICATING THE NUMBER
CD                        OF MATRIX EXPONENTIAL DATA ENTRIES
CD      LSEXCH         OPTION IF .GT.0 INDICATING THE NUMBER
CD                        OF ENTRIES IN THE SUPPLEMENTING TABLE OF EXPLICIT
CD                        CHAIN DATA (USED WITH MATRIX DATA)
CD      LBENCH         OPTION IF .GT.0 INDICATING THE NUMBER
CD                        OF ENTRIES IN THE BASIC TABLE OF EXPLICIT
CD                        CHAIN DATA (USED ONLY ALONE)
CD      NEXP15         RESERVED
CD      NOEDCY         OPTION INDICATING DATA FOR THE DECAY PROCESS
CD                        IS INCLUDED FOR GAMMA RAYS AND BETA PARTICLES
CD      NOEFIS         OPTION INDICATING DATA FOR THE FISSION PROCESS
CD                        IS INCLUDED FOR GAMMA RAYS AND BETA PARTICLES
CD      NOECAP         OPTION INDICATING DATA FOR THE CAPTURE PROCESS
CD                        IS INCLUDED FOR GAMMA RAYS AND BETA PARTICLES
CD      NEXP19         RESERVED
CD      NEXP20         RESERVED
C
C-----

```

```

C-----
CR      2D      TITLE AND NUCLIDE NAMES
C
CC      ALWAYS PRESENT
C
CN      HEREAFTER ALL REFERENCES TO NUCLIDES IN THIS FILE ARE
CN      BY THE ORDER NUMBER IN THIS TABLE OF NAMES
C
CL      (HTL(J),J=1,12),(HNUC(I),I=1,NISOE)
C
CW      MULT*(12+NISOE)
C
CD      HTL      DOCUMENTING TITLE (12A6)
CD      HNUC(I)   NAME OF NUCLIDE ORDERED I (A6) SEE NAMOPT OPTION
C
CN      ALL NUCLIDES TO BE TREATED (EXPOSURE CALCULATED) MUST BE
CN      NAMED IN THIS LIST (NORMALLY EXCLUDE COOLANT, STRUCTURE).
C
CN      WHEN THE AVERAGE GENERATION RATE METHOD IS USED, THESE
CN      SPECIFICATIONS ARE PROCESSED IN THE ORDER IN THIS LIST, SO-
CN      THEY SHOULD BE ORDERED ALONG CHAINS, DOMINATING ROUTES
CN      FIRST (EXAMPLE, U....PU, I...XE, XE..CS), FISSION
CN      PRODUCTS LAST.
C
CN      NUCLIDES SPECIFIED HERE BUT ABSENT IN THE SYSTEM OF COURSE-
CN      ARE NOT TREATED - IMPACTS ARE DOCUMENTED ELSEWHERE
C
C-----

```



```

C-----
CR      3D      REFERENCE DATA
C
CC      PRESENT IF NYER+NGER+NFSLR+NFPR+NDCYR.GT.0
C
CL      (YER(N).N=1.NYER).(GER(J).J=1.NGER).(IFSLR(K).K=1.NFSLR).
CL      (IFPR(L).L=1.NFPR).(IDCYR(I).I=1.NDCYR)
C
CW      NYER+NGER+NFSLR+NFPR+NDCYR
C
CD      YER      LOWER ENERGY OF RANGE OF INCIDENT
CD      NEUTRON ENERGY (EV). DECREASING ORDER
CD      (LAST NUMBER TYPICALLY ZERO. SINGLE VALUE USUALLY 0)
CD      GER      MEAN OR EFFECTIVE ENERGY OF EACH RANGE
CD      OF DATA FOR GAMMA RAY ENERGY DATA. ORDERED BY
CD      DECREASING ENERGY. FOR DOCUMENTATION (EV PER PART.)
CD      IFSLR     REFERENCE ORDER NUMBER OF IDENTIFIED
CD      NUCLIDES WHICH FISSION
CD      IFPR      REFERENCE ORDER NUMBER OF FISSION PRODUCTS
CD      (NUCLIDES FOR WHICH FISSION YIELD DATA IS GIVEN)
CD      IDCYR     REFERENCE ORDER NUMBER OF NUCLIDES WHICH DECAY
C
C-----

```

```

C-----
CR      4D      DECAY DATA
C
CC      PRESENT IF NDCYR.GT.0
C
CL      (ALMDA(I).I=1.NDCYR)
C
CW      NDCYR
C
CD      ALMDA     TOTAL DECAY CONSTANT FOR NUCLIDE ORDERED I IN THE
CD      REFERENCE SET IDCYR(I) (SEC-1)
C
C-----

```

```

C-----
CR      5D      FISSION PRODUCT YIELD DATA
C
CC              PRESENT IF NFSLR*NFPR*NYER.GT.0
C
CL      (((YFFP(K,L,N).K=1.NFSLR).L=1.NFPR).N=1.NYER)
C
CW              NFSLR*NFPR*NYER
C
CD      YFFP(K,L,N)  YIELD OF FISSION PRODUCT IFPR(L) FROM
CD                      FISSION OF NUCLIDE IFSLR(K) DUE TO FISSIONING
CD                      NEUTRON IN ENERGY RANGE N
CD                      (ATOMS PER SECOND PER FISSION PER SECOND)
C-----

```

```

C-----
CR      6D      CHAIN DATA FOR MATRIX EXPONENTIAL OR AVERAGE GENERATION RATE
C
CC              PRESENT IF NMATXE.GT.0
C
CL      ((MATXE(J,I).J=1.3).I=1.NMATXE)
C
CW              3*NMATXE
C
CD      MATXE(1,I)   SOURCE NUCLIDE
CD      MATXE(2,I)   PRODUCT NUCLIDE
CD      MATXE(3,I)   SPECIFIES THE TRANSMUTATION PROCESS.
CD                      0- NOT ALLOWED
CD                      1- DECAY
CD                      2- (N.GAMMA). USUAL CAPTURE UP THE CHAIN
CD                      3- (N.ALPHA)
CD                      4- (N.P)
CD                      5- (N.2N). DOWN THE CHAIN
CD                      6- (N.D)
CD                      7- (N.T)
CD                      8- FISSION (DO NOT SPECIFY FOR A FISSION PRODUCT
CD                          FOR WHICH YIELD DATA IS GIVEN. THIS IS TREATED
CD                          DIRECTLY)
CD                      9- TOTAL CAPTURE. TOTAL ABSORPTION LESS FISSION
C

```

CN PARTIAL RATES OF PRODUCT GENERATION CAN BE CONSIDERED. THE
 CN PARTS PER MILLION IS EXPRESSED AS AN INTEGER (500000 IS THE
 CN FRACTION 0.5). ROUNDED TO THE NEAREST TEN (LAST DIGIT ZERO).
 CN ADDED TO THE NUMBER FROM THE ABOVE TABLE TO SPECIFY THE
 CN TRANSMUTATION PROCESS. FOR EXAMPLE. IF THE PARTIAL CAPTURE
 CN ROUTES OF PM-147 TO PM-148 AND TO PM-148M ARE BOTH TO BE
 CN CONSIDERED. THE FIRST AT FRACTION 0.53. THE APPROPRIATE
 CN ENTRIES TO INDICATE (N.GAMMA) REACTION PRODUCTS ARE 530002
 CN FOR THE PRODUCT PM-148 AND 470002 FOR PM148M. LESS THAN
 CN A TOTAL FRACTION OF UNITY MAY BE SPECIFIED. BUT TAKE CARE.
 C
 C-----

C-----
 CR 7D CHAIN DATA. SUPPLEMENTAL EXPLICIT
 C
 CC PRESENT IF LSEXCH.GT.0
 C
 CL (NXSCH(I).I=1.LSEXCH)
 C
 CW LSEXCH
 C
 CD NSXCH ENTRY IN THE SUPPLEMENTAL EXPLICIT CHAIN
 CD DATA TABLE (SEE DESCRIPTION BELOW)
 C
 C-----

C-----
 CR 8D CHAIN DATA. COMPLETE BASIC DATA TO APPLY EXPLICIT SOLUTION
 C
 CC PRESENT IF LBEXCH.GT.0
 C
 CL (NBXCH(I).I=1.LBEXCH)
 C
 CW LBEXCH
 C
 CD NBXCH ENTRY IN THE BASIC EXPLICIT CHAIN DATA TABLE.
 CD OUTLINED HERE
 C
 CN THE FIRST ENTRY IS THE FIRST NUCLIDE IN THE FIRST
 CN CHAIN. THE NEXT ENTRY IS THE TRANSMUTATION PROCESS FOR
 CN GENERATION OF THE PRODUCT (SEE THE VALUES OF MATXE(3,I) IN
 CN THE TABLE ABOVE). THE NEXT ENTRY IN THE LIST IS THE FIRST
 CN PRODUCT IN THE FIRST CHAIN. THUS FOR N NUCLIDES IN A CHAIN.
 CN THERE ARE 2*(N-1)+1 ENTRIES FOR THE CHAIN. THEN THERE IS A
 CN ZERO ENTRY. DATA FOLLOWS FOR THE NEXT CHAIN. A FINAL
 CN EXTRA ZERO IS PLACED AT THE END AFTER THE LAST CHAIN WHICH
 CN FLAGS THE END OF CHAINS. TWO ZERO ENTRIES AT THE END.
 CN ENTER ACTINIDE CHAINS FIRST.

C
 CN REPEAT OF A NUCLIDE REFERENCE IN A CHAIN IS NOT ALLOWED.
 CN GIVEN A FIRST APPEARANCE IN ONE CHAIN. SUBSEQUENT ENTRIES OF
 CN A NUCLIDE REFERENCE INDICATE OTHER GENERATION ROUTES WHICH
 CN CONTRIBUTE INDEPENDENTLY. CARE MUST BE TAKEN TO SUPPLY
 CN REASONABLE SPECIFICATIONS. ONLY THE ACTUAL CHAINS SHOWN
 CN WILL BE TREATED. SO FULL SPECIFICATIONS REQUIRING REPEATS
 CN ARE REQUIRED. AND ONLY LIMITED BRANCHING IS ALLOWED.
 CN THE CONTRIBUTIONS ALONG A ROUTE THROUGH THE CHAINS ARE ONLY
 CN THOSE FOR THE NUCLIDES ACTUALLY GIVEN FOR THAT CHAIN.
 CN AS AN EXAMPLE. THE TABLE
 CN 1 -02 2 +02 3 +01 4 +02 5 0 1 +02 2 +01 6 +02 -4 +02 -5 0 0
 CN ALLOWS TWO ROUTES TO BE TREATED FOR GENERATION OF NUCLIDES
 CN REFERENCED 4 AND 5. THE -4 AND -5 IN THE SECOND CHAIN
 CN INDICATE THESE CONTRIBUTIONS ARE ADDITIONAL.

C
 CN ONLY NUCLIDES GIVEN IN THESE CHAINS WILL BE TREATED
 CN (EXPOSED)
 C

C-----

C-----

CR 9D DECAY ENERGY RELEASE DATA
 C
 CC PRESENT IF NOEDCY.GT.0.AND.NDCYR*NGER+2).GT.0
 C
 CL ((EGAMA(I,J).I=1.NDCIR).J=1.NGER).(EBETA(I).I=1.NDCYR).
 CL (EDCY(I).I=1.NDCYR)
 C
 CW NDCYR*(NGER+2)
 C
 CD EGAMA(I,J) THE AMOUNT OF ENERGY RELEASED PER ATOMIC
 CD DECAY OF PARENT NUCLIDE IDCYR(I)
 CD AS GAMMA RAYS IN ENERGY RANGE J (EV)
 CD EBETA(I) THE AMOUNT OF ENERGY RELEASED PER
 CD ATOMIC DECAY OF PARENT NUCLIDE IDCYR(I)
 CD AS BETA PARTICLES (EV)
 CD EDCY(I) THE AMOUNT OF ENERGY RELEASED PER ATOMIC DECAY OF
 CD PARENT NUCLIDE IDCYR(I). (EV)
 C

C-----

```

C-----
CR    10D    SECONDARY ENERGY FROM FISSION
C
CC          PRESENT IF NOEFIS.GT.0.AND.NFSLR*(NGER+1).GT.0
C
CL    ((EFGAM(I,J),I=1,NFSLR),J=1,NGER).(EFBAT(I),I=1,NFSLR)
C
CW          NFSLR*(NGER+1)
C
CD    EFGAM(I,J)    THE AMOUNT OF ENERGY RELEASED PER
CD                   ATOMIC FISSION OF NUCLIDE IFSLR(I)
CD                   AS GAMMA RAYS IN ENERGY RANGE J (EV)
CD    EFBAT(I)      THE AMOUNT OF ENERGY RELEASED PER ATOMIC
CD                   FISSION OF NUCLIDE IFSLR(I) AS BETA PARTICLES (EV)
C
C-----

```

```

C-----
CR    11D    ENERGY RELEASE PER CAPTURE
C
CC          PRESENT IF NOECAP.GT.0.AND.NISOE*(NGER+1).GT.0
C
CL    ((ECGAM(I,J),I=1,NISOE),J=1,NGER).(ECBAT(I),I=1,NISOE)
C
CW          NISOE*(NGER+1)
CD    ECGAM(I,J)    THE AMOUNT OF ENERGY RELEASED PER
CD                   ATOMIC CAPTURE OF NUCLIDE I AS GAMMA RAYS
CD                   IN ENERGY RANGE J (EV)
CD    ECBAT(I)      THE AMOUNT OF ENERGY RELEASED PER ATOMIC
CD                   CAPTURE OF NUCLIDE I AS BETA PARTICLES (EV)
C
C-----

```

```

C*****
C
CEOF
C
C*****

```

```

C*****
C              REVISED  04/01/80
C
CF          FISSOR
C
CE          FISSION SOURCE BY INTERVAL AND DISTRIBUTION FUNCTION
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME.(HUSE(I),I=1,2),IVERS
C
CW          3*MULT + 1
C
CD          HNAME          HOLLERITH FILE NAME - FISSOR - (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION  (A6)
CD          IVERS          FILE VERSION NUMBER
C
CN          MULT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----

C-----
CR          FILE REFERENCE IDENTIFICATION
C
CL          TIME, POWER, KEFF, IM, JM, KM, NCT, NG, NZ
C
CW          9
CD          TIME           REFERENCE REAL TIME, DAYS
CD          POWER          POWER LEVEL FOR ACTUAL NEUTRONICS PROBLEM.
CD                      WATTS THERMAL
CD          KEFF           MULTIPLICATION FACTOR
CD          IM             NUMBER OF FIRST DIMENSION FINE INTERVALS
CD          JM             NUMBER OF SECOND DIMENSION FINE INTERVALS
C
CN          FOR SPECIAL TRIANGULAR GEOMETRIES, IM IS THE NUMBER OF *-
CN          TRIANGLES ON EACH PLANE AND JM IS NOT DEFINED (SET TO 1)*-
C
CD          KM             NUMBER OF THIRD DIMENSION FINE INTERVALS
CD          NCY            REFERENCE COUNT (CYCLE NUMBER)
CD          NG             NUMBER OF ENERGY GROUPS
CD          NZ             NUMBER OF ZONES
C
C-----

```

```

C-----
CR          FISSION SOURCE DISTRIBUTION FUNCTION  (2D RECORD)
C
CL      ((CHIM(M,K),M=1,NZ),K=1,MG)
C
CW      NG*NZ
C
CD      CHIM(M,K)   SOURCE OF NEUTRONS IN GROUP K.  ZONE M
C
C-----

```

```

C-----
CR          FISSION SOURCE VALUES  (3D RECORD)
C
CL      ((PFS(I,J),I=1,IM),J=1,JM)-----NOTE STRUCTURE BELOW-----
C
CW      IM*JM
C
CS      DO 1 K=1,KM
CS      1 READ(N)  *LIST AS ABOVE*
C
CD      PFS(I,J)      FISSION SOURCE BY INTERVAL.  NEUTRONS/SEC/CC
C
C-----

```

```

C*****
C
CEOF      FISSOR
C
C*****

```

```

C*****
C                                     DATE 12/20/85
C
CF          FISSRC
CE          CODE DEPENDENT FISSION SOURCE FOR TWODANT CODE
C
C*****

```

```

C-----
C
C
CN          THIS FILE PROVIDES THE FISSION SOURCE
C
C
C-----

```

```

C-----
C
C
CD          NOTE THAT DOUBLE PRECISION FISSIONS
CD          ARE GIVEN WHEN MULT=2
C
C
C-----

```

```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME, (HUSE(I), I=1,2), IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CD          HNAME          HOLLERITH FILE NAME - FISSRC - (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
CD          MULT           DOUBLE PRECISION PARAMETER
CD                          1- A6 WORD IS SINGLE WORD
CD                          2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          SPECIFICATIONS      (1D RECORD)
C
CL          NDIM,NGROUP,NINTI,NINTJ,NINTK,ITER,EFFK,POWER,NBLOK
C
CW          9 =NUMBER OF WORDS
C
CD          NDIM           SET TO 2
CD          NGROUP         NUMBER OF ENERGY GROUPS

```


CD	NINTI	NUMBER OF FIRST DIMENSION FINE MESH INTERVALS	-
CD	NINTJ	NUMBER OF SECOND DIMENSION FINE MESH INTERVALS	-
CD	NINTK	SET TO 1	-
CD	ITER	OUTER ITERATION NUMBER AT WHICH FISSION WAS	-
CD		WRITTEN	-
CD	EFFK	EFFECTIVE MULTIPLICATION FACTOR	-
CD	POWER	POWER IN WAITS TO WHICH FISSION IS NORMALIZED	-
CD	NBLOK	SET TO 1	-
C			-
C	-----		

C	-----		
CR	FISSION SOURCE	(2D RECORD)	-
C			-
CL	((FISS(I,J),I=1,NINTI),J=1,NINTJ)		-
C			-
CW	NINTI*NINTJ*MULT=NUMBER OF WORDS		-
C			-
CD	FISS(I,J)	FISSION SOURCE WITHOUT VOLUME AT FINE MESH	-
CD		POINT (I,J), I.E., NUSIGF*FLUX	-
C			-
C	-----		
CEOF			

C*****
C REVISED 07/23/75 - REVISED 04/01/80
C

CF FIXSRC-IV
CE DISTRIBUTED AND SURFACE FIXED SOURCES
C

C*****

C-----
CR FILE IDENTIFICATION
C HNAME.(HUSE(I),I=1,2),IVERS
C
CW 1+3*MULT=NUMBER OF WORDS
C
CD HNAME HOLLERITH FILE NAME - FIXSRC - (A6)
CD HUSE(I) HOLLERITH USER IDENTIFICATION (A6)
CD IVERS FILE VERSION NUMBER
CD MULT DOUBLE PRECISION PARAMETER
CD 1- A6 WORD IS SINGLE WORD
CD 2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR SPECIFICATIONS (1D RECORD)
C
CL ITYPE,NDIM,NGROUP,NINTI,NINTJ,NINTK,IDISTS,NDCOMP,NSCOMP,NEDGI,
CL NEDGJ,NEDGK
C
CW 12=NUMBER OF WORDS
C
CD ITYPE TYPE SOURCE. 0=DIFFUSION
CD 1=SN
CD NDIM NUMBER OF DIMENSIONS
CD NGROUP NUMBER OF GROUPS
CD NINTI NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD NINTJ NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD NINTK NUMBER OF THIRD DIMENSION FINE MESH INTERVALS
C
CN FOR MESHPOINT EDGE LOCATIONS, NINTI, NINTJ, AND NINTK ARE *-
CN INTERPRETED AS THE NUMBER OF POINTS (ONE MORE THAN THE *-
CN NUMBER OF INTERVALS). *-
CN FOR SPECIAL TRIANGULAR GEOMETRIES, NINTI IS THE NUMBER OF *-
CN POINTS ON EACH PLANE, AND NINTJ IS SET TO 1. *-
C

```

CD      IDISTS          DISTRIBUTED SOURCE FLAG.
CD                               0= NO DISTRIBUTED SOURCE GIVEN.
CD                               1= DISTRIBUTED SOURCE IS GIVEN BY POINT
CD                               2= DISTRIBUTED SOURCE IS GIVEN BY ZONE
CD                               3= SAME AS 1 BUT AN ADDITIONAL RECORD IS
CD                               PRESENT AT END OF DATA
CD                               4= SAME AS 2 BUT AN ADDITIONAL RECORD IS
CD                               PRESENT AT END OF DATA
CD      NDCOMP          NUMBER OF DISTRIBUTED SOURCE COMPONENTS
CD                               = NUMBER OF ZONES IF IDISTS IS 2 OR 4
CD      NSCOMP          NUMBER OF SURFACE SOURCE COMPONENTS (0)
CD      NEDGI          NUMBER OF FIRST DIMENSION BOUNDARY SOURCES (0)
CD      NEDGJ          NUMBER OF SECOND DIMENSION BOUNDARY SOURCES (0)
CD      NEDGK          NUMBER OF THIRD DIMENSION BOUNDARY SOURCES (0)
C-----

```

```

C-----
CR      ONE DIMENSIONAL DISTRIBUTED FIXED SOURCE (2D RECORD)
C
CC      PRESENT IF NDIM.EQ.1 AND IDISTS IS 1 OR 3
C
CL      ((QDIST(L,I).L=1.NDCOMP).I=1.NINTI)---NOTE STRUCTURE BELOW---
C
CW      NDCOMP*NINTI=NUMBER OF WORDS
C
C      DO 1 J=1.NGROUP
C      1 READ(N) *LIST AS ABOVE*
C
CD      QDIST(L,I)      DISTRIBUTED SOURCE TIMES POINT VOLUME (CC)
CD                        BY COMPONENT, INTERVAL, AND GROUP
C
C-----

```

```

C-----
CR      MULT-DIMENSIONAL DISTRIBUTED FIXED SOURCE (3D RECORD)
C
CC      PRESENT IF NDIM.GE.2 AND IDISTS IS 1 OR 3
C
CL      ((QDIST(I,J).I=1.NINTI).J=1.NINTJ)---NOTE STRUCTURE BELOW---
C
CW      NINTI*NINTJ=NUMBER OF WORDS
C
CS      DO 1 N = 1.NGROUP
CS      DO 1 L = 1.NDCOMP
CS      DO 1 K=1.NINTK
CS      1 READ(N) *LIST AS ABOVE*
C
CD      QDIST(I,J)      AS DEFINED ABOVE.
C
C-----

```

Figure VIII.1 Special Options for FIXSRC Interface File (con't.)

C	-----	
CR	FIRST DIMENSION SURFACE SOURCE POINTERS (4D RECORD)	-
C		-
CC	PRESENT IF NEDGI.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C	-----	
C	-----	
CR	FIRST DIMENSION SURFACE SOURCES (3D RECORD)	-
C		-
CC	PRESENT IF NEDGI.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C	-----	
C	-----	
CR	SECOND DIMENSION SURFACE SOURCE POINTERS (6D RECORD)	-
C		-
CC	PRESENT IF NDIM.GE.2 AND NEDGJ.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C	-----	
C	-----	
CR	SECOND DIMENSION SURFACE SOURCES (7D RECORD)	-
C		-
CC	PRESENT IF NDIM.GE.2 AND NEDGJ.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C	-----	
C	-----	
CR	THIRD DIMENSION SURFACE SOURCE POINTERS (8D RECORD)	-
C		-
CC	PRESENT IF NDIM.EQ.3 AND NEDGK.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C	-----	
C	-----	
CR	THIRD DIMENSION SURFACE SOURCES (9D RECORD)	-
C		-
CC	PRESENT IF NDIM.EQ.3 AND NEDGK.NE.0	-
C		-
CN	NOT ALLOWED IN VENTURE	-
C	-----	

Figure VIII.1 Specifications for FIXSRC Interface File (con't.)

```

C-----
CR          SOURCE BY ZONE AND GROUP (10D RECORD)          *-
C                                                    *-
CC          PRESENT IF IDISTS IS 2 OR 4                    *-
C                                                    *-
CL          ((ZSOR(L,N).L=1.NDCOMP).N=1.NGROUP)           *-
C                                                    *-
CW          NDCOMP*NGROUP=NUMBER OF WORDS                  *-
C                                                    *-
CD          ZSOR(L,N)          SOURCE BY ZONE AND GROUP - NOT MULTIPLIED *-
CD          BY ZONE VOLUME                                     *-
C                                                    *-
C-----

C-----
C          ADDITIONAL RECORD IF IDISTS IS 3 OR 4 (11D RECORD) *-
C                                                    *-
CL          (R(N).N=1.20)                                   *-
C                                                    *-
CW          20=NUMBER OF WORDS                             *-
C                                                    *-
CD          R(1)          KEFFECTIVE                       *-
C                                                    *-
C-----

C*****
C
CEOF          FIXSRC
C
C*****

```

SPECIFICATIONS FOR INTERFACE FILE PPRINT

```

C.....
C          REVISED 10/18/73
C          REVISED  9/14/75 (ORNL)
C          REVISED 11/16/78 (ORNL)
C
C          PPRINT
C
C          CODE-DEPENDENT INPUT DATA FILE FOR PPRINT MODULE
C
C          CONTROLS FILE PRINTING AND PUNCHING.
C          FILES MAY BE PRINTED AND/OR SAVED IN CARD IMAGE FORM
C          SUITABLE FOR INPUT TO THE STANDARD INPUT PROCESSOR.
C          THE CARD IMAGES MAY BE SAVED ON TAPE, DISK, OR CARDS.
C.....

```

```

C-----
C          FILE STRUCTURE
C-----
C          RECORD TYPE          PRESENT IF
C          -----
C          0V      FILE IDENTIFICATION      ALWAYS
C          10      FILE CONTROL              ALWAYS
C          * * * * * (REPEAT FROM 1 TO NSPRCS)
C          * 20      FILE PRINT/PUNCH CONTROL      ALWAYS
C          * 30      RECORD-TYPE I.D. NUMBERS      NPREC.67.0
C          * * * * *
C-----

```

```

C-----
C          FILE IDENTIFICATION
C-----
C          HNAME, (HUSE(I), I=1, 2), IVERS
C
C          3=MULT=1
C
C          HNAME      HOLLERITH FILE NAME - PPRINT - (16)
C          HUSE(1)     HOLLERITH USER IDENTIFICATION (216)
C          IVERS       FILE VERSION NUMBER
C          MULT        DOUBLE PRECISION PARAMETER
C                     1- 16 WORD IS SINGLE WORD
C                     2- 16 WORD IS DOUBLE WORD
C-----

```

(CONT)

```

C-----
CR  10  FILE CONTROL
C
CL  NSPECS,NBCD,NSTOP,NDOH
C
CV  4
C
CD  NSPECS          NUMBER OF STANDARD FILES TO BE PROCESSED
CD                      (MUST BE .LE.20)
CD  NBCD            UNIT NUMBER FOR SAVING FILES IN CARD IMAGE FORM
CD                      DEFAULT IS UNIT 7 AND NO ENDFILE OR REWIND
CD                      IS PERFORMED. ANY OTHER UNIT SPECIFIED WILL
CD                      BE CLOSED OUT WITH ENDFILE AND REWIND.
CD  NSTOP           OPTION TO PLACE THE CHARACTERS 'STOP' AT THE
CD                      END OF THE CARD IMAGES
CD                      0- YES
CD                      1- NO
CD  NDOH            OPTION TO PURGE OR RETAIN THE PRINT FILE
CD                      AFTER EXECUTION OF LAST PRINT/PUNCH
CD                      PROCESSOR
CD                      0- PURGE
CD                      1- RETAIN
C-----

```

```

C-----
CR  20  FILE PRINT/PUNCH CONTROL
C
CL  FILEID,IYER,NOPT,NPREC
C
CV  MULT+3
C
CD  FILEID          HOLLERITH NAME OF FILE TO BE PROCESSED - (A6)
CD  IYER            VERSION OF FILE TO BE PROCESSED (IF IYER=0,
CD                      THE LATEST VERSION WILL BE PROCESSED)
CD  NOPT            PRINT/PUNCH OPTION
CD                      0- PRINT ONLY
CD                      1- PUNCH ONLY
CD                      2- PRINT AND PUNCH
CD  NPREC           SELECTED RECORDS FLAG
CD                      .EQ.0 - PRINT COMPLETE FILE
CD                      .GT.0 - PRINT SELECTED RECORD-TYPES AS
CD                      SPECIFIED IN THE NEXT RECORD
CD                      (MUST BE .LE.10)
C-----

```

(CONT)

```

C-----
CR      3D      RECORD-TYPE I.D. NUMBERS
C
CC      PRESENT IF NPREC.GT.0
C
CL      (ID(I),I=1,NPREC)
C
CW      NPREC
C
CD      ID(I)          IDENTIFICATION NUMBERS OF SELECTED
CD                      RECORD-TYPES TO BE PRINTED
CD                      (MUST BE .LZ.10)
C
C-----

C.....
C
CSTOP      FPRINT
C
C.....

```



```

C*****
C                      REVISED 11/30/76
C
CF                      GEODST - IV
C
CE                      GEOMETRY DESCRIPTION
C
C*****

```

```

C-----
CR          FILE IDENTIFICATION  (0V RECORD)
C
CL  HNAME.(HUSE(I),I=1,2).IVERS
C
CW  1+3*MULT
C
CD  HNAME          HOLLERITH FILE NAME - GEODST - (A6)
CD  HUSE           HOLLERITH USER IDENTIFICATION (A6)
CD  IVERS          FILE VERSION NUMBER
CD  MULT           DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS A SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          FILE SPECIFICATIONS  (1D RECORD)
C
CL  IGOM.NZONE.NREG.NZCL.NCINTI.NCINTJ.NCINTK.NINTI.NINTJ.NINTK.IMB1.
CL  IMB2.JMB1.JMB2.KMB1.KMB2.NBS.NBCS.NIBCS.NZWB.NTRIAG.NRASS.NTHPT.
CL  (NGOP(I),I=1,4)
C
CW  27
C
CD  IGOM          GEOMETRY  0- POINT (FUNDAMENTAL MODE)
CD                  1- SLAB
CD                  2- CYLINDER
CD                  3- SPHERE
CD                  6- X-Y
CD                  7- R-Z
CD                  8- THETA-R
CD                  9- UNIFORM TRIANGULAR
CD                  10- HEXAGONAL (1 MESH POINT IN EACH
CD                        HEXAGONAL ELEMENT)
CD                  11- R-THETA

```

CD		12- R-THETA-Z	-
CD		13- R-THETA-ALPHA	-
CD		14- X-Y-Z	-
CD		15- THETA-R-Z	-
CD		16- THETA-R-ALPHA	-
CD		17- UNIFORM TRIANGULAR-Z	-
CD		18- HEXAGON-Z (MESH POINTS AS IN 10	-
CD		ABOVE	-
CD	NZONE	NUMBER OF ZONES (EACH HOMOGENEOUS IN NEUTRONICS	-
CD		PROBLEM - A ZONE CONTAINS ONE OR MORE REGIONS)	-
CD	NREG	NUMBER OF REGIONS	-
CD	NZCL	NUMBER OF ZONE CLASSIFICATIONS (EDIT PURPOSES)	-
CD	NCINTI	NUMBER OF FIRST DIMENSION COARSE MESH INTERVALS	-
CD	NCINTJ	NUMBER OF SECOND DIMENSION COARSE COARSE MESH	-
CD		INTERVALS. NCINTJ.EQ.1 FOR ONE DIMENSIONAL	-
CD		CASE.	-
CD	NCINTK	NUMBER OF THIRD DIMENSION COARSE MESH INTERVALS	-
CD		NCINTK.EQ.1 FOR ONE AND TWO DIMENSION CASES	-
CD	NINTI	NUMBER OF FIRST DIMENSION FINE MESH INTERVALS	-
CD	NINTJ	NUMBER OF SECOND DIMENSION FINE MESH INTERVALS	-
CD		NINTJ.EQ.1 FOR ONE DIMENSIONAL CASE.	-
CD	NINTK	NUMBER OF THIRD DIMENSION FINE MESH INTERVALS	-
CD		NINTK.EQ.1 FOR ONE AND TWO DIMENSION CASES.	-
CD	IMB1	FIRST BOUNDARY OF FIRST DIMENSION	-
CD		0 - ZERO FLUX (DIFFUSION)	-
CD		1 - REFLECTED	-
CD		2 - EXTRAPOLATED (DIFFUSION - DEL PHI/PHI	-
CD		= -C/D WHERE C IS GIVEN AS BNDC BELOW	-
CD		AND D IS THE GROUP DIFFUSION CONSTANT,	-
CD		TRANSPORT - NO RETURN).	-
CD		3 - REPEATING (PERIODIC) WITH OPPOSITE FACE	-
CD		4 - REPEATING (PERIODIC) WITH NEXT ADJACENT	-
CD		FACE.	-
CD		5 - INVERTED REPEATING ALONG THIS FACE.	-
CD		(180 DEGREE ROTATION)	-
CD		6 - ISOTROPIC RETURN (TRANSPORT)	-
C			-
CC		NOTE FOR REPEATING CONDITIONS (3,4,5) - LET I1 DENOTE FIRST-	
CC		BOUNDARY ON FIRST DIMENSION. I2 THE SECOND BOUNDARY ON THE	-
CC		FIRST DIMENSION, J1 THE FIRST BOUNDARY ON THE SECOND	-
CC		DIMENSION, ETC. THEN THESE REPEATING BOUNDARY CONDITIONS	-
CC		ONLY APPLY TO BOUNDARIES I1, I2, J1, AND J2, GOING IN ORDER-	-
CC		OF I1, J1, I2, J2. THE FIRST BOUNDARY WHICH IS INVOLVED	-
CC		CARRIES THE DESIGNATOR DEFINING THE REPEATING CONDITION.	-

C		
CD	IMB2	LAST BOUNDARY ON FIRST DIMENSION
CD	JMB1	FIRST BOUNDARY ON SECOND DIMENSION
CD	JMB2	LAST BOUNDARY ON SECOND DIMENSION
CD	KMB1	FIRST BOUNDARY ON THIRD DIMENSION
CD	KMB2	LAST BOUNDARY ON THIRD DIMENSION
CD	NBS	NUMBER OF BUCKLING SPECIFICATIONS
CD		0 - NONE
CD		1 - SINGLE VALUE APPLIES EVERYWHERE
CD		.EQ.NZONE- ZONE DEPENDENT
CD		M*NZONE - DATA IS GIVEN OVER ALL ZONES FOR
CD		THE FIRST ENERGY GROUP. THEN FOR THE
CD		NEXT GROUP. TO END OF LIST. IF
CD		M.LT.NGROUP THEN THE M-TH GROUP DATA
CD		APPLIES TO ALL ADDITIONAL GROUPS.
CD		(2.LE.M.LE.NGROUP)
CD	NBCS	NUMBER OF CONSTANTS FOR EXTERNAL BOUNDARIES
CD		0 - NONE
CD		1 - SINGLE VALUE USED EVERYWHERE
CD		2 - INDIVIDUAL VALUE GIVEN FOR EACH
CD		EXTERNAL BOUNDARY. THE ORDERING OF THE
CD		VALUES IS THE SAME AS THE ORDERING OF
CD		THE BOUNDARY CONDITIONS.
CD		6*M - SIX VALUES GIVEN FOR FIRST ENERGY
CD		GROUP (ORDERED AS DESCRIBED ABOVE).
CD		THEN 6 FOR THE NEXT GROUP. TO END OF
CD		LIST. (2.LE.M.LE.NGROUP).
CD		IF M.LT.NGROUP THEN THE M-TH GROUP DATA
CD		APPLIES TO ALL REMAINING GROUPS.
CD	NIBCS	NUMBER OF CONSTANTS FOR INTERNAL BOUNDARIES
CD		0 - NONE
CD		1 - SINGLE VALUE USED EVERYWHERE
CD		.GT.1 - VALUES ARE GIVEN BY ENERGY GROUP
CD		WITH NON-BLACK CONDITION INDICATED BY
CD		ZERO ENTRY - LAST VALUE APPLIES TO
CD		ADDITIONAL GROUPS.
CD	NZWBB	NUMBER OF ZONES WHICH ARE BLACK ABSORBERS

CD	NTRIAG	TRIANGULAR/HEXAGONAL GEOMETRY OPTION	-
CD		0 - REGION OF SOLUTION IS A RHOMBUS IN	-
CD		WHICH THE 1ST AND 2ND DIMENSION AXES	-
CD		INTERSECT AT AN ANGLE OF 120 DEGREES.	-
CD		1 - REGION OF SOLUTION IS A RHOMBUS IN	-
CD		WHICH THE 1ST AND 2ND DIMENSION AXES	-
CD		INTERSECT AT AN ANGLE OF 60 DEGREES.	-
CD		2 - REGION OF SOLUTION IS A RECTANGLE. THE	-
CD		BOUNDARIES I1 AND I2 BISECT MESH	-
CD		TRIANGLES. SEE NTHPT BELOW.	-
CD		(IGOM=9, 17 ONLY)	-
CD		3 - REGION OF SOLUTION IS AN EQUILATERAL	-
CD		60 DEGREE TRIANGLE. (IGOM=9, 17 ONLY)	-
CD		4 - REGION OF SOLUTION IS A 30-60 DEGREE	-
CD		RIGHT TRIANGLE IN WHICH THE 1ST AND 2ND	-
CD		DIMENSION AXES INTERSECT AT THE 30	-
CD		DEGREE ANGLE. (IGOM=9, 17 ONLY)	-
CD		5 - REGION OF SOLUTION IS A RHOMBUS IN	-
CD		WHICH THE 1ST AND 2ND DIMENSION AXES	-
CD		INTERSECT AT AN ANGLE OF 30 DEGREES.	-
CD		(IGOM=9, 17 ONLY)	-
CD	NRASS	REGION ASSIGNMENTS	-
CD		0- TO COARSE MESH	-
CD		1- TO FINE MESH	-
CD	NTHPT	ORIENTATION OF FIRST FINE MESH INTERVAL IN	-
CD		TRIANGULAR GEOMETRIES. NTRIAG = 2 ONLY.	-
CD		1- TRIANGLE(1,1) POINTS AWAY FROM FIRST	-
CD		DIMENSION AXIS. I.E., NO INTERNAL MESH	-
CD		LINE INTERSECTS THE ORIGIN.	-
CD		2- TRIANGLE(1,1) POINTS TOWARD THE FIRST	-
CD		DIMENSION AXIS. I.E., AN INTERNAL MESH	-
CD		LINE INTERSECTS THE ORIGIN.	-
CD	NGOP	RESERVED	-
C			-
C			-

```

C-----
CR      ONE DIMENSIONAL COARSE MESH INTERVAL BOUNDARIES AND FINE
CR      MESH INTERVALS (2D RECORD)
C
CC      PRESENT IF IGOM.GT.0 AND IGOM.LE.3
C
CL      (XMESH(I),I=1,NCBNDI),(IFINTS(I),I=1,NCINTI)
C
CW      NCBNDI*MULT+NCINTI
C
CD      XMESH          COARSE MESH BOUNDARIES, FIRST DIMENSION
CD      IFINTS         NUMBER OF EQUALLY SPACED FINE MESH INTERVALS
CD                      PER COARSE MESH INTERVAL, FIRST DIMENSION
CD      NCBNDI         NCINTI+1, NUMBER OF FIRST DIMENSION COARSE
CD                      MESH BOUNDARIES
C
CC      UNITS ARE CM FOR LINEAR DIMENSIONS AND RADIANS FOR ANGULAR
C      DIMENSIONS
C-----

C-----
CR      TWO DIMENSIONAL COARSE MESH INTERVAL BOUNDARIES AND FINE
CR      MESH INTERVALS (3D RECORD)
C
CC      PRESENT IF IGOM.GT.6 AND IGOM.LE.11
C
CL      (XMESH(I),I=1,NCBNDI),(YMESH(J),J=1,NCBNDJ),
CL      1(IFINTS(I),I=1,NCINTI),(JFINTS(J),J=1,NCINTJ)
C
CW      (NCBNDI+NCBNDJ)*MULT+NCINTI+NCINTJ
C
CD      YMESH          COARSE MESH BOUNDARIES, SECOND DIMENSION
CD      JFINTS         NUMBER OF EQUALLY SPACED FINE MESH INTERVALS
CD                      PER COARSE MESH INTERVAL, SECOND DIMENSION
CD      NCBNDJ         NCINTJ+1, NUMBER OF SECOND DIMENSION COARSE
CD                      MESH BOUNDARIES
C
CC      FOR UNIFORM-TRIANGULAR-MESH GEOMETRY (IGOM = 9) THE
CC      LENGTH (L) OF THE SIDE OF A MESH TRIANGLE MUST BE GIVEN
CC      BY THE EXPRESSION
CC               $L = 2*(XMESH(2)-XMESH(1))/IFINTS(1)$ 
CC      FOR UNIFORM-HEXAGONAL-MESH GEOMETRY (IGOM = 10) THE
CC      FLAT-TO-FLAT DISTANCE (FTF) ACROSS A MESH HEXAGON MUST
CC      BE GIVEN BY THE EXPRESSION
CC               $FTF = (XMESH(2)-XMESH(1))/IFINTS(1)$ 
C-----

```

```

C-----
CR          THREE DIMENSIONAL COARSE MESH INTERVAL BOUNDARIES AND FINE
CR          MESH INTERVALS (4D RECORD)
C
CC          PRESENT IF IGOM.GE.12
C
CL          (XMESH(I),I=1,NCBNDI),(YMESH(J),J=1,NCBNDJ),
CL          1(ZMESH(K),K=1,NCBNDK),(IFINTS(I),I=1,NCINTI),
CL          2(JFINTS(J),J=1,NCINTJ),(KFINTS(K),K=1,NCINTK)
C
C*          (NCBNDI+NCBNDJ+NCBNDK)*MULT+NCINTI+NCINTJ+NCINTK
C
CD          ZMESH          COARSE MESH BOUNDARIES, THIRD DIMENSION
CD          KFINTS          NUMBER OF EQUALLY SPACED FINE MESH INTERVALS
CD                      PER COARSE MESH INTERVAL, THIRD DIMENSION
CD          NCBNDK          NCINTK+1, NUMBER OF THIRD DIMENSION COARSE MESH
CD                      BOUNDARIES
C
CC          FOR UNIFORM-TRIANGULAR-MESH GEOMETRY (IGOM =17) THE
CC          LENGTH (L) OF THE SIDE OF A MESH TRIANGLE MUST BE GIVEN
CC          BY THE EXPRESSION
CC                      L = 2.*(XMESH(2)-XMESH(1))/IFINTS(1).
CC          FOR UNIFORM-HEXAGONAL-MESH GEOMETRY (IGOM = 18) THE
CC          FLAT-TO-FLAT DISTANCE (FTF) ACROSS A MESH HEXAGON MUST
CC          BE GIVEN BY THE EXPRESSION
C                      FTF = (XMESH(2)-XMESH(1))/IFINTS(1)
C
C-----

```

```

C-----
CR          GEOMETRY DATA (5D RECORD)
C
CC          PRESENT IF IGOM.GT.0 OR NBS.GT.0
C
CL          (VOLR(N),N=1,NREG),(BSQ(N),N=1,NBS),(BNDC(N),N=1,NBCS),
CL          (BNCI(N),N=1,NIBCS),((NZHBB(N),N=1,NZWBB),(NZC(N),N=1,NZONE),
CL          (NZNR(N),N=1,NREG)
C
C*          2*NREG+NBS+NBCS+NIBCS+NZWBB+NZONE
C
CD          VOLR          REGION VOLUMES (CC)
CD          BSQ          BUCKLING (B**2) VALUES (CM**-2)
CD          BNDC          BOUNDARY CONSTANTS ((DEL PHI)/PHI = -C/D)
CD          BNCI          INTERNAL BLACK BOUNDARY CONSTANTS
CD          NZHBB          ZONE NUMBERS WITH BLACK ABSORBER CONDITIONS
CD          NZC          ZONE CLASSIFICATIONS
CD          NZNR          ZONE NUMBER ASSIGNED TO EACH REGION
C
C-----

```

```

C-----
CR      REGION ASSIGNMENTS TO COARSE MESH INTERVALS  (6D RECORD)
C
CC      PRESENT IF IGOM.GT.0 AND NRASS.EQ.0
C
CL      ((MR(I,J),I=1,NCINTI),J=1,NCINTJ)---NOTE STRUCTURE BELOW---
C
CW      NCINTI*NCINTJ
C
CS      DO 1 K=1,NCINTK
CS      1 READ(N)  *LIST AS ABOVE*
C
CD      MR                      REGION NUMBERS ASSIGNED TO COARSE MESH
CD                        INTERVALS
C
C-----

```

```

C-----
CR      REGION ASSIGNMENTS TO FINE MESH INTERVALS  (7D RECORD)
C
CC      PRESENT IF IGOM.GT.0 AND NRASS.EQ.1
C
CL      ((MR(I,J),I=1,NINTI),J=1,NINTJ)----NOTE STRUCTURE BELOW----
C
CW      NCINTI*NCINTJ
C
CS      DO 1 K=1,NINTK
CS      1 READ(N)  *LIST AS ABOVE*
C
CD      MR                      REGION NUMBERS ASSIGNED TO FINE MESH INTERVALS-
C
C-----

```

CEOF

```

C*****
C              REVISED 11/30/76
C
CF          GRUPXS-IV
CE          MICROSCOPIC GROUP NEUTRON CROSS SECTIONS
C
CN              THIS FILE PROVIDES A BASIC BROAD GROUP
C              LIBRARY. ORDERED BY GROUP
C
C*****

```

```

C-----
CS          FILE STRUCTURE
CS
CS          RECORD TYPE                PRESENT IF
CS                                                    
CS          FILE IDENTIFICATION        ALWAYS
CS          FILE CONTROL                ALWAYS
CS          FILE DATA                 ALWAYS
CS          SET CHI DATA              ICHIST.GT.1
CS          ISOTOPE CONTROL AND GROUP
CS          INDEPENDENT DATA          ALWAYS
CS          ***** (REPEAT OVER ALL ENERGY GROUPS)
CS          *      PRINCIPAL CROSS SECTIONS      ALWAYS
CS          *****
CS          ***** (REPEAT OVER NISO ISOTOPES)  NCHIN.GT.0
CS          *      ISOTOPE CHI DATA            ICHI(I).GT.1
CS          *****
CS          ***** (REPEAT OVER ALL ENERGY GROUPS)
CS          *      SCATTERING CONTROL            ALWAYS
CS          *      ***** (REPEAT TO NSCMAX SCATTERING BLOCKS)
CS          * *      ***** (REPEAT FROM 1 TO NSBLOK)
CS          * * *    SCATTERING SUB-BLOCK        LORD(N).GT.0
CS          *****
C
C-----

```


C-----

CR FILE IDENTIFICATION

C

CL HNAME.(HUSE(I).I=1.2).IVERS

C

CW 1+3*MULT=NUMBER OF WORDS

C

CD HNAME HOLLERITH FILE NAME - GRUPXS - (A6)

CD HUSE(I) HOLLERITH USER IDENTIFICATION (A6)

CD IVERS FILE VERSION NUMBER

CD MULT DOUBLE PRECISION PARAMETER

CD 1 - A6 WORD IS SINGLE WORD

CD 2 - A6 WORD IS DOUBLE PRECISION WORD

C

C-----

C-----

CR FILE CONTROL (1D RECORD)

C

CL NGROUP.NISO.MAXUP.MAXDN.MAXORD.ICHIST.NPSCS.NSTRPD.NCHIN.NICHI.

CL NSCMAX.NSBLOK.NRG.NRH

C

CW 14 - NUMBER OF WORDS

C

CD NGROUP NUMBER OF ENERGY GROUPS IN SET

CD NISO NUMBER OF ISOTOPES IN SET

CD MAXUP MAXIMUM NUMBER OF UPSCATTER GROUPS

CD MAXDN MAXIMUM NUMBER OF DOWNSCATTER GROUPS

CD MAXORD MAXIMUM SCATTERING ORDER (MAXIMUM VALUE OF

CD LEGENDRE EXPANSION INDEX USED IN FILE)

CD ICHIST SET FISSION SPECTRUM FLAG

CD 1 - SET FISSION SPECTRUM VECTOR

CD GT.1- NUMBER OF SPECTRA FOR RANGES IN

CD INCIDENT ENERGY DEPENDENT CHI

CD NPSCS LENGTH OF THE PRINCIPAL CROSS SECTION RECORDS

CD NSTRPD NUMBER OF COORDINATE DIRECTIONS FOR WHICH

CD TRANSPORT CROSS SECTIONS ARE GIVEN. LE.3

CD NCHIN NUMBER OF ISOTOPES FOR WHICH THERE ARE INCIDENT

CD ENERGY DEPENDENT CHI DATA

CD NICHI NUMBER OF INCIDENT ENERGY SPECTRA FOR ISOTOPE CHI-

CD DATA (MAXIMUM)

CD NSCMAX MAXIMUM NUMBER OF BLOCKS OF SCATTERING DATA

CD FOR EACH GROUP SCATTERED INTO - CAN BE THE

CD NUMBER OF TYPES OF SCATTERING FOR WHICH THERE

CD ARE DATA.

CD NSBLOK BLOCKING CONTROL FOR SCATTERING MATRICES. THE

CD SCATTERING DATA ARE BLOCKED INTO NSBLOK

CD RECORDS PER SCATTERING BLOCK.

```

CD      NRG      RESERVED
CD      NRH      RESERVED
C
C-----
C-----
CR      FILE DATA      (2D RECORD)
C
CL      (HSETID(I),I=1,12),(HISONM(I),I=1,NISO),
CL      (CHI(J),J=1,NGROUP),(VEL(J),J=1,NGROUP),
CL      (EMAX(J),J=1,NGROUP),EMIN
C
CW      3*NGROUP+MULT*(NISO+12)+1=NUMBER OF WORDS
C
CD      HSETID(I)      HOLLERITH IDENTIFICATION OF SET (A6)
CD      HISONM(I)      HOLLERITH ISOTOPE LABEL FOR ISOTOPE I (A6)
CD      CHI(J)         SET FISSION SPECTRUM
CD      VEL(J)         MEAN NEUTRON VELOCITY IN GROUP J (CM/SEC)
CD      EMAX(J)        MAXIMUM ENERGY BOUND OF GROUP J (EV)
CD      EMIN           MINIMUM ENERGY BOUND OF SET (EV)
C
C-----
C-----
CR      SET CHI DATA      (3D RECORD)
C
CC      PRESENT IF ICHIST.GT.1
C
CL      ((CHII(K,J),K=1,ICHIST),(J=1,NGROUP),(ISSPEC(I),I=1,NGROUP)
C
CW      NGROUP*(ICHIST+1)=NUMBER OF WORDS
C
CD      CHII(K,J)      FRACTION OF NEUTRONS EMITTED IN GROUP J AS A
CD                      RESULT OF FISSION IN ANY GROUP USING SPECTRUM K
CD      ISSPEC(I)      ISSPEC(I)=K IMPLIES THAT SPECTRUM K IS USED TO
CD                      CALCULATE EMISSION SPECTRUM FROM FISSION IN
CD                      GROUP I
C
C-----

```

```

C .....
CR      ISOTOPE CONTROL AND GROUP INDEPENDENT DATA (4D RECORD)
C
CL      (HABSID(I),I=1,NISO),(HIDENT(I),I=1,NISO),(HMAT(I),I=1,NISO),
CL      (AMASS(I),I=1,NISO),
CL      (EFISS(I),I=1,NISO),(ECAPT(I),I=1,NISO),(XN9I),I=1,NISO),
CL      (TEMP(I),I=1,NISO),(SIGPOT(I),I=1,NISO),(ADENS(I),I=1,NISO),
CL      (KBR(I),I=1,NISO),(IDSCT(N),N=1,NSCMAX),(LORD(N),N=1,NSCMAX),
CL      (ICHI(I),I=1,NISO),IALF,INP,IN2N,IND,INT,IX,IY
C
CW      NISO*(3*MULT+9)+2*NSCMAX+7=NUMBER OF WORDS
C
CD      HABSID(I)      HOLLERITH ABSOLUTE ISOTOPE LABEL (A6)
CD      HIDENT        IDENTIFIER, USUALLY ENDF NUMBER (A6)
CD      HMAT(I)        MATERIAL REFERENCE FOR IDENTIFICATION (A6)
CD      AMASS(I)       GRAM ATOMIC WEIGHT
CD      EFISS(I)       TOTAL THERMAL ENERGY YIELD/FISSION (W SEC/FISS)
CD      ECAPT(I)       THERMAL ENERGY YIELD PER CAPTURE (W SEC/CAP)
CD      XN(I)          RESERVED
CD      TEMP(I)        ISOTOPE TEMPERATURE (DEGREES KELVIN)
CD      SIGPOT(I)      AVERAGE EFFECTIVE POTENTIAL SCATTERING IN
CD                      RESONANCE RANGE (BARNS/ATOM)
CD      ADENS(I)       DENSITY OF ISOTOPE IN MIXTURE IN WHICH ISOTOPE
CD                      CROSS SECTIONS WERE GENERATED (A/BARN/CC)
CD      KBR(I)         ISOTOPE CLASSIFICATION
CD                      0=UNDEFINED
CD                      1=FISSILE
CD                      2=FERTILE
CD                      3=OTHER ACTINIDE
CD                      4=FISSION PRODUCT
CD                      5=STRUCTURE
CD                      6=COOLANT
CD                      7=CONTROL
CD      IDSCT(N)       SCATTERING MATRIX TYPE IDENTIFICATION FOR
CD                      SCATTERING BLOCK N, SIGNIFICANT ONLY IF
CD                      LORD(N).GT.0
CD                      IDSCT(N)=000+NN, TOTAL SCATTERING (SUM OF
CD                      ELASTIC, INELASTIC, AND (N,2N) SCATTERING)
CD                      =100 + NN, ELASTIC SCATTERING
CD                      =200 + NN, INELASTIC SCATTERING
CD                      =300 + NN, (N,2N) SCATTERING.....SEE
CD                      NOTE BELOW-----
CD                      WHERE NN IS EXPANSION ORDER OF BLOCK N DATA,
CD                      DATA ORDERED BY INCREASING EXPANSION ORDER
CD                      FOR EACH OF THE TYPES IN THE ABOVE ORDER

```

CD	LORD(N)	NUMBER OF SCATTERING ORDERS IN BLOCK N IF	-
CD		LORD(N)=0. THIS BLOCK IS NOT PRESENT FOR THIS	-
CD		ISOTOPE BLOCK. IF NN IS THE VALUE TAKEN FROM	-
CD		IDSCT(N). THEN THE MATRICES IN THIS BLOCK	-
CD		HAVE LEGENDRE EXPANSION INDICES OF NN,NN+1.	-
CD		LORD(N)	-
CD	ICHI(I)	ISOTOPE FISSION SPECTRUM FLAG	-
CD		0 - USE SET CHI	-
CD		1 - ISOTOPE CHI VECTOR	-
CD		.GT.1 - NUMBER OF SPECTRA FOR RANGES IN INCIDENT	-
CD		ENERGY DEPENDENT CHI	-
CD	IALF	(N.ALPHA) CROSS SECTION FLAG	-
CD		IALF=1. (N.ALPHA) DATA IN THE FILE	-
CD		IALF=0. NO (N.ALPHA) DATA IN THE FILE	-
CD	INP	(N.P) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	IN2N	(N.2N) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	IND	(N.D) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	INT	(N.T) CROSS SECTION FLAG	-
CD		SAME OPTIONS AS FOR IALF	-
CD	IX	RESERVED	-
CD	IY	RESERVED	-
C			-
CN		NOTE - FOR (N.2N) SCATTER. THE MATRIX CONTAINS	-
CN		TERMS. SS(G TO J). WHICH ARE EMISSION	-
CN		(PRODUCTION) - BASED. I.E., ARE DEFINED SUCH	-
CN		THAT MACROSCOPIC SS(G TO J) TIMES THE FLUX IN	-
CN		GROUP G GIVES THE RATE OF EMISSION (PRODUCTION)	-
CN		OF NEUTRONS INTO GROUP J.	-
C			-
C			-

```

C-----
CR          PRINCIPAL CROSS SECTIONS      (3D RECORD)
C
CL          ((STRPL(I,L),I=1,NISO),L=1,MAXT).
CL          ((STOTPL(I,L),I=1,NISO),L=1,MAXT),(SNGAM(I),I=1,NISO).
CL          (SFIS(I),I=1,NISO),(SNUTOT(I),I=1,NISO).
CL          (CHISO(I),I=1,NISO),(SNALF9I),I=1,NISO).
CL          (SNP(I),I=1,NISO),(SN2N(I),I=1,NISO).
CL          (SND(I),I=1,NISO),(SNT(I),I=1,NISO).
CL          ((STRPD(I,J),I=1,NISO),J=1,NSTRPD)
C
CW          NPSCS=NISO*(2*MAXT+4+IALF+INP+IN2N+IND+INT+NSTRPD)=NUMBER
CW          OF WORDS
C
CD          STRPL(I,L)      PL WEIGHTED TRANSPORT CROSS SECTIONS
CD                          THE LEGENDRE EXPANSION COEFFICIENT FACTOR (2L+1)
CD                          IS NOT INCLUDED IN STOTPL(I,L)
CD          SNGAM(I)        (N.GAMMA) CROSS SECTION
CD          SFIS(I)         (N.FISSION) CROSS SECTION
CD          SNUTOT(I)       TOTAL NEUTRON YIELD/FISSION
CD          CHISO(I)        ISOTOPE CHI VECTOR
CD          SNALF(I)        (N.ALPHA)                (PRESENT IF IALF.GT.0)
CD          SNP(I)          (N.P)                    (PRESENT IF INP.GT.0)
CD          SN2N(I)         (N.2N)                   (PRESENT IF IN2N.FT0) ----SEE
CD                          NOTE BELOW
CD          SND(I)          (N.D)                    (PRESENT IF IND.GT.0)
CD          SNT(I)          (N.T)                    (PRESENT IF INT.GT.0)
CD          STRPD(I,J)      COORDINATE DIRECTION J DEPENDENT TRANSPORT CROSS
CD                          SECTION (PRESENT IF NSTRPD.GT.0)
CD          MAXT            MAXORD+1
C
CN          NOTE - THE PRINCIPAL (N.2N) CROSS SECTION SN2N FOR
CN          A GIVEN GROUP IS THE (N.2N) REACTION CROSS
CN          SECTION FOR THAT GROUP. I.E., SUCH THAT
CN          MACROSCOPIC SN2N FOR A GIVEN GROUP TIMES THE
CN          GROUP FLUX GIVES THE RATE AT WHICH (N.2N)
CN          REACTIONS OCCUR IN THAT GROUP
C-----

```

```

C-----
CR      ISOTOPE CHI DATA    (6D RECORD)      -
C                                           -
CC      PRESENT IF NCHIN.GT.0AND ICHI(I).GT.1  -
C                                           -
CL      ((CHISI(K,J),K-1,ICHII),J-1,NGROUP),(ISOPEC(I),I-1,NGROUP) -
C                                           -
CW      NGROUP*(ICHII + 1)-NUMBER OF WORDS    -
C                                           -
CD      ICHII      -ICHI(I)                  -
CD      CHISI(K,J)  FRACTION OF NEUTRONS EMITTED IN GROUP J AS A RESULT -
CD                        OF FISSION IN ANY GROUP USING SPECTRUM K      -
CD      ISOPEC(I)   ISOPEC(I)=K IMPLIES THAT SPECTRUM K IS USED TO     -
CD                        CALCULATE EMISSION SPECTRUM FROM FISSION IN    -
C                        GROUP I                                           -
C                                           -
C-----

```

```

C-----
CR      SCATTERING CONTROL    (7D RECORD)      -
C                                           -
CL      ((JBAND(I,N),I-1,NISO), N-1,NSCMAX)   -
CL      ((IJJ(I,N), I-1,NISO), N-1,NSCMAX)     -
C                                           -
CW      2*NISO*NSCMAX=NUMBER OF WORDS          -
C                                           -
CD      JBAND(I,N)   NUMBER OF GROUPS THAT SCATTER INTO THE GROUP,     -
CD                        INCLUDING SELF SCATTER, FOR ISOTOPE I, BLOCK N- -
CD                        IF JBAND=0, NO SCATTER DATA IS PRESENT IN THAT- -
CD                        BLOCK.                                           -
CD      IJJ(I,N)     POSITION OF IN-GROUP SCATTERING CROSS SECTION IN    -
CD                        SCATTERING DATA FOR ISOTOPE I, SCATTERING     -
CD                        BLOCK N, COUNTED FROM THE FIRST WORD OF        -
CD                        ISOTOPE I DATA. IF JBAND(I,N).NE.0 THEN       -
CD                        IJJ(I,N) MUST SATISFY THE RELATION             -
CD                        1.LE.IJJ.LE.JBAND.                              -
C                                           -
C-----

```

```

C-----
CR      SCATTERING SUB-BLOCK   (8D RECORD)
C
CC      PRESENT IF LORD(N).GT.0
C
CL      ((SCAT(K,L),K=1,KMAX),L=1,LORDN)
C
CC      KMAX=SUM OVER I OF JBAND(I,N) WITHIN THE I - ISOTOPE RANGE OF THIS-
CC      SUB-BLOCK. IF M IS THE INDEX OF THE SUB-BLOCK, THE I - ISOTOPE -
CC      RANGE CONTAINED WITHIN THIS SUB-BLOCK IS
CC      IL=(M-1)*((NISO-1)/NSBLOK + 1) TO IU=MINO(NISO,IUP),
CC      WHERE IUP=M*((NISO-1)/NSBLOK + 1).
C
CC      LORDN = LORD(N)
CC      N IS THE INDEX FOR THE LOOP OVER NSCMAX (SEE FILE STRUCTURE)
C
CW      KMAX*LORDN=NUMBER OF WORDS
C
CD      SCAT(K,L)      SCATTERING MATRIX OF SCATTERING ORDER L, FOR
CD                      REACTION TYPE IDENTIFIED BY IDSCT(N) FOR THIS
CD                      BLOCK. JBAND(I) VALUES FOR SCATTERING INTO
CD                      GROUP J ARE STORED AT LOCATIONS K=SUM FROM 1
CD                      TO (I-1) OF JBAND (I) PLUS 1 TO K-1+JBAND(I).
CD                      THE SUM IS ZERO WHEN I=1. J-TO-J SCATTER IS
CD                      THE IJJ(I)-TH ENTRY IN THE RANGE JBAND(I).
CD                      VALUES ARE STORED IN THE ORDER (J+JUP),
CD                      (J+JUP-1),...,(J+1),J,(J-1),...,(J-JDN),
CD                      WHERE JUP=IJJ(I)-1 AND JDN=JBAND(I)-IJJ(I)
C
CN                      BLOCKING OVER ISOTOPES FOR EACH ORDER IS
CN                      NECESSARY IF THE DATA IS TO BE PROCESSED ONCE
CN                      SEQUENTIALLY AND THE MACROSCOPIC DATA STORED
CN                      ONE ORDER AT A TIME. IN THIS EVENT, EITHER
CN                      VALUES OF LORD(N) MUST BE LIMITED TO 1 OR
CN                      NSBLOK BE 1.
C
C-----

```

CEOF

```

C-----
CR      ISOTOPE CHI DATA   (6D RECORD)
C
CC      PRESENT IF NCHIN.GT.0AND ICHI(I).GT.1
C
CL      ((CHISI(K,J).K=1.ICHII).J=1.NGROUP).(ISOPEC(I).I=1.NGROUP)
C
CW      NGROUP*(ICHII + 1)=NUMBER OF WORDS
C
CD      ICHII              =ICHI(I)
CD      CHISI(K,J)         FRACTION OF NEUTRONS EMITTED IN GROUP J AS A RESULT
CD                          OF FISSION IN ANY GROUP USING SPECTRUM K
CD      ISOPEC(I)          ISOPEC(I)=K IMPLIES THAT SPECTRUM K IS USED TO
CD                          CALCULATE EMISSION SPECTRUM FROM FISSION IN
C                          GROUP I
C
C-----

C-----
CR      SCATTERING CONTROL   (7D RECORD)
C
CC      PRESENT IF LORD(N).GT.0
C
CL      ((SCAT(K,L).K=1.KMAX).L=1.LORDN)
C
CC      KMAX=SUM OVER I OF JBAND(I,N) WITHIN THE I - ISOTOPE RANGE OF THIS
CC      SUB-BLOCK. IF M IS THE INDEX OF THE SUB-BLOCK. THE I - ISOTOPE
CC      RANGE CONTAINED WITHIN THIS SUB-BLOCK IS
CC      IL=(M-1)*((NISO-1)/NSBLOK + 1) TO IU=M*INO(NISO,IUP).
CC      WHERE IUP=M*((NISO-1)/NSBLOK + 1).
C
CC      LORDN = LORD(N)
CC      N IS THE INDEX FOR THE LOOP OVER NSCMAX (SEE FILE STRUCTURE)
C
CW      KMAX*LORDN=NUMBER OF WORDS

```



```

C
CD   SCAT(K,L)   SCATTERING MATRIX OF SCATTERING ORDER L. FOR
CD               REACTION TYPE IDENTIFIED BY IDSCT(N) FOR THIS
CD               BLOCK. JBAND(I) VALUES FOR SCATTERING INTO
CD               GROUP J ARE STORED AT LOCATIONS K=SUM FROM 1
CD               TO (I-1) OF JBAND (I) PLUS 1 TO K-1+JBAND(I).
CD               THE SUM IS ZERO WHEN I=1. J-TO-J SCATTER IS
CD               THE IJJ(I)-TH ENTRY IN THE RANGE JBAND(I).
CD               VALUES ARE STORED IN THE ORDER (J+JUP).
CD               (J+JUP-1).....(J+1).J.(J-1).....(J-JDN).
CD               WHERE JUP=IJJ(I)-1 AND JDN=JBAND(I)-IJJ(I)
C
CN               BLOCKING OVER ISOTOPES FOR EACH ORDER IS
CN               NECESSARY IF THE DATA IS TO BE PROCESSED ONCE
CN               SEQUENTIALLY AND THE MACROSCOPIC DATA STORED
CN               ONE ORDER AT A TIME. IN THIS EVENT, EITHER
CN               VALUES OF LORD(N) MUST BE LIMITED TO 1 OR
CN               NSBLOK BE 1.
C
C-----
CEOF

```

```

C*****
C                                     REVISED 11/30/76
C
C
CF      ISOGXS-IV
CE      MICROSCOPIC GROUP GAMMA CROSS SECTIONS
C
CN      THIS FILE PROVIDES A BASIC BROAD GROUP
CN      LIBRARY, ORDERED BY ISOTOPE
CN      FORMATS GIVEN ARE FOR FILE EXCHANGE PURPOSES
CN      ONLY.
C
C*****

```

```

C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      -----                                -----
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS      FILE DATA                                ALWAYS
CS      ***** (REPEAT FOR ALL ISOTOPES)
CS      *      ISOTOPE CONTROL                      ALWAYS
CS      *      PRINCIPAL CROSS SECTIONS             ALWAYS
CS      *      ***** (REPEAT FROM 1 TO LGN)
CS      *      *      ***** (REPEAT FROM 1 TO NBLKGN)
CS      *      *      NEUTRON PRODUCTION CROSS SECTIONS  IGN.EQ.1 AND
CS      *      *      NBLKGN.GT.0
CS      *      *****
CS      *
CS      *      ***** (REPEAT FROM 1 TO LNG)
CS      *      *      ***** (REPEAT FROM 1 TO NBLKNG)
CS      *      *      GAMMA PRODUCTION CROSS SECTIONS  ING.EQ.1 AND
CS      *      *      NBLKNG.GT.0
CS      *      *****
CS      *
CS      *      ***** (REPEAT FROM 1 TO LGG)
CS      *      *      ***** (REPEAT FROM 1 TO NBLKGG)
CS      *      *      GAMMA SCATTERING CROSS SECTIONS  IGG.EQ.1 AND
CS      *      *      NBLKGG.NE.0
CS      *****
C
C-----

```

```

C-----
CR          FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1, 2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CB      FORMAT(11H OV ISOGXS , 1H*, 2A6, 1H*, I6)
C
CD      HNAME          HOLLERITH FILE NAME - ISOGXS - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C-----

```

```

C-----
CR          FILE CONTROL      (1D RECORD)
C
CL      NGROUP, NGGRUP, NGIS, IDUM
C
CW      4=NUMBER OF WORDS
C
CB      FORMAT(4H 1D , 4I6)
C
CD      NGROUP        NUMBER OF NEUTRON ENERGY GROUPS
CD      NGGRUP        NUMBER OF GAMMA ENERGY GROUPS
CD      NGIS          NUMBER OF ISOTOPES WITH GAMMA CROSS SECTIONS
CD      IDUM          UNDEFINED. USED TO OBTAIN FOUR WORD RECORD
C-----

```

```

C-----
CR          FILE DATA      (2D RECORD)
C
CL      (HSETID(I), I=1, 12), (HGISON(I), I=1, NGIS), (VEL(J), J=1, NGROUP),
CL      1(EMAX(J), J=1, NGROUP), EMIN, (EMAXG(K), K=1, NGGRUP), EMING
C
CW      2*NGROUP+NGGRUP+MULT*(NGIS+12)+2=NUMBER OF WORDS
C
CB      FORMAT(5H 2D *, 11A6, 1H*/          HSETID, HGISON
CB      1(10(1X, A6)))
CB      FORMAT ( 6E12.5)                    VEL, EMAX, EMIN, EMAXG, EMING

```

C
CD HSETID(I) HOLLERITH IDENTIFICATION OF SET (A6)
CD HGISON(I) HOLLERITH ISOTOPE LABEL FOR ISOTOPE I (A6)
CD VEL(J) MEAN NEUTRON VELOCITY IN GROUP J (CM/SEC)
CD EMAX(J) MAXIMUM ENERGY BOUND OF NEUTRON GROUP J (EV)
CD EMIN MINIMUM NEUTRON ENERGY BOUND (EV)
CD EMAXG(K) MAXIMUM ENERGY BOUND OF GAMMA GROUP K (EV)
CD EMING MINIMUM GAMMA ENERGY BOUND (EV)
C
C-----

C-----
CR ISOTOPE CONTROL (3D RECORD)
C
CL HABSID,LGTOT,LGTRN,IGN,ING,IGG
C
CW MULT+5=NUMBER OF WORDS
C
CB FORMAT(4H 3D ,A6,5I6)
C
CD HABSID HOLLERITH ABSOLUTE ISOTOPE LABEL - SAME FOR ALL
CD VERSIONS OF SAME ISOTOPE IN SET
CD LGTOT NUMBER OF MOMENTS OF TOTAL CROSS SECTION
CD LGTRN NUMBER OF MOMENTS OF TRANSPORT CROSS SECTION
CD IGN GAMMA,N CROSS SECTIONS PRESENT. 1=YES,0=NO
CD ING N,GAMMA CROSS SECTIONS PRESENT. 1=YES,0=NO
CD IGG GAMMA SCATTERING CROSS SECTIONS PRESENT. 1=YES,0=NO
C
C-----

C-----
CR PRINCIPAL CROSS SECTIONS (4D RECORD)
C
CL ((GTRPL(K,L),K=1,NGGRUP),L=1,LGTRN),
CL 1((GTOTPL(K,L),K=1,NGGRUP),L=1,LGTOT),(GABS(K),K=1,NGGRUP),
CL 2(GEDEP(K),K=1,NGGRUP),(GDGR(K),K=1,NGGRUP)
C
CW (LGTRN+LGTOT+2)*NGGRUP=NUMBER OF WORDS
C
CB FORMAT(4H 4D , 5E12.5/(6E12.5))
C
CD GTRPL(K,L) PL WEIGHTED TRANSPORT CROSS SECTION
CD GTOTPL(K,L) PL WEIGHTED TOTAL CROSS SECTION
CD GABS(K) TOTAL ABSORPTION CROSS SECTION
CD GEDEP(K) ENERGY DEPOSITION-CROSS SECTION X ENERGY (EV)
CD DEPOSITED
CD GDGR(K) SOURCE FROM TOTAL DECAY (PHOTONS/DIS)
C
C-----

C-----
CR NEUTRON PRODUCTION CONTROL (5D RECORD)
C

```

CC          PRESENT IF IGN.EQ.1
C
CL          LGN,NBLKGN,(JBNDGN(J),J=1,NGROUP),(IJJGN(J),J=1,NGROUP)
C
CW          2*(NGROUP+1)=NUMBER OF WORDS
C
CB          FORMAT(4H 5D ,11I6/(12I6))
C
CD          LGN          NUMBER OF ORDERS OF GAMMA ,N CROSS SECTIONS
CD          NBLKGN       NUMBER OF BLOCKS OF GAMMA,N CROSS SECTIONS
CD                      PER ORDER
CD          JBNDGN(J)    BANDWIDTH OF GAMMA GROUPS YIELDING NEUTRONS IN
CD                      GROUP J
CD          IJJGN(J)     LOWEST ENERGY GAMMA GROUP OF BAND JBNDGN(J)
C
C-----

```

```

C-----
CR          NEUTRON PRODUCTION CROSS SECTIONS      (6D RECORD)
C
CC          PRESENT IF IGN.EQ.1 AND NBLKGN.GT.0
C
CL          (GGN(L),L=1,LGNMAX)
C
CC          LGNMAX=SUM OVER J OF JBNDGN(J) WITHIN THE J-GROUP RANGE OF THIS
CC          BLOCK. IF M IS THE INDEX OF THE BLOCK, THE J-GROUP RANGE
CC          CONTAINED WITHIN THIS BLOCK IS JL=(M-1)*((NGROUP-1)/NBLKGN+1)+1
CC          TO JU=MINO(NGROUP,JUP) WHERE JUP=M*((NGROUP-1)/NBLKGN +1).
C
CW          LGNMAX=NUMBER OF WORDS
C
CB          FORMAT(4H 6D , 5E12.5/(6E12.5))
C
CD          GGN(L)       CROSS SECTIONS FOR PRODUCTION OF NEUTRONS BY
CD                      GAMMAS. JBNDGN(J) VALUES OF THE CROSS SECTIONS
CD                      FOR EACH NEUTRON GROUP J ARE STORED ACCORDING TO
CD                      THE GAMMA GROUP ORDER K=IJJGN(J),IJJGN(J)-1,...
CD                      ...,IJJGN(J)-JBNDGN(J)+1. IN EACH BLOCK M,
CD                      THE JBNDGN(J) VALUES ARE STORED IN LOCATIONS
CD                      L=LL TO L=LU WHERE LL=1 PLUS SUM OVER JBNDGN(N)
CD                      FROM N=JL TO N=J-1 AND LU=LL PLUS JBNDGN(J)-1
C
C-----

```

```

C-----
CR          GAMMA PRODUCTION CONTROL      (7D RECORD)
C
CC          PRESENT IF ING.EQ.1
C

```

```

C
CL   LNG,NBLKNG,(JBNDNG(J),J=1,NGGRUP),(IJJNG(J),J=1,NGGRUP)
C
CW   2*(NGGRUP+1)=NUMBER OF WORDS
C
CB   FORMAT(4H 7D ,1116/(1216))
C
CD   LNG           NUMBER OF ORDERS OF N,GAMMA CROSS SECTIONS
CD   NBLKNG        NUMBER OF BLOCKS OF N,GAMMA CROSS SECTIONS
CD                   PER ORDER
CD   JBNDNG(K)     BANDWIDTH OF NEUTRON GROUPS YIELDING GAMMAS IN
CD                   GROUP K
CD   IJJNG(K)      LOWEST ENERGY NEUTRON GROUP OF BAND JBNDNG(K)
C
C-----

```

```

C-----
CR           GAMMA PRODUCTION CROSS SECTIONS   (8D RECORD)
C
CC           PRESENT IF ING.EQ.1 AND NBLKNG.GT.0
C
CL   (GNG(L),L=1,LNGMAX)
C
CC   LNGMAX IS SAME AS LGNMAX ABOVE EXCEPT JBNDNG(K) AND NBLKNG ARE
CC   USED INSTEAD OF JBNDGN(J) AND NBLKGN
C
CW   LNGMAX=NUMBER OF WORDS
C
CB   FORMAT(4H 8D , 5E12.5/(6E12.5))
C
CD   GNG(L)        CROSS SECTIONS FOR PRODUCTION OF GAMMAS BY
CD                   NEUTRONS. STORAGE IS SIMILAR TO THAT FOR GGN(L)
CD                   EXCEPT JBNDNG(K) AND IJJNG(K) REPLACE JBNDGN(J)
CD                   AND IJJGN(J).
C
C-----

```

```

C-----
CR           GAMMA SCATTERING CONTROL   (9D RECORD)
C
CC           PRESENT IF IGG.EQ.1
C
CL   LGG,NBLKGG,(JBNDGG(J),J=1,NGGRUP),(IJJGG(J),J=1,NGGRUP)
C
CW   2*(NGGRUP+1)=NUMBER OF WORDS
C

```

```

CB      FORMAT(4H 9D ,1116/(1216))
C
CD      LGG          NUMBER OF ORDERS OF GAMMA SCATTERING CROSS SECTIONS-
CD      NBLKGG       NUMBER OF BLOCKS OF GAMMA SCATTERING CROSS SECTIONS-
CD                        PER ORDER
CD      JBNDGG(K)    BANDWIDTH OF GAMMA GROUPS YIELDING GAMMAS IN
CD                        GROUP K
CD      IJJGG(K)     LOWEST ENERGY GAMMA GROUP OF BAND JBNDGG(K)
C
C-----
C
CR      GAMMA SCATTERING CROSS SECTIONS      (100 RECORD)
C
CC      PRESENT IF IGG.EQ.1 AND NBLKGG.GT.0
C
CL      (GGG(L),L=1,LGGMAX)
C
CC      LGGMAX IS SAME AS LGNMAX ABOVE EXCEPT JBNDGG(K) AND NBLKGG ARE
CC      USED INSTEAD OF JBNDGN(J) AND NBLKGN.
C
CW      LGGMAX=NUMBER OF WORDS
C
CB      FORMAT(5H 10D , 5E12.5/(6E12.5))
C
CD      GGG(L).      CROSS SECTIONS FOR GAMMA SCATTERING. STORAGE IS
CD                        SIMILAR TO THAT FOR GGN(L) EXCEPT JBNDGG(K) AND
CD                        IJJGG(K) REPLACE JBNDGN(J) AND IJJGN(J).
C
C-----
CEOF

```

```

C*****
C              REVISED 11/30/76
C
CF          ISOTXS-IV
CE          MICROSCOPIC GROUP NEUTRON CROSS SECTIONS
C
CN              THIS FILE PROVIDES A BASIC BROAD GROUP
CN              LIBRARY. ORDERED BY ISOTOPE
CN              FORMATS GIVEN ARE FOR FILE EXCHANGE PURPOSES
CN              ONLY.
C
C*****

```

```

C-----
CS          FILE STRUCTURE
C
CS          RECORD TYPE                PRESENT IF
CS          -----
CS          FILE IDENTIFICATION        ALWAYS
CS          FILE CONTROL                ALWAYS
CS          FILE DATA                 ALWAYS
CS          FILE-WIDE CHI DATA        ICHIST.GT.1
CS
CS          ***** (REPEAT FOR ALL ISOTOPES)
CS          *          ISOTOPE CONTROL AND GROUP
CS          *          INDEPENDENT DATA    ALWAYS
CS          *          PRINCIPAL CROSS SECTIONS    ALWAYS
CS          *          ISOTOPE CHI DATA    ICHI.GT.1
CS          *
CS          *          ***** (REPEAT TO NSCMAX SCATTERING BLOCKS)
CS          * *          ***** (REPEAT FROM 1 TO NSBLOK)
CS          * * *          SCATTERING SUB-BLOK    LORD(N).GT.0
CS          *****
C
C-----

```



```

C-----
CR          FILE IDENTIFICATION
C
CL      HNAME.(HUSE(I).I=1.2).IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CB      FORMAT(11H OV ISOTXS . 1H*
CB      12A6.1H*.I6)
C
CD      HNAME          HOLLERITH FILE NAME - ISOTXS - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILR VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                        1 - A6 WORD IS A SINGLE WORD
CD                        2 - A6 WORD IS A DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          FILE CONTROL      (1D RECORD)
C
CL      NGROUP.NISO.MAXUP.MAXDN.MAXORD.ICHIST.NSCMAX.NSBLOK
C
CW      8=NUMBER OF WORDS
C
CB      FORMAT(4H 1D .8I6)
C
CD      NGROUP        NUMBER OF ENERGY GROUPS IN FILE
CD      NISO          NUMBER OF ISOTOPES IN FILE
CD      MAXUP         MAXIMUM NUMBER OF UPSCATTER GROUPS
CD      MAXDN         MAXIMUM NUMBER OF DOWNSCATTER GROUPS
CD      MAXORD        MAXIMUM SCATTERING ORDER (MAXIMUM VALUE OF
CD                    LEGENDRE EXPANSION INDEX USED IN FILE).
CD      ICHIST        FILE WIDE FISSION SPECTRUM FLAG
CD                    ICHIST.EQ.0.      NO FILE-WIDE SPECTRUM
CD                    ICHIST.EQ.1      FILE-WIDE CHI VECTOR
CD                    ICHIST.GT.1      FILE WIDE CHI MATRIX
CD      NSCMAX        MAXIMUM NUMBER OF BLOCKS OF SCATTERING DATA
CD      NSBLOK        SUBBLOCKING CONTROL FOR SCATTER MATRICES. THE
CD                    SCATTERING DATA ARE SUBBLOCKED INTO NSBLOK
CD                    RECORDS (SUBBLOCKS) PER SCATTERING BLOCK.
C
C-----

```

```

C-----
CR          FILE DATA      (2D RECORD)
C
CL      (HSETID(I),I=1,12),(HISONM(I),I=1,NISO),
CL      1(CHI(J),J=1,NGROUP),(VEL(J),J=1,NGROUP),
CL      2(EMAX(J),J=1,NGROUP),EMIN,(LOCA91),I=1,NISO)
C
CW      (NISO+12)*MULT+1+NISO
CW      +NGROUP*(2+ICHIST*(2/(ICHIST+1)))=NUMBER OF WORDS
C
CB      FORMAT(4H 2D ,1H*.11A6,1H*/          HSETID,HISONM
CB      11H*.A6,1H*.9(1X.A6)/(10(1X.A6)))
CB      FORMAT(6E12.5)          CHI (PRESENT IF ICHIST.EQ.1)
CB      FORMAT(6E12.5)          VEL,EMAX,EMIN
CB      FORMAT(12I6)            LOCA
C
CD      HSETID(I)      HOLLERITH IDENTIFICATION OF FILE (A6)
CD      HISONM(I)      HOLLEREITH ISOTOPE LABEL FOR ISOTOPE I (A6)
CD      CHI(J)         FILE-WIDE FISSION SPECTRUM (PRESENT IF ICHIST.EQ.1)
CD      VEL(J)         MEAN NEUTRON VELOCITY IN GROUP J (CM/SEC)
CD      EMAX(J)        MAXIMUM ENERGY BOUND OF GROUP J (EV)
CD      EMIN          MINIMUM ENERGY BOUND OF SET (EV)
CD      LOCA(I)        NUMBER OF RECORDS TO BE SKIPPED TO READ DATA FOR
CD                      ISOTOPE I. LOCA(I)=0
C
C-----

C-----
CR          FILE-WIDE CHI DATA      (3D RECORD)
C
CC          PRESENT IF ICHIST.GT.1
C
CL      ((CHI(K,J),K=1,ICHIST),J=1,NGROUP),(ISSPEC(I),I=1,NGROUP)
C
CW      NGROUP*(ICHIST+1)=NUMBER OF WORDS
C
CB      FORMAT(4H 3D , 5E12.5/(6E12.5))      CHI
CB      FORMAT(12I6)          ISSPEC
C
CD      CHI(K,J)      FRACTION OF NEUTRONS EMITTED INTO GROUP J AS A
CD                      RESULT OF FISSION IN ANY GROUP. USING SPECTRUM K-
CD      ISSPEC(I)      ISSPEC(I)=K IMPLIES THAT SPECTRUM K IS USED
CD                      TO CALCULATE EMISSION SPECTRUM FROM FISSION
CD                      IN GROUP I
C
C-----

```

```

C-----
CR      ISOTOPE CONTROL AND GROUP INDEPENDENT DATA  (4D RECORD)
C
CL      HABSID,HIDENT,HMAT,AMASS,EFISS,ECAPT,TEMP,SIGPOT,ADENS,KBR,ICHI,
CL      1IFIS,IALF,INP,IN2N,IND,INT,LTOT,LTRN,ISTRPD,
CL      2(IDSCT(N),N=1,NSCMAX),(LORD(N),N=1,NSCMAX,
CL      3((JBAND(J,N),J=1,NGROUP),N=1,NSCMAX),
CL      4((IJJ(J,N),J=1,NGROUP),N=1,NSCMAX)
C
CW      3*MULT+17+NSCMAX*(2*NGROUP+2)=NUMBER OF WORDS
C
CB      FORMAT(H 4D .3(1X,A6)/ 6E12.5/
CB      1(12I6)
C
CD      HABSID          HOLLERITH ABSOLUTE ISOTOPE LABEL - SAME FOR ALL
CD                        VERSIONS OF THE SAME ISOTOPE IN FILE (A6)
CD      HIDENT          IDENTIFIER OF LIBRARY FROM WHICH BASIC DATA
CD                        CAME (E.G. ENDF/B) (A6)
CD      HMAT            ISOTOPE IDENTIFICATION (E.G. ENDF/B MAT NO.) (A6)
CD      AMASS           GRAM ATOMIC WEIGHT
CD      EFISS           TOTAL THERMAL ENERGY YIELD/FISSION (W.SEC/FISS)
CD      ECAPT           TOTAL THERMAL ENERGY YIELD/CAPTURE (W.SEC/FISS)
CD      TEMP            ISOTOPE TEMPERATURE (DEGREES KELVIN)
CD      SIGPOT          AVERAGE EFFECTIVE POTENTIAL SCATTERING IN
CD                        RESONANCE RANGE (BARNS/ATOM)
CD      ADENS           DENSITY OF ISOTOPE IN MIXTURE IN WHICH ISOTOPE
CD                        CROSS SECTIONS WERE GENERATED (A/BARN-CM)
CD      KBR             ISOTOPE CLASSIFICATION
CD                        0=UNDEFINED
CD                        1=FISSILE
CD                        2=FERTILE
CD                        3=OTHER ACTINIDE
CD                        4=FISSION PRODUCT
CD                        5=STRUCTURE
CD                        6=COOLANT
CD                        7=CONTROL
CD      ICHI            ISOTOPE FISSION SPECTRUM FLAG
CD                        ICHI.EQ.0.    USE FILE-WIDE CHI
CD                        ICHI.EQ.1.    ISOTOPE CHI VECTOR
CD                        ICHI.GT.1.    ISOTOPE CHI MATRIX
CD      IFIS            (N.F) CROSS SECTION FLAG
CD                        IFIS=0.    NO FISSION DATA IN PRINCIPAL CROSS
CD                                SECTION RECORD
CD                        1.    FISSION DATA PRESENT IN PRINCIPAL
CD                                CROSS SECTION RECORD

```

CD	IALF	(N.ALPHA) CROSS SECTION FLAG.
CD		SAME OPTIONS AS IFIS
CD	INP	(N.P) CROSS SECTION FLAG
CD		SAME OPTIONS AS IFIS
CD	IN2N	(N.2N) CROSS SECTION FLAG
CD		SAME OPTIONS AS IFIS
CD	IND	(N.D) CROSS SECTION FLAG
CD		SAME OPTIONS AS IFIS
CD	INT	(N.T) CROSS SECTION FLAG
CD		SAME OPTIONS AS IFIS
CD	LTOT	NUMBER OF MOMENTS OF TOTAL CROSS PROVIDED
CD		IN PRINCIPAL CROSS SECTIONS RECORD
CD	LTRN	NUMBER OF MOMENTS OF TRANSPORT CROSS SECTION
CD		PROVIDED IN PRINCIPAL CROSS SECTIONS RECORD
CD	ISTRPD	NUMBER OF COORDINATE DIRECTIONS FOR WHICH
CD		COORDINATE DEPENDENT TRANSPORT CROSS SECTIONS
CD		ARE GIVEN. IF ISTRPD=0, NO COORDINATE DEPENDENT
CD		TRANSPORT CROSS SECTIONS ARE GIVEN.
CD	IDSCT(N)	SCATTERING MATRIX TYPE IDENTIFICATION FOR
CD		SCATTERING BLOCK N. SIGNIFICANT ONLY IF
CD		LORD(N).GT.0
CD		IDSCT(N)=000 + NN.TOTAL SCATTERING. (SUM OF
CD		ELASTIC, INELASTIC, AND (N.2N) SCATTERING
CD		MATRIX TERMS).
CD		-100 + NN. ELASTIC SCATTERING
CD		-200 + NN. INELASTIC SCATTERING
CD		-300 + NN. (N.2N) SCATTERING.-----SEE
CD		NOTE BELOW-----
CD		WHERE NN IS THE LEGENDRE EXPANSION INDEX OF THE
CD		FIRST MATRIX IN BLOCK N
CD	LORD(N)	NUMBER OF SCATTERING ORDERS IN BLOCK N. IF
CD		LORD(N)=0. THIS BLOCK IS NOT PRESENT FOR THIS
CD		ISOTOPE. IF NN IS THE VALUE TAKEN FROM
CD		IDSCT(N). THEN THE MATRICES IN THIS BLOCK
CD		HAVE LEGENDRE EXPANSION INDICES OF NN, NN+1,
CD		NN+2, ..., NN+LORD(N)-1
CD	JBAND(J,N)	NUMBER OF GROUPS THAT SCATTER INTO GROUP J,
CD		INCLUDING SELF-SCATTER. IN SCATTERING BLOCK N.
CD		IF JBAND(J,N).NE.0 THEN IJJ(J,N) MUST SATISFY
CD		THE RELATION 1.LE.IJJ(J,N).LE.JBAND(J,N)
CD	IJJ(J,N)	POSITION OF IN-GROUP SCATTERING CROSS SECTION IN
CD		SCATTERING DATA FOR GROUP J. SCATTERING BLOCK
CD		N. COUNTED FROM THE FIRST WORD OF GROUP J DATA.
CD		IF JBAND(J,N).NE.0 THEN IJJ(J,N) MUST SATISFY
CD		THE RELATION 1.LE.IJJ(J,N).LE.JBAND(J,N)

C
 CN NOTE - FOR (N,2N) SCATTER. THE MATRIX CONTAINS TERMS
 CN SCAT(J TO G). WHICH ARE EMISSION (PRODUCTION)
 CN BASED I.E. ARE DEFINED SUCH THAT MACROSCOPIC
 CN SCAT(J TO G) TIMES THE FLUX IN GROUP J GIVES
 CN THE RATE OF EMISSION (PRODUCTION) OF NEUTRONS
 CN INTO GROUP G.
 C
 C-----

C-----
 CR PRINCIPAL CROSS SECTIONS (5D RECORD)
 C
 CL ((STRPL(J,L),J=1,NGROUP),L=1,LTRN).
 CL 1((STOTPL(J,L),J=1,NGROUP),L=1,LTOT),(SNGAM(J),J=1,NGROUP).
 CL 2(SFIS(J),J=1,NGROUP),(SNUTOT(J),J=1,NGROUP).
 CL 3(CHISO(J),J=1,NGROUP),(SNALF(J),J=1,NGROUP).
 CL 4(SNP(J),J=1,NGROUP),(SN2N(J),J=1,NGROUP).
 CL 5(SND(J),J=1,NGROUP),(SNT(J),J=1,NGROUP).
 CL 6(STRPD(J,I),J=1,NGROUP),I=1,ISTRPD)
 C
 CW (1+LTRN+LTOT+IALF+INP+IN2N+IND+INT+ISTRPD+2*IFIS+
 CW ICHI*(2/(ICHI+1)))*NGROUP=NUMBER OF WORDS
 C
 CB FORMAT(4H 5D . 5E12.5/(6E12.5) LENGTH OF LIST AS ABOVE
 C
 CD STRPL(J,L) PL WEIGHTED TRANSPORT CROSS SECTION
 CD THE FIRST ELEMENT OF ARRAY STRPL IS THE
 CD CURRENT (P1) WEIGHTED TRANSPORT CROSS SECTION
 CD THE LEGENDRE EXPANSION COEFFICIENT FACTOR (2L+1)
 CD IS NOT INCLUDED IN STRPL(J,L).
 CD STOTPL(J,L) PL WEIGHTED TOTAL CROSS SECTION
 CD THE FIRST ELEMENT OF ARRAY STOTPL IS THE
 CD FLUX (P0) WEIGHTED TOTAL CROSS SECTION
 CD THE LEGENDRE EXPANSION COEFFICIENT FACTOR (2L+1)
 CD IS NOT INCLUDED ON STOTPL(J,L).
 CD SNGAM(J) (N,GAMMA)
 CD SFIS(J) (N,F)
 CD SNUTOT(J) TOTAL NEUTRON YIELD/FISSION (PRESENT IF IFIS.GT.0)
 CD CHISO(J) ISOTOPE CHI (PRESENT IF ICHI.EQ.1)
 CD SNALF(J) (N,ALPHA) (PRESENT IF IALF.GT.0)
 CD SNP(J) (N,P) (PRESENT IF INP.GT.0)
 CD SN2N(J) (N,2N) (PRESENT IF IN2N.GT.0) ----SEE
 CD NOTE BELOW----
 CD SND(J) (N,D) (PRESENT IF IND.GT.0)
 CD SNT(J) (N,T) (PRESENT IF INT.GT.0)
 CD STRPD(J,I) COORDINATE DIRECTION I TRANSPORT CROSS SECTION
 CD (PRESENT IF ISTRPD.GT.0)

C
 CN NOTE - THE PRINCIPAL (N,2N) CROSS SECTION SN2N(J) -
 CN IS DEFINED AS THE (N,2N) REACTION CROSS SECTION, -
 CN I.E., SUCH THAT MACROSCOPIC SN2N(J) TIMES THE -
 CN FLUX IN GROUP J GIVES THE RATE AT WHICH (N,2N) -
 CN REACTIONS OCCUR IN GROUP J. tHUS, FOR (N,2,) -
 CN SCATTERING, SN2N(J) = 0.5*(SUM OF SCAT(J TO G) -
 CN SUMMED OVER ALL G). -
 C
 C-----

C-----
 CR ISOTOPE CHI DATA (6D RECORD) -
 C
 CC PRESENT IF ICHI.GT.1 -
 C
 CL ((CHIISO(K,J),K=1,ICHI),J=1,NGROUP),(ISOPEC(I),I=1,NGROUP) -
 C
 CW NGROUP*(ICHI+1)=NUMBER OF WORDS -
 C
 CB FORMAT(4H 6D , 5E12.5/((6E12.5)) CHIISO -
 CB FORMAT(12I6) ISOPEC -
 C
 CD CHIISO(K,J) FRACTION OF NEUTRONS EMITTED INTO GROUP J AS A -
 CD RESULT OF FISSION IN ANY GROUP, USING SPECTRUM K -
 CD ISOPEC(I) ISOPEC(I)=K IMPLIES THAT SPECTRUM K IS USED -
 CD TO CALCULATE EMISSION SPECTRUM FROM FISSION -
 CD IN GROUP I -
 C
 C
 C-----

C-----
 CR SCATTERING SUB-BLOCK (7D RECORD) -
 C
 CC PRESENT IF LORD(N).GT.0 -
 CL ((SCAT(K,L),K=1,KMAX),L=1,LORDN) -
 C
 CC KMAX=SUM OVER J OF JBAND(J,N) WITHIN THE J-GROUP RANGE OF THIS -
 CC SUB-BLOCK. IF M IS THE INDEX OF THE SUB-BLOCK, THE J-GROUP -
 CC RANGE CONTAINED WITHIN THIS SUB-BLOCK IS -
 CC JL=(M-1)*(NGROUP-1)/NSBLOCK+1 TO JU=MINO(NGROUP,JUP), -
 CC WHERE JUP=M*((NGROUP-1)/NSBLOK+1). -
 C
 CC LORDN=LORD(N) -
 CC N IS THE INDEX FOR THE LOOP OVER NSCMAX (SEE FILE STRUCTURE) -
 C

```

C
CD      SCAT(K,L)      SCATTERING MATRIX OF SCATTERING ORDER L. FOR
CD                        REACTION TYPE IDENTIFIED BY IDSCT(N) FOR THIS
CD                        BLOCK. JBAND(J,N) VALUES FOR SCATTERING INTO
CD                        GROUP J ARE STORED AT LOCATIONS K=SUM FROM 1
CD                        TO (J-1) OF JBAND(J,N) PLUS 1 TO K-1+JBAND(J,N).
CD                        THE SUM IS ZERO WHEN J=1. J-TO-J SCATTER IS
CD                        THE IJJ(J,N)-TH ENTRY IN THE RANGE JBAND(J,N).
CD                        VALUES ARE STORED IN THE ORDER (J+JUP),
CD                        (J+JUP-1),...,(J+1),J,(J-1),...,(J-JDN).
CD                        WHERE JUP=IJJ(J,N)-1 AND JDN=JBAND(J,N)-IJJ(J,N).
C
C.....

```

```

C *****
C                                     DATE 05/12/83
C
C
CF      MACRXS
CE      CODE DEPENDENT MACROSCOPIC MULTIGROUP CROSS SECTION FILE
CE      FOR USE IN ONEDANT SOLVER MODULE
C
C
C *****
C
CN      THIS FILE PROVIDES A BASIC BROAD GROUP
CN      LIBRARY, ORDERED BY GROUP
C
C      ORDER OF GROUPS IS ACCORDING TO DECREASING ENERGY
C
C -----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====                                =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS      FILE DATA                                ALWAYS
CS
CS      ***** (REPEAT FOR ALL GROUPS)
CS      *      PRINCIPAL CROSS SECTIONS            ALWAYS
CS      *      SCATTERING CONTROL DATA            NORD.NE.0
CS      *      SCATTERING MATRIX                  NORD.NE.0
CS      *****
C
C -----
C
C -----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME      HOLLERITH FILE NAME - MACRXS - (A6)
CD      HUSE(I)    HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS      FILE VERSION NUMBER
CD      MULT       DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C -----
C -----
CR      FILE CONTROL
C
CL      NGROUP, NMAT, NORD, NED, IOPF, LNG, MAXUP, MAXDN, NPRIN, I2LP1
C
CW      10=NUMBER OF WORDS

```



```

C
CD  NGROUP      NUMBER OF ENERGY GROUPS IN FILE
CD  NMAT        NUMBER OF MATERIALS IN FILE
CD  NGRD        NUMBER OF LEGENDRE SCATTERING ORDERS
CD  NED         NUMBER OF EXTRA EDIT CROSS SECTIONS (IN ADDITION
CD              TO THE BASIC PRINCIPAL CROSS SECTIONS)
CD  IDPF        0/1 NO/YES CROSS SECTION DATA ARE DOUBLE PRECISION
CD  LNG         NUMBER OF THE LAST NEUTRON GROUP(FOR COUPLED SETS)
CD  MAXUP       MAXIMUM NUMBER OF UPSCATTER GROUPS
CD  MAXDN       MAXIMUM NUMBER OF DOWNSCATTER GROUPS
CD  NPRIN       NUMBER OF PRINCIPAL CROSS SECTIONS
CD  IZLP1       0/1 = NO/YES 2L+1 TERM WAS INCLUDED IN LIBRARY
C
C-----
C
C-----
CR          FILE DATA
C
CL  (HMAT(I), I=1,NMAT), (HED(J), J=1,NEDT), (VEL(N), N=1,NGROUP),
CL  1(EMAX(N), N=1,NGROUP), EMIN
C
CW  NMAT+NEDT+2*NGROUP+1=NUMBER OF WORDS
C
CD  HMAT(I)     HOLLERITH MATERIAL LABEL FOR MATERIAL I (A6)
CD  HED(J)      HOLLERITH LABEL FOR J-TH CROSS SECTION POSITION(A6)
CD  VEL(N)      MEAN NEUTRON VELOCITY IN GROUP N (CM/SEC)
CD  EMAX(N)     MAXIMUM ENERGY BOUND OF GROUP N (EV)
CD  EMIN        MINIMUM ENERGY BOUND OF SET (EV)
CD  NEDT        NED+NPRIN
C
CN          THE FOUR BASIC PRINCIPAL CROSS SECTIONS
CN          ALWAYS PRESENT ARE:
CN
CN          HED(1) = 3HCHI
CN          HED(2) = 6HNUSIGF
CN          HED(3) = 5HTOTAL
CN          HED(4) = 3HABS
C
CN          ALSO PRESENT WHEN NPRIN=5 IS:
C
CN          HED(5) = 5HTRANS
C
C-----
C-----
CR          PRINCIPAL CROSS SECTIONS FOR GROUP N
C
CL  ((C(I,J), I=1,NMAT), J=1,NEDT)
C
CW  NMAT*NEDT=NUMBER OF WORDS
C
CD  C(I,J)      PRINCIPAL CROSS SECTIONS
C
CN          BASIC PRINCIPAL CROSS SECTIONS ALWAYS PRESENT ARE:

```

```

CN
CN      J=1  FISSION SPECTRUM
CN      J=2  FISSION NU*FISSION CROSS SECTION
CN      J=3  TOTAL CROSS SECTION
CN      J=4  ABSORPTION CROSS SECTION
C
CN      ALSO PRESENT WHEN NPRIN=5 IS:
C
CN      J=5  TRANSPORT CROSS SECTION
C
C-----
C
C-----
CR      SCATTERING CONTROL BLOCK FOR GROUP N
C
CC      PRESENT IF NORD.GT.0
C
CL      ((NGPB(L,J),L=1,NORD),J=1,NMAT)
CL      ((IFSG(L,J),L=1,NORD),J=1,NMAT)
C
CW      2*NORD*NMAT=NUMBER OF WORDS
C
CD      NGPB(L,J)  NUMBER OF SOURCE GROUPS THAT CAN SCATTER INTO GROUP N
CD      IFSG(L,J)  GROUP NUMBER OF THE FIRST SOURCE GROUP
CD      L          LEGENDRE ORDER NUMBER
CD      J          MATERIAL NUMBER
C
C-----
C-----
CR      SCATTERING SUB-BLOCK FOR GROUP N
C
CC      PRESENT IF NORD.GT.0
C
CL      (SCAT(I),I=1,NTAB)
C
CW      NTAB=NUMBER OF WORDS
C
CD      SCAT(I)    SCATTERING CROSS SECTION
C
CD      NTAB       TABLE LENGTH OF THE CROSS SECTIONS FOR SCATTERING
CD                  INTO GROUP N.  THIS IS FOR ALL MATERIALS AND ALL
CD                  LEGENDRE ORDERS, THUS IT IS THE SUM OF NGPB(L,J)
CD                  OVER L FROM 1 TO NORD AND OVER J FROM 1 TO NMAT.
C
CN      THE SCATTERING CROSS SECTIONS ARE PACKED IN BANDS,
CN      ONE FOR EACH LEGENDRE ORDER AND MATERIAL.  EACH BAND
CN      CONTAINS THE NGPB GROUPS WHICH SCATTER INTO GROUP
CN      N.  THE FIRST SOURCE GROUP NUMBER IS IFSG AND
CN      THE LAST IS IFSG-NGPB+1.  THE NORD BANDS FOR THE
CN      FIRST MATERIAL APPEAR FIRST (P0, P1, ....) FOLLOWED
CN      BY THE NORD BANDS FOR THE SECOND, ETC.
C
CN      HIGHER LEGENDRE ORDER SCATTERING CROSS SECTIONS
CN      INCLUDE A 2*L+1 FACTOR WHERE L IS THE LEGENDRE

```

CN ORDER.
C
C-----
CEOF

SPECIFICATIONS FOR INTERFACE FILE HASBAL

```

C.....
CN                      DATE 07-28-80
C
CP                      HASBAL
C
CE                      MASS BALANCE INFORMATION
C.....

```

```

C-----
CR                      FILE IDENTIFICATION
C
CL                      HNAME, (HUSE (1), 1=1, 2), IVERS
C
CV                      J*MULT + 1 = NUMBER OF WORDS
C
CD                      HNAME      FILE NAME (16)  = 'HASBAL'
CD                      HUSE       USER IDENTIFICATION (216)
CD                      IVERS      FILE VERSION NUMBER
C
CN                      MULT       1 FOR LONG WORD, 2 FOR SHORT WORD BACHETTES
C-----

```

```

C-----
CS                      FILE STRUCTURE
C
CS                      RECORD TYPE      PRESENT IF
CS                      =====
CS                      FILE IDENTIFICATION  ALWAYS
CS                      FILE CONTROL        ALWAYS
CS                      NUCLEIDE IDENTIFICATION AND BASE DATA  ALWAYS
CS                      DISCHARGE BLOCK MATERIAL  HHPD*(HNOB+HPDOB).GT.0
CS                      SUPPLY BLOCK MATERIAL    HMPB*HPSB.GT.0
CS                      INITIAL REACTOR INVENTORY  ALWAYS
CS
CS                      ***** (REPEAT TO SAICT)
CS                      * FUELING INFORMATION      ALWAYS
CS                      * INITIAL LOADING MASS BALANCE DATA  ALWAYS
CS                      * DISCHARGE MATERIAL MASS BALANCE DATA  HHPD*HYPDB.GT.0
CS                      * FIRED FEED MASS BALANCE DATA    HHPF*HPPF.GT.0
CS                      * SUPPLY MATERIAL MASS BALANCE DATA  HMPB*HPSB.GT.0
CS                      * FINAL LOADING MASS BALANCE DATA    ALWAYS
CS                      *****
C-----

```

```

C-----
CR                      FILE CONTROL (10 RECORD)
C
CL                      HNR, HNO, SAICT, HPDB, HHPD, HPDOB, HPSB, HMTS, HPPB, HMPF,
CL                      (KZ (2), 1=1, 10)
C
CV                      20 = NUMBER OF WORDS

```

(CONT)

```

C
C      UNDEFINED DATA IS RESERVED FOR FUTURE USE
C
C      NRP      NUMBER OF NUCLIDES FOR WHICH MASS ACCOUNTING IS
C      MAINTAINED
C      NNO      NUCLIDE NAME REFERENCE OPTION:
C      0 - BY ABSOLUTE NAME (NAME)
C      1 - BY UNIQUE NAME (UNNAME)
C      NAXCT     NUMBER OF SETS OF FUELING MASS BALANCE DATA
C      WRITTEN
C      NPDB      NUMBER OF FUEL DISCHARGE BLOCKS
C      NMPD      MAXIMUM NUMBER OF NUCLIDES IN ANY FUEL
C      DISCHARGE BLOCK
C      NPDBS     NUMBER OF FUEL DELAYED DISCHARGE BLOCKS
C      NPSB      NUMBER OF FUEL SUPPLY BLOCKS
C      NMPS      MAXIMUM NUMBER OF NUCLIDES IN ANY FUEL SUPPLY
C      BLOCK
C      NPFB      NUMBER OF FIXED FEED FUEL BLOCKS
C      NMFP      MAXIMUM NUMBER OF NUCLIDES IN ANY FIXED
C      FEED FUEL BLOCK
C
-----

```

```

C
C      NUCLIDE IDENTIFICATION AND BASIC DATA (2D RECORD)
C
C      (NPN(I), I=1, NNR),
C      ((NPN(K, N), K=1, NMPD), N=1, NPDB),
C      ((NPN(K, N), K=1, NMPS), N=1, NPSB),
C      ((NPN(K, N), K=1, NMFP), N=1, NPFB)
C
C      NULC=NNR + NMPD*NPDB + NMPS*NPSB + NMFP*NPFB = NUMBER OF WORDS
C
C      NPN      NUCLIDE REFERENCE NAME FOR WHICH MASS
C      ACCOUNTING IS MAINTAINED. (16)
C      NDN      REFERENCE NUCLIDES FOR DISCHARGE BLOCK N (ORDER
C      NUMBER IN NPN LIST)
C      NPN      REFERENCE NUCLIDES FOR SUPPLY BLOCK N (ORDER
C      NUMBER IN NPN LIST)
C      NPN      REFERENCE NUCLIDES FOR FIXED FEED BLOCK N
C      (ORDER NUMBER IN NPN LIST)
C
-----

```

```

C
C      DISCHARGE BLOCK MATERIAL (3D RECORD)
C
C      PRESENT IF NMPD*(NPDB + NPDBS).GT.0
C
C      ((DBRASS(I, J), I=1, NMPD), J=1, NPDB),
C      (NDOB(J), J=1, NPDBS), (NCTDOB(J), J=1, NPDBS),
C      (NPDLAY(J), J=1, NPDBS), ((DBRASS(I, J), I=1, NMPD), J=1, NPDBS)
C
C      NPDB*NMPD + NPDBS*(J + NMPD) = NUMBER OF WORDS
C

```

(CONT)

```

C
C0 DBMASS      MASS OF NUCLIDE I IN DISCHARGE BLOCK J
C0 WDOB       DISCHARGE BLOCK TO RECEIVE MATERIAL FROM
C0           DELAYED BLOCK J WHEN THE BLOCK BECOMES
C0           ACTIVE (0 ENTRY IMPLIES SLOT J IS AVAILABLE
C0           FOR DELAYED DISCHARGE).
C0 ECTDOB     FUELING CYCLE REFERENCE NUMBER WHEN DELAYED
C0           DISCHARGE IS CREATED
C0 EFDLAY     FUELING DELAY IN CYCLES ASSOCIATED WITH DELAYED
C0           DISCHARGE BLOCK J
C0 DDBMASS     MASS OF NUCLIDE I IN DELAYED DISCHARGE BLOCK J
C
C-----

```

```

C-----
C0          SUPPLY BLOCK MATERIAL (40 RECORD)
C
C0 PRESENT IF ENPS=EP5B.GT.0
C0
C0 (SBMASS(I,J),I=1,ENPS),J=1,EP5B)
C
C0          EP5B*ENPS = NUMBER OF WORDS
C
C0 SBMASS      MASS OF NUCLIDE I IN SUPPLY BLOCK J
C
C-----

```

```

C-----
C0 INITIAL REACTOR INVENTORY AND FUELING INFORMATION (50 RECORD)
C
C0 NCTI,RTIME,(RMASS(I),I=1,ENR)
C
C0          ENR*2 = NUMBER OF WORDS
C
C0 NCTI       REFERENCE CYCLE NUMBER FOR THE INITIAL REACTOR
C0           MASS BALANCE HISTORY
C0 RTIME      REFERENCE REAL EXPOSURE TIME IN DAYS FOR THE
C0           INITIAL REACTOR MASS BALANCE HISTORY
C0 RMASS      REACTOR INVENTORY OF NUCLIDE I AT BEGINNING OF
C0           MASS BALANCE HISTORY
C
C-----

```

```

C-----
C0          FUELING INFORMATION (60 RECORD)
C
C0 NCT,(ZK(I),I=1,18),RTIE,POWER,THREL,CYSHPT
C
C0          20 = NUMBER OF WORDS
C
C-----

```

(CONT)

C	NCY	REFERENCE CYCLE NUMBER FOR THIS SET OF MASS	-
CD		BALANCE DATA	-
CD	RTIN	REFERENCE REAL EXPOSURE TIME IN DAYS	-
CD		REPRESENTED BY THIS SET OF MASS BALANCE DATA	-
CD	POWER	ELECTRICAL POWER LEVEL OF THE REACTOR (WATTS)	-
CD	THPFL	THERMAL CONVERSION FACTOR FOR THE REACTOR	-
CD		(ELECTRICAL POWER/THERMAL POWER)	-
CD	CNSMPT	RATE OF FUEL CONSUMPTION PER UNIT THERMAL	-
CD		ENERGY GENERATED (KG FISSILE/WATT-DAY)	-
C			-

C	-----		
CR	INITIAL LOADING MASS BALANCE DATA (70 RECORD)		
C			-
CL	(RIHASS(I), I=1, NNRI)		
C			-
CV	NNR = NUMBER OF WORDS		
C			-
CD	RHASS	INITIAL REACTOR MASS (PRIOR TO FUELING) OF	-
CD		NUCLIDE I	-
C			-

C	-----		
CR	DISCHARGE MATERIAL MASS BALANCE DATA (80 RECORD)		
C			-
CC	PRESENT IF NNPD>NNPD.GT.0		
C			-
CL	((TDHASS(I,J), I=1, NNPD), J=1, NNPD),		
CL	((UDHASS(I,J), I=1, NNPD), J=1, NNPD)		
C			-
CV	2*NNPD>NNPD = NUMBER OF WORDS		
C			-
CD	TDHASS	MASS OF NUCLIDE I TRANSFERRED TO DISCHARGE	-
CD		BLOCK J FOR THIS FUELING	-
CD	UDHASS	MASS OF UNAVAILABLE DISCHARGE FROM DISCHARGE	-
CD		BLOCK J	-
C			-

C	-----		
CR	FIXED FEED MASS BALANCE DATA (90 RECORD)		
C			-
CC	PRESENT IF NNPF>NNPF.GT.0		
C			-
CL	((PPHASS(I,J), I=1, NNPF), J=1, NNPF)		
C			-
CV	NNPF>NNPF = NUMBER OF WORDS		
C			-
CD	PPHASS	MASS OF NUCLIDE I ADDED FROM FIXED FEED BLOCK J	-
C			-

(CONT)

```

C-----
CR              SUPPLY MATERIAL MASS BALANCE DATA (100 RECORD)
C
CC      PRESENT IF  NTPS=NTPSB.GT.0
C
CL      ((SPMASS(I,J),I=1,NMPS),J=1,NPSS),
CL      ((PMMASS(I,J),I=1,NMPS),J=1,NPSS),
CL      ((PRMASS(I,J),I=1,NMPS),J=1,NPSS),
CL      ((USMASS(I,J),I=1,NMPS),J=1,NPSS)
C
CW              1*NTPSB*NMPS = NUMBER OF WORDS
C
CD      SPMASS      MASS OF NUCLIDE I ADDED FROM SUPPLY BLOCK J
CD      PMMASS      MASS OF NUCLIDE I LOST FROM INITIAL VOLUME
CD                      TRANSFERRED TO SUPPLY BLOCK J DUE TO
CD                      FABRICATION LOSSES
CD      PRMASS      MASS OF NUCLIDE I LOST FROM INITIAL VOLUME
CD                      TRANSFERRED TO SUPPLY BLOCK J DUE TO
CD                      PROCESSING LOSSES
CD      USMASS      MASS OF NUCLIDE I LOST FROM INITIAL VOLUME
CD                      TRANSFERRED TO SUPPLY BLOCK J DUE TO
CD                      UNAVAILABLE SUPPLY.
C-----

```

```

C-----
CR              FINAL LOADING MASS BALANCE DATA (110 RECORD)
C
CL      (RPMMASS(I),I=1,NMR)
C
CW              NMR = NUMBER OF WORDS
C
CD      RPMMASS      FINAL REACTOR MASS (AFTER FUELING) OF
CD                      NUCLIDE I
C-----

```

```

C.....
C
CDDP      MASSBAL
C
C.....

```



```

C*****
C                      REVISED 11/30/76
C
C
CF          NDXSRF - IR
C
CE          NUCLIDE DENSITY, DATA, CROSS SECTION REFERENCING
C
C*****

C-----
CR          FILE IDENTIFICATION
CL  HNAME.(HUSE(I),I=1,2),IVERS
C
CW  1+3*MULT=NUMBER OF WORDS
C
CD  HNAME          HOLLERITH FILE NAME - NDXSRF - (A6)
CD  HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD  IVERS          FILE VERSION NUMBER
CD  MULT           DOUBLE PRECISION PARAMETER
CD                  1 - A6 WORD IS SINGLE WORD
CD                  2 - A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          SPECIFICATIONS          (1D RECORD)
C
CL  NON.NSN.NNS.NAN.NZONE.NSZ
C
CW  6 - NUMBER OF WORDS
C
CD  NON            NUMBER OF NUCLIDES IN CROSS SECTION DATA
CD  NSN            NUMBER OF NUCLIDE SETS IDENTIFIED
CD  NNS            MAXIMUM NUMBER OF NUCLIDES IN ANY SET
CD  NAN            NUMBER OF DIFFERENT NUCLIDES IN DATA
CD  NZONE          NUMBER OF ZONES
CD  NSZ            NUMBER OF SUBZONES (SUBASSEMBLIES)
C
C-----

```

Figure VII.1 Nuclide Density and Cross Section Referencing File, NDXSRF

```

C-----
C      NUCLIDE REFERENCING DATA      (2D RECORD)
C
CL      (HNNAME(N),N=1,NON),(HNAME(N),N=1,NON),(WPF(N),N=1,NON),
CL      (ATWT(J),J=1,NAN),(NCLN(N),N=1,NON),(NDXS(K,L),K=1,4),L=1,NSN),
CL      ((NOS(I,L),I=1,NNS),L=1,NSN),(NOR(N,L),N=1,NON),L=1,NSN)
C
CW      NAN+2*NON*(1+MULT)+NSN*(4+NNS+NON)=NUMBER OF WORDS
C
CD      HNNAME(N)      UNIQUE REFERENCE NUCLIDE NAME, IN LIBRARY ORDER
CD                        (A6) ALPHANUMERIC
CD      HNAME(N)      ABSOLUTE NUCLIDE REFERENCE, IN LIBRARY ORDER
CD                        (A6) ALPHANUMERIC
CD      WPF(N)      RESERVED
CD      ATWT(N)      ATOMIC WEIGHT
CD      NCLN(N)      NUCLIDE CLASSIFICATION
CD                        1 - FISSILE
CD                        2 - FERTILE
CD                        3 - OTHER CLASSIFICATION
CD                        4 - FISSION PRODUCT
CD                        5 - STRUCTURAL
CD                        6 - COOLANT
CD                        7 - CONTROL ROD
CD                        GREATER THAN 7, UNDEFINED
CD      NDXS(K,L)      REFERENCE DATA FOR SET L
CD                        K = 1, NUMBER OF NUCLIDES IN SET
CD                        K = 2, RESERVED
CD                        K = 3, RESERVED
CD                        K = 4, RESERVED
CD      NOS(I,L)      ORDER NUMBER OF NUCLIDE IN CROSS SECTION DATA
CD                        (IN HNAME LIST) OF NUCLIDE ORDERED I IN
CD                        SET L
CD      NOR(N,L)      ORDER NUMBER OF NUCLIDE IN SET L GIVEN ORDER
CD                        NUMBER N IN CROSS SECTION DATA
C-----

```

Figure VII.1. Nuclide Data and Cross Section Referencing File, NDXSRF (cont)

```

C-----
CR      NUCLIDE CONCENTRATION ASSIGNMENT DATA (3D RECORD)
C
CL      (VOLZ(N).N=1.NZONE).(VFPA(N).N=1.NZONE).(VLSA(M).M=1.NSZ)
CL      (NSPA(N).N=1.NZONE).(NSSA(M).M=1.NSZ).(NZSZ(M).M=1.NSZ)
C
CW      3*(NZONE+NSZ)=NUMBER OF WORDS
C
CD      VOLZ(N)          VOLUMES OF ZONES. CC
CD      VFPA(N)          VOLUME FRACTIONS FOR PRIMARY ZONE ASSIGNMENTS
CD      VLSA             VOLUMES OF SUBZONES
CD      NSPA(N)          NUCLIDE SET REFERENCE. PRIMARY ZONE ASSIGNMENT
CD                        (MAY BE ZERO ONLY IF THERE ARE SUBZONES)
CD      NSSA(M)          NUCLIDE SET REFERENCE ASSIGNMENT TO SUBZONES
CD      NZSZ(M)          ZONE CONTAINING SUBZONE
C
CN      NOTE THAT TO CALCULATE MACROSCOPIC CROSS SECTIONS FOR A ZONE.
CN      IT IS NECESSARY TO CONSIDER THE CONCENTRATION OF EACH NUCLIDE
CN      IN THE PRIMARY SET ASSIGNMENT (UNLESS A ZERO IN NSPA INDICATES
CN      THERE ARE NONE) TIMES THE VOLUME FRACTION. AND THE CONCENTRATION
CN      OF EACH NUCLIDE IN EACH SUBZONE ASSIGNED TO THE ZONE TIMES THE
CN      RATIO OF THE SUBZONE VOLUME TO THE ZONE VOLUME.
C
C-----
CEOF

```

SPECIFICATIONS FOR INTERFACE FILE PERTUB

REVISED 03/01/80

PERTUB

PERTURBATION DATA - REGULAR AND ADJOINT FLUX INTEGRALS

FILE IDENTIFICATION

HNAME, (HUSE(I), I=1,2), IVERS

3*40LT + 1

HNAME HOLLERITH FILE NAME - PERTUB - (A6)

HUSE(I) HOLLERITH USER IDENTIFICATION - (A6)

IVERS FILE VERSION NUMBER

MULT 1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES

FILE REFERENCE INFORMATION (10 RECORD)

BIGDAD, IK, CR, I1, NZONE, NGROUP, IND, N1, N2, N3, N4

11

BIGDAD BIG-DADDY FORMALIZATION FACTOR
INTEGRAL ADJOINT-CHI*FORWARD=HUSIGP/K

IK MULTIPLICATION FACTOR (K-EFF)

CR PRIMITIVE FISSILE CONVERSION RATIO

I1 ABSORPTION RATE IN FISSILE NUCLIDES

NZONE NUMBER OF GEOMETRIC ZONES

NGROUP NUMBER OF NEUTRON ENERGY GROUPS

IND OPTION FOR INCLUDING TRANSPORT INTEGRALS

N1 FLAG ON PROBLEM TYPES -

0- MEANING NO PROBLEMS WERE SOLVED, OR THEY
WERE PSEUDOVALUE PROBLEMS

1 IS ADDED TO THIS IF A FIXED SOURCE FORWARD
PROBLEM WAS SOLVED

10 IS ADDED TO THIS IF A FIXED SOURCE ADJOINT
PROBLEM WAS SOLVED

N2 RESERVED FOR FUTURE USE

N3 RESERVED FOR FUTURE USE

N4 RESERVED FOR FUTURE USE

(CONT)

```

C-----
C      INTEGRALS FOR PRODUCTION SACRO (20 RECORD)
C
C      ((T(N,K),N=1,NZONE),K=1,NGROUP)
C
C      NZONE*NGROUP
C
C      T      FLUX(N)*CHI(KK)*ADJOINT(KK), INTEGRAL OVER KK
C              AND VOLUME, DIVIDED BY THE MULTIPLICATION
C              FACTOR, VOLUME INTEGRALS
C-----

```

```

C-----
C      FLUX, ADJOINT VOLUME INTEGRALS (30 RECORD)
C
C      ((S(N,KK),N=1,NZONE),KK=1,NGROUP)-----NOTE STRUCTURE BELOW-----
C
C      NZONE*NGROUP
C
C      DO 1 K=1,NGROUP
C      1 READ(N) *LIST AS ABOVE*
C
C      S      FLUX(KK)*ADJOINT(N) VOLUME INTEGRALS
C              (INTO GROUP K)
C-----

```

```

C-----
C      INTEGRALS FOR TRANSPORT (40 RECORD)
C
C      PRESENT ONLY IF END.GT.0
C
C      ((D(N,K),N=1,NZONE),K=1,NGROUP)
C
C      NZONE*NGROUP
C
C      D      FLUX(N)*ADJOINT(K) VOLUME INTEGRALS
C-----

```

```

C-----
C
C      PERCENT
C-----

```

SPECIFICATIONS FOR INTERFACE FILE PTATON

```

C.....
C              REFERENCE 02/01/79 ORNL-5180
C
CPT          PTATON
C
CZ          POINT NUCLIDE DENSITIES
C
C.....
  
```

```

C-----
CR          FILE IDENTIFICATION
C
CL          RNAME, (RUSE(I), I=1,2), IVERS
C
CW          3=90LS + 1
C
CD          RNAME          FILE NAME (A6) 'PTATON'
CD          RUSE          USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CW          MULT          1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----
  
```

```

C-----
CR          10          FILE REFERENCE INFORMATION
C
CL          TIME, IPTD2, IPTD3, NCT, NZPT, NPT, NNS, NBLKPT, IPTD9, IPTD10,
CL          NZONE, NSZ, NINTZ, NINTJ, NINR, IPTD16, IPTD17, IPTD18, IPTD19, IPTD20
C
CW          20
C
CD          TIME          REFERENCE REAL TIME, DAYS
CD          IPTD2          RESERVED
CD          IPTD3          RESERVED
CD          NCT          REFERENCE CYCLE NUMBER
CD          NZPT          NUMBER OF ZONES FOR WHICH POINT DATA IS PRESENT
CD          NPT          NUMBER OF POINTS
C
CW          NPT = NZPT(1) + NZPT(2) + ... + NZPT(NZPT)
C
CD          NNS          MAXIMUM NUMBER OF NUCLIDES IN ANY SET
CD          NBLKPT        NUMBER OF BLOCKS OF ATOM DENSITY DATA
CD                      (MUST DIVIDE EVENLY INTO NPT)
CD          IPTD9          RESERVED
CD          IPTD10         OPTION TO INCLUDE VOLUME INFORMATION IF .EQ. 1
CD          NZONE          NUMBER OF ZONES
CD                      FOR DOCUMENTATION (IF NONZERO MUST AGREE WITH OTHER
CD                      PARAMETERS)
CD          NSZ           NUMBER OF SUBZONES
CD                      FOR DOCUMENTATION (IF NONZERO MUST AGREE WITH OTHER
CD                      PARAMETERS)
CD          NINTZ          NUMBER OF FIRST DIMENSION TIME MESH INTERVALS
CD                      FOR DOCUMENTATION (IF NONZERO MUST AGREE WITH OTHER
CD                      PARAMETERS)
  
```

(CONT)

```

CD  NINTJ      NUMBER OF SECOND DIMENSION FINE MESH INTERVALS -
CD  FOR DOCUMENTATION (IF NONZERO MUST AGREE WITH OTHER -
CD  PARAMETERS) -
CD  NINTK      NUMBER OF THIRD DIMENSION FINE MESH INTERVALS -
CD  FOR DOCUMENTATION (IF NONZERO MUST AGREE WITH OTHER -
CD  PARAMETERS) -
CD  IPTD16     RESERVED -
CD  IPTD17     RESERVED -
CD  IPTD18     RESERVED -
CD  IPTD19     RESERVED -
CD  IPTD20     RESERVED -
C
C-----

```

```

C-----
CR  2D      GENERAL INFORMATION -
C
CL  (NZPNT(NZ), NZ=1, NZPT), (NCPNT(NC), NZ=1, NZPT), -
CL  (LCPNT(NZ), NZ=1, NZPT), (LOCPT(NP), NP=1, NPT) -
C
CF  3=NZPT*NPT -
C
CD  NZPNT(NZ)   ZONE NUMBERS -
CD  NCPNT(NZ)   NUMBER OF POINTS IN EACH ZONE -
CD  LCPNT(NZ)   NUCLIDE SET REFERENCE -
CD  FOR DOCUMENTATION -
CD  LOCPT(NP)   POINT LOCATIONS IN THE RANGE 1 TO NINTI*NINTJ*NINTK -
CD  FOR DOCUMENTATION -
CD  (MAY BE ZERO IF NINTI, NINTJ AND NINTK ARE ZERO) -
C
CN  LOCPT = (K-1)*NINTI*NINTJ + (J-1)*NINTI + I -
CN  WHERE I IS FIRST DIMENSION INDEX -
CN  J IS SECOND DIMENSION INDEX -
CN  K IS THIRD DIMENSION INDEX -
C
CN  GIVEN NINTI, NINTJ, NINTK AND LOCPT THE INDICES -
CN  I, J, K MAY BE DETERMINED -
C-----

```

```

C-----
CR  3D      VOLUME INFORMATION -
C
CC  PRESENT IF IPTD10 .EQ. 1 -
C
CL  (VZPNT(NZ), NZ=1, NZPT), (VOLPT(NP), NP=1, NPT) -
C
CF  NZPT*NPT -
C
CD  VZPNT(NZ)   ZONE VOLUME (CM**3) -
CD  VOLPT(NP)   POINT VOLUME (CM**3) -
C
C-----

```

(CONT)

```

C-----
C9      80      POINT NUCLIDE DENSITIES
C9
C9      ((PDEN(N,J),N=1,NNS),J=JL,J0) ---SEE STRUCTURE BELOW---
C9
C9      NNS=((NPT-1)/NBLKPT+1)
C9
C9      DO 1 N=1,NBLKPT
C9      1 READ(I) *LIST AS ABOVE*
C9
C9      WITH N AS THE BLOCK INDEX, JL=(N-1)*((NPT-1)/NBLKPT+1)+1
C9      AND J0=N*((NPT-1)/NBLKPT+1)
C9
C9      PDEN(N,J)      ATOMIC DENSITY OF NUCLIDE ORDERED N IN THE
C9                      ASSOCIATED SET GIVEN IN ORDER FOR EACH POINT
C9
C-----
C=====
C9
C9      PTATDN
C9
C=====

```



```

C*****
C              REVISED 07/23/75 - REVISED 04/01/80
C
CF          PWDINT
C
CE          POWER DENSITY BY INTERVAL
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL      HNAME.(HUSE(I).I=1.2).IVERS
C
CW      1 + 3*MULT=NUMBER OF WORDS
C
CD      HNAME              HOLLERITH FILE NAME - PWDINT - (A6)
CD      HUSE(I)            HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS              FILE VERSION NUMBER
CD      MULT                DOUBLE PRECISION PARAMETER
CD                        1- A6 WORD IS SINGLE WORD
CD                        2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          SPECIFICATIONS (1D RECORD)
C
CL      TIME. POWER. VOL. IM. JM. KM. NCY. NBLK
C
CD      8=NUMBER OF WORDS
C
CD      TIME              REFERENCE REAL TIME. DAYS
CD      POWER              POWER LEVEL FOR ACTUAL NEUTRONICS PROBLEM.
CD                        WATTS THERMAL
CD      VOL                VOLUME OVER WHICH POWER WAS DETERMINED.CC
CD      IM                NUMBER OF FIRST DIMENSION FINE INTERVALS
CD      JM                NUMBER OF SECOND DIMENSION FINE INTERVALS
C
CN          FOR SPECIAL TRIANGULAR GEOMETRIES. IM IS THE NUMBER OF
CN          TRIANGLES ON EACH PLANE AND JM IS NOT DEFINED (SET TO 1)
C
CD      KM                NUMBER OF THIRD DIMENSION FINE INTERVALS
CD      NCY                REFERENCE COUNT (CYCLE NUMBER)
CD      NBLK              =1
C
C-----

```

Figure XII.4 Specifications For Interface File PWDINT

```

C-----
CR                POWER DENSITY VALUES (2D RECORD)
C
CL      ((PWR(I,J),I=1,IM),J=1,JM)-----NOTE STRUCTURE BELOW-----
C
CW      IM*JM=NUMBER OF WORDS
C
CS      DO 1 K=1,KM
CS  1  READ(N)  *LIST AS ABOVE*
C
CD      PWR(I,J)          POWER DENSITY BY INTERVAL, WATTS/CC
C
C-----

C*****
C
CEOF      PWDINT
C
C*****

```

```

C-----
CR 29 ZONE (SUBZONE) NUCLIDE DENSITIES (DISCHARGE) -
C -
CL ((ADEN(N,J),N=1,NNS),J=JL,JU) ---SEE STRUCTURE BELOW--- -
C -
C NNS=((NTZSZ-1)/NBLKAD+1) -
C -
CC DO 1 N=1,NBLKAD -
CC 1 READ(I) *LIST AS ABOVE* -
C -
C WITH N AS THE BLOCK INDEX, JL=(N-1)*((NTZSZ-1)/NBLKAD+1)+1 -
C AND JU=N*((NTZSZ-1)/NBLKAD+1) -
C -
CD ADEN(N,J) ATOMIC DENSITY OF NUCLIDE ORDERED N IN THE -
CD ASSOCIATED SET GIVEN IN ORDER FOR EACH ZONE -
CD FOLLOWED IN ORDER FOR EACH SUBZONE -
C-----

C-----
C QNATON -
C-----

```

SPECIFICATIONS FOR INTERPACE FILE QNATCH

```

C.....
C          REFERENCE 02/01/79 ORNL-5180
C
CQ          QNATCH
C
CZ          ZONE (SUBZONE) NUCLIDE DENSITIES (DISCHARGE)
C
C.....
  
```

```

C-----
C          FILE IDENTIFICATION
C
CZ          NAME, (N7SZ (I), I=1,2), IVERS
C
CQ          3=NUCL * 1
C
CZ          NAME          FILE NAME (A6) 'QNATCH'
CZ          N7SZ          USER IDENTIFICATION (A6)
CZ          IVERS          FILE VERSION NUMBER
C
CQ          N7SZ          1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----
  
```

```

C-----
C          10 FILE REFERENCE INFORMATION
C
CZ          TIME, NCT, N7SZ, NMS, NBLRAD
C
CQ          5
C
CZ          TIME          REFERENCE REAL TIME, DAYS
CZ          NCT          REFERENCE CYCLE NUMBER
CZ          N7SZ          NUMBER OF ZONES PLUS NUMBER OF SUBZONES
CZ          NMS          MAXIMUM NUMBER OF NUCLIDES IN ANY SET
CZ          NBLRAD          NUMBER OF BLOCKS OF ATOM DENSITY DATA
CZ                          (N7SZ DIVIDED EVENLY INTO N7SZ)
C
C-----
  
```

(CONT)

```

C*****
C                                     REVISED 11/30/76
C
CF      RAFLUX-IV
CE      REGULAR ANGULAR FLUX
C
C*****

```

```

CD      ORDER OF GROUPS IS ACCORDING TO DECREASING
CD      ENERGY.

```

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2),IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - RAFLUX - (A6)
CD      HNAME          HOLLERITH FILE NAME -      -(A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR      SPECIFICATIONS      (1D RECORD)
C
CL      NDIM,NGROUP,NINTI,NINTJ,NINTK,NDIR,EFFK,POWER
C
CW      8=NUMBER OF WORDS
C
CD      NDIM           NUMBER OF DIMENSIONS
CD      NGROUP         NUMBER OF GROUPS
CD      NINTI          NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD      NINTJ          NUMBER OF SECOND DIMENSION FINE MESH INTERVALS.
CD                   NINTJ.EQ.1 IF NDIM.EQ.1
CD      NINTK          NUMBER OF THIRD DIMENSION FINE MESH INTERVALS.
CD                   NINTK.EQ.1 IF NDIM.LE.2
CD      NDIR           NUMBER OF DIRECTIONS
CD      EFFK           EFFECTIVE MULTIPLICATION FACTOR
CD      POWER          POWER IN WATTS TO WHICH FLUX IS NORMALIZED
C
C-----

```

```

C-----
CR          REGULAR ANGULAR FLUXES AT FIRST DIMENSION BOUNDARIES
C          (2D RECORD)
C
CL          ((AFREGI(M,I),M=1,NDIR),I=1,NBDYI)----NOTE STRUCTURE BELOW---
C
CW          NDIR*NBDYI=NUMBER OF WORDS
C
C          DO 1 L=1,NGROUP
C          DO 1 K=1,NINTK
C          DO 1 J=1,NINTJ
C          1 READ (N) *LIST AS ABOVE*
C
CD          AFREGI(M,I)          REGULAR FIRST DIMENSION BOUNDARY ANGULAR FLUX
CD          NBDYI                =NINTI+1, NUMBER OF FIRST DIMENSION FINE MESH
CD                                BOUNDARIES.
C
C-----

```

```

C-----
CR          REGULAR ANGULAR FLUXES AT SECOND DIMENSION BOUNDARIES
C          (3D RECORD)
C
CC          PRESENT IF NDIM.GE.2
C
CL          ((AFREGJ(M,I),M=1,NDIR),I=1,NINTI)----NOTE STRUCTURE BELOW----
C
CW          NDIR*NINTI=NUMBER OF WORDS
C
C          DO 1 L=1,NGROUP
C          DO 1 K=1,NINTK
C          DO 1 J=1,NBDYJ
C          1 READ (N) *LIST AS ABOVE*
C
CD          AFREGJ(M,I)          REGULAR SECOND DIMENSION BOUNDARY ANGULAR FLUX
CD          NBDYJ                =NINTJ+1, NUMBER OF SECOND DIMENSION FINE MESH
CD                                BOUNDARIES.
C
C-----

```

```

C-----
CR      REGULAR ANGULAR FLUXES AT THIRD DIMENSION BOUNDARIES -
C      (4D RECORD) -
C -
CC      PRESENT IF NDIM.EQ.3 -
C -
CL      ((AFREGK(M,I),M=1,NDIR),I=1,NINTI)-----NOTE STRUCTURE BELOW----- -
C -
CW      NDIR*NINTI=NUMBER OF WORDS -
C -
C      DO 1 L=1,NGROUP -
C      DO 1 K=1,NBDRYK -
C      DO 1 J=1,NINTJ -
C      1 READ (N) *LIST AS ABOVE* -
C -
CD      AFREGK(M,I)      REGULAR THIRD DIMENSION BOUNDARY ANGULAR FLUX -
CD      NBDRYK          =NINTK+1, NUMBER OF THIRD DIMENSION FINE MESH -
CD                      BOUNDARIES. -
C -
C-----
CEOF

```

```

C*****
C                                     DATE 12/13/85
C
CF      RAFLXM
CE      CODE DEPENDENT COMPUTATIONAL-ORDERED ANGULAR FLUX AT CELL
CE      EDGES FOR TWODANT CODE
C
C*****

```

```

C-----
C
C
CN      THIS FILE PROVIDES THE EDGE ANGULAR FLUX AS ORDERED
CN      BY THE CODE
C
C
C-----

```

```

C-----
C
CD      ORDER OF GROUPS IS ACCORDING TO DECREASING
CD      ENERGY. NOTE THAT DOUBLE PRECISION FLUXES ARE
CD      GIVEN WHEN MULT=2
C
C-----

```

```

C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS
CS      ***** (REPEAT FOR ALL GROUPS)
CS      *      (GROUP 1 IS FIRST)
CS      *      ***** (REPEAT FOR ALL DIRECTIONS)
CS      *      *      COMPUTATIONAL COSINES                ALWAYS
CS      *      *      VERTICAL-EDGE ANGULAR FLUX          ALWAYS
CS      *      *      HORIZONTAL-EDGE ANGULAR FLUX        ALWAYS
CS      *      *****
CS      *****
C
C-----

```

```

C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C

```



```

CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - RAFLXM - (A6)
CD      HUSE(I)         HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT            DOUBLE PRECISION PARAMETER
CD                        1- A6 WORD IS SINGLE WORD
CD                        2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR      SPECIFICATIONS      (1D RECORD)
C
CL      NDIM,NGROUP,NINTI,NINTJ,NINTK,EFFK,POWER
C
CW      8 =NUMBER OF WORDS
C
CD      NDIM            NUMBER OF DIMENSIONS
CD      NGROUP          NUMBER OF ENERGY GROUPS
CD      NINTI           NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD      NINTJ           NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD      NINTK           NUMBER OF THIRD DIMENSION FINE MESH INTERVALS.
CD                        NINTK.EQ.1 IF NDIM.LE.2
CD      EFFK            EFFECTIVE MULTIPLICATION FACTOR
CD      POWER           POWER IN WATTS TO WHICH FLUX IS NORMALIZED
C
C-----

```

```

C-----
CR      COMPUTATIONAL COSINES
C
CL      XMU,XETA,WEIGHT,XM
C
CW      4*MULTI
C
CD      XMU             MU COSINE
CD      XETA            ETA COSINE
CD      WEIGHT          WEIGHT
CD      XM              COMPRESSED COSINE TABLE INDEX
C
C-----

```

```

C-----
CR      VERTICAL EDGE ANGULAR FLUX
C
CL      ((VEDGE(I,J),I=NBDRI),J=1,NINTJ)
C
CW      NBDRI*NINTJ*MULTI=NUMBER OF WORDS
C
CD      VEDGE(I,J)      VERTICAL-EDGE-BOUNDARY ANGULAR FLUX

```

```

C
CD      NBDRYI      NINTI+1 (NUMBER OF FIRST DIMENSION FINE MESH
CD      BOUNDARIES)
C
C-----

```

```

C-----
CR      HORIZONTAL EDGE ANGULAR FLUX
C
CL      ((HEDGE(I,J),I=1,NINTI),J=1,NBDRYJ)
C
CW      NINTI*NBDRYJ*MULTI=NUMBER OF WORDS
C
CD      HEDGE(I,J)   HORIZONTAL-EDGE-BOUNDARY ANGULAR FLUX
C
CD      NBDRYJ      NINTJ+1 (NUMBER OF SECOND DIMENSION FINE MESH
CD      BOUNDARIES)
C
C-----

```

CEOF

```

C*****
C          REVISED 07/23/75 - REVISED 04/01/80
C
CF          RTFLUX
C
CE.         REGULAR TOTAL FLUXES
C
C*****

```

ORDER OF GROUPS IS ACCORDING TO DECREASING
ENERGY. NOTE THAT DOUBLE PRECISION FLUXES ARE
GIVEN WHEN MULT.EQ.2

```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME.(HUSE(I),I=1,2).IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CD          HNAME          HOLLERITH FILE NAME - RTFLUX - (A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CD          MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS A SINGLE WORD
CD                      2- A6 WORD IS A DOUBLE PRECISION WORD
C
C-----

```

Figure XII.1 Specifications for Interface File RTFLUX

```

C-----
CR          SPECIFICATIONS   (1D RECORD)
C
CL  NDIM,NGROUP,NINTI,NINTJ,NINTK,ITER,EFFK,POWER
C
CW  8=NUMBER OF WORDS
C
CD  NDIM          NUMBER OF DIMENSIONS
CD  NGROUP        NUMBER OF ENERGY GROUPS
CD  NINTI         NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD  NINTJ         NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD  NINTK         NUMBER OF THIRD DIMENSION FINE MESH INTERVALS
CD                NINTK.EQ.1 IF NDIM.LE.2
C
CN          FOR MESHPOINT EDGE LOCATIONS. NINTI,NINTJ, AND NINTK ARE
CN          INTERPRETED AS THE NUMBER OF POINTS (ONE MORE THAN THE
CN          NUMBER OF INTERVALS)
CN          FOR SPECIAL TRIANGULAR GEOMETRIES. NINTI IS THE NUMBER OF
CN          POINTS ON EACH PLANE. AND NINTJ IS SET TO 1.
C
CD  ITER          OUTER ITERATION NUMBER AT WHICH FLUX WAS WRITTEN
CD                MADE NEGATIVE FOR MESH EDGE POINTS
CD  EFFK          EFFECTIVE MULTIPLICATION FACTOR
CD                SET TO ZERO IF FIXED SOURCE PROBLEM
CD  POWER         POWER IN WATTS TO WHICH FLUX IS NORMALIZED
C
C-----

C-----
CR          ONE DIMENSIONAL REGULAR TOTAL FLUX (2D RECORD)
C
CC          PRESENT IF NDIM.EQ.1
C
CL  ((FREG(I,J),I=1,NINTI),J=1,NGROUP)
C
CW  NINTI*NGROUP*MULT=NUMBER OF WORDS
C
CD  FREG(I,J)     ONE DIMENSIONAL REGULAR TOTAL FLUX BY INTERVAL
CD                AND GROUP
C
C-----

```

Figure XII.1 Specifications for Interface File RTFLUX (con't.)

```

C-----
CR          MULTI-DIMENSIONAL REGULAR TOTAL FLUX (3D RECORD)
C
CC          PRESENT IF NDIM.GE.2
C
CL          ((FREG(I,J),I=1,NINTI),J=1,NINTJ)-----NOTE STRUCTURE BELOW
C
CW          NINTI*NINTJ*MULT=NUMBER OF WORDS
C
CS          DO 1 L=1,NGROUP
CS          DO 1 K=1,NINTK
CS          1 READ(N) *LIST AS ABOVE*
C
CD          FREG(I,J)    MULTIDIMENSIONAL REGULAR TOTAL FLUX
CD                      BY INTERVAL FOR EACH GROUP
C
C-----

C*****
C
CEOF          RTFLUX
C
C*****

```

SPECIFICATIONS FOR INTERFACE FILE REFUEL

```

C.....
CM                                DATE 01-16-81
C
C*                                REFUEL
C
CS                                FUEL MANAGEMENT SPECIFICATIONS
C.....

```

```

C-----
CM                                FILE IDENTIFICATION
C
CL                                RNAME, (HUSE (1), I=1,2), IVERS
C
CS                                J=HULT * 1 = NUMBER OF WORDS
C
CD                                RNAME          FILE NAME (A6) = 'REFUEL'
CD                                HUSE           USER IDENTIFICATION (2A6)
CD                                IVERS          FILE VERSION NUMBER
C
CM                                HULT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C-----

```

```

C-----
CS                                FILE STRUCTURE
CS
CS                                RECORD TYPE          PRESENT IF
CS                                =====
CS                                FILE IDENTIFICATION    ALWAYS
CS                                FILE CONTROL          ALWAYS
CS                                NOCLINE IDENTIFICATION AND BASE DATA  ALWAYS
CS                                TRANSITION DATA FOR FUEL RECYCLE      NTS.GT.0
CS                                FIXED FUEL PRED MATERIAL DATA BLOCKS  NHTF*NTPB.GT.0
CS                                SUPPLY AND DISCHARGE REFERENCE DATA  NHTS*NPSB+NHPD*NPD8.GT.0
CS                                SUPPLY BLOCK MATERIAL ALLOCATION        NPD8=NPSB.GT.0
CS
CS                                ***** (REPEAT TO NPTS)
CS                                * FUEL MANAGEMENT CONTROL SPECIFICATIONS  ALWAYS
CS                                * FUEL MANAGEMENT SPECIFICATIONS          ALWAYS
CS                                *****
C-----

```

```

C-----
CM                                FILE CONTROL (10 RECORD)
C
CL                                RNC, RNX, RNR, RNO, RQ1, RQ2, RQ3, RQ4, RQ5, RQ6, RQ7, RQ8, RQ9, RQ0,
CL                                RNP0, RNP1, RNP2, RNP3, RNP4, RNP5, RNP6, RNP7, RNP8, RNP9, RNP0,
C
CM                                20 = NUMBER OF WORDS
C
CM                                UNOZPNPD DATA IS RESERVED FOR FUTURE USE

```

(CONT)

```

C.      NWZ      *** RESERVED ***
CD      NWX      *** RESERVED ***
CD      NWR      TOTAL NUMBER OF NUCLIDE REFERENCES
CD      NWO      NUCLIDE REFERENCING OPTION
CD              0 BY ABSOLUTE NAME (NANAME)
CD              1 BY UNIQUE USER NAME (NNNAME)
CD      NQN      NUMBER OF NUCLIDE REFERENCES IN SUPPLEMENTAL
CD              LIST (IF THIS VALUE IS 0, A DEFAULT LIST IS
CD              GENERATED--SEE NIN DESCRIPTION IN NUCLIDE
CD              IDENTIFICATION AND BASE DATA)
CD      NTD      *** RESERVED ***
CD      NTS      NUMBER OF TRANSITION SPECIFICATIONS
CD      NQ      *** RESERVED ***
CD      NTPB     NUMBER OF FIXED FUEL FEED BLOCKS
CD      NMPB     MAXIMUM NUMBER OF NUCLIDES IN ANY FIXED FUEL
CD              FEED BLOCK
CD      NPSB     NUMBER OF FUEL SUPPLY (RECYCLE) BLOCKS
CD      NMPS     MAXIMUM NUMBER OF NUCLIDES IN ANY SUPPLY BLOCK
CD              (IF NMPS IS 0 WHILE NPSB IS NOT, A DEFAULT
CD              NUCLIDE LIST IS GENERATED FOR EACH SUPPLY BLOCK
CD              --SEE NSPN DESCRIPTION IN SUPPLY AND DISCHARGE
CD              REFERENCE DATA)
CD      NPOB     NUMBER OF FUEL DISCHARGE BLOCKS
CD      NMPO     MAXIMUM NUMBER OF NUCLIDES IN ANY DISCHARGE
CD              BLOCK (IF THIS VALUE IS 0 WHILE NPOB IS NOT,
CD              A DEFAULT NUCLIDE LIST IS GENERATED FOR EACH
CD              BLOCK--SEE NDNH DESCRIPTION IN SUPPLY AND
CD              DISCHARGE REFERENCE DATA)
CD      NPTS     NUMBER OF FUEL MANAGEMENT SPECIFICATION SETS
CD      NEC      *** RESERVED ***
CD      NPDDB     MAXIMUM NUMBER OF DELAYED DISCHARGE BLOCKS
CD              (A DELAYED DISCHARGE BLOCK IS CREATED AND
CD              MAINTAINED FOR ANY MATERIAL DISCHARGED WITH A
CD              FUELING DELAY)
C
C-----
C      NUCLIDE IDENTIFICATION AND BASE DATA (2D RECORD)
C
C      (NPN(I), I=1, NNR), (NIN(J), J=1, NQN), (PLP(I), I=1, NNR),
C      (PLP(I), I=1, NNR), (PQ(I), I=1, NNR), (NQ(I), I=1, NNR)
C
C      NULT* (NNR + NQN) + 3*NMP = NUMBER OF WORDS
C
C      NPN      NUCLIDE REFERENCE NAMES FOR NUCLIDE ORDERED 1
C              IN THESE SPECIFICATIONS FOR FUEL MOVEMENT (SEE
C              OPTION NMO). THIS LIST IS FOR ALL MATERIALS
C              MOVED AND ACCOUNTED FOR. (A6)
C

```

(CONT)

CO HIM NUCLEIDE REFERENCE NAMES FOR NORMAL FUEL
 CO MOVEMENT AND FOR FUEL DISCHARGE; HOWEVER, NO
 CO MASS BALANCE ACCOUNTING IS MADE FOR THESE
 CO NUCLEIDES. IN ADDITION, THESE NUCLEIDES ARE NOT
 CO INCLUDED IN RECYCLE SUPPLY PROCESSING. (A6)
 C
 CN NOTE: IF HQ=0 IN THE FILE CONTROL (10) RECORD, THEN A
 CN DEFAULT HIM LIST IS GENERATED FROM THE LIBRARY
 CN MATERIALS THAT ARE CLASSIFIED AS FISSILE,
 CN FERTILE, OTHER ACTINIDE OR FISSION PRODUCT AND
 CN THAT ARE NOT ALREADY PRESENT IN THE HIM LIST.
 C
 CN NOTE: NUCLEIDES NOT PRESENT IN EITHER HFP OR HIM ARE
 CN ASSUMED TO BE NON-MOBILE STRUCTURAL OR COOLANT
 CN MATERIAL.
 C
 CO PLP FABRICATION LOSS FRACTIONS
 CO PLP PROCESSING LOSS FRACTIONS
 CO PQ *** RESERVED ***
 CO HQ *** RESERVED ***
 C

C-----
 CR TRANSITION DATA FOR FUEL RECYCLE (30 RECORD)
 C
 CO PRESENT IF HTS.GT.0
 C
 CL (TSP(I), I=1, HTS), ((NTRN(K,I), K=1, 2), I=1, HTS)
 C
 CN J=HTS = NUMBER OF WORDS
 C
 CO TSP(I) TRANSITION FRACTION FOR THE NUCLEIDE PAIR I
 CO NTRN(1,I) ORIGINAL NUCLEIDE I REFERENCE (ORDER NUMBER IN
 CO HFP LIST)
 CO NTRN(2,I) PRODUCT NUCLEIDE I REFERENCE (ORDER NUMBER IN
 CO HFP LIST)
 C
 CN THESE SPECIFICATIONS ALLOW DECAY OF ONE NUCLEIDE TO ITS
 CN PRODUCT, OR ALLOW TRANSLATION OF NUCLEIDES IN RECYCLED
 CN MATERIAL. MULTIPLE PRODUCTS CAN BE SPECIFIED FOR THE
 CN SAME ORIGINAL NUCLEIDE BUT THE SUM OF THE TRANSITION
 CN FRACTIONS MUST BE LESS THAN OR EQUAL TO 1.0
 C

C-----
 CR FIRED FUEL FEED MATERIAL DATA BLOCKS (40 RECORD)
 C
 CO PRESENT IF HFPF=HFPB.GT.0
 C
 CL ((HFPN(I,J), I=1, HFPF), J=1, HFPB), ((ADB(I,J), I=1, HFPF), J=1, HFPB)
 C
 CN 2*HFPF*HFPB = NUMBER OF WORDS
 C

(CONT)


```

C      NPN          REFERENCE NUCLIDES FOR BLOCK J (ORDER NUMBER
C      CD          IN NPN LIST)
C      CN
C      CN          NOTE: ZEROS MUST BE ADDED TO THE END OF THE NPN STRINGS
C      CD          IN ORDER TO BLOCK THE ARRAY PROPERLY.
C      CD
C      CD          ADB          ATOM DENSITY OF NUCLIDE NPN(I,J) FOR FEED
C      CD          MATERIAL (ATOMS/B-CM)
C      C

```

```

C-----
C      CN          SUPPLY AND DISCHARGE REFERENCE DATA (50 RECORD)
C      C
C      CC          PRESENT IF NPNF=NPSB+NPD=NPDN.GT.0
C      C
C      CL          ((NPN(I,J),I=1,NPFS),J=1,NPSB),
C      CL          ((NPN(K,I),K=1,NPD),I=1,NPDN)
C      C
C      CD          NPFS=NPSB + NPD=NPDN = NUMBER OF WORDS
C      C
C      CD          NPN          REFERENCE NUCLIDES FOR SUPPLY BLOCK J (ORDER
C      CD          NUMBER IN NPN LIST)
C      C
C      CN          NOTE: IF NPFS .EQ. 0 WHILE NPSB .NE. 0, A DEFAULT LIST OF
C      CN          ALL NPN NUCLIDES IS GENERATED FOR EACH SUPPLY BLOCK
C      C
C      CD          NPN          REFERENCE NUCLIDES FOR DISCHARGE BLOCK I (ORDER
C      CD          NUMBER IN NPN LIST)
C      C
C      CN          NOTE: IF NPD .EQ. 0 WHILE NPDN .NE. 0, A DEFAULT LIST OF
C      CN          ALL NPN NUCLIDES IS GENERATED FOR EACH DISCHARGE
C      CN          BLOCK
C      C
C      CN          NOTE: ZEROS MUST BE ADDED TO THE END OF THE NPN AND NPN
C      CN          STRINGS IN ORDER TO BLOCK THE ARRAY PROPERLY.
C      C
C-----

```

```

C-----
C      CN          SUPPLY BLOCK MATERIAL ALLOCATION (60 RECORD)
C      C
C      CC          PRESENT IF NPDN=NPSB.GT.0
C      C
C      CC          ((NPN(J,I),J=1,NPSB),I=1,NPDN), (NPN(I),I=1,NPDN)
C      C
C      CD          NPDN=(1 + NPSB) = NUMBER OF WORDS
C      C
C      CD          NPN          FRACTION OF MATERIAL IN DISCHARGE BLOCK I TO
C      CD          PUT IN SUPPLY BLOCK J.
C      CD          NPN          EXCESS MATERIAL OPTION FOR FUEL DISCHARGE
C      CD          0-EXCESS MATERIAL NOT USED IN THE REACTOR
C      CD          1-EXCESS AVAILABLE IN THE NEXT REFUELING
C      C

```

(CONT)

C
 CN A RECORD IS KEPT OF THE MASS OF THE DISCHARGE
 CN MATERIAL FOR EACH BLOCK. SUPPLY BLOCKS ARE MADE UP
 CN OF MATERIAL TRANSFERRED FROM DISCHARGE BLOCKS AFTER
 CN A RECYCLE DELAY, ACCOUNTING FOR PROCESSING AND
 CN FABRICATION LOSSES AND TRANSITIONS. SUPPLY MATERIAL IS
 CN ALLOCATED UNIFORMLY INTO ALL FEED ZONES REFERENCED
 CN BASED ON VOLUME FRACTIONS.
 C
 C-----

C-----
 CR FUEL MANAGEMENT CONTROL SPECIFICATIONS (7D RECORD)
 C
 CL NPST,NIS,ISZN,NPHO, (JI (I), I=1, 16)
 C
 CN 20 = NUMBER OF WORDS
 C
 CD NPST NUMBER OF DIFFERENT INSTRUCTION LISTS IN THIS
 CD SPECIFICATION
 CD NIS MAXIMUM NUMBER OF ZONES (SUBZONES) IN EACH
 CD INSTRUCTION LIST
 C
 CN NOTE: FOR NPHO=1 (FUEL RELOCATION), NIS IS THE NUMBER
 CN OF ZONE ENTRIES INCLUDING THE 0 TO TERMINATE
 CN THE EXIT ZONE AND FEED ZONE LIST AND THE TWO
 CN 0'S AT THE END OF THE MOVEMENT LIST.
 C
 CD ISZN FLAG TO INDICATE ZONE OR SUBZONE REFERENCES
 CD 0-MOVE ZONES
 CD 1-MOVE SUBZONES
 CD 2-MOVE ZONES TO SUBZONES (FOR NPHO=1 ONLY)
 CD 3-MOVE SUBZONES TO ZONES (FOR NPHO=1 ONLY)
 CD NPHO FUEL MOVEMENT SPECIFICATION OPTION:
 CD 0-NORMAL FUEL ZONE MOVEMENT
 CD 1-FUEL RELOCATION ZONE MOVEMENT (CONTENTS OF
 CD THE SPECIFIED EXIT ZONES ARE TO BE VOLUME
 CD AVERAGED AND ADDED TO SPECIFIED FEED ZONES
 CD WITHOUT CHECKING THE FEED ZONE VOLUMES)
 C
 CN NOTE: NPST MUST BE 1 FOR NPHO=1.
 C
 C-----

C-----
 CR FUEL MANAGEMENT SPECIFICATIONS (8D RECORD)
 C
 CL (NFB (L), L=1, NPST), (NFPB (L), L=1, NPST), (NSB (L), L=1, NPST),
 CL (NOB (L), L=1, NPST), (NPD (L), L=1, NPST),
 CL ((NZ (Z, L), I=1, NZS), L=1, NPST)
 C
 CN NPST*(NIS + 5) = NUMBER OF WORDS
 C
 (CONT)

C
 CD NPB FIXED FEED BLOCK REFERENCE PRIOR TO RECYCLE
 CD NPPB FIXED FEED BLOCK IF RECYCLE IS PRESENT
 CD NSB SUPPLY BLOCK REFERENCE (RECYCLE)
 CD NDB DISCHARGE BLOCK REFERENCE
 CD NPD REFUELING DELAY IN AVAILABILITY FOR RECYCLE
 CD 0-NO DELAY; THE DISCHARGED MATERIAL IS
 CD AVAILABLE AS RECYCLE SUPPLY FOR THE
 CD NEXT FUEL CYCLE
 CD N-DELAY "N" CYCLES; THE DISCHARGED MATERIAL
 CD IS AVAILABLE AS RECYCLE SUPPLY AFTER "N"
 CD CYCLES FROM THE CURRENT CYCLE HAVE
 CD ELAPSED (A DELAYED DISCHARGE BLOCK IS
 CD CREATED FOR EACH ZONE/SUBZONE DISCHARGED
 CD WITH A DELAY)
 CD NZ ZONE/SUBZONE (SEE ISM) NUMBER FOR FUEL
 CD MOVEMENT
 C
 C
 CN FOR NPHO=0: NPHO SETS OF LISTS OF ZONES (SUBZONES) ARE PRESENTED
 CN IN WHICH THE STARTING ZONE IS TO BE REFUELED AND ITS
 CN MATERIAL IS TO BE MOVED INTO THE NEXT ZONE SPECIFIED,
 CN CONTINUING TO MOVE MATERIAL THROUGH THE LIST UNTIL THE
 CN LAST ZONE IS REACHED. ITS MATERIAL IS TRANSFERRED TO
 CN A DISCHARGE BLOCK UNLESS THE ZONE NUMBER IS NEGATIVE,
 CN INDICATING CLOSED-LOOP FUEL MOVEMENT IN WHICH THE
 CN CONTENTS OF THE LAST ZONE ARE MOVED TO THE FIRST ZONE.
 CN THE ZONE LIST IS TERMINATED BY THE FIRST NZ VALUE
 CN .LE. 0.
 C
 CN FOR NPHO=1: ONE LIST OF ZONES (SUBZONES) IS PRESENTED FOR FUEL
 CN RELOCATION. THE ZONE LIST CONSISTS OF A SET OF EXIT
 CN ZONES TERMINATED BY A 0 ZONE VALUE FOLLOWED BY A SET
 CN OF FEED ZONES TERMINATED BY A 0 ZONE VALUE. FOLLOWING
 CN THE FEED ZONE SET, OTHER SETS OF EXIT ZONES AND FEED
 CN ZONES MAY BE GIVEN. THE MOVEMENT LIST IS TERMINATED
 CN WHEN TWO SUCCESSIVE 0 ZONE VALUES ARE ENCOUNTERED OR
 CN WHEN THE END OF THE NZS LIST OF ZONES IS ENCOUNTERED.
 CN FOR EACH EXIT ZONE/FEED ZONE SET, THE CONCENTRATIONS IN
 CN THE EXIT ZONES ARE VOLUME AVERAGED AND PLACED IN THE
 CN FEED ZONES SPECIFIED WITHOUT CHECKING THE FEED ZONE
 CN VOLUMES. THE ORIGINAL EXIT ZONES REMAIN UNCHANGED
 CN (OTHER SPECIFICATIONS ARE NEEDED TO REFUEL OR TO MOVE
 CN MATERIAL INTO EXIT ZONES). IN ADDITION, THERE IS NO
 CN MASS BALANCE ADJUSTING FOR FUEL RELOCATION. NPB, NPPB,
 CN NSB, NDB, AND NPD MUST BE 0 FOR FUEL RELOCATION
 CN ZONE MOVEMENT.
 C
 C-----

(CONT)

```

C-----
C1 COST DATA (90 RECORD)
C1
C1 PXL,PXL,PXI,PXI,PLF,PLA,PLB,PCT,PPT,PST,PST,PST,PST,
C1 PET,PRA,PRB,UOC,UWC,UPC,UTE,UTE,IFE,IFE,IFE,IFE,IFE,IFE,
C1 IFE,IFE,IFE,IFE,IFE,IFE,IFE,IFE,IFE,IFE,IFE,IFE,IFE,IFE,
C1
C1 47 = NUMBER OF WORDS
C1
C1
C1 PXL FABRICATION LOSS FRACTION
C1 PXL PROCESSING LOSS FRACTION
C1 PXI FRACTION OF INITIAL LOADING AND FABRICATION TO BE
C1 PXI CARRIED OVER LIFE OF PLANT
C1 PPT FRACTION OF ACTUAL MAKE-UP FUEL THAT MUST BE CARRIED
C1 PPT ON HAND FOR REPLACEMENT OVER AND ABOVE USUAL REFUELING
C1 PPT (NOT APPLIED TO INITIAL INVENTORY, BUT TO MAKE-UP
C1 PPT QUANTITIES OVER PERIOD)
C1 PLF REACTOR PLANT LOAD FACTOR
C1 PLF (CAPACITY DIVIDED BY DESIGN CAPACITY)
C1
C1 NOTE: THE DESIGN CAPACITY IS USED IF THE CORE HISTORY IS RUN
C1 AT THE DESIGN CAPACITY. IF THE CORE HISTORY IS RUN ON
C1 AN EXPONENTIAL LOAD FACTOR, THE AVERAGE CAPACITY IS USED.
C1
C1 PLI INITIAL PLANT LOAD FACTOR IF THE LOAD FACTOR DECREASES
C1 PLI EXPONENTIALLY. NOT USED IF LOAD FACTOR IS CONSTANT.
C1
C1 PLA ***RESERVED***
C1 PLB ***RESERVED***
C1 PCT CONVERSION COST LEAD TIME (FROM START OF USE OF FUEL,
C1 PCT IN YEARS)
C1 PPT FABRICATION COST LEAD TIME
C1 PST SHIPPING COST LEAD TIME
C1 PPT HOT STORAGE LAG TIME (FROM REMOVAL FROM THE REACTOR,
C1 PPT IN YEARS)
C1 PST SHIPPING COST LAG TIME
C1 PPT WASTE DISPOSAL COST LAG TIME
C1 PET UNUSED MATERIAL COST LAG TIME
C1 PRA ***RESERVED***
C1 PRB ***RESERVED***
C1 UOC UNIT ORE FEED COST ( /KG)
C1 UWC UNIT SEPARATIVE WORK COST, EQUIVALENT ( /KG)
C1 UPC UNIT PRODUCT TREATMENT COST ( /KG)
C1 UTE REFERENCE TAILS ENRICHMENT (FRACTION)
C1 UTE REFERENCE FEED ENRICHMENT (FRACTION)
C1
C1 ***10 MORE UNDEFINED FLOATING POINT NUMBERS***
C1
C1

```

(CONT)


```

CD      PEG (H)  COST OF HANDLING INFUSED MATERIAL (COULD BE A DISPOSAL
CD      COST ( /KG DISCHARGE)
CD      ***RESERVED***
CD      PIQ (H)  COST OF NUCLIDE ORDERED I IN NUCLIDE REFERENCE LIST
CD      PNC (I)  PURCHASED ( /KG)
CD      PNW (I)  WORTH OF NUCLIDE ORDERED I IN NUCLIDE REFERENCE LIST
CD      SOLD ( /KG)
C
CH      NOTE:  NEGATIVE VALUES FOR PNC AND PNW MAY BE APPROPRIATE,
CH      SUCH AS A PENALTY FOR 2236
C
CD      PNO (I)  ***RESERVED***
CD      ISI (I,J) ACTINIDE ISOTOPE ORDER NUMBER IN NUCLIDE REFERENCE NAME
CD      LIST (2D RECORD) IN SET J INDEX I.  ZERO ENTRIES ALLOW
CD      AT THE END OF LIST (REQUIRED TO DETERMINE ENRICHMENT
CD      WORTH)
CD      IXY (I,J) REFERENCE FISSIONABLE NUCLIDE IN SET I FOR WHICH ENRICHMENT
CD      COSTS ARE CALCULATED
C
CH      NOTE:  ENRICHMENT FACTORS ARE BASED ON THE SUM OF THE INDIVIDUAL
CH      FISSIONABLE ISOTOPE FRACTIONS AND DISTRIBUTED BY RELATIVE WORTH
C
C-----
C.....
C
C      REPTTEL
C
C.....

```

SPECIFICATIONS FOR INTERFACE FILE RODSET

```

C.....
C              REVISED 04/01/80
C
C  RODSET
C
C  CONTROL ROD REFERENCE POSITIONING DATA
C
C.....
  
```

```

C-----
C  FILE IDENTIFICATION
C
C  NAME, (NUSE(I), I=1,2), IVERS
C
C  (J=MULT*1) = NUMBER OF WORDS.
C
C  NAME      FILE NAME (A6) 'RODSET'.
C  NUSE      USER IDENTIFICATION (A6).
C  IVERS     FILE VERSION NUMBER.
C
C  MULT      1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES.
C
C-----
  
```

```

C-----
C  FILE REFERENCE INFORMATION (10 RECORD)
C
C  NCRN, NFRN, NCR, NERT, NSRPS, NCTD, NSE, NCE, ISV, NRZ, NRZ1, NSH,
C  (I(I), I=1,8)
C
C  (20) = NUMBER OF WORDS.
C
C  NCRN      NUMBER OF CONTROL ROD ZONE NUCLIDES.
C
C  NFRN      NUMBER OF CONTROL ROD FOLLOWER ZONE NUCLIDES.
C
C  NCR       NUMBER OF DIFFERENT ZONE SETS (RODS).
C
C  NERT      NUMBER OF ENTRIES IN THE REFERENCE TABLE OF ROD
C            ZONES.
C
C  NSRPS     NUMBER OF SETS OF ROD POSITION SPECIFICATIONS.
C
C  NCTD      NUMBER OF POINTS IN THE HISTORY (BETWEEN REPELINGS)
C            FOR WHICH ROD POSITIONING DATA IS SPECIFIED.
C
C  NSE       NUMBER OF ZONES FOR WHICH SPECIAL FULL ROD INSERTION-
C            (OR WITHDRAWAL) DATA ARE SPECIFIED BELOW, USED FOR
C            'PODINS' OPTION IX(10)=-2, OR -1. IF FULL ROD
C            INSERTION (WITHDRAWAL) IS SPECIFIED AND THIS SPECIAL-
C            DATA IS NOT PRESENT, THE MATERIAL ADR (ADR) WILL BE
C            INSERTED IN ALL ROD ZONES NRZ BELOW.
C
C-----
  
```

(CONT)

C
 C3 NOZ OPTION ON USING FULL ROD INSERTION (WITHDRAWAL) DATA.
 C3 0- USE ONLY SPECIFICATIONS GIVEN BY SPECIAL
 C3 FULL ROD INSERTION (WITHDRAWAL) DATA.
 C3 1- INSERT MATERIAL ADP (ADP) IN ALL ROD ZONES FIRST,
 C3 THEN APPLY SPECIAL FULL ROD INSERTION
 C3 (WITHDRAWAL) DATA IN AN OVERLAY SENSE.
 C
 C4 *****NOTE FOR FULL ROD INSERTION, OR FULL ROD
 C4 WITHDRAWAL, ALL ROD AND FOLLOWER CONCENTRATIONS
 C4 ARE ZEROED IN THE SPECIFIED ZONES PRIOR TO
 C4 THE INSERTION.
 C
 C3 ISV OPTION ON SAVE DATA RECORDS.
 C3 0- NO SAVE DATA RECORDS PRESENT ON THIS FILE.
 C3 GT.0- THE TWO SAVE DATA RECORDS ARE PRESENT ON
 C3 THIS FILE.
 C
 C4 *****NOTE - THE SAVE DATA RECORDS ARE A RECORD OF
 C4 THE POSITIONING. IT IS RECOMMENDED THAT THIS
 C4 OPTION BE 0 IN WHICH CASE THE CODE CREATES
 C4 THE TWO RECORDS ON FIRST ACCESS.
 C
 C3 HRV OPTION ON CONCENTRATIONS IN MAKE-UP ZONE FOR ROD
 C3 WITHDRAWAL (WHI .GT. 0 BELOW) FOR 'RODINS' OPTION
 C3 II(10) GE. 0.
 C3 0- ZERO ROD CONCENTRATIONS AND REPLACE FOLLOWER
 C3 CONCENTRATIONS WITH ADP DATA (IF PRESENT).
 C3 1- ONLY ZERO ROD CONCENTRATIONS.
 C3 2- DO NOT CHANGE ANY CONCENTRATIONS.
 C
 C3 HRI OPTION ON CONCENTRATIONS IN MAKE-UP ZONE FOR ROD
 C3 INSERTION (WHI .LT. 0 BELOW) FOR 'RODINS' OPTION
 C3 IX(10) GE. 0.
 C3 0- REPLACE ROD CONCENTRATIONS WITH ADP DATA.
 C3 1- DO NOT CHANGE ANY CONCENTRATIONS.
 C3 2- ONLY ZERO ROD CONCENTRATIONS.
 C3 3- ZERO ROD CONCENTRATIONS AND REPLACE FOLLOWER
 C3 CONCENTRATIONS WITH ADP DATA (IF PRESENT).
 C
 C3 NSH NUMBER OF ZONES FOR WHICH SPECIAL SHORT-ROD DATA
 C3 ARE GIVEN BELOW. THIS DATA MUST BE PRESENT IF THE
 C3 'RODINS' OPTION IX(11)=1.
 C

(CONT)


```

C-----
CZ REFERENCE NUCLIDE DATA (2D RECORD)
C
CC PRESENT IF NCRN * NFRN .GT. 0
C
CL (NFR(I), I=1, NFRN), (NRP(N), N=1, NFRN), (ADR(N), N=1, NCRN), (ADP(N), I=1,
CL NFRN)
C
CW ((NULT*1) * (NCRN+NFRN)) = NUMBER OF WORDS.
C
CD NFR ROD ZONE NUCLIDE USER UNIQUE NAME, HISORH (16).
C
CD NRP FOLLOWER ZONE NUCLIDE USER UNIQUE NAME, HISORH (16).
CD MAY INCLUDE NUCLIDES IN THE ROD LIST NFR.
C
CD ADR ROD NUCLIDE DENSITIES (ATOMS/BN-CM) - MAY BE ROD
CD INSERTION FOLLOWER (TOP OF ROD) MATERIAL. IF SO
CD IT CANNOT BE USED FOR FULL ROD INSERTION.
C
CD ADP FOLLOWER NUCLIDE DENSITY (ATOMS/BN-CM) - USED FOR
CD ROD REMOVAL (BOTTOM OF ROD).
C-----

```

```

C-----
CZ REFERENCE TABLE OF ROD ZONES (3D RECORD)
C
CC ALWAYS PRESENT
C
CL (NRZ(I), I=1, NNRZ)
C
CW (NNRZ) = NUMBER OF WORDS.
C
CD NRZ NUMBER OF A ZONE.
C
CN THIS DATA IS PRESENTED IN SETS OF ZONE NUMBERS, EACH SET
CN REPRESENTING A ROD OR BLOCK OF THEM. EACH SET OF DATA IS
CN FOLLOWED BY A ZERO ENTRY. REFERENCE TO A SET IS BY ORDER OF
CN PRESENTATION (=J IN NZI(J,L) BELOW). THE ORDERING OF THE
CN ZONE NUMBERS IN EACH SET INDICATES ROD END POSITION BY
CN INSERTION. THIS ROD INSERTION IS ONLY THE FIRST ZONE GIVEN
CN WOULD BE MINIMUM INSERTION AND ROD INSERTION IN THE LAST
CN ZONE IN THE LIST WOULD BE MAXIMUM INSERTION.
CN IF THE LAST ZONE NUMBER IN A SET IS THE SAME AS THE FIRST
CN ZONE NUMBER, THIS INDICATES A 'CLOSED-LOOP' SET OF ZONES.
CN A 'CLOSED-LOOP' SET OF ZONES IS NOT A SET OF ROD ZONES, BUT
CN IS A SET IN WHICH ALL NUCLIDES IN THE ZONES MAY BE
CN INTERCHANGED. ONLY THE OPTIONS IX(10) =0 OR =1 APPLY AND
CN THESE SETS WILL BE IGNORED FOR ALL OTHERS. SEE NZI BELOW.
CN THERE MAY BE SUBZONES IN THE PROBLEM, BUT THE ROD AND
CN FOLLOWER NUCLIDES MUST BE ASSIGNED TO AND HANDLED ON A
CN ZONE BASIS, NOT SUBZONE.
C
CN NO SETS OF ZONE NUMBERS ARE REQUIRED.
C-----

```

(CONT)

 C THE FOLLOWING RECORDS ARE IN SETS OF TWO, HERE OF THEM.
 C-----

 C REFERENCE POINT IN HISTORY (40 RECORD)
 C
 C PRESENT IF NCTD .GT. 0
 C
 C (PEH(L), L=1, NCTD), NOP, (J1(Z), I=1, 10)
 C
 C (NCTD+11) = NUMBER OF WORDS.
 C
 C PEM FRACTION OF THE EXPOSURE TIME BETWEEN PEELINGS,
 C 0 MEANS START, 1.0 MEANS END, GT 1.0 IS GARBAGE.
 C
 C NOP OPTION DISCUSSED BELOW.
 C-----

 C REFERENCE SET OF ROD POSITION SPECIFICATIONS (50 RECORD)
 C
 C PRESENT IF NCTD .GT. 0
 C
 C ((NZZ(J,L), J=1, NCB), L=1, NCTD)
 C
 C (NCTD=NCTD) = NUMBER OF WORDS.
 C
 C NZZ HAS A MEANING WHICH IS DEPENDENT ON OPTION NOP.
 C
 C IF NOP IS 0
 C
 C NZZ IS THE NUMBER OF THE LAST ZONE IN SET J (NRZ ABOVE)
 C HAVING ROD INSERTION AT POINT L IN THE HISTORY, I.E., ALL
 C ROD AND FOLLOWER MATERIAL CONCENTRATIONS ARE ZEROED IN ALL
 C ZONES IN THE SET - THEN ROD MATERIAL (CONCENTRATIONS ADP)
 C IS INSERTED IN ORDER IN ALL ZONES IN THE SET THROUGH NZZ AND
 C FOLLOWER (CONCENTRATIONS ADP) IS INSERTED IN ORDER FOR ALL
 C REMAINING ZONES IN THE SET. NOTE THAT ONLY THE NUCLEIDES
 C THAT ARE ASSIGNED TO EACH CONE, OUT OF THE HNR AND HNP LIST
 C ABOVE, ARE INVOLVED. THIS OPTION COULD BE USED TO INITIALIZE
 C THE CONTENTS OF THE ROD ZONES AT SOME POINT IN THE HISTORY.
 C ROD-FOLLOWER EXPOSURE CANNOT BE FOLLOWED.
 C IF NZZ=0 FOR SOME SET J, NO CHANGES WILL BE MADE IN THAT
 C SET OF ROD ZONES.
 C THIS OPTION WILL BE IGNORED FOR A 'CLOSED-LOOP' SET.
 C IF NOP .EQ. 1
 C

(CONT)

CN FOR BOTH THE ABOVE OPTIONS FOR NON 'CLOSED-LOOP' SETS, ONLY
 CN THOSE NUCLIDES HNR AND HNP THAT ARE ASSIGNED TO THE ZONES
 CN ARE INVOLVED. GENERALLY THE SAME ROD AND/OR FOLLOWER
 CN NUCLIDES MUST BE ASSIGNED TO ALL ZONES OF A SET J (EPC
 CN ABOVE), BUT NOT NECESSARILY IN THE SAME ORDER. CONSTANT
 CN NUCLIDE-ZONE-CROSS SECTION REFERENCING IS ESSENTIAL.

IF NOP .EQ. 2

CN WZC IS PARTS PER 1000, EQUAL TO THE FRACTION OF ROD
 CN INSERTION WHEN THE ROD ZONES ARE NOT REPRESENTED
 CN EXPLICITLY, I.E., FOR TWO-DIMENSIONAL CALCULATIONS.
 CN LET $X = WZC(J,L)/1000$. THEN FIRST, ALL ROD AND FOLLOWER
 CN CONCENTRATIONS ARE CEROED IN THE ZONES ARE IN SET J AT THIS
 CN POINT IN THE HISTORY. THEN THE ROD CONCENTRATIONS ARE
 CN INSERTED AS $R = X \cdot ADR$, THEN THE FOLLOWER CONCENTRATIONS
 CN ARE ADDED, $F = F + (1-X) \cdot ADF$.
 CN *****NOTE THAT IF THE FULL ROD INSERTION (WITHDRAWAL) DATA
 CN IS PRESENT (WSE .GT. 0), THEN THE DATA WZR, ADR, ADF IS
 CN USED INSTEAD OF THE DATA WZC, ADR, ADF. THE FULL ROD
 CN INSERTION OPTION DOES NOT APPLY. IN THIS CASE ONLY THE
 CN WZC (J=1,L) DATA IS USED TO APPLY TO THE 1 SET OF ZONES WZR.
 CN FOR ALL SET J FOR WHICH WZC.LT.0, NO CHANGES IN THE ZONES
 CN IN THAT SET WILL BE MADE.

C-----
 CN SPECIAL FULL ROD INSERTION (WITHDRAWAL) DATA (60 RECORD)
 C
 CN PRESENT IF WSE.GT.0
 C
 CN (WZR(I),I=1,WSE)
 C
 CN (WSE) = NUMBER OF WORDS.
 C
 CN WZR NUMBER OF ROD ZONE.
 C-----

(CONT)

```

C-----
C      SPECIAL FULL ROD INSERTION (WITHDRAWAL) DATA (70 RECORDS)
C
C      PRESENT IF NSZ.GT.0
C
C      (ARD(J),J=1,NCRN),(APD(K),K=1,NFRN) ----SEE STRUCTURE BELOW----
C
C      DO 1 N = 1,NSZ
C      1 READ(N) *LIST AS ABOVE*
C
C      (NCRN*NFRN) = NUMBER OF WORDS.
C
C      APD          ATOM DENSITY OF ROD NUCLEIDE.
C
C      APD          ATOM DENSITY OF FOLLOWER NUCLEIDE.
C-----

```

```

C-----
C      SPECIAL SHUT-DOWN ROD DATA (80 RECORD)
C
C      PRESENT IF NSH.GT.0
C
C      (NSH(I),I=1,NSH)
C
C      (NSH) = NUMBER OF WORDS.
C
C      NSH      NUMBER OF ROD ZONE.
C-----

```

```

C-----
C      SPECIAL SHUT-DOWN ROD DATA (90 RECORDS)
C
C      PRESENT IF NSH.GT.0
C
C      (SNP(J),J=1,NCRN) ----SEE STRUCTURE BELOW----
C
C      DO 1 N = 1,NSH
C      1 READ(N) *LIST AS ABOVE*
C
C      (NCRN) = NUMBER OF WORDS.
C
C      SNR      ATOM DENSITY OF ROD NUCLEIDE.
C-----

```

(CONT)

```

C-----
C      INTEGER SAVE DATA  (100 RECORD)
C
C      PRESENT IF ISV.GT.0
C
C      (IR(I),I=1,100)
C
C      (100) = NUMBER OF WORDS.
C
C      IR          INTEGER SAVE DATA - INITIALIZED ZERO.
C
C      IR(1)       COUNT OF C.R.P. ACCESSES.
C      IR(2)       CYCLE NUMBER OF LAST C.R.P. ACCESS.
C      IR(3)       C.R.P. OPTION (IR(10) - 'RODINS') OF LAST ACCESS.
C      IR(4)       MEMORY REQUESTED FOR LAST C.R.P. ACCESS.
C      IR(5)       PCNT IN HISTORY OF LAST ACCESS.
C-----

```

```

C-----
C      REAL SAVE DATA  (10 RECORD)
C
C      PRESENT IF ISV.GT.0
C
C      (IR(I),I=1,100)
C
C      (100) = NUMBER OF WORDS.
C
C      IR          REAL SAVE DATA - INITIALIZED ZERO.
C
C      IR(1)       TOTAL CYCLE TIME (IR(1) - 'RODINS') OF LAST ACCESS.
C      IR(2)       TIME INTO CYCLE (TIME-INITIATION) OF LAST ACCESS.
C      IR(3)       FRACTION TIME INTO CYCLE OF LAST ACCESS.
C
C      INFORMATION IS PLACED IN THESE TWO RECORDS BY THE CODE
C      WHICH IS NEEDED FOR AUTOMATION OF POD POSITIONING AND
C      VERIFICATION TESTING. DATA NOT SPECIFIED HERE IS RESERVED
C      FOR CODE INTERNAL USE AND SHOULD NOT BE SUPPLIED BY THE
C      USER, BUT MAY BE RETOVED FROM A FILE WRITTEN IN A
C      PREVIOUS RUN TO CONTINUE A CALCULATION. THE USER SHOULD NOT
C      SPECIFY THIS DATA AS A NORMAL INPUT.
C-----

```

```

C.....
C
C      CROPP      RODSET
C
C.....

```

SPECIFICATIONS FOR INTERPACE FILE RESTART

```

C.....
C              REVISED 04/01/80
C
C  CR          RESTART
C
C  CE          CODE-BLOCK-DEPENDENT RESTART DATA SAVED FOR RECOVERY
C
C.....
  
```

```

C-----
C  CR          FILE IDENTIFICATION
C
C  CL          RNAME, (RUSE (I), I=1,2), IVERS
C
C  CV          J=WORD * 1
C
C  CD          RNAME          HOLLERITH FILE NAME - RESTART - (16)
C  CD          RUSE(I)        HOLLERITH USER IDENTIFICATION (2A6)
C  CD          IVERS          FILE VERSION NUMBER
C  CD                               VERSION 1 RESERVED FOR VENTURE
C
C  CV          MULT          1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----
  
```

```

C-----
C  CR          FILE REFERENCE INFORMATION
C
C  CL          RPI1, RPI2, RPI3, R1, R2, R3, R4, R5, R1, R2, L2
C
C  CV          11
C
C  CD          RPI1 - RPI3    FILE IDENTIFICATION FLAGS
C  CD          R1 - R5        RESERVED
C  CD          R1            NUMBER OF RECORDS OF TYPE 1 DATA
C  CD          R2            NUMBER OF RECORDS OF TYPE 2 DATA
C  CD          L2            LENGTH OF ALL RECORDS OF TYPE 2 DATA
C
C-----
  
```

```

C-----
C  CR          RECORD LENGTHS OF TYPE 1 DATA
C
C  CL          (RWER (J), J=1, R1)
C
C  CV          R1
C
C  CD          RWER(J)        NUMBER OF WORDS IN TYPE 1 DATA RECORD RECORD J
C
C-----
  
```

(CONT)

```

C-----
C      RESTART DATA RECORDS, TYPE 1
C
C      (DARS(I), I=1, N)
C
C      N, WHICH IS NWIR(J) FOR RECORD SEQUENCE J, NR1 RECORDS
C
C      DARS(I)          CODE DEPENDENT RECOVERY DATA ARRAY TYPE 1
C-----

```

```

C-----
C      RESTART DATA RECORDS, TYPE 2
C
C      (DARR(I), I=1, L2)
C
C      L2, NR2 RECORDS
C
C      DARR(I)          CODE DEPENDENT RECOVERY DATA ARRAY TYPE 2
C-----

```

```

C-----
C
C      RESTART
C-----

```



```

C*****
C
C          REVISED 11/30/76
C
CF          RCURNT-IV
CE          REGULAR CURRENTS
C
C*****

```

```

CD          ORDER OF GROUPS IS ACCORDING TO DECREASING
CD          ENERGY.

```

```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME,(HUSE(I),I=1,2),IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CD          HNAME          HOLLERITH FILE NAME - RCURNT - (A6)
CD          HNAME          HOLLERITH FILE NAME -      -(A6)
CD          HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
CD          MULT           DOUBLE PRECISION PARAMETER
CD                        1- A6 WORD IS SINGLE WORD
CD                        2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          SPECIFICATIONS      (1D RECORD)
C
CL          NDIM,NGROUP,NINTI,NINTJ,NINTK,NBLOK
C
CW          6=NUMBER OF WORDS
C
CD          NDIM           NUMBER OF DIMENSIONS
CD          NGROUP         NUMBER OF GROUPS
CD          NINTI          NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD          NINTJ          NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD          NINTK          NUMBER OF THIRD DIMENSION FINE MESH INTERVALS.
CD                        NINTK.EQ.1 IF NDIM.LE.2
CD          NBLOK          DATA BLOCKING FACTOR
CD                        IF NDIM.EQ.1 THE GROUP VARIABLE IS BLOCKED
CD                        INTO NBLOK BLOCKS (SEE 2D RECORD BELOW)
CD                        IF NDIM.GE.2 THE 2ND DIMENSION VARIABLE IS
CD                        BLOCKED INTO NBLOK BLOCKS (SEE 3D RECORD)
C

```

C-----

```
C-----
CR          ONE DIMENSIONAL REGULAR CURRENT    (2D RECORD)
C
CC          PRESENT IF NDIM.EQ.1
C
CL          ((RCURI(I,J),I=1,NBDYI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW          NBDYI*(JU-JL+1) = NUMBER OF WORDS
C
C          DO 1 M=1,NBLOK
C          1 READ(N)  *LIST AS ABOVE*
C
CC          WITH M AS THE BLOCK INDEX, JL=(M-1)*((NGROUP-1)/NBLOK+1)+1
CC          AND JU=MINO(NGROUP,JUP) WHERE JUP=M*((NGROUP-1)/NBLOK +1)
C
CD          RCURI(I,J)          ONE DIMENSIONAL REGULAR CURRENT BY MESH POINT
CD                               BOUNDARY AND GROUP
CD          NBDYI              =NINTI+1, NUMBER OF FIRST DIMENSION FINE MESH
CD                               BOUNDARIES
C
C-----
```

```
C-----
CR          MULTI-DIMENSIONAL REGULAR CURRENTS AT FIRST DIMENSION
CR          BOUNDARIES          (3D RECORD)
C
CC          PRESENT IF NDIM.GE.2
C
CL          ((RCURI(I,J),I=1,NBDYI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW          NBDYI*(JU-JL+1) = NUMBER OF WORDS
C
C          DO 1 L=1,NGROUP
C          DO 1 K=1,NINTK
C          DO 1 M=1,NBLOK
C          1 READ(N) *LIST AS ABOVE*
C
CC          WITH M AS THE BLOCK INDEX, JL=(M-1)*((NINTJ-1)/NBLOK +1)+1
CC          AND JU=MINO(NINTJ,JUP) WHERE JUP=M*((NINTJ-1)/NBLOK +1)
C
CD          RCURI(I,J)          REGULAR FIRST DIMENSION BOUNDARY CURRENT
C
C-----
```

```

C-----
CR          MULTI-DIMENSIONAL REGULAR CURRENTS AT SECOND DIMENSION
CR          BOUNDARIES          (4D RECORD)
C
CC          PRESENT IF NDIM.GE.2
C
CL          ((RCURJ(I,J),I=1,NINTI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW          NINTI*(JU - JL + 1) = NUMBER OF WORDS
C
C          DO 1 L=1,NGROUP
C          DO 1 K=1,NINTK
C          DO 1 M=1,NBLOK
C 1 READ(N) *LIST AS ABOVE*
C
CC          WITH M AS THE BLOCK INDEX, JL=(M-1)*((NBDRYJ-1)/NBLOK+1)+1
CC          AND JU=MINO(NBDRYJ,JUP) WHERE JUP=M*((NBDRYJ-1)/NBLOK+1)
C
CD          RCURJ(I,J)          REGULAR SECOND DIMENSION BOUNDARY CURRENT
CD          NBDRYJ              =NINTJ+1, NUMBER OF SECOND DIMENSION FINE MESH
CD                               BOUNDARIES
C
C-----

```

```

C-----
CR          MULTI-DIMENSIONAL REGULAR CURRENTS AT THIRD DIMENSION
CR          BOUNDARIES.          (5D RECORD)
C
CC          PRESENT IF NDIM.EQ.3
C
CL          ((RCURK(I,J),I=1,NINTI),J=JL,JU) -----SEE STRUCTURE BELOW-----
C
CW          NINTI*(JU - JL + 1) = NUMBER OF WORDS
C
C          DO 1 L=1,NGROUP
C          DO 1 K=1,NBDRYK
C          DO 1 M=1,NBLOK
C 1 READ(N) *LIST AS ABOVE*
C
CC          WITH M AS THE BLOCK INDEX, JL=(M-1)*((NINTJ-1)/NBLOK +1)+1
CC          AND JU=MINO(NINTJ,JUP) WHERE JUP=M*((NINTJ-1)/NBLOK +1)
C
CD          RCURK(I,J)          REGULAR THIRD DIMENSION BOUNDARY CURRENT
CD          NBDRYK              =NINTK+1, NUMBER OF THIRD DIMENSION FINE MESH
CD                               BOUNDARIES
C
C-----

```

CEOF

```

C*****
C                                     DATE 04/01/85
C
C
CF      RMFLUX-IV
CE      REGULAR MOMENTS FLUX
C
C*****
C-----
CR      FILE IDENTIFICATION
C
CL      HNAME,(HUSE(I),I=1,2),IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - RMFLUX - (A6)
CD      HNAME          HOLLERITH FILE NAME - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT            DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C-----
CR      SPECIFICATIONS      (1D RECORD)
C
CL      NDIM,NGROUP,NINTI,NINTJ,NINTK,NORD,EFFK,POWER
C
CW      8=NUMBER OF WORDS
C
CD      NDIM            NUMBER OF DIMENSIONS
CD      NGROUP          NUMBER OF GROUPS
CD      NINTI           NUMBER OF FIRST DIMENSION INTERVALS
CD      NINTJ           NUMBER OF SECOND DIMENSION INTERVALS
CD                      NINTJ.EQ.1 IF NDIM.EQ.1
CD      NINTK           NUMBER OF THIRD DIMENSION INTERVALS
CD                      NINTK.EQ.1 IF NDIM.LE.2
CD      NORD            NUMBER OF LEGENDRE MOMENTS
CD      EFFK            EFFECTIVE MULTIPLICATION FACTOR
CD      POWER           POWER IN WATTS TO WHICH FLUX IS NORMALIZED
C
C-----
C-----
CR      REGULAR MOMENTS FLUXES ON MULTIDIMENSIONAL INTERVALS
C      (2D RECORD)
C
CL      ((FLUX(M,I),M=1,NORD),I=1,NINTI)----NOTE STRUCTURE BELOW---
C
CW      NORD*NINTI=NUMBER OF WORDS
C
C      DO 1 L=1,NGROUP
C      DO 1 K=1,NINTK
C      DO 1 J=1,NINTJ
C      1 READ (N) *LIST AS ABOVE*

```

C			-
CD	FLUX(M,I)	REGULAR MOMENTS FLUX ON FIRST DIMENSION	-
CD		INTERVALS. ORDER OF GROUPS IS ACCORDING	-
CD		TO DECREASING ENERGY.	-
C			-
C	-----		-
CEOF			-

```

C*****
C          REFERENCE 02/01/79  ORNL-5180
CF          RZFLUX
C
CE          REGULAR ZONE FLUX BY GROUP. AVERAGED OVER EACH ZONE
C
CN          AN ASTRISK IN COLUMN 71 INDICATES LOCAL MODIFICATION
C
C*****

```

```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME.(HUSE(I),I=1,2), IVERS
C
CW          3*MULT + 1
C
CD          HNAME          FILE NAME (A6) 'RZFLUX'
CD          HUSE           USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CN          MULT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----

```

```

C-----
CR          1D          FILE REFERENCE INFORMATION
C
CL          TIME.POWER.VOL.EFFK.EIVS.DKDS.TNL.TNA.TNSL.TNBL.TNBAL.TNCRA.
CL          CF.CE.CR.CC.ITPS.NZONE.NGROUP.NPV
C
CW          20
C
CD          TIME          REFERENCE REAL TIME, DAYS
CD          POWER         POWER LEVEL FOR ACTUAL NEUTRONICS PROBLEM, WATTS
CD                      THERMAL
CD          VOL           VOLUME OVER WHICH POWER WAS DETERMINED, CC
CD          EFFK          MULTIPLICATION FACTOR
CD          EIVS          EIGENVALUE OF SEARCH OF SEARCH PROBLEM
CD          DKDS          DERIVATIVE OF SEARCH PROBLEM
CD          TNL           TOTAL NEUTRON LOSSES
CD          TNA           TOTAL NEUTRON ABSORPTIONS
CD          TNSL          TOTAL NEUTRON SURFACE LEAKAGE
CD          TNBL          TOTAL NEUTRON BUCKLING LOSS
CD          TNBAL         TOTAL NEUTRON BLACK ABSORBER LOSS
CD          TNCRA         TOTAL NEUTRON CONTROL ROD ABSORPTIONS

```

Figure XII Applications for interface File RZFLUX

```

CD    CF          FRACTION OF CORE TREATED IN PROBLEM          *
CD    CE          CONVERSION FACTOR. RATIO OF THERMAL ENERGY TO *
CD          FISSION + CAPTURE ENERGY AVAILABLE WITH          *
CD          THE CROSS SECTIONS                                *
CD    CR          ADDITIONAL DATA FLAG IF .GT.0 (TWO RECORDS) *
CD    CC          RESERVED                                     *
CD    ITPS        ITERATIVE PROCESS STATE                     *
CD          =0. NO ITERATIONS DONE                           *
CD          =1. CONVERGENCE SATISFIED                         *
CD          =2. NOT CONVERGED. BUT CONVERGING                 *
CD          =3. NOT CONVERGED. NOT CONVERGING                 *
CD    NZONE       NUMBER OF GEOMETRIC ZONES                    *
CD    NGROUP      NUMBER OF NEUTRON ENERGY GROUPS            *
CD    NPV         NUMBER OF BLOCKS OF LOCAL FINE SCALE FLUX VALUES *
C
C-----
C-----
CR    2D          FLUX VALUES                                *
C
CL    ((ZGF(K,M).K=1,NGROUP).N=1,NZONE)                      *
C
CW          NGROUP*NZONE                                     *
C
CD    ZGF          REGULAR ZONE FLUX BY GROUP. AVERAGED OVER ZONE *
CD          NEUTRONS/SEC-CM**2                                *
C
C-----
C-----
CR    3D          ADDITIONAL DATA. FIRST OF TWO RECORDS      *
C
CC          PRESENT IF CR.GT.0                                *
C
CL    (SHARE8(I).I=1,100).(SHARE(I).I=1,100).(LX(I).I=1,200) *
C
CW          100*MULT + 300                                    *
C
CD    SHARE8       NEUTRONICS DATA FOR REFERENCE             *
C          DOUBLE PRECISION ON A SHORT WORD MACHINE          *
CD    SHARE        NEUTRONICS DATA FOR REFERENCE             *
CD    LX          NEUTRONICS FLAGS FOR REFERENCE              *
C
C-----

```

Figure XII.3 Specifications for interface File RZFLUX (con't.)

```

C-----
CR      4D      ADDITIONAL DATA. SECOND OF TWO RECORDS      *-
C                                          *-
CC              PRESENT IF CR.GT.0                            *-
C                                          *-
CL      (INRS(I),I=1,NGROUP).(RHGO(I),I=1,NGROUP).(BATA(I),I=1,NGROUP) *-
C                                          *-
CW              3*NGROUP                                       *-
C                                          *-
CD      INRS          NEUTRONICS ITERATION FLAGS              *-
CD      RHO           NEUTRONICS ITERATION DATA              *-
CD      BATA          NEUTRONICS ITERATION DATA              *-
C                                          *-
CN              NOTE NONSTANDARD DATA TYPE ORDER            *-
C                                          *-
C-----
                                *-
                                *
                                *
C-----
CR      5D      LOCAL FLUX RECORD REFERENCE DATA            *-
C                                          *-
CL      (XFV(I),I=1,10).NLP.NRZ.(IFV(J),J=1,8)              *-
C                                          *-
CW              20                                             *-
C                                          *-
CD      XFV(1)        REFERENCE VOLUME. CC                    *-
CD      XFV(2)        REFERENCE POWER LEVEL. WATTS            *-
CD      NLP           NUMBER OF LOCATIONS FOR WHICH DATA IS GIVEN *-
CD      NRZ           REFERENCE ZONE NUMBER                    *-
C                                          *-
C-----
C-----
CR      6D      LOCAL NEUTRON FLUX VALUES                    *-
C                                          *-
CL      ((FLF(K,M),K=1,NGROUP),M=1,NLP)                      *-
C                                          *-
CW              NGROUP*NLP                                     *-
C                                          *-
CD      FLF           LOCAL VALUE OF THE NEUTRON TOTAL FLUX.  *-
CD                        AS ASSOCIATED WITH A SUB-VOLUME WITHIN THE *-
CD                        REFERENCE ZONE NRZ                    *-
C                                          *-
C-----

C*****
C
CEOF      RZFLUX
C
C*****

```



```

C*****
C              REVISED 7/22/75 - REVISED 04/01/80
C
CF          SEARCH - III
C
CE          CRITICALITY SEARCH FILE
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME.(HUSE(I),I=1,2).IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CD          HNAME              HOLLERITH FILE NAME - SEARCH - (A6)
CD          HUSE(I)            HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS              FILE VERSION NUMBER
CD          MULT                DOUBLE PRECISION PARAMETER
CD                               1- A6 WORD IS SINGLE WORD
CD                               2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          INDIVIDUAL DATA SET IDENTIFIER (1D RECORD)
C
CL          NSHID.NREC.(NSO(I),I=1,18)
C
CW          20=NUMBER OF WORDS
C
CD          NSHID              POSITIVE INTEGER IDENTIFYING A SET OF SEARCH
CD                               DATA. THIS AND FOLLOWING RECORDS REPEATED
CD                               UNTIL NEGATIVE NSHID TERMINATES FILE
CD          NREC              NUMBER OF RECORDS TO SKIP TO POSITION ON NEXT
CD                               INDIVIDUAL DATA SET IDENTIFIER RECORD
CD          NSP(I)            RESERVED
C
C-----

C-----
CR          FILE SPECIFICATIONS (2D RECORD)
C
CL          EFFK.DKEFF.EPSK.EPSEL.CMOD.(SRCH(I),I=1,5).ISRCH.ISZOP.NMAXNP.
CL          NCINTI.NCINTJ.NCINTK.NISOSR.NSETS.NEIRNG.ITEND.ICEND.
CL          NRCH(I),I=1,19)

```

Figure IX.1 Specifications for Innterface File SEARCH.

C		
CW	40=NUMBER OF WORDS	
C		
CD	EFFK	DESIRED MULTIPLICATION FACTOR
CD	DKEFF	MULTIPLICATION FACTOR SLOPE
CD	EPSK	CONVERGENCE CRITERION TO BE MET BY EFFK
CD	EPSEI	CONVERGENCE CRITERION TO BE MET BY PRIMARY
CD		VARIABLE
CD	CMOD	MODIFIER APPLIED TO NUCLIDE CONCENTRATIONS
CD		VARIED SPECIALLY (ISRCH=7 BELOW). MAY BE
CD		LT.0
CD	SRCH(I)	RESERVED
CD	ISRCH	TYPE OF SEARCH
CD		0- NOT DEFINED
CD		1- BUCKLING SEARCH
CD		2- ALPHA SEARCH
CD		3- DIMENSION SEARCH
CD		7- NUCLIDE CONCENTRATION SEARCH BY
CD		PROPORTIONAL ADJUSTMENTS OF SELECTED
CD		INITIAL CONCENTRATIONS
CD	ISZOP	SUBZONE OPTION FOR ISRCH = 7 OR 9
CD		0- SEARCH DATA IS BY ZONE
CD		1- SEARCH DATA IS BY SUBZONE
CD	NMAXNP	MAXIMUM NUMBER OF NEUTRONICS PROBLEMS OR
CD		TRIAL EIGENVALUES ALLOWED IN A SEARCH.
CD		A ZERO HERE SPECIFIES A DIRECT SEARCH.
CD	NCINTI	NUMBER OF FIRST DIMENSION COARSE MESH
CD		INTERVALS.
CD	NCINTJ	NUMBER OF SECOND DIMENSION COARSE MESH
CD		INTERVALS.
CD	NCINTK	NUMBER OF THIRD DIMENSION COARSE MESH
CD		INTERVALS.
CD	NISOSR	NUMBER OF ISOTOPES OR NUCLIDES INVOLVED IN
CD		CONCENTRATION SEARCH (ISRCH=7 OR 9)
CD	NSETS	NUMBER OF SPECIFICATION SETS IN CONCENTRATION-
CD		SEARCH (ISRCH = 7 OR 9)
CD	NEIRNG	EIGENVALUE (EI) RANGE RESTRICTIONS. SEARCH
CD		TERMINATED IF SPECIFIED RANGE IS VIOLATED.
CD		-1 EI.LT.0
CD		0- NO RESTRICTION ON EI
CD		1- EI.GT.0 AND .LT. 1
CD		2- EI.GT.1

Figure IX.1 Specifications for Interface File SEARCH (con't.)

```

CD      ITEND      TERMINATION OPTION ON ITERATIVE PROCESS.
CD      SEARCH IS LIMITED BY NMAXNP. NUMBER OF OUTER-
CD      ITERATIONS. OR OTHER PARAMETER. THEN
CD      0- NO RESTRAINT
CD      1- TERMINATE IF CONVERGENCE CRITERIA ARE
CD      NOT MET
CD      2- IF CONVERGENCE CRITERIA ARE NOT MET.
CD      TERMINATE ONLY IF PROBLEM IS NOT
CD      CONVERGING.
CD      ICEND      TERMINATION OPTIONS ON NUCLIDE CONCENTRATIONS-
CD      0- TERMINATE IF ANY NUCLIDE CONCENTRATION
CD      BECOMES NEGATIVE AT ANY STAGE OF THE
CD      CALCULATION.
CD      1- TERMINATE IF ANY NUCLIDE CONCENTRATION
CD      IS NEGATIVE AT THE END OF THE SEARCH
CD      2- ALLOW NEGATIVE NUCLIDE CONCENTRATIONS
CD      NRCH(1)     .GT.0 - INDICATES THAT MACROSCOPIC CROSS *-
CD      SECTIONS ARE TO BE RECALCULATED DURING *-
CD      A DIRECT SEARCH *-
CD      NRCH(2)     .GT.0 - INDICATES SECONDARY SEARCH *-
CD      SPECIFICATIONS (REFERENCE SET) ARE TO BE *-
CD      USED IF THE SPECIFIED CONSTRAINTS ON THE *-
CD      SEARCH EIGENVALUE ARE NOT SATISFIED USING *-
CD      THE PRIMARY SEARCH DATA *-
CD      NRCH(3-19)  RESERVED *-
C
C-----
C-----
CR      COARSE MESH MODIFIERS FOR DIMENSION SEARCH
CR      (3D RECORD)
C
CC      PRESENT IDF ISRCH.EQ.5
C
CL      (SRHDI(I).I=1.NCINTI).(SRHDJ(J).J=1.NCINTJ).SRHDK(K).K=1.NCINTK)
C
CW      NCINTI+NCINTJ+NCINTK=NUMBER OF WORDS
C
CD      SRHDI(I)    FIRST DIMENSION COARSE MESH MODIFIERS
CD      SRHDJ(J)    SECOND DIMENSION COARSE MESH MODIFIERS
CD      SRHDK(K)    THIRD DIMENSION COARSE MESH MODIFIERS
C
C-----

```

Figure IX.1 Specification of Interface File SEARCH (con't.)

```

C-----
CR          NUCLIDES FOR PROPORTIONAL SEARCH AND SPECIAL SEARCH
CR          (A6 RECORD)
C
CC          PRESENT IF ISRCH.EQ.7
C
CL          (NSHZ1(I),I=1,NSETS),(NSHZ2(I),I=1,NSETS),
CL          ((HNNAMS(N,I),N=1,NISOSR),I=1,NSETS),(HNSHN(J),J=1,10)
C
CW          2*NSETS+MULT*(NISOSR*NSETS+10)=NUMBER OF WORDS
C
CD          NSHZ1(I)          FIRST NUMBER OF A CONSECUTIVE SET OF ZONES
CD                               IF ISZOP.EQ.0. OR OF A CONSECUTIVE SET OF
CD                               SUBZONES IF ISZOP.EQ.1
CD          NSHZ2(I)          LAST NUMBER OF A SET OF ZONES OR SUBZONES
CD          HNNAMS(N,I)       REFERENCE NAMES OF NUCLIDES WHOSE
CD                               CONCENTRATIONS ARE TO BE ADJUSTED
CD                               PROPORTIONATELY IN ABOVE ZONES (A6)
CD          HNSHN(J)          SEARCH NUCLIDE REFERENCE USED AS NOTED BELOW
CD                               (A6)
C
CC          HNNAMS CONCENTRATIONS ADJUSTED ACCORDING TO
CC          C2 = C1*EI AND HNSHN CONCENTRATIONS ADJUSTED
CC          ACCORDING TO C2 = C1 + C1*(1.0-EI)*CMOD WHERE
CC          EI IS THE EIGENVALUE.
CC          C1 IS THE INITIAL CONCENTRATION. AND
CC          C2 IS THE FINAL OR INTERMEDIATE VALUE OF
CC          THE CONCENTRATION
C-----

```

Figure IX.1 Specifications for Interface File SEARCH (con't.)

```

C-----
CR      NUCLIDES FOR SEARCH INVOLVING WEIGHTED EIGENVALUE
CR      ADJUSTMENTS TO INITIAL CONCENTRATIONS
CR      (5D RECORD)
C
CC      PRESENT IF ISRCH.EQ.9
C
CL      (NSHZ1(I),I=1,NSETS),(NSHZ2(I),I=1,NSETS),
CL      ((HNNAMS(N,I),N=1,NISOSR),I=1,NSETS),
CL      ((CHZDN(N,I),N=1,NISOSR),I=1,NSETS)
C
CW      NSETS*(2+NISOSR*(1+MULT))=NUMBER OF WORDS
C
CD      NSHZ1(I0)          FIRST NUMBER OF A CONSECUTIVE SET OF ZONES
CD                          IF ISZOP.EQ.0, OR OF A CONSECUTIVE SET OF
CD                          SUBZONES IF ISZOP.EQ.1
CD      NSHZ2(I)          LAST NUMBER OF A SET OF ZONES OR SUBZONES
CD      HNNAMS(N,I)        REFERENCE NAMES OF NUCLIDES WHOSE
CD                          CONCENTRATIONS ARE TO BE ADJUSTED (A6)
CD      CHZDN(N,I)        CONCENTRATION MODIFIERS
C
CC                          CONCENTRATIONS ADJUSTED ACCORDING TO
CC                           $C2 = C1 + EI * CHZDN$  WHERE EI,C1, AND C2 ARE
CC                          AS DEFINED UNDER ISRCH .EQ. 7
C
C-----

```

```

C*****
C                                     REVISED 11/30/76
C
C
CF          SNCONS-IV
CE          SN CONSTANTS
C
C*****

```

```

C-----
CR          FILE IDENTIFICATION
C
CL          HNAME, (HUSE(I), I=1, 2), IVERS
C
CW          1+3*MULT=NUMBER OF WORDS
C
CD          HNAME                HOLLERITH FILE NAME - (A6)
CD          HUSE(I)              HOLLERITH USER IDENTIFICATION (A6)
CD          IVERS                FILE VERSION NUMBER
CD          MULT                  DOUBLE PRECISION PARAMETER
CD                                1- A6 WORD IS SINGLE WORD
CD                                2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          SPECIFICATIONS          (1D RECORD)
C
CL          NDIM, NDIR, IDUM, IDUM
C
CW          4=NUMBER OF WORDS
C
CD          NDIM                  NUMBER OF DIMENSIONS
CD          NDIR                  NUMBER OF DIRECTIONS
CD          IDUM                  UNDEFINED. USED TO OBTAIN FOUR WORD RECORD.
C
C-----

```

```

C-----
CR          ONE DIMENSIONAL SN CONSTANTS      (2D RECORD)
C
CC          PRESENT IF NDIM.EQ.1
C
CL          (DIRWGT(I), I=1, NDIR), (DIRMU(I), I=1, NDIR)
C
CW          2*NDIR=NUMBER OF WORDS
C
CD          DIRWGT(I)             DIRECTION WEIGHT FOR EACH DIRECTION
CD          DIRMU                 DIRECTION COSINE FOR EACH DIRECTION

```



```

C*****
C                                     DATE 05/12/83
C
C
CF      SNXEDT
CE      CODE DEPENDENT MICROSCOPIC MULTIGROUP CROSS SECTION FILE
CE      FOR USE IN ONEDANT EDITS
C*****
C
C
CN      THIS FILE PROVIDES A BASIC BROAD GROUP
CN      LIBRARY, ORDERED BY GROUP
C
C
C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====                                =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      FILE CONTROL                              ALWAYS
CS      FILE DATA                                ALWAYS
CS
CS      ***** (REPEAT FOR ALL GROUPS)
CS      *          (GROUP 1 IS FIRST)
CS      *          PRINCIPAL CROSS SECTIONS        ALWAYS
CS      *          SCATTERING CONTROL DATA        NORD.NE.0
CS      *          SCATTERING MATRIX              NORD.NE.0
CS      *****
C
C-----
C
C
C-----
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1, 2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - SNXEDT - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                     1- A6 WORD IS SINGLE WORD
CD                     2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C-----
CR      FILE CONTROL
C
CL      NGROUP, NISO, NORD, NED, IDPF, LNG, MAXUP, MAXDN, NPRIN, I2LP1
C
CW      10=NUMBER OF WORDS

```


C		
CD	NGROUP	NUMBER OF ENERGY GROUPS IN FILE
CD	NISO	NUMBER OF ISOTOPES IN FILE
CD	NORD	NUMBER OF LEGENDRE SCATTERING ORDERS
CD	NED	NUMBER OF EXTRA EDIT CROSS SECTIONS (IN ADDITION
CD		TO THE BASIC PRINCIPAL CROSS SECTIONS)
CD	IDPF	0/1 NO/YES CROSS SECTION DATA ARE DOUBLE PRECISION
CD	LNG	NUMBER OF THE LAST NEUTRON GROUP(FOR COUPLED SETS)
CD	MAXUP	MAXIMUM NUMBER OF UPSCATTER GROUPS
CD	MAXDN	MAXIMUM NUMBER OF DOWNSCATTER GROUPS
CD	NPRIN	NUMBER OF PRINCIPAL CROSS SECTIONS (4 FOR SNXEDT)
CD	I2LP1	0/1 = NO/YES 2L+1 TERM WAS INCLUDED IN LIBRARY

C

C-----

C

C

C-----

CR FILE DATA

C

CL (HISO(I),I=1,NISO),(HED(J),J=1,NEDT),(VEL(N),N=1,NGROUP),
 CL 1(EMAX(N),N=1,NGROUP),EMIN

C

CW NISO+NEDT+2*NGROUP+1=NUMBER OF WORDS

C

CD	HISO(I)	HOLLERITH ISOTOPE LABEL FOR ISOTOPE (A6)
CD	HED(J)	HOLLERITH LABEL FOR EDIT NUMBER J (A6)
CD	VEL(N)	MEAN NEUTRON VELOCITY IN GROUP N (CM/SEC)
CD	EMAX(N)	MAXIMUM ENERGY BOUND OF GROUP N (EV)
CD	EMIN	MINIMUM ENERGY BOUND OF SET (EV)
CD	NEDT	NED+NPRIN

C

CN THE FOUR BASIC PRINCIPAL CROSS SECTIONS
 CN ALWAYS PRESENT ARE:

CN

CN

CN

CN

CN

CN

C

CN

C

CN

C

C-----

C-----

CR PRINCIPAL CROSS SECTIONS FOR GROUP N

C

CL ((C(I,J),I=1,NISO),J=1,NEDT)

C

CW NISO*NEDT=NUMBER OF WORDS

C

CD C(I,J) PRINCIPAL CROSS SECTIONS

C

CN BASIC PRINCIPAL CROSS SECTIONS ALWAYS PRESENT ARE:

CN		
CN	J=1	FISSION SPECTRUM
CN	J=2	FISSION NU*FISSION CROSS SECTION
CN	J=3	TOTAL CROSS SECTION
CN	J=4	ABSORPTION CROSS SECTION
C		
CN	ALSO PRESENT WHEN NPRIN=5 IS:	
C		
CN	J=5	TRANSPORT CROSS SECTION
C		
C	-----	
C	-----	
CR	SCATTERING CONTROL BLOCK FOR GROUP N	
C		
CC	PRESENT IF NORD.GT.0	
C		
CL	((NGPB(L,J),L=1,NORD),J=1,NISO)	
CL	((IFSG(L,J),L=1,NORD),J=1,NISO)	
C		
CW	2*NORD*NISO=NUMBER OF WORDS	
C		
CD	NGPB(L,J)	NUMBER OF SOURCE GROUPS THAT CAN SCATTER INTO GROUP N-
CD	IFSG(L,J)	GROUP NUMBER OF THE FIRST SOURCE GROUP
CD	L	LEGENDRE ORDER NUMBER
CD	J	ISOTOPE NUMBER
C		
C	-----	
C	-----	
CR	SCATTERING SUB-BLOCK FOR GROUP N	
C		
CC	PRESENT IF NORD.GT.0	
C		
CL	(SCAT(I),I=1,NTAB)	
C		
CW	NTAB=NUMBER OF WORDS	
C		
CD	SC/T(I)	SCATTERING CROSS SECTION
C		
CD	NTAB	TABLE LENGTH OF THE CROSS SECTIONS FOR SCATTERING
CD		INTO GROUP N. THIS IS FOR ALL ISOTOPES AND ALL
CD		LEGENDRE ORDERS, THUS IT IS THE SUM OF NGPB(L,J)
CD		OVER L FROM 1 TO NORD AND OVER J FROM 1 TO NISO.
C		
CN	THE SCATTERING CROSS SECTIONS ARE PACKED IN BANDS,	
CN	ONE FOR EACH LEGENDRE ORDER AND ISOTOPE. EACH BAND	
CN	CONTAINS THE NGPB GROUPS WHICH SCATTER INTO GROUP	
CN	N. THE FIRST SOURCE GROUP NUMBER IS IFSG AND	
CN	THE LAST IS IFSG-NGPB+1. THE NORD BANDS FOR THE	
CN	FIRST ISOTOPE APPEAR FIRST (P0, P1,) FOLLOWED	
CN	BY THE NORD BANDS FOR THE SECOND, ETC.	
C		
CN	HIGHER LEGENDRE ORDER SCATTERING CROSS SECTIONS	
CN	INCLUDE A 2*L+1 FACTOR WHERE L IS THE LEGENDRE	

CN ORDER.
C
C-----
CEOF

```

C*****
C
C
C
CF      SOLINP
CE      CODE DEPENDENT FILE OF INFORMATION SPECIFIC TO THE
CE      ONEDANT SOLVER MODULE
C
C
C*****
C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                                PRESENT IF
CS      =====
CS      FILE IDENTIFICATION                        ALWAYS
CS      TITLE CARD COUNT                          ALWAYS
CS      ***** (REPEAT FOR UP TO 10 CDS)
CS      *      TITLE CARD                          NHEAD.GT.0
CS      *****
CS      DIMENSION                                  ALWAYS
CS      RAW CONTROLS AND DIMENSIONS                ALWAYS
CS      RAW FLOATING INPUT DATA                   ALWAYS
CS      DEFAULTED CONTROLS AND DIMENSIONS          ALWAYS
CS      DEFAULTED FLOATING INPUT DATA              ALWAYS
CS      BNDRY TRANSFER FIRST SOURCE GROUP          IBL.EQ.4.OR.IBR.EQ.4
CS      BNDRY TRANSFER VECTOR LENGTHS              IBL.EQ.4.OR.IBR.EQ.4
CS      ***** (REPEAT FOR ALL GROUPS)
CS      *      LEFT BDRY TRANSFER VECTOR            IBL.EQ.4
CS      *      RIGHT BDRY TRANSFER VECTOR           IBR.EQ.4
CS      *****
CS      FINE MESH DENSITY FACTORS                   IDEN.EQ.1
CS      RADIUS MODIFIERS                           IEVT.EQ.4
CS      LEFT ALBEDOES                               IBL.EQ.4
CS      RIGHT ALBEDOES                              IBR.EQ.4
CS      SINGLE CHI ARRAY(FISSION SPECTRA)          INCHI.EQ.1
CS      ***** (REPEAT FOR ALL ZONES)
CS      *      CHI ARRAY(FISSION SPECTRA)           INCHI.EQ.2
CS      *****
CS      QUADRATURE WEIGHTS                         IQUAD.EQ.3
CS      QUADRATURE COSINES                         IQUAD.EQ.3
CS      ***** (REPEAT FOR ALL MOMENTS)
CS      *      SOURCE SPECTRUM                     IQOPT.EQ.1
CS      *      SOURCE SPATIAL DISTRIBUTION          IQOPT.EQ.2
CS      * ***** (REPEAT FOR ALL GROUPS)
CS      * *      SOURCE SPATIAL DISTRIBUTION        IQOPT.EQ.3
CS      * *****
CS      *      SOURCE SPECTRUM                     IQOPT.EQ.4
CS      *      SOURCE SPATIAL DISTRIBUTION          IQOPT.EQ.4
CS      *****
CS      LEFT BOUNDARY ISOTROPIC SOURCES             IQL.EQ.-1
CS      RIGHT BOUNDARY ISOTROPIC SOURCES            IQR.EQ.-1
CS      ***** (REPEAT FOR ALL GROUPS)
CS      *      LEFT BOUNDARY ANISOTROPIC SOURCE     IQL.EQ.+1
CS      *      RIGHT BOUNDARY ANISOTROPIC SOURCE    IQR.EQ.+1

```

```

CS      *****
C
C-----
C
CR      FILE IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - SOLINP - (A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT            DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----
C
CR      TITLE CARD COUNT
C
CL      NHEAD
C
CW      1=NUMBER OF WORDS
C
CD      NHEAD          NUMBER OF TITLE CARDS TO FOLLOW
C
C-----
C
CR      TITLE CARD
C
CC      PRESENT IF NHEAD.GT.0
C
CL      (TITLE(I), I=1,12)
C
CW      12=NUMBER OF A6 WORDS
C
C-----
C
CR      SPATIAL DIMENSION
C
CL      IDIMEN
C
CW      1=NUMBER OF WORDS
C
CD      IDIMEN=1 FOR ONEDANT
C
C-----
C
CR      RAW CONTROLS AND DIMENSIONS
C
CL      IEVT, ITH,     ISCT, ISN,    IQUAD, ISTART, ICSM, INCHI, IBL, IBR,

```

CL	1	IDEN, IPVT, I2ANG, IQOPT, IQAN, IQL, IQR, OITM, IITL, IITM,	-
CL	2	ITLIM, I1, FLUXP, XSECTP, FISSRP, SOURCP, GEOMP, IANG, IACC, DUM1,	-
CL	3	DUM2, IAFLUX, ISBEDO, IBALP, DUM3, IBB, IBT, IITLD, IQT, IQB,	-
CL	4	IXM, IYM, IZM, IDENY, IDENZ	-
C			-
CW		100=NUMBER OF WORDS	-
C			-
CD	1	IEVT TYPE OF CALCULATION	-
CD	2	ITH 0/1 - DIRECT/ADJOINT CALCULATION	-
CD	3	ISCT LEGENDRE ORDER OF SCATTERING	-
CD	4	ISN ANGULAR QUADRATURE ORDER	-
CD	5	IQUAD SOURCE OF QUADRATURE SET	-
CD	6	ISTART FLUX GUESS FLAG (ZERO FOR ONEDANT)	-
CD	7	ICSM 0/1 - NO/YES IN-SOLVER MIXING (FROM ASSIGN=)	-
CD	8	INCHI 0/1/2 - NONE/ONE CHI/ZONEWISE CHI	-
CD	9	IBL 0/1/2/3/4 - LEFT BDY CONDITION	-
CD	10	IBR 0/1/2/3/4 - RIGHT BDY CONDITION	-
CD			-
CD	11	IDEN 0/1 - NO/YES FINE MESH DENSITY FACTORS	-
CD	12	IPVT 0/1/2 - NONE/K-EFF/ALPHA PARAMETRIC EIGENVALUE TYPE	-
CD	13	I2ANG 0/1 - NO/YES DO 2 ANGLE SLAB CALCULATION	-
CD	14	IQOPT 0/1/2/3/4/5 - INHOMOGENEOUS SOURCE OPTION	-
CD	15	IQAN INHOMOGENEOUS SOURCE LEGENDRE ORDER	-
CD	16	IQL -1/0/1 - ISOTROPIC/NONE/ANGULAR LEFT BOUNDARY SOURCE	-
CD	17	IQR -1/0/1 - ISOTROPIC/NONE/ANGULAR RIGHT BOUNDARY SOURCE	-
CD	18	OITM OUTER ITERATION LIMIT	-
CD	19	IITL EARLY INNER ITERATION LIMIT	-
CD	20	IITM NEAR CONVERGENCE INNER ITERATION LIMIT	-
CD			-
CD	21	ITLIM TIME LIMIT IN SECONDS	-
CD	22	I1 NOT USED	-
CD	23	FLUXP 0/1/2 - NONE/ISOTROPIC/ALL MOMENTS FLUX PRINT	-
CD	24	XSECTP 0/1/2 - NONE/PRINCIPAL/ALL CROSS SECTION PRINT	-
CD	25	FISSRP 0/1 - NO/YES FISSION RATE PRINT	-
CD	26	SOURCP 0/1/2/3 - NO/AS READ/NORMALIZED/BOTH SOURCE PRINT	-
CD	27	GEOMP 0/1 - NO/YES FINE MESH GEOMETRY PRINT	-
CD	28	ANGP 0/1 - NO/YES ANGULAR FLUX PRINT	-
CD	29	IACC ACCELERATION TYPE (FIXED AT 2 FOR ONEDANT)	-
CD	30	DUM1 NOT USED	-
CD			-
CD	31	DUM2 NOT USED	-
CD	32	RAFLUX 0/1 - NO/YES WRITE ANGULAR FLUX FILE RAFLUX	-
CD	33	ISBEDO ALBEDO PRESENCE CODE	-
CD	34	IBALP 0/1 - NO/YES PRINT BALANCES BY ZONE	-
CD	35	DUM3 NOT USED	-
CD	36	IBB NOT USED BY ONEDANT	-
CD	37	IBT NOT USED BY ONEDANT	-
CD	38	IITLD NOT USED BY ONEDANT	-
CD	39	IQT NOT USED BY ONEDANT	-
CD	40	IQB NOT USED BY ONEDANT	-
CD			-
CD	41	IXM NOT USED BY ONEDANT	-
CD	42	IYM NOT USED BY ONEDANT	-
CD	43	IZM NOT USED BY ONEDANT	-

CD 44 IDENY NOT USED BY ONEDANT
CD 45 IDENZ NOT USED BY ONEDANT

C
C
C
C

CR RAW FLOATING DATA

C
CL
CL
C

EV, NORM, EPSO, EPSI, BHGT, BWTH, EVM, PV, XLAL, XLAH,
XLAX, POD, EPSR, EPSX, EPST

CW 90=NUMBER OF WORDS

C

CD 1 EV EIGENVALUE GUESS
CD 2 NORM NORMALIZATION CONSTANT
CD 3 EPSO OUTER ITERATION CONVERGENCE CRITERION
CD 4 EPSI INNER ITERATION CONVERGENCE CRITERION
CD 5 BHGT BUCKLING HEIGHT
CD 6 BWTH BUCKLING WIDTH
CD 7 EVM EIGENVALUE MODIFIER
CD 8 PV PARAMETRIC VALUE
CD 9 XLAL LAMBDA LOWER LIMIT FOR SEARCHES
CD 10 XLAH LAMBDA UPPER LIMIT FOR SEARCHES
CD
CD 11 XLAX SEARCH CONVERGENCE CRITERION
CD 12 POD PARAMETER OSCILLATION DAMPER
CD 13 EPSR DIFFUSION PERIODIC BDY ITERATION CONV. CRITERION
CD 14 EPSX MAX FRACTIONAL POINTWISE CHANGE CRITERION
CD 15 EPST NOT USED BY ONEDANT

C
C

CR DEFAULTED CONTROLS AND DIMENSIONS

C

CN THIS RECORD IS THE SAME FORMAT AS THE RAW CONTROLS AND DIMENSION
CN RECORD ABOVE, BUT IT CONTAINS THE DEFAULTED VALUES FOR EACH
CN VARIABLE

C
C
C

CR DEFAULTED FLOATING DATA

C

CN THIS RECORD IS THE SAME FORMAT AS THE RAW FLOATING DATA
CN RECORD ABOVE, BUT IT CONTAINS THE DEFAULTED VALUES FOR EACH
CN VARIABLE

C
C
C

CR BOUNDARY TRANSFER FIRST SOURCE GROUP

C

CC PRESENT IF IBL.EQ.4 .OR. IBR.EQ.4

C

CL (IFSGL(N),N=1,NGROUP),(IFSGR(N),N=1,NGROUP)

```

C
CW      2*NGROUP=NUMBER OF WORDS
C
CD      IFSGL    FIRST SOURCE GROUP FOR LEFT BOUNDARY
CD      IFSGR    FIRST SOURCE GROUP FOR RIGHT BOUNDARY
CD      NGROUP   NUMBER OF ENERGY GROUPS
C
C-----
C
C-----
CR      BOUNDARY TRANSFER VECTOR LENGTHS
C
CC      PRESENT IF IBL.EQ.4 .OR. IBR.EQ.4
C
CL      (LENL(N),N=1,NGROUP),(LENR(N),N=1,NGROUP)
C
CW      2*NGROUP=NUMBER OF WORDS
C
CD      LENL     LENGTH OF THE VECTOR OF TRANSFERS INTO GRP N
CD              AT THE LEFT BOUNDARY
CD      LENR     LENGTH OF THE VECTOR OF TRANSFERS INTO GRP N
CD              AT THE RIGHT BOUNDARY
C
C-----
C
C-----
CR      LEFT BOUNDARY TRANSFER VECTOR
C
CC      PRESENT IF IBL.EQ.4
C
CL      (TRL(I),I=1,NW)
C
CW      NW=NUMBER OF WORDS
C
CD      TRL(I)   I-TH TRANSFER INTO GROUP N FOR LEFT BOUNDARY
CD              THE FIRST VALUE IS THE TRANSFER FROM GROUP IFSGL(N)
CD              INTO GROUP N, NEXT IS FROM GROUP IFSGL(N)-1 TO N, ETC.-
CD      NW      LENL(N)
CD      N       NUMBER OF THE RECEIVING GROUP
C
C-----
C
C-----
CR      RIGHT BOUNDARY TRANSFER VECTOR
C
CC      PRESENT IF IBR.EQ.4
C
CL      (TRR(I),I=1,NW)
C
CW      NW=NUMBER OF WORDS
C
CD      TRR(I)   I-TH TRANSFER INTO GROUP N FOR RIGHT BOUNDARY
CD              THE FIRST VALUE IS THE TRANSFER FROM GROUP IFSGR(N)
CD              INTO GROUP N, NEXT IS FROM GROUP IFSGR(N)-1 TO N, ETC.-

```


CD NW LENR(N)
 CD N NUMBER OF THE RECEIVING GROUP

C

C-----

C

C-----

CR FINE MESH DENSITY FACTORS

C

CC PRESENT IF IDEN.EQ.1

C

CL (DEN(I),I=1,IT)

C

CW IT=NUMBER OF WORDS

C

CD IT NUMBER OF FINE MESH INTERVALS

C

C-----

C

C-----

CR RADIAL MODIFIERS

C

CC PRESENT IF IEVT.EQ.4

C

CL (RM(I),I=1,IM)

C

CW IM=NUMBER OF WORDS

C

CD IM NUMBER OF COARSE MESH INTERVALS

C

C-----

C

C-----

CR LEFT ALBEDOES

C

CC PRESENT IF IBL.EQ.4

C

CL (LBEDO(N),N=1,NGROUP)

C

CW NGROUP=NUMBER OF WORDS

C

C-----

C

C-----

CR RIGHT ALBEDOES

C

CC PRESENT IF IBR.EQ.4

C

CL (RBEDO(N),N=1,NGROUP)

C

CW NGROUP=NUMBER OF WORDS

C

C-----

C

C-----

```

CR          CHI - FISSION SPECTRA
C
CC          PRESENT IF INCHI.NE.0
C
CL          (CHI(N),N=1,NGROUP)
C
CW          NGROUP=NUMBER OF WORDS
C
C-----
C
C-----
CR          QUADRATURE WEIGHTS
C
CC          PRESENT IF IQUAD.EQ.3
C
CL          (WGT(M),M=1,MM)
C
CW          MM=NUMBER OF WORDS
C
CD          MM          NUMBER OF ANGLES IN QUADRATURE SET
C
C-----
C
C-----
CR          QUADRATURE COSINES
C
CC          PRESENT IF IQUAD.EQ.3
C
CL          (MU(M),M=1,MM)
C
CW          MM=NUMBER OF WORDS
C
C-----
C
C-----
CR          SOURCE SPECTRUM
C
CC          PRESENT IF IQOPT.EQ.1 .OR. IQOPT.EQ.4
C
CL          (SOURCE(N),N=1,NGROUP)
C
CW          NGROUP=NUMBER OF WORDS
C
C-----
C
C-----
CR          SOURCE SPATIAL DISTRIBUTION
C
CC          PRESENT IF IQOPT.EQ.2 .OR. IQOPT.EQ.3 .OR. IQOPT.EQ.4
C
CL          (SOURCX(I),I=1,IT)
C
CW          IT=NUMBER OF WORDS

```


SPECIFICATIONS FOR INTERFACE FILE TRIGON

```

C.....
C              REVISED 04/01/80
C
C
CF          TRIGON
C
C          TRIANGULAR GEOMETRY DESCRIPTION
C
C.....

```

```

C-----
CR          FILE IDENTIFICATION (NV)
C
CL          NNAME, (NUSE(I), I=1,2), IVERS
C
CV          1+3=HOLT
C
CD          NNAME          HOLLEPITH FILE NAME - TRIGON - (A6)
CD          NUSE          HOLLEPITH USER IDENTIFICATION (A6)
CD          IVERS          FILE VERSION NUMBER
C
CN          HOLT          1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C
C-----

```

```

C-----
CR          FILE REFERENCE INFORMATION (10 RECORD)
C
CL          IGOH, NZONE, NREG, NZCL, NCINTI, NCINTJ, NCINTK, NINTI, NINTJ, NINTK, INB1,
CL          INB2, JNB1, JNB2, KNB1, KNB2, NBS, NBS1, NBS2, NBS3, NBS4, NBS5, NBS6, NBS7, NBS8, NBS9, NBS10,
CL          (NGOP(I), I=1,5)
C
CV          27
C
CD          IGOH          GEOMETRY 5- SPECIAL TRIANGULAR, TWO-DIMENSIONAL
CD                      19- SPECIAL TRIANGULAR-2, THREE-DIMENSIONAL
CD          NZONE          NUMBER OF ZONES (EACH HOMOGENEOUS IN NEUTRONICS
CD                      PROBLEM)
CD          NREG          NOT DEFINED
CD          NZCL          NUMBER OF ZONE CLASSIFICATIONS (EDIT PURPOSES)
CD          NCINTI          NOT DEFINED
CD          NCINTJ          NOT DEFINED
CD          NCINTK          NUMBER OF THIRD DIMENSION COARSE MESH INTERVALS
CD                      NCINTK.EQ.1 FOR ONE AND TWO
CD                      DIMENSIONAL CASES.
CD                      A COARSE MESH INTERVAL IS DEFINED AS ONE
CD                      CONTAINING ONE OR MORE FINE MESH INTERVALS, EACH
CD                      OF WHICH CONTAINS THE SAME MATERIAL ZONE.
CD          NINTI          THE NUMBER OF POINTS ON A PLANE. POINTS ARE AT
CD                      THE INTERSECTIONS OF MESH LINES.
CD          NINTJ          NOT DEFINED
CD          NINTK          NUMBER OF THIRD DIMENSION FINE MESH INTERVALS
CD                      NINTK.EQ.1 FOR ONE AND TWO DIMENSIONAL
CD                      CASES.

```

(CONT)

C9 1781 FIRST BOUNDARY ON FIRST DIMENSION
 C9 0- ZERO FLUX (DIFFUSION)
 C9 1- REFLECTED
 C9 2- EXTRAPOLATED (DIFFUSION - DEL PHI
 C9 /PHI = -C/D WHERE C IS GIVEN AS BNOC
 C9 BELOW AND D IS THE GROUP DIFFUSION
 C9 CONSTANT, TRANSPORT - NO RETURN)
 C9 3- NOT DEFINED
 C9 4- REPEATING (PERIODIC) WITH TEXT
 C9 ADJACENT FACE 60 OR 120 DEGREE
 C9 ROTATION).
 C9 THE LEFT AND TOP BOUNDARIES ARE
 C9 REPEATING.
 C9 5- NOT DEFINED
 C9 6- NOT DEFINED
 C
 C9 NOTE THAT FOR REPEATING BOUNDARIES, THE FIRST BOUNDARY IN
 C9 ORDER WHICH IS INVOLVED CARRIES THE DESIGNATOR DEFINING
 C9 THE REPEATING CONDITION.
 C
 C9 1782 LAST BOUNDARY ON FIRST DIMENSION
 C9 1781 FIRST BOUNDARY ON SECOND DIMENSION
 C9 5- REPEATING ALONG THIS BOUNDARY - 180
 C9 DEGREES. IF NPP EQUALS THE NUMBER OF
 C9 POINTS ON THIS BOUNDARY, THEN THE FLUXES
 C9 AT POINTS NPP/2 THROUGH NPP ARE EQUAL
 C9 TO THE FLUXES AT POINTS 1 THROUGH NPP/2
 C9 FOR THIS OPTION, INB1=1782 AND
 C9 NTRIAG=1.
 C9 1782 LAST BOUNDARY ON SECOND DIMENSION
 C9 1781 FIRST BOUNDARY ON THIRD DIMENSION
 C9 1782 LAST BOUNDARY ON THIRD DIMENSION
 C9 NBS NUMBER OF BUCKLING SPECIFICATIONS
 C9 1- SINGLE VALUE APPLIES EVERYWHERE
 C9 .EQ.NZONE, ZONE-DEPENDENT
 C9 N=1ZONE, DATA IS GIVEN OVER ALL ZONES FOR
 C9 THE FIRST ENERGY GROUP, THEN FOR THE NEXT
 C9 GROUP, TO END OF LIST - IF THERE ARE MORE
 C9 GROUPS, LAST GROUP DATA GIVEN IS USED
 C9 NBGS NUMBER OF CONSTANTS FOR EXTERNAL BOUNDARIES
 C9 1- SINGLE VALUE USED EVERYWHERE
 C9 6- INDIVIDUAL VALUES FOR EACH POSSIBLE
 C9 SURFACE (BOUNDARY SPECS GIVE ACTUAL USE)
 C9 N=6- SIX VALUES ARE GIVEN FOR THE FIRST
 C9 ENERGY GROUP, THEN SIX FOR THE NEXT, TO
 C9 THE END OF THE LIST - THE LAST GROUP DATA
 C9 GIVEN APPLIES TO ALL ADDITIONAL GROUPS
 C9 NIBGS NUMBER OF CONSTANTS FOR INTERNAL BOUNDARIES
 C9 1- SINGLE VALUES USED EVERYWHERE
 C9 .GT.1- VALUES ARE GIVEN BY ENERGY GROUP
 C9 WITH NON-BLACK CONDITION INDICATED BY
 C9 ZERO ENTRY - LAST VALUE APPLIES TO
 C9 ADDITIONAL GROUPS

(CONT)

```

      (CONT)
CD   NZWBB      BLACK ABSORBER ZONE INDICATOR.
CD           0- NO BLACK ZONES.
CD           1- ONE BLACK ABSORBER ZONE.
CD   NTRIAG     MESH ORIENTATION
CD           0- RHOMBUS WITH 120 DEGREES AT UPPER LEFT
CD              CORNER (NPL.SQ.NPP BELOW).
CD           1- TRAPEZOID (OR TRIANGLE) WITH 60 DEGREES AT
CD              UPPER LEFT AND UPPER RIGHT CORNERS
CD              (NPL.LT.NPP).
CD           2- TRIANGLE WITH 30 DEGREES AT UPPER LEFT
CD              CORNER AND 60 DEGREES AT UPPER RIGHT
CD              CORNER (NPL.LT.NPP). INB1 AND JNB2 MUST BE 1
CD              AND NPP.GE. 3.
CD   NTRASS     ZONE ASSIGNMENTS.
CD           0- TO COARSE MESH
CD           1- TO FINE MESH
CD   NGOP       NOT DEFINED.
C
C-----

```

```

C-----
CR      GEOMETRY DATA (2D RECORD)
C
CL      (BSQ(N),N=1,NBS), (BNDC(N),N=1,NBCS), (BNCI(N),N=1,NIBCS),
CL      (NZWBB(N),N=1,NZWBB), (NZC(N),N=1,NZONE)
C
CV      NBS+NBCS+NIBCS+NZWBB+NZONE
C
CD      BSQ      BUCKLING (B=2) VALUES (CH=2)
CD      BNDC     BOUNDARY CONSTANTS (DEL PHI/PHI =-C/D)
CD      BNCI     INTERNAL BLACK BOUNDARY CONSTANTS
CD      NZWBB    ZONE NUMBER WITH BLACK ABSORBER CONDITIONS
CD      NZC      ZONE CLASSIFICATIONS
C
C-----

```

```

C-----
CR      REFERENCE MESHPOINT DATA (3D RECORD)
C
CL      NPO,NPP,NPL,NRP,NRP,NRS,NOS,N03,NZA,NB,NC, (KPINTS(L),L=1,NCINTK)
C
CV      NCINTK = 11
C
CD      NPO      MESHPOINT LOCATION OPTION
CD           0- UNIFORM, EQUILATERAL MESH ARRANGEMENT
CD              (SIMPLE GEOMETRY DESCRIBED BY DATA IN THIS
CD              RECORD, NRP=6)
CD           1- PARALLEL ROWS OF MESH POINTS
CD           2- GENERAL ARRANGEMENT
CD      NPP      NUMBER OF POINTS ALONG FIRST (TOP) ROW
CD              -- USED IF NPO = 0
C

```

(CONT)

```

CD   NPL          NUMBER OF POINTS ALONG LAST (BOTTOM) ROW
CD           -- USED IF NPD = 0. NPL MUST BE .EQ. OR .LT. NPP.
CD           FOR NPL.EQ.NPP, 120 DEGREES IS IN UPPER LEFT
CD           CORNER. IF NPL.LT.NPP, THE UPPER LEFT CORNER
CD           IS 30 OR 60 DEGREES (SEE NTRIAG ABOVE).
CD   NRP          NUMBER OF ROWS OF POINTS
CD           -- USED IF NPD .LT. 2
CD   NRP          REFERENCE OR MAXIMUM NUMBER OF NEIGHBOR POINTS ON A
CD           PLANE
CD   NRS          NUMBER OF CONE ASSIGNMENTS ON EACH PLANE
CD   NOS          NOT DEFINED
CD   NOJ          NOT DEFINED
CD   NOA          NOT DEFINED
CD   NB          NOT DEFINED
CD   NC          NOT DEFINED
CD   NPINTS       NUMBER OF FINE MESH INTERVALS PER COARSE MESH
CD               INTERVAL, THIRD DIMENSION
C
CN   MESHPOINTS HERE MAY BE INTERPRETED AS TRIANGLE CORNERS
C
C-----

```

```

C-----
C   REFERENCE DATA (40 RECORD)
C
CL   PRESH,QRESH,X1,X2,X3,(ZRESH(K),K=1,NCBNDK)
C
CV   NULT* (NCINTK*6)
C
CD   PRESH       LENGTH OF TRIANGLE LEG (MESHPOINT SPACING) IF FIXED
CD           -- USED IF NPD = 0
CD   QRESH       NOT DEFINED
CD   X1          NOT DEFINED
CD   X2          NOT DEFINED
CD   X3          NOT DEFINED
CD   ZRESH       COARSE MESH BOUNDARIES, THIRD DIMENSION
CD   NCBNDK      NCINTK+1, NUMBER OF THIRD DIMENSION COARSE MESH
CD               BOUNDARIES
C
CN   NOTE THAT FOR TWO-DIMENSIONAL PROBLEMS, NCINTK=1, NCBNDK=2,
CN   ALTHOUGH DATA FOR THE THIRD DIMENSION ARE NOT USED (ICOR=5)
C
C-----

```

```

C-----
C   MESHPOINT ARRANGEMENTS (50 RECORD)
C
CC   PRESENT IF NPD.EQ.1
C
CL   (XRESH(I),I=1,NINTI),(YROR(J),J=1,NRP),(YRPR(J),J=1,NRP)
C
CV   NULT* (NINTI * NRP) * NRP
C
C-----

```

(CONT)

C
 CD XRESH LOCATION OF EACH MESHPOINT ON A PLANE MEASURED FROM
 CD REFERENCE ALONG X COORDINATE, CH
 CD YROW ROW LOCATION MEASURED FROM REFERENCE ALONG Y
 CD COORDINATE (NORMAL TO X), CH
 CD NRPB NUMBER OF MESH POINTS ON THE ROW
 C
 C-----

C-----
 CH MESHPOINT ARRANGEMENTS (6D RECORD)
 C
 CC PRESENT IF NPO.EQ.2
 C
 CL ((XRESH(I,J),I=1,2),J=1,NINTI)
 C
 CV 2*NULT*NINTI
 C
 CD XRESH(1,J) LOCATION OF MESHPOINT MEASURED ALONG X COORDINATE
 CD FROM REFERENCE (INCREASING ORDER FOR ANY Y), CH
 CD XRESH(2,J) LOCATION OF MESHPOINT MEASURED ALONG Y COORDINATE
 CD FROM REFERENCE, Y NORMAL TO X, (INCREASING), CH
 C
 C-----

THERE ARE NINTI RECORDS WHICH FOLLOW IF NPAIS IS 0
 NINTI RECORDS WHICH FOLLOW IF NPAIS IS 1
 BUT ONLY ONE SET IF IGON IS 5

C-----
 CH TRIANGLE ZONE ASSIGNMENTS (7D RECORD)
 C
 CC ALWAYS PRESENT
 C
 CL (NR(I),I=1,NRS)
 C
 CV NRS
 C
 CD NR ZONE NUMBER ASSIGNMENT TO MESH INTERVAL
 C
 CH CONSIDER THAT NEAR-NEIGHBOR POINTS HAVE A LINE OF COUPLING.
 CH COUPLING LINES FORM TRIANGLES. THE TRIANGLES LYING
 CH WHOLLY BELOW A LOCAL HORIZONTAL LINE ARE ASSIGNED ZONE
 CH NUMBERS THROUGH THE MESH STARTING WITH THE FIRST (TOP)
 CH HORIZONTAL ROW, INCREASING I GIVEN Y, THEN INCREASING Y
 C
 C-----

C-----
 CH
 C
 CD? TRIGON
 C
 C-----


```

C*****
C                                     REVISED 11/30/76
C
C
CF      WORTHS-IV
CE      REACTIVITY PER CC BY FINE MESH INTERVAL
C
C*****

```

```

C-----
CS      FILE STRUCTURE
CS
CS      RECORD TYPE                      PRESENT IF
CS      =====
CS      IDENTIFICATION                   ALWAYS
CS      SPECIFICATIONS                   ALWAYS
CS      DELAYED NEUTRON DATA            ALWAYS
CS
CS      ***** (REPEAT FOR ALL REACTIVITY SETS)
CS      *   REACTIVITY SET DATA         ALWAYS
CS      *   ONE DIMENSIONAL REACTIVITIES NDIM.EQ.1
CS      *   MULTI-DIMENSIONAL REACTIVITIES NDIM.GE.2
CS      *****
C
C-----

```

```

C-----
CR      IDENTIFICATION
C
CL      HNAME, (HUSE(I), I=1,2), IVERS
C
CW      1+3*MULT=NUMBER OF WORDS
C
CD      HNAME          HOLLERITH FILE NAME - WORTHS -(A6)
CD      HUSE(I)        HOLLERITH USER IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
CD      MULT           DOUBLE PRECISION PARAMETER
CD                      1- A6 WORD IS SINGLE WORD
CD                      2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

```

```

C-----
CR          SPECIFICATIONS      (1D RECORD)
C
CL    GTIME,BETAEF,NDIM,NINTI,NINTJ,NINTK,NFI,NISOD,NFAM,NSETS,NBLOK
C
CW    10 = NUMBER OF WORDS
C
CD    GTIME          PROMPT NEUTRON GENERATION TIME (SECONDS)
CD    BETAEF         TOTAL DELAYED NEUTRON FRACTION
CD    NDIM           NUMBER OF DIMENSIONS
CD    NINTI          NUMBER OF FIRST DIMENSION FINE MESH INTERVALS
CD    NINTJ          NUMBER OF SECOND DIMENSION FINE MESH INTERVALS
CD    NINTK          NUMBER OF THIRD DIMENSION FINE MESH INTERVALS
CD    NISOD          NUMBER OF FISSIONABLE ISOTOPES OR MATERIALS
CD    NFAM           NUMBER OF DELAYED NEUTRON FAMILIES
CD    NSETS          NUMBER OF REACTIVITY SETS
CD    NBLOK          DATA BLOCKING FACTOR. THE SECOND DIMENSION
CD                   VARIABLE IS BLOCKED INTO NBLOK BLOCKS.
CD                   ----SEE 5D RECORD BELOW----
C
C-----

```

```

C-----
CR          DELAYED NEUTRON DATA      (2D RECORD)
C
CL    (NFISO(NF),NF=1,NISOD),((FBETA(I,NF),I=1,NFAM),NF=1,NISOD)
C
CW    NISOD*(NFAM+1) = NUMBER OF WORDS
C
CD    NFISO(NF)       ORDER NUMBER OF FISSIONABLE ISOTOPE
CD                   OR MATERIAL NF IN CROSS SECTION FILE
CD    FBETA(I,NF)     DELAYED NEUTRON FRACTION FOR ISOTOPE OR
CD                   MATERIAL NF AND DELAYED NEUTRON FAMILY I
C
C-----

```

```

C-----
CR          REACTIVITY SET DATA      (3D RECORD)
C
CL    (HPERTD(I),I=1,12),HSETID,RHO,TEMP1,TEMP2
C
CW    13*MULT+3=NUMBER OF WORDS
C
CD    HPERTD(I)       PERTURBATION DESCRIPTION (12A6)
CD    HSETID          HOLLERITH REFERENCE NAME OF REACTIVITY SET (A6)

```

```

CD      RHO          TOTAL REACTIVITY IN SET (INTEGRATED OVER MESH) -
CD      TEMP1        AVERAGE REFERENCE FUEL TEMPERATURE - KELVIN -
CD      TEMP2        AVERAGE PERTURBED FUEL TEMPERATURE - KELVIN -
C
CC      TEMP1 AND TEMP2 UNDEFINED EXCEPT WHEN THE SET WORTHS ARE DUE -
CC      TO A TEMPERATURE PERTURBATION OF CROSS SECTIONS -
C
C-----

```

```

C-----
CR      ONE-DIMENSIONAL REACTIVITIES      (4D RECORD) -
C
CC      PRESENT IF NDIM.EQ.1 -
C
CL      (WORTHS(I),I=1,NINTI) -
C
CW      NINTI=NUMBER OF WORDS -
C
CD      WORTHS(I)          REACTIVITY PER CC BY FINE MESH INTERVAL -
C
C-----

```

```

C-----
CR      MULTI-DIMENSIONAL REACTIVITIES    (5D RECORD) -
C
CC      PRESENT IF NDIM.GE.2 -
C
CL      ((WORTHS(I,J),I=1,NINTI),J=JL,JU) ----NOTE STRUCTURE BELOW---- -
C
CW      NINTI*(JU-JL+1) = NUMBER OF WORDS -
C
C      DO 1 K=1,NINTK -
C      DO 1 M=1,NBLOK -
C      1 READ(N) *LIST AS ABOVE* -
C
CC      WITH M AS THE BLOCK INDEX, JL=(M-1)*((NINTJ-1)/NBLOK +1)+1 -
CC      AND JU=MINO(NINTJ,JUP) WHERE JUP=M*((NINTJ-1)/NBLOK +1) -
C
CD      WORTHS(I,J)          REACTIVITY PER CC BY FINE MESH INTERVAL -
C
C-----

```

CEOF

```

C*****
C              REVISED 11/30/76
C
CF          ZNATDN-IV
CE          ZONE ATOMIC DENSITIES (OF NUCLIDES)
C
C*****

C-----
CR          FILE IDENTIFICATION
C
CL  HNAME.(HUSE(I).I=1.2).IVERS
C
CW  1+3*MULT=NUMBER OF WORDS
C
CD  HNAME          HOLLERITH FILE NAME - ZNATDN - (A6)
CD  HUSE(I)        HOLLERITH USER IDENTIFICATION - (A6)
CD  IVERS          FILE VERSION NUMBER
CD  MULT           DOUBLE PRECISION PARAMETER
CD                  1- A6 WORD IS SINGLE WORD
CD                  2- A6 WORD IS DOUBLE PRECISION WORD
C
C-----

C-----
CR          SPECIFICATIONS          (1D RECORD)
C
CL  TIME.NCY.NTZSZ.NNS.NBLKAD
C
CW  5=NUMBER OF WORDS
C
CD  TIME          REFERENCE REAL TIME. DAYS
CD  NCY           REFERENCE CYCLE NUMBER
CD  NTZSZ         NUMBER OF ZONES PLUS NUMBER OF SUBZONES
CD  NNS           MAXIMUM NUMBER OF NUCLIDES IN ANY SET
CD  NBLKAD        NUMBER OF BLOCKS OF ATOM DENSITY DATA
C
C-----

```

Figure VII.2 Specifications for ZNATDN Interface File

```

C-----
CR          ZONE ATOMIC DENSITIES (OF NUCLIDES)      ED RECORD)
C
CL      ((ADEN(N,J).N=1.NNS).J=JL.JU)----SEE STRUCTURE BELOW-
C
CW      NNS*(JL - JU + 1) = NUMBER OF WORDS
C
CC      DO 1 M=1.NBLKAD
CC 1 READ(N)  *LIST AS ABOVE*
C
CC          WITH M AS THE BLOCK INDEX. JL=(M-1)*((NTZSZ-1)/NBLKAD+1)+1
CC          AND JU=MINO(NTZSZ.JUP) WITH JUP=M*((NTZSZ-1)/NBLKAD + 1)
C
CD      ADEN(N,J)          ATOMIC DENSITY OF NUCLIDE ORDERED N IN THE
CD                          ASSOCIATED SET GIVEN IN ORDER FOR EACH ZONE
C
C-----

```

CEOF

SPECIFICATIONS FOR INTERFACE FILE ZNPWD

```

C.....
C          REFERENCE 02/01/79 ORNL-5180
C
C  CN      ORIGINAL SPECS REVISED TO INCLUDE SUBZONE DATA WHEN NEEDED
C
C  CP      ZNPWD
C
C  CZ      ZONE AVERAGE AND PEAK POWER DENSITY
C.....

```

```

C-----
C          FILE IDENTIFICATION
C
C  CL      RNAME, (RUSE(I), I=1,2), IVERS
C
C  CW      RESULT * 1
C
C  CD      RNAME      FILE NAME (A6) 'ZNPWD'
C          RUSE      USER IDENTIFICATION (A6)
C          IVERS     FILE VERSION NUMBER
C
C  CN      MULT      1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C-----

```

```

C-----
C          ID      FILE REFERENCE INFORMATION
C
C  CL      POW, TIME, XZPD3, XZPD4, XZPD5, XZPD6, XZPD7, XZPD8,
C          XZONE, XZPD10, XZPD11, NSZ, XZPD13, XZPD14, XZPD15,
C          XZPD16, XZPD17, XZPD18, XZPD19, XZPD20
C
C  CW      20
C
C  CD      POW      REFERENCE REACTOR POWER LEVEL, WATTS
C          TIME     REFERENCE TIME IN THE HISTORY, DAYS
C          XZPD3    RESERVED
C          XZPD4    RESERVED
C          XZPD5    RESERVED
C          XZPD6    RESERVED
C          XZPD7    RESERVED
C          XZPD8    RESERVED
C          XZONE    NUMBER OF REACTOR ZONES
C          XZPD10   OPTION FOR PEAK ZONE DATA
C          XZPD11   OPTION ON FILE CONTENTS
C                  0- ZONE POWER DENSITY INCLUDES ANY SUBZONE
C                     CONTRIBUTION (ALTHOUGH NSZ MAY BE ZERO)
C                  1- ZONE POWER DENSITY AND SUBZONE POWER DENSITY
C                     CARRIED SEPARATELY
C          NSZ      NUMBER OF REACTOR SUBZONES
C          XZPD13   OPTION FOR REFERENCE INFORMATION
C-----

```

(CONT)

CD	I2PD18	RESERVED
CD	I2PD19	RESERVED
CD	I2PD16	RESERVED
CD	I2PD17	RESERVED
CD	I2PD18	RESERVED
CD	I2PD19	RESERVED
CD	I2PD20	RESERVED

C

C-----

C-----

CR 2D ZONE AVERAGE POWER DENSITIES (TOTAL)

C

CC PRESENT IF I2PD11 .EQ. 0

C

CL (ZPCW (N) , N=1, NZONE)

C

CF NZONE

C

CD ZPCW ZONE AVERAGE POWER DENSITY, WATTS/CC

C

CH $ZPCW(N) = VPPA(N) * ZPD(N) + SUM(OVER J FOR NZSZ(J) = N) OF$

CF $VBSZ(J) * SZPD(J)$

C

C-----

C-----

CR 3D PEAK ZONE POWER DENSITIES

C

CC PRESENT IF I2PD11 .EQ. 0 AND I2PD10 .EQ. 1

C

CL (PZPCW (N) , N=1, NZONE)

C

CF NZONE

C

CD PZPCW PEAK ZONE POWER DENSITY AT THE HESH POINT LEVEL,

CD WATTS/CC

C

C-----

C-----

CR 4D ZONE AVERAGE POWER DENSITIES

C

CC PRESENT IF I2PD11 .EQ. 1

C

CL (ZPD (N) , N=1, NZONE)

C

CF NZONE

C

CD ZPD ZONE AVERAGE POWER DENSITY, WATTS/CC

C

C-----

(CONT)

```

C-----
CR 50 SUBZONE AVERAGE POWER DENSITIES
C
CC PRESENT IF IZPD11 .EQ. 1 AND NSZ .GT. 0
C
CL (SZPD(J), J=1, NSZ)
C
CV NSZ
C
CD SZPD SUBZONE AVERAGE POWER DENSITY, WATTS/CC
C-----

```

```

C-----
CR 60 SUBZONE TO ZONE CORRESPONDENCE
C
CC PRESENT IF IZPD13 .EQ. 1 AND NSZ .GT. 0
C
CL (NZSZ(J), J=1, NSZ)
C
CV NSZ
C
CD NZSZ ZONE CONTAINING SUBZONE
C-----

```

```

C-----
CR 70 ZONE VOLUME INFORMATION
C
CC PRESENT IF IZPD13 .EQ. 1
C
CL (VOLZ(N), N=1, NZONZ)
C
CV NZONZ
C
CD VOLZ ZONE VOLUMES, CC
C-----

```

```

C-----
CR 80 VOLUME FRACTION INFORMATION
C
CC PRESENT IF IZPD13 .EQ. 1
C
CL (VPPA(N), N=1, NZONZ), (VRSZ(J), J=1, NSZ)
C
CV NZONZ + NSZ
C
CD VPPA VOLUME FRACTIONS FOR PRIMARY ZONE ASSIGNMENTS
CD VRSZ VOLUME FRACTIONS FOR SUBZONE ASSIGNMENTS
C-----

```

(CONT)

C.....
C
C207 ZNPOED
C
C.....

SPECIFICATIONS FOR INTERSPACE FILE SYSTEM

```

C.....
C          REFERENCE 02/01/79 ORNL-5180
C
C          ORIGINAL SPECS REVISED TO INCLUDE SUBZONE DATA WHEN NEEDED
C
C          ZTEMP
C
C          ZONE TEMPERATURE DATA
C.....

```

```

C-----
CP          FILE IDENTIFICATION
C
CL      RNAME, (HUSE(I), I=1, 2), IVERS
C
CN          3*HOLT + 1
C
CD      RNAME          FILE NAME (A6) 'INTERP'
CD      HUSE           USE* IDENTIFICATION (A6)
CD      IVERS          FILE VERSION NUMBER
C
CN      HOLT           1 FOR LONG WORD, 2 FOR SHORT WORD MACHINES
C-----

```

```

C-----
C      FILE REFERENCE INFORMATION
C
C      NRZ,NRT,NSZ, (NA (I),I=1,17)
C
C      20
C
C      NRZ      NUMBER OF REACTOR ZONES , NOT ZERO
C      NRT      NUMBER OF TEMPERATURES FOR EACH ZONE .LE. 5
C      NSZ      NUMBER OF REACTOR SUBZONES
C      NA       RESERVED
C
C      OFTEN A SINGLE TEMPERATURE WILL BE CARRIED WHICH SERVES AS A
C      REFERENCE, AS TO EXPRESS THE EFFECTIVE TEMPERATURE OF THE ZONE:
C      WHICH MAY BE USED SIMPLY FOR SUCH PURPOSE AS CROSS SECTION
C      CORRELATION.  OFTEN IF TWO TEMPERATURES ARE CARRIED TO INCLUDE
C      THE COOLANT TEMPERATURE, THE FIRST IS INTENDED TO ADMIT SUCH
C      SIMPLE APPLICATION (LINEAR INTERPOLATION OF CROSS SECTIONS
C      IS ADMITTED WHICH MAY BE DONE AT THE MACROSCOPIC LEVEL USING
C      TWO MICROSCOPIC CROSS SECTION SETS).
C-----

```

(2374)

```

C-----
CZ      ZONE TEMPERATURES
C
CZ      ALWAYS PRESENT
C
CZ      ((ZTEMP(I,N),I=1,NZT),N=1,NRZ)
C
CZ      NZT*NRZ
C
CZ      ZTEMP      TEMPERATURE OF REFERENCE I IN ZONE N (DEGREES C)
CZ                  1      REFERENCE
CZ                  1      FUELS (FUEL) --- REFERENCE
CZ                  2      COOLANT
CZ                  3      MODERATOR
CZ                  4      STRUCTURAL
CZ                  5      SPECIAL
C-----

```

```

C-----
CZ      SUBZONE TEMPERATURES
C
CZ      PRESENT IF NSZ .NE. 0
C
CZ      ((SZTEMP(I,N),I=1,NZT),N=1,NSZ)
C
CZ      NZT*NSZ
C
CZ      SZTEMP      TEMPERATURE OF REFERENCE I IN SUBZONE N (DEGREES C)
C
CZ      SEE NOTES ABOUT ZONE TEMPERATURE DATA
C-----

```

```

C-----
CZ      ZTEMP
C-----

```

END

**DATE
FILMED**

3 / 9 / 93