Energy

F
O
S
S
I
L

150
10/9/84
(20)

(1)

DR-0464-2

DOE/OR/03054-17-Suppl.
(DE84015100)

SRC-I QUARTERLY TECHNICAL REPORT

Supplement for the Period January—March 1983

June 1984

Work Performed Under Contract No. AC05-78OR03054

International Coal Refining Company
Allentown, Pennsylvania

Technical Information Center
Office of Scientific and Technical Information
United States Department of Energy

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available from the National Technical Information Service, U. S. Department of Commerce, Springfield, Virginia 22161.

Price: Printed Copy A05
Microfiche A01

Codes are used for pricing all publications. The code is determined by the number of pages in the publication. Information pertaining to the pricing codes can be found in the current issues of the following publications, which are generally available in most libraries: *Energy Research Abstracts (ERA)*; *Government Reports Announcements and Index (GRA and I)*; *Scientific and Technical Abstract Reports (STAR)*; and publication NTIS-PR-360 available from NTIS at the above address.

DOE/OR/03054-17-Suppl.
(DE84015100)
Distribution Category UC-89

**SRC-I
QUARTERLY TECHNICAL REPORT
SUPPLEMENT
JANUARY—MARCH 1983**

**International Coal Refining Company
Allentown, Pennsylvania**

TABLE OF CONTENTS

	<u>Page no.</u>
RHEOLOGY AND STABILITY OF SRC RESIDUAL FUEL OILS - FINAL REPORT K. C. Tewari	1
EFFECT OF ASPHALTENE-RICH SOLVENT ON COAL LIQUEFACTION D. Kang and E. N. Givens	55

RHEOLOGY AND STABILITY OF SRC RESIDUAL FUEL OILS

FINAL REPORT

K. C. Tewari*

Air Products has completed a laboratory evaluation characterizing the rheology and storage stability of various SRC residual fuel oils. Initial studies determined that molecular weight of the SRC residual-oil components is the main factor in determining the viscosity of the final SRC residual-oil blends. These studies also determined the optimum blend compositions allowing the oils to be handled by conventional fuel handling equipment:

<u>Components</u>	<u>Wt % ratio</u>
HSRC/heavy oil	45/55
TSL SRC/heavy oil	53/47
LSRC/heavy oil	64/36
HSRC/middle oil	65/35
HSRC/middle oil/heavy oil	52/38/10

These blends meet the following criteria: at $\leq 225^{\circ}\text{F}$, viscosity is below 1,000 centipoise (cP) to facilitate pumping; at $\leq 325^{\circ}\text{F}$, viscosity is below 30 cP to properly atomize the fuel. Finally, pumping and atomizing temperatures were found to depend on the type and amount of solid, and increased in the order LSRC < TSL SRC < HSRC.

A second series of studies revealed that storage of blends in air increased viscosity compared to blends stored under nitrogen. However, a blend stored in air for 60 days at 150°F would require a pumping temperature only about 10°F higher than that specified for an unaged blend. It was further determined that some loss of volatiles occurs with high-temperature storage in air or nitrogen.

*Corporate Research Services Department, Air Products and Chemicals, Inc. (APCI).

Final studies in this program revealed the following:

- ° Excepting blends of HSRC and 2nd-stage liquids, SRC residual-oil blends have viscosity/temperature characteristics that permit their use as a No. 6 Fuel Oil substitute using conventional fuel handling equipment.

- ° Complete solubilization of HSRC to form single-phase blends with 2nd-stage middle and heavy oils requires the addition of 1st-stage liquids.

- ° The viscosity characteristics of SRC residual oils depend on solvent boiling range, the type and amount of solid dissolved in the blend, and the heteroatom content.

- ° Long-term storage under air in a closed system at 150°F adversely affects the stability of No. 6 Fuel Oil and HSRC residual oils, but has very little effect on TSL SRC residual oils.

- ° Long-term storage stability of HSRC residual oils is comparable to that of No. 6 Fuel Oil.

INTRODUCTION

Air Products has conducted a laboratory evaluation for International Coal Refining Company (ICRC) to characterize the rheology and storage stability of various SRC residual fuel oils. SRC residual fuel oils are defined as homogeneous, single-phase blends of SRC distillate oils (400-850°F boiling range) and solid SRC (850°F+ boiling range) derived from the first and second stages of the SRC-I coal liquefaction process. The objectives of this program have been to provide the temperature/viscosity characteristics of various residual oil blends prepared in the laboratory, to investigate the storage stability of selected blends, and to develop data that will support future investigations designed to evaluate the potential of these residual oils as viable utility fuel replacements for No. 6 Fuel Oil.

During Phase I of the program, variation of viscosity with temperature was determined for several combinations of the following SRC materials (Tewari et al., 1982):

Solids (850°F+ boiling range)

- ° LSRC (light SRC) - intermediate stream derived from the Kerr-McGee deashing process.
- ° HSRC (heavy SRC) - first-stage SRC product recovered from the SRC-I process after Kerr-McGee deashing.
- ° TSL SRC - two-stage liquefaction or hydrocracked SRC.

Liquids

- ° Middle oil - 400-650°F 1st-stage SRC-I distillate fraction.
- ° Heavy oil - 650-850°F 1st-stage SRC-I distillate fraction.
- ° Process solvent - 450-850°F 1st- and 2nd-stage SRC-I liquids.

It was determined that the fluid characteristics of SRC residual oil blends at a given temperature and composition depend on the average molecular weight of the solid and the amount of low-boiling materials in the liquids used in the blends. The optimum compositions of the blends were based on criteria selected as reasonable upper limits allowing the blends to be handled by conventional fuel handling equipment: at $\leq 225^{\circ}\text{F}$, the viscosity must be below 1,000 cP to facilitate pumping and at $\leq 325^{\circ}\text{F}$, the viscosity must be below 30 cP to properly atomize the fuel. The pumping and atomizing temperatures of the blends were found to depend on the type and amount of solid, and increased in the order LSRC < TSL SRC < HSRC. It was also determined that 30/70 and 40/60 wt % ratio blends of HSRC and middle oil possessed viscosity/temperature characteristics better than or similar to No. 6 Fuel Oil.

To evaluate the storage stability of SRC residual oils, single-phase blends of 50 wt % HSRC and TSL SRC in 1:1 mixtures of 1st- and 2nd-stage process solvents were subjected to 60-day storage stability tests at 150°F in nitrogen and air atmospheres (Tewari, 1982). A 30-oz wide-mouth glass bottle containing approximately 100 mL of the blend was capped after flushing with the desired gas, and was then stored in an isothermal oven with the same gas atmosphere. At specified intervals, each blend was removed from the storage bottle and mixed thoroughly. A 10-mL aliquot of representative sample was then extracted to measure viscosities at three temperatures specified to monitor blend deteriora-

tion with time. The increase in viscosity of the blends with storage time was greater with air storage than with nitrogen storage. In fact, the viscosity difference between unaged and 60-day air-aged blends suggested that the temperature increases required to bring an aged blend to original viscosity would be 15 and 10°F, respectively, for SRC and TSL SRC residual oils. Although the blends were stored in closed glass bottles, some loss of volatiles undoubtedly occurred during high-temperature storage. A major loss of lighter components was observed during each extraction and transfer procedure of the blend samples for viscosity measurements. Such losses contributed to an increase in the viscosity of a given blend. To quantify the weight loss during storage, about 16 g of freshly prepared SRC residual oil blend were stored at 150°F for 47 days in closed and open 1-oz glass vials. Both vials showed a significant weight loss during the first 10 days of storage. After 10 days, the loss of material in open vials increased rectilinearly with storage time, while in closed vials the loss became insignificant after 20 days.

The present report covers the work performed under Phase II of the program. The work included determining viscosity/temperature/composition relationships of various residual-oil blends composed of SRC-I 1st- and 2nd-stage solid and liquid products, and analytical characterization of components and selected blends. In addition, extended storage stability tests (i.e., 4-5 months) were conducted under controlled volatile loss conditions on simulated blends representing 1st- and 2nd-stage SRC-I Demonstration Plant total blended products (excluding naphtha and anode coke) and on No. 6 Fuel Oil.

RESULTS AND DISCUSSION

Sample Acquisition and Distillation

The 1st- and 2nd-stage SRC-I solid and liquid samples were acquired through ICRC from the Wilsonville (WV) Advanced Coal Liquefaction Facility. Solid samples included HSRC derived from Kerr-McGee's Critical Solvent Deashing process and TSL SRC solids produced after catalytic hydrocracking. The liquid samples received were WV run no. 235 1st- and 2nd-stage light oils with a final boiling point (FBP)

of 450°F and process solvents with an initial boiling point (IBP) of 450°F.

To obtain the 1st- and 2nd-stage middle (400-650°F) and heavy (650°F-FBP) oil fractions required for the program, the blends of light oil and process solvent were distilled in a 50-liter still with a 25-plate fractionating column. The weight percent blending ratios based on the material balance data of Wilsonville run 235, API gravities of the blends, and the percent recovery of each middle and heavy distillate cut are as follows:

<u>Blend composition (wt %)</u>	<u>1st-stage</u>	<u>2nd-stage</u>
Light oil (IBP-450°F)	57.3	34
Process solvent (650°F-FBP)	42.7	66
 <u>API gravity of the blend</u>	 19.5	 18.2
 <u>Distillate recovery (wt %)</u>		
Middle oil (400-650°F)	44.5	36.2
Heavy oil (650°F-FBP)	11.2	28.1

To provide information on the boiling point distribution of the distillate components, the standard ASTM D2887 simulated distillation method was applied to both the blends and their distillate cuts (Tables 1-6). An examination of these results shows that the 2nd-stage middle oil and 1st-stage heavy oil contained more heavy components and would therefore be more viscous than 1st-stage middle oil and 2nd-stage heavy oil, respectively.

Component Characterization

Table 7 shows that the 1st-stage products had lower H/C ratios, lower heating values, and higher heteroatom contents (N + O + S) than the corresponding products of the 2nd stage. Tables 8 and 9 show the relationship of temperature and viscosity for the 1st- and 2nd-stage middle and heavy oils. The liquids exhibited Newtonian behavior in the temperature range studied.

Preparation and Flow Characteristics of Single-Phase Solid/Liquid Blends

HSRC and TSL SRC solids were pulverized to a fineness of 100% through 140 mesh, approximately 105 μm . Single-phase blends were prepared in a three-necked, round-bottomed flask (500 mL) equipped with a thermometer and a glass stirrer. The requisite amount of pulverized solid was added to the preheated liquids with constant stirring. To assure complete dissolution and homogeneous mixing, the solid was added slowly over a 4-hr period at the required blending temperature (i.e., $200 \pm 5^\circ\text{F}$ and $150 \pm 5^\circ\text{F}$ for HSRC and TSL SRC, respectively), which was maintained for at least 12 hr.

The following blends of 50 wt % solid composition were added:

- HSRC/1st-stage middle oil
- HSRC/1st-stage heavy oil
- HSRC/2nd-stage middle oil
- HSRC/2nd-stage heavy oil
- TSL SRC/1st-stage middle oil
- TSL SRC/1st-stage heavy oil
- TSL SRC/2nd-stage middle oil
- TSL SRC/2nd-stage heavy oil

Tables 10-17 list the viscosities of the blends at specified temperatures and at various shear rates, as determined by a Brookfield viscometer. The range of applied shear rates varied with viscosity of the blend and the spindle used. Excepting HSRC blends in 2nd-stage liquids, each blend behaved like a Newtonian liquid, within experimental error.

Figures 1 and 2 summarize the relationship of viscosity and temperature for middle- and heavy-oil blends, respectively; the viscosity values were at the highest shear rate applied. The temperatures required for the blends to reach viscosities of 30 cP (atomizing) and 1,000 cP (pumping) were as follows:

<u>Solid composition (50/50 wt % blend)</u>	<u>Temperature (°F) at:</u>	
	<u>30 cP</u>	<u>1,000 cP</u>
HSRC/1st-stage middle oil	253	156
HSRC/1st-stage heavy oil	381	274
TSL SRC/1st-stage middle oil	198	104
TSL SRC/1st-stage heavy oil	329	227
TSL SRC/2nd-stage middle oil	207	111
TSL SRC/2nd-stage heavy oil	313	209

As predicted by the simulated distillation data, blends of TSL SRC in 2nd-stage middle oil and in 1st-stage heavy oil required higher atomizing and pumping temperatures to reach a given viscosity than did the corresponding blends of TSL SRC in 1st-stage middle oil and in 2nd-stage heavy oil.

Tables 16 and 17, which list the observed viscosities of HSRC mixtures in 2nd-stage middle and heavy oils, show that at a specified temperature, the viscosity of each mixture depended on the applied shear rate. The non-Newtonian behavior of these mixtures suggests that the blends were not single-phase, probably a result of the limited solubility of HSRC in 2nd-stage oils. A partial separation of the oil phase was also observed when the mixtures were allowed to cool to ambient temperature, which further substantiated the nonhomogeneous nature of these mixtures. A major portion of HSRC consists of preasphaltenes, operationally defined as pyridine solubles and benzene insolubles, which are mixtures of compounds rich in polar functional groups. Complete solubilization of HSRC of high polarity requires solvents of polarity equivalent to or greater than pyridine. Therefore, the low-heteroatom, second-stage oils cannot fully dissolve HSRC. On the other hand, TSL SRC having negligible preasphaltenes and a reduced heteroatom content dissolves in 2nd-stage oils. Table 7 shows that the total heteroatom content, hence the polarity, of 2nd-stage oils, is relatively lower than that of 1st-stage oils. Thus, increasing the polarity of 2nd-stage oil by adding a requisite amount of 1st-stage oil should solubilize HSRC. To determine the minimum concentration of 1st-stage oils required, various blends of the following solid/liquid compositions were evaluated:

<u>Blend component</u>	<u>Blend composition (wt %)</u>				
	<u>#1</u>	<u>#2</u>	<u>#3</u>	<u>#4</u>	<u>#5</u>
HSRC	40	40	40	40	50
1st-stage middle oil	10	-	-	-	-
1st-stage heavy oil	-	10	15	10	10
2nd-stage middle oil	50	50	45	-	-
2nd-stage heavy oil	-	-	-	50	40
Single phase:	No	No	No	Yes	Yes
Partial separation of oil phase at ambient temperature:	Yes	Yes	Yes	No	No

Viscosity/temperature data for the blends are summarized in Tables 18-22. The results indicate that adding 10 wt % 1st-stage heavy oil is sufficient to prepare a 50 wt % HSRC single-phase blend in 2nd-stage heavy oil. However, much higher concentrations of 1st-stage oils are needed to prepare single-phase HSRC blends in 2nd-stage middle oil.

Storage Stability Test

Following are the compositions of the residual fuel oils subjected to storage stability tests:

<u>Component</u>	<u>Fuel composition (wt %)</u>		
	<u>#1</u>	<u>#2</u>	<u>#3</u>
HSRC	50	-	-
1st-stage middle oil	40	30	-
1st-stage heavy oil	10	5	-
TSL SRC	-	50	-
2nd-stage middle oil	-	12	-
2nd-stage heavy oil	-	3	-
No. 6 Fuel Oil	-	-	100

The above HSRC and TSL SRC blend compositions simulate, respectively, the 1st- and 2nd-stage SRC-I Demonstration Plant total blended products

(excluding naphtha and anode coke). Table 23 shows that the H/C ratio and heating value increase in the order HSRC blend < TSL SRC blend < No. 6 Fuel Oil.

After 1 day, evaporation of volatile components to reach vapor/liquid equilibrium in the vapor space of the storage bottle raised the sample viscosity such that a 3°F higher temperature would be required to maintain the original viscosity. As shown in Figure 3 (Tables 24-27), the temperatures required for the residual oils to reach viscosities of 30 cP (atomizing) and 1,000 cP (pumping) are:

<u>Residual oil</u>	<u>Temperature (°F) at:</u>	
	<u>30 cP</u>	<u>1,000 cP</u>
HSRC blend (#1)	282	180
TSL SRC blend (#2)	217	121
No. 6 Fuel Oil (#3)	203	92

Density vs. temperature data for the residual oils are listed in Table 28. (Densities were determined using the pycnometric procedure.)

The residual oils were then subjected to a 4-5 month storage stability test at 150°F in controlled nitrogen and air atmospheres. Various 1-oz vials, each containing approximately 10 mL of the residual oil, were capped after flushing with the desired gas and then stored in a 150°F isothermal oven. The temperature and atmosphere of the oven were maintained by the slow circulation of the gas. At specified intervals, one vial of each residual oil was taken from the oven to measure viscosities at three temperatures to monitor fuel aging with time. Figures 4-6 (Tables 29-34) reveal that the viscosities of HSRC blends and No. 6 Fuel Oil stored in air increased to a greater extent than they did under nitrogen; however, the viscosity of TSL SRC was virtually unaffected by storage in air. Although the residual oils were stored in closed vials of the same size, some loss of volatiles undoubtedly occurred during high-temperature storage, and such losses contribute to an increase in the viscosity. However, since storage conditions, temperatures, and viscosity measurement procedures were the same, the loss of material and its impact upon viscosity should be considered constant for the same residual oil stored under air or nitrogen.

In air-stored HSRC residual oil, the most rapid increase in viscosity occurred during the 20-60-day storage period; after 60 days, viscosity increased less rapidly. Figure 7 shows that the temperature increases required to bring 140-day air- and nitrogen-aged HSRC residual-oil samples to the original pumping viscosity of 1,000 cP were 10 and 6°F, respectively. Figure 8 shows that the temperature increases required to bring 120-day air- and nitrogen-aged No. 6 Fuel Oil samples to the original pumping viscosity of 1,000 cP were 8 and 4°F, respectively. These results indicate that the storage stability of HSRC residual oils is comparable to that of No. 6 Fuel Oil, and that nitrogen blanketing during storage is important in maintaining the specified viscosity characteristics of the residual oils. An almost identical change in the viscosity of TSL SRC residual oil with storage time in nitrogen and air atmospheres suggests that such oils are relatively more stable than No. 6 Fuel Oil and HSRC residual oil, and that the viscosity increase during storage is mainly due to the loss of volatile components rather than to any associated aging effect.

CONCLUSIONS

- ° Excepting blends of HSRC and 2nd-stage liquids, SRC residual-oil blends have viscosity/temperature characteristics that permit their use as a No. 6 Fuel Oil substitute using conventional fuel handling equipment.

- ° The viscosity characteristics of SRC residual oils depend on solvent boiling range, the type and amount of solid dissolved in the blend, and the heteroatom content.

- ° Long-term storage under air in a closed system at 150°F has some adverse effect on the viscosity of No. 6 Fuel Oil and HSRC residual oils, but virtually no effect on TSL SRC residual oils.

- ° Under air and nitrogen blanketing, the temperature increases required to bring a 140-day stored HSRC blend to its original pumping viscosity are 10 and 6°F, respectively. Similarly, the temperature

increases required to bring No. 6 Fuel Oil samples stored 120 days under air and nitrogen to original pumping viscosity are 8 and 4°F, respectively. Thus, the long-term storage stability of HSRC residual oils is comparable to that of No. 6 Fuel Oil.

° Because of the low polarity of the solvent, HSRC cannot be solubilized completely to form single-phase blends with 2nd-stage middle and heavy oils. Complete solubilization requires the addition of a requisite amount of 1st-stage liquids.

REFERENCES

- Tewari, K. C. 1982. Rheology and stability of SRC residual fuel oils - storage evaluation. Pages 1-48 in SRC-I Quarterly Technical Report Supplement, October-December. DOE/OR/03054-11 (Suppl). International Coal Refining Co., Allentown, Pa.
- Tewari, K. C., P. J. Persico, and D. R. Lennon. 1982. Rheology and stability of SRC residual fuel oils. Pages 45-95 in SRC-I Quarterly Technical Report Supplement, April-June. DOE/OR/03054-8 (Suppl). International Coal Refining Co., Allentown, Pa.

Table 1
Boiling Point Distribution of 1st-Stage Blend by ASTM D2887

Vol % dist.	Temp. (°F)	Vol % dist.	Temp. (°F)
IBP	137	60	427
5	204	70	465
10	245	80	553
20	315	90	659
30	366	95	739
40	392	99	884
50	412	FBP	927

Table 2

Boiling Point Distribution of 1st-Stage Middle Oil by ASTM D2887

Vol % dist.	Temp. (°F)	Vol % dist.	Temp. (°F)
IBP	391	60	540
5	416	70	574
10	424	80	607
20	438	90	641
30	462	95	664
40	486	99	729
50	516	FBP	783

Table 3

Boiling Point Distribution of 1st-Stage Heavy Oil by ASTM D2887

Vol % dist.	Temp. (°F)	Vol % dist.	Temp. (°F)
IBP	660	60	781
5	682	70	806
10	692	80	841
20	710	90	899
30	726	95	952
40	743	99	1010
50	761	FBP	1027

Table 4
Boiling Point Distribution of 2nd-Stage Blend by ASTM D2887

Vol % dist.	Temp. (°F)	Vol % dist.	Temp. (°F)
IBP	171	60	629
5	212	70	682
10	243	80	738
20	319	90	807
30	401	95	865
40	500	99	958
50	571	FBP	989

Table 5
Boiling Point Distribution of 2nd-Stage Middle Oil by ASTM D2887

Vol % dist.	Temp. (°F)	Vol % dist.	Temp. (°F)
IBP	375	60	587
5	422	70	606
10	450	80	626
20	489	90	647
30	520	95	658
40	541	99	681
50	562	FBP	708

Table 6

Boiling Point Distribution of 2nd-Stage Heavy Oil by ASTM D2887

Vol % dist.	Temp. (°F)	Vol % dist.	Temp. (°F)
IBP	640	60	759
5	663	70	783
10	674	80	813
20	691	90	862
30	705	95	906
40	722	99	1010
50	739	FBP	1035

Table 7
Properties of Fuel Oil Blend Components

Component	1st stage			2nd stage		
	HSRC	Middle oil	Heavy oil	TSL SRC	Middle oil	Heavy oil
Ultimate analysis (wt %)						
C	85.86	86.24	86.89	89.95	88.89	89.46
H	6.03	8.98	7.81	6.98	10.28	9.11
N	1.78	0.60	1.25	1.34	0.39	0.85
O	5.15	3.93	3.28	1.56	0.44	0.61
S	1.08	0.25	0.77	0.17	0.00	0.03
Ash	0.10	--	--	--	--	--
H/C	0.843	1.249	1.079	0.931	1.388	1.223
Higher heating value (Btu/lb)	15,763	17,636	16,776	16,851	18,625	17,893

Table 8
Variation of Viscosity with Temperature
in 1st-Stage Middle and Heavy Oils

Oil	Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
Middle	70	79.20	9.6
		39.60	9.6
	80	79.20	7.2
		39.60	7.0
	90	79.60	4.8
		39.60	4.7
Heavy	100	2.04	8,288
		1.02	8,292
		0.51	8,300
	110	4.08	3,019
		2.04	3,021
		1.02	3,025
	120	10.20	1,343
		4.08	1,350
		2.04	1,350
	125	20.40	925
		10.20	935
		4.08	938
	135	20.40	500
		10.20	500
		4.08	500
	145	15.84	274
		7.92	273
		3.96	275
	155	39.60	163
		15.84	164
		7.92	164
	165	79.20	103
		39.60	104
		15.84	104
	180	79.20	57.9
		39.60	58.0
		15.84	57.9
	200	79.20	30.4
		39.60	30.5

Table 9
Variation of Viscosity with Temperature
in 2nd-Stage Middle and Heavy Oils

Oil	Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
Middle	70	79.20	10.6
		39.60	10.7
	80	79.20	7.7
		39.60	7.6
	90	79.20	5.9
		39.60	5.9
Heavy	74	1.98	2,915
		0.79	2,917
	80	3.96	1,715
		1.98	1,730
		0.79	1,738
	85	7.92	1,178
		3.96	1,180
		1.98	1,185
	90	7.92	829
		3.96	833
		1.98	835
	95	15.84	584
		7.92	591
		3.96	593
	100	15.84	441
		7.92	444
		3.96	443
	110	15.84	256
		7.92	258
		3.96	260
	120	39.60	152
		15.84	154
		7.92	155
	140	79.20	66.8
		39.60	66.8
		15.84	66.9
	165	79.20	29.9
		39.60	30.0
		15.84	30.0

Table 10
Variation of Viscosity with Temperature
in 50 wt % HSRC Blended with 1st-Stage Middle Oil

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
100	0.20	68,500
	0.10	69,000
115	1.02	16,600
	0.51	16,800
	0.20	17,000
130	4.00	5,125
	2.04	5,175
	1.02	5,200
145	10.20	1,938
	4.08	1,956
	2.04	1,963
160	20.40	859
	10.20	868
	4.08	869
175	15.84	382
	7.92	385
	3.96	388
190	39.60	200
	15.84	201
	7.92	204
215	79.20	82.1
	39.60	83.0
	15.84	83.1
240	79.20	41.5
	39.60	41.3
	15.84	41.9
265	79.20	22.6
	39.60	23.0

Table II
Variation of Viscosity with Temperature
in 50 wt % HSRC Blended with 1st-Stage Heavy Oil

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
220	0.84	31,350
	0.42	31,533
	0.17	31,750
230	1.68	14,950
	0.84	14,950
	0.42	15,000
240	3.36	7,450
	1.68	7,467
	0.84	7,467
250	1.98	3,700
	0.79	3,725
	0.40	3,750
270	7.92	1,201
	3.96	1,213
	1.98	1,220
290	15.84	463
	7.92	464
	3.96	468
310	39.60	209
	15.84	211
	7.92	214
335	79.20	95.0
	39.60	95.0
	15.84	96.3
360	79.20	48.4
	39.60	48.3
385	79.20	27.9
	39.60	28.3
415	79.20	16.1
	39.60	16.0

Table 12

Variation of Viscosity with Temperature
in 50 wt % TSL SRC Blended with 1st-Stage Middle Oil

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
75	2.04	6,738
	1.02	6,775
	0.51	6,900
85	4.08	3,300
	2.04	3,325
	1.02	3,350
95	10.20	1,683
	4.08	1,700
	2.04	1,725
105	20.40	931
	10.20	943
	4.08	956
120	15.84	423
	7.92	428
	3.96	433
135	39.60	212
	15.84	215
	7.92	219
155	79.20	99.1
	39.60	100
	15.84	102
180	79.20	47.6
	39.60	47.5
	15.84	48.8
200	79.20	28.8
	39.60	29.3
	15.84	30.6
225	79.20	17.4
	39.60	18.0

Table 13
Variation of Viscosity with Temperature
in 50 wt % TSL SRC Blended with 2nd-Stage Middle Oil

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
75	2.04	11,188
	1.02	11,300
	0.51	11,350
85	4.08	5,231
	2.04	5,300
	1.02	5,300
95	4.08	2,694
	2.04	2,700
	1.02	2,700
105	10.20	1,465
	4.08	1,469
	2.04	1,471
120	15.84	607
	7.92	615
	3.96	618
135	15.84	305
	7.92	306
	3.96	308
155	39.60	137
	15.84	137
	7.92	138
180	79.20	60.3
	39.60	60.8
	15.84	61.3
200	79.20	35.8
	39.60	35.8
225	79.20	20.6
	39.60	20.8

Table 14
Variation of Viscosity with Temperature
in 50 wt % TSL SRC Blended with 1st-Stage Heavy Oil

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
170	0.20	58,125
	0.10	58,500
185	1.02	15,825
	0.51	15,850
	0.20	15,875
200	4.08	5,200
	2.04	5,225
	1.02	5,225
215	10.20	1,980
	4.08	1,981
	2.04	1,988
230	20.40	861
	10.20	861
	4.08	863
245	15.84	408
	7.92	409
	3.96	410
260	39.60	221
	15.84	221
	7.92	221
275	39.60	129
	15.84	129
	7.92	129
295	79.20	69.0
	39.60	69.4
315	79.20	40.6
	39.60	40.6
340	79.20	23.4
	39.60	23.3
365	79.20	14.6
	39.60	14.5

Table 15
Variation of Viscosity with Temperature
in 50 wt% TSL SRC Blended with 2nd-Stage Heavy Oil

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
150	0.20	58,750
	0.10	56,750
170	2.04	11,100
	1.02	11,125
	0.51	11,150
190	4.08	2,994
	2.04	3,000
	1.02	3,000
210	20.40	973
	10.20	978
	4.08	975
220	20.40	601
	10.20	603
	4.08	606
240	39.60	247
	15.84	248
	7.92	250
265	79.20	106
	39.60	106
	15.84	105
290	79.20	52.5
	39.60	52.5
310	79.20	32.4
	39.60	32.3
330	79.20	17.9
	39.60	17.9

Table 16
Variation of Viscosity with Temperature
in 50 wt % HSRC Blended with 2nd-Stage Middle Oil^a

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
115	0.79	8,125
	0.40	12,100
130	1.98	2,170
	0.79	3,925
	0.40	6,242
145	7.92	788
	3.96	1,043
	1.98	1,257
160	15.84	372
	7.92	496
	3.96	719
175	39.60	228
	15.84	281
	7.92	405
250	79.20	67
	39.60	102
	15.84	216

^aPartial separation of oil phase at ambient temperature.

Table 17

Variation of Viscosity with Temperature
in 50 wt % HSRC Blended with 2nd-Stage Heavy Oil^a

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
240	0.20	9,738
	0.10	16,150
265	20.40	686
	10.20	1,217
	4.08	2,569
290	20.40	529
	10.20	1,018
	4.08	1,738
315	20.40	341
	10.20	425

^aPartial separation of oil phase at ambient temperature.

Table 18
Variation of Viscosity with Temperature
in Blend #1^a
(HSRC - 40 wt %, Middle Oil 1st-Stage - 10 wt %,
Middle Oil 2nd-Stage - 50 wt %)

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
70	10.20	1,482
	4.08	1,760
	2.04	2,132
80	20.40	961
	10.20	1,038
	4.08	1,233
90	20.40	746
	10.20	814
	4.08	960
110	20.40	470
	10.20	513
	4.08	616
130	20.40	310
	10.20	341
150	79.20	107
	39.60	112
	15.84	129
180	79.20	72.1
	39.60	75.4
225	79.20	32.5
	39.60	38.2

^aPartial separation of oil phase at ambient temperature.

Table 19
Variation of Viscosity with Temperature
in Blend #2^a.
(HSRC - 40 wt %, Heavy Oil 1st-Stage - 10 wt %,
Middle Oil 2nd-Stage - 50 wt %)

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
105	10.20	1,465
	4.08	1,894
	2.04	2,663
120	20.40	850
	10.20	935
	4.08	1,275
150	20.40	316
	10.20	343

^aPartial separation of oil phase at ambient temperature.

Table 20
 Variation of Viscosity with Temperature
 in Blend #3^a
 (HSRC - 40 wt %, Heavy Oil 1st-Stage - 15 wt %,
 Middle Oil 2nd-Stage - 45 wt %)

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
120	10.20	2,155
	4.08	2,775
	2.04	3,738
150	20.40	843
	10.20	898
	4.08	1,181
180	20.40	329
	10.20	345

^aPartial separation of oil phase at ambient temperature.

Table 21
Variation of Viscosity with Temperature
in Blend #4
(HSRC - 40 wt %, Heavy Oil 1st-Stage - 10 wt %,
Heavy Oil 2nd-Stage - 50 wt %)

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
180	0.20	54,750
	0.10	54,750
200	2.04	7,350
	1.02	7,350
	0.51	7,400
220	10.20	1,755
	4.08	1,763
	2.04	1,775
230	20.40	1,055
	10.20	1,066
	4.08	1,069
240	20.40	628
	10.20	628
	4.08	631
260	39.60	238
	15.84	239
	7.92	240
280	79.20	110
	39.60	110
	15.84	113
305	79.20	50.9
	39.60	51.0
330	79.20	27.4
	39.60	28.0

Table 22
Variation of Viscosity with Temperature
in Blend #5
(HSRC - 50 wt %, Heavy Oil 1st-Stage - 10 wt %,
Heavy Oil 2nd-Stage - 40 wt %)

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
220	0.20	52,500
	0.10	53,250
240	2.04	9,188
	1.02	9,175
	0.51	9,200
255	4.08	3,100
	2.04	3,125
	1.02	3,125
265	10.20	1,685
	4.08	1,688
	2.04	1,688
275	20.40	980
	10.20	983
	4.08	988
295	20.40	379
	10.20	380
315	39.60	165
	15.84	167
	7.92	168
335	79.20	87.5
	39.60	87.5
360	79.20	45.1
	39.60	45.2
390	79.20	23.4
	39.60	23.4

Table 23
Properties of Residual Fuel Oils Used for Stability Tests

	HSRC blend #1	TSL SRC blend #2	No. 6 Fuel Oil #3
Ultimate analysis (wt %)			
C	85.60	88.40	86.34
H	7.23	8.13	11.48
N	1.24	1.01	0.27
O	4.81	2.23	0.87
S	1.04	0.23	0.99
Ash	0.08	-	0.05
H/C	1.014	1.104	1.596
Higher heating value (Btu/lb)	16,849	17,343	18,749

Table 24
Variation of Viscosity with Temperature
in HSRC Blend (#1)^a

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
160	4.08	3,375
	2.04	3,375
	1.02	3,375
170	10.20	1,700
	4.08	1,719
	2.04	1,721
175	10.20	1,265
	4.08	1,275
	2.04	1,275
180	20.40	976
	10.20	980
	4.08	988
190	20.40	600
	10.20	605
	4.08	600
200	15.84	381
	7.92	383
	3.96	383
210	39.60	246
	15.84	253
	7.92	253
225	39.60	140
	15.84	144
	7.92	148
240	79.20	85.8
	39.60	85.8
	15.84	86.3
260	79.20	49.1
	39.60	50.0
275	79.20	34.6
	39.60	35.0
280	79.20	31.5
	39.60	32.0

^a Sample was extracted immediately after the blend was prepared at 200°F. Before viscosity measurements, the sample was allowed to cool at room temperature for 1 hr.

Table 25
Variation of Viscosity with Temperature
in HSRC Blend (#1) After 1-day Storage at 150°F

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
150	2.04	7,613
	1.02	7,750
	0.51	7,800
160	4.08	3,856
	2.04	3,875
	1.02	3,875
170	10.20	2,040
	4.08	2,043
	2.04	2,050
175	10.20	1,545
	4.08	1,550
	2.04	1,550
180	20.40	1,183
	10.20	1,188
	4.08	1,188
190	20.40	711
	10.20	715
	4.08	719
200	15.84	423
	7.92	423
	3.96	423
225	39.60	160
	15.84	161
	7.92	159
240	79.20	95.6
	39.60	95.8
	15.84	96.3
260	79.20	54.4
	39.60	54.8
	15.84	55.6
280	79.20	34.3
	39.60	34.3
290	79.20	26.9
	39.60	26.1

Table 26
Variation of Viscosity with Temperature
in TSL SRC Blend (#2)^a

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
75	1.02	24,650
	0.51	25,000
	0.20	25,000
90	2.04	7,400
	1.02	7,425
	0.51	7,450
100	4.08	3,519
	2.04	3,525
	1.02	3,550
115	10.20	1,400
	4.08	1,425
	2.04	1,425
120	20.40	1,041
	10.20	1,050
	4.08	1,056
145	20.40	313
	10.20	313
	4.08	319
160	39.60	160
	15.84	162
	7.92	163
175	79.20	92.9
	39.60	93.3
	15.84	93.8
195	79.20	51.3
	39.60	51.3
	15.84	51.9
215	79.20	30.8
	39.60	30.8
235	79.20	20.3
	39.60	20.3

^aBlend was prepared at 150°F. Sample was cooled at room temperature for 1 hr before viscosity measurements.

Table 27
Variation of Viscosity with Temperature
in No. 6 Fuel Oil (#3)

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP)
72	0.79	6,038
	0.40	6,100
75	3.96	4,225
	0.79	4,313
	0.40	4,375
80	3.96	2,178
	0.79	2,210
	0.40	2,288
85	3.96	1,528
	0.79	1,530
	0.40	1,563
90	7.92	1,084
	3.96	1,105
	0.79	1,120
100	7.92	641
	3.96	643
	0.79	645
110	15.84	394
	7.92	398
	3.96	398
120	15.84	259
	7.92	260
	3.96	263
130	39.60	182
	15.84	185
	7.92	189
145	79.20	113
	39.60	114
	15.84	115
165	79.20	66.3
	39.60	66.5
	15.84	67.5
185	79.20	42.3
	39.60	42.5
200	79.20	31.3
	39.60	31.5
215	79.20	23.8
	39.60	24.3
235	79.20	17.9
	39.60	18.0

Table 28
Residual-Oil Density as a Function of Temperature

Residual oil	Temperature (°F)	Density (g/mL)
HSRC blend (#1)	155	1.1130
	170	1.1050
	190	1.0950
	250	1.0700
	262	1.0660
TSL SRC blend (#2)	82	1.0739
	100	1.0685
	130	1.0576
	164	1.0449
	215	1.0264
	244	1.0152
No. 6 Fuel Oil (#3)	90	0.9414
	110	0.9341
	135	0.9256
	175	0.9091
	200	0.9001

Table 29

Aging Characteristics of HSRC Blend (#1) Stored at 150°F in Air Atmosphere

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP) after storage time (days)											
		0	1	5	11	20	25	36	56	62	76	96	131
180	20.40	976	1,183	-	-	-	-	-	-	-	-	-	-
	10.20	980	1,188	-	-	-	-	1,460	1,868	1,923	-	-	2,190
	7.92	-	-	1,181	-	-	-	-	-	-	-	-	-
	4.08	988	1,188	-	-	-	-	1,485	1,888	1,950	-	-	2,213
	3.96	-	-	1,183	1,230	1,295	1,375	-	-	-	1,905	2,018	-
	2.04	-	-	-	-	-	-	1,495	1,883	1,975	-	-	2,213
	1.98	-	-	1,183	1,290	1,305	1,375	-	-	-	1,905	2,015	-
	0.79	-	-	-	1,300	1,313	1,375	-	-	-	1,913	2,025	-
200	15.84	381	423	424	464	468	485	-	-	-	-	-	-
	7.92	383	423	424	468	471	486	520	641	675	654	700	755
	3.96	383	423	425	473	473	486	520	645	678	660	700	760
	1.98	-	-	-	-	-	-	527	660	680	660	705	760
290	79.20	-	26.9	26.1	27.9	27.7	30.2	31.7	33.0	34.2	33.7	34.7	36.0
	39.60	-	26.1	25.8	27.8	27.7	30.5	31.7	33.0	34.7	33.7	34.7	36.0

Table 30
Aging Characteristics of HSRC Blend (#1) Stored at 150°F in Nitrogen Atmosphere

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP) after storage time (days)											
		1	5	11	20	25	36	56	62	77	96	126	144
180	20.40	1,183	-	-	-	-	1,146	-	-	-	-	-	-
	10.20	1,188	-	-	-	-	1,160	1,245	1,273	-	-	1,530	1,545
	7.92	-	1,181	1,178	1,175	-	-	-	-	-	-	-	-
	4.08	1,188	-	-	-	-	1,165	1,263	1,288	-	-	1,531	1,563
	3.96	-	1,183	1,183	1,177	1,240	-	-	-	1,250	1,473	-	-
	2.04	-	-	-	-	-	-	1,263	1,300	-	-	1,538	1,575
	1.98	-	1,183	1,185	1,182	1,240	-	-	-	1,260	1,475	-	-
	0.79	-	-	-	-	1,250	-	-	-	1,263	1,488	-	-
200	15.84	423	424	424	426	437	428	457	464	462	538	549	555
	7.92	423	425	424	428	439	428	465	469	465	540	555	558
	3.96	423	425	428	428	440	428	468	473	470	540	558	558
290	79.20	25.9	26.1	26.1	26.2	27.0	27.0	27.2	27.7	27.6	28.0	30.0	31.0
	39.60	25.9	26.0	26.3	26.2	27.0	27.8	27.2	28.2	27.8	28.0	30.0	32.0

Table 31

Aging Characteristics of TSL SRC Blend (#2) Stored at 150°F in Air Atmosphere

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP) after storage time (days)							
		0	5	12	24	48	63	87	112
120	20.40	1,041	-	-	-	1,090	1,095	1,214	1,229
	10.20	1,050	-	-	1,150	1,100	1,110	1,220	1,238
	7.92	-	1,041	1,110	-	-	-	-	-
	4.08	1,056	-	-	1,156	1,100	1,125	1,219	1,250
	3.96	-	1,045	1,118	-	-	-	-	-
	2.04	-	-	-	1,150	-	-	-	-
	1.98	-	1,050	1,130	-	-	-	-	-
175	79.20	92.9	92.5	101	102	101	101	109	109
	39.60	93.3	92.5	102	103	101	101	109	110
	15.84	93.8	93.8	103	105	102	101	109	111
215	79.20	30.8	30.8	33.4	34.3	33.6	33.5	35.0	35.0
	39.60	30.8	30.8	33.3	34.5	34.3	33.3	35.0	35.0

Table 32

Aging Characteristics of TSL SRC Blend (#2) Stored at 150°F in Nitrogen Atmosphere

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP) after storage time (days)								
		0	5	12	24	48	68	87	112	130
120	20.40	1,041	-	-	-	1,126	1,041	1,169	1,169	-
	10.20	1,050	-	-	-	1,135	1,045	1,178	1,178	1,308
	7.92	-	1,041	1,051	1,164	-	-	-	-	-
	4.08	1,056	-	-	-	1,131	1,046	1,181	1,181	1,319
	3.96	-	1,045	1,063	1,173	-	-	-	-	-
	1.98	-	1,050	1,075	1,170	-	-	-	-	-
175	79.20	92.9	92.5	96.6	98.0	101	98.0	105	105	108
	39.60	93.3	92.5	97.8	99.0	102	99.0	105	105	110
	15.84	93.8	93.8	97.5	100.0	103	99.0	105	105	111
215	79.20	30.8	30.8	31.6	34.5	33.8	32.3	34.1	34.1	35.4
	39.60	30.8	30.8	31.8	35.0	34.5	32.3	34.3	34.3	35.3

Table 33

Aging Characteristics of No. 6 Fuel Oil (#3) Stored at 150°F in Air Atmosphere

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP) after storage time (days)								
		0	5	14	24	34	51	71	104	121
90	10.20	-	-	-	-	1,455	1,531	-	1,883	1,935
	7.92	1,084	1,091	-	-	-	-	-	-	-
	4.08	-	-	-	-	1,469	1,533	-	1,925	1,975
	3.96	1,105	1,113	1,338	1,430	-	-	1,536	-	-
	2.04	-	-	-	-	1,475	-	-	1,938	1,988
	1.98	-	1,115	1,345	1,435	-	-	1,536	-	-
	0.79	1,120	-	1,375	1,438	-	-	-	-	-
145	79.20	113	113	119	-	-	132	-	-	-
	39.60	114	115	121	121	125	133	132	148	151
	15.84	115	117	122	122	126	135	133	148	154
	7.92	-	-	-	122	126	-	135	149	155
200	79.20	31.3	31.5	33.1	36.5	34.9	36.1	35.8	39.4	40.0
	39.60	31.5	31.8	33.3	36.5	35.0	36.3	35.8	39.3	40.1

Table 34

Aging Characteristics of No. 6 Fuel Oil (#3) Stored at 150°F in Nitrogen Atmosphere

Temperature (°F)	Shear rate (sec ⁻¹)	Viscosity (cP) after storage time (days)								
		0	5	14	24	34	51	71	104	121
90	10.20	-	-	-	-	1,298	1,298	-	1,583	1,605
	7.92	1,084	1,091	1,185	1,231	-	-	-	-	-
	4.08	-	-	-	-	1,325	-	-	1,619	1,631
	3.96	1,105	1,113	1,203	1,253	-	-	1,298	-	-
	2.04	-	-	-	-	1,325	-	-	1,613	1,650
	1.98	-	1,115	1,215	1,275	-	-	1,325	-	-
	0.79	1,120	-	-	-	-	-	1,325	-	-
145	79.20	113	113	115	116	116	115	114	124	-
	39.60	114	115	117	116	118	-	115	125	133
	15.84	115	117	119	116	122	-	115	125	136
	7.92	-	-	-	-	-	-	-	-	140
200	79.20	31.3	31.5	31.8	32.6	33.0	33.8	33.0	34.4	36.9
	39.60	31.5	31.8	32.0	32.6	33.0	-	33.0	34.5	37.0

Figure 1
Viscosity as a Function of Temperature
in Middle-Oil Blends

Figure 2
Viscosity as a Function of Temperature
in Heavy-Oil Blends

Figure 3
Viscosity of Residual Oils as a Function of Temperature

Figure 4
Viscosity Change in HSRC Blend Stored at 150°F

Figure 5
Viscosity Change in TSL SRC Blend Stored at 150°F

Figure 6
Viscosity Change in No. 6 Fuel Oil Stored at 150°F

Figure 7
Viscosity/Temperature Comparison of
Aged and Unaged HSRC Blend

Figure 8
Viscosity/Temperature Comparison of Aged and
Unaged No. 6 Fuel Oil

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

EFFECT OF ASPHALTENE-RICH SOLVENT ON COAL LIQUEFACTION

D. Kang* and E. N. Givens*

Program 12.1.12 was initiated to develop more accurate data on light SRC (LSRC) recycle in the SRC-I Process. In the first task of this program, Kentucky #9 Mulford coal was reacted with an asphaltene-rich solvent containing 30 wt % Kerr-McGee LSRC. The results showed that use of an asphaltene-rich solvent dramatically affected the coal liquefaction yield structure. Residence times of 40 minutes or more and temperatures of 800°F or lower yielded significant increases in oil yield with less hydrogen consumption per unit oil yield. However, at higher temperatures commonly used for conventional recycle solvent (i.e., ~840°F), severe retrograde reactions caused a significant decrease in conversion. Data comparison also revealed higher hydrocarbon gas yields with asphaltene-rich solvent at higher temperatures.

INTRODUCTION

Previous studies have revealed that solvent make (i.e., oil yield) in direct coal liquefaction is enhanced by the addition of heavy solvent-refined coal (HSRC) to the feed slurry. Under ICRC's program 12.1.4, "Impact of SRC Recycle on Commercial Design," statistically significant data on solvent make with LSRC recycle could not be developed. Under a subsequent program, 12.1.12, a computer simulation study on recycling asphaltene- and preasphaltene-rich products was performed using past data in a sequential reaction kinetic model. This study showed that dissolver performance over a range of operating conditions could not be predicted from the model because of a lack of sufficient data. Program 12.1.12 was therefore modified to include three tasks; the first task comprises a series of coal liquefaction runs

*International Coal Refining Co. (ICRC).

using asphaltene-rich solvent or straight-run solvent. The results of this task to date are discussed in this report.

METHODS

Feed Materials

Coal. Kentucky #9 Mulford is a high volatile C bituminous coal that meets SRC-I Demonstration Plant feed coal specifications. Proximate and ultimate analyses of this coal are provided in Table 1.

Process Solvent. The asphaltene-rich process solvent containing 30 wt % light SRC comprised 85.6% pentane-soluble oil, 12.6% asphaltenes, and 1.8% preasphaltenes, as determined by sequential solvent fractionation in the order of pentane, benzene, and pyridine, respectively. Table 2 illustrates the variability in solvent fractionation data determined for the asphaltene-rich solvent and its composites.

Addition of 30 wt % LSRC to the straight recycle solvent resulted in a 10.5 wt % decrease in oils and 8.8 and 1.8 wt % increases in asphaltenes and preasphaltenes, respectively.

Figure 1 depicts viscosity/temperature data for solvent containing 30% LSRC. Viscosities of recycle solvents at room temperature ranged between 4-10 cP. The addition of 30% LSRC caused a two-to-three-order-of-magnitude increase in viscosity, which required about 250°F to maintain fluidity equivalent to typical recycle solvent at room temperature.

Process Runs

Kentucky #9 Mulford coal was processed through continuous stirred tank reactors (one or two reactors in series) with an asphaltene-rich process solvent. As at Wilsonville, considerable care was exercised to properly prepare the individual batches. The coal was taken from a uniform supply, and the Wilsonville asphaltene-rich material was processed through a riffler before use.

The asphaltene-rich solvent was prepared by dissolving 30 wt % Kerr-McGee LSRC from Wilsonville run 203 in heated Ft. Lewis recycle solvent produced in the SRC-I mode. Coal was then added to the solvent and the resulting slurry was injected into the feed recycle loop for

ultimate feeding into the process reactors. The tests required that the composition of the coal and the asphaltene-rich material be constant during each single-pass recycle run.

Process conditions maintained during these runs are provided in Table 3. Temperature and residence time were the independent process variables that were varied to determine the effect of asphaltene-rich solvent addition on the liquefaction process.

The products from these runs were analyzed for coal conversion, hydrogen consumption, gas and water make, oil, asphaltene and preasphaltene yield, insoluble organic material.

RESULTS AND DISCUSSION

Table 4 provides yield data of Kentucky #9 coal reacted with asphaltene-rich solvent or with straight solvent.

Figure 2 shows that for a given temperature and solvent, oil yield increased with residence time. However, the rates of increase in oil yields with increasing residence time varied depending on process temperature and solvent. In addition, the relative performance of asphaltene-rich solvent and straight solvent depended on the process conditions. For example, at 20 minutes residence time and 800°F, oil yield with asphaltene-rich solvent was 6% lower than oil yield with straight solvent; however, at 60 minutes and 800°F, oil yield with asphaltene-rich solvent was 7% higher than that with straight solvent. Although the asphaltene-rich solvent produced more oil at 800°F and residence times of 40 minutes or more, it produced less oil at 840°F and residence times of 40 minutes or less compared with the straight-solvent yields.

The effect of process temperature is more clearly depicted in Figure 3, for which data were obtained at 60 minutes residence time. Oil yields with asphaltene-rich and straight solvents increased as temperature increased from 760 to 800°F and from 780 to 810°F, respectively. However, further increases in temperature to 840°F resulted in decreases in oil yield, especially with the asphaltene-rich solvent. Optimum temperatures apparently lie between 800 and 810°F.

Figure 4 shows the effects of solvent type on coal conversion at various temperatures and residence times. At 800°F, the level of unconverted coal with asphaltene-rich solvent was similar to that with straight solvent. However, at 840°F, the level of unconverted coal increased dramatically with asphaltene-rich solvent; this increase reflects the occurrence of severe retrograde reactions and is in marked contrast to the marginal increase resulting with straight solvent. The increase in temperature from 800 to 840°F resulted in an approximate 10% loss in coal conversion with asphaltene-rich solvent over the range of residence times examined.

As shown in Figure 5, preasphaltene yields with asphaltene-rich solvent decreased rapidly as residence time increased from 20 to 80 minutes and from 20 to 60 minutes. Figure 6 shows that asphaltene yield decreased at much slower rates than preasphaltene yield at 840°F as residence time increased from 20 to 60 minutes. However, at 800°F, asphaltene yield increased between 20 and 40 minutes, but then decreased between 40 and 80 minutes.

Hydrogen consumption for both solvents is depicted in Figure 7. The results clearly show that asphaltene-rich solvent significantly increases hydrogen consumption, especially at higher temperatures and longer residence times. However, when the ratios of oil yield to hydrogen consumed were plotted vs. oil yield (Figure 8), the data indicate that the selectivity of hydrogen use was not adversely affected; on this basis, the performance of asphaltene-rich solvent at 800°F was comparable to or better than that of straight solvent, but poorer at 840°F, as indicated by both the higher oil-to-hydrogen ratios and the higher oil yields.

A selectivity index of hydrogen consumption was then defined as the geometric mean of oil yield/hydrogen and oil yield, i.e., $(\% \text{ oil yield} / \% \text{ hydrogen consumption} \times \% \text{ oil yield})^{1/2}$ and plotted in Figure 9. Again, the hydrogen consumption selectivity index for oil yields was shown to be greater with asphaltene-rich solvent at 800°F than with straight solvent, except at a 20-minute residence time. At 840°F, the trends were reversed.

Figure 10 reveals that asphaltene-rich solvent increased hydrocarbon gas yields at 840°F within a residence time range of 20 to 60 minutes. At lower reaction temperatures of 800-810°F, hydrocarbon gas yields were not affected by the type of solvent used.

Figure 11 shows that sulfur content in SRC is a complex function of temperature, time, and asphaltene material addition, but it is mainly affected by process temperature and residence time. Generally, sulfur content in SRC decreased as temperature and residence time increased. Sulfur content in SRC generated from asphaltene-rich solvent tended to be lower than that in SRC generated from straight distillate. However, a fair comparison of sulfur content between the two process options can be made only if sulfur data generated from optimum conditions become available. If it is assumed that 800°F and 60 minutes are close to the optimized conditions maximizing oil yield with asphaltene-rich solvent (indicated in Figure 3), the data suggest that sulfur content under such conditions would be similar to that in SRC generated from straight solvent at 840°F and 40 minutes, which are typical demonstration plant conditions.

CONCLUSIONS

A comparison of coal liquefaction results using conventional straight solvent and asphaltene-rich light SRC solvent revealed that LSRC:

- ° increased oil yields at favorable reaction conditions, i.e., at lower temperatures and longer residence times,
- ° induced severe retrograde reactions at higher temperatures, resulting in a significant loss in conversion,
- ° increased hydrogen consumption selectivity index [oil yield/ $(H_2 \text{ consumption})^{1/2}$] at favorable conditions, and
- ° increased light gaseous products at a higher reaction temperature.

Table 1

Proximate and Ultimate Analysis of a
Representative Kentucky #9 Mulford Coal

<u>Proximate analysis (wt %)</u>		
Moisture	2.10	
Volatile matter	36.91	
Fixed carbon	61.38	
Ash	9.61	
 <u>Ultimate analysis (wt %)</u>		
	<u>Moisture-free basis</u>	<u>Moisture- and ash-free basis</u>
Carbon	73.40	80.96
Hydrogen	4.89	5.39
Oxygen	8.80	9.71
Nitrogen	1.68	1.85
Sulfur	3.14	2.08
Organic	1.89	2.08
Pyritic	1.25	
Ash	9.82	

Table 2

Solvent Fractionation Data for Feed Solvent Materials

	<u>Straight solvent</u>			<u>LSRC</u>	<u>Asphaltene-rich solvent</u>	
	<u>(Gulf PLM #1967)</u>			<u>(FSSRC 29)</u>	<u>(30% LSRC/70% solvent)</u>	
	(wt %)			(wt %)	Measured	Calculated
					(wt %)	
Oils	96.14,	96.30,	96.09	59.76	86.18, 85.33, 85.39	85.19
Asphaltenes	3.86,	3.70,	3.91	37.45	12.35, 12.84, 12.60	13.97
Preasphaltenes	--	--	--	2.79	1.47, 1.83, 2.01	0.84

Table 3

Operating Conditions of Run Conducted with Asphaltene-Rich Material

Coal concentration (wt %)	Asphaltene-rich material concentration in solvent (wt %)	H ₂ feed rate (M scf/ton)	H ₂ pressure (psig)	Residence time (min)	Temperature (°F)
40	30	30	2,000	60	760
40	30	30	2,000	20, 40, 60, 80	800
40	30	30	2,000	20, 40, 60	840

Table 4
Summary of Yield Distribution Data
for Kentucky #9 Mulford Coal

Sample no.	59-8	59-26	59-52	59-71	59-21	59-37	59-44	59-59	55-28	55-75	55-118	55-42	55-41	55-55	55-107
Temperature (°F)	800	800	800	800	840	840	840	760	810	810	810	840	840	840	780
Residence time (min)	20	20 + 20 ^a	30 + 30	40 + 40	20	20 + 20	30 + 30	30 + 30	20	40	30 + 30	20	20 + 20	30 + 30	30 + 30
% SRC in solvent	30	30	30	30	30	30	30	30	0	0	0	0	0	0	0
Conversion (% MAF coal)	87.0	91.3	91.4	93.6	78.2	80.1	81.9	92.0	88.4	89.6	91.8	88.0	89.5	88.2	91.5
H ₂ consumption	1.4	2.1	2.9	3.1	2.0	3.4	4.1	2.0	1.5	2.0	2.4	1.5	2.6	3.1	2.1
Gas	0.9	1.5	2.3	2.6	1.1	2.4	3.0	1.6	1.2	1.8	2.2	1.1	2.0	2.6	2.1
Solvent	0.5	0.7	0.6	0.5	0.9	1.0	1.1	0.3	0.3	0.3	0.3	0.4	0.6	0.6	0.1
C ₁ - C ₄	4.9	8.5	9.1	10.2	10.3	16.2	19.1	3.2	4.4	7.2	9.3	6.3	12.3	14.9	4.9
CO + CO ₂	1.4	1.9	1.7	1.6	1.8	2.3	2.2	1.4	1.5	1.8	2.0	1.6	1.7	2.2	0.5
H ₂ S + NH ₃	1.2	1.7	1.7	1.5	1.5	2.1	2.0	1.3	1.6	2.0	2.3	1.4	2.8	2.7	1.0
H ₂ O	2.9	3.1	5.0	4.7	4.5	5.0	5.9	3.8	3.2	3.6	3.0	2.2	4.0	4.9	4.4
Oil	12.3	23.9	33.7	39.1	12.5	16.8	25.4	28.5	17.9	20.0	26.9	15.5	20.2	22.6	25.0
SRC	64.2	54.7	42.7	39.7	49.3	39.0	29.5	55.8	58.4	53.1	48.9	60.3	49.0	40.9	54.5
Asphaltene	16.2	21.0	19.1	18.2	18.8	11.8	8.7	27.1	31.0	29.1	25.3	31.0	24.6	23.0	31.2
Preasphaltene	48.0	33.7	23.5	21.5	30.5	27.2	20.8	28.7	27.4	24.0	23.7	29.2	24.4	18.0	23.3
Unconverted coal	14.5	11.2	11.5	9.6	23.9	23.4	22.6	10.0	12.9	12.1	10.1	13.2	12.5	14.6	10.1
S in SRC (wt %)	0.9	0.7	0.7	0.5	0.7	0.6	0.5	0.8	0.9	0.8	0.7	0.8	0.6	0.5	0.9
Solvent H (wt %)															
in	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	8.2	8.2	8.2	8.2	8.2	8.2	8.2
out	7.4	7.4	7.4	7.4	7.2	7.1	7.1	7.6	8.1	8.1	8.1	8.0	7.9	7.9	8.2

^aAddition of two numbers indicates two reactors in series.

Figure 1
Viscosity (cP) of Asphaltene-Rich Solvent vs. Temperature

Figure 2
Oil Yield vs. Residence Time and Temperature

Figure 3
Oil Yield vs. Temperature

- KY #9 MULFORD COAL/30% LSRC/70% FT. LEWIS SOLVENT
○ STRAIGHT DISTILLATE
RESIDENCE TIME = 60 MINUTES

Figure 4
Unconverted Coal vs. Residence Time and Temperature

Figure 5
Preasphaltene Yields vs. Residence Time

Figure 6
Asphaltene Yields vs. Residence Time

Figure 7
Hydrogen Consumption vs. Residence Time and Temperature

Figure 8
Wt % Oil Yield per Wt % Hydrogen Consumed vs. Wt % Oil Yield

Figure 9
Hydrogen Consumption Selectivity to Oil Yield vs. Time and Temperature

Figure 10
Hydrocarbon Gas Yields vs. Residence Time

Figure 11
Sulfur Content in SRC vs. Residence Time