DOE/ER/54169--1

DE93 008046

Annual Performance Report
Grant No. DE-FG02-92ER54169

**"Thomson Scattering Diagnostic Analyses to Determine
the Energetic Particle Distributions in TFTR"**

R. E. Aarnodt (P.I.), Peter Cheung, and D. A. Russell

12 February 1993

RECEIVED
FEB 22 1993
OSTI

LODESTAR RESEARCH CORPORATION
2400 Central Avenue
Boulder, Colorado 80301

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *SR*

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

Annual Performance Report
Grant No. DE-FG02-92ER54169
**"Thomson Scattering Diagnostic Analyses to Determine
the Energetic Particle Distributions in TFTR"**

R. E. Aamodt (P.I.), Peter Cheung, and D. A. Russell
Lodestar Research Corporation

Abstract

The research completed and in progress for the first period of this grant is reviewed. Specific scattering scenarios for TFTR and JET and ITER were studied. The Lodestar scattering code, SKATR, was upgraded to include anisotropic energetic ion distributions and an analytic diffraction formulation was completed. Research continues on JET studies and upgrading the code for JET and ITER relevant conditions.

I. Executive Summary of Progress

During the initial six-month period of this grant the major part of our effort was spent helping define and resolve technical issues brought up as a result of the evolving politics at the PPPL laboratory concerning the status of the gyrotron scattering experiment on TFTR. These "optimization" exercises used the unique characteristics of Lodestar's "SKATR" scattering code which includes the important electromagnetic effects necessary to describe scattering enhancement using the lower hybrid resonance. In addition, SKATR was upgraded to use anisotropic bi-Maxwellian energetic ion distributions to model anisotropic ICH particles expected in TFTR and JET, and our ray tracing code was refined. The analytic formalism for calculating diffraction corrections to the standard ray calculations was also completed and simple equilibrium models examined. Our scattering codes and signal-to-noise analyses were also applied to TEXT and DIII-D to evaluate the role that a 60 GHz experiment (60 GHz scattering receiver is available) could play in each device. Each facility showed promise for learning about the energetic ion distributions but there were some compromises involved for each machine relative to the scattering experiments proposed for TFTR and JET. We also assessed gyrotron use for ITER, using both the 4.8 T and 6 T field machine concluding that "off the shelf" (by year 2000) gyrotron tubes could easily be the drivers of an excellent alpha particle detection system (subject to port access) and had many advantages over high frequency, 150 μ and 10 μ , sources.

For the remaining part of this contracting period work will center on predictions for JET and upgrading SKATR and the ray tracing codes to be more applicable to JET and ITER.

In the following section of this report we detail the specifics of our findings to date.

II. Detailed Technical Progress Report

Quantitative analysis was made regarding the performance and physics issues of the TFTR gyrotron scattering system. Several critical issues were carefully analyzed and studied:

A. The presence of scattering resonances, such as the lower hybrid resonance, were carefully studied using our fully electromagnetic scattering code, SKATR. For the specific situation of X $\rightarrow$ X scattering with the incidence gyrotron frequency less than the cyclotron frequency, the scattering conditions and geometry under which such resonances are impor-

tant were documented. The electromagnetic correction to the lower hybrid resonance frequency, as calculated by our code, is observed to be significant under typical TFTR operating conditions at near perpendicular scattering (ie., for scattering angles with respect to the magnetic field of 83° or more). The spectral characteristics of the resonance peak is also studied. In particular, strong dependence on input electron and ion temperatures were observed. The understanding of the variability of the lower hybrid resonance peak, when present, and the accumulation of a data base of such spectra enhances our capability of extracting useful information of alpha particle distributions from actual experimental data.

B. Extensive signal to noise calculations for both near perpendicular and off perpendicular scattering were performed using realistic and up-to-date TFTR operating parameters. Such calculations were made in the following procedure: i) scattering spectra were first generated using SKATR for a given set of operating parameters and scattering geometry; ii) plasma dielectric factors were then calculated from cold plasma dispersion relations; iii) experimental constraints such as incidence power, antenna characteristics, post-processing gain factors, etc., were then calculated; iv) all the above factors are folded in to obtain a realistic signal to noise ratio. A minimum signal to noise ratio (typically 10 at the alpha's knee) is then selected as the threshold of detection and the minimum detection sensitivity of the gyrotron system was then evaluated as a function of alpha particle density. Calculations have been performed for both near perpendicular and off perpendicular scattering. Significant enhancement of signal to noise ratio was obtained in the presence of low hybrid resonance at near perpendicular scattering.

C. The issue of extracting the slowing-down alpha particle distributions from scattered spectra was considered. The results depend sensitively on scattering geometry and signal to noise ratio. For situation where scattering resonances and magnetic effects are not important, the one-dimensional alpha particle distribution can be unfolded from experimental data if the signal to noise ratio is large and the alpha knee can be clearly identified. Effects of various types of fast ion distributions on the scattering signal were also studied with SKATR. Besides slowing down distributions, anisotropic (bi-Maxwellian) fast ion distributions such as those due to ICH heating have been studied.

D. Experimental complications such as finite beam width and refraction effects were considered. The effect of finite incidence beam radius and divergence was considered in two ways. First, the situation was modelled theoretically by assuming that the spread in beam width resulted in a spread in wavenumber of detected scattered radiation. A simple analytical estimate was then obtained regarding the change in the scattering form factor. A

second method was to perform spectra calculations iteratively using SKATR over the finite beam width and obtained estimate of the actual integrated spectra. Refractive effects were checked with ray tracing calculations. Such calculations were performed for various launching configurations and operating parameters. For typical TFTR operating conditions, refractive effects are not critical and do not significantly affect experiment.

E. A low power, 1KW gyrotron option was considered as a backup to the high power system in collaboration with MIT (J. Machuzak and P. Woskov). To maintain the same signal to noise ratio with a substantially lower incidence gyrotron power, the lower hybrid resonance was utilized to enhance the scattered signal strength. The scattering geometry was designed to be near perpendicular. The effect of finite beam spread ($\Delta\theta$) was taken into consideration. Through SKATR, a scattering regime was discovered where the frequency of the lower hybrid resonance remains fairly constant within $\Delta\theta$. As a result, significant signal enhancement can still be achieved with the scattering resonance and the desirable signal to noise ratio can be achieved even with a low incidence power of 1 KW.

Similar efforts and quantitative analysis were also made regarding the JET gyrotron scattering system. Issues such as scattering resonances, signal to noise ratio, and refraction have been considered. In addition, the following studies were also performed:

1. Comparison studies were made regarding the performance characteristics of the TFTR system and the JET system. The 140 GHz JET gyrotron system is designed to operate between the fundamental and the second harmonic of the cyclotron frequency (~ 95 GHz) where both O mode and the first branch of X mode can be used. On the other hand, the 60 GHz TFTR system is designed to operate below the fundamental of the cyclotron frequency (~ 145 GHz) where only the second branch of X mode is accessible. We are currently in the process of making systematic scattered spectra and ray tracing calculations for JET.

2. The effects of geometric and polarization factors in the scattering cross section were carefully analyzed. In particular, conditions where O $\rightarrow$ O and X $\rightarrow$ X scattering cross sections can be optimized were analyzed because as mentioned above at 140 GHz, the JET system has the unique capability of operating either in O mode (O $\rightarrow$ O scattering) or X mode (X $\rightarrow$ X scattering). For the same plasma conditions and scattering geometry and assuming either mode is near cutoff, the O mode (O $\rightarrow$ O) scattering cross section is typically larger than the X mode (X $\rightarrow$ X) scattering cross section. This results from the difference in the polarization factor of the two modes. The possibility of cross mode (polarization) scattering has also been considered. Through our fully electromagnetic scattering code, SKATR,

we observed that the scattering cross sections for cross mode scattering processes ($O \rightarrow X$ and $X \rightarrow O$ scattering) are strongly influenced by electromagnetic effects. Strong enhancement of cross mode scattering cross section can be achieved by optimizing the polarization factors and scattering geometry.

F. The feasibility of Thomson scattering alpha particle diagnostic for ITER was also analyzed. Three scattering systems were considered: a low frequency (70 GHz and 110 GHz) gyrotron scattering system, a mid-frequency (152 μm) FIR system, and a high frequency (10.6 μm) CO_2 system. The performance characteristics, physics and technical issues were carefully analyzed. The results of our first analysis, based on old ITER design parameters (70 GHz gyrotron system), was summarized in a memo to the ITER diagnostic community. Recently, we received information regarding new and updated ITER design parameters and a second analysis was performed. The new gyrotron frequency was chosen to be at 110 GHz to incorporate changes in higher density and magnetic field requirement for ITER and the fact that 110 GHz high power gyrotron tubes are now available commercially. In both studies, we concluded that the gyrotron scattering system remains an excellent choice in terms of cost, development and testing time, and other various physics and technical issues.

G. We have also considered the feasibility of a gyrotron scattering system for fast ion detection in other tokamaks. In particular, we have considered the diagnosis of rippled trapped fast ions resulted from neutral beam injection in TEXT. A 56 GHz gyrotron scattering system was studied. Various operating regimes and launch configurations were analyzed and the optimum regimes were identified. The criteria used for identifying these regimes were: accessibility of both O and X modes, signal to noise ratio, and the dissipation and absorption of the incident beam. Although operating regimes do exist on TEXT, we concluded that it will be a difficult experiment. As a result of the low fast ion beam density ($< 0.1\%$) resulting from the 40 KV diagnostic beam, signal to noise ratio is small and the enhancement of the scattered signal strength with the lower hybrid resonance is necessary. This requires experimental access and steerable optics for near perpendicular scattering. Without the installation of an absorbing beam dump, interference from incident gyrotron beam is also a concern.

The possibility of a 60 GHz gyrotron scattering system on DIIID was also considered. With the availability of high power 60 GHz gyrotron tubes at DIIID and their expertise in ECH heating, the implementation of a gyrotron scattering system appears to be a logical choice. There is also the availability of high power neutral beams as compared

to TEXT. However, at a nominal central toroidal magnetic field of 2.1 T, the cyclotron frequency (~ 59 GHz) is too close to the gyrotron frequency. This results in large ECE noise near scattered wave frequency and severely degrade the signal to noise ratio to below the experimental threshold of detection. The operating magnetic field has to be lowered substantially (< 1.5 T) before ECE noise level is small enough and a reasonable signal to noise level can be achieved. At such a low operating field, it is questionable that the scattering experiment would be of interest to the DIID group.

H. For the remaining period of this first contract year we will continue to upgrade the SKATR code and study the results of the code for the JET scattering system.

I. Diffraction Analysis

Focussed gyrotron beams play an important role in defining limits for scattering geometries and radial resolution for energetic ion detection. As no correct plasma models for retaining diffraction effects have previously been explicitly worked out, focussing apparatuses have been designed using vacuum diffraction rules. We have considerably altered this situation by deriving the equations for X and O mode propagation which include plasma and magnetic field effects and are rather simple generalizations of the ray equations in the relevant limit of a cold magnetoplasma. Three-dimensional analytic solutions have been obtained for the simple case of one-dimensional inhomogeneity in cartesian geometry and they show the expected anisotropic spreading of the beams as they propagate. These model solutions certainly demonstrate that vacuum calculations are inaccurate ;and use of the vacuum models will lead to over or under focussed beams. This feature is compounded by the nature of determining the scattering volume by the overlap of the transmitted and receive antenna beams. We also have noted that low frequency fluctuation scattering of the beams, normally calculated by the scattering of rays, can in fact be dominated by standard diffraction effects. All of these results will be presented at the spring (93) Sherwood meeting.

In the remaining part of this first contract period we will attempt to incorporate the diffraction effect into our ray tracing codes so we will be able to accurately evaluate scattering volumes and angles in realistic tokamak geometries.

END

**DATE
FILMED**

3 / 26 / 93