Technical Progress Report
For First Year Efforts Related To

DOE/ER/61403--1

DE93 009398

Project Entitled:

**Hydrodynamic Controls On Particle Transport Through Heterogeneous
Porous Media**

As Supported By The
U.S. Department of Energy
Subsurface Science Program

Report Submitted By:

Dr. Stephen E. Silliman
Department of Civil Engineering and Geological Sciences
University of Notre Dame
Notre Dame, Indiana 46556

RECEIVED

MAR 22 1993

OSTI

Date of Submission: September 30, 1992

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Executive Summary

The initial stages of this project have been focused on equipment development and preliminary experimental efforts. Among the accomplishments to date are the development of a successful flow cell design, proof of the utility of the UV resin, adjustment of the Laser Particle Counter to produce reliable readings, installation of a low particle content water supply, installation of a microscope for viewing discharge samples, development of a fiber/rod optic system for freezing the UV resin in situ and performance of initial experiments on layered and complex heterogeneities. The work is currently following very closely the original schedule for research efforts. Continuing efforts in year one will include continued efforts in simple and complex heterogeneity in two-dimensions, extension into three-dimensions, consideration of the most appropriate methods for creating geologically realistic structures in the laboratory, interaction with other SSP research programs and organization of the spring meeting on intermediate-scale experimentation to be held at Notre Dame. Efforts in year two will be focused on three-dimensional experiments in saturated media, extension of results into unsaturated media, development of techniques for unsaturated media characterization, and development of research ties with outside research interests.

Primary Objectives of the Research

The primary objectives of the research have not been altered substantially from those outlined in the original proposal. Specifically, this research addresses the following primary issues:

- 1) Determine the dependence of particle transport on medium heterogeneity.
- 2) Through direct observation, identify relationships among the structure of particle flow paths, particle size, and dimension of heterogeneity.
- 3) Develop a data base regarding hydrodynamic behavior of particle transport.
- 4) Determine dependence of transport on length scale of heterogeneity.
- 5) Determine dependence of transport on degree of saturation.
- 6) Test and improve macroscopic predictions of particle transport
- 7) Develop innovative technologies for application in the laboratory.

Development of UV Curable Resin Technology

Perhaps the most dramatic accomplishment of the project to date has been the testing and design of technology to take advantage of a UV curable resin for use as the carrying fluid in porous media experiments. The resin, purchased from a commercial vendor, is a newtonian fluid with a viscosity of approximately 200 cp. When exposed to high intensity ultraviolet light, the resin rapidly changes from a fluid to a clear solid.

The resin has been used quite successfully in our laboratory experiments. In each of these experiments, the resin has been used in place of water as the primary fluid within the flow cells. Among the applications are:

- 1) Curing of samples of flow cell discharge for storage and analysis of particle content.
- 2) Curing of the resin *in situ* along the edge of the flow cell during flow experiments through exposure to UV light through a plexiglass plate forming the edge of the flow cell (both the size and location of the solidified sample is controllable).
- 3) Point curing of the resin *in situ* at interior points within the flow cell through exposure to UV light via fiber optics and small diameter glass rods (the location of the solidified sample is controllable while control of the size of the sample is still under investigation).
- 4) Curing of the resin in a multiphase system to permanently capture the shape of contact interfaces. Initial efforts in this area indicate that the curing process does not significantly alter the contact angles or contact areas.

It has been determined that the resin is the wetting fluid when in competition with water in a medium consisting of glass beads. Although no direct measurements have yet been completed, there does not appear to be any substantial volume changes in the resin during curing. Curing time for direct exposure of resin to UV light (e.g. flow cell outflow) is a matter of seconds. Curing within a glass bead medium through a 0.5 inch plexiglass plate occurs within 5-10 seconds. The exact time of cure may be altered in order to alter the size of the cured sample. Exposure times as short as 3 seconds have produced successful samples. Curing through a 2.0 mm glass rod placed within a glass bead medium requires approximately 15 seconds to produce a cured sample of approximately 1 cubic centimeter volume at the end of the rod.

The latex particles used in this study appear compatible with the resin as no degradation has been observed and, in the absence of water or air, the particles do not show any tendency towards aggregation. Unusual behavior was observed in small latex spheres when suspended in the resin with small air bubbles present. Although the subject of further study, the behavior of the beads appeared to be one of collecting on the air/resin interface in such large numbers that the air/

resin interface became unstable and the air bubble dispersed (became unstable and then vanished) within the resin. We are currently attempting to arrange equipment loans in order to capture this behavior on video.

Flow Cell Design

Several flow cell designs have been investigated. In all designs, the flow cell construction is based on the use of plexiglass for all surfaces. The use of plexiglass is compatible with these experiments as no bacterial studies are planned (and therefore there are no concerns regarding interaction of the bacteria with the plexiglass or plexiglass glues/solvents). Further, the chemicals currently in use as tracers are non-reactive with the plexiglass (e.g. sodium chloride, calcium chloride, sodium bromide). Studies with the UV curing resin demonstrate that the resin does not degrade the plexiglass, UV passes through the plexiglass in sufficient quantity to allow rapid curing, and the cured epoxy forms a significantly stronger bond with the glass beads than with the plexiglass. This last observation is important as it allows cured samples along the wall of the flow cell to be removed without destroying the bead structure captured in the cured sample.

All connections on these cells are performed through drill and tap, or external clamp techniques. Waterproofing of the tanks is currently performed using silicon sealant. We have found that this combination of connections and sealant allows for repeated disassembly / reassembly of the flow cell.

The cost of the flow cells have ranged from approximately \$300 to approximately \$500. This minimal cost allows cells to be redesigned and manufactured for specific experiments. When compared to the design utilized at SERF, this design is significantly less expensive and, therefore, more flexible in its application on a fixed budget (i.e. additional flow cells can be constructed). However, the SERF design provides for long term use of the constructed flow cell and is based on construction materials consistent with the use of reactive chemicals and biological experimentation. The combination of the two design approaches provides the SSP with substantial flexibility in approaching future intermediate-scale experiments.

Equipment Development

During the initial stages of this project, several pieces of experimental equipment have been purchased, tested, and/or refined. The Spectrex Laser Particle Counter which was in place at the beginning of this project has been refined to provide reliable, reproducible counts of particles in the size range of 5 - 100 microns. The reported lower limit of the instrument is 1.0 micron. However, our efforts with the counter have indicated that a persistent peak of particle counts in the 2-4 micron range may reduce the accuracy of counts on small particles. The reason for the peak at this small micron range is either a persistent presence of particles of this size or a random scatter of the laser beam used to perform the count. This peak may be masked by raising the tolerance on the count. However, we suspect that this may substantially reduce the sensitivity of the instrument to real particles in this size range.

A low particle count water supply has been installed in the laboratory. Based on a reverse osmosis treatment system in combination with a series of filters, this water supply is providing excellent quality water with minimal background particle counts. This water will be used for all experiments.

Through the Center for Bioengineering and Pollution Control, a trifocal microscope has been purchased which, in combination with the diopter microscope already in place, allows direct visual inspection of particles within the flow cell, in the flow cell discharge and in cured samples removed from the flow cell. The trifocal scope provides relatively easy examination of discharge samples to the micron or sub-micron range. Techniques for examination of particles within the flow cell and examination of cured samples removed from the cell are still in development. At present, we have identified some particles in the 5-10 micron range. However, reliable identification appears to be limited to particles of size greater than 10 microns. New techniques being investigated revolve around reducing the thickness of the cured sample, increasing the light penetration, and using brighter fluorescent particles.

Experiments Performed to Date

Most experiments performed to date have been directed towards improving experimental technique and flow cell design. Several two-dimensional flow cells and one flow cell capable of performing three-dimensional experiments have been constructed. Experiments within these cells have involved either water or the UV resin as the carrying fluid

Preliminary results have been obtained from two flow designs. The first involved a complex heterogeneity which included several lens structures. The second involved a simple layered medium with flow parallel to layers. The first experiment was run using resin as the carrying fluid. The second was run using water as the carrying fluid. Both experiments were run at relatively high velocities (again, the focus of these experiments was experimental design and not collection of final results). In both experiments, a mixture of various sized particles were added to the flow cell and the arrival of these particles at the cell outflow was monitored.

Although rigorous procedures were not used in these experiments, the results show an interesting difference between the two systems. The absolute particle counts for selected particle sizes are shown in the first set of figures. It should be noted that the vertical axis is on a log scale as there were far more small particles added to the system than large particles. The top figure, representing the layered medium, shows similar structure in the arrival peaks for all particle sizes. The bottom figure, representing the complex heterogeneity, shows quite dissimilar structure in the arrival peaks for the various sized particles.

This comparison can also be seen in the second set of plots provided. These two plots show the percent of particles in a particular size class. It is noted for the layered system that, with the exception of the sample at 4 minutes, the percentage in each size class does not vary appreciably with time during the heart of the breakthrough curve. The results for the complex heterogeneity, however, demonstrate that the percentage of particles arriving in the outflow vary substantially with time.

Experiments currently being performed are directed towards repeating these results under more controlled conditions. If these results can be repeated, they would imply that the relative transport of particles (large versus small) is dependent on the complexity of the flow field encountered. Such a result would firmly support our initial hypothesis that particle transport will be dependent on the form and length scales of the heterogeneity.

Theoretical Efforts

Three distinct theoretical efforts are being developed towards the completion of the objectives of this project. First, numerical simulation is being utilized to determine the dependence of flow and transport predictions on the form of the random field assumed. This work is directed specifically to demonstrating the degree to which the geologic setting needs to be considered when selecting random fields for study. This work is ongoing and conclusions have not yet been reached.

The second numerical effort involves use of a simple flow and particle transport code for identifying random fields which may be simulated in the laboratory without substantially altering flow and transport patterns near the no-flow boundaries imposed by the flow cell. This work, performed by an undergraduate, is progressing well.

The third theoretical effort, also being performed by an undergraduate, is the delineation of a variety of geologic settings and the identification of structures common to individual geologic conditions. Specifically, this student is reviewing river alluviums, catastrophic floods, outwash plains, and glacial tills to determine whether we can identify classic sediment patterns in any or all of these settings. Patterns which are identified will be used to guide the selection of conductivity fields for future flow cell experiments. This work was just recently initiated and has therefore not led to any conclusions at this time.

Interaction With Other Research Programs

As a partial focus of this research project, Notre Dame has actively encouraged interaction with outside investigators. Considerable interest has been expressed in both the current research program and the program proposed under the SERDP efforts. Among the investigators who have actively pursued interaction with the Notre Dame facility are investigators from the SERF facility, investigators from Argonne National Laboratory, an investigator from Lawrence Berkely National Laboratory, an investigator from the Desert Reserach Institute, and an investigator from Wright State. Interaction is being encouraged through (i) solicitation by Notre Dame for input regarding design of random fields, (ii) open discussion with other investigators regarding sharing of data with other projects to be supported under the SSP, and (iii) through invitations from Notre Dame for (unsupported) visits to the Notre Dame facility. In addition, outside investigators will be encouraged to attend the intermediate-scale workshop this coming spring.

Projected Activities During Second Year of Project

The continuing efforts currently being expended should result in three-dimensional experiments actively being pursued at the end of the first budget period (April, 1993). During the second year, it is anticipated that many of the hypotheses regarding control of hydraulic transport in saturated media will be addressed. Further, it is anticipated that the experiments will be extended into unsaturated media. This extension will involve substantial development of new techniques for control of flow, injection of particles, and sampling. As a result, it is anticipated that the bulk of the unsaturated experiments will be completed during the third year of this project.

Additional efforts during the second year involve advancing the focus on the role of geology on transport characteristics. Among the ideas to be pursued are extensions of the theoretical approach discussed above in which geologic settings will be characterized by classic features. This work is not to be directed towards development of new generation methods. Rather, we will focus on utilizing available technologies (modified where necessary) to produce random fields which reflect both the structure and variability observed in actual sediments. This work will have a direct bearing on the permeability fields utilized in the intermediate-scale flow cells.

Efforts during the second year will also be extended towards closer interaction with SERF to delineate the roles which SERF and the new lab at Notre Dame may play in advancing the goals of the SSP. In particular, Notre Dame expects that the lab at Notre Dame will become dedicated to investigations of the role heterogeneity plays in transport and remediation processes whereas the SERF facility will be dedicated to investigations of the complex interactions among chemical and microbial processes.

Total Counts Per Drop For Layered Medium

Number of Particles Per Drop - Complex Heterogeneity

Percentage Of Observed Particles By Size Class
Layered Medium

Percentage Of Observed Particles In Size Class
Complex Heterogeneity

END

DATE
FILMED

4/13/93