DOE/PC/91054--T3

(3)

DOE/PC/91054--T3

DE93 013608

QUARTERLY PROGRESS REPORT

Submitted to: Department of Energy

for Project

Effect of Pretreating of Host Oil on Coprocessing

Contract DE-AC22-91PC91054

October 1, 1992 through December 31, 1992

by

Chemical and Petroleum Engineering Department

University of Pittsburgh

Irving Wender, Principal Investigator

John W. Tierney, Co-Principal Investigator

March 25, 1993

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

no 9mm
B.D.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

INTRODUCTION

The principal objective of this research is to determine the role host petroleum-derived oils (1000°F+), as well as that of catalytically treated host oils, play when used as liquefaction solvents in coprocessing with coal. The host oils will be extensively characterized and then pretreated in a number of ways which involve catalytic reactions such as hydrogenation, hydrocracking, isomerization, and dehydrogenation. The pretreated oils will then be characterized. The effects of the host oil on coprocessing with coal will be compared to those obtained using catalytically modified heavy oils. When appropriate, model compounds will be used to study specific reactions brought about by the pretreatments. Highly dispersed iron catalysts modified by the addition of small amounts of other metals will be used to modify the chemical composition of the host oils.

EXPERIMENTAL WORK

Work continued on Task II during this quarter. In the first phase of this task, the test oil, an Amoco resid, is being treated with hydrogenation catalysts such as $\text{Mo}(\text{CO})_6$ and $\text{Fe}_2\text{O}_3/\text{SO}_4$ to determine the conditions necessary to increase the hydrogen content from about 10.2 wt% to about 11.5 wt%. In the second phase, more severe hydrogenation/hydrorefining is being carried out to determine the conditions necessary to further increase the hydrogen content to over 12 wt%. Five pretreatment runs were made during this quarter. The conditions for these runs are listed in Table 1. The experimental procedure and product yields were summarized in the quarterly report for July-August, 1992.

Table 1. Conditions for Pretreatment, Runs 1 to 5					
	Run 1	Run 2	Run 3	Run 4	Run 5
Average Temperature °C	405	404	405	414	398
Average Pressure psig	1533	1630	1490	1890	1852
Gas	H ₂	H ₂	H ₂	H ₂	H ₂ /H ₂ S
Catalyst	None	Fe ₂ O ₃ /SO ₄	Fe ₂ O ₃ /SO ₄	Fe(CO) ₅ /Mo(CO) ₆	Shell 324*
Reaction Time (min)	60	60	60	60	60
* Shell 324: Ni/MO/Al ₂ O ₃					

Samples of the starting oil resid and the liquid products (THF soluble fractions) from these runs were analyzed to determine their elemental composition. Results are displayed in Table 2. Run 1 is a thermal treatment with no catalyst. It resulted in a reduction in the hydrogen content of the starting oil as well as a drop in H/C ratio. The sulfur and nitrogen content of the oil remained essentially constant. The reduction in hydrogen content was probably due to cracking of the oil, producing light hydrocarbon gases.

In Runs 2-4, iron-based catalysts were used. A sulfated iron oxide was used in Run 2,

Table 2. Elemental Analysis of Liquid Products							
	Amoco Resid*	Amoco Resid THF Soluble	Run 1	Run 2	Run 3	Run 4	Run 5
Sulfur	4.6	4.4	4.6	4.7	4.4	4.4	1.6
Nitrogen	0.5	0.5	NA	0.5	0.5	0.5	0.3
Hydrogen	10.2	10.3	9.7	10.1	10.3	10.3	11.2
Carbon	84.3	84.0	84.2	84.4	84.4	83.9	86.4
H/C	1.45	1.47	1.38	1.44	1.46	1.47	1.56
* Average of three samples.							
Liquid products from Runs 1-5 are THF Soluble Fraction.							

a molybdenum promoted sulfated iron oxide catalyst in Run 3, and a mixture of iron and molybdenum carbonyls were used in Run 4. These runs had little effect on increasing the hydrogen content of the starting oil. Sulfur and nitrogen contents also remained constant.

Run 5, using a Shell Ni/Mo/Al₂O₃ supported catalyst, produced a liquid product that had a higher hydrogen content than that of the starting oil. The H/C ratio was also higher, 1.56 vs 1.47. The sulfur content was lowered from 4.4 to 1.6 wt% and the nitrogen content was reduced from 0.5 to 0.3 wt%. The hydrogen content of the liquid product is close to 11.5 %, which is the target value we hope to reach using dispersed iron sulfated catalysts, with and

without addition of small amounts of catalysts such as molybdenum or tungsten.

A sample of the pentane soluble fraction of the untreated Amoco resid and the liquid products from Runs 1, 3 and 5 were analyzed in a GC/MS in order to study the chemical composition of these oils. Table 3 presents the instrument settings used for these runs. Figure

Table 3. Parameters for GC/MS	
GC Type	Hewlett Packard 5890 Series II
MS Type	Hewlett Packard 5970
Column Type	Capillary Crosslinked Methyl Silicone Gum
Column Dimension	12m x 0.2 mm x .33 μ m film thickness
Test Conditions	
Gas Flow	30 cc/min
Initial Temperature	40°C
Final Temperature	320°C
Heat Rate	10 °C/ min

1 shows a chromatograph of the untreated oil. Some of the peaks are identified in Figure 1 by matching the peak mass/charge spectrum to that of known compounds. It was determined that the untreated oil contains paraffins in the C22 to C35 range.

Figure 2 shows a chromatograph of the pentane soluble fraction from Run 1, the thermal

Figure 1. Chromatograph of Pentane Soluble Fraction of Amoco Resid.

Figure 2. Chromatograph of Pentane Soluble Fraction of Run 1 Products.

treatment. The thermally treated oil contains lighter hydrocarbon compounds than the untreated oil. These results suggest that many of the heavier compounds in the untreated oil were cracked.

Figures 3 and 4 are chromatographs from Run 3 and Run 5 respectively. Run 3 was made with a $\text{Mo/Fe}_2\text{O}_3/\text{SO}_4$ catalyst and Run 5 with the Shell 324 catalyst. The oils from these runs differ from those in the thermally treated oil fraction since they appear to contain heavier hydrocarbons. The thermally treated oil appeared to be devoid of heavier hydrocarbon compounds.

The first four pretreatment runs had little effect on increasing the hydrogen content of the Amoco resid. Additional pretreatments at more severe conditions (higher hydrogen pressures) are needed. Two more pretreatment runs were made during this quarter and the experimental conditions are summarized in Table 4. The initial pressure for Run 7 was raised to 2670 psig; during the run, the pressure dropped to 2350 psig as shown in Figure 5. In Run 8, the initial pressure was 3380 psig. After 30 minutes the pressure dropped below 2000 psig and then increased to about 100 psig over the starting pressure as shown in Figure 6. These results suggest a high hydrogen uptake in the beginning of the run followed by the release of gases. A material balance for this run is given in Table 5 and shows that 33.8% of the starting material was converted to gas, and that 9.4% was converted to solid (coke). The liquid product from this run was lighter and less viscous than liquids from previous runs, further evidence that the starting resid was cracked. The reaction temperature was 413°C , apparently sufficient to promote cracking. Additional runs will be made at 400°C or lower to minimize cracking.

Paul Hajdu met with Dr. Mildred Perry during the quarter to discuss techniques for separating heavy oils by liquid chromatography. The heavy oil is first deposited on activated alumina in a column. Solvents of increasing polarity are passed through the column to

Figure 3 Chromatograph of Pentane Soluble Fraction of Run 3 Products.

Figure 4. Chromatograph of Pentane Soluble Fraction of Run 5 Products.

Figure 5. Pressure Profile for Run 7.

Figure 6. Pressure Profile for Run 8.

selectively remove saturates plus monoaromatics, aromatics and polar compounds. A column may be constructed for characterizing liquid products obtained in this project.

Table 4. Test Conditions for Pretreatment Runs 7 and 8		
	Run 7	Run 8
Wt. Heavy Oil, g	75.39	65.78
Catalyst	Mo/Fe ₂ O ₃ /SO ₄	Fe ₂ O ₃ /SO ₄
Wt. Catalyst, g	0.8	0.74
Temperature, °C		
Range	390-402	410-417
Average	399	413
Gas Used	H ₂ /H ₂ S	H ₂ /H ₂ S
Pressure, psig		
Initial	2670	3380
Final	2348	3179
Average	2526	2852
Reaction Time, min	60	60

Table 5. Product Distribution for Pretreatments Runs 7 and 8			
	Starting Oil	Run 7	Run 8
THF Solubles, wt%	99.9	86.5	52.3
THF Insolubles, wt%	0.1	1.6	9.4
Gas + Loss, wt%		11.9	38.3
Pentane Soluble, wt%*	74.7	70.4	71.1
Pentane Insoluble, wt%	20.1	18.6	22.7
Losses	5.2	11.0	6.2
* Weight Percent of THF Soluble Fraction			

FUTURE WORK

The same catalysts as used in Runs 1-5, namely $\text{Fe}_2\text{O}_3/\text{SO}_4$, $\text{Mo}/\text{Fe}_2\text{O}_3/\text{SO}_4$, $\text{Fe}(\text{CO})_5/\text{Mo}(\text{CO})_6$ and Shell 324 as well as a thermal run, will be carried out on the Amoco Resid during the next quarter, but at a higher initial hydrogen pressure. High temperatures tend to crack the heavy oil and so temperatures used will not exceed 400°C . It is known that higher hydrogen pressures are effective in adding hydrogen to heavy oils so that these reactions will be carried out at higher initial hydrogen pressures (2600 to 3400 psig). It is quite possible that a lower temperature (375°C) and a higher initial pressure (3400 psig) may be more effective in raising the H/C ratio of the Amoco resid.

END

**DATE
FILMED**

6 / 10 / 93