12.25
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

MASTER

8-3-78
PRELIMINARY CATALOG OF EARTHQUAKES
IN NORTHERN IMPERIAL VALLEY, CALIFORNIA
APRIL 1977 - JUNE 1977

By
Donna Jenkins and Gary Fuis

OPEN-FILE REPORT

77-694

EW-78-X-05-1924
This report is preliminary and has not
been edited or reviewed for conformity with
Geological Survey standards and nomenclature.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED
fig

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

**PRELIMINARY CATALOG OF EARTHQUAKES
IN NORTHERN IMPERIAL VALLEY, CALIFORNIA**

APRIL 1, 1977 - JUNE 30, 1977

CONTENTS

	Page
Introduction	1
Area Covered and Instrumentation	1
Data Analysis	2
Discussion	3
References	6

ILLUSTRATIONS

Figure 1. Base Map of Southern California	7
Figure 2. Earthquake Epicenters and Seismograph Stations	8
Table 1. Station Data	9
Table 2. Preliminary Hypocenter Solutions for Earthquakes April 1, 1977 - June 30, 1977	11

INTRODUCTION

The northern section of the Imperial Valley region in southern California is an area of known geothermal resources and an area of high seismicity. To study in detail the relationship between geothermal areas and earthquakes, the U.S. Geological Survey has been monitoring seismicity in the Imperial Valley with a 16 - station network since 1973. Six new stations were added to the network in November 1976. This catalog contains a description of the network and a list of preliminary data on earthquakes recorded by the network from April 1977 through June 1977.

AREA COVERED AND INSTRUMENTATION

Earthquakes reported in this catalog are located in the area indicated in Figure 1. Major faults are shown. Locations of most of the seismographic stations used in locating earthquakes reported here are shown on Figure 2 and are listed in Table 1.

The telemetered seismographic network in the Imperial Valley employs the same type of instrumentation developed by the U.S. Geological Survey for use in the central California network (see Wesson and others, 1973). Seismometers are vertical-component L-4C Mark Products ^{1/} seismometers ($T_{seis} = 1 \text{ sec}$). Signals from these instruments are filtered in the field ($T_{filter} = 0.1 \text{ sec}$) and telemetered to the California Institute of Technology in Pasadena, California, where they are recorded on 16 mm films along with a WWVB time code in Develocorders ^{1/} ($T_{galvo} = 0.06 \text{ sec}$). Peak magnification

^{1/} Any use of trade names and trademarks in this publication is for descriptive purposes only and does not constitute endorsement by the U.S. Geological Survey.

ranges from 10^5 to about 10^8 and occurs at $T_{\text{peak}} = 0.06$ sec (or 14 Hz). (Refer to Wesson and others, 1973, or Hill and others, 1975, for a somewhat more detailed description of USGS instrumentation.)

DATA ANALYSIS

The data is analyzed using methods developed for the analysis of similar data from the U.S. Geological Survey's central California network (see, for example, Lee and others, 1972b and Wesson and others, 1973). In particular, each roll of film, which contains 24 hours of data, is processed in the following steps.

- 1) Each film is visually scanned to note approximate times of earthquakes and the stations on which they are recorded.
- 2) Earthquakes that are recorded "impulsively" on 3 or more stations are manually timed. An "impulsive" signal is formally defined as one in which a) there is no question that the first motion seen is the first arrival, b) the amplitude of the first swing is five times the amplitude of the noise and c) the arrival can be picked with an error of 0.1 second or less.
- 3) The arrival-time data are punched on computer cards, and the cards are processed using the computer program HYPO 71 (Lee and Lahr, 1972) to yield preliminary determinations of origin time, hypocenter location, magnitudes, and statistical data concerning the hypocenter solution. HYPO 71 generates a summary card containing the above information for each earthquake.
- 4) Information from the summary cards is listed in this catalog in Table 2, and the preliminary epicenters are plotted on a map (Figure 2).

DISCUSSION

Earthquake locations are dependent strongly on the velocity model used in the location program. Epicentral determinations are less strongly dependent on the model than depth determinations, unless the earthquake occurs outside of the perimeter of the station group used in the location. The velocity model used for the earthquake locations in this catalog is based on a seismic refraction study of the Imperial Valley by Blehler and others (1964):

VELOCITY (km/sec)	DEPTH TO TOP OF LAYER (km)
2.0	0.0
2.6	1.0
3.6	2.0
4.7	3.0
6.1	6.0
8.0	20.0

The P-wave delay times assigned to each station (Table 1) were established from a calibration blast detonated by the U.S. Geological Survey on March 23, 1976, at 33° 05.30' N. Latitude and 115° 37.87' W. Longitude, 5 kilometers north of Westmorland. This calibration shot is very near the epicenters of most of the earthquakes of the November 1976 earthquake swarm. Our studies indicate that epicentral locations are probably as accurate as ± 0.5 km; hypocentral locations (depths) are probably accurate only to ± 2 km. The hypocentral locations of these earthquakes relative to one another is probably more accurate, however.

Magnitudes reported in this catalog are based on the method of signal duration described by Lee and others (1972a). The magnitude of a given earthquake is the average at several stations of magnitudes determined by

$$M = - 0.87 + 2.00 \log (\tau) + 0.0035\Delta$$

where

Δ is epicentral distance in km, and

τ is signal duration in seconds.

Signal duration is the time interval in seconds from the onset of the P wave arrival to a point where the trace amplitude (peak-to-peak) falls below 1 cm as it is seen on the Geotech film viewer. A 0.0 magnitude (Table 2) indicates that the magnitude was not calculated. In many cases an earthquake signal was truncated by the onset of a larger event or extended by the onset of smaller events. In these cases the method of determining magnitude using signal duration could not be used.

The hypocentral parameters listed in Table 2 are the following

1) Y, year of occurrence	}	GCT
2) M, month of occurrence		
3) D, day of occurrence		
4) H, hour of occurrence		
5) M, minute of occurrence		
6) SEC, second of occurrence		
7) LAT, north latitude of epicenter, in degrees		
8) LONG, west longitude of epicenter in degrees		
9) DEP, depth of hypocenter in kilometers		

- 10) MAG, magnitude
- 11) N, number of P arrivals used in locating the earthquake
- 12) GAP, maximum gap between stations contributing P-arrivals
- 13) DM, distance from epicenter to nearest station used in locating the earthquake
- 14) RMS, root mean square of travel time residuals, R_i , in seconds

$$RMS = \sqrt{\sum_{i=1}^N R_i / N}$$

- 15) ERH, standard error of the epicenter, in kilometers
- 16) ERZ, standard error of the focal depth, in kilometers
- 17) Q, solution quality of the hypocenter.
- 18) M, model used in location. M = 1 throughout this preliminary catalog.

A filter is applied to the events in this catalog, to eliminate very bad hypocenter solutions. A solution was not listed or plotted unless

$$RMS \leq 0.50 \text{ seconds}$$

REFERENCES CITED

- Biehler, S., R. L. Kovach and C. R. Allen, 1964, Geophysical framework of the northern end of the Gulf of California structural province, in Marine Geology of the Gulf of California (T. J. van Andel and G. G. Shor, Jr., eds.): Am. Assoc. Pet. Geol. Memoir, 3, p. 126-156.
- Hill, D. P., P. Mowinckel and K. M. Lahr, 1975, Catalog of earthquakes in the Imperial Valley, California, June 1973 - May 1974: U.S. Geol. Survey, Open-file Rept. 75-401, 25 p.
- Lee, W. H. K. and J. C. Lahr, 1972, HYPO71: A computer program for determining hypocenter magnitude, and first motion pattern of local earthquakes: U.S. Geol. Survey, Open-file Rept., 100 p.
- Lee, W. H. K., R. E. Bennett and K. L. Meagher, 1972a, A method of estimating magnitude of local earthquakes from signal duration: U.S. Geol. Survey, Open-file Rept., 48 p.
- Lee, W. H. K., J. C. Roller, P. G. Bauer and J. D. Johnson, 1972b, Catalog of earthquakes along the San Andreas fault system in central California for the year 1969: U.S. Geol. Survey, Open-file Rept., 48p.
- Wesson, R. L., K. M. Meagher, and F. W. Lester, 1973, Catalogue of earthquakes along the San Andreas fault system in central California, July-September, 1972: U.S. Geol. Survey, Open-file Rept., 49 p.

Figure 2. Locations of earthquake epicenters in the Imperial Valley with respect to major faults for the period April 1, 1977 through June 30, 1977. Solid triangles are seismograph stations in the Imperial Valley network installed in 1973 (see Figure 1 and Table 1). Solid circles are the seismograph stations installed in November 1976.

NO. STATION LATITUDE LONGITUDE ELEV DELAY

		DEG	MIN	DEG	MIN	FEET	SEC
1	RUGR 33	2.73N	115	34.10W		-47	-0.02
2	VERD 33	7.07N	115	33.76W		-61	0.02
3	EPIC 33	5.28N	115	36.28W		-61	0.0
4	BANG 33	5.29N	115	37.84W		-62	0.0
5	ELR 33	8.84N	115	49.95W		-63	-0.55
6	NWR 33	6.10N	115	41.01W		-69	-0.64
7	WIS 33	16.56N	115	35.58W		-68	-0.91
8	WML 33	0.91N	115	37.35W		-44	-0.29
9	CLI 33	8.45N	115	31.64W		-59	-0.20
10	FNK 33	22.98N	115	38.26W	12	-1.13	
11	COY 33	21.84N	116	18.63W	210	-1.58	
12	HOT 33	18.84N	116	34.89W	1975	-1.39	
13	SMO 33	32.15N	116	27.70W	0	-1.34	
14	PLT 32	43.87N	114	43.76W	61	-1.52	
15	SLU 32	30.10N	114	46.64W	41	-0.97	
16	AMS 33	8.48N	115	15.25W	140	-1.13	
17	* COA 32	51.81N	115	7.36W	-35	0.0	
18	* BSC 32	43.49N	115	2.64W	43	0.0	
19	* BLU 34	24.40N	117	43.61W	1880	0.0	
20	CPE 32	52.80N	117	6.00W	213	-0.65	
21	GLA 33	3.10N	114	49.60W	627	-1.05	
22	IKP 32	38.93N	116	6.48W	957	-1.17	
23	TPC 34	6.35N	116	2.92W	761	-0.77	
24	PLM 33	21.20N	116	51.70W	1692	-0.59	
25	BC2 33	39.42N	115	27.67W	1185	-1.05	
26	CPM 34	9.24N	116	11.80W	937	-0.61	
27	CO2 33	50.83N	115	20.68W	276	-1.10	
28	INS 33	56.14N	116	11.66W	1700	-1.35	
29	LTC 33	29.34N	115	4.20W	458	-1.21	
30	LTM 33	54.9CN	114	55.10W	744	-0.66	
31	PNM 33	58.64N	115	48.05W	1147	-0.75	
32	SHH 34	11.26N	115	39.27W	1122	-0.66	
33	KEE 33	38.30N	116	39.19W	1366	-0.92	
34	VGR 33	50.25N	116	48.53W	1500	-0.71	
35	WWR 33	59.51N	116	39.36W	702	-0.53	
36	BON 32	41.67N	115	16.11W	14	-0.22	
37	CCM 33	25.75N	115	27.88W	488	-1.30	
38	COK 32	50.95N	115	43.61W	-15	-0.40	
39	CRR 32	53.18N	115	58.10W	98	-1.07	
40	DAH 32	44.07N	115	33.47W	-6	0.20	
41	HSP 32	44.81N	115	33.71W	-6	0.13	
42	ING 32	59.30N	115	18.61W	2	-0.37	
43	KBY 33	2.41N	115	42.06W	-51	-0.27	
44	QBB 33	10.04N	115	38.20W	-61	-0.62	
45	RSE 32	55.53N	115	29.95W	-41	-0.22	
46	RUN 32	58.33N	114	58.63W	152	-1.01	
47	SGL 32	38.95N	115	43.52W	110	-1.08	
48	SNR 32	51.71N	115	26.21W	-30	-0.32	
49	SUP 32	57.31N	115	49.43W	219	-1.07	

NO.	STATION	LATITUDE	LONGITUDE	ELEV	DELAY
		DEG MIN	DEG MIN	FEET	SEC
50	HLK 33	3.08N	115.29.44W	48	-0.11
51	FTM 32	33.29N	114 20.01W	263	-1.68
52	PIC 32	54.85N	114 38.59W	263	-0.95
53	YMD 32	33.28N	114 32.68W	76	-0.48
54	EA11 33	46.44N	115 35.83W	780	-1.13
55	HA10 33	42.80N	115 34.90W	536	-0.59
56	ORO9 33	37.05N	115 35.50W	555	-0.79
57	CHO8 33	30.25N	115 35.68W	634	-1.14
58	CHO7 33	27.21N	115 35.50W	585	-1.14
59	COA5 33	22.20N	115 36.10W	18	-1.16
60	HIL4 33	20.37N	115 35.73W	-40	-1.06
61	SAL2 33	15.82N	115 35.25W	-69	-0.83
62	MUD1 33	13.21N	115 35.16W	-70	-0.71
63	ROCX 33	10.58N	115 36.29W	-69	-0.74
64	YNGX 33	7.98N	115 36.61W	-64	-0.08

Table 2.

Preliminary hypocenter solutions for
earthquakes in southern California
April 1, 1977 through June 30, 1977

	TIME	HR	MIN	SEC	LAT	LONG	DEP	MAG	N	GAP	DM	RMS	ERR	ERZ	Q			
1	77	4	1	23	25	7.05	32-59.67	115-30.95	3.90	1.55	15	57	6.7	0.10	0.4	0.5	B	1
2	77	4	2	0	41	48.85	32-59.72	115-31.27	3.97	1.57	10	81	6.8	0.08	0.4	0.5	B	1
3	77	4	6	8	5	7.30	32-52.93	115-28.27	6.74	0.0	10	98	3.9	0.10	0.7	1.1	B	1
4	77	4	6	20	52	32.02	33-27.43	115-46.41	13.02	2.19	15	65	15.1	0.20	0.9	0.9	B	1
5	77	4	7	11	1	0.06	33- 5.56	115-35.93	4.20	0.72	11	80	8.0	0.11	0.5	0.5	B	1
6	77	4	8	12	45	28.91	33- 6.00	115-36.14	5.00	1.65	20	43	7.6	0.12	0.3	0.3	B	1
7	77	4	9	3	50	46.95	32-56.17	115-48.74	8.05	1.94	17	84	2.4	0.16	0.6	0.8	B	1
8	77	4	9	15	40	14.96	33- 3.44	115-33.27	4.62	1.11	18	81	6.0	0.12	0.4	0.3	B	1
9	77	4	9	19	16	27.43	33- 3.54	115-33.34	7.10	3.36	25	46	6.1	0.13	0.4	0.8	A	1
0	77	4	9	19	23	8.52	33- 3.44	115-33.32	5.19	2.17	22	46	6.1	0.10	0.3	0.3	B	1
1	77	4	9	19	29	2.90	33- 3.50	115-33.63	4.80	1.25	16	81	6.6	0.11	0.4	0.3	B	1
2	77	4	11	2	7	53.04	32-50.76	115-20.21	5.00	1.51	7	95	16.0	0.08	0.6	15.9	C	1
3	77	4	12	17	23	31.94	32-48.95	115-28.13	5.60	2.00	9	107	5.9	0.07	0.5	0.4	B	1
4	77	4	15	4	18	5.92	33- 6.64	115-36.84	5.17	1.81	19	63	6.6	0.10	0.3	0.3	B	1
5	77	4	18	5	31	59.78	32-58.06	115-43.34	5.00	3.37	26	79	9.6	0.10	0.3	0.4	B	1
6	77	4	18	5	38	7.67	32-58.18	115-43.36	5.00	2.77	22	79	9.6	0.09	0.3	0.3	B	1
7	77	4	18	5	41	10.95	32-58.27	115-43.57	5.28	1.61	9	113	9.3	0.04	0.2	0.2	E	1
8	77	4	18	5	58	49.05	32-57.99	115-43.54	5.16	2.03	14	94	9.3	0.09	0.4	0.3	B	1
9	77	4	19	11	47	17.46	33-19.26	115-41.62	9.02	1.48	13	138	10.6	0.09	0.5	0.8	E	1
0	77	4	22	11	57	56.61	32-59.49	115-45.91	5.03	2.39	21	64	6.8	0.16	0.5	0.7	B	1
1	77	4	25	8	3	6.92	32-56.03	115-42.32	5.50	1.39	12	85	9.6	0.08	0.4	0.5	B	1
2	77	4	25	23	51	22.38	33- 6.15	115-35.36	4.58	1.90	16	73	7.2	0.09	0.3	0.3	B	1
3	77	4	26	0	50	44.13	32-55.40	115-49.21	8.04	2.21	11	101	3.6	0.08	0.4	0.7	B	1
4	77	4	28	15	35	33.37	33-18.79	115-40.98	8.26	3.47	25	55	8.8	0.15	0.5	0.7	B	1
5	77	4	28	18	15	26.63	33-19.32	115-41.36	0.43	2.32	18	77	8.3	0.10	0.4	3.9	B	1
6	77	4	29	7	51	22.88	33-15.39	115-38.20	4.63	1.71	14	89	4.6	0.18	0.8	0.7	B	1
7	77	5	1	9	10	40.56	32-57.68	115-32.14	4.05	1.10	10	99	10.1	0.10	0.5	0.5	B	1
8	77	5	4	9	33	51.35	33- 9.99	115-36.60	0.68	2.63	20	60	2.5	0.12	0.3	3.3	E	1
9	77	5	4	14	8	52.41	32-56.69	115-32.21	3.69	1.31	10	105	12.6	0.09	0.6	0.7	B	1
0	77	5	11	14	48	29.31	32-50.20	115-36.41	4.30	2.74	20	92	11.3	0.16	0.6	0.9	C	1
1	77	5	14	4	15	14.18	33-14.48	115-59.38	8.28	2.09	19	72	18.0	0.31	1.9	2.5	C	1
2	77	5	15	14	58	17.17	33-14.67	115-40.74	6.04	2.69	26	52	8.7	0.15	0.5	1.0	B	1
3	77	5	16	0	24	20.34	33- 3.36	115-33.23	5.09	2.09	20	32	5.9	0.13	0.4	0.4	B	1
4	77	5	16	4	46	55.92	33-16.00	115-41.48	4.12	1.98	13	103	9.2	0.35	1.6	1.6	C	1
5	77	5	16	8	5	54.42	33-15.37	115-41.41	3.43	3.39	17	100	11.0	0.13	0.5	0.6	B	1
6	77	5	16	8	16	44.45	33-14.94	115-40.87	5.81	2.34	18	97	8.7	0.12	0.5	3.4	B	1
7	77	5	21	5	34	20.29	33- 7.25	115-35.17	3.71	2.07	17	63	5.9	0.15	0.5	0.5	B	1
8	77	5	26	13	11	24.64	33-15.77	115-59.15	1.54	1.44	9	113	32.3	0.13	0.8	12.3	C	1
9	77	5	27	8	5	10.06	32-59.01	115-32.70	4.85	1.64	18	120	8.0	0.22	0.8	0.7	B	1
0	77	5	29	4	34	43.79	32-54.89	115-47.14	8.29	2.71	22	33	5.7	0.21	0.7	0.9	B	1
1	77	6	2	17	51	26.38	33- 1.47	115-23.23	4.41	2.59	21	71	6.5	0.11	0.3	0.3	B	1
2	77	6	2	18	14	12.21	33- 1.53	115-33.26	4.61	1.80	16	106	6.5	0.10	0.4	0.3	B	1
3	77	6	4	5	45	43.43	33- 1.01	115-34.67	5.86	0.99	10	183	4.2	0.29	2.2	1.2	C	1
4	77	6	4	6	59	16.94	32-59.68	115-33.29	5.84	1.43	16	131	6.7	0.17	0.6	0.7	B	1
5	77	6	4	12	9	48.29	32-48.83	115-26.80	11.62	1.43	11	150	5.4	0.10	0.6	0.6	B	1
6	77	6	10	5	11	58.72	33- 7.27	115-36.49	6.00	1.02	8	101	5.8	0.09	0.6	25.5	C	1
7	77	6	13	15	40	50.25	32-49.16	115-35.57	2.11	2.38	15	99	13.0	0.16	0.7	1.2	C	1
8	77	6	13	23	12	13.25	32-51.70	115-48.79	1.68	1.69	6	74	8.2	0.49	3.8	29.6	C	1
9	77	6	14	9	52	17.59	32-53.66	115-47.32	5.09	1.09	4	157	7.5	0.0			C	1
0	77	6	17	2	1	54.06	32-56.00	115-34.43	2.08	1.47	11	97	7.0	0.33	1.9	8.2	C	1

Y	M	D	H	M	SEC	LAT	LONG	DEP	PAG	N	GAP	CM	RMS	ERR	ERZ	Q	P
77	618	11	26	19.09	32-52.63	115-27.29	3.67	1.01	4	169	2.4	0.02					C 1
77	620	9	51	38.94	32-58.86	115-31.66	4.75	1.22	14	59	8.5	0.10	0.4	0.4	B	1	
77	620	16	38	1.10	32-46.52	115-27.02	6.41	2.23	20	124	9.7	0.28	1.0	2.7	B	1	
77	622	3	4	24.30	32-47.99	115-26.82	5.83	2.29	13	113	7.0	0.12	0.6	0.5	B	1	
77	622	4	57	35.05	32-47.09	115-27.18	4.80	1.69	13	120	8.7	0.39	2.1	2.4	C	1	
77	622	13	45	53.39	32-46.30	115-19.52	4.11	1.93	10	102	10.1	0.16	1.0	1.0	C	1	
77	623	13	36	10.86	33-15.07	115-58.47	5.00	1.01	4	227	35.7	0.03					C 1
77	623	16	46	24.64	32-48.45	115-27.06	7.73	1.98	11	109	6.2	0.10	0.5	0.8	B	1	
77	625	15	56	17.55	33-17.61	115-40.16	5.52	2.19	11	87	7.4	0.13	0.7	0.6	B	1	
77	625	21	20	37.17	33- 3.30	115-33.52	5.09	1.66	12	82	6.4	0.13	0.6	0.6	B	1	
77	626	4	26	52.41	33-17.53	115-39.75	1.92	2.03	11	138	14.0	0.17	1.0	1.3	C	1	
77	626	11	16	24.33	33-17.15	115-39.83	7.10	2.35	19	61	6.7	0.25	1.0	1.4	B	1	
77	626	11	59	53.68	33-17.90	115-40.44	5.07	1.98	17	128	7.9	0.28	1.2	1.0	B	1	
77	626	12	10	41.58	33-17.59	115-40.10	0.45	1.48	7	174	40.2	0.08	0.7	18.6	C	1	
77	626	19	48	55.80	32-55.86	115-31.90	4.28	1.27	10	132	11.7	0.14	0.7	0.8	B	1	
77	627	10	19	0.74	32-56.79	115-49.96	8.82	2.25	14	89	1.3	0.18	0.9	0.8	B	1	
77	627	20	11	38.19	33- 0.72	115-34.40	3.54	1.84	13	88	4.6	0.15	0.7	0.7	B	1	

OF SET
CF JCB