DOE/PC/90756--T5

DOE/PC/90756--T5

DE93 003892

**Research on Thermophoretic and Inertial Aspects of Ash Particle
Deposition on Heat Exchanger Surfaces in Coal-Fired Equipment**

**Daniel B. Rosner
Principal Investigator**

Quarterly Technical Report on: DE-FG22-86 PC 90756

Total Contract Period: 9/1/86 - 8/31/89

Quarterly Period Covered: 9/1/86 - 11/30/86

Attention: J. Hickerson (COTR)

High Temperature Chemical Reaction Engineering Laboratory
Yale University, Department of Chemical Engineering
New Haven, CT 06520 U.S.A.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

1. Introduction

DOE-PETC has initiated at the Yale HTRC Laboratory a systematic three-year experimental and theoretical research program directed toward providing engineers with the data, methods, and rational correlations needed to dramatically improve the generality and accuracy of predictions of inorganic particle deposition rates under typical coal combustion conditions (i.e., those leading to the importance of thermophoretically-enhanced diffusion (submicron mode) and the inertially-enhanced "impaction" (supermicron mode). After a brief statement of objectives (Section 2) we outline our experimental and theoretical progress during this quarterly reporting period (Section 3), with our results summarized in Section 4 and in the references documented in Section 6. Section 5 gives relevant administrative information (personnel, research plans).

2. Background Statement: Objectives

The goal of our research in the area of ash transport is to develop the capability of making reliable engineering predictions of the dynamics of net deposit growth for surfaces exposed to the products of coal combustion. To accomplish this for a wide variety of combustor types, coal types, and operating conditions, this capability must be based on a quantitative understanding of each of the important mechanisms of mineral matter transport, as well as the nature of the interactions between these substances and the prevailing "fireside" surface of the deposit. This level of understanding and predictive capability could be translated into very significant cost reductions for coal-fired equipment design, development and operation.

Our emphasis in the present program: "Research on Thermophoretic and Inertial Aspects of Ash Particle Deposition on Heat Exchanger Surfaces in Coal-Fired Equipment" is on experimentally validating* and developing rational, theoretical methods for predicting the role of inertia and ash particle thermophoresis in determining net deposition rates. We also wish to quantify how simultaneous vapor deposition (eg., alkali sulfate) can influence the sticking and erosion associated with impacting particles. Specifically, as a result of this DOE-PETC

* Our previous DOE-PETC supported experiments have been confined to vapor and submicron particle systems in the absence of inertial phenomena. For an overview of convective mass transfer, see the PI's recent textbook (Rosner, 1986), especially Chapters 6, 8.

supported program, we believe that it will be possible for us to develop:

- a. An understanding of the factors governing impacting particle capture and deposit erosion probabilities, leading to rational correlations.
- b. Clever applications of recent mass transfer theories and available heat and momentum transfer data to develop predictions methods for important practical situations - eg. deep tube bundles ('banks').
- c. Necessary extensions of available particle deposition rate theory: eg. 'eddy impaction' for general nonisothermal turbulent gaseous boundary layers on curved surfaces.

To be able to develop tractable but realistic/rational 'subroutines' to predict the evolution of wall deposits*, it will be necessary to intensify our communication with more empirically oriented engineers/chemists who have the necessary boiler fouling/slagging experience. If we are succesful, we will ultimately be able to recommend economical 'subroutines' (compatible with practical requirements of global computer codes, recent deposition research results and cumulative empirical observations) to predict the evolution of wall deposits for, say, design studies of coal-fired furnaces and boilers.

3. Experimental/Theoretical Research Plan

3.1. Inertial Impaction Experiments Using Optical Techniques and the Free Jet Produced by a Seeded, Pressurized, Microcombustor

To study the behavior of impacting particles over a three-decade particle diameter range (say 10^{-1} - 10^2 μm) at gas velocities up to ca. 10^4 cm/s[‡], Dr. Y. Goldman has designed and

* While beyond the scope of the present program, we believe it will also be timely and necessary to determine the relation between deposit micro-structure (and ancillary thermophysical properties) and deposition conditions (eg., arrival rate mechanisms).

‡ Gas velocities in our seeded premixed flat-flame burners used in our laboratory for studying alkali sulfate vapor and submicron particle deposition (Rosner and Atkins, 1983; Rosner and Kim, 1984; Rosner and Liang, 1986; Liang and Rosner, to appear, 1987) are of the order of only 10cm/s. Under these conditions, inertial effects, of primary interest in the present program, are negligible.

initiated the construction of the micro-combustor based facility shown (schematically) in Fig. 3.1. This micro-combustor is expected to provide a well-defined 5 x 5 mm jet of ca. 1500 K particle-laden gas suitable for both particle sticking and deposit erosion studies. It can be supplied with a monodispersed spray of aqueous droplets (which will simultaneously produce particles and alkali vapors), or the output of the powder feeder for the introduction of larger solid particles (say, $d_p > 20 \mu\text{m}$ diam.). Real-time reflectivity changes and post-mortem microscopy will be used to characterize deposition and erosion rates on initially reflective targets of different geometry. These experiments will be initiated once the construction and preliminary calibration measurements are completed.

Fig. 3.1. Micro-combustor facility (under construction) for the production of high-speed dust-laden gas flows to study impacting particle sticking and deposit erosion (Yale High Temperature Chemical Reaction Engineering Laboratory (12/86)).

3.2. Theoretical Studies

In support of the abovementioned objectives, we have initiated theoretical studies in the following three interrelated areas:

- a. Interaction of inertial- and thermophoretic effects in well-defined laminar 'dusty-gas' flows (Park and Rosner, to appear, 1987).
- b. Self-regulated sticking and deposit erosion in the simultaneous presence of vapor or submicron 'glue' (Rosner and Nagarajan, 1986, a, b).
- c. Use of packed bed and tube-bank heat transfer and friction correlations to provide the basis for future tube-bank fouling predictions (Rosner and Timmins).

These initial studies will be broadened considerably, and the results brought to bear the objectives outlined in Section 2, later in the present program.

4. Results^{*}

During the first three months of Grant DE-FG22-86 PC 90756, we have:

1. Designed and initiated construction of the micro-combustor particle-laden jet facility described in Section 3.1. (see Fig. 3.1.).
2. Initiated theoretical studies of the interaction of inertial and thermophoretic effects, the role of simultaneous vapor arrival in determining particle sticking and erosion probabilities, and mass transport phenomena in deep tube banks (Section 3.2.).

* See, also, the archive publications cited in Section 3, and spelled out in Section 6.

5. Administrative Information

During this 3 month period, the following personnel have contributed to the present program:

Name	Position	Role
D.E. Rosner	Professor ChE, P.I.	Overall program direction
Y. Goldman	Visiting Research Engineer [§]	Microburner facility development
B. Liang	GRA [*]	Burner seeding techniques and laser diagnostics
H.M. Park	GRA [*]	Theory of combined inertial and thermophoretic effects

[§] On leave from Technion-Israel Institute of Technology, Dept. of Aeronautical Engineering.

^{*} Graduate Research Assistant.

During the next quarterly reporting period, our research group will be joined by A. Konstandopoulos (now completing his master's degree dissertation (A. Konstandopoulos, 1987) on the subject of diesel engine particulate emissions control) and M. Timmins, (Yale ChE Department undergraduate senior). We will also submit our important DOE special equipment proposal to provide us with supplementary particle diagnostic equipment which will greatly facilitate the measurements which underly the objectives cited in Section 2. Finally, we will host a visit by a former HTCRES Lab. research collaborator, Dr. S.S. Kim (now at KAIST-Korea) to describe his recent flat-flame burner experiments using (nonuniform size) supermicron powders (S.S. Kim and Y.J. Kim, 1986). Our present theoretical studies (Park and Rosner, to appear, 1987) will offer a means to interpret the combined inertial and thermophoretic effects implied in these recent experiments.

6. References

- Kim S.S., and Kim Y.J. (1986) "Experimental Studies of Particle Deposition by Thermophoresis and Inertial Impaction from Particulate High Temperature Gas Flow", Presented at the 4th Miami Int. Symposium on Multiphase Transport, Dec. 15-17, '86
- Konstandopoulos A. (to appear, 1987) "An Experimental and Theoretical Study of Ceramic Monolith Traps in Conjunction with a Manganese-Copper Fuel Additive for Diesel Particulate Emissions Control", Master's Degree Dissertation, Michigan Technological University
- Rosner D.E., and Atkins R.M. (1983) "Experimental Studies of Salt/Ash Deposition Rates from Combustion Products Using Optical Techniques", in Fouling and Slagging Resulting from Impurities in Combustion Gases, R. Bryers, ed., Engrg Foundation, NY, 469-492
- Rosner D.E., and Kim S.S. (1984) "Optical Experiments on Thermophoretically Augmented Submicron Particle Deposition from 'Dusty' High Temperature Gas Flows", The Chemical Engrg J. 29, No. 3, 147-157
- Rosner D.E., and Liang B. (1986) "Experimental Studies of Deposition Rates in the Presence of Alkali Sulfate Vapor Scavenging by Submicron Particle in Combustion Gas Boundary Layers", Chem. Engrg Communications, (submitted)
- Rosner D.E., and Liang B. (to appear, 1987) "Laboratory Studies of the Deposition of Binary Alkali Sulfate Vapor from Salt-Seeded Combustion Gases Using a Flash-Evaporation Technique", AIChE J. (submitted)
- Rosner D.E., and Nagarajan R. (July 1986) "Toward a Mechanistic Theory of Net Deposit Growth from Ash-Laden Flowing Combustion Gases: Self-Regulated Sticking of Impacting Particles and Deposit Erosion in the Presence of Vapor 'Glue'", Proc. July 1986 NATO Summer School on Physico-chemical Hydrodynamics: Interfacial Phenomena
- Rosner D.E., and Nagarajan R. (August 1986) "Toward a Mechanistic Theory of Deposit Growth from Ash-Laden Flowing Combustion Gases: Self-Regulated Sticking of Impacting Particle in the Presence of Vapo- or Submicron Mist 'Glue'", August revision of original July 1986 manuscript, to be presented at the 1987 AIChE-ASME-ANS National Heat Transfer Conference for a session on High Temperature Heat Transfer, Pittsburgh-PA, 9-12 August 1987

Rosner D.E., and Park H.M. (1987) "Thermophoretic and Inertial Effects on Particle Deposition Rates for Highly Loaded Dusty Gas Systems - Laminar Stagnation Point Flow Between Two Parallel Stationary Disks" (Prepared for submission to Chemical Engrg Sci., Pergamon)

Rosner D.E., (1986) "Transport Processes in Chemically Reacting Flow Systems", Butterworths Publisher, Stoneham, MA

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

DATE
FILMED
12/28/92