DOE/ID/12754--T2

DE90 012432

**Multimegawatt Space
Nuclear Power Supply
Phase I Final Report
Volume III--Annotated Outline of Preliminary
Safety Assessment D180-30619-7**

17 February 1989

Submitted to:
U.S. Department of Energy
Idaho Operations Office
Contracts Management Division
785 DOE Place
Idaho Falls, ID 83402
In response to Contract No. DE-AC07-88ID12754

Approval:

Richard L. Hornung
Phase I Program Manager

Boeing Aerospace
Kent, Washington 98124

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Phase I Multimegawatt Space Nuclear Power Supply Documentation Flow

CONTENTS

	<u>Page</u>
1.0 PRELIMINARY SAFETY ASSESSMENT OUTLINE	1
2.0 SAFETY ASSESSMENT SUPPLEMENT	3
2.1 Reactor Safety	4
2.1.1 Introduction	4
2.1.2 Hazardous Events	4
2.1.2.1 Hazardous Events Pre-Launch	4
2.1.2.2 Hazardous Events on Launch and During Ascent	6
2.1.2.3 Hazardous Events once in Orbit on Disposal	6
2.1.3 Sample Analyses	7
2.1.3.1 Preliminary Hazard Assessment for Criticality	7
2.1.3.2 Failure Modes and Effects for Components Associated with Criticality	7
2.1.3.3 Non-Qualified Fault Trees Associated with Criticality	7
2.2 Autonomous Reactor Core Booster ARC	18
2.2.1 Description	18
2.2.2 Safety Assessment ARCB	18
2.3 Interface and Integration Hazard Assessment	26
2.3.1 Introduction	26
2.3.2 Interface/Integration Hazard Assessment	26

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FIGURES

	<u>Page</u>
2.1.3.1-1 Preliminary Hazard Assessment: Criticality Accident During Transport	8
2.1.3.1-2 Preliminary Hazard Assessment: Criticality Accident During Transport	9
2.1.3.1-3 Preliminary Hazard Assessment: Criticality Accident During Core Assembly or Storage	10
2.1.3.1-4 Preliminary Hazard Assessment: Criticality Accident During Prelaunch Tests	11
2.1.3.1-5 Preliminary Hazard Assessment: Criticality Accident During Launch or Ascent to Initial Orbit	12
2.1.3.2-1 Failure Modes and Effects Analyses: Components Related to Criticality (4 sheets)	13
2.1.3.3-1 Fault Trees: Criticality Related	17
2.2.1-1 MSNPS Design Integrated With the Weapons Platform	19
2.2.1-2 Autonomous Reactor Core Booster Separation Concept	20
2.2.1-3 Autonomous Reactor Core Booster	21
2.2.2-1 MSNPS Sample Preliminary Safety Assessment: ARCB122	22
2.3.2-1 MSNPS Sample Preliminary Safety Assessment: Interface/Integration	26

GLOSSARY

ACRR	Annular Core Research Reactor
ACS	attitude control system
ALS	Advanced Launch System
ALV	advanced launch vehicle
ARCB	autonomous reactor core booster
AS	Allied Signal
BA	Boeing Aerospace
CBGS	confinement by ground surface
CBM	confinement by missile
DBTT	ductile to brittle transition temperature
DDT&E	design, development, test, and evaluation
DIDO	(research reactor at UKAEA - Harwell)
DIPS	dynamic isotope power subsystem
DOD	Department of Defense
EM	electromagnetic
EPS	electrical power system
F&OR	functional and operational requirements
FBR	fast breeder reactor
FET	field effect transistor
FFTF	fast flux test facility
FSAR	final safety analysis report
GCFR	gas cooled fast reactor
HIF	Horizontal Impact Facility
ICS	instrumentation and control system
ICWG	interface control working group
INSRP	Interagency Nuclear Safety Review Panel
IOCC	integrated operations control center
LANL	Los Alamos National Laboratories
LCU	local control units
LEO	low earth orbit
LIM	linear induction motor
LIMRV	LIM research vehicle
LLO	low lunar orbit
LRU	line replaceable unit

MSNPS	Multimegawatt Space Nuclear Power Supply
MTR	materials test reactor
MURAL	(computer code)
NEP	nuclear-electric propulsion
NPS	nuclear power supply
NTR	nuclear thermal rocket
OSTP	Office of Science and Technology Policy
PCM	parametric cost model
PFR	prototype fast reactor
PLR	parasitic load resistor
PRA	probabilistic risk analysis
PSAR	preliminary safety analysis report
PSICS	power system instrument and control subsystem
PSP	power system processor
PV	photovoltaic
RFLSS	radiofrequency laser subsystem
R/M	reliability/maintainability
RRA	Rolls-Royce and Associates
RTG	radioisotope thermoelectric generator
SAE	Science and Engineering
SAR	safety analysis report
SBFEL	space-based free electron laser
SDI	Space Defense Initiative
SER	safety evaluation report
SNAP	Space Nuclear Auxillary Power
SPA	space processor array
SSEPS	space station electrical power system
STEM	(computer code)
STS	Space Transportation System
UC	uranium carbide
UK	United Kingdom
UKAEA	United Kingdom Atomic Energy Authority
UN	uranium nitride
USAR	updated safety analysis report
WBS	work breakdown structure
WIMS	(computer code)

Functional and Operational Requirements	Phase I Final Report
1. INTRODUCTION	vol I sec 1 and 2
1.1 Overview	vol I sec 1 and 2
1.2 Weapon System Interface	vol I sec 2.0, 2.3, 13.3, vol II sec 4.0, 4.1, vol III
1.3 MSNPS Role and Availability	vol I sec 2
1.4 Classified Material	supplement sec 2
1.5 Units	-
2. SCOPE	vol I sec 2, vol II sec 4
3. GENERAL DESIGN REQUIREMENTS	vol I sec 2, vol II sec 4
3.1 Performance Requirements	vol I sec 2, 3.1, 4.1, 5.1, 6.1
3.1.1 Category I	vol I sec 2, 3.1, 4.1, 5.1, 6.1
3.1.2 Category II	-
3.1.3 Category III	-
3.1.4 Design Life	vol I sec 2
3.1.5 Prime Power Electrical Output	vol I sec 5.1, 5.3, 6.1, 6.3, vol II sec 3, 4.6, 4.7, 6.4, 6.5
3.1.6 Reactor Radiation Limits	vol I sec 3
3.1.7 Power System Reliability, Availability, and Maintainability	vol I sec 12, 13 vol II sec 4.2
3.1.8 Fission Product Release	vol I sec 3.1, 3.3
3.1.9 Propulsion Application	vol I sec 14, vol II sec 4.3, 4.9
3.2 Operational Requirements	vol I sec 13
3.2.1 Initial Orbital Assembly	vol I sec 2.0, 10.2, 10.3, 13
3.2.2 Testing	N/A
3.2.3 Startup and Operation	vol I sec 2.2, 3, 4, 5, 6, 13.1
3.2.4 Ready Status	vol I sec 2.2, 3, 4, 5, 6, 13
3.2.5 Operations Phase	vol I sec 2.2, 3, 4, 5, 6, 13.1
3.2.6 Final Shutdown and Disposal	vol I sec 2.2, 13
3.3 System Integration	vol I sec 2, vol II sec 4.1
3.3.1 General Integration Requirements	vol I sec 2.2, vol II sec 4.1
3.3.2 Hydrogen/Thermal Integration (Categories I and III Only)	vol I sec 2, vol II sec 4.9
3.3.3 Structural Integration	vol I sec 2.2, vol II sec 4.0, 4.1
3.3.4 Instrumentation and Control Integration	vol I sec 8, vol II sec 4.8
3.4 System Packaging	-
3.4.1 Launch Vehicle Interface	vol I sec 2, 10
3.4.2 Launch Mass and Volume	vol I sec 10
3.5 Dynamic Requirements	supplement sec 4
3.5.1 Launch Dynamics	vol I sec 3.3, 10.2
3.5.2 Orbital Transfer	vol I sec 2.2
3.5.3 Platform Maneuvering	vol I sec 2.2
3.6 Maintainability and Repair	vol I sec 3, 4, 5, 6, 8, 12.2, vol II sec 4.2
3.7 Materials and Components	vol I sec 3.3, 4.3, 5.3, 6.3, 8, vol II sec 4, 6
4. SPACE ENVIRONMENT	
4.1 Orbits	supplement sec 4
4.2 Space Environment	supplement sec 4
4.2.1 Radiation Fields	supplement sec 4
4.2.2 Meteoroids and Space Debris	vol I sec 2.2, supplement sec 2, 4
4.2.3 Hostile Threats	vol I sec 2.2, supplement sec 2
4.2.4 Atomic Oxygen Interaction	supplement sec 4
4.2.5 Natural Thermal Radiation and Heat Rejection	supplement sec 4
5. SAFETY REQUIREMENTS	vol I sec 9.0, vol II, sec 2, vol III
6. REFERENCES	-

Functional and Operational Requirements Cross-Reference Matrix

MMW-Phase II-U90004-7-R4

1.0 PRELIMINARY SAFETY ASSESSMENT OUTLINE

The preliminary safety assessment report will analyze the potential radiological risk of the integrated MSNPS with the launch vehicle including interface with the weapon system. Most emphasis will be placed the prime power concept design. Safety problems can occur any time during the entire life cycle of the system including contingency phases.

The following is an outline of the intended form of the preliminary safety assessment report, which is to be delivered at the end of phase II. This assessment will be the basis of the safety requirements which will be applied to the design of the MSNPS as it develops in subsequent phases.

The assessment will also focus design activities on specific high-risk scenarios and missions that may impact safety.

The report will consist of three parts as follows:

Reference System Design

This part will consist of summary descriptions of the following:

- a. Mission and flight system summary (if available).
- b. Nuclear reactor (including type of fuel, design requirements, reactor materials and materials properties, radiation field at launch and during operation).
- c. Ground support equipment.
- d. Spacecraft (including location and attachment of nuclear reactor).
- e. Mission profile (if available).
- f. Launch vehicle (including flight safety and tracking plans).
- g. Reference trajectory and flight characteristics (including launch conditions).
- h. Launch site (including demographic, topographic, and meteorological characteristics).
- i. Range and radiological safety operations.
- j. Safety-related systems, subsystems, and components (engineered safety features).

Accident Model

This part of the safety assessment report will contain a description of--

- a. Accident and radiological models and data (including test data and verified and validated computer codes that support the analysis).

- b. Vehicle and reactor failure mode analysis (from prelaunch through final disposition, with a description of the potential accident environments and flight contingency options).
- c. Nuclear power source response to accident environments (including prelaunch, launch, ascent, reentry, breakup, impact, postimpact--both land and water).
- d. Mission failure evaluation (includes accident probabilities and quantity of radioactive material potentially released to provide a risk profile).

Nuclear Risk Analysis

This final part of the preliminary assessment report will be a description of the potential radiological risk of those potential accidents which could involve the MSNPS as supported by the available conceptual design database.

In general, the safety assessment report will consider the following types of accident environments (categorized by mission phase):

Prelaunch, Launch, and Ascent Phases:

- Explosion overpressure.
- Projectile impact.
- Land or water impact.
- Liquid propellant fire.
- Solid propellant fire.
- Sequential combination of the above.

Orbit and/or Flight Trajectory Phases:

- Reentry.
- Land or water impact or collisions in space (meteroids, space debris).
- Post impact environment (land or water).

On-orbit contingency phases will be considered as appropriate.

The safety assessment report will comply with the FYOR Rev. 2, DOE order 5480.1B and meet the criteria of as "low as reasonably achievable" (ALARA) exposure and risk factor.

2.0 SAFETY ASSESSMENT SUPPLEMENT

The Safety Assessment Supplement (SAS) provides details supporting the various safety features cited in Volume I, Section 9. The safety features in Volume I, Section 9 respond to the safety technical specifications and criteria of particular concern to the DOE. In addition to supporting Section 9, the SAS provides a description of the autonomous reactor core booster and the subsequent safety analyses that will support the Phase II safety assessment as described in Volume II, Section 2. Finally, the SAS lists some of the interface/integration hazards found in Phase I. This list of hazards will expand during Phase II, as the MSNPS design evolves.

Since the reactor is the dominate concern of the Boeing team thus far, Section 2.1 of this volume summarizes the hazard analysis performed on the reactor. Rolls-Royce has utilized a variety of hazard analyses methods for their reactor safety assessment: preliminary hazard analyses, failure modes/effects analyses, and fault trees.

The Boeing team's Autonomous Reactor Core Booster (ARCB) concept is summarized in section 2.2. During Phase I we had developed a hazards list associated with this concept. In Phase II we will expand this hazards list as well as assess the design features used to mitigate or alleviate the hazards.

Section 2.3 presents a listing of hazards concerned with the interface and integration of the entire MSNPS. The reactor is not an isolated entity; the reactor supplies hot gas to the turbine to power an entire weapon system. Boeing is uniquely qualified to expand this list of hazards during Phase II because of Boeing IUS experience. Boeing developed the IUS (Inertial Upper Stage) that transports various space shuttle payloads from a lower to a higher orbit. Furthermore, the IUS is transported to its initial orbit by the shuttle or an unmanned rocket. Both transporters offer significant interface and integration hazards. Despite the complexity, Boeing has safety certified the IUS for a variety of missions for numerous customers: DoD, NASA, and the Air Force.

2.1 REACTOR SAFETY

The safety technical specifications and criteria (see Volume I, Section 9 for a listing), specified by DOE, provide a starting point for the safety assessment process.

Specific reactor design features supporting the safety technical specifications are noted in Volume I, Section 9.1, while inherent safety features are noted in Volume I, Section 9.2. The safety assessment process utilized by the Boeing team during Phase I is described in Volume I, Section 9.3. That section also lists additional standards and regulations that Boeing uses to evaluate its design.

This section is a summary of the hazards assessment performed on the reactor. This assessment includes evaluation of the design features incorporated to respond to the safety technical specifications.

2.1.1 Introduction

This section describes the primary hazards during various stages of operation and their potential effects on the reactor system.

2.1.2 Hazardous events

The Boeing team has determined that there will be three possible hazardous scenarios: pre-launch, launch and during ascent, during orbit, or on disposal.

2.1.2.1 Hazardous Events Pre-Launch

During pre-launch the fuel assemblies will exist as individual fuel assemblies and/or assembled in a core matrix.

a. Individual Fuel Assemblies:

- 1) Transport of new fuel modules to the core assembly area at the launch site.
- 2) Storage of the new fuel.
- 3) Core assembly.

b. Assembled in a Core Matrix:

- 1) Installation of the reactor in the launch vehicle.
- 2) Transport to the launch pad.
- 3) Installed in the launch vehicle on the launch pad.

The hazardous events associated with the two pre-launch conditions of the fuel include:

a. Fuel criticalities;

b. Dispersion of toxic and radioactive material.

The major hazard during the transport of new fuel modules prior to core assembly is inadvertent prompt criticalities. To mitigate these hazards the fuel will be transported in containers that meet all transport regulations. Absorber material will be built into the transport containers to prevent criticality on flooding.

Criticalities are also a problem during core assembly and fuel storage. Criticalities are avoided by assembling and storing the fuel modules under strictly controlled conditions. Container assembly will be performed by trained staff following a well defined procedure. The assembly and storage areas will be constantly monitored to provide early warning of potential criticality.

Pre-assembly bench-mark experiments addressing criticality will have determined:

- a. Control Worths;
- b. Core flux distributions;
- c. Temperature coefficients;
- d. The effect of flooding.

Following core assembly, calibration of the critical rod positions will be required prior to the reactor being fitted into the launch vehicle. This calibration will require taking the reactor critical at a very low power level. Accidents will be avoided by a controlled and fully instrumented approach to criticality. The reactor control system will prevent equipment failures that could cause a system fault or operator error that would result in a criticality accident.

Once the core assembly is fixed in the reactor pressure vessel, criticalities could occur if both the control rods are ejected from the core and the reflector wings become closed. Alternatively, the rods could be ejected and the core flooded with a liquid. Both the rod and reflector wings will be independently locked in position following core assembly. Absorbing material has been incorporated into the fuel assemblies to prevent flooding alone to lead to criticality in the core. Additionally, the amount of liquid that can fill the reactor pressure vessel has been limited by filling the empty space with beryllium. Furthermore, additional features to protect the control rods and reflector wings from external hazards will be further considered.

The above scenarios could only occur following events that would lead to a large scale disruption of the reactor assembly. The events that have been identified in this assessment, as being capable of disrupting the core, are listed below:

- a. Dropping of the reactor assembly while it is fitted into the launch vehicle;
- b. Toppling of the launch vehicle while being transported to the launch site or while on the launch site;

c. Large fire or explosion on the launch pad or during transport to the launch site, including the effects of the resulting shrapnel and overexposure.

A large launch pad fire or explosion could also cause aerosolization and dispersion of the beryllium, which is toxic, and uranium 235. Since the reactor will not have been operated, there will be no significant fission or activation products. Approximately 0.5 Curie (Ci) of uranium 235 will be present as radioactive material.

2.1.2.2 Hazardous Events on Launch and During Ascent

The hazardous events at launch, prior to lift off from the launch pad, will be the same as those described in Section 2.1.2.1.

As a result of a failed launch the vehicle can be subject to a crash with the ground leading to reactor criticality. However, a criticality could only occur if both the control rods are ejected and the reflector wings close, or the rods are ejected and the core becomes flooded with a liquid.

Core compaction following an impact with the ground will increase the potential for criticality to occur, but will not on its own cause criticality.

An explosion while in flight could cause aerosolization and dispersion of beryllium; in this instance the toxic and radioactive material will be more widely dispersed.

2.1.2.3 Hazardous Events Once in Orbit or On Disposal

Once the reactor has been operated, there will be fission products within the fuel cladding. Any accident that leads to a re-entry of the reactor could lead to a failure of the cladding either during re-entry or on subsequent impact with the ground. Failure of the fuel cladding on or following re-entry will result in a release of fission products to the earth's atmosphere. The fission product inventory will decay following reactor operation; therefore, the magnitude of the radiological consequences will depend on the time from the last period of reactor operation.

Once the reactor has operated, radioactive fission products will build-up in the fuel, and other reactor components will also become activated. Reentry of the reactor, even if the cladding remains intact, will result in the radioactive fuel and activated reactor components being a source of alpha, beta and gamma radiation. The radiological consequences will depend on the time elapsed since the last period of reactor operation.

As with a failure during launch, an accident that leads to reactor reentry and a subsequent impact with the ground has the potential to lead to a criticality. The reactor incorporates features which should allow the reflector wings to be ejected prior

to re-entry, and the rods locked in the inserted position. If a system failure prevents the reflectors from being ejected, it is most likely that the reflectors will burn-up during re-entry. The reactor core ejection system will also reduce the potential for a re-entry to occur.

2.1.3 Sample Analyses

A brief sample of the analyses methods follow. The analyses included are those catering to criticality alone. Furthermore, only a sample of each method are included.

The final report for Phase II will include the analyses performed for all safety hazards associated with the MSNPS program.

2.1.3.1 Preliminary Hazard Assessment for Criticality

Reference: Figures 2.1.3.1-1 to 2.1.3.1-5.

2.1.3.2 Failure Modes and Effects for Components Associated With Criticality

Reference: Figure 2.1.3.2-1.

2.1.3.3 Non-Quantified Fault Trees Associated With Criticality

Reference: Figure 2.1.3.3-1.

Hazardous event	Cause	Proposed corrective preventative measures	Remarks
<p>Criticality accident during transport</p> <p>Leading to --</p> <ul style="list-style-type: none"> ● High doses from fission spike in the form of neutron and gamma rays ● Fuel vaporized leading to the release of fission products into an active cloud ● Direct dose and ingestion hazard to personnel from alpha, beta, and gamma radiation 	<p>Truck accident during delivery to site</p> <p>Failure of transport containers due to the impact plus flooding of the reactor vessel</p> <p>Load drop while the reactor is being lifted into the launch vehicle</p>	<p>Fuel transported in transport containers that are fully cleared to satisfy the transport regulations</p> <p>Absorber material built into the fuel as a passive safeguard to help prevent a criticality accident if the core is immersed in water</p> <p>Additional absorber material will be incorporated into the transport containers to prevent criticality on flooding</p> <p>High-integrity lifting mechanism should be used</p> <p>Control rods locked in the inserted position</p> <p>Reflector wings will be independently locked in the open position</p> <p>Fully welded reactor pressure vessel</p>	<p>Extremely unlikely that a road transport accident would involve sufficient liquid that a criticality could occur</p> <p>Fuel loading of the transporter will be such that there will be insufficient fuel for a criticality to occur unless the fuel is immersed in water</p> <p>Beryllium reflector will be transported to the launch site separately from the fuel</p> <p>Transport in accordance with 10CFR71</p>

Figure 2.1.3.1-1 Preliminary Hazard Assessment: Criticality Accident During Transport

Hazardous event	Cause	Proposed corrective preventative measures	Remarks
Criticality accident during transport (continued)	<p>Tip over of launch vehicle during transport to the launch pad</p> <p>Either –</p> <ul style="list-style-type: none"> ● Withdrawal of the control rods and closing of the reflector wings caused by the impact or an explosion <p>or</p> <ul style="list-style-type: none"> ● Withdrawal of the control rods due to the impact, plus immersion of the core in liquid (liquid propellant) 	<p>Control rods locked in the inserted position, and the reflector wings independently locked in the open position prior to reactor operation</p> <p>Fully welded pressure vessel</p> <p>As above, plus:</p> <ul style="list-style-type: none"> ● Absorber material built into the core to help prevent criticality in the event of immersion in water ● The amount of liquid that can fill the pressure vessel has been limited by filling empty spaces with beryllium ● Tight fuel pin pitch reduces the amount of voidage in the core 	

MMW-301

Figure 2.1.3.1-2 Preliminary Hazard Assessment: Criticality Accident During Transport

Hazardous event	Cause	Proposed corrective preventative measures	Remarks
<p>Prompt criticality during core build or storage prior to build</p> <p>Leading to —</p> <ul style="list-style-type: none"> • High doses from fission spike in the form of neutron and gamma rays • Fuel vaporized leading to the release of fission products into an active cloud • Direct dose and ingestion hazard to personnel from alpha, beta, and gamma radiation 	<ul style="list-style-type: none"> • Inadequate calculations and/or incorrect validation analysis • Incorrect procedure 	<p>Benchmark experiments</p> <p>Independent analysis of experiments by experienced physicists</p> <p>Well-defined assembly procedure undertaken by expert staff</p> <p>Fully controlled and instrumented procedure</p>	<p>Core assembly will take place at the launch site</p>

MMW-302

Figure 2.1.3.1-3 Preliminary Hazard Assessment: Criticality Accident During Core Assembly or Storage

Hazardous event	Cause	Proposed corrective preventative measures	Remarks
<p>Criticality accident during pre-launch tests</p> <p>Leading to –</p> <ul style="list-style-type: none"> • High doses from fission spike in the form of neutron and gamma rays • Fuel vaporized, leading to the release of fission products into an active cloud • Direct dose and ingestion hazard to personnel from alpha, beta, and gamma radiation 	Control system fault or operator error	<p>Controlled approach to criticality based on previous experiments in accordance with written procedures</p> <p>Control systems will be designed to prevent operator error resulting in a criticality</p> <p>Control system will be designed to prevent control system faults resulting in a criticality</p>	<p>Calibration of the critical rod positions will be required prior to launch. This will be done before the reactor is fitted into the launch vehicle</p> <p>Criticality calculation carried out using MONK Monte Carlo code</p>

MMW-303

Figure 2.1.3.1-4 Preliminary Hazard Assessment: Criticality Accident During Prelaunch Tests

Hazardous event	Cause	Proposed corrective preventative measures	Remarks
<p>Criticality accident during launch or ascent to initial orbit</p> <p>Leading to –</p> <ul style="list-style-type: none"> ● High doses from fission spike in the form of neutron and gamma rays ● Fuel vaporized leading to the release of fission products into an active cloud ● Direct dose and ingestion hazard to personnel from alpha, beta, and gamma radiation 	<p>On launch pad, pre- or during launch</p> <p>Launch pad fire or explosion</p> <p>Withdrawal of control rods and immersion in liquid – Fuel or liquid hydrogen</p> <p>or</p> <p>Withdrawal of control rods and closing or reflector wings</p> <p>During ascent</p> <p>Failure during launch resulting in an impact on land or with the sea-withdrawal of control rods and closing of the reflector wings</p> <p>or</p> <p>Withdrawal of control rods and immersion in liquid or moist soil</p>	<p>Absorber material built into the fuel bundles to maintain the core subcritical in the event of immersion in liquid</p> <p>The amount of liquid that can fill the pressure vessel has been limited by filling empty space with beryllium</p> <p>Fully welded pressure vessel should provide a degree of protection and containment</p> <p>Control rods locked in the inserted position and wings independently locked in the open position</p> <p>As above</p>	<p>Core compaction increases the potential for a criticality accident to occur, but will not on its own cause a prompt criticality</p>

MMW-304

Figure 2.1.3.1-5 Preliminary Hazard Assessment: Criticality Accident During Launch or Ascent to Initial Orbit

Component: controls rods plus actuators and locking mechanisms

Hazard	Failure mode	Effects	Effects on other equipment	Consequences	Safeguards
Operator error	Failure due to incorrect design or assembly	a) Rod (or rods) fail in when required out or fail out when required in	Unable to maintain or take the core critical Unable to shut down the reactor or maintain the reactor shutdown	Loss of power availability. Potential for core damage or criticality accident and fuel product release to space environment	Prelaunch prototype and rig testing. All rods out will not be sufficient to take the reactor critical, wings will have to be in as well Rods and reflector wings mechanically lock in position on launch. Wings will be ejected on final disposal.
Equipment failure	Failure due to thermal/mechanical shock or fatigue mechanical vibration	As a) above, plus rod locking mechanisms jam	As above	As above	A single rod or pair of rods jamming will not prevent operation of the reactor.
Shock loads	Failure due to shock during launch or transfer to initial orbit	Rods ejected during launch or rod control gear fails because of shock imposed	As above	As above	As above, plus rods will be designed to withstand launch shock requirements
Flood	On launch disruption of vessel and flooding by liquid propellant. Or impact with the sea during launch or accidental re-entry.	Flooding of the core.	Thermalization of neutrons in the core.	Potential for criticality accident.	Rods locked into position on launch and following final disposal. Absorber material built into core to prevent criticality when immersed in water. Empty space in pressure vessel filled with beryllium to limit the space that can be flooded.
Environmental conditions	Failure due to thermal conditions within the core.	Rods fail or jam	Loss of control of reactor	Loss of power availability	Rods designed to withstand core environment
Fire	During transport to site or on launch.	Failure leading to withdrawal of rods.	Increase in core reactivity	Potential for criticality accident	Rods mechanically locked in position

MMW-305

D180-30619-7

Figure 2.1.3.2-1 Failure Modes and Effects Analyses: Components Related to Criticality (Sheet 1 of 4)

Component: controls rods plus actuators and locking mechanisms

Hazard	Failure mode	Effects	Effects on other equipment	Consequences	Safeguards
Impact	Failure due to— a) Projectiles produced by explosive failure on launch b) Impact with the ground following failure during ascent or accidental reentry c) Failure due to impact from space debris or meteorites	For a) and b) Wings shut when required to be open For c) Loss of control of wing or wings	Increase in core reactivity	Potential for prompt criticality accident	Closing all reflector wings is not sufficient on its own to cause a criticality, rods will have to be out as well. Reactor and reflector wings mechanically locked in position on launch. Wings will be ejected on final disposal For c) Critical components armored to protect against space debris. A single wing failing should not cause loss of power availability. Reflector wings will fail safe.
Explosion	Failure due to— a) Explosion on launch or ascent or during transport b) From weapon during operation	For a) Dispersion of beryllium b) Wings shut when required to be open. Loss of control of wing or wings	As above	As above plus for a) Dispersion of toxic material	Transport container will be designed to withstand credible explosions
Radiation	—	—	—	—	—
Chemical	Corrosion due to atomic oxygen	Loss of control of wing or wings	Loss of reactor control	Loss of power availability	Critical components coated to prevent oxidation. A single wing failing will not cause loss of power availability.
Storms	—	—	—	—	Protected by transport container and launch vehicle
Electro-magnetic	Interference with actuators during operation or standby	—	—	—	Actuators will be designed to operate in the anticipated electromagnetic environment

MMW-308

D180-30619-7

Figure 2.1.3.2-1 Failure Modes and Effects Analyses: Components Related to Criticality (Sheet 2 of 4)

Component: reflector wings plus actuators

Hazard	Failure mode	Effects	Effects on other equipment	Consequences	Safeguards
Operator error	Failure due to incorrect design or assembly	Wing (or wings) fail open when required shut or wing or wings fail shut when required open	Unable to maintain or take the core critical Unable to shut down the reactor or maintain the reactor shutdown	Loss of power availability. Potential for fuel product release to space environment	Prelaunch prototype and rig testing. Closing reflector wings will not be sufficient on its own to cause a criticality; rods and reflector wings mechanically locked in position on launch. Wings will be ejected on final disposal. A single reflector wing jamming will not prevent operation of the reactor.
Equipment failure	Failure due to thermal/mechanical shock, fatigue, vibration, etc.	As above	As above	As above	As above, plus no movement normally required from the reflectors once a stable orbit has been achieved. Reflector wings will fail safe.
Shock loads	Failure due to shock during launch or transfer to initial orbit	As above	Unable to take core critical or unable to maintain the reactor shutdown	As above	As above, plus wings will be designed to withstand launch shock loads specified in the Functional and Operational Requirements document.
Flood	On launch, disruption of vessel and flooding by liquid propellant. On impact with the sea during ascent or accidental re-entry.	Flooding of core	Thermalization of neutrons in the core	Potential for prompt criticality accident	Rods locked into position on launch and followig final disposal. Absorber material built into core to prevent criticality when immersed in water.
Environmental conditions	Cold welding of moving parts and oxidation by atomic oxygen	As equipment failure	As equipment failure	As equipment failure.	Moving parts will be coated to prevent cold welding and prevent oxidation by atomic O ₂ .
Fire	During transport to site or on launch	a) Failure leading to reflector wings closing b) Melting of beryllium	Increase in core reactivity	a) Potential for prompt criticality accident b) Dispersion of toxic material	Wings mechanically locked in position during launch. Wings transported separately to site from the core. Transport container will be designed to withstand all credible magntiude fires.

MMW-307

D180-30619-7

Figure 2.1.3.2-1 Failure Modes and Effects Analyses: Components Related to Criticality (Sheet 3 of 4)

Component: controls rods plus actuators and locking mechanisms

Hazard	Failure mode	Effects	Effects on other equipment	Consequences	Safeguards
Impact	Failure due to a) Projectiles produced by explosive failure on launch b) Impact with the ground following failure during launch or accidental reentry c) Failure due to impact from space debris	For a) and b) rods out when required to be in c) loss of control of rods d) Failure of control rod drive housing could lead to rod injection	Loss of reactor control	For c) Loss of power availability For a), b), and d) Potential for prompt criticality and hence fuel product release to space environment	Rods mechanically locked in position on launch and on final disposal. Failure of one rod insufficient to prevent reactor operation. Rods protected from space debris by pressure vessel and casing around control rod drive mechanisms which will be armored against space debris. Rod latches prevent rod withdrawal
Explosion	Failure due to a) Explosiion before or during launch b) From weapon during operation	For a) Rod out when required in. b) Loss of control of rods	As above	For a) prompt criticality b) Loss of power availability. Potential for prompt criticality and hence fuel product release to space environment.	As above
Radiation	—	—	—	—	—
Chemical	—	—	—	—	Rods will be designed to operate in reactor environment
Storms	—	—	—	—	Protected by transport and launch vehicle
Electro-magnetic	Interference with control rod drive motors during operation or standby	Loss of control of rods	Loss of reactor control	Loss of power availability potential for core damage, and hence fuel product release to space environment	Rod control motors will be screened to protect them from the anticipated electromagnetic environment

MMW-306

D180-30619-7

Figure 2.1.3.2-1 Failure Modes and Effects Analyses: Components Related to Criticality (Sheet 4 of 4)

Figure 2.1.3.3-1 Fault Trees: Criticality Related

MMW-310

2.2 AUTONOMOUS REACTOR CORE BOOSTER ARCB

2.2.1 Description

In addition to a failed launch, another catastrophe would be the failure of the vehicle to reach required orbit. For that scenario the Boeing team is providing an autonomous reactor core booster system to boost the core to a storage orbit, where it would not reenter earth's atmosphere for at least 300 years. Furthermore, the ARCB will provide for ultimate disposal of the reactor.

The booster system basically consists of twelve, solid propellant rocket motors strapped to the astromast container (see fig. 2.2.1-1). Separation planes are provided at the base of the astromast container, the base of the reflector wings support ring, and the coolant lines at the base of the reactor bottle (see fig. 2.2.1-2). These joints are held together with explosive bolts. Spring loaded ejection plungers, located on the primary support ring of the MSNPS structure (see fig. 2.2.1-2) provide the separation force. Figures 2.2.1-1 and 2.2.1-3 show the separated configuration. An attitude control system (ACS) is located in the bays at the base of the rocket motors along with the necessary electronics.

2.2.2 Safety Assessment ARCB

The following hazards list is an initial assessment of the hazards associated with the ARCB. During Phase II, this list will be refined.

A sample hazard table from the ARCB set of hazard tables is included, Figure 2.2.2-1.

Figure 2 2 1-1 MSNPS Design
Integrated With
the Weapons
Platform

Figure 2.2.1-2 Autonomous Reactor Core Booster Separation Concept

Figure 2 2.1-3 Autonomous Reactor Core Booster

D180-30619-7

Hazard	Cause	Proposed corrective/preventive measures	Remarks
Inadvertent ignition of solid rocket motors (SRM) prior to ARCB separation	1. Electrical component failures	1a. SRM firing circuits shall have electrical inhibits and monitoring per MIL-STD-1574A 1b. A safe and arm (S&A) shall provide mechanical interrupt in pyrotechnic train immediately downstream of initiators 1c. Firing circuit components shall be qualified to applicable environments as specified in ICD-TBD 1d. Sneak circuits shall not be allowed to defeat the system inhibits	
	2. Operator errors	2a. Precautions and safety equipment for storage, handling, transportation, maintenance, assembly, and installation preclude exposure of SRM to fire and sparks 2b. Hazardous procedures shall be approved and controlled by BA Safety 2c. Electrical connection of SRM S&A's shall be performed as late as possible in launch preparation 2d. Firing circuit design shall physically lock out flight or ground crew commanding of premature SRM ignition	
	3. EM/EMC	3a. Ordnance circuits shall be designed in accordance with MIL-STD-1576 3b. Pyrotechnic train, SRM igniter, and SRM propellant shall not be susceptible to extraneous electrical stimuli	

MMW-311

Figure 2.2.2-1 MSNPS Sample Preliminary Safety Assessment: ARCB122

HAZARD LIST
AUTONOMOUS REACTOR CORE BOOSTER (ARCB)

1. Propulsion Subsystem

- a. Inadvertent ignition of solid rocket motors (SRM) prior to ARCB separation could damage/destroy the launch vehicle or injure personnel—Caused by inadvertent or spurious fire signals; electrostatic discharge; self-initiation false start caused by ARCB/primary support ring separation switch failure; extraneous electrical stimuli (radio frequency (RF) energy/electromagnetic interference (EMI)); SRM propellant, explosive train or igniter auto-ignition; failure of SRM or Safe & Arm device to withstand exposure to shock and/or vibration; or lightning strike.
- b. Attitude control system leakage or rupture could damage/destroy the launch vehicle or injure personnel—Caused by induced environments, activation of dormant contamination, tank fatigue, failed-on tank heaters, inadequate tank safety factors, inadequate testing, or adiabatic compression detonation.
- c. Attitude control system (ACS) inadvertent/premature activation could damage the launch vehicle by collision or cause personnel injury—Caused by inadvertent ACS activation commands prior to ARCB achieving a safe separation from the spacecraft.
- d. Failure of the flight termination system (FTS) to perform the SRM destruct function could jeopardize public/private property or the ecology—Caused by electrical component failures or uplink or vehicle-generated command failure.
- e. Inadvertent FTS activation could result in launch vehicle destruction or personnel injury—Caused by inadvertent or spurious fire signals; electrostatic discharge; self-initiation caused by break-up switch failure; extraneous electrical stimuli (RF/EMI); destruct charge, explosive train or igniter auto-ignition; failure of FTS to withstand exposure to mechanical environment; or lightning strike.
- f. ARCB orbital decay and errant re-entry could result in hazard to public—Caused by failure of the SRM's to ignite, low or incomplete impulse, tumbling, erratic attitude during firing, or stable misaligned firing.

2. Electrical System

- a. Failure of avionics could result in premature issuance of or absence of safety-critical commands—Caused by electrical component failure, uplink or vehicle-generated commands, or software errors.
- b. Battery overpressure/leakage could result in release of electrolyte and explosive gases which could cause equipment corrosion and possible fire and explosion leading to launch vehicle damage and/or personnel injury—Caused by short circuits, vent failures, or exposure to excessive environments.
- c. Rupture of sealed electronic units could damage adjacent equipment, injure personnel, and create fragments/debris within the launch vehicle—Caused by failure to account for pressure differential created during ascent.
- d. Ignition of flammable atmosphere within the launch vehicle compartment could result in launch vehicle damage or personnel injury—Caused by arcing of electrical contacts during power switching or high temperature surfaces.
- e. Ignition of flammable materials could result in flame propagation and damage to the launch vehicle or personnel injury—Caused by high temperatures of electrical components in the vicinity of a flammable material, electrical system faults, or conductive contaminant shorts across exposed electrical terminals.
- f. Inadvertent RF radiation in excess of allowable levels given in the applicable interface control drawing could interfere with launch vehicle electronics and lead to launch vehicle loss—Caused by premature activation of ARCB transmitter during on-orbit checkout prior to proper accommodation of RF transmission.
- g. EMI generated by the ARCB in excess of the allowable levels given in the applicable interface control drawing could interfere with launch vehicle electronics and lead to launch vehicle loss—Caused by inadequate design controls and test.

3. Structures

- a. Failure of primary structure could result in launch vehicle damage, release of the reactor, or personnel injury—Caused by insufficient design strength, failure to account for unique requirements of high-strength parts, failure of stress corrosion sensitive parts, or propagation of pre-existing flaws.

4. Materials

- a. Material flammability could result in flame propagation from the source to cause extensive launch vehicle damage or personnel injury—Caused by inadequate selection of materials or insufficient clearance from heat sources.

5. Mechanical Systems

- a. Inadvertent separation of the ARCB from the spacecraft could cause catastrophic damage to the launch vehicle, spacecraft or the reactor—Caused by structural failure of the mechanical interface, inadvertent/premature/spurious separation signals, electrostatic discharge initiation of electroexplosive devices (EED), RF energy/EMI, or autoignition of separation EED's.
- b. ARCB collision with the spacecraft could cause catastrophic damage to the reactor and/or prevent achievement of safe parking orbit—Caused by failure of thrust vector control during SRM firing, premature ACS thrusting during deployment of the ARCB from the spacecraft, excessive tip-off during deployment due to ejection plunger spring failure or out of tolerance condition, spacecraft maneuvering during ARCB deployment, or incomplete action of separation devices.

2.3 INTERFACE AND INTEGRATION HAZARD ASSESSMENT

2.3.1 Introduction

Integration issues affecting the reactor and other systems are recognized early in the design process to ensure the safety of the complete space package: reactor, power conditioning, platform weapon, and housekeeping power system (SP-100).

Boeing Aerospace has extensive experience with complex integration tasks: AWACS, ALCM, and other programs are well known examples of complex integration tasks. Furthermore, NASA has recognized Boeing's integration capability by selecting Boeing to build various modules for the space station. In addition, the Air Force recently awarded Boeing one of the contracts for the advanced launch systems (ALS). This award was the result of Boeing integration of propulsion, fuel storage, and avionics into a next generation advanced launch system (ALS).

2.3.2 Interface/Integration Hazard Assessment

An abbreviated listing of interface/integration hazards is provided below. Figure 2.3.2-1 provides an example of reactor cooling interface/integration hazards.

Hazard	Cause	Proposed corrective/preventive measures	Remarks
Interface/Integration hazard Loss of reactor cooling	Disruption in hydrogen supply: a) Coolant line leak/break due to space debris or system generated missile b) Control/command failure c) Depleted coolant supply d) Other	1. Shield coolant flow paths from space debris or system-generated missiles 2. Provide voting logic to avoid command errors 3. Provide auxiliary hydrogen supply if necessary	Safety Technical Specifications: reactor power control and reactor cooling. Additional Safety Concerns: control of radiation exposure for both personnel and environment. Codes: Supporting criteria: analysis, literature, etc.

MMW-312

Figure 2.3.2-1 MSNPS Sample Preliminary Safety Assessment: Interface/Integration

Reactor cooling

Reactor cooling is dependent not only on the reactor system, but also on platform supply.

- a. Coolant Line Leak/Break disrupts flow to the reactor—Caused by space debris impact on coolant lines; platform generated missile/fragment impact on coolant supply system (flow line and system supply); space transportation system (shuttle) or ALS impact on coolant supply system.
- b. Control/Command failure closes valves, turns off pumps, and misrepresents hydrogen supply—Caused by failure of control system to respond to control signals prompted by either platform/reactor control system or ground intervention; subsystem failure to respond to control signal, i.e., valve failure, pump failure, level gauge failure.
- c. Depleted Coolant supply disrupts flow—Caused by failure of quantity measuring system; failure of original or resupply to fill tanks to specific level; leakage in supply system and failure of measuring system.

2. House-keeping power

- a. SP-100 fails to provide power to reactor control system—Caused by SP-100 system failure; failure of power transfer system from SP-100 to main platform power bus; failure of platform power bus.
- b. Platform power bus fails to distribute power to loads—Caused by hardware failure of platform power bus; excessive load on power bus prompts bus to stop all power to stabilize or identify excessive load; instrumentation fails prompting the platform power bus to turn off loads.

3. Reactor Coolant Temperature Variation

- a. Weapon system excessively heats hydrogen coolant flow—Caused by unexpected weapon performance; disruption in flow to weapon; unexpected flow path alteration in weapon system; leakage in coolant flow path of weapon system.
- b. Coolant storage temperature surpasses expected temperature variation—Caused by failure of coolant insulation; failure of coolant storage instrumentation; failure of coolant refrigeration system.
- c. Unexpected Joule-Thompson cooling of hydrogen flow—Caused by leakage of coolant flow lines; unanticipated valve pressure drops; line restrictions in coolant flow path.

4. Reactor Disposal Failure

- a. ARCB fails to separate core from reactor—Caused by failure of core separation system to initiate or complete the separation process; failure of ARCB to maneuver core out of reactor; entanglement of ARCB with other platform hardware.
- b. ARCB fails to place core in safe orbit—Caused by failures in ARCB system: see Section 2.2 of this safety assessment supplement.

5. Weapon/Platform Failure

- a. Projectiles emanate from weapon and impact reactor—Caused by weapon system catastrophic failure; by failure of adversary projectiles to hit weapon and continue through to reactor.
- b. Platform structure fails to support weapon or reactor—Caused by structural fatigue or other material failure; dynamic loads exceeding expected structural loads; failure of space construction to assemble structure properly.
- c. Electromagnetic interference from weapons prompt control failure on reactor—Caused by failure to account for weapon electromagnetic fields in combination with structure, MSNPS reactor, SP-100, and platform power bus; unexpected performance of weapon causing transient electromagnetic fields.

6. SP-100 Radiation

- a. SP-100 radiation degrades MSNPS control performance and/or mechanical systems—Caused by inadequate shielding of SP-100; inadequate shielding of MSNPS control systems; unexpected radiation/material interactions in MSNPS.
- b. SP-100 radiation adversely impacts weapon system—Caused by inadequate shielding of SP-100; inadequate shielding of weapon system components; unexpected SP-100 location.