DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

UCRL--53723

DE87 003972

**The Final Report of Static
and Dynamic Analyses
on the
MFTF-B Axicell Vacuum
Vessel System**

D. S. Ng

Manuscript date: September 1986

LAWRENCE LIVERMORE NATIONAL LABORATORY
University of California • Livermore, California • 94550

Available from: National Technical Information Service • U.S. Department of Commerce
5285 Port Royal Road • Springfield, VA 22161 • A03 • (Microfiche A01)

MASTER

RECEIVED
SEP 23 1987
NATIONAL TECHNICAL INFORMATION SERVICE
SPRINGFIELD, VA 22161

Contents

Abstract	1
1. Introduction	1
2. Objective of the Independent Analyses	2
2.1 Verification of the PDM Engineering Design	2
2.2 Verification of Modeling Assumptions by Additional Analyses	2
2.3 Provision of Magnet Hanger and Vessel Support Design Loads for Corresponding Design Contractors	2
2.4 Provision of Structural Responses of Magnet and Vessel for Attached Equipment Design	3
2.5 Input for the Soil-Structure Interaction Analyses	3
3. Geometric Configuration of MFTF-B	3
3.1 Vacuum Vessel System	3
3.2 Superconducting Magnet System	4
3.3 Foundation Array	4
4. Description of LLNL Finite-Element Model	5
4.1 Realistic Modeling Assumptions	5
4.2 Proper Element Type	7
4.3 Appropriate Model Size for Computer Analysis	10
4.4 Adequate Model Detail	10
5. Quality Assurance of the Finite-Element Model	11
5.1 Model Configuration Check by Graphics	11
5.2 Modeling Assumption Check by Detailed Investigation	13
5.3 Force Equilibrium Check in Static Behavior	13
5.4 Dynamic Characteristics Check in Modal Extraction	13
6. Static Analysis	14
6.1 Gravity Load	14
6.2 Vacuum Pressure Load	14
6.3 Magnetic Load under Normal Operation	14
6.4 Magnetic Load under Fault Condition	17
6.5 Magnetic Load Caused by Misalignment of Magnets	17
6.6 Environmental Thermal Load	17
6.7 Magnet Cool-Down Thermal Load	17
7. Dynamic Analyses	17
7.1 Damping Coefficient	18
7.2 Design Response Spectrum	18
7.3 Modal Truncation	19
7.4 Computer Program for Dynamic Analysis	19
7.5 Dominant Mode Shapes	20
8. Evaluation of Analysis Results	28
8.1 Load Combination Scheme	28
8.2 Allowable Design Stress Criteria	28
8.3 Model Deformation	28
8.4 Magnet Hanger and Strut Load	35
8.5 Vessel Foundation Load	39
8.6 Efficiency of Mode Selection Methods	47
9. Result Comparison of the PDM and LLNL Models	47
9.1 Static Behavior	47
9.2 Dynamic Behavior	48
10. Comparison of the Results for Fixed-Base Analyses and Soil-Structure Interaction Analysis	50
10.1 Model Revision	50
10.2 Reasonable Correlation between Two Models in Dynamic Characteristics	52
10.3 The Translational Acceleration Responses of SSI Analysis	52

10.4	Relative Seismic Displacements between the Vessel and the Vault Walls	54
10.5	Force and Moment Evaluation	55
11.	Summary	63
12.	Acknowledgments	65
References		66

The Final Report of Static and Dynamic Analyses on the MFTF-B Axicell Vacuum Vessel System

Abstract

The Mirror Fusion Test Facility (MFTF-B) at Lawrence Livermore National Laboratory (LLNL) is a large-scale, tandem-mirror-fusion experiment. MFTF-B comprises many highly interconnected systems, including a magnet array and a vacuum vessel. The vessel, which houses the magnet array, is supported by reinforced concrete piers and steel frames resting on an array of foundations and surrounded by a 7-ft-thick concrete shielding vault. The Pittsburgh-Des Moines (PDM) Corporation, which was awarded the contract to design and construct the vessel, carried out fixed-base static and dynamic analyses of a finite-element model of the axicell vessel and magnet systems, including the simulation of various loading conditions and three postulated earthquake excitations. Meanwhile, LLNL monitored PDM's analyses with modeling studies of its own, and independently evaluated the structural responses of the vessel in order to define design criteria for the interface members and other project equipment. The assumptions underlying the finite-element model and the behavior of the axicell vessel are described in detail in this report, with particular emphasis placed on comparing the LLNL and PDM studies and on analyzing the fixed-base behavior with the soil-structure interaction, which occurs between the vessel and the massive concrete vault wall during a postulated seismic event. The structural members that proved sensitive to the soil effect are also reevaluated.

1. Introduction

The Mirror Fusion Test Facility (MFTF-B) at Lawrence Livermore National Laboratory (LLNL), is a large-scale, tandem-mirror-fusion experiment. In the magnetic fusion concept, a fusion reaction is created by injecting beams of energetic neutrons into a high-temperature plasma that is confined in a vacuum chamber by magnetic fields. The magnetic fields are produced at each end by a tandem-mirror cell containing a pair of C-shaped magnets called the Yin-Yang pair. The central cell of the plasma chamber experiences a solenoidal magnetic field. The vacuum environment provided by the vessel serves to minimize heat conduction from the high-temperature plasma. The vacuum pressure in this cylindrical vessel is maintained by a pumping system.

This experimental facility is composed of many highly interconnected systems, such as the magnet array, vacuum vessel, cryogenics, diagnostics, vacuum, and various electrical systems. Each system is designed and constructed by a different contractor. The magnet array is housed inside the vessel, which is supported by reinforced concrete piers and steel frames resting on an array of foundations. The cryogenic, diagnostic, vacuum, and electrical systems are supported either on the vessel or on the space frames. The vessel is also surrounded by a 7-ft-thick concrete shielding vault.

2. Objective of the Independent Analyses

The Pittsburgh-Des Moines (PDM) Corporation was awarded the contract to design and construct the vessel system. The structural design was aided by the finite-element analysis simulating various loading conditions and postulated earthquake excitations. The PDM analyses are documented in Ref. 1. An independent analysis on the vacuum vessel was performed by LLNL for the reasons described below.

2.1 Verification of the PDM Engineering Design

LLNL prepared a detailed specification package for the vessel design. However, the vessel is a highly complicated structure and is interconnected to many systems such as the magnet, cryogenic, vacuum, and diagnostic systems. A well planned monitoring procedure can enhance the quality of the communication and information exchange between two organizations.

As planned, an independent analysis at LLNL aided in the development of modeling assumptions, computer codes, and analysis methods. This approach also led to a better understanding of the difficulties involved in developing the finite-element model, and gave us a better understanding of the crucial areas of the structure. As a result, PDM generated a finite-element model of about 2,800 node points and 15,000 degrees of freedom to substantiate and augment their simple two-dimensional analyses and closed-form hand calculation results.

This large model reasonably represented the structure for design purposes but was cumbersome for repetitive analyses in verifying modeling assumptions. Therefore, LLNL generated a compact finite-element model that was half the size of PDM's. The LLNL model has adequate detail to ensure reasonable structure representation, yet a size appropriate for repetitive tests. However, both models have compatible modeling criteria for the purpose of model verification.

As the finite-element models were assembled to a satisfactory configuration, a series of tests was performed on them for quality assurance. The behaviors of both models were then compared. Differences were identified and minimized by improving the finite-element models based on addi-

tional models of local areas such as the beam dome walls² and the plug legs.

To closely monitor the design, the analyses were scheduled to proceed in several stages, each of which took place in both organizations concurrently. The analytical teams held conferences at the beginning of each stage starting with the discussion of modeling assumptions. After reaching an agreement about and an understanding of the modeling assumptions used by both teams, the load cases were defined and the formal analyses were conducted. Following static and dynamic analyses, the resulting element forces and moments were compared at such critical locations as magnet supports, vessel legs, piers, columns, and knees.

2.2 Verification of Modeling Assumptions by Additional Analyses

The LLNL model was used to verify modeling assumptions. Verification required repetitive analyses of the model with certain changes implemented to identify the effects of various assumptions. The boundary conditions at foundations, the refinement of the transition cone region, and other areas were evaluated by additional analyses, which are discussed in detail in Secs. 4.1.2 and 5.2.

2.3 Provision of Magnet Hanger and Vessel Support Design Loads for Corresponding Design Contractors

The two crucial components in MFTF-B are the superconducting magnet support system and the foundations supporting the vessel system. General Dynamics/Convair (GDC) held the design and fabrication contract for the magnet system whereas the foundations, being part of the conventional facility, were the responsibility of the Plant Engineering Department at LLNL. The analytical team of the MFTF-B program was responsible for providing the design loads to the corresponding contractors to ensure consistency in the design of the interfaces at both ends of the magnet support members and at the foundations.

2.4 Provision of Structural Responses of Magnet and Vessel for Attached Equipment Design

The various apparatus and equipment attached to the magnets and vessel were designed by different contractors. The structural responses of the magnets and vessel governed their design. LLNL provided the structural response in various formats depending upon the design criteria defined.

From the LLNL model the equivalent acceleration level (g factor) at a specific location can be estimated by separately scaling the static results of the structure's gravity load, activated in three global directions, to the respective seismic results. This equivalent acceleration level is normally used as an input in pseudoseismic analysis.

Some aiming apparatus, such as beamline and diagnostic equipment, are governed by the displacements at their interfaces on the vessel. The total deformations from the static and dynamic analyses of the LLNL model define the design guidelines for these apparatus.

The LLNL model was modified and analyzed to obtain the required information for many other purposes. For diagnostic alignment the displacement on the vessel caused only by the weight of magnet arrays was computed.³ For magnet design

the stiffnesses of the vessel at the hanger locations were calculated from the analysis that involved applying unit loads on the vessel at the hanger attachment points in the absence of the magnet array.⁴ Other than the design load cases, an additional operating condition named the choke mode was analyzed for vessel displacement at hanger attachment points for magnet alignment.⁵

2.5 Input for the Soil-Structure Interaction Analyses

The vessel is surrounded by a 7-ft-thick vault wall that stands on a foundation separated from the vessel foundations. We were concerned about the soil-structure interaction (SSI) between the vessel and vault walls. Structural Mechanics Associates (SMA) performed an SSI analysis on the MFTF-B structure, utilizing the LLNL model in conjunction with a vault wall model. The SSI analysis results were compared to the fixed-base analysis results to confirm the reduced dynamic input spectrum assumption.

As a whole the LLNL model was the major tool in coordinating the design of most components in the MFTF-B program. We have used the model to the maximum extent to accomplish the project goals.

3. Geometric Configuration of MFTF-B

A horizontal cylindrical shape was chosen for the vessel in order to effectively maintain a vacuum environment (Fig. 3-1). The diameters of the cylinder at both ends are larger than that in the center section. The vessel is reinforced by T-beam stiffeners. The longitudinal stiffeners carry loads to the adjacent ring stiffeners, which in turn transfer the loads downward to the legs.

3.1 Vacuum Vessel System

The center vessel (central cell of the plasma chamber) that houses the axicell and solenoid magnets is a cylinder 26 ft in diameter and 72 ft in length. In the longitudinal direction the center vessel is strengthened by 4 stiffeners and 36 small reinforcing bars. The cylinder is constructed of

eight sections, six of which are removable. Each module contains two ring stiffeners supported on two pairs of legs. Each end section has one pair of legs at one end with the other end connected to the end plug vessel by a 45° divergent transition cone cylinder. These 14 pairs of legs rest on a pair of longitudinal box beams supported on two steel frames.

The 45° divergent transition cone leads to a 65-ft-long cylinder that is 35 ft in diameter and is known as the end-plug vessel (tandem-mirror end plug). It is reinforced by eight longitudinal stiffeners and four ring stiffeners that are welded on four pairs of legs. Because of the heavy weight of the tandem mirror magnets, the inner ring stiffeners and legs are in double sections. The end vessel legs are welded and grouted to four reinforced concrete piers, each having a 10- by 13-ft cross

Figure 3-1. Conceptual illustration of the Mirror Fusion Test Facility (MFTF-B).

section. There are four spherical beam domes in the midsection of the plug vessel, which is capped by a spherical end dome.

The vessel, legs, and support-box beams are built of nonmagnetic stainless steel (304), whereas the support frames at the center vessel are made of carbon steel. To provide access to the inside of the vessel, numerous circular and rectangular penetrations are scattered over the vessel shell. Beamlines, cryogenics, diagnostics, and other types of equipment are connected through the penetrations. Some superstructures, such as platforms and stairways, are also built onto the vessel.

3.2 Superconducting Magnet System

Inside the vessel the superconducting magnet system consists of 42 magnets. These are

- Two pairs of C-shaped Yin-Yang anchor cells (EM2, EM1; WM2, WM1).
- Two pairs of C-shaped transition coils (ET2, ET1; WT2, WT1).
- Two sets of eight trim coils (ETR1 to ETR8, WTR1 to WTR8).
- Two sets of three axicells (EA2o, EA2i, EA1; WA2o, WA2i, WA1).

- Twelve solenoids (ES6 to ES1, WS6 to WS1).

The magnets are suspended to the ring stiffeners in five groups by vertical hangers and transverse struts. Each group is linked by drag struts to the longitudinal stiffeners that are bridged over two adjacent ring stiffeners.

The end-plug modules contain M2, M1, and T2 magnets while the axicell modules have T1, A2o, A2i, A1, and S6. The rest of the solenoids are in the solenoid module. The middle eight solenoids are paired by box beams. The trim coils are grouped in fours. Each trim coil group is hung on the T2 or T1 magnet.

3.3 Foundation Array

The vessel is supported on an array of 4-ft-thick reinforced-concrete foundation mats. The east-center vessel mat is 30 by 52 ft and the west center mat is 30 by 48 ft, separated by the vault shear wall foundation. The mats carrying the end-plug piers are 48 by 52 ft with a 22-ft-square opening in the middle. These foundations are close to each other.

4. Description of LLNL Finite-Element Model

4.1 Realistic Modeling Assumptions

To realistically model this complicated test facility, we made certain assumptions in order to simplify the computer model while retaining adequate representation of the structure.

4.1.1 Symmetric Boundary Condition at the Vertical Midplane of the Vessel

The vacuum vessel, support structures, and magnet system (except for the C-shaped magnets) are symmetrical with respect to the vertical midplane. As the exception, the west C-coils are rotated 90° about the longitudinal axis relative to the east C-coils, as are the Yin-Yang drag struts. In addition, the solenoid module has one group of

drag struts that span across the plane of symmetry from the east-vessel ring stiffeners to the west solenoid WS1. Despite these unsymmetrical entities, to optimize the usage of node points we assumed the system to be symmetric to the midplane; therefore, we simulate only the west half of the structure in the finite-element model.

Figure 4-1 is a plot of the MFTF-B Axicell Vacuum Vessel finite-element-model mesh. The triad indicates the coordinate system adopted in the model, where x, y, and z are the transverse, vertical, and longitudinal directions, respectively. The specific boundary conditions allow us to generate half of the structure yet simulate the full structure as shown in Fig. 4-2.

Figure 4-1. MFTF-B Axicell-Vacuum-Vessel finite-element-model mesh.

Figure 4-2. Whole model representation.

Of necessity, the unsymmetric entities had to be modified to fulfill the symmetry requirement. We modified the solenoid-module drag struts by turning them backward. We assumed that they were connected to the west-vessel shell and that they crossed the face of symmetry to the position of the east solenoid ES1. Because the east half is not modeled, the drag struts are tied to the west solenoid WS1 by rigid beam elements.

The solenoid-module drag struts carry heavy longitudinal loads to the vessel stiffeners. Consequently, in the real structure, the first module of the east center vessel is strengthened to resist these heavy loads. In the model, this first east module with its support legs replaces the first west module of the west center vessel.

The boundary conditions at the face of symmetry restrain the longitudinal (east-west) translation as well as the rotations about the vertical (up-down) and transverse (north-south) axes. These boundary conditions apply to most loading conditions except for unsymmetric loadings such as the magnet fault load and the longitudinal seismic load.

Under the unsymmetric longitudinal magnetic force the drag struts of the solenoid module produce high stress concentration in the 49-in.-wide cylindrical plate next to the face of symmetry, because of its longitudinal translational restraints. This high stress phenomenon does not exist in the real structure because the stress propagates along the shell across the face of symmetry to the adjacent east ring stiffener. In this load case we modified the symmetric boundary condition

by replacing the longitudinal translational restraints with a series of longitudinal translational springs to simulate the missing stiffness. The stiffnesses of these boundary elements were obtained by applying a unit force on each boundary node point on the face of symmetry simultaneously in a longitudinal static analysis, then dividing the unit force by the resulting model displacements.

For seismic analysis, symmetric boundary conditions apply to transverse and vertical excitations. For longitudinal excitation analysis, anti-symmetric boundary conditions are enforced. This allows the model to translate in the longitudinal direction and to rotate about both axes in the vertical midplane.

4.1.2 Fixed-Base Boundary Conditions on the Foundation

The foundation array is assumed to bear on a thick layer of rigid soil so that the structure has fixed-base boundary conditions. The 4-ft-thick foundation mat is also relatively rigid in deflection and torsion; therefore, the boundary conditions at the base of piers were fixed in three translations and torsion.

At the end-plug vessel, the rotational stiffness of the massive concrete piers is greater than that of their foundations. Obviously the foundation can be driven to rotate by the piers. This foundation flexibility considerably affects the load distribution between the end plug and the center vessel. As such, it was necessary to apply transverse and longitudinal rotational springs beneath each

pier to simulate the foundation flexibility. Their rotational stiffnesses are computed based on "beams-on-elastic-foundation" theory.⁶

Although the supporting columns and knees in the center vessel have a relatively small stiffness compared to that of the 4-ft foundation, the evaluations show that the rotational flexibility of the foundation affects the load distribution between the plug and center vessel.⁷ For consistency in modeling technique, the same type of rotational springs is applied to the base of the columns and knees of the center vessel supporting frame. The rotational springs only capture the local rotational flexibility. The coupling effect between piers or columns is assumed to be insignificant. The remaining boundary conditions at the base of the columns and knees are restrained in three translations and in torsion, just as for the piers.

The box beams are supported at the middle by a pair of short columns resting on the shear wall. The boundary conditions at the base of these columns are restrained in vertical translation only. Neither horizontal translations nor rotations are resisted by the shear wall.

4.1.3 Equivalent Weight and Mass Densities

The superconducting magnets are composed of the conductor bundles, coil cases, and thermal shields. The coil case is made from nonmagnetic stainless steel (304 LN) and provides most of the stiffness in the magnet. The beam elements representing the magnets include only the stiffness of the magnet cases. The total weight of the magnet, including the conductor pack and support components, is uniformly distributed in the beam in the form of equivalent weight and mass densities. Because the trim coils are small and are attached on transition magnets T2 and T1, only their weights are included as concentrated loads.

Numerous types of auxiliary equipment are installed on the vessel. Their weights are uniformly distributed over the shell within the corresponding regions where the plate densities are adjusted to include these equipment weights. Two 6,000-lb beam-injector loads are applied as concentrated loads on the top beam dome. Equipment weighing over 6,000 lb, such as beamline tanks, will be supported off the vessel by space frames.

4.1.4 End Dome Representation

The vacuum vessel is capped at both ends by end domes. The end dome is hung at the vessel periphery on two major supports. Four additional

pins serve to stabilize the dome cover in the case of an earthquake.

The end dome does not provide any radial stiffness to the vessel shell; therefore, it is not included in the model. By design, the total weight of the end dome is carried by a cantilever beam on the two top supports extending inward and resting on the first single-ring and double-ring stiffeners. This supporting configuration imposes a 60,000-lb downward load on the single-ring stiffener and a 10,000-lb upward load on the double-ring stiffener.

When the vessel is under vacuum pressure, the end dome is pressed tightly on the vessel periphery. The vacuum pressure from the dome cover is represented by concentrated loads applied along the vessel rim. In seismic analysis, we assumed the vessel to be in vacuum when the earthquake occurs; therefore, we uniformly distribute the end dome mass along the periphery in all three directions of excitation.

4.2 Proper Element Type

4.2.1 Plate/Shell Element

The vessel shell and support legs are modeled by four-node, quadrilateral, thin, plate/shell elements (Fig. 4-3). These elements can handle in-plane and out-of-plane loadings. The aspect ratio of the plate elements is limited to less than 1:5. All plate/shell elements have a modulus of elasticity equal to 28 million psi, a Poisson ratio of 0.3, and a weight density of 490 lb/ft³.

4.2.2 Three-Dimensional Beam Element

We modeled the magnets, vessel stiffeners, and support-leg flanges by using two-node, prismatic, three-dimensional (3-D) beam elements (Figs. 4-4 and 4-5). Because the shell and beam elements share common node points, the offset effect of the stiffeners and ribs must be included. To compensate for this offset effect, we included a portion of the shell in the calculation of the moment of inertia about the major neutral axis for the stiffeners. All beam elements have the same material properties as the plate/shell elements except those for the concrete piers that have a modulus of elasticity of 3.6 million psi, a Poisson ratio of 0.17, and a weight density of 150 lb/ft³.

The hangers and struts are designed to be two-force members because the monoball connections are pinned joints. In the input data for the geometric properties of the beam elements, a very

Figure 4-3. Plate/shell elements representing the vessel shell and legs.

Figure 4-4. Beam elements representing the magnets and their support system.

Figure 4-5. Beam elements representing the vessel ring stiffeners and support system.

small value is used for the shear areas and moments of inertia. This technique simulates the truss-like action of the hangers and struts by 3-D beam elements.

Because the 3-D beam element does not handle thermal analysis, the truss elements were superimposed on the 3-D beam elements. The 3-D beam element provides the shear and bending stiffnesses while the two-dimensional (2-D) truss elements only provide the cross-sectional areas that determine the contraction or the elongation due to temperature change.

4.2.3 Rigid Element Method

All beam elements are placed on the center line of the structure components. This creates an element-connectivity problem. When the interfaces are located at the surface of the components, and not at the center line, a rigid beam is inserted between node points at the end of one component

and at the center line of the connecting component. This rigid element provides only stiffnesses in all six degrees of freedom but contains no weight or mass densities.

For example, the rigid element is used to connect the node points at each hanger end and at the magnet center line where the hanger intercepts in order to maintain the true hanger length. Similarly, a rigid beam is inserted between the end of the hanger and the vessel ring stiffener. In the vessel support, rigid beams are used to connect the bottom of the legs to the piers or box beams. The support frame in the center vessel is managed in the same manner.

At the base of the supporting structure some rigid elements are also used to tie the supporting components to the center of the foundation. Because the rigid elements are extremely stiff the restrained boundary conditions at the base of the supporting elements remain effectively fixed as

assumed. The rotational capability of the rigid elements beneath the piers is released to allow the bending to be resisted by the springs.

4.2.4 Boundary Elements

The boundary elements (springs) are implemented to serve different functions. As mentioned previously, the rotational springs capture the flexibility of the foundations and the translational springs simulate the stiffness of the missing east vessel.

To speed up the force equilibrium check, the resultant forces at the restraints at the face of symmetry are captured by rigid springs, a series of longitudinal translational springs with rigid stiffnesses replacing the longitudinal restraints. Similarly, a short vertical beam is added below the center of the foundation mat to capture the resultant forces and moments. These resultant forces from below the mats and from the face of symmetry should balance the applied loads in the model's equilibrium check.

4.3 Appropriate Model Size for Computer Analysis

To reasonably simulate the complicated test facility, refinement of the model is crucial. The primary concern is to properly represent the structure; secondary concerns are that the model size be manageable by the analytical computer program and that the computer run time not exceed the daily allocated run time.

The refinement of the model is mainly dependent on the configuration of the structure. For example, the C-shaped magnets consist of two major lobes and two minor lobes. We use six elements to represent each lobe regardless of radii because the lobes serve comparably important functions. The minor lobes are subjected to compression forces whereas the major lobes are spread open by the large magnetic forces.

Each magnet consists of 24 node points and 24 beam elements, except for the trim coils. The coordinates of the node points in the magnets are assigned to coincide with the hanger interfaces within each lobe. The importance of maintaining true hanger lengths justifies having additional node points at the ends of hangers and struts. The trim coils produce small magnetic forces and function as tuning devices. They are affixed on the transition magnets and contribute minimum stiffness to the model; therefore, only their weights are added to the model as concentrated loads.

The top half of the vessel carries numerous apparatus while the bottom half sits on legs; therefore, both halves are equally important. The ring stiffeners and shell plates are divided evenly into 24 elements in the radial direction except at the leg interfaces where the plate element sizes are adjusted to fit the legs.

Along the longitudinal axis the vessel is sectioned into 20 segments that are primarily defined by the locations of ring stiffeners, beamline tanks, and the changes of plate thicknesses. At the mid-section of the end plug, three segments configure the two-directional curvature of the beam domes. The transition zone, where the load is transferred back and forth between the plug and the center vessel, also contains three segments to represent the proper stiffness of a cone-shaped structure.

Consequently, the LLNL finite-element-model mesh contains 1397 node points, with 1656 beam, 644 plate, and 50 boundary elements. It has 7626 degrees of freedom, and its half bandwidth consists of 582 equations.

SAP4, which is a well-developed, linear, elastic, structural analysis program,⁸ is used for static analyses. It also forms the matrices for seismic analysis. Twenty-two minutes of CDC-7600 computer time are required to complete a static analysis. Generally, an analysis of this size can be completed only in the evenings in either active mode or batch mode on the OCTOPUS system or during weekends on the National Magnetic Fusion Energy Computer Center (NMFECC) system.

4.4 Adequate Model Detail

Overall the structure has been adequately represented. For some local areas, however, we can only capture the essential details. For example, the beam dome walls are heavily gusseted to the stiffeners. In the model, we tied the beam dome cover directly to the stiffeners and still obtained a realistic representation.

The double ring stiffeners and legs are also simplified by using equivalent beams that possess the stiffnesses of the double section. The wing plates of the plug legs and the webs of the center vessel legs are modeled in detail to maintain their reinforcing function.

Numerous penetrations of different sizes and shapes are scattered over the vessel. The periphery of these openings is reinforced by pad plates and walls capped with a flange. The pad plates are designed according to the area requirements to properly distribute the stresses caused by the

opening discontinuity.⁹ Practically we can assume that the openings do not affect the global behavior; therefore, they are not included in the model.

At the vessel module interface, the splice joint is designed to carry longitudinal force, shear,

and bending.⁹ The module flanges are bolted together and covered by a welded belt to maintain the vacuum. Effectively, the module joints are as strong as continuous plates, just as they were modeled to be.

5. Quality Assurance of the Finite-Element Model

The most important process of assembling a finite-element mesh is its quality assurance. It is accomplished in several steps. Other than displaying the model using a dynamic graphics program like GRAPE,¹⁰ a thorough understanding of structural behavior aids in the discovery of model errors. A detailed-model investigation that isolates suspicious areas can aid in the understanding of its behavior.

5.1 Model Configuration Check by Graphics

Proper grouping in assembling the model is helpful in displaying mesh elements. The LLNL

model is divided into 47 parts. The first 16 parts are magnets and their supports. Parts 17 through 22 contain vessel stiffeners. The following 8 parts are leg and support systems. The vessel shells are in parts 31 to 43 and the last three parts represent leg plates. The model is plotted by parts with node points labeled and then rotated through various angles about the three global axes to reveal all elements. The "remove-hidden-line" option enhances the three-dimensional effect of the plate/shell elements as shown in Figs. 5-1 through 5-3. Note that the triad on the plots indicates the rotated angles.

Restrained nodal points can be identified by displaying the deformation of the model under gravity load using a relatively large-scale factor. In

Figure 5-1. Plate/shell element group rotated 315° about the vertical axis.

Figure 5-2. Plate/shell element group rotated 295° about the vertical axis.

Figure 5-3. Plate/shell element group rotated 45° about the vertical axis.

the deformed figure, the elements are drastically distorted, leaving the restrained node points remaining in their original locations. With this approach, erroneously restrained node points can be easily identified from the distorted plots.

5.2 Modeling Assumption Check by Detailed Investigation

Some of the more influential assumptions in the model are the foundation boundary conditions. Based on the "beams-on-elastic-foundation" theory, we calculated an equivalent rotational stiffness for the boundary elements. In the center vessel region, four columns and knees rest on a continuous foundation mat. The effective beam-width-selection methods were evaluated to identify the reasonableness of the approach.⁷ Based on these evaluations, we decided to define the beam width by a 45° shear-plane approach. The analytical results also confirm that the base shear shifts between the plug and the center vessel because of the addition of the center vessel foundation springs.

Another assumption that was examined deals with the beam dome walls. We tied the beam dome directly to the stiffeners, while PDM's team included the walls. They captured the reinforcing gusset plate on the wall with equivalent beams. The geometric properties of the equivalent beams were obtained by analyzing a refined model of the beam dome walls, the gusset plates, and the stiffeners.²

According to the preliminary results, the plug legs are over stressed and need modification. A refined model of the double legs, generated to compute the leg stiffnesses, leads to the addition of the wing plates.

In comparing the PDM and LLNL models, we noticed that the degree of refinement in the transition-cone affects the load distribution between the plug and center vessel. PDM proved that the effective refinement of the transition cone is three segments.

5.3 Force Equilibrium Check in Static Behavior

The force equilibrium of the model is checked by applying the model's gravity load (1 g) sepa-

ately in three global directions: transverse, vertical, and longitudinal. In each of these test cases the sum of the resultant forces from the restraints should total the weight of the structure. Any unbalanced load indicates unexpected fixation of node points. Further investigation of the load path in each test case reveals the model behavior, which should coincide with the intended structural behavior. Furthermore, both PDM and LLNL models should behave similarly. Any significant difference between the two models in those test cases led to investigation and discussion by the analytical teams and resulted in improved accuracies of both models.

The equivalent mass method is validated by these test cases. In the 1-g vertical-load test case, the vertical hangers carry the magnet weight while the transverse struts resist the weight in the 1-g transverse-load test case. In the same manner, the total longitudinal force components in the drag struts should equal the total weight of the magnet module in the 1-g longitudinal-load test case. Some twisting of the magnet module was discovered in the process of tracing load paths and led to fine tuning of the hanger-magnet interfaces.

5.4 Dynamic Characteristics Check in Modal Extraction

The dynamic behavior of a model depends on its dynamic characteristics, namely free vibration frequencies and dominant mode shapes, which in turn are dependent on the geometric configurations, mass, and stiffness distributions. As mentioned in Sec. 4, a symmetric model is used in the transverse and vertical excitations while an antisymmetric model is used in the longitudinal excitation. The modal frequencies of both models were extracted. For checking purposes, only a few modes should be extracted and the mode shape should be plotted to identify the meaningless local modes caused by a deficiency in the local stiffnesses.

For example, the membrane element in the PDM model legs is a two-dimensional element. Although the leg plates are reinforced by ribs, the out-of-plane stiffnesses are weak and cause some meaningless local modes. Additional stiffnesses in those degrees of freedom can eliminate those local modes with minimum effect on the global behavior.

6. Static Analysis

The quality-assurance processes described above confirmed that the model was satisfactory, so we were ready to define the load cases and to proceed with the formal analyses. Under normal operating conditions the structure is subjected to various types of load. In order to better understand structural behavior, the loads were applied to the model separately. To satisfy the design requirements of the magnetic fusion experiments, the static load cases are designated as follows:

- Gravity load (G).
- Vacuum pressure load (V).
- Magnetic load under normal operation (Mn).
- Magnetic load under fault conditions (Mf).
- Magnetic load caused by misalignment of magnets (Mk).
- Environmental thermal load (Te).
- Magnet cool-down thermal load (Tc).

6.1 Gravity Load

Other than its weight, the vessel carries the magnet array and the external auxiliary equipment. The model representing the west half of the vessel produces a total weight of over four million pounds at the foundation.

The vessel and legs weigh one million pounds and the magnet array 1,340,000 lb. The auxiliary equipment accounts for 550,000 lb, and the rest of the weight belongs to the piers and support frames. The magnet weights appear in Table 6-1 and the auxiliary equipment weights are listed in Table 6-2. Designs corresponding to the vessel-region identification numbers in Table 6-2 appear in Fig. 6-1.

Table 6-1. Magnet weights.

Module	Magnet	Weight (10 ³ lb)
Yin Yang	M2,M1	400 (each)
	T2	110
	TR1 to TR4	15 (total)
Axicell	T1	60
	TR5 to TR8	12 (total)
	A2o	70
	A2i	20
	A1	65
	S6	35
Solenoid	S1 to S5	32 (each)

6.2 Vacuum Pressure Load

During operation the vessel maintains a vacuum environment of 10^{-8} Torr that is equivalent to a pressure of 14.7 psi normal to the vessel shell. Also, an additional uniform normal force of 10 percent of the vacuum pressure induced on the vessel shell by the eddy current is included. The total pressure of 16.2 psi is applied normal to the vessel shell.

6.3 Magnetic Load under Normal Operation

The magnet array that was designed to provide the required magnetic field for plasma confinement produces large magnetic forces as well. The radial magnetic forces in each magnet are self-balanced. Within the whole array, the longitudinal forces are also in equilibrium. However,

Figure 6-1. Vessel section identification for the auxiliary equipment loads.

Table 6-2. Vessel auxiliary equipment weights in 10^3 lb.

Section	End dome 8000 ^a	Plug and center											Subtotal
		Plug section					Center section						
		6500 ^a	6600 ^a	6700 ^a	6800 ^a	6200 ^a	+	6300 ^a	5900 ^a	5800 ^a	5700 ^a	5600 ^a	
						A	B	C					
A&B	34.0	14.6	2.35 ^b	14.1	2.35	95.9			41.5	20.75	17.15	36.5	291.2
C1	0	0	0	0	0	40.0	35.0	0	0	0	0	0	
C2	0	0	0	0	0				5.0				
C3	2.0	0	0	0	0	5.6			7.0				
C4	4.5	0	0	0	0				0				
C5	0	0	0	0	0	2.5			0				
C6	0	0	0	0	0	0			5.0				
C7	0	0	0	0	0				2.0				108.6
D2	0	0	0	0	0	16.0			0				
D4	0	0	0	0	0	12.7			0				
D6	0	0	0	0	0	1.3			0				
D7	0	0	0	0	0				12.3				
D8	0	0	0	0	0				17.5				
D9	0	0	0	0	0	0			90.0				
Total													549.6

^a Region identification No.^b Two concentrated loads weighing 6×10^3 lb each.

within one-half of the magnet system, the longitudinal forces are cumulative. They are transferred to the vessel by the drag struts in each magnet module. The drag struts of the solenoid module are located in the middle of the solenoid array where the longitudinal magnetic force is balanced. The drag struts of the axicell module carry

2,018,000 lb whereas the Yin-Yang module carries 933,000 lb. These longitudinal magnetic forces are defined as magnetic load under normal operation; and they are divided among the drag struts in each module and applied as concentrated loads at the hanger-magnet attachment points.

Table 6-3. Magnetic forces caused by magnet misalignment.

Load combination	Magnet	Hanger No.	Force (lb)	Hanger No.	Force (lb)	Hanger No.	Force (lb)
1	M2-M1	6001	Fy = 27,605	6005	Fx = 15,010	6007	Fx = - 34,865
	T2	6101	Fy = - 96,500	6102	Fx = - 4,149	6104	Fx = 53,000
	T1	5922	Fy = 74,645	5923	Fy = - 13,372	5924	Fx = - 14,015
2	T2	6101	Fy = 71,910	6102	Fy = - 11,103	6104	Fx = - 38,580
	T1	5922	Fy = - 85,500	5923	Fy = - 28,000	5924	Fx = 90,000
	A2	5913	Fy = 26,957	5912	Fy = 25,725	5914	Fx = - 48,000
3	T1	5922	Fy = 31,000	5923	Fy = 10,000		
	A2	5913	Fy = - 37,206	5912	Fy = - 34,475		
	A1	5903	Fy = 17,755	5902	Fy = 12,746		
4	T1	5924	Fx = - 41,000				
	A2	5914	Fx = 71,500				
	A1	5904	Fx = - 30,500				
5	T1	5922	Fy = 15,000	5923	Fy = 5,000		
	A2	5913	Fy = 37,026	5912	Fy = 34,475		
	A1	5903	Fy = - 15,250	5902	Fy = - 15,250		
	S6	5813	Fy = - 30,500	5812	Fy = - 30,500		
6	T1	5924	Fx = 20,000				
	A2	5914	Fx = - 71,500				
	A1	5904	Fx = 30,500				
	S6	5814	Fx = 61,000				
7	S5	5803	Fy = - 11,000	5802	Fy = - 11,000		
	S3	5703	Fy = 34,250	5702	Fy = 34,250		
	S1	5603	Fy = - 34,250	5602	Fy = - 34,250		
8	S5	5804	Fx = 22,000				
	S3	5704	Fx = 68,500				
	S1	5604	Fx = 68,500				
9	S5	5803	Fy = 11,000	5802	Fy = 11,000		
	S3	5703	Fy = - 34,250	5702	Fy = - 34,250		
	S1	5603	Fy = 23,250	5602	Fy = 23,250		
10	S5	5804	Fx = - 22,000				
	S3	5704	Fx = 68,500				
	S1	5604	Fx = - 46,500				
11	S6	5905 - 8	Fz = - 359,250				
	S1	5405 - 8	Fz = 359,250				

6.4 Magnetic Load under Fault Condition

In the event of an emergency, any of the magnets can be in a fast dump condition. The change of electric voltage can induce eddy currents in adjacent magnets accompanied by magnetic forces. This situation defines the fault condition. The magnetic fault forces produced during the fault condition are quite different from those produced under normal operation. The worst fault-load combination was defined as the magnetic load under the fault conditions.

Because the fault conditions do not arise simultaneously under normal operation, only the fault cases producing higher stresses on the structure than those posed during normal operation are considered. Based on this guideline, the fault load is 2,874,000 lb on both the axicell and solenoid modules but in opposite directions. No magnetic force is produced in the Yin-Yang module.

6.5 Magnetic Load Caused by Misalignment of Magnets

Theoretically, all magnets are perfectly parallel to each other. Because of their complicated interior structure and external link configuration, it is impossible to guarantee perfect magnet alignment. The misalignment of any magnet can produce different magnetic forces in the array.

Assuming a 5° misalignment in the magnets, a matrix of magnetic forces is computed corresponding to ten load combinations under the magnet misalignment case. The forces in each load case are given in Table 6-3. These misalignment loads can be either symmetric or antisym-

metric; therefore, half of the loads in all 10 load cases are applied to symmetric and antisymmetric models, then the results are combined for stress evaluation.

6.6 Environmental Thermal Load

The vessel is surrounded by a 7-ft-thick vault wall where the expected environmental temperature variation is $\pm 10^\circ\text{F}$. The environmental thermal load case is defined as the vessel being uniformly cooled down by 10°F with a thermal coefficient of expansion of 8.44×10^{-6} .

6.7 Magnet Cool-Down Thermal Load

The superconducting magnets are operated at cryogenic temperature, but the vessel remains at room temperature. The hangers and struts are held at 4 K at the magnet end and room temperature at the vessel end. The configuration of the magnet support system is designed to avoid lock-in thermal stresses. To verify this condition, a cool-down thermal load case is defined as a 525°F temperature difference between the vessel and the magnet.

The hangers and struts are equipped with a thermal sleeve in the midspan to control the heat loss by maintaining the temperature at 90 K. Since the hangers and struts are represented by one beam element, an equivalent thermal coefficient is computed based on the total elongation of the whole hanger. Consequently the thermal expansion coefficients for this load case are 8.44×10^{-6} , 4.5×10^{-6} , and 5.7×10^{-6} for the vessel, magnets, and supports, respectively.

7. Dynamic Analyses

In addition to static analyses a seismic analysis is required for structures residing in seismic Zone 4 such as the LLNL site. The response spectrum method was selected for the test facility design because it consumes less computer time than does the time history analysis. Both methods produce comparable results. This method estimates the approximate maximum responses of a structure by means of modal analysis and a response spectrum curve. The modal analysis extracts the available free-vibration mode shapes of a finite-element model. The dynamic element loads in the

model for each free-vibration mode shape are computed on the basis of the modal frequency and the corresponding spectral acceleration on the design spectrum curve. The total structural responses to a dynamic forcing function are the combination of the responses from all mode shapes.

Because the model is quite large, the method of modal truncation is implemented to optimize the use of computer time in the analysis. The test facility is not a nuclear-related structure and the Nuclear Regulatory Commission (NRC) design

guidelines serve only as a reference for this analytical task. The selection of most of the parameters in our seismic analyser is influenced by the NRC guidelines.

7.1 Damping Coefficient

The stainless steel vessel rests on massive reinforced concrete piers and foundations. A series of dynamic excitations was applied to the vessel plug standing by itself and the structural response to these impulsive input functions was measured at different locations. The frequencies and damping values were then extracted for each mode shape by the Fourier theory.¹¹ The average computed damping value was close to 5 percent, which is considered to be the structural damping ratio for the vessel.

7.2 Design Response Spectrum

A response spectrum curve is the maximum response of a series of single-degree-of-freedom systems subjected to an earthquake. Generally, a design response spectrum curve is the envelope of

a group of spectrum curves obtained from an ensemble of earthquakes. A group of spectra (Fig. 7-1) for the LLNL site was generated at various damping ratios based on the time history of an ensemble of West Coast earthquakes.¹² The zero-period acceleration (ZPA) of the spectrum at a 5-percent damping ratio is scaled down to 0.25 g for the input spectrum in the horizontal excitations. The ZPA for vertical excitation is two-thirds of the horizontal spectrum (0.17 g). As shown in Fig. 7-2, the peak spectral acceleration is 0.78 g at a period of 0.33 s (3 Hz), tapering down to 0.18 g at a period of 2 s (0.5 Hz). For reasonable accuracy, 25 input data points were extrapolated from the spectrum curve (see Table 7-1).

The response spectra were applied to the fixed-base models. It is believed that due to the horizontal soil effect we can reduce the horizontal ZPA of the input spectra by 25 percent (0.19 g). However, the vertical flexibility of the soil is not significant and we kept the vertical spectrum at 0.17 g. The two-thirds reduction for vertical excitation and one-fourth reduction for transverse and longitudinal excitations are accounted for by the scale factor, one of the options available in the computer programs.

Figure 7-1. Site-specific response spectrum at 0.5 g for LLNL.

Figure 7-2. Input response spectrum for seismic analyses.

Table 7-1. Input response spectrum data points.

Period (s)	Acceleration (g)
0.0100	0.25
0.0303	0.25
0.0500	0.35
0.0700	0.45
0.0800	0.55
0.1000	0.65
0.1575	0.68
0.2150	0.72
0.2725	0.75
0.3300	0.78
0.4425	0.70
0.5550	0.61
0.6675	0.53
0.7800	0.44
0.8850	0.41
0.9900	0.37
1.0950	0.34
1.2000	0.30
1.2900	0.28
1.3900	0.26
1.4800	0.24
1.5700	0.22
1.6800	0.21
1.7900	0.20
2.0000	0.18

7.3 Modal Truncation

Theoretically a computer model has as many free-vibration mode shapes as degrees of freedom. Generally, the first few modes (low-frequency modes) dominate the structural response. The responses of these modes are magnified by their high participation factors and spectral accelerations. The high-frequency modes have low magnification in response and can usually be truncated. The *Recommended Revisions to Nuclear Regulatory Commission Seismic Design Criteria*¹³ suggests a modal truncation technique to ensure adequate seismic design. It recommends that the cutoff frequency be 33 Hz and the captured effective modal mass be 90 percent of the total structural mass. If less than 90 percent of the total mass is captured, the remaining mass should be accounted for by static analysis. We adopted this modal truncation technique in our seismic analyses.

In modal truncation methods there are other recommended approaches in measuring the ex-

cited mass in each modal frequency, i.e., those based on effective mass, strain energy, or elastic force. The MFTF-B axicell vessel model is one of those large computer models that have too many modal frequencies below the recommended cutoff frequency to be managed by the computer program. To maximize the inclusion of excited modal masses, we select the highest effective modal-mass frequencies among those that are below the cutoff frequency. To confirm the effective modal mass method as being the most effective approach, the author conducted a numerical study on mode selection in response spectrum analysis. Three mode selection methods were tested on two simple two-dimensional-frame type structures and on the MFTF-B axicell vacuum-vessel model. The results are published in the author's thesis¹⁴ and will be discussed later in this report.

7.4 Computer Program for Dynamic Analysis

The SAP4 program was originally selected for dynamic analysis, but there is a better modal extraction program (SUBSP) available. This SUBSP¹⁵ is a stand-alone program that reads the matrices from SAP4 output and performs modal extraction, using a subspace iteration algorithm with shifting, to solve for the eigenvalues and eigenvectors. SUBSP is more efficient and faster than the modal extraction subroutine in the SAP4 program that eventually is used to initiate the dynamic analysis by forming the mass and stiffness matrices of the model.

The mode selection process is performed by the program MODPAR.¹⁶ MODPAR was developed for this MFTF-B program to select modal frequencies by effective modal mass. It rearranges the mode shape sequence based on the quantity of effective modal mass and copies the requested number of modes having the highest effective modal mass onto a tape for force calculation.

RESPAN is a force calculation program using the response spectrum method. It was revised to become a stand-alone program from a subroutine of MODSAP,¹⁷ which is also an improved version of SAP4. Unfortunately, RESPAN stores all eigenvectors and eigenvalues in the memory core and the remaining memory size is allocated for force calculation. For a model of 7600 degrees of freedom, the mode shape data take up a large portion of the memory core, and the remaining space limits the number of the selected modes to 38.

To process the force combination, SRSS was developed to manipulate three dynamic load cases and three static load cases. This complicated dynamic analysis process is depicted on the schematic flowchart shown in Fig. 7-3, which delineates the task in each procedure of the analysis and identifies parenthetically the computer program performing each task. The modal extraction is performed on both the symmetric and antisymmetric models.

The mode selection is conducted on the symmetric model using both transverse and vertical modal masses, whereas the mode selection using the longitudinal modal mass is done on the antisymmetric model. The force calculation is obtained from three excitations separately.

7.5 Dominant Mode Shapes

The modal extraction is an iterative process that consumes considerable computer time. For a

Figure 7-3. Response-spectrum-analysis procedure.

model with 7600 degrees of freedom, it takes 75 modes to reach the 33-Hz cutoff frequency, devouring one hour of central processing unit (CPU) time and four hours of input/output (I/O) time to converge to the required precision. Among these 75 modes, the 38 highest effective modal mass modes are selected for the force calculation and the rest of the mode shapes are truncated.

Table 7-2 tabulates these 38 selected modal frequencies with their corresponding effective modal masses in percent of total mass. The bottom row indicates the total percent of effective modal mass. The most dominant modal frequencies are 3.04, 4.37, and 6.35 Hz in the transverse, longitudinal, and vertical directions, respectively.

Figures 7-4 through 7-6 depict the spectral accelerations at the selected modal frequencies (marked by A) and their corresponding captured percent of modal masses (marked by M) superimposed on the input spectrum curves in three excitation directions. Note that the transverse and longitudinal dominant modal frequencies are located close to the peak of the input response spectrum. This indicates that the captured effective modal masses of those modes in these two directions are excited at high acceleration amplitudes. Consequently, significantly high dynamic forces are expected.

These plots indicate that the effective modal masses are concentrated in the first few dominant modes. In the transverse free vibration, roughly 68.2 percent of the total mass is excited at an acceleration of 0.59 g, with 18.3 percent of the mass is excited between accelerations of 0.53 and 0.22 g. In the vertical free vibration, only 18 percent of the total mass is excited at 0.47 g and 36.4 percent of the mass is excited from 0.43 g through 0.17 g. The remaining 45.6 percent of the mass is captured by static analysis at 0.17 g. In the longitudinal free vibration, 75.5 percent of the total mass is excited at 0.58 g and 12.5 percent of the mass is excited between 0.51 and 0.19 g.

The averages of the spectral accelerations weighted by the modal masses are 0.4, 0.13, and 0.42 g in the transverse, vertical, and longitudinal directions, respectively. These spectral accelerations will be used to identify the dynamic force responses of the structure.

In proportion, more effective modal mass is excited from the top of the vessel than from the lower part of the structure. For example, most of the masses in all magnets are excited. The mass in the node point representing the top of the pier is excited from 80 to 100 percent in three excitations whereas the mass in the node point representing

the bottom of the pier is excited only up to 12 percent.

The transverse and longitudinal masses are close to 90-percent excited and no capturing of remaining mass is pursued. The remaining mass in

the vertical direction is significantly large and its dynamic effect is captured by pseudoseismic analysis. This analysis is executed by applying the remaining mass of each translational degree of freedom to the node point in the corresponding

Table 7-2. Dynamic characteristics of the finite-element model.

Order of importance	Transverse		Vertical		Longitudinal	
	Modal frequency (Hz)	Effective modal mass (%)	Modal frequency (Hz)	Effective modal mass (%)	Modal frequency (Hz)	Effective modal mass (%)
1	3.04	68.23	6.35	17.91	4.37	75.49
2	5.15	7.20	9.57	3.73	21.20	5.44
3	13.73	3.06	8.29	3.50	20.40	0.96
4	6.10	0.95	17.03	2.46	18.75	0.86
5	13.91	0.88	15.62	2.33	17.89	0.57
6	17.84	0.87	27.56	2.32	11.07	0.47
7	7.32	0.78	19.85	1.74	22.89	0.35
8	10.63	0.48	11.30	1.40	20.64	0.33
9	21.82	0.35	10.63	1.40	11.94	0.30
10	21.27	0.34	23.46	1.22	19.20	0.28
11	15.62	0.33	24.61	1.13	6.36	0.27
12	26.64	0.32	18.45	1.08	10.77	0.26
13	18.23	0.31	6.10	1.00	18.22	0.25
14	18.96	0.31	32.29	0.97	16.79	0.24
15	6.90	0.30	14.94	0.87	5.74	0.22
16	22.93	0.19	12.91	0.87	19.85	0.19
17	12.91	0.16	17.25	0.81	15.67	0.18
18	8.01	0.16	22.93	0.79	31.77	0.17
19	20.42	0.16	11.52	0.78	32.69	0.17
20	31.68	0.13	8.72	0.74	11.83	0.12
21	29.37	0.11	26.13	0.67	3.00	0.11
22	20.23	0.10	21.82	0.65	30.88	0.09
23	17.03	0.08	13.91	0.65	32.27	0.08
24	8.72	0.08	16.82	0.57	7.29	0.07
25	13.37	0.08	31.21	0.54	19.54	0.06
26	11.79	0.06	13.74	0.48	29.92	0.06
27	9.57	0.06	19.27	0.47	16.16	0.05
28	28.89	0.05	20.95	0.46	17.19	0.04
29	11.30	0.04	18.23	0.43	19.31	0.04
30	19.52	0.04	30.19	0.39	25.39	0.03
31	12.72	0.04	5.15	0.34	19.37	0.03
32	16.82	0.03	17.55	0.27	21.03	0.03
33	20.95	0.03	14.16	0.25	32.88	0.03
34	17.55	0.03	21.50	0.24	19.59	0.03
35	8.29	0.03	21.27	0.23	29.64	0.03
36	32.29	0.03	33.00	0.22	9.64	0.03
37	17.25	0.03	23.72	0.21	12.42	0.02
38	15.27	0.02	12.72	0.17	11.26	0.02
Total		86.50		54.40		88.00

Figure 7-4. Spectral acceleration and modal mass distribution of the dominant modal frequencies in the transverse direction.

Figure 7-5. Spectral acceleration and modal mass distribution of the dominant modal frequencies in the vertical direction.

Figure 7-6. Spectral acceleration and modal mass distribution of the dominant modal frequencies in the longitudinal direction.

direction as concentrated loads. The pseudoseismic analysis results are scaled by the gravity factor to obtain the correct force unit before being combined with the dynamic analysis results.

Figures 7-7 through 7-9 portray the most dominant mode shapes as a solid line and the original configuration as dots. As shown in Fig. 7-7, the longitudinal mode shape at 4.37 Hz reveals a rigid-body motion. In Fig. 7-8, the transverse

mode shape at 3.04 Hz indicates a slight rotation in: the Yin-Yang magnet pair and axicell magnets. The vertical mode shape at 6.35 Hz shown in Fig. 7-9 also exhibits a noticeable rotation in the Yin-Yang magnet pair and axicell magnets. This indicates a dynamic coupling effect in the model. The rotating motions in the transverse and vertical dominant modes can be viewed clearly in the animated movie generated by computer graphics.

Figure 7-7. Longitudinal dominant mode shape at a frequency of 4.37 Hz and a modal mass of 75.49 percent.

Figure 7-8. Transverse dominant mode shape at a frequency of 3.04 Hz and a modal mass of 68.2 percent.

Figure 7-9. Vertical dominant mode shape at a frequency of 6.35 Hz and a modal mass of 17.91 percent.

8. Evaluation of Analysis Results

The structural responses from the various analyses were evaluated to ensure compliance with program objectives. For contract monitoring purposes, the resulting forces and moments were verified with the PDM responses for all load cases separately. The PDM combined structural responses are compared to the allowable design stresses. The structural responses from the LLNL model at the magnet and vessel support members were tabulated and transmitted to the corresponding contractors for design and evaluation. The displacement responses from the analyses were evaluated for magnet alignment and in light of equipment design requirements.

8.1 Load Combination Scheme

The sequence of operation during the experiment starts with vessel vacuum pumping followed by magnet energization. The structures are loaded by gravity, vacuum, thermal, and magnetic forces (defined as Mn, Mf, and Mk). The Mn and Mf conditions do not occur simultaneously, and Mk events are possible but uncertain. These ten load cases are divided into three groups (with respect to the magnet modules): two groups in the Yin-Yang module, four groups in the axicell module, and four groups in the solenoid module. Only one case can occur in each of three groups.

The environmental thermal forces in the structure are self-induced and self-contained; however, the temperature can be increasing or decreasing. The forces in the model can be either in tension or in compression, as can be the seismic responses that are produced by a low probability event. The operating sequence and probability of each load case are considered in determining the load combination scheme as follows:

1. G
2. G + V
3. G + V + Tc
4. G + V + Tc + Mn (or Mf)
5. G + V + Tc + Mn (or Mf) + Mk.

These are the basic load combinations. The earthquake load and the environmental thermal load are then added to these five combinations separately, as follows:

6. E + G
7. E + G + V
8. E + G + V + Tc
9. E + G + V + Tc + Mn (or Mf)
10. E + G + V + Tc + Mn (or Mf) + Mk

11. Te + G
12. Te + G + V
13. Te + G + V + Tc
14. Te + G + V + Tc + Mn (or Mf)
15. Te + G + V + Tc + Mn (or Mf) + Mk.

The stresses from all 15 combinations are compared to the corresponding allowable design stresses.

8.2 Allowable Design Stress Criteria

Based on the nature of the structure components, the allowable stress criteria fall into one of two categories: one for pressurized components (vessel shell and stiffeners) and the other for unpressurized components (legs and supports). The nature of the working stress is also identified as either primary or secondary. For primary stresses the allowable stress is one-fourth of the ultimate stress (18,750 psi) and, for the secondary stress, it is two-thirds of the yield stress (20,000 psi), based on an ultimate stress of 75,000 psi and a yield stress of 30,000 psi for stainless steel (304).

A load factor of 1.2 is applied to the earthquake load combination because there is a low probability of its occurrence. A shape factor is also adopted to ease the local membrane stress and the primary bending stress. The environmental thermal stresses are self-induced and self-contained; therefore, they are categorized as secondary stresses with different allowable stress criteria. Table 8-1 gives the allowable design stresses for the analysis.

8.3 Model Deformation

The mirror fusion experiment demands high precision with respect to magnet locations. The vessel is designed to maintain minimum deformation so as to provide adequate support to the magnets. Tables 8-2 through 8-6 give the displacements at the vessel attachment points for all magnets from gravity load, vacuum load, environmental thermal load, normal magnetic load, and fault magnetic load cases respectively. Most of these tables are submitted to the magnet group for magnet alignment.

The 9.25×10^5 lb Yin-Yang module deflects a little over a quarter of an inch (0.279 in.) at the bottom major lobe of the M2, under its own weight. The largest deflection (0.1915 in.) occurs at

Table 8-1. Allowable stresses for the MFTF-B vessel and support design.^a

Load combination ^c	Vessel and stiffening rings ^b				Legs and component supports ^b			
	Primary		Primary plus secondary range ^e	Buckling ^f	Primary			Primary plus secondary range ^e
	Membrane	Local membrane plus bending ^d			Axial compression	Membrane	Local membrane and bending ^d	
G,V,M,T _c	S ₁	KS ₁	NA	FS = 3	FS = 4	S ₂	KS = 4	NA
G,V,M,T _c and E	1.2 S ₁	1.2 KS ₁	NA	FS = 3	FS = 3 ^g	S ₂	4 KS ₂ /3	NA
G,V,M,T _c and T _e	NA	NA	2 S _y	FS = 3	FS = 3 ^g	NA	NA	2 S _y

^a The bolt allowable stress, S_b is determined as in ASME Sec. VIII, Div. 1, with the exception that when thermal loads are included, the allowable stress is 2 S_b.

^b S₁ = S_u/4 for 304SS, S₂ = S_y/3 for 304SS.

^c Any combination of those listed in Sec. 8.1.

^d K is the cross-section factor (and equals 1.5 for a solid rectangular section).

^e Fictitious elastic stress.

^f FS = 3 applies for general stability and critical buckling of stiffeners. FS = 2.5 for local buckling of shell sections. (ASME Sec. VIII, Div. 1.)

^g FS = 1.67 for strain-controlled buckling.

Table 8-2. Vessel displacements at hanger attachment points for the gravity load case.

Magnet name	Hanger No.	Location	Node No.	Transverse Δx^a (in.)	Vertical Δy^b (in.)	Longitudinal Δz^c (in.)
Yin Yang	6001	N-vertical	341	- 0.0067	- 0.1122	0.0095
	6005	S-vertical	344	0.0072	- 0.1123	0.0103
	6002	M-vertical	347	- 0.0017	- 0.1915	- 0.0088
	6007	Transverse	555	0.0978	- 0.0167	- 0.0004
	6003	S-drag	353	0.0468	- 0.0782	0.0029
	6004	N-drag	356	- 0.0280	0.0162	0.0021
T2	6101	S-vertical	631	0.0004	- 0.1434	0.0225
	6102	N-vertical	362	0.0007	- 0.1410	0.0218
	6103	Transverse	365	0.0629	- 0.0163	- 0.0066
T1	5922	N-vertical	368	0.0019	- 0.0900	0.0264
	5923	S-vertical	678	0.0034	- 0.0744	0.0143
	5924	Transverse	374	- 0.0152	- 0.0026	- 0.0248
A2	5913	N-vertical	377	0.0035	- 0.0858	0.0081
	5912	S-vertical	380	0.0014	- 0.0828	0.0076
	5914	Transverse	383	0.0443	- 0.0230	- 0.0058
A1	5903	N-vertical	386	0.0031	- 0.0767	0.0060
	5902	S-vertical	389	0.0022	- 0.0737	0.0069
	5904	Transverse	392	0.0319	- 0.0194	- 0.0042
S6	5813	N-vertical	395	- 0.0013	- 0.0600	0.0028
	5812	S-vertical	398	0.0066	- 0.0573	0.0032
	5814	Transverse	401	0.0305	- 0.0193	- 0.0038
	5905	S-top	404	0.0020	- 0.0776	0.0074
	5906	N-top	407	- 0.0425	- 0.0222	- 0.0038
	5907	N-bottom	410	0.0000	- 0.0016	0.0041
	5908	S-bottom	413	0.0225	- 0.0189	- 0.0051
S5	5803	N-vertical	416	0.0001	- 0.0579	0.0023
	5802	S-vertical	419	0.0055	- 0.0554	0.0025
	5804	Transverse	422	0.0275	- 0.0182	- 0.0027
S3	5703	N-vertical	425	0.0011	- 0.0538	0.0014
	5702	S-vertical	428	0.0043	- 0.0516	0.0015
	5704	Transverse	431	0.0241	- 0.0186	- 0.0012
S1	5603	N-vertical	434	0.0000	- 0.0476	0.0001
	5602	S-vertical	437	0.0056	- 0.0454	0.0001
	5604	Transverse	440	0.0234	- 0.0192	- 0.0001
	5405	S-top	443	0.0030	- 0.0528	0.0001
	5406	N-top	446	- 0.0281	- 0.0195	- 0.0003
	5407	N-bottom	449	0.0003	- 0.0123	0
	5408	S-bottom	452	0.0093	- 0.0168	- 0.0003

^a South represents the positive x direction.

^b Up represents the positive y direction.

^c West represents the positive z direction.

Table 8-3. Vessel displacements at hanger attachment points for the pressure vacuum load case.

Magnet name	Hanger No.	Location	Node No.	Transverse Δx^a (in.)	Vertical Δy^b (in.)	Longitudinal Δz^c (in.)
Yin Yang	6001	N-vertical	341	0.0172	-0.0199	-0.0488
	6005	S-vertical	344	-0.0178	-0.0199	-0.0490
	6002	M-vertical	347	0.0002	0.0288	-0.0318
	6007	Transverse	555	-0.0179	-0.0107	-0.0371
	6003	S-drag	353	-0.0252	-0.0214	-0.0517
	6004	N-drag	356	0.0168	0.0023	-0.0479
T2	6101	S-vertical	631	-0.0004	0.0034	-0.0519
	6102	N-vertical	362	0.0016	0.0030	-0.0519
	6103	Transverse	365	0.0005	-0.0041	-0.0476
T1	5922	N-vertical	368	-0.0006	-0.0177	-0.0258
	5923	S-vertical	678	-0.0041	-0.0185	-0.0184
	5924	Transverse	374	-0.0152	-0.0026	-0.0248
A2	5913	N-vertical	377	0.0017	-0.0114	-0.0111
	5912	S-vertical	380	-0.0028	-0.0115	-0.0102
	5914	Transverse	383	-0.0107	-0.0030	-0.0114
A1	5903	N-vertical	386	-0.0014	-0.0088	-0.0092
	5902	S-vertical	389	-0.0024	-0.0086	-0.0096
	5904	Transverse	392	-0.0100	-0.0041	-0.0096
S6	5813	N-vertical	395	0.0065	-0.0127	-0.0085
	5812	S-vertical	398	-0.0077	-0.0127	-0.0085
	5814	Transverse	401	-0.0103	-0.0044	-0.0086
	5905	S-top	404	-0.0027	-0.0103	-0.0099
	5906	N-top	407	0.0088	-0.0053	-0.0105
	5907	N-bottom	410	0.0020	0.0031	-0.0094
	5908	S-bottom	413	-0.0099	-0.0015	-0.0099
S5	5803	N-vertical	416	0.0082	-0.0152	-0.0068
	5802	S-vertical	419	-0.0093	-0.0152	-0.0068
	5804	Transverse	422	-0.0185	-0.0052	-0.0066
S3	5703	N-vertical	425	0.0072	-0.0139	-0.0039
	5702	S-vertical	428	-0.0084	-0.0142	-0.0038
	5704	Transverse	431	-0.0114	-0.0054	-0.0033
S1	5603	N-vertical	434	0.0042	-0.0097	-0.0005
	5602	S-vertical	437	-0.0054	-0.0097	-0.0004
	5604	Transverse	440	-0.0109	-0.0051	-0.0004
	5405	S-top	443	-0.0029	-0.0105	-0.0011
	5406	N-top	446	0.0110	-0.0074	-0.0009
	5407	N-bottom	449	0.0020	0.0021	-0.0009
	5408	S-bottom	452	-0.0106	-0.0030	-0.0009

^a South represents the positive x direction.

^b Up represents the positive y direction.

^c West represents the positive z direction.

Table 8-4. Vessel displacements at hanger attachment points for the environmental thermal load case.

Magnet name	Hanger No.	Location	Node No.	Transverse Δx^a (in.)	Vertical Δy^b (in.)	Longitudinal Δz^c (in.)
Yin Yang	6001	N-vertical	341	0.0077	- 0.0449	- 0.0507
	6005	S-vertical	344	- 0.0084	- 0.0449	- 0.0507
	6002	M-vertical	347	- 0.0005	- 0.0430	- 0.0755
	6007	Transverse	555	- 0.0225	- 0.0332	- 0.0736
	6003	S-drag	353	- 0.0138	- 0.0423	- 0.0782
	6004	N-drag	356	0.0089	- 0.0221	- 0.0731
T2	6101	S-vertical	631	- 0.0004	- 0.0467	0.0511
	6102	N-vertical	362	0.0014	- 0.0467	- 0.0511
	6103	Transverse	365	- 0.0211	- 0.0284	- 0.0469
T1	5922	N-vertical	368	- 0.0003	- 0.0463	- 0.0368
	5923	S-vertical	678	- 0.0040	- 0.0459	- 0.0368
	5924	Transverse	374	- 0.0134	0.0326	- 0.0353
A2	5913	N-vertical	377	- 0.0033	0.0447	0.0311
	5912	S-vertical	380	- 0.0037	0.0447	0.0312
	5914	Transverse	383	0.0133	- 0.0322	0.0312
A1	5903	N-vertical	386	0.0033	- 0.0436	- 0.0237
	5902	S-vertical	389	- 0.0037	- 0.0437	- 0.0236
	5904	Transverse	392	- 0.0143	- 0.0314	- 0.0241
S6	5813	N-vertical	395	0.0073	- 0.0418	- 0.0208
	5812	S-vertical	398	- 0.0077	- 0.0419	- 0.0208
	5814	Transverse	401	- 0.0145	- 0.0312	- 0.0212
	5905	S-top	404	- 0.0037	- 0.0442	- 0.0276
	5906	N-top	407	0.0133	0.0354	- 0.0279
	5907	N-bottom	410	0.0032	- 0.0162	- 0.0280
	5908	S-bottom	413	- 0.0127	- 0.0283	- 0.0279
S5	5803	N-vertical	416	0.0074	- 0.0410	- 0.0170
	5802	S-vertical	419	- 0.0077	- 0.0410	- 0.0169
	5804	Transverse	422	- 0.0151	- 0.0309	- 0.0174
S3	5703	N-vertical	425	0.0073	- 0.0396	- 0.0094
	5702	S-vertical	428	- 0.0077	- 0.0396	- 0.0094
	5704	Transverse	431	- 0.0153	- 0.0294	- 0.0096
S1	5603	N-vertical	434	0.0068	- 0.0385	- 0.0019
	5602	S-vertical	437	- 0.0072	- 0.0386	- 0.0019
	5604	Transverse	440	- 0.0154	- 0.0270	- 0.0019
	5405	S-top	443	- 0.0037	- 0.0408	- 0.0039
	5406	N-top	446	0.0132	- 0.0309	- 0.0038
	5407	N-bottom	449	0.0033	0.0156	- 0.0039
	5408	S-bottom	452	- 0.0161	- 0.0236	- 0.0040

^a South represents the positive x direction.

^b Up represents the positive y direction.

^c West represents the positive z direction.

Table 8-5. Vessel displacements at hanger attachment points for the normal magnetic load case.

Magnet name	Hanger No.	Location	Node No.	Transverse Δx^a (in.)	Vertical Δy^b (in.)	Longitudinal Δz^c (in.)
Yin Yang	6001	N-vertical	341	-0.0290	-0.0007	-0.0636
	6005	S-vertical	344	-0.0266	-0.0025	-0.0653
	6002	M-vertical	347	-0.0482	0.0020	-0.0684
	6007	Transverse	555	-0.0196	-0.0050	-0.0609
	6003	S-drag	353	-0.0731	-0.0415	-0.0771
	6004	N-drag	356	0.0092	0.0270	-0.0774
T2	6101	S-vertical	631	-0.0276	-0.0067	-0.0627
	6102	N-vertical	362	-0.0276	-0.0054	-0.0630
	6103	Transverse	365	-0.0161	0.0037	-0.0579
T1	5922	N-vertical	368	-0.0238	-0.0038	-0.0513
	5923	S-vertical	678	-0.0253	-0.0052	-0.0500
	5924	Transverse	374	-0.0155	-0.0012	-0.0487
A2	5913	N-vertical	377	-0.0346	0.0118	-0.0395
	5912	S-vertical	380	-0.0397	-0.0667	-0.0465
	5914	Transverse	383	-0.0361	0.0053	-0.0390
A1	5903	N-vertical	386	-0.0349	0.0123	-0.0364
	5902	S-vertical	389	-0.0383	-0.0689	-0.0427
	5904	Transverse	392	-0.0246	0.0049	-0.0349
S6	5813	N-vertical	395	-0.0373	0.0277	-0.0338
	5812	S-vertical	398	-0.0169	-0.0163	-0.0322
	5814	Transverse	401	-0.0118	0.0012	-0.0314
	5905	S-top	404	-0.0442	-0.0870	-0.0466
	5906	N-top	407	0.0532	-0.0135	-0.0473
	5907	N-bottom	410	0.0123	0.0785	-0.0443
	5908	S-bottom	413	-0.0773	0.0169	-0.0437
S5	5803	N-vertical	416	-0.0326	0.0199	-0.0286
	5802	S-vertical	419	-0.0174	-0.0121	-0.0256
	5804	Transverse	422	-0.0071	-0.0005	-0.0251
S3	5703	N-vertical	425	-0.0232	0.0065	-0.0149
	5702	S-vertical	428	-0.0157	-0.0048	-0.0124
	5704	Transverse	431	-0.0070	-0.0016	-0.0124
S1	5603	N-vertical	434	-0.0192	0.0012	-0.0025
	5602	S-vertical	437	-0.0156	-0.0031	-0.0018
	5604	Transverse	440	-0.0072	-0.0017	-0.0019
	5405	S-top	443	-0.0164	-0.0031	-0.0040
	5406	N-top	446	-0.0212	0.0012	-0.0043
	5407	N-bottom	449	-0.0094	0.0024	-0.0039
	5408	S-bottom	452	-0.0055	-0.0025	-0.0039

^a South represents the positive x direction.

^b Up represents the positive y direction.

^c West represents the positive z direction.

Table 8-6. Vessel displacements at hanger attachment points for the fault magnetic load case.

Magnet name	Hanger No.	Location	Node No.	Transverse Δx^a (in.)	Vertical Δy^b (in.)	Longitudinal Δz^c (in.)
Yin Yang	6001	N-vertical	341	0.0000	- 0.0003	- 0.0198
	6005	S-vertical	344	0.0003	0.0013	- 0.0193
	6002	M-vertical	347	- 0.0012	0.0011	- 0.0195
	6007	Transverse	555	- 0.0018	- 0.0006	- 0.0171
	6003	S-drag	353	- 0.0018	0.0005	- 0.0187
	6004	N-drag	356	- 0.0007	- 0.0004	- 0.0188
T2	6101	S-vertical	631	0.0002	0.0001	- 0.0199
	6102	N-vertical	362	0.0002	- 0.0009	- 0.0200
	6103	Transverse	365	0.0016	- 0.0003	- 0.0170
T1	5922	N-vertical	368	0.0004	- 0.0021	- 0.0271
	5923	S-vertical	678	0.0007	- 0.0017	- 0.0248
	5924	Transverse	374	0.0073	- 0.0029	- 0.0214
A2	5913	N-vertical	377	- 0.0160	0.0109	0.0176
	5912	S-vertical	380	- 0.0245	- 0.0960	- 0.0300
	5914	Transverse	383	0.0289	0.0081	0.0211
A1	5903	N-vertical	386	- 0.0193	0.0163	- 0.0175
	5902	S-vertical	389	- 0.0244	- 0.0978	0.0255
	5904	Transverse	392	- 0.0127	0.0080	0.0187
S6	5813	N-vertical	395	- 0.0218	0.0380	- 0.0171
	5812	S-vertical	398	0.0064	- 0.0207	- 0.0130
	5814	Transverse	401	0.0049	0.0034	- 0.0151
	5905	S-top	404	- 0.0320	- 1.2456	- 0.0306
	5906	N-top	407	0.1084	0.0233	- 0.0339
	5907	N-bottom	410	- 0.0328	0.1123	- 0.0309
	5908	S-bottom	413	- 0.0917	0.0256	- 0.0300
S5	5803	N-vertical	416	- 0.0167	0.0306	- 0.0146
	5802	S-vertical	419	0.0054	- 0.0145	- 0.0050
	5864	Transverse	422	0.0086	0.0034	- 0.0082
S3	5703	N-vertical	425	0.0063	- 0.0004	- 0.0087
	5702	S-vertical	428	0.0098	0.0079	0.0109
	5704	Transverse	431	0.0099	0.0048	0.0065
S1	5603	N-vertical	434	0.0423	- 0.0522	- 0.0042
	5602	S-vertical	437	0.0158	0.0517	0.0209
	5604	Transverse	440	0.0280	- 0.0020	0.0163
	5405	S-top	443	0.0339	0.0947	0.0393
	5406	N-top	446	- 0.0644	0.0119	0.0297
	5407	N-bottom	449	- 0.0136	- 0.0743	- 0.0334
	5408	S-bottom	452	0.0684	- 0.0090	0.0318

^a South represents the positive x direction.

^b Up represents the positive y direction.

^c West represents the positive z direction.

Hanger 6002. A gravity deflection of 0.165 in. occurs at the top of the west vessel periphery, whereas only a 0.05-in. deflection is caused by vacuum pressure.

In the environmental thermal case, a deformation of 0.086 in. at the vessel shell is caused by the 10°F change of temperature. In the magnet cool-down load case, since the magnet hanger configuration is designed to avoid the thermal lock-in stress, no force is created in any hanger or in the vessel. The magnets are allowed to shrink; consequently, the maximum deformation is close to 1 in. (0.982 in.) at the lower major lobe of the transition magnet T2.

Under the 9.33×10^5 lb magnetic force in the normal operation condition, the vessel shell is displaced 0.156 in. longitudinally whereas the Yin-Yang magnet pair translates 0.182 in. The axicell module transfers a two-million-pound magnetic force to the vessel and displaces it by 0.182 in. The magnetic loads under fault condition are bigger than the normal magnetic operating loads and produce a 0.125-in. displacement in the center vessel. The misalignment load cases produce negligible displacement on the magnets and vessel.

In summary, the total static displacement in any of the three global directions at any point on the vessel is less than a quarter of an inch. The magnet deformations exceed 1 in., especially in the longitudinal direction; this is mostly caused by the magnet cool-down thermal load case. For the purpose of magnet alignment, the cool-down deformation is provided for by the GDC model, which was computed by a different program.

Like the seismic-induced forces, the seismic displacements can be in both positive and negative directions of any axis. The Yin-Yang module experiences the largest dynamic deflection of the whole magnet and vessel system, especially in the transverse direction (0.937 in.) under transverse excitation. Combining the seismic and static cases, the Yin-Yang module deflects about 1 in. in each of the three directions whereas the vessel plug deflects 0.845, 0.316, and 0.523 in. in the transverse, vertical, and longitudinal directions, respectively. At the northwest beam dome on the plug vessel, deformations are 0.715, 0.339, and 0.499 in. in the transverse, vertical, and longitudinal directions, respectively.

8.4 Magnet Hanger and Strut Load

GDC provided monoball hinges at the magnet end of the support, and PDM furnished the

brackets at the vessel interface. To be consistent, both contractors designed their components to the hanger loads issued by LLNL from our analyses.

In the gravity load case most vertical hangers carry only the magnet weight. Exceptions are hangers on solenoids S1 and S6 that couple with the drag struts to resist the moment caused by the eccentricity of the trim coils and the solenoid pair (Table 8-7). As a result, those hangers (5813 and 5812, 5603 and 5602) bear forces higher than the weight of the solenoids.

Two of the vertical hangers (6101 and 5922) supporting magnets T2 and T1 are located close to the center of gravity; therefore, they carry most of the loads whereas the adjacent vertical hangers (6102 and 5923) only function as stabilizers. The vacuum and two thermal load cases generate negligible loads in the magnet support system.

In both magnetic load cases, the longitudinal force components in the drag struts sum up to the total input magnetic forces. Similarly, the forces in the hangers and struts reflect the input loads in the 10 magnet misalignment load cases.

When the gravity load of the model is applied in the transverse direction (1-g transverse case), the transverse strut solenoids 5814 and 5604 carry forces greater than the solenoid weights because of eccentricity of the solenoid pair. The magnet weight in the 1-g longitudinal case is resisted by drag struts in all modules.

One way to qualify the seismic response is to evaluate the equivalent acceleration levels (g factors); a g factor is simply the ratio of an element's dynamic forces to its corresponding static forces. In the case of hanger loads, we combine the results from three static cases in the same way as the seismic forces are combined by the method of square root of the sum of the square (SRSS), as shown in Tables 8-8 and 8-9. The g factors of the hangers and struts are shown in the last column of Table 8-9.

On average, the Yin-Yang module has the highest g factors whereas the solenoid module has the lowest in the magnet array except for the vertical Hangers 6102 and 5923, which have values of 1.29 g and 0.89 g, respectively. Statically, the function of these two hangers is stabilization but they become active in dynamic excitation. Nevertheless, their stresses are too far below the design load to cause any concern.

The transverse struts are expected to resist the load from transverse excitation; however, when under the vertical excitation some of them experience a dynamic coupling effect and carry considerable dynamic loads (see Table 8-9). As a

Table 8-7. Magnet hanger and strut load for six static load cases.

Magnet	Hanger No.	Location	Element No.	Gravity (10 ³ lb)	Vacuum pressure case (10 ³ lb)	Mn (10 ³ lb)	Mf (10 ³ lb)	Te (10 ³ lb)	Tc (10 ³ lb)
Yin Yang	6001	N-vertical	313	- 209.3	0.4	- 0.3	0	0	2.2
	6005	S-vertical	314	- 269.9	0.4	0.4	0	0	0.5
	6002	M-vertical	315	- 381.2	- 0.3	0.1	0	0	- 3.0
	6007	Transverse	316	0.2	- 0.3	- 0.1	0	0	- 2.5
	6003	S-drag	317	0.3	- 0.5	- 478.6	0	- 0.1	- 4.9
	6004	N-drag	318	- 0.3	0.5	- 478.3	0	0.1	4.9
T2	6101	S-vertical	319	- 123.8	- 0.4	- 0.1	0	0	3.3
	6102	N-vertical	320	- 0.7	0.1	0.1	0	0	1.4
	6103	Transverse	321	0	0.4	0.1	0	0	4.3
T1	5922	N-vertical	322	- 64.4	0	0.1	0.1	0	- 0.4
	5923	S-vertical	323	1.7	0	- 0.1	- 0.1	0	0.1
	5924	Transverse	324	0	0	- 0.1	- 0.1	0	- 0.5
A2	5913	N-vertical	333	40.8	0	0	0	0	0.4
	5912	S-vertical	334	40.7	0	0.1	0.2	0	- 0.5
	5914	Transverse	335	81.5	0	- 0.1	- 0.1	0	- 1.0
A1	5903	N-vertical	336	- 33.6	0	0	0	0	0.2
	5902	S-vertical	337	- 33.6	0	0	0	0	0.2
	5904	Transverse	338	67.2	0	0	0	0	0.5
S6	5813	N-vertical	339	- 32.8	0	0.1	0.1	0	1.0
	5812	S-vertical	340	- 32.8	0	- 0.1	0.1	0	1.0
	5814	Transverse	341	0	0	0.1	0.1	0	2.6
	5905	S-top	342	28.1	- 0.7	- 610.9	- 872.4	- 0.2	- 0.9
	5906	N-top	343	- 9.5	0.7	- 620.0	- 880.5	0.2	0.6
	5907	N-bottom	344	- 0.5	- 0.7	- 611.0	- 872.5	- 0.2	1.7
	5908	S-bottom	345	- 17.1	0.7	- 620.0	- 880.6	0.2	- 1.4
S5	5803	N-vertical	346	- 16.0	0	0	0	0	0
	5802	S-vertical	347	- 16.0	0	0	0	0	0
	5804	Transverse	348	0	0	0	0	0	- 0.1
S3	5703	N-vertical	349	- 32.0	0	0	0	0	0
	5702	S-vertical	350	- 32.0	0	0	0	0	0
	5704	Transverse	351	0	0	0	0.1	0	0
S1	5603	N-vertical	352	- 37.9	0	0	- 0.1	0	- 0.1
	5602	S-vertical	353	- 37.9	0	0	0.1	0	0.1
	5604	Transverse	354	75.8	0	0	- 0.1	0	0.2
	5405	S-top	355	13.6	- 0.2	0.5	792.4	0.1	- 0.1
	5406	N-top	356	0.4	0.2	- 0.5	795.3	- 0.1	- 0.1
	5407	N-bottom	357	- 8.6	- 0.2	0.5	792.4	0.1	0.1
	5408	S-bottom	358	- 5.5	0.2	- 0.5	795.4	- 0.1	- 0.1

Table 8-8. Magnet hanger and strut load for three 1-g gravity load cases.

Magnet	Hanger No.	Location	Element No.	1-g transverse (10 ³ lb)	1-g vertical (10 ³ lb)	1-g longitudinal (10 ³ lb)	SRSS (10 ³ lb)
Yin Yang	6001	N-vertical	313	- 243.7	- 209.3	3.5	321.2
	6005	S-vertical	314	- 244.4	- 209.9	0.3	322.2
	6002	M-vertical	315	315.0	- 381.2	0.1	494.5
	6007	Transverse	316	646.2	0.2	0.1	646.2
	6003	S-drag	317	511.1	0.3	- 474.4	697.1
	6004	N-drag	318	- 511.1	- 0.3	- 474.4	697.3
T2	6101	S-vertical	319	- 20.6	- 123.8	0	125.5
	6102	N-vertical	320	20.4	- 0.7	0.2	20.4
	6103	Transverse	321	126.8	0	- 0.2	126.8
T1	5922	N-vertical	322	7.5	- 64.4	0.1	64.8
	5923	S-vertical	323	- 7.5	- 7.7	0	10.8
	5924	Transverse	324	72.2	0	0	72.2
A2	5913	N-vertical	333	0.1	- 40.8	0	40.8
	5912	S-vertical	334	0	- 40.7	0	40.7
	5914	Transverse	335	81.1	0	0	81.1
A1	5903	N-vertical	336	0	- 33.6	0	33.6
	5902	S-vertical	337	0	- 33.6	0	33.6
	5904	Transverse	338	66.2	0	0	66.2
S6	5813	N-vertical	339	0	- 32.8	- 0.1	32.8
	5812	S-vertical	340	0	- 32.8	- 0.1	32.8
	5814	Transverse	341	64.3	0	- 0.1	64.3
	5905	S-top	342	- 19.6	28.1	- 81.1	88.0
	5906	N-top	343	29.1	- 9.5	- 82.0	87.5
	5907	N-bottom	344	- 12.2	- 0.5	- 81.3	82.3
	5908	S-bottom	345	1.8	- 17.1	82.0	83.8
S5	5803	N-vertical	346	0	- 16.0	0	16.0
	5802	S-vertical	347	0	- 16.0	0	16.0
	5804	Transverse	348	32.1	0	0	32.1
S3	5703	N-vertical	349	0	- 32.0	0	32.0
	5702	S-vertical	350	0	- 32.0	0	32.0
	5704	Transverse	351	64.0	0	0	64.0
S1	5603	N-vertical	352	0	- 37.9	0	37.9
	5602	S-vertical	353	0	- 37.9	0	37.9
	5604	Transverse	354	75.8	0	0	75.8
	5405	S-top	355	- 2.1	13.6	- 44.4	46.5
	5406	N-top	356	10.2	0.4	- 45.2	46.3
	5407	N-bottom	357	3.9	8.6	- 44.4	45.4
	5408	S-bottom	358	- 12.0	- 5.5	- 45.2	47.1

Table 8-9. Magnet hanger and strut load for seismic load cases.

Magnet	Hanger No.	Location	Element No.	1-g transverse (10 ³ lb)	1-g vertical (10 ³ lb)	1-g longitudinal (10 ³ lb)	SRSS (10 ³ lb)	g factor
Yin	6001	N-vertical	313	236.0	57.1	19.1	244.0	0.76
	6005	S-vertical	314	223.0	55.5	29.4	228.0	0.71
Yang	6002	M-vertical	315	266.0	195.0	53.1	334.0	0.68
	6007	Transverse	316	535.0	39.4	51.0	539.0	0.83
	6003	S-drag	317	445.0	46.7	278.0	527.0	0.78
	6004	N-drag	318	430.0	77.6	347.0	557.0	0.80
T2	6101	S-vertical	319	28.4	61.3	6.8	67.9	0.54
	6102	N-vertical	320	13.6	22.1	4.4	26.4	1.29
	6103	Transverse	321	70.3	22.4	9.8	74.4	0.59
T1	5922	N-vertical	322	8.6	17.3	9.4	21.5	0.33
	5923	S-vertical	323	5.6	5.4	5.6	9.6	0.89
	5924	Transverse	324	35.1	14.0	5.2	38.1	0.53
A2	5913	N-vertical	333	7.5	10.7	3.0	13.4	0.33
	5912	S-vertical	334	5.8	15.0	5.3	17.0	0.42
	5914	Transverse	335	32.8	13.9	6.1	36.1	0.45
A1	5903	N-vertical	336	5.8	9.3	3.9	11.7	0.35
	5902	S-vertical	337	4.8	12.3	5.1	14.2	0.42
	5904	Transverse	338	31.9	13.5	4.0	34.9	0.53
S6	5813	N-vertical	339	6.5	12.6	5.2	15.1	0.46
	5812	S-vertical	340	6.0	12.7	5.2	15.0	0.46
	5814	Transverse	341	55.1	21.6	5.1	59.4	0.92
	5905	S-top	342	14.4	15.2	45.4	50.0	0.57
	5906	N-top	343	21.6	11.7	43.4	49.9	0.57
	5907	N-bottom	344	12.8	15.5	39.4	44.2	0.54
	5908	S-bottom	345	27.3	12.9	41.4	53.2	0.64
S5	5803	N-vertical	346	5.4	6.4	2.7	8.8	0.55
	5802	S-vertical	347	4.2	6.5	2.7	8.3	0.52
	5804	Transverse	348	15.5	6.5	1.4	16.9	0.53
S3	5703	N-vertical	349	10.2	13.0	3.3	16.8	0.53
	5702	S-vertical	350	6.4	12.5	3.8	14.6	0.46
	5704	Transverse	351	31.7	17.1	6.3	36.6	0.57
S1	5603	N-vertical	352	7.6	11.9	1.2	14.2	0.38
	5602	S-vertical	353	7.8	11.7	1.3	14.1	0.37
	5604	Transverse	354	38.8	23.2	8.3	46.0	0.61
	5405	S-top	355	14.0	14.2	47.2	51.2	0.55
	5406	N-top	356	13.4	11.8	47.4	50.6	0.55
	5407	N-bottom	357	13.2	14.8	45.2	49.4	0.54
	5408	S-bottom	358	18.6	20.2	46.2	53.8	0.57

result, the combined dynamic load of strut 5814 has a g factor of up to 0.92. The rotation in the two most dominant mode shapes explains this dynamic coupling effect as can be seen clearly from the figures.

8.5 Vessel Foundation Load

The load from the vessel is distributed among the support members according to their relative stiffnesses. The plug vessel sits on four massive reinforced concrete piers that are stiffer than the carbon steel frames of the center vessel support system (CVSS). The middle of the vessel is restrained in the vertical direction only at the shear wall by two short steel columns that are quite flexible compared to the rest of the support structure. The boundary springs representing the rotational stiffness of the foundation mats also contribute to the overall support stiffnesses.

The foundation loads are the resisting forces and moments of the piers, columns, and knees extracted at the center line of the foundation mats from the computer model. Their static load cases are tabulated in Tables 8-10 through 8-14. The support member locations designated in Tables 8-10

through 8-14 as NW and SW are to the north and south of the outer pair (see Fig. 4-1) whereas those designated NE and SE are to the north and south of the inner pair.

Under the gravity load case, the total vertical force carried by the support system is about 4.1×10^6 lb, which equals the total weight of half of the vessel. The total vertical force (Fy) on the four piers is 3.3×10^6 lb or 80 percent of the total load (see Table 8-10). The inner-pier pair carries more axial load than the outer pair by about 356,000 lb. Part of this load is from the weight of the axicell region. The four columns in the center vessel carry approximately equal amounts of the axial forces, which sum to 641,700 lb (16 percent). The remaining load of 185,400 lb (4 percent) goes to the two short columns at the middle of the vessel.

The bending moments about the transverse axis (Mx) produced by the gravity load case in all four piers are on the order of 3.0×10^6 in.-lb. The moments about the longitudinal axis (Mz) in the outer piers at the open end of the vessel are about twice as large as those on the inner pair. The difference in torsion (My) between the outer and inner piers is more significant because the inner-pier pair is restrained by the center vessel.

Table 8-10. Foundation loads for the gravity load.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	30.0	741.4	-14.4	3,205.0	-1,534.0	6,310.0
SE pier	247	12.9	910.8	12.7	-3,138.0	-24.1	3,828.0
NW pier	246	-32.9	727.5	-14.4	3,153.0	1,776.0	-6,396.0
NE pier	248	-11.5	913.9	12.7	-3,004.0	-17.6	-3,880.0
Subtotal		-1.1	3,294.0	-3.0			
SW CVSS column	388	0.9	127.2	-14.4	-526.2	-17.1	-114.5
SE CVSS column	390	0.5	132.5	10.5	278.4	17.3	-116.0
NW CVSS column	389	-0.7	131.6	-14.6	-536.2	16.2	104.9
NE CVSS column	391	-0.4	135.1	11.0	290.7	-16.5	112.6
SW CVSS knee	408	-12.2	28.8	-0.2	-18.8	-6.6	198.6
SE CVSS knee	410	-12.1	28.0	-0.1	-11.3	-4.4	190.0
NW CVSS knee	409	12.9	30.2	-0.2	-19.2	-6.8	-215.4
NE CVSS knee	411	12.3	28.4	-0.1	-11.1	4.4	-195.5
Subtotal		1.1	641.7	-8.0			
N short column	434	0.0	92.0	0.0			
S short column	435	0.0	93.4	0.0			
Subtotal		0.0	185.4	0.0			
Total		0.0	4,121.0	-11.0			

Table 8-11. Foundation loads for the vacuum pressure load.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	46.9	- 38.6	48.8	2,742.0	5,305.0	4,128.0
SE pier	247	46.1	45.2	2.1	2,745.0	9,191.0	1,802.0
NW pier	246	- 47.1	- 42.3	50.0	2,820.0	5,536.0	4,083.0
NE pier	248	- 46.1	48.7	1.9	2,688.0	- 9,261.0	1,827.0
Subtotal		- 0.2	12.9	102.8			
SW CVSS column	388	1.3	1.1	0.1	1.2	- 26.4	240.3
SE CVSS column	390	1.5	10.0	1.3	24.7	23.2	- 269.4
NW CVSS column	389	- 1.2	0.5	0.1	1.6	26.1	236.3
NE CVSS column	391	1.5	9.9	1.2	23.0	- 22.8	265.4
SW CVSS knee	408	5.6	- 10.9	0.0	0.9	0.0	189.1
SE CVSS knee	410	5.7	- 11.0	0.0	- 2.7	- 1.1	200.8
NW CVSS knee	409	- 5.6	- 10.8	0.0	0.0	0.1	187.1
NE CVSS knee	411	- 5.5	- 10.6	0.0	- 2.9	1.2	196.2
Subtotal		0.3	- 21.9	2.6			
N short column	434	0.0	4.7	0.0			
S short column	435	0.0	4.5	0.0			
Subtotal		0.0	9.1	0.0			
Total		0.1	0.1	105.4			

Table 8-12. Foundation loads for the environmental thermal load.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	20.2	35.7	41.1	3,929.0	1,430.0	- 3,443.0
SE pier	247	26.4	- 17.5	27.8	2,070.0	691.0	- 3,747.0
NW pier	246	- 20.9	38.0	42.8	4,001.0	- 1,587.0	3,349.0
NE pier	248	- 26.0	- 18.3	27.8	2,077.0	- 675.9	3,667.0
Subtotal		0.3	37.9	139.5			
SW CVSS column	388	- 2.8	42.1	51.9	1,944.0	- 12.3	- 27.0
SE CVSS column	390	- 0.6	- 76.3	27.1	965.4	8.3	- 191.4
NW CVSS column	389	2.8	42.2	51.9	1,945.0	11.9	22.8
NE CVSS column	391	0.6	- 76.1	27.1	965.3	- 8.0	186.5
SW CVSS knee	408	17.7	33.6	0.4	47.2	17.6	- 616.5
SE CVSS knee	410	14.6	25.3	1.7	16.0	5.7	- 597.4
NW CVSS knee	409	- 17.5	33.3	0.4	47.2	- 17.6	612.2
NE CVSS knee	411	- 14.5	25.1	0.2	16.0	- 5.7	593.4
Subtotal		0.3	49.3	159.2			
N short column	434	0.0	- 43.7	0.0			
S short column	435	0.0	- 43.8	0.0			
Subtotal		0.0	- 87.5	0.0			
Total		0.6	- 0.3	298.7			

Table 8-13. Foundation loads for the magnetic load under normal conditions.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	-0.8	35.6	29.0	3,871.0	2,905.0	-1,830.0
SE pier	247	-1.1	8.2	28.0	3,886.0	3,408.0	-1,444.0
NW pier	246	-23.1	-129.6	48.6	3,252.0	2,180.0	-1,551.0
NE pier	248	13.0	61.3	36.3	3,689.0	-2,475.0	-2,648.0
Subtotal		-12.1	-24.5	141.9			
SW CVSS column	388	-10.0	-47.3	0.5	-34.5	43.1	560.5
SE CVSS column	390	-3.5	25.1	0.6	-8.4	-45.5	195.7
NW CVSS column	389	-0.8	-23.7	2.9	42.6	-44.2	-371.6
NE CVSS column	391	2.4	5.4	3.2	73.5	35.0	-499.3
SW CVSS knee	408	3.5	-16.9	0.0	3.5	1.2	163.4
SE CVSS knee	410	-3.4	4.5	0.0	0.0	-0.1	130.1
NW CVSS knee	409	10.8	24.3	-0.1	-8.0	2.2	-314.1
NE CVSS knee	411	13.4	26.7	0.1	-1.5	-0.1	-425.4
Subtotal		12.3	-1.8	7.0			
N short column	434	0.0	16.4	0.0			
S short column	435	0.0	9.8	0.0			
Subtotal		0.0	26.3	0.0			
Total		0.3	-0.1	148.9			

Table 8-14. Foundation loads for the magnetic load under fault conditions.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	1.0	-10.8	9.5	916.1	668.6	-245.9
SE pier	247	-2.6	29.8	9.1	924.6	1,013.0	305.9
NW pier	246	1.1	-10.7	11.7	1,050.0	-402.5	-167.4
NE pier	248	-5.7	-22.1	12.1	806.8	100.3	236.2
Subtotal		-6.3	-13.9	42.3			
SW CVSS column	388	-19.0	-84.1	4.5	133.0	73.0	1,529.0
SE CVSS column	390	10.3	21.2	-0.5	-3.8	-105.4	-740.7
NW CVSS column	389	2.4	-4.0	8.9	294.8	-34.4	-470.8
NE CVSS column	391	-0.3	40.8	13.2	482.5	35.8	35.7
SW CVSS knee	408	-11.9	8.2	0.2	23.5	8.4	829.7
SE CVSS knee	410	9.9	-10.9	0.1	6.6	2.4	-530.5
NW CVSS knee	409	13.1	26.5	0.0	6.4	-2.8	-413.8
NE CVSS knee	411	1.8	3.8	0.2	19.5	-6.8	-24.8
Subtotal		6.4	1.4	26.6			
N short column	434	0.0	47.3	0.0			
S short column	435	0.0	-34.9	0.0			
Subtotal		0.0	12.4	0.0			
Total		1.6	0.1	68.9			

The moments and torsions on the CVSS are much smaller than those the piers experience because the steel frame has a lower stiffness than the massive concrete piers and because the weight of the center vessel is much smaller than that of the plug. The knees (transverse bracings of the CVSS) resist nearly twice as much moment about the longitudinal axis as do the columns.

All other static load cases produce foundation loads either smaller than or of the same magnitude as those produced by the gravity load case, with a few exceptions (see Tables 8-11 through 8-14). For example, the vacuum load case generates a large torsion of 9×10^6 in.-lb in the inner pier pair. The environmental thermal load case bends the outer CVSS column pair with an M_x of close to 2.0×10^6 million in.-lb. The normal operating magnetic force produces an axial force of 130,000 lb in the north-west pier. The fault-condition magnetic force in the solenoid module is directed opposite to that in the axicell module; therefore, most of the forces are cancelled at the vessel shell, and very little force is transferred to the foundations.

The seismic loads produced by the earthquake excitation in the three global directions are fractions of the static loads generated by the 1-g gravity load in the corresponding directions. Tables 8-10, 8-15, and 8-16 depict the 1-g static

loads in the foundations. Table 8-17 gives the SRSS combined 1-g loads. The seismic loads are shown in Tables 8-18 through 8-19.

The 1-g vertical gravity load case is the same as the static gravity load case that was discussed above. The vertical excitation generally produces low total axial forces but high moments (see Table 8-18). The equivalent g factors of the axial force and moment are 0.13 and 0.99.

The 1-g transverse gravity load case reveals that the transverse vessel load distribution, in its support system, differs from the vertical gravity load case. The total transverse base shear (F_x) absorbed by the plug is 68 percent of the total load, which is smaller than the axial load (80 percent) caused by the 1-g vertical load case (see Table 8-15). The remaining shear (32 percent) goes to the CVSS where the knees are designed to resist the transverse load. The short columns are not active in this load case because they are not allowed to resist shear or bending. The transverse seismic excitation produces transverse shear at a g factor of 0.38.

The transverse excitation creates a large overturning moment about the longitudinal axis of the vessel. To counteract this overturning moment, the inner-pier pair experiences axial loads that are about the same as those from the vertical gravity

Table 8-15. Foundation loads for 1-g gravity in the transverse direction.

Location	Element No.	F_x (10^3 lb)	F_y (10^3 lb)	F_z (10^3 lb)	M_x (10^3 in.-lb)	M_y (10^3 in.-lb)	M_z (10^3 in.-lb)
SW pier	245	- 620.0	9.8	20.9	3,628.0	5,975.0	136,000.0
SE pier	247	- 697.1	919.1	16.3	4,269.0	- 9,027.0	123,200.0
NW pier	246	- 782.1	- 78.4	- 0.4	- 4,292.0	6,085.0	129,600.0
NE pier	248	743.6	- 818.0	- 2.8	- 5,460.0	- 3,241.0	111,000.0
Subtotal		2,842.8	1,825.3	40.4	17,649.0	24,328.0	499,800.0
SW CVSS column	388	10.9	- 603.9	46.0	1,184.0	983.0	10,940.0
SE CVSS column	390	- 14.3	- 526.8	- 50.6	- 1,436.0	- 824.0	11,540.0
NW CVSS column	389	- 9.4	534.3	- 43.0	- 1,108.0	1,068.0	11,390.0
NE CVSS column	391	- 40.0	498.7	45.2	1,273.0	- 890.2	12,710.0
SW CVSS knee	408	- 309.7	678.4	- 1.2	- 43.1	- 4.3	9,359.0
SE CVSS knee	410	- 313.3	662.0	- 1.5	- 26.2	8.4	9,652.0
NW CVSS knee	409	- 298.6	- 635.2	1.0	30.6	- 1.2	9,386.0
NE CVSS knee	411	- 315.8	- 643.8	1.1	1.5	15.2	10,210.0
Subtotal		1,290.0	4,783.0	189.5	5,102.4	3,794.3	85,187.0
N short column	434	0.0	0.0	0.0			
S short column	435	0.0	0.0	0.0			
Subtotal		0.0	0.0	0.0			
Total ^a		4,133.0	6,608.4	230.0	22,751.4	28,122.3	584,987.0

^a Absolute sum.

Table 8-16. Foundation loads for 1-g gravity in the longitudinal direction.

Location	Element No.	F _x (10 ³ lb)	F _y (10 ³ lb)	F _z (10 ³ lb)	M _x (10 ³ in.-lb)	M _y (10 ³ in.-lb)	M _z (10 ³ in.-lb)
SW pier	245	2.6	- 283.9	512.4	33,610.0	14,570.0	- 1,381.0
SE pier	247	21.4	70.2	513.4	32,290.0	12,320.0	- 3,724.0
NW pier	246	22.4	- 457.3	543.5	33,700.0	- 14,470.0	- 3,339.0
NE pier	248	- 10.7	150.8	524.3	32,280.0	- 11,000.0	- 167.0
Subtotal		57.1	962.2	2,093.6	131,880.0	53,360.0	8,611.0
SW CVSS column	388	6.2	- 1,033.0	523.1	18,510.0	- 146.4	- 940.2
SE CVSS column	390	10.4	804.7	475.3	16,950.0	140.5	- 1,157.0
NW CVSS column	389	- 8.1	- 1,054.0	529.8	18,750.0	142.8	865.8
NE CVSS column	391	- 11.3	808.5	480.2	17,130.0	138.6	1,125.0
SW CVSS knee	408	84.8	- 181.6	4.8	438.5	153.1	- 1,795.0
SE CVSS knee	410	- 22.5	50.7	4.6	420.8	146.4	366.2
NW CVSS knee	409	80.8	- 171.2	4.8	442.2	- 154.8	1,703.0
NE CVSS knee	411	24.8	56.3	4.7	425.2	- 148.3	- 422.6
Subtotal		248.9	4,160.0	2,027.3	73,066.7	1,170.9	3,374.8
N short column	434	0.0	0.0	0.0			
S short column	435	0.0	0.0	0.0			
Subtotal		0.0	0.0	0.0			
Total ^a		306.0	5,122.0	4,120.9	204,946.7	54, ^a 10.9	16,985.8

^a Absolute sum.**Table 8-17. Foundation loads for the combined (SRSS) 1-g gravity load.**

Location	Element No.	F _x (10 ³ lb)	F _y (10 ³ lb)	F _z (10 ³ lb)	M _x (10 ³ in.-lb)	M _y (10 ³ in.-lb)	M _z (10 ³ in.-lb)
SW pier	245	620.7	794.0	513.0	33,957.0	15,822.0	136,146.0
SE pier	247	697.6	1,295.9	513.8	32,722.0	15,273.0	123,316.0
NW pier	246	783.1	911.5	543.7	34,118.0	15,798.0	129,801.0
NE pier	248	743.8	1,235.8	524.5	32,876.0	11,468.0	111,068.0
Subtotal		2,845.2	4,237.2	2,095.0	133,673.0	58,361.0	500,331.0
SW CVSS column	388	12.6	1,203.0	525.3	18,548.0	994.0	10,980.0
SE CVSS column	390	17.7	971.0	475.5	17,011.0	836.0	11,598.0
NW CVSS column	389	12.4	1,189.0	531.7	18,783.0	1,078.0	11,423.0
NE CVSS column	391	41.6	959.5	482.5	17,177.0	901.1	12,760.0
SW CVSS knee	408	321.3	702.9	5.0	441.0	153.3	9,531.0
SE CVSS knee	410	314.3	664.5	4.8	422.0	146.7	9,660.0
NW CVSS knee	409	309.6	658.6	4.9	443.5	155.0	9,541.0
NE CVSS knee	411	317.0	646.9	4.8	425.3	149.1	10,020.0
Subtotal		1,346.5	6,995.4	2,034.5	73,250.0	4,413.2	85,713.0
N shortcolumn	434	0.0	92.0	0.7			
S shortcolumn	435	0.0	93.4	0.7			
Subtotal		0.0	185.4	0.0			
Total		4,191.7	11,232.6	4,129.5	206,923.0	62,774.0	586,044.0

Table 8-18. Foundation loads for the transverse seismic excitation load.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	228.0	38.9	25.1	3,410.0	2,840.0	76,100.0
SE pier	247	254.0	537.0	23.5	3,220.0	8,690.0	62,800.0
NW pier	246	347.0	36.1	13.0	3,550.0	2,760.0	68,300.0
NE pier	248	286.0	425.0	13.3	4,390.0	2,950.0	53,600.0
Subtotal		1,115.0	1,037.0	74.9	14,570.0	17,240.0	260,800.0
SW CVSS column	388	10.8	283.0	20.5	80.2	412.0	4,840.0
SE CVSS column	390	4.3	232.0	23.2	664.0	344.0	4,860.0
NW CVSS column	389	1.1	249.0	19.2	489.0	455.0	5,070.0
NE CVSS column	391	12.2	220.0	20.5	583.0	379.0	5,420.0
SW CVSS knee	408	4.3	317.0	0.6	21.1	22.6	4,250.0
SE CVSS knee	410	139.0	300.0	0.7	17.9	2.5	4,200.0
NW CVSS knee	409	137.0	295.0	0.5	14.5	0.8	4,260.0
NE CVSS knee	411	140.0	291.0	0.6	6.6	5.5	4,450.0
Subtotal		448.0	2,187.0	85.8	1,876.3	5,329.4	37,350.0
N short column	434	0.0	13.8	0.0			
S short column	435	0.0	15.8	0.0			
Subtotal		0.0	29.6	0.0			
Total		1,563.7	3,253.6	160.7	16,446.3	22,569.4	298,450.0

Table 8-19. Foundation loads for the vertical seismic excitation load.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	24.7	96.0	14.6	1,050.0	1,550.0	4,070.0
SE pier	247	11.3	75.8	8.8	949.0	1,220.0	1,850.0
NW pier	246	16.0	89.1	11.5	1,150.0	2,200.0	6,350.0
NE pier	248	11.6	91.4	11.5	916.0	1,996.0	2,230.0
Subtotal		63.6	352.3	46.4	4,065.0	6,960.0	14,500.0
SW CVSS column	388	2.3	18.7	2.1	71.5	27.1	269.0
SE CVSS column	390	3.4	23.8	1.9	51.4	23.2	350.0
NW CVSS column	389	1.3	17.5	1.7	56.5	28.2	274.0
NE CVSS column	391	2.6	19.7	1.8	48.0	23.2	376.0
SW CVSS knee	408	6.9	15.4	0.1	3.1	1.0	211.0
SE CVSS knee	410	8.0	17.3	0.1	4.1	1.3	261.0
NW CVSS knee	409	7.7	17.2	0.0	1.5	0.8	232.0
NE CVSS knee	411	9.0	18.7	0.0	2.8	0.9	294.0
Subtotal		41.2	148.3	7.7	238.9	105.7	2,267.0
N short column	434	0.0	11.3	0.0			
S short column	435	0.0	10.0	0.0			
Subtotal		0.0	21.3	0.0			
Total		104.8	521.9	54.1	4,303.9	7,065.7	16,767.0

load case. In addition to the axial load in the support members, large bending moments are produced.

When subjected to a 1-g longitudinal gravity load the antisymmetric model of the vessel reveals another load distribution in the vessel support systems. The plug vessel resists 51 percent of the longitudinal shear whereas the CVSS, stiffened by the longitudinal cross-bracings, carries 49 percent.

The dynamic longitudinal shear is at 0.48 g. In this excitation direction, the load is applied in the direction coincident with the foundation array. The overturning moment is shared among the support systems. As a result, the moments in the piers (see Table 8-20) are not as great as those from the 1-g transverse load case. The torsions in the piers are 15 million in.-lb, the largest torsion of the three gravity load cases.

The seismic results are combined by SRSS as shown in Table 8-21. The ratios of the combined seismic and static loads depicted in Table 8-22 are the equivalent acceleration levels (g factors).

As mentioned in Sec. 7.5, the average spectral accelerations weighted by the modal masses are 0.4, 0.13, and 0.32 g in the transverse, vertical, and longitudinal earthquake excitations, respectively.

Computed from the major-component dynamic force responses in the vessel, the corresponding g factors in three excitations are 0.38, 0.13, and 0.48 g. The dynamic responses are in good agreement with the model's dynamic characteristics, which verifies the model and the analysis method.

Each excitation produces forces and moments in the primary component as well as in the orthogonal components. The combined dynamic response of three excitations could yield different equivalent g's than those computed in each excitation direction. Table 8-22 gives the equivalent g factors of the combined dynamic responses. The masses of the bottom half of the piers are hardly excited. This causes the low force and shear g factors in the piers, from 0.32 to 0.39 g. The CVSS has slightly higher g factors ranging from 0.45 to 0.52 g.

The static and seismic foundation loads are combined and tabulated for evaluation of the pier and foundation mats. The west piers are designed for this program, and they are able to resist MFTF-B axicell configuration loads. Unfortunately, the east piers were originally designed for the MFTF program's plug-vessel stand-alone configuration. At that time the piers were designed to resist smaller values of Mx and Mz than those the MFTF-B axicell configuration produces.

Table 8-20. Foundation loads for the longitudinal seismic excitation load.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	16.5	139.0	160.0	15,200.0	7,840.0	4,160.0
SE pier	247	11.7	33.1	159.0	14,500.0	6,420.0	2,480.0
NW pier	246	33.0	253.0	178.0	14,900.0	7,860.0	3,820.0
NE pier	248	16.0	61.3	165.0	14,200.0	6,400.0	2,410.0
Subtotal		77.2	486.4	662.0	58,800.0	28,520.0	12,870.0
SW CVSS column	388	3.5	553.0	274.0	9,690.0	74.0	463.0
SE CVSS column	390	5.6	421.0	248.0	8,840.0	71.6	583.0
NW CVSS column	389	4.8	550.0	273.0	9,670.0	82.7	589.0
NE CVSS column	391	6.0	421.0	247.0	8,830.0	80.3	633.0
SW CVSS knee	408	43.7	93.4	1.8	208.0	80.5	916.0
SE CVSS knee	410	12.7	28.6	1.7	199.0	76.9	223.0
NW CVSS knee	409	45.5	96.0	1.7	207.0	79.9	1,000.0
NE CVSS knee	411	11.9	27.2	1.7	197.0	76.4	191.0
Subtotal		133.7	2,190.2	1,048.9	35,111.0	622.3	4,598.0
N short column	434	0.0	0.0	0.0			
S short column	435	0.0	0.0	0.0			
Subtotal		0.0	0.0	0.0			
Total		210.9	2,676.6	1,170.9	93,911.0	29,142.3	17,468.0

Table 8-21. Foundation loads for the combined (SRSS) seismic load.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	230.0	198.0	163.0	15,600.0	8,480.0	76,300.0
SE pier	247	255.0	548.0	161.0	14,800.0	10,900.0	62,900.0
NW pier	246	349.0	280.0	179.0	15,400.0	8,620.0	68,700.0
NE pier	248	287.0	444.0	166.0	14,900.0	7,320.0	53,700.0
Subtotal		1,121.0	1,459.0	669.0	60,700.0	35,320.0	261,600.0
SW CVSS column	388	11.6	622.0	275.0	9,700.0	419.0	4,870.0
SE CVSS column	390	7.8	481.0	249.0	8,870.0	352.0	4,910.0
NW CVSS column	389	5.1	604.0	274.0	9,680.0	463.0	5,110.0
NE CVSS column	391	13.8	475.0	248.0	8,850.0	388.0	5,470.0
SW CVSS knee	408	150.0	331.0	1.8	209.0	80.5	4,350.0
SE CVSS knee	410	140.0	302.0	1.8	200.0	77.0	4,210.0
NW CVSS knee	409	145.0	311.0	1.8	208.0	79.9	4,380.0
NE CVSS knee	411	141.0	293.0	1.8	197.0	76.6	4,460.0
Subtotal		614.0	3,419.0	1,053.2	37,914.0	1,936.0	37,760.0
N short column	434	0.0	18.1	0.0			
S short column	435	0.0	19.2	0.0			
Subtotal		0.0	37.3	0.0			
Total		1,735.3	4,915.3	1,722.2	98,614.0	37,256.0	299,360.0

Table 8-22. Equivalent acceleration levels (g factors) of the foundation loads.

Location	Element No.	Fx (10 ³ lb)	Fy (10 ³ lb)	Fz (10 ³ lb)	Mx (10 ³ in.-lb)	My (10 ³ in.-lb)	Mz (10 ³ in.-lb)
SW pier	245	0.37	0.24	0.32	0.46	0.54	0.56
SE pier	247	0.37	0.42	0.31	0.45	0.71	0.51
NW pier	246	0.45	0.31	0.33	0.45	0.55	0.53
NE pier	248	0.39	0.36	0.32	0.45	0.64	0.48
Combined load		0.39	0.34	0.32	0.45	0.61	0.52
SW CVSS column	388	0.92	0.52	0.52	0.52	0.42	0.44
SE CVSS column	390	0.44	0.50	0.52	0.52	0.42	0.42
NW CVSS column	389	0.41	0.51	0.52	0.52	0.43	0.45
NE CVSS column	391	0.33	0.50	0.51	0.52	0.43	0.43
SW CVSS knee	408	0.47	0.47	0.36	0.47	0.53	0.46
SE CVSS knee	410	0.45	0.45	0.38	0.47	0.52	0.46
NW CVSS knee	409	0.47	0.47	0.37	0.47	0.52	0.46
NE CVSS knee	411	0.44	0.45	0.38	0.46	0.51	0.44
Combined load		0.46	0.49	0.52	0.52	0.44	0.39
N short column	434	0.0	0.20	0.0			
S short column	435	0.0	0.21	0.0			
Combined load		0.0	0.20	0.0			
Total load		0.41	0.44	0.42	0.48	0.59	0.50

We intensely evaluated the existing pier bending capacity of the new loads based on some carefully defined guidelines that adapt Newmark's recommendation in a seismic combination approach.¹⁸ Biaxial bending is considered with 100 percent of the major seismic bending, 40 percent of the minor seismic bending, and 110 percent of both major and minor static bendings.¹⁹ Based on the fixed-based analysis results, the east piers are overstressed by 8 percent, which is a small value considering the uncertainty of the seismic event and does not require any upgrading.

The foundation also undergoes evaluation based on the analysis results. According to the photograph taken at the time the foundation was constructed, the reinforcement in the foundation is doubled between every two piers and is therefore capable of resisting the working stresses.

8.6 Efficiency of Mode Selection Methods

In our seismic analyses, we selected the modal frequencies on the basis of effective modal mass (EMM), which is a well-accepted method. The author conducted a numerical study of the mode selection method and discovered that the effective modal strain-energy (EMSE) method is more efficient in capturing structural responses for low-frequency-dominated structures, such as the vessel, for a given number of modes.¹⁴ The FMSE method drastically amplifies the effect of the frequency content of the low-frequency modes in the input spectrum. It selects more low-frequency modes than does the EMM method.

The eigenvectors and eigenvalues from the analysis of the antisymmetric vessel model sub-

jected to a longitudinal excitation were used in the numerical study. When only the first 20 dominant modes are included, the loads in most of the vessel legs, piers, and support frame converge to the "reference responses," the design analysis responses obtained by the EMM method with 38 modes. This indicates that for those loads, an inclusion of 20 modes is sufficient. Some structural members, such as vertical hangers located far away from the base support, have convergences as low as 70 percent and definitely should include as many as 38 modes in order to capture proper loads.

In comparing the results of both methods at 38 modes the ratios of the loads in all primary and secondary structural members converge to 100 percent except in the vertical hangers. These hangers show a load increase of up to 17 percent by the EMSE method. This phenomenon could be caused by the fact that they are tied to the top of the vessel (located 43 ft above the foundations) and are subjected to the eccentricity effect and the dynamic coupling effect. The axial load in a vertical member produced by a longitudinal seismic excitation is secondary to and much smaller than those created by the vertical seismic excitation, therefore 17-percent-underestimated load is insignificant compared to the combined design load of that vertical member.

To summarize this numerical study, the convergence of 20-mode responses indicates that including 38 modes in the analysis produces reasonably accurate responses in the structure. As a result, the fact that the EMM method is not as efficient as the EMSE method has no significant effect on the results of the design analysis.

9. Result Comparison of the PDM And LLNL Models

The comparison of the PDM and LLNL models starts at the beginning of the analysis. As we evaluate the models, the target is to generate two models, each of which serves its individual purposes yet fully represents the real structure. Both models are based on similar assumptions. While we proceed in the comparison process, the models' differences are identified and resolved as much as possible. The models' behavior must be satisfactory to both parties before the formal analyses are performed. As a result, the responses

in the structural members are pretty much comparable for the two models. The load comparison tables of each load case are tabulated and documented in Ref. 1 by the PDM analytical team.

9.1 Static Behavior

Both models use the same number of elements to represent the magnets; therefore, the magnets and hangers behave in similar fashions,

as the comparison tables show. The slight difference in drag strut loads is caused by the selected coordinates of the magnet-strut interfaces.

The similar global static behavior of the vessel between the two models is confirmed by the leg and foundation load comparison tables. The total leg and foundation loads of the LLNL model are smaller than those of the PDM model by less than 1 percent in all three 1-g static analyses, as shown in Table 9-1. Note that the tabulated PDM foundation loads do not include half of the pier or column weights (543,700 lb), but the LLNL foundation loads do. The comparisons are made after subtracting the half-support-system weight from the LLNL total foundation load.

To capture the longitudinal translational stiffness of the vessel we apply a group of translational springs to the face of symmetry. The total stiffness of those springs in the PDM model is about 88 percent of the LLNL model's value. Most

of the vacuum-pressure, environmental-thermal, and magnetic forces are balanced at the vessel's face of symmetry. Some small portions are resisted by the support system. The base shear differences for the two models from those load cases are within 3 percent of the total applied loads.

9.2 Dynamic Behavior

A model's dynamic behavior is determined by its dynamic characteristics, which are listed for both models in Table 9-2. These include dominant modal frequencies, modal masses, spectral accelerations, and equivalent accelerations. The transverse and longitudinal dynamic characteristics agree quite closely. In the vertical free vibration, the PDM model's two most dominant modal frequencies excite a total structural mass of 18.6 percent, which is 4 percent more than that excited by

Table 9-1. Comparison of total leg and foundation loads.

Load case	Force component	Total leg load			Total foundation load		
		PDM model (10 ³ lb)	LLNL model (10 ³ lb)	Difference ^a (%)	PDM model (10 ³ lb)	LLNL model (10 ³ lb)	Difference ^a (%)
1-g transverse	Fx	2993.1	2969.1	0.8	3614.9	3590.2 ^b	0.7
1-g vertical	Fy	2993.3	2969.6	0.8	3613.9	3578.1 ^c	1.0
1-g longitudinal	Fz	2993.4	2970.0	-0.8	3614.3	3578.2 ^d	1.0
Dx	Fx	1516.8	1567.4	-3.2	1580.5	1702.5	-7.2
Dy	Fy	387.6	437.8	-11.5	665.7	521.8	27.6
Dz	Fz	1608.6	1629.5	-1.3	1670.8	1710.8	-2.3
SRSS	Fx	1847.5	1926.7	-4.1	1616.6	1735.3	-6.8
	Fy	1621.1	1634.1	-0.8	5014.0	4915.3	2.0
	Fz	3231.3	3400.1	-5.8	1690.9	1722.1	-1.8

^a All differences are normalized to LLNL model loads.

^b Fx = 4132.9 - 542.7 = 3590.2.

^c Fy = 4120.8 - 542.7 = 3578.1.

^d Fz = 4120.9 - 542.7 = 3578.2.

Table 9-2. Modal parameter comparison.

Excitation direction	Model	Dominant mode		Total mass (%)	Spectral (g)	Equivalent (g)
		Frequency	Mass (%)			
Transverse	PDM	2.8	75.6	96.3	0.44	0.44
	LLNL	3.0	68.2	86.5	0.40	0.38
Vertical	PDM	5.4, 9.4	13.4, 5.2	64.6	0.10	0.20
	LLNL	6.4	17.9	54.4	0.13	0.13
Longitudinal	PDM	4.4	84.7	89.5	0.46	0.48
	LLNL	4.4	75.5	88.0	0.42	0.42

the single-most-dominant modal frequency in the LLNL model. Overall the PDM model captures slightly more modal mass than does the LLNL model because it uses a different modeling technique at the foundation. The percentage of modal mass is proportional to the force response as well as to the equivalent g factor.

The global dynamic loads in the two models are expected to be as comparable as their dynamic characteristics are. As shown in Table 9-1, the differences of the combined dynamic loads (SRSS) are within 2 to 7 percent except for the vertical forces. Because dynamic loads are computed by adding the loads produced in each of the selected modal frequencies, the loads of the structural components are affected by the local areas. In fact the loads in the hanger, struts, legs, piers, and columns vary more than the total leg and foundation loads. Note that the LLNL dynamic foundation loads are not adjusted by subtracting the lost support member weight because the mass at the bottom node points of the piers and columns is hardly excited.

As for comparison of local behavior, the loads in the individual hangers, struts, legs, knees, columns, and piers reveal consistent differences. Among the three magnet modules listed in Table 9-3, the Yin-Yang module demonstrates the closest agreement (within 4.4 percent). In the solenoid module, the transverse struts and drag struts have differences below 7.3 percent, but those of the vertical hangers vary up to 35.2 percent. In the axicell module, the difference magnitudes in transverse struts and drag struts are limited to below 9.5 percent. The vertical hanger loads vary up to 76.8 percent.

Those differences due to the larger LLNL model loads do not raise concern because the magnet support members are designed for the LLNL model loads. The hangers with differences caused by larger PDM loads are evaluated against their design margins of safety, provided by GDC. Fortunately, the increased dynamic loads are only a small fraction of the combined loads in the hangers and are within their margins of safety.

The vessel legs are mostly grouped and they are designed for the largest load among each group. In comparing loads, our attention is concentrated on the largest load among each group. Nevertheless, the detail design is based on the refined PDM model, which gives a better representation of the local areas than does the LLNL model.

The main concern is the pier loads with respect to the east pier capacity. The pier design is

controlled by the pier's bending moments about its transverse and longitudinal axes. The combined gravity and dynamic moments of the two

Table 9-3. Comparison of SRSS dynamic loads in the magnet supports.

Magnet	Hanger	PDM model (10 ³ lb)	LLNL model (10 ³ lb)	Differences ^a (%)
YinYang	6001	240.4	244.0	- 1.5
	6005	233.8	228.0	2.5
	6002	319.4	334.0	- 4.4
	6007	537.3	539.0	- 0.3
	6003	527.2	527.0	0.0
T2	6004	569.1	557.0	2.2
	6101	69.9	67.9	3.0
	6102	26.0	26.4	- 1.5
T1	6103	72.3	74.4	- 2.8
	5922	20.0	21.5	- 7.0
	5923	8.3	9.6	- 13.5
A2	5924	34.5	38.1	- 9.5
	5913	15.4	13.4	14.9
	5912	19.1	17.0	12.4
A1	5914	37.6	36.1	4.2
	5903	9.3	11.7	- 20.5
	5902	10.7	14.2	- 24.7
S6	5904	34.0	34.9	- 2.6
	5813	26.7	15.1	76.8
	5812	25.8	15.0	72.0
	5814	61.5	59.4	3.5
	5905	51.2	50.0	2.4
	5906	45.9	49.9	- 8.0
	5907	48.1	44.2	8.8
S5	5908	49.1	53.2	- 7.7
	5803	5.7	8.8	- 35.2
	5802	7.0	8.3	15.7
S3	5804	17.7	16.9	4.7
	5703	11.7	16.8	- 30.4
	5702	15.6	14.6	6.9
S1	5704	36.3	36.6	- 0.8
	5603	10.3	14.2	27.5
	5602	11.6	14.1	17.7
	5604	45.8	46.0	0.4
	5405	23.9	25.6	6.6
	5406	24.8	25.3	2.0
	5407	22.9	24.7	7.3
	5408	26.6	26.9	1.1

^a Negative differences correspond to larger LLNL model results and positive differences correspond to larger PDM model results.

models yield a difference of 27.8 percent, which augments the overstress condition from 8 to 53 percent in the east piers but creates no threat to the west piers. However, the PDM model terminates at the bottom end of the pier, and the LLNL model extends to include the foundation beam.

We believe that the LLNL model represents the support configuration more realistically. Furthermore, the piers are reevaluated later in the report when comparing the soil-structure interaction results.

10. Comparison of the Results for Fixed-Base Analyses and Soil-Structure Interaction Analysis

The adjacent structures can affect each other through the soil effect during a seismic event. It was believed that the soil effect could lead to a 25-percent reduction in structural responses computed by fixed-base analysis; therefore, we reduced the peak ground accelerations of the free-field spectra in the fixed base analyses by 25 percent. To verify this assumption and to identify the SSI between the vessel and vault walls, SMA contracted to perform the SSI analyses on the MFIF-B axicell vessel and magnet system using a program package named CLASSI.

The analysis of capturing the SSI requires sophisticated methodology. The CLASSI computer program involves tremendous calculations so it is very costly to analyze a refined model that is generated for local detail design. Being confined by these limitations, we separate the tasks by generating a fixed-base model for detail design and a compact model for SSI analysis. The response calculations are limited to the most critical structural members.

The foundation modeling approach of the LLNL fixed-base model is revised to satisfy CLASSI requirements and also to capture the soil effect. This revised model, referred to as the SMA model is, first, analyzed by the SAP4 code package for model comparison, then by the CLASSI code package for SSI analysis. The resulting loads in the critical structural members for these two analyses are compared to those obtained from the fixed-base analysis. The SSI analysis methodology and result comparisons are well documented in Ref. 20. The evaluation of the SSI results is elaborated in this section.

10.1 Model Revision

The revision of the model is limited to the foundation area. One of our modeling assumptions is that we can capture the relative rotational flexibility between the piers and the foundation

mat by boundary springs. This improves upon the assumption of fully fixed piers. The shortcoming of using springs is that the springs do not capture the coupling effect between piers as the beam elements do. Since we have rigid elements tying the piers together, we believe the coupling effect missed by the springs is insignificant.

At the plug foundation, SMA chooses to replace the boundary springs by a beam element with a stiffness equivalent to that of a reinforced concrete beam designed by an ultimate strength approach (see Fig. 10-1). In addition to this beam, a pair of beams is superimposed to capture the coupling effect. Besides superimposing these additional beams, the original rigid elements connecting the piers to the center of the foundation mat remain as they are. Furthermore, instead of being fully fixed at the center of the mat a soil spring is added to capture the soil flexibility in rotation about the transverse axis.

At the center vessel foundation, all foundation springs are replaced by plate elements. A similar soil spring is applied at the center of the foundation mat. With the soil springs both the plug and vessel foundation mats are allowed to rotate about their transverse axes independently of each other.

Another revision to the model involves tying the two separated foundations together by a rigid element that extends to a reference point at the face of symmetry of the vessel at the foundation level. The reference point is restrained by the soil stiffnesses in the form of a 6-by-6 matrix as input in the CLASSI codes. The purpose of this revision is to allow the two foundations to rock as one rigid body about the transverse axis at the face of symmetry. All these revisions effectively add rotational degrees of freedom to the foundation mats that are constrained only by soil properties.

To capture the effect of the vault wall through the soil, the eigenvectors and eigenvalues of the vessel model are merged with those from the vault wall model in the response calculation.

Figure 10-1. SMA vessel and vault wall models.

The forces, displacements, and response spectra are specifically computed at the selected locations.

10.2 Reasonable Correlation between Two Models in Dynamic Characteristics

The revision of the vessel model causes no change in the vertical free-vibration fundamental frequency; however, there is an increase of 0.29 Hz in the transverse fundamental frequency and a decrease of 0.43 Hz in longitudinal fundamental frequency (see Table 10-1). The fixed-base model has a constant damping value of 5 percent whereas the SSI model has computed modal dampings of 5.4, 4.5, and 3.6 percent in the first dominant mode of transverse, longitudinal, and vertical free vibration, respectively.²⁰ Most of the dynamic characteristics of both models are quite comparable.

The dynamic characteristics of the vault are different from those of the vessel. The vault's transverse fundamental modal frequency is 2.02 Hz, which is lower than that of the vessel by 1.31 Hz. Its longitudinal and vertical fundamental frequencies are 10.10 and 31.03 Hz, which are much higher than the vessel's. The peak of the design response spectrum is at 3 Hz. Based on the fundamental modal frequencies, the vault has lower dominant spectral acceleration amplitudes than the vessel has. The effect on the vessel from the vault will be to decrease the vessel responses because of the vault's lower spectral acceleration amplitudes. This phenomenon is confirmed by the response spectra comparison later in this section.

10.3 The Translational Acceleration Responses of SSI Analysis

The translational acceleration responses of the vessel from SSI analyses are recorded in the form of acceleration spectra in each of the three global directions. They are mainly used for the design of equipment attached to the vessel. As shown in Fig. 10-2 and Table 10-2, the spectra are generated at locations selected to represent the major structural components such as hangers, ring stiffeners, and support systems.

A direct comparison of the fixed-base analysis and the SSI analysis can be made by collating the free-field spectra used in the fixed-base analysis to the resulting response spectra at the foundation reference point by SSI analyses. Figure 10-3 is a composite plot of the response spectra in three global directions, with the free-field spectra (dashed line) superimposed on the coupled SSI spectra (solid lines). The discrepancy in acceleration amplitude at the fundamental frequency in each direction between the two spectra is an indication of the reduction in responses caused by the SSI's coupling of the vault to the vessel. Evidence of some reduction is still noticeable at the bottom of the southeast pier and northwest CVSS column, as shown in Figs. 10-4 and 10-5, in the vertical and longitudinal directions.

Although the SSI response spectra at the base of the foundation, piers, and columns depict reductions in spectral acceleration at most dominant modes, the local areas can react to an amplification due to their local modal frequencies. In fact, the response of the vessel at locations far above the base supports is amplified by their height.

Table 10-1. A comparison of dynamic characteristics for the SMA and LLNL models.

Model	Transverse excitation			Longitudinal excitation			Vertical excitation		
	Frequency (Hz)	MPF ^a (%)	Damping (%)	Frequency (Hz)	MPF ^a (%)	Damping (%)	Frequency (Hz)	MPF ^a (%)	Damping (%)
LLNL vessel	3.04	68.23	5.0	4.37	75.49	5.0	6.35	17.91	5.0
	5.15	7.20	5.0	21.20	5.44	5.0	9.57	3.73	5.0
SMA vessel	3.33	63.30	5.4	3.93	75.35	4.5	6.35	10.97	3.6
	5.28	8.76	4.1	21.80	1.87	4.5	6.45	8.42	4.3
Vault	2.02	22.11	5.0	10.10	18.01	5.0	31.03	23.96	5.0
	3.23	17.20	5.0	7.57	15.26	5.0	32.50	31.56	5.0
	15.15	7.03	5.0	17.03	8.51	5.0	34.37	3.97	5.0
	27.05	4.70	5.0	17.82	6.53	5.0	31.67	3.79	5.0

^a Modal participation factor.

Figure 10-2. Locations selected for equipment design response spectrum calculation with node numbers as indicated.

Table 10-2. Node points for the equipment design response spectra.

Magnet supports.								
<u>Region</u>	<u>Vessel</u>		<u>Magnet</u>					
Yin Yang	341, 347, 355		343, 349					
Axicell	401		382					
Solenoid	458		445					
Vessel ring stiffeners.								
<u>Region</u>	<u>South</u>	<u>S-T</u>	<u>Top</u>	<u>N-T</u>	<u>North</u>	<u>N-B</u>	<u>Bottom</u>	<u>S-B</u>
West single	531	—	537	—	—	—	549	—
West double	555	—	—	—	—	—	—	—
West dome	577	—	583	—	589	—	—	—
East dome	601	604	—	610	613	—	—	—
East single	649	—	655	—	—	—	667	—
T1 ring	697	—	703	—	—	—	715	—
West beamline	—	745	—	750	—	755	—	—
S6 ring	—	—	812	—	—	—	824	—
East beamline	—	879	—	885	—	—	—	891
S2 ring	923	—	—	—	—	—	940	—
Support system								
<u>Region</u>	<u>Support</u>							
Bottom of southeast double leg	1238							
Bottom of southeast pier	1250							
Top of northwest column	1276							
Top of northeast column	1296							
Bottom of northwest column	1303							
Face of symmetry at bottom of foundation	1318							

Table 10-3 tabulates the maximum possible translation acceleration responses on the vessel at various elevations. It is obvious that acceleration responses at the top of the vessel are larger than responses at the lower part of the vessel. The attached equipment should be designed to avoid having natural frequencies coinciding with the high response frequencies. However, the acceleration amplitudes in these spectra are unusually high and we believe that the calculation of the spectra is quite conservative.

10.4 Relative Seismic Displacements between the Vessel and the Vault Walls

Numerous pipes run from Building 431 through the vault wall to the vessel. The relative displacement between the vessel and vault determines the tolerance in movement required for pipe installation. The relative displacements of se-

lected locations (shown in Fig. 10-6) are tabulated in the appendix of Ref. 20. The reference point (Node 170) for the displacement calculation is at the grade elevation of the vault wall for which minimum displacement is assumed.

Table 10-4 tabulates the maximum relative displacement between the vessel and vault at the corresponding elevations and longitudinal coordinates. The maximum relative displacements can be either positive or negative; therefore, the vessel at Node 539 can sway a maximum distance of about 1 in. towards or away from the vault wall at Node 30. At the beamline locations, the ports on the vessel at Node 885 can move up to 0.815 in. towards or away from the vault wall at Node 160. The magnitude of this relative displacement is very close to the beamline-tank-design displacement requirement of 1 in. The beamline tanks are supported by the space frame. Connecting the space frame to the vault wall is not recommended.

At the face of symmetry, the short column indicated by Node 972 on the vessel ring could

Figure 10-3. SSI in-structure response spectra at the reference point. All spectra are at 5-percent damping. The dashed line represents the free-field response spectrum and the solid line the coupled SSI for (a) transverse, (b) vertical, and (c) longitudinal frequencies.

slide up to 0.585 in. on the shear wall. When the short column is prohibited from sliding 0.585 in. in the transverse direction or ± 0.382 in. in the longitudinal direction, shears in these two directions will result.

10.5 Force and Moment Evaluation

Such critical structural members as the magnet and vessel support systems are chosen for

force and moment calculation in the SSI analysis. To identify the effect of the modeling techniques, both models (SMA's and LLNL's) are analyzed by the same computer program package SAP4. Tables 4.1A through 4.1C in Ref. 20 show the element responses. The load ratios in these tables reflect the response changes due to the foundation revision.

SAP4 uses response spectrum analysis methods whereas CLASSI adapts time history analysis methods for a fixed-base model. The load ratios in

Figure 10-4. SSI in-structure response spectra at the southeast pier. All spectra are at 5-percent damping. The dashed line represents the free-field response spectrum and the solid line the coupled SSI for (a) transverse, (b) vertical, and (c) longitudinal frequencies.

Figure 10-5. SSI in-structure response spectra at the northwest CVSS column. All spectra are at 5-percent damping. The dashed line represents the free-field response spectrum and the solid line the coupled SSI for (a) transverse, (b) vertical, and (c) longitudinal frequencies.

Table 10-3. Maximum translational acceleration response and corresponding vessel frequency.

Elevation (ft)	Transverse		Longitudinal		Vertical	
	Frequency (Hz)	Acceleration (g)	Frequency (Hz)	Acceleration (g)	Frequency (Hz)	Acceleration (g)
32.2 to 24.2	3.0	4.4, 3.4	3.7	4.0	6.0, 16.0	1.9, 1.4
23.3 to 20.3	3.0	4.0, 2.9	3.7	3.9	2.7, 14.0	1.0, 0.8
11.0	3.0	3.9, 2.5	3.7	3.7	2.0	1.0
1.3 to 1.7	3.0	1.6	3.7	3.6	3.3, 10.0	0.8, 0.9
- 2.2 to 6.4	3.0	2.0, 1.6	3.7	3.6	7.3, 10.0	2.3, 1.2
- 6.0 to - 8.0	2.6	1.4	3.1, 3.8	1.4, 2.6	2.7	1.0, 0.9
23.0	2.6	0.9	2.0, 3.3	1.1	3.8	0.9
23.3	3.0	0.9	2.8	1.1	3.1	0.6

Tables 4.2A through 4.2C in Ref. 20 demonstrate the variation of load response from a fixed-base approach caused by different methodologies. As shown in Tables 4.3A through 4.3C of that work, these load ratios indicate the effect of soil-structure interaction on the SMA model. The combined effect of these three sources were given in Tables 4.4A through 4.4C. From these tables we can sort out the effects from various sources, as stated in the reference.

As shown in Tables 4.3A through 4.3C in Ref. 20 and stated on page 5.2 of that report, the reduction from the effect of SSI and vault interaction is only about 20 percent. However, the combined effect from modeling revision, analysis methodology, soil-structure interaction, and vault interaction causes a load increase in most of the elements. The assumption of a 25-percent reduction in the free-field spectra overestimates the soil effect in some locations of the vessel, and the fixed-base assumption is proven not to be conservative. As a result, a thorough stress evaluation is conducted on the vessel model subjected to the best estimate of seismic load from the SSI analysis.

A systematic approach of evaluation is to study the global effect at various elevations. The critical structural members with SSI force and moment outputs are grouped together based on the elevation of the vessel where they are connected. Their load ratios, from Tables 4.4A through 4.4C in the cited reference, represent all other structural elements at the corresponding elevations. The whole structure is divided into the following regions based on elevation:

- Region A: From the top of the cylinder to 45° off its vertical axis (governed by the vertical hangers).

- Region B: From 45° above to below the horizontal center line of the cylinder (governed by the transverse struts).

- Region C: From 45° below the horizontal center line of the cylinder to the bottom (represented by some drag struts).

- Region D: Leg elevations (represented by the rigid elements at the base of each leg).

- Region E: Piers or columns to foundations (covered by the rigid elements tied to the center line of the foundations).

As shown in the load comparison tables (Tables 4.4A through 4.4C from Ref. 20), the load ratios vary from less than 1.0 to over 2.0. The SSI analyses are conducted on three types of soil properties, one of which is the nominal soil. The nominal soil properties are the best estimate values for a 0.25-g ground surface excitation (see Ref. 21); therefore, all load evaluation is based on the results obtained from the nominal soil properties.

The SSI loads in each region are summed up and normalized to the LLNL loads. They roughly represent the global differences at each elevation. Since the magnet support members are two-force elements, their axial forces are the sum of the forces from the three excitation directions; therefore, they represent the seismic responses in three directions.

The center vessel legs are designed to be quite strong with the intention of attracting more load from the piers. Their load conditions are known to be understressed. Their load responses are not as critical as the plug leg, consequently, they are not computed in the SSI analyses.

For the regions that have load ratios (as shown in Table 10-5) close to unity, the combined SSI effect is indeed equivalent to the 25-percent

Figure 10-6. Locations selected for relative displacement calculation with node numbers indicated.

Table 10-4. Relative displacements between the vessel and vault wall.

Point of interest	Vault wall ^a			Vessel ^b			Maximum relative displacement ^c (in.)
	Location	Direction	Displacement (in.)	Location	Direction	Displacement (in.)	
Cryo-piping	Node 30	T	0.193	Node 539	T	0.259	0.974
	Elev 30.7 ft	V	0.014	Elev 26.0 ft	V	0.151	0.383
	Long 91.8 ft	L	0.014	Long 88.6 ft	L	0.062	0.396
Plug beamline	Node 167	T	0.023	Node 586	T	0.204	0.749
	Elev 0.0 ft	V	0.004	Elev 1.3 ft	V	0.119	0.341
	Long 73.5 ft	L	0.001	Long 69.9 ft	L	0.067	0.398
Axicell beamline	Node 157	T	0.134	Node 745	T	0.054	0.710
	Elev 15.3 ft	V	0.002	Elev 20.3 ft	V	0.027	0.247
	Long 18.4 ft	L	0.008	Long 29.5 ft	L	0.008	0.336
Solenoid beamline	Node 160	T	0.268	Node 885	T	0.025	0.815
	Elev 15.3 ft	V	0.003	Elev 20.3 ft	V	0.065	0.286
	Long 11.0 ft	L	0.002	Long 12.3 ft	L	0.041	0.363
Axicell dump	Node 170	T	0.0	Node 755	T	0.332	0.854
	Elev 0.0 ft	V	0.0	Long 1.3 ft	V	0.065	0.283
	Long 18.4 ft	L	0.0	Long 29.5 ft	L	0.037	0.357
Center shear wall	Node 353	T	0.032	Node 972	T	0.031	0.585
	Elev 0.0 ft	V	0.043	Elev 0.0 ft	V	0.010	0.271
	Long 0.0 ft	L	0.026	Long 0.0 ft	L	0.036	0.392

^a All vault wall displacements are relative to Node 170.^b All vessel displacements are relative to Node 879.^c These displacements relate to the corresponding vault wall and vessel node displacements. The displacements of Node 170 relative to Node 879 are $D_T = 0.522$ in., $D_V = 0.219$ in., $D_L = 0.320$ in. All displacements can be either positive or negative.

Table 10-5. Load ratios of the combined forces.

Region	Element	Plug vessel			Center vessel					
		Yin Yang			Axicell			Solenoid		
		Fx ^a	Fy ^b	Fz ^c	Fx ^a	Fy ^b	Fz ^c	Fx ^a	Fy ^b	Fz ^c
A	Vertical hanger	—	1.071	—	—	1.262	—	—	1.000	—
B	Transverse strut	1.073	—	—	1.131	—	—	1.040	—	—
C	Drag strut	—	—	1.060	—	—	1.118	—	—	1.166
D	Legs	1.29	0.94	1.01	NA	NA	NA	NA	NA	NA
E	Foundations	1.379	2.212	1.607	NA	NA	NA	0.937	1.052	0.824

^a Fx = force component in transverse x direction.^b Fy = force component in vertical y direction.^c Fz = force component in longitudinal z direction.

reduction in free-field spectra that we assume. In some areas, the ratios are larger than unity. These locations experience an increase in load responses.

As shown in Table 10-5 the center vessel support system has a load ratio less than or close to unity, which indicates a load reduction of more than 25 percent. Because the stiffness of the steel columns and knees is so much smaller than that

of the 4-ft concrete foundation mat, the base of the columns and knees is indeed behaving as a fixed base regardless of the modeling methods.

In the plug vessel, the relative stiffness of the piers and foundation mat is quite comparable. The assumption of the pier being a fixed base is not realistic. In fact the stiffness is sensitive to the support configuration. As shown in Table 10-5,

the piers experience a large load increase from the soil effect. Fortunately, the effect is limited to the piers and the increase is gradually reduced to about 7 percent toward the cylinder.

Because of the uncertainty in a seismic event, SMA takes a conservative approach in generating the foundation input motion, namely to neglect the embedment effect. The vault is 21 ft below grade. The vault wall is embedded 21 ft on the outside. The wave scattering due to the layering of the soils and the embedded structure reduce the foundation input motion. For reasons stated in Ref. 21, it is recommended that the free-field peak acceleration at the foundation level be reduced by 15 to 20 percent from that at the ground surface. We adopt the lower bound of the recommendation and evaluate the structural integrity at the local areas where the load ratios are higher than 1.15.

In the center vessel region, several magnet support members experience load increases from the SSI effect. All magnet support members are designed for a certain margin of safety.²² For example, the 20-percent increase in dynamic load in Hanger 5912 is equivalent to 7 percent of its total load and is smaller than its 17-percent margin of safety (see Ref. 22).

For vessel evaluation, the PDM dynamic stresses are multiplied by the load increase ratios and are combined with the static loads before being compared to the allowable design stresses. In the ring stiffener 33 ft from the middle of the vessel, the maximum working stress (24.3×10^3 psi) occurs at the top of the cylinder. The SSI load increase (1.5×10^3 psi) is equivalent to 1.2 percent of the total working stress and does not exceed the seismic allowable stress.

The plates adjacent to this 33-ft ring experience a maximum stress of 17.5×10^3 psi on the south side of the cylinder. A 20-percent increase of 5.9×10^3 psi in seismic stress, equivalent to a 7-percent increase in the total working stress, still keeps the total working stress below the design allowable stress.

The same type of evaluation is conducted on the hangers, struts, ring stiffeners, and vessel shells in the center vessel with an SMA load ratio larger than 1.15. No overstress condition occurs for these members due to the SSI load increases.

Judging from the load ratios in the center vessel columns, most of the force and moment components are well sheltered by the embedment reduction with a few exceptions. Applying these same load ratios to the center vessel legs and to the bottom half of the vessel cylinder, we see that the small increases in load produced by the SSI

effect in regions C and D of the center vessel are insignificant because of their low working stresses.

The load ratios of the transverse shear (F_x) and the moment about the transverse axis (M_x) in rigid element below the east column pair are larger than those that can be sheltered by the embedment effect. However, stress from F_x is insignificantly small in both columns and M_x is resisted by the longitudinal cross-bracing that experiences working stresses below the design allowable stresses. That is, the SSI does not affect the center vessel support system.

In the plug vessel, the hangers, struts, ring stiffeners, and vessel shell experience stresses below the allowable stresses. Exceptions occur for the bottom halves of the ring stiffeners, which are welded to the support legs. From Table 4.4C in Ref. 20, the plug legs experience an average increase of about 40 percent in force and moment components; therefore, we assume that the beam elements representing the bottom half of the cylinder are subjected to the same increase in seismic load as are the legs.

As mentioned in Sec. 4.2, the plate and beam elements representing the cylinder shell and ring stiffeners share common node points. The top of the leg flanges should connect to the ring stiffener flanges so that the stress from the legs can be propagated along the ring web and flange. In the model the leg is tied to the shell that coincides with the ring, and this creates a fictitious stress concentration and bending moment in the beam elements (see Ref. 19, Sec. A-6, p. 6.8.8).

When we evaluate the ring stiffeners at the vessel-leg interface and subtract the stresses caused by the fictitious bending from the total working stresses of the element, the remaining stresses are below the seismic allowable stress except for the stress in one beam element at the northwest single leg. Fortunately, in this beam element the load increase in the major stress-driven moment component of this leg is 23 percent, smaller than the average value. Using 23 percent as the local load ratio and eliminating the fictitious bending moment, the working stress in this beam still exceeds that allowable by 12 percent. The fictitious stress concentration due to the element connectivity could possibly be the same, 12 percent. The fact that the stresses in the adjacent plate are in the low range of 5000 to 9000 psi is consistent with this concept. An analysis on a refined model that simulates the correct connectivity of the leg and ring stiffener might estimate the real stress in this ring stiffener.

There are few beam elements that simulate the longitudinal stiffeners having working stresses exceeding those allowable due to the load increase. As explained in Ref. 19, Sec. A-6, p. 6.8.12, the moment of inertia used in the beam element is too conservative. The correct calculation method brings the working stress below the design allowable stress. As mentioned in the previous paragraph, the plate elements in the plug vessel carry stresses well below those allowable; therefore, the 40-percent load increase due to SSI poses no threat to the integrity of the plate elements.

The seismic allowable stresses in the legs are much higher than those in the shell and ring stiffener because they are not subjected to vacuum pressure. However, the plug legs transfer substantial load from the vessel to the piers mostly in bending about the longitudinal direction (Mz). Some of these legs have been retrofitted, i.e., a wing plate has been added to the outer flange and a high strength material (A240, Type XM-29) with a yield stress of 55×10^3 psi has been used for the inner flanges of the double legs.

Upon adding a 40-percent load increase to these legs, a few elements show signs of overstress. For this case the elements are evaluated at their actual load ratios and not at the average ratio. For example, the local load ratio of the major stress-driven moment component (Mz) in Leg 10 is close to zero. The stress increases in the other moment components do not push the stress beyond the allowable level. The rest of the single legs are able to withstand even the 40-percent seismic-load increase.

The east base of the outer flange in the double leg pairs appears to be overstressed when subjected to a 40-percent load increase. As explained in Ref. 19, Sec. A-5, p. 5.2, the triangular plates representing the base of the outer flange in the west leg pair produce higher stresses due to their triangular configuration. Judging from the plate adjacent to these triangular plates, the high stress is unreal. Extrapolating from the adjacent plates, the stresses at the base of the flange should be below the allowable stresses. Even if the stresses slightly exceed those allowable, as for the outer flange of the east leg pair, the overstress condition is locally limited to the outer corner of the base.

The load ratio in the piers is scattered over a wide range from 1.14 to 2.64 according to nominal soil results. The large ratio occurs in the bending moment about the transverse axis (Mx). An extended study was conducted by SMA and LLNL engineers to identify the cause of this large ratio. At first, two simplified models were generated to

represent the plug vessel of the SMA and LLNL models. The rotational stiffnesses of the foundation beam and foundation spring in the SMA and LLNL models, respectively, were computed by applying a unit moment about the transverse axis at the pier-foundation interfaces and a unit force in the longitudinal direction at the center of the vessel cylinder. The load case corresponding to the application of unit moment calculated the local rotational stiffness whereas the load case corresponding to the application of unit force simulated the global load condition.

The results of both cases indicated that the SMA foundation beam is stiffer than the LLNL foundation boundary spring in rotation by 35 to 40 percent. Because these simplified models do not include the center vessel, they do not capture any possible effects from the center vessel, or from the other half of the vessel, whereas the full models do. The same unit moment is applied to both the full models and the stiffness difference between the beam and spring is about 44 percent.

As explained previously, a boundary spring ties the pier to an independent fixed-node point while a beam element connects two adjacent piers. The coupling effect between two piers is captured by the beam element, but not by the boundary springs. The existence of the center vessel may amplify this coupling effect. To identify the coupling effect, an additional test is conducted that simply replaces the spring in the LLNL model with the foundation beam in the plug alone and leaves the center vessel unchanged. The results confirm that the coupling effect between the adjacent piers significantly increases the longitudinal moment.

After completing the above study, we were convinced that the bending stiffness and the coupling effect are the two major contributors to the discrepancy. Fortunately, the effect is limited to the bending about the transverse axis (Mx), which is not the major component of stress-driven moment. Besides, Mx produces stress on the east-west faces whereas Mz generates stress on the north-south faces. All four piers are independently evaluated by the above-mentioned method based on the SMA result with embedment reduction.

The west piers are designed for this MFTF-B program. They are properly reinforced to support the vessel even under the SSI effect. The east piers were designed for the MFTF-A program and were adapted for this program. They were designed to have a bending capacity on the east-west faces three times as large as that on the north-south

faces. The east-west faces with higher bending capacity can adequately withstand M_x , but the north-south faces with lower bending capacity are overstressed by the high M_z . Of the four east piers only the northeast pier is understressed, while the other three are overstressed from 21 to 43 percent.

In the case that the local fault becomes active, the piers will be subjected to seismic cycling bending. At the base of the north-south faces, the concrete will spall off, possibly exposing the reinforcement. The bending capacity about the longitudinal axis will gradually diminish. As the bending resistance is reduced, the load will redistribute among the plug and the center vessel. Part of the bending will be shifted to the columns in the center vessel support system and part of it will be resisted by the axial force in the piers.

To study the load redistribution due to the bending, a 1-g transverse static analysis is conducted on the LLNL model with a change of end boundary conditions in the piers from moment resisting (fixed ends), to non-moment resisting (hinged ends) in the base of all four piers. Comparison of results from both the moment-resisting and non-moment-resisting load cases reveals that the bending and the axial force increase in the columns.

By multiplying the g factors by the increased static loads, the new dynamic loads in the columns and knees are obtained. Under these new loads, the working stresses in these members are

still slightly below the allowable stresses. This indicates that when all four piers totally lose their bending capacity about the longitudinal axis, the induced stresses in the center vessel are bearable. In fact only three out of four piers can possibly lose a fraction of their bending capacities. The additional study was done to investigate the impact of the worst condition should the local fault become active.

Another factor we have investigated is the damping ratio. The damping values used in the SSI analyses are on the lower bound of the recommended limits at a design stress level of about 50 percent of the yield stress. The vessel cylinder is designed at about 70 percent of the yield stress for non-seismic load cases and at about 86 percent of yield stress for seismic load cases. The vessel support system is designed at higher stress capacity than is the pressurized vessel tank. As the working stresses in the structure approach the yield stress the damping value of the structure increases. The damping value can increase up to 10 percent. The additional SSI analyses are conducted using a 10-percent damping value for the whole structure and the results are reduced by 5 to 15 percent. The major stress-driven moment component in the piers is reduced by more than 15 percent. This reduction can eliminate the overload situation in the plug legs and reduce the bending in piers.

11. Summary

The goals set for the LLNL independent analyses on the MFTF-B Axicell Vacuum Vessel and Magnet System have been fully achieved with the cooperation of the analytical teams from the design contractors. The modeling assumptions were based on our best knowledge at the time. Quality assurance for both refined and compact models involved lengthy discussions and repetitive tests. In the process of achieving these goals, both models are used to their maximum capacity.

A total of 16 static load cases and 3 postulated seismic excitations are defined to fully simulate the experimental operating condition and its environmental impact. A detailed allowable stress is defined specifically for various practical load combinations to account for the uncertainty in load occurrence.

The dominant modal frequencies of free vibration are 3.04, 4.37, and 6.35 Hz in the trans-

verse, longitudinal, and vertical directions, respectively. The frequency content in the free-field response spectra reveals that the maximum acceleration amplitude occurs at 3 Hz. As a result, the seismic loads from the transverse excitation are high.

The responses of the critical structural members from various load cases in both PDM and LLNL models are compared separately to confirm consistent model behavior that is acceptable to both analytical teams. The load comparison tables clearly indicate that the load paths in each load condition are as expected. The responses of the interface structural members are transmitted to the system design contractors and responsible engineers as requested. The animated model behavior demonstrates the realism and causes of the resulting responses to our satisfaction.

The dynamic characteristics of both models are comparable. The load agreement in the global sense is excellent. Although both PDM and LLNL models have different degrees of model refinement, the load agreement in the local areas is still satisfactory, with a few exceptions affected by the local modeling technique.

All elements in the PDM model are evaluated according to the corresponding design allowable stresses. A few elements are reported to be overstressed. Most of the overstress conditions are caused by modeling discontinuities and are proven to be unrealistic. Only one beam-element stress in the ring stiffener supporting the axicell A2 magnet in the model appears to exceed the allowable stress of 21,600 psi, by 5.6 percent. Of 22,800 psi experienced by this element, 17,000 psi is due to the magnetic load under the fault condition corresponding to the possible load estimate in the case of a fast dump current by some magnets. This remotely possible overstress situation can be corrected for by adding a plate on the flange.

The soil-structure interaction analyses are conducted on the LLNL model with some minor revision at the foundation level. The SMA and LLNL models reveal collated dynamic characteristics. The relative displacements between the vessel and vault at the beamline locations are up to ± 0.815 in., which is close to the 1-in. displacement criteria for the beamline design. Minimizing the space frame displacement by connecting the space frame to the vault wall can create a displacement problem in the beamline tank and is therefore not recommended.

In the review of the SSI analysis report, the assumption of a 25-percent reduction in peak ground acceleration in the free field response spectra seems to slightly overestimate the soil effect in the plug vessel. Only 20 percent of the reduction is due to soil structure and vault interaction computed by the CLASSI code. The load comparison tables show some load increase in the critical structural members. It is believed that the load discrepancy is caused by the analytical methodology and modeling techniques.

Improving the fixed-base assumption by applying the boundary spring elements captures the rotational flexibility in the foundation; however, it does not simulate the coupling between adjacent piers. Moreover, the rotational stiffness computed from the "beams-on-elastic-foundation" theory is 44 percent smaller than that of a beam calculated with the ultimate reinforced-concrete design approach. The revision in the foundation level unexpectedly contributes significantly to the pier loads.

To be conservative, SMA does not account for the reduction from the embedment effect that is thought to be about 15 percent. To account for this effect, the load ratios from the SSI analyses are reduced by 15 percent, and the vessel is re-evaluated based on the new load ratios. The magnet support members are designed for some margins of safety that can shelter the load increase from the SSI effect.

The ring stiffeners, shell, and the center vessel support system are also able to withstand the load increase. The outer flanges of the double legs are overstressed slightly. The west piers are capable of resisting the SSI loads. The east piers are overloaded on the north-south faces. If the local fault were to become active, the north-south faces of three piers would experience damage and would lose their bending capability. Close inspection and repairs would be needed after a seismic event. On the whole, the overstress situation is caused mostly by the SSI analysis results and occurs only at the plug legs and east piers.

The SMA model allows the foundation mat to rotate in many possible ways. The free-field input spectrum excludes the embedment effect. The damping value used in the analyses could be increased due to the working stress approaching the yield stress. All of these conditions indicate that the overstress condition could very well be less than our conservative estimate. Based on past experience, the characteristics of the local fault system would create short cycling motions with only a few significant peaks. This can be interpreted to mean that only a few cycles of high bending motion will occur in the piers.

We estimate that when the first pier starts to be overloaded, the concrete at its base will spall off and that the pier will lose some of its bending capability. At that moment the vessel load will begin to redistribute based on the stiffnesses of the rest of the east piers, the west piers, and the center vessel support system. Part of the bending will be transferred to the center vessel columns and knees and part of it will be resisted by the piers in axial forces. The piers have a 10- by 13-ft cross section and are able to withstand large axial forces.

We expect that, in the worst possible condition, the center vessel support system will adequately resist the load redistribution but that the east piers will experience a certain amount of damage. It is therefore our recommendation that the piers undergo a thorough inspection following an earthquake.

12. Acknowledgments

The cooperation and dedication of organizations under contract to Lawrence Livermore National Laboratory, the assistance of in-house consultants, and the support of project supervisors are greatly acknowledged. Their names are as follows:

Contracting organization:

Magnet system—GDC.

R. E. Tatro, J. W. Wohlwend, and D. S. Ring.

Vessel System—PDM Corporation.

M. McGahey, G. Reiling, R. Williams, and R. Angerhofer.

Soil-Structure Interaction Analyses—SMA.

J. J. Johnson, O. R. Maslenikov, and M. J. Mraz.

In-house consultants:

Structural Analyses—Structural/Civil Engineering Section.

D. Coats.

Soil-Structure Interaction Analyses—Soil Mechanics Science Group.

D. Bernreuters and J. C. Chan.

Program engineers:

V. Karpenko, Project Manager,

T. Kozman, Associate Project Manager,

W. Sterbetz, Associate Project Manager,

J. Gerich, Project Engineer for the MFTF-B

vacuum vessel.

My sincere thanks also go to the LLNL Technical Information Department for editorial assistance.

References

1. Pittsburgh Engineering, *MFTF-B Axicell Retrofit Final Analysis Report*, Pittsburgh-Des Moines Corp., Pittsburgh, PA (1984), vol. 1.
2. D. S. Ng, *Beam Dome Cover Wall Study*, Lawrence Livermore National Laboratory, Livermore, CA, ENC-82-15 (1982).
3. D. S. Ng, *Vessel Displacement Increment Caused by the Weight of Magnets*, Lawrence Livermore National Laboratory, Livermore, CA, memorandum to F. J. Deadrich (April 1, 1985).
4. D. S. Ng, *Translational Stiffness Coefficients of MFTF-B Axicell Vacuum Vessel at Hanger Attachment Points*, Lawrence Livermore National Laboratory, Livermore, CA, ENC-83-5 (1983).
5. D. S. Ng, *Vessel Displacements at Hanger Attachment Points*, Lawrence Livermore National Laboratory, Livermore, CA, memorandum to John Zbasnik (Dec. 21, 1984).
6. M. Hetenhi, *Beams on Elastic Foundation*, University of Michigan Studies, Scientific Series, (The University of Michigan Press, Ann Arbor, 1946), vol. XVI.
7. D. S. Ng, *Rotational Spring Stiffness Calculation for Central Cell Foundation*, Lawrence Livermore National Laboratory, Livermore, CA, ENC-83-18 (1983).
8. S. J. Sackett, *Users Manual for SAP4*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-18226 (May 1979).
9. Pittsburgh Engineering, *MFTF-B Axicell Retrofit Final Design Report*, Pittsburgh-Des Moines Corp., Pittsburgh, PA (1984), vol. 2.
10. B. E. Brown, *Displaying the Results of Three-Dimensional Analysis Using GRAPE, Part One - Vector Graphics*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-18507 (1979).
11. H. J. Weaver, D. B. McCallen, and M. W. Eli, *Dynamic Testing of MFTF Containment Vessel Structural System*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-53307 (1982).
12. J. A. Blume and Associates, Engineers, *Investigation of Faulting at Lawrence Livermore Laboratory*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-13568 (1972).
13. D. W. Coats, *Recommended Revisions to Nuclear Regulatory Commission Seismic Design Criteria*, Lawrence Livermore National Laboratory, Livermore, CA, NUREG/CR-1161 (1979).
14. D. S. Ng, *A Numerical Study of Mode Selection in Response Spectrum Analysis*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-53699 (1986).
15. G. L. Gondreau and D. S. Ng, *SUBSP Users Manual*, Lawrence Livermore National Laboratory, Livermore, CA (1982).
16. S. E. Bumpus, *Work Summary on MFTF-B Vessel Analysis (MODPAR)*, Lawrence Livermore National Laboratory, Livermore, CA, memorandum to K. Vepa, SM-81-211 (Aug. 1981).
17. J. J. Johnson, *MODSAP—A Modified Version of the Structural Analysis Program SAP IV for the Static and Dynamic Response of Linear and Localized Nonlinear Structures*, General Atomic Company, San Diego, CA, GA-A14006 (Rev.), (1978).
18. N. M. Newmark and W. J. Hall, *Development of Criteria for Seismic Review of Selected Nuclear Power Plants*, N. M. Newmark Consulting Engineering Services, NUREG/CR-0098 (1978).
19. D. W. Coats, D. S. Ng, and R. Pachinger, *Capacity Evaluation of East Piers*, Lawrence Livermore National Laboratory, Livermore, CA, ENC-84-11 (1984).
20. O. R. Maslennikov, M. J. Mraz, and J. J. Johnson, *Seismic Analysis of the Mirror Fusion Test Facility: Soil Structure Interaction Analysis of the Axicell Vacuum Vessel*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-15806 (1986).
21. D. Bernreuter and J. C. Chen, *Review of SMA's Draft Report Seismic Analysis of the Mirror Fusion Facility: Soil Structure Interaction Analyses of the Axicell Vacuum Vessel*, Lawrence Livermore National Laboratory, Livermore, CA, EG-85-086 (1985).
22. D. S. Ring, *MFTF-Axicell Final Stress Report*, General Dynamics/Convair Division, San Diego, CA, GDC-LLNL-84-002, vol. II, App. D (Oct. 1983).