COMPATIBILITY OF REFRIGERANTS AND LUBRICANTS WITH ELASTOMERS

Quarterly Report

1 October 1992 - 30 December 1992

Dr. Gary R. Hamed
Robert H. Seiple

**Institute/Department of Polymer Science
Polymer Science Building
University of Akron
Akron, Ohio 44325-3909**

January 1993

**Prepared for
The Air-Conditioning and Refrigeration Technology Institute
Under
ARTI MCLR Project Number 650-50500**

RECEIVED
FEB 24 1993
STI

This research project is supported, in whole or in part, by U.S. Department of Energy grant number DE-FG02-91CE23810: Materials Compatibility and Lubricants Research (MCLR) on CFC-Refrigerant Substitutes. Federal funding supporting this project constitutes 93.94 % of allowable costs. Funding from non-government sources supporting this project consists of direct cost sharing of 6.06 % of allowable costs; and in-kind contributions from the air-conditioning and refrigeration industry.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

The U.S. Department of Energy's and the air-conditioning industry's support for the Materials Compatibility and Lubricants Research (MCLR) program does not constitute an endorsement by the U.S. Department of Energy, nor by the air-conditioning and refrigeration industry, of the views expressed herein.

NOTICE

This report was prepared on account of work sponsored by the United States Government. Neither the United States Government, nor the Department of Energy, nor the Air-Conditioning and Refrigeration Technology Institute, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

COMPLIANCE WITH AGREEMENT

The University of Akron has complied with all aspects of the agreement.

PRINCIPAL INVESTIGATOR EFFORT

Dr. Gary Hamed and R.H. Seiple are the principal investigators for the UA/ARTI MCLR program. During the fourth quarter of the contract period, Dr. Gary Hamed has devoted a total of 20 hours (4 % of his available work hours) and R. Seiple has devoted 100 hours (20 % of his available work hours) on the UA/ARTI MCLR program.

COPYRIGHT NOTICE

(for journal publication submissions)

By acceptance of this article, the publisher and/or recipient acknowledges the right of the U.S. Government and the Air-Conditioning and Refrigeration Technology Institute, Inc. (ARTI) to retain a nonexclusive, royalty-free license in and to any copyrights covering this paper.

TABLE OF CONTENTS

ABSTRACT		2
SCOPE		2-3
SIGNIFICANT RESULTS-Phase I		4-5
SIGNIFICANT RESULTS-Phase II		6-7
APPENDIX A	TEST MATERIAL FORMULATIONS	8-21
APPENDIX B	INDUSTRIALLY SUPPLIED GASKET MATERIAL INFORMATION	22-23
APPENDIX C	TEST METHODOLOGY-PHASE I	24-27
APPENDIX D	ELASTOMER DIAMETER CHANGE IN TEST FLUIDS	28-160
APPENDIX E	ELASTOMER SWELL DATA CHARTS	161-258
APPENDIX F	PHYSICAL PROPERTY DATA	259-271
APPENDIX G	LUBRICANT TYPES	272-273
APPENDIX H	TEST METHODOLOGY	274-275
APPENDIX I	LUBRICANT/REFRIGERANT TEST MIXTURES-PHASE II	276-277
APPENDIX J	PRESSURE CALIBRATION CURVES PHASE II PROGRAM	278-290

COMPATIBILITY OF REFRIGERANTS AND LUBRICANTS WITH ELASTOMERS

ABSTRACT

The information contained in this report is designed to assist the air-conditioning and refrigeration industry in the selection of suitable elastomeric gasket and seal materials that will prove useful in various refrigerant and refrigeration lubricant environments. 97 % of the swell measurements have been made to date. The other 3 % of the measurements are contingent on the availability of additional quantities of R-32. Swell behavior in the fluids have been determined using weight and in situ diameter measurements for the refrigerants and weight, diameter and thickness measurements for the lubricants. Weight and diameter measurements are repeated after 2 hours and 24 hours for samples removed from the refrigerant test fluids and 24 hours after removal from the lubricants.

SCOPE

The Compatibility of Refrigerants and Lubricants with elastomers program is an 12 month research effort supported by a grant from the Department of Energy through the Air-Conditioning and Refrigeration Technology Institute. The elastomers research effort was initiated at the University of Akron on March 1, 1992 and is expected to continue through April of, 1993 at which time a final report will be submitted to ARTI.

First quarter (Jan 1, 1992-Mar 31, 1992) efforts centered around ordering materials, mixing some of the 84 compounds needed for the study and the fabrication of 120 pressure vessels required for the in situ evaluation of the swell behavior of elastomers in refrigerants. The moisture content was determined for the lubricant samples.

Second quarter (April 1, 1992-Jun 30, 1992) efforts revolved around the implementation of proposed methodologies for the acquisition of elastomer swell data in refrigerants and lubricants. During the second quarter, swell tests were begun and the appropriate measurements were made on approximately 50 % of the proposed elastomer formulations.

Third quarter (July 1, 1992-September 30, 1992) efforts centered around the completion of phase I work. Approximately 97 % of the Phase I testing has been completed. Work also focused on preparing immersion pressure vessels for the Phase II work effort.

Fourth quarter (October 1, 1992 - December 30 1992) efforts have centered on the initiation of phase II tasks and additional data analysis and presentation of the phase I program. Delay in completing the phase I work is the result of delays in the receipt of R-32 refrigerant.

Significant Results-Phase I

Presently, nearly all of the rubber formulations (# 1 - 85) proposed have been tested for swell in refrigerants: R-123, R-142b, R-124, R-22, R-125, R-134, R-134a, R-143a, R-152a, R-32, and in lubricants: alkyl benzene (AB), mineral oil (MO), pentaerythritol ester mixed acid (PEMA), pentaerythritol ester branched acid (PEBA), polypropylene glycol diol (PPGD), polypropylene glycol butyl monoether (PPGBM), or a modified polyglycol (MPG). The rubber formulations include general purpose and specialty thermoset elastomers, and thermoplastic elastomers. Some compounds were filled, others were not. In addition, several vendor supplied materials (# 86 - 95) have been tested for swelling resistance in the various fluids. Results are given in Figures 1-17, Appendix D. Solid bars (with brief composition descriptors) are used to show the in situ percent change in diameter after 14 days of immersion. A blank indicates that the composition has not been tested. In all cases, filled compositions had less swelling compared to corresponding unfilled ones. R-123, the dichloro-substituted HCFC, generally gave the greatest swelling. There were, however, several compositions which swelled little in this refrigerant, including EPDM/PP thermoplastic elastomers (# 45 - 48), a butyl rubber/PP TPE (# 85), and four of the vendor supplied compositions (# 88 - 91, 93). Some compositions (e.g., # 46 - 48) shrunk during immersion, indicating that the swellant was removing plasticizer from the rubber.

The refrigerants with the next highest swelling power were the monochlorinated HCFCs, R-124 and R-22, which usually had similar swelling behavior. A notable exception was # 91, which swelled significantly in R-22 but not in R-124. Compositions #45 - 48, #56 - 57, #74, #86, #88 - 90, #92 - 93 all had good resistance to R-124 and R-22. The other monochlorinated HCFC, R-142b, swelled most elastomers less than the previous two. Epichlorohydrin and nitrile elastomers were much more resistant to R-142b than they were to R-124 or R-22. Additionally, compositions #45 - 48, #49 - 51, #56 - 59, #63, #85 - 93, and #95 were resistant to R-142b.

The HFCs give much less swelling than the HCFCs. The two tetrafluoroethane isomers, R-134 and R-134a, show similar swelling behavior. The fluoroelastomers and fluorosilicone elastomers exhibit high swelling in the HFCs. However, most of the elastomer samples have 5% or less increase in diameter after immersion in the HFCs. A great variety of elastomers are resistant to swelling in the HFCs including both the inexpensive, general purpose hydrocarbon elastomers as well as several of the specialty and thermoplastic elastomers. Among the vendor samples submitted #94 is clearly the worst for swelling resistance. Some of the vendor samples resisted swelling in all refrigerants.

The hydrocarbon lubricants, AB and MO, greatly swelled the general purpose hydrocarbon elastomers, while the nitrile rubbers, fluoroelastomers, and nitrile/PP thermoplastic elastomers were quite resistant to these lubricants. The glycol and ester lubricants swelled the hydrocarbon elastomers a little. The two pentaerythritol ester lubricants (PEMA and PEBA) gave similar swelling behavior.

Several of the compositions including some of the vindow supplied materials were resistant to swelling in all lubricants. These included: #89 - 93, #17 - 18, #28 - 30, #53 - 55, #49 - 51, and #56 - 59.

Significant Results-Phase II

There will be approximately 25 of the 95 sample materials that will be tested in phase II of the program. These materials were selected through the analysis of both refrigerant and lubricant material swell behavior. A list of the top 25 materials for each of the refrigerant/lubricant mixtures was developed using low swell behavior as the criteria. A master list was developed of 25 elastomers that showed up frequently on the individual lists. These elastomers were submitted to the MCLR Advisory Board for approval.

The list of phase II materials was reviewed by the key individuals and returned with some changes. The materials to be tested in the phase II MCLR program is as follows:

Compound	Compound Type	Compound	Compound Type
47	Santoprene 203-40	54	Hytrel G6356
56	FA Polysulfide	95	Green Tweed 956
90	Specialty Paper Board NI-2085G	35	Epichlorohydrin H/CB
45	Santoprene 201-87	61	Polyurethane
49	Geolast 701-87	83	Royalene 552/CB
58	ST Polysulfide	7	Polysar Butyl 402
55	Hytrel 7246	12	Chlorobutyl 1068/CB
57	FA Polysulfide/Carbon Black	17	Nitrile
50	Geolast 701-80	33	Kel-F 3700
74	Vistalon 707/Carbon Black	66	Millable Polyurethane
46	Santoprene 201-73		
63	Polyurethane		
85	Trefsin		
86	Precision Rubber Products 2167		
8	Polysar Butyl 402/CB		

Phase II pressure vessels were used to determine the weight percentage of refrigerant charge that would be required to generate pressures of 275 PSI to 300 PSI at 100 degrees centigrade. The test results are included in the table on the following page.

Phase II Calibration Table for 275 PSI to 300 PSI Pressures @ 100 Degrees Centigrade

Refrigerant	Wt % Refrigerant @ 100 C to Yield 275 PSI to 300 PSI	Lubricant (Description)	ID	Lubricant (Trade Name)
R-22	32.0 - 34.0	Naphthenic mineral oil	MO	Witco Suniso 3GS
R-123	50.0	Naphthenic mineral oil	MO	Witco Suniso 3GS
R-134a	38.0 - 40.5	Polypropylene glycol diol	PPGD	DOW P425
R-134a	33.5 - 36.0	Modified polyglycol	MPG	Allied-Signal BRL-150
R-134a	38.5 - 42.0	Penta erythritol ester mixed-acid polyolester	PEMA	ICI Emkarate RL 244
R-134a	44.5 - 48.0	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-142b	50.0	Alkylbenzene	AB	Shrieve Zerol 150
R-152a	32.5 - 35.0	Alkylbenzene	AB	Shrieve Zerol 150
R-32		Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-124	50.0	Alkylbenzene	MO	Shrieve Zerol 150
R-125	49.5 - 52.0	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-143a	50.5 - 53.0	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-134	65.0 - 68.0	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-32		Penta erythritol ester mixed-acid polyolester	PEMA	ICI Emkarate RL 244
R-125		Polypropylene glycol diol	PPGD	Dow P425
R-125		Penta erythritol ester mixed-acid polyolester	PEMA	ICI Emkarate RL 244
R-152a		Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A

APPENDIX A: TEST MATERIAL FORMULATIONS

Note:

All values in this Appendix are in Parts Per Hundred Parts of Elastomer

Formula #1	Polyisoprene (Natsyn 2200)	100
	Zinc Oxide	5
	Sulfur	2.25
	Stearic acid	2
	TBBS	0.7
Formula #2	Polyisoprene (Natsyn 2200)	100
	Zinc Oxide	5
	Sulfur	2.25
	Stearic acid	2
	TBBS	0.7
	IRB6 (Carbon Black)	35
Formula #3	Polyisoprene (Natsyn 2200)	100
	Zinc Oxide	5
	Stearic acid	2
	Santocure MOR	1.0
	Thiurad	1.0
	Sulfasan R	1.0
Formula #4	Neoprene W	100
	Stearic acid	0.5
	Magnesium oxide	4
	Zinc oxide	5
Formula #5	Neoprene W	100
	Stearic acid	0.5
	Magnesium oxide	4
	Zinc oxide	5
	IRB6 (Carbon black)	30
Formula #6	Isobutyl isoprene	100
	(Polysar Butyl 100/0.7% unsaturated)	
	Zinc oxide	3
	Sulfur	1.65
	Stearic acid	1
	TMTD	1

Formula #7	Isobutyl isoprene	100
	(Polysar Butyl 402/2.2% unsaturated)	
	Zinc oxide	3
	Sulfur	1.75
	Stearic acid	1
	TMTD	1
Formula #8	Isobutyl isoprene	100
	(Polysar Butyl 402/2.2% unsaturated)	
	Zinc oxide	3
	Sulfur	1.75
	Stearic acid	1
	TMTD	1
	IRB6 (Carbon black)	50
Formula #9	Bromobutyl	100
	(Polysar Bromobutyl X2)	
	Zinc oxide	5
	Stearic acid	1
Formula #10	Bromobutyl	100
	(Polysar Bromobutyl X2)	
	Zinc oxide	5
	Stearic acid	1
	IRB6	40
Formula #11	Chlorobutyl 1068	100
	Zinc oxide	5
	Stearic acid	1
Formula #12	Chlorobutyl 1068	100
	Zinc oxide	5
	Stearic acid	1
	IRB6	40
Formula #13	SBR 1502 (23.5% styrene)	100
	Zinc oxide	3
	Sulfur	1.75
	Stearic acid	1
	TBBS	1

Formula #14 SBR 1502 (23.5% styrene)	100
Zinc oxide	3
Sulfur	1.75
Stearic acid	1
TBBS	1
IRB6	50
Formula #15 Stereon 730A(29% styrene)	100
Zinc oxide	3
Sulfur	1.75
Stearic acid	1
TBBS	1
Formula #16 Stereon 840A (40% styrene)	100
Zinc oxide	3
Sulfur	1.75
Stearic acid	1
TBBS	1
Formula #17 Nitrile	100
(Chemigum N206 very high ACN)	
Zinc oxide	3
Sulfur (MgCO ₃ coated)	1.5
Stearic acid	1
TBBS	0.7
Formula #18 Nitrile	100
(Chemigum N300 high ACN)	
Zinc oxide	3
Sulfur (MgCO ₃ coated)	1.5
Stearic acid	1
TBBS	0.7
Formula #19 Nitrile	100
(Chemigum N615B medium ACN)	
Zinc oxide	3
Sulfur (MgCO ₃ coated)	1.5
Stearic acid	1
TBBS	0.7

Formula #20	Nitrile	100
	(Chemigum N917 low ACN)	
	Zinc oxide	3
	Sulfur (MgCO ₃ coated)	1.5
	Stearic acid	1
	TBBS	0.7
Formula #21	Nitrile	100
	(Chemigum N917 low ACN)	
	Zinc oxide	3
	Sulfur (MgCO ₃ coated)	1.5
	Stearic acid	1
	TBBS	0.7
	IRB6	35
Formula #22	Nitrile (Chemigum N206)	100
	Zinc oxide	3
	Sulfur (MgCO ₃ coated)	1.5
	Stearic acid	1
	TBBS	0.7
	IRB6	35
Formula #23	Hydrogenated nitrile	100
	(Polysar Tornac A3850 38% ACN)	
	Zinc oxide	5
	Stearic acid	1
	Magnesium oxide	10
	Varox DBPH-50	10
	Ricon 153-D	6.5
Formula #24	Hydrogenated nitrile	100
	(Polysar Tornac A3850 38% ACN)	
	Zinc oxide	5
	Stearic acid	1
	N 774 Carbon black	40
	MC Sulphur	1.5
	TMTM	0.3
	MBTS	1.5

Formula #25	Hydrogenated nitrile	100
	(Polysar Tornac A4555 45% ACN)	
	Zinc oxide	5
	Stearic acid	1
	Varox DBPH-50	10
	Ricon 153-D	6.5
Formula #26	Hydrogenated nitrile	100
	(Polysar Tornac A4555 45% ACN)	
	Zinc oxide	5
	Stearic acid	1
	Varox DBPH-50	10
	Ricon 153-D	6.5
	N 774 Carbon black	40
Formula #27	Viton A	100
	Maglite Y	15
	Diak No. 3	3
Formula #28	Viton B	100
	Maglite Y	15
	Diak No. 3	3
Formula #29	Viton GF	100
	Litharge (sublimed)	3
	Diak No. 7	3
	Luperco 101-XL	3
Formula #30	Viton GF	100
	Litharge (sublimed)	3
	Diak No. 7	3
	Luperco 101-XL	3
	IRB6 (Carbon black)	30
Formula #31	KEL-F 3700	100
	Litharge (sublimed)	1.8
	Diak No. 7	1.8
	Luperco 101-XL	1.8

Formula #32	KEL-F 3700	100
	Maglite Y	15
	Diak No. 3	3
Formula #33	KEL-F 3700	100
	Maglite Y	15
	Diak No. 3	3
	IRB6 (Carbon black)	30
Formula #34	Epichlorohydrin homopolymer (Hydrin H-65)	100
	Stearic acid	1
	NBC	1
	Red lead	5
	NA-22	1.85
Formula #35	Epichlorohydrin homopolymer (Hydrin H-65)	100
	Stearic acid	1
	NBC	1
	Red lead	5
	NA-22	1.85
	IRB6 (Carbon black)	40
Formula #36	Epichlorohydrin copolymer (Hydrin C-65)	100
	Stearic acid	1
	NBC	1
	Red lead	1.0
	NA-22	1.85
Formula #37	Epichlorohydrin copolymer (Hydrin C-65)	100
	Stearic acid	1
	NBC	1
	Red lead	5
	NA-22	1.85
	IRB6 (Carbon black)	40

Formula #38 Epichlorohydrin copolymer (Hydrin T-75)	100
Stearic acid	1
NBC	1
Red lead	5
NA-22	1.85
Formula #39 Epichlorohydrin copolymer (Hydrin T-75)	100
Stearic acid	1
NBC	1
Red lead	5
NA-22	1.85
IRB6 (Carbon black)	40
Formula #40 SE-33 (VMQ)	100
Luperco CST	1.5
Formula #41 SE-436 U	100
DiCup 40C	1
Formula #42 SE-565 U	100
Dicup 40C	0.6
Formula #43 SE-3808 U	100
Dicup 40C	0.8
Formula #44 LS-63 U	100
Mapico 297	1.5
Kadox TS 50	1.3
Formula #45 Santoprene 201-87 (87 shore A)	100
Formula #46 Santoprene 201-73 (73 shore A)	100
Formula #47 Santoprene 203-40 (40 shore D)	100
Formula #48 Santoprene 203-50 (50 shore D)	100
Formula #49 Geolast 701-87 (87 shore A)	100

Formula #50 Geolast 701-80 (80 shore A)	100
Formula #51 Geolast 703-40 (40 shore D)	100
Formula #52 Hytrel 4056 (40 shore D)	100
Formula #53 Hytrel 5526 (55 shore D)	100
Formula #54 Hytrel G6356 (63 shore D)	100
Formula #55 Hytrel 7246 (72 shore D)	100
Formula #56 FA Polysulfide Rubber	100
Zinc oxide	10
Stearic acid	0.5
Altax	0.4
DPG	0.1
2-mercapto imidazoline	0.1
Formula #57 FA Polysulfide Rubber	100
Zinc oxide	10
Stearic acid	0.5
Altax	0.4
DPG	0.1
2-mercapto imidazoline	0.1
IRB6 (Carbon black)	60
Formula #58 ST Polysulfide Rubber	100
Zinc peroxide	5
Stearic acid	1
Calcium Hydroxide	1
Formula #59 ST Polysulfide Rubber	100
Zinc peroxide	5
Stearic acid	1
Calcium Hydroxide	1
IRB6 (carbon black)	60

Formula #60	Polyurethane	100
	(Airthane PET-95A)	
	(Ether Based)	
	Moca	21.7
Formula #61	Polyurethane	100
	(Airthane PET-60D)	
	(Ether Based)	
	Moca	25.9
Formula #62	Polyurethane (Cyanaprene A-8)	100
	(Ester Based)	
	Moca	10.9
Formula #63	Polyurethane (Cyanaprene D-55)	100
	(Ester Based)	
	Moca	19.8
Formula #64	Polyurethane (Millathane 76)	100
	(Ester based)	
	MBTS	1.0
	MBT	0.5
	THANECURE	1.0
	Sulfur	1.5
Formula #65	Polyurethane (Millathane E-34)	100
	(Ether based)	
	MBTS	1.0
	MBT	0.5
	THANECURE	1.0
	Sulfur	1.5
Formula #66	Polyurethane (Millathane 76)	100
	(Ester based)	
	MBTS	1.0
	MBT	0.5
	THANECURE	1.0
	Sulfur	1.5
	IRB6 (Carbon black)	40

Formula #67	Hypalon 20	100
	Litharge	25
	Altax	0.5
	Sulfads	2
Formula #68	Hypalon 40	100
	Litharge	25
	Altax	0.5
	Sulfads	2
Formula #69	Hypalon 40	100
	Magnesia	4
	Pentaerythritol	3
	Sulfads	2
Formula #70	Hypalon 40	100
	Litharge	20
	Altax	0.5
	Sulfads	0.75
	Magnesia	10
	NBC	3
Formula #71	Hypalon 4085	100
	Litharge	25
	Altax	0.5
	Sulfads	2
Formula #72	Vistalon 404	100
	DiCup R	3.0
Formula #73	Vistalon 707	100
	DiCup R	3.0
Formula #74	Vistalon 707	100
	DiCup R	3.0
	IRB6	40
Formula # 75	Vamac G	100
	Methylene Dianiline	1
	DPG	3.2

Formula # 76	Vamac B-124 Masterbatch	124
	N774	35
	Methylene Dianiline	1
	DPG	3.2
Formula # 77	DOW CM0136	100
	STAN MAG MLW	10
	Triallyl Isocyanurate	2
	Varox DCP-R	4.0
Formula # 78	DOW CM0136	100
	STAN MAG MLW	10
	Triallyl Isocyanurate	2
	Varox DCP-R	4.0
	IRB6	40
Formula # 79	DOW 4211P	100
	STAN MAG MLW	10
	Triallyl Isocyanurate	2
	Varox DCP-R	4
Formula # 80	Royalene 552	100
	(high ethylene content)	
	Zinc Oxide	5
	Sulfur	1.5
	Stearic Acid	1.0
	TMTD	1.0
Formula # 81	MBT	.5
	Royalene 525	100
	(high unsaturation)	
	Zinc Oxide	5
	Sulfur	1.5
	Stearic Acid	1
	TMTD	1
	MBT	.5

Formula # 82	Royalene 359	100
	Zinc Oxide	5
	Sulfur	1.5
	Stearic Acid	1.0
	TMTD	1.0
	MBT	.5
Formula # 83	Royalene 552	100
	Zinc Oxide	5
	Sulfur	1.5
	Stearic Acid	1
	TMTD	1
	MBT	.5
	IRB6	40
Formula # 84	Royalene 359	100
	Zinc Oxide	5
	Stearic Acid	1
	DiCup R	1

APPENDIX B: INDUSTRIALLY SUPPLIED GASKET MATERIAL INFORMATION

Industrially Supplied Gasket Material Information

Formulation #	From	Material	Type/Description
Formulation # 86	The Trane Company	Precision Rubber Products #2167	Chloroprene compound (35%wt) with carbon black (45%), mineral (5%), and extractables (15%)
Formulation # 87	The Train Company	Precision Rubber Products #7507	Acrylonitrile compound (17% wt) with carbon black (37%), mineral (3%), butadiene (32%) and extractables (12%)
Formulation # 88	Carrier Corporation	Garlock 2930 (gasket)	Neoprene with synthetic fibers
Formulation # 89	Tecumseh Products	Armstrong N-8092	A non-asbestos nitrile bound reinforced cellulose fiber product
Formulation # 90	Tecumseh Products	Specialty Paperboard NI-2085G	A non-asbestos material composed of inorganic filler blend, encapsulated with nitrile rubber, with a small proportion of cellulosic fiber
Formulation # 91	Copeland Corporation	Victopac 69 (gasket)	Non-asbestos
Formulation # 92	Copeland Corporation	Klinger C-4401 (gasket)	Nitrile/non-asbestos
Formulation # 93	Copeland Corporation	Specialty Paperboard 2099	Nitrile/aramid fiber
Formulation # 94	Copeland Corporation	Parker V747-75	Fluorocarbon
Formulation # 95	Carrier Corporation	Green Tweed 956	Neoprene

APPENDIX C: TEST METHODOLOGY-PHASE I

TEST METHODOLOGY

- Mixing:** Most of the formulations tested in this study were mixed on a laboratory size rubber mill. The base polymer was milled for a short period of time to allow the normal breakdown of the elastomer. The ingredients were then added to the elastomer on the 2 roll mill in the order they appear in the compound recipe. The materials are mixed thoroughly until the rubber compound appears to be homogeneous.
- Cure Characteristics:** The cure time for each of the formulations is determined using normal cure temperature ranges as suggested by the manufacturers or temperatures commonly used by the rubber industry. The oscillating disk rheometer (ODR) is used to determine the cure characteristics of the compound in question at the appropriate temperature.
- The ODR is used to obtain information concerning the state of cure of the formulation with time. This instrument produces a cure curve (torque vs. time) and the cure time to 95 % of the maximum torque is calculated from this graph. All test compounds formulated at the University of Akron were cured into sheets at the T_{95} % cure level.
- Other Compounds:** The thermoplastic elastomer materials were either tested as received (when received in sheet form) or injection molded when received in pellet form.
- Gasket materials received from vendors were tested as received.
- Sample Preparation:** Sheet materials were placed on a vacuum table attached to a drill press fitted with a cutter assembly. The cutter assembly consists of a holder and a stainless steel blade. The machine was turned on and the cutter lowered so as to cut through the rubber sheet. Round disk-like samples were prepared in this manner for the swell tests.

- Measurements:** Diameter measurements were obtained using a travelling microscope.
- Thickness measurements were obtained using a thickness gauge.
- Weight measurements were obtained using an analytical balance.
- Lubricant Swell:** The round disk samples were measured (2 each test) and placed in 2 oz. jars with lids, the predried lubricants were poured into each of the containers and sealed. The containers were placed in an oven at 60 degrees centigrade.
- Diameter measurements on the top most sample were taken at 1 day and 14 days. Weight, thickness and diameter measurements were taken on both samples at 14 days.
- Refrigerant Swell:** The round disk-like samples were measured (2 each test) and placed in the bottom of the refrigerant test vessel (figure 4). Stainless steel screens were placed in between the samples so that the samples could be differentiated from each other. They also acted as weights to submerge the rubber disks.
- The test vessels were closed using a hydraulic press to compress the die springs. The springs maintained a constant force (2500 lbs.) on the Teflon O-Ring such that the volatile refrigerant gases were contained in the vessel.
- Test vessels were filled with refrigerant by first pulling a vacuum in the chamber. The refrigerant valve was then opened and refrigerant was allowed to fill the chamber to a mark slightly above the samples.
- In situ diameter changes were taken at 1 day, 3 day and 14 days through the use of a travelling microscope and microscope lights. These measurements were made possible by the use of a glass/polycarbonate window in the top of the test vessel.

TEST VESSEL IN SITU DIAMETER CHANGE MEASUREMENTS

APPENDIX D: ELASTOMER DIAMETER CHANGE IN TEST FLUIDS

Test Conditions

- insitu refrigerant exposure measurements taken after 14 days at room temperature
- insitu lubricant exposure measurements taken after 14 days at 60°C (140°F)

FIGURE 1A

% Insitu Diameter Change In R-22

FIGURE 1B
% Insitu Diameter Change In R-22

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 1C

% Insitu Diameter Change In R-22

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 1D
% Insitu Diameter Change In R-22

Silicones

Thermoplastic Elastomers

FIGURE 1E

% Insitu Diameter Change In R-22

Polysulfide Rubbers

Polyurethanes

FIGURE 1F

% Insitu Diameter Change In R-22

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 1G
% Insitu Diameter Change In R-22

FIGURE 1H
% Insitu Diameter Change In R-22

% Insitu Diameter Change In R-32

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 2B
% Insitu Diameter Change In R-32

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 2C

% Insitu Diameter Change In R-32

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 2D

% Insitu Diameter Change In R-32

Silicones

Thermoplastic Elastomers

% Insitu Diameter Change In R-124

FIGURE 3B
% Insitu Diameter Change In R-124

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 3C

% Insitu Diameter Change In R-124

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 3D

% Insitu Diameter Change In R-124

Silicones

Thermoplastic Elastomers

FIGURE 3E**% Insitu Diameter Change In R-124****Polysulfide Rubbers** **Polyurethanes**

FIGURE 3F
% Insitu Diameter Change In R-124

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 3G
% Insitu Diameter Change In R-124

FIGURE 3H
% Insitu Diameter Change In R-124

FIGURE 4A
% Insitu Diameter Change In R-134a

FIGURE 4B
% Insitu Diameter Change In R-134a

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 4C
 % Insitu Diameter Change In R-134a

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 4D
% Insitu Diameter Change In R-134a

FIGURE 4E
% Insitu Diameter Change In R-134a

Polysulfide Rubbers

Polyurethanes

FIGURE 4F
% Insitu Diameter Change In R-134a

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 4G
% Insitu Diameter Change In R-134a

FIGURE 4H
% Insitu Diameter Change In R-134a

% Insitu Diameter Change In R-125

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 5B**% Insitu Diameter Change In R-125****Styrene Butadiene Rubbers** **Nitrile Rubbers**

FIGURE 5C

% Insitu Diameter Change In R-125

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 5D

% Insitu Diameter Change In R-125

Silicones

Thermoplastic Elastomers

FIGURE 5E

% Insitu Diameter Change In R-125

Polysulfide Rubbers

Polyurethanes

FIGURE 5F

% Insitu Diameter Change In R-125

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 5G

% Insitu Diameter Change In R-125

FIGURE 5H**% Insitu Diameter Change In R-125** **Gasket Materials Supplied By Industry**

FIGURE 6A
 % In situ Diameter Change In R-143a

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 6B
% Insitu Diameter Change In R-143a

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 6C
% Insitu Diameter Change In R-143a

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 6D
% Insitu Diameter Change In R-143a

Silicones

Thermoplastic Elastomers

FIGURE 6E
% Insitu Diameter Change In R-143a

Polysulfide Rubbers

Polyurethanes

FIGURE 6E
% Insitu Diameter Change In R-143a

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 6G
% Insitu Diameter Change In R-143a

FIGURE 6H
% Insitu Diameter Change In R-143a

FIGURE 7A
% Insitu Diameter Change In R-152a

FIGURE 7B
% Insitu Diameter Change In R-152a

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 7C
% Insitu Diameter Change In R-152a

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 7D
% Insitu Diameter Change In R-152a

FIGURE 7E
% Insitu Diameter Change In R-152a

Polysulfide Rubbers

Polyurethanes

FIGURE 7F
% Insitu Diameter Change In R-152a

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 7G
% Insitu Diameter Change In R-152a

FIGURE 7H
% Insitu Diameter Change In R-152a

% Insitu Diameter Change In R-123

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 8B

% Insitu Diameter Change In R-123

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 8C**% Insitu Diameter Change In R-123****Fluorinated Rubbers** **Epichlorohydrin Based Rubbers**

FIGURE 8D**% Insitu Diameter Change In R-123****Silicones** **Thermoplastic Elastomers**

FIGURE 8E**% Insitu Diameter Change In R-123****Polysulfide Rubbers** **Polyurethanes**

FIGURE 8F

% Insitu Diameter Change In R-123

Chlorosulfonated Polyethylenes

EPM Rubbers

*rB

% Insitu Diameter Change In R-123

FIGURE 8H**% Insitu Diameter Change In R-123** **Gasket Materials Supplied By Industry**

FIGURE 9A
% Insitu Diameter Change In R-142b

FIGURE 9B
% Insitu Diameter Change In R-142b

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 9C
% Insitu Diameter Change In R-142b

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 9D
% Insitu Diameter Change In R-142b

FIGURE 9E
% Insitu Diameter Change In R-142b

FIGURE 9F
% Insitu Diameter Change In R-142b

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 9G
% Insitu Diameter Change In R-142b

FIGURE 9H
% Insitu Diameter Change In R-142b

FIGURE 10A

% Insitu Diameter Change In R-134

FIGURE 10B**% Insitu Diameter Change In R-134****Styrene Butadiene Rubbers** **Nitrile Rubbers**

FIGURE 10C

% Insitu Diameter Change In R-134

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 10D

% Insitu Diameter Change In R-134

Silicones

Thermoplastic Elastomers

FIGURE 10E**% Insitu Diameter Change In R-134****Polysulfide Rubbers** **Polyurethanes**

FIGURE 10F

% Insitu Diameter Change In R-134

Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 10G

% Insitu Diameter Change In R-134

FIGURE 10H

% Insitu Diameter Change In R-134

Gasket Materials Supplied By Industry

FIGURE 11A

% Diameter Change In Alkyl Benzene

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 11B
% Diameter Change In
Alkyl Benzene

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 11C
% Diameter Change In
Alkyl Benzene

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 11D
% Diameter Change In
Alkyl Benzene

Silicones

Thermoplastic Elastomers

FIGURE 11E
% Diameter Change In
Alkyl Benzene

Polysulfide Rubbers

Polyurethanes

FIGURE 11F
% Diameter Change In
Alkyl Benzene
Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 11G
% Diameter Change In
Alkyl Benzene

Ethylene Acrylic Elastomers

Chlorinated Polyethylenes

Ethylene Propylene Diene Rubbers

FIGURE 11H
% Diameter Change In
Alkyl Benzenel

Gasket Materials Supplied By Industry

FIGURE 12A

% Diameter Change In Minerol Oil

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 12B

% Diameter Change In Mineral Oil

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 12C

% Diameter Change In Mineral Oil

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

% Diameter Change In Mineral Oil

Silicones

Thermoplastic Elastomers

% Diameter Change In Mineral Oil

Polysulfide Rubbers

Polyurethanes

FIGURE 12F

% Diameter Change In Mineral Oil

Chlorosulfonated Polyethylenes

EPM Rubbers

% Diameter Change In Mineral Oil

Ethylene Acrylic Elastomers

Chlorinated Polyethylenes

Ethylene Propylene Diene Rubbers

FIGURE 12H
 % Diameter Change In
 Mineral Oil

Gasket Materials Supplied By Industry

FIGURE 13A
% Diameter Change In
Pentaerythritol Ester Mixed Acid

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 13B
% Diameter Change In
Pentaerythritol Ester Mixed Acid

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 13C
% Diameter Change In
Pentaerythritol Ester Mixed Acid

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 13D
% Diameter Change In
Pentaerythritol Ester Mixed Acid

Silicones

Thermoplastic Elastomers

FIGURE 13E
% Diameter Change In
Pentaerythritol Ester Mixed Acid
Polysulfide Rubbers

Polyurethanes

FIGURE 13F
% Diameter Change In
Pentaerythritol Ester Mixed Acid
Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 13G
% Diameter Change In
Pentaerythritol Ester Mixed Acid

Ethylene Acrylic Elastomers

Chlorinated Polyethylenes

Ethylene Propylene Diene Rubbers

FIGURE 13H
 % Diameter Change In
 Pentaerythritol Ester Mixed Acid

Gasket Materials Supplied By Industry

FIGURE 14A

% Diameter Change In Pentaerythritol Ester Branched Acid

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 14B

% Diameter Change In Pentaerythritol Ester Branched Acid

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 14C

% Diameter Change In Pentaerythritol Ester Branched Acid

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

% Diameter Change In Pentaerythritol Ester Branched Acid

Silicones

Thermoplastic Elastomers

% Diameter Change In
Pentaerythritol Ester Branched Acid

Polysulfide Rubbers

Polyurethanes

FIGURE 14F

% Diameter Change In
Pentaerythritol Ester Branched Acid
Chlorosulfonated Polyethylenes

EPM Rubbers

% Diameter Change In
Pentaerythritol Ester Branched Acid

Ethylene Acrylic Elastomers

Chlorinated Polyethylenes

Ethylene Propylene Diene Rubbers

FIGURE 14H

% Diameter Change In
Pentaerythritol Ester Branched Acid

Gasket Materials Supplied By Industry

FIGURE 15A

% Diameter Change In Polypropylene Glycol Diol

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 15B
% Diameter Change In
Polypropylene Glycol Diol

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 15C
% Diameter Change In
Polypropylene Glycol Diol

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 15D
% Diameter Change In
Polypropylene Glycol Diol

Silicones

Thermoplastic Elastomers

FIGURE 15E
% Diameter Change In
Polypropylene Glycol Diol

Polysulfide Rubbers

Polyurethanes

FIGURE 15F
% Diameter Change In
Polypropylene Glycol Diol
Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 15G
% Diameter Change In
Polypropylene Glycol Diol

FIGURE 15H
 % Diameter Change In
 Polypropylene Glycol Diol

Gasket Materials Supplied By Industry

FIGURE 16A

% Diameter Change In Polypropylene Glycol Butyl Monoether

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 16B
% Diameter Change In
Polypropylene Glycol Butyl Monoether

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 16C
% Diameter Change In
Polypropylene Glycol Butyl Monoether

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 16D
% Diameter Change In
Polypropylene Glycol Butyl Monoether
Silicones

Thermoplastic Elastomers

FIGURE 16E
% Diameter Change In
Polypropylene Glycol Butyl Monoether
Polysulfide Rubbers

Polyurethanes

FIGURE 16F
% Diameter Change In
Polypropylene Glycol Butyl Monoether
Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 16G

% Diameter Change In Polypropylene Glycol Butyl Monoether

Ethylene Acrylic Elastomers

Chlorinated Polyethylenes

Ethylene Propylene Diene Rubbers

FIGURE 16H

% Diameter Change In
Polypropylene Glycol Butyl Monoether

Gasket Materials Supplied By Industry

FIGURE 17A

% Diameter Change In Modified Polyglycol

Polyisoprenes

Polychloroprenes

Butyl Rubbers

FIGURE 17B

% Diameter Change In Modified Polyglycol

Styrene Butadiene Rubbers

Nitrile Rubbers

FIGURE 17C

% Diameter Change In Modified Polyglycol

Fluorinated Rubbers

Epichlorohydrin Based Rubbers

FIGURE 17D

% Diameter Change In Modified Polyglycol

Silicones

Thermoplastic Elastomers

% Diameter Change In Modified Polyglycol

Polysulfide Rubbers

Polyurethanes

FIGURE 17F
% Diameter Change In
Modified Polyglycol
Chlorosulfonated Polyethylenes

EPM Rubbers

FIGURE 17G

% Diameter Change In Modified Polyglycol

Ethylene Acrylic Elastomers

Chlorinated Polyethylenes

Ethylene Propylene Diene Rubbers

FIGURE 17H

% Diameter Change In
Modified Polyglycol

Gasket Materials Supplied By Industry

APPENDIX E: ELASTOMER SWELL DATA CHARTS

- refrigerant exposures at room temperature and measurements were taken after:

insitu: 1 day
3 day
14 day

after 14 day exposure: 2 hour
24 hour

- lubricant exposures are at 60°C (140°F) and measurements were taken after:

insitu: 1 day
14 day

after 14 day exposure: 24 hour

Description of Information and Test Results Contained in Appendix E

- Test Sample Recipe:** The test sample recipe is contained in the upper left hand corner of the data sheets. The information identifies the generic classification of elastomer and ingredients used in the compound formulation. More specific information regarding the exact materials used is contained in Appendix A. Also given in this portion of the data sheet is the corresponding quantities of each of the compound ingredients.
- Lubricant Legend:** Generic identification of the lubricants used in this study is located in the upper right hand corner of the data sheets. More detailed information concerning the exact material and supplier is found in Appendix G.
- Column 1:** Each of the test formulation sample materials was submersed in 17 different test fluids. This column of information identifies each of the test fluids used in the phase I study. More detailed information concerning each of the test fluids is contained in Appendix G.
- Columns 2,3 & 4:** Measurements of the diameters of the test samples were made at various time intervals while in contact with the test fluids. Samples tested in refrigerants were measured insitu. Samples being tested in the lubricants were removed from the test fluid, quickly measured and returned to the test medium. These columns of data reflect the % diameter change of the samples over the indicated time interval and the values are based on the original sample dimensions.
- Column 5:** The sample materials were submersed in the test fluids for a period of 14 days after which time they were removed from the fluid and certain measurements were made. This column of information reflects the % weight change of the samples due to contact with the specified test fluid and the measurement is made immediately after removal from the test medium.

Columns 6 and 7:

During the initial testing it was observed that some sample materials in some of the refrigerant test fluids were observed to quickly increase and then decrease in size during the first several hours subsequent to their removal from the refrigerant test fluid. These columns of data provides information concerning the state of the sample material 2 hours and 24 hours after their removal from the specified test fluid. The data is based on the original sample diameters.

Through the comparison of column 4 (14 day diameter change) information and columns 6 and 7 (2 hr. and 1 day diameter change) one is able to determine the state of the sample during this time interval. Extreme and violent outgasing can lead to drastic changes in the size of the sample during this time period. This phenomenon can lead to changes in the integrity of the sample material such as fractures and perhaps a permanent dimensional change.

Column 8:

This column provides information that can be used to determine the permanent/reversible effect of the indicated solvent with the sample material. Negative values indicate some degree of extractibility of the sample material. Large positive values indicate the non-reversible swelling behavior of the fluid.

Column 9:

This column provides information relating to the change of the hardness of the material 24 hours after removal from the indicated test fluid.

Formula # 1		Polyisoprene		100.00		Lubricant Legend Information						PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc Oxide		5.00								PEBA - Pentaerythritol Ester Branched Acid	
		Stearic Acid		2.00								PPGBM - Polypropylene Glycol Butyl Monoether	
		Sulfur		2.25								MO - Mineral Oil	
		N-t-butyl-2-benzothiazyl sulfenamide		.7				MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean
R-22	10.3	10.4	10.2	-	45.3/42.4	43.9			-2.1/0.5	-8	-2.0/-1.5	-1.8	
R-32	2.8	2.7	2.7	-	8.9/8.6	8.8	1.0/0.4	.8	0.3/-0.7	-0.2	1.7/1.8	1.8	46/47 A
R-124	5.6	5.6	5.8	-	30.2/29.8	30.0	2.7/3.3	3.0	-0.4/0.8	0.2	-1.3/1.3	0	
R-134a	1.4	-	1.2	-	4.9/4.8	4.9	-0.4		-0.2/-0.3	-0.3	-0.9/-0.9	-0.9	
R-125	4.6	4.2	4.2	-	14.9/14.3	14.6	3.4		2.7/2.2	2.5	9.1/8.7	8.9	
R-143a	2.2	1.7	1.9	-	5.4/4.9	5.2	1.5		1.1/0	0.6	-0.7/-0.7	-0.7	
R-152a	4.1	4.2	4.2	-	12.3/13.1	12.7	1.1		-0.3/0.2	-0.1	1.6/2.1	1.9	
R-123	48.1	47.5	48.0	-	328/327	328.	3.0		0.2/0	0.1	0.9/1.7	1.3	
R-142b	10.3	10.0	10.2	-	40.1/38.7	39.4	1.6		0.7/0.5	0.6	-1.3/-1.1	-1.2	
R-134	1.7	1.5	1.5	-	7.8/7.6	7.7	-0.4/0.1	-0.2	-1.5/-0.9	-1.2	-0.1/0	-0.1	45/46 A
AB	41.8	-	57.3/55.7	56.5	264/261	263.			54.4/54.4	54.4	251/520	251	
MO	43.1	-	53.1/53.2	53.2	248/247	247.					238/236	237	
PEMA	16.1	-	29.2/28.0	28.6	117/113	115.			24.7/25.5	25.1	105/102	104	
PEBA	16.6	-	26.5/25.7	26.1	106/104	105.					97.7/96.1	96.9	
PPGD	1.0	-	2.1/2.2	2.2	7.9/7.7	7.8					7.4/7.1	7.3	
PPGBM	4.3	-	8.1/8.0	8.1	28.1/27.8	28.0			6.9/5.9	6.4	19.2/19.9	19.6	
MPG	1.7	-	2.3/2.8	2.6	8.5/8.6	8.6			1.5/2.0	1.8	7.6/7.6	7.6	39/40 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 3		Polyisoprene		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid				
		Zinc Oxide		5.00						PEBA - Pentaerythritol Ester Branched Acid		
		Stearic Acid		2.00								
		N-oxydiethylene-2-benzothiazyl-sulfenamide		1.00								
		Tetramethylthiuram disulfide		1.00		MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol				
		Di-morpholino disulfide		1.00								
						AB - Alkyl Benzene						
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness	
			values	mean	values	mean	2 hr. Diameter (%)	1 Day Diameter (%)	1 Day Weight (%)	values		mean
R-22	9.6	10.1	8.9		44.4/42.5	43.5			-1.9/0.8	-0.5	-3.7/-3.4	-3.6
R-32	1.3	0.8	1.5		4.7/4.4	4.6	2.5/0.5	1.5	0.7/-0.6	0.1	-1.8/-1.7	-1.8
R-124	6.5	6.5	6.1		28.2/28.3	28.3	1.8/1.2	1.5	-0.5/-0.9	-0.7	-2.6/-2.1	-2.4
R-134a	1.0	-	1.2		3.8/3.4	3.6	-0.8		-0.6/0.5	-0.1	-2.4/-2.0	-2.2
R-125	3.3	2.9	2.7		10.3/10.1	10.2	2.0		0.9/1.3	1.1	4.7/4.6	4.7
R-143a	2.0	2.5	2.7		4.6/4.1	4.4	2.1		1.5/-0.3	0.6	-0.2/-1.7	-1.9
R-152a	3.1	2.8	3.1		8.3/9.5	8.9	0.2		-0.9/-1.2	-1.1	-2.3/-1.8	-2.1
R-123	52.7	52.3	51.8		386/390	388	8.2/8.1	8.2	-1.1/-0.7	-0.9	-1.0/-0.2	-0.6
R-142b	9.2	9.1	9.5		40.1/39.1	39.6	-0.5		-1.3/-0.9	-1.1	-2.9/-2.4	-2.7
R-134	0.8	0.9	1.0		6.3/5.9	6.1	-0.6/-0.6	-0.6	-1.5/-1.4	-1.5	-1.5/-1.5	-1.5
AB	47.0	-	56.2/55.6	55.9	257/257	257			64.1/67.3	65.7	247/247	247
MO	49.5	-	56.7/57.0	56.9	271/272	271					262/261	262
PEMA	18.8	-	22.0/21.9	22.0	83.1/83.2	83.2			19.0/18.4	18.7	70.7/71.3	71.0
PEBA	14.7	-	20.3/20.2	20.3	75.8/76.4	76.1					65.9/66.6	66.3
PPGD	0.6	-	0.7/0.6	0.7	1.4/1.7	1.6					1.1/1.1	1.1
PPGBM	4.5	-	5.7/5.9	5.8	17.7/18.1	17.9			3.0/3.9	3.5	9.2/9.5	9.4
MPG	1.2	-	1.8/2.2	2.0	5.7/6.4	6.1			-0.2/0.3	0.1	4.6/5.1	4.9
												32/33 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 4		Poly(chlorobutadiene)		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid							
		Zinc Oxide		5.00						PEBA - Pentaerythritol Ester Branched Acid					
		Stearic Acid		0.50											
		Magnesium Oxide		4.00											
								MO - Mineral Oil		MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness				
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)			
			values	mean	values	mean	values	mean	values	mean		values	mean		
R-22	6.3	6.1	6.1	22.2/21.6	2.19	24.8/28.0	26.4	-5.7/5.1	-0.3						
R-32	1.1	1.1	1.0	4.3/4.4	4.4	1.4/0.4	0.9	0.6/0.4	0.5						68/69 A
R-124	1.9	2.7	2.8	10.3/10.1	10.2	2.4/3.0	2.7	1.5/1.4	5.1						
R-134a	1.1		1.2	3.4/3.4	3.4	1.3		0.6/0.7	0.7						
R-125	1.4	2.4	2.7	5.5/5.0	5.3	1.8		2.7/2.3	2.5						
R-143a	1.1	1.3	1.2	3.3/3.6	3.5	2.5		3.1/3.4	3.3						
R-152a	2.9	3.1	3.0	7.6/7.5	7.6	2.1		0.7/0.1	0.4						
R-123	16.0	15.6	15.3	65.0/65.2	65.1	6.2		1.4/1.3	1.4						
R-142b	6.6	6.6	6.5	18.4/18.6	18.5	4.9		2.9/0.7	1.8						
R-134	-0.1	0.3	0.6	3.3/3.4	3.4	0.7/0.7	0.7	1.8/1.1	1.5						73/74 A
AB	10.0	-	19.6/20.1	19.9	51.1/53.2	52.2		19.7/20.8	20.3						
MO	12.9	-	26.5/26.0	26.3	74.7/71.9	73.3									
PEMA	25.7	-	53.7/53.3	53.5	202/211	206		52.3/52.6	52.5						
PEBA	11.4	-	35.4/26.0	30.7	128/77.1	103									
PPGD	3.7	-	7.3/7.9	7.6	19.9/18.7	19.3									
PPGBM	4.8	-	12.3/11.4	11.9	29.7/31.1	30.4									
MPG	0.4	-	3.9/4.1	4.0	11.7/12.0	11.9									35/36 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 5		Poly(chlorobutadiene)		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid											
		Zinc Oxide		5.00				PEBA - Pentaerythritol Ester Branched Acid											
		Stearic Acid		0.50				PPGBM - Polypropylene Glycol Butyl Monoether											
		Magnesium Oxide		4.00				MO - Mineral Oil											
		N330 Carbon Black		30.00				MPG - Modified Polyglycol											
								PPGD - Polypropylene Glycol Diol											
								AB - Alkyl Benzene											
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness						
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)								
			values	mean	values	mean	values	mean	values	mean	values	mean							
R-22	4.8	4.9	4.9		17.2/16.8	17.0	3.2		-0.7/-1.0	-0.9	0.6/1.0	0.8							
R-32	1.3	1.6	1.4		3.7/3.6	3.7	0.7/1.1	0.9	-0.2/-0.1	-0.2	0.3/0.3	0.3	81/82 A						
R-124	1.1	2.8	1.6		7.6/7.7	7.7	1.3/2.0	1.7	0.4/1.3	0.9	4.0/4.2	4.1							
R-134a	0.6		1.0		2.7/2.6	2.7	0.3		0.1/0.7	0.4	1.3/1.3	1.3							
R-125	0.5	1.8	2.1		4.6/4.6	4.6	1.3		1.3/1.1	1.2	3.7/3.8	3.8							
R-143a	0.4	0.9	0.8		2.5/5.1	2.3	0.4		0.1/0.6	0.4	1.1/1.0	1.1							
R-152a	2.5	2.9	2.9		5.6/5.9	5.8	1.9		0.6/0	0.3	1.6/1.2	1.4							
R-123	11.9	11.8	11.4		48.9/49.5	49.2	5.0		1.4/0.9	1.2	7.2/6.9	7.1							
R-142b	4.6	5.1	4.8		14.4/14.5	14.5	2.0		1.2/1.2	1.2	3.4/3.9	3.7							
R-134	0.4	0.9	0.9		2.7/2.7	2.7	0.6/0.3	0.5	0.3/0.2	0.3	1.4/1.4	1.4	82/83 A						
AB	7.6	-	16.1/15.3	15.7	23.5/38.5	31.0			14.2/15.0	14.6	35.0/35.7	35.4							
MO	7.9	-	18.9/18.2	18.6	49.0/48.4	48.7					46.2/45.3	45.8							
PEMA	12.5	-	30.5/28.7	29.6	93.0/91.8	92.4			27.3/27.3	27.3	90.1/88.6	89.4							
PEBA	7.3	-	22.1/22.1	22.1	65.9/63.6	64.9					64.4/62.6	63.5							
PPGD	2.5	-	5.0/4.8	4.9	13.2/13.9	13.6					13.2/13.9	13.5							
PPGBM	3.2	-	9.2/9.5	9.4	23.0/23.0	23.0			8.5/9.2	8.9	22.0/22.2	22.1							
MPG	8.4	-	2.8/2.9	2.9	8.3/6.7	7.5			2.2/2.2	2.2	8.1/6.5	7.3	57/58 A						

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 6		Isobutyl isoprene (0.7% unsaturated)		100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid			
		Zinc Oxide		3.00									
		Stearic Acid		1.00									
		Sulfur		1.66									
		Tetramethyl thiuram disulfide		1.00		MPG - Modified Polyglycol				PPGD - Polypropylene Glycol Diol			
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness
			values	mean	values	mean	2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		
							values	mean	values	mean	values	mean	
R-22*	4.5	4.5	3.9		21.8/22.4	22.1	2.0		55.2/60.6	57.9	1.9/2.6	2.3	
R-32	0.5	0.7	1.0		4.0/4.0	4.0	45.9/47.0	46.5	33.7/33.3	33.5	1.7/1.7	1.7	25/26 A
R-124	1.0	1.5	3.2		16.3/16.4	16.4	2.5/4.0	3.3	2.5/2.9	2.7	13.1/13.1	13.1	
R-134a	0.3		0.6		3.0/2.7	2.9	0.4		0.5/0.1	0.3	1.8/1.9	1.9	
R-125	1.6	2.4	2.6		8.2/7.2	7.7	2.6		9.5/7.5	8.5	7.1/6.3	6.7	
R-143a	0.7	0.6	1.3		4.1/3.5	3.8	10.1		31.0/25.1	28.1	3.1/2.7	2.9	
R-152a	0.6	1.0	1.7		7.6/6.4	7.0	1.6		2.7/2.5	2.6	3.9/4.0	4.0	
R-123	16.8	16.8	16.3		90.2/90.2	90.2	8.1		5.5/5.5	5.5	26.2/28.1	27.2	
R-142b	4.7	6.1	6.2		25.5/25.8	25.7	4.5		4.1/3.2	3.7	13.0/13.5	13.3	
R-134	-0.1	0.1	0.5		2.9/2.8	2.9	-0.1/-0.2	-0.2	0.2/-0.1	0.1	1.7/1.8	1.8	33/34 A
AB	23.4	-	67.5/67.7	67.6	341/338	339			67.2/66.7	67.0	329/327	328	
MO	27.7	-	72.1/65.7	68.9	386/335	361					374/326	350	
PEMA	1.6	-	3.1/2.8	3.0	10.1/9.9	10.0			2.5/2.6	2.6	8.7/8.9	8.8	
PEBA	0.9	-	2.0/2.4	2.2	6.9/7.5	7.2					6.0/7.0	6.5	
PPGD	-0.1	-	0.4/-0.3	0.1	-0.1/-0.1	-0.1					-0.3/-0.3	-0.3	
PPGBM	0	-	0.2/0.2	0.2	0.4/0.4	0.4			-0.1/0.6	0.3	0.1/-0.1	0	
MPG	3.2	-	-2.1/-0.3	-1.2	-0.1/-0.1	-0.1			-0.4/-0.6	-0.5	-0.5/-0.5	-0.5	27/28 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 7		Isobutyl isoprene (2.2% unsaturated)		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid							
		Zinc Oxide		3.00				PEBA - Pentaerythritol Ester Branched Acid							
		Stearic Acid		1.00				PPGBM - Polypropylene Glycol Butyl Monoether							
		Sulfur		1.75				MO - Mineral Oil							
		Tetramethyl thiuram disulfide		1.00				MPG - Modified Polyglycol							
								PPGD - Polypropylene Glycol Diol							
								AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness				
			values		mean		values		mean			1 Day Diameter (%)		1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean		
R-22	5.6	5.2	5.2		22.5/22.5	22.5	3.8		1.9/2.3	2.1	-0.9/-0.6	-0.8			
R-32*	0.4	0.6	1.2		4.0/4.0	4.0	37.3/36.4	36.9	10.3/9.0	9.7	1.1/1.0	1.1	33/34 A		
R-124	1.3	1.4	3.5		17.1/16.7	16.9	3.1/3.0	3.1	2.4		13.2/13.3	13.3			
R-134a	0.2		0.6		2.7/2.8	2.8	0.3		0.6/0.2	0.4	1.8/1.8	1.8			
R-125	2.1	2.6	3.0		8.9/7.9	8.4	2.5		3.5/2.8	3.2	7.6/6.8	7.2			
R-143a	0.5	0.7	1.4		4.2/4.3	4.3	2.1		11.9/12.9	12.4	3.3/3.5	3.4			
R-152a	1.1	1.4	1.9		10.1/7.9	9.0	1.2		1.2/1.3	1.3	3.8/4.0	3.9			
R-123	16.6	16.5	16.3		90.1/89.9	90.0	8.9		5.2/5.1	5.2	27.5/26.7	27.1			
R-142b	4.1	6.5	6.6		26.7/25.8	26.3	4.5		3.5/4.0	3.8	13.8/13.4	13.6			
R-134	-0.1	0.6	0.5		3.2/2.9	3.1	0.6/0.1	0.4	0.5/-0.3	0.1	2.3/2.1	2.2			
AB	18.0	-	54.6/55.2	54.9	254/253	253			53.4/54.6	54.0	246/245	246			
MO	24.7	-	59.4/56.4	57.9	292/271	282					282/263	273			
PEMA	1.8	-	3.0/3.0	3.0	10.0/10.7	10.4			2.2/2.4	2.4	9.5/10.2	9.9			
PEBA	0.1	-	1.3/2.6	2.0	7.2/7.9	7.6					6.6/7.4	7.0			
PPGD	0.1	-	0.5/-0.5	0	0.30/5	0.4					0.20/2	0.2			
PPGBM	0.2	-	0.70/5	0.6	1.0/1.4	1.2			-0.2/-0.6	-0.4	0.8/0.9	0.9			
MPG	-0.1	-	-0.20/2	0	0.20/2	0.2			-0.9/-0.5	-0.7	-0.2/-0.2	-0.2	34/35 A		

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 8		Isobutyl isoprene (2.2% unsaturated)		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc Oxide		3.00												PEBA - Pentaerythritol Ester Branched Acid	
		Stearic Acid		1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
		Sulfur		1.75												MO - Mineral Oil	
		Tetramethyl thiuram disulfide		1.00												MPG - Modified Polyglycol	
		N330 Carbon Black														PPGD - Polypropylene Glycol Diol	
																AB - Alkyl Benzene	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22*	4.2	4.4	4.4		15.0/15.1	15.1	4.8		1.6/1.6	1.6	6.0/6.3	6.2					
R-32	0.4	0.8	1.0		2.8/2.6	2.7	1.0/0.5	0.8	0.7/0.7	0.7	2.3/0.5	1.4	64/65 A				
R-124	0.4	1.0	2.7		19.5/18.2	18.9	3.1/2.1	2.6	2.1/2.1	2.1	16.6/15.6	16.1					
R-134a	0.1		0.4		1.9/1.9	1.9	0.4		0.6/0.3	0.5	1.1/1.1	1.1					
R-125	0.6	1.5	1.9		5.4/5.4	5.4	1.1		0.7/1.0	0.9	4.7/4.6	4.7					
R-143a	0.3	0.1	0.7		2.7/2.3	2.5	0.5		0.6/0.8	0.7	2.0/2.0	2.0					
R-152a	0.6	0.4	1.6		-3.4/-2.4	-2.9	1.2/1.4	1.3	0.9/1.4	1.2	-4.8/-3.7	-4.3					
R-123	11.9	11.9	12.0		57.9/57.8	57.9	6.4		4.0/3.9	4.0	20.0/20.3	20.2					
R-142b	2.5	4.9	4.7		17.3/17.3	17.3	2.9		2.9/2.0	2.5	9.8/8.9	9.4					
R-134	-0.2	0.1	0.4		1.8/1.7	1.8	-0.3/0.1	-0.1	0.1/0.1	0.1	1.1/1.1	1.1	65/66 A				
AB	8.1	-	35.9/35.3	35.6	129/126	128			34.4/34.5	34.5	126/123	124					
MO	10.7	-	39.8/39.4	39.6	151/151	151					147/147	147					
PEMA	0.5	-	2.1/2.3	2.2	6.7/6.6	6.7			1.8/2.3	2.1	6.8/6.4	6.6					
PEBA	0.5	-	1.5/1.7	1.6	4.1/4.8	4.5					3.8/4.3	4.1					
PPGD	-0.1	-	0.4/0.3	0.4	0.1/0.2	0.1					0.2/0.3	0.3					
PPGBM	0.2	-	0.5/0.5	0.5	0.7/0.6	0.7			0.2/0.7	0.5	0.5/0.4	0.5					
MPG	0.1	-	-0.1/-0.1	-0.1	-0.1/-0.1	-0.1			-0.3/-0.3	-0.3	-0.3/-0.3	-0.3	62/63 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 9		Bromobutyl		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid							
		Zinc Oxide		5.00						PEBA - Pentaerythritol Ester Branched Acid					
		Stearic Acid		1.00											
								PPGBM - Polypropylene Glycol Butyl Monoether							
								MO - Mineral Oil							
								MPG - Modified Polyglycol							
								PPGD - Polypropylene Glycol Diol							
								AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness				
			values		mean		values		mean			values		mean	
			values	mean	values	mean	values	mean	values	mean		values	mean		
R-22	5.3	5.6	5.3		23.5/23.4	23.5	3.4	83.7/85.0	84.4	4.3/4.4	4.4				
R-32	0.8	1.1	1.1		4.1/4.0	4.1	61.3/661.0	61.2	37.0/39.2	38.1	1.3/1.4	1.4			
R-124	1.7	2.4	4.1		17.4/18.3	17.9	3.8/3.2	3.5	3.0	13.5/13.1	13.3				
R-134a	0.1		0.6		3.1/2.8	3.0	1.1		0.6/0.3	0.5	2.0/2.1	2.1			
R-125	1.6	2.6	2.9		8.5/7.6	8.1	12.4		19.7/13.0	16.4	7.6/6.6	7.1			
R-143a	0.4	0.4	1.1		4.3/4.4	4.4	20.9		39.2/41.2	40.2	3.4/3.3	3.4			
R-152a	0.6	1.6	1.9		6.9/6.1	6.5	1.6		1.6/6.2	3.9	4.0/3.9	4.0			
R-123	18.7	18.9	18.8		102/102	102	10.1		6.0/5.1	5.6	28.0/27.4	27.7			
R-142b	4.9	6.7	6.5		26.9/26.3	26.6	4.2		2.5/3.4	3.0	12.9/13.8	13.4			
R-134	0.3	0.2	0.2		2.9/2.7	2.8	0.2/0.1	0.1	-0.1/-0.1	-0.1	2.1/2.1	2.1			
AB	30.3	-	85.9/77.2	81.6	523/447	485			84.1/77.3	80.7	475/412	444			
MO	37.8	-	86.2/86.2	86.2	521/509	515					496/486	491			
PEMA	1.6	-	5.9/6.0	6.0	21.2/21.5	21.4			5.8/4.5	5.2	20.8/21.2	21.0			
PEBA	1.1	-	3.3/4.0	3.7	10.9/12.9	11.9					10.5/12.5	11.5			
PPGD	0.6	-	0.8/1.5	1.2	5.1/5.3	5.2					5.1/5.1	5.1			
PPGBM	0.1	-	1.0/0.8	0.9	4.0/4.1	4.1			1.2/0.1	0.7	3.7/3.9	3.8			
MPG	0.1	-	0.2/-0.1	0.1	1.0/1.1	1.1			-0.5/-0.3	-0.4	0.8/0.8	0.8			
												28/29 A			

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 10		Bromobutyl		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc Oxide		5.00												PEBA - Pentaerythritol Ester Branched Acid	
		Stearic Acid		1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
		N330 Carbon Black		40.00												MO - Mineral Oil	
										MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene			
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid.				1 Day Shore A/D Hardness						
			Change (%)		Values Based On Original Sample Measurements.		Values Based On Original Sample Measurements.										
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean			
R-22	3.9	3.9	3.8		17.0/16.8	16.9	2.8		1.00/6	0.8	6.4/6.2	6.3					
R-32	0.3	0.2	0.5		3.5/3.3	3.4	0.6/1.0	0.8	0.1/1.0	0.6	1.6/1.5	1.6		57/58 A			
R-124	0.8	1.4	2.5		12.5/12.6	12.6	2.4/3.2	2.8	1.7		10.2/10.2	10.2					
R-134a	0.2		0.4		1.6/1.9	1.8	0.4		0.4/-0.3	0.1	1.2/1.3	1.3					
R-125	1.3	2.0	2.7		7.9/7.1	7.5	2.1		2.1/2.1	2.1	6.9/6.2	6.6					
R-143a	0.5	0.4	0.9		3.1/2.7	2.9	0.8		0.8/0.7	0.8	2.3/2.5	2.4					
R-152a	0.4	0.7	1.2		4.6/5.0	4.8	0.9		0.9/0.8	0.9	3.1/3.0	3.1					
R-123	14.3	14.4	14.4		71.6/71.8	71.7	8.3		4.1/3.9	4.0	20.8/21.6	21.2					
R-142b	2.2	5.3	5.6		19.2/19.2	19.2	4.1		2.5/3.1	2.8	10.5/10.4	10.5					
R-134	-0.1	0.4	-0.2		2.1/2.4	2.3	0.2/0.2	0.2	0.5/0.2	0.4	1.5/1.6	1.6		55/56 A			
AB	15.5	-	47.1/47.6	47.4	187/190	188			43.1/46.1	44.6	178/180	179					
MO	19.2	-	52.2/50.9	51.6	229/225	227					223/219	221					
PEMA	1.5	-	4.0/3.9	4.0	12.6/12.3	12.5			4.2/4.0	4.1	12.2/12.0	12.1					
PEBA	0.2	-	1.9/2.2	2.1	7.8/6.4	7.1					7.5/6.1	6.8					
PPGD	0.5	-	1.4/1.1	1.3	3.2/3.2	3.2					3.3/3.2	3.3					
PPGBM	0.5	-	1.0/0.6	0.8	3.0/2.7	2.9			0.7/0.5	0.6	2.4/2.3	2.4					
MPG	-0.1	-	0.3/0.2	0.3	0.8/0.7	0.8			0.3/-0.6	-0.2	0.5/0.4	0.5		56/57 A			

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 11		Chlorobutyl		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc Oxide		5.00												PEBA - Pentaerythritol Ester Branched Acid	
		Stearic Acid		1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
																MO - Mineral Oil	
										MPG - Modified Polyglycol				PPGD - Polypropylene Glycol Diol			
												AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean			
R-22*	5.8	6.1	5.7		26.2/25.5	25.9	152/151	152	42.6/37.3	40.0	3.0/5.3	4.2					
R-32	0.6	0.7	1.2		4.5/4.6	4.6	44.0/42.4	43.2	28.4/26.3	27.4	1.6/1.5	1.6	27/28 A				
R-124	1.3	2.0	3.6		19.7/17.6	18.7	2.4/2.4	2.4	2.2/2.3	2.3	12.9/12.9	12.9					
R-134a	0.1	0.3	0.5		2.8/2.6	2.7	-0.3/-0.1	-0.2	-0.2/0.2	0.0	2.1/2.1	2.1					
R-125	1.8	2.1	2.5		8.1/7.2	7.7	9.8/8.2	9.0	9.3/6.0	7.7	6.8/6.0	6.4					
R-143a	0.5	0.7	1.3		4.0/3.8	3.9	17.9/23.4	20.7	22.7/23.4	23.1	3.1/3.1	3.1					
R-152a	0.8	1.1	1.9		6.7/6.6	6.7	1.1/1.4	1.3	1.1/1.0	1.1	4.2/4.4	4.3	33/34 A				
R-123	18.2	18.2	18.5		32.9/34.1	33.5	11.9/11.7	11.8	6.1/4.9	5.5	26.7/27.5	27.1	32/33 A				
R-142b	4.9	6.7	7.0		27.9/28.0	28.1	5.6/6.2	5.9	3.8/3.1	3.4	14.9/15.2	15.1					
R-134	-0.2	0.1	-0.1		3.0/2.7	2.9	0.2/-0.3	-0.1	0.1/0.4	0.2	2.1/2.0	2.1	34/35 A				
AB	29.9	-	62.7/61.3	61.9	304/292	298			60.7/61.2	60.9	300/289	294	5/6 A				
MO	38.3	-	69.1/68.7	68.9	385/371	378			67.9/67.1	67.5	371/367	369	8/9 A				
PEMA	1.4	-	4.2/4.1	4.2	14.8/14.5	14.7			3.3/3.1	3.2	14.5/14.3	14.4	24/25 A				
PEBA	0.9	-	3.4/3.7	3.6	13.0/13.1	13.1			3.1/2.7	2.9	12.5/12.5	12.5	25/26 A				
PPGD	0.3	-	1.3/1.4	1.3	4.4/4.4	4.4			0.2/-0.1	0.1	4.2/4.3	4.3	27/28 A				
PPGBM	-0.2	-	0.6/0.7	0.7	3.0/3.3	3.2			0.1/0.1	0.1	2.8/3.0	2.9	29/30 A				
MPG	0.5	-	0.1/0.1	0.1	1.1/1.1	1.1			-0.5/-0.1	-0.3	0.9/1.0	1.0	30/31 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 12		Chlorobutyl				100.00				Lubricant Legend Information				Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness	
		Zinc Oxide				5.00													
		Stearic Acid				1.00													
		N330 Carbon Black				40.00													
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)				1 Day Diameter (%)				1 Day Weight (%)				
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean					
R-22	4.9	5.1	4.0		25.6/14.7	20.2	4.2/4.3	4.3	2.7/2.6	2.7	13.1/3.7	8.4							
R-32	0.3	0.3	0.4		3.0/3.0	3.0	0.6/1.3	1.0	0.7/0.7	0.7	1.4/1.4	1.4		55/56 A					
R-124	0.7	1.5	2.6		13.2/13.2	13.2	2.2/1.8	2.0	0.6/1.4	1.0	9.7/9.6	9.7							
R-134a	0.1	0.1	0.3		2.0/1.7	1.9	0.2/0.1	0.1	-0.3/-0.3	-0.3	1.4/1.3	1.4							
R-125	0.9	1.1	1.5		4.5/3.9	4.2	1.1/1.2	1.2	1.4/0.6	1.0	3.8/3.4	3.6							
R-143a	0.2	0.2	0.8		2.0/2.5	2.3	0.2/0.5	0.4	0.8/0.4	0.6	1.6/2.1	1.9							
R-152a	0.4	0.6	1.1		5.1/4.9	5.0	0.8/0.8	0.8	0.6/0.6	0.6	3.2/3.2	3.2	55/56 A						
R-123	13.8	13.6	13.6		73.2/73.4	73.3	8.5/10.8	9.7	3.6/4.8	4.2	21.7/23.9	22.8	50/51 A						
R-142b	3.7	4.9	5.3		20.0/20.1	20.0	4.4/4.2	4.3	3.2/2.8	3.0	11.0/11.4	11.2							
R-134	-0.1	0.1	-0.6		2.5/2.0	2.3	0.4/-0.1	0.2	0.4/-0.2	0.1	1.4/1.5	1.5	55/56 A						
AB	17.6	-	39.5/38.6	39.1	151/145	148			35.1/37.9	36.5	151/144	148	26/27 A						
MO	23.4	-	45.1/43.9	44.5	186/183	184			46.9/44.2	45.6	185/182	184	31/32 A						
PEMA	1.0	-	3.3/3.4	3.3	10.4/10.5	10.5			2.9/3.1	3.0	10.2/10.4	10.3	48/49 A						
PEBA	1.1	-	2.7/3.2	2.9	8.7/9.3	9.0			2.5/3.6	3.1	8.3/9.1	8.7	48/49 A						
PPGD	0.2	-	0.8/0.5	0.6	2.7/2.4	2.6			0.5/0.4	0.5	2.6/2.4	2.6	52/53 A						
PPGBM	-0.3	-	0.2/0.3	0.3	2.3/2.3	2.3			0.4/0.1	0.3	1.9/1.9	1.9	51/52 A						
MPG	-0.3	-	0.3/-0.1	0.1	0.9/1.0	1.0			-0.1/-0.3	-0.2	0.8/0.8	0.8	54/55 A						

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 13		SBR (23.5% Styrene Content)		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc Oxide		3.00				PEBA - Pentaerythritol Ester Branched Acid	
		Sulfur		1.75				PPGBM - Polypropylene Glycol Butyl Monoether	
		Stearic Acid		1.00				MO - Mineral Oil	
		N-t-butyl-2-benzothiazyl sulfenamide		1.00		MPG - Modified Polyglycol			
						PPGD - Polypropylene Glycol Diol			
						AB - Alkyl Benzene			

Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness		
			values		mean	values		mean	2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean	values	mean		values	mean
R-22	9.9	10.0	9.8		41.1/39.5	40.3	7.6		-0.1/-1.9	-1.0	13.4/-18.6	-2.6			
R-32	2.0	1.6	2.0		7.0/6.6	6.8	0.7/0.1	0.4	-1.3/-0.7	-1.0	-1.0/-0.9	-1.0	49/50 A		
R-124	5.9	5.4	4.1		22.5/22.5	22.5	3.5/2.7	3.1	0.5		2.5/1.3	1.9			
R-134a	1.1		1.0		5.0/5.0	5.0	-0.4		-0.2/-0.8	-0.5	-0.4/-0.3	-0.4			
R-125	3.1	3.8	3.6		10.8/10.0	10.4	6.4		3.0/1.3	2.2	6.6/5.8	6.2			
R-143a	1.4	1.5	1.5		5.2/5.2	5.2	0.3		-1.1/0.1	-0.6	0.2/0.2	0.2			
R-152a	30.	3.1	2.8		11.1/10.6	10.9	0.4		-1.6/-1.2	-1.4	-1.6/-1.5	-1.6			
R-123	41.4	41.2	40.8		27.1/27.1	27.1	4.4		-0.9/-1.2	-1.1	-0.4/-0.9	-0.7			
R-142b	7.8	7.5	7.3		31.1/30.3	30.7	1.0		-1.0/-1.8	-1.4	-3.0/-2.2	-2.6			
R-134	1.9	2.0	1.4		7.3/7.5	7.4	0.9/0.8	0.9	-0.2/-0.1	-0.2	0.8/0.5	0.7	47/48 A		
AB	29.7	-	43.6/42.3	43.0	175/171	173			42.2/41.5	41.9	160/156	158			
MO	32.5	-	44.5/44.1	44.3	186/186	186					175/175	175			
PEMA	16.3	-	22.9/22.6	22.8	85.6/84.7	85.2			21.4/20.7	21.1	78.8/78.5	78.7			
PEBA	9.4	-	16.0/16.1	16.1	57.0/56.5	56.8					51.4/51.1	51.2			
PPGD	1.6	-	1.2/1.8	1.5	5.9/5.5	5.7					4.6/4.4	4.5			
PPGBM	5.9	-	10.0/9.2	9.6	29.4/29.5	29.5			8.2/7.9	8.1	21.4/21.7	21.6			
MPG	1.6	-	2.5/2.7	2.6	8.1/8.3	8.2			1.5/1.7	1.6	7.4/7.5	7.5	39/40 A		

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 14		SBR 1502 (23.5% Styrene content)			100.00			Lubricant Legend Information			Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.			1 Day Shore A/D Hardness		
		Zinc Oxide			3.00											
		Stearic Acid			1.00											
		Sulfur			1.75											
		N-t-butyl-2-benzothiazyl sulfenamide			1.00			PPGD - Polypropylene Glycol Diol			AB - Alkyl Benzene					
		N330 Carbon Black			50.00											
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		values	mean	values	mean
			values	mean	values	mean	values	mean	values	mean	values	mean				
R-22	7.6	7.1	7.1		26.9/27.1	27.0	4.7		-0.9/-1.2	-1.1	-2.9/-2.5	-2.7				
R-32	1.2	1.2	1.1		4.5/4.4	4.5	0.20/5	0.4	-0.7/-0.7	-0.7	-0.7/-0.7	-0.7				72/73 A
R-124	3.4	3.4	3.1		15.0/15.3	15.2	1.6/2.7	2.2	-0.7		1.7/2.3	2.0				
R-134a	9		0.6		3.3/3.7	3.5	0.2		-0.5/0.3	-0.1	0.1/0.4	0.3				
R-125	2.0	2.1	2.1		7.0/6.5	6.8	1.4		0.9/1.0	1.0	4.4/4.1	4.3				
R-143a	0.9	1.1	0.9		3.7/3.6	3.7	0.30/7	0.5	-0.2/0.1	-0.1	0.30/3	0.3				
R-152a	2.3	2.1	2.0		6.4/6.6	6.5	1.0		-1.0/-0.4	-0.7	-0.9/-0.6	-0.8				
R-123	24.3	24.2	24.9		138/138	138	5.7		0.8/-0.9	-0.1	1.9/1.5	1.7				
R-142b	6.0	6.0	5.9		20.1/20.0	20.1	2.4		0.2/0.3	0.3	-1.4/-0.7	-1.1				
R-134	1.2	1.3	1.1		4.6/4.8	4.7	-0.2/0.4	0.1	-0.5/-0.2	-0.4	0.6/0.5	0.6				70/71
AB	15.7	-	24.0/24.2	24.1	81.9/81.2	81.6			22.9/23.1	23.0	75.9/75.3	75.6				
MC	17.4	-	24.2/23.7	24.0	88.8/88.6	88.7					84.6/83.9	84.3				
PEMA	8.8	-	13.2/13.2	13.2	45.5/45.1	45.3			12.9/13.3	13.1	42.7/42.8	42.8				
PEBA	4.2	-	9.2/9.2	9.2	31.3/30.8	31.1					29.6/29.2	29.4				
PPGD	1.1	-	2.1/1.4	1.8	5.0/4.8	4.9					4.4/4.1	4.3				
PPGBM	3.3	-	5.5/5.4	5.5	18.8/19.0	18.9			5.3/5.1	5.2	15.0/15.3	15.2				
MPG	1.1	-	1.8/1.8	1.8	5.6/5.6	5.6			1.6/1.2	1.4	5.3/5.4	5.4				67/68 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 15		SBR (Medium Styrene) Content		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid											
		Zinc Oxide		3.00				PEBA - Pentaerythritol Ester Branched Acid											
		Stearic Acid		1.00				PPGBM - Polypropylene Glycol Butyl Monoether											
		Sulfur		1.75				MO - Mineral Oil											
		N-4-butyl-2-benzothiazyl sulfenamid*		1.00		MPG - Modified Polyglycol													
						PPGD - Polypropylene Glycol Diol													
						AB - Alkyl Benzene													
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness						
			values		mean		values		mean		2 hr. Diameter (%)			1 Day Diameter (%)		1 Day Weight (%)			
			values	mean	values	mean	values	mean	values	mean	values	mean		values	mean				
R-22	10.2	11.3	11.4		43.8/41.90	42.9				2.1/0.3	1.3	-1.4/-1.5	-1.5	63/64 A					
R-32	1.3	1.2	1.2		7.8/7.4	7.6	-1.0/-0.5	-0.8	-1.6/-1.3	-1.5	-0.3/-0.2	-0.3	-0.3	67/68 A					
R-124	4.4	4.2	3.7		24.0/23.1	23.6	3.0/0.6	1.8	-0.7/1.0	0.2	0.1/-0.1	0	0	66/67 A					
R-134a	1.9	1.6	1.7		7.5/7.4	7.5	2.1/1.8	2.0	1.6/1.4	1.5	1.3/1.4	1.4	1.4						
R-125	2.3	2.7	1.9		10.1/9.8	10.0	1.8/1.7	1.7	0.4/0.1	0.3	6.0/6.0	6.0	6.0	67/68 A					
R-143a	1.7	1.6	1.6		7.1/6.9	7.0			0.1/2.1	1.1	1.0/0.9	1.0	1.0	67/68 A					
R-152a	2.7	2.4	3.0		10.2/10.0	10.1	0.4/-0.4	0	0.4/0.6	0.5	-0.4/-0.3	-0.4	-0.4	66/67 A					
R-123	43.5	44.6	45.7		316/313	315	14.0/11.2	12.6	4.9/3.7	4.3	33.6/35.5	34.6	34.6	64/65 A					
R-142b	8.3	8.6	7.6		31.7/30.6	31.1			-0.7/-0.9	-0.8	-0.4/-0.3	-0.4	-0.4	67/68 A					
R-134	1.2	1.3	1.2		8.5/8.1	8.3	0.5/1.2	0.9	-0.3/-1.0	-0.7	0.5/0.5	0.5	0.5	68/69 A					
AB	34.0	-	43.5/61.3	52.4	179/292	236			40.8/53.1	47.0	176/287	232	232	19/20 A					
MO	32.7	-	42.1/41.1	41.6	179/176	178			39.2/36.2	37.7	173/170	172	172						
PEMA	14.0	-	20.3/20.2	20.3	78.0/78.0	78.0			19.8/19.0	19.4	76.1/76.0	76.1	76.1	31/32 A					
PEBA	11.0	-	16.9/47.0	32.0	64.5/62.2	63.4			15.3/15.5	15.4	63.5/61.3	62.4	62.4	35/36 A					
PPGD	2.6	-	3.4/3.2	3.3	12.7/12.1	12.4			2.2/1.9	2.0	11.0/10.3	10.7	10.7	57/68 A					
PPGBM	5.2	-	8.5/7.7	8.1	28.5/28.1	28.3			7.0/7.3	7.2	26.1/26.1	26.1	26.1	51/52 A					
MPG	2.2	-	2.8/2.6	2.7	10.0/10.2	10.1			3.7/2.8	3.3	9.3/9.5	9.4	9.4	60/61 A					

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 17	Very High ACN Nitrile			100.00		Lubricant Legend Information	PEMA - Pentaerythritol Ester Mixed Acid											
	Zinc Oxide			3.00			PEBA - Pentaerythritol Ester Branched Acid											
	Stearic Acid			1.00			PPGBM - Polypropylene Glycol Butyl Monoether											
	Magnesium Carbonate Coated Sulfur			1.50			MO - Mineral Oil											
	N-t-butyl-2-benzothiazyl sulfenamide			0.70			MPG - Modified Polyglycol											
							PPGD - Polypropylene Glycol Diol										AB - Alkyl Benzene	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness					
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)							
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean				
R-22*	47.8	47.5	47.6		255/238	247	4.3/3.7	4.0	1.1/0.6	0.9	3.0/2.8	2.9						
R-32*	8.5	8.5	8.4		30.0/29.3	29.7	28.3/25.4	26.9	6.2/6.6	6.4	0.1/0.4	0.3	35/36 A					
R-124	39.6	39.7	40.2		257/241	249	12.9/11.6	12.3	6.2/5.5	5.9	29.1/27.1	28.1						
R-134a	2.0	3.0	4.9		20.7/20.4	20.6	4.2/4.4	4.3	3.9/3.8	3.9	15.2/15.2	15.2						
R-125*	0.8	0	1.7		7.4/9.7	8.6	6.5/10.2	8.4	7.6/10.7	9.2	6.0/7.6	6.8						
R-143a	0.2	0.4	0.9		3.2/3.4	3.3	2.7/1.6	2.2	1.6/1.3	1.5	2.7/2.9	2.8						
R-152a	7.8	7.9	7.9		24.9/24.3	24.6	6.0/5.3	5.7	2.9/3.1	3.0	9.6/9.9	9.8	55/56 A					
R-123	78.5	79.2	77.5		669/664	666	20.3/20.4	20.4	7.6/7.7	7.7	38.0/37.5	37.8	52/53 A					
R-142b	3.8	5.6	7.3		28.8/28.7	28.8	6.6/6.8	6.7	4.6/5.1	4.9	18.4/18.7	18.6						
R-134	21.7	22.0	21.4		111/109	110	10.8/10.3	10.6	4.8/4.5	4.7	22.1/21.7	21.9	47/48 A					
AB	0.2	-	0.2/-0.1	0.1	0.2/0.2	0.2			0.0/1	0.1	0.3/0.4	0.4	55/56 A					
MO	-0.2	-	0.3/0.3	0.3	1.5/1.6	1.6			0.1/0.6	0.4	1.4/1.4	1.4	54/55 A					
PEMA	0.8	-	1.6/1.9	1.7	5.0/5.3	5.2			1.6/1.8	1.7	5.0/5.5	5.3	55/56 A					
PEBA	0.4	-	0.9/1.1	1.0	3.1/3.6	3.4			1.4/1.3	1.4	2.8/3.3	3.1	56/57 A					
PPGD	1.0	-	2.0/2.0	2.0	5.6/5.7	5.7			1.9/1.8	1.8	5.8/5.8	5.8	52/53 A					
PPGBM	0.4	-	0.3/0.1	0.2	0.3/0.5	0.4			0.1/0	0.1	0.5/0.6	0.6	55/56 A					
MPG	0.4	-	-0.4/-0.3	-0.3	-0.2/-0.1	-0.1			-0.5/-0.2	-0.4	-0.1/-0.1	-0.1	58/59 A					

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 18		High ACN Nitrile		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
		Zinc Oxide		3.00				PEBA - Pentaerythritol Ester Branched Acid					
		Stearic Acid		1.00				PPGBM - Polypropylene Glycol Butyl Monoether					
		Magnesium Carbonate Coated Sulfur		1.50				MO - Mineral Oil					
		N-t-butyl-2-benzothiazyl sulfenamide		0.70				MPGD - Polypropylene Glycol Diol					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			values	mean	values	mean	2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)	
							values	mean	values	mean		values	mean
R-22*	51.4	50.8	51.4		275/260	268	4.5/4.4	4.5	0.5/0.7	0.6	3.3/3.6	3.5	
R-32*	8.3	8.3	8.3		30.0/29.3	29.7	6.6/6.8	6.7	2.5/1.8	2.2	-0.3/-0.4	-0.4	38/39 A
R-124	45.4	45.3	45.9		289/274	282	11.7/11.1	11.4	5.4/4.9	5.2	25.3/24.5	24.9	
R-134a	2.5	4.1	5.1		22.0/21.9	21.9	4.2/4.4	4.3	3.6/3.3	3.5	14.6/14.5	14.6	
R-125*	1.5	2.0	3.9		16.2/15.9	16.1	3.6/5.6	4.6	5.4/8.2	6.8	12.7/12.3	12.5	
R-143a	0.6	1.0	2.0		5.8/5.8	5.8	1.4/1.5	1.5	1.3/1.2	1.3	4.7/4.8	4.8	
R-152a	8.9	8.7	8.8		27.5/27.3	27.4	6.2/6.0	6.1	2.4/2.5	2.5	7.5/7.6	7.6	53/54 A
R-123	82.9	83.4	83.7		720/713	716	19.3/20.1	19.7	7.0/7.1	7.1	35.1/35.8	35.5	53/54 A
R-142b	6.5	8.6	8.7		34.2/34.4	34.3	7.4/7.7	7.6	4.1/4.4	4.3	17.1/17.1	17.1	
R-134	20.4	20.6	20.6		104/103	103	10.7/10.0	10.4	4.4/4.2	4.3	20.2/20.1	20.2	53/54 A
AB	0.4	-	0.2/0.2	0.2	0.7/0.9	0.8			0.3/0	0.2	0.8/1.0	0.9	51/52 A
MO	0.4	-	0.7/0.9	0.8	2.5/2.7	2.6			0.6/1.0	0.8	2.4/2.6	2.5	51/52 A
PEMA	1.6	-	3.8/3.2	3.5	10.9/10.4	10.7			3.8/3.3	3.6	10.8/10.5	10.7	49/50 A
PEBA	1.0	-	2.1/2.6	2.4	6.3/7.2	6.7			2.2/2.6	2.4	6.0/7.1	6.6	52/53 A
PPGD	1.5	-	3.2/2.7	2.9	9.7/8.3	9.0			2.9/2.4	2.7	10.1/8.4	9.3	48/49 A
PPGBM	0.3	-	0.4/0.2	0.3	1.0/1.1	1.1			0.4/0.3	0.3	1.2/1.2	1.2	52/53 A
MPG	0.3	-	-0.2/-0.3	-0.2	0.1/0.1	0.1			0.5/-0.4	0.1	0.0/1	0.1	54/55 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 19	Medium ACN Nitrile		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid									
	Zinc Oxide		3.00				PEBA - Pentaerythritol Ester Branched Acid									
	Stearic Acid		1.00				PPGBM - Polypropylene Glycol Butyl Monoether									
	Magnesium Carbonate Coated Sulfur		1.50				MO - Mineral Oil									
	N-t-butyl-2-benzothiazyl sulfenamide		0.70				MPG - Modified Polyglycol									
							PPGD - Polypropylene Glycol Diol									
							AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness			
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)					
			values	mean	values	mean	values	mean	values	mean	values	mean				
R-22*	49.8	49.8	50.4		262/244	253	2.6/2.1	2.4	-0.8/-0.9	-0.9	-1.6/-1.9	-1.8				
R-32*	7.7	7.7	7.8		26.8/26.0	26.4	37.7/39.2	38.5	5.9/6.6	6.3	-0.5/-0.5	-0.5	41/42 A			
R-124	46.2	46.1	45.8		311/284	298	7.8/3.7	5.8	3.0/0.9	2.0	13.8/4.9	9.4				
R-134a*	5.1	5.8	5.7		25.0/23.7	24.4	4.1/3.8	4.0	2.2/2.4	2.3	10.1/11.9	11.0				
R-125*	3.5	5.1	6.2		23.5/23.1	23.3	10.7/9.5	10.1	13.6/11.5	12.6	11.9/11.9	11.9				
R-143a	1.4	2.3	2.7		9.0/9.0	9.0	1.9/1.9	1.9	1.4/1.3	1.3	4.8/4.7	4.8				
R-152a	8.8	8.9	8.7		28.4/27.8	28.1	4.5/5.5	5.0	-0.4/1.3	0.5	3.4/3.7	3.6	51/52 A			
R-123	94.2	94.1	94.4		875/883	879	14.8/16.1	15.5	3.9/5.0	4.5	22.9/22.5	22.7	50/51 A			
R-142b	11.6	11.6	11.6		47.2/46.8	47.0	7.8/8.3	8.1	2.4/2.5	2.5	10.0/10.5	10.3				
R-134	14.9	14.5	14.6		75.5/74.8	75.2	6.2/6.7	6.5	1.2/2.1	1.7	11.6/11.8	11.7	48/49 A			
AB	0.9	-	1.7/1.9	1.8	5.1/4.9	5.0			1.6/1.5	1.6	4.9/4.9	4.9	45/46 A			
MC	1.3	-	2.6/2.7	2.7	8.3/8.7	8.5			1.7/1.9	1.8	8.1/8.3	8.2	44/45 A			
PEMA	6.4	-	9.9/9.7	9.8	33.2/33.2	33.2			10.2/9.9	10.1	32.7/32.9	32.8	38/39 A			
PEBA	3.8	-	7.7/7.7	7.7	25.4/25.6	25.5			7.5/7.7	7.6	24.9/25.2	25.1	39/40 A			
PPGD	5.8	-	8.0/7.9	7.9	25.6/25.4	25.5			7.3/7.4	7.4	25.4/25.3	25.4	37/38 A			
PPGBM	1.3	-	2.0/1.8	1.9	5.9/5.8	5.9			1.5/1.3	1.4	5.9/5.9	5.9	46/47 A			
MPG	0.5	-	0.7/0.7	0.7	2.6/2.9	2.8			0.2/0.4	0.3	2.7/2.8	2.8	47/48 A			

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 20		Low ACN Nitrile		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid											
		Zinc Oxide		3.00				PEBA - Pentaerythritol Ester Branched Acid											
		Stearic Acid		1.00				PPGBM - Polypropylene Glycol Butyl Monoether											
		Magnesium Carbonate Coated Sulfur		1.50				MO - Mineral Oil											
		N-t-butyl-2-benzothiazyl sulfenamide		0.70		MPG - Modified Polyglycol													
						PPGD - Polypropylene Glycol Diol													
						AB - Alkyl Benzene													
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness						
			values	mean	values	mean	2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)								
							values	mean	values	mean	values	mean							
R-22*	35.6	35.1	35.4		180/174	177	0.2/0	0.1	-1.8/-2.2	-2.0	-3.4/-3.5	-3.5							
R-32*	6.2	6.1	6.1		21.6/21.0	21.3	8.2/9.4	8.8	0.7/0.3	0.5	-0.2/-0.1	-0.2	49/50 A						
R-124	31.0	31.2	29.9		199/187	193	4.9/5.2	5.1	0.6/0.6	0.6	5.6/6.5	6.1							
R-134a	4.5	4.3	4.3		19.2/18.8	19.0	1.4/5.3	3.4	-0.6/3.1	1.3	3.6/3.4	3.5							
R-125*	5.0	5.3	5.2		21.9/21.4	21.7	7.4/10.1	8.8	3.9/3.4	3.7	6.5/5.7	6.1							
R-143a	2.8	3.2	3.4		11.9/11.1	11.5	1.1/1.8	1.5	0.2/0.7	0.5	3.8/3.1	3.5							
R-152a	7.4	8.1	7.4		27.3/27.0	27.2	3.2/3.3	3.3	-0.4/-0.9	-0.7	1.2/1.0	1.1	47/48 A						
R-123	73.9	71.3	73.2		739/755	747	12.1/11.7	11.9	1.0/1.5	1.3	10.5/11.4	10.9	52/53 A						
R-142b	13.8	14.1	14.0		59.9/58.9	59.4	7.1/7.5	7.3	0.6/0.7	0.7	5.0/4.9	5.0							
R-134	9.4	9.1	8.9		45.4/44.1	44.8	4.1/3.8	4.0	-0.5/1.0	0.3	5.6/5.6	5.6	50/51 A						
AB	4.8	-	6.9/7.1	7.0	21.0/22.0	21.5			6.1/6.1	6.1	20.5/20.4	20.5	41/42 A						
MO	4.2	-	7.0/8.4	7.7	26.9/26.9	26.9			7.5/7.3	7.4	26.3/26.3	26.3	42/43 A						
PEMA	21.5		23.9/24.7	24.1	98.4/98.9	98.6			22.0/23.5	22.8	96.6/97.4	97.0	31/32 A						
PEBA	13.1		18.9/19.2	19.0	72.0/72.1	72.1			17.4/18.2	17.8	70.6/70.7	70.7	33/34 A						
PPGD	11.0	-	11.1/11.4	11.3	39.9/39.9	39.9			9.7/9.4	9.6	37.7/38.0	37.9	37/38 A						
PPGBM	24.0	-	7.2/7.6	7.4	23.7/23.8	23.7			6.9/7.3	7.1	23.5/23.4	23.5	38/39 A						
MPG	2.3	-	4.3/3.9	4.1	13.9/14.3	14.1			4.2/3.4	3.8	13.8/14.1	14.0	42/43 A						

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 21		Low ACN Nitrile		100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid			
		Zinc Oxide		3.00						PEBA - Pentaerythritol Ester Branched Acid			
		Stearic Acid		1.00						PPGBM - Polypropylene Glycol Butyl Monoether			
		MgCo3 Coated Sulfur		1.50						MO - Mineral Oil			
		N-t-butyl-2-benzothiazyl sulfenamide		0.70		MPG - Modified Polyglycol							
		N330 Carbon Black		35.00		PPGD - Polypropylene Glycol Diol							
						AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			values mean		values mean		values mean		values mean			values mean	
R-22	25.8	23.0	22.0		121/115	118			-2.0/-1.3	-1.7	-0.7/-0.9	-0.8	65/66 A
R-32	4.3	4.5	4.2		15.9/15.7	15.8	1.3/1.0	1.2	-0.2/0.1	-0.1	0.2/0.2	0.2	67/68 A
R-124	20.3	23.5	23.5		110/106	108	8.1/5.7	6.9	1.3/1.0	1.2	9.1/7.1	8.1	65/66 A
R-134a	3.3	3.4	3.5		15.5/15.4	15.5	1.7/1.9	1.8	0.6/0.9	0.8	2.3/2.3	2.3	
R-125	3.0	3.8	3.4		15.8/15.6	15.7	2.5/2.6	2.5	1.5/1.2	1.4	8.0/8.1	8.1	68/69 A
R-143a	1.6	1.7	1.4		8.0/7.9	8.0			0.2/0.3	0.3	2.8/2.5	2.7	67/68 A
R-152a	5.6	5.3	5.2		19.6/19.0	19.3	1.7/2.6	2.2	-0.6/-0.6	-0.6	1.4/1.5	1.5	65/66 A
R-123	42.5	41.9	40.9		352/362	357	10.0/10.8	10.4	0.9/0.4	0.7	-17.4/-19.5	-18.4	68/69 A
R-142b	8.5	9.0	9.1		41.3/40.5	40.9			0.5/1.1	0.8	4.0/4.6	4.3	67/68 A
R-134	7.3	7.3	7.0		33.9/33.3	33.6	3.9/3.3	3.6	1.5/0.4	1.0	6.7/6.1	6.4	67/68 A
AB	3.4	-	4.8/4.4	4.6	13.7/14.1	13.9			4.2/4.4	4.3	14.3/14.4	14.4	60/61 A
MO	2.9	-	5.3/5.0	5.2	18.4/18.3	18.4			4.2/4.4	4.3	18.1/17.9	18.0	63/64 A
PEMA	7.3	-	15.0/14.0	14.5	57.0/57.0	57.0			14.5/12.8	13.7	57.0/56.8	56.9	53/54 A
PEBA	5.8	-	12.2/11.6	11.9	46.5/46.4	46.5			12.5/11.2	11.9	46.6/46.8	46.7	53/54 A
PPGD	4.7	-	6.1/7.1	6.6	26.6/27.1	26.9			5.6/5.0	5.3	26.3/26.5	26.4	60/61 A
PPGBM	2.1	-	4.5/4.4	4.5	16.0/15.6	15.8			4.2/3.8	4.0	15.4/15.6	15.5	63/64 A
MPG	1.4	-	2.5/2.9	2.7	9.7/9.8	9.8			1.7/1.7	1.7	9.6/9.8	9.7	64/65 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 22	Very High ACN Nitrile			100.00	Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
	Zinc Oxide			3.00											PEBA - Pentaerythritol Ester Branched Acid	
	Stearic Acid			1.00											PPGBM - Polypropylene Glycol Butyl Monoether	
	MgCo 3 Coated Sulfur			1.50											MO - Mineral Oil	
	N-t-butyl-2-benzothiazyl sulfenamide			0.70											MPG - Modified Polyglycol	
N330 Carbon Black			35.00	PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene										
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness			
			values		mean	values		mean	2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean	values	mean				
R-22	31.5	31.6	31.7		157/165	161			-1.2/3.8	1.3	3.0/11.4	7.2	63/64 A			
R-32	6.3	6.4	6.2		22.4/22.2	22.3	3.0/3.3	3.2	0.6/0.8	0.7	4.3/4.5	4.4	66/67 A			
R-124	27.9	29.2	28.7		136/138	137	11.0/11.1	11.1	3.8/4.2	4.0	21.7/21.7	21.7	62/63 A			
R-134a	1.2	2.5	4.2		15.7/15.8	15.8	3.3/3.0	3.2	3.1/2.5	2.8	10.0/9.9	10.0				
R-125	0.4	0.8	1.6		6.8/7.0	6.9	1.5/1.8	1.7	1.7/1.4	1.6	6.2/6.3	6.2	68/69 A			
R-143a	0.4	0.3	0.8		2.8/2.3	2.6			0.2/0.6	0.4	2.2/2.0	2.1	71/72 A			
R-152a	5.6	5.9	5.6		18.3/18.4	18.4	3.4/2.4	2.9	1.6/1.1	1.4	7.2/7.2	7.2	63/64 A			
R-123	49.3	49.4	49.7		388/391	390	17.6/20.1	18.8	5.6/5.6	5.6	30.5/32.3	31.4	61/62 A			
R-142b	1.9	4.2	5.5		21.1/21.3	21.2	4.6/4.8	4.7	3.2/3.0	3.1	13.7/13.7	13.7				
R-134	16.0	15.6	16.5		80.4/78.6	79.5	7.4/8.6	8.0	2.9/3.4	3.2	18.1/18.1	18.1	62/63 A			
AB	-0.1	-	0.1/0.1	0.1	0.3/0.3	0.3			-0.2/-0.3	-0.3	0.8/0.8	0.8	74/75 A			
MO	0.1	-	0.4/0.5	0.5	1.1/1.2	1.2			-0.1/0.3	0.1	0.8/0.9	0.9	75/76 A			
PEMA	0.1	-	0.8/0.8	0.8	3.0/2.5	2.8			1.0/0.3	0.7	2.6/2.5	2.6	73/74 A			
PEBA	0.4	-	7.5/-1.3	3.1	2.4/2.6	2.5			-0.3/-0.1	-0.2	3.3/3.2	3.2	74/75 A			
PPGD	1.0	-	2.2/2.0	2.1	6.4/6.6	6.5			1.9/1.4	1.7	6.5/6.6	6.6	69/70 A			
PPGBM	0.2	-	0.2/0.1	0.1	0.3/0.3	0.3			-0.6/0.5	-0.1	0.2/0.3	0.3	75/76 A			
MPG	-0.2	-	-0.1/-0.1	-0.1	-0.4/-0.2	-0.3			-0.7/-0.6	-0.7	-0.4/-0.3	-0.4	75/76 A			

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 23		38% ACN Hydrogenated Nitrile			100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid		
		Zinc Oxide			5.00												PEBA - Pentaerythritol Ester Branched Acid		
		Stearic Acid			1.00												PPGBM - Polypropylene Glycol Butyl Monoether		
		Magnesium oxide			10.00												MO - Mineral Oil		
		2,5-dimethyl-2,5-di(t-butyl-peroxy) hexane			10.00		MPG - Modified Polyglycol			PPGD - Polypropylene Glycol Diol			AB - Alkyl Benzene						
		Ricon 153-D			6.50														
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness						
			values	mean	values	mean	2 hr. Diameter (%)	values	mean	1 Day Diameter (%)	values	mean							
R-22	33.7	34.1	34.2		171/159	165	3.3/4.7	4.0		0/-0.7	-0.3	4.7/4.9	4.8	67/68 A					
R-32																			
R-124	31.8	32.2	31.8		189/181	185	8.4/8.0	8.2		2.1/2.0	2.1	17.6/15.9	16.8	69/70 A					
R-134a	4.2	4.9	5.0		23.3/23.3	23.3	2.8/3.4	3.1		1.0/1.0	1.0	9.7/8.5	9.1	68/69 A					
R-125	4.4	7.6	7.1		30.0/29.2	29.6	5.5/4.8	5.2		3.0/2.2	2.6	15.0/15.2	15.1	68/69 A					
R-143a	0.7	0.8	1.3		3.6/3.5	3.6	1.2/-0.1	0.6		-0.2/-0.7	-0.5	0.6/0.6	0.6	70/71 A					
R-152a	7.7	6.8	6.8		22.8/23.1	23.0	4.1/3.4	3.8		0.6/0.1	0.4	3.0/2.9	3.0	69/70 A					
R-123	45.8	44.0	45.2		314/317	316	12.9/12.2	12.5		3.8/3.3	3.6	24.3/23.6	23.9	68/69 A					
R-142b	9.7	10.6	10.8		44.1/44.0	44.1	5.0/5.4	5.2		1.5/1.2	1.3	9.3/9.4	9.4	69/70 A					
R-134	14.9	13.9	14.3		69.7/68.8	69.3	7.8/7.0	7.4		2.4/2.2	2.3	13.2/13.2	13.2	69/70 A					
AB	0.3	-	1.6/1.8	1.7	5.5/6.0	5.8				0.7/0.6	0.7	5.1/5.2	5.2	64/65 A					
MO	1.2	-	2.8/2.6	2.7	10.6/9.6	10.1				3.1/1.5	2.3	8.7/8.5	8.6	66/67 A					
PEMA	0.4	-	4.2/5.3	4.8	17.6/17.9	17.8				3.8/5.1	4.5	17.7/17.8	17.8	66/67 A					
PEBA	1.3	-	5.6/3.8	4.7	15.3/13.1	14.2				5.2/3.3	4.2	15.3/13.2	14.2	63/64 A					
PPGD	1.1	-	2.4/2.9	2.6	8.2/9.0	8.6				1.5/2.6	2.1	8.1/8.8	8.4	65/66 A					
PPGBM	-0.1	-	0.4/0.3	0.4	3.4/3.1	3.3				0.5/0.1	0.3	2.3/2.3	2.3	65/66 A					
MPG	0	-	-0.1/0.1	0	2.1/1.2	1.7				-0.4/-0.3	-0.4	0.9/0.9	0.9	65/66 A					

• Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 24		38% ACN Hydrogenated Nitrile			100.00		Lubricant Legend Information						PEMA - Pentaerythritol Ester Mixed Acid		
		Zinc Oxide			5.00								PEBA - Pentaerythritol Ester Branched Acid		
		Stearic Acid			1.00								PPGBM - Polypropylene Glycol Butyl Monoether		
		MgCo 3 Coated Sulfur			1.50								MO - Mineral Oil		
		TMTM			0.30		MPG - Modified Polyglycol								
		MBTS			1.50		PPGD - Polypropylene Glycol Diol								
		N774 Carbon Black			40.00		AB - Alkyl Benzene								
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness		
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)				
			values	mean	values	mean	values	mean	values	mean	values	mean			
R-22*	68.4	66.4	66.0		320/208	264			113/72.3	92.7	-11.9/-10.2	-11.1			
R-32*	6.3	6.2	6.0		20.4/20.5	20.5	99.6/115	107	20.1/28.1	24.1	-0.2/0.2	0	37/38 A		
R-124*	69.9	68.9	68.0		338/328	333	240/96.0	168	209/63.1	136	2.3/-8.9	-3.3			
R-134a	4.7	5.3	5.5		21.1/21.2	21.2	2.2/2.6	2.4	0.9/0.7	0.8	4.3/4.4	4.4			
R-125*	5.2	6.7	6.7		26.0/26.1	26.1	63.1/56.5	59.8	66.8/63.8	65.3	11.2/11.1	11.1	35/36 A		
R-143a	1.2	2.1	2.4		8.0/15.2	11.6			1.0/0.9	1.0	4.6/4.3	4.5	59/60 A		
R-152a	7.1	6.9	7.0		22.0/22.0	22.0	3.8/3.6	3.7	0.4/0.7	0.6	3.3/3.4	3.4	59/60 A		
R-123*	122	121	115		1294/1300	1297	16.2/14.6	15.4	5.8/5.5	5.7	-8.2/-8.3	-8.2	51/52 A		
R-142b	10.8	10.6	11.0		42.1/40.8	41.5			1.6/0.9	1.3	7.7/8.2	8.0	56/57 A		
R-134	15.3	15.5	15.4		70.8/69.9	70.4	5.6/5.1	5.4	1.3/1.3	1.3	10.4/10.8	10.6	55/56		
AB	1.0	-	1.9/1.9	1.9	4.9/4.9	4.9			1.4/1.9	1.7	5.5/5.4	5.5	59/60 A		
MO	1.3	-	3.3/3.0	3.2	8.8/8.7	8.8			2.8/2.3	2.6	8.3/8.3	8.3	56/57 A		
PEMA	3.4	-	6.9/6.8	6.9	16.0/28.1	22.1			6.4/6.7	6.6	15.6/27.7	21.7	48/49 A		
PEBA	2.0	-	5.7/7.6	6.7	18.4/18.4	18.4			4.9/4.6	4.8	19.1/18.9	18.9	52/53 A		
PPGD	-0.6	-	0.1/2.7	1.4	8.6/8.5	8.6			1.3/1.6	1.5	8.3/8.5	8.4	57/58 A		
PPGBM	-1.4	-	-1.3/0.6	-0.4	1.6/1.7	1.7			-0.3/-0.3	-0.3	1.4/1.4	1.4	63/64 A		
MPG	-1.0	-	-0.6/-0.1	-0.4	0.2/0.4	0.3			-1.0/-0.8	-0.9	0.0/0.1	0.1	65/66		

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 25		45% ACN Hydrogenated Nitrile			100.00		Lubricant Legend Information						PEMA - Pentaerythritol Ester Mixed Acid		
		Zinc Oxide			5.00								PEBA - Pentaerythritol Ester Branched Acid		
		Stearic Acid			1.00								PPGBM - Polypropylene Glycol Butyl Monoether		
		2,5-dimethyl-2,5-di(t-butyl-peroxy) hexane			10.00								MO - Mineral Oil		
		Ricon 153-D			6.50								MPG - Modified Polyglycol		
							PPGD - Polypropylene Glycol Diol						AB - Alkyl Benzene		
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness		
			values	mean	values	mean	2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)				
							values	mean	values	mean	values	mean			
R-22	41.9	41.9	42.0		215/203	209	3.6/4.9	4.3	0/0.6	0.3	6.0/6.0	6.0	63/64 A		
R-32															
R-124	39.5	39.3	39.1		260/246	253	9.1/9.7	9.4	2.3/2.4	2.4	20.6/20.6	20.6	62/63 A		
R-134a	4.3	5.4	5.2		25.3/25.8	25.6	2.9/3.0	3.0	1.4/1.6	1.5	11.1/10.4	10.8	64/65 A		
R-125	4.0	6.2	6.2		29.0/30.0	29.5	4.3/3.7	4.0	2.4/2.6	2.5	16.8/16.2	16.5	61/62 A		
R-143a	1.3	1.6	2.1		7.9/7.7	7.8	1.2/1.6	1.4	0.6/0.2	0.4	4.8/4.9	4.9	61/62 A		
R-152a	7.8	8.0	7.8		26.6/25.6	26.1	2.6/3.4	3.0	-0.1/0.8	0.4	4.3/4.6	4.5	64/65 A		
R-123	56.1	56.9	57.2		442/449	446	13.9/13.7	13.8	3.6/3.9	3.7	30.5/29.5	30.0	62/63 A		
R-142b	9.9	10.2	10.1		42.9/42.4	42.6	5.1/5.2	5.2	1.2/1.9	1.5	12.4/12.4	12.4	62/63 A		
R-134	20.8	19.8	20.0		105/103	104	8.8/8.9	8.9	2.1/2.9	2.5	16.5/18.0	17.2	61/62 A		
AB	0.4	-	0.9/0.3	0.6	3.5/2.5	3.0			0.2/-0.3	-0.1	2.8/2.2	2.5	60/61 A		
MO	0.4	-	1.6/1.9	1.8	7.8/7.5	7.7			1.5/1.6	1.6	6.5/6.2	6.4	59/60 A		
PEMA	1.4	-	4.5/3.4	4.0	12.8/12.3	12.6			4.1/3.7	3.9	12.8/12.1	12.5	61/62 A		
PEBA	1.0	-	2.6/3.3	3.0	9.5/11.2	10.4			2.3/3.2	2.8	9.5/11.3	10.4	57/58 A		
PPGD	1.5	-	2.6/2.2	2.4	7.0/7.3	7.2			1.4/1.3	1.4	7.1/7.2	7.2	60/61 A		
PPGBM	-1.5	-	-0.9/0.4	-0.3	2.0/2.8	2.4			-0.3/0.5	0.1	1.0/0.9	1.0	61/62 A		
MPG	-0.3	-	-0.6/-0.2	-0.4	0.6/0.4	0.5			-1.0/-0.5	-0.8	-0.1/-0.3	-0.2	59/60 A		

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 26		45% ACN Hydrogenated Nitrile			100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid		
		Zinc Oxide			5.00												PEBA - Pentaerythritol Ester Branched Acid		
		Stearic Acid			1.00												PPGBM - Polypropylene Glycol Butyl Monoether		
		2,5-dimethyl-2,5-di(t-butyl-peroxy) hexane			10.00												MO - Mineral Oil		
		Ricon 153-D			6.50		MPG - Modified Polyglycol			PPGD - Polypropylene Glycol Diol			AB - Alkyl Benzene						
		N774 Carbon Black			40.00														
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness						
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)								
			values	mean	values	mean	values	mean	values	mean	values	mean							
R-22	24.3	25.3	25.8		130/123	127	1.7/2.1	1.9	-0.1/-0.1	-0.1	2.3/2.2	2.3	79/80 A						
R-32																			
R-124	23.2	23.6	23.7		145/129	137	5.9/6.2	6.1	1.5/1.4	1.5	12.4/11.7	12.1	80/81 A						
R-134a	3.1	3.2	3.1		16.4/16.1	16.3	1.6/1.7	1.7	6.3/0	3.7	4.3/4.7	4.5	80/81 A						
R-125	3.6	4.6	4.8		22.7/23.2	23.0	3.5/3.7	3.6	2.1/2.3	2.2	11.3/11.2	11.3	79/80 A						
R-143a	0.6	0.6	0.6		3.4/3.5	3.5	0.3/0.8	0.6	0.1/0.6	0.3	1.7/1.3	0.5	81/82 A						
R-152a	6.1	4.8	5.3		16.3/16.3	16.3	1.7/1.8	1.8	-0.1/-0.8	-0.4	0.7/0.9	0.8	81/82 A						
R-123	32.4	31.7	35.2		211/216	213	7.6/7.9	7.8	2.3/2.9	2.6	18.3/19.3	18.8	80/81 A						
R-142b	5.6	6.7	6.6		27.5/27.4	27.4	3.4/2.8	3.1	0.8/1.0	0.9	5.7/6.0	5.9	80/81 A						
R-134	13.1	13.5	13.4		67.4/66.9	67.2	4.2/5.0	4.6	1.1/1.9	1.5	7.9/8.5	8.2	81/82 A						
AB	0.4	-	0.3/0.5	0.4	1.2/0.9	1.0			0.7/-0.2	0.3	0.9/0.7	0.8	79/80 A						
MO	0.1	-	1.0/0.5	0.8	3.8/3.1	3.5			0.9/0.3	0.6	3.9/3.2	3.6	80/81 A						
PEMA	0.1	-	2.2/2.7	2.5	8.2/9.2	8.7			2.3/3.0	2.7	8.0/9.1	8.6	78/79 A						
PEBA	0.5	-	2.8/2.1	2.5	7.3/7.0	7.2			2.5/2.4	2.5	7.5/7.1	7.3	78/79 A						
PPGD	0.5	-	1.0/1.1	1.1	4.2/4.2	4.2			1.4/1.0	1.2	4.3/4.3	4.3	78/79 A						
PPGBM	-0.6	-	-1.0/-0.4	-0.7	-0.7/-0.5	-0.6			-0.1/0.2	0.1	-0.7/-0.6	-0.7	80/81 A						
MPG	-0.4	-	-1.1/-0.2	-0.7	-1.7/-1.9	-1.8			-0.7/-0.3	-0.5	-1.7/-1.9	-1.8	82/83 A						

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 27		Fluorinated rubber		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Magnesium Oxide		15.00												PEBA - Pentaerythritol Ester Branched Acid	
		N,N'-dicinnamylidene-1,6-hexanediamine		3.00												PPGBM - Polypropylene Glycol Butyl Monoether	
																MO - Mineral Oil	
										MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene			
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			Change (%)		Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
R-22*	34.2	34.2	33.2		84.4/81.5	83.0	3.4/3.5	3.5	0.6/0.2	0.4	2.5/2.2	2.3			58/59 A		
R-32																	
R-124	27.9	29.6	28.9		91.0/88.0	89.5	7.5/6.9	7.2	2.8/1.9	2.4	9.5/10.0	9.8			57/58		
R-134a	25.8	26.1	25.6		68.2/67.3	67.8	6.9/6.0	6.5	2.9/1.9	2.4	7.1/6.3	6.7			57/58 A		
R-125	11.0	11.8	11.7		31.5/31.2	31.4	5.8/5.7	5.8	3.0/2.4	2.7	8.5/9.0	8.8			54/55 A		
R-143a*	17.1	14.3	13.6		28.6/28.0	28.3	5.2/5.8	5.5	1.9/2.3	2.1	6.5/5.9	6.2			56/57 A		
R-152a	39.0	39.4	39.1		63.8/79.3	81.6	6.2/4.9	5.6	1.8/1.8	1.8	2.4/1.7	2.1			59/60 A		
R-123	34.8	31.8	31.6		105/103	104	11.0/12.7	11.9	4.3/3.7	4.0	13.1/14.2	13.7			56/57 A		
R-142b	32.6	32.6	31.8		82.4/77.9	80.1	6.9/6.0	6.4	2.7/2.2	2.4	7.4/6.7	7.0			52/53 A		
R-134	36.6	37.9	37.8		122/114	118	6.7/4.7	5.7	2.8/1.4	2.1	5.1/4.4	4.7			61/62 A		
AB	0.7	-	0.1/0.1	0.1	0.4/0.5	0.5			0.1/-0.7	-0.3	0.2/0.2	0.2			63/64 A		
MO	-1.1	-	-1.4/0.2	-0.6	0.6/0.5	0.6			-0.4/-0.9	-0.7	0.2/0.2	0.2			61/62 A		
PEMA	1.3	-	3.3/3.2	3.3	6.6/6.0	6.3			2.8/2.6	2.7	6.5/5.8	6.2			57/58 A		
PEBA	2.2	-	8.1/8.9	8.5	16.5/16.7	16.6			6.7/7.5	7.1	16.7/16.9	16.8			50/51 A		
PPGD	1.0	-	0.8/1.2	1.0	1.4/1.7	1.6			0.2/0.3	0.3	1.4/1.6	1.5			62/63 A		
PPGBM	-0.2	-	0.0/0.3	0.2	0.7/0.9	0.8			-0.4/0	-0.2	0.2/0.4	0.3			64/65 A		
MPG	0.1	-	0.1		0.7				-0.3		0.4				61/62 A		

* 1 indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 28	Fluorocastomer		100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid									
	Magnesium oxide		15.00						PEBA - Pentaerythritol Ester Branched Acid									
	N,N'-dicinnamylidene-1,6-hexanediamine		3.00						PPGBM - Polypropylene Glycol Butyl Monoether									
									MO - Mineral Oil									
									MPGD - Polypropylene Glycol Diol									
														AB - Alkyl Benzene				
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day							
			values	mean	values	mean	values	mean	1 Day Diameter (%)		1 Day Weight (%)							
									values	mean	values	mean						
R-22*	37.2	36.4	35.6		99.6/94.0	96.8	2.8/4.2	3.5	0.1/1.2	0.7	-0.3/-0.9	-0.6	57/58 A					
R-32																		
R-124	38.6	38.4	37.8		125/120	123	7.3/6.6	7.0	2.7/2.6	2.7	7.7/8.0	7.9	58/59 A					
R-134a	29.2	29.9	29.4		84.1/81.5	82.8	5.2/5.1	5.2	2.4/2.0	2.2	4.0/3.8	3.9	57/58 A					
R-125*	15.1	15.2	15.2		42.0/41.6	41.8	10.7/12.1	11.4	3.8/3.6	3.7	4.8/4.9	4.9	53/54 A					
R-143a*	16.9	16.6	17.1		26.5/26.2	26.4	7.6/6.6	7.1	3.1/4.5	3.8	3.6/2.7	3.2	53/54 A					
R-152a*	41.0	40.7	40.1		92.9/82.8	87.9	2.8/4.4	3.6	0.9/1.1	1.0	-1.0/-0.1	-0.5	61/62 A					
R-123	37.5	37.9	37.4		133/134	133	12.3/12.4	12.4	3.5/3.9	3.7	10.9/10.7	10.9	60/61 A					
R-142b	38.6	39.3	38.7		102/96.6	99.1	6.2/7.2	6.7	2.3/2.3	2.3	5.0/5.3	5.2	57/58 A					
R-134	38.2	38.5	37.7		119/112	115	5.4/4.9	5.2	1.6/1.6	1.6	3.4/2.1	2.7	59/60 A					
AB	0.5	-	0.3/0.1	0.2	0.5/0.3	0.4			-0.2/-0.5	-0.4	0.2/0.2	0.2	61/62 A					
MO	-0.5	-	0.2/0	0.1	0.5/0.4	0.5			-0.1/-0.9	-0.5	0.2/0.1	0.2	63/64 A					
PEMA	0.5	-	1.0/0.9	1.0	2.3/2.2	2.3			0.3/0.8	0.6	2.0/1.8	1.9	61/62 A					
PEBA	0.8	-	2.1/1.9	2.0	3.5/4.0	3.7			1.4/1.7	1.5	3.6/4.0	3.8	59/60 A					
PPGD	-0.5	-	1.3/0.6	1.0	1.1/1.2	1.2			0.7/0.2	0.5	1.0/1.0	1.0	62/63 A					
PPGBM	-0.1	-	0/-1.0	-0.5	1.0/1.1	1.1			-1.0/-0.8	-0.9	0.2/0.2	0.2	63/64 A					
MPG	-0.7	-	-0.6/0.9	0.2	0.7/0.6	0.7			-0.4/0.5	0.1	0.3/0.3	0.3	65/66 A					

Formula # 30		Fluoroelastomer		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid									
		Litharge (Sublimed)		3.00												PEBA - Pentaerythritol Ester Branched Acid									
		Triallyl Isocyanurate		3.00												PPGBM - Polypropylene Glycol Butyl Monoether									
		2,5-Dimethyl-2,5-bis (t-butyl-peroxy) hexane		3.00												MO - Mineral Oil									
		N330 Carbon Black		30.00		MPG - Modified Polyglycol										PPGD - Polypropylene Glycol Diol									
																AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness												
			values	mean	values	mean	2 hr. Diameter (%)	values	mean	1 Day Diameter (%)	values	mean													
R-22	22.0	22.2	22.5		57.8/56.4	57.1	5.1/5.2	5.2	1.7/1.5	1.6	2.8/3.1	3.0													
R-32	13.6	12.7	13.7		27.0/25.6	26.3	3.0/3.8	3.4	0.3/1.6	1.0	2.0/1.8	1.9		83/84 A											
R-124	24.1	23.4	24.0		73.7/68.4	71.1	5.0/5.6	5.3	2.6/3.1	2.9	7.1/7.4	7.3													
R-134a	19.2	18.8	18.2		50.0/47.2	48.6	5.2/4.4	4.8	1.3/1.6	1.5	5.8/5.3	5.6													
R-125*	13.4	13.5	13.3		36.5/35.8	36.2	5.3/6.2	5.8	3.6/3.4	3.5	7.4/7.9	7.7													
R-143a	13.8	14.2	14.0		27.9/26.9	27.4	3.8/4.3	4.1	1.9/2.8	2.4	4.6/4.6	4.6		60/61 A											
R-152a	21.5	21.9	21.5		41.8/40.2	41.0	5.9/6.3	6.1	1.6/2.2	1.9	2.3/2.2	2.3		86/87 A											
R-123	22.6	22.9	24.3		70.7/58.5	64.6	8.7/10.6	9.7	4.6/4.0	4.3	10.8/11.1	11.0		82/83 A											
R-142b	23.2	23.6	23.0		56.2/52.5	54.4	10.2/13.7	12.0	3.5/4.4	4.0	5.5/7.7	6.6													
R-134	19.9	19.1	21.1		54.0/53.0	53.5	4.9/5.6	5.3	2.4/2.5	2.5	5.0/5.0	5.0		78/79 A											
AB	0.3	-	0.1/0.1	0.1	0.2/0.3	0.3			-0.1/0.5	0.2	0.1/0.2	0.2		90/91 A											
MO	-0.1	-	0.5/0.3	0.4	0.3/0.3	0.3			0.1/0.1	0.1	0.2/0.2	0.2		89/90 A											
PEMA	0.4	-	1.0/0.4	0.7	1.0/1.0	1.0			1.0/0.8	0.9	0.9/0.9	0.9		88/89 A											
PEBA	0.3	-	1.0/0.5	0.8	1.5/1.6	1.6			0.1/1.0	0.6	1.2/1.3	1.3		88/89 A											
PPGD	-0.1	-	0.4/0.5	0.5	0.9/0.9	0.9			1.5/-0.3	0.6	0.9/0.9	0.9		89/90 A											
PPGBM	0.2	-	0.3/0.2	0.2	0.4/0.4	0.4			0.1/-0.1	0.0	0.3/0.3	0.3		89/90 A											
MPG	0.1	-	0.3/0.4	0.3	0.2/0.2	0.2			-0.2/-0.3	-0.3	0.2/0.2	0.2		88/89 A											

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 31		Fluoroelastomer		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid									
		Litharge (Sublimed)		1.80				PEBA - Pentaerythritol Ester Branched Acid									
		Triallyl Isocyanurate		1.80				PPGBM - Polypropylene Glycol Butyl Monoether									
		2,5-Dinethyl-2,5-bis(t-butyl-peroxy) hexane		1.80				MO - Mineral Oil									
								MPG - Modified Polyglycol									
						PPGD - Polypropylene Glycol Diol											
						AB - Alkyl Benzene											
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22	25.8	25.6	25.9		71.6/69.1	70.4			1.4/2.7	2.1	7.0/7.1	7.1	58/59 A				
R-32*	17.4	17.5	16.7		34.2/34.0	34.1	3.4/3.1	3.3	1.0/0.4	0.7	2.8/3.0	2.9	60/61 A				
R-124	20.8	21.1	21.5		64.0/63.5	63.8	9.2/10.6	9.9	4.4/5.1	4.8	15.3/15.0	15.2	60/61 A				
R-134a	15.7	15.6	16.2		43.2/42.2	42.7	4.5/4.8	4.7	2.9/2.2	2.6	8.1/7.7	7.9					
R-125	5.8	7.6	8.6		22.0/22.0	22.0	7.4/5.5	6.5	5.5/4.3	4.9	14.2/12.0	13.1	60/61 A				
R-143a	9.9	10.0	10.2		22.7/22.4	22.6			2.8/3.6	3.2	9.0/8.8	8.9					
R-152a	27.9	27.2	27.0		59.3/57.0	58.2	7.6/7.5	7.6	3.0/2.3	2.7	6.3/6.4	6.4	59/60 A				
R-123	27.8	27.3	29.1		106/108	107	15.6/14.9	15.2	5.2/6.6	5.9	20.9/19.1	20.0	58/59 A				
R-142b	26.3	25.9	25.1		67.1/66.9	67.0			2.3/4.8	3.4	11.4/11.3	11.4	59/60 A				
R-134	22.7	22.8	22.3		67.0/66.1	66.6	9.0/8.0	8.5	3.7/4.1	3.9	11.4/11.3	11.4	58/59 A				
AB	-2.6	-	-0.1/0.4	0.2	0.3/0.3	0.3			-1.4/-0.5	-1.0	0.5/0.5	0.5	59/60 A				
MO	-0.1	-	0.6/0.3	0.5	0.4/0.3	0.4			-0.3/0.1	-0.1	0.2/0.1	0.2	59/60 A				
PEMA	10.8	-	31.5/31.5	31.5	77.3/77.4	77.4			30.0/30.6	30.3	77.3/77.3	77.3	57/58 A				
PEBA	14.6	-	35.6/28.7	32.2	85.9/66.8	76.4			33.2/26.5	29.9	86.2/66.9	76.6	49/50 A				
PPGD	1.5	-	4.5/4.9	4.7	9.8/8.6	9.2			4.0/4.4	4.2	9.7/8.5	9.1	59/60 A				
PPGBM	0.1	-	0.4/0.1	0.3	1.0/1.1	1.1			0.4/2.7	1.6	0.9/0.9	0.9	59/60 A				
MPG	0.1	-	0.5/0.4	0.5	1.0/0.8	0.9			-0.3/0.1	-0.2	0.8/0.8	0.8	61/62 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 32	Fluoroelastomer		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
	Magnesium oxide		15.00												PEBA - Pentaerythritol Ester Branch Acid	
	N,N'-dicinnamylidene-1,6-hexanediamine		3.00												PPGBM - Polypropylene Glycol Butyl Monoether	
															MO - Mineral Oil	
								MPG - Modified Polyglycol				PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene		
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness			
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)					
			values	mean	values	mean	values	mean	values	mean	values	mean				
			values	mean	values	mean	values	mean	values	mean	values	mean				
R-22*	24.8	24.9	23.5		87.0/81.0	84.0	5.5/6.4	6.0	1.9/4.6	3.3	2.8/3.6	3.2	56/57 A			
R-32																
R-124	19.3	20.1	19.7		81.0/78.0	79.5	7.0/6.7	6.9	3.0/3.2	3.1	12.5/12.9	12.7	60/61 A			
R-134a*	12.6	13.2	13.0		45.0/44.5	44.8	6.4/7.0	6.7	2.4/3.4	2.9	9.8/9.5	9.7	65/66 A			
R-125*	5.2	6.0	6.5		22.3/22.7	22.5	13.0/19.4	16.2	7.0/8.9	8.0	7.5/8.1	7.8	53/54 A			
R-143a*	7.6	7.5	8.1		22.2/22.0	22.1	13.4/6.7	10.1	7.2/3.2	5.2	5.0/7.0	6.0	53/54 A			
R-152a	26.1	26.8	25.4		70.0/66.5	68.3	4.3/6.0	5.2	1.8/2.1	1.9	2.7/2.5	2.6	57/58 A			
R-123	34.1	36.8	36.0		169/166	168	11.3/11.8	11.6	4.5/4.7	4.6	10.6/11.2	10.9	64/65 A			
R-142b	29.3	27.3	28.9		91.1/80.2	85.6	6.2/6.2	6.2	3.3/3.5	3.4	7.0/7.8	7.4	58/59 A			
R-134	19.8	19.7	20.0		69.4/72.6	71.0	11.3/9.4	10.3	5.5/4.6	5.0	11.8/10.3	11.1	65/66 A			
AB	0.5	-	0.7/0	0.4	1.5/1.3	1.4			-0.1/-0.9	-0.5	1.1/0.9	1.0	74/75 A			
MO	0.5	-	1.5/0.4	0.9	2.1/1.6	1.9			1.3/0.8	1.1	1.4/1.4	1.4	65/66 A			
PEMA	9.9	-	50.2/43.9	47.1	197/167	182			51.6/44.6	48.1	197/168	183	26/27 A			
PEBA	8.9	-	48.8/45.7	47.3	171/143	157			52.1/41.8	47.0	171/144	157	28/29 A			
PPGD	1.3	-	3.5/3.1	3.3	9.5/9.0	9.3			3.0/4.0	3.5	9.9/9.3	9.6	65/66 A			
PPGBM	1.0	-	0.9/0.7	0.8	3.0/3.3	3.2			0.2/0.4	0.3	2.1/2.2	2.2	71/72 A			
MPG	-0.1	-	0.8/0.8	0.8	2.5/3.2	2.9			-0.5/0.4	-0.1	1.9/2.0	2.0	74/75 A			

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 34		Epichlorohydrin Homopolymer		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
		Stearic Acid		1.00						PEBA - Pentaerythritol Ester Branched Acid			
		Nickel Dibutyldithiocarbamate		1.00									
		Red Lead		5.00									
		Ethylene Thiourea		1.85		MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol					
						AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			values	mean	values	mean	values	mean	2 hr. Diameter (%)	1 Day Diameter (%)		1 Day Weight (%)	
R-22*	12.3	12.1	12.3		38.9/38.4	38.7		-0.3/0.2	-0.1	-1.9/-1.7	-1.8	37/38 A	
R-32*	4.7	4.3	4.2		11.9/11.8	11.9	2.4/2.4	2.4	0.2/-0.2	0	-0.6/-0.5	-0.6	37/38 A
R-124	0.8	1.7	3.4		11.7/11.3	11.5	2.4/2.4	2.4	2.2/2.4	2.3	9.0/9.0	9.0	41/42 A
R-134a	0.3	0.9	1.3		4.2/4.3	4.3	0.8/0.7	0.8	0.5/0.4	0.5	2.7/2.8	2.8	
R-125	0	0.1	0.1		1.3/1.4	1.4	0.5/0.8	0.7	0.5/0.8	0.7	1.3/1.5	1.4	38/39 A
R-143a	0.2	0.4	0.9		2.6/2.7	2.7			1.9/2.0	2.0	1.9/2.0	2.0	40/41 A
R-152a	4.3	4.9	4.8		11.9/11.9	11.9	3.6/3.6	3.6	1.3/2.2	1.8	4.6/4.9	4.8	41/42 A
R-123	16.4	17.5	17.1		68.0/68.0	68.0	13.3/12.9	13.1	5.8/5.6	5.7	25.9/23.6	24.8	39/40 A
R-142b	2.3	4.3	5.0		14.4/14.3	14.4			2.9/2.7	2.8	8.9/8.9	8.9	37/38 A
R-134	1.3	2.8	3.5		12.7/12.0	12.4	3.1/3.1	3.1	2.3/2.1	2.2	8.6/8.8	8.7	40/41 A
AB	1.6	-	0.2/0.3	0.3	0.5/0.5	0.5			-0.5/-0.2	-0.4	0.9/1.0	1.0	40/41 A
MO	0.6	-	1.2/0.7	1.0	2.6/2.6	2.6			0.4/0.7	0.6	2.3/2.4	2.4	38/39 A
PEMA	13.4	-	26.8/26.8	26.8	73.0/72.7	72.9			25.8/25.8	25.8	72.1/72.1	72.1	31/32 A
PEBA	7.7	-	17.2/17.5	17.4	44.0/44.9	44.5			16.2/15.4	15.8	44.4/45.4	44.9	32/33 A
PPGD	9.0	-	18.2/17.9	18.1	46.4/46.6	46.5			17.2/16.4	16.8	46.2/46.6	46.4	33/34 A
PPGBM	0.4	-	2.0/2.0	2.0	3.9/4.0	4.0			0.7/1.3	1.0	3.8/3.8	3.8	38/39 a
MPG	0.3	-	0.4/0.4	0.4	0.5/0.6	0.6			-0.8/-0.7	-0.8	0.4/0.5	0.5	40/41 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 35			Epichlorohydrin Homopolymer			100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid	
			Stearic Acid			1.00						PEBA - Pentaerythritol Ester Branched Acid	
			Nickel Dibutylidithiocarbamate			1.00						PPGBM - Polypropylene Glycol Butyl Monoether	
			Red Lead			5.00						MO - Mineral Oil	
			Ethylene Thiourea			1.85						MPG - Modified Polyglycol	
			N330 Carbon Black			40.00		PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			values	mean	values	mean	2 hr. Diameter (%)	values	mean	1 Day Diameter (%)		values	mean
R-22	8.7	8.7	5.6		28.8/28.1	28.5			1.9/1.9	1.9	4.8/5.1	5.0	66/67 A
R-32	3.7	3.4	3.3		8.5/8.3	8.4	2.2/2.7	2.5	0.6/1.1	0.9	1.8/2.3	2.1	70/71 A
R-124	0.5	1.0	1.8		7.4/7.7	7.6	0.5/1.0	0.8	1.3/1.2	1.3	6.1/6.3	6.2	70/71 A
R-134a	0.2	0.3	1.0		2.7/3.0	2.9	1.1/0.7	0.9	0.8/0.6	0.7	1.9/2.1	2.0	
R-125	0	0.1	0.1		0.9/0.9	0.9	1.0/0.2	0.6	0.2/0.3	0.3	0.9/0.9	0.9	71/72 A
R-143a	0.2	0.4	0.6		1.6/1.8	1.7			0.7/0.8	0.8	1.3/1.5	1.4	71/72 A
R-152a	2.0	3.5	3.5		8.5/8.4	8.5	3.1/2.8	3.0	2.0/1.5	1.8	3.9/3.7	3.8	70/71 A
R-123	10.4	12.0	11.8		45.7/45.8	45.8	9.0/8.7	8.8	4.2/5.0	4.6	18.9/20.5	19.7	66/67 A
R-142b	1.1	2.8	2.9		10.3/10.5	10.4			2.0/2.5	2.3	6.8/6.9	6.9	69/70 A
R-134	0.4	1.5	2.8		8.7/8.8	8.8	1.4/1.6	1.5	1.4/1.0	1.2	6.5/6.3	6.4	70/71 A
AB	-0.1	-	0.3/0.4	0.4	0.4/0.4	0.4			-0.1/0.2	0.1	0.8/0.8	0.8	74/75 A
MO	0.4	-	1.1/1.0	1.1	2.0/1.9	2.0			1.1/0.9	1.0	1.7/1.7	1.7	73/74 A
PEMA	5.8	-	15.6/15.1	15.4	39.7/40.2	40.0			15.0/14.3	14.7	39.6/40.2	39.9	59/60 A
PEBA	3.8	-	10.7/10.6	10.7	26.6/26.6	26.6			9.6/9.9	9.8	27.2/27.1	27.1	61/62 A
PPGD	4.1	-	10.5/10.5	10.5	26.2/27.0	26.6			9.9/10.0	10.0	26.4/27.2	26.8	62/63 A
PPGBM	0.4	-	1.4/1.4	1.4	2.8/2.6	2.7			1.1/1.5	1.3	2.8/2.6	2.7	71/72 A
MPG	0.2	-	0.2/0.2	0.2	0.5/0.5	0.5			0.1/-0.6	-0.3	0.4/0.4	0.4	74/75 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 36		Epichlorohydrin Copolymer			100.00			Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid		
		Stearic Acid			1.00													PEBA - Pentaerythritol Ester Branched Acid		
		Nickel Dibutyldithiocarbamate			1.00													PPGBM - Polypropylene Glycol Butyl Monoether		
		Red Lead			5.00													MO - Mineral Oil		
		Ethylene Thiourea			1.85			MPG - Modified Polyglycol			PPGD - Polypropylene Glycol Diol			AB - Alkyl Benzene						

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 37		Epichlorohydrin Copolymer			100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Stearic Acid			1.00												PEBA - Pentaerythritol Ester Branched Acid	
		Nickel Dibutyldithiocarbamate			1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
		Red Lead			5.00												MO - Mineral Oil	
		Ethylene Thiourea			1.85												MPG - Modified Polyglycol	
		N330 Carbon Black			40.00		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day - Shore A/D Hardness					
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)							
			values	mean	values	mean	values	mean	values	mean	values	mean						
R-22	25.6	26.1	23.8		89.6/83.8	86.7			-0.9/-0.7	-0.8	-1.5/-2.0	-1.8	67/68 A					
R-32	5.5	5.7	5.4		14.7/14.6	14.7	1.2/1.2	1.2	-0.6/0.1	-0.3	-0.6/-0.3	-0.5	69/70 A					
R-124	16.4	15.9	15.6		55/52.4	53.7	5.6/5.5	5.6	-0.0/0.6	0.3	3.5/2.8	3.2	68/69 A					
R-134a	2.7	2.5	2.7		8.8/8.3	8.6	1.8/1.6	1.7	0.2/0.4	0.3	-0.04/0.1	-0.07						
R-125	1.5	2.1	2.4		7.3/7.3	7.3	1.8/2.2	2.0	0.9/0.9	0.9	3.4/3.3	3.4	67/68 A					
R-143a	.8	1.1	1.2		3.4/4.3	3.9			0.7/0.2	0.5	1.1/1.4	1.3	67/68 A					
R-152a	5.3	5.2	2.0		11.6/11.5	11.6	1.5/1.1	1.3	-0.9/-0.3	-0.6	0.1/-0.1	0	71/72 A					
R-123	43.1	44.6	43.2		209/213	211	11.8/11.2	11.5	0.3/1.1	0.7	5.7/6.5	6.1	67/68 A					
R-142b	5.0	5.3	4.8		14.9/15.0	15.0			0.3/0.5	0.4	1.6/2.1	1.9	69/70 A					
R-134	9.8	9.2	9.0		35.2/34.5	34.9	4.0/4.7	4.4	-0.8/0.5	-0.2	2.4/3.4	2.9	69/70 A					
AB	-0.2		0.1/0.2	0.1	0.2/0.2	0.2			-0.2/0.3	0.1	0.9/0.9	0.9	69/70 A					
MO	0.5		0.5/0.9	0.7	1.9/1.9	1.9			0.9/0.6	0.8	1.9/2.0	2.0	68/69 A					
PEMA	3.9		5.1/5.0	5.1	11.5/11.7	11.6			3.4/3.9	3.7	11.6/11.4	11.5	63/64 A					
PEBA	2.1		3.8/3.7	3.8	8.5/8.7	8.6			2.7/3.7	3.2	9.1/9.2	9.2	4/65 A					
PPGD	6.5		8.5/8.2	8.4	20.8/21.0	20.9			7.2/6.8	7.0	20.7/26.6		60/61 A					
PGBM	0.2		0.7/0.5	0.6	1.1/1.5	1.3			0.2/-0.4	-0.1	1.3/1.5	1.4	69/70 A					
MPG	-0.4		-0.2/-0.1	-0.2	-0.2/-0.2	-0.2			-0.5/-0.4	-0.5	0.1/0.1	0.1	70/71 A					

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 38		Epichlorohydrin Terpolymer			100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid			
		Stearic Acid			1.00						PEBA - Pentaerythritol Ester Branched Acid			
		Nickel Dibutyldithiocarbamate			1.00						PPGBM - Polypropylene Glycol Butyl Monoether			
		Red Lead			5.00						MO - Mineral Oil			
		Ethylene Thiourea			1.86						MPG - Modified Polyglycol			
											PPGD - Polypropylene Glycol Diol			
											AB - Alkyl Benzene			
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness	
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)			
			values	mean	values	mean	values	mean	values	mean	values	mean		
R-22*	39.8	39.0	38.4		154/145	149			-2.3/-2.5	-2.4	-4.8/-4.5	-4.7	41/42 A	
R-32*	7.5	7.4	7.3		21.7/21.0	21.4	0.5/0.4	0.5	0/0.1	0.1	-1.1/-1.0	-1.1	44/45 A	
R-124	26.2	26.1	25.6		97.0/95.0	96.0	7.5/8.3	7.9	-1.3/-0.1	-0.7	2.6/3.1	2.9	44/45 A	
R-134a	4.3	3.4	4.5		14.4/14.5	14.5	1.0/0.9	1.0	-1.2/-1.0	-1.1	-0.8/-0.5	-0.7		
R-125*	2.8	3.2	3.4		12.2/12.0	12.1	18.0/15.9	17.0	0.1/1.2	0.7	1.7/2.0	1.9	37/38 A	
R-143a	1.7	1.7	1.5		4.8/1.7	4.8			-0.3/-0.6	-0.5	0.8/0.6	0.7	43/44 A	
R-152a	6.9	6.7	6.8		18.0/17.9	18.0	3.0/2.3	2.7	-0.9/-1.0	-1.0	-0.8/-0.5	-0.7	46/47 A	
R-123	69.4	69.5	70.5		44.7/44.9	44.8	15.2/21.1	18.2	0.4/1.7	1.1	6.3/11.4	8.9	44/45 A	
R-142b	8.0	7.4	7.4		22.5/22.3	22.4			-0.3/0.4	0.1	1.3/1.4	1.4	46/47 A	
R-134	14.9	15.0	14.3		56.4/56.3	56.4	5.8/4.3	5.1	0.2/-1.3	-0.6	2.4/1.9	2.2	48/49 A	
AB	0.2	-	-1.5/0.3	-0.9	0.8/0.7	0.8			-0.5/0.1	-0.2	1.6/1.6	1.6	42/43 A	
MO	0.1	-	0.8/0.9	0.9	2.6/2.7	2.7			-0.2/0.3	0.1	2.8/2.8	2.8	42/43 A	
PEMA	5.4	-	8.1/7.6	7.9	18.9/19.0	19.0			5.8/6.2	6.0	18.7/18.4	18.6	39/40 A	
PEBA	4.0	-	5.1/6.4	5.8	13.3/13.5	13.4			4.3/4.8	4.5	14.0/41.2	14.1	40/41 A	
PPGD	10.9	-	13.9/13.5	13.7	37.0/37.1	37.1			12.7/11.5	12.1	36.2/36.5	36.4	36/37 A	
PPGBM	0.2	-	1.3/1.1	1.2	2.7/2.9	2.8			0.4/-0.1	0.2	3.1/3.0	3.1	43/44 A	
MPG	0.1	-	-0.1/-0.2	-0.1	0.2/0.3	0.3			-0.8/-0.9	-0.9	0.5/0.7	0.6	43/44 A	

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 39		Epichlorohydrin Terpolymer		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Stearic Acid		1.00												PEBA - Pentaerythritol Ester Branched Acid	
		Nickel dibutyldithiocarbamate		1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
		Red Lead		5.00												MO - Mineral Oil	
		Ethylene Thiourea		1.85												MPG - Modified Polyglycol	
IRB6		40.00		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene											
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22*	26.7	26.8	26.3		103/95.9	99.2			-1.6/-1.0	-1.3	-3.2/-1.9	-2.6	69/70 A				
R-32	5.1	5.5	5.4		15.4/15.2	15.3	0.6/1.2	0.9	-0.7/-0.7	-0.7	-0.7/-0.5	-0.6	70/71 A				
R-124	17.6	17.7	17.4		70.4/68.9	69.7	5.8/5.9	5.9	0.1/0.4	0.3	0.1/0.4	0.3	69/70 A				
R-134a	3.0	3.0	3.1		10.2/10.3	10.3	1.5/1.6	1.6	0.2/-0.2	0	-0.3/-0.3	-0.3					
R-125	1.9	2.5	3.0		9.0/8.6	8.8	1.5/1.6	1.6	0.7/0.7	0.7	3.4/3.1	3.3	68/69 A				
R-143a	0.7	0.8	1.3		3.6/3.5	3.6	1.2/-0.1	0.6	-0.2/-0.7	-0.5	0.6/0.6	0.6	70/71 A				
R-152a	5.1	4.7	4.8		12.6/12.6	12.6	2.4/2.6	2.5	-0.4/-0.6	-0.5	-0.4/-0.4	-0.4	69/70 A				
R-123	42.3	43.2	41.8		228/227	227	10.9/10.1	10.5	0.5/0.5	0.5	5.9/5.2	5.5	68/69 A				
R-142b	5.5	5.5	5.1		16.4/16.1	16.3			0.4/0.2	0.3	1.6/1.6	1.6	69/70 A				
R-134	9.8	10.0	10.3		39.3/38.8	39.1	2.9/4.0	3.5	-1.4/-1.0	-1.2	1.6/2.0	1.8	69/70 A				
AB	0.2	-	-2.0/0.3	-0.9	0.2/0.3	0.3			0.5/0.5	0.5	1.0/1.1	1.1	69/70 A				
MO	1.3	-	-1.1/1.0	-1.1	2.1/2.0	2.1			0.2/0.7	0.5	2.1/2.2	2.2	68/69 A				
PEMA	4.0	-	5.2/5.2	5.2	12.9/13.0	13.0			4.6/4.0	4.3	12.9/13.0	13.0	63/64 A				
PEBA	1.8	-	3.7/3.8	3.8	9.3/9.2	9.2			2.8/3.1	3.0	9.9/9.9	9.9	63/64 A				
PPGD	7.8	-	8.7/8.6	8.7	22.7/22.9	22.8			6.3/7.5	6.9	22.6/16.9	19.8	59/60 A				
PPGBM	-0.2	-	1.3/1.2	1.3	1.9/2.3	2.1			1.1/6.5	3.8	2.1/2.4	2.3	69/70 A				
MPG	0.8	-	0.8/0.2	0.5	0.3/0.3	0.3			0.5/0.1	0.3	0.6/0.7	0.7	70/71 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 40	Silicone elastomer		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid		PEBA - Pentaerythritol Ester Branched Acid		PPGBM - Polypropylene Glycol Butyl Monoether		MO - Mineral Oil		MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene	
	Peroxide		1.50																	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness							
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)									
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean						
R-22*	64.0	64.4	64.3		395/332	364	-0.8/-1.0	-0.9	-2.0/-1.0	-1.5	-3.0/-3.4	-3.2								32/33 A
R-32																				
R-124	53.9	54.1	52.8		338/315	326	-1.6/-2.0	-1.8	-1.6/-2.3	-2.0	-4.4/-3.9	-4.2								29/30 A
R-134a	6.5	6.2	5.9		26.6/25.3	26.0	-1.5/-1.1	-1.3	-1.1/-1.4	-1.3	-2.7/-2.6	-2.7								31/32 A
R-125*	8.4	8.5	8.4		34.3/33.5	33.9	0.8/1.4	1.1	0.6/0.4	0.5	2.4/3.0	2.7								25/26 A
R-143a	11.2	11.5	11.0		25.5/21.3	23.4	-0.5/-1.3	-0.9	-0.6/-1.1	-0.9	-3.5/-2.6	-3.1								31/32 A
R-152a	21.3	21.0	19.4		53.6/50.2	51.9	-1.1/-2.0	-1.6	-1.2/-2.3	-1.8	-4.1/-4.2	-4.2								29/30 A
R-123*	74.6	74.2	73.5		639/635	637	-2.3/-1.7	-2.0	-1.8/-1.7	-1.8	-4.9/-4.7	-4.8								29/30 A
R-142b	66.8	67.1	66.2		363/318	341	-1.5/-1.6	-1.5	-1.7/-2.0	-1.9	-4.4/-3.9	-4.1								30/31 A
R-134	7.8	6.3	6.7		22.8/21.8	22.3	-1.3/2.2	0.5	-0.3/0.8	0.3	-2.3/-2.1	-2.2								31/32 A
AB	14.8	-	14.4/18.4	16.4	58.4/58.9	58.7			10.2/14.5	12.4	45.8/44.3	45.1								22/23 A
MO	10.1	-	9.2/10.1	9.6	26.9/26.2	26.6			6.6/6.9	6.8	18.7/18.3	18.5								26/27 A
PEMA	1.7	-	1.6/1.2	1.4	4.7/0.8	2.8			0.9/0.2	0.6	2.2/-1.4	0.4								32/33 A
PEBA	2.5	-	2.9/2.9	2.9	7.7/7.8	7.7			0.6/-0.1	0.2	3.2/3.8	3.5								24/25 A
PPGD	0.6	-	-0.6/-0.2	-0.4	-0.5/0.1	-0.2			-0.9/-0.2	-0.5	-1.1/-0.8	-1.0								29/30 A
PPGBM	0.7	-	0.3/0.5	0.4	0.1/0	0.1			0.1/-0.2	-0.1	-1.0/-1.0	-1.0								31/32 A
MPG	1.5	-	0.4/-0.3	0.1	-0.1/-0.6	-0.4			-0.1/0.2	0.1	-0.6/-1.6	-1.1								27/28 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 41	dimethyl Silicone Rubber		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid	
	Dicumyl Peroxide on Calcium Carbonate		1.00				PEBA - Pentaerythritol Ester Branched Acid	
							PPGBM - Polypropylene Glycol Butyl Monoether	
							MO - Mineral Oil	
						MPG - Modified Polyglycol		
						PPGD - Polypropylene Glycol Diol		
						AB - Alkyl Benzene		

Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness		
			values		mean		values		mean		1 Day Diameter (%)			1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean	values	mean		values	mean
R-22	49.9	51.9	52.4		223/200	211	2.5/-2.2	-2.4	2.3/-2.2	-2.3	-5.1/-5.3	-5.2			
R-32*	5.8	5.9	5.8		15.4/12.2	13.8	0.5/-0.3	0.1	0.5/-0.6	-0.1	-1.7/-1.4	-1.6	38/39 A		
R-124	41.5	40.7	40.0		211/190	200	-2.0/-1.7	-1.9	-2.0/-1.7	-1.9	-5.2/-5.1	-5.2			
R-134a	6.1	18.3	6.0		18.5/16.4	17.5	-1.3/-1.0	-1.2	-1.3/-0.7	-1.0	-2.0/-1.7	-1.9			
R-125*	7.2	7.6	7.2		21.7/21.8	21.8	0.6/0.7	0.7	0.3/0.7	0.5	1.1/2.1	1.6			
R-143a*	9.9	9.8	9.3		21.0/19.1	20.1	-0.7/0.3	-0.2	-0.8/-0.2	-0.5	-2.8/-2.5	-2.7			
R-152a	17.3	17.1	17.0		48.9/39.7	44.3	-3.0/-2.3	-2.7	-2.2/-1.7	-2.0	-3.9/3.7	-0.1	42/43 A		
R-123	60.4	60.9	59.9		398/387	393	-1.5/-2.2	-1.9	-1.7/-2.2	-2.0	-6.3/-6.2	-6.3	44/45 A		
R-142b	52.6	51.6	50.7		247/216	232	-0.7/-1.2	-1.0	-1.7/-2.0	-1.9	-3.8/-3.3	-3.6			
R-134	4.8	5.1	5.5		18.5/17.6	18.1	-1.1/-0.8	-1.0	-1.3/-0.8	-1.1	-1.7/-1.4	-1.6	42/43 A		
AB	15.9	-	15.7/15.9	15.8	44.6/44.2	44.4			11.9/10.4	11.2	34.7/34.5	34.6	29/30 A		
MO	7.9	-	7.1/7.4	7.3	19.5/19.4	19.5			5.3/5.3	5.3	14.7/14.4	14.6	33/34 A		
PEMA	1.5	-	1.2/1.5	1.4	3.7/3.7	3.7			0.6/0.5	0.6	2.3/2.4	2.4	39/40 A		
PEBA	2.8	-	2.5/2.3	2.4	7.3/7.2	7.2			0.9/1.4	1.1	5.3/5.2	5.2	38/39 A		
PPGD	0.6	-	0.2/0.2	0.2	0.2/0.2	0.2			-0.4/-0.7	-0.6	-0.3/-0.2	-0.3	38/39 A		
PPGBM	0.4	-	-0.1/0.1	0	0.7/0.6	0.6			-1.0/-0.5	-0.8	0.1/0.1	0.1	39/40 A		
MPG	0.4	-	-0.3/-0.4	-0.4	-0.2/-0.4	-0.3			-0.7/-1.1	-0.9	-0.8/-0.7	-0.8	41/42 A		

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 45		EPDM/Polypropylene TPE Shore A 87		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid						
								PEBA - Pentaerythritol Ester Branched Acid						
								PPGBM - Polypropylene Glycol Butyl Monoether						
								MO - Mineral Oil						
								MPG - Modified Polyglycol						
								PPGD - Polypropylene Glycol Diol						
								AB - Alkyl Benzene						
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness			
							2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean		values	mean	
R-22	-0.7	-0.9	-0.9		5.9/3.1	4.5		0.6/0.7	0.7	-0.1/-0.1	-4.7	-24.7/-24.3	-24.5	
R-32	0.7	0.9	0.8		3.3/3.2	3.3		2.4/-2.2	-2.3	-0.1/-0.1	-0.1	-0.1/-0.1	-0.1	93/94 A
R-124	-0.8	-0.9	-1.3		8.8/8.9	8.9		-0.2		-0.6/-0.5	-0.6	-21.0/-20.8	-20.9	
R-134a	0.0		0.1		2.4/2.3	2.4		1.2		0.7/1.3	1.0	5.9/6.5	6.2	
R-125	1.0	1.4	1.7		9.6/10.4	10.0		-0.1		0.3/-0.4	-0.1	-1.1/-0.9	-1.0	
R-143a	0.8	0.6	0.9		2.9/3.0	3.0		-0.2		-1.1/-0.8	-1.0	-1.5/-1.0	-1.3	
R-152a	0.8	0.7	0.8		5.9/4.2	5.1		-6.7		-8.3/-8.6	-8.5	-24.3/-24.3	-24.3	
R-123	0.3	0.1	0.1		19.2/19.2	19.2		-4.5		-6.3/-6.0	-6.2	-27.0/-26.0	-26.5	
R-142b	-0.1	-0.3	-0.6		7.0/6.2	6.6		-0.3/-0.1	-0.2	-0.7/-0.4	-0.6	-0.7/-0.5	-0.6	92/93 A
R-134	0.4	0.5	0.5		2.7/2.5	2.6				3.9/3.7	3.8	14.9/14.9	14.9	
AB	3.6	-	4.5/4.6	4.6	17.3/18.1	17.7						24.4/24.1	24.3	
MO	6.6	-	6.6/6.7	6.7	26.0/26.2	26.1				-1.9/-1.7	-1.8	-2.6/-2.9	-2.8	
PEMA	-1.3	-	-1.7/-1.7	-1.7	-1.7/-2.0	-1.7						-2.7/-2.7	-2.7	
PEBA	-0.8	-	-1.2/-1.6	-1.4	-1.7/-1.8	-1.8						-7.3/-8.1	-7.7	
PPGD	-2.8	-	-3.5/-2.7	-3.1	-9.0/-8.9	-8.9						-5.1/-5.2	-5.2	
PPGBM	-1.2	-	-1.9/-2.4	-2.2	4.4/-4.4	-4.4				-2.2/-2.4	-2.3	-4.2/-4.1	-4.2	93/94 A
MPG	-1.7	-	-2.1/-2.5	-2.3	-4.1/-3.7	-3.9				-2.7/-2.5	-2.6			

Formula # 46		EPDM/Polypropylene TPE Shore A 73		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid	
								PEBA - Pentaerythritol Ester Branched Acid	
								PPGBM - Polypropylene Glycol Butyl Monoether	
								MO - Mineral Oil	
								MPG - Modified Polyglycol	
								PPGD - Polypropylene Glycol Diol	
								AB - Alkyl Benzene	

Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean	values	mean	
R-22	-2.5	-3.2	-3.5		-7.0/-8.1	-7.6	4.7		-9.2/-9.0	-9.1	-29.4/-29.1	-29.3	
R-32	0.7	0.7	0.7		3.6/3.5	3.6	-0.2/0.5	0.2	-0.5/-0.1	-0.3	-0.1/-0.1	-0.1	74/75 A
R-124	-2.4	-3.4	-4.2		-5.9/-6.4	-6.2	-3.9/-4.6	-4.3	-6.9		-22.2/-20.9	-21.6	
R-134a	0.4		0.1		2.6/2.7	2.7	-0.3		-0.1/-0.9	-0.5	-0.5/-0.5	-0.5	
R-125	1.3	2.7	3.2		11.3/12.9	12.1	2.2		2.2/1.2	1.7	8.2/9.1	8.7	
R-143a	0.1	0.2	0.4		3.3/3.5	3.4	-0.4		-1.1/-0.7	-0.9	-1.2/-1.0	-1.1	
R-152a	0.7	0.3	0.6		4.5/3.9	4.2	-1.0		-1.6/-1.2	-1.4	-2.9/-2.0	-2.5	
R-123	-1.3	-1.3	-1.4		15.2/15.1	15.2	-9.6		-11.2/-11.0	-11.1	-33.1/-32.9	-33.0	
R-142b	-3.3	-3.8	-4.2		-6.1/-6.4	-6.3	-8.6		-11.1/-11.7	-11.4	-32.9/-32.1	-32.5	
R-134	0.6	0.6	0.5		2.7/2.9	2.8	-0.1/0.3	0.1	-0.1/-0.4	-0.2	-0.4/-0.3	-0.4	76/77 A
AB	8.7	-	11.1/10.3	10.7	38.6/38.5	38.6			9.0/9.3	9.2	35.5/35.9	35.7	
MO	13.8	-	13.2/14.1	13.7	54.2/54.0	54.1					51.1/50.9	51.0	
PEMA	-3.9	-	-8.0/-5.1	-6.6	-13.5/-13.7	-13.6			-5.1/-5.1	-5.1	-14.9/-15.1	-15.0	
PEBA	-3.2	-	-4.2/-4.3	-4.3	-12.5/-12.6	-12.5					-14.3/-13.9	-14.1	
PPGD	-5.6	-	-6.0/-7.2	-6.7	-21.6/-21.3	-21.5					-19.3/-20.4	-19.9	
PPGBM	-4.0	-	-6.1/-6.5	-6.3	-18.1/-17.9	-18.0			-6.5/-2.0	-4.3	-19.0/-18.7	-18.9	
MPG	-5.0	-	-6.4/-6.4	-6.4	-18.6/-18.6	-18.6			-5.8/-7.0	-6.4	-19.0/-18.8	-18.9	84/85 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 47	EPDM/Polypropylene TPE Shore D 40		100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid			
									PEBA - Pentaerythritol Ester Branched Acid			
									PPGBM - Polypropylene Glycol Butyl Monoether			
									MO - Mineral Oil			
								MPG - Modified Polyglycol				
								PPGD - Polypropylene Glycol Diol				
								AB - Alkyl Benzene				
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid.				1 Day Shore A/D Hardness	
			Change (%)		Change (%)		Values Based On Original Sample Measurements.					
			values	mean	values	mean	2 hr. Diameter (%)	1 Day Diameter (%)	1 Day Weight (%)	values		mean
R-22	-0.4	-0.4	-0.5		7.6/3.4	5.5	-0.8	-3.6/-3.5	-3.6	-21.6/-21.2	-21.4	
R-32	0.4	0.2	0.2		3.0/2.7	2.9	-0.2/0.5	0.1	-0.5	0/0	0	43/44 D
R-124	-0.4	-0.5	-0.5		11.8/10.6	11.2	-2.3/-0.9	-1.3		-3.2	-18.6/-17.1	-17.9
R-134a	0.2		0.3		2.2/2.1	2.2	0.3		0	0.1/-0.1	-0.5/-0.2	-0.4
R-125	0.8	1.7	1.8		9.4/9.5	9.5	1.1		0.6	0.7/0.5	6.3/5.9	6.1
R-143a	0.7	0.6	0.6		2.8/2.7	2.8	0		-0.3	-0.1/-0.4	-1.0/-0.9	-1.0
R-152a	0.3	0.6	0.6		6.1/4.8	5.5	-0.1		-0.4	-0.4/-0.3	-0.5/-0.4	-0.5
R-123	0.9	0.5	0.5		18.8/18.5	18.7	-5.1		-6.5	-6.4/-6.6	-18.8/-19.8	-19.3
R-142b	0.2	-0.2	-0.2		8.1/7.0	7.6	-3.9		-4.2	-4.5/-3.9	-23.7/-23.0	-23.4
R-134	0.1	0.2	0.1		1.5/1.8	1.7	0.1/-0.3	-0.1	-0.5	-0.5/-0.4	-0.6/-0.4	-0.5
AB	2.9	-	3.4/2.9	3.2	13.5/14.4	14.0			2.6	2.6/2.5	11.2/11.3	11.3
MO		-	4.1/3.9	4.0	18.3/18.0	18.2					17.3/17.1	17.2
PEMA	-0.5	-	-0.6/-0.2	-0.4	1.0/1.2	1.1			-0.6	-0.8/-0.3	0.3/0.5	0.4
PEBA	-0.5	-	0.1/-0.4	-0.2	0.9/1.1	1.0					0.1/0.3	0.2
PPGD	-1.0	-	-1.2/-1.1	-1.2	-3.2/-3.2	-3.2					-2.8/-2.5	-2.7
PPGBM	-0.4	-	-0.3/-0.9	-0.5	-0.4/-0.5	-0.5			-1.2	-1.1/-1.2	-1.2/-1.4	-1.3
MPG	-0.2	-	0.4/-0.7	-0.2	-0.3/-0.3	-0.3			-0.9	-0.8/-1.0	-0.7/0.7	-0.7
												44/45 D

Formula # 48	EPDM/Polypropylene TPE Shore D 50		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
															PEBA - Pentaerythritol Ester Branched Acid	
															PPGBM - Polypropylene Glycol Butyl Monoether	
															MO - Mineral Oil	
															MPG - Modified Polyglycol	
										PPGD - Polypropylene Glycol Diol						
												AB - Alkyl Benzene				
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness			
			values	mean	values	mean	2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)					
							values	mean	values	mean	values	mean				
R-22	0.1	0.5	0.1		7.8/6.4	7.0	-0.6		-2.5/-2.7	-2.6	-16.6/-16.6	-16.6				
R-32																
R-124	0.1	-0.2	-0.3		9.7/9.3	9.5	-1.6/-0.8	-1.2	-2.7		-13.4/-13.0	-13.2				
R-134a	0.3		0.3		1.9/2.2	2.1	-0.1		0/-0.3	-0.2	0/0.3	0.2				
R-125	0.6	1.3	1.4		8.8/9.4	9.1	0.8		0.5/0.9	0.7	6.1/6.0	6.1				
R-143a	0.2	0.4	0.7		2.3/2.4	2.4	0.1		0/-0.2	-0.1	-0.3/-0.4	-0.4				
R-152a	0.1	-0.2	-0.1		2.0/1.2	1.6	-0.6		-1.5/-1.2	-1.4	-3.4/-3.1	-3.3				
R-123	1.4	1.0	1.1		17.8/17.8	17.8	-2.9		-4.2/-5.0	-4.6	-12.9/-12.9	-12.9				
R-142b	0.7	0.7	0.4		7.9/7.7	7.8	-2.1		-3.5/-3.6	-3.6	-17.8/-17.2	-17.5				
R-134	0.1	0.2	-0.1		2.6/1.8	2.2	-0.1/-0.4	-0.3	-0.3/-0.4	-0.4	0.1/0.4	0.3	47/48 D			
AB	1.5	-	2.5/2.2	2.4	9.5/9.2	9.4			1.9/2.3	2.1	9.1/9.0	9.1				
MO	2.6	-	2.7/2.6	2.7	13.9/13.7	13.8					12.8/12.5	12.7				
PEMA	0.6	-	0.2/0	0.1	2.0/1.6	1.8			0.1/-0.3	-0.1	1.5/1.1	1.3				
PEBA	0	-	-2.5/0	-1.3	1.5/1.8	1.6					1.1/1.2	1.2				
PPGD	-0.6	-	-1.1/-1.3	-1.2	-1.5/-1.6	-1.6					-0.1/-0.6	-0.4				
PPGBM	-0.5	-	-0.4/-0.4	-0.4	0.8/0.7	0.8			-0.8/-0.6	-0.7	0.3/0.2	0.3				
MPG	-0.2	-	-0.8/-0.7	-0.8	0.9/0.8	0.9			-0.5/-0.9	-0.7	0.4/0.4	0.4	47/48 D			

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 49		Nitrile/Polypropylene TPE Shore A 87		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
								PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
							2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean
R-22	9.9	10.3	10.2		65.2/54.7	60.0	-1.0/-0.8	-0.9	-3.7/-3.3	-3.5	-12.9/-11.5	-12.2	
R-32													
R-124	5.7	5.8	6.6		51.1/50.0	50.6	-0.9/-0.6	-0.8	-2.8/-2.6	-2.7	-5.5/-4.8	-5.2	
R-134a	0.4	0.7	-0.2		4.4/4.0	4.2	-0.6/-0.5	-0.6	-1.4/-1.1	-1.3	-3.0/-2.7	-2.9	
R-125	1.3	14.2	1.7		7.8/8.8	8.3	0.8/0.8	0.8	0.4/0.6	0.5	2.2/2.5	2.3	
R-143a	1.1	0.4	-0.4		0.7/1.5	1.1	-0.7/-0.2	-0.5	-1.3/-0.9	-1.1	-4.5/-3.9	-4.2	
R-152a	1.0	0.3	0.4		2.6/3.4	3.0	-1.1/-1.2	-1.2	-3.2/-3.0	-3.1	-10.8/-10.3	-10.6	95/96 A
R-123	19.6	20.0	20.6		140/139	140	0.7/1.4	1.1	-2.6/-2.0	-2.3	-2.6/-2.6	-2.6	95/96 A
R-142b	2.3	1.7	1.7		12.3/12.1	12.2	-0.6/-0.8	-0.7	-3.4/-3.4	-3.4	-10.0/-9.7	-9.9	
R-134	2.1	1.7	1.2		14.7/14.6	14.7	-0.1/0.4	0.2	-2.0/-1.7	-1.9	-1.7/-1.7	-1.7	96/97 A
AB	1.0	-	0.5/0.7	0.6	-0.9/-0.9	-0.9			0.1/0.3	0.5	-1.2/-1.1	-1.2	37/38 D
MO	1.8	-	0.9/0.4	0.7	1.1/1.1	1.1			0.9/0.5	0.7	0.8/0.9	0.9	37/38 D
PEMA	0.9	-	0.7/1.1	0.9	3.6/3.6	3.6			1.1/1.1	1.1	3.3/3.3	3.3	38/39 D
PEBA	-0.1	-	0.3/0.9	0.6	2.5/2.5	2.5			0.8/0.7	0.8	2.2/2.2	2.2	38/39 D
PPGD	0.6	-	0.4/-0.1	0.2	0.5/0.8	0.6			0.1/0.4	0.3	0.8/0.9	0.9	36/37 D
PPGBM	-0.2	-	-0.4/-0.8	-0.6	-2.2/-2.1	-2.1			-0.6/-0.4	-0.5	-2.0/2.0	2.0	40/41 D
MPG	-1.34	-	-1.2/-1.2	-1.2	-2.7/-2.4	-2.6			-1.1/-0.9	-1.0	-2.6/-2.5	-2.6	42/43 D

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 50			Nitrile/Polypropylene TPE Shore A 80				100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid					
													PEBA - Pentaerythritol Ester Branched Acid					
													PPGBM - Polypropylene Glycol Butyl Monoether					
													MO - Mineral Oil					
													MPG - Modified Polyglycol					
													PPGD - Polypropylene Glycol Diol					
													AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Short A/D Hardness					
			values	mean	values	mean	2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		values	mean				
							values	mean	values	mean	values	mean			values	mean		
R-22	14.3	14.6	14.6		78.4/75.5	77.0	-2.6/-2.1	-2.4	-5.7/-4.7	-5.2	-17.6/-16.5	-17.1						
R-32																		
R-124	10.5	10.2	10.6		77.7/74.8	76.3	-2.0/-2.2	-2.1	-4.3/-4.5	-4.4	-11.3/-10.2	-10.8						
R-134a	0.7	-0.2	-1.3		1.2/3.7	2.5	-2.3/-2.1	-2.2	-3.6/-2.7	-3.2	-10.0/-7.1	-8.6						
R-125	1.8	1.7	0.3		4.8/4.7	4.8	-1.0/-0.4	-0.7	-1.3/-1.6	-1.5	-3.3/-3.8	-3.6						
R-143a	0.4	2.8	-1.2		-2.6/-0.2	-1.4	-1.9/-1.5	-1.7	-2.6/-2.1	-2.4	-8.6/-6.4	-7.5						
R-152a	-0.1	-0.3	-0.4		0.4/0.1	0.3	-3.6/-3.2	-3.4	-5.6/-5.4	-5.5	-16.8/-16.2	-16.5	94/95 A					
R-123	31.1	31.5	31.8		216/216	216	0.3/0.4	0.4	-4.0/-4.1	-4.1	-8.6/-8.5	-8.6	89/90 A					
R-142b	1.5	1.1	0.6		11.1/11.5	11.3	-1.4/-1.3	-1.4	-5.1/-5.0	-5.1	-14.9/-14.0	-14.5						
R-134	3.0	2.2	1.6		19.1/19.4	19.3	-1.6/-0.4	-1.0	-4.1/-2.9	-3.5	-8.9/-8.1	-8.5	86/87 A					
AB	-0.3	-	-1.4/-1.3	-1.4	-5.9/-5.7	-5.8			-1.2/-1.0	-1.1	-6.3/-6.2	-6.3	23/24 D					
MO	0.7	-	-0.8/-0.9	-0.9	-3.3/-3.1	-3.2			-0.7/-0.5	-0.6	-3.5/-3.4	-3.5	83/84 A					
PEMA	1.4	-	0.9/0.8	0.9	3.3/3.5	3.4			1.4/1.1	1.3	3.1/3.3	3.2	82/83 A					
PEBA	0.5	-	0.3/-0.1	0.1	1.4/1.4	1.4			1.0/0.2	0.6	1.0/1.1	1.1	83/84 A					
PPGD	1.0	-	0.6/0.7	0.7	1.2/1.4	1.3			0.5/0.6	0.6	0.4/0.7	0.6	22/23 D					
PPGBM	-0.8	-	-1.9/-1.9	-1.9	-6.0/-6.2	-6.1			-1.3/-1.4	-1.4	-6.0/-6.0	-6.0	24/25 D					
MPG	-1.9	-	-2.8/-2.5	-2.7	-7.7/-7.9	-7.8			-2.6/-2.4	-2.5	-7.6/-7.8	-7.7	87/88 A					

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 51		Nitrile/Polypropylene TPE Shore D 40				100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid									
												PEBA - Pentaerythritol Ester Branched Acid									
												PPGBM - Polypropylene Glycol Butyl Monoether									
												MO - Mineral Oil									
										MPG - Modified Polyglycol				PPGD - Polypropylene Glycol Diol				AB - Alkyl Benzene			
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness										
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean							
R-22	6.9	7.1	7.4		47.4/42.9	45.2	-0.2/-0.2	-0.2	-2.5/-2.4	-2.5	-8.5/-8.4	-8.5									
R-32																					
R-124	4.7	4.6	4.5		39.7/39.0	39.4	0.2/0.4	0.3	-1.3/-1.3	-1.3	-1.7/-1.4	-1.6									
R-134a	0.9	0.9	0.5		6.6/7.2	6.9	0.9/0.8	0.9	0.4/0.7	0.6	2.4/2.4	2.4									
R-125	1.0	1.8	1.8		7.5/8.2	7.9	1.0/1.4	1.2	0.7/0.8	0.8	3.4/3.6	3.5									
R-143a	0.8	1.3	0.3		1.8/2.0	1.9	0.2/-0.2	0	-0.6/-0.7	-0.7	-2.2/-2.2	-2.2									
R-152a	1.2	0.4	0.3		3.0/3.0	3.0	-0.3/0.3	0	-1.7/-2.0	-1.9	-7.4/-7.3	-7.4	51/52 D								
R-123	14.2	14.5	15.4		103/101	102	1.6/1.6	1.6	-1.1/-1.1	-1.1	0.9/1.0	1.0	96/97 A								
R-142b	2.3	1.9	1.7		12.0/11.5	11.8	0.3/0.3	0.3	-2.4/-2.3	-2.4	-6.7/-6.1	-6.4									
R-134	1.6	1.6	0.8		11.9/12.6	12.3	0.6/0.5	0.6	-0.6/-0.5	-0.6	1.9/2.4	2.2	96/97 A								
AB	1.4	-	0.7/1.1	0.9	1.0/1.0	1.0			1.2/0.8	1.0	0.7/0.9	0.8	44/45 D								
MO	1.8	-	1.1/1.1	1.1	2.9/3.1	3.0			1.5/1.3	1.4	2.8/2.7	2.8	44/45 D								
PEMA	0.8	-	0.9/0.8	0.9	3.4/3.3	3.4			1.0/1.2	1.1	3.1/3.0	3.1	44/45 D								
PEBA	0.1	-	0.5/0.4	0.5	2.8/2.6	2.7			0.9/0.7	0.8	2.3/2.1	2.2	45/46 D								
PPGD	0.1	-	-0.2/-0.2	-0.2	0.4/0.5	0.5			0.1/0.3	0.2	0.6/0.7	0.7	44/45 D								
PPGBM	-0.1	-	-0.2/-0.4	-0.3	-0.8/-0.9	-0.9			-0.2/-0.2	-0.2	-1.0/-1.0	-1.0	45/46 D								
MPG	-0.6	-	-1.0/-0.6	-0.8	-1.6/-1.5	-1.5			-0.8/0.8	0	-1.6/-1.6	-1.6	47/48 D								

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 52		Polyester TPE (40 shore D)		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
																PEBA - Pentaerythritol Ester Branched Acid	
																PPGBM - Polypropylene Glycol Butyl Monoether	
																MO - Mineral Oil	
								MPG - Modified Polyglycol									
								PPGD - Polypropylene Glycol Diol									
								AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22	25.5	25.7	26.4		128/124	126	-4.8/-7.6	-6.2	-2.0/-8.7	-5.4	-2.4/-2.2	-2.3	35/36 D				
R-32																	
R-124	19.9	19.8	19.3		109/102	105	4.5/4.3	4.4	-2.7/-0.3	-1.5	0.5/0.6	0.6	36/37 D				
R-134a	3.7	3.3	3.3		12.3/12.0	12.2	1.2/1.7	1.5	-0.4/0.2	-0.1	0.4/1.2	0.8	39/40 D				
R-125	4.4	4.6	4.9		16.4/16.2	16.3	3.1/2.5	2.8	1.2/1.5	1.4	5.3/5.2	5.3	39/40 D				
R-143a	1.6	2.2	2.1		5.3/5.2	5.3	1.1/0.5	0.8	-0.8/-0.4	-0.6	0.4/0.6	0.5	39/40 D				
R-152a	4.1	4.4	4.2		12.1/11.5	11.8	0.2/0.4	0.3	-0.8/-1.2	-1.0	-0.5/-0.5	-0.5	40/41 D				
R-123*		Dissolved															
R-142b	7.1	6.6	6.7		24.4/22.8	23.6	1.0/1.3	1.1	-0.9/-1.2	-1.1	0.2/0	0.1	37/38 D				
R-134	6.7	7.7	6.7		31.0/29.7	30.0	1.6/1.5	1.6	-0.3/-1.3	-0.8	0.1/0.2	0.2	39/40 D				
AB	2.4	-	2.8/3.3	3.1	6.4/6.3	6.4			2.2/2.1	2.2	6.0/6.0	6.0	37/42 D				
MO	1.8	-	9.5/3.4	6.5	8.7/8.9	8.8			3.7/3.0	3.4	8.5/8.6	8.6	35/36 D				
PEMA	3.2	-	4.6/4.7	4.7	12.7/12.9	12.8			4.8/3.9	4.4	12.6/12.6	12.6	32/32 D				
PEBA	3.0	-	4.7/4.4	4.6	10.3/10.5	10.4			4.4/3.8	4.1	10.4/10.5	10.5	36/38 D				
PPGD	3.5	-	4.2/4.4	4.3	11.4/11.4	11.4			3.8/3.6	3.7	10.9/10.7	10.8	37/38 D				
PPGBM	1.6	-	2.3/2.7	2.5	6.0/6.2	6.1			2.3/1.8	2.1	6.1/6.1	6.1	35/36 D				
MPG	0.7	-	1.9/1.9	1.9	3.8/3.6	3.7			0.5/1.6	1.1	3.8/3.6	3.7	40/41 D				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 53			Polyester TPE (63 Shore D)			100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid									
												PEBA - Pentaerythritol Ester Branched Acid									
												PPGBM - Polypropylene Glycol Butyl Monoether									
												MO - Mineral Oil									
												MPG - Modified Polyglycol									
												PPGD - Polypropylene Glycol Diol									
												AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness								
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)										
			values	mean	values	mean	values	mean	values	mean	values	mean									
R-22	14.4	14.0	13.8		52.0/47.6	49.8	0.8/0.6	0.7	-0.8/-1.5	-1.2	-0.5/-0.5	-0.5	43/44 D								
R-32																					
R-124	8.6	9.5	9.4		39.0/38.3	38.7	2.9/3.1	3.0	-0.3/-0.4	-0.4	2.9/3.0	3.0	46/47 D								
R-134a	2.4	2.7	2.5		8.7/8.3	8.5	1.5/1.3	1.4	0.3/-0.1	0.1	1.5/1.3	1.4	50/51 D								
R-125	1.9	2.6	2.8		10.0/10.4	10.2	1.6/2.4	2.0	0.9/1.6	1.3	4.4/4.3	4.4	47/48 D								
R-143a	1.4	1.3	1.2		3.5/3.4	3.5	0.7/1.2	1.0	-0.1/-0.2	-0.2	1.1/1.1	1.1	49/50 D								
R-152a	3.5	3.0	2.8		7.2/7.1	7.2	1.1/1.4	1.2	-0.9/-0.4	-0.7	-0.3/-0.1	-0.2	51/52 D								
R-123	25.4	25.0	24.9		125/128	126	3.5/3.9	3.7	0.5/-0.7	-0.1	3.6/3.6	3.6	47/48 D								
R-142b	5.0	4.4	4.5		13.9/13.6	13.7	1.4/1.9	1.6	0/-0.2	-0.1	1.2/1.4	1.3	47/48 D								
R-134	5.7	5.1	5.2		18.8/18.1	18.4	2.1/1.8	2.0	0.4/0.1	0.3	1.3/1.5	1.4	52/53 D								
AB	0.8	-	1.3/1.7	1.5	2.7/3.1	2.9			0.9/1.3	1.1	2.7/3.0	2.9	51/52 D								
MO	0.9	-	1.9/2.0	2.0	4.6/4.7	4.7			1.8/2.4	2.1	4.6/4.7	4.7	49/50 D								
PEMA	0.6	-	1.9/1.8	1.9	5.2/5.4	5.3			1.9/1.7	1.8	5.1/5.2	5.2	47/48 D								
PEBA	0.8	-	1.8/1.6	1.7	4.0/4.2	4.1			2.1/1.2	1.6	4.1/4.3	4.2	49/50 D								
PPGD	1.2	-	1.9/2.0	2.0	5.1/4.8	5.0			1.8/2.0	1.9	5.2/5.0	5.1	49/50 D								
PPGBM	0.6	-	0.8/0.9	0.9	2.5/2.4	2.5			0.7/0.4	0.6	2.6/2.6	2.6	48/49 D								
MPG	0.3	-	0.6/0.5	0.6	1.4/1.5	1.5			-0.1/0.4	0.2	1.3/1.5	1.4	51/52 D								

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 54		Polyester TPE (72 Shore D)		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
								PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
						AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean	values	mean	
R-22	9.9	10.3	9.9		40.7/38.6	39.7	0.9/0.4	0.7	-0.4/-1.1	-0.8	1.0/1.2	1.1	50/51 D
R-32													
R-124	7.2	7.0	6.9		27.2/26.6	26.9	2.9/2.4	2.7	0.7/0.2	0.5	5.1/4.8	5.0	52/53 D
R-134a	1.2	1.9	2.0		7.7/7.5	7.6	1.3/1.4	1.4	0.1/0.6	0.4	2.9/3.1	3.0	54/55 D
R-125	0.4	2.1	2.2		7.4/7.8	7.6	1.8/1.3	1.6	0.8/1.1	1.0	4.6/4.7	4.7	54/55 D
R-143a	1.1	1.4	1.2		2.9/2.8	2.9	0.4		0.2/0.2	0.2	1.8/1.7	1.8	55/56 D
R-152a	3.1	2.6	2.6		6.8/6.5	6.7	0.9/1.2	1.1	0.1/0.3	0.2	1.2/0.5	5.4	55/56 D
R-123	14.7	15.4	16.4		74.4/80.5	77.5	4.1/4.1	4.1	1.2/0.6	0.9	7.4/7.9	7.7	55/56 D
R-142b	3.3	3.6	3.4		12.9/11.2	12.1	1.7/1.7	1.7	0.1/0.4	0.2	2.6/2.9	2.8	51/52 D
R-134	4.9	4.4	4.4		15.9/15.6	15.7	2.6/2.8	2.7	0.9/1.0	1.0	4.0/4.0	4.0	53/54 D
AB	0.3	-	0.7/1.0	0.9	2.0/2.1	2.1			0.6/0.5	0.6	1.7/2.0	1.9	54/55 D
MO	0.7	-	1.0/1.9	1.5	3.4/3.2	3.3			1.3/0.6	1.0	3.5/3.5	3.5	54/55 D
PEMA	0	-	1.2/1.2	1.2	3.4/3.6	3.5			0.8/0.8	0.8	3.4/3.4	3.4	52/53 D
PEBA	0	-	0.8/1.1	1.0	2.8/2.7	2.7			1.3/1.0	1.2	3.0/2.8	2.9	54/55 D
PPGD	0.6	-	1.4/1.0	1.2	3.5/3.6	3.6			1.1/2.4	1.5	3.7/4.2	4.0	54/55 D
PPGBM	0.3	-	0.5/0.6	0.6	1.8/1.6	1.7			0.4/0.6	0.5	1.6/1.6	1.6	54/55 D
MPG	-0.3	-	-0.1/0.5	0.2	0.9/1.0	1.0			-0.1/0.2	0.1	0.9/1.0	1.0	55/56 D

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 56		FA Polysulfide Rubber		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc oxide		10.00												PEBA - Pentaerythritol Ester Branched Acid	
		Stearic Acid		0.50												PPGBM - Polypropylene Glycol Butyl Monoether	
		2,2'-Benzothiazyl disulfide		0.40												MO - Mineral Oil	
		Diphenyl guanidine		0.10		MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene							
		2-mercapto imidazoline		0.10													
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22	3.5	4.4	3.8		12.3/12.3	12.3	1.3/-0.4	0.5	-0.8/-1.9	-1.4	-3.9/-3.6	-3.8	45/46 A				
R-32																	
R-124	-0.1	0.4	0.5		1.6/1.7	1.7	-0.4/0.3	-0.1	-0.6/-0.2	-0.4	-0.2/-4.4	-2.3	51/52 A				
R-134a	-0.7	-0.5	-0.4		-0.4/0.4	0	-0.8/0.3	-0.3	-1.1/-0.3	-0.7	-1.0/-0.5	-0.8	49/50 A				
R-125*	-0.1	0.3	0.6		0.5/1.0	0.8	-0.1/0.8	0.4	9.4/11.9	10.7	0.3/0.3	0.3	32/33 A				
R-143a	-0.2	0.3	0.1		-0.3/0.1	-0.1	-0.2/-0.1	-0.1	7.2/10.2	8.7	-0.7/-0.3	-0.5	36/37 A				
R-152a	0.5	1.0	0.5		1.0/1.5	1.3	1.4/0.1	0.7	2.3/-0.6	0.9	-1.8/-1.1	-1.5	47/48 A				
R-123	7.6	8.0	7.8		32.2/32.3	32.2	4.3/3.7	4.0	-0.6/-0.8	-0.7	6.1/6.3	6.2	49/50 A				
R-142b	0.5	0.7	1.0		2.3/2.7	2.5	-0.4/0.4	0	-0.5/-0.4	-0.5	0/0.3	0.2	49/50 A				
R-134	-0.5	0.5	0.6		2.7/2.8	2.8	-0.4/0.7	0.2	-0.9/0.1	-0.5	0.8/0.9	0.9	53/54 A				
AB	-0.3	-	-0.8/-0.9	-0.9	-3.9/-3.7	-3.8			-0.8/-1.4	-1.1	-4.7/-4.0	-4.4	57/58 A				
MO	0.4	-	-0.4/-0.2	-0.3	-1.8/-1.1	-1.5			-0.8/-0.3	-0.6	-2.2/-1.4	-1.8	44/45 A				
PEMA	-0.3	-	-3.0/-2.7	-2.9	-9.0/-8.3	-8.7			-3.3/-2.3	-2.8	-9.3/-8.6	-9.0	49/50 A				
PEBA	-0.6	-	-3.9/-3.1	-3.5	-10.8/-8.7	-9.7			-4.4/-3.7	-4.1	-10.8/-8.9	-9.8	47/48 A				
PPGD	0	-	-3.7/-2.4	-3.1	-11.2/-10.4	-10.8			-4.1/-4.0	-4.1	-11.6/-10.5	-11.0	48/49 A				
PPGBM	-1.9	-	-3.2/-4.1	-3.7	-8.6/-6.5	-7.6			-3.1/-3.7	-3.4	-9.5/-8.0	-8.7	49/50 A				
MPG	-1.1	-	-2.6/-2.5	-2.6	-8.4/-6.2	-7.3			-3.3/-2.5	-2.9	-9.1/-7.2	-8.2	46/47 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 57		FA Polysulfide Rubber		100.00		Lubricant Legend Information						PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc oxide		10.00								PEBA - Pentaerythritol Ester Branched Acid	
		Stearic acid		0.50								PPGBM - Polypropylene Glycol Butyl Monoether	
		2,2'-Benzothiazyl disulfide		0.40								MO - Mineral Oil	
		Diphenyl guanidine		0.10		MPG - Modified Polyglycol						PPGD - Polypropylene Glycol Diol	
		2-mercapto imidazoline		0.10								AB - Alkyl Benzene	
		IR B6 (Carbon Black)		60.00									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean	values	mean	
R-22	4.0	2.3	3.1		8.1/8.3	8.2	1.7/1.4	1.6	0.1/-0.6	-0.3	0.3/0.5	0.4	78/79 A
R-32													
R-124	0.1	0.2	0.3		0.9/1.2	1.1	0.1/0.1	0.1	-0.3/-0.4	-0.4	0.2/0.4	0.3	80/81 A
R-134a	-0.1	-0.1	0.1		-0.3/-0.1	-0.2	-0.2/-0.7	-0.5	-0.4/-0.5	-0.5	-0.4/-0.4	-0.4	81/82 A
R-125													
R-143a	-0.4	0.3	-0.1		-0.3/-0.2	-0.3	0.4/-0.1	0.2	-0.3/-0.1	-0.2	-0.2/-0.1	-0.2	80/81 A
R-152a	0.7	1.0	0.9		0.6/0.8	0.7	0.4/3.5	2.0	-0.3/3.1	1.4	-0.4/-0.5	-0.5	81/82 A
R-123	4.1	5.9	6.0		20.3/20.5	20.4	3.9/4.2	4.0	0.7/1.3	1.0	7.3/7.1	7.2	76/77 A
R-142b	0.2	0.6	0.5		1.6/1.9	1.8	0.5/0.4	0.4	-0.3/-0.3	-0.3	0.3/0.6	0.5	80/81 A
R-134	-0.1	0.9	1.7		1.2/1.4	1.3	0.3/0.2	0.3	-0.2/0.2	0	0.4/0.5	0.5	82/83 A
AB	-0.5	-	-0.9/-0.7	-0.8	-1.7/-1.7	-1.7			-1.0/-0.5	-0.8	-1.7/-1.7	-1.7	80/81 A
MO	-0.1	-	-0.5/-0.7	-0.6	-0.4/-0.2	-0.3			0.2/-0.5	-0.2	-0.7/-0.5	-0.6	80/81 A
PEMA	-0.5	-	-0.6/-1.4	-1.0	-1.5/-1.6	-1.6			-0.8/-0.9	-0.9	-2.0/-1.8	-1.9	79/80 A
PEBA	-0.7	-	-0.7/-0.8	-0.8	-1.5/-1.7	-1.6			-0.5/-1.0	-0.8	-2.2/-1.9	-2.0	81/82 A
PPGD	-0.6	-	-0.6/-0.5	-0.6	-1.7/-1.4	-1.6			-0.4/-0.7	-0.6	-1.8/-1.6	-1.7	81/82 A
PPGBM	-0.8	-	-1.0/-0.7	-0.8	-1.9/-1.3	-1.6			-0.9/-0.7	-0.8	-2.8/-2.2	-2.5	79/80 A
MPG	-0.8	-	-0.6/-0.7	-0.7	-2.4/-2.2	-2.3			-0.8/-1.2	-1.0	-2.8/-2.4	-2.6	83/84 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 58		ST Polysulfide Rubber		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc peroxide		5.00												PEBA - Pentaerythritol Ester Branched Acid	
		Stearic Acid		1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
		Calcium Hydroxide		1.00												MO - Mineral Oil	
																MPG - Modified Polyglycol	
								PPGD - Polypropylene Glycol Diol									
								AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22*	8.1	10.6	8.6		30.6/30.2	30.4	-3.1/-3.3	-3.2	-3.1/-3.1	-3.1	-10.2/-9.7	-10.0	41/42 A				
R-32																	
R-124	1.2	1.7	2.5		11.2/9.6	10.4	1.0/1.2	1.1	-1.3/-1.0	-1.2	1.9/2.0	2.0	41/42 A				
R-134a	-0.1	-0.1	-0.1		1.5/2.0	1.8	-0.7/0.3	-0.2	-0.9/-0.9	-0.9	-0.6/-0.4	-0.5	42/43 A				
R-125	-1.2	-0.1	0.2		1.8/2.4	2.1	8.6/7.8	8.2	-0.3/0.1	-0.2	0.1/0.6	0.3	31/32 A				
R-143a	0.1	0.2	0.3		0.8/0.9	0.9	6.9/7.8	7.4	0.1/-0.1	0	-1.0/-1.0	-1.0	37/38 A				
R-152a	2.1	2.3	1.6		3.7/4.0	3.9	0.1/0.1	0.1	-1.5/-1.6	-1.6	-1.9/1.9	-1.9	43/44 A				
R-123	59.1	57.6	56.0		330/321	325	12.8/12.1	12.4	-4.3/-4.3	-4.3	-4.9/-5.4	-5.1	43/44 A				
R-142b	1.3	2.3	2.1		6.5/7.1	6.8	0.7/0.9	0.8	-1.1/-0.7	-0.9	-0.2/0.6	0.2	42/43 A				
R-134	2.3	2.3	1.8		7.7/7.9	7.8	0.2/-15.8	-7.8	-1.9/-17.4	-9.7	-2.2/-1.9	-2.1	46/47 A				
AB	-0.5	-	-2.5/-2.5	-2.5	-9.0/-8.7	-8.9			-3.2/-3.2	-3.2	-9.4/-8.8	-9.1	47/48 A				
MO	-0.1	-	-1.8/-1.3	-1.6	-4.5/-2.8	-3.7			-1.6/-1.7	-1.7	-5.0/-3.4	-4.2	39/40 A				
PEMA	1.0	-	-3.9/-3.7	-3.8	-11.0/-10.5	-10.8			-4.4/-3.5	-4.0	-11.7/-11.2	-11.5	39/40 A				
PEBA	-1.2	-	-8.6/-8.2	-8.4	-24.7/-22.8	-23.7			-8.7/-8.0	-8.3	-25.3/-23.2	-24.3	47/48 A				
PPGD	1.6	-	-4.5/-3.9	-4.2	-24.7/-20.9	-22.8			-5.4/-3.9	-4.7	-24.9/-21.2	-23.1	44/45 A				
PPGBM	-0.7	-	-4.8/-4.8	-4.8	-12.3/-10.7	-11.5			-5.1/-4.5	-4.8	-13.5/-11.7	-12.6	42/43 A				
MPG	-1.0	-	-4.0/-2.9	-3.5	-11.3/-11.5	-11.4			-3.9/-4.1	-4.0	-11.5/-11.8	-11.7	48/49 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 59		ST Polysulfide Rubber		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc peroxide		5.00												PEBA - Pentaerythritol Ester Branched Acid	
		Stearic acid		1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
		Calcium Hydroxide		1.00												MO - Mineral Oil	
		IR B6 (Carbon Black)		60.00												MPG - Modified Polyglycol	
												PPGD - Polypropylene Glycol Diol					
												AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22	39.6	7.8	6.3		19.1/18.9	19.0	0.9/0.1	0.5	-1.1/-1.8	-1.5	-3.4/-3.4	-3.4	78/79 A				
R-32																	
R-124	1.3	2.2	1.4		5.1/5.4	5.3	1.0/1.0	1.0	0.1/-0.1	0	1.3/1.7	1.5	75/76 A				
R-134a	0.6	-0.1	0.1		0.9/1.1	1.0	-0.2/0.3	0.1	-0.4/-0.6	-0.5	-0.1/0.1	0	78/79 A				
R-125	-4.1	0.9	0.7		0.9/1.8	0.4	0.4/0.1	0.3	0.1/-0.1	0	0.5/0.8	0.7	77/78 A				
R-143a	0.2	0.3	0.3		0.3/0.3	0.3	-0.1/-0.1	-0.1	-0.2/-0.3	-0.3	-0.1/-0.1	-0.1	76/77 A				
R-152a	1.6	1.9	1.5		2.1/2.2	2.2	0.8/-0.2	0.3	-0.6/-0.7	-0.7	-0.6/-0.9	-0.8	80/81 A				
R-123	26.9	26.5	27.2		115/115	115	9.0/9.5	9.2	-1.2/-0.9	-1.0	2.7/2.6	2.6	78/79 A				
R-142b	0.8	1.7	1.6		3.4/3.3	3.4	0.4/0.5	0.5	-0.5/-0.5	-0.5	0.4/0.3	0.3	75/76 A				
R-134	0.8	2.1	1.6		4.9/4.8	4.9	0.6/0.7	0.7	0.1/0.4	0.3	1.2/1.5	1.4	79/80 A				
AB	-0.4	-	-0.9/-0.9	-0.9	-2.0/-2.3	-2.2			-1.0/-1.2	-1.1	-2.3/-2.2	-2.3	80/81 A				
MO	0.2	-	-0.5/-0.4	-0.5	-0.9/-0.5	-0.7			-0.8/-0.5	-0.7	-1.1/-0.7	-0.9	76/77 A				
PEMA	-0.3	-	-1.7/-1.4	-1.6	-3.4/-2.8	-3.1			-1.8/-1.4	-1.6	-3.7/-3.3	-3.5	80/81 A				
PEBA	-0.4	-	-1.7/-2.0	-1.9	-3.4/-4.0	-3.7			-1.7/-2.0	-1.8	-3.8/-4.1	-4.0	77/78 A				
PPGD	0.6	-	-0.5/-0.7	-0.6	-2.0/-1.3	-1.7			-0.7/-0.7	-0.7	-2.0/-5.0	-3.5	77/78 A				
PPGBM	-0.5	-	-2.0/-2.3	-2.2	-4.0/-2.4	-3.2			-2.5/-1.4	-2.0	-4.9/-3.8	-4.4	81/82 A				
MPG	-3.4	-	-2.2/-1.7	-2.0	-3.4/-3.1	-3.3			-1.8/-0.8	-1.3	-3.7/-3.2	-3.5	82/83 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula #61		Polyurethane (Ether-50 shore D)		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Moca-95% stoichiometry														PEBA - Pentaerythritol Ester Branched Acid	
																PPGBM - Polypropylene Glycol Butyl Monoether	
																MO - Mineral Oil	
																MPG - Modified Polyglycol	
																PPGD - Polypropylene Glycol Diol	
																AB - Alkyl Benzene	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			values	mean	values	mean	2 hr. Diameter (%)	values	mean	values	mean	1 Day Weight (%)		values	mean		
R-22	15.5	15.7	16.1		58.3/79.2	68.8	5.9/4.7	5.3	2.1/3.0	2.6	1.0/15.0	8.0	49/50 D				
R-32																	
R-124	11.5	12.7	13.0		59.9/58.1	59.0	7.5/8.2	7.9	3.6/4.7	4.2	18.0/19.0	18.5	47/48 D				
R-134a	1.0	2.0	2.0		10.1/8.9	9.5	1.8/1.8	1.8	1.4/1.7	1.6	6.1/6.5	6.3	47/48 D				
R-125	0.1	2.1	1.9		8.5/8.4	8.5	1.7/1.9	1.8	1.3/2.6	2.0	6.5/6.4	6.5	48/49 A				
R-143a	0.6	1.2	1.3		4.2/4.2	4.2	2.7/1.1	1.9	1.4/1.3	1.4	3.3/3.4	3.4	49/50 D				
R-152a	2.9	3.3	2.5		10.0/10.0	10.0	2.6/2.5	2.6	1.7/3.2	2.5	4.7/5.2	5.0	51/52 D				
R-123	28.9	29.0	30.6		168/173	170	14.6/14.3	14.4	5.7/6.3	6.0	29.2/26.9	28.0	45/46 D				
R-142b	2.8	5.9	5.1		19.4/19.2	19.3	4.5/6.7	5.6	2.5/3.6	3.0	10.4/9.4	9.9	48/49 D				
R-134	2.7	4.8	4.6		19.5/19.6	19.5	4.2/4.4	4.3	2.1/1.9	2.0	10.0/10.6	10.3	92/93 A				
AB	-0.3	-	0.4/1.2	0.8	2.0/1.8	1.9			0.2/0.8	0.5	1.6/1.5	1.6	51/52 D				
MO	0.1	-	1.8/1.4	1.6	2.9/3.9	3.4			0.5/1.6	1.1	3.0/4.0	3.5	52/53 D				
PEMA	0.2	-	2.0/0.8	1.4	2.5/2.9	2.7			0.8/1.7	1.3	2.4/3.0	2.7	51/52 D				
PEBA	0.5	-	0.9/0.9	0.9	2.2/2.6	2.4			0.9/-0.4	0.2	2.5/2.8	2.6	49/51 D				
PPGD	0.7	-	3.8/4.5	4.2	12.4/13.9	13.2			4.8/4.3	4.6	12.7/14.2	13.5	41/42 D				
PPGBM	0.2	-	1.0/1.3	1.2	2.6/2.9	2.8			0.7/0.4	0.6	2.8/3.1	3.0	52/52 D				
MPG	-0.4	-	0.3/0.1	0.2	1.2/0.9	1.1			-0.4/-0.1	-0.3	1.3/1.0	1.2	53/56 D				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 65		Polyurethane (Millable-Ether based)		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid			
		Moca- 95% stoichiometry																PEBA - Pentaerythritol Ester Branched Acid	
																		PPGBM - Polypropylene Glycol Butyl Monoether	
																		MO - Mineral Oil	
												MPG - Modified Polyglycol							
												PPGD - Polypropylene Glycol Diol							
												AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness						
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)								
			values	mean	values	mean	values	mean	values	mean	values	mean							
R-22*	48.0	48.0	46.9		246/235	240	-1.6/-0.5	-1.1	-3.2/-2.1	-2.7	-6.5/-6.7	-6.6	48/49 A						
R-32																			
R-124	52.7	52.9	51.4		343/325	334	5.8/6.7	6.3	-2.5/-1.5	-2.0	1.7/1.2	1.5	46/47 A						
R-134a	5.4	5.6	5.3		19.9/19.9	19.9	2.3/2.4	2.4	-0.4/-0.3	-0.4	1.2/1.2	1.2	50/51 A						
R-125	7.2	7.0	6.8		26.4/26.9	26.7	4.0/4.8	4.4	0.7/0.6	0.7	6.0/6.6	6.3	49/50 A						
R-143a	2.8	2.7	2.7		9.2/9.3	9.3	0.7/0.1	0.4	-0.2/-0.7	-0.5	0.1/0.2	0.2	49/50 A						
R-152a	7.2	6.7	6.9		21.3/21.6	21.5	1.9/1.7	1.8	-1.1/-1.1	-1.1	-1.4/-1.2	-1.3	50/51 A						
R-123	96.2	98.8	103		917/920	918	13.2/13.1	13.1	-3.6/-2.2	-2.9	-1.9/-1.7	-1.8	50/51 A						
R-142b	15.5	15.8	15.2		61.2/59.4	60.3	3.9/3.4	3.6	-0.5/-1.5	-1.0	1.3/1.7	1.5	50/51 A						
R-134	10.0	9.0	10.3		52.2/48.6	50.4	-0.2/1.6	0.7	-2.1/-1.4	-1.8	-1.3/-1.3	-1.3	51/52 A						
AB	6.6	-	9.7/9.8	9.8	24.7/25.2	25.0			8.1/8.5	8.3	22.9/23.3	23.1	38/39 A						
MO	9.0	-	7.8/8.7	8.3	26.0/27.0	26.5			7.3/7.3	7.3	22.6/22.7	22.7	43/44 A						
PEMA	22.9	-	27.3/27.4	27.4	100/98.9	99.6			23.7/24.3	24.0	89.8/88.7	89.3	30/31 A						
PEBA	8.9	-	17.5/18.7	18.1	60.8/58.9	59.2			16.3/18.4	17.3	55.8/55.6	55.7	33/34 A						
PPGD	23.5	-	48.2/48.5	48.4	216/216	216			44.5/45.4	45.0	209/210	210	14/15 A						
PPGBM	22.7	-	32.8/31.0	31.9	126/121	123			30.8/29.8	30.3	124/119	121	19/20 A						
MPG	4.3	-	11.1/10.6	10.9	36.0/36.0	36.0			10.2/10.7	10.5	36.0/36.2	36.1	40/41 A						

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 66		Polyurethane (Millable-Ester Based)		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
		Moca-95% stoichiometry						PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			values	mean	values	mean	values	mean	values	mean		values	mean
R-22	36.9	34.4	34.8		147/117	132	0.1/-0.6	-0.3	-2.8/-2.0	-2.4	-3.9/-4.1	-4.0	76/77 A
R-32													
R-124	33.7	35.2	35.8		169/145	157	5.4/5.8	5.6	-1.0/-0.5	-0.8	3.9/5.2	4.6	72/73 A
R-134a	3.2	3.0	3.1		10.8/11.0	10.9	1.9/1.1	1.5	0.1/-0.3	-0.1	3.1/2.9	3.0	74/75 A
R-125	1.2	2.2	2.3		8.7/9.3	9.0	2.0/2.1	2.1	0.6/0.1	0.4	4.4/4.9	4.7	72/73 A
R-143a	0.2	1.0	1.1		2.7/2.8	2.8	-0.1/0.1	0	-0.5/-0.5	-0.5	1.5/1.7	1.6	76/77 A
R-152a	4.5	4.3	4.2		10.5/11.0	10.8	1.3/1.1	1.2	-1.4/-0.3	-0.9	0.7/0.8	0.8	76/77 A
R-123	61.9	59.4	63.9		360/360	360	6.0/4.3	5.1	0.5/-1.1	-0.3	5.3/3.9	4.6	71/72 A
R-142b	4.6	4.1	3.7		12.1/12.3	12.2	1.6/2.3	2.0	0.9/0.6	0.7	3.5/3.7	3.6	74/75 A
R-134	18.8	19.2	19.6		79.1/75.7	77.4	5.5/4.3	4.9	0.1/0.1	0.1	3.9/3.5	3.7	73/74 A
AB	-0.2	-	-0.4/-0.8	-0.6	-1.2/-1.1	-1.2			-1.1/-1.0	-1.1	-1.0/-1.0	-1.0	79/80 A
MO	-0.5	-	-1.1/-0.1	-0.6	-0.8/-0.4	-0.6			-1.3/-0.3	-0.8	-0.3/-0.2	-0.3	32/32 D
PEMA	-0.7	-	-0.1/-0.8	-0.5	-0.1/0	-0.1			-0.4/-0.7	-0.6	-0.2/0.2	0	31/32 D
PEBA	-0.2	-	-0.4/-0.6	-0.5	-0.2/-0.2	-0.2			-1.0/0.3	-0.4	-0.1/0	-0.1	33/35 D
PPGD	1.4	-	5.5/6.1	5.8	13.8/14.5	14.2			5.1/5.9	5.5	14.4/15.2	14.8	64/65 A
PPGBM	-0.4	-	-0.4/-0.6	-0.5	-1.0/-0.9	-1.0			-1.3/-0.6	-1.0	-0.7/-0.5	-0.6	32/32 D
MPG	-0.8	-	-1.0/0	-0.5	-1.6/-1.6	-1.6			-0.9/-0.9	-0.9	-1.3/-1.3	-1.3	32/33 D

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 68		Chlorosulfonated polyethylene		100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid					
		Litharge		25.00						PEBA - Pentaerythritol Ester Branched Acid					
		Benzothiazyl disulfide		0.50						PPGBM - Polypropylene Glycol Butyl Monoether					
		Sulfur		2.00						MO - Mineral Oil					
						MPG - Modified Polyglycol									
						PPGD - Polypropylene Glycol Diol									
						AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness		
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)				
			values	mean	values	mean	values	mean	values	mean	values	mean			
R-22	9.1	8.6	8.2		27.8/27.9	27.9				2.0/2.0	2.0	5.9/6.7	6.3	58/59 A	
R-32															
R-124	1.1	1.4	3.5		12.7/12.8	12.8	2.7/2.8	2.8	1.7/2.3	2.0	1.7/2.3	2.0	1.7/2.3	2.0	55/56 A
R-134a	0.3	0.3	1.2		3.5/3.2	3.4	0.7/0.9	0.8	0.7/0.9	0.8	2.1/2.0	2.1	2.1/2.0	2.1	
R-125	0.7	0.9	1.2		3.5/2.8	3.2	1.2/1.0	1.0	0.9/1.0	1.0	3.2/2.5	2.9	3.2/2.5	2.9	55/56 A
R-143a	1.0	1.4	2.2		5.0/4.9	5.0			1.7/1.4	1.6	4.0/4.0	4.0	4.0/4.0	4.0	55/56 A
R-152a	1.8	3.0	3.5		8.3/8.4	8.4	1.5/3.3	2.4	1.0/2.4	1.7	4.5/4.5	4.5	4.5/4.5	4.5	56/57 A
R-123	18.6	18.9	18.7		75.2/75.0	75.1	13.3/12.6	13.0	5.2/5.0	5.1	21.6/21.5	21.5	21.6/21.5	21.5	53/54 A
R-142b	3.6	6.0	6.1		17.7/17.9	17.8			3.3/3.6	3.5	10.0/10.1	10.1	10.0/10.1	10.1	54/55 A
R-134	0.5	0.9	1.5		4.7/4.8	4.6	2.2/1.3	1.8	2.1/1.2	1.7	3.5/3.7	3.6	3.5/3.7	3.6	57/58 A
AB	3.2	-	7.6/7.3	7.5	15.5/15.5	15.5			7.5/7.3	7.4	15.7/15.7	15.7	15.7/15.7	15.7	52/53 A
MO	4.3	-	12.2/12.1	12.2	29.0/28.5	28.8			12.1/12.0	12.1	28.1/27.9	28.0	28.1/27.9	28.0	49/50 A
PEMA	10.0	-	23.2/23.0	23.1	64.0/64.0	64.0			22.9/22.7	22.8	63.9/63.6	63.8	63.9/63.6	63.8	43/44 A
PEBA	-0.6	-	15.5/15.3	15.4	40.0/39.0	40.0			15.6/14.9	15.2	40.2/39.3	39.8	40.2/39.3	39.8	46/47 A
PPGD	1.7	-	3.5/3.2	3.4	7.5/7.3	7.4			3.4/5.1	4.3	7.4/7.3	7.4	7.4/7.3	7.4	54/55 A
PPGBM	0.3	-	1.5/1.7	1.6	3.7/3.7	3.7			1.5/1.7	1.6	3.4/3.5	3.5	3.4/3.5	3.5	55/56 A
MPG	0.1	-	0.3/0.2	0.3	1.1/1.1	1.1			0.1/0.1	0.1	0.9/0.9	0.9	0.9/0.9	0.9	59/60 A

* indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 69		Chlorosulfonated polyethylene (Cl 35%, S 1.0%)		100.00		Labrificant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid									
		Magnesia		4.00												PEBA - Pentaerythritol Ester Branched Acid									
		Pentaerythritol		3.00												PPGBM - Polypropylene Glycol Butyl Monoether									
		Dipentamethylenethiuram hexasulfide		2.00												MO - Mineral Oil									

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 70	Chlorosulfonated polyethylene				100.00		Lubricant Legend Information	PEMA - Pentaerythritol Ester Mixed Acid							
	Litharge				20.00			PEBA - Pentaerythritol Ester Branched Acid							
	Benzothiazyl disulfide				0.50			PPGBM - Polypropylene Glycol Butyl Monoether							
	Dipentamethylenethiuram hexasulfide				0.75			MO - Mineral Oil							
	Magnesia				10.00			MPG - Modified Polyglycol							
Nickel Dibutyldithiocarbamate				3.00		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness				
			values		mean		values		mean			1 Day Diameter (%)		1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean		
R-22	7.8	7.2	7.3		23.2/23.1	23.2				0.3/0.9	0.6	2.8/3.6	3.2	52/53 A	
R-32															
R-124	0.9	1.7	3.0		11.1/11.1	11.1		3.7/2.6	3.2	2.9/2.6	2.8	2.9/2.6	2.8	50/51 A	
R-134a	-0.1	0	0.9		3.6/3.5	3.6		0.3/0.5	0.4	0.1/0.1	0.1	2.1/2.1	2.1		
R-125	1.1	1.2	1.3		3.8/3.8	3.8		1.5/1.5	1.5	1.1/1.1	1.1	3.4/3.4	3.4	53/54 A	
R-143a	0.7	1.3	1.9		4.4/4.2	4.3				1.2/1.2	1.2	3.4/3.3	3.4	51/52 A	
R-152a	1.7	3.0	3.1		7.6/7.5	7.6		2.3/1.9	2.1	1.0/1.2	1.1	3.9/3.7	3.8	52/53 A	
R-123	17.9	17.8	17.5		71.2/71.3	71.2		10.8/11.5	11.2	3.5/3.2	3.4	17.1/16.4	16.8	46/47 A	
R-142b	3.9	5.9	5.7		16.6/16.8	16.7				2.2/2.5	2.4	7.9/8.3	8.1	50/51	
AR-134	0.4	0.6	0.8		4.5/4.2	4.4		0.1/0.4	0.3	0.4/0.7	0.6	3.0/3.2	3.1	53/54 A	
AB	3.5	-	8.2/7.9	8.1	17.4/17.8	17.6				8.5/7.0	7.8	17.6/17.9	17.8	41/42 A	
MO	2.6	-	12.2/11.3	11.8	34.9/26.5	30.7				12.2/12.0	12.1	34.2/25.9	30.1	37/38 A	
PEMA	14.0	-	34.3/31.4	32.9	107/99.1	103				33.0/31.2	32.1	107/99.0	103	21/22 A	
PEBA	8.1	-	25.9/25.0	25.5	73.3/71.6	72.2				25.3/25.0	25.1	73.7/71.4	72.5	27/28 A	
PPGD	0.7	-	1.8/2.2	2.0	4.9/5.4	5.2				1.4/1.6	1.5	4.9/5.4	5.2	51/52 A	
PPGBM	1.1	-	1.5/1.3	1.4	2.7/2.9	2.8				1.3/0.1	0.7	2.5/2.7	2.6	49/50 A	
MPG	-0.1	-	-0.2/-0.1	-0.2	0.7/0.8	0.8				-1.2/-1.2	-1.2	0.5/0.7	0.6	52/53 A	

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 71			Chlorosulfonated polyethylene		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
			Litharge		25.00												PEBA - Pentaerythritol Ester Branched Acid	
			2,2'-Benzothiazyl disulfide		0.50												PPGBM - Polypropylene Glycol Butyl Monoether	
			Dipentamethylenethiuram		2.00												MO - Mineral Oil	
																	MPG - Modified Polyglycol	
							PPGD - Polypropylene Glycol Diol											
							AB - Alkyl Benzene											
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness					
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)							
			values	mean	values	mean	values	mean	values	mean	values	mean						
R-22	7.8	8.0	8.8		26.6/26.5	26.6	6.3/2.1	4.2	2.6/1.2	1.9	7.4/7.3	7.4						
R-32																		
R-124	2.9	3.7	5.1		21.1/4.9	13.0	5.0/1.0	3.0	4.5/1.0	2.8	18.8/2.9	10.9	61/62 A					
R-134a	0.1	0	0.6		2.2/2.3	2.3	-0.6/0.7	0.1	0.4/-0.1	0.1	1.6/1.7	1.7						
R-125	0.5	0.4	1.0		2.4/2.5	2.5	0.6/0.8	0.7	0.5/0.8	0.7	2.1/2.1	2.1	63/64 A					
R-143a	-0.1	0.5	0.7		2.3/2.2	2.3	0.5/0.2	0.4	0.5/0.3	0.4	1.7/1.7	1.7						
R-152a	-0.6	0.6	-1.8		-1.6/13.7	6.1	0.2/3.5	1.9	-0.5/3.1	1.3	-4.4/10.6	3.1	63/64 A					
R-123	16.8	17.6	16.5		68.5/68.3	68.4	11.6/11.0	11.3	6.0/6.4	6.2	24.0/23.1	23.6	62/63 A					
R-142b	3.1	5.1	5.7		17.0/17.0	17.0	5.0/5.1	5.1	3.2/3.2	3.2	10.7/10.4	10.6	61/62 A					
R-134	0.1	0.7	-0.4		4.0/4.0	4.0	0.7/0.9	0.8	0.4/0.6	0.5	3.0/3.0	3.0	62/63 A					
AB	1.1	-	4.3/4.6	4.5	9.4/10.1	9.8			3.7/4.2	4.0	8.7/9.8	9.3	61/62 A					
MO	3.9	-	9.2/9.5	9.4	22.5/23.5	23.0			8.5/9.2	8.9	22.1/23.0	22.6	57/58 A					
PEMA	4.7	-	17.7/20.3	19.0	50.0/53.6	51.8			18.4/20.7	19.6	49.9/53.4	51.7	55/56 A					
PEBA	2.5	-	10.6/11.6	11.1	27.2/28.8	28.0			10.9/11.7	11.3	26.9/28.6	27.7	55/56 A					
PPGD	0.7	-	1.9/1.8	1.9	5.2/4.9	5.1			1.7/1.2	1.5	4.8/4.7	4.8	60/61 A					
PPGBM	0.9	-	1.4/1.4	1.4	3.7/3.6	3.7			1.4/1.3	1.4	3.4/3.5	3.5	63/64 A					
MPG	0.2	-	0.3/-2.5	-1.1	1.6/1.4	1.5			-0.1/-0.2	-0.2	1.0/0.9	1.0	62/63 A					

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 72	EP Rubber		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid						
	Dicumyl Peroxide		3.00				PEBA - Pentaerythritol Ester Branched Acid						
							PPGBM - Polypropylene Glycol Butyl Monoether						
							MO - Mineral Oil						
						MPG - Modified Polyglycol							
						PPGD - Polypropylene Glycol Diol							
						AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			values	mean	values	mean	values	mean	2 hr. Diameter (%)	1 Day Diameter (%)		1 Day Weight (%)	
R-22*	6.0	6.0	5.9		27.6/26.9	27.3	11.1/10.9	11.0	-0.5/-0.5	-0.5	-1.1/-0.7	-0.9	
R-32													
R-124	2.8	3.0	2.7		19.1/18.2	18.7	0.5/0.4	0.5	-1.2/-0.9	-1.1	-0.2/0.1	-0.1	
R-134a	1.8	2.3	3.4		10.3/5.6	8.0	1.7/0.9	1.3	1.7/1.1	1.4	5.0/1.7	3.4	
R-125*	3.3	3.3	2.8		9.2/7.6	8.4	3.8/2.7	3.3	1.9/0.5	1.2	4.9/3.6	4.3	
R-143a*	1.4	1.5	0.9		4.1/3.7	3.9	0.9/1.9	1.4	-0.2/0	-0.1	-1.5/-1.8	-1.7	
R-152a	1.0	1.0	1.1		5.8/5.0	5.4	-0.2/-0.1	-0.2	-1.3/-1.4	-1.4	-2.0/-2.1	-2.1	43/44 A
R-123	15.9	16.1	16.2		105/105	105	4.2/3.6	3.9	-0.9/-1.2	-1.1	1.9/0.3	1.1	44/45 A
R-142b	7.5	7.4	7.6		31.7/31.7	31.7	4.8/4.0	4.4	-0.8/-0.5	-0.7	0.1/0.8	0.5	
R-134	0.6	0.6	0.1		3.5/3.4	3.5	-0.6/0.2	-0.2	-0.6/-0.3	-0.5	-0.3/-0.2	-0.3	45/46 A
AB	58.9	-	70.7/72.8	71.7	434/425	429			69.6/68.8	69.2	430/422	426	78 A
MO	66.2	-	83.4/83.3	83.4	560/534	547			79.3/82.6	81.0	553/532	542	67 A
PEMA	3.1	-	3.2/3.1	3.2	12.7/12.6	12.7			1.9/2.8	2.4	11.9/11.9	11.9	33/34 A
PEBA	3.2	-	3.2/2.6	2.9	12.1/12.3	12.2			3.3/2.2	2.7	11.2/11.3	11.2	34/35 A
PPGD	0.1	-	0.2/-0.1	0.1	0.4/0.3	0.3			-0.4/-0.4	-0.4	0.1/0.1	0.1	36/37 A
PPGBM	0.7	-	0.4/0.4	0.4	1.5/1.6	1.6			-0.6/0.1	-0.3	1.3/1.2	1.3	36/37 A
MPG	-0.2	-	-0.5/-0.1	-0.3	-0.3/0.4	0.1			-0.9/-0.5	-0.7	-0.5/0.1	-0.4	36/37 A

Formula # 73		EP Rubber		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
		Dicumyl Peroxide		3.00				PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
						MPG - Modified Polyglycol							
						PPGD - Polypropylene Glycol Diol							
						AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid.				1 Day Shore A/D Hardness		
			Change (%)		Change (%)		Values Based On Original Sample Measurements.						
			values	mean	values	mean	2 hr. Diameter (%)	1 Day Diameter (%)	1 Day Weight (%)	values		mean	
R-22	4.5	4.4	4.5		19.5/19.3	19.4	1.4/1.1	1.3	-1.5/-0.6	-1.1	-1.2/0.2	-0.5	
R-32													
R-124	2.1	2.4	2.4		10.8/11.3	11.1	0.4/0.6	0.5	0/-0.2	-0.1	-0.3/0.1	-0.2	
R-134a	0.9	1.1	0.8		2.0/1.3	1.7	-0.2/0.2	0	0.1/-0.1	0	-1.1/-1.1	-1.1	
R-125	2.2	2.1	2.1		7.8/6.7	7.3	1.5/1.5	1.5	1.5/1.2	1.4	4.9/4.0	4.5	
R-143a	1.3	1.3	1.2		2.7/2.6	2.7	0.9/0.5	0.7	0.8/0.5	0.7	-1.1/-1.0	-1.1	
R-152a	1.1	1.1	1.2		4.3/3.8	4.1	-1.1/-0.4	-0.8	-1.2/-1.0	-1.1	-1.5/-1.5	-1.5	66/67 A
R-123	9.1	9.0	9.0		52.1/52.2	52.2	2.7/2.5	2.6	-0.7/-0.9	-0.8	0.1/0.7	0.4	67/68 A
R-142b	4.9	4.9	4.8		19.8/19.5	19.7	3.0/2.9	3.0	-0.3/-0.2	-0.3	0.5/1.1	0.8	
R-134	0.3	0.6	0.9		2.5/2.4	2.5	0.3/-0.7	-0.2	-0.6/-1.0	-0.8	-0.1/0	-0.1	69/70 A
AB	41.0	-	49.7/48.4	49.1	231/232	232			47.2/44.5	45.9	279/219	249	28/29 A
MO	53.6	-	58.2/59.3	58.8	314/317	315			57.4/56.7	57.1	309/310	310	22/23 A
PEMA	2.6	-	2.5/1.6	2.1	9.4/9.3	9.4			1.7/2.2	2.0	8.7/8.6	8.7	60/61 A
PEBA	2.5	-	2.8/2.4	2.6	9.6/9.8	9.7			2.2/2.3	2.3	8.7/8.8	8.7	62/63 A
PPGD	0.8	-	0.4/0.1	0.3	1.2/1.4	1.3			-0.4/-0.2	-0.3	0.6/1.0	0.8	63/64 A
PPGBM	1.3	-	1.1/0.4	0.7	2.9/1.3	2.1			0.5/-0.3	0.1	2.6/0.9	1.8	64/65 A
MPG	0.4	-	0.1/0	0.1	0.3/-0.1	0.1			-0.4/-0.5	-0.5	0.1/-0.3	-0.1	62/63 A

Formula # 74		EP Rubber		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
Dicumyl Peroxide		3.00		PEBA - Pentaerythritol Ester Branched Acid									
N330 Carbon Black		40.00		PPGBM - Polypropylene Glycol Butyl Monoether									
				MO - Mineral Oil									
				MPG - Modified Polyglycol									
				PPGD - Polypropylene Glycol Diol									
				AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean	values	mean	
R-22	2.7	2.8	2.6	13.0/13.2	13.1	1.2/0.6	0.9	-0.7/-0.6	-0.7	-0.6/-0.4	-0.5		
R-32													
R-124	1.1	1.2	1.2	7.1/7.4	7.3	-0.3/0.4	0.1	-0.6/-0.2	-0.4	-0.4/0.4	0		
R-134a	0.2	0.3	0.2	0.3/0.3	0.3	-0.6/-0.7	-0.7	-0.6/-0.7	-0.7	-1.1/-1.1	-1.1		
R-125	1.8	1.8	1.7	5.6/5.4	5.5	0.5/1.1	0.8	0.8/0.8	0.8	3.5/3.4	3.5		
R-143a	1.2	0.9	1.21	2.4/3.1	2.8	0.3/0.4	0.4	0/0.2	0.1	-0.3/0.5	0.1		
R-152a	0.6	0.3	0.5	2.9/3.0	3.0	-0.5/0.1	-0.2	-0.6/-0.3	-0.5	-1.4/-1.3	-1.4	82/83 A	
R-123	6.8	6.6	6.1	35.9/36.3	36.1	1.9/2.4	2.3	-0.6/0	-0.3	-0.3/0.4	0.1	81/82 A	
R-142b	3.5	3.4	3.3	13.6/13.3	13.5	1.4/1.9	1.7	-0.5/-0.5	-0.5	0.1/0.6	0.4		
R-134	0.3	0.6	-0.2	1.4/1.1	1.3	0.1/0.1	0.1	-0.4/-0.4	-0.4	-0.2/-0.3	-0.3	83/84 A	
AB	31.5	-	36.6/36.6	36.6	148/147			34.6/34.4	34.5	140/140	140	44/45 A	
MO	38.5	-	45.0/43.4	44.2	206/200			45.1/43.5	44.3	202/197	200	38/39 A	
PEMA	2.0	-	1.4/1.1	1.3	6.0/6.0			1.2/1.9	1.6	5.5/5.5	5.5	79/80 A	
PEBA	1.4	-	1.9/1.4	1.6	6.3/6.5			1.4/1.5	1.5	5.5/5.5	5.5	78/79 A	
PPGD	0.3	-	0.1/0.1	0.1	0.4/0.4			0.2/0	0.1	0.1/0	0.1	81/82 A	
PPGBM	-0.1	-	-0.2/0.4	0.1	0.8/0.9			0.2/0.1	0.2	0.7/0.8	0.8	81/82 A	
MPG	0.1	-	-0.6/-0.1	-0.4	-0.2/0.2	0		-0.3/-0.1	-0.2	-0.4/0.1	-0.2	81/82 A	

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 75		Ethylene Acrylic Elastomer		100.00		Lubricant Legend Information						PEMA - Pentaerythritol Ester Mixed Acid		
		Methylene Diamine		1.00								PEBA - Pentaerythritol Ester Branched Acid		
		Diphenylguanidine		3.20								PPGBM - Polypropylene Glycol Butyl Monoether		
												MO - Mineral Oil		
										MPG - Modified Polyglycol				
										PPGD - Polypropylene Glycol Diol				
										AB - Alkyl Benzene				
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness	
			values mean		values mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)			
							values	mean	values	mean	values	mean		
R-22*	78.6	77.5	77.4		116/334	225			4.2/-3.2	-3.7	-10.7/-10.3	-10.5	41/42 A	
R-32														
R-124*	88.8	87.3	86.3		603/564	585		74.4/70.1	72.3	-2.5/-2.7	-2.6	-2.5/-2.7	-2.6	38/39 A
R-134a*	11.9	11.9	12.3		50.7/49.6	50.2		3.3/5.3	4.3	1.6/2.8	2.2	3.2/3.6	3.4	
R-125*	16.9	17.0	16.7		74.2/73.9	74.1		5.5/3.0	4.3	1.6/1.8	1.7	4.0/5.0	4.5	36/37 A
R-143a	5.3	5.5	5.5		18.5/18.0	18.3				2.6/8.1	5.4	1.0/1.1	1.1	31/32 A
R-152a	14.4	14.3	14.2		46.4/44.9	45.7		4.6/4.8	4.7	-1.0/0.4	-0.3	1.8/2.3	2.1	37/38 A
R-123*	119	117	116		1209/1194	1202		7.5/5.9	6.7	-0.5/-2.0	-1.3	-4.1/-4.7	-4.4	33/34 A
R-142b	31.4	30.6	31.1		130/126	128				-0.6/0.5	-0.1	4.4/5.4	4.9	38/39 A
R-134	27.2	27.3	27.0		135/128	131		11.4/7.5	9.5	2.7/1.1	1.9	15.9/13.5	14.7	34/35 A
AB	8.1	-	14.2/14.3	14.3	40.9/41.2	41.1				12.6/13.0	12.8	40.7/41.3	41.0	24/25 A
MC	6.1	-	11.0/10.6	10.8	31.6/31.8	31.7				10.1/8.8	9.5	31.0/31.3	31.2	26/27 A
PEMA	38.8	-	54.7/54.7	54.7	260/257	259				51.2/51.4	51.3	257/255	256	13/14 A
PEBA	28.9	-	51.2/51.3	51.3	242/232	237				51.2/50.2	50.7	240/232	236	14/15 A
PPGD	37.5	-	50.9/50.8	50.9	237/235	236				46.8/46.1	46.5	232/228	230	14/15 A
PPGBM	22.0	-	47.8/46.5	47.2	208/204	206				46.6/44.1	45.4	207/201	204	14/15 A
MPG	19.1	-	49.4/40.5	45.0	221/180	201				45.7/38.6	42.2	219/180	200	14/15 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 76		Ethylene Acrylic Elastomer		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
		N 774		35.00												PEBA - Pentaerythritol Ester Branched Acid																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
		Methylene Dianiline		1.00												PPGBM - Polypropylene Glycol Butyl Monoether																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
		Diphenylguanidine		4.00												MO - Mineral Oil																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
																MPG - Modified Polyglycol																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
																PPGD - Polypropylene Glycol Diol																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
																AB - Alkyl Benzene																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
			values	mean	values	mean	values	mean	values	mean	values	mean	values	mean																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
R-22	47.2	46.0	46.7		183/164	174																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 78		Chlorinated PE		100.00		Lubricant Legend Information						PEMA - Pentaerythritol Ester Mixed Acid	
		Magnesium Dioxide		10.00								PEBA - Pentaerythritol Ester Branched Acid	
		Triallyl Isocyanurate		2.00								PPGBM - Polypropylene Glycol Butyl Monoether	
		Dicumyl Peroxide on Clay		4.00								MO - Mineral Oil	
		N330 Carbon Black		40.00								MPG - Modified Polyglycol	
												PPGD - Polypropylene Glycol Diol	
												AB - Alkyl Benzene	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean	values	mean	
R-22	4.7	4.2	4.5		18.6/18.4	18.5			0.8/1.2	1.0	4.0/3.8	3.9	78/79 A
R-32													
R-124	0	0.4	1.3		7.5/7.3	7.4	1.2/1.5	1.4	1.0/1.6	1.3	1.0/1.6	1.3	75/76 A
R-134a	0.2	0.3	0.6		2.2/2.0	2.1	0.5/0.1	0.3	0.4/-0.1	0.2	1.1/0.9	1.0	
R-125	0.0	0.3			2.2/2.1	2.2	1.1/1.0	1.1	0.7/0.2	0.5	1.8/1.8	1.8	81/82 A
R-143a	-0.1	0.2	0.5		1.7/1.8	1.8			1.1/0.9	1.0	1.2/1.3	1.3	81/82 A
R-152a	1.1	2.0	2.0		4.7/4.9	4.8	2.1/1.8	2.0	0.4/1.5	1.0	2.5/2.7	2.6	80/81 A
R-123	10.2	11.7	10.2		49.0/49.5	49.2	8.3/9.4	8.8	3.4/4.7	4.1	16.6/20.5	18.6	75/76 A
R-142b	1.0	3.5	3.8		12.6/12.6	12.6			1.3/2.5	1.9	7.0/7.1	7.1	74/75 A
R-134	0.1	0.2	0.4		1.7/2.2	2.0	-0.1/0.5	0.2	-0.8/-0.2	-0.5	1.8/1.8	1.8	82/83 A
AB	1.8	-	6.4/6.5	6.5	14.5/14.8	14.7			5.9/6.9	6.4	14.6/15.0	14.8	70/71 A
MO	3.1	-	9.9/9.4	9.7	25.8/25.4	25.6			9.6/9.0	9.3	25.2/24.9	25.1	70/71 A
PEMA	5.7	-	14.2/13.8	14.0	42.0/40.8	41.4			14.2/13.0	13.6	41.8/41.0	41.04	65/66 A
PEBA	2.1	-	11.1/10.7	10.9	31.6/30.2	30.9			11.4/11.0	11.2	32.0/31.0	32.0	66/67 A
PPGD	0.6	-	1.3/1.6	1.5	4.0/4.1	4.1			1.9/1.4	1.7	4.6/4.6	4.6	78/79 A
PPGBM	0.2	-	1.0/1.0	1.0	2.1/2.0	2.1			-0.1/-0.6	-0.3	1.9/1.7	1.8	78/79 A
MPG	0.4	-	-0.1/-0.1	-0.1	0.1/0.1	0.1			-1.1/0.1	-0.5	-0.1/-0.1	-0.1	83/84 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 79		Chlorinated Polyethylene		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid							
		Magnesium Oxide		10.00				PEBA - Pentaerythritol Ester Branched Acid							
		Triallyl Isocyanurate		2.00				PPGBM - Polypropylene Glycol Butyl Monoether							
		Dicumyl peroxide		8.00				MO - Mineral Oil							
								MPG - Modified Polyglycol							
						PPGD - Polypropylene Glycol Diol									
						AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness				
			values		mean		values		mean			1 Day Diameter (%)		1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean		
R-22	5.4	5.3	5.0		18.6/18.8	18.7	2.2/3.0	2.6	0.6/0.9	0.8	5.2/6.4	5.8	64/65 A		
R-32															
R-124	0.6	0.8	0.8		4.2/3.7	4.0	1.1/0.8	1.0	0.8/0.5	0.7	4.1/3.6	3.9	62/63 A		
R-134a	0.1	-0.1	-0.1		0.5/0.9	0.7	-0.7/-0.5	-0.6	-0.4/0.1	-0.2	0.9/1.0	1.0	68/69 A		
R-125	-0.1	0.6	0.8		1.9/2.5	2.2	0.4/0.4	0.4	0.8/0.5	0.7	1.5/1.5	1.5	69/70 A		
R-143a	-0.1	0.4	0.3		0.6/0.6	0.6	0.7/-0.3	0.2	0.3/-0.3	0	1.2/1.3	1.3	67/68 A		
R-152a	1.4	1.9	2.3		5.1/6.2	5.7	1.6/2.2	1.9	1.0/1.1	1.1	3.6/4.5	4.1	63/64 A		
R-123	9.8	10.2	9.8		47.2/46.2	46.7	7.7/7.2	7.4	3.5/3.7	3.6	20.7/19.0	19.8	55/56 A		
R-142b	1.7	2.6	3.4		12.7/13.3	13.0	2.9/3.0	3.0	1.6/3.0	2.3	9.7/10.6	10.2	59/60 A		
R-134	-0.1	0.5	0.5		2.4/2.1	2.2	-0.5/0.4	-0.1	-0.1/-0.1	-0.1	2.0/1.9	2.0	69/70 A		
AB	1.2	-	5.0/4.2	4.6	11.7/10.7	11.2			3.6/3.7	3.7	11.4/10.5	11.0	61/62 A		
MO	-1.2	-	5.6/5.7	5.7	14.3/15.8	15.1			5.7/5.7	5.7	13.0/14.7	13.9	62/63 A		
PEMA	8.3	-	31.7/34.5	33.1	119/131	125			28.4/34.9	31.7	119/131	125	35/36 A		
PEBA	6.6	-	23.2		78.2				20.7		74.4		36/37 A		
PPGD	0.2	-	0/0.7	0.4	2.0/2.1	2.1			0.8/-0.4	0.2	1.9/1.9	1.9	66/67 A		
PPGBM	-6.3	-	-0.2/-0.2	-0.2	1.3/1.0	1.2			-0.3/0.4	0.1	-0.1/0	-0.1	70/71 A		
MPG	-0.2	-	-0.7/-1.6	-1.2	-1.5/-1.4	-1.5			-2.1/-1.7	-1.9	-1.8/-1.5	-1.7	74/75 A		

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 80		EPDM (High Ethylene Content)		100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid		
		Zinc Oxide		5.00						PEBA - Pentaerythritol Ester Branched Acid		
		Sulfur		1.50						PPGBM - Polypropylene Glycol Butyl Monoether		
		Stearic Acid		1.00						MO - Mineral Oil		
		TMTD		1.00		MPG - Modified Polyglycol				PPGD - Polypropylene Glycol Diol		
		MBT		0.50						AB - Alkyl Benzene		
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness	
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean	values	mean
R-22	3.9	4.3	3.8		16.7/16.0	16.4	0.9		-0.3/-1.1	-0.7	-1.2/-1.5	-1.4
R-32												
R-124	1.7	2.2	2.1		10.2/10.6	10.4	1.1/2.2	1.7	0.5		2.4/2.5	2.5
R-134a	0.5		0.6		2.4/2.5	2.5	-0.3		-0.5/-0.3	-0.4	0.1/0.1	0.1
R-125	2.3	2.9	2.8		9.0/9.0	9.0	2.5		2.2/1.2	1.7	6.3/5.8	6.1
R-143a	1.0	0.9	0.7		2.7/2.4	2.6	-0.1		0/-0.5	-0.3	-0.1/-0.1	-0.1
R-152a	1.1	1.0	0.9		4.0/3.6	3.8	0.1		-1.2/-0.5	-0.9	-0.7/-0.6	-0.7
R-123	7.9	8.8	8.8		46.5/46.4	46.5	3.6		0.2/1.0	0.6	5.1/5.9	5.5
R142b	3.7	3.6	3.9		15.3/15.5	15.4	0.9		-0.4/0.7	0.2	0.3/0.4	0.4
R-134	0.5	0.8	0.6		2.6/2.5	2.6	-0.6/-0.4	-0.5	-0.6/-0.7	-0.7	0.4/0.8	0.6
AB	30.3	-	35.8/35.6	35.7	142/141	142			34.8/34.8	34.8	130/130	130
MO	37.6	-	42.4/42.2	42.3	186/185	186					181/181	181
PEMA	2.7	-	2.3/2.3	2.3	7.1/7.4	7.3			1.0/1.4	1.2	5.8/6.0	5.9
PEBA	1.9	-	2.3/2.4	2.4	8.2/8.0	8.1					6.9/6.7	6.8
PPGD	0.3	-	0.2/0	0.1	0.1/0.2	0.2					-0.1/-0.1	-0.1
PPGBM	0.9	-	0.2/0.6	0.4	1.5/1.6	1.6			-0.1/0.4	0.2	0.6/0.7	0.7
MPG	-0.1	-	-0.2/-0.3	-0.3	0.2/0.1	0.2			-0.7/-0.5	-0.6	-0.4/-0.4	-0.4
												73/74 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 81		EPDM (High Unsaturation)		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
		Zinc Oxide		5.00				PEBA - Pentaerythritol Ester Branched Acid					
		Sulfur		1.50				PPGBM - Polypropylene Glycol Butyl Monoether					
		Stearic Acid		1.00				MO - Mineral Oil					
		TMTD		1.00		MPG - Modified Polyglycol							
		MBT		0.50		PPGD - Polypropylene Glycol Diol							
						AB - Alkyl Benzene							
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
							2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean
R-22	5.5	5.3	5.0		24.3/23.8	24.1	3.4		-1.0/-0.2	-0.6	-1.6/-1.6	-1.6	
R-32													
R-124	3.1	3.8	3.5		15.5/19.1	17.3	2.5/2.7	2.6	0.8		2.0/5.4	3.7	
R-134a	0.9		0.7		3.7/3.8	3.8	-0.4		0.1/0.3	0.2	0.2/0.4	0.3	
R-125	3.8	3.6	3.6		11.5/10.9	11.2	3.3		3.1/0.9	2.0	7.8/6.7	7.3	
R-143a	1.1	1.2	1.0		5.0/4.5	4.8	0.3		-0.2/0	-0.1	4.3/0.1	2.2	
R-152a	1.4	1.6	1.6		5.6/5.9	5.8	1.1		-0.3/-0.7	-0.5	-0.4/-0.4	-0.4	
R-123	14.6	14.6	14.5		79.3/79.6	79.5	4.0		0.8/0.9	0.9	5.8/6.2	6.0	
R-142b	6.3	6.3	6.1		25.5/25.3	25.4	2.5		-0.2/0.1	-0.1	0.5/0.8	0.7	
R-134	0.3	0.8	-0.6		4.1/3.6	3.9	0.3/0.2	0.3	-0.5/-0.6	-0.6	0.5/0.6	0.6	56/57 A
AB	28.5	-	35.6/37.1	36.4	149/148	148			37.0/36.4	36.7	149/149	149	
MO	32.0	-	41.7/42.6	42.2	188/188	188					183/184	184	
PEMA	2.6	-	3.2/3.2	3.2	10.6/10.6	10.6			2.3/1.8	2.1	8.1/8.2	8.2	
PEBA	2.2	-	3.4/3.3	3.4	11.1/10.9	11.0					9.0/8.9	9.0	
PPGD	0.5	-	-0.6/-0.1	-0.4	0.3/0.6	0.5					0.1/0.1	0.1	
PPGBM	0.5	-	-0.3/0.6	0.2	2.2/2.4	2.3			-0.2/-0.3	-0.3	1.0/1.1	1.1	
MPG	0.3	-	0.2/0.2	0.2	0.8/0.7	0.8			-0.1/-0.5	-0.3	0.2/0.2	0.2	55/56 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 82		EPDM		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc Oxide		5.00												PEBA - Pentaerythritol Ester Branched Acid	
		Sulfur		1.50												PPGBM - Polypropylene Glycol Butyl Monoether	
		Stearic Acid		1.00												MO - Mineral Oil	
		TMTD		1.00				MPG - Modified Polyglycol		PPGD - Polypropylene Glycol Diol		AB - Alkyl Benzene					
		MBT		0.50													
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			values mean		values mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
R-22	4.4	4.9	4.5	19.0/18.5	18.8	2.5/4.2	3.4	-0.5/-0.3	-0.4	-1.9/-1.8	-1.9						
R-32																	
R-124	2.2	2.5	2.5	12.5/12.1	12.3	1.7/2.3	2.0	-0.2/-0.2	-0.2	2.2/1.9	2.1						
R-134a	0.3	0.3	0.2	2.9/2.9	2.9	0.2/0.5	0.4	-0.5/-0.3	-0.4	0.4/0.1	0.3						
R-125	2.6	3.5	3.3	10.6/9.5	10.1	3.3		2.5/1.1	1.8	7.5/6.3	6.9						
R-143a	0.8	0.7	0.6	3.4/3.4	3.4	-0.2		0.1/-0.9	-0.4	0/-0.4	-0.2						
R-152a	1.3	1.3	1.3	4.0/5.2	4.6	0.2		-1.0/-0.2	-0.6	-1.0/-0.8	-0.9						
R-123	10.0	9.8	9.6	56.4/56.2	56.3	4.1		0.7/0.6	0.7	4.5/3.4	4.0						
R-142b	4.9	5.0	5.1	19.5/19.1	19.3	2.6		0.1/-0.3	-0.1	-0.5/-0.3	-0.4						
R-134	0.6	0.9	0.6	2.9/2.6	2.8	-0.2/0.1	-0.1	1.1/-0.6	0.3	0.1/0.1	0.1	70/71 A					
AB	28.4	-	35.1/34.9	143/143	143			36.4/35.3	36.0	138/138	138						
MO	35.9	-	41.9/41.8	184/186	185					180/181	181						
PEMA	2.8	-	2.4/2.3	7.4/7.4	7.4			1.0/1.5	1.3	5.9/5.9	5.9						
PEBA	1.5	-	2.2/2.3	8.0/8.0	8.0					6.6/6.3	6.5						
PPGD	0.2	-	0.2/-0.4	0.1/0	0.1					-0.1/-0.1	-0.1						
PPGBM	0.4	-	-0.5/1.1	1.6/1.6	1.6			-0.3/0.5	0.1	0.5/0.7	0.6						
MPG	0.2	-	0.1/-0.1	0.2/0.1	0.2			-0.5/-0.8	-0.7	-0.3/-0.3	-0.3	64/65 A					

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 83		EPDM		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid				
		Zinc Oxide		5.00						PEBA - Pentaerythritol Ester Branched Acid		
		Sulfur		1.50								
		Stearic Acid		1.00								
		TMTD		1.00								PPGBM - Polypropylene Glycol Butyl Monoether
MBT		0.50										
N330 Carbon Black		40.00		MO - Mineral Oil								
						MPG - Modified Polyglycol						
								PPGD - Polypropylene Glycol Diol				
				AB - Alkyl Benzene								
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness	
			values	mean	values	mean	2 hr. Diameter (%)	values	mean	1 Day Diameter (%)		values
R-22	3.1	3.4	2.8		11.3/11.2	11.3	1.5		-0.2/-0.5	-0.4	-1.0/-1.0	-1.0
R-32												
R-124	1.3	1.8	1.5		7.1/7.1	7.1	0.6/1.9	1.3	-0.2		2.0/1.9	2.0
R-134a	0.2		0.7		1.5/1.7	1.6	0.2		0.6/0.2	0.4	0.1/0	0.1
R-125	1.7	2.6	2.5		7.4/7.4	7.4	1.5		5.8/1.1	3.5	0.7/10.2	5.5
R-143a	0.8	0.6	0.4		2.1/1.9	2.0	-0.2		0.0/0.8	0.4	0/-0.1	-0.1
R-152a	1.0	1.0	0.8		3.5/2.6	3.1	0.6		-0.4/-0.5	-0.5	-0.7/-0.5	-0.6
R-123	6.5	6.3	6.5		32.6/32.4	32.5	2.6		0.6/0.4	0.5	3.3/3.9	3.6
R-142b	3.8	3.8	3.4		11.1/10.9	11.0	1.0		0.3/-0.8	-0.3	0.2/0.3	0.3
R-134	0.3	-0.3	0.7		1.4/2.0	1.7	0.3/-0.1	0.2	0.1/-0.2	-0.1	0.2/0.3	0.3
AB	20.6	-	26.8/25.3	26.1	85.8/85.6	85.7			24.0/23.6	23.8	77.7/77.3	77.5
MO	25.9	-	29.4/29.8	29.6	113/112	113					110/109	110
PEMA	0.6	-	1.3/1.5	1.4	5.3/5.3	5.3			0.8/1.1	1.0	4.3/4.3	4.3
PEBA	1.5	-	1.8/1.5	1.7	5.4/5.7	5.6					4.3/4.7	4.5
PPGD	0.3	-	0.4/0.5	0.5	0.3/0.2	0.3					0.1/0.1	0.1
PPGBM	0.6	-	1.1/0	0.6	1.3/1.2	1.3			0.4/-0.2	0.1	0.6/0.7	0.7
MPG	0.1	-	0.2/0.1	0.2	0.1/0.2	0.2			-0.4/-0.2	-0.3	-0.3/-0.3	-0.3
												86/87

• Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 84		EPDM		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
		Zinc Oxide		5.00												PEBA - Pentaerythritol Ester Branched Acid	
		Stearic Acid		1.00												PPGBM - Polypropylene Glycol Butyl Monoether	
		Sicunyl Peroxide		1.00												MO - Mineral Oil	
												MPG - Modified Polyglycol					
												PPGD - Polypropylene Glycol Diol					
												AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
			values		mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean							
			values	mean	values	mean	values	mean	values	mean							
R-22	4.3	4.3	4.0		19.7/19.8	19.8	0.9/1.3	1.1	-1.3/-0.7	-1.0	-0.5/-0.2	-0.4					
R-32																	
R-124	2.4	2.5	2.4		12.8/12.3	12.6	0.7/0.8	0.8	-0.4/-0.2	-0.3	1.0/-0.2	0.4					
R-134a	0.5	0.6	0.6		2.2/2.2	2.2	0.5/1.2	-0.4	0.5/1.0	-0.3	0.1/0	0.1					
R-125	2.6	3.1	2.7		9.8/8.7	9.3	1.1/1.6	1.4	1.6/1.8	1.7	6.6/5.7	6.2					
R-143a	0.7	0.8	0.8		3.2/3.1	3.2	-0.6/0	0.3	-1.6/-0.3	-1.0	-0.2/-0.2	-0.2					
R-152a	1.3	1.1	1.2		4.5/4.2	4.4	0.1/0.3	0.2	-0.7/-0.8	-0.8	-0.8/0.8	0	68/67 A				
R-123	9.9	10.1	9.9		55.4/55.5	55.5	3.2		-0.6/15.8	7.6	2.8/2.9	2.9	67/68 A				
R-142b	4.7	4.7	4.4		19.1/18.6	18.9	2.2/2.5	2.4	-1.2/-1.2	-1.2	0.5/0.6	0.6					
R-134	0.6	0.9	0.8		3.3/3.2	3.3	0.3/0.2	0.3	-0.1/-0.1	-0.1	0.4/0.5	0.5	69/70 A				
AB	48.5	-	59.0/59.5	59.3	28.5/28.6	28.6			54.7/56.6	55.7	278/280	279	17/18 A				
MO	61.8	-	72.8/72.3	72.6	41.2/40.3	40.8			71.4/70.5	71.0	410/402	406	13/14 A				
PEMA	3.0	-	2.6/2.5	2.6	8.7/6.8	7.8			1.6/1.0	2.3	8.3/6.3	7.3	64/65 A				
PEBA	0.5	-	2.6/2.6	2.6	9.8/9.8	9.8			2.6/1.9	2.3	9.0/9.1	9.1	64/65 A				
PPGD	0.8	-	0.5/1.0	0.7	1.9/1.8	1.9			-1.1/-1.0	-1.1	1.4/1.5	1.5	66/67 A				
PPGBM	1.0	-	0.7/0.9	0.8	2.5/2.4	2.5			0/0	0	2.3/2.2	2.3	66/67 A				
MPG	0.5	-	0.1/0.2	0.2	0.9/0.8	0.9			0.2/-0.9	-0.4	0.7/0.6	0.7	67/68 A				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 85		Butyl/Polypropylene TPE		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
								PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			values	mean	values	mean	2 hr. Diameter (%)	1 Day Diameter (%)	1 Day Weight (%)	values		mean	
R-22	-0.4	-2.2	-2.8		-3.2/-2.7	-3.0	-5.5/-4.2	-4.9	-5.7/-5.4	-5.6	-17.5/-16.9	-17.2	70/71 A
R-32													
R-124	0.4	-0.2	-1.8		-0.7/0.7	0	-2.9/-2.4	-2.7	-3.5/-2.8	-3.2	-7.8/-6.4	-7.1	
R-134a	0.2	0.3	0.3		2.7/2.7	2.7	-0.7/2.4	0.9	-0.7/3.1	1.2	1.1/1.2	1.2	
R-125	1.8	2.0	2.3		10.0/8.3	9.2	1.0/0.9	1.0	1.6/0.9	1.3	7.3/6.0	6.7	
R-143a	0.3	0.3	0.5		3.2/3.8	3.5	0.2/0	0.1	-0.3/-0.2	-0.3	-0.1/0.4	0.2	
R-152a	-0.3	-0.7	-1.4		-1.5/0.1	-0.8	-1.7/1.5	-0.1	-2.2/1.9	-0.2	-6.0/-4.9	-5.5	66/67 A
R-123	2.1	1.9	2.4		33.7/33.7	33.7	-3.5/-3.5	-3.5	-5.7/-5.7	-5.7	-12.6/-12.4	-12.5	70/71 A
R-142b	0.3	-1.2	-2.4		-1.2/-0.8	-1.0	-3.3/-3.9	-3.6	-5.3/-6.0	-5.7	-15.4/-14.8	-15.1	
R-134	0.4	0.8	0.7		3.4/3.2	3.3	0.5/-0.2	0.2	-0.1/-0.3	-0.2	1.1/1.1	1.1	62/63 A
AB	11.9	-	20.5/20.9	20.7	87.4/85.1	86.3			22.0/18.5	20.3	87.1/84.6	85.9	36/37 A
MO	16.7	-	25.7/25.1	25.4	114/112	113			22.5/26.3	24.4	113/111	112	36/37 A
PEMA	-2.6	-	-2.9/-2.9	-2.9	-6.4/-6.1	-6.3			-2.7/-3.3	-3.0	-7.0/-6.9	-7.0	64/65 A
PEBA	-2.0	-	-3.2/-3.5	-3.4	-6.4/-6.1	-6.2			-3.7/-3.1	-3.4	-7.4/-7.0	-7.2	63/64 A
PPGD	-2.8	-	-5.7/-5.5	-5.6	-15.9/-15.7	-15.8			-6.2/-5.8	-6.0	-16.4/-16.1	-16.3	68/69 A
PPGBM	-2.4	-	-5.8/-5.4	-5.6	-15.7/-14.5	-15.1			-5.6/-5.5	-5.6	-15.8/-14.5	-15.2	68/69 A
MPG	-1.6	-	-4.9/-4.8	-4.9	-14.7/-14.9	-14.8			-5.6/-5.3	-5.5	-15.1/-15.1	-15.1	68/69 A

• Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 86			Precision Rubber Products #2167			Lubricant Legend Information			PEMA - Pentaerythritol Ester Mixed Acid					
									PEBA - Pentaerythritol Ester Branched Acid					
									PPGBM - Polypropylene Glycol Butyl Monoether					
									MO - Mineral Oil					
									MPG - Modified Polyglycol					
									PPGD - Polypropylene Glycol Diol					
									AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid.				1 Day Shore A/D Hardness			
			14 Day Diameter Change (%)		14 Day Weight Change (%)		Values Based On Original Sample Measurements.							
			values	mean	values	mean	2 hr. Diameter (%)	1 Day Diameter (%)	1 Day Weight (%)	values		mean		
R-22	0.3	-0.6	-0.8		2.1/2.3	2.2			-4.6/-4.7	-4.7	-10.8/-10.2	-10.5	84/85 A	
R-32														
R-124	1.3	0.8	-1.3		2.6/3.0	2.8		-2.7/2.3	-2.5	-3.8/-4.0	-3.9	-3.8/-4.0	-3.9	79/80 A
R-134a	-0.6	-1.5	-2.6		-4.8/-4.8	-4.8		-2.4/-2.5	-2.5	-2.9/-2.8	-2.9	-7.6/-7.4	-7.5	
R-125	-0.3	-0.9	-2.2		-4.0/-4.0	-4.0		-2.4/-2.2	-2.3	-2.7/-2.5	-2.6	-5.0/-4.8	-4.9	75/76 A
R-143a	-0.8	-1.6	-2.5		-5.2/-5.2	-5.2				-3.4/-3.1	-3.3	-6.6/-6.5	-6.6	80/81 A
R-152a	-1.3	-2.0	-3.1		-5.2/-5.2	-5.2		-3.6/-3.3	-3.5	-4.9/-5.8	-5.4	-9.1/-8.9	-9.0	86/87 A
R-123	5.7	5.5	4.9		24.1/23.7	23.9		-0.4/-0.4	-0.4	-4.0/-4.2	-4.1	-6.9/-7.4	-7.2	80/81 A
R-142b	0.1	-1.2	-1.5		92.2/107	99.4				-3.2/-5.5	-4.4	-7.8/-9.9	-8.9	81/82 A
R-134	-0.9	-1.2	-2.0		-1.9/-1.4	-1.7		-2.3/-2.1	-2.2	-2.8/-3.0	-2.9	-4.2/-4.6	-4.4	78/79 A
AB	2.3	-	3.4/3.6	3.5	6.1/6.1	6.1				2.7/3.2	3.0	6.3/6.2	6.3	63/64 A
MO	2.8	-	5.8/3.7	4.8	12.1/12.0	12.1				5.7/5.0	5.4	11.5/11.1	11.3	60/61 A
PEMA	6.4	-	8.7/8.9	8.8	21.1/21.0	21.1				9.0/8.8	8.9	20.9/20.9	20.9	58/59 A
PEBA	1.7	-	6.2/6.4	6.3	14.9/14.8	14.8				5.8/5.0	5.4	15.2/15.2	15.2	60/61 A
PPGD	-0.7	-	-0.6/-0.6	-0.6	-0.2/-0.2	-0.2				-0.3/-0.7	-0.5	0.4/0.5	0.5	72/73 A
PPGBM	-0.7	-	1.3/1.3	1.3	2.9/3.0	3.0				1.8/0.4	1.1	2.7/2.7	2.7	68/69 A
MPG	-2.4	-	0.7/-1.9	-0.6	-3.5/-3.0	-3.3				-2.2/-2.3	-2.3	-3.5/-3.2	-3.4	77/78 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 87		Precision Rubber Products #7507		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
								PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)		
			values	mean	values	mean	values	mean	values	mean	values	mean	
R-22	23.8	23.7	23.9		118/106	112			-1.7/-2.1	-1.9	-5.5/-5.1	-5.3	73/74 A
R-32													
R-124	21.1	21.1	20.5		111/101	106	5.0/4.5	4.8	-0.5/-1.0	-0.8	-0.5/-1.0	-0.8	70/71 A
R-134a	1.7	1.6	1.3		6.7/7.1	6.9	0.6/0.4	0.5	-0.3/-0.6	-0.5	-2.6/-2.1	-2.4	
R-125	1.9	2.5	2.1		8.2/8.9	8.5	1.4/2.1	1.8	0.5/0.6	0.6	4.0/4.0	4.0	70/71 A
R-143a	0.7	1.3	1.3		2.6/2.7	2.7			0.3/-0.1	0.1	0.2/0.2	0.2	69/70 A
R-152a	3.3	2.8	2.6		8.0/8.0	8.0	1.2/0.4	0.8	-1.4/-2.2	-1.8	-4.6/-4.2	-4.4	74/75 A
R-123	42.5	40.7	39.9		239/237	238	7.0/7.2	7.1	-0.4/-0.4	-0.4	4.2/3.5	3.9	70/71 A
R-142b	5.1	3.9	3.8		16.4/17.0	16.7			-1.1/-1.0	-1.1	-2.6/-1.9	-2.3	70/71 A
R-134	7.1	7.1	6.8		29.6/30.0	29.8	3.1/3.3	3.2	-0.3/-0.6	-0.5	1.1/1.5	1.3	73/74 A
AB	-0.3	-	0.1/0.1	0.1	-0.7/-0.9	-0.8			2.0/-0.6	0.7	-0.3/-0.3	-0.3	74/75 A
MO	0.4	-	1.0/1.2	1.1	1.7/2.0	1.9			0.6/1.1	0.9	1.4/1.6	1.5	71/72 A
PEMA	1.5	-	4.0/4.1	4.1	11.3/11.2	11.3			3.5/4.4	4.0	11.0/11.0	11.0	68/69 A
PEBA	0.9	-	3.1/3.0	3.1	8.0/7.9	8.0			3.2/2.6	2.9	8.3/8.3	8.3	68/69 A
PPGD	1.2	-	1.9/1.6	1.8	4.3/4.3	4.3			1.4/1.3	1.4	5.1/5.2	5.2	70/71 A
PPGBM	-0.6	-	-0.6/-0.8	-0.7	-2.6/-2.3	-2.5			-0.6/-0.7	-0.7	-3.0/-2.7	-2.9	72/73 A
MPG	-0.7	-	-1.5/-1.7	-1.6	-4.7/-4.5	-4.6			-1.5/-1.8	-1.7	-4.8/-4.6	-4.7	74/75 A

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 89		Armstrong N-8092		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
								PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean
R-22	0	-0.1	-0.4		58.1/31.8	44.9	0.5/0.7	0.6	0.6/0.8	0.7	-0.5/-0.5	-0.5	
R-32													
R-124	0.1	0.2	0.2		69.6/28.1	48.9	0.8/-0.4	0.2	0.8/0.2	0.5	1.7/-2.1	-0.2	57/58 D
R-134a	0.3	0.3	-0.1		37.3/19.0	28.2	-0.1/0.1	0	0.4/0.6	0.5	-0.1/-0.1	-0.1	
R-125	0.2	0.2	0.2		3.7/2.0	2.9	-0.3/0.1	-0.1	-0.2/-0.8	-0.5	0.8/1.4	1.1	54/55 D
R-143a	-0.3	0.4	0.2		13.5/2.4	8.0	-0.3/0.3	0	-0.3/0.3	0	-0.2/-0.2	-0.2	
R-152a	0.2	0.4	0.2		23.5/9.4	16.5	-0.1/0.1	0	-0.2/-0.1	-0.2	-2.6/1.1	-0.8	63/64 D
R-123	0.4	0.5	0		95.6/95.6	95.6	0.2/0.2	0.2	0.2/0.3	0.3	-1.0/-1.0	-1.0	57/58 D
R-142b	0.4	-0.1	-0.1		35.7/29.4	32.6	0.8/0.2	0.5	0.1/0.4	0.3	-0.4/-0.3	-0.4	58/59 D
R-134	0.3	0.1	0.1		48.8/30.7	39.8	0.4/0.1	0.3	-0.1/-0.8	-0.5	-0.3/-0.4	-0.4	57/58 D
AB	2.5	-	2.1/0.4	1.3	22.2/20.9	21.6			2.4/0.4	1.4	20.4/19.7	20.1	55/56 D
MO	-0.2	-	-0.4/0.1	-0.2	24.3/23.6	24.0			-0.4/-0.1	-0.2	22.1/19.7	20.9	54/55 D
PEMA	-0.2	-	-0.1/0.2	-0.1	27.9/26.8	27.4			0.8/-0.7	0.1	27.6/26.7	27.2	49/50 D
PEBA	0.2	-	-0.2/-0.2	-0.2	27.2/27.9	27.6			-0.1/-0.1	-0.1	26.5/27.5	27.0	49/50 D
PPGD	-0.6	-	0.1/-0.2	-0.1	33.9/34.6	34.3			0.4/-0.1	0.2	30.2/30.4	30.3	46/47 D
PPGBM	-0.4	-	-0.2/-0.1	-0.1	26.4/27.7	27.1			-0.1/0.1	0	26.0/27.4	26.7	47/48 D
MPG	-0.4	-	-0.5/-0.2	-0.4	29.1/27.1	28.1			0.1/-0.1	0	28.7/26.2	27.5	50/51 D

Formula # 90		Specialty Paperboard NI-2085G		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid			
																		PEBA - Pentaerythritol Ester Branched Acid	
																		PPGBM - Polypropylene Glycol Butyl Monoether	
																		MO - Mineral Oil	
										MPG - Modified Polyglycol									
										PPGD - Polypropylene Glycol Diol									
										AB - Alkyl Benzene									
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness						
			values	mean	values	mean	2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)								
							values	mean	values	mean	values	mean							
R-22	0.1	0.1	-0.6		70.4/21.4	45.9	-0.1/-0.7	-0.4	0.5/-0.4	0.1	-2.0/-2.0	-2.0							
R-32																			
R-124	0.6	1.0	0.8		39.4/17.6	28.5	0/-0.1	-0.1	0.3/-0.1	0.1	-8.6/-0.1	-4.4	54/55 D						
R-134a	0	0.1	-0.1		17.5/0.6	9.1	-0.5/-0.1	-0.3	0.1/-0.1	0	-0.3/-0.2	-0.3							
R-125	-0.1	-0.1	0.1		13.7/2.2	8.0	-0.6/-0.4	-0.5	-0.7/-0.2	-0.5	1.1/1.0	1.1	54/55 D						
R-143a	-0.1	0.1	-0.3		7.2/0.8	4.0	-0.6/0.5	-0.1	-0.4/0.4	0	-0.3/-0.3	-0.3							
R-152a	0.3	0.3	0.1		27.2/-1.2	13.0	-0.1/-0.5	-0.3	-0.3/-0.2	-0.3	6.4/-2.5	2.0	62/63 D						
R-123	0.5	0	0.6		121/135	128	0.3/0	0.2	0/0.2	0.1	-3.4/-3.6	-3.5	50/51 D						
R-142b	-0.3	0.2	0.1		20.1/14.1	17.1	-0.1/0.2	0.1	-0.1/0.1	0	-0.9/-0.6	-0.8	58/59 D						
R-134	0.5	-	-0.2		32.0/9.1	20.6	0.1/0.1	0.1	-0.5/-0.9	-0.7	-0.5/-0.6	-0.6	54/55 D						
AB	-0.1	-	-0.5/0.1	-0.2	17.6/12.3	15.0			-0.8/-0.2	-0.5	16.7/16.4	16.6	56/57 D						
MO	-0.4	-	-0.2/-0.1	-0.1	17.9/22.2	20.1			0.1/-0.1	0	17.6/21.8	19.7	53/54 D						
PEMA	-0.2	-	0.1/-0.2	-0.1	26.7/28.8	27.8			0.2/-0.2	0	24.0/27.1	25.6	49/50 D						
PEBA	0.1	-	-0.2/-0.3	-0.3	23.6/23.7	23.7			0.2/-0.5	-0.2	23.0/22.7	22.9	49/50 D						
PPGD	0.1	-	0.1/-0.1	0	22.8/27.8	25.3			0.2/0.6	0.4	22.8/28.1	25.5	49/50 D						
PPGBM	-0.4	-	-0.1/-0.2	-0.1	22.8/19.6	21.2			-0.6/0.4	-0.1	22.1/19.6	21.0	48/49 D						
MPG	-1.0	-	-0.5/0.1	-0.2	22.6/22.0	22.3			-0.8/0.3	-0.3	22.3/21.5	21.9	53/54 D						

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 91		Victopac 69		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
																PEBA - Pentaerythritol Ester Branched Acid	
																PPGBM - Polypropylene Glycol Butyl Monoether	
																MO - Mineral Oil	
																MPG - Modified Polyglycol	
																PPGD - Polypropylene Glycol Diol	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness				
							2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)						
			values	mean	values	mean	values	mean	values	mean	values	mean					
R-22	23.0	23.1	23.0		11.9/4.4	8.2	22.6/0.2	11.4	22.3/0.2	11.3	-0.2/-0.3	-0.3					
R-32																	
R-124	-2.8	-2.1	-2.9		7.9/15.7	11.8	-2.7/2.3	-0.2	-3.2/2.4	-0.4	-5.3/4.7	-0.3	64/65 D				
R-134a	-0.1	-0.1	-0.2		9.3/5.3	7.3	-0.5/-0.2	-0.4	-1.5/-0.1	-0.8	-0.1/-0.1	-0.1					
R-125	0.1	0.3	0.1		1.9/1.0	1.5	-0.6/-0.9	-0.8	-0.6/-0.7	-0.7	0.8/0.8	0.8	63/64 D				
R-143a	-0.2	0	-0.2		7.0/1.9	4.5	0.3/-0.4	-0.1	-1.0/-0.2	-0.6	-0.1/-0.1	-0.1					
R-152a	2.9	3.1	2.6		15.2/-0.4	7.4	2.0/-2.8	-0.4	2.4/-3.0	-0.3	5.2/-4.8	2.0	63/64 D				
R-123	0.5	0.7	0.7		19.0/19.1	19.1	0.1/-0.1	0	-0.1/-0.1	-0.1	-0.2/-0.2	-0.2	64/65 D				
R-142b	0.5	0.4	0.4		12.1/11.4	11.8	-0.1/-0.3	-0.2	-0.3/-0.6	-0.5	-0.2/-0.2	-0.2	64/65 D				
R-134	0.1	0.5	0.1		13.5/11.4	12.4	-0.7/-0.8	-0.8	13.5/-0.4	6.6	-0.1/0.1	0	65/66 D				
AB	0.5	-	0.5/0.5	0.5	12.4/12.1	12.3			0.3/0.2	0.3	11.6/11.4	11.5	56/57 D				
MO	0.7	-	0.7/0.5	0.6	13.2/13.7	13.5			0.4/0.4	0.4	12.8/13.4	13.1	56/57 D				
PEMA	0.4	-	0.7/0.5	0.6	14.8/14.6	14.7			0.4/0.5	0.5	14.3/14.4	14.4	53/54 D				
PEBA	0.9	-	0.6/4.1	2.4	14.1/14.4	14.2			0.7/0.5	0.6	13.6/13.7	13.6	52/53 D				
PPGD	0.5	-	0.4/0.5	0.5	13.1/12.6	12.9			0.4/-0.1	0.2	12.6/12.4	12.5	55/56 D				
PPGBM	1.0	-	0.6/6.2	3.4	13.5/13.4	13.5			0.1/5.9	3.0	12.8/12.6	12.7	53/54 D				
MPG	0.5	-	0.3/0.5	0.4	12.0/12.4	12.2			0.4/0.5	0.5	11.5/11.9	11.7	54/55 D				

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 92		Klingsil C-4401		100.00		Lubricant Legend Information		PEMA - Pentaerythritol Ester Mixed Acid					
								PEBA - Pentaerythritol Ester Branched Acid					
								PPGBM - Polypropylene Glycol Butyl Monoether					
								MO - Mineral Oil					
								MPG - Modified Polyglycol					
								PPGD - Polypropylene Glycol Diol					
								AB - Alkyl Benzene					
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.				1 Day Shore A/D Hardness		
							2 hr. Diameter (%)		1 Day Diameter (%)			1 Day Weight (%)	
			values	mean	values	mean	values	mean	values	mean		values	mean
R-22	4.0	2.8	1.9		30.3/13.2	21.8	-0.1/-0.1	-0.1	-0.5/-0.9	-0.7	-0.5/-0.5	-0.5	
R-32													
R-124	1.8	1.9	1.8		30.2/16.5	23.4	-0.4/-0.4	-0.4	-0.6/-0.1	-0.4	-0.8/-0.5	-0.7	63/64 D
R-134a	-0.1	0.5	0.1		8.5/4.5	6.5	-0.6/-0.5	-0.6	-0.1/-0.5	-0.3	-0.2/-0.1	-0.2	
R-125	0.5	0.4	0.1		2.5/1.7	2.1	0.1/-1.1	-0.5	-0.1/-0.7	-0.4	0.7/0.8	0.8	62/63 D
R-143a	0.6	0.2	0.4		3.8/1.4	2.6	-0.4/-0.3	-0.4	-0.2/-0.1	-0.2	-0.1/-0.1	-0.1	
R-152a	0.9	0.9	0.8		8.8/3.2	6.0	0.4/-0.6	-0.1	-0.3/-0.7	-0.5	0.1/-0.1	0	63/64 D
R-123	5.0	0.4	4.4		53.5/54.9	54.2	0.4/-0.3	0.1	1.0/-0.1	0.5	-0.6/-0.6	-0.6	62/63 D
R-142b	7.2	7.0	1.0		11.8/11.1	11.5	-0.4/-0.3	-0.4	-0.2/-0.9	-0.6	-0.4/-0.3	-0.4	64/65 D
R-134	0.4	1.0	0.8		14.2/11.9	13.0	-0.6/-0.8	-0.7	-0.6/-0.3	-0.5	-0.8/0.4	-0.2	66/67 D
AB	0.6	-	0.2/0.5	0.4	7.5/6.9	7.2			-0.1/-0.3	-0.2	6.6/6.7	6.7	59/60 D
MO	0.5	-	0.4/0.6	0.5	10.6/10.5	10.6			-0.1/0.7	0.3	8.3/8.7	8.5	57/58 D
PEMA	1.1	-	-0.8/1.2	0.2	11.7/11.5	11.6			0.5/0.7	0.6	10.8/10.7	10.8	47/48 D
PEBA	0.5	-	0.7/0.5	0.6	10.2/10.3	10.3			-0.1/-0.3	-0.2	9.7/9.6	9.7	53/54 D
PPGD	0.8	-	0.7/-1.0	-0.2	9.9/10.3	10.1			-0.1/0.1	0	9.8/10.0	9.9	50/51 D
PPGBM	0.3	-	0.1/0.1	0.1	9.7/9.1	9.4			0.1/-0.4	-0.2	9.0/8.7	8.9	52/53 D
MPG	0.7	-	0.3/0.2	0.3	8.8/9.0	8.9			-0.1/-0.2	-0.2	8.3/8.6	8.5	55/56 D

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula #93		Specialty Paperboard NI-2099			100.00		Lubricant Legend Information				PEMA - Pentaerythritol Ester Mixed Acid										
		PEBA - Pentaerythritol Ester Branched Acid																			
		PPGBM - Polypropylene Glycol Butyl Monoether																			
		MO - Mineral Oil																			
		MPG - Modified Polyglycol										PPGD - Polypropylene Glycol Diol									
		AB - Alkyl Benzene																			
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness								
			values mean		values mean		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)										
							values	mean	values	mean	values	mean									
R-22	0.6	0.6	0.6		22.1/0.8	11.5	-0.1/-0.2	-0.2	-0.6/-0.6	-0.6	-0.9/-0.8	-0.9									
R-32																					
R-124	0.4	0.4	0.4	0.4	36.0/14.0	25.0	-0.5/-0.1	-0.3	-0.4/-0.1	-0.3	-0.8/1.2	0.2	60/61 D								
R-134a	-0.1	0.3	0.3	0.1	15.1/1.2	8.2	-0.8/-0.9	-0.9	-0.2/-0.5	-0.4	-0.2/-0.2	-0.2									
R-125	0.3	0.4	0.4	0.1	1.8/1.2	1.5	-0.4/-0.6	-0.5	-0.4/-0.3	-0.4	0.5/0.9	0.7	62/63 D								
R-143a	-0.4	-2.7	-2.7	-0.3	1.2/0.6	0.9	-0.7/-0.1	-0.4	-0.6/-0.8	-0.7	-0.2/-0.2	-0.2									
R-152a	-0.3	-0.1	-0.1	0.1	16.0/1.9	8.9	-0.3/-0.2	-0.3	-0.7/-0.5	-0.6	-0.3/-2.1	-1.2	62/63 D								
R-123	0.5	0.2	0.2	0.5	60.2/60.2	60.2	-0.6/-0.2	-0.4	-0.5/-0.1	-0.3	-1.3/-1.3	-1.3	58/59 D								
R-142b	-0.4	-0.1	-0.1	-0.4	18.0/15.8	16.9	-0.6/-0.4	-0.5	-1.0/0.1	-0.5	-0.7/-0.6	-0.7	62/63 D								
R-134	0.1	0.3	0.3	0.4	26.8/7.0	16.9	0.1/-1.2	-0.6	-0.4/-0.6	-0.5	-0.4/-0.4	-0.4	57/58 D								
AB	-0.1	-	-	-0.1/-0.1	16.0/15.9	16.0			0.1/-0.2	-0.1	14.8/14.6	14.7	54/55 D								
MO	0.2	-	-	-0.1/-0.1	20.3/18.5	19.4			-0.1/0	-0.1	15.5/16.1	15.8	54/55 D								
PEMA	0.4	-	-	0.1/0.2	20.2/18.7	19.5			0.4/-0.3	0.1	18.4/17.3	17.9	49/50 D								
PEBA	-4.0	-	-	0.1/2.0	18.5/18.2	18.4			-0.4/-0.2	-0.3	17.2/17.2	17.2	52/53 D								
PPGD	0.1	-	-	-0.1/0	21.5/22.2	21.9			-0.7/-0.6	-0.7	20.2/21.0	20.6	48/49 D								
PPGBM	0.5	-	-	0.1/2.2	19.0/21.2	20.1			-0.2/-0.3	-0.3	17.4/18.9	18.2	52/53 D								
MPG	0.4	-	-	-0.1/0.3	19.7/18.7	19.2			0.6/0.7	0.7	19.1/17.9	18.5	51/52 D								

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

Formula # 94	Parker V747-75		100.00		Lubricant Legend Information										PEMA - Pentaerythritol Ester Mixed Acid	
															PEBA - Pentaerythritol Ester Branched Acid	
															PPGBM - Polypropylene Glycol Butyl Monoether	
															MO - Mineral Oil	
															MPG - Modified Polyglycol	
															PPGD - Polypropylene Glycol Diol	
															AB - Alkyl Benzene	
Test Fluid	1 Day Diameter Change (%)	3 Day Diameter Change (%)	14 Day Diameter Change (%)		14 Day Weight Change (%)		Diameter/Weight After Removal From Test Fluid. Values Based On Original Sample Measurements.						1 Day Shore A/D Hardness			
			14 Day Diameter Change (%)		14 Day Weight Change (%)		2 hr. Diameter (%)		1 Day Diameter (%)		1 Day Weight (%)					
			values	mean	values	mean	values	mean	values	mean	values	mean				
R-22	25.8	24.2	23.4		68.6/65.0	66.8	3.6/4.4	4.0	1.1/1.7	1.4	3.4/3.6	3.5				
R-32																
R-124	20.9	20.5	20.7		66.0/58.5	62.3	5.8/5.3	5.6	3.4/3.1	3.3	9.2/6.0	7.6	72/73 A			
R-134a	19.1	20.7	20.3		53.0/51.0	52.0	6.3/5.3	5.8	2.8/1.7	2.3	6.2/6.3	6.3				
R-125	10.1	10.0	1.0		27.1/26.4	26.8	5.4/4.6	5.0	3.2/2.5	2.9	8.4/8.5	8.5	71/72 A			
R-143a	11.7	12.2	11.8		25.6/25.5	25.6	4.1/5.3	4.7	1.7/1.7	1.7	5.5/5.6	5.6				
R-152a	29.1	28.8	30.2		57.9/54.7	56.3	3.6/3.5	3.6	1.5/1.6	1.6	2.3/5.3	3.8	73/74 A			
R-123	21.8	21.7	23.2		69.0/69.1	69.1	7.5/7.8	7.7	3.9/4.3	4.1	12.2/12.2	12.2	72/73 A			
R-142b	26.3	23.8	23.8		58.3/57.0	57.7	6.1/6.5	6.3	2.6/2.5	2.6	6.4/6.4	6.4	69/70 A			
R-134	25.4	25.6	26.9		74.7/73.7	74.2	6.2/7.2	6.7	2.7/2.5	2.6	6.8/6.9	6.9	69/70 A			
AB	0.1	-	0.1/0.1	0.1	0.5/0.3	0.4			-0.1/-0.1	-0.1	0.3/0.2	0.3	73/74 A			
MO	-0.5	-	0.1/0.2	0.2	2.4/2.3	2.4			-0.4/-0.1	-0.2	0.9/1.5	1.2	74/75 A			
PEMA	1.1	-	3.0/3.7	3.4	7.5/7.6	7.6			3.6/3.7	3.7	7.5/7.7	7.6	70/71 A			
PEBA	1.5	-	7.3/9.3	8.3	14.6/14.8	14.7			7.8/8.2	7.9	14.7/14.6	14.7	46/45 A			
PPGD	0.6	-	1.1/0.8	1.0	2.1/2.2	2.2			0.4/0.9	0.7	1.7/1.9	1.8	72/73 A			
PPGBM	-0.1	-	-0.2/0.1	-0.1	0.8/0.8	0.8			-0.3/-0.4	-0.4	0.9/0.7	0.8	73/74 A			
MPG	0.2	-	0.1/0.1	0.1	0.5/0.3	0.4			-0.5/0.4	-0.1	0.2/0.3	0.3	74/75 A			

* Indicates that material shows some form of deteriorative effect after removal from the test fluid, i.e. fracture due to outgassing of test fluid/extreme cavitation.

APPENDIX F: PHYSICAL PROPERTY DATA

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
1	26		42		77		115		175		249		4435		801		
	26		41		75		114		173		245		3701		768		
	30	27	40	41	74	75	112	114	170	173	239	244	3498	3878	769	779	38/39
2	67		106		186		320		752		1414		4013		577		
	69		107		197		352		831		1505		4220		601		
	69	68	108	107	194	192	348	340	827	803	1500	1473	4330	4188	616	598	62/63
3	22		30		49		67		90		113		442		757		
	24		34		53		69		94		118		1359		877		
	30	25	47	37	58	53	79	72	111	98	141	124	2159	1320	860	831	42/43
4	88		132		162		181		203		243		2707		983		
	62		90		122		144		169		203		2691		973		
	79	76	106	109	136	142	153	159	179	184	214	220	2781	2726	982	972	63/64
5	258		337		440		685		1467		2359		3564		529		
	225		300		396		600		1306		2176		3566		547		
	236	240	302	313	408	415	637	641	1396	1390	2293	2276	3541	3557	519	532	82/83
6	19		27		45		61		78		98		1506		861		
	21		29		47		60		79		101		1972		865		
	20	20	30	29	46	46	62	61	80	79	100	100	1962	1813	881	869	35/36
7	19		32		55		79		114		161		240		407		
	21		33		56		81		112		174		286		416		
	24	21	33	33	55	55	79	80	116	117	165	167	200	242	350	391	41/42
8	80		115		176		278		583		957		2262		603		
	83		115		175		280		590		966		2197		594		
	81	81	112	114	169	173	265	274	548	574	900	941	2242	2234	619	605	68/69

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
17	55		89		149		198		271		348		2340		646		63/64
	64		99		157		207		283		361		2254		625		
	60	60	95	94	155	154	206	204	281	278	359	356	2619	2404	631	634	
18	43		71		122		163		212		258		2431		706		60/61
	39		69		122		165		216		264		1350		749		
	43	42	73	71	122	122	165	164	214	214	260	261	2161	1981	783	679	
19	38		61		105		140		180		216		653		688		58/59
	38		61		105		140		177		211		512		654		
	36	37	60	61	104	105	141	140	181	179	216	214	326	497	515	619	
20	33		55		99		142		214		292		437		445		56/57
	40		63		113		173		189		411		477		350		
	37	37	61	60	110	107	169	161	286	263	411	371	520	478	380	392	
21	99		163		332		611		1171		1794		2283		377		73/74
	102		175		367		681		1303		1994		2292		342		
	102	101	178	172	388	362	756	683	1433	1302		1894	2057	2211	288	336	
22	136		211		349		525		1076		1840		4343		607		80/81
	128		211		350		527		1066		1830		3810		540		
	136	133	213	212	346	348	518	523	1065	1069	1837	1836	4118	4090	571	573	
23	59		105		207		376		865				835		180		62/63
	57		104		201		363						712		167		
	47	54	93	101	187	198	327	355					986	844	213	197	
24	79		132		196		233		382		616		2320		870		67/68
	80		130		192		228		370		603		2192		861		
	76	78	129	130	192	193	227	229	366	373	600	606	2310	2274	881	871	

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)			20 % Modulus (Psi)			50 % Modulus (Psi)			100 % Modulus (Psi)			200 % Modulus (Psi)			300 % Modulus (Psi)			Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean		values	mean		values	mean		values	mean		values	mean		values	mean		values	mean	values	mean	
25	48			84			158			244			612						1501		276		
	49			85			157			240			574						1782		300		
	49	49		86	85		158	158		240	241		570	585					1360	1548	281	286	62/63
26	136			246			576			1477									3489		196		
	131			243			582			1503									3273		181		
	142	136		251	247		598	585		1533	1504								3045	3269	167	181	83/84
27																							
28																							68/69
29																							68/69
30																							66/67
31																							93/94
32																							62/63
																							73/74

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
41	27		42		81		122		168		214		1182		1092		43/44
	28		45		85		126		177		224		1217		1084		
	27	27	43	43	82	83	120	123	169	171	214	217	1209	1203	1096	1091	
42	49		73		104		132		229		384		1277		691		56/57
	49		75		108		140		243		402		1177		645		
	49	49	74	74	106	106	140	137	239	237	392	393	1242	1232	681	672	
43	170		265		466		804						1122		168		80/81
	190		279		483		835						1145		164		
	173	178	271	272	481	477	833	824					1126	1131	160	164	
44																	65/66
45	656		821		950		1009		1103		1252		2095		530		93/94
	639		809		943		1002		1101		1245		2188		545		
	654	650	812	814	943	945	1004	1005	1104	1103	1254	1250	2086	2123	523	533	
46	208		290		405		510		661		822		1425		516		78/79
	204		283		403		507		657		818		1291		488		
	206	206	285	286	399	402	505	507	657	658	822	821	1404	1373	513	506	
47	1078		1295		1388		1399		1440		1560		2375		540		41/42
	1078		1280		1377		1389		1444		1565		2376		528		
	1083	1080	1277	1284	1361	1375	1372	1387	1422	1435	1550	1558	2347	2366	532	533	
48	1743		1959		1979		1911		1881		1976		2584		498		49/50
	1747		1920		1912		1848		1868		1917		2550		501		
	1774	1755	1953	1944	1966	1952	1896	1885	1866	1872	1963	1952	2708	2614	521	507	

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
49	946		1127		1258		1339		1520		1824		2357		413		
	919		1116		1251		1338		1530		1829		2457		428		
	902	922	1109	1117	1251	1253	1338	1338	1517	1522	1809	1821	2410	2408	420	420	93/94
50	304		427		581		718		955		1307		1423		325		
	311		418		565		695		932		1284		1303		305		
	311	309	420	422	562	569	692	702	932	940	1284	1292	1345	1357	313	314	82/83
51	1476		1682		1746		1775		1878		2146		2676		412		
	1482		1680		1733		1756		1842		2088		2777		439		45/46
	1444	1467	1654	1672	1718	1732	1743	1758	1832	1851	2080	2105	2676	2710	418	423	D
52																	40/41 D
53																	52/53 D
54																	58/59 D
55																	59/60 D
56																	51/52

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
57	190		284		456		671		1067				1140		224		81/82
	195		304		475		696		987				992		177		
	196	194	301	296	474	468	661	676		1027			1013	1048	210	204	
58	17		24		39		53		72		92		96		322		44/45
	15		23		36		49		66		84		95		350		
	16	16	23	23	38	38	52	51	70	69	90	89	98	96	335	336	
59	126		201		331		523		1135				1464		248		80/81
	125		198		323		512		1097				1209		217		
	129	127	207	202	336	330	533	523	1149	1127			1378	1350	236	234	
60																	82/83
61																	51/52 D
62																	81/82
63																	55/56 D
64	27		46		76		101		127		151		2249		799		49/50
	30		46		77		100		128		154		1705		705		
	29	29	46	46	76	76	99	100	127	127	152	152	2539	2164	671	725	

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
65	31		50		86		115		141		166		1142		691		66/67
	32		52		88		117		145		171		1136		677		
	33	32	53	52	88	87	116	116	143	143	168	168	1555	1278	711	693	
66	129		189		295		473		1037		1764		3739		561		79/80
	117		182		287		458		988		1680		3550		559		
	121	122	185	185	291	291	465	465	1003	1009	1699	1714	3490	3593	546	555	
67	48		81		160		304		746				94635		234		60/61
	44		79		157		302		739				1274		282		
	42	45	77	79	167	161	336	314		743			663	961	170	229	
68	45		78		134		202		422		785		1678		399		60/61
	46		82		139		210		445		822		2228		423		
	47	46	79	80	137	137	198	203	403	423	749	785	2424	2110	435	419	
69	41		72		117		151		227		382		3191		550		61/62
	44		73		117		153		222		372		3242		559		
	44	43	70	72	119	118	152	152	223	224	371	375	3283	3239	555	555	
70	43		74		140		248		639		1220		1525		352		58/59
	52		84		152		283		750		1355		1382		308		
	49	48	83	80	146	146	252	261	644	678	1239	1271	1372	1426	321	327	
71	49		87		170		311		844				1230		238		65/66
	53		93		176		319		867				1186		232		
	53	52	93	91	179	175	321	321	904	872			1093	1170	221	230	
72	25		42		71		96		115		128		207		547		45/46
	29		47		74		95		115		128		210		626		
	31	28	44	44	71	72	94	95		115		128	242	220	693	622	

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
73	98		168		243		281		311		351		581		555		71/72
	101		163		243		291		328		370		610		518		
	95	98	153	161	230	239	268	280	299	313	341	354	544	578	488	520	
74	218		317		448		550		770				899		268		84/85
	229		329		461		558		786				928		264		
	219	222	318	321	449	453	549	552	772	776			894	907	259	264	
75																	45/46
76																	72/73
77	58		97		171		250		526		979		776		261		69/70
	61		103		174		252		527		969		1087		316		
	54	58	96	99	174	173	251	251	522	525		974	1466	1110	356	311	
78	177		276		534		1391		4021				4061		199		87/88
	178		273		519		1373		3993				4125		204		
	155	170	260	270	507	520	1349	1371		4007			4232	4139	210	204	
79																	78/79
80	128		200		267		294		369		533		722		344		78/79
	121		194		259		283		357		510		579		322		
	121	123	194	196	263	263	288	288	367	364	525	523	628	643	333	333	

PHYSICAL PROPERTIES ON UNAGED ORIGINAL SAMPLE MATERIALS

Form #	10 % Modulus (Psi)		20 % Modulus (Psi)		50 % Modulus (Psi)		100 % Modulus (Psi)		200 % Modulus (Psi)		300 % Modulus (Psi)		Tensile Strength (Psi)		Elongation @ Break (%)		Shore
	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	values	mean	
89																	64/65 D
90																	62/63 D
91																	67/68 D
92																	69/70 D
93																	65/66 D
94																	75/76
95																	86/87

APPENDIX G: LUBRICANT TYPES

**Lubricants Utilized in the Research
Compatibility of Refrigerants and Lubricants with Elastomers**

<u>mineral oil</u> MO	naphthenic mineral oil	Witco Sunisco #GS (32cSt)
<u>alkylbenzene</u> AB	alkylbenzene	Shrieve Zerol ^(R) 150 (32 cSt)
<u>polyglycols</u> PPGBM PPGD MPG	polypropylene glycol butyl monoether polypropylene glycol diol modified polyglycol	ICI Emkarox ^(R) (32 cSt) Dow P425 (32 cSt) Allied Signal BRL-150 (32 cSt)
<u>polyolesters</u> PEMA PEBA	pentaerythritol ester mixed acid pentaerythritol ester branched-acid	ICI Emkarate ^(R) RL 244 (22 cSt) Emery 2927-A (32 cSt)

APPENDIX H: TEST METHODOLOGY

Test Methodology-Phase II

Test samples for this phase of the program are either cut from flat sheet stock as in the case of the TPE materials or the industrially supplied gasket materials. Other elastomers that are suitable for compression molding are molded into ring samples.

The test samples are loaded into pressure vessels that are charged with the appropriate quantities of refrigerant and lubricant fluids. The correct refrigerant to lubricant weight ratio is determined through the construction of % weight refrigerant vs. pressure calibration curves.

The test samples are measured and submersed in test fluid in the bottom of the pressure vessels. The pressure vessels are placed in a heated silicone bath and allowed to remain for 14 days at 100 degrees centigrade.

At the end of the 14 day time period, the test samples are removed from the vessels and the tensile strength is determined for the aged samples. These values are compared with original, unaged data and deteriorative properties are determined for each of the tested materials.

APPENDIX I: LUBRICANT/REFRIGERANT TEST MIXTURES-PHASE II

Phase II Refrigerant/Lubricant Test Mixtures

Refrigerant	Lubricant (Description)	ID	Lubricant (Trade Name)
R-22	Naphthenic mineral oil	MO	Witco Suniso 3GS
R-123	Naphthenic mineral oil	MO	Witco Suniso 3GS
R-134a	Polypropylene glycol diol	PPGD	DOW P425
R-134a	Modified polyglycol	MPG	Allied-Signal BRL-150
R-134a	Penta erythritol ester mixed-acid polyolester	PEMA	ICI Emkarate RL 244
R-134a	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-142b	Alkylbenzene	AB	Shrieve Zerol 150
R-152a	Alkylbenzene	AB	Shrieve Zerol 150
R-32	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-124	Alkylbenzene	MO	Shrieve Zerol 150
R-125	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-143a	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-134	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A
R-32	Penta erythritol ester mixed-acid polyolester	PEMA	ICI Emkarate RL 244
R-125	Polypropylene glycol diol	PPGD	Dow P425
R-125	Penta erythritol ester mixed-acid polyolester	PEMA	ICI Emkarate RL 244
R-152a	Penta erythritol ester branched-acid polyolester	PEBA	Emery 2927-A

APPENDIX J: PRESSURE CALIBRATION CURVES-PHASE II PROGRAM

R-143a/2927 A

R-134/2927 A

R-123/SUNISCO

R-134a/EMKARATE RL244

R-134a/Polyglycol P425

R-152a/ZEROL 150

R-134a/BRL 150

R-134a/Emery 2927-A

R-125/2927- A

R-124/ZEROL

END

**DATE
FILMED**

3 / 17 / 93