TECHNICAL PROGRESS REPORT

CONTRACT TITLE: Rapid Pressure Swing Absorption Cleanup of Post-Shift
Reactor Synthesis Gas

CONTRACT NUMBER: DE-FG22-90PC90300

CONTRACT PERIOD: 9/7/90 - 8/31/93

CONTRACTOR'S NAME: Dept. of Chemistry and Chemical Engineering
Stevens Institute of Technology
Hoboken, NJ 07030

SUBCONTRACTOR'S NAME: Department of Chemical Engineering, Chemistry
and Environmental Science
New Jersey Institute of Technology
Newark, NJ 07102

INVESTIGATORS: Dr. K. K. Sirkar
AT NJIT Dr. S. Majumdar
Mr. S. Bhaumik

REPORT NUMBER: 8

REPORT PERIOD: 8/1/92 - 10/31/92

REPORTING DATE: January 29, 1993

PREVIOUS REPORT DATE: September 24, 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

Overview of Progress

The theoretical model for the absorption part of a particular type of RAPSAB cycle (Mode 3) (see Technical Progress Report No. 7) has been developed. The numerical simulations of the model compare well with the experimental results presented in the last report (Technical Progress Report No. 7). A number of experiments were carried out also for Mode 2 type of operation by varying the time for initial pressurization of the hollow fiber module as well as the total absorption time. These were done to provide a basis for comparison with the theoretical model to be developed later. We have initiated RAPSAB studies with reactive absorbents such as 19.5% aqueous solution of diethanolamine (DEA) for the absorption of CO₂ from a CO₂-N₂ mixture. Six experiments were carried out using Mode 3 type of operation and a CO₂-N₂ mixture containing 9.9% CO₂ and balance N₂. Excellent purification was obtained. No CO₂ was observed in the purified high pressure gas outlet for absorption time of up to 14 seconds; the purified high pressure gas flow rate was also considerable. Module No. 5 was used for all experiments. The details of the module are given in Technical Progress Report No. 7.

Experimental Procedure

Mode 2: The schematic of the setup for Mode 2 of operation is given in Figure 1.

All experiments were done in the following manner.

The feed gas was allowed to enter into the module for a certain time through valve no. 1 (Figure 2) while both valves no. 2 and 3 remained closed. Immediately afterwards, valve no. 1 was closed and simultaneously

valve no. 3 was opened for a certain time to withdraw the purified front of the mixture of gases. Then valve no. 3 was closed and simultaneously valve no. 2 was opened for vacuum desorption for a certain length of time. The time for the feed coming into the module was varied as well as the time for the withdrawal of purified front of the mixture of gases. A desorption time of 15 seconds was maintained constant in all experiments.

After 1 to 2 hours of operation, purified gas mixture was injected into the GC periodically to find out the gas composition. A constant flow rate from the surge drum was maintained using a metering valve.

Mode 3: The schematic of the setup for Mode 3 type of operation is given in Figure 3. All experiments were done in the following manner.

The feed gas was allowed to enter through the feed entrance port of the three way solenoid valve (3-WSV) (Figure 4) while the other end of the three-way solenoid valve was closed. The two-way (2-WSV) solenoid valve at the exit end of the permeator was opened simultaneously to withdraw the purified front of the mixture of gases. After some time the feed entrance port of the three-way solenoid valve as well as the two-way solenoid valve at the exit was closed; simultaneously the other end of the three-way solenoid valve was opened for vacuum desorption for a certain length of time. This completed one whole cycle of operation. The time for the absorption part of the cycle was changed in different experiments.

After a certain length of operation, the purified gas mixture was injected into the GC periodically to find out the gas composition. A constant gas flow rate from the surge drum was maintained using a metering valve.

Experiments with a Reactive Absorbent

Diethanolamine is a wellknown hazardous material. So experiments had to be conducted with care. During the operation the discharged gas will carry DEA vapor due to evaporation from the absorbent liquid. Therefore, all purified gas lines and the desorbed gases were discharged to the exhaust hood.

All experiments using the reactive absorbent were carried out using Mode 3 described earlier. In the first four experiments, 15 seconds was allowed for vacuum desorption; 20 seconds was used in the last two experiments.

Theoretical Model Development

A simplified model for gas absorption in Mode 3 has been developed using Happel's (1958) free surface model. One fiber is considered in a unit cell of radius r_c (Figure 5) surrounded by absorbents. Gas flows through the lumen of one fiber. Gas pressure drop in the fiber lumen was included in the model. The governing balance equations and boundary conditions for any species j (N_2 , CO_2) in the gas and liquid phases are given below.

$$\text{Gas Phase:} \quad \frac{\partial C_{jg}}{\partial t} = D_{jg} \frac{\partial^2 C_{jg}}{\partial z^2} - \frac{\partial}{\partial z} (v_z C_{jg}) - \frac{4K_{jg}d_o}{d_i^2} (C_{jg} - C_{jg}^i) \quad (1)$$

$$\text{where } C_{jg}^i = \frac{C_{jl}|_{r=r_e}}{H_j RT} \text{ and } v_z = -\frac{RTd_i^2}{32\mu_g} \sum_{j=1}^n \frac{\partial C_{jg}}{\partial z} \quad (2)$$

$$\text{Initial condition: at } t = 0, C_{jg} = 0 \quad (0 < z < L) \quad (3)$$

Boundary conditions:

$$v_z C_{jg}|_{z=0} = v_z C_{jg}|_{z=0} - D_{jg} \frac{\partial C_{jg}}{\partial z} \Big|_{z=0} \quad (4); \quad -D_{jg} \frac{\partial C_{jg}}{\partial z} \Big|_{z=L} = 0 \quad (5)$$

$$\text{Liquid Phase: } \frac{\partial C_{jl}}{\partial t} = D_{jl} \left[\frac{\partial^2 C_{jl}}{\partial r^2} + \frac{1}{r} \frac{\partial C_{jl}}{\partial r} \right] \quad (6)$$

$$\text{Initial condition: at } t = 0, C_{jl} = 0 \quad (0 < z < L \text{ and } r_o < r < r_e) \quad (7)$$

Boundary conditions:

$$-D_{jl} \frac{\partial C_{jl}}{\partial r} \Big|_{r=r_o} = K_{jg} \left[C_{jg} - \frac{C_{jl}|_{r=r_e}}{H_j RT} \right] \quad (8); \quad \frac{\partial C_{jl}}{\partial r} \Big|_{r=r_e} = 0 \quad (9)$$

The governing mass balance equations with the initial and boundary conditions were solved numerically to find out the purified product composition at any time. They were solved using the method of lines technique to convert the PDEs (partial differential equations) into ODEs (ordinary differential equations) in time and spatial dimensions. Then computer codes were written in Fortran 77 using IMSL subroutine, DIVPAG; the program was run in the mainframe computer, VAX/VMS environment.

Results

The numerical model simulations have been compared with the experimental results obtained from module no. 5 and Mode 3 as reported in Technical Progress Report No. 7. They are identified in Figure 6. Normalized high pressure exit composition have been plotted against the normalized absorption time ($D_{11}t/r_e^2$) for numerical model simulations as well as experimental data. The experimental values of the purified gas flow

rate for different normalized absorption times are also given in the same plot. From the figure, it is obvious that the theoretical model for the normalized exit compositions predicts the experimental data reasonably well.

For different experimental runs in Mode 2 operation, the duration of the open and close settings of the solenoid valves and the corresponding values of the feed gas pressure have been identified in Table 1. The purification results for each such run identified in Table 1 are provided in Table 2. In the first set of experiments, the feed inlet metering valve was set at 800 cc/min and the feed gas mixture was allowed to enter the module for 3 seconds; the purified gas mixture was taken out for different times. In the second set of experiments, feed gas mixture was allowed to enter the module for 2 seconds while the feed inlet metering valve was set at the same feed flow rate. A CO₂-N₂ mixture of 9.9% CO₂ and balance N₂ was used for all experiments. It was found that the extent of purification in the high pressure purified gas mixture was higher when the feed gas was allowed into the module for only 2 seconds. The higher purification is most likely due to a longer gas mixture residence time when less amount of gas enters into the module. A desorption time of 15 seconds was used for all experiments.

We report now CO₂ removal using a 19.5% aqueous DEA solution as an absorbent. The time duration for absorption and desorption part of the simple cycle in Mode 3, the feed flow rate, and the purified product flow rate for all experiments are identified in Table 3 along with the purified gas composition in each case. The feed gas flow rate was kept constant at 460 cc/min as the absorption time was changed. Module No. 5 was used for all experiments. One observes that at this inlet feed flow rate, there

was no CO_2 in the purified gas up to an absorption time of 14 seconds. When the absorption time is increased beyond 14 seconds, small amounts of CO_2 appear in the purified gas stream. It appears that up to an absorption time of 16 seconds, 15 seconds desorption was enough; but for longer absorption periods, 15 seconds desorption time was not enough and it was increased to 20 seconds to make the system stable. These experiments with aqueous DEA solution indicate first that the level of gas purification achieved was much higher than that with water. Second, the rate of production of the purified high pressure gas was an order of magnitude higher than that with plain water as an absorbent. These results demonstrate the considerable potential for RAPSAB as a gas purification technique.

NOTATION

C_{jg}, C_{jg}^i	: species j concentration, bulk gas and gas-liquid interface, mole/cm ³
C_{jl}	: species j concentration in liquid phase, mole/cm ³
D_{jg}, D_{jl}	: species j diffusion coefficient, gas phase and liquid phase, cm ² /s
H_j	: Henry's law constant for species j, mole/cm ³ -atm
K_{jg}	: gas phase mass transfer coefficient, cm/s
P	: pressure at any axial location, atm
d_i, d_o	: inside and outside diameters of microporous hollow fiber, cm
R	: universal gas constant, atm-cm ³ /mole-°K
r, r_i, r_o	: radius at any radial location, at fiber ID, at fiber OD, cm
r_e	: radius of Happel's free surface, cm
T	: temperature, °K
t	: time, s
v_z	: gas velocity at any axial location, cm/s
z	: axial location, cm

Table 1: Duration of Different Settings of Solenoid Valves
for Mode 2 Operation with Water

Experiment No.	Module No.	Mode of Operation	Pressure in fiber lumen (psig)	Valve # 1		Valve # 3		Valve # 2		Total Cycle Time (Seconds)
				Open (Seconds)	Close (Seconds)	Close (Seconds)	Open (Seconds)	Close (Seconds)	Open (Seconds)	
8-1	5	2	30~35	3	17	3	2	5	15	20
8-2	5	2	30~35	3	18	3	3	6	15	21
8-3	5	2	30~35	3	19	3	4	7	15	22
8-4	5	2	30~35	3	20	3	5	8	15	23
8-5	5	2	30~35	3	21.5	3	6.5	9.5	15	24.5
8-6	5	2	30~35	3	23	3	8	11	15	26
8-7	5	2	30~35	3	24	3	9	12	15	27
8-8	5	2	20~25	2	20.8	2	5.8	7.8	15	22.8
8-9	5	2	20~25	2	21.8	2	6.8	8.8	15	23.8
8-10	5	2	20~25	2	22.8	2	7.8	9.8	15	24.8
8-11	5	2	20~25	2	23.8	2	8.8	10.8	15	25.8
8-12	5	2	20~25	2	25	2	10	12	15	27

Table 2: Experimental Results for RAPSAB using Water as Absorbent
and Mode 2

Experiment No.	Module No.	Mode of Operation	Feed Pressure (psig)	Feed Gas Composition*	Purified Gas Composition*	Purified Product Gas Flow Rate (cc/min)
8-1**	5	2	30 ~ 35	CO ₂ : 9.9%	CO ₂ : 1.005%	4
8-2	5	2	30 ~ 35	CO ₂ : 9.9%	CO ₂ : 1.05%	4 ~ 5
8-3	5	2	30 ~ 35	CO ₂ : 9.9%	CO ₂ : 1.12%	5
8-4	5	2	30 ~ 35	CO ₂ : 9.9%	CO ₂ : 1.28%	5 ~ 6
8-5	5	2	30 ~ 35	CO ₂ : 9.9%	CO ₂ : 1.41%	6 ~ 7
8-6	5	2	30 ~ 35	CO ₂ : 9.9%	CO ₂ : 1.69%	7 ~ 8
8-7	5	2	30 ~ 35	CO ₂ : 9.9%	CO ₂ : 1.86%	8
8-8	5	2	20 ~ 25	CO ₂ : 9.9%	CO ₂ : 0.95%	2 ~ 2.5
8-9	5	2	20 ~ 25	CO ₂ : 9.9%	CO ₂ : 1.06%	3.5 ~ 4
8-10	5	2	20 ~ 25	CO ₂ : 9.9%	CO ₂ : 1.27%	4.5
8-11	5	2	20 ~ 25	CO ₂ : 9.9%	CO ₂ : 1.40%	4.5 ~ 5
8-12	5	2	20 ~ 25	CO ₂ : 9.9%	CO ₂ : 1.50%	5

* Balance N₂

** For valve settings, see Table 1.

Feed metering valve set at 800 cc/min.

Table 3. Experimental Results for RAPSAB using DEA Solution
and Mode 3

Experiment No.	Module No.	Absorption Time (Seconds)	Desorption Time (Seconds)	Feed Flow Rate (cc/min)	Feed Pressure (psig)	Product Outlet Composition*	Product Flow Rate (cc/min)
8.1-1	5	10	15	460	25	CO ₂ : 0.0%	20 ~ 25
8.1-2	5	12	15	460	25	CO ₂ : 0.0%	30 ~ 35
8.1-3	5	14	15	460	25	CO ₂ : 0.0%	50 ~ 55
8.1-4	5	16	15	460	25	CO ₂ : 0.088%	65 ~ 70
8.1-5	5	20	20	460	25	CO ₂ : 0.214%	~ 90
8.1-6	5	22	20	460	25	CO ₂ : 0.403%	~ 100

Feed Composition: CO₂: 9.9%, N₂: 90.1%

* Balance N₂

Figure 1. RAPSAB setup for Mode 2

Figure 2. Solenoid valve locations in RAPSAB apparatus for Mode 2

Figure 3. RAPSAB setup for Mode 3

Figure 4. Solenoid valve locations in RAPSAB apparatus for Mode 3

Figure 5. Concentration profile for absorbed species in gas and liquid phases

Figure 6. RAPSAB performance (Mode 3) with water as absorbent

END

DATE
FILMED

5 / 11 / 93