QUARTERLY TECHNICAL REPORT

September 1, 1992 to November 30, 1992

DOE/PC/91300--T5

DE93 008120

MAR 02 1993

1. Project Title

Thermodynamic and Rheological Properties of Solid-Liquid Systems in Coal Processing

U.S. DOE Grant No: DE-FG22-91PC91300

OSTI

2. Investigators:

Vinayak N. Kabadi, and Shamsuddin Ilias, Department of Chemical engineering, North Carolina A&T State University, Greensboro, NC 27411

3. Project Objectives and Scope:

The objective of this project is to develop a model for solid-liquid equilibria and a model for viscosities of the products of coal liquefaction processes. The same characterization procedure and representation by continuous distributions as used in our previous work on vapor-liquid equilibria and excess enthalpies of coal liquids will be used. Models when fully developed will give the solid-liquid phase equilibrium properties and viscosities as factors of temperature and pressure for known molecular weight distribution and structural characterization of the coal liquid. To accomplish this well, the project requires three tasks:

- (1) Solid-liquid phase equilibrium model development: This will require data compilations for vapor pressures of solids and available single and multi-component solid-liquid phase equilibrium data. Model development will include models for thermodynamics of solids such as in coal products, thermodynamics of defined solid-liquid systems and finally application to complex coal derived products.
- (2) Experimental Viscosity Measurements: A viscometer will be purchased to measure viscosities of coal liquids and slurries at different temperatures and pressures. The data will be used in conjunction with literature data for viscosity model development.
- (3) Viscosity Model Development: Viscosity model development will require collection of physical property data for model compounds to estimate the model parameters. Both group contribution and corresponding states methods will be used to account for the effect of pressure and temperature on the liquid viscosity. The model will then be extended to coal liquid fractions. The experimentally measured viscosity data will be used to evaluate the model and recommend modifications.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

4. Technical Highlights and Milestones:

None of the models available in the literature are known to work very well for aromatic compounds such as the ones that occur in coal derived materials. Two models - one by Van Velzen et al. (Ind Eng. Chem. Fundam. Vol 11, 1972, pp. 20-25) using a group contribution method and the other by Hwang et al (Ind. Eng. Chem. Process Des. Dev., Vol. 21, 1982, pp. 127-134) using a corresponding states method - were tested for some typical compounds that occur in coal liquids. These methods give errors ranging from 10 to 50% for viscosities of such compounds. These errors are too high and considering further errors in extension of these models to coal liquids, these models were considered unacceptable in our work. We have therefore set out to develop a new model for viscosities of aromatic compounds. We plan to base the model on the procedure similar to that of Van Velzen, however developed for just aromatic compounds. Our model, once developed will therefore be a group contribution method centered around the benzene ring structure.

In what follows, we present the progress in the model development work. This work will continue through the next year.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

VISCOSITY MODEL FOR COAL LIQUIDS

The viscosity behaviour of model compounds found in coal liquids have been analysed in detail. The experimental data (1700 points) were studied using a linear regression model

$$\ln \eta = A + B/T$$

The rationale for using the above model was that the viscosity of liquids have been found to reduce exponentially with increasing temperature. The slopes (B) and intercepts (A) were studied carefully. Since coal liquids contain predominantly aromatic compounds with a high percentage of compounds with fused benzene structure, the pattern of slope and intercept for increasing fused rings were tabulated. The pattern for alkane as well as hetero atom substituted benzene ring structure were also tabulated. The tables appear in appendix A.

The slopes and intercepts were analysed graphically also to study their trends and patterns.

Not surprisingly, most of the compounds fitted the model reasonably well with the exception of a few compounds where some deviations (minor curvature) from the model were observed. However the exact nature of fit for individual compounds has to be confirmed at this stage, with more extensive experimental data, both from published literature as well as from measurements in the laboratory.

It was observed that the structure of the molecule has a strong effect on the viscosity of liquids. Some definite trends emerge from the analysis of the regression results. Some of these trends are:

- a) Benzene ring structure with n-Alkane substituted in the ring does not appreciably alter the slope (B) from that of benzene.
- b) Hetero atom substitution in the naphthalene ring (quinoline) or hetero atom attached to the benzene ring (phenol), or hetero atom substituted in the cyclopentane structure (thiophene) etc. alter the slope markedly, but to different extents.
- c) Slope increases as the number of condensed rings increases as is apparent for the set of compounds from benzene to pyrene.

- d) The effect of substitution of an hydroxyl group to a naphthalene ring is not as much as the effect of substitution to the benzene ring.
- e) Substitution of alkyl groups to cyclopentane structure increases the slope from methyl to n-hexyl groups progressively.
- f) Slope increases from benzene to cyclohexane.
- g) Slope does not change much from naphthalene->tetralin->decalin.

There may be other marginal effects due to the substitution to the benzene ring, of branched alkanes. But the data available for confirming such effects is too few and hence not dependable.

After the effect on slope has been correlated to molecular structure as a mathematical formulation, using the benzene ring as the basis, the next step would be to use these values of slope to regress the experimental values again to obtain the best fit values of intercepts. The reason for choosing the benzene ring structure as the basis is that coal liquids are predominantly comprised of aromatic compounds.

This work is now in progress simultaneously with the creation of a more extensive data bank on viscosity to confirm the results.

Trends of intercepts have then to be analysed and correlated to molecular structure. The combined effects would then be crystallised as a mathematical model to be extended to mixtures and finally to coal liquids.

APPENDIX-A

compound name	formula	no of pts	intercept (A)	slope (B)	error* (A)	error* (B)	corr. coeff.
benzene		39	-4.508	1199.7	0.12	36.5	0.983
naphthalene		12	-4.296	1502.1	0.05	17.7	0.999
anthracene		10	-3.779	1663.1	0.27	145	0.971
phenanthrene		14	-3.445	1515.2	0.14	56.6	0.992
chrysene		4	-4.913	2076.7	0.17	67.7	0.999
pyrene		12	-5.188	2514.1	0.20	48.1	0.984
toluene		34	-4.123	1051.3	0.02	4.86	0.999
o-xylene		25	-4.184	1165.1	0.04	13.0	0.999
m-xylene		21	-4.034	1041.7	0.01	2.04	1.000
p-xylene		21	-4.118	1078.5	0.02	6.42	0.999
isopropyl benzene (cumene)		18	-4.101	1131.1	0.03	9.73	0.999
1,2,4-tri methyl benzene pseudocumene		5	-6.647	1951.8	0.11	34.3	0.999
n-propyl benzene		7	-2.949	817.97	0.19	59.4	0.987
n-butyl benzene		4	-3.805	1168.6	0.04	11.7	0.999
ethyl benzene		23	-4.070	1075.6	0.03	7.88	0.999
p-ethyl toluene		5	-3.446	948.6	0.06	19.6	0.999

compound name	formula	no of pts	intercept (A)	slope (B)	error* (A)	error* (B)	corr. coeff.
biphenyl		16	-4.577	1694.2	0.02	6.64	0.999
phenyl ether		24	-4.709	1762.2	0.02	13.8	0.999
phenol		30	-6.868	2633.1	0.19	67.4	0.991
1-naphthol		5	-6.220	2690.6	0.23	88.2	0.998
o-cresol		27	-7.470	2839.1	0.29	98.1	0.985
m-cresol		27	-8.326	3261.4	0.33	114	0.985
p-cresol		22	-8.314	3288.9	0.38	132	0.984
2,5-xyleneol		13	-5.581	2099.5	0.08	34.8	0.998
3,4-xyleneol		13	-5.865	2404.6	0.18	76.7	0.995
3,5-xyleneol		13	-6.507	2583.5	0.18	72.5	0.996
resorcinol		13	-6.918	3395.9	0.16	75.2	0.997
lepidine		3	-6.803	2527.4	0.36	112	0.999
pyridine		11	-5.658	2516.5	0.08	39.2	0.999
a-picoline		11	-4.160	1158.5	0.02	6.60	0.999
aniline		28	-5.650	2058.4	0.12	41.8	0.995
2,4-dimethyl pyridine		4	-4.295	1223.7	0.03	9.98	0.999
2,6-dimethyl pyridine		5	-4.235	1200.5	0.01	3.31	1.000

compound name	formula	no of pts	intercept (A)	slope (B)	error* (A)	error* (B)	corr. coeff.
o-toluidine		24	-5.729	2110.3	0.13	46.9	0.995
m-toluidine		19	-5.429	1961.1	0.10	34.5	0.997
p-toluidine		15	-5.045	1800.2	0.06	24.2	0.999
p-ethyl aniline		3	-6.125	2187.7	0.29	91.7	0.999
n-butyl aniline		4	-5.475	1960.6	0.30	97.0	0.998
pyrrole		12	-5.387	1676.8	0.15	44.3	0.996
quinoline		22	-4.534	1714.5	0.06	22.2	0.998
isoquinoline		16	-4.703	1781.9	0.10	34.9	0.997
quinaldine		3	-6.076	2203.3	0.27	84.2	0.999
cyclopentane		6	-4.061	948.5	0.01	3.67	1.000
thiophene		17	-11.31	3150.0	1.21	399	0.897
methyl cyclopentane		7	-4.198	1028.2	0.02	6.29	0.999
ethyl cyclopentane		4	-2.167	484.73	0.56	175	0.890
n-propyl cyclopentane		4	-3.585	1014.3	0.04	10.8	0.999
n-butyl cyclopentane		10	-3.883	1133.6	0.57	186	0.906
n-pentyl cyclopentane		3	-3.887	1246.6	0.13	38.0	0.999
n-hexyl cyclopentane		4	-3.923	1332.2	0.10	29.6	0.999

compound name	formula	no of pts	intercept (A)	slope (B)	error* (A)	error* (B)	corr. coeff
cyclopentene		4	-6.133	1503.5	1.67	486	0.909
cyclohexane		32	-5.161	1506.1	0.05	15.3	0.998
methyl cyclohexane		31	-4.472	1219.1	0.01	2.33	0.999
ethyl cyclohexane		8	-4.101	1149.9	0.12	38.9	0.997
1,3-dimethyl cyclohexane (cis)		2	-4.301	1205.1	#	#	#
1,3-dimethyl cyclohexane (trans)		2	-4.025	1042.5	#	#	#
1,4-dimethyl cyclohexane (cis)		2	-4.305	1157.4	#	#	#
1,4-dimethyl cyclohexane (trans)		2	-4.509	1279.2	#	#	#
x,x'-dimethyl cyclohexane		5	-4.692	1356.1	3.41	1005	0.614
n-propyl cyclohexane		5	-4.574	1341.5	0.00	2.78	1.000
n-butyl cyclohexane		3	-5.133	1582.9	0.06	20.9	0.999
cyclohexene		7	-4.316	1140.2	0.10	32.3	0.998
1-methyl naphthalene		61	-4.640	1688.0	0.04	15.0	0.997
2-methyl naphthalene		22	4.8585	1682.4	0.07	23.8	0.998
tetralin		33	-4.518	1557.3	0.05	15.9	0.998

compound name	formula	no of pts	intercept (A)	slope (B)	error* (A)	error* (B)	corr. coeff.
cis-decalin		3	-4.642	1581.3	0.09	28.5	0.999
trans-decalin		3	-5.082	1846.1	0.09	28.6	0.999
2,3-dimethyl naphthalene		10	-4.057	1475.1	0.06	23.4	0.999
2,6-dimethyl naphthalene		10	-3.915	1383.3	0.04	16.9	0.999
fluorene		12	-4.114	1658.0	0.05	23.0	0.999
fluoranthene		8	-4.738	2326.8	0.14	56.8	0.998
acenaphthene		11	-4.910	1955.3	0.22	83.4	0.992
furan		11	-4.010	892.0	0.00	1.14	1.000
tetrahydro furan		24	-3.870	919.55	0.00	0.33	1.000
indane		9	-4.515	1441.7	0.11	35.4	0.998
indene		9	-4.981	1645.6	0.14	42.9	0.998
styrene		24	-4.367	1196.6	0.03	9.46	0.999
n-hexane	C_6H_{14}	34	-4.051	843.3	0.02	5.11	0.999
n-heptane	C_7H_{16}	40	-4.283	1001.4	0.03	8.30	0.999
thionaphthene		2	-1.46	734.56	#	#	#
n-octane	C_8H_{18}	37	-4.288	1084.8	0.02	5.44	0.999
mesitylene		4	-3.742	1003.6	0.02	6.66	1.000
n-dodecane	$CH_3(CH_2)_{10}CH_3$	46	-4.565	1460.9	0.02	6.57	0.999

* — standard Error for slope (B) is :

$$\text{Std. Error} = \frac{s}{\{\sum (x_i - \bar{x})^2\}^{1/2}}$$

where $s = \frac{SS}{(n-2)}$

SS = Sum of Squares

and $x_i = \left(\frac{1}{\text{Temp}}\right)_i$, $i = 1, n$

n = number of data points.

Standard error for intercept (A) is :

$$\text{Std. Error} = \left\{ \frac{\sum x_i^2}{n \sum (x_i - \bar{x})^2} \right\}^{1/2} \cdot s$$

— No statistical inference were made.

END

**DATE
FILMED**

3 / 30 / 93