MAR 11 1993

DOE/PC/91058--T5

DE93 012457

3572 Iron Works Pike
Lexington, KY 40511-8463
FAX: 606-257-0302

QUARTERLY REPORT FOR PERIOD ENDING

DECEMBER 30, 1992

RECEIVED

MAY 05 1993

OSTI

RATE ENHANCEMENT FOR CATALYTIC

UPGRADING COAL NAPHTHAS

#DE-AC22-90PC91058

P.I.: B. H. Davis

Begin Date: 9/30/91

End Date: 9/29/93

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

BD
No Issues

UK

An Equal Opportunity/
Affirmative Action University

QUARTERLY TECHNICAL PROGRESS REPORT

Rate Enhancement for Catalytic Upgrading Naphthas - Period ending December 30, 1992

Contract No.: DE-AC22-90PC91058

Contractor: University of Kentucky Research Foundation
Kinkead Hall
Lexington, KY 40506-0057

Starting Date: September 30, 1991

Ending Date: September 29, 1993

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

SUMMARY

The removal of heteroatoms from naphtha using first row unsupported metal sulfide catalysts were completed. The maxima HDS activity, normalizing to the same weight of metal, is obtained for manganese sulfide while the minimum HDS activity is obtained for nickel sulfide. Chianelli et al. (1) reported that, for the first row transition metal sulfides, chromium sulfide has the highest activity for HDS of dibenzothiophene and manganese sulfide is the least active. The catalyst activity pattern of the first row transition metal sulfide for hydrodesulfurization of naphtha and dibenzothiophene is different. The maxima HDN activity, normalizing to the same weight of metal, is obtained for chromium sulfide and the minimum HDN activity is obtained for cobalt sulfide.

The effect of substituents on the conversion of nitrogen compounds from the naphtha was also determined. The HDN conversion of alkyl-substituted pyridines and anilines are dominated by electronic effects rather than substituent effects. The effect of alkyl-substitution on the conversion of quinolines is relatively insignificant.

(1) HYDROTREATMENT OF ILLINOIS #6 NAPHTHA USING FIRST ROW TRANSITION METAL SULFIDES

INTRODUCTION:

Exxon workers (1) showed that some metal sulfides of the second and third row transition metals that were more than 10 times as active as MoS_2 for the hydrodesulfurization of dibenzothiophene. Our study is designed to define the possibility of increasing the rate of heteroatom removal by an order of magnitude over the attainable rate with current Co-Mo-alumina or Ni-Mo-alumina catalysts. It is also

designed to define whether heteroatom removal has a common rate for all compounds in each heteroatom class or whether some heteroatom compounds are especially difficult to convert. To characterize a catalyst in terms of its selectivity for individual heteroatom removal reactions for individual compounds in a coal-derived naphtha, methods to determine the amount of each sulfur and nitrogen compounds present in the feed and hydrotreated naphtha is needed. Recently instrumentation with the potential to sample directly from a flame ionization detector to determine the amount of sulfur present in the effluent from a capillary gas chromatograph has become available. Likewise, a nitrogen sensitive GC detector can be utilized for a quantitative determination of individual nitrogen compounds. Thus, the naphtha can be analyzed for composition using a high resolution capillary column gas chromatography.

Although Chianelli et al. (1) showed that the metal sulfides of the first row transition metals have lower activity for the hydrodesulfurization of dibenzothiophene than second and third row transition metal sulfides (Figure 1), the first row transition metal sulfides were evaluated for the following reasons. First, the feedstock used in this work, naphtha, is different from the model compound used for the Chianelli et al. study. Most of the components of naphtha are one ring compounds which are smaller than dibenzothiophene, a two ring compound. The second reason is that Chianelli et al. only studied the hydrodesulfurization; we want to study the hydrodenitrogenation and hydrodeoxygenation as well. Also, the second and third row transition metals are more expensive than the first row transition metals. It would be preferable to use the

first row transition metal sulfides as the catalysts, if they can be shown to have good activities.

EXPERIMENTAL:

Hydrotreatment of the Ill. #6 naphtha sample was carried out using the first row unsupported transition metal sulfides at temperatures of 350 and 400°C. The temperature was varied while holding constant the total pressure (660 psig) and weight hourly space velocity ($\text{WHSV} = 1 \text{ g of feedstock} / \text{g of catalyst} / \text{hour}$). For each experiment, 3 grams of the row 1 unsupported transition sulfides was used.

Individual nitrogen compounds of the hydrotreated Ill. #6 naphtha were analyzed using a Thermionic Specific Detector (TSD) coupled with an Varian 3700 gas chromatograph containing a carbowax column. Sulfur compounds were analyzed using a Sievers Model 350B Chemiluminescence Sulfur Detector (CSD) coupled with an HP 5890 Series II gas chromatograph containing a SPB-1 column. Identification of the nitrogen and sulfur compounds was accomplished by comparison of the retention time to a standard compound.

RESULTS:

Table 1 shows the conditions and results for the preparation of the transition metal sulfides. We were able to obtain transition sulfides with intermediate to high surface areas; these are comparable to the earlier Exxon work.

The nitrogen and sulfur content of products and the % HDN and % HDS are shown in Table 2. These catalysts do not exhibit an especially high activity for the removal of sulfur and nitrogen, compared to Ni-Mo-alumina and Co-Mo-alumina catalysts.

The activities of catalysts are compared on three bases: (1) % HDN and % HDS, based on three grams of catalyst (2) normalizing % HDN and % HDS, based on the 1 gram of transition metal, and (3) normalizing % HDN and % HDS, based on a surface area of 1.7 m²/g (manganese sulfide).

For the HDS reaction, the maximum % HDS activity, based on three grams of catalyst, is obtained for manganese sulfide (Figure 2). Increasing the temperature from 350°C to 400°C results an increase of approximately 25 % for sulfur removal. When normalizing the % HDS to the 1 gram of transition metal (Figure 3), the maxima HDS activity is still obtained for manganese sulfide; the minimum HDS activity is obtained for nickel sulfide. Chianelli et al. (1) reported that chromium sulfide has the highest activity for HDS of dibenzothiophene and manganese sulfide has the lowest activity for the first row transition metals. When normalizing to the same surface area of 1.7 m²/g (Figure 4), the maximum HDS activity is obtained for manganese sulfide and nickel sulfide. Manganese sulfide and nickel sulfide have a relatively low surface area compared to the other catalysts (Table 1), and one may question the validity of comparing low to high surface area. Chianelli et al (1) showed that the surface area normalization results in maximum HDS conversion of dibenzothiophene for manganese and nickel sulfides.

The % HDN based on catalyst weight is approximately the same for all of the catalysts, about 40 % (Figure 5). Increasing the temperature from 350 to 400°C results an increase of approximately 10 % for nitrogen removal. The % HDN, based on the same weight of transition metal (Figure 6) shows that the maximum is obtained for chromium sulfide, and the minimum is obtained for cobalt sulfide. When the % HDN is

normalized to surface area (Figure 7), a significant difference is noted in the curves. The maximum HDN activities is obtained for manganese and nickel sulfides, just as was the case for the HDS reaction.

A comparison of the % HDN vs % HDS based on catalyst weight shows that sulfur removal varies while nitrogen removal remains nearly constant (~40%) (Figure 8).

Conversion of Individual Nitrogen Compounds:

The conversion of individual nitrogen compounds was studied at 350°C, 660 psig and a weight hourly space velocity of 1 g/g/hr.

Pyridines

Figures 9-13 show the results for the conversion of compounds in the pyridine class using vanadium, manganese, iron, cobalt, and nickel sulfides, respectively. For this class, pyridine is the easiest compound to convert for all of the catalysts. The rate of conversion of pyridine substituted by a methyl or ethyl group decreases in the order: unsubstituted > 4- > 2- > 3- for all catalysts. Similar results were observed for the commercial Co-Mo-Alumina and Ni-W-Alumina catalysts. Pyridines with a 2 or more carbons substituent are harder to convert than pyridine with a one carbon substituent.

Anilines

The conversion of compounds in the aniline class using vanadium (Figures 14-15), manganese (Figures 16-17), iron (Figures 18-19), cobalt (Figures 20-21), and nickel (Figures 22-23) sulfides show that unsubstituted aniline is the easiest compound to convert; this is analogous to the pyridine class where the unsubstituted compound

is easier to convert. For all catalysts, anilines substituted with 2 to 4 carbons are harder to convert than anilines with only a one carbon substituent. These figures also show that the conversion of nitrogen compounds depends on the position the group(s) substituted on the ring. The rate of conversion for the mono-methyl or mono-ethyl substituted anilines are: unsubstituted > 4- $\approx$ 2- > 3-. This is the case for all catalysts. However, the conversion of mono-methyl and mono-ethyl aniline is not so dependent on substituents as the pyridines were.

Quinolines

Figures 24-28 show results of the conversion of compounds in the quinoline class using vanadium, manganese, iron, cobalt, and nickel sulfides, respectively. The data show that quinoline is harder to convert than the pyridines were. Unsubstituted quinoline, is converted at about the same rate as one carbon alkyl substituted quinoline with the all catalysts.

Indole and Indoline

Indoline is easier to convert than 1,2-dimethylinole for all catalysts (Figures 29-33).

DISCUSSION:

In general, hydrotreatment of the heavy fractions of coal derived materials is complicated by the molecular weight, and the corresponding large size, of the molecules converted. The large size introduces severe diffusional problems during processing. However, this is not a problem in the hydrotreatment of coal derived naphtha, since the dominant fraction of the material contains only one ring of five or six carbons; two ring components are the largest molecules that will be encountered

and these represent only approximately 10 % of the nitrogen compounds and approximately 24 % of the sulfur compounds. Thus, diffusion limitations due to size exclusion should not be a problem in this study.

Alkyl-substituted heterocyclic compounds were found in the Illinois #6 naphtha. The position of the substituent influences the rate of HDN. For the first row unsupported transition metal catalysts, HDN reactivities of pyridine, aniline and quinoline varies according to the position of substituent added as follows:

pyridine > 4-R-pyridine > 2-R-pyridine > 3-R-pyridine,

Aniline > 4-R-Aniline $\approx$ 2-R-Aniline > 3-R-Aniline, and

Quinoline $\approx$ 3-Methyl-Quinoline $\approx$ 4-Methyl-quinoline,

where R = methyl or ethyl group. 2-Methylquinoline is present in the naphtha in such small quantities that its conversion could not be followed.

Many publications (2-5) have reported that steric and electronic effects may play an important role for the HDS of a number of sulfur compounds. From the point view of steric hindrance, the order of reaction rates for HDN should be 4 > 3 > 2. However, from the point view of electronic effect, the rates should be 4 $\approx$ 2 > 3. HDN of alkyl-substituted anilines and pyridines show the order expect for an electronic effect. The effect of alkyl substituents on the reactivity of quinoline is relatively insignificant. Gates et. al. (5) reported that HDN conversion of 2,6-, 2,7-, and 2,8-dimethylquinoline is approximately the same as that of quinoline.

For the conversion of pyridine and methyl-substituted pyridine, higher conversion were obtained using the iron and nickel sulfides, and lower conversion were obtain using manganese and cobalt sulfides (Figure 34). The conversions of

ethyl-substituted pyridines are approximately the same for all of the catalysts (Figure 35). The conversion of methyl- and ethyl-anilines show a similar pattern where the maximum activity is obtained for iron and nickel sulfides (Figures 36 and 37). However, for the removal of total nitrogen was the highest for vanadium and chromium sulfides (Figure 6).

(2) UPGRADED SULFUR DETECTOR

The model 355 SCD is a sulfur-selective detector for gas chromatography. Operation of the SCD is based on chemiluminescence (light-producing reaction) from the reaction of ozone with sulfur monoxide (SO) produced from combustion of the sample:

A vacuum pump draws the combustion products into a reaction cell at a low pressure and excess ozone is added. Light produced from the subsequent reaction is detected with a blue-sensitive photomultiplier tube and the signal is amplified for display or output to a data system.

The model 355 SCD has an enclosed, dedicated hydrogen burner designed to enhance production of the SO intermediate. The burner mounts in the detector slot of the gas chromatograph (Figure 38). A controller box (Figure 39) provides the temperature control and gas-flow regulation to operate the burner, which is the advantage of the upgraded 355 SCD.

The model 355 SCD provides high sensitivity (<1 pg S/sec), linear, equimolar (per S atom) response, and high selectivity for common solvents.

The interface controller has been preset at the factory to the following:

H ₂ flow turn-on temperature	450°C
Control temperature	780°C
Maximum heater temperature	950°C
Pressure limit	300 torr
H ₂ flow rate	100 std mL/min at 80 psig
Air flow rate	20 std mL/min at 80 psig
Maximum H ₂ inlet pressure	200 psig
Maximum air inlet pressure	200 psig

A characterization of the Ill. #6 naphtha using the SCD couple with the capillary GC shows these materials to contain an extremely complex mixture sulfur compounds. The availability of only a few alkyl substituted thiophenes and benzothiophenes limits the number of peaks in the sulfur chromatograph that can be identified by injection of standard compounds. The organic sulfur compounds will be separated from the naphtha based on a method published by Poirier et. al. (6) The concentrated sulfur will be identified by using GC-MS.

REFERENCES

1. T. A. Pecoraro and R. R. Chianelli, *J. Catal.*, **67**, 430 (1981).
2. B. C. Gates, J. R. Katzer, and G. C. A. Schuit, "Chemistry of Catalytic Processes," McGraw-Hill, New York, 1979.
3. M. Houalla, D. H. Broderick, A. V. Sapre, N. K. Nag, V. H. J. Beer, B. C. Gates, and H. J. Kwart, *J. Catal.*, **61**, 523 (1980).
4. J. H. Singhal, R. L. Espino, and J. E. Sobel, *J. Catal.*, **67**, 446 (1981).

5. B. C. Gates, J. R. Katzer, J. H. Olson, H. Kwart, and A. B. Stiles, Quarterly Report to DOE, June 21 to September 20, 1978.
6. M. A. Poirier and G. T. Smiley, *J. Chromatographic Science*, **22**, July, 1984.

Table 1

Row 1 Transition Sulfide Preparation Conditions and Results

	Ti	V	Cr	Mn	Fe	Co	Ni
Metal	20g	20g	25g	25g	25g	30g	25g
Chloride	TiCl ₄	VCl ₄	CrCl ₃	MnCl ₃	FeCl ₃	CoCl ₂	NiCl ₂
Li ₂ S	9.70g	9.53g	10.88g	10.68g	10.83g	5.79g	8.86
EA, mL	None	None	None	800	800	800	800
THF, mL	800	800	800	None	None	None	None
S _g , m ² /g	4.4	25.82	13.02	1.7	10.18	9.34	1.99

EA = Ethyl Acetate

THF = Tetrahydrofuran

S_g = Surface Area

Table 2

Nitrogen and Sulfur Content of Products
from the Hydrotreatment of Ill. #6 Naphtha

Temp. C	Pressure PSIG	Catalyst	Nitrogen Wt. ppm	Sulfur Wt. ppm	Nitrogen % HDN	Sulfur % HDS
350	660	VSx	1030	370	36.6	52.8
350	660	CrSx	1058	465	36.4	40.7
350	660	MnSx	1034	105	37.8	86.6
350	660	FeSx	1049	393	36.9	49.9
350	660	CoSx	1113	301	33.1	61.6
350	660	NiSx	977	446	39.8	43.1
400	660	VSx	958	223	41	71.6
400	660	CrSx	995	385	38.7	50.9
400	660	MnSx	998	87	40	88.9
400	660	FeSx	1047	288	37	63.3
400	660	CoSx	1103	220	33.7	71.9
400	660	NiSx	970	376	40.3	52

Periodic trends for HDS of DBT/gram of catalyst at 400°C.

HDS of III. #6 Naphtha %HDS, Based on Three Grames of Catalyst

HDS of III. #6 Naphtha %HDS, Based on the 1 Gram of Metal

4

HDS of III. #6 Naphtha
%HDS, Based on Surface Area of 1.7m²/g

HDN of III. #6 Naphtha %HDN, Based on 3 Grams of catalyst

HDN of III. #6 Naphtha %HDN, Based on 1 g of Transition Metal

HDN of III. #6 Naphtha %HDN, Based on Surface Area of 1.7m²/g

% HDS vs % HDN Based on the 3 Grams of Catalysts

HDN for Pyridine Compounds
350 C, 660 Psig, WHSV =1

HDN for Pyridine Compounds 350 C, 660 Psig, WHSV =1

HDN for Pyridine Compounds 350 C, 660 Psig, WHSV =1

HDN for Pyridine Compounds 350 C, 660 Psig, WHSV =1

—▲— NiSx

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

VSx

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

—*— MnSx

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

—□— FeSx

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

—x— CoSx

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Aniline Compounds 350 C, 660 Psig, WHSV = 1

22

HDN for Quinoline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Quinoline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Quinoline Compounds 350 C, 660 Psig, WHSV = 1

—□— FeSx

27

HDN for Quinoline Compounds 350 C, 660 Psig, WHSV = 1

HDN for Quinoline Compounds 350 C, 660 Psig, WHSV = 1

29

HDN for Indoline Compounds 350 C, 660 Psig, WHSV =1

HDN for Indoline Compounds 350 C, 660 Psig, WHSV =1

HDN for Indoline Compounds 350 C, 660 Psig, WHSV =1

HDN for Indoline Compounds 350 C, 660 Psig, WHSV =1

HDN for Indoline Compounds 350 C, 660 Psig, WHSV =1

37

9

Rear Panel Layout

END

DATE
FILMED

5 / 20 / 93