DOE/PC/88812--T15

**PROCESS AND ANALYTICAL STUDIES OF ENHANCED LOW
SEVERITY CO-PROCESSING USING SELECTIVE COAL
PRETREATMENT**

— DOE/PC/88812--T15

DE93 004915

**Robert M. Baldwin and Ronald L. Miller
Chemical Engineering and Petroleum Refining Dept.
Colorado School of Mines
Golden, CO 80401**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**Final Technical Report
December, 1991**

DOE Contract No. DE-AC22-88PC88812

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

The primary objective of this research program was to investigate a variety of mild chemical pretreatment methods for purposes of reactivity enhancement of coal. The application of these pretreatment methods will be used to increase the rate and extent of coal conversion to THF soluble products in the first stage of a two-stage coupled coal liquefaction reaction scheme. If achieved, this will facilitate operation of the reaction system at lower severity (time and/or temperature) conditions where the economics of coal conversion are more favorable.

This research program was divided into two phases. The first phase of the project consisted of an examination of two mild chemical alkylation procedures, and an evaluation of these methods with respect to coal reactivity enhancement. Both selective (oxygen) alkylation and non-selective alkylation procedures from the literature were evaluated on two different coals. The effects of these procedures on coal liquefaction reactivity were measured at low and high severity reaction conditions and under both direct hydro-liquefaction and coal/oil co-processing reaction environments by varying the vehicle used in the liquefaction experiments. Reactivity enhancement was measured by determining the extent of conversion of coal to THF solubles, and comparison of these data with baseline liquefaction data for the untreated coals. Additionally, procedures utilizing photoacoustic FTIR for determining the

chemical changes in coal associated with alkylation procedures were developed.

The findings in this phase were as follows:

1. Both reductive (non-selective) alkylation and selective oxygen alkylation brought about an increase in liquefaction reactivity for both coals.

2. Selective oxygen alkylation is more effective in enhancing the reactivity of low rank coals.

Phase II of the program consisted of three related studies. The first study examined the effect of extent of alkylation on the degree of reactivity enhancement. For this portion of the project, only selective oxygen alkylation was employed as the reactivity enhancement procedure. As before, data were collected at both low and high severity, and under both direct hydrogenation and coal/oil co-processing conditions. The second study examined the effect of solvent swelling on the reactivity of coal. As the oxygen alkylation procedure is carried out in an organic medium that swells coal, this study was designed to separate the chemical effects due to oxygen alkylation from the physical effect (changes in the coal's porosity, etc.) that are associated with swelling. As above, measurements of reactivity change were made at both low and high severity, and under both direct hydrogenation and co-processing reaction conditions.

Finally, the effect of selective mild chemical alkylation on the global kinetics and activation energy for

liquefaction was determined from rate data for both a raw and alkylated subbituminous coal.

In this phase of studies, the major findings were as follows:

1. Liquefaction reactivity increases with increasing level of alkylation for both hydroliquefaction and co-processing reaction conditions.

2. The increase in reactivity found for O-alkylated Wyodak subbituminous coal is caused by chemical changes at phenolic and carboxylic functional sites.

3. O-methylation of Wyodak subbituminous coal reduced the apparent activation energy for liquefaction of this coal.

TABLE OF CONTENTS

	Page
ABSTRACT	iii
1. INTRODUCTION	1
2. LITERATURE SURVEY	4
2.1 Coal Liquefaction	4
2.1.1 Traditional Coal Liquefaction Mechanism	4
2.1.2 Radical Hydrogen Transfer Mechanism	7
2.1.3 Liquefaction Process	9
2.1.4 Two-Stage Liquefaction	13
2.2 Low Severity Liquefaction	14
2.2.1 Promoter Compound Addition	16
2.2.2 Catalyst Addition	17
2.3 Chemical Pretreatment Methods	18
2.3.1 Friedel Crafts Alkylation of Coal	18
2.3.2 Friedel Crafts Acetylation of Coal	20
2.3.3 Acid Catalyst Depolymerization of Coal .	20
2.3.4 Reductive Alkylation	21
2.3.5 Oxygen Alkylation	23
2.3.6 Solvent Swelling Pretreatment	25
2.4 Coal Reactivity	27
2.5 Lumped Parameter Kinetic Models	32
2.6 Kinetic Modeling	33
2.7 FTIR Studies of Coal	35
2.7.1 Aliphatic and Aromatic Hydrogen	37
2.7.2 The Hydroxyl Functional Group	38

2.7.3	The 1600 $^{-1}$ cm Absorption Band	39
3.	EXPERIMENTAL	41
3.1	Equipment	41
3.1.1	Reactor System	41
3.1.2	Analytical Equipment	44
3.2	Coals and Reagents	44
3.2.1	Coals	44
3.2.2	Reagents	45
3.3	Batch Reactor Run Procedure	45
3.4	Analytical Procedures	50
3.4.1	THF/Hexane Conversion Analysis	50
3.4.2	FTIR Analysis Procedure	51
3.4.3	Solvent Swelling Ratio	54
3.4.4	Gas Analysis	57
3.5	Pretreatment Methods	60
3.5.1	Reductive Alkylation	60
3.5.2	Oxygen Alkylation	62
3.5.3	Coal Swelling Pretreatment	63
3.5.4	Residuum Hydrotreating	64
3.6	Determination of Extent of Alkylation	65
4.	EXPERIMENTAL DESIGN	68
5.	RESULTS AND DISCUSSION	75
5.1	Phase I Preliminary Work	75
5.1.1	Introduction	75
5.1.2	Liquefaction Reactivity Preliminary Experiments	78
5.1.2.1	Untreated Coal	78

5.1.2.2	O-Alkylation of Coal	80
5.1.2.3	Reductively Alkylation of Coal .	83
5.1.3	Co-processing Reactivity Preliminary	
	Experiments	86
5.1.3.1	Untreated Coal	86
5.1.3.2	O-Alkylated Coal	88
5.1.3.3	Reductively Alkylated Coal	91
5.1.4	FTIR Studies of Treated and	
	Untreated Coal	95
5.1.4.1	FTIR Spectra of Raw Coal	95
5.1.4.2	Spectra for O-Alkylated Coal .	99
5.1.4.3	Spectra for Reductively	
	Alkylated Coal	103
5.1.4.4	Spectra for Solvent	
	Swollen Coal	104
5.2	Phase II Further Studies of Selectively	
	Alkylation of Wyodak Coal	104
5.2.1	Introduction	104
5.2.2	The Effect of Solvent Preswelling	
	on Coal Reactivity	109
5.2.2.1	Effect of Non-polar and Polar	
	Solvents on Coal Swelling	110
5.2.2.2	Effect of THF Preswelling on	
	Liquefaction of Wyodak and	
	Illinois #6 Coals	113
5.2.2.3	Effect of Operating Conditions	

	on Liquefaction Reactivity of	
	THF Preswollen Wyodak Coal ...	117
5.2.3	Effect of Extent of Oxygen Methylation	121
5.2.3.1	Effect of the Extent of Oxygen	
	Methylation of Wyodak Coal on	
	Intrinsic THF Solubility	121
5.2.3.2	Effect of the Extent of	
	O-Methylated Wyodak Coal on	
	Liquefaction Reactivity	126
5.2.3.3	Effect of Extent of Alkylation	
	on Co-processing of Wyodak Coal	138
5.2.3.4	Gas Analysis Results	140
5.2.4	Effect of Coal O-Methylation on Global	
	Reaction Kinetics and Apparent	
	Activation Energy	145
	LITERATURE CITED	174

1. INTRODUCTION

From a chemical viewpoint, the principal difference between coal and petroleum is the much lower H/C ratio of coal (1). Berthelot, in 1869, reported that coal could be converted by reduction to an oil-like product (2). This concept has subsequently led to many developments in coal liquefaction. In order to produce liquids from coal, the following general chemical changes must be accomplished:

- Reduction of average molecular weight by bond rupture
- Addition of hydrogen to increase H/C ratio
- Removal of mineral matter
- Removal of heteroatomic species (S,O,N) by transformation into their hydrogenated gaseous states (3).

Early development schemes for coal liquefaction such as the Bergius process involved extremely high temperatures (500 °C) in the presence of hydrogen gas at pressures as high as 133 MPa (2). These conditions caused thermal scission of bonds, and extensive disruption of the coal structure. Radicals from thermal scission were then capped by hydrogen atoms. In the absence of a hydrogen source (radical quenching mechanism), the primary free radicals can recombine to form products of high molecular weight, in some cases larger than that of the parent coal (3).

At high temperatures, many undesirable side reactions such as cracking, char formation, and dehydrogenation can occur. This is especially true for low rank coals which

contain many oxygen functionalities, and therefore are more reactive than higher rank coals. Recently, liquefaction research has been focused on lower severity operating conditions. Liquefaction at low severity conditions (temperature lower than 350 °C and reaction time shorter than 30 min) has several advantages including (4,5):

- Reduced production of undesirable light hydrocarbon gases,
- Lower hydrogen consumption,
- Less coke and char formation,
- Significant energy saving.

Unfortunately, operation at lower severity gives lower conversion rates and levels for coal. To overcome this problem, several techniques can be employed to enhance the reactivity of coal, including:

- chemical pretreatment
- addition of catalysts
- impregnation of coal with catalysts or promoters.

1.1 Objective

The primary objective of this research program is to investigate a variety of mild chemical pretreatment methods for purposes of reactivity enhancement of coal. The application of these pretreatment methods will be used to increase the rate and extent of coal conversion to THF soluble products in the first stage of a two-stage coupled coal liquefaction reaction scheme. If achieved, this will facilitate operation of the reaction system at lower

severity (time and/or temperature) conditions where the economics of coal conversion are more favorable.

There are many techniques potentially available which can be used to pretreat coal. The objective of this project is to evaluate mild chemical alkylation methods which only minimally disrupt the coal structure but which may significantly enhance the coal's reactivity with respect to low severity direct liquefaction or co-processing.

2. LITERATURE SURVEY

2.1 Coal Liquefaction

Coal liquefaction can be considered as the process of converting solid coal into a liquid (1, 2). Most of the current processes for liquefaction of coal have many features in common, and are largely extensions of the early work by Berguis. Most direct coal hydroliquefaction procedures consist of first drying and pulverizing coal, and then slurring with a coal-derived recycle oil. The slurry is then pumped into a high pressure reactor, wherein the coal is liquefied by hydrogenation at high temperature and pressure.

Under mild conditions (low temperature, low pressure, and short reaction times) or in the absence of catalyst, the liquefaction product is usually a heavy oil suitable for boiler fuel applications. Under more severe conditions the heavy oil can be further converted into distillate products. In either case the products generally require extensive further upgrading before they are suitable for use as fuels (2).

2.1.1 Traditional Coal Liquefaction Mechanism

The process of direct hydroliquefaction of coal is widely believed to follow a free radical mechanism. Thermal cleavage of weak bonds in the coal matrix (C-O, C-S, -S-S-, etc.) are assumed to initiate the free radical process. It has been reasonably well established that at temperatures above 350 °C the pyrolytic breakup of the coal

matrix begins. A large number of concurrent and competitive chemical reactions occur during the liquefaction process, such as thermolysis, hydrogen abstraction, dealkylation, cleavage of bridges between structural units, desulfurization, dehydration, and ring opening. After one or more of these weak bonds has been cleaved, the free radicals generated are thought to be stabilized by the addition of hydrogen. The hydrogen may be added either from molecular hydrogen (indirectly via hydrogen dissociation catalysts) or from a hydrogen-donor solvent, especially when a hydroaromatic such as tetralin or a tetralin-like species is present. Hydroaromatics are, in general, good donors due to the fact that the partially dehydrogenated intermediate is a relatively stable benzylic-type free radical and the product after the loss of four hydrogen atoms is a stable aromatic compound. In the absence of a good hydrogen source, the free radicals may couple (regressive reaction) to form coke or char. In the traditional picture, the solvent serves merely to stabilize or scavenge radicals generated by the thermal scission of inherently weak links in the coal structure.

The solvent effectiveness thus depends on two factors:

1. ease of conversion of Ar to ArH_2 and,
2. effectiveness of ArH_2 as a scavenger (3).

There are some features of coal liquefaction which, however, can not be explained by the traditional concepts outlined above. These features include:

1. The lack of correlation between coal conversion effectiveness of hydroaromatic hydrogen donor molecules and the benzyl radical scavenging ability of these same hydroaromatics;

2. The lack of an explanation for why a purely aromatic fluid can serve as an effective coal liquefaction solvent.

2.1.2 Radical Hydrogen Transfer Mechanism

McMillen and his co-workers have recently proposed a radical hydrogen transfer mechanism in an attempt to rationalize some of the above inconsistencies. McMillen et al. (4, 5) found that hydrogen transfer plays a critical role both in bond scission and in bond formation. Hydrogen transfer includes not only abstraction of hydrogen by free radicals from donor solvent components, but also hydrogen transfer to closed shell alkyl-aromatic structures. This latter type of H-transfer can bring about cleavage of strong bonds during coal conversion, as shown first by Vernon (6).

Evidence is available from the literature to support the suggestion that the better solvents are those that more effectively mediate the transfer of hydrogen to positions on aromatic clusters bearing linkages. It is well known from the technology of high-temperature hydropyrolysis that formation of cyclohexadienyl intermediates will lead extremely rapidly at 400 °C to cleavage of virtually any except di-aryl linkages (3). McMillen et al. have coined the phrase "radical hydrogen transfer" to describe the type

of hydrogen atom chemistry that may take place under hydroliquefaction conditions.

2.1.3 Liquefaction Processes

The first large scale direct coal liquefaction process was developed by Berguis in 1913 and used in Germany for producing transportation fuels and heating oils during World War II. This process used high temperatures (c.a. 500 °C) and high pressures (up to 140 MPa) in the presence of added catalysts in order to obtain total coal conversions of nearly 100 % (moisture and ash free basis).

There are two types of direct coal liquefaction processes: solvent extraction and direct hydrogenation. For the solvent extraction process, there is no catalyst used and the hydrogen necessary is supplied by an overpressure of hydrogen gas which reaches the coal both by direct contact and via the solvent, which enhances the hydrogenation process by shuttling hydrogen from the gas phase to reactive coal sites. Solvent extraction results in a low degree of hydrogenation, and was initially developed as a tool for studying the composition of coal by analysis of the liquefaction products which were artifacts of the original coal structure. An example of this type of process is the SRC-I (Solvent Refined Coal-I) process developed by Gulf Corporation. In the SRC-I process (2, 3), ground coal is mixed with recycle solvent and hydrogen gas. The slurry is preheated, then reacted for 30-90 minutes at 800 °F, 1000-2000 psig operating pressure. Following this dissolution

step, the products are filtered in a rotary pressure precoat filter drum to remove ash and unconverted coal. The primary products of this process are a solid fuel which melts at 350 °F and is low in sulfur and ash content (0.5 and 0.1 wt % respectively).

Direct hydrogenation is another type of coal liquefaction process. The degree of hydrogenation in this process is much higher than for the solvent extraction process. This process, which may be operated thermally or in the presence of a heterogeneous catalyst, produces a cleaner product since most of the sulfur, oxygen and nitrogen compounds in coal are converted into hydrogen sulfide, water, and ammonia respectively. Examples of this type of process are SRC-II, H-Coal, and the Exxon Donor Solvent Process.

Liquefaction processes which were developed before the 1980's were single stage operations. These single stage liquefaction processes had several features in common:

1. Reaction severity was high with temperatures of 820-860 °F and liquid residence times of 20-60 minutes. These severe conditions were considered necessary to achieve coal conversions of over 90 percent.

2. Distillate yields were low (about 50 percent of MAF coal with bituminous coal and even lower for subbituminous coal).

3. Hydrogen efficiency was low due to the high yield of hydrocarbon gases (3).

2.1.4 Two-Stage Liquefaction Processes

A new generation of direct liquefaction processes have been developed during the 1980's. These processes are based on two-stage liquefaction which separates the upgrading and hydrol liquefaction reactions into separate reaction vessels. In two-stage liquefaction both stages can be operated somewhat independently in order to optimize reaction efficiency for the primary coal conversion and upgrading steps. Most two-stage liquefaction processes use the first stage of the process to dissolve and depolymerize the coal, exposing more of the coal's surface area as dissolution starts to occur. The depolymerized coal is then injected into a second stage where it is catalytically upgraded to distillate products (5, 7).

As mentioned earlier, most liquefaction processes operate at high severity (high temperature, long reaction time) conditions. The disadvantages of these processes are as follows (5):

- more hydrocarbon gas products are formed,
- higher hydrogen consumption,
- shorter catalyst life (Stage II).

2.2 Low Severity Liquefaction

In order to make coal liquefaction economically acceptable, the process must be operated at a lower temperature and pressure in order to reduce operating costs while maintaining high conversion and a high degree of

selectivity to liquid products. To achieve this goal one might propose the following methods:

- add promoters to aid coal dissolution,
- add catalysts to enhance reaction rate, or
- pretreat coal in order to enhance coal reactivity

2.2.1 Promoter Compound Addition

Promoter compounds can be added to aid dissolution of coal. Well known promoters are basic nitrogen compounds such as 1,2,3,4-tetrahydroquinoline (THQ) and dipropylamine. These compounds have provided a remarkable increase in coal conversion at severe reaction conditions, with up to 100% coal dissolution obtained in some cases. A drawback, however, is that these compounds are often adducted into product fractions (8). Nitrogen compounds of these types promote coal dissolution via electron attack and subsequent reaction with electron deficient sites. The nitrogen atom in these compounds is electron rich, and thus it promotes bond cleavage by attacking electron deficient sites. Electron deficient sites are largely represented by heteroatomic bond linkages in the coal structure. THQ is also a very effective hydrogen donor, which can cap coal-derived radicals as they are formed during thermal dissolution. These nitrogen compounds are, however, often irreversibly incorporated into product fractions especially at high reaction severity. At low reaction severity nitrogen compound adduction may be reduced. Giacomelli and Miller (8) found that at low severity co-processing

conditions, adduction losses were as low as 14% by weight. However, even this small loss made the process economically unfeasible due to process solvent that would be lost to the final liquefaction products. The other major disadvantage of nitrogen compound addition is due to the problem of poisoning of downstream hydroprocessing catalysts (9).

2.2.2 Catalyst Addition

Catalysts have been used in coal liquefaction in order to accelerate the process of bond rupture, to transfer hydrogen to stabilize coal radical molecules in order to prevent polymerization reactions, and to remove heteroatoms such as sulfur, nitrogen, and oxygen.

There are many studies using catalysts in liquefaction as reviewed by Derbyshire (10), Anderson (11), Wu (12), and others. These and other studies have shown that if the right catalyst is selected, conversion to a low boiling point range hydrocarbon liquid can be achieved.

Anderson (11) tested more than eighty catalysts for the direct conversion of coal to liquids. He found that there is a direct correlation between the liquefaction products yield and the electronic "softness" of the Lewis acids. Lewis acids have an effect on cleavage of etheric linkages, alkyl linkages attached to ring systems and carbon-heteroatomic bonds.

Gorin and co-workers (13) have published the results of an extensive investigation using molten halide catalysts for the hydrogenation of polynuclear hydrocarbons, coal extract

effluents, and coal. They found that, by using massive quantities of zinc halide catalysts, single-stage conversion of either coal or coal effluent to high octane gasoline at relatively mild conditions was possible.

2.3 Chemical Pretreatment Methods

2.3.1 Friedel-Crafts Alkylation of Coal

Friedel-Crafts alkylation is considered to be a carbon alkylation (C-alkylation) procedure. Kroger (2,14) used Friedel-Crafts alkylation to increase solubility of coal by treating coal with an alkyl chloride (such as isopropyl chloride) and AlCl_3 in carbon disulfide at 45 °C. The reaction relied on the strong acidic nature of the aluminium trichloride. The alkyl halide used is thought to be converted to the alkene necessary for the reaction. Up to 10 or 11 alkyl groups were added per 100 carbon atoms and up to 70 % of the alkylated material was found to be soluble in pyridine. Despite its greater solubility, the reaction product was more highly aromatic than its precursor coal, probably as a result of simultaneous AlCl_3 -catalyzed condensation.

AlCl_3 has also been found to accelerate formation of graphite from aromatic compounds(9). Later findings have shown that the increase in solubility was due to the cleavage of methylene and ethylene linkages, oxygen alkylation (O-alkylation) and disruption of coal structure (15).

Schlosberg (16) alkylated coal under Friedel-Crafts conditions using isopropanol and methyl halide as reagents. The treated coals were then liquefied in tetralin at 10.3 MPa hydrogen pressure at 425 °C for 130 min. Schloberg found that liquefaction yields increased upon alkylation, and he put forward the premise that alkylation disrupts the coal structure sufficiently to allow improved contacting between coal and tetralin solvent during liquefaction.

2.3.2 Friedel-Crafts Acetylation of Coal

Hodek and Koelling (17) have shown that the Friedel-Crafts acylation of coal resulted in an increase in extractability which was dependent on the chain length of the inserted acyl groups. They used carboxylic acid chlorides to acylate coals with an aluminium chloride catalyst. The possible mechanisms are believed to be: (1) depolymerization of coal through the rupture of methylene bridges to form lower molecular weight fragments which are then capped with acyl groups, (2) cleavage of hydrogen bonding by esterification of the phenolic-hydroxyl groups, and (3) neutralization of intermolecular forces between the aromatic clusters by insertion of long chain substituents.

2.3.3 Acid-Catalysed Depolymerization of Coal

Heredy and Nueworth (15) discovered that coal could be depolymerized by a reaction in which phenol and acid catalysts (BF_3) were used. They found that partial depolymerization of coal occurred when an alkylation process cleaved a methylene chain between adjoining aromatic

structures. The cleavage methylene groups were then free to alkylate with other aromatic substrates, resulting in shorter aromatic chains within the coal structure.

2.3.4 Reductive Alkylation

Reductive alkylation of coal was first developed by Sternberg (18, 19, 20). In the Sternberg method, coal is reacted with an alkali metal in the presence of an electron transfer agent to form an anion at aromatic coal sites. An alkyl halide is next introduced to the solution and reacted with anionic coal. The reaction also can occur at aromatic oxygen functionalities. Sternberg (18) reported that this procedure resulted in the addition of 8.1 methyl groups /100 C atoms addition for a Pocahontas (lvb) vitrain sample. Methylation and butylation of Pocahontas coal resulted in a 47% and 92% increase in pyridine solubilities for each alkylation process respectively. From the studies of Date (21) and Lazarov (22), it was concluded that the change in coal solubility in benzene and THF upon alkylation increased with increasing coal rank.

The Sternberg process is considered to be a non-selective alkylation procedure which occurs at polar coal sites such as hydroxyl and carboxylic functionalities or aromatic anionic carbon sites in the coal. Sternberg's method is a very effective technique for rendering coal soluble in an organic solvent under mild conditions, but there are problems associated with this method such as:

1. Long reaction time required (2-14 days)

2. Contamination of reaction products by naphthalene.

There have been many attempts to improve on Sternberg's method. Miyaki (23) used molten potassium metal instead of solid potassium and naphthalene. Miyaki found that a 50% yield of hexane solubles products could be obtained from ethylated Yabari coal. However this process was not economically suitable as a pretreatment method due to longer reaction time and problems with potassium separation.

2.3.5 Oxygen Alkylation

This procedure has been developed by Liotta (24, 25) and is referred to as oxygen alkylation (O-alkylation) due to the fact that the method selectively alkylates oxygen functional groups (phenolic and carboxylic group) to ether or ester functional groups. Alkylation of these acidic sites dramatically changes the properties of the coal, significantly reducing the degree of hydrogen bonding.

In this procedure coal is first reacted with tetrabutyl ammonium hydroxide, which is a good swelling agent and a strong base, displacing the acidic protons with the tetrabutyl ammonium ion. An alkyl halide is then introduced into the mixture, replacing the tetrabutyl ammonium group with an alkyl group.

Liotta used this procedure to alkylated bituminous and subbituminous coals. In his study approximately 5 methyl groups/100 C atoms were added to a sample of Illinois #6 coal and approximately 8 methyl groups/100 C atoms were added to a Rawhide subbituminous coal. From IR spectroscopy

of untreated and treated coals, Liotta showed that hydroxyl functional groups were converted to ether derivatives and carboxylic acid functional groups were converted to O-methylcarboxylic ester derivatives.

Lazarov (22) reported that for bituminous coals, the increase in THF solubility upon butylation was roughly proportional to the number of butyl groups added to the coal. For 0.02 butyl groups added per 100 C atoms, the coal's THF solubility increased by 1.2%, whereas the addition of 1.4 butyl groups per 100 C atoms increased the THF solubility of coal by 15 %. Date (21) reported that low rank coals showed a higher percentage increase in THF solubility than did higher rank coal upon oxygen alkylation. This finding is similar to the conclusion reached by these researchers using reductive alkylation.

2.3.6 Solvent Swelling Pretreatment

In recent years, there has been rapid growth in research that deals with the subject of solvent swelling of coal. Much of this effort has been directed towards the application of modern polymer and network theories of coal, with the purpose of better understanding coal structure (26, 27). Few studies have been published on the effect of solvent swelling on coal reactivity. The method used most frequently in coal swelling studies is vapor sorption (gravimetric method) which has a major drawback due to the time consuming nature of the procedure. Liotta (28) developed a volumetric swelling test for coal which was more

convenient than the gravimetric (vapor sorption) technique. Green (29) applied the method developed by Liotta to Bruceton and Illinois #6 coals using 10 solvents. The results were compared with results of gravimetric swelling experiments, and very good linear correlations were observed between the two methods. Green also suggested that the pore volume of coal can be determined by plots of gravimetric vs. volumetric swelling. Green and West (30) studied the degree of swelling of coal in different types of n-amines and n-alcohols. These researchers found that the degree of coal swelling increased with increasing size and increasing chain length of n-alkylamine, but the amount of absorbed n-alkyl alcohols decreased with increasing size of alcohol.

Rincon and Cruz (31) performed swelling experiments on three different ranks of coal in THF, and found that the swelling ratio was higher for low rank coals. The coal was swollen in THF for 48 hrs. and solvent was removed, then the preswollen coal was liquefied in tetralin, petroleum heavy oil (PHO), anthracene oil (AO) and a mixture of PHO and AO. The preswollen coal showed an increase in the yield of THF soluble material after liquefaction. This enhancement was greater for coals with a higher swelling ratio (lower rank).

Joseph (32, 33) studied the swelling behavior of coal of three different ranks (bituminous, subbituminous, and lignite) and the effect of preswelling on their thermal and catalytic hydroliquefaction behavior. Tetrahydrofuran, tetrabutyl ammoniumhydroxide and methanol were used as

preswelling solvents. He found that preswelling of coal improved subsequent liquefaction yield and product quality. The enhancement was dependent on coal rank and the swelling agent and was a maximum for bituminous coal. Joseph suggested that the beneficial effect of swelling may be due to the expansion of the coal macromolecular structure, making it more accessible to hydrogen donor solvent. The enhanced accessibility may enable prompt capping of the coal free radicals with concomitant reduction in retrograde reactions and facilitation of solvent-induced bond cleavage reactions. These effects are reflected in higher liquefaction yields and improved product quality.

2.4 Coal Reactivity

The relationship between coal chemical and structural features and coal reactivity has been the subject of considerable research for well over 70 years (34, 35, 36, 37, 38). Early studies on the influence of coal properties on coal reactivity were focused on an attempt to find a single parameter or group of parameters capable of correlating physical, chemical and geochemical properties with the degree of conversion to some solvent-soluble products under a fixed set of reaction conditions. In the late 1970's, Given et al. (39, 40, 41, 42) completed an extensive liquefaction reactivity study using more than one hundred different U.S. coals. In these studies, Given and his co-workers attempted to establish parameters capable of correlating liquefaction behavior to composition, and

ultimately these researchers developed multiparameter statistical correlations for coal reactivity for an extensive suite of U.S. coals. These correlations were partitioned according to geographical location in order to increase the significance of the relationships.

In their study, Given et al. defined coal reactivity as the percentage of coal converted to ethyl acetate soluble products for a reaction time of 60 minutes. The results of their work can be summarized as follows:

1. Attempts to correlate coal properties solely with a rank parameter, such as carbon content were not adequate.

2. Geographic origin is one of the key factors affecting coal liquefaction behavior.

3. The liquefaction behavior of coals can vary widely depending on their chemical and petrographic characteristics.

4. Sulfur content is one of the major factors in defining coal reactivity populations.

Other researchers have attempted to correlate coal hydroliquefaction reactivity with mineral matter in coal (43, 44, 45, 46), most notably pyrites, and other physical and chemical properties (47, 48, 49, 50).

The concept of point-yield conversion at a given residence time as the definition of reactivity has been used by many researchers. This definition of reactivity does not however provide any insight into the rate processes involved in coal liquefaction. Furlong (51) proposed that a

kinetically defined reactivity would have a more direct correlation with parent coal properties than a reactivity defined by a single point yield conversion. Furlong showed that a kinetic definition was superior in ranking reactivity among closely related coals.

Shin (52, 53) proposed an "area" reactivity parameter that combined both rate of reaction and extent of reaction concepts based on the measured liquefaction kinetic profiles. He used the "area" reactivity parameter in single variable linear correlations with basic coal chemical and geochemical features such as volatile matter content, atomic H/C and O/C ratios and vitrinite reflectance.

Two coals with the same rate constant may also show different conversions at long reaction times, and these differences must also be considered in the definition of reactivity. Further, it is clear that the relationship between reactivity and composition found at some specified reaction temperature can not be generally applied to other reaction temperatures. In general, the definitions applied in the literature for coal reactivity can be categorized as:

- 1) a point-yield at fixed time and temperature
- 2) a reaction profile with time at fixed temperature.

While both of these reactivity definitions can be correlated with liquefaction reactivity, the correlations developed are not truly universal in that they may not hold at different time and/or temperature levels. The above discussion highlights the need for a reactivity parameter that is

independent of both time and temperature. This leads logically to consideration of activation energy as a fundamental reactivity parameter, since:

- activation energy includes temperature effects;
- activation energy should reflect more closely the chemical nature of the parent coal;
- activation energy is obtained by measuring time and temperature effects, but the result is time and temperature independent.

Anthony and Howard (54, 55) used the concept of a normal distribution of activation energies in order to obtain an expression for the formation of volatile products from coal pyrolysis reactions. This, they found, fitted the experimentally observed volatile yields both for a low rank Montana lignite and high volatile bituminous coal.

Szladow and Given (56) presented a phenomenological approach based on the theoretical analysis of many parallel reaction pathways in a complex reacting mixture. Szladow and Given calculated the apparent activation energy for coal dissolution reactions producing pyridine solubles. The apparent activation energy was found to increase with conversion. They showed that the use of apparent activation energy concept reduced the number of possible kinetic structures.

Shin (57, 58) correlated the activation energy of coal conversion to THF and toluene solubles with fundamental coal chemical properties. In this research, five bituminous coal

from the Argonne Premium Sample Bank were used. This researcher found that there was a strong correlation of aliphatic hydrogen content of the coal with activation energy for THF solubles. Toluene solubles activation energies were highly correlated ($R^2 > 0.90$) with total oxygen and with protonated aliphatic carbon. He also found that etheric oxygen in cross-linking structures was important for determination of bituminous coal hydroliquefaction reactivity.

2.5 Lumped Parameter Kinetic Models

In reactions that involve numerous species it is often not practical to develop kinetic models that describe the behavior of all the participating species. It is convenient therefore to group various species together and treat them as pseudocomponents. Models based on such an approach have been termed lumped parameter models (59, 60, 61, 62). The success of such a model depend upon the kinetic similarity of the species present in the lump. The numerous product species of coal liquefaction are usually lumped together into several groups based on solubility criteria. Coal liquefaction products are often defined as follows:

- preasphaltenes: products which are soluble in tetrahydrofuran and insoluble in toluene,
- asphaltenes: products soluble in toluene but insoluble in hexane, and
- oils: products which are soluble in hexane.

It is imperative to realize that a proper kinetic model can be developed only if the lumped pseudocomponents display similar reactivity. This problem with lumped models is not unique to coal liquefaction and indeed is common to many complex reaction systems involving simultaneous interaction of numerous species. The obvious advantage in the lumped-component approach lies in the ease of product analysis, the most expensive part of developing any model. The major disadvantage of the lumped model is the fact that such models are based on pseudocomponents and thus are essentially correlative in nature; these models have very little scope for generalization. Hence they cannot be used to predict the liquefaction behavior of coals other than the one used in developing the model. The essential feature of this modeling strategy is the inherent assumption that lumping leads to kinetically similar fractions which, in conjunction with simple series/parallel reaction networks can adequately correlate the experimental data.

2.6 Kinetic Modeling

Coal liquefaction in donor solvents has been extensively studied, with many complex reaction schemes suggested to model the dissolution/hydrogenation of coal in liquefaction processes. In 1951, one of the earliest models for the liquefaction of bituminous Dutch coals using anthracene oil and beta-naphtol as solvents was proposed by Oele et al. (63). The rate data obtained by these researchers were correlated with a reversible model,

assuming that the forward reaction was zero order and that reverse reaction was first order with respect to the fraction of extracted material.

As many cyclic hydrocarbons show a second-order concentration dependency for thermal decomposition, Hill (64) and later Wiser (65) modeled batch coal dissolution data in tetralin with second-order rate expressions, explaining coal conversion as a series of reactions, each producing liquids, gases, and reactive fractions.

Falkum and Glenn (66) proposed that the hydrogenation of Spitsbergen coal occurred in two distinct stages and suggested that two constituents are present in coal, one of which degrades much faster than the other. A similar model, involving two reactive constituents, was utilized by Curran et al. (67) to fit their experimental conversion data on coal extraction and coal-extract hydrocracking processes. Weller et al. (68) proposed that the conversion of coal to oils involved two consecutive first order reactions, with asphaltenes as an intermediate products. On the other hand Liebenberg and Potgieter (69) proposed two simultaneous reactions for the formation of oils and asphaltenes in order to explain their experimental data. Yoshida et al. (70) expanded this model to allow for oils formation by two paths.

More complex models have been proposed using preasphaltenes as products in addition to oils and asphaltenes. These models have been employed by Shalabi et

al. (71) for batch liquefaction data and by Cronauer(72) for data from continuous reactor.

A summary of some of the published models is presented in Table 1 (73). All kinetic models mentioned above were obtained by assuming reaction paths among the various lumped coal-derived products, and best-fit models were obtained for the experimental data by using regression schemes. These kinetic models thus do not necessarily represent the true reaction mechanism and due to their empirical nature, do not allow any generalizations based on the derived parameters (rate constants).

2.7 FTIR Studies of Coal

Infrared spectroscopy (IR) is an important and extensively used analytical tool for determining the structure of organic materials. In the late 1950's and early 1960's IR was a widely used analytical tool for investigating coal structure. The IR technique was however, limited by the overlap and superposition of vibrational modes characteristic of complex multicomponent systems. The introduction of Fourier transform infrared (FTIR) spectrometers has opened up new possibilities for the spectroscopic characterization of coal and coal-derived materials. Because of the difficulty associated with measuring the spectra of solid samples with traditional transmission (KBr disc) methods, photoacoustic FTIR was developed. This technique allows IR spectra of solid samples to be obtained essentially without preparation.

Table 1
Summary of Some Published Kinetic Models (73)

Investigators	Year	Kinetic model	Coal	Donor solvent	Catal
Weller <i>et al.</i>	1951	$C^* \rightarrow A \rightarrow O$	Pittsburgh Anthraxylon	None	SnS
Falkum and Glenn	1952	$\begin{array}{c} C_1^* \\ \diagdown \\ C_2^* \end{array} \rightarrow A + O$	Spitsbergen	None	Cf
Pelipetz <i>et al.</i>	1955	$C^* \rightarrow A + O$	Wyoming	None	†
Hill <i>et al.</i>	1966	$C^* \rightarrow A + O$	Utah	Tetralin	
Curran <i>et al.</i>	1967	$\begin{array}{c} C_1^* \\ \diagdown \\ C_2^* \end{array} \rightarrow A + O$	Pittsburgh	Tetralin	
Struck <i>et al.</i>	1969	$\begin{array}{c} C_1^* \\ \diagdown \\ C_2^* \end{array} \rightarrow A + O$	Pittsburgh extract	None	
Liebenberg and Potgieter	1973	$C^* \begin{array}{l} \nearrow A \\ \searrow O \end{array} \left[\begin{array}{l} \text{Suggested} \\ \text{model} \end{array} \right] \begin{array}{l} C^* \begin{array}{l} \nearrow A \\ \searrow H-O \end{array} \\ \nearrow A-HO \\ \searrow H-O \end{array}$	Bituminous	Tetralin	N
Yoshida <i>et al.</i>	1976	$C^* \begin{array}{l} \nearrow A \\ \searrow O \end{array}$	Japanese	Decrystallized anthracene oil	Red sulph
Cronouer <i>et al.</i>	1978	$\begin{array}{c} G \\ \diagdown \\ C \begin{array}{c} \nearrow O \\ \searrow A \\ \diagdown P \end{array} \end{array}$	Belle Ayr (subbituminous)	Hydrogenated phenanthrene	None
Shalabi <i>et al.</i>	1979	$\begin{array}{c} O \\ \diagdown \\ C \begin{array}{c} \nearrow A \\ \searrow P \end{array} \end{array}$	Kentucky No. 9 (bituminous)	Tetralin	None
Gun <i>et al.</i>	1979	$\begin{array}{c} C-O-A-O_2 \\ \diagdown \\ BI-O_3 \end{array}$	Assam (Makum)	Tetralin	Impregnat sulphur
Mohan and Silla	1981	$C \begin{array}{c} \nearrow P \\ \searrow A \\ \diagdown O \end{array}$	Illinois No. 6 (bituminous)	Tetralin	None
Gertenbach <i>et al.</i>	1982	$\begin{array}{c} C \begin{array}{c} \nearrow P \\ \searrow H \\ \diagdown O \end{array} \begin{array}{c} \nearrow A \\ \searrow A \end{array} \end{array}$	Kentucky No. 9 (bituminous)	Steady state recycle oil from the Fort Lewis pilot plant (< 250 C vacuum cut)	None
Abusleme <i>et al.</i>	1983	$\begin{array}{c} P \\ \diagdown \\ C \begin{array}{c} \nearrow O \\ \searrow A \end{array} \end{array}$	Chilean subbituminous (Catamutun and pecket)	Coal-derived liquid	Commercial Co-Mo ₂ -Al ₂ O ₃
Ozawa <i>et al.</i>	1984	$\begin{array}{c} C \begin{array}{c} \nearrow O_1 \\ \searrow P \\ \diagdown A \end{array} \begin{array}{c} \nearrow O_2 \\ \searrow O_2 \end{array} \end{array}$	Japanese bituminous (Shin-Yubari)	None	With and without molten tin

BI = benzene-insoluble; G = gas

Photoacoustic spectroscopy is still believed to be primarily a measure of surface rather than bulk properties. Some studies have shown that, because of time limitations for heat transfer in a solid, the photoacoustic technique can only measure absorbance less than 40 angstroms below the solid surface (74).

2.7.1 Aliphatic and Aromatic Hydrogen

Because of the complexity of the IR spectra of coals, most quantitative studies have been limited to the determination of hydroxyl groups and aliphatic and aromatic C-H bonds. Brown (75) attempted to obtain a measure of relative proportion of these latter groups by measuring the ratio of the peak height of the aromatic and aliphatic C-H stretching modes at 3030 and 2925 cm^{-1} , respectively. This approach requires a knowledge of the extinction coefficients, e_{ar} and e_{al} which Brown estimated from measurements on a number of low molecular weight model compounds. An average value of 0.5 for e_{ar}/e_{al} was used. Later Brown and Ladner (76) applied both IR and proton NMR spectroscopy to the study of soluble coal products and proposed the Brown-Ladner equation for determining aromaticities from IR measurement.

The main features of coal spectra do not show significant changes as a function of rank, varying only in the relative intensities of some features and the appearance of prominent bands due to carbonyl groups and carboxylic acid in low rank, (or oxidized) materials (77).

Solomon (78) has used FTIR to examine the relationship between coal structure and thermal decomposition products. For this work, spectra of a number of coals were "corrected" in order to account for particle scattering and mineral content. Each spectra was fitted to a selected set of 24 Gaussian bands whose individual width and position were held constant so that only their relative intensities were allowed to vary. A quantitative measure of aliphatic and aromatic C-H content was determined using the area under the peaks between 3000 and 2800 cm^{-1} and between 900 and 700 cm^{-1} , respectively.

Solomon has used a difference method to obtain extinction coefficients of O-H. Essentially, total hydrogen content from elemental analysis and hydroxyl content from measurement of the area of the O-H stretching band near 3450 cm^{-1} were correlated with the peak area of the aliphatic and aromatic bands to obtain a plot from which extinction coefficients could be determined (78).

2.7.2 The Hydroxyl Function Group

The hydroxyl O-H stretch absorbance for coal appears to be a broad band ranging from 3600 to 2000 cm^{-1} . The broadness of band has been attributed to hydrogen bonding.

Shin and Osawa (78) used the absorption at 3450 cm^{-1} to measure O-H stretching. A problem occurred when this band was used due to interference from water in the coal or in the KBr disc. Painter (77, 79) has suggested an alternative way to determine hydroxyl group content in coal by employing

acetylation of the coal and analysis of the difference between the spectra of the raw and acetylated coal. This procedure has the advantage of avoiding problems with water and in distinguishing different types of OH groups but it is time consuming. Solomon (78) found that the 3200 cm^{-1} band gave a good correlation to O-H stretching (better than 3450 cm^{-1}) and there was no evidence of water interference at this band.

2.7.3 The 1600 cm^{-1} Absorption

The absorption at 1600 cm^{-1} is characteristic of an aromatic ring stretching mode. In coal and coal liquids this absorption band is larger than pure hydrocarbon species due to the presence of hydroxyl attached to the ring which enhances this absorption (75, 80).

Usually four absorption bands are observed near 1600 , 1590 , 1490 and 1450 cm^{-1} (81, 82). The 1490 cm^{-1} band has a weak shoulder while the 1450 cm^{-1} band is particularly indicative of the aliphatic CH_2 and CH_3 bending modes. The detection of the band at 1590 cm^{-1} is complicated by a number of factors, including the heterogeneity of coal, with its distribution of aromatic ring sizes and degree and type of ring substitution.

3. EXPERIMENTAL METHODS

3.1 Equipment

3.1.1 Reactor System

A schematic diagram of the reactor system used in this study is shown in Figure 1. The system consists mainly of three parts: gas feed system, heating system and reactor system. The gas feed system is designed to allow the reactor to be purged and charged with gas with precise control of the initial pressure. After pressurization, the reactor is isolated from the gas delivery system. The heating system is designed to heat the micro tubing-bomb reactors to the desired reaction temperature very rapidly by using a fluidized sandbath, Tecam Model SBL-2D. The bath temperature is controlled by a Leeds & Northrup EMAX III controller with a 11906 zero voltage power pack. The temperature of the reactor contents generally attains the desired value within two minutes by using this heating method. The fluidized bed sand bath is positioned on an adjustable hoist. The hoist can be raised or lowered in order to initiate reactor heating or cooling.

The reactor body consists of 1/2" O.D. 316 stainless steel tubing, capped at the bottom by a Swagelok 1/2" nut and end plug, as shown in Figure 2. The top of the reactor consists of a Cajon VCR female gland fitting welded to the tubing body. The reactor head is a combination of a VCR male fitting, a Swagelok male run tee, a K-type thermocouple

FIGURE 1

SCHEMATIC DIAGRAM OF REACTOR SYSTEM

FIGURE 2
TUBING-BOMB MICROAUTOCLAVE REACTOR

and a 1/8" Autoclave Engineers valve. A disposable nickel gasket is used for sealing purposes. The reactor is designed to be shaken vertically by a eccentrically-driven arm at a rate of approximately 120 strokes per minute.

Runs in the batch autoclave generally utilized one gram of coal and 2 grams of solvent. Where catalysts were applied, a 1/10 (wt/wt) ratio of catalyst to coal was normally maintained. Initial (cold) hydrogen pressure was held constant for most runs at 1000 psig. Further details of run procedures have been described in the literature (46, 64).

3.1.2 Analytical Equipment

The equipment used for the THF/Hexane conversion analyses included an ultrasonic bath, centrifuge, rotary evaporator, top-loading balance (Mettler PC-2000, 0.01 gram resolution) and a Precision Scientific Model 114 drying oven.

For gas analysis, a Carle analytical gas chromatograph Model 111H was used with Hewlett-Packard integrator model 3390A. A FTIR with a photoacoustic detector, Digilab model FTS-40, was used to determine the extent of alkylation and to detect solvent left behind from pretreatment.

3.2 Coal and reagents

3.2.1 Coals

Two coals (Illinois # 6 Wyodak) from the Argonne National Laboratory Premium Coal Sample Bank were used for this study. These coals were supplied crushed to -100 mesh

and sealed in an amber borosilicate glass ampules under nitrogen. Characterization data for these coals are shown given in Table 2.

3.2.2 Reagents

The reagents required for this research are listed in Table 3. The reagents used in all alkylation experiments were analytical grade, while solvents used in THF/Hexane conversion analysis and swelling pretreatment studies were industrial grade.

In this study two different process solvents were employed. The first was 9,10-dihydrophenanthrene (DHP) which was the process solvent for direct liquefaction runs. This material was chosen based upon its known excellent hydrogen donor capabilities. The other process solvent was Cold Lake atmospheric petroleum residuum. This material was used in runs where co-processing conditions were desired. Hydrogen gas (industrial grade) was used as a feed gas except for certain experiments where a gaseous mixture of 99 mole % hydrogen and 1 mole % krypton was used as feed gas. Krypton was employed as a non-reactive tracer gas in order to quantitatively speciate hydrocarbon gas products in selected runs.

3.4 Analytical Procedures

3.4.1 THF/Hexane Conversion Analysis

After reaction the liquid reaction products were collected in a 250 ml centrifuge jar and extracted sequentially

Table 2
Feed Coal Properties (83)

Ultimate Analysis (wt% maf basis) -----	Illinois#6 Bituminous -----	Wyodak Subbituminous -----
Carbon	77.67	75.01
Hydrogen	5.00	5.35
Nitrogen	1.37	1.12
Organic Sulfur	2.38	0.47
Chlorine	0.06	0.03
Fluorine	0.00	0.00
Oxygen	13.51 -----	18.02 -----
Total	100.00 -----	100.00 -----

Table 3

Reagents Used in Alkylation and Solvent Swelling
Pretreatment Experiments

Reagents -----	Formula -----	Process used -----
9,10 dihydro- phrenanthrene	$C_{14}H_{12}$	Liquefaction solvent
Naphthalene Potassium metal	$C_{10}H_8$ K	Sternberg Alkylation " "
Ethyl iodide	C_2H_5I	" "
Ethanol	C_2H_5OH	" "
Tetrabutyl ammonium hydroxide	$(C_4H_9)_4NOH$	O-Alkylation (Liotta)
Methyl iodide	CH_3I	" "
THF	C_4H_8O	Swelling Pretreatment, THF/Hexane conversion analysis, Liotta & Sternberg Alkylation
Hexane	C_6H_{14}	THF/Hexane conversion analysis

with THF and hexane. THF/Hexane conversions were determined from the definitions shown in Table 4.

3.4.2 FTIR Analysis Procedure

For this study, the FTIR system used was a Digilab Biorad spectrometer, model FTS-40, with a Digilab interfaced 3240-SPC computer. The system used a plotter, model SP 600/601, for plotting hard copy spectra.

To measure an infrared spectrum, the coal sample was first dried in order to avoid interference of water and solvent left behind from pretreatment. Table 5 shows the IR band assignments used in this study.

3.4.3 Swelling Ratio

The volumetric method as described by Greene (30) was used to measure the swelling ratio of coal because it was rapid and convenient. In every case the coal sample was left in solvent for several hours to ensure that the sample had enough time to swell to its maximum volume.

The volumetric swelling ratio is defined as

$$Q_{v,dry} = \frac{h_2}{h_1} \\ = \frac{(v_{c,dry} + v_s)}{v_{c,dry}}$$

where v_s = volume of solvent adsorbed by a unit volume of dry coal ($v_{c,dry}$).

Table 4

THF/HEXANE Conversion Definitions

$$\% \text{ THF Conversion} = \frac{(\text{MAF Coal in} - \text{THF ins. out} - \text{THF Int. sol.}) * 100}{\text{MAF in}}$$

$$\% \text{ Hexane Conversion} = \frac{(\text{MAF Coal in} - \text{HEX Ins. out} - \text{HEX Int. sol.}) * 100}{\text{MAF in}}$$

MAF Coal in = wt. of moisture & ash free coal used in experiment

THF ins. out = wt. of ash free THF insoluble residual

$$\text{THF Int. sol.} = \frac{\text{MAF in} * (\% \text{ wt. Intrinsic THF soluble})}{100}$$

HEX Ins. out = wt. of moisture & ash free Hexane insoluble and THF soluble residual

$$\text{HEX Int. sol.} = \frac{\text{MAF in} * (\% \text{ wt. Intrinsic Hexane soluble})}{100}$$

Note: 1. This calculation used MAF (moisture ash free basis of coal)

2. Intrinsic solubility is defined as the amount of material in coal which can be dissolved in that kind of solvent without any treatment.

Table 5

Band assignments for the infrared spectra of coal

A. Aliphatic and aromatic group (74, 75, 76, 77, 78, 80)

<u>Wave number</u> (cm ⁻¹)	<u>Assignment</u>
3030	Aromatic C-H stretching
2950	C-H stretching in CH ₃
2920, 2850	C-H stretching in CH ₂ and CH ₃ aliphatic
1600	Aromatic ring stretching
1450	CH ₂ , CH ₃ bend, possibility of some aromatic ring mode
1375	C-H bending in CH ₃ group
900-700	Aromatic C-H out of plane bending modes

B. Oxygen containing function groups (75, 79, 81, 82)

<u>Wave number</u> (cm ⁻¹)	<u>Assignment</u>
3200	O-H stretching in phenol
1400	O-H deformation in phenol
1735	C=O stretching in ester
1690-1720	C=O stretching in ketone, aldehyde and, -COOH
1265-1230	C-O in aryl ether
1200-1100	C-O in ether
1100-1000	C-O aliphatic ether, alcohol
1030	C-O in aromatic ether

C. Mineral band assignment (75, 77, 82)

<u>Wave number</u> (cm ⁻¹)	<u>Assignment</u>
1035	Kaolinite
1080, 799, 779	Quartz
near 700	Carbonate
near 1420, 872, 712	Calcite

3.4.4 Gas Analysis

Gaseous products gas from selected liquefaction experiments were analyzed by gas chromatography in order to quantify the gas make and carbon conversion to gas that occurred during the coal liquefaction reactions. Major gases produced were carbon dioxide, carbon monoxide, methane, ethane and propane. Krypton added to the feed gas was used as a non-reactive tracer gas in order to facilitate determining of the amount of gas produced, hydrogen consumption, and the yield for each gaseous product. The following procedure was used:

1. The total number of moles of krypton fed to the reactor was calculated based upon known feed gas composition, reactor volume, initial temperature, and initial pressure.

2. Response factors of each gaseous component were determined by calibration with a reference gas of known composition. Response factors of each gas and krypton from the GC calibration were determined from the following expression:

$$R = \frac{\text{Area of species } i}{\text{Amount of species } i}$$

3. The corrected area of each gas component (i) was determined as:

$$\text{Corrected Area}_i = \text{Area}_i * \text{Response factor}$$

4. The total amount of gas produced, mole fractions, and hydrogen consumption were calculated by the following expression:

$$\text{Moles of gas Produced} = \text{Mole of Kr in feed gas} * \frac{\text{Area}_i}{\text{Area}_{Kr}} * \frac{\text{RF}_i}{\text{RF}_{Kr}}$$

$$\text{Total amount of gas} = \sum_i^n [\text{mole of species } i] * \{M.W._i\}$$

$$\text{Hydrogen Consumption} = \frac{\text{weight of hydrogen in gas feed} - \text{weight of hydrogen in gas product}}{\text{MAF feed coal}}$$

3.5 Pretreatment Methods

3.5.1 Reductive Alkylation

Reductive alkylation was conducted using the method developed by Sternberg (18). The alkylated sample was stored in a vacuum dessicator until used.

3.5.2 Oxygen Alkylation

Coal pretreatment by oxygen alkylation (O-alkylation) was based upon the method first developed by Liotta (24). The O-alkylated coal sample was bottled and stored in vacuum dessicator for future use.

3.5.3 Coal Swelling Pretreatment

For swelling pretreatment, 10 g of coal was slowly added to 80 ml of solvent. The slurry was stirred for 3 hr. under a nitrogen blanket, and roto-evaporated under vacuum in order to remove the majority of the solvent. The swollen coal was dried at 50 °C and at a vacuum of less than 10⁻³

torr, followed by subsequent high vacuum drying at 100 °C for 1 hr. The swollen coal was then used immediately in liquefaction experiments.

3.5.4 Residuum Hydrotreating

Cold Lake atmospheric residuum was used as the solvent for all co-processing experiments in this program. Cold Lake atmospheric residuum is a low grade petroleum product. Physico-chemical properties of this material are shown in Table 6. Preliminary experiments (84) indicated that operational difficulties were encountered when using this material due to excessive coking at high temperatures. The residuum was thus hydrotreated to reduced coking tendencies under the thermal liquefaction reaction conditions employed in this study. An Autoclave Engineers Magnedrive II 300 cm³ batch reactor was used for the hydrotreating procedure. Hydrotreating of 100 g of Cold Lake atmospheric residuum involved addition of 10 g of Shell 324 Ni/Mo catalyst which was sulfided in-situ by the addition of 2.0 g dimethyl disulfide. The reactor was then charged with 15.5 MPa hydrogen gas and heated to 400 °C for 1 hour. After hydrotreating, the catalyst was separated via centrifugation, and the resulting hydrotreated Cold Lake residuum was distilled using a micro-spinning band distillation column. Distillation data for the hydrotreated resid are listed in Table 6.

Table 6

Properties of Cold Lake Atmospheric Residuum (84)

Distillate Yields

Distillate Boiling Range	WEIGHT PERCENT DISTILLED	
	As Received	After Hydrotreating
Water	0.0	0.0
IBP - 177 °C	0.0	0.0
177 - 455 °C	25.1	32.0
455 + °C	74.9	68.0
	-----	-----
Total	100.0	100.0

Ultimate Analysis

<u>Component</u>	<u>Weight percent</u>
Carbon	88.30
Hydrogen	8.10
Nitrogen	1.00
Oxygen	1.70
Sulfur	0.90
Ash	0.00

Total	100.00

3.5.5 Determination of Extent of Alkylation

The extent of alkylation was determined by elemental analysis of the alkylated coal in order to measure the hydrogen to carbon ratio. Hydrogen to carbon ratios of the untreated coals were computed using information supplied by the Argonne National Laboratory (83). The extent of alkylation due to pretreatment was calculated using the following equation:

$$X = \frac{100*(C3 - C1)}{(C2 - C3)}$$

where:

X = the extent of alkylation (grams of alkyl groups added per 100 grams of parent MAF coal),

C1 = the normalized weight percent of carbon in the untreated feed coal $\{(wt \% C)/(wt \% C + wt \% H)\}$,

C2 = the normalized weight percent of carbon in the alkyl group being introduced into the coal,

C3 = the normalized weight percent of carbon in the alkylated coal.

The extent of alkylation can also be defined in terms of the number of alkyl groups added per 100 carbon atoms of moisture and ash free (MAF) coal:

$$A = \frac{(X * MWC)}{(MWA * MFC)}$$

where:

A = the extent of alkylation in terms of number of

alkyl groups added per 100 carbon atoms of MAF
coal,

X = the extent of alkylation (gram of alkyl groups
added per 100 grams of MAF coal),

MWC = the molecular weight of carbon (12.01),

MWA = the molecular weight of the alkyl group being
incorporated into the coal,

MFC = the mass fraction of carbon in the untreated
coal on a MAF basis.

4. EXPERIMENTAL DESIGN

This research program was divided into two phases. The first phase of the project consisted of an examination of two chemical alkylation procedures, and an evaluation of these methods with respect to coal reactivity enhancement. Both selective (oxygen) alkylation and non-selective alkylation procedures from the literature were evaluated on two different coals. Additionally, procedures utilizing photoacoustic FTIR for determining the chemical changes in coal associated with alkylation procedures were developed.

Phase II of the program consisted of three related studies. The first study examined the effect of solvent swelling on the reactivity of coal. Since the oxygen alkylation procedure was carried out in an organic medium that swells coal, this study was designed to separate the chemical effects due to oxygen alkylation from the physical effect (changes in the coal's porosity, etc.) that are associated with swelling. The second study was designed to examine the effect of extent of oxygen alkylation on the degree of reactivity enhancement. The third study examined the effect of O-alkylation on the global reaction kinetics and the apparent liquefaction activation energy.

5.0 RESULTS AND DISCUSSION

Results for both phases of this research project will be presented and discussed in the following order:

1. Phase I: Preliminary work

1.1 Liquefaction results

1.2 Co-processing results

1.3 FTIR studies of raw and alkylated coal

2. Phase II: Further studies of the effect of O-alkylation on Wyodak subbituminous coal

2.1 The effect of solvent swelling on the reactivity of coal.

2.2 The effect of extent of oxygen alkylation on the degree of reactivity enhancement.

2.3 The effect of O-alkylation on the global reaction kinetics and the apparent liquefaction activation energy for Wyodak subbituminous coal.

5.1 Phase I Preliminary Work

5.1.1 Introduction

Several techniques and procedures are available that can be used to increase liquefaction yield at low severity reaction conditions. The first phase of this project involved evaluation of two mild chemical coal pretreatment methods, and FTIR analysis of raw and chemically pretreated coals. Non-selective carbon alkylation (Sternberg procedure) and selective oxygen alkylation (Liotta procedure) were used as the chemical pretreatment methods with Illinois #6 and Wyodak coals. The pretreated coals

were then used in liquefaction and co-processing experiments at high and low severity reaction conditions. Conversion to THF solubles was measured for the pretreated coals and compared to the THF conversion of untreated coals at the same reaction conditions. The extent of alkylation and the intrinsic solubilities of untreated and treated coal samples are shown in Table 7. In order to compare the results of each pretreatment method, untreated coal was used as a basepoint in all liquefaction experiments and the experiments were run in parallel at the same reaction conditions.

The results of these preliminary experiments can be categorized into two groups as:

1. Liquefaction reactivity experiments (9,10 dihydrophenanthrene used as solvent)
2. Co-processing reactivity experiments (hydrotreated Cold Lake atmospheric residuum used as solvent).

Both groups of experiments were completed at low severity (350 °C) and high severity (425 °C) conditions and reaction times of 5 min. and 30 min. The results of these preliminary experiments are discussed below.

5.1.2 Liquefaction Reactivity Preliminary Experiments

In these studies DHP was used as the solvent for coal liquefaction. These data and results are discussed in the following order:

5.1.2.1 Untreated coal

Table 7

Extent of Alkylation, Intrinsic THF Solubility, and Ash
Content of Pretreated and Untreated Coals

	No. of Alkyl Group Added per 100 Carbon Atoms	Intrinsic Solubility	Ash Content
	-----	-----	-----
Raw Wyodak Coal	0.00	0.0163	0.0877
O-methylated Wyodak Coal	8.00	0.1359	0.0656
Sternberg Alkylated Wyodak Coal	5.70	0.0000	0.1268
Raw Illinois #6 Coal	0.00	0.1172	0.1590
O-methylated Illinois #6 coal	4.70	0.2532	0.1434
Sternberg Alkylated Illinois #6 Coal	6.70	0.0648	0.1487

Note: Intrinsic solubility units are wt%, MAF basis

Ash content units are wt%, MAF basis

5.1.2.2 O-alkylated coal

5.1.2.3 Reductively alkylated coal

5.1.2.1 Untreated Coal

For untreated coal, the different combinations of liquefaction reactivity conditions are divided into two groups: low severity combinations (350 °C, 5 and 30 minutes reaction time) and high severity reaction conditions (425 °C, 5 and 30 minutes). Results for untreated coal liquefaction experiments are shown in Figure 3. At both low and high severity conditions, coal conversion is a function of coal rank, with bituminous coal (Illinois #6) giving a higher conversion to THF solubles than subbituminous coal (Wyodak). At low severity liquefaction conditions, THF conversion for both coals more than doubled when reaction time increased from 5 to 30 min.

5.1.2.2 O-Alkylation of Coal

Figure 4 shows the results for O-alkylated coals compared with untreated coals at low and high severity conditions. The percent increase in liquefaction conversion caused by the O-alkylation pretreatment procedure compared with the parent coal is shown in Figure 5. For low severity liquefaction conditions, O-alkylated Wyodak coal gives a greater increase in conversion than pretreated Illinois #6 coal at both 5 and 30 min. reaction times. At the lowest severity conditions (350 °C, 5 min.), O-alkylated Wyodak coal exhibited a 119% increase in conversion compared with untreated Wyodak while Illinois #6 showed only a 24%

FIGURE 3

BASELINE CONVERSIONS FOR UNTREATED COALS
DIRECT LIQUEFACTION CONDITIONS

■ Untreated Coal

W = WYODAK

I = ILLINOIS #6

FIGURE 4

EFFECT OF O-ALKYLATION ON REACTIVITY
DIRECT LIQUEFACTION CONDITIONS

W = WYODAK I=ILLINOIS #6

FIGURE 5

INCREASE IN THF CONVERSION FOR O-ALKYLATED COALS
DIRECT LIQUEFACTION CONDITIONS

W = WYODAK I = ILLINOIS #6

increase in conversion. Likewise, at a reaction time of 30 min. O-alkylated Wyodak coal gave a 39% increase in conversion with respect to the untreated coal, while Illinois #6 showed only a 4% increase in conversion. This difference in the extent of reactivity enhancement with coal rank was expected, since the Wyodak (low rank) coal contains more organic oxygen. Hence, selective O-alkylation is more effective in enhancing the reactivity of low rank coal compared with the high rank coal.

The increase in conversion found for the O-alkylated Wyodak coal suggested one of the studies proposed in the second phase of this project, namely an investigation of the effect of extent of O-alkylation in Wyodak coal on the degree of reactivity enhancement.

At high severity liquefaction conditions (425 °C) the O-alkylated coals showed a lesser degree of reactivity enhancement with respect to the untreated coal. This result can be attributed to the fact that at high severity liquefaction conditions, the coal conversion is close to the maximum attainable limit. Because the maximum coal conversion has already been approached, pretreatment of the parent coal results in a negligible reactivity enhancement.

5.1.2.3 Sternberg Reductive Alkylation of Coal

Liquefaction conversion results for non-selective (reductive) alkylated coals compared with untreated coals are shown in Figure 6. The percent increase in conversion for reductively alkylated coal is shown in Figure 7. Like

FIGURE 6

EFFECT OF REDUCTIVE ALKYLATION ON REACTIVITY
DIRECT LIQUEFACTION CONDITIONS

FIGURE 7

INCREASE IN THF CONVERSION FOR REDUCTIVELY ALKYLATED COALS
DIRECT LIQUEFACTION CONDITIONS

W = WYODAK I = ILLINOIS #6

O-alkylation, at low and high severity, liquefaction of chemically pretreated Wyodak coal gave a higher percent increase in conversion when compared to Illinois #6 coal. This might be due to untreated Illinois #6 having a higher conversion level as opposed to untreated Wyodak for both low and high severity liquefaction.

5.1.3 Co-Processing Reactivity Preliminary Experiments

In these studies hydrotreated Cold Lake atmospheric residuum was used as a solvent instead of untreated Cold Lake atmospheric residuum since the untreated solvent caused a problem by coking at high temperature (425 °C) and longer reaction times (30 min.). Hence, the Cold Lake Atmospheric residuum was hydrotreated before being used as a solvent since:

1. *Stabilization of this material by mild hydrotreating reduced the tendency of the residuum to coke and made it easier to use in the experiments.*

2. *In a real co-processing system, catalysts are employed. Thus at steady state the solvent is not a raw residuum but a partial hydrogenated residuum. All co-processing reactivity experiments in this study were performed without catalyst. From this point of view, it was considered that hydrotreated residuum was more suitable for use in the co-processing experiments.*

The co-processing preliminary results are discussed below.

5.1.3.1 Untreated Coal

The baseline data for coal conversion for co-processing experiments at low and high severity for both 5 min. and 30 min. reaction times are shown in Figure 8. At low severity (350 °C) and 5 min. reaction time, both Wyodak and Illinois #6 coals gave slightly negative conversions. These negative conversions were most likely caused by adduction of co-processing solvent into the primary liquefaction products, thus forming high molecular weight coal/solvent adducts that are insoluble in THF. At 30 min. reaction time, positive THF conversion results were observed.

At high severity co-processing conditions for Wyodak subbituminous coal, conversion increased with increasing time (28.4 wt% THF soluble at 5 min. to 69.3 wt% THF soluble at 30 min. reaction time). For the high rank coal (Illinois #6 bituminous) conversions were identical within experimental error for both 5 min. and 30 min. reaction times.

5.1.3.2 Co-processing of O-Alkylated Coals

Co-processing conversion results for O-alkylated coals compared with untreated coals are shown in Figure 9, and the percent increases in conversion for O-alkylated coals are shown in Figure 10. At 350 °C and 5 min. reaction time, co-processing results showed negative conversions. This result again might be due to adduction of solvent/primary products which are not soluble in THF and are formed at short reaction times. At 30 min. reaction time, O-alkylated

FIGURE 8

BASELINE CONVERSIONS FOR UNTREATED COALS
CO-PROCESSING CONDITIONS

W = WYODAK I = ILLINOIS #6

FIGURE 9

EFFECT OF O-ALKYLATION ON REACTIVITY
CO-PROCESSING CONDITIONS

W = WYODAK I = ILLINOIS #6

FIGURE 10

INCREASE IN THF CONVERSION FOR O-ALKYLATED COALS
CO-PROCESSING CONDITIONS

W = WYODAK I = ILLINOIS #6

Wyodak coal showed a significant increase in THF conversion, while O-alkylated Illinois #6 showed a decrease in THF conversion. At high severity, O-alkylated Wyodak coal exhibited a significant increase in conversion at 5 min. and a small increase in conversion at 30 min. reaction time while O-alkylated Illinois #6 showed a decrease in conversion for both 5 min. and 30 min. reaction times. These data indicate that O-alkylation enhanced the reactivity of the low rank coal and may have promoted retrogressive reactions in the higher rank coal under co-processing reaction conditions.

5.1.3.3 Co-Processing of Reductively Alkylated Coals

Co-processing conversion data for reductively alkylated coal compared with untreated coal are shown in Figure 11 while Figure 12 shows the percentage increase in conversion for reductively alkylated coals. At low severity conditions both pretreated coals showed an increase in conversion at both 5 min. and 30 min. reaction times. At high severity conditions, pretreated Wyodak coal showed a significant increase in conversion at 5 min. reaction times, while at 30 min. reaction times there was no change in conversion within experimental error. For pretreated Illinois #6 and high severity conditions, 5 min. reaction times showed higher conversion than 30 min. reaction times. This indicated that at longer reaction times, retrogressive reactions may be taking place.

FIGURE 11

EFFECT OF REDUCTIVE ALKYLATION ON REACTIVITY
CO-PROCESSING CONDITIONS

FIGURE 12

INCREASE IN THF CONVERSION FOR REDUCTIVELY ALKYLATED COALS
CO-PROCESSING CONDITIONS

5.1.4 PAS-FTIR Studies of Treated and Untreated Coal

5.1.4.1 FTIR Spectra of Raw Coal

FTIR spectra of coal are very complex. There are certain peaks in coal spectra which overlap and so must be carefully assigned. Figure 13 shows a spectrum of raw Wyodak coal (dried at 50 °C under high vacuum for 18 hours) with a functional group assignment based upon data in the literature.

Figure 14 shows spectra of five different types of raw coal (dried at 50 °C under high vacuum for 18 hours). From this figure, one can see that the main features of coal spectra do not show significant changes as a function of rank, but vary only in the relative intensity of some features and the appearance of prominent bands due to carbonyl groups and carboxylic acids in low rank or oxidized material.

5.1.4.2 The PAS-FTIR Oxygen Alkylated Coal Spectra

Figure 15 shows the oxygen alkylated Wyodak coal spectra at different alkylation levels compared with raw Wyodak coal spectrum. Figure 16 shows subtraction spectra of oxygen alkylated Wyodak coal and raw Wyodak coal. The major differences between oxygen alkylated Wyodak coal spectra and the raw Wyodak coal spectrum are:

1. A decrease with increasing alkylation level of the intensity of a broad band with a maximum at 3300 cm^{-1} , which indicates that there is a decrease in the number and concentration of hydroxyl groups;

FIGURE 13
PAS-FTIR OF RAW WYODAK COAL

FIGURE 14
PAS-FTIR OF 5 DIFFERENT COALS

FIGURE 15
PAS-FTIR OF O-ALKYLATED WYODAK COAL

- A) Raw Wyodak coal
- B) O-methylated Wyodak, 3.6 CH₃ groups/100 C atoms
- C) O-methylated Wyodak, 8.0 CH₃ groups/100 C atoms
- D) O-methylated Wyodak, 17.2 CH₃ groups/100 C atoms

FIGURE 16
PAS-FTIR SUBTRACTION SPECTRA

2. Increased intensity for oxygen alkylated coal in a band around 2920 cm^{-1} due to aliphatic stretching and at 1375 cm^{-1} due to an increase in CH_3 groups;

3. An intensity increase at 1730 cm^{-1} which is due to C=O vibrational stretching in the ester group. This indicates that there is ester formation during oxygen alkylation. This band intensity increases with an increase in the level of alkylation as shown in Figure 15;

4. An increase in the 1450 cm^{-1} band intensity which is due to an increase in CH_3 groups during alkylation;

5. No change in the band at $1270\text{--}1275\text{ cm}^{-1}$ since the number of ether groups added by the oxygen alkylation process is small compared to the number of ether groups in the raw Wyodak coal. It should be noted that the ether which is formed by oxygen alkylation is very difficult to detect by the FTIR technique due to the fact that the IR absorption of ether occurs in the same region as other structures in native coal (the fingerprint region).

5.1.4.3 PAS-FTIR Spectra of Reductively Alkylated Coal

Figure 17 shows a reductively ethylated spectrum for Wyodak coal compared with a raw Wyodak spectrum. There is a decrease in intensity of the hydroxyl absorption band, which means that there is alkylation of a phenol or carboxylic acid functional group occurring during reductive alkylation. There is an increase in the intensity of C-H aliphatic stretching, which indicates that alkyl groups are being added to the coal structure. There is also an increase in

FIGURE 17

PAS-FTIR OF REDUCTIVELY ALKYLATED WYODAK COAL

the intensity of the absorption band near 1100 cm^{-1} in alkylated coal due to the formation of aryl-alkyl ethers by alkylation of aryloxides coming from ether cleavage and phenolic groups.

Figure 18 shows a reductively ethylated Illinois coal spectrum compared with an untreated Illinois coal spectrum. Like Figure 17, there is an increase in the intensity of aliphatic stretching, which means that ethyl groups have been added to the coal structure. In this particular coal, it is hard to observe the change due to ether bond cleavage.

5.1.4.4 PAS-FTIR Spectra for Solvent Swollen Coal

For this portion of the project, PAS-FTIR was used as a quick tool to detect solvent left behind and to observe functional group changes after solvent swelling pretreatment. Figure 19 shows the spectra of raw Wyodak compared with THF swollen Wyodak coal. From this figure, the only change which is apparent is in the hydroxyl group which may occur simply due to drying.

5.2 Phase II Further Studies of Selective O-Alkylation of Wyodak Coal:

5.2.1 Rationale

The preliminary results discussed in the last section indicate that selective oxygen alkylation is a very effective chemical pretreatment technique for enhancing the reactivity of coal. This method has been shown to be especially effective for low rank coals which are high in organic oxygen. The exact chemical and physical mechanisms

FIGURE 18

PAS-FTIR OF REDUCTIVELY ALKYLATED ILLINOIS #6 COAL

FIGURE 19

PAS-FTIR OF RAW AND SWOLLEN WYODAK COALS

responsible for this change in reactivity are, however, unknown. Accordingly, the second phase of this research program dealt with an investigation of the reactivity changes taking place due to selective O-alkylation by:

- 1) investigating the effect of solvent swelling on coal reactivity;

- 2) examining the effect of extent of alkylation (in terms of numbers of alkyl groups added per 100 carbon atoms) on reactivity change, and;

- 3) studying the effect of O-alkylation on global reaction kinetics and the apparent activation energy.

5.2.2 The Effect of Solvent Preswelling on Coal Reactivity

The effect of solvent preswelling on coal reactivity was investigated for the following reasons:

1. As mentioned earlier, many researchers believe that when a solvent swells the coal the accessibility of the coal to penetration by the solvent is improved, thus improving the access of hydrogen donating fluids to reactive sites in the coal structure. We wished to investigate whether this is true for solvent preswelling of coal in polar and non-polar model compounds.

2. All pretreatment processes used in this program involved stirring coal in a polar solvent such as tetrahydrofuran (THF) for a long period of time. For example, the oxygen alkylation process involved stirring of coal in THF for up to 24 hours. It is well known that THF

is an effective swelling agent for most coals, so we wanted to know if these procedures had any effect on coal reactivity.

The experimental work carried out during this phase of the research can be categorized as follows:

1. Investigation of swelling of Wyodak and Illinois #6 coals in a suite of polar and non-polar solvents.

2. Investigation of the effect of THF preswelling on direct hydroliquefaction of Wyodak and Illinois #6 coals.

5.2.2.1 Effect of Non-polar and Polar Solvents on Coal Swelling

In order to understand the effect of solvent type used in preswelling on direct hydroliquefaction, two different types of solvents, non-polar and polar, were chosen in this part of study. Dryden (85, 86) reported that the best swelling solvents are those containing nitrogen or oxygen atoms with a lone pair of electrons available for coordination.

Figure 20 shows the swelling ratio for Illinois #6 coal and Wyodak coal in both a non-polar solvent (hexane) and polar solvents (methanol, acetone, n-propylamine, THF, pyridine, and tetrabutyl ammoniumhydroxide). The rank of solvent swelling ratios for Illinois #6 coal was as follows:

hexane < methanol < acetone < n-propylamine < THF <
pyridine < tetrabutyl ammoniumhydroxide.

The rank of solvent swelling ratio for Wyodak coal was as follows:

FIGURE 20

SWELLING RATIOS FOR ILLINOIS #6 AND WYODAK COALS
7 DIFFERENT SOLVENTS

hexane < acetone < methanol < THF < pyridine <
n-propylamine < tetrabutyl ammoniumhydroxide.

Where: HEX - Hexane
MeOH - Methanol
ACET - Acetone
PA - N-propylamine
THF - Tetrahydrofuran
PYR - Pyridine
TBAH - Tetrabutyl ammonium hydroxide

Tetrabutyl ammoniumhydroxide (TBAH) is the best swelling solvent for both Wyodak coal (swelling ratio = 3.56) and Illinois #6 coal (swelling ratio = 2.97). Similar results have been recently reported by Joseph (32, 33).

The difference in swelling ratio caused by the different solvents may be explained on the basis of their interaction with the various types of bridging bonds in coals (32, 85, 86). Bridging bonds are formed through: 1) covalent bonding 2) ionic bonding 3) hydrogen bonding and 4) charge transfer complexing. Swelling of coal is caused by disrupting (breaking or extending) one or more of these bonds. The extent of swelling depends on the type of bond predominating in a coal and the nature of the solvent. Covalent bonds are not likely to be broken by a common solvent under ambient conditions. Therefore, only ionic interactions, hydrogen bonding, and charge transfer complexing are important in the swelling phenomena. Ionic and hydrogen bonds are believed to be significant in low rank coal because of the presence of relatively large number of polar functional groups, such as hydroxyl (-OH), carboxyl

(-COOH), and carbonyl (-CO-). Charge transfer complexing is expected to be predominant only in higher rank coals because of their higher aromatic content compared to lower rank coals. Because of the difference in their electronic properties, various solvents react differently with the bridging bonds mentioned above. TBAH, being a strong base, disrupts both ionic and hydrogen bonds easily, and therefore swells the low rank coal more than the bituminous coals. In contrast, THF and methanol may not be strong enough bases to break ionic bonds. Therefore, they will not swell low rank coal as much as TBAH does. Since charge transfer complexing is expected to be more pronounced in the bituminous coal than in the low rank coals, THF, which can disrupt such bonding, will swell bituminous coal. Methanol and acetone being the least effective of all solvents used in disrupting any of the bonding types mentioned above, are the least efficient swelling agents.

5.2.2.2 Effect of THF Preswelling on Liquefaction of Wyodak and Illinois #6 Coals

The effect of THF preswelling on direct hydroliquefaction of coal was studied specifically since both the oxygen alkylation and reductive alkylation procedures involved stirring of coal in THF up to a maximum of 24 hours. To investigate this effect, both Illinois #6 and Wyodak coals were stirred in THF for 24 hours, then roto-evaporated to remove THF, and dried in a high vacuum system (pressure about 10^{-2} torr) at 50 °C for 18 hours.

The treated Illinois #6 coal was then reacted under liquefaction conditions in DHP at 425 °C for a five minute reaction times. The treated Wyodak coal was reacted under liquefaction conditions in DHP at 350 °C and 425 °C for both 5 and 30 minute reaction times.

Figure 21 shows the THF and hexane conversions for treated Wyodak coal (preswelling in THF for 24 hours) liquefied in DHP at 350 °C and 425 °C for both 5 and 30 minute reaction times. From this figure, it can be seen that there is essentially no difference in THF and hexane conversion for treated (preswollen) Wyodak coal when compared with raw Wyodak coal for both low and high severity conditions. This result leads to the conclusion that THF preswelling of Wyodak coal does not have an effect on coal reactivity under liquefaction reaction conditions.

Figure 22 shows data for the THF and hexane conversions of preswollen Illinois #6 coal (24 hours). Liquefaction was carried out at 425 °C for 5 minute reaction times. From this figure we can see that THF conversion of raw coal and treated coal remained essentially constant, while toluene soluble products and hexane solubles products increased with increasing preswelling time. The difference noted between the effect of preswelling on the reactivity of Illinois #6 and Wyodak coals may be explained in terms of differences in the properties of these two materials. The molecular structure of Illinois #6 bituminous coal is held together very tightly, and in the THF preswelling step the

FIGURE 21

EFFECT OF SWELLING ON THF AND HEXANE CONVERSION
 WYODAK COAL
 VARIABLE REACTION CONDITIONS

Liquefied in DHP

Treated Wyodak = 24 hrs. THF preswelled

Wyodak coal

FIGURE 22

EFFECT OF SWELLING ON THF, TOLUENE, AND HEXANE CONVERSIONS
ILLINOIS #6 COAL

LIQUEFIED IN DHP AT 425 C FOR 5 MIN.

macromolecular structure was slightly expanded rendering it easier to liquefy than the untreated coal. It is apparent that the overall conversion remained constant because the THF conversion of this coal has reached the maximum obtainable limit. These effects were not observed in the case of Wyodak coal since the structure is held together more loosely than Illinois #6.

5.2.2.3 Effect of Operating Conditions on Liquefaction Reactivity of THF Preswollen Wyodak Coals

This set of experiments was designed to investigate the effect of operating conditions on liquefaction reactivity of THF preswollen Wyodak coals. In this set of experiments, preswollen Wyodak coal was liquefied at the following reaction conditions

1. reaction time: 5 and 30 minutes
2. temperature: 350 °C, 375 °C, 400 °C, 425 °C, and 450 °C

Wyodak coal was stirred in THF for 3 hours, then roto-evaporated and dried in a high vacuum system (pressure = 0.01 torr) for 2 hours. In this set of experiments tetralin was used as the liquefaction solvent instead of DHP in order to attempt to magnify the effect of preswelling on reactivity. Figures 23 and 24 show THF and hexane conversion for preswollen Wyodak coal compared with raw, dried Wyodak coal at both 5 and 30 minute reaction times. From both figures it can be seen that the THF and hexane conversions for the preswollen Wyodak coal are the same as

FIGURE 23

EFFECT OF SWELLING ON COAL REACTIVITY
5 MINUTE REACTION TIME
WYODAK COAL

FIGURE 24

EFFECT OF SWELLING ON COAL REACTIVITY
30 MINUTE REACTION TIME
WYODAK COAL

for raw Wyodak coal. Hence, we conclude that in the temperature range between 350 and 450 °C, THF preswelling does not have any effect on liquefaction reactivity of Wyodak coal.

5.2.3 Effect of Extent of Oxygen Methylation

5.2.3.1 Effect of the Extent of Oxygen Methylation of Wyodak Coal on Intrinsic THF Solubility

Oxygen alkylation of Wyodak coal was carried out with varying alkylation times. Results for alkylation times ranging from 3 to 24 hours on the extent of oxygen alkylation for Wyodak coal are shown below:

Alkylation Time (hours)	No. of methyl group added per 100 C atoms
3	1.95, 2.05*
6	3.57, 4.29*
12	8.00, 8.18*
24	17.16, 12.56*

Note: The number with * indicates duplicated runs.

Figure 25 shows the effects of alkylation time on the number of methyl groups added per 100 carbon atoms. From this result, it can be seen that longer alkylation times result in a higher extent of alkylation, with the number of methyl groups added increasing with increasing time. Liotta (24, 25) used oxygen methylation to quantitatively measure the phenolic groups in coals. For Rawhide coal (Wyodak

FIGURE 25

EFFECT OF TIME ON EXTENT OF O-ALKYLATION
WYODAK COAL

coal), Liotta found about 8 phenolic groups per 100 carbon atoms with 12 hours of alkylation. These experimental results indicate that there are about 15 methyl groups added per 100 carbon atoms with 24 hours of alkylation. This difference can be explained by the presence of carboxylic acid groups in Wyodak coal which also undergo alkylation by the Liotta procedure and by some carbon alkylation which is also known to occur by this procedure.

Figure 26 shows the intrinsic THF solubility for O-methylated Wyodak coal at different levels of methylation. From these data one can see that there is an increase in the intrinsic THF solubility of more than 300 % when 4 methyl groups have been added. The intrinsic THF solubility increases by more than 400 % when 12 methyl groups have been added to Wyodak coal. The increase in intrinsic THF solubility occurs in part because the degree of hydrogen bonding in Wyodak coal has been reduced. There is also the possibility that the swelling in THF for Wyodak coal dissolved some of the THF solubles from the inner structure of the coal and hence made this material more accessible. This hypothesis was, however, shown not to be the case since the intrinsic THF solubility of THF swollen (for 24 hours) Wyodak coal without any alkylation is the same as that of raw Wyodak coal as shown below:

FIGURE 26

EFFECT OF EXTENT OF O-ALKYLATION ON INTRINSIC THF SOLUBILITY
WYODAK COAL

	Weight percent intrinsic THF solubility (MAF basis)
Raw Wyodak Coal	1.63
THF-preswollen (for 24 hours) Wyodak coal	2.05
O-methylated Wyodak Coal with 4.29 methyl group added/100 C atoms	7.65
O-methylated Wyodak Coal with 12.56 methyl group added/100 C atoms	9.16

5.2.3.2 Effect of the Extent of O-Methylated Wyodak Coal on Liquefaction on Reactivity

Iodine has often been used as a catalyst in coal liquefaction processes (10, 11). The O-methylation procedure used for this research (Liotta recipe) uses methyl iodide (CH_3I) as the alkylating reagent. Although Liotta recommends removing iodide from the alkylated coal by water washing until the water tests negative with silver nitrate, it is still possible that small quantities of iodide or CH_3I are left behind in the alkylated coal. Some of the O-methylated samples and raw Wyodak coal were checked for residual iodine content by Huffman Laboratory, of Golden, Colorado. The result for weight percent of iodine in sample is shown below:

	Weight percent Iodine in sample
Raw Wyodak Coal	0.10
O-methylated Wyodak Coal (6.50 CH_3 /100 C atoms)	0.17
O-methylated Wyodak Coal (4.32 CH_3 /100 C atoms)	0.28
O-methylated Wyodak Coal (5.25 CH_3 /100 C atoms)	0.32

The results show that in raw and methylated Wyodak coal small amounts of iodine, up to 0.32 wt %, exist. This is considered to be a high enough concentration for the possibility of iodine to act as a catalyst. The iodine in raw Wyodak coal and O-methylated Wyodak coal shown by the above data can be considered to be approximately of the same magnitude. However in order to eliminate this as a possible reason for the liquefaction reactivity enhancement noted for the alkylated coals, liquefaction of raw Wyodak and coal spiked with CH_3I was carried out using DHP as a liquefaction solvent at 350 °C and 30 minutes reaction times. These reaction conditions were selected because at lower temperature the catalyst effect is more pronounced than at higher temperature. Experiments were performed by adding methyl iodide up to 1.0 wt % of iodide. The results of these experiments are shown below:

	no CH_3I -----	1 wt% CH_3I added -----
% THF conversion	41.05	43.92

From this result we can see that there is no catalyst effect from residual iodine even when the concentration of iodine is as high as 1 wt%. Therefore, we can conclude that the increase in THF conversion for O-methylated Wyodak coal is not the result of catalysis by residual iodine.

Data for THF conversion of liquefied O-methylated Wyodak coal as a function of extent of alkylation (corrected for intrinsic THF solubility) are shown in Figures 27-32.

Figure 27 shows THF conversion and Figure 28 shows percent increase in THF conversion for liquefaction of O-methylated Wyodak coal at different levels of methylation at 350 °C for both 5 minute and 30 minute reaction times. From these figures we can see that there is an increase in THF conversion with an increase in the number of methyl groups added. For 5 minute reaction times, the increase in THF conversion is up to as high as 195 %, and for 30 minute reaction times THF conversion is increased by up to 95%.

Figure 29 shows THF conversion and Figure 30 shows percent increase in THF conversion for liquefaction of O-methylated Wyodak coal at different levels of methylation at 425 °C for both 5 minute and 30 minute reaction times. From these figures we can see that there is an increase in THF conversion with an increase in the extent of methylation, but the effects are much less pronounced than at lower reaction temperature. THF conversion increases are less than 15% at the 5 minute reaction times and less than 12% for the 30 minute reaction times. However, if pretreatment can improve THF conversion by as little as 5% at high reaction severity, it may be considered to be a successful method. Therefore, we can conclude that O-methylation of Wyodak coal is an effective method for improving the liquefaction yield. Figures 31 and 32 show a comparison of the increase in THF conversion between low and high temperatures at 5 minute and 30 minute reaction times. From both figures we can clearly see that the effect of

FIGURE 27

EFFECT OF EXTENT OF O-METHYLATION ON REACTIVITY
WYODAK COAL
DIRECT LIQUEFACTION AT 350 C

Liquefied in DHP at 350 degree C

FIGURE 28

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
WYODAK COAL
DIRECT LIQUEFACTION AT 350 C

Liquefied in DHP at 350 degree C

FIGURE 29
EFFECT OF EXTENT OF O-METHYLATION ON REACTIVITY
WYODAK COAL
DIRECT LIQUEFACTION AT 425 C

Liquefied in DHP at 425 degree C

FIGURE 30

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
WYODAK COAL
DIRECT LIQUEFACTION AT 425 C

Liquefied in DHP at 425 degree C

FIGURE 31

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
SHORT RESIDENCE TIME DATA

Liquefied in DHP for 5 min.

FIGURE 32

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
LONG RESIDENCE TIME DATA

Liquefied in DHP for 30 min.

alkylation on reactivity is more significant at lower temperature. This finding is reasonable since at higher temperature THF conversion is usually near the maximum obtainable limit (total reactive organics) for that reaction time and that coal.

The increase in conversion noted for the O-methylated Wyodak coal may be due to the effect of alkylation in decreasing regressive reactions between reactive oxygen sites by changing the reactive oxygen functional groups from phenolics and carboxylics to ethers and esters, respectively. Some possible regressive reactions involving phenolic oxygen include ether linkage formation via dehydration of two phenolic functional groups in coal to form an ether bridge. McMillen (86) has shown that ether linkage formation can occur at very low temperatures (300 °C) via this type of reaction. In a model compound study, McMillen showed that the hydroxyl coupling reaction resulted in peroxide bond formation, hence generating reaction products which were highly refractory:

McMillen observed that these coupling reactions were strongly promoted at 400 °C. The formation of these products can be considered representative of regressive reactions observed in low rank coal under certain liquefaction conditions.

The Scholl condensation involving a dehydration reaction between phenolic and aromatic functional groups in

coal to form a carbon-carbon bond has also been reported to be taking place during the early stages of coal liquefaction. Stohl (86) studied the type of compound and process conditions that give rise to regressive reactions during preconversion processing using dibenzyl ether (DBE) as the model compound. Stohl found that regressive reactions of DBE can occur even in the presence of a good hydrogenation catalyst, and coal mineral matter. Stohl further suggested that detrimental reactions can occur at low temperatures during the initial stages of coal dissolution.

Both ether linkage formation and the Scholl condensation reaction can occur at temperatures below 300 °C, and thus decrease the reactivity of coal. It is clear that, under coal liquefaction conditions, dihydroxyaromatics present in low rank coals can react either in "simple" dehydration or condensation processes to form high molecular weight products.

5.2.3.3 Effect of Extent of Alkylation on Co-processing of Wyodak Coal

Figure 33 shows THF conversion for co-processing of raw, dried Wyodak coal at 350 °C compared with O-methylated Wyodak coal at different levels of methylation using hydrotreated Cold Lake atmospheric residuum as the process solvent. From this figure one can see that there is a significant increase in THF conversion with an increase in levels of methylation for both 5 minute and 30 minute

FIGURE 33

EFFECT OF EXTENT OF O-METHYLATION ON REACTIVITY
WYODAK COAL
CO-PROCESSING AT 350 C

Liquefied in hydrotreated A-8
at 425 degree C

FIGURE 34

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
CO-PROCESSING AT 350 C
WYODAK COAL

Liquefied in hydrotreated A-8
at 350 degree C for 30 minutes.

FIGURE 21

EFFECT OF SWELLING ON THF AND HEXANE CONVERSION
 WYODAK COAL
 VARIABLE REACTION CONDITIONS

Liquefied in DHP

Treated Wyodak = 24 hrs. THF preswelled

Wyodak coal

FIGURE 22

EFFECT OF SWELLING ON THF, TOLUENE, AND HEXANE CONVERSIONS
ILLINOIS #6 COAL

LIQUEFIED IN DHP AT 425 C FOR 5 MIN.

macromolecular structure was slightly expanded rendering it easier to liquefy than the untreated coal. It is apparent that the overall conversion remained constant because the THF conversion of this coal has reached the maximum obtainable limit. These effects were not observed in the case of Wyodak coal since the structure is held together more loosely than Illinois #6.

5.2.2.3 Effect of Operating Conditions on Liquefaction Reactivity of THF Preswollen Wyodak Coals

This set of experiments was designed to investigate the effect of operating conditions on liquefaction reactivity of THF preswollen Wyodak coals. In this set of experiments, preswollen Wyodak coal was liquefied at the following reaction conditions

1. reaction time: 5 and 30 minutes
2. temperature: 350 °C, 375 °C, 400 °C, 425 °C, and 450 °C

Wyodak coal was stirred in THF for 3 hours, then roto-evaporated and dried in a high vacuum system (pressure = 0.01 torr) for 2 hours. In this set of experiments tetralin was used as the liquefaction solvent instead of DHP in order to attempt to magnify the effect of preswelling on reactivity. Figures 23 and 24 show THF and hexane conversion for preswollen Wyodak coal compared with raw, dried Wyodak coal at both 5 and 30 minute reaction times. From both figures it can be seen that the THF and hexane conversions for the preswollen Wyodak coal are the same as

FIGURE 23

EFFECT OF SWELLING ON COAL REACTIVITY
5 MINUTE REACTION TIME
WYODAK COAL

FIGURE 24

EFFECT OF SWELLING ON COAL REACTIVITY
30 MINUTE REACTION TIME
WYODAK COAL

for raw Wyodak coal. Hence, we conclude that in the temperature range between 350 and 450 °C, THF preswelling does not have any effect on liquefaction reactivity of Wyodak coal.

5.2.3 Effect of Extent of Oxygen Methylation

5.2.3.1 Effect of the Extent of Oxygen Methylation of Wyodak Coal on Intrinsic THF Solubility

Oxygen alkylation of Wyodak coal was carried out with varying alkylation times. Results for alkylation times ranging from 3 to 24 hours on the extent of oxygen alkylation for Wyodak coal are shown below:

Alkylation Time (hours)	No. of methyl group added per 100 C atoms
3	1.95, 2.05*
6	3.57, 4.29*
12	8.00, 8.18*
24	17.16, 12.56*

Note: The number with * indicates duplicated runs.

Figure 25 shows the effects of alkylation time on the number of methyl groups added per 100 carbon atoms. From this result, it can be seen that longer alkylation times result in a higher extent of alkylation, with the number of methyl groups added increasing with increasing time. Liotta (24, 25) used oxygen methylation to quantitatively measure the phenolic groups in coals. For Rawhide coal (Wyodak

FIGURE 25
EFFECT OF TIME ON EXTENT OF O-ALKYLATION
WYODAK COAL

coal), Liotta found about 8 phenolic groups per 100 carbon atoms with 12 hours of alkylation. These experimental results indicate that there are about 15 methyl groups added per 100 carbon atoms with 24 hours of alkylation. This difference can be explained by the presence of carboxylic acid groups in Wyodak coal which also undergo alkylation by the Liotta procedure and by some carbon alkylation which is also known to occur by this procedure.

Figure 26 shows the intrinsic THF solubility for O-methylated Wyodak coal at different levels of methylation. From these data one can see that there is an increase in the intrinsic THF solubility of more than 300 % when 4 methyl groups have been added. The intrinsic THF solubility increases by more than 400 % when 12 methyl groups have been added to Wyodak coal. The increase in intrinsic THF solubility occurs in part because the degree of hydrogen bonding in Wyodak coal has been reduced. There is also the possibility that the swelling in THF for Wyodak coal dissolved some of the THF solubles from the inner structure of the coal and hence made this material more accessible. This hypothesis was, however, shown not to be the case since the intrinsic THF solubility of THF swollen (for 24 hours) Wyodak coal without any alkylation is the same as that of raw Wyodak coal as shown below:

FIGURE 26

EFFECT OF EXTENT OF O-ALKYLATION ON INTRINSIC THF SOLUBILITY
WYODAK COAL

	Weight percent intrinsic THF solubility (MAF basis)
Raw Wyodak Coal	1.63
THF-preswollen (for 24 hours) Wyodak coal	2.05
O-methylated Wyodak Coal with 4.29 methyl group added/100 C atoms	7.65
O-methylated Wyodak Coal with 12.56 methyl group added/100 C atoms	9.16

5.2.3.2 Effect of the Extent of O-Methylated Wyodak Coal on Liquefaction on Reactivity

Iodine has often been used as a catalyst in coal liquefaction processes (10, 11). The O-methylation procedure used for this research (Liotta recipe) uses methyl iodide (CH_3I) as the alkylating reagent. Although Liotta recommends removing iodide from the alkylated coal by water washing until the water tests negative with silver nitrate, it is still possible that small quantities of iodide or CH_3I are left behind in the alkylated coal. Some of the O-methylated samples and raw Wyodak coal were checked for residual iodine content by Huffman Laboratory, of Golden, Colorado. The result for weight percent of iodine in sample is shown below:

	Weight percent Iodine in sample
Raw Wyodak Coal	0.10
O-methylated Wyodak Coal (6.50 CH_3 /100 C atoms)	0.17
O-methylated Wyodak Coal (4.32 CH_3 /100 C atoms)	0.28
O-methylated Wyodak Coal (5.25 CH_3 /100 C atoms)	0.32

The results show that in raw and methylated Wyodak coal small amounts of iodine, up to 0.32 wt %, exist. This is considered to be a high enough concentration for the possibility of iodine to act as a catalyst. The iodine in raw Wyodak coal and O-methylated Wyodak coal shown by the above data can be considered to be approximately of the same magnitude. However in order to eliminate this as a possible reason for the liquefaction reactivity enhancement noted for the alkylated coals, liquefaction of raw Wyodak and coal spiked with CH_3I was carried out using DHP as a liquefaction solvent at 350 °C and 30 minutes reaction times. These reaction conditions were selected because at lower temperature the catalyst effect is more pronounced than at higher temperature. Experiments were performed by adding methyl iodide up to 1.0 wt % of iodide. The results of these experiments are shown below:

	<u>no CH_3I</u>	<u>1 wt% CH_3I added</u>
% THF conversion	41.05	43.92

From this result we can see that there is no catalyst effect from residual iodine even when the concentration of iodine is as high as 1 wt%. Therefore, we can conclude that the increase in THF conversion for O-methylated Wyodak coal is not the result of catalysis by residual iodine.

Data for THF conversion of liquefied O-methylated Wyodak coal as a function of extent of alkylation (corrected for intrinsic THF solubility) are shown in Figures 27-32.

Figure 27 shows THF conversion and Figure 28 shows percent increase in THF conversion for liquefaction of O-methylated Wyodak coal at different levels of methylation at 350 °C for both 5 minute and 30 minute reaction times. From these figures we can see that there is an increase in THF conversion with an increase in the number of methyl groups added. For 5 minute reaction times, the increase in THF conversion is up to as high as 195 %, and for 30 minute reaction times THF conversion is increased by up to 95%.

Figure 29 shows THF conversion and Figure 30 shows percent increase in THF conversion for liquefaction of O-methylated Wyodak coal at different levels of methylation at 425 °C for both 5 minute and 30 minute reaction times. From these figures we can see that there is an increase in THF conversion with an increase in the extent of methylation, but the effects are much less pronounced than at lower reaction temperature. THF conversion increases are less than 15% at the 5 minute reaction times and less than 12% for the 30 minute reaction times. However, if pretreatment can improve THF conversion by as little as 5% at high reaction severity, it may be considered to be a successful method. Therefore, we can conclude that O-methylation of Wyodak coal is an effective method for improving the liquefaction yield. Figures 31 and 32 show a comparison of the increase in THF conversion between low and high temperatures at 5 minute and 30 minute reaction times. From both figures we can clearly see that the effect of

FIGURE 27

EFFECT OF EXTENT OF O-METHYLATION ON REACTIVITY
WYODAK COAL
DIRECT LIQUEFACTION AT 350 C

Liquefied in DHP at 350 degree C

FIGURE 28

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
WYODAK COAL
DIRECT LIQUEFACTION AT 350 C

Liquefied in DHP at 350 degree C

FIGURE 29

EFFECT OF EXTENT OF O-METHYLATION ON REACTIVITY
 WYODAK COAL
 DIRECT LIQUEFACTION AT 425 C

Liquefied in DHP at 425 degree C

FIGURE 30

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
WYODAK COAL
DIRECT LIQUEFACTION AT 425 C

Liquefied in DHP at 425 degree C

FIGURE 31

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
SHORT RESIDENCE TIME DATA

Liquefied in DHP for 5 min.

FIGURE 32

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
LONG RESIDENCE TIME DATA

Liquefied in DHP for 30 min.

reaction times. Figure 34 shows the increase in THF conversion at 350 °C and 30 minutes reaction times as a percentage of the base (raw) coal conversion. As shown, the THF conversion is roughly doubled when the number methyl groups added is doubled. Figure 35 shows THF conversion for co-processing of O-methylated Wyodak coal using hydrotreated Cold Lake atmospheric residuum at 425 °C for both 5 and 30 minute reaction times. At the 5 minute reaction times it can be seen that there is an increase in THF conversion with coal methylation level. This increase in THF conversion is a maximum at 3.57 methyl groups added per 100 C atoms. At 30 minutes reaction time there is a significant increase in conversion from 0 to 1.95 groups added to 3.57 groups added. There is, however, no difference in THF conversion among 3.57, 8.00 and 17.16 methyl groups added. This is probably due to the fact that Wyodak coal has reached the maximum obtainable THF conversion for these reaction conditions.

5.2.3.4 Gas Analysis Results

Results from gas analyses of liquefaction runs made at 350 °C and 425 °C for 30 minute reaction times are shown in Table 8.

From these results one can see that most of the gases produced are carbon dioxide and methane. Carbon in coal converted into gaseous products amounts to approximately 3.07 wt% for untreated Wyodak coal liquefied in tetralin at 425 °C for a 30 minute reaction time. Carbon converted into gaseous products was only 1.52 wt% at 350 °C, and 2.76 wt%

FIGURE 34

INCREASE IN REACTIVITY VS. EXTENT OF O-METHYLATION
CO-PROCESSING AT 350 C
WYODAK COAL

Liquefied in hydrotreated A-8
at 350 degree C for 30 minutes.

FIGURE 35
EFFECT OF EXTENT OF O-METHYLATION ON REACTIVITY
WYODAK COAL
CO-PROCESSING AT 425 C

Liquefied in hydrotreated A-8
at 425 degree C

Table 8

Gas Analysis Results from Liquefaction Runs

	Raw Wyodak Coal	O-Methylated Coal	Wyodak
	425 °C 30 min.	350 °C 30 min.	425 °C 30 min.
Gas Produced (% mole)			
CO ₂	3.48	1.39	4.49
CH ₄	5.36	0.14	1.24
C ₂ H ₄	0.51	0.00	0.07
C ₂ H ₆	2.94	0.04	1.03
C ₃ H ₆	0.47	0.02	0.10
C ₃ H ₈	2.09	0.06	1.22
n-C ₄	0.34	0.12	0.98
H ₂ S	1.35	0.02	0.13
% C in coal converted into gas	3.07	1.52	2.76
H ₂ consumption (wt % MAF coal)	9.00	2.00	8.00

at 425 °C for O-methylated Wyodak coal. For all cases, one can see that the carbon conversion to gas product is low. As expected, at lower severity operating conditions the hydrocarbon gas make was lower (50%) than at higher severity. Gas production for liquefaction of O-methylated Wyodak coal was about the same magnitude as gas produced by liquefaction of raw Wyodak coal. From these results, one can conclude that gas produced by liquefaction under the conditions of this study was negligible.

Hydrogen consumption in these studies was very low. As expected the hydrogen consumption at lower temperature was lower than at higher temperature.

5.2.4 Effect of O-Methylation on Global Reaction Kinetics and Apparent Activation Energy of Wyodak Subbituminous Coal

The effect of alkylation on conversion of Wyodak coal has been shown in the above discussion to be significant in promoting enhanced conversions over a broad range of reaction severities. As an additional check on the effect of alkylation, rate data for liquefaction were obtained for raw and O-methylated Wyodak coal at 350, 375, and 400 °C by measuring reaction profiles at 5, 10, 15, 30, and 60 minutes reaction time. For these studies, a fresh batch of Wyodak subbituminous coal was alkylated following the Liotta procedures outlined previously. Subsequent elemental analysis of the alkylated coal indicated that the extent of

alkylation achieved was 8 methyl groups per 100 carbon atoms.

Rate data for conversion of dry and O-methylated Wyodak coal to THF, toluene, and hexane solubles are shown in Figures 36 through 41. From these data it can be readily seen that the O-methylated Wyodak coal exhibits higher conversions over the entire reaction profile and at each reaction temperature when compared to dry Wyodak coal.

In order to examine the effect of alkylation in more detail, the global rate data was next fit to a variety of kinetic models in order to facilitate calculation of an overall (global) activation energy for liquefaction of both raw and alkylated coals. Two kinetic models were tested with the rate data as shown below:

	Rate expression -----	Integrated Form -----
1 st order	$\frac{dx}{dt} = k(a-x)$	$x = a[1-\exp(-kt)]$
2 nd order	$\frac{dx}{dt} = k(a-x)^2$	$x = \frac{ka^2t}{kat + 1}$

where x = coal conversion (moisture and ash-free (MAF)
basis, wt%)

a = pseudo-equilibrium conversion

k = kinetic constant

t = reaction time (min.)

FIGURE 36

CONVERSION TO THF SOLUBLES VS. TIME
WYODAK COAL

FIGURE 37

CONVERSION TO TOLUENE SOLUBLES VS. TIME
WYODAK COAL

FIGURE 38

CONVERSION TO HEXANE SOLUBLES VS. TIME
WYODAK COAL

FIGURE 39

CONVERSION TO THF SOLUBLES VS. TIME
ALKYLATED WYODAK COAL

FIGURE 40

CONVERSION TO TOLUENE SOLUBLES VS. TIME
ALKYLATED WYODAK COAL

FIGURE 41

CONVERSION TO HEXANE SOLUBLES VS. TIME
ALKYLATED WYODAK COAL

Two different interpretations for the parameter "a" are possible. First, "a" can represent a reactive fraction of the coal that indicates that all of the organic material is not convertible even at infinite reaction time. Under this interpretation, "a" is a true constant that is a characteristic of the organic geochemistry of the coal. Traditionally, this fraction has been obtained by other researchers from a maceral analysis of the raw coal, and defined as total macerals (vitrinite + liptinite + inertinite) less the fusinite and semi-fusinite maceral subgroups. Data from the Argonne National Laboratories are available which would permit estimation of this factor for raw Wyodak coal, but use of this approach for alkylated coal presents a problem. It is likely that the chemistry of the maceral groups are significantly altered by the alkylation procedure, and "a" for alkylated coal is hence not the same as for the parent material. A second interpretation is that the "a" parameter reflects a pseudo-equilibrium conversion level. Under this interpretation, "a" introduces reversibility into the otherwise irreversible batch reactor material balance expressions shown above ("a" = 1.0 if reaction is irreversible), and hence represents a parameter that is not a pure constant but one that changes with temperature. In this type of model, parameter "a" is treated as an additional fitting parameter and the only restrictions on this factor are:

1) "a" · maximum observed conversion for each solvent solubility classification;

2) "a" must increase with increasing temperature.

In the following discussion, the second interpretation has been applied to parameter "a".

The results of fitting data to the integrated forms of the rate models are presented in Tables 9 and 10 for dry Wyodak coal, and Tables 11 and 12 for O-methylated coal. The test statistic used to discriminate between these various models in terms of overall adequacy was based on regression analysis of the linearized rate models to give the highest value of R^2 and the smallest value of the standard error of estimate (SEE) defined as:

$$SEE = \frac{[\sum (X - X^*)^2]^{\frac{1}{2}}}{n-1}$$

Where, X = the experimental values of coal conversion
(wt %)

X^* = the calculated values of coal conversion
by the model (wt %)

n = the number of data points

As can be seen, the first-order pseudo irreversible model and the second-order pseudo irreversible model both gave nearly identical results for the SEE test statistic for THF, toluene, and hexane solubles conversion data sets. However, the second order irreversible model give R^2 values higher than 0.90 for the linearized batch reactor material

Table 9

Pseudo First Order Irreversible Model for Raw Wyodak Coal

Hexane Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	7.92	0.0086	0.74	1.41
375 °C	9.67	0.0115	0.69	0.95
400 °C	20.90	0.0221	0.73	0.82

Toluene Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	11.13	0.0080	0.71	1.22
375 °C	18.19	0.0097	0.74	0.83
400 °C	23.10	0.0174	0.68	0.92

THF Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	15.18	0.0059	0.67	1.21
375 °C	20.08	0.0097	0.70	0.96
400 °C	26.04	0.0129	0.69	0.74

Table 10

Pseudo Second Order Irreversible Model for Raw Wyodak Coal

Hexane Solubles

<u>Temperature</u>	<u>a</u>	<u>k</u>	<u>R²</u>	<u>SEE</u>
350 °C	30.95	0.0017	0.94	1.29
375 °C	30.76	0.0046	0.99	0.49
400 °C	34.16	0.0069	0.96	0.57

Toluene Solubles

<u>Temperature</u>	<u>a</u>	<u>k</u>	<u>R²</u>	<u>SEE</u>
350 °C	32.78	0.0019	0.95	0.56
375 °C	34.72	0.0062	0.95	0.74
400 °C	36.63	0.0067	0.97	0.55

THF Solubles

<u>Temperature</u>	<u>a</u>	<u>k</u>	<u>R²</u>	<u>SEE</u>
350 °C	34.01	0.0033	0.98	0.83
375 °C	35.58	0.0053	0.95	0.65
400 °C	36.23	0.0106	0.92	0.71

Table 11

Pseudo First Order Irreversible Model for O-methylated
Wyodak Coal

Hexane Solubles

<u>Temperature</u>	<u>a</u>	<u>k</u>	<u>R²</u>	<u>SEE</u>
350 °C	18.17	0.0043	0.79	1.09
375 °C	28.50	0.0058	0.74	1.07
400 °C	37.33	0.0100	0.62	1.20

Toluene Solubles

<u>Temperature</u>	<u>a</u>	<u>k</u>	<u>R²</u>	<u>SEE</u>
350 °C	25.27	0.0041	0.70	1.73
375 °C	36.23	0.0057	0.69	1.39
400 °C	43.38	0.0092	0.66	1.23

THF Solubles

<u>Temperature</u>	<u>a</u>	<u>k</u>	<u>R²</u>	<u>SEE</u>
350 °C	28.78	0.0037	0.70	1.66
375 °C	38.09	0.0051	0.71	1.26
400 °C	45.15	0.0081	0.65	1.16

Table 12

Pseudo Second Order Irreversible Model for O-methylated
Wyodak Coal

Hexane Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	34.01	0.0045	0.95	0.58
375 °C	39.37	0.0100	0.96	0.39
400 °C	47.39	0.0120	0.99	0.15

Toluene Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	42.91	0.0049	0.95	0.82
375 °C	49.75	0.0080	0.95	0.52
400 °C	53.76	0.0119	0.93	0.45

THF Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	45.45	0.0056	0.97	0.56
375 °C	50.50	0.0092	0.95	0.51
400 °C	55.24	0.0116	0.94	0.48

balance (for all cases) while the first order model gave R^2 values ranging from 0.63 to 0.79. The superior R^2 values for the second-order model indicates that this expression is better in terms of the ability to describe the data when compared to the first-order. Additionally, unrealistically low values for the pseudo-equilibrium conversion parameter ("a") are obtained from the first-order model while reasonable and realistic values for "a" are obtained when the data are fit with the second-order expression. Therefore, the second-order pseudo irreversible rate model was selected for subsequent calculation of reaction rate parameters (rate constants) and the global activation energy.

Parity plots (observed conversion vs. calculated conversion using the pseudo second order irreversible model) for dry Wyodak coal are shown in Figure 42 for hexane solubles, Figure 43 for toluene solubles, and Figure 44 for THF solubles. As can be seen, the second-order model provides an excellent description of the liquefaction data.

Arrhenius plots of these rate constants vs. absolute temperature for conversion of raw and O-methylated Wyodak coal to THF, toluene, and hexane solubles are shown in Figures 45 to 47. The coefficient of determination (R^2) for the Arrhenius plots was over 0.9 for all data sets except for the case of toluene soluble of dry Wyodak coal ($R^2 = 0.81$).

FIGURE 42

PARITY PLOT FOR THF SOLUBLES

FIGURE 43

PARITY PLOT FOR TOLUENE SOLUBLES

FIGURE 44
PARITY PLOT FOR HEXANE SOLUBLES

FIGURE 45
ARRHENIUS PLOTS FOR THF SOLUBLES

FIGURE 46
ARRHENIUS PLOTS FOR TOLUENE SOLUBLES

FIGURE 47
ARRHENIUS PLOTS FOR HEXANE SOLUBLES

The calculated activation energies based on the slope of the Arrhenius plots are shown in Table 13. As can be seen, the derived global activation energy is significantly lower for the O-methylated coals as compared to liquefaction of raw Wyodak coal for all solvent solubility groups (THF, toluene, hexane). The difference in activation energy is approximately 6 Kcal/mole for all three solubility classifications. These parameters indicate that a very significant enhancement in the rate of liquefaction to THF, toluene, and hexane solubles is brought about by the O-methylation process employed.

It is important to note that the activation energies derived from the rate data and modeling do not have any fundamental significance in terms of the chemical rate processes involved in coal liquefaction. In fact, these parameters are only useful for purposes of making relative comparisons between coals, and should not be used for generalization and/or extrapolation to other coals or processing conditions. As relative indicators of reactivity however, these results do show that the effect of O-methylation on the rate of liquefaction of Wyodak subbituminous coal is highly significant and nearly catalytic in magnitude.

Table 13
Activation Energy and Frequency Factor

	Dry Wyodak Coal -----	O-methylated Wyodak Coal -----
Hexane Solubles -----		
Activation Energy (Kcal/mole)	23.71	16.99
Frequency Factor	3.60E+5	4536.00
R ²	0.95	0.92
Toluene Solubles -----		
Activation Energy (Kcal/mole)	21.02	14.53
Frequency Factor	5.42E+4	626.41
R ²	0.81	0.99
THF Solubles -----		
Activation Energy (Kcal/mole)	19.09	12.32
Frequency Factor	1.60E+4	121.51
R ²	0.97	0.98

6.0 LITERATURE CITED

1. Berkowitz, B.J. "Introduction to Coal Technology", Academic Press, Chapter 12, (1982).
2. Whitehurst, D.D., Mitchell, T.O., Farcasiu, M., "Coal Liquefaction: The Chemistry and Technology of Thermal Processes", Academic Press Chapter 1, 4, and 5, (1980).
3. Schindler, H.D., "Coal Liquefaction: A Research and Development Needs Assessment", DOE Final Report Vol. II, (March 1989).
4. McMillen, D.F., Malhotra, R., Hum, G.P., and Chang, S.J., "Hydrogen-Transfer-Promoted Bond Scission Initiated by Coal Fragments", Energy & Fuels, 1, p193, (1987).
5. McMillen, D.F., Malhotra, R., Chang, S.J., and Nignda, E.S., "Hydrogenolysis in Coal Liquefaction and Pyrolysis: The Relative Importance of Solvent Radicals and Free Hydrogen Atoms", American Chemical Society Fuel Preprints, 30, p397, (1985).
6. Vernon, L.W., "Free Radical Chemistry of Coal Liquefaction: Role of Molecular Hydrogen", Fuel, 59, p102 (1980).
7. Shinn, J.H., Dahlberg, A.J., "The Chevron Co-Refining Process", The Ninth Annual EPRI Contractor Conference on Coal Liquefaction Report, Palo Alto, CA, (1984).
8. Giacamelli, G.F., "Low Severity Coal/Oil Co-processing Using Model Nitrogen Compounds" Master's Thesis, Colorado School of Mines, Golden, Colorado (1987).
9. Satterfield, C.N., "Heterogeneous Catalysis in Practice", McGraw Hill, pp 282, 292-294, (1980).
10. Derbyshire, F., "Catalysis in Coal Liquefaction", IEA Coal Research Release, Chapter 4, (1988).
11. Anderson, L.L. and Miin, T.C., "Catalysis of Coal Conversion at Mild Temperatures", Fuel Proc. Tech., 12, p165, (1986).
12. Wu, W.K. and Storch, H.H., "Hydrogenation of Coal and Tar", Bureau of Mines Bull. 633, (1968).
13. Gorin, E., Ziekle, C.W., Struck, R.T., "Molten Zinc Halide for Hydrocracking Coal Extract and Coal", Ind. Eng. Chem. Proc. Des. Dev., 5, 151, (1966).

14. Sharma, D.K., Sarkar, M.K. and Mirza, Z.B., "Coal Extraction: Enhancement Through Novel Prior Alkylation Procedures at Atmospheric Pressure", Fuel, 64, p449, (1983).
15. Larsen, J.W. and Kuemerle, E.W., "Alkylation and Depolymerization Reactions of Coal: A Selected Review with Supplementary Experiments", Fuel 55, p162, (1976).
16. Schlosberg, R.H., Neavel, R.C., Maa, P.S. and Gorbarty, M.L., "Alkylation: A Beneficial Pretreatment for Coal Liquefaction", Fuel, 59, p45, (1980).
17. Hodek, W. and Koelling, G., "Increase in Extractability of Bituminous Coal Caused by Friedel-Crafts Acylation", Fuel 52, p220, (1973).
18. Sternberg, H.W., Delle Donne, C.L., Pantages, P., Moroni, E.C. and Markby, R.E., "Solubilization of a lvb Coal by Reductive Alkylation", Fuel, 50, p 432, (1971).
19. Sternberg, H.W. and Delle Donne, C.L., "Solubilization of Coals by Reductive Alkylation", Fuel, 53, p172, (1974).
20. Stock, L.M., "The Reductive Alkylation Reaction", Coal Science, Vol. I, Academic Press, p161, (1982).
21. Date, A.C. and Johns, R.B., "A Study of Reductive Alkylation on a Rank Range of Australia Coals", 1987 Int'l. Conf. on Coal Science, edited by J.A. Moulijn, et al, Elsevier Science Publishers B.V., Amsterdam, (1987).
22. Lazarov, L., Marinokv, S.P., Stefanova, M. and Angelova, G., "Solubility of O- and C-Alkylated Coals of Different Rank", 1987 Int'l. Conf. on Coal Science, edited by J.A. Moulijn, et al, Elsevier Science Publishers B.V., Amsterdam, (1987).
23. Miyaki, M., Yamamoto, S., Normura, M., "Reductive Alkylation with Short Anionization Time Using Molten K", Fuel, 67, p589, (1988).
24. Liotta, R., Selective Alkylation of Acidic Hydroxyl Group in Coal", Fuel, 58, p724, (1979).
25. Liotta, R., Rose, K., and Hippo, E., "O-alkylation Chemistry of Coal and its Implication for the Chemical and Physical Structure of Coal", J. Org. Chem. 46, p277, (1981).
26. Marzec, A., Kisielow, W., "Mechanism of Swelling and Extraction and Coal Structure.", Fuel, 62, p977, (1983).
27. Green, T.K., Chamberlain, J.M., "Swelling of Coal Extracts" Fuel, 65, p759, (1986).

28. Liotta, R., Brons, G., Isaacs, J., "Oxidative Weathering of Illinois #6 Coal", J. Am. Chem. Soc., 103, p1735, (1981).
29. Green, T.K., West, T.A., "Coal Swelling in Straight Chain Amines: Evidence for Specific Site Binding.", Fuel, 65, p1435, (1986).
30. Green, T.K., Kovac, J., Larsen, J.W., "A Rapid and Convenient Method for Measuring the Swelling of Coal by Solvents", Fuel, 63, p935, (1984).
31. Ricon, M.J., Cruz, S., "Influence of Preswelling on Liquefaction of Coal", Fuel, 67 p1162, (1988).
32. Joseph, J.T., "Liquefaction Behavior of Solvent-swollen Coals", Fuel, 70, p139, (1991).
33. Joseph, J.T., "Beneficial Effect of Preswelling on Conversion and Catalytic Activity during Coal Liquefaction", Amoco Research Center, (1991).
34. Shatwell, H.G., Graham, J.L., "The Hydrogenation and Liquefaction of Coal-I", Fuel, V4, (1925).
35. Hegarty, M., "The Effect of Mineral Matter in Donor Solvent Coal Conversion", Master Thesis T-2114, Colorado School of Mines, Golden, Colorado (Dec, 1978).
36. Neavel, R.C., et al., "Interrelationships between Coal Composition Parameters", Fuel, 65, p312 (1986).
37. Kwon, K.C., "Comparison of Anthracene and Phenanthrene in Coal Liquefaction", Fuel, 64, p747, (1985).
38. Mori, K., et al, "Relationship between Coal Characteristics and It's Reactivity on Hydroliquefaction", ACS Fuel Preprints 24, No.2 (1979)
39. Given, P.H., Cronauer, D.C., Spackman, W., Lovell, H.L., Davis, A., Biswas, B., "Dependence of Coal Liquefaction Behavior on Coal Characteristics. 1. Vitrinite-Rich Samples", Fuel, 54, p34 (1975).
40. Given, P.H., Cronauer, D.C., Spackman, W., Lovell, H.L., Davis, A., Biswas, B., "Dependence of Coal Liquefaction Behavior on Coal Characteristics. 2. Role of Petrographic Composition", Fuel, 54, p40 (1975).
41. Given, P.H., Cronauer, D.C., Spackman, W., Lovell, H.L., Davis, A., Biswas, B., "Dependence of Coal Liquefaction Behavior on Coal Characteristics. 3. Statistical Correlations of Conversion in Coal-Tetralin Interactions", Fuel, 54, p89 (1978).

42. Yarzab, R.F., Given, P.H., Spackman, W., Davis, A., "Dependence of Coal Liquefaction Behavior on Coal Characteristics. 4. Cluster Analysis for Characteristics of 104 Coals", Fuel, 59, p. 81 (1980).
43. Niell, P.H., et al., "A Search for Systematic Relations Between Aromaticity and Rank of High Sulfur Coals", Fuel, 66, p96, (1987).
44. Niell, P.H. et al., "Aromaticity of Some High Sulfur Coals: Suppressing Degree of Heterogeneity", Fuel, 96, (1987).
45. Gray, D., "Inherent Mineral Matter in Coal and It's Effect upon Hydrogenation", Fuel, 57, p213, (1978).
46. Nguanprasert, O., "Use of Mild Chemical Pretreatment to Enhance Coal Reactivity", Unpublished PhD Thesis #T-4053, Arthur Lakes Library, Colorado School of Mines, July, 1991.
47. Gray, D., Barrass, G., Jezko, J., and Kershew, J.R., "Relationship between Hydroliquefaction Behavior and Organic Properties of a Variety of South African Coals", Fuel, 59, p146, (1980).
48. Makabe, K., "Hydrogenation Characteristics of some Coal Macerals", International Conference on Coal Science, p295, 1987.
49. Durie, R.H., "The Characteristics of Australian Coals and Their Implication in Coal Liquefaction", ACS Fuel Preprints, 24, No.2, (1977).
50. Miller, R.L., Baldwin, R.M., "Effect of Wyodak Coal Properties on Hydroliquefaction Reactivity", Fuel, 64, p1235, (1985).
51. Furlong, M.W., "Correlation of Parent Coal Properties with a Kinetically-Defined Donor Solvent Liquefaction Reactivity", Ph.D. Thesis T-2472, Colorado School of Mines, Golden, Colorado (April 1981).
52. Shin, S.C., "Reactivity of Coal in Direct Hydrogenation", Master Thesis T-3267, Colorado School of Mines, Golden, Colorado.
53. Shin, S.C., Baldwin, R.M., and Miller, R.L., "Coal Reactivity in Direct Hydrogenation Liquefaction Process: Measurement and Correlation With Coal Properties", Energy & Fuels, 1, p377, (1987).
54. Anthony, D.B., et al. "Rapid Devolatilization of Pulverized Coal", Fifteenth Symposium (International) on

Combustion, p1303, The Combustion Institute, Pittsburgh, PA, (1976).

55. Anthony D.B., Howard, J.B., "Coal Devolatilization and Hydrogasification", AICHE J. , 22, p625 (1976).

56. Szladow, A.J., and Given P.H., "Models and Activation Energies for Coal Liquefaction Reactions", I&EC Proc. Des. Dev., 20, p27, (1981).

57. Shin, S.C., "Correlation of Bituminous Coal Hydroliquefaction Rate with Coal Properties", Ph.D. Thesis T-3569, Colorado School of Mines, Golden CO, (April, 1988).

58. Shin, S.C., Baldwin, R. M., and Miller, R.L., "Correlation of Bituminous Coal Hydroliquefaction Activation Energy with Fundamental Coal Chemical Properties", Energy & Fuels, 3, p193, (1989).

59. Shiotsuka, T., Onoe, K., and Nonomura, A., "Kinetic Analysis of Molecular-Weight Distribution in Coal Liquefaction. Effect of Lowering of the Molecular Weight of Liquefied Oil", International Chemical Engineering, 29, p279, (1989).

60. Ho, T.C., White, B.S., and Hu, R., "Lumped Kinetics of Many Parallel n^{th} -Order Reactions", AIChE J., 36, p685, (1990).

61. Prasad, G.N., Wittman, C.V., Agnew, J.B., "Modeling of Coal Liquefaction Kinetic Based on Reaction in Continuous Mixtures: Part 1. Theory", AICHE J., 32, p1277 (1986).

62. Prasad, G.N., Wittman, C.V., Agnew, J.B., "Modeling of Coal Liquefaction Kinetic Based on Reaction in Continuous Mixtures: Part 2. Comparison with Experiments on Catalyzed and Uncatalyzed Liquefaction of Coals of Different Rank", AICHE J., 32, p1288, (1986).

63. Oele, A.P., et al., "Extractive Disintegration of Bituminous Coals", Fuel, 30, p169, (1951).

64. Baldwin, R.M., Kennar, D.R., Nguanprasert, O., and Miller, R.L., "Liquefaction Reactivity Enhancement of Coal by Mild Alkylation and Solvent Swelling Techniques", Fuel, 70, p429 (1991)

65. Curran, G.P., Struck, R.T., Gorin, E., "Mechanism of Hydrogen Transfer Process to Coal and Coal Extract", I&EC Proc. Des. Dev., 6, p166 (1967).

66. Falkum, E., and Glenn, R. A., "Coal Hydrogenation Studies II-Effect of Time on Restricted Hydrogenolysis of

Sptitsbugen Coal with Adkins Catalyst", Fuel, 31, p133 (1952).

68. Weller, S., Pelipets, M.G., and Friedman, S., "Conversion of Anthraxylon", Ind. Eng. Proc. Des. Dev., V6, p166, (1973).

69. Libenberg, B.J., and Potgieter, H.B., "The Uncatalysed Hydrogenation of Coal", Fuel, 52, p130, (1973).

70. Yoshida, R., and Maekawa, Y., "Mechanism of High Pressure Hydrogenolysis of Hokkaido Coal", Fuel, 55, p337, (1976).

71. Shalabi, M.A., Baldwin, R.M., Bain, B.L., Gary, J.H., and Golden, J.O., I&EC Proc. Des. Dev., 18, p474, (1979).

72. Cronauer, D.C., Shah, Y.T., Roberto, R.G., "Kinetics of Thermal Liquefaction of Belle Ayr Subbituminous Coal", I&EC Proc. Des. Dev., 17, p.281, (1987).

73. Dasgupta, R., Gun, S.R., and Mukherjee, D.K., "Kinetic Modeling of High Temperature Hydrogenation of Assam Coal", Fuel, V67, p198, (1988).

74. Vidrine, W.D., "Photoacoustic Fourier Transform Infrared Spectroscopy of Solid Samples", Applied Spectroscopy, 34, p314, (1980).

75. Solomon, P.R., Carangelo, R.M., "FTIR Analysis of Coal: 1. Techniques and determination of hydroxyl Concentrations", Fuel, 61, p663, (1982).

76. Brown and Ladner" A Study of Hydrogen Distribution in Coal-like Materials By High NMR" ,Fuel, 39, p79, (1960).

77. Painter, P.C., Snyder, R.W., Starsinic, M., Coleman, M.M., Kuehn, D.W., Davis, A., "Concerning the Application of FTIR to the Study of Coal: A Critical Assessment of Band Assignments and the Application of Spectral Analysis Programs", Applied Spectroscopy, 35, p475, (1981).

78. Painter, P.C., Sobkowiak, M., Youtcheff, J., "FTIR Study of Hydrogen Bonding in Coal", Fuel, 66, p973, (1987).

79. Solomon, P.R., Carangelo, R.M., "FTIR Analysis of Coal: 2. Aliphatic and Aromatic Hydrogen Concentration", Fuel, 61, p670, (1982).

80. Painter, P.C., Starsinic, M., Davis, A.A., "Concerning the 1600 cm^{-1} Region in the IR spectrum of Coal", Fuel, 62, p742, (1983).

81. Supaluknari, S., Larkin, F.P., " An FTIR Study of Australian Coals: Characterization of oxygen functional groups." Fuel Proc. Tech., 19, p123, (1988).
82. Redlich, P.J., Jackson, W.R., Larkin, F.P., Rash, D., "Studies Related to the Structure and Reactivity of Coals.", Fuel, 68, p222, (1989).
83. Vorres, K.S., "Users Handbook for The Argonne Premium Coal Sample Program", D.O.E. Division of Chemical Sciences, p 11, (1989).
84. Kennar, D.R., "The Effect of Selective Coal Pretreatment Methods Upon Low Severity Coal Liquefaction and Coal/Oil Co-processing", Masters Thesis T-3714, Colorado School of Mines, Golden, Colorado (June, 1991).
85. Dryden I.G.C., "Action of Solvents on Coals at Lower Temperature: I. A Quantitative Survey on the Effect of Liquids upon Bright Coal for Low Rank", Fuel, 30, p30, (1951).
86. Sternberg, V.I., Baltisbeger, R.J., Patal, M., "The Role of Noncovalent Bonding in Coal", Coal Science Vol. II, p125, (1983).
87. Stohl, F.V., "Studies of the Initial Reactions that Occur During Direct Coal Liquefaction" ACS Fuel Preprints 35, p814, (1990).

END

**DATE
FILMED**

1 / 20 / 93