UCRL- 85074
PREPRINT

CONF-81C314--54

MASTER

Beam Optics in the FXR
1.5 MeV, 4 kA Injector

R. Scarpetti
R. Kuenning
K. C. Wong

This paper was prepared for submittal to
the
Particle Accelerator Conference
Washington, D.C.
March 11-13, 1981

March 4, 1981

DISCLAIMER

This document contains information which may be classified as "Confidential" or "Secret" under the provisions of the Atomic Energy Act of 1954, as amended, and the Atomic Energy Regulations. It is the policy of the Lawrence Livermore Laboratory to protect such information from unauthorized disclosure. It is the responsibility of the user of this document to ensure that it is not disclosed to unauthorized persons. If you are a contractor or subcontractor of the Lawrence Livermore Laboratory, you are hereby notified that this document is the property of the Lawrence Livermore Laboratory and is to be returned to the Laboratory upon completion of your work. If you are not a contractor or subcontractor of the Lawrence Livermore Laboratory, you are hereby notified that this document is the property of the Lawrence Livermore Laboratory and is to be returned to the Laboratory upon completion of your work. If you are a contractor or subcontractor of the Lawrence Livermore Laboratory, you are hereby notified that this document is the property of the Lawrence Livermore Laboratory and is to be returned to the Laboratory upon completion of your work. If you are not a contractor or subcontractor of the Lawrence Livermore Laboratory, you are hereby notified that this document is the property of the Lawrence Livermore Laboratory and is to be returned to the Laboratory upon completion of your work.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

BEAM OPTICS IN THE FXR 1.5 MeV, 4 kA INJECTOR*

R. D. Scarpetti, R. W. Kuenfny, and K. C. Wong
Lawrence Livermore National Laboratory
Livermore, California 94550

Abstract

The 20 MeV, 4 kA linear induction accelerator (FXR), currently under construction at LLNL, will use a cold cathode injector. The foil cathode consists of a 0.03 mm tantalum ribbon wound in a spiral with successive turns spaced 0.8 mm apart. The emitted current will be 15-20 kA but will be reduced to 4 kA by collimating immediately beyond the anode. This will minimize the beam emittance and maintain a good impedance match with the low impedance driving source. Computer simulation was used extensively to optimize the configuration of the beam forming electrodes, the emitter geometry, and the overall focusing and beam transport system in the injector region. This paper will discuss the approach used and the problems encountered in the design of the diode geometry and of the overall beam optics. Preliminary experimental results will be presented and will be compared with the computer model predictions.

Introduction

FXR is a linear-induction accelerator being built at Lawrence Livermore National Laboratory (LLNL). It will accelerate a 4 kA electron beam to an energy of 20 MeV. The accelerator consists of a 1.5 MeV injector, plus 48 accelerator modules, each of which produces a 350-400 kV, 90 ns pulse. The overall injector design is given in a companion paper¹. This paper will describe the electron injector only, and in particular, the design of the anode and cathode and the design of the beam transport system. Initial experimental results show an injector beam current of 3.4 kA having an emittance of 60-70 mm-cm.

The Injector

The injector has been designed to emit approximately 18 kA from the cathode, mainly to improve impedance matching. Immediately after passing through the anode, the beam is collimated and the central 4 kA of the beam is transported through the injector into the accelerator proper. By collimating, the outer edges of the beam are stopped and only the cooler, central portion of the beam is transported.

Earlier work had indicated that a cold emitter could serve as an electron source for FXR.² Although a cold emitter is not as well understood as a thermionic emitter and is prone to nonuniform emission, it costs less, is simpler, and is not susceptible to poisoning, as are thermionic emitters.

The Diode

Some basic considerations in the diode design were:

- 1) The electric field at the emitting surface had to be high enough to cause fast "turn-on" for uniform emission over the entire surface.

- 2) The electric field at the non-emitting electrode surfaces had to be low enough to render electron emission from these surfaces negligible.
- 3) Beam pinching beyond the anode mesh could not occur.
- 4) Feasible fabrication methods, materials, and mechanical tolerances had to be established.

Because of the first and second considerations, we chose an anode-cathode (A-K) spacing such that the average field was 400 kV/cm at the cathode. Since an estimated macroscopic field enhancement of 5 to 6 times is obtained on the emitting surface, an electric field of 2-2.4 MV/cm exists there. The "turn-on" time for this material at these field strengths is estimated to be $5 - 10 \text{ ns}$.

The Cathode Assembly. The cathode assembly consists of a focus electrode and an electron emitter. The purpose of the focus electrode is to aid in focusing the beam and to minimize the electric field enhancement at the edge of the emitter. The focus electrode is stainless steel, which has been electro-polished to remove surface irregularities and buffed to a mirror finish. Initial testing has shown no problem of emission from the focus electrode. The focus electrode with the emitter in place is shown in Figure 1. The emitter consists of a tantalum foil strip, 0.03 mm X 10 mm wide, laid on its edge in a spiral over a convex stainless steel form. This form is coated with a 0.08 mm thick layer of copper. Each successive tantalum layer is separated by 0.6 mm with three strips of 0.25 mm X 6 mm wide stainless steel foil strip. The emitter is furnace-brazed using this copper coating as the base brazing material.

If we assume a Child-Langmuir space-charge limited behavior, then the radius of the emitting surface is related to the other diode parameters by:

$$R_{\text{cath}} = \left(\frac{I \times d_{A-K}}{7.3 \times 10^{-6} V^{3/2}} \right)^{1/2}$$

Allowing for a beam current of 18 kA, an A-K spacing 3.75 cm, and a diode voltage of 1.1 MV, the cathode radius was fixed at 4.4 cm. In the vicinity of the anode mesh, the radially-outward space-charged fields of the beam are shorted out by the mesh, leaving only the radially-inward magnetic self-fields. To compensate for this, the emitting surface was made convex which provides the electrons with an initially outward-directed momentum. This outward momentum maximizes the beam radius and minimizes the angle of convergence at the cathode, two desirable characteristics a planar emitter could not supply. A secondary effect is that the electric fields are greatest near the axis, causing the central portion of the cathode to turn on first.

The Anode Assembly. The anode is planar and consists of a grid. This anode grid is made of a 0.033 mm thick, 16 lines/cm, tungsten mesh. The mesh has a transmission of 80%. The tungsten mesh was a photo-etched grid (not a weave) forcing us to design mounting rims to minimize wrinkles. Directly

*Work performed under the auspices of the U.S. Department of Energy by the Lawrence Livermore Laboratory under contract number W-7405-ENG-48.

behind this grid is a low-conductance-water (LCW) cooled, aluminum-to-stainless steel, roll-bonded collimator. The collimator is water-cooled to dissipate the 400 watts generated in stopping part of the beam. We chose aluminum for the collimator because back-scattered and side-scattered electrons are thereby kept to a minimum. Scattered electrons would cause an increase in beam emittance. The stainless steel backing served as the cooling channel, thus eliminating electrolysis problems which would develop in a LCW system of combined aluminum, copper, and stainless steel plumbing.

The anode stem has an inner liner. This liner is tapered to aid in beam transport by minimizing the space-charge potential depression. The inner liner was perforated for vacuum pumpout.

To arrive at the final diode design, the computer code EBQ⁴ was used. This is a relativistic beam transport code which takes into account the self-forces on the beam. EBQ was also used to predict the beam behavior up to 15 cm beyond the anode mesh. To predict the beam behavior beyond 15 cm, we used the TRANSPORT⁵ code.

The diode configuration is shown in Figure 2. This figure shows the electron trajectories, the equipotential surfaces set up by the anode and cathode, and the electron beam itself. The focus electrode design and emitter design ensure uniform current emission over the entire emitting surface. This is shown in Figure 2 where a uniform spacing between the emitting surface and the first equipotential line illustrates a constant electric field across the emitter surface.

The Transition Region

The 76 cm long transition section, the axial magnetic field profile and the calculated beam envelope are shown in Figure 3a, b. The transition section was designed to allow some axial coil adjustment and for access to the anode and cathode electrodes. The electrical continuity through the mechanical joints is maintained by a silver-plated expansion band and soft tin solder. Both the anode and cathode surfaces are visible through viewports.

Test Results

Initial testing of the injector has begun. An overlay of the total emitted current and the diode voltage is shown in Figure 4a. Notice there is a 10-20 ns time delay between the voltage rise and current rise which corresponds to an emitter "turn-on" delay of 10-15 ns which is reasonable for the predicted electric field at the emitter. A 10 shot overlay for the transmitted current is shown in Figure 4b. From these figures we see a peak emitted current of 15.1 kA and a peak transmitted current of 3.1 kA for a diode voltage of 1.5 MV. Also notice in Figure 4a that the current ramps up with time. If this is a result solely of plasma closure, the resulting plasma velocity is between 5 and 8 cm/us.

The total emitted and transmitted currents are measured on resistive monitors located on the anode stem support structure. Summing the voltage of the six capacitor monitors yields the diode voltage. Table 1 shows the peak emitted beam current for peak diode voltages ranging from 1.0 MV to 1.5 MV. Note that the perveance remains essentially constant for all voltages, indicating space-charge limited behavior.

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use could not infringe privately owned rights. References herein to any specific commercial products, process, or service

Table 1

Voltage (MeV)	1.05	1.26	1.46	1.56
Current (kA)	7.54	10.70	12.40	13.70
Perveance ($I/V^{3/2}$)	7.01	7.14	7.03	7.03

Preliminary measurements on beam emittance have been obtained by letting the beam strike a 1 mm thick perforated brass plate. The beamlets passing through impinge upon an aluminum-backed phosphor screen. A picture is taken of the fluorescing phosphor. One such picture is shown in Figure 5. The negative of the picture is scanned with a microdensitometer to determine beamlet sizes. Preliminary measurements show that the beam has an emittance of 60-70 mr-cm.

Future Work

Testing will continue to further optimize beam emission and transport. This will include modifying the injector magnetic fields as well as experimenting with a graphite emitter and an aluminum foil anode.

ACKNOWLEDGEMENTS

The authors wish to acknowledge L. Booth, J. Claer, R. Kihara, A. Lopez, and C. Parkison for their contributions to the design, construction, and operation of the injector. A special thanks to R. Heatherland for his work on the unique fabrication of the emitter and to A. Paul for the use of his computer codes and hours of consultation. The authors also wish to thank A. Scarpetti for editorial assistance and K. Densberger and D. Wood for preparing the manuscript.

REFERENCES

1. B. Kulke, D. Ravenscroft, G. Vogtlin, "Design and Performance of a 1.5 MV Injector for FXR", this Conference, Paper 1-58.
2. B. Kulke, R. Kihara, "Emittance Measurements on Field Emitter Diodes," UCRL-82533, Lawrence Livermore National Laboratory (April 5, 1979).
3. G. A. Mesyats, S. P. Bugayev, et al., "Study of Initiation and Development of Short Vacuum Gaps Pulse Breakdown in Nanosecond Range, Part I", Third International Symposium on Discharge and Electrical Insulation in Vacuum, 212, (September 1968).
4. A. C. Paul, "EBQ - Transport of Space-Charge Beams in Axially Symmetric Devices", Lawrence Berkeley National Laboratory/UCID 8005 (November 1978).
5. A. C. Paul, "Transport - An Ion Optic Program LBL Version", Lawrence Berkeley National Laboratory/LBL2697 (February 1975).

by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute an implied endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government thereof, and shall not be used for advertising or product endorsement purposes.

Fig. 1. Cathode focus electrode with tantalum spiral emitter

Fig. 2. Diode configuration showing the electron trajectories. The emitter radius of curvature is 9.6 cm.

Fig. 3a. Transition Section

Fig. 3b. Transition Section

Fig. 4a. Beam current (15.1 kA peak) and diode voltage (1.5 MeV) 50 ns/div

Fig. 4b. Transmitted current 3.1 kA peak 50 ns/div

Fig. 5. Beam emittance picture