Princeton University
Plasma Physics Laboratory
P.O. Box 451
Princeton, NJ 08543

PPPL--2536

DE88 012721

ENVIRONMENTAL MONITORING REPORT FOR CALENDAR YEAR 1987

By

Joseph R. Stencel

May 1988

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

26

ENVIRONMENTAL MONITORING REPORT
FOR CALENDAR YEAR 1987

Joseph R. Stencel

Plasma Physics Laboratory, Princeton University
Princeton, New Jersey 08543

ABSTRACT

The results of the 1987 environmental monitoring program for the Princeton Plasma Physics Laboratory (PPPL) are presented and discussed. Two of three large tokamak machines, the Princeton Beta Experiment Modification (PBX-M) and the Tokamak Fusion Test Reactor (TFTR) were in operation during the year. In addition, the S-1 Spheromak and the Radio-Frequency Test Facility (RFTF) were operated on a limited basis in 1987.

The Environmental Committee which is a standing committee of the Executive Safety Board (ESB) continued to review items of environmental importance. During CY87 no adverse effects to the environment or public resulted from any operational program activities at PPPL, and the Laboratory was in compliance with all applicable Federal, State, and local environmental regulations.

TABLE OF CONTENTS

	<u>Page</u>
Abstract	i
Table of Contents	ii
List of Tables	iv
List of Figures	v
1.0 Introduction	1
1.1 General	1
1.2 Description of the Site	5
2.0 Summary	7
3.0 Monitoring, Environmental Program Information, Data Collection, Analyses, and Evaluation	8
3.1 Radioactivity	9
3.1.1 Penetrating Radiation	9
3.1.2 Special Surveys	11
3.1.3 Airborne Radioactivity	12
3.1.4 Waterborne Radioactivity	13
3.1.5 Foodstuffs	14
3.1.6 Soil, Grass, Vegetation	14
3.2 Nonradioactive Pollutants	15
3.2.1 Airborne Effluents	15
3.2.2 Water Utilization	15
3.2.3 Spills	17
3.2.4 Herbicides, Fertilizer, and Pesticides	18
3.2.5 Polychlorinated Biphenyls	18
3.2.6 Hazardous Waste	19
3.3 Environmental Impact	20
3.3.1 Assessment of Radiation Dose to the Public	20
3.3.2 Assessment of Nonradioactive Pollutants	20

	<u>Page</u>
4.0 Quality Assurance for Laboratory Analyses	21
5.0 Future Program Expansion	22
5.1 Meteorological	22
5.2 Water Quality	22
5.3 Radioactive Effluents	22
5.4 Nonradioactive Effluents	23
6.0 Regulations and Safety Criteria	23
7.0 Acknowledgments	24
8.0 References	25

LIST OF TABLES

	<u>Page</u>
Table 1 TFTR Radiation Exposure Criteria	30
Table 2 Critical Pathways.....	31
Table 3 Monitoring Program Covering Critical Pathways	32
Table 4 Population of Municipalities Within 0-10 Miles of PPPL (1985-2010)	33
Table 5 Population of Counties Within 10-50 Miles of PPPL (1985-2010)	34
Table 6 Population of Metropolitan Areas Within 50 Miles of PPPL	35
Table 7 1985 Population Estimates Within Annular Sectors, 0-10 Miles	36
Table 8 1995 Population Estimates Within Annular Sectors, 0-10 Miles	37
Table 9 2000 Population Estimates Within Annular Sectors, 0-10 Miles	38
Table 10 2005 Population Estimates Within Annular Sectors, 0-10 Miles	39
Table 11 2010 Population Estimates Within Annular Sectors, 0-10 Miles	40
Table 12 1985 Population Estimates Within Annular Sectors, 10-50 Miles	41
Table 13 1995 Population Estimates Within Annular Sectors, 10-50 Miles	42
Table 14 2000 Population Estimates Within Annular Sectors, 10-50 Miles	43
Table 15 2010 Population Estimates Within Annular Sectors, 10-50 Miles	44
Table 16 Sectorized Population Data to 1 mile.....	45
Table 17 Well Water Monitoring Data	46
Table 18 Water Quality Monitoring Data: Location B1	48
Table 19 Water Quality Monitoring Data: Location B2	49
Table 20 Water Quality Monitoring Data: Location C1	50
Table 21 Water Quality Monitoring Data: Location D1	51
Table 22 Water Quality Monitoring Data: Location D2	52
Table 23 Water Quality Monitoring Data: Location E1	53
Table 24 Water Quality Monitoring Data: Location M1	54

	<u>Page</u>
Table 25 Water Quality Monitoring Data: Location P1	55
Table 26 Water Quality Monitoring Data: Location P2	56
Table 27 Water Quality Monitoring Data: Location W4 (C-site) ..	57
Table 28 Water Quality Monitoring Data: Location W5 (C-Site) ..	58
Table 29 Water Quality Monitoring Data: Location TW1 (D-Site).	59
Table 30 Water Quality Monitoring Data: Location TW10 (D-site).	60
Table 31 Fertilizer, Pesticides, and Herbicide Application CY87 ..	61
Table 32 QA/QC EPA Las Vegas Cross-Check Program 1987	62
Table 33 Nonradioactive QA Results (Split Samples)	63
Table 34 USGS Water Quality for Test Wells 1 and 10, FY87	64

LIST OF FIGURES

	<u>Page</u>
Fig. 1 Photo of S-1 Spheromak	65
Fig. 2 Photo of RFTF	66
Fig. 3 Photo of PBX-M	67
Fig. 4 Photo of TFTR	68
Fig. 5 Wind Rose (30 m)	69
Fig. 6 Wind Rose (60 m)	70
Fig. 7 80 km (59-mile) radius of site	71
Fig. 8 Immediate Site Vicinity (5-mile radius)	72
Fig. 9 Plasma Physics Laboratory, James Forrestal Campus ...	73
Fig. 10 1985 Population Estimates Within Annular Sectors 0-10 miles	74
Fig. 11 1995 Population Estimates Within Annular Sectors 0-10 miles	75
Fig. 12 2000 Population Estimates Within Annular Sectors 0-10 miles	76
Fig. 13 2005 Population Estimates Within Annular Sectors 0-10 miles	77
Fig. 14 2010 Population Estimates Within Annular Sectors 0-10 miles	78
Fig. 15 1985 Population Estimates Within Annular Sectors 10-50 miles	79
Fig. 16 1995 Population Estimates Within Annular Sectors 10-50 miles	80

	<u>Page</u>
Fig. 17 2000 Population Estimates Within Annular Sectors	
10-50 miles	81
Fig. 18 2005 Population Estimates Within Annular Sectors	
10-50 miles	82
Fig. 19 2010 Population Estimates Within Annular Sectors	
10-50 miles	83
Fig. 20 PPPL C and D Sites with Environmental Monitoring	
Locations	84
Fig. 21 Millstone River Basin Off-Site Water Sampling	
Locations	85
Fig. 22 Potentiometric Surface of the Bedrock Aquifer	86
Fig. 23 Schematic Representation of Hydrogeologic	
Framework and Potential Flow Paths of Spilled Water ..	87
Fig. 24 Planned Off-Site Monitoring Locations	88

1.0 INTRODUCTION

1.1 General

This report gives the results of the environmental monitoring program at the Princeton Plasma Physics Laboratory (PPPL) for Calendar Year 1987 (CY87). The report is prepared to provide the U.S. Department of Energy (DOE) and the public with information on the level of radioactive and nonradioactive pollutants, if any, added to the environment as a result of PPPL operations. The objective of the environmental monitoring report is to document evidence that DOE facility environmental protection programs adequately protect the environment and the public health.

PPPL has engaged in fusion energy research since 1951 and in CY87 had two of its three large tokamak devices in operation; namely, the Princeton Beta Experiment - Modification (PBX-M) and the Tokamak Fusion Test Reactor (TFTR). The Princeton Beta Experiment (PBX), which was shut down at the end of 1985 to undergo a major modification (PBX-M), was put back into operation in October 1987. The Princeton Large Torus (PLT) was shut down in December 1986. In addition, the S-1 Spheromak, which began operation in CY83 continued on a program of plasma research operation, following upgrades to the flux core liner, before being shut down at the end of CY87. The goal of the Magnetic Fusion Energy Research Program is to develop and demonstrate the practical application of fusion power as an alternate energy source.

The Spheromak is a compact toroidal concept. The S-1 (Fig. 1) achieved an initial goal of producing hot (>100 eV) plasmas with a lifetime of 1 msec or more. With the achievement of toroidal currents of over 300 kA, electron densities in the mid-to-upper 10^{13} cm $^{-3}$ range, and with the new flux core liner installed, the

confinement features of the spheromak configuration were successfully investigated. A novel feature of the recent experiments was a magnetic compression of spheromak plasmas. In this experiment the plasma parameters improved, supporting constant β scaling as $n_e T_e \propto B^2$ ($T_i > T_e$). Operation and maintenance of the S-1 had no expected potential for impact on the environment, a conclusion that is documented in the project's Safety Assessment Document [E184]. The S-1 was mothballed at the beginning of CY88.

Another small device, the Radio-Frequency Test Facility (RFTF) began operation in CY84 (Fig. 2). RF wave launcher testing for both PLT and TFTR operations were undertaken in 1985 and continued throughout 1987. The conclusion of the RFTF Safety Assessment Document was that the device would have no effect on the environment [Na84]. This proved to be the case in operations to date.

After 12 years of operation the PLT was shut down in December 1986, and for the immediate future remains mothballed. The PLT had no effect on the environment and has no decommissioning activities which would affect the environment.

The PBX (Fig. 3), after achieving a $>5\%$ beta (ratio of plasma pressure/magnetic pressure) in CY84 experiments, was shut down at the end of 1985 to undergo modifications to permit further examination of theoretical predictions on plasma shaping. The addition of new coils within the vessel, new power supplies, and a new control system began in 1986. The modified device (PBX-M) came back into operation in October 1987. A Safety Assessment Document (SAD) was published for the PBX in 1984 [F184] which indicated that the PBX did not pose any potential environmental concerns. A new SAD published for the PBX-M reaches the same conclusion [St88d].

The TFTR (Fig. 4), which had its first full year of operation in CY83, had an increase in total neutron production in CY87 to 3×10^{18} [He88]. The higher neutron production increased the activation level of the machine to the point where health physics surveys were required in the test cell following a machine run and before any personnel entry was permitted for inspection, routine maintenance, or installation work. In addition, tritium from D-D reactions absorbed in graphite measured during opening of the vessel in 1987 posed the first known health physics contamination challenges for any tokamak operations. The TFTR is a toroidal device in which a deuterium-tritium (D-T) plasma will be magnetically confined and heated to extremely high temperatures by neutral beam injectors. D-T operations are presently scheduled for 1990. Ion Cyclotron Radio-Frequency (ICRF) heating is expected to be operational in 1988. A major achievement in 1986 was an increase in neutron production and fusion power by operating in what is now called the "supershot" pulse mode. Using this technique a new record temperature of >300 million degrees Celsius was achieved. The potential hazards of this program are addressed in Safety Analysis Reports for the Project [PSAR78 and FSAR82]. The FSAR is being updated to reflect operational requirements and parameters using tritium. The initial reviews for the update will begin in CY88.

Although PPPL for security purposes operates with access controls, as an unfenced site, for environmental purposes it is considered to be open to the public. This free access has necessitated a thorough evaluation of the on-site discharges as well as the potential for off-site releases of radioactive and toxic nonradioactive effluents. An extensive monitoring program tailored to these needs has been instituted and expanded over recent years. The PPPL radiological environmental monitoring program generally follows the guidance given in two DOE reports, namely A Guide for: Environmental Radiological

Surveillance at U.S. Department of Energy Installations [Co81] and Environmental Dose Assessment Methods for Normal Operations at DOE Nuclear Sites (PNL-4410) [St82]. This includes adherence to the standards given in DOE Orders, in particular, DOE Order 5480.1A, Chapter XI (DOE81), which pertains to permissible doses and concentration guides, and gives guidance on maintaining exposures "to as low as reasonably achievable" (ALARA). Additional interim criteria were forwarded by memo [Mi85] and are expected to become an official part of the Order in the near future. Specific criteria for implementing these standards on TFTR are contained in a TFTR Operational Safety Requirement (OSR/TFTR/O-2F-C) (see Table 1). This table was updated in 1986 to include the EPA airborne emission requirements and will be updated to include the 100 mrem limit for non-occupational exposures to the general public.

The emphasis of the monitoring program has been placed on exposure pathways appropriate to fusion energy projects at PPPL. These pathways include external exposure from direct penetrating radiation and eventually from airborne radionuclides, such as ^{41}Ar , ^{13}N , ^{16}N , and internal exposure from radionuclides, such as ^3H in air and water. Six major critical pathways are considered as appropriate (see Table 2). Prompt radiation was also considered and is being measured. The monitoring program, as envisioned by the TFTR Final Safety Analysis Report (FSAR82), has been updated to reflect the current environment around TFTR (see Table 3). At present, the radioactive pollutant potential to the environment by any pathway is essentially nonexistent. Small amounts of tritium produced from D-D reactions (approximately 145 mCi total in 1987 if all neutrons were D-D produced) are not measurable outside the TFTR facility. Low levels of tritium (exempt quantities, i.e., less than levels defined as radioactive materials by the Department of Transportation) are now detectable in pump oils. Also HTO was detectable in the vacuum vessel air

during the 1987 maintenance and upgrade period [St88b].

Preliminary meteorological considerations and associated methodology, which were established at the time of the installation of PPPL's first meteorological tower, were reported in Section 2 of the TFTR FSAR. Subsequently, improved methodologies were implemented and a new meteorological tower was erected and began operation in November 1983 [Mc83]. The improved measurements and methodologies are being included in the updated FSAR being prepared for tritium operations. Data have been collected for four years using the monitors on the new tower. Wind rose plots from the data for the first three years (1984-86) are shown in Figs. 5 and 6.

1.2 Description of the Site

PPPL is located at the James Forrestal Research Campus of Princeton University. As shown in Fig. 7, the location is in central New Jersey within Middlesex County. The site has undisturbed areas with virgin forest, open grass areas, an airplane runway, and a small brook (Bee Brook) running through its eastern boundary. The closest urban centers are New Brunswick, 14 miles to the northeast and Trenton, 12 miles to the southwest. Major metropolitan areas including New York City, Philadelphia, and Newark are within 50 miles of the site. As shown in Fig. 8, the municipalities of Princeton, Plainsboro, Kingston, West Windsor, and Cranbury, among others, are in the immediate vicinity of the site. Also, the main campus of Princeton University, located primarily within the borough of Princeton is approximately three miles to the west of the site. The general layout of the facilities at the Forrestal Campus is indicated in Fig. 9, where the specific location of TFTR is located at D-site. In September of 1987, under agreements contained within the new DOE-Princeton University contract, PPPL vacated facilities at A and B-sites of the Forrestal Campus, and now

occupies only C and D-sites, plus some off-site office and light laboratory space.

A demographic study was completed in CY87 as part of the requirement for the Environmental Assessment for the Compact Ignition Tokamak (CIT) [Be87a]. Other information gathered and updated from previous TFTR studies included socioeconomic information [Be87b] and an ecological survey [En87]. The demographic data were based on the 1980 census and show both estimated and projected data out to the year 2010 (Tables 4 to 16 and Figs. 10 to 19) in a zone from 1 mile out to 50 miles. The site is in the center of a highly urbanized region extending from Boston, Massachusetts to Washington, D.C. The previous population projections for the States of New Jersey, New York, and Pennsylvania had indicated a substantial population increase within 50 miles of the PPPL site. The actual change from 1970 to 1980, as indicated by the census in these two years, was not as large as had been expected. In fact, the population in New York City and Philadelphia decreased. The Princeton area continues to experience a substantial increase in new business moving into the Route 1 corridor near the site. This increase, however, has not been as great as the projections had indicated. A sectorized population data summary was prepared in 1986 for use with several standard codes used for the determination of off-site dose due to the release of airborne activated nuclides and tritium [Ko86b]. Table 16 shows data supplied by the Princeton Forrestal Center on the population within one mile of the TFTR site. The numbers indicated have been divided by 4 to obtain an equivalent exposure for habitation [Ko86b].

2.0 SUMMARY

During CY87 there were no accidents, incidents, or occurrences that had a significant impact on PPPL facilities, program operations, or the environment. Small oil spills occurred in 1987, but were promptly mitigated and cleaned up so that they had minimal impacts on the environment [St87a, St87b, St88a]. Weed control and grass fertilization were applied under the direction of the Princeton University Buildings and Grounds Department. The work was done by University personnel or certified contractors in accordance with EPA regulations. In 1988, this work will be carried out by PPPL staff and then subcontractors. Transformers and capacitors containing PCB oils are being removed from service and disposed of in accordance with prepared schedules and EPA regulations. The Laboratory has an ongoing program to monitor, inventory, and dispose of PCB and other potentially toxic materials.

Surface water analyses for both radioactive and nonradioactive pollutants have not shown anything above normally expected background values. The initial phase of a program for ground water analysis was initiated in 1985. The U.S. Geological Service (USGS) finished their drilling programs in 1986, but continue to monitor a bromine tracer test initiated in the fall of 1986. Ambient tritium levels of slightly less than 100 pCi/l (3.7 Bq/l) were measured by the USGS on D-site wells. These data are in agreement with the old on-site drinking water wells and surface water measurements by PPPL. Soil and vegetation samples were collected and analyzed as part of the continuing baseline studies.

Radiation exposure via airborne effluents into the environment is still at a concentration that is too low to be measurable under present operations. From known D-D reactions less than 145 mCi (5.4 GBq) was released in 1987. This included controlled tritium

releases to the air and less than 1.7 mCi (63 MBq) to the sanitary sewer. Prompt radiation is detectable at extremely low levels during high power pulses from TFTR. The integrated level at the Exclusion Zone Boundary (EZB) around TFTR, from TFTR operations, was less than 1 mrem (0.01 mSv) for CY87 for measured prompted radiation plus postulated tritium releases and air activation [Gi88].

Off-site surface water, soils, and biota continued to be analyzed for radioactive baselines in CY87. In addition, the placement of air, particulate, and passive tritium air monitors was completed at the EZB. The passive tritium monitors were tested on-site in 1986 and tested in a field modeling experiment in Canada in 1987 [Gr88a].

3.0 MONITORING, ENVIRONMENTAL PROGRAM INFORMATION, DATA COLLECTION, ANALYSES, AND EVALUATION

The monitoring program implementation has followed a phased approach commensurate with the potential hazards and the needs of an expanding program. Nonradioactive water pollutant monitoring has been conducted for many years. A more extensive program, which began in 1979, presently includes eight surface water sampling points (four on-site and four off-site), four ground water sites (two former drinking water wells and two new wells near the TFTR liquid effluent collection tanks), and the potable water supply source. Monitoring for sources of potential radiological exposures is quite extensive. Real-time prompt gamma/neutron environmental monitoring began on the TFTR site in 1981 to establish baselines prior to machine operation. Four monitoring stations are located at the TFTR EZB. Neutron monitors were added at these locations at the end of CY84. Passive tritium monitors were added in CY87. Radiological water samples are being collected at the same

locations as the nonradioactive sample points (see Figs. 20 and 21). Soil and biota samples are also being analyzed for tritium baselines.

3.1 Radioactivity

3.1.1 Penetrating Radiation

Operation of the Princeton Beta Experiment Modification (PBX-M) results in the production of some penetrating radiation (primarily bremsstrahlung X rays and neutrons). Because the PBX-M has no roof shield, skyshine radiation (primarily neutron) is seen at the TFTR EZB site monitoring stations. The shielding installed for the PBX-M machine has kept the total exposure dose equivalents in occupied areas below occupational exposure guidelines. Skyshine radiation from the neutron production by PBX-M, tempered by limited operation of the device in CY87, added less than 1 mrem (0.01 mSv) to the D-site environs [Gi88].

It is stated Laboratory policy that when occupational exposures have the potential to exceed 1000 mrem/yr (10 mSv/yr), the appropriate project manager must petition the PPPL Executive Safety Board (ESB) for an exemption. In addition, the Laboratory applies the DOE ALARA policy to all its operations. This philosophy for control of occupational exposure means that environmental radiation levels, as a result of experimental device operation, are also very low, and acceptable. To illustrate this point, a 1000 mrem exposure dose from direct radiation at the outer TFTR test cell wall will result in less than 10 mrem at the EZB.

The design objective for TFTR is to stay below 10 mrem/yr (0.1 mSv/yr) above natural background from all sources of radiation at the EZB. The TFTR, like other tokamaks, produces bremsstrahlung radiation from the electrons striking internal

hardware at the end of a pulse. These X rays, in the range of 0 to 20 MeV, also produce photoneutrons. Injection of deuterium neutral beams began at the end of CY84. With these D-D runs the neutron fluxes have increased each year as the neutral beam heating power has increased. In CY85 the neutron production was on the order of 5×10^{16} for the entire year. This number increased to 2.4×10^{18} in CY86 and to 3×10^{18} during a short run year in CY87. Additional shielding was added to the TFTR test cell walls in the middle of CY85. This added shielding prevented the addition of any significant penetrating radiation to the environs due to TFTR operations in 1987. Radiation levels (μR) were recorded for some pulses outside the test cell, with the total exposure dose equivalent at the TFTR EZB being less than 1 mrem (0.01 mSv) for CY87 [Gi88].

The TFTR real-time site boundary monitors are Reuter-Stokes Senti 1011 pressurized ionization chambers and He-3-moderated neutron detectors. The electronics in the ionization chambers were modified to allow the integration of any prompt radiation resulting from a TFTR machine pulse which may be above natural background. These data are stored and processed using the Central Instrumentation Control and Data Acquisition (CICADA) computer system. Four of these monitoring stations are placed at the EZB (see Fig. 20). An additional eight ionization chambers of lower sensitivity paired with neutron monitors are located nearer the TFTR device (four outside the test cell wall, three in the basement, and one on the roof). These eight detector locations are for personnel safety and are not considered environmental detectors per se. However, data collected from them are used to help correlate the environmental measurements. Besides the moderated He-3 and fission neutron detectors, Bonner-type-moderated Li(I) detectors were also used for monitoring neutron doses at various locations throughout the TFTR facility.

3.1.2 Special Surveys

In August 1980, EG&G Idaho, Inc., under DOE contract, conducted an aerial radiological survey of PPPL and surrounding areas [St81]. The detection system consisted of 20 sodium iodide detectors, a multichannel analyzer, and a magnetic tape recording system. The nominal gamma-ray exposure rate range observed was 8 to 10 $\mu\text{R/h}$. Detected radioisotopes were consistent with normal background emitters. Since conditions have not changed at C or D-sites since 1980, there is no need at this time to repeat the survey.

Other special surveys included a ground water study by the U.S. Geological Survey (USGS) which began in 1985 and was completed in 1987 [Le87]. Figure 22 shows the potentiometric surface of the bedrock aquifer from this report. The report also indicated that the sumps under the TFTR complex create a cone of depression (Fig. 23). The USGS also presented PPPL some data developed in an unrelated study on natural occurring radioactivity in the ground. Uranium-enriched rocks can be a source of radioactivity in ground water [Sz87, Za87].

In relation to potential ground water contaminants at A and B-sites, analyses for volatile organics were performed on water from all the wells at Forrestal. These data are indicated in Table 17. No contamination has been related to any PPPL DOE-funded activities. The NJDEP has been notified of the results and further studies are being carried out by the University and surrounding companies to try to determine the source and implication of any contaminants now present in ground water within this area.

3.1.3 Airborne Radioactivity

Radioactivation of air and release of tritium in measurable concentrations are not expected until TFTR D-T operations. A silica gel environmental tritium monitor [Gr88b] was tested in 1986, and was placed in operation during the summer of 1987. Based on D-D neutron production during CY87, it is estimated that a maximum of approximately 145 mCi (5.4 GBq) of tritium could have been added to the environs outside the TFTR facility. This is essentially nonmeasurable because it is not produced and released all at once. However, our actual experience with the absorption and adsorption of tritium in TFTR vessel graphite tiles in 1987 indicates that most of the tritium produced over the last two years by D-D reactions has been retained in the tiles [St88d].

In November 1983, a three-level, 60 meter tower was installed for gathering meteorological data. Four years worth of data have now been collected. The wind rose data for the first three years of tower operation are shown in Figs. 5 and 6. Analysis indicates that the site is dominated by neutral to moderately stable conditions, with moderately unstable to extremely unstable conditions occurring less than a few percent of the time. Average surface winds are about 2.1 m/s and rise to about 4.1 m/s at 60 m (Ko86a). Based on data from this tower, X/Q values will be recalculated for the updated TFTR FSAR before tritium operation. The data were also checked for consistency by the Idaho National Engineering Laboratory (INEL) in their preparation of an Environmental Assessment (EA) for the CIT project.

3.1.4 Waterborne Radioactivity

3.1.4.1 Surface Water

Surface water samples at eight locations (four on-site and four off-site) have been analyzed for tritium and photon emitters. Five of these locations have been monitored since CY82. Downstream sampling occurs after mixing of effluent and ambient water is complete. Locations are indicated on Figs. 20 and 21.

Sample analysis has shown no unusual background radionuclides. Tritium analysis by liquid scintillation methods has shown tritium values to be less than 100 pCi/l (3.7 Bq/l) on all samples analyzed to date. Tritium enrichment procedures are used on some samples to detect lower levels. Rain water samples collected and analyzed ranged from 26 to 144 pCi/l, which was similar to the 1985 range of 45 to 160 pCi/l and the 1986 range of 40 to 140 pCi/l.

3.1.4.2 Ground Water

Two existing on-site wells (W4 and W5 on C-site) were sampled (see Fig. 20). As a part of continuing efforts to characterize the site, a more comprehensive ground water program was initiated in June 1985 through the U.S. Geological Survey. This program entailed the drilling of several monitoring wells on the TFTR site in order to help profile the ground water system. The final survey report was issued in 1987 [Le87]. This report indicates a cone of depression created by the TFTR sump system (Fig. 23). The samples collected from two of the wells (W1 and W10 at D-site) were analyzed for tritium by PPPL and the University of Miami under a USGS sampling program. The split sample results were consistent and indicated tritium levels of slightly less than

100 pCi/l (3.7 Bq/l) (see Table 34). These values are consistent with the results from wells W4 and W5 noted above, as well as the surface water measurements.

3.1.4.3 Drinking Water

Potable water is supplied by the public utility, Elizabethtown Water Co. In April 1984 a sample point at the input to PPPL was established (E1 location, Fig. 20) to provide baseline data for water coming onto the site. Radiological analysis has included gamma spectroscopy and tritium level determination. Tritium levels are similar to surface and well waters with measurements indicating less than 100 pCi/l (3.7 Bq/l) and also there are no unusual gamma-emitting radioisotopes. Radium and radon levels have not been measured.

3.1.5 Foodstuffs

Because there are so few dairy farms in this area, milk is not a viable analysis medium around the site. Also the fish population is very scarce to nonexistent in Ditch 5 and Bee Brook, which carry the runoff from the site. DOE agreed in 1986 that a substitute of vegetables and other biota from the surrounding area can be used for reference data. Sampling in 1987 indicated tritium levels below 100 pCi/l (3.7 Bq/l) [Gi88]. These levels are indicative of tritium in the environment.

3.1.6 Soil, Grass, Vegetation

Off-site sample locations were established in late 1985 (see Fig. 24). Soil and grass samples collected on-site and off-site in 1987 indicated tritium levels below 100 pCi/l (3.7 Bq/l). Laboratory techniques for doing these analyses were perfected in CY84 [Gr85] and the techniques are documented in the Radiological Environmental Monitoring Laboratory Handbook [REML86]. These baselines are being established since surface soils and

vegetation are among the best indicators of the presence of tritium after a release [Jo74], [Mu77], [Mu82]. The present detected levels are indicative of tritium in the environment.

3.2 Nonradioactive Pollutants

3.2.1 Airborne Effluents [Ki88a]

PPPL has a New Jersey Department of Environmental Protection (NJDEP) Permit for its C-site boilers and fuel tank vents. The seven permit certificates numbered 061294 through 061300, were renewed in 1987 and will next expire on March 31, 1992.

Measurements of actual emissions are not required. Emissions were initially calculated using formulas supplied by the NJDEP. These formulas are based solely on the percent sulfur and the number of gallons of oil burned per hour in each boiler. In the last quarter of CY87 PPPL purchased a combustion efficiency analyzer. This device indicates boiler efficiency, oxygen content, flue gas temperature, and carbon dioxide content of the stack gas for both oil and natural gas fuels. This information is recorded and entered into a log book on a monthly basis [Ki88b].

3.2.2 Water Utilization [Ki88a]

3.2.2.1 Drinking Water

Potable water is supplied by the public utility, Elizabethtown Water Co. PPPL used approximately 15 million gallons in CY87. This is a significant reduction from previous years because of the changeover to Delaware & Raritan (D&R) Canal water for cooling water systems. Water quality analysis at the input to PPPL was initiated in CY84 nonradioactive pollutants (Table 23, E-1 location) in addition to potential radioactive pollutants exclusive of radium or radon.

3.2.2.2 Process (nonpotable) Water

Nonpotable water is pumped by PPPL from the D&R Canal as authorized by a permit agreement with the New Jersey Water Supply Authority. The present agreement gives PPPL the right to draw up to one million gallons of water per day for process and fire fighting purposes for the period beginning July 1984 and ending on September 30, 1991. Renewal is expected at the end of the present contract. Treatment consists of filtration to remove suspended solids. In 1986 a multimedia sand filter was installed to allow the source of the D-site cooling tower make-up water to be changed from potable water to process water supply. PPPL used approximately 81 million gallons of canal water during CY87. The sampling point (C-1) was established to provide baseline data for process water coming on-site. Table 20 indicates results of water quality analysis at the canal.

3.2.2.3 Storm Sewage

Storm sewage that includes cooling tower and boiler blowdown is discharged into surface waters and is governed at C- and D-sites by National Pollutant Discharge Elimination System (NPDES) Permit No. NJ0023922 (effective date November 1, 1984 - expiration date October 31, 1989). All process water and most runoff water from C- and D-sites now pass through a detention basin. Upgrades to the detention basin, including an oil spill detection and alarm system, were completed in 1986. An oil spill in 1987 [St 87c] resulted in a reevaluation of the detention basin features. Quarterly water chemistry reports compiled from the data of Table 22 were submitted to the State of New Jersey in 1987 in accordance with NJDEP requirements. PPPL was well within the allowable limits for all testing parameters during CY87.

Cooling water treatment was changed from a chromate-based corrosion inhibitor to a nonchromate inhibitor in June 1983. Water analyses downstream and ground water tests (see Tables 18-30) have not indicated concentrations of any environmental pollutants above applicable codes, regulations, or standards. As a result of the initial improvements made to the detention basin in 1986, the NJDEP is now requiring an application for discharge to ground water. This permit was applied for in 1986 and is still awaiting NJDEP processing. An updated Spill Prevention Control and Countermeasures (SPCC) Plan was received in January 1985 and will be upgraded in CY88. All major action items of the plan have been addressed. The SPCC response team meets quarterly for training sessions to improve their response efficiency in case a spill were to be detected. In addition, the Environmental Protection Committee (EPC) wrote a Health and Safety Directive [HSD 5012] which made the EPC a subcommittee of the Executive Safety Board (ESB).

3.2.2.4 Sanitary Sewage

Sanitary sewage is discharged to the publicly owned treatment works operated by South Brunswick Township at the Stony Brook Regional Authority. Flow rates are measured by the PPPL sanitary sewage metering station and indicated a total volume discharge of approximately 11.4 million gallons in CY87. Sampling of PPPL discharges, performed by the publicly owned treatment works, has determined that pretreatment is unnecessary. Therefore, PPPL is in compliance with the EPA Pretreatment Standard, 40 CFR Part 403.

3.2.3 Spills

Several minor oil spills were recorded in CY87. Those which posed a potential threat to the environment were reported to the NJDEP in accordance with their reporting requirements. An

employee dumped approximately 25 gallons of motor oil into a dumpster. The oily waste was retrieved and disposed of through an EPA certified vendor [St87a]. An unknown individual dumped motor oil into a storm sewer. The oil was retrieved in the detention basin [St87b]. A barrel sitting in storage on A-site leaked oil onto the ground in the storage area. Soil was removed until sampling indicated less than the NJ guideline of 100 mg/kg petroleum hydrocarbon [St88a]. All oil spills were cleaned up promptly resulting in little or no impact to the environment.

3.2.4 Herbicides, Fertilizer, and Pesticides [CI88]

During CY87 the use of herbicides, pesticides, and fertilizers was not controlled by PPPL but by Princeton University buildings and grounds maintenance personnel. These materials are applied in accordance with State and Federal regulations. Herbicides are applied by a certified applicator. Table 31 lists the quantities applied during CY87. This work will be performed by PPPL using subcontractors in CY88.

3.2.5 Polychlorinated Biphenyls (PCBs)

Beginning in CY82 PPPL started a program to dispose of PCB containing capacitors, transformers, and other similarly contaminated items. During the early phases of the program all stored items in a GSA Warehouse in Belle Mead, NJ were discarded through approved disposal contractors. Remaining PCB items were labeled, as required by EPA regulations, and an inventory, inspection, and status report program was initiated. A Hazardous Material Coordinator was appointed to ensure that any newly identified leaking capacitors or transformers would be dispositioned promptly and properly. At the beginning of CY84 PPPL still had 15 PCB transformers and 6005 large capacitors containing PCBs. In CY84 375 large and 54 small PCB capacitors were disposed of as well as the oil and containers of

two transformers (Ho85). In 1985, an additional 1330 large capacitors and 22 small capacitors were properly removed from the site. In 1986 a few small capacitors but no transformers were discarded. In 1987 two transformers containing 700 gallons of PCB fluid were disposed of. In addition, 1145 gallons of < 500 ppm PCB fluid were generated from rework/classification of six PCB transformers to non-PCB transformers, and 391 capacitors were disposed of. PCB capacitors are being disposed of as they are taken out of service. Transformer replacement has been initiated and is scheduled to meet the EPA requirements. Depending on funding approval, the present plan would have all PCB transformers removed by October 1989.

3.2.6 Hazardous Wastes

Responsibility for this program rests with the PPPL Hazardous Material Coordinator under the Materiel Control Office. A facility was set up in CY82 for temporary storage of hazardous materials. A new area was built in 1986. This facility has concrete floors with containment walls, fire alarms and security surveillance, fire extinguishers, an eye wash station, an emergency shower, and telephones. Improvements to the facility, following experience gained from operational needs, will be made in CY88.

The Hazardous Waste Generator Annual Report (EPA ID number NJ1960011152) has been submitted for 1987 in accordance with EPA requirements [St88c]. During 1987, 111,034 pounds of solid materials and 9,751 gallons of liquid waste were disposed of at EPA-certified treatment, storage, and disposal facilities. These totals included 50,470 pounds (including packaging material) and 1845 gallons of PCBs (oil plus containers). These numbers reflect actual waste, plus containers and packing materials.

3.3 Environmental Impact

3.3.1 Assessment of Radiation Dose to the Public

PPPL is located in one of the less densely populated, but also one of the fastest growth areas in the metropolitan region between New York City and Philadelphia. Census data indicate that approximately 16 million people live within 80 km (50 miles) of the site and approximately 212,000 within 16 km (10 miles) of PPPL. The detailed distribution of population as a function of distance is given in Tables 4-16. Because of ever-increasing commercial growth in this area, a demographic update was planned for TFTR but was completed as a requirement for the CIT Environmental Assessment [Be87a].

The overall integrated exposure dose equivalent from all sources (excluding natural background) to a hypothetical individual residing at the PPPL site boundary 24 h/day, 365 d/y was estimated to be less than 1 mrem (0.01 mSv) for CY87 (Gi88). Detailed person-rem calculations for the surrounding population were not performed, because the value would be insignificant in comparison to the approximately 100 mrem (1 mSv) each individual receives from the natural background, exclusive of radon, in New Jersey.

3.3.2 Assessment of Nonradioactive Pollutants

There were no activities during CY87 that created problems with respect to nonradioactive pollutants. Oil spills were detected and cleaned up with no significant environmental impact.

Polychlorinated biphenyls (PCB's) and other toxic materials continue to be disposed of in accordance with EPA requirements. Herbicides, pesticides, and fertilizers were used in very limited quantities and are not expected to have any noticeable negative impact on the environment.

4.0 QUALITY ASSURANCE FOR LABORATORY ANALYSIS

Analysis of water samples for radioactivity was accomplished in-house. In general, in-house procedures follow the HASL-300 Manual [Vo82]. In-house procedures adopt accepted techniques and are documented in the REML manual [REML86]. PPPL participates in the EPA (Las Vegas) program and has reinitiated its analyses of samples provided by the DOE Environmental Measurement Laboratory (EML) in New York City. These programs provide blind samples for analysis and subsequent comparison to values obtained by other participants, as well as to known values. Tritium results are shown in Table 32.

In CY84 PPPL initiated a program to have its radiation counting laboratory certified by the State of New Jersey through the EPA QA program. In March 1986 the Laboratory facilities and procedures were reviewed and inspected by EPA/Las Vegas and the NJDEP. The laboratory was certified for tritium analysis in urine and water and recertified in these areas in 1987. The goal in the coming year is to extend this certification to gamma spectroscopy and all other procedures and techniques.

The vendor used for nonradioactive water quality analysis participates in a State of New Jersey QA program and has a quality assurance plan [Al85]. Blind split samples were also submitted for analysis in 1987 (Table 33).

5.0 FUTURE PROGRAM EXPANSION

5.1 Meteorological

A meteorological tower was installed in November 1983. Data from this system are being used in updating dose calculations for the updated version of the TFTR FSAR. Data were also evaluated by the CIT project in relation to siting the CIT at PPPL. Several dose assessment codes are being employed by PPPL to utilize the data from this tower in the calculation of projected doses. These codes include the required DOE standard AIRDOS-EPA, as well as PANVAN, XOQDOQ, and an Ontario Hydro version of TRITMOD. Future plans include considerations of hooking up a real-time output of the meteorological data.

5.2 Water Quality

The initial phases of a ground water monitoring program began in CY85. Analysis of water samples from two D-site wells was added to the monitoring program in CY86 utilizing USGS data. PPPL took over the water quality program on these two wells in December 1987. Evaluations for the CIT Project will determine whether or not this program must be expanded.

5.3 Radioactive Effluents

5.3.1.1 Air, Gaseous and Particulates

Based on collected data, a decision was made in CY84 to limit the specific air and particulate real-time monitors at the EZB to a beta detector only. Environmental tritium monitors tested in CY86 were deployed at the EZB in CY87. In CY88 these will be extended to off-site locations.

5.3.2.2 Off-Site Radiological Monitoring

An off-site grab sample water analysis program is well established. Whether more sampling points will be added in the future depends on reevaluation of the program, which is done annually. Locations for off-site tritium and particulate monitoring stations were negotiated in CY86. Placement of hardware at these sites is expected to be finished in CY88. Soil and vegetation sampling is underway and will continue.

5.4 Nonradioactive Effluents

Air effluent standards will continue to be met by following the guidelines of the NJDEP. Any potential toxic materials will be monitored and disposed of in accordance with applicable regulations and accepted guidelines. With respect to the detention basin, application has been made for a ground water discharge permit. Also, because of the addition of an oil separator on the detention basin, the NJDEP had requested that we apply for a treatment works permit. A permit application was made and a subsequent waiver was granted for the treatment works permit [Ku86]. Upgrades to the detention basin are under consideration by an outside vendor.

6.0 REGULATIONS AND SAFETY CRITERIA

The appropriate Radiation Protection Standard for penetrating radiation was taken from DOE Order 5480.1A, Chapter XI. Specific criteria for implementing these standards on TFTR are contained in TFTR Operational Safety Requirements, in particular OSR/TFTR/0-2F-C. The Concentration Guides used in the analyses of surface water samples for radioactivity were taken from DOE Order 5480.1A, Chapter XI, Table II, Column 2 (Water in Uncontrolled Areas). The concentration guides for airborne

activity are taken from the same DOE Order, Table I, Column 1 (Concentration in Air in Uncontrolled Areas). Tritium, for example, is listed as 2×10^{-7} uCi/ml. The Laboratory was also in compliance with the new DOE draft Order 5480.11, of which some interim requirements on dose to the public were established by a DOE letter [Mi85].

Air and Water Pollution Standards for nonradioactive pollutants were taken from the New Jersey Administrative Code (NJAC), Department of Environmental Protection 7:1-1, et seq and 7:27-1, et seq. The appropriate regulations for hazardous waste are found in the U.S. Code of Federal Regulations, 40 CFR 761 and 40 CFR 260-265, respectively.

7.0 ACKNOWLEDGEMENTS

E. Mitman, III, D. Hwang, and J. Gilbert compiled the data for radiation analysis. O. Griesbach performed in-house radiation analyses, and J. Fennimore, K. Chase, and R. Jensen worked on instrument installation and calibration. These individuals are staff members of the PPPL Project and Operational Safety Office, Health Physics Branch. D. Abramowitz, the PPPL Industrial Hygienist, reviewed nonradioactive pollutant analysis data. C. Kircher is responsible for all water utilization information and the forwarding of relevant data to DOE for environmental protection permits. S. Larson is responsible for toxic waste disposal. Various other PPPL individuals have reviewed the manuscript.

This work is supported by the U.S. Department of Energy Contract No. DE-AC02-76CHO3073.

8.0 REFERENCES

- Al85 Alinea, E.A., 1985, Princeton Testing Laboratory Quality Control Manual, Princeton Testing Laboratory, Princeton, NJ.
- Be87a Bentz, L. K., and Bender, D.S., 1987, "Population Projections, 0-50 Mile Radius from the CIT Facility: Supplementary Documentation for an Environmental Assessment for the CIT at PPPL," EGG-EP-7751, INEL, Idaho Falls, Idaho.
- Be87b Bentz, L.K., and Bender, D.S., 1987, "Socioeconomic Information, Plainsboro Area, New Jersey: Supplementary Documentation for an Environmental Assessment for the CIT at PPPL," EGG-EP-7752, INEL, Idaho Falls, Idaho.
- Cl88 Clark, G. J., 2/1/88, "Chemical Use," Princeton University Internal memo.
- Co81 Corley, J.P., et al., 1982, A Guide for: Environmental Radiological Surveillance at U.S. Department of Energy Installations DOE/EP-023, (National Technical Information Service).
- DOE81 DOE Order 5480.1, Ch. XI, 8/13/81, Environmental Protection, Safety and Health Protection Program for DOE Operations, U.S. Department of Energy, Operational and Environmental Safety Division.
- El84 Ellis, R., Jr., and Stencel, J.R., February 1984, Safety Assessment for the S-1 Spheromak, Princeton Plasma Physics Laboratory Report PPPL-2083.
- En87 Envirosphere Company, 1987, "Ecological Survey of Compact Ignition Tokamak Site and Surroundings at Princeton University's Forrestal Campus," Envirosphere Company, Division of Ebasco, Report to INEL for the CIT.
- Fl84 Fleming, R.B., et al., February 1984, Safety Assessment Document for the Princeton Beta Experiment, Princeton Plasma Physics Laboratory (unpublished).

FSAR82 Final Safety Analysis Report, Tokamak Fusion Test Reactor Facilities, Princeton Plasmas Physics Laboratory, 1982.

Gi88 Gilbert, J., May 1988, "PPPL Ionizing Radiation Report for Calendar Year 1987," JG-88, Princeton Plasma Physics Laboratory Internal Report.

Gr85 Griesbach, O., and Stencel, J.R., January 1985, "An Environmental Monitoring Program for a Fusion Test Reactor," Proceedings of the 18th Midyear Topical Symposium of the Health Physics Society, Colorado Springs, CO, 227-233.

Gr88a Griesbach, O., and Stencel, J.R., "Operational Experience with the DATS Sampler During the Canadian Tritium Modeling Experiment," presented at the 3rd Topical Meeting on Tritium Technology in Fission, Fusion, and Isotopic Applications, Toronto, Canada, May 1988, to appear in *Fusion Technol.*, 1988.

Gr88b Griesbach, O., and Stencel, J.R., "The PPPL Differential Atmospheric Tritium System (DATS)," submitted to the 22nd Midyear Topical Meeting of the Health Physics Society, San Antonio, TX, Dec. 1988.

He88 Hendel, H., 1988, personal communication.

HSD5012 Environmental Protection, PPPL Health and Safety Directive (HSD) 5012, 1988, internal PPPL document.

Jo74 Jordan, C.F., Stewart, M., and Kline, J., 1974, "Tritium Movement in Soils: The Importance of Exchange and High Initial Dispersion," Health Physics, 27, 37-43.

Ki88a Kircher, C., 3/3/88, "Annual Environmental Report for CY87," Princeton Plasma Physics Laboratory, Internal Memo.

Ki88b Kircher, C., 3/14/88, "Calculations for Boiler Emissions," Princeton Plasma Physics Laboratory, Internal Memo.

Ko86a Kolibal, J., et al., 1986, Meteorological Data Summaries for the TFTR from January 1984 to December 1985, Princeton Plasma Physics Laboratory Report No. PPPL-2369.

Ko86b Kolibal, J., 3/24/86, "Sectorized Agricultural and Population Data Estimates," EAD-1442, Plasma Physics Laboratory Internal Memo.

Ku86 Kurisko, P.C., 12/5/86, "Treatment Works Approval Waiver NJPDES No. NJ0023922," NJDEP letter to H. Mix, DOE/PAO.

Le87 Lewis, J.C. and Spitz, F.J., 1987, "Hydrogeology, Ground-Water Quality, and The Possible Effects of a Hypothetical Radioactive-Water Spill, Plainsboro Township, New Jersey," U.S. Geological Survey Water-Resources Investigations Report 87-4092, West Trenton, NJ.

Mc83 McCarthy, E.F., and Errera, L.J., 8/15/83, Final Monitoring Plan: Tokamak Fusion Test Reactor Meteorological Monitoring Program, TRC Consultants, Inc., 800 Connecticut Blvd., East Hartford, CT. 06108.

Mi85 Mix, H. C., Nov. 85, "Radiation Standard for Protection of the Public in the Vicinity of the Department of Energy (DoE) Facilities," DOE/PAO letter to PPPL.

Mu77 Murphy, C.E., Jr., Watts, J.R., and Corey, J.C., 1977, "Environmental Tritium Transport from Atmospheric Release of Molecular Tritium," Health Physics, 33, 325-331.

Mu82 Murphy, C.E., Jr., Sweet, C.W., and Fallon, R.D., 1982, "Tritium Transport Around Nuclear Facilities," Nuclear Safety, 23, 667-685.

Na84 Nagy, A., and Beane, F., August 1984, Safety Assessment for the RF Test Facility, Princeton Plasma Physics Laboratory Report No. PPPL-2129.

PSAR78 Preliminary Safety Analysis Report, Princeton Plasma Physics Laboratory Tokamak Fusion Test Reactor, 1978.

REML86 Radiological Environmental Monitoring Laboratory Manual, Princeton Plasma Physics Laboratory, 1986.

St81 Steiner, P.A., 1981, An Aerial Radiological Survey of the Princeton Plasma Physics Laboratory and Surrounding Area, U.S. DOE Remote Sensing Laboratory Report, EGG-1182-1806, UC-41.

- St82 Strenge, D.L., Kennedy, W.E., Jr, and Corley, J.P., 1982, Environmental Dose Assessment Methods for Normal Operations of DOE Nuclear Sites, PNL-4410/UC-11.
- St87a Stencel, J.R., 1987, "Environmental Protection Spill Cleanup Report EP87-02, Employee Dumping of Oil in A-Site Dumpster, 8/15/87," DEP ID# 87-08-17-0916, Internal PPPL Environmental Committee Report.
- St87b Stencel, J.R., 1987, "Environmental Protection Spill Cleanup Report EP87-05, Retention Basin, 10/29/87," DEP ID# 87-10-29-1624, Internal PPPL Environmental Committee Report.
- St88a Stencel, J.R., 1988, "Environmental Protection Spill Cleanup Report EP87-06, A-Site Boneyard, May 1987," DEP ID# 87-09-16-1539., Internal PPPL Environmental Committee Report.
- St88b Stencel, J.R., Gilbert, J.D., Griesbach, J.M., and Greco, J.M., "TFTR Health Physics Tritium Measurements Following D-D Operations," to be presented at the Third Topical Meeting on Tritium Technology in Fission, Fusion and Isotopic Application, Toronto, Canada, May 1988 and published in Fusion Technology in 1988.
- St88c Stencel, J.R., 1988, "Annual Hazardous Waste Generator Report for CY87," JRS-1058, PPPL memo to DOE/PAO.
- St88d Stencel, J.R. and Parsells, R.F., Editors, April 1988, Safety Assessment Document (SAD) for the Princeton Beta Experiment Modification (PBX-M), Princeton Plasma Physics Laboratory Report PPPL-2496.
- Sz87 Szabo, Z. and Zapecza, O.S., "Relation Between Natural Radionuclide Activities and Chemical Constituents in Ground Water in the Newark Basin, New Jersey," Radon, Radium, and Other Radioactivity in Ground Water, Hydrogeologic Impact and Application to Indoor Airborne Contamination, Proceedings of the National Water Well Association Conference, April 7-9, 1987, Somerset, NJ, available from Lewis Publishers.
- Vo82 Volchok, H.L., and de Planque, G., 1982, EML Procedures Manual HASL 300, Department of Energy, Environmental Measurements Laboratory, 376 Hudson St., NY, NY 10014.

Za87 Zapecza, O.S. and Szabo, Z., "Source and Distribution of Natural Radioactivity in Ground Water in the Newark Basin, New Jersey," Radon, Radium, and Other Radioactivity in Ground Water, Hydrogeologic Impact and Application to Indoor Airborne Contamination, Proceedings of the National Water Well Association Conference, April 7-9, 1987, Somerset, NJ, available from Lewis Publishers.

30
Table 1

TFTR Radiation Exposure Criteria

The research facility radiation exposure criteria itemized in this table shall be invoked for the TFTR only and shall not be construed as being applicable to subsequent fusion test facilities, research facilities, or reactor projects. The values quoted are for whole body exposures, however, the DOE manual requirements for other organs (hands, arms, bones, etc.) and other time periods (quarterly) are also applicable to TFTR and reductions between limits and design objective shall be consistent with those of the table.

Condition	Off-Site ≥ 125 m		On-Site <125 m	
	Limit	Design Objective	Limit	Design Objective
Routine Operation mrem/yr [footnotes (a), (b) & (c)]	500 to an individual (c)	≤ 100 to an individual (b)	500 in an uncontrolled area	≤ 100 in an uncontrolled area
	170 average population member (c)	≤ 35 average population member	5000 in a controlled area	≤ 1000 in a controlled area
Accident rem [footnotes (c) and (d)]	25	≤ 5 (d)	25	25

- (a) Routine operation consist of:
- 1) Normal component operation including shutdown, repair, maintenance, checkout, adjustment, etc.
 - 2) Operational occurrences such as leaks, loss of power, and component malfunctions that are likely to occur once or more during the life of the facility.
- (b) For normal operation, defined in (a) 1) above, the off-site design objective shall be 10 mrem/yr.
- (c) Accident conditions consist of:
- 1) Very low probability events such as "most intense predicted" phenomena.
 - 2) Low probability events such as "most probable" natural phenomena and other component failure events that are not likely to occur during the life of the facility.
- (d) For those accident conditions defined by (c) 1) above, the off-site design objective shall be 5 rem and that for (c) 2) above, 1 rem.
- (e) For emission of airborne radionuclides, the off-site limit on dose equivalent is 25 mrem/yr to the whole body and 75 mrem/yr to the critical organ.

Table 2

Critical Pathways

<u>Path I.D.</u>	<u>Discharge Pathway</u>		
A1	Atmospheric	--->	Whole Body Exposure
A2	Atmospheric	--->	Inhalation Exposure
A3	Atmospheric	--->	Deposition on Soil & Vegetation, Ingestion, Whole Body Exposure
L1	Liquid	Water Way ---> Supply ----->	Drinking Water Man
L2	Liquid	Water Way --->	External Exposure
L3	Liquid	Water Way --->	Fish ---> Man

Table 3

Monitoring Program Covering Critical Pathways

Type of Sample	Critical Path I.D.	Sample Point Description	Sampling Frequency	Analysis
Surface	L1,L2,L3 & A3	1) Cooling Water Discharge Drainage 2) Bee Brook Upstream & Downstream 3) D&R Canal	Monthly	Tritium Gamma Spectroscopy
Soil & Sod	A3	Within 1 km radius	4 times per year	Tritium Gamma Spec.
Biota (Fruits & Vegetables)	A3	Within 1 km radius	Seasonal	Tritium Gamma Spec.
Surface Water	L1,L2	Liquid Effluent Collection Tanks	As Required by Filling	Tritium Gamma Spec. Volume
Air	A1-A3	Test Cell	Continuous	Activated Air (Gross β) ^3H (HT & HTO)
Air	A1-A3	Vault	Continuous	^3H (HT and HTO)
Air	A1-A3	HVAC Discharge (Stack)	Continuous	Activated Air (Gross β) HT & HTO, Particulates, Volume
Direct & Air (on-site)		4 Locations at EZB on-site	Continuous	γ , n, ^3H (HT and HTO), Gross β for Activated air & particulates with Gamma Spec., TLD
Direct & Air (off-site)		6 Locations off-site within 1 km radius	Continuous (integrated)	^3H (HT & HTO) TLD for air γ Gamma spec. for particulates

Table 4*
Population of Municipalities Within 0 - 10 Miles of PPPL

1985 - 2010

Municipality	1985 (1)	1995	2000	2005	2010	
Mercer County (Total) (2)	317,685	349,700	359,400	364,200	377,100	Mercer County (Total)
Mercer County (Part)	190,683	219,550	228,100	230,550	240,500	Mercer County (Part)
East Windsor Twp.	22,682	24,750	26,000	26,350	29,350	East Windsor Twp.
Nightstown B.	4,494	5,050	5,100	5,100	5,100	Nightstown B.
Hamilton Twp.	85,766	88,850	90,000	91,200	94,450	Hamilton Twp.
Hopewell Twp.	11,040	13,025	15,000	15,200	16,200	Hopewell Twp.
Hopewell B.	2,013	2,075	2,100	2,100	2,100	Hopewell B.
Pennington B.	2,232	2,300	2,300	2,350	2,400	Pennington B.
Lawrence Twp.	22,804	31,100	33,900	34,000	34,100	Lawrence Twp.
Princeton Twp.	14,202	14,550	14,700	14,900	15,400	Princeton Twp.
Princeton B.	12,031	12,650	12,700	12,700	12,700	Princeton B.
Washington Twp.	3,719	8,650	8,800	8,900	9,200	Washington Twp.
West Windsor Twp.	9,700	16,550	17,500	17,750	19,500	West Windsor Twp.
Middlesex County (Total) (2)	626,703	695,432	724,610	760,800	791,800	Middlesex County (Total)
Middlesex County (Part)	121,984	171,183	192,396	202,000	219,100	Middlesex County (Part)
Cranbury Twp.	2,145	5,695	8,033	8,450	8,800	Cranbury Twp.
East Brunswick Twp.	40,770	43,630	44,753	47,000	50,900	East Brunswick Twp.
Helmetta B.	973	965	949	950	950	Helmetta Twp.
Monroe Twp.	19,255	28,711	34,737	36,500	38,200	Monroe Twp.
Jamesburg B.	4,402	4,723	4,805	5,050	5,050	Jamesburg B.
North Brunswick Twp.	25,427	31,495	33,916	35,600	37,000	North Brunswick Twp.
Plainsboro Twp.	9,040	15,662	17,161	18,000	20,700	Plainsboro Twp.
South Brunswick Twp.	19,972	40,304	48,042	50,450	57,500	South Brunswick Twp.
Somerset County (Total) (2)	210,318	250,025	263,800	279,765	295,730	Somerset County (Total)
Somerset County (Part)	65,276	89,280	97,820	106,610	115,400	Somerset County (Part)
Franklin Twp.	33,952	47,945	52,790	57,790	62,790	Franklin Twp.
Hillsborough Twp.	22,652	28,485	30,900	33,375	35,850	Hillsborough Twp.
Montgomery Twp.	7,970	12,145	13,420	14,725	16,030	Montgomery Twp.
Rocky Hill B.	702	705	710	720	730	Rocky Hill B.
Monmouth County (Total) (2)	530,913	568,100	591,600	604,300	613,450	Monmouth County
Millstone Twp.	4,234	5,617	7,000	9,286	11,571	Millstone Twp.

(1) New Jersey Department of Labor. Population Estimates for New Jersey, July 1, 1985.

(2) See methodology in Appendix for details on the source and derivation of County and Municipal Projections.

* Taken from Be87a

Table 5*

Population of Counties Within 10 - 50 Miles of PPPL

1985 - 2010

County	1985 Estimates	1995 Projections	2000 Projections	2005 Projections	2010 Projections
New Jersey (1)	7,562,000	8,154,000	8,450,300	8,685,200	8,895,700
Atlantic	205,100	245,100	260,100	272,300	283,200
Bergen	841,200	861,800	878,700	891,900	904,000
Burlington	380,100	437,100	467,200	494,900	521,300
Camden	488,100	555,400	577,200	597,300	616,700
Essex	845,700	794,000	795,500	779,900	762,300
Gloucester	207,100	234,500	249,100	263,500	277,400
Hudson	555,900	560,100	548,100	528,500	507,300
Hunterdon	92,800	104,500	113,000	121,900	131,000
Mercer	317,700	349,700	359,400	364,200	377,100
Middlesex	626,700	695,432	724,610	760,800	791,800
Morrmouth	530,900	568,100	591,680	604,300	613,450
Morris	417,100	479,900	510,500	540,800	570,500
Ocean	380,000	449,600	484,400	515,800	545,900
Passaic	461,400	468,600	469,100	466,500	462,000
Somerset	210,300	250,025	263,800	279,765	295,730
Sussex	119,600	146,100	159,600	172,900	185,700
Union	506,700	534,500	539,700	540,900	540,000
Warren	85,200	92,700	96,200	99,300	101,900
New York (2)	17,783,000	18,314,022	18,548,262	18,750,076	18,948,273
Bronx	1,198,598	1,199,410	1,205,047	1,213,270	1,224,052
Kings	2,248,139	2,228,361	2,232,835	2,242,890	2,254,228
Nassau	1,332,393	1,344,197	1,333,458	1,315,938	1,292,457
New York	1,455,619	1,454,633	1,454,251	1,456,272	1,456,707
Queens	1,917,172	1,919,057	1,925,510	1,933,829	1,953,634
Richmond	371,679	419,706	443,048	465,818	489,111
Pennsylvania (3)	11,863,674	12,100,149	12,101,253	12,161,780	12,222,306
Bucks	512,705	576,716	601,168	636,276	673,345
Chester	334,311	379,733	395,958	418,726	442,802
Delaware	557,180	541,442	531,068	525,279	519,554
Lehigh	277,914	291,083	294,836	300,762	306,808
Monroe	78,967	104,133	117,583	134,162	153,079
Montgomery	663,164	692,521	698,281	712,666	727,346
Northampton	231,430	244,668	249,000	255,275	261,707
Philadelphia	1,637,434	1,599,620	1,513,674	1,472,959	1,433,333

(1) Office of Demographic and Economic Analysis, N.J. Department of Labor and Industry, 1986.

(2) State Data Center, New York State Department of Commerce, 1985.

(3) State Data Center, Pennsylvania Department of Commerce, 1986. See methodology in Appendix for details on 2005 and 2010 projections.

* Taken from Be87a

Table 6 **

Population of Metropolitan Areas Within 50 Miles of PPPL

Metropolitan Areas*	1980 Census	July 1985 Estimate	Percent Change
Allentown-Bethlehem MSA (N J Portion)	84,429	85,200	0.9%
Jersey City, N J PMSA	556,972	555,900	-0.2%
Monmouth-Ocean PMSA	849,211	910,900	7.3%
Middlesex-Somerset-Hunterdon PMSA	886,383	929,800	4.9%
New York, N Y CMSA	8,274,961	8,410,058	1.6%
Newark, N J PMSA	1,879,147	1,889,000	0.5%
Bergen-Passaic PMSA	1,292,970	1,302,600	0.7%
Philadelphia, P A PMSA (N J Portion)	1,034,109	1,075,300	4.0%
Trenton, N J PMSA	307,863	317,700	3.2%

* MSA = Metropolitan Statistical Area

CMSA = Consolidated Metropolitan Statistical Area

PMSA = Primary Metropolitan Statistical Area

** Taken from Be87a

Source: State of New Jersey, Department of Labor.
New York State Department of Commerce.

Table 7^{*}

1985 Population Estimates Within Annular Sectors, 0 - 10 Miles

Total								
SECTOR	0-1 Miles	1-2 Miles	2-3 Miles	3-4 Miles	4-5 Miles	5-10 Miles	0-10 Miles	SECTOR
N	0	100	289	0	68	4,666	5,123	N
NNE	0	20	290	2,497	4,334	9,600	16,741	NNE
NE	0	0	0	0	0	16,799	16,799	NE
ENE	0	1,160	204	200	100	3,792	5,456	ENE
E	0	0	200	100	10	10,238	10,548	E
ESE	0	100	1,600	1,200	219	3,469	6,588	ESE
SE	113	1,200	0	253	161	18,964	20,691	SE
SSE	362	50	150	0	600	8,255	9,417	SSE
S	0	734	3,837	2,312	1,760	4,156	12,799	S
SSW	3	0	2,500	600	100	27,788	30,991	SSW
SW	0	805	10	250	50	18,525	19,640	SW
WSW	0	739	1,000	1,019	1,449	8,095	12,302	WSW
W	0	1,735	5,820	6,777	2,386	6,253	22,971	W
WNW	40	437	772	3,139	0	2,313	6,401	WNW
NW	0	1,020	866	300	350	3,526	6,062	NW
NNW	0	600	499	200	502	7,093	8,894	NNW
Totals	518	8,700	18,037	18,847	12,089	153,232	211,423	Totals

*Taken from Be87a

Table 8*

1995 Population Projections Within Annular Sectors, 0 - 10 Miles

SECTOR	Total							SECTOR
	0-1 Miles	1-2 Miles	2-3 Miles	3-4 Miles	4-5 Miles	5-10 Miles	0-10 Miles	
N	0	134	387	0	91	6,241	6,853	N
NNE	0	27	388	3,340	5,242	12,841	21,838	NNE
NE	0	0	0	486	902	21,084	22,472	NE
ENE	0	1,551	273	268	689	5,072	7,853	ENE
E	0	0	268	134	1,678	13,695	15,775	E
ESE	0	827	2,140	1,605	2,235	5,195	12,002	ESE
SE	151	1,605	291	338	493	20,928	23,806	SE
SSE	484	1,454	894	166	803	11,042	14,843	SSE
S	0	982	4,675	3,093	2,354	5,559	16,663	S
SSW	4	188	3,344	2,522	2,908	32,176	41,142	SSW
SW	0	1,077	332	544	2,796	21,450	26,199	SW
WSW	0	989	2,828	1,130	1,594	10,828	17,369	WSW
W	0	2,321	6,005	6,963	2,487	9,277	27,053	W
WNW	53	585	800	3,256	128	4,438	9,260	WNW
NW	0	1,365	898	335	468	4,716	7,782	NW
NNW	0	803	668	268	671	9,487	11,897	NNW
Totals	692	13,908	24,191	24,448	25,539	194,029	282,807	Totals

*Taken from Be87a

Table 9^{*}

2000 Population Projections Within Annular Sectors, 0 - 10 Miles

SECTOR	Total							SECTOR
	0-1 Miles	1-2 Miles	2-3 Miles	3-4 Miles	4-5 Miles	5-10 Miles	0-10 Miles	
N	0	146	421	0	99	6,792	7,458	N
NNE	0	29	422	3,635	5,560	13,974	23,620	NNE
NE	0	0	0	656	1,217	22,582	24,455	NE
ENE	0	1,688	297	292	895	5,520	8,692	ENE
E	0	0	292	146	2,261	14,904	17,603	E
ESE	0	1,081	2,329	1,747	2,940	5,799	13,896	ESE
SE	164	1,747	393	368	609	21,615	24,896	SE
SSE	527	1,945	1,154	224	874	12,016	16,740	SSE
S	0	1,069	4,968	3,366	2,562	6,050	18,015	S
SSW	4	254	3,639	3,869	3,890	33,710	45,366	SSW
SW	0	1,172	252	449	4,566	22,473	28,932	SW
WSW	0	1,076	2,354	1,169	1,645	11,784	18,028	WSW
W	0	2,526	6,070	7,028	2,522	10,334	28,480	W
WNW	58	637	810	3,297	173	5,286	10,261	WNW
NW	0	1,485	909	347	509	5,132	8,382	NW
NNW	0	874	727	292	730	10,316	12,939	NNW
Totals	753	15,729	25,037	26,905	31,052	208,287	307,763	Totals

* Taken from Be87a

Table 10*

2005 Population Projections Within Annular Sectors, 0 - 10 Miles

Total								
SECTOR	0-1 Miles	1-2 Miles	2-3 Miles	3-4 Miles	4-5 Miles	5-10 Miles	0-10 Miles	SECTOR
N	0	151	435	0	102	7,014	7,702	N
NNE	0	30	436	3,754	5,688	14,431	24,339	NNE
NE	0	0	0	723	1,344	23,187	25,256	NE
ENE	0	1,743	307	302	978	5,701	9,031	ENE
E	0	0	302	151	2,496	15,392	18,341	E
ESE	0	1,184	2,405	1,804	3,224	6,043	14,660	ESE
SE	169	1,804	434	380	656	21,892	25,335	SE
SSE	544	2,143	1,259	247	903	12,409	17,505	SSE
S	0	1,104	5,086	3,476	2,646	6,248	18,560	S
SSW	4	281	3,758	4,211	4,286	34,329	46,869	SSW
SW	0	1,210	277	492	5,038	22,986	30,003	SW
WSW	0	1,111	2,496	1,185	1,666	12,170	18,628	WSW
W	0	2,609	6,096	7,054	2,536	10,761	29,056	W
WNW	60	658	814	3,313	191	5,628	10,664	WNW
NW	0	1,534	913	352	526	5,300	8,625	NW
NNW	0	903	751	302	754	10,651	13,361	NNW
Totals	777	16,465	25,769	27,748	33,034	214,142	317,935	Totals

* Taken from Be87a

Table 11 *

2010 Population Projections Within Annular Sectors, 0-10 Miles

Total								
SECTOR	0-1 Miles	1-2 Miles	2-3 Miles	3-4 Miles	4-5 Miles	5-10 Miles	0-10 Miles	SECTOR
N	0	161	465	0	109	7,505	8,240	N
NNE	0	32	466	4,016	5,971	15,441	25,926	NNE
NE	0	0	0	875	1,625	24,521	27,021	NE
ENE	0	1,865	328	322	1,161	6,099	9,775	ENE
E	0	0	322	161	3,016	16,468	19,967	E
ESE	0	1,411	2,574	1,930	3,852	6,580	16,347	ESE
SE	182	1,930	525	407	759	22,503	26,306	SE
SSE	582	2,580	1,491	300	965	13,278	19,196	SSE
S	0	1,181	5,347	3,719	2,831	6,685	19,763	S
SSW	5	339	4,021	4,965	5,161	35,696	50,187	SSW
SW	0.00	1,295	333	542	6,080	23,797	32,047	SW
WSW	0	1,189	2,808	1,219	1,711	13,021	19,948	WSW
W	0	2,791	6,154	7,112	2,568	11,703	30,328	W
WNW	64	703	822	3,349	230	6,383	11,551	WNW
NW	0	1,641	923	363	563	5,671	9,161	NW
NNW	0	965	803	322	807	11,408	14,305	NNW
Totals	833	18,083	27,382	29,602	37,409	226,759	340,068	Totals

* Taken from Be87a

Table 12*

1985 Population Estimates Within Annular Sectors, 10 - 50 Miles

Total						
SECTOR	10-20 Miles	20-30 Miles	30-40 Miles	40-50 Miles	10-50 Miles	SECTOR
N	66,118	36,704	181,881	68,882	353,586	N
NNE	134,838	226,290	341,211	488,415	1,190,754	NNE
NE	178,403	431,968	1,293,973	3,522,231	5,426,575	NE
ENE	142,397	220,455	1,076,490	1,449,544	2,888,886	ENE
E	52,020	121,842	75,175	0	249,037	E
ESE	38,489	41,729	135,843	0	216,061	ESE
SE	14,219	81,760	179,854	5,852	281,685	SE
SSE	2,926	13,262	20,520	36,784	73,492	SSE
S	5,446	57,129	11,859	2,908	77,342	S
SSW	54,390	61,310	117,286	196,892	429,878	SSW
SW	230,879	361,455	1,147,177	1,032,046	2,771,556	SW
WSW	52,379	151,542	311,433	299,453	814,807	WSW
W	13,955	39,888	106,238	64,611	224,693	W
WNW	8,287	12,555	15,439	252,047	288,328	WNW
NW	13,920	18,653	66,682	86,917	186,172	NW
NNW	26,092	13,716	34,241	22,704	96,753	NNW
Totals	1,034,758	1,890,257	5,115,303	7,529,287	15,569,605	Totals

* Taken from Be87a

Table 13*

1995 Population Estimates Within Annular Sectors, 10 - 50 Miles

Total						
SECTOR	10-20 Miles	20-30 Miles	30-40 Miles	40-50 Miles	10-50 Miles	SECTOR
N	77,600	43,286	209,880	82,344	413,110	N
NNE	151,656	244,555	345,449	501,569	1,243,229	NNE
NE	189,192	466,816	1,282,528	3,531,064	5,469,602	NE
ENE	149,614	244,189	1,075,798	1,444,205	2,913,807	ENE
E	48,224	130,379	80,443	0	259,046	E
ESE	33,170	44,653	147,906	0	225,728	ESE
SE	15,551	95,456	212,796	6,924	330,726	SE
SSE	3,462	15,691	24,278	43,521	86,953	SSE
S	3,798	65,696	13,638	3,437	86,568	S
SSW	58,457	70,504	134,375	224,101	487,438	SSW
SW	254,358	385,409	1,167,023	1,035,758	2,842,548	SW
WSW	55,741	167,298	319,088	309,761	851,889	WSW
W	13,209	44,869	115,585	68,595	242,258	W
WNW	9,332	14,133	17,280	265,316	306,061	WNW
NW	15,675	21,005	72,663	91,959	201,302	NW
NNW	29,653	15,445	38,640	25,334	109,071	NNW
Totals	1,108,692	2,069,384	5,257,370	7,633,889	16,069,335	Totals

* Taken from Be87a

Table 14^{*}

2000 Population Estimates Within Annular Sectors, 10 - 50 Miles

Total						
SECTOR	10-20 Miles	20-30 Miles	30-40 Miles	40-50 Miles	10-50 Miles	SECTOR
N	81,590	45,762	223,566	89,117	440,035	N
NNE	158,049	250,338	354,421	507,150	1,269,959	NNE
NE	193,977	478,786	1,286,928	3,538,387	5,498,078	NE
ENE	152,903	256,310	1,081,795	1,447,794	2,938,803	ENE
E	47,314	135,772	83,771	0	266,857	E
ESE	31,627	46,500	154,983	0	233,110	ESE
SE	16,320	102,409	229,267	7,460	355,455	SE
SSE	3,730	16,906	26,158	46,890	93,683	SSE
S	3,687	70,220	14,577	3,655	92,139	S
SSW	60,661	75,359	142,235	234,143	512,399	SSW
SW	262,872	389,374	1,137,316	1,011,964	2,801,526	SW
WSW	57,234	172,994	316,136	311,387	857,751	WSW
W	13,585	46,771	118,755	69,700	248,812	W
WNW	10,091	15,112	18,138	269,393	312,733	WNW
NW	16,950	22,713	75,734	93,637	209,035	NW
NNW	31,170	16,701	40,885	26,602	115,358	NNW
Totals	1,141,761	2,142,027	5,304,664	7,657,280	16,245,732	Totals

* Taken from Be87a

Table 15^{*}

2010 Population Estimates Within Annular Sectors, 10 - 50 Miles

Total						
SECTOR	10-20 Miles	20-30 Miles	30-40 Miles	40-50 Miles	10-50 Miles	SECTOR
N	91,018	51,262	250,373	102,263	494,916	N
NNE	172,722	258,877	362,497	510,423	1,304,520	NNE
NE	209,861	499,736	1,260,255	3,552,301	5,522,153	NE
ENE	164,784	277,228	1,099,303	1,464,153	3,005,468	ENE
E	47,676	140,787	86,865	0	275,327	E
ESE	30,472	48,217	163,289	0	241,978	ESE
SE	17,263	114,276	258,374	8,407	398,321	SE
SSE	4,203	19,052	29,479	52,843	105,577	SSE
S	4,009	78,351	16,265	4,007	102,632	S
SSW	65,172	84,086	156,390	252,607	558,255	SSW
SW	284,516	410,918	1,123,253	998,753	2,817,440	SW
WSW	61,714	190,521	321,293	322,263	895,791	WSW
W	15,337	52,386	128,998	73,884	270,605	W
WNW	11,698	17,340	20,389	281,867	331,295	WNW
NW	19,650	26,331	81,471	98,437	225,889	NW
NNW	34,761	19,362	45,199	28,849	128,171	NNW
Totals	1,234,856	2,288,731	5,403,694	7,751,059	16,678,339	Totals

* Taken from Be87a

TABLE 16 (Ku86b)

SECTORIZED POPULATION DATA TO 1 MILE

		radial distances (m)*				
		<u>50</u>	<u>125</u>	<u>375</u>	<u>1105</u>	<u>2416</u>
S	n	0	0	0	377	486
	nnw	0	0	63	0	469
	nw	0	0	0	20	416
E	wnw	0	0	0	800	830
	w	0	0	103	0	1587
C	ws w	0	0	116	192	749
	sw	0	0	116	317	12
T	ss w	0	0	0	950	247
	s	0	0	317	317	820
O	sse	0	0	0	0	3848
	se	0	0	18	0	64
R	ese	0	0	73	0	60
	e	0	0	73	0	30
	ene	0	0	18	34	17
	ne	0	0	0	250	66
	nne	0	0	0	186	25

* The radii shown are midpoints of the sector radial boundaries.

Table 17. Well Water Monitoring Data

Location of Well-->	B-Site #1	B-Site #2	B-Site #3	B-Site #3	B-Site #3	B-Site #4	B-Site #5	D-Site TW#1	D-Site TW#1	D-Site TW#10	D-Site TW#10	New Jersey
Requester-->	PPPL Test	PPPL Test	USGE	PPPL	PPPL	PPPL	PPPL	PPPL	PPPL	PPPL	PPPL	DW Sids.
Collection Date -->	5/18/87	6/30/87	4/28/87	5/18/87	6/30/87	5/18/87	5/18/87	7/30/87	9/16/87	7/30/87	9/16/87	
Units	Parameter											
ug/L	1,1 Dichloroethane	<5	<5	<3	<5	<5	<5	0.6	<0.2	<0.2	<0.2	No Standard
ug/L	1,1 Dichloroethylene	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	1,1,1 Trichloroethane	<5	<5	5.3	<5	<5	<5	1.5	<0.2	<0.2	<0.2	26
ug/L	1,1,2 Chloroethane			<3				<0.2	<0.2	<0.2	<0.2	
ug/L	1,1,2,2 Tetra. C. Ethane	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	1,2 Dibromocetylthene			<3				<0.2	<0.2	<0.2	<0.2	
ug/L	1,2 Dichloroethane			<3				<0.2	<0.2	<0.2	<0.2	
ug/L	1,2 Transdichloroethylene	<5	<5	4.2	<5	<5	<5	<0.2	0.6	<0.2	<0.2	No Standard
ug/L	1,2-Dichlorobenzene	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	1,2-Dichloropropane	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	1,3-Dichlorobenzene	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	1,3-Dichloropropane	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	1,4-Dichlorobenzene	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	2-Chlo.Ethyl.Vyl. Eth	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
Deg.C	Air Temp							29.5			24.5	
mg/L as CaCO3	Alkalinity			24				181			173	
ug/L as Al	Aluminum Dissolved			10								
ug/L as As	Arsenic Dissolved			1								
ug/L	Benzene, Total	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	Bromochloromethane	<5	<10	<10	<10	<10	<10					
ug/L	Bromodichloromethane	<5	<5	<5	<5	<5	<5					
ug/L	Bromoforn Total	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L as Cd	Cadmium Dissolved			1								
mg/L as Ca	Calcium Diss Ca			15								
mg/L as C	Carbon Dis Organic			0.8								
ug/L	Carbon Tetra Total	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
mg/L as Cl	Chloride			41								
ug/L	Chloroethane	<10	<10	<3	<10	<10	<10	<10				
ug/L	Chlorobenzene	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	Chlorodibromometh T			<3				<0.2	<0.2	<0.2	<0.2	
ug/L	Chloroethane	<10	<10	<3	<10	<10	<10	<0.2	<0.2	<0.2	<0.2	
ug/L	Cateroforn Total	<5	<5	<3	<5	<5	<5	<0.2	0.7	<0.2	<0.2	
ug/L as Cr	Chromium Dissolved			1								
ug/L	Cis 1,3-Dich Propene	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L as Cu	Copper Dissolved			7								
feet	Depth Below L9D (Ft)			35								
ug/L	DChlorobromometha T	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
mg/L	Dissolved Solids Sum			140								
ug/L	Ethyl-Benzene	<5	<5	<3	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
mg/L as F	Fluoride Dissolved			0.1								
mg/L as CaCO3	Hardness Total			64								
ug/L as Fe	Iron Dissolved			110								
ug/L as Pb	Lead Dissolved			5								
mg/L as Mg	Magnesium Dissolved			64								
ug/L as Mn	Manganese Dissolved			30								
ug/L as Hg	Mercury Dissolved			0.1								
ug/L	Methyl Total			<3				<0.2		<0.2		

Table 17. Well Water Monitoring Data (Continued)

		B-Site #1	B-Site #2	B-Site #3	B-Site #3	B-Site #3	C-Site #4	C-Site #5	D-Site TW#1	D-Site TW#1	D-Site TW#10	D-Site TW#10	New Jersey
Location of Well-->		PPPL Test	PPPL Test	USGS	PPPL	PPPL	PPPL	PPPL	PPPL	PPPL	PPPL	USGS	DW Sids.
Collection Date -->		5/18/87	6/30/87	4/28/87	5/18/87	6/30/87	5/18/87	5/18/87	7/30/87	9/16/87	7/30/87	9/16/87	
Units	Parameter												
ug/L	Methyl-Bromide			<1					<0.2	<0.2	<0.2	<0.2	
ug/L	Methylene Chloride	<5	<5	<3	<5	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
mg/L as N	Nitrogen NH4 as N Dis			0.01									
mg/L as N	Nitrogen Diss KJD			0.9									
mg/L as N	Nitrogen NO2 as N Dis			0.01									
mg/L as N	NO2 + NO3 as N Diss			1.6									
mg/L	Oxygen Dissolved			6.6					4.9		4.6		
	pH (Laboratory)			6.6					7.4		7.4		
ug/L	Phenols, Total			5.8									
mg/L as P	Phos Ortho Dis as P			1									
mg/L as P	Phosphorus Dis as P			0.07									
mg/L as K	Potassium Dissolved			0.08									
mg/L	Residue Dis 180C			2									
Ratio	SAR			155									
mg/L as SiO2	Silica Dissolved			1									
mg/L as Na	Sodium Dissolved			24									
%	Sodium Percent			21									
uS/cm	Specific Conductance			41					369		358		
ug/l	Styrene, Total			<3					<0.2	<0.2	<0.2	<0.2	
mg/L as SO4	Sulfate Dissolved			20									
ug/L	Tetrachlorethylene	<5	13	76	286	58	<5	<5	8.8	9.3	3.6	1.8	1
ug/L	Toluene	<5	<5	<3	<5	<5	<5	<5	<0.2	<0.2	<0.2	<0.2	
ug/L	Trans-1,3-Di			<3	<5				<0.2		<0.2		
ug/L	Trichlorethylene	<5	31	210	246	120	<5	<5	0.4	7.8	<0.2	0.2	1
ug/L	Trichlorofluoromethane	<5	<5	<3	<5	<5	<5	<5	<0.2		<0.2		
ug/L	Vinyl Chloride	<10	<10	<3	<10	<10	<10	<10	<0.2	<0.2	<0.2	<0.2	
DoC	Water Temperature			11.7					12.2		12		
ug/l	Xylene, Total Rec.			<3					<0.2	<0.2	<0.2	<0.2	
ug/L as Zn	Zinc Dissolved			10									
USGS = United	States Geological Survey												

Table 18. B1 Water Quality Monitoring Data

		Forrestal Campus, Princeton University Station: B1 (Bee Brook)											
Collection Date -->		1/29/87	2/26/87	3/16/87	4/20/87	5/18/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87
Parameter		2:40 PM	5:15 PM	3:00 PM	12:40 PM	12:45 PM	12:20 PM	12:05 PM	12:05 PM	12:00 PM	3:45 PM	1:30 PM	5:05 PM
Units													
mg/L CaCO ₃ eq.	Alkalinity	3.0	1.6	1.2	1.6	4.4	4.4	1.4	2.4	3.2	5.6	3.2	2.8
mg/L O ₂	BOD ₅	3.8	5.8	3.5	11.4	4.8	9	3	4.8	<1	<1	1.4	2.5
mg/L CaCO ₃ eq.	Calcium Hardness	1.6	4.0	2.4	2.4	3.8		3.6	2.8	5.6	3.6	5.2	1.6
mg/L Cr	Chromium - Total	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	0.02	<0.02
mg/L Cr	Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/L O ₂	COD	<2.0	1.22	<2.0	2.1	<2.0	2.2	3	<2.0	3.3	1.2	2.5	2.2
mg/L Cu	Copper	<0.02	<0.02	<0.02	0.02	<0.02	0.03	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/L O ₂	Dissolved Oxygen	>15	13	13.3	13	9	9	8.6	8.2	8.4	6.8	10.4	1.2
mg/L Cu eq.	EDTA	0.06	0.06	0.05	0.04	0.04	0.07	0.25	0.25	0.6	0.6	0.41	0.28
MPN/100 ml	Total Coliform Count	1100	920	170	180	130	350	1600	>2400	180	920	540	79
ft ³ /sec	Flow	Frozen	Frozen	0.16	0.18	0.9	0.08	0.08	0.06	0.02	0.01	0.02	0.11
mg/L Fe	Iron	0.14	2.5	0.22	0.63	0.23	0.28	0.43	0.21	0.36	0.25	0.21	0.35
mg/L N	Nitrogen, Total Kjeldahl	0.15	0.75	0.4	0.55	0.45	0.35	0.7	<0.1	0.35	0.85	0.4	0.15
mg/L N	Nitrogen, Nitrate	0.59	0.84	1	0.8	1.25	1.35	1.65	1.65	2.15	1.2	1.15	0.56
mg/L	Oil & Grease	<0.5	2.2	<0.5	<0.5	<0.5	1	<0.5	4.9	0.9	<0.5	2.3	0.7
unit	pH	6.9	6.8	7.5	6.65	6.7	6.85	7	7.55	7.15	7.2	6.95	6.7
mg/L P	Phosphate, Total	<0.2	0.15	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
mg/L P	Phosphate, Ortho	<0.2	<1.0	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
mg/L	Solids - Dissolved	103	234	98	101	95	119	91	101	110	165	0.08	87
mg/L	Solids - Suspended	3	23	7	<1	4	<1	5	2	8	5	1	12
mg/L SO ₄	Sulfate	17	1.2	1.7	1.5	19	20	24	24	23	27	20	19
DegC	Temperature	0	4	8	15.5	16.5	21.5	21.1	23	1.6	13	6	4
NTU	Turbidity	3.3	3.0	3.5	5.5	2	2.5	2.5	4.5	3.5	3.25	3.1	5
mg/L Zn	Zinc	0.03	0.06	0.02	0.03	0.01	0.03	0.02	0.02	0.04	0.04	0.02	0.03
	Clarity	Clear	Mod.Cldy	St.Cloudy	Clear	Clear	Clear	Clear	Clear	Clear	St.Cloudy	Clear	Clear

Table 19. B2 Water Quality Monitoring Data

		Forrestal Campus, Princeton University											
		Station: B2 (Bee Brook)											
Collection Date -->		1/29/87	2/26/87	3/16/87	4/20/87	5/18/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87
Units	Parameter	2:00 PM	4:30 PM	2:30 PM	12:25 PM	12:25 PM	12:00 PM	11:25 AM	12:00 PM	11:35 AM	3:15 PM	12:15 PM	4:40 PM
mg/l CaCO3 eq.	Alkalinity	54	36	42	36	32	36	54	54	54	50	24	22
mg/l O2	BOD5	3.4	4.8	2.3	9.4	4.8	9.8	2.6	5.6	<1	<1	3.2	1.2
mg/l CaCO3 eq.	Calcium Hardness	52	56	28	28	44	48	40	60	100	24	56	48
mg/l Cr	Chromium - Total	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cr	Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l O2	COD	<2.0	3.8	9	8	7	2.8	10	5	<2.0	14	41	<2.5
mg/l Cu	Copper	0.05	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	0.04	<0.02
mg/l O2	Dissolved Oxygen	12.8	12.6	13.4	13	9.8	9.8	9	8.4	8.3	8.3	8.6	11.2
mg/l Cu eq.	EDTA	0.08	0.07	0.04	0.04	0.04	0.09	0.87	0.87	0.82	0.74	0.41	0.32
MPN/100 ml	Total Coliform Count	>2400	350	34	130	350	920	<2400	>2,400	350	920	180	220
ft3/sec	Flow	2.7	0.42	0.39	0.44	3.5	2.6	0.25	0.19	0.25	0.14	0.25	0.23
mg/l Fe	Iron	0.21	2.3	0.28	<0.02	0.39	0.32	0.92	0.19	0.51	0.24	0.58	0.26
mg/l N	Nitrogen, Total Kjeldahl	0.2	0.45	0.4	0.25	0.6	1.1	0.5	<0.1	0.5	0.15	1.2	0.8
mg/l N	Nitrogen, Nitrate	1.2	1.15	1.13	1.45	1.45	4.5	2.15	1.4	3.1	1.2	0.9	0.9
mg/l	Oil & Grease	<5	1.9	<0.5	0.9	<0.5	<0.05	<0.5	2.2	<0.5	<0.5	8.5	2.8
unit	pH	7.15	7.05	7.8	7.25	7.15	7.45	7.1	7.85	7.35	7.45	7.3	7.25
mg/l P	Phosphate, Total	0.2	0.25	0.2	0.2	0.4	1.6	0.75	0.4	0.65	0.7	1.2	0.3
mg/l P	Phosphate, Ortho	<0.2	<0.10	0.1	<0.1	0.2	1.1	0.45	0.3	0.4	0.6	1.2	0.1
mg/l	Solids - Dissolved	178	219	139	147	161	326	157	152	175	160	220	137
mg/l	Solids - Suspended	0	25	4	8	10	5	13	1	5	4	3	2
mg/l SO4	Sulfate	22	15	20	18	20	82	30	26	26	22	40	24
DegC	Temperature	7	7	11	16	18	22.5	22	23.5	18	17	13	8
NTU	Turbidity	4.6	2.8	3.5	7	2.5	4.25	4	3.25	4	3.3	3.25	3.5
mg/l Zn	Zinc	0.03	0.06	0.02	0.01	0.02	0.04	0.04	0.01	0.04	0.02	0.06	0.03
	Clarity	Clear	Mod Clty	Sl.Cloidy	Sl.Cloidy	Clear	Clear	Sl.Cloidy	Clear	Clear	Clear	Sl.Cloidy	Clear

Table 20. C1 Water Quality Monitoring Data

		Forrestal Campus, Princeton University											
		Station: C1 (Canal)											
Collection Date -->		1/29/87	2/26/87	3/16/87	4/20/87	5/16/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87
Units	Parameter	1:30 PM	5:05 PM	5:40 PM	3:30 PM	2:40 PM	12:00 PM	3:05 PM	10:45 AM	11:40 AM	6:45 PM	3:25 PM	6:15 PM
mg/l CaCO ₃ eq	Alkalinity	36	44	26	24	24	46	34	52	20	14	30	26
mg/l CaCO ₃ eq	Calcium Hardness	48	52	24	20	52	52	40	44	56	72	76	40
mg/l Cr	Chromium - Total	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu	Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	2.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu	Copper	<0.02	<0.02	<0.02	0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu eq	EDTA	0.05	0.05	0.04	0.06	0.06	0.05	0.41	42	0.81	0.7	0.62	0.48
mg/l Fe	Iron	0.29	0.31	0.36	1.4	1.4	0.36	2.1	1.1	1.2	0.74	0.27	0.3
mg/l N	Nitrogen, Nitrate	1	1.25	0.83	1.15	1.35	1.5	1.9	1.4	3	1.2	1.35	1.35
mg/l	Oil & Grease	<0.5	1.2	<0.5	2.7	<0.5	<0.5	<0.5	2.6	<0.5	<0.5	4.2	1.8
unit	pH	7.5	7.25	7.15	6.9	7.1	7.35	6.8	7.8	6.5	7.15	7.2	7.1
mg/l P	Phosphate, Total	<0.2	<0.10	<0.1	0.1	0.15	0.1	0.2	0.15	0.2	<0.1	<0.1	<0.1
mg/l P	Phosphate, Ortho	<0.2	<0.10	<0.1	<0.1	<0.1	<0.1	0.15	<0.1	0.1	<0.1	<0.1	<0.1
mg/l	Solids - Dissolved	141	131	94	96	141	133	115	134	90	111	122	103
mg/l	Solids - Suspended	1	5	9	28	30	11	50	3	13	0.4	5	2
mg/l SO ₄	Sulfate	21	22	21	17	21	19	22	24	21	19	19	19
NTU	Turbidity	4.5	4.4	3.75	17	3.25	1.75	1.5	6.5	6.5	4.5	4.3	3.5
mg/l Zn	Zinc	0.03	0.03	0.02	0.04	0.02	0.02	0.04	0.02	0.03	0.02	0.02	0.02
	Clarity	Clear	Clear	Sl. Cloudy	Sl. Cloudy	Sl. Cloudy	Sl. Cloudy	Mod. Cldy	Mod. Cldy	Sl. Cloudy	Sl. Cloudy	Clear	Sl. Cloudy

Table 21. D1 Water Quality Monitoring Data

Forrestal Campus, Princeton University Station: D1 (Drainage Ditch)												
Collection Date -->	2/26/87	3/16/87	4/20/87	5/18/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87	
Units	11:45 AM	1:35 PM	11:55 AM	10:55 AM	10:55 AM	11:00 AM	10:40 AM	10:45 AM	2:40 PM	11:05 AM	2:05 PM	
mg/l CaCO ₃ eq. Alkalinity	4.0	2.6	1.8	2.6	4.0	4.0	4.9	2.0	3.4	3.6	2.0	
mg/l O ₂ BOD ₅	4.7	2.7	8.2	4	1.0	2.8	6.4	1.2	<1	<1	<1	
mg/l CaCO ₃ eq. Calcium Hardness	5.2	3.2	3.2	4.0	3.6	4.4	3.6	6.4	4.4	3.2	5.6	
mg/l Cr Chromium - Total	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	
mg/l Cr Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	
mg/l O ₂ COD	2	5	1.1	7	2	2.4	2	0.3	1.6	2.3	2	
mg/l Cu Copper	0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	
mg/l O ₂ Dissolved Oxygen	11.5	11	11.4	9.5	10	8.8	8.4	7.6	8.3	9.6	1.1	
mg/l Cu eq. EDTA	0.6	0.03	0.04	0.04	0.03	0.27	0.35	1.6	1.2	0.4	0.32	
MPN/100 ml Total Coliform Count	3.3	54.0	28.0	14.0	35.0	160.0	17.0	9.4	54.0	<2	<2	
ft ³ /sec Flow	0.08	0.6	0.1	0.7	0.07	0.06	0.02	0.05	0.03	0.04	0.05	
mg/l Fe Iron	0.36	0.51	0.61	1.5	0.27	1.3	0.48	1	0.45	0.23	0.25	
mg/l N Nitrogen, Total Kjeldahl	0.8	0.5	0.35	0.85	1.25	0.5	<0.1	0.3	<0.1	0.6	0.3	
mg/l N Nitrogen, Nitrate	0.65	1.4	1.35	1.8	1.1	1.75	1.4	3.9	1.5	0.18	1.25	
mg/l Oil & Grease	<0.5	<0.5	2.2	<0.5	0.5	<0.5	5.3	<0.5	<0.5	4.7	1.3	
unit pH	7.05	6.95	6.65	6.85	6.95	6.8	7.65	6.65	7.2	7.15	7.1	
mg/l P Phosphate, Total	0.6	<0.1	0.6	0.8	1.25	0.65	0.65	1.3	1.1	1	0.7	
mg/l P Phosphate, Ortho	0.17	0.15	0.15	0.25	0.55	0.35	0.35	0.65	0.5	0.5	0.25	
mg/l Solids - Dissolved	155	136	131	142	139	112	141	104	110	137	144	
mg/l Solids - Suspended	7	10	14	31	2	16	1	6	2	7	5	
mg/l SO ₄ Sulfate	23	25	23	21	23	24	24	21	21	21	23	
Deg C Temperature	9	10	14.5	18.5	21.5	23.5	24.5	21	Broken	14.5	10	
NTU Turbidity	5.8	5.8	1.1	4.5	2.25	2.1	5	6.5	4.75	4.45	3.7	
mg/l Zn Zinc	0.04	0.04	0.03	0.03	0.03	0.05	0.05	0.03	0.02	0.02	0.04	
Clarity	SI Cloudy	SI Cloudy	SI Cloudy	SI Cloudy	Clear	SI Cloudy	SI Cloudy	Clear	SI Cloudy	SI Cloudy	Clear	

Table 22. D2 Water Quality Monitoring Data

		Forrestal Campus, Princeton University Station: D2 (Orange Ditch)											
Collection Date -->		1/29/87	2/26/87	3/16/87	4/20/87	5/18/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87
Units	Parameter	1:20 PM	5:40 PM	3:30 PM	1:10 PM	3:10 PM	12:45 PM	12:25 PM	10:40 AM	12:20 PM	4:05 PM	2:30 PM	5:20 PM
mg/L CaCO ₃ eq.	Alkalinity	70	54	54	48	30	44	70	60	60	36	16	14
mg/L O ₂	BOD ₅	<1	3.6	1.9	7.4	5.8	10	1.8	7.8	<1	<1	1.2	1.2
mg/L CaCO ₃ eq.	Calcium Hardness	72	69	24	28	36	44	48	70	100	84	52	36
mg/L Cr	Chromium - Total	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	0.02	<0.02	0.03	<0.02	<0.02	<0.02
mg/L Cr	Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/L O ₂	COD	<2	<2	<2	10	<2	<2	17	5	<2	12	19	<2
mg/L Cu	Copper	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	0.02	<0.02	0.2	<0.02
mg/L O ₂	Dissolved Oxygen	12.3	11.4	11.5	12	9.7	10	9.8	8.8	8.4	8.6	9.5	10.4
mg/L Cu eq.	EDTA	0.04	0.05	0.04	0.05	0.05	0.07	0.65	0.65	1.8	1.4	0.43	0.34
MPN/100 ml	Total Coliform Count	350	2400	46	290	240	540	2400	2400	280	540	110	49
lit/sec	Flow	1.6	0.15	0.12	0.19	2.5	0.1	0.17	0.13	0.16	0.15	0.15	0.12
mg/L Fe	Iron	0.27	2.7	0.27	0.45	0.49	0.24	0.87	0.52	0.82	0.31	0.54	0.23
mg/L N	Nitrogen, Total Kjeldahl	0.7	0.55	0.5	0.2	0.25	0.7	0.35	<0.1	<0.1	0.1	0.55	<0.1
mg/L N	Nitrogen, Nitrate	1	1.2	0.98	1.35	1.45	1.35	1.75	1.4	2.15	1.2	2.25	0.78
mg/L	Oil & Grease	<0.5	1.5	<0.5	1.1	<0.5	0.9	<0.5	<0.5	5.9	2	<0.5	1
unit	pH	7.15	7.5	7.45	7.25	7.3	7.2	7.2	7.75	7.2	7.45	6	7.45
mg/L P	Phosphate, Total	0.3	0.35	0.3	0.3	0.5	0.95	0.6	0.6	0.9	0.8	1	0.65
mg/L P	Phosphate, Ortho	<0.2	0.13	0.1	0.1	0.2	0.4	0.3	0.35	0.45	0.35	0.6	0.15
mg/L	Solids - Dissolved	213	170	182	144	181	172	167	149	123	140	276	161
mg/L	Solids - Suspended	5	30	7	6	11	4	8	1	7	6	3	8
mg/L SO ₄	Sulfate	24	19	23	26	23	22	28	25	21	19	23	8
Deg C	Temperature	11	9.5	12	16	18	22	22.5	24	20	17	14	10
NTU	Turbidity	4.5	3.2	3.3	7	2.75	2.5	2.3	5.5	5.5	3.5	3.75	3.7
mg/L Zn	Zinc	0.05	0.06	0.02	0.03	0.02	0.02	0.05	0.04	0.05	0.02	0.4	0.04
	Clarity	St.Cloudy	Mod.Cldy	St.Cloudy	St.Cloudy	Clear	Clear	St.Cloudy	St.Cloudy	St.Cloudy	St.Cloudy	St.Cloudy	Clear

Table 23. E1 Water Quality Monitoring Data

		Forrestal Campus, Princeton University Station: E1 (Elizabethtown Water)											
Collection Date -->		2/26/87	3/16/87	4/20/87	5/18/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87	
Units	Parameter	11:20 AM	1:20 PM	11:40 AM	10:40 AM	10:40 AM	10:30 AM	10:25 AM	10:30 AM	2:20 PM	10:45 AM	1:45 PM	
mg/l CaCO3 eq.	Alkalinity	66	44	16	26	44	88	74	72	26	28	26	
mg/l CaCO3 eq.	Calcium Hardness	88	32	28	48	52	16	72	116	24	44	84	
mg/l Cu	Copper	<0.02	<0.02	0.04	<0.02	<0.02	<0.02	0.08	<0.02	<0.02	<0.02	<0.02	
MPN/100 ml	Total Coliform Count	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	
mg/l Fe	Iron	0.11	0.11	0.22	0.11	0.05	0.04	0.06	0.12	0.04	0.07	0.04	
mg/l N	Nitrogen, Total Kjeldahl	0.55	0.55	0.3	0.6	1.5	0.5	<0.1	0.4	0.3	0.35	0.4	
mg/l N	Nitrogen, Nitrate	2.45	3.3	5.6	1.25	1.5	3	1.65	0.5	1.3	2.9	1.58	
unit	pH	7.05	6.85	7.1	6.95	6.9	6.7	7.85	6.6	7.15	7	7.1	
mg/l P	Phosphate, Total	<0.10	<0.1	<0.1	<0.1	0.1	<0.1	0.1	0.1	<0.1	<0.1	<0.1	
mg/l P	Phosphate, Ortho	<0.10	<0.1	<0.1	<0.1	0.1	<0.1	0.1	0.1	<0.1	<0.1	<0.1	
mg/l	Solids - Dissolved	195	148	210	182	212	192	196	190	183	216	188	
mg/l Mn	Manganese	<0.01	<0.01	0.03	<0.01	<0.01	<0.01	<0.01	0.02	<0.01	<0.01	<0.01	
mg/l Cl	Chloride	39	24	30	26	10	23	26	26	16	25	21	
mg/l SO4	Sulfate	38	25	56	42	58	40	53	32	36	37	34	
DegC	Temperature	8	8	12	14.5	18	20	22	19	13.5	10	8	
NTU	Turbidity	2.3	2	2.5	0.7	0.45	0.65	0.4	1.5	0.725	0.575	0.8	

Table 24. M1 Water Quality Monitoring Data

Forrestal Campus, Princeton University													
Station: M1 (Millstone River)													
Collection Date -->		1/29/87	2/26/87	3/16/87	4/20/87	5/18/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87
Units	Parameter	2:00 PM	5:30 PM	5:55 PM	3:45 PM	3:00 PM	12:15 PM	3:25 PM	11:00 AM	12:10 PM	7:00 PM	3:45 PM	6:35 PM
mg/l CaCO3 eq.	Alkalinity	14	20	16	16	36	42	22	20	22	20	30	28
mg/l CaCO3 eq.	Calcium Hardness	36	44	16	24	72	48	28	16	60	48	32	32
mg/l Cr	Chromium - Total	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cr	Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	2.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu	Copper	<0.02	<0.02	<0.02	0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu eq.	EDTA	0.07	0.05	0.07	0.06	0.06	0.05	0.41	1	1.4	1.2	1.03	0.88
mg/l Fe	Iron	0.37	0.37	0.48	0.6	0.88	0.7	1.6	1.3	1.1	0.27	0.67	0.59
mg/l N	Nitrogen, Nitrate	3.1	2.7	2.9	2.25	3	2	2.4	1.9	5.6	3.85	1.65	1.4
mg/l	Oil & Grease	<0.5	<0.5	<0.5	2.3	<0.5	<0.05	<0.5	3.9	<0.5	2.1	2.4	6
unit	pH	6.8	6.85	7.05	6.55	6.85	6.8	7.1	7.65	6.3	6.55	6.8	6.7
mg/l P	Phosphate, Total	<0.2	0.2	0.15	0.15	0.25	0.2	0.25	0.25	0.2	0.25	0.25	0.2
mg/l P	Phosphate, Ortho	<0.2	0.11	0.13	<0.1	0.15	0.15	<0.1	0.15	0.15	0.2	<0.1	0.1
mg/l	Solids - Dissolved	146	174	125	110	132	120	83	96	111	122	125	99
mg/l	Solids - Suspended	6	7	7	7	12	2	5	4	8	11	3	10
mg/l SO4	Sulfate	23	23	25	21	19	16	20	17	21	19	21	19
NTU	Turbidity	7	5.1	4.25	8.5	2.5	3.25	3.15	7.5	5.75	2.5	1	6.5
mg/l Zn	Zinc	0.06	0.04	0.02	0.03	<0.01	0.01	0.03	0.01	0.02	0.02	0.02	0.01
	Clarity	Clear	Sl. Cloudy	Sl. Cloudy	Mod. Cldy	Clear	Clear	Clear	Sl. Cloudy	Clear	Sl. Cloudy	Clear	Sl. Cloudy

Table 25. P1 Water Quality Monitoring Data

Forrestal Campus, Princeton University													
Station: P1 (Off-Site Location)													
Collection Date -->		1/29/87	2/26/87	3/16/87	4/20/87	5/18/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87
Units	Parameter	3:10 PM	4:15 PM	5:05 PM	3:00 PM	2:00 PM	11:10 AM	2:15 PM	10:15 AM	10:45 AM	6:15 PM	2:35 PM	5:30 PM
mg/l CaCO ₃ eq.	Alkalinity	10	12	10	22	28	36	24	24	18	30	12	16
mg/l CaCO ₃ eq.	Calcium Hardness	36	36	28	24	44	44	30	8	40	64	52	28
mg/l Cr	Chromium - Total	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cr	Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu	Copper	<0.02	<0.02	0.02	0.02	<0.02	0.03	<0.02	<0.02	<0.02	<0.02	0.02	<0.02
mg/l Cu eq.	EDTA	0.04	0.05	0.04	0.09	0.09	0.03	0.36	0.35	2	1.8	0.91	0.68
mg/l Fe	Iron	0.35	0.89	1.1	0.9	1.4	1	1.7	1.5	1.3	0.43	0.84	0.56
mg/l N	Nitrogen, Nitrate	2.65	2.7	2.3	2.05	2.25	1.85	2.15	1.15	4.1	1.3	1.65	1.45
mg/l	Oil & Grease	<0.5	<0.5	<0.5	1.4	<0.5	<0.5	<0.5	0.6	1	<0.5	1.7	3.3
unit	pH	7.05	6.45	6.35	6.6	6.55	6.95	6.6	7.25	6.1	6.7	6.65	6.45
mg/l P	Phosphate, Total	<0.2	0.1	0.1	0.2	0.2	0.3	0.25	0.2	0.1	<0.1	0.1	<0.1
mg/l P	Phosphate, Ortho	<0.2	<0.10	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
mg/l	Solids - Dissolved	141	145	116	109	114	0.22	101	93	95	102	103	94
mg/l	Solids - Suspended	4	20	18	23	18	13	8	3	5	3	4	2
mg/l SO ₄	Sulfate	29	26	29	20	9.4	12	17	13	19	19	23	21
NTU	Turbidity	5.5	12	3.6	18	4.25	3.5	3.2	6.25	5.5	3.75	2.25	7.5
mg/l Zn	Zinc	0.05	0.03	0.02	0.03	0.01	0.01	0.02	0.02	0.02	0.02	0.03	<0.01
	Clarity	Clear	Sl. Cloudy	Mod. Cldy	Sl. Cloudy	Sl. Cloudy	Sl. Cloudy	Sl. Cloudy	Sl. Cloudy	Clear	Sl. Cloudy	Clear	Clear

Table 26. P2 Water Quality Monitoring Data

Forestral Campus, Princeton University													
Station: P2 (Off-Site Location)													
Units	Collection Date -->	1/29/87	2/26/87	3/16/87	4/20/87	5/16/87	6/15/87	7/20/87	8/17/87	9/21/87	10/19/87	11/24/87	12/21/87
Parameter		3:40 PM	4:40 PM	5:20 PM	3:15 PM	2:20 PM	11:30 AM	2:45 PM	10:30 AM	11:20 AM	6:30 PM	2:55 PM	5:50 PM
mg/l CaCO ₃ eq.	Alkalinity	8	14	8	10	18	38	16	20	20	30	64	32
mg/l CaCO ₃ eq.	Calcium Hardness	20	24	28	28	48	52	32	16	60	56	72	16
mg/l Cr	Chromium - Total	<0.02	<0.02	<0.02	0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cr	Chromium - Hexavalent	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<2.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu	Copper	0.02	<0.02	<0.02	0.02	0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
mg/l Cu eq.	EDTA	0.07	0.07	0.05	0.09	0.09	0.11	0.95	0.35	1.9	1.8	0.86	0.72
mg/l Fe	Iron	0.32	0.22	0.27	22	0.96	0.63	1.5	1.1	0.95	0.18	0.43	0.41
mg/l N	Nitrogen, Nitrate	2.5	1.45	1.8	1.5	2.7	4.1	2.9	2.4	5.1	4.1	1.35	0.8
mg/l	Oil & Grease	<0.5	<0.5	<0.5	2.5	<0.5	<0.5	<0.5	4.2	<0.5	<0.5	3	1.8
unit	pH	6.8	6.75	6.65	6.6	6.75	6.85	6.8	7.15	6.4	6.65	6.65	6.45
mg/l P	Phosphate, Total	<0.2	<0.10	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
mg/l P	Phosphate, Ortho	<0.2	<0.10	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
mg/l	Solids - Dissolved	76	67	66	53	98	108	75	83	64	90	80	62
mg/l	Solids - Suspended	5	5	1	3	6	2	8	5	11	3	2	4
mg/l SO ₄	Sulfate	13	12	13	10	11	5	13	13	12	7.7	11	12
NTU	Turbidity	5	3.5	10	5	2	2.5	2.25	4	3	1.25	4	4
mg/l Zn	Zinc	0.04	0.03	0.02	0.03	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02
	Clarity	St Cloudy	Clear	St Cloudy	St Cloudy	Clear	Clear	Clear	Clear	Clear	Clear	Clear	St Cloudy

Table 27. W4 Water Quality Monitoring Data

Forrestal Campus, Princeton University					
Station: W4 (Underground Well)					
	Collection Date -->	2/26/87	5/18/87	8/17/87	11/24/87
Units	Parameter	4:00 PM	2:49 PM	11:20 AM	11:45 AM
mg/l CaCO3 eq.	Alkalinity	118	36	114	26
mg/l CaCO3 eq.	Calcium Hardness	68	40	16	24
mg/l Cu	Copper	0.04	0.02	0.06	0.07
MPN/100 ml	Total Coliform Count	<2	<2	17	<2
mg/l Fe	Iron	4	4.2	1.4	4.5
mg/l N	Nitrogen, Total Kjeldahl	0.18	0.6	<0.1	0.65
mg/l N	Nitrogen, Nitrate	0.28	1.35	0.7	1.15
unit	pH	7.45	7.15	8.05	7.6
mg/l P	Phosphate, Total	0.35	0.3	0.25	0.45
mg/l P	Phosphate, Ortho	0.11	0.1	0.15	<0.1
mg/l Mn	Manganese	0.15	0.18	0.15	0.22
mg/l Cl	Chloride	12	0.18	7	6
mg/l	Solids - Dissolved	103	9	155	168
mg/l SO4	Sulfate	12	18	14	12
DegC	Temperature	12	13	15.5	13
NTU	Turbidity	1.8	4.75	4.75	3.05

Table 28. W5 Water Quality Monitoring Data

Forrestal Campus, Princeton University					
Station: W5 (Underground Well)					
	Collection Date -->	3/16/87	6/16/87	10/20/87	12/21/87
Units	Parameter	3:50 PM	11:30 AM	11:20 AM	4:10 PM
mg/l CaCO3 eq.	Alkalinity	44	46	48	40
mg/l CaCO3 eq.	Calcium Hardness	40	52	72	36
mg/l Cu	Copper	<0.02	<0.02	<0.02	<0.02
MPN/100 ml	Total Coliform Count	<2	<2	<2	<2
mg/l Fe	Iron	0.41	0.41	0.18	0.36
mg/l N	Nitrogen, Total Kjeldahl	0.4	0.65	<0.1	<0.1
mg/l N	Nitrogen, Nitrate	1.4	1.85	4.85	1.1
unit	pH	6.3	6.95	5.85	6.35
mg/l P	Phosphate, Total	0.15	0.2	0.1	0.15
mg/l P	Phosphate, Ortho	0.13	0.1	0.1	0.1
mg/l	Solids - Dissolved	0.04	112	0.02	111
mg/l Mn	Manganese	5	0.01	6	0.02
mg/l Cl	Chloride	94	7	91	5
mg/l SO4	Sulfate	15	14	15	12
DegC	Temperature	11	13.5	11	11
NTU	Turbidity	2.75	1.5	1.5	1.5

Table 29. TW1 Water Quality Monitoring Data

Forrestal Campus, Princeton University		
Station: TW1 (Test Well #1 D-Site)		
	Collection Date -->	12/21/87
Units	Parameter	3:35 PM
mg/l CaCO ₃ eq.	Alkalinity	14
mg/l CaCO ₃ eq.	Calcium Hardness	108
mg/l Cu	Copper	0.02
MPN/100 ml	Total Coliform Count	240
mg/l Fe	Iron	2.6
mg/l N	Nitrogen, Total Kjeldahl	<0.1
mg/l N	Nitrogen, Nitrate	0.11
unit	pH	7.3
mg/l P	Phosphate, Total	<0.1
mg/l P	Phosphate, Ortho	<0.1
mg/l	Solids - Dissolved	222
mg/l	Manganese	0.11
mg/l	Chloride	12
mg/l	Sulfate	18
DegC	Temperature	10.5
NTU	Turbidity	6

Table 30. TW10 Water Quality Monitoring Data

Forrestal Campus, Princeton University		
Station: TW10 (Test Well #10 D-Site)		
	Collection Date -->	12/21/87
Units	Parameter	3:05 PM
mg/l CaCO ₃ eq.	Alkalinity	16
mg/l CaCO ₃ eq.	Calcium Hardness	120
mg/l Cu	Copper	0.03
MPN/100 ml	Total Coliform Count	<2
mg/l Fe	Iron	1.1
mg/l N	Nitrogen, Total Kjeldahl	<0.15
mg/l N	Nitrogen, Nitrate	0.044
unit	pH	7.15
mg/l P	Phosphate, Total	<0.1
mg/l P	Phosphate, Ortho	<0.1
mg/l	Solids - Dissolved	207
mg/l	Manganese	0.26
mg/l	Chloride	12
mg/l	Sulfate	14
°C	Temperature	11
NTU	Turbidity	5.4

TABLE 31

FERTILIZER, PESTICIDES, AND HERBICIDE APPLICATION [C188]FERTILIZER

(Applied by University)

10-6-4 50% Organic

A Site	1000 lbs.
B Site	1200 lbs.
C Site	1000 lbs.
D Site	800 lbs.

PESTICIDES

(Applied by University)

A Site	No pesticides applied
B Site	No pesticides applied
C Site	No pesticides applied
D Site	No pesticides applied

HERBICIDES

<u>DATE</u>	<u>LOCATION</u>	<u>PRODUCT</u>	<u>AMOUNT</u>
5/11/87	C-Site	Round Up	0.5 gal.
	D-Site	Round Up	0.5 gal.
6/4/87	A,B,C-Site Substations	Arsenal (Cyanamid)	2 pts/100 gal. Total 300 gal.
6/10/87	D-Site Electrical Yards	Arsenal (Cyanamid)	2 qts/100 gal. Total 300 gal.
6/11/87	D-Site QA Trailers	Trimec	25 gal @ 1 gal/100 gal water
6/11/87	D-Site Picnic Area	Trimec	25 gal @ 1 gal/100 gal water
6/17/87	C-Site	Round Up	0.5 gal.
	D-Site	Round Up	0.5 gal.
6/25	A-Site Boneyard	Round Up/Surflan AS	2 qts/50 gal. water Total 50 gal.

TABLE 32

QA/QC EPA LAS VEGAS CROSS-CHECK PROGRAM 1987

<u>SAMPLE DATE</u>	<u>TYPE SAMPLE</u>	<u>KNOWN VALUES HTO CONCENTRATION (pCi/l) PLUS EXPECTED LAB PRECISION</u>	<u>PPPL VALUES (pCi/l)</u>
2/13/87	Water	4209 +/- 729	4220 4290 4290
4/24/87	Urine	5620 +/- 973	5570 5580 5490
6/12/87	Water	2895 +/- 502	3100 3230 3150

Table 33. Nonradioactive QA Results (Split Samples)

Sample Date ->		5/18/87	5/18/87	12/21/87	12/21/87
Units	Parameter	a1	a2	b1	b2
mg/l CaCO3 eq.	Alkalinity	36	44	10	14
mg/l	BOD5	<1	4	1.5	1.6
mg/l CaCO3 eq.	Calcium Hardness	48	32	68	60
mg/l Cr	Chromium	<.02	<.02	<.02	<.02
mg/l Cr	Chromium, Hex.	<.02	<.02	<.02	<.02
mg/l O2	COD	1.5	7	<2.0	<2.0
mg/l Cu	Copper	<.02	<.02	<.02	<.02
mg/l O2	Dissolved Oxygen	10.4	10.2	10.8	11.2
mg/l Cu eq.	EDTA	0.39	0.38	0.42	0.38
MPN/100ml	Total Coliform Count	1600	1600	49	34
mg/l Fe	Iron	1.2	1.2	0.16	0.07
mg/l N	Total Kjeldahl Nitrogen	0.7	0.75	0.45	0.65
mg/l N	Nitrate Nitrogen	1.7	1.45	0.9	2
mg/l	Oil & Grease	2.3	2.4	<0.5	5.4
unit	pH	6.95	7.15	7.45	7.3
mg/l P	Phosphate, Total	0.1	0.15	0.5	0.5
mg/l P	Phosphate, Ortho	<0.1	<.01	0.17	0.18
mg/l	Solids - Dissolved	132	127	174	163
mg/l	Solids -Suspended	28	28	10	2
mg/l Mn	Manganese	*	*	*	*
mg/l Cl	Chloride	*	*	*	*
mg/l SO4	Sulfate	21	22	*	*
NTU	Turbidity	4.75	3.25	3.5	4.1
m/l Zn	Zinc	0.02	0.02	0.03	0.02
	Clarity	Sl. Cloudy	Sl. Cloudy	Clear	Sl. Cloudy
* = no results					

Table 34. USGS Water Quality for Test Wells 1 and 10, FY87

	Location of Well-->	TW #1	TW#1	TW#1	TW#1	TW#10	TW#10	TW#10	TW#10
	Collection Date -->	10/29/86	1/15/87	4/22/87	7/30/87	10/29/86	1/15/87	4/22/87	7/30/87
Units	Parameter								
mg/l as CaCO ₃	Alkalinity, field total	NA	151	150	181	NA	143	152	173
mg/l as N	Ammonium, dissolved	<0.010	<0.010	<0.010	<0.010	<0.010	0.03	0.021	0.03
ug/l	Barium, dissolved	350	290	330	330	390	369	400	400
ug/l	Beryllium, dissolved	1	<0.5	<0.5	<0.5	1	<0.5	<0.5	<0.5
ug/l	Cadmium, dissolved	<1	<1	1	<1	<1	1	2	<1
mg/l	Calcium, dissolved	46	39	46	45	46	43	45	46
mg/l	Chloride, dissolved	12	10	17	15	12	12	16	13
ug/l	Cobalt, dissolved	<3.0	<3.0	<3.0	<3.0	<3.0	<3.0	<3.0	<3.0
ug/l	Copper, dissolved	<10	<10	<10	<10	<10	<10	<10	<10
mg/l	Fluoride, dissolved	0.1	0.1	0.1	<0.1	0.1	0.1	0.2	<0.1
ug/l	Iron, dissolved	12	3	27	24	510	<3	400	410
ug/l	Lead, dissolved	<10	<10	<10	<10	<10	<10	<10	<10
ug/l	Lithium, dissolved	7	6	4	8	8	7	10	12
mg/l	Magnesium, dissolved	14	12	14	14	12	10	12	12
ug/l	Manganese, dissolved	170	6	56	50	300	300	300	310
ug/l	Molybdenum, dissolved	<10	<10	<10	<10	<10	<10	<10	<10
mg/l as N	Nitrite, dissolved	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
mg/l as N	Nitrite + Nitrate, diss.	<0.1	0.19	0.13	0.14	<0.1	<0.1	<0.1	<0.1
mg/l	Nitrogen, dissolved, KjD	0.8	<0.2	0.3	0.3	0.4	<0.2	0.3	0.3
mg/l	Oxygen, dissolved	0.8	0.2	0.6	NR	0.5	0.07	0.5	NR
pH, field		7.3	7.22	7.2	7.4	7.5	7.3	7.4	7.4
mg/l as P	Phosphate, Ortho, diss.	0.021	0.021	0.01	0.01	0.021	0.021	0.01	0.021
mg/l	Potassium, dissolved	1.5	1.3	1.4	2.1	1.6	1.6	1.6	2
mg/l	Silica, dissolved	25	23	27	26	25	25	26	26
mg/l	Sodium, dissolved	10	8.6	11	11	9.7	9.2	9.8	9.9
usiemens/cm	Specific Conductance, field	359	350	390	369	307	333	360	358
ug/l	Strontium, dissolved	380	319	360	360	410	390	400	400
mg/l	Sulfate, dissolved	20	21	24	22	17	17	19	18
pCi/l	Tritium, PPPL	64	NA	NA	66	60	NA	NA	72
pCi/l	Tritium, Miami	NA	68.4	NA	64	NR	71.5	NA	61
ug/l	Vanadium, dissolved	<6.0	<6.0	<6.0	<6.0	<6.0	<6.0	<6.0	<6.0
DegC	Water Temperature	12.2	11.8	12.4	12.2	12	11.7	12.1	12
ug/l	Zinc, dissolved	<3	12	<3	10	<3	7	10	6
	NA=sample was not analyzed for this constituent.								
	NR=value not reported because of malfunction of analytical equipment

FIG. 1. S-1 Spheromak

FIG. 2. RFTF

FIG. 3. PBX-11

FIG. 4. TFTR

Figure 5

Wind Rose
 Joint Frequency Data for TFTR
 84/ 1 to 86/12
 Elevation 30 m
 For All Stability Classes (100.0%)

Wind Rose
 Joint Frequency Data for TFTR
 84/ 1 to 86/12
 Elevation 60 m
 For All Stability Classes (100.0%)

Figure 6

FIG. 7

FIG. 8
IMMEDIATE SITE VICINITY
(5-MILE RADIUS)

Princeton Plasma Physics
1985 POPULATION ESTIMATES
WITHIN ANNUAL SECTIONS
0-10 MILES
Figure 10

Princeton Plasma Physics
 1995 POPULATION PROJECTIONS
 WITHIN ANGULAR SECTORS
 0 - 10 MILES
 Figure 11

*Taken from Be87a

Princeton Plasma Physics

2000 POPULATION PROJECTIONS
WITHIN ANGULAR SECTORS
4° - 10 MILES

Figure 12

*Taken from Be87a

Princeton Plasma Physics

2005 POPULATION PROJECTIONS
WITHIN ANGULAR SECTORS
0 - 10 MILES

Figure 13

*Taken from Be87a

Princeton Plasma Physics

2010 POPULATION PROJECTIONS
WITHIN ANNUAL SECTIONS
0 - 10 MILES

Figure 14

*Taken from Be87a

Princeton Plasma Physics

1985 POPULATION ESTIMATES
WITHIN AZIMUTHAL SECTORS
10 - 50 MILES

Figure 15

*Taken from Be87a

Princeton Plasma Physics

1005 POPULATION ESTIMATES
WITHIN 10-MILE SECTORS
10 - 50 MILES

Figure 16

*Taken From Be87a

Princeton Plasma Physics

2000 POPULATION ESTIMATES
WITHIN ANNULAR SECTORS
10 - 50 MILES

Figure 17

*Taken from Be87a

Princeton Plasma Physics

2005 POPULATION ESTIMATES
WITHIN ANNULAR SECTORS
10 - 50 MILES
Figure 18

*Taken from Be87a

Princeton Plasma Physics

2010 POPULATION ESTIMATES
WITHIN ANNULAR SECTORS
10 - 50 MILES

Figure 19

*Taken from Be87a

FIG. 21

MILLSTONE RIVER BASIN OFFSITE WATER SAMPLE LOCATION

Figure 22. Potentiometric surface of the bedrock aquifer, October 30, 1986.
(Taken from Le87)

Figure 23. Schematic representation of hydrogeologic framework and potential flow paths of spilled water. (Taken from Le87).

FIG. 24

OFF-SITE MONITORING LOCATIONS

201
- 8/9/88