UNCLASSIFIED

WSRC-TR--92-61

DE93 002401

**FOURTH QUARTER 1991
AND 1991 SUMMARY**

K-AREA ACID/CAUSTIC BASIN GROUNDWATER MONITORING REPORT (U)

KEY WORDS

hazardous waste
iron
KAC wells
lead
total organic halogens

PUBLICATION DATE: MARCH 1992

Authorized Derivative Classifier:

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER SITE
AIKEN, SC 29808

UNCLASSIFIED

MASTER

Abstract

During fourth quarter 1991, samples from the KAC monitoring wells at the K-Area Acid/Caustic Basin were analyzed for indicator parameters, turbidity, major ions, volatile organic compounds, radionuclides, and other constituents. Monitoring results that exceeded the U.S. Environmental Protection Agency primary drinking water standards (PDWS) and the Savannah River Site (SRS) flagging criteria and turbidity standards during the quarter, with summary results for the year, are presented in this report.

During fourth quarter 1991, no constituents exceeded the PDWS at the K-Area Acid/Caustic Basin. Iron and total organic halogens exceeded Flag 2 criteria in sidegradient-to-downgradient well KAC 7 but not in other KAC wells. No priority pollutants (EPA, 1990) exceeded the PDWS or the Flag 2 criteria in wells KAC 1 and 3. None of the KAC wells exceeded the SRS turbidity standard.

During 1991, lead exceeded the PDWS in well KAC 7 during first quarter. No other constituent exceeded the PDWS at the K-Area Acid/Caustic Basin during the year.

Contents

	Page
Abstract	iii
List of Figures	vii
List of Tables	vii
Executive Summary	1
Introduction	2
Discussion	3
Groundwater Monitoring Data	3
Analytical Results Exceeding Standards	4
Turbidity Results Exceeding Standards	4
Water Elevations, Flow Directions, and Flow Rates	4
Results of Upgradient vs. Downgradient Wells	5
Conclusions	6
Summary 1991	7
Errata	8
References Cited	9
Appendix A—Primary Drinking Water Standards	A-1
Appendix B—Flagging Criteria	B-1
Appendix C—Figures	C-1
Appendix D—Groundwater Monitoring Results Tables	D-1

List of Figures

	Page
1. Location of the K-Area Acid/Caustic Basin at the Savannah River Site.	C-2
2. Location of Groundwater Monitoring Wells at the K-Area Acid/Caustic Basin	C-3
3. Potentiometric Surface Map of the Water Table at the K-Area Acid/Caustic Basin	C-4

List of Tables

	Page
1. Constituents Exceeding the Primary Drinking Water Standards for 1991	D-3
2. Constituents Exceeding Other Flagging Criteria	D-3
3. Groundwater Monitoring Results for Individual Wells	D-4

Executive Summary

The monitoring wells at the K-Area Acid/Caustic Basin are sampled quarterly as part of the Savannah River Site (SRS) Groundwater Monitoring Program to comply with South Carolina Hazardous Waste Management Regulations.

During fourth quarter 1991, samples from seven monitoring wells at the K-Area Acid/Caustic Basin were analyzed for turbidity, pH, specific conductance, major ions, total organic halogens, total organic carbon, total dissolved solids, radionuclides, pesticides, herbicides, and other constituents. Monitoring results that exceeded the U.S. Environmental Protection Agency primary drinking water standards (PDWS) and the SRS flagging criteria and turbidity standards are the focus of this report.

Wells KAC 6 and 7 at the K-Area Acid/Caustic Basin did not yield four well volumes prior to sampling; both KAC 6 and 7 produced 9 gallons prior to purging dry. The samples collected from these wells may not, therefore, be representative groundwater samples.

No constituents exceeded the PDWS at the K-Area Acid/Caustic Basin during fourth quarter 1991. Iron exceeded the Flag 2 criterion in well KAC 7, with a value of 1,390 $\mu\text{g/L}$. Total organic halogens exceeded the Flag 2 criterion in well KAC 7 with a value of 55 $\mu\text{g/L}$.

Downgradient-to-sidegradient well KAC 7 contained elevated levels of total organic halogens as well as elevated iron when compared to upgradient wells.

No priority pollutants (EPA, 1990) were detected above the PDWS or Flag 2 criteria in wells KAC 1 (upgradient) and KAC 3 (downgradient).

During fourth quarter 1991, wells KAC 1, 3, and 4 had turbidity values of fewer than 5 NTU. No well exceeded the standard of 50 NTU.

Water-table elevations at the K-Area Acid/Caustic Basin indicate that groundwater flow direction is toward the west to southwest; flow has been generally toward the west to southwest for at least 12 quarters. The screen in well KAC 4 is submerged, which may affect the accuracy of the potentiometric contour map and complicates the determination of the groundwater flow direction.

Introduction

The K-Area Acid/Caustic Basin lies in the eastern portion of K Area at the Savannah River Site (SRS) near a tributary of Pen Branch. The basin, constructed in the early 1950s, is an unlined earthen pit that received dilute sulfuric acid and sodium hydroxide solutions and other wastes from several areas within SRS. The basin provided an area for the mixing and neutralization of the dilute solutions before their discharge to nearby streams. The K-Area Acid/Caustic Basin remained in service until new neutralization facilities became operational in 1982 (Heffner and Exploration Resources, 1991).

Four groundwater monitoring wells were installed in the K-Area Acid/Caustic Basin between October 1983 and July 1984. Under the terms of a consent decree executed May 26, 1988, by the U.S. District Court (District of South Carolina, Aiken Division), the basin became subject to requirements of Subtitle C of the Resource Conservation and Recovery Act (RCRA), the South Carolina Hazardous Waste Management Regulations (SCHWMR), and associated regulations. The basin monitoring wells were reevaluated during the summer of 1988 to ensure compliance with SCHWMR. As part of this compliance effort, three additional wells were installed at the K-Area Acid/Caustic Basin during third quarter 1988.

The monitoring wells at the K-Area Acid/Caustic Basin are sampled quarterly as part of the SRS Groundwater Monitoring Program to comply with SCHWMR. The revised Groundwater Quality Assessment Plan (WSRC, 1991), which was submitted to the South Carolina Department of Health and Environmental Control on April 30, 1991, proposes the installation of two additional water-table wells at the K-Area Acid/Caustic Basin; drilling has begun to install these two wells. In addition, at least one borehole will be logged by geophysical methods to provide additional stratigraphic information and to help identify the most transmissive zones.

Discussion

Groundwater Monitoring Data

The standard practice at SRS is to purge four well volumes from each well and ensure that the field parameters have stabilized before sample collection. In the event a well goes dry before purging is completed, it is allowed to recover and sampling is attempted within 24 hours without further purging. If successful, this sampling constitutes a single sampling event. During fourth quarter 1991, wells KAC 6 and 7 at the K-Area Acid/Caustic Basin did not yield four well volumes prior to sampling; both KAC 6 and 7 produced 9 gallons prior to purging dry. The samples collected from these wells may not, therefore, be representative groundwater samples.

Samples from seven monitoring wells at the K-Area Acid/Caustic Basin were analyzed for turbidity, pH, specific conductance, major ions, total organic halogens, total organic carbon, total dissolved solids, radionuclides, pesticides, herbicides, and other constituents. During this quarter, samples from wells KAC 1 and 3 were analyzed for priority pollutants (EPA, 1990). These analyses were performed to satisfy a South Carolina Department of Health and Environmental Control Notice of Deficiency on the F-, H-, K-, and P-Area Acid/Caustic Basins Groundwater Quality Assessment Plan to ensure that there are no hazardous organics in the groundwater.

This report describes monitoring results that exceeded the U.S. Environmental Protection Agency (EPA) primary drinking water standards (PDWS) (Appendix A), the SRS flagging criteria (Appendix B), and the SRS turbidity standards. The Environmental Monitoring Section of the Environmental Protection Department at SRS recently revised the flagging criteria for identifying constituents in high concentrations in groundwater. In general, the criteria are as follows:

- Flag 2 criteria are based on the PDWS; if the constituents do not have a PDWS, Flag 2 criteria are based on the secondary drinking water standards (SDWS) or 10 times the method detection limits as described in Appendix B. Constituent levels that equal or exceed Flag 2 criteria are described as *elevated*.
- Flag 1 criteria are based on half the PDWS; if the constituents do not have a PDWS, Flag 1 criteria are based on half the SDWS or 5 times the method detection limits as described in Appendix B. A Flag 1 for a constituent may reflect analytical error or it may indicate the initial detection of a contaminant. Thus, constituents exceeding Flag 1 criteria are included in this report and are described as *slightly elevated*.
- Flag 0 criteria are based on constituent levels below Flag 1.

Illustrations of the monitored unit at SRS (Figure 1), the individual monitoring wells (Figure 2), and the flow directions of the groundwater beneath the unit (Figure 3) are

in Appendix C; monitoring results tables are in Appendix D. Samples that exceeded holding times (the time between sample collection and sample analysis) also are shown in Appendix D.

Analytical Results Exceeding Standards

Results for analytes that exceeded their respective PDWS (see Appendix A) during 1991 are summarized in Table 1 (Appendix D). No constituents exceeded the PDWS at the K-Area Acid/Caustic Basin during fourth quarter 1991.

Constituents that exceeded other Flag 1 or 2 criteria (see Appendix B) during fourth quarter 1991 are summarized in Table 2 (Appendix D). Iron exceeded the Flag 2 criterion in well KAC 7, with a value of 1,390 $\mu\text{g/L}$. Total organic halogens exceeded the Flag 2 criterion in well KAC 7, with a value of 55 $\mu\text{g/L}$.

No priority pollutants (EPA, 1990) were detected in wells KAC 1 and 3.

All results for individual wells are presented in Table 3 (Appendix D).

Turbidity Results Exceeding Standards

Turbidity results, in nephelometric turbidity units (NTU), are reported for well samples exceeding 5 and 50 NTU. During fourth quarter 1991, wells KAC 1, 3, and 4 all had turbidity values of less than 5 NTU. No well exceeded the standard of 50 NTU.

A detection value of 5 NTU, established by EPA (1986) as a general standard, is considered unrealistic for monitoring wells at SRS. Gass (1989) has documented turbidity measurements ranging up to 5,000 NTU from properly designed wells screened in poorly productive formations. During the 1989 RCRA Compliance Evaluation Inspection, officials from EPA Region IV indicated that the SRS turbidity standard of 50 NTU is conservative. These officials also agreed that water-table wells in this area often correspond to nonaquifer formations, rendering development of these wells more difficult due to the low yield and high proportion of mobile fines typical of these formations (Bergren and Bennett, 1989).

Water Elevations, Flow Directions, and Flow Rates

Water-table elevations and the groundwater flow direction beneath the K-Area Acid/Caustic Basin are shown in Figure 3 (Appendix C). The data indicate a ponding or losing stream effect (water entering the groundwater from the K-Area outfall effluent stream) in this area, creating a mound of groundwater to the east of the basin. Water-table elevations indicate that groundwater flow direction is toward the west to southwest (using SRS grid coordinates); flow has been generally toward the west to southwest for at least 12 quarters.

The top of the screen in monitoring well KAC 4 is submerged approximately 13 ft, resulting in a water-level measurement that may be artificially low and, thus, somewhat skewed potentiometric contours. The revised Groundwater Quality Assessment Plan for the basin

(WSRC, 1991) proposed the installation of two additional wells at the K-Area Acid/Caustic Basin (see Figure 3, Appendix C) to provide more accurate water-elevation data.

The groundwater flow rate in the water table (Aquifer Zone IIB₂) beneath the K-Area Acid/Caustic Basin is estimated using the following equation:

$$\text{Flow (ft/day)} = \frac{\text{Hydraulic Conductivity (ft/day)}}{\text{Porosity (unitless)}} \times \frac{dh \text{ (ft)}}{dl \text{ (ft)}}$$

A hydraulic conductivity constant of 10 ft/day (Geraghty & Miller, Inc., 1990) is a conservative estimate (i.e., the actual hydraulic conductivity should be somewhat less than 10 ft/day). The effective porosity value is estimated at 20% (Killian et al., 1987), dh is the difference in head, and dl is the length of the flow path. Flow rate estimates vary depending on the vertical gradient between wells, the size of the area under consideration, and the number of data points. The calculated flow rate should be regarded only as an order of magnitude for flow rates in this area.

The flow rate estimate for groundwater beneath the K-Area Acid/Caustic Basin is as follows:

$$\frac{10}{0.20} \times \frac{1.5}{97.76} = 0.77 \text{ ft/day}$$

$$0.77 \text{ ft/day} \times 365 \text{ days} = 280 \text{ ft/year}$$

Results of Upgradient vs. Downgradient Wells

Well KAC 1 is downgradient, KAC 2 is sidegradient, wells KAC 3 and 5 are upgradient, and wells KAC 4, 6, and 7 are sidegradient to downgradient. Sidegradient-to-downgradient well KAC 7 contained elevated levels of total organic halogens and iron in comparison with the upgradient wells.

Conclusions

Total organic halogens and iron exceeded the Flag 2 criteria in sidegradient-to-downgradient well KAC 7 during fourth quarter 1991. No constituent exceeded the PDWS or the turbidity standard for fourth quarter 1991. No priority pollutants (EPA, 1990) were detected in wells KAC 1 and 3.

Summary 1991

Lead was the only constituent to exceed its PDWS during 1991. Sidegradient-to-downgradient well KAC 7 yielded a value of 76 $\mu\text{g/L}$ for this constituent during the first quarter of the year.

Errata

Errors in the computer program used to mark analyses that exceed holding times caused a number of analyses to be incorrectly flagged as exceeding holding time in the third quarter 1991 report.

The only analyses performed by General Engineering on samples from the KAC well series during third quarter 1991 that exceeded holding time were the cyanide analyses for wells KAC 1 and 3 (1 replicate); the total organic halogen analyses for KAC 3 (4 duplicates), KAC 4, and KAC 5 (4 duplicates); and the gas chromatograph/mass spectrometer volatile organic analyses (28 constituents) for the replicate of KAC 3, which were run only one day out of holding.

References Cited

Bergren, C. L., and C. B. Bennett, 1989. **Assessment of SRS Groundwater Monitoring Wells Impacted by Turbidity**, WSRC-RP-89-891. Westinghouse Savannah River Company, Aiken, SC.

EPA (U.S. Environmental Protection Agency), 1986. **RCRA Ground-water Monitoring Technical Enforcement Guidance Document**, OSWER-9950.1. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. *Appendix A—126 Priority Pollutants*. 40, **Code of Federal Regulations**, Part 423, pp. 735–736. Washington, DC.

Gass, T. E., 1989. *Monitoring Wells in Non-Aquifer Formations*. **Water Well Journal** 43(2):27–29.

Geraghty & Miller, Inc., 1990. **Evaluation of Integrated Waste Facility Closure Capping on Ground-Water Flow and Solute Transport in General Separations Area, Savannah River Site: Flow Model and Particle-Tracking Analysis, Final Report**. Prepared for Westinghouse Savannah River Company, Waste Management Technology, Savannah River Site, Aiken, SC.

Heffner, J. D., and Exploration Resources, Inc., 1991. **Technical Summary of Groundwater Quality Protection Program at the Savannah River Site (1952–1986), Volume 1—Site Geology and Waste Sites**, DPSP-88-1002. Westinghouse Savannah River Company, Aiken, SC.

Killian, R. H., N. L. Kolb, P. Corbo, and I. W. Marine, 1987. **F-Area Seepage Basins**, DPST-85-704. Savannah River Laboratory, E. I. du Pont de Nemours and Company, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1991. **F-, H-, K-, and P-Area Acid/Caustic Basins Groundwater Quality Assessment Plan**, WSRC-TR-91-178, Revision 1.0. Westinghouse Savannah River Company, Aiken, SC.

Appendix A – Primary Drinking Water Standards

Primary Drinking Water Standards

<u>Analyte</u>	<u>Unit</u>	<u>PDWS</u>	<u>Source</u>
Antimony-125	pCi/L	300	Final PDWS (EPA, 1977)
Arsenic	µg/L	50	Final PDWS (EPA, 1990)
Barium	µg/L	2,000	Final PDWS (EPA, 1991c)
Barium-140	pCi/L	90	Final PDWS (EPA, 1977)
Benzene	µg/L	5	Final PDWS (EPA, 1990)
Beryllium-7	pCi/L	6,000	Final PDWS (EPA, 1977)
Bromodichloromethane	µg/L	100	Final PDWS (EPA, 1991c)
Bromoform	µg/L	100	Final PDWS (EPA, 1991c)
Cadmium	µg/L	10	Final PDWS (EPA, 1990)
Carbon tetrachloride	µg/L	5	Final PDWS (EPA, 1990)
Carbon-14	pCi/L	2,000	Final PDWS (EPA, 1977)
Cerium-141	pCi/L	300	Final PDWS (EPA, 1977)
Cesium-137	pCi/L	200	Final PDWS (EPA, 1977)
Chlordane	µg/L	2	Final PDWS (EPA, 1991a)
Chloroethene (Vinyl chloride)	µg/L	2	Final PDWS (EPA, 1990)
Chloroform	µg/L	100	Final PDWS (EPA, 1991c)
Chromium	µg/L	100	Final PDWS (EPA, 1991a)
Chromium-51	pCi/L	6,000	Final PDWS (EPA, 1977)
Cobalt-58	pCi/L	9,000	Final PDWS (EPA, 1977)
Cobalt-60	pCi/L	100	Final PDWS (EPA, 1977)
Copper	µg/L	1,300	Final PDWS (EPA, 1991b)
Dibromochloromethane	µg/L	100	Final PDWS (EPA, 1991c)
Dibromochloropropane	µg/L	0.2	Final PDWS (EPA, 1991a)
1,4-Dichlorobenzene	µg/L	75	Final PDWS (EPA, 1990)
1,2-Dichloroethane	µg/L	5	Final PDWS (EPA, 1990)
cis 1,2-Dichloroethene	µg/L	70	Final PDWS (EPA, 1991a)
1,1-Dichloroethylene	µg/L	7	Final PDWS (EPA, 1990)
trans-1,2-Dichloroethylene	µg/L	100	Final PDWS (EPA, 1991a)
2,4-Dichlorophenoxyacetic acid	µg/L	100	Final PDWS (EPA, 1990)
1,2-Dichloropropane	µg/L	5	Final PDWS (EPA, 1991a)
Endrin	µg/L	0.2	Final PDWS (EPA, 1990)
Ethylbenzene	µg/L	700	Final PDWS (EPA, 1991a)
Europium-154	pCi/L	200	Final PDWS (EPA, 1977)
Europium-155	pCi/L	600	Final PDWS (EPA, 1977)
Fluoride	µg/L	4,000	Final PDWS (EPA, 1991c)
Gross alpha	pCi/L	15	Final PDWS (EPA, 1990)
Heptachlor	µg/L	0.4	Final PDWS (EPA, 1991a)
Heptachlor epoxide	µg/L	0.2	Final PDWS (EPA, 1991a)
Iodine-129	pCi/L	1	Final PDWS (EPA, 1977)
Iodine-131	pCi/L	3	Final PDWS (EPA, 1977)
Iron-55	pCi/L	2,000	Final PDWS (EPA, 1977)
Iron-59	pCi/L	200	Final PDWS (EPA, 1977)
Lanthanum-140	pCi/L	60	Final PDWS (EPA, 1977)
Lead	µg/L	15	Final PDWS (EPA, 1991b)
Lindane	µg/L	4	Final PDWS (EPA, 1990)
Manganese-54	pCi/L	300	Final PDWS (EPA, 1977)
Mercury	µg/L	2	Final PDWS (EPA, 1991a)
Methoxychlor	µg/L	100	Final PDWS (EPA, 1990)
Nickel-59	pCi/L	300	Final PDWS (EPA, 1977)
Nickel-63	pCi/L	50	Final PDWS (EPA, 1977)
Niobium-95	pCi/L	300	Final PDWS (EPA, 1977)
Nitrate as nitrogen	µg/L	10,000	Final PDWS (EPA, 1991a)
Nitrite as nitrogen	µg/L	1,000	Final PDWS (EPA, 1991a)
PCB 1016	µg/L	0.5	Final PDWS (EPA, 1991a)
PCB 1221	µg/L	0.5	Final PDWS (EPA, 1991a)

<u>Analyte</u>	<u>Unit</u>	<u>PDWS</u>	<u>Source</u>
PCB 1232	µg/L	0.5	Final PDWS (EPA, 1991a)
PCB 1242	µg/L	0.5	Final PDWS (EPA, 1991a)
PCB 1248	µg/L	0.5	Final PDWS (EPA, 1991a)
PCB 1254	µg/L	0.5	Final PDWS (EPA, 1991a)
PCB 1260	µg/L	0.5	Final PDWS (EPA, 1991a)
PCB 1262	µg/L	0.5	Final PDWS (EPA, 1991a)
Pentachlorophenol	µg/L	1	Final PDWS (EPA, 1991c)
Ruthenium-103	pCi/L	200	Final PDWS (EPA, 1977)
Ruthenium-106	pCi/L	30	Final PDWS (EPA, 1977)
Selenium	µg/L	50	Final PDWS (EPA, 1991a)
Silver	µg/L	50	Final PDWS (EPA, 1990)
Strontium-89	pCi/L	20	Final PDWS (EPA, 1977)
Strontium-90	pCi/L	8	Final PDWS (EPA, 1990)
Styrene	µg/L	100	Final PDWS (EPA, 1991a)
Technetium-99	pCi/L	900	Final PDWS (EPA, 1977)
Tetrachloroethylene	µg/L	5	Final PDWS (EPA, 1991a)
Tin-113	pCi/L	300	Final PDWS (EPA, 1977)
Toluene	µg/L	1,000	Final PDWS (EPA, 1991a)
Total radium	pCi/L	5	Final PDWS (EPA, 1990)
Toxaphene	µg/L	3	Final PDWS (EPA, 1991a)
2,4,5-TP (Silvex)	µg/L	10	Final PDWS (EPA, 1990)
1,1,1-Trichloroethane	µg/L	200	Final PDWS (EPA, 1990)
Trichloroethylene	µg/L	5	Final PDWS (EPA, 1990)
Tritium	pCi/mL	20	Final PDWS (EPA, 1990)
Xylenes	µg/L	10,000	Final PDWS (EPA, 1991a)
Zinc-65	pCi/L	300	Final PDWS (EPA, 1977)
Zirconium-95	pCi/L	200	Final PDWS (EPA, 1977)
Zirconium/Niobium-95	pCi/L	200	Final PDWS (EPA, 1977) ^a

^a When radionuclide analyses are combined, the lower PDWS of the two isotopes is used.

References

EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**. EPA-570/9-76-003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. **National Primary Drinking Water Regulations**. 40, Code of Federal Regulations, Part 141, pp. 553-638. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991a. **National Primary Drinking Water Regulations; Final Rule**. **Federal Register**, January 30, 1991, pp. 3592-3597. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991b. **Maximum Contaminant Level Goals and National Primary Drinking Water Regulations for Lead and Copper; Final Rule**. **Federal Register**, June 7, 1991, p. 26477. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991c. **National Primary Drinking Water Regulations; Final Rule**. **Federal Register**, July 1, 1991, pp. 30274-30280. Washington, DC.

Appendix B – Flagging Criteria

Flagging Criteria

Beginning in 1991, the Environmental Monitoring Section of the Environmental Protection Department (EPD/EMS) modified its guidelines for flagging constituents in the Groundwater Monitoring Program. These flagging criteria are as follows:

- Flag 2 criterion for a constituent equals the U.S. Environmental Protection Agency (EPA) primary drinking water standard, the EPA proposed primary drinking water standard, or the EPA secondary drinking water standard for that constituent. If a constituent does not have a drinking water standard, the Flag 2 criterion equals 10 times the method detection limit calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 1 criterion for a constituent equals one-half of the EPA primary drinking water standard, one-half the EPA proposed primary drinking water standard, or one-half the EPA secondary drinking water standard for that constituent. If a constituent does not have an EPA drinking water standard, the Flag 1 criterion equals 5 times the method detection limit calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Analytical results for a constituent below Flag 1 are classified as Flag 0.

The following parameters are not assigned flagging criteria: alkalinity, calcium, carbonate, color, corrosivity, magnesium, odor, potassium, Eh, silica, sodium, total dissolved solids, total phosphorus, total phosphates (as P), and turbidity. In addition, common laboratory contaminants and cleaners including phthalates, methylene chloride, ketones, and toluene are not assigned flagging criteria.

Analyte	Unit	Flag 1	Flag 2	Source
Acenaphthene	µg/L	50	100	EPA Method 8270
Acenaphthylene	µg/L	50	100	EPA Method 8270
Acetone	µg/L	50	100	EPA Method 8240
Acetonitrile (Methyl cyanide)	µg/L	500	1,000	EPA Method 8240
Acetophenone	µg/L	50	100	EPA Method 8270
2-Acetylaminofluorene	µg/L	50	100	EPA Method 8270
Acrolein	µg/L	100	200	EPA Method 8240
Acrylonitrile	µg/L	100	200	EPA Method 8240
Aldrin	µg/L	2.5	5	EPA Method 8080
Alkalinity (as CaCO ₃)		No flag	No flag	Set by EPD/EMS
Allyl chloride	µg/L	250	500	EPA Method 8240
Aluminum	µg/L	100	200	EPA Method 6010
Americium-241	pCi/L	3.17	6.34	Proposed DWS (EPA, 1991d)
Americium-243	pCi/L	3.19	6.37	Proposed DWS (EPA, 1991d)
4-Aminobiphenyl	µg/L	50	100	EPA Method 8270
Ammonia	µg/L	500	1,000	APHA Method 417B
Ammonia nitrogen	µg/L	50	100	EPA Method 350.1
Aniline	µg/L	50	100	EPA Method 8270
Anthracene	µg/L	50	100	EPA Method 8270
Antimony	µg/L	2.5	5	Proposed DWS (EPA, 1990a)
Antimony-125	pCi/L	150	300	Final DWS (EPA, 1977)
Aramite	µg/L	50	100	EPA Method 8270
Arsenic	µg/L	25	50	Final DWS (EPA, 1990b)

Analyte	Unit	Flag 1	Flag 2	Source
Azobenzene	µg/L	50	100	EPA Method 625
Barium	µg/L	1,000	2,000	Final DWS (EPA, 1991c)
Barium-140	pCi/L	45	90	Final DWS (EPA, 1977)
Benzene	µg/L	2.5	5	Final DWS (EPA, 1990b)
alpha-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
beta-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
delta-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
Benzidine	µg/L	250	500	EPA Method 8270
Benzo[a]anthracene	µg/L	0.05	0.1	Proposed DWS (EPA, 1990a)
Benzo[b]fluoranthene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990a)
Benzo[k]fluoranthene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990a)
Benzoic acid	µg/L	250	500	EPA Method 8270
Benzo[g,h,i]perylene	µg/L	50	100	EPA Method 8270
Benzo[a]pyrene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990a)
1,4-Benzquinone	µg/L	50	100	EPA Method 8270
Benzyl alcohol	µg/L	100	200	EPA Method 8270
Beryllium	µg/L	0.5	1	Proposed DWS (EPA, 1990a)
Beryllium-7	pCi/L	3,000	6,000	Final DWS (EPA, 1977)
Bis(2-chloroethoxy) methane	µg/L	50	100	EPA Method 8270
Bis(2-chloroethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-chloroisopropyl) ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl)ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl-ethyl)ether	µg/L	50	100	EPA Method 8270
Bis(2-ethylhexyl) phthalate		No flag	No flag	Set by EPD/EMS
Bromide	µg/L	5,000	10,000	EPA Method 300.0
Bromodichloromethane	µg/L	50	100	Final DWS (EPA, 1991c)
Bromoform	µg/L	50	100	Final DWS (EPA, 1991c)
Bromomethane (Methyl bromide)	µg/L	5	10	EPA Method 8240
4-Bromophenyl phenyl ether	µg/L	50	100	EPA Method 8270
2-sec-Butyl-4,6-dinitrophenol	µg/L	3.5	7	Proposed DWS (EPA, 1990a)
Butylbenzyl phthalate		No flag	No flag	Set by EPD/EMS
Cadmium	µg/L	5	10	Final DWS (EPA, 1990c)
Calcium		No flag	No flag	Set by EPD/EMS
Carbon disulfide	µg/L	5	10	EPA Method 8240
Carbon tetrachloride	µg/L	2.5	5	Final DWS (EPA, 1990b)
Carbon 12-labeled 2,3,7,8-TCDD	µg/L	0.00225	0.0045	EPA Method 8280
Carbon 12-labeled 2,3,7,8-TCDF	µg/L	0.002	0.004	EPA Method 8280
Carbon-14	pCi/L	1,000	2,000	Final DWS (EPA, 1977)
Carbonate		No flag	No flag	Set by EPD/EMS
Cerium-141	pCi/L	150	300	Final DWS (EPA, 1977)
Cerium-144	pCi/L	131	261	Proposed DWS (EPA, 1991d)
Cesium-134	pCi/L	40.7	81.3	Set by EPD/EMS ^a
Cesium-137	pCi/L	100	200	Final DWS (EPA, 1977)
Chlordane	µg/L	1	2	Final DWS (EPA, 1991a)
Chloride	µg/L	125,000	250,000	Secondary DWS (EPA, 1991a)
4-Chloroaniline	µg/L	50	100	EPA Method 8270
Chlorobenzene	µg/L	5	10	EPA Method 8240
Chlorobenzilate	µg/L	50	100	EPA Method 8270
Chloroethane	µg/L	5	10	EPA Method 8240
Chloroethene (Vinyl chloride)	µg/L	1	2	Final DWS (EPA, 1990b)
Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
2-Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
Chloroform	µg/L	50	100	Final DWS (EPA, 1991c)
para-Chloro-meta-cresol	µg/L	50	100	EPA Method 8270
Chloromethane (Methyl chloride)	µg/L	5	10	EPA Method 8240
2-Chloronaphthalene	µg/L	50	100	EPA Method 8240
2-Chlorophenol	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
4-Chlorophenyl phenyl ether	µg/L	50	100	EPA Method 8270
Chloroprene	µg/L	1,000	2,000	EPA Method 8240
Chromium	µg/L	50	100	Final DWS (EPA, 1991a)
Chromium-51	pCi/L	3,000	6,000	Final DWS (EPA, 1977)
Chrysene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990a)
Cobalt	µg/L	20	40	EPA Method 6010
Cobalt-58	pCi/L	4,500	9,000	Final DWS (EPA, 1977)
Cobalt-60	pCi/L	50	100	Final DWS (EPA, 1977)
Color		No flag	No flag	Set by EPD/EMS
Copper	µg/L	650	1,300	Final DWS (EPA, 1991b)
Corrosivity		No flag	No flag	Set by EPD/EMS
m-Cresol (3-Methylphenol)	µg/L	50	100	EPA Method 8270
o-Cresol (2-Methylphenol)	µg/L	50	100	EPA Method 8270
p-Cresol (4-Methylphenol)	µg/L	50	100	EPA Method 8270
Curium-242	pCi/L	66.5	133	Proposed DWS (EPA, 1991d)
Curium-243	pCi/L	4.15	8.3	Proposed DWS (EPA, 1991d)
Curium-244	pCi/L	4.92	9.84	Proposed DWS (EPA, 1991d)
Curium-246	pCi/L	3.14	6.27	Proposed DWS (EPA, 1991d)
Cyanide	µg/L	100	200	Proposed DWS (EPA, 1990a)
p,p'-DDD	µg/L	2.5	5	EPA Method 8080
p,p'-DDE	µg/L	2.5	5	EPA Method 8080
p,p'-DDT	µg/L	2.5	5	EPA Method 8080
Di-n-butyl phthalate		No flag	No flag	Set by EPD/EMS
Di-n-octyl phthalate		No flag	No flag	Set by EPD/EMS
Diallate	µg/L	50	100	EPA Method 8270
Dibenz[a,h]anthracene	µg/L	0.15	0.3	Proposed DWS (EPA, 1990a)
Dibenzofuran	µg/L	50	100	EPA Method 8270
Dibromochloromethane	µg/L	50	100	Final DWS (EPA, 1991c)
Dibromochloropropane	µg/L	0.1	0.2	Final DWS (EPA, 1991a)
1,2-Dibromo-3-chloropropane	µg/L	250	500	EPA Method 8240
1,2-Dibromoethane	µg/L	100	200	EPA Method 8240
Dibromomethane				
(Methylene bromide)	µg/L	5	10	EPA Method 8240
1,2-Dichlorobenzene	µg/L	50	100	EPA Method 8270
1,3-Dichlorobenzene	µg/L	50	100	EPA Method 8270
1,4-Dichlorobenzene	µg/L	37.5	75	Final DWS (EPA, 1990b)
3,3'-Dichlorobenzidine	µg/L	50	100	EPA Method 8270
trans-1,4-Dichloro-2-butene	µg/L	150	300	EPA Method 8240
Dichlorodifluoromethane	µg/L	5	10	EPA Method 8240
1,1-Dichloroethane	µg/L	5	10	EPA Method 8240
1,2-Dichloroethane	µg/L	2.5	5	Final DWS (EPA, 1990b)
cis-1,2-Dichloroethene	µg/L	35	70	Final DWS (EPA, 1991a)
1,1-Dichloroethylene	µg/L	3.5	7	Final DWS (EPA, 1990b)
1,2-Dichloroethylene	µg/L	25	50	EPA Method 8240
trans-1,2-Dichloroethylene	µg/L	50	100	Final DWS (EPA, 1991a)
Dichloromethane				
(Methylene chloride)		No flag	No flag	Set by EPD/EMS
2,4-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,6-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,4-Dichlorophenoxyacetic acid	µg/L	50	100	Final DWS (EPA, 1990b)
1,2-Dichloropropane	µg/L	2.5	5	Final DWS (EPA, 1991a)
cis-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
trans-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
Dieldrin	µg/L	2.5	5	EPA Method 8080
Diethyl phthalate		No flag	No flag	Set by EPD/EMS
Dimethoate	µg/L	50	100	EPA Method 8270
p-Dimethylaminoazobenzene	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
p-(Dimethylamino)ethylbenzene	µg/L	50	100	EPA Method 8270
7,12-Dimethylbenz[a]anthracene	µg/L	50	100	EPA Method 8270
3,3'-Dimethylbenzidine	µg/L	50	100	EPA Method 8270
a,a-Dimethylphenethylamine	µg/L	50	100	EPA Method 8270
2,4-Dimethyl phenol	µg/L	50	100	EPA Method 8270
Dimethyl phthalate		No flag	No flag	Set by EPD/EMS
1,3-Dinitrobenzene	µg/L	50	100	EPA Method 8270
4,6-Dinitro-ortho-cresol	µg/L	250	500	EPA Method 8270
2,4-Dinitrophenol	µg/L	250	500	EPA Method 8270
2,4-Dinitrotoluene	µg/L	50	100	EPA Method 8270
2,6-Dinitrotoluene	µg/L	50	100	EPA Method 8270
1,4-Dioxane	µg/L	50	100	EPA Method 8270
Diphenylamine	µg/L	50	100	EPA Method 8270
1,2-Diphenylhydrazine	µg/L	50	100	EPA Method 8270
Dissolved organic carbon	µg/L	5,000	10,000	EPA Method 9060
Disulfoton	µg/L	50	100	EPA Method 8270
Eh		No flag	No flag	Set by EPD/EMS
alpha-Endosulfan	µg/L	50	100	EPA Method 8270
beta-Endosulfan	µg/L	50	100	EPA Method 8270
Endosulfan I	µg/L	2.5	5	EPA Method 8080
Endosulfan II	µg/L	2.5	5	EPA Method 8080
Endosulfan sulfate	µg/L	2.5	5	EPA Method 8080
Endrin	µg/L	0.1	0.2	Final DWS (EPA, 1990b)
Endrin aldehyde	µg/L	2.5	5	EPA Method 8080
Endrin ketone		No flag	No flag	Set by EPD/EMS
Ethyl methacrylate	µg/L	50	100	EPA Method 8270
Ethyl methanesulfonate	µg/L	50	100	EPA Method 8270
Ethylbenzene	µg/L	350	700	Final DWS (EPA, 1991a)
Europium-154	pCi/L	100	200	Final DWS (EPA, 1977)
Europium-155	pCi/L	300	600	Final DWS (EPA, 1977)
Famphur	µg/L	50	100	EPA Method 8270
Fluoranthene	µg/L	50	100	EPA Method 8270
Fluorene	µg/L	50	100	EPA Method 8270
Fluoride	µg/L	2,000	4,000	Final DWS (EPA, 1991c)
Gross alpha	pCi/L	7.5	15	Final DWS (EPA, 1990b)
Heptachlor	µg/L	0.2	0.4	Final DWS (EPA, 1991a)
Heptachlor epoxide	µg/L	0.1	0.2	Final DWS (EPA, 1991a)
Heptachlorodibenzo-p-dioxin isomers	µg/L	0.00325	0.0065	EPA Method 8280
1,2,3,4,6,7,8-Heptachlorodibenzo-p- dioxin	µg/L	0.00325	0.0065	EPA Method 8280
Heptachlorodibenzo-p-furan isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,6,7,8-Heptachlorodibenzo-p- furan	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorobenzene	µg/L	0.5	1	Proposed DWS (EPA, 1990a)
Hexachlorobutadiene	µg/L	50	100	EPA Method 8270
Hexachlorocyclopentadiene	µg/L	25	50	Proposed DWS (EPA, 1990a)
Hexachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,7,8-Hexachlorodibenzo-p- dioxin	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,2,3,4,7,8-Hexachlorodibenzo-p- furan	µg/L	0.002	0.004	EPA Method 8280
Hexachloroethane	µg/L	50	100	EPA Method 8270
Hexachlorophene	µg/L	250	500	EPA Method 8270
Hexachloropropene	µg/L	50	100	EPA Method 8270

<u>Analyte</u>	<u>Unit</u>	<u>Flag 1</u>	<u>Flag 2</u>	<u>Source</u>
2-Hexanone	µg/L	100	200	EPA Method 8240
Indeno[1,2,3-c,d]pyrene	µg/L	50	100	EPA Method 8270
Iodine	µg/L	500	1,000	EPA Method 415
Iodine-129	pCi/L	0.5	1	Final DWS (EPA, 1977)
Iodine-131	pCi/L	1.5	3	Final DWS (EPA, 1977)
Iodomethane (Methyl iodide)	µg/L	75	150	EPA Method 8240
Iron	µg/L	150	300	Secondary DWS (EPA, 1991a)
Iron-55	pCi/L	1,000	2,000	Final DWS (EPA, 1977)
Iron-59	pCi/L	100	200	Final DWS (EPA, 1977)
Isobutyl alcohol	µg/L	500	1,000	EPA Method 8240
Isodrin	µg/L	50	100	EPA Method 8270
Isophorone	µg/L	50	100	EPA Method 8270
Isosafrole	µg/L	50	100	EPA Method 8270
Kepone	µg/L	50	100	EPA Method 8270
Lanthanum-140	pCi/L	30	60	Final DWS (EPA, 1977)
Lead	µg/L	7.5	15	Final DWS (EPA, 1991b)
Lindane	µg/L	2	4	Final DWS (EPA, 1990b)
Lithium	µg/L	25	50	EPA Method 6010
Magnesium		No flag	No flag	Set by EPD/EMS
Manganese	µg/L	25	50	Secondary DWS (EPA, 1991a)
Manganese-54	pCi/L	150	300	Final DWS (EPA, 1977)
Mercury	µg/L	1	2	Final DWS (EPA, 1991a)
Methacrylonitrile	µg/L	250	500	EPA Method 8240
Methapyrilene	µg/L	50	100	EPA Method 8270
Methoxychlor	µg/L	50	100	Final DWS (EPA, 1990b)
3-Methylcholanthrene	µg/L	50	100	EPA Method 8270
2-Methyl-4,6-dinitrophenol	µg/L	250	500	EPA Method 8270
Methyl ethyl ketone		No flag	No flag	Set by EPD/EMS
Methyl isobutyl ketone		No flag	No flag	Set by EPD/EMS
Methyl methacrylate	µg/L	50	100	EPA Method 8270
Methyl methanesulfonate	µg/L	50	100	EPA Method 8270
2-Methylnaphthalene	µg/L	50	100	EPA Method 8270
Molybdenum	µg/L	250	500	EPA Method 6010
Naphthalene	µg/L	50	100	EPA Method 8270
1,4-Naphthoquinone	µg/L	50	100	EPA Method 8270
1-Naphthylamine	µg/L	50	100	EPA Method 8270
2-Naphthylamine	µg/L	50	100	EPA Method 8270
Neptunium-237	pCi/L	3.53	7.06	Proposed DWS (EPA, 1991d)
Nickel	µg/L	50	100	Proposed DWS (EPA, 1990a)
Nickel-59	pCi/L	150	300	Final DWS (EPA, 1977)
Nickel-63	pCi/L	25	50	Final DWS (EPA, 1977)
Niobium-95	pCi/L	150	300	Final DWS (EPA, 1977)
Nitrate as nitrogen	µg/L	5,000	10,000	Final DWS (EPA, 1991a)
Nitrite as nitrogen	µg/L	500	1,000	Final DWS (EPA, 1991a)
2-Nitroaniline	µg/L	50	100	EPA Method 8270
3-Nitroaniline	µg/L	50	100	EPA Method 8270
4-Nitroaniline	µg/L	50	100	EPA Method 8270
Nitrobenzene	µg/L	50	100	EPA Method 8270
Nitrogen by Kjeldahl method	µg/L	500	1,000	EPA Method 351.2
2-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitroquinoline-1-oxide	µg/L	50	100	EPA Method 8270
N-Nitrosodi-n-butylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodimethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiphenylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodi-propylamine	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
N-Nitrosomethylethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosomorpholine	µg/L	50	100	EPA Method 8270
N-Nitrosopiperidine	µg/L	50	100	EPA Method 8270
N-Nitrosopyrrolidine	µg/L	50	100	EPA Method 8270
5-Nitro-o-toluidine	µg/L	50	100	EPA Method 8270
Nonvolatile beta	pCi/L	25	50	Proposed DWS (EPA, 1986)
Octachlorodibenzo-p-dioxin isomers	µg/L	0.005	0.01	EPA Method 8280
Octachlorodibenzo-p-furan isomers	µg/L	0.005	0.01	EPA Method 8280
Odor		No flag	No flag	Set by EPD/EMS
Oil & Grease	µg/L	5,000	10,000	EPA Method 413.1
Parathion	µg/L	2.5	5	EPA Method 8080
Parathion methyl	µg/L	2.5	5	EPA Method 8080
PCB 1016	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
PCB 1221	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
PCB 1232	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
PCB 1242	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
PCB 1248	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
PCB 1254	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
PCB 1260	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
PCB 1262	µg/L	0.25	0.5	Final DWS (EPA, 1991a)
Pentachlorobenzene	µg/L	50	100	EPA Method 8270
Pentachlorodibenzo-p-dioxin isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-Pentachlorodibenzo-p-dioxin	µg/L	0.00275	0.0055	EPA Method 8280
Pentachlorodibenzo-p-furan isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-Pentachlorodibenzo-p-furan	µg/L	0.00275	0.0055	EPA Method 8280
Pentachloroethane	µg/L	50	100	EPA Method 8270
Pentachloronitrobenzene	µg/L	50	100	EPA Method 8270
Pentachlorophenol	µg/L	0.5	1	Final DWS (EPA, 1991c)
pH	pH	8	10	Set by EPD/EMS
pH	pH	4	3	Set by EPD/EMS
Phenacetin	µg/L	50	100	EPA Method 8270
Phenanthrene	µg/L	50	100	EPA Method 8270
Phenol	µg/L	50	100	EPA Method 8270
Phenols	µg/L	25	50	EPA Method 420.2
p-Phenylenediamine	µg/L	50	100	EPA Method 8270
Phorate	µg/L	2.5	5	EPA Method 8080
2-Picoline	µg/L	50	100	EPA Method 8270
Plutonium-238	pCi/L	3.51	7.02	Proposed DWS (EPA, 1991d)
Plutonium-239	pCi/L	31.1	62.1	Proposed DWS (EPA, 1991d)
Plutonium-239/240	pCi/L	31.1	62.1	Proposed DWS (EPA, 1991d) ^a
Plutonium-240	pCi/L	31.1	62.2	Proposed DWS (EPA, 1991d)
Plutonium-241		No flag	No flag	Set by EPD/EMS
Plutonium-242	pCi/L	32.7	65.4	Proposed DWS (EPA, 1991d)
Potassium		No flag	No flag	Set by EPD/EMS
Potassium-40	pCi/L	150	300	Proposed DWS (EPA, 1986)
Pronamid	µg/L	50	100	EPA Method 8270
Propionitrile	µg/L	1,000	2,000	EPA Method 8240
Pyrene	µg/L	50	100	EPA Method 8270
Pyridine	µg/L	50	100	EPA Method 8270
Radium-226	pCi/L	7.85	15.7	Proposed DWS (EPA, 1991d)
Radium-228	pCi/L	3.93	7.85	Proposed DWS (EPA, 1991d)
Radon-222	pCi/L	150	300	Proposed DWS (EPA, 1991d)
Ruthenium-103	pCi/L	100	200	Final DWS (EPA, 1977)
Ruthenium-106	pCi/L	15	30	Final DWS (EPA, 1977)

Analyte	Unit	Flag 1	Flag 2	Source
Safrole	µg/L	50	100	EPA Method 8270
Selenium	µg/L	25	50	Final DWS (EPA, 1991a)
Silica		No flag	No flag	Set by EPD/EMS
Silver	µg/L	25	50	Final DWS (EPA, 1990b)
Sodium		No flag	No flag	Set by EPD/EMS
Sodium-22	pCi/L	233	466	Proposed DWS (EPA, 1991d)
Specific conductance	µS/cm	250	500	Set by EPD/EMS
Strontium-89	pCi/L	10	20	Final DWS (EPA, 1977)
Strontium-90	pCi/L	4	8	Final DWS (EPA, 1990b)
Styrene	µg/L	50	100	Final DWS (EPA, 1991a)
Sulfate	µg/L	200,000	400,000	Proposed DWS (EPA, 1990a)
Sulfide	µg/L	5,000	10,000	EPA Method 9030
Sulfotep	µg/L	50	100	EPA Method 8270
Surfactants		No flag	No flag	Set by EPD/EMS
Technetium-99	pCi/L	450	900	Final DWS (EPA, 1977)
1,2,4,5-Tetrachlorobenzene	µg/L	50	100	EPA Method 8270
Tetrachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
Tetrachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,1,1,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
1,1,2,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
Tetrachloroethylene	µg/L	2.5	5	Final DWS (EPA, 1991a)
2,3,4,6-Tetrachlorophenol	µg/L	50	100	EPA Method 8270
Tetraethyl dithiopyrophosphate	µg/L	50	100	EPA Method 8270
Thallium	µg/L	0.5	1	Proposed DWS (EPA, 1990a)
Thionazin	µg/L	50	100	EPA Method 8270
Thorium-228	pCi/L	62.5	125	Proposed DWS (EPA, 1991d)
Thorium-230	pCi/L	39.6	79.2	Proposed DWS (EPA, 1991d)
Thorium-232	pCi/L	44	88	Proposed DWS (EPA, 1991d)
Thorium-234	pCi/L	200	401	Proposed DWS (EPA, 1991d)
Tin	µg/L	10	20	EPA Method 282.2
Tin-113	pCi/L	150	300	Final DWS (EPA, 1977)
Toluene	µg/L	500	1,000	Final DWS (EPA, 1991a)
o-Toluidine	µg/L	50	100	EPA Method 8270
Total carbon	µg/L	5,000	10,000	EPA Method 9060
Total dissolved solids		No flag	No flag	Set by EPD/EMS
Total hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total inorganic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic halogens	µg/L	25	50	EPA Method 9020
Total organic nitrogen	µg/L	500	1,000	EPA Method 420
Total petroleum hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total phosphates (as P)		No flag	No flag	Set by EPD/EMS
Total phosphorus		No flag	No flag	Set by EPD/EMS
Total radium	pCi/L	2.5	5	Final DWS (EPA, 1990b)
Total silica	µg/L	500	1,000	EPA Method 6010
Toxaphene	µg/L	1.5	3	Final DWS (EPA, 1991a)
2,4,5-TP (Silvex)	µg/L	5	10	Final DWS (EPA, 1990b)
Tributyl phosphate	µg/L	50	100	EPA Method 8270
1,2,4-Trichlorobenzene	µg/L	4.5	9	Proposed DWS (EPA, 1990a)
1,1,1-Trichloroethane	µg/L	100	200	Final DWS (EPA, 1990b)
1,1,2-Trichloroethane	µg/L	2.5	5	Proposed DWS (EPA, 1990a)
Trichloroethylene	µg/L	2.5	5	Final DWS (EPA, 1990b)
Trichlorofluoromethane	µg/L	5	10	EPA Method 8240
2,4,5-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,6-Trichlorophenol	µg/L	50	100	EPA Method 8270

<u>Analyte</u>	<u>Unit</u>	<u>Flag 1</u>	<u>Flag 2</u>	<u>Source</u>
2,4,5-Trichlorophenoxyacetic acid	µg/L	2.5	5	EPA Method 8150
1,2,3-Trichloropropane	µg/L	5	10	EPA Method 8240
O,O,O-Triethyl phosphorothioate	µg/L	50	100	EPA Method 8270
1,3,5-Trinitrobenzene	µg/L	50	100	EPA Method 8270
Tritium	pCi/mL	10	20	Final DWS (EPA, 1990b)
Turbidity		No flag	No flag	Set by EPD/EMS
Uranium	µg/L	10	20	Proposed DWS (EPA, 1991d)
Uranium alpha activity	pCi/L	15	30	Proposed DWS (EPA, 1991d)
Uranium-234	pCi/L	6.95	13.9	Proposed DWS (EPA, 1991d)
Uranium-235	pCi/L	7.25	14.5	Proposed DWS (EPA, 1991d)
Uranium-238	pCi/L	7.3	14.6	Proposed DWS (EPA, 1991d)
Vanadium	µg/L	50	100	EPA Method 6010
Vinyl acetate	µg/L	5	10	EPA Method 8240
Xylenes	µg/L	5,000	10,000	Final DWS (EPA, 1991a)
Zinc	µg/L	2,500	5,000	Secondary DWS (EPA, 1991a)
Zinc-65	pCi/L	150	300	Final DWS (EPA, 1977)
Zirconium-95	pCi/L	100	200	Final DWS (EPA, 1977)
Zirconium/Niobium-95	pCi/L	100	200	Final DWS (EPA, 1977) ^a

^a When radionuclide analyses are combined, the lower DWS of the two isotopes is used for flagging.

References

APHA (American Public Health Association, American Water Works Association, and Water Pollution Control Federation), 1985. **Standard Methods for the Examination of Water and Wastewater**, 16th edition. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**, EPA-570/9-76-003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. *Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides (Proposed)*. **Federal Register**, September 30, 1986, pp. 34836–34862. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990a. *National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals (Proposed Rule)*. **Federal Register**, July 25, 1990, pp. 30369–30448. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990b. *National Primary Drinking Water Regulations*. 40, **Code of Federal Regulations**, Part 141, pp. 553–638. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991a. *National Primary Drinking Water Regulations; Final Rule*. **Federal Register**, January 30, 1991, pp. 3592–3597. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991b. *Maximum Contaminant Level Goals and National Primary Drinking Water Regulations for Lead and Copper; Final Rule*. **Federal Register**, June 7, 1991, p. 26477. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991c. *National Primary Drinking Water Regulations; Final Rule*. **Federal Register**, July 1, 1991, pp. 30274–30280. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991d. *National Primary Drinking Water Regulations; Radionuclides; Proposed Rule*. **Federal Register**, July 18, 1991, pp. 33120–33121. Washington, DC.

Appendix C – Figures

Figure 1. Location of the K-Area Acid/Caustic Basin at the Savannah River Site

Figure 2. Location of Groundwater Monitoring Wells at the K-Area Acid/Caustic Basin

Figure 3. Potentiometric Surface Map of the Water Table at the K-Area Acid/Caustic Basin

Appendix D – Groundwater Monitoring Results Tables

Key to Reading the Tables

Abbreviations which may appear in the tabular data:

B = analyte detected in associated blank as well as in sample
D = drinking water standard
E = exponential notation (e.g., $1.1\text{E}-09 \mu\text{Ci/mL} = 1.1 \times 10^{-9} \mu\text{Ci/mL} = 0.0000000011 \mu\text{Ci/mL}$)
EM = EPD/EMS Laboratory
GE = General Engineering
H = holding time
1,2,3,4,6,7,8-HPCDD = 1,2,3,4,6,7,8-heptachlorodibenzo-p-dioxin
1,2,3,4,6,7,8-HPCDF = 1,2,3,4,6,7,8-heptachlorodibenzo-p-furan
1,2,3,4,7,8-HXCDD = 1,2,3,4,7,8-hexachlorodibenzo-p-dioxin
1,2,3,4,7,8-HXCDF = 1,2,3,4,7,8-heptachlorodibenzo-p-furan
J = estimated value
Lindane = gamma-benzene hexachloride
MA = M-Area Laboratory
msl = mean sea level
NTU = turbidity units
pH = pH units
pCi/L = picocuries per liter
pCi/mL = picocuries per milliliter
PVC = polyvinyl chloride
TOC = top of casing
Sp. = specific
 $\mu\text{g/L}$ = micrograms per liter
 $\mu\text{S/cm}$ = microsiemens per centimeter

Holding Times

Standard analytical methods include a limit, called holding time, on the maximum elapsed time between sample collection and extraction or analysis by the laboratory. In the data tables, a large dot (●) in the H (holding time) column indicates that holding time was exceeded. Analyses performed beyond holding time may not yield valid results.

EPA method 150.1 for pH analyses requires "immediate" analysis. During fourth quarter, this was generally interpreted as allowing no more than 24 hours between sample collection in the field and analysis in the laboratory. Due to time involved in shipping, most laboratory pH analyses are performed out of holding time.

Laboratory-initiated procedures for reducing the number of other analyses performed out of holding include subcontracting analyses when difficulties with equipment, personnel, or work load would prevent timely analyses. Beginning fourth quarter 1991, SRS reduces the compensation to laboratories for analyses performed out of holding time.

Table 1. Constituents Exceeding the Primary Drinking Water Standards for 1991

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>Quarter 1</u>	<u>Quarter 2</u>	<u>Quarter 3</u>	<u>Quarter 4</u>
KAC 7	Lead	µg/L	76	-	-	-

Note: The PDWS for listed constituents may have been altered between the second and third quarters of 1991 as the standards were updated. Consult the second and third quarter reports for details on the appropriate standard for the period.

Table 2. Constituents Exceeding Other Flagging Criteria

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>Quarter 4</u>	<u>Flag Exceeded</u>
KAC 1	Specific conductance ^a	µS/cm	310	1
	Specific conductance ^a	µS/cm	295	1
	Total organic halogens	µg/L	35	1
KAC 2	Specific conductance	µS/cm	350	1
KAC 7	Iron	µg/L	1,390	2
	Total organic carbon	µg/L	5,000	1
	Total organic halogens	µg/L	55	2

^a Duplicate samples.

Table 3. Groundwater Monitoring Results for Individual Wells**WELL KAC 1**

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53167.0 E42614.8	33.212893 °N 81.657866 °W	229.0-199.0 ft msl	266.0 ft msl	4" PVC	Water Table

MEASUREMENTS CONDUCTED IN THE FIELD

Sample date: 11/18/91

Time: 12:40

Depth to water: 44.17 ft (13.46 m) below TOC

pH: 5.7

Water elevation: 221.83 ft (67.61 m) msl

Alkalinity: 13 mg/L

Sp. conductance: 313 μ S/cm

Water temperature: 18.6°C

Water evacuated before sampling: 60 gal

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	6.0	pH	0	GE
•		pH	6.0	pH	0	GE
		Specific conductance	310	μ S/cm	1	GE
		Specific conductance	295	μ S/cm	1	GE
		Turbidity	2.8	NTU	0	GE
		Turbidity	3.3	NTU	0	GE
		Acenaphthene	<10	μ g/L	0	GE
		Acenaphthene	<10	μ g/L	0	GE
		Acenaphthylene	<10	μ g/L	0	GE
		Acenaphthylene	<10	μ g/L	0	GE
		Aldrin	<10	μ g/L	0	GE
		Aldrin	<10	μ g/L	0	GE
		Aluminum	<20	μ g/L	0	GE
		Aluminum	<20	μ g/L	0	GE
		Anthracene	<10	μ g/L	0	GE
		Anthracene	<10	μ g/L	0	GE
		Antimony	<2.0	μ g/L	0	GE
		Antimony	2.4	μ g/L	0	GE
		Arsenic	<2.0	μ g/L	0	GE
		Arsenic	<2.0	μ g/L	0	GE
		Barium	<3.0	μ g/L	0	GE
		Barium	<3.0	μ g/L	0	GE
		Benzene	<1.0	μ g/L	0	GE
		Benzene	<1.0	μ g/L	0	GE
		alpha-Benzene hexachloride	<10	μ g/L	0	GE
		alpha-Benzene hexachloride	<10	μ g/L	0	GE
		beta-Benzene hexachloride	<10	μ g/L	0	GE
		beta-Benzene hexachloride	<10	μ g/L	0	GE
		delta-Benzene hexachloride	<10	μ g/L	0	GE
		delta-Benzene hexachloride	<10	μ g/L	0	GE
		Benzidine	<10	μ g/L	0	GE
		Benzidine	<10	μ g/L	0	GE
		Benzo[a]anthracene	<10	μ g/L	0	GE
		Benzo[a]anthracene	<10	μ g/L	0	GE
		Benzo[a]pyrene	<10	μ g/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 1 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Benzo[a]pyrene	< 10	µg/L	0	GE
		Benzo[b]fluoranthene	< 10	µg/L	0	GE
		Benzo[b]fluoranthene	< 10	µg/L	0	GE
		Benzo[g,h,i]perylene	< 10	µg/L	0	GE
		Benzo[g,h,i]perylene	< 10	µg/L	0	GE
		Benzo[k]fluoranthene	< 10	µg/L	0	GE
		Benzo[k]fluoranthene	< 10	µg/L	0	GE
		Beryllium	< 3.0	µg/L	0	GE
		Beryllium	< 3.0	µg/L	0	GE
		Bis(2-chloroethoxy) methane	< 10	µg/L	0	GE
		Bis(2-chloroethoxy) methane	< 10	µg/L	0	GE
		Bis(2-chloroethyl) ether	< 10	µg/L	0	GE
		Bis(2-chloroethyl) ether	< 10	µg/L	0	GE
		Bis(2-chloroisopropyl) ether	< 10	µg/L	0	GE
		Bis(2-chloroisopropyl) ether	< 10	µg/L	0	GE
		Bis(2-ethylhexyl) phthalate	< 10	µg/L	0	GE
		Bis(2-ethylhexyl) phthalate	< 10	µg/L	0	GE
		Bromide	< 1,000	µg/L	0	GE
		Bromide	< 1,000	µg/L	0	GE
		Bromide	< 1,000	µg/L	0	GE
		Bromodichloromethane	< 1.0	µg/L	0	GE
		Bromodichloromethane	< 1.0	µg/L	0	GE
		Bromoform	< 1.0	µg/L	0	GE
		Bromoform	< 1.0	µg/L	0	GE
		Bromomethane (Methyl bromide)	< 1.0	µg/L	0	GE
		Bromomethane (Methyl bromide)	< 1.0	µg/L	0	GE
		4-Bromophenyl phenyl ether	< 10	µg/L	0	GE
		4-Bromophenyl phenyl ether	< 10	µg/L	0	GE
		Butylbenzyl phthalate	< 10	µg/L	0	GE
		Butylbenzyl phthalate	< 10	µg/L	0	GE
		Cadmium	< 2.0	µg/L	0	GE
		Cadmium	< 2.0	µg/L	0	GE
		Calcium	165	µg/L	0	GE
		Calcium	162	µg/L	0	GE
		Carbon tetrachloride	< 1.0	µg/L	0	GE
		Carbon tetrachloride	< 1.0	µg/L	0	GE
		Chlordane	< 10	µg/L	0	GE
		Chlordane	< 10	µg/L	0	GE
		Chloride	13,100	µg/L	0	GE
		Chloride	12,600	µg/L	0	GE
		para-Chloro-meta-cresol	< 10	µg/L	0	GE
		para-Chloro-meta-cresol	< 10	µg/L	0	GE
		Chlorobenzene	< 1.0	µg/L	0	GE
		Chlorobenzene	< 1.0	µg/L	0	GE
		Chloroethane	< 1.0	µg/L	0	GE
		Chloroethane	< 1.0	µg/L	0	GE
		Chloroethene (Vinyl chloride)	< 1.0	µg/L	0	GE
		Chloroethene (Vinyl chloride)	< 1.0	µg/L	0	GE
		2-Chloroethyl vinyl ether	< 1.0	µg/L	0	GE
		2-Chloroethyl vinyl ether	< 1.0	µg/L	0	GE
		Chloroform	< 1.0	µg/L	0	GE
		Chloroform	< 1.0	µg/L	0	GE
		Chloromethane (Methyl chloride)	< 1.0	µg/L	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 1 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Chloromethane (Methyl chloride)	<1.0	µg/L	0	GE
		2-Chloronaphthalene	<10	µg/L	0	GE
		2-Chloronaphthalene	<10	µg/L	0	GE
		2-Chlorophenol	<10	µg/L	0	GE
		2-Chlorophenol	<10	µg/L	0	GE
		4-Chlorophenyl phenyl ether	<10	µg/L	0	GE
		4-Chlorophenyl phenyl ether	<10	µg/L	0	GE
		Chromium	<4.0	µg/L	0	GE
		Chromium	<4.0	µg/L	0	GE
		Chrysene	<10	µg/L	0	GE
		Chrysene	<10	µg/L	0	GE
		Cobalt	<4.0	µg/L	0	GE
		Cobalt	<4.0	µg/L	0	GE
		Copper	14	µg/L	0	GE
		Copper	15	µg/L	0	GE
		Cyanide	<5.0	µg/L	0	GE
		Cyanide	<5.0	µg/L	0	GE
		p,p'-DDD	<10	µg/L	0	GE
		p,p'-DDD	<10	µg/L	0	GE
		p,p'-DDE	<10	µg/L	0	GE
		p,p'-DDE	<10	µg/L	0	GE
		p,p'-DDT	<10	µg/L	0	GE
		p,p'-DDT	<10	µg/L	0	GE
		Di-n-butyl phthalate	<10	µg/L	0	GE
		Di-n-butyl phthalate	<10	µg/L	0	GE
		Di-n-octyl phthalate	<10	µg/L	0	GE
		Di-n-octyl phthalate	<10	µg/L	0	GE
		Dibenz[a,h]anthracene	<10	µg/L	0	GE
		Dibenz[a,h]anthracene	<10	µg/L	0	GE
		Dibromochloromethane	<1.0	µg/L	0	GE
		Dibromochloromethane	<1.0	µg/L	0	GE
		3,3'-Dichlorobenzidine	<10	µg/L	0	GE
		3,3'-Dichlorobenzidine	<10	µg/L	0	GE
		1,1-Dichloroethane	<1.0	µg/L	0	GE
		1,1-Dichloroethane	<1.0	µg/L	0	GE
		1,2-Dichloroethane	<1.0	µg/L	0	GE
		1,2-Dichloroethane	<1.0	µg/L	0	GE
		1,1-Dichloroethylene	<1.0	µg/L	0	GE
		1,1-Dichloroethylene	<1.0	µg/L	0	GE
		trans-1,2-Dichloroethylene	<1.0	µg/L	0	GE
		trans-1,2-Dichloroethylene	<1.0	µg/L	0	GE
		Dichloromethane (Methylene chloride)	1.0	µg/L	0	GE
		Dichloromethane (Methylene chloride)	1.0	µg/L	0	GE
		2,4-Dichlorophenol	<10	µg/L	0	GE
		2,4-Dichlorophenol	<10	µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30	µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30	µg/L	0	GE
		1,2-Dichloropropane	<1.0	µg/L	0	GE
		1,2-Dichloropropane	<1.0	µg/L	0	GE
		trans-1,3-Dichloropropene	<1.0	µg/L	0	GE
		trans-1,3-Dichloropropene	<1.0	µg/L	0	GE
		cis-1,3-Dichloropropene	<1.0	µg/L	0	GE
		cis-1,3-Dichloropropene	<1.0	µg/L	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 1 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Dieldrin	<10	µg/L	0	GE
		Dieldrin	<10	µg/L	0	GE
		Diethyl phthalate	<10	µg/L	0	GE
		Diethyl phthalate	<10	µg/L	0	GE
		2,4-Dimethyl phenol	<10	µg/L	0	GE
		2,4-Dimethyl phenol	<10	µg/L	0	GE
		Dimethyl phthalate	<10	µg/L	0	GE
		Dimethyl phthalate	<10	µg/L	0	GE
		2,4-Dinitrophenol	<45	µg/L	0	GE
		2,4-Dinitrophenol	<45	µg/L	0	GE
		2,4-Dinitrotoluene	<10	µg/L	0	GE
		2,4-Dinitrotoluene	<10	µg/L	0	GE
		2,6-Dinitrotoluene	<10	µg/L	0	GE
		2,6-Dinitrotoluene	<10	µg/L	0	GE
		1,2-Diphenylhydrazine	<10	µg/L	0	GE
		1,2-Diphenylhydrazine	<10	µg/L	0	GE
		Endosulfan I	<10	µg/L	0	GE
		Endosulfan I	<10	µg/L	0	GE
		Endosulfan II	<10	µg/L	0	GE
		Endosulfan II	<10	µg/L	0	GE
		Endosulfan sulfate	<10	µg/L	0	GE
		Endosulfan sulfate	<10	µg/L	0	GE
		Endrin	<10	µg/L	0	GE
		Endrin	<10	µg/L	0	GE
		Endrin aldehyde	<10	µg/L	0	GE
		Endrin aldehyde	<10	µg/L	0	GE
		Ethylbenzene	<1.0	µg/L	0	GE
		Ethylbenzene	<1.0	µg/L	0	GE
		Fluoranthene	<10	µg/L	0	GE
		Fluoranthene	<10	µg/L	0	GE
		Fluorene	<10	µg/L	0	GE
		Fluorene	<10	µg/L	0	GE
		Fluoride	<100	µg/L	0	GE
		Fluoride	<100	µg/L	0	GE
		Fluoride	<100	µg/L	0	GE
		Heptachlor	<10	µg/L	0	GE
		Heptachlor	<10	µg/L	0	GE
		Heptachlor epoxide	<10	µg/L	0	GE
		Heptachlor epoxide	<10	µg/L	0	GE
		Hexachlorobenzene	<10	µg/L	0	GE
		Hexachlorobenzene	<10	µg/L	0	GE
		Hexachlorobutadiene	<10	µg/L	0	GE
		Hexachlorobutadiene	<10	µg/L	0	GE
		Hexachlorocyclopentadiene	<10	µg/L	0	GE
		Hexachlorocyclopentadiene	<10	µg/L	0	GE
		Hexachloroethane	<10	µg/L	0	GE
		Hexachloroethane	<10	µg/L	0	GE
		Indeno[1,2,3-c,d]pyrene	<10	µg/L	0	GE
		Indeno[1,2,3-c,d]pyrene	<10	µg/L	0	GE
		Iron	22	µg/L	0	GE
		Iron	22	µg/L	0	GE
		Isophorone	<10	µg/L	0	GE
		Isophorone	<10	µg/L	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 1 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Lead	3.2	µg/L	0	GE
		Lead	<3.0	µg/L	0	GE
		Lindane	<10	µg/L	0	GE
		Lindane	<10	µg/L	0	GE
		Magnesium	241	µg/L	0	GE
		Magnesium	244	µg/L	0	GE
		Manganese	2.1	µg/L	0	GE
		Manganese	2.1	µg/L	0	GE
		Mercury	<0.20	µg/L	0	GE
		Mercury	<0.20	µg/L	0	GE
•		Methoxychlor	<0.50	µg/L	0	GE
		Methoxychlor	<0.50	µg/L	0	GE
		2-Methyl-4,6-dinitrophenol	<10	µg/L	0	GE
		2-Methyl-4,6-dinitrophenol	<10	µg/L	0	GE
		N-Nitrosodi-propylamine	<10	µg/L	0	GE
		N-Nitrosodi-propylamine	<10	µg/L	0	GE
		N-Nitrosodimethylamine	<10	µg/L	0	GE
		N-Nitrosodimethylamine	<10	µg/L	0	GE
		N-Nitrosodiphenylamine	<10	µg/L	0	GE
		N-Nitrosodiphenylamine	<10	µg/L	0	GE
		Naphthalene	<10	µg/L	0	GE
		Naphthalene	<10	µg/L	0	GE
		Nickel	<4.0	µg/L	0	GE
		Nickel	5.2	µg/L	0	GE
		Nitrate as nitrogen	500	µg/L	0	GE
		Nitrate as nitrogen	51	µg/L	0	GE
		Nitrobenzene	<10	µg/L	0	GE
		Nitrobenzene	<10	µg/L	0	GE
		2-Nitrophenol	<10	µg/L	0	GE
		2-Nitrophenol	<10	µg/L	0	GE
		4-Nitrophenol	<10	µg/L	0	GE
		4-Nitrophenol	<10	µg/L	0	GE
		PCB 1016	<150	µg/L	0	GE
		PCB 1016	<150	µg/L	0	GE
		PCB 1221	<150	µg/L	0	GE
		PCB 1221	<150	µg/L	0	GE
		PCB 1232	<150	µg/L	0	GE
		PCB 1232	<150	µg/L	0	GE
		PCB 1242	<150	µg/L	0	GE
		PCB 1242	<150	µg/L	0	GE
		PCB 1248	<150	µg/L	0	GE
		PCB 1248	<150	µg/L	0	GE
		PCB 1254	<150	µg/L	0	GE
		PCB 1254	<150	µg/L	0	GE
		PCB 1260	<150	µg/L	0	GE
		PCB 1260	<150	µg/L	0	GE
		Pentachlorophenol	<10	µg/L	0	GE
		Pentachlorophenol	<10	µg/L	0	GE
		Phenanthrene	<10	µg/L	0	GE
		Phenanthrene	<10	µg/L	0	GE
		Phenol	<10	µg/L	0	GE
		Phenol	<10	µg/L	0	GE
		Phenols	<5.0	µg/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 1 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Phenols	< 5.0	µg/L	0	GE
		Potassium	< 500	µg/L	0	GE
		Potassium	< 500	µg/L	0	GE
		Pyrene	< 10	µg/L	0	GE
		Pyrene	< 10	µg/L	0	GE
		Selenium	< 2.0	µg/L	0	GE
		Selenium	< 2.0	µg/L	0	GE
		Silica	5,940	µg/L	0	GE
		Silica	5,960	µg/L	0	GE
		Silver	< 2.0	µg/L	0	GE
		Silver	< 2.0	µg/L	0	GE
		Sodium	57,200	µg/L	0	GE
		Sodium	57,100	µg/L	0	GE
		1,1,2,2-Tetrachloroethane	< 1.0	µg/L	0	GE
		1,1,2,2-Tetrachloroethane	< 1.0	µg/L	0	GE
		Tetrachloroethylene	< 1.0	µg/L	0	GE
		Tetrachloroethylene	< 1.0	µg/L	0	GE
		Thallium	< 2.0	µg/L	0	GE
		Thallium	< 2.0	µg/L	0	GE
		Toluene	< 1.0	µg/L	0	GE
		Toluene	< 1.0	µg/L	0	GE
		Total dissolved solids	186,000	µg/L	0	GE
		Total dissolved solids	197,000	µg/L	0	GE
		Total organic carbon	< 1,000	µg/L	0	GE
		Total organic carbon	< 1,000	µg/L	0	GE
		Total organic halogens	35	µg/L	1	GE
		Total organic halogens	13	µg/L	0	GE
		Total organic halogens	13	µg/L	0	GE
		Total phosphates (as P)	< 50	µg/L	0	GE
		Total phosphates (as P)	50	µg/L	0	GE
		Toxaphene	< 10	µg/L	0	GE
		Toxaphene	< 10	µg/L	0	GE
		2,4,5-TP (Silvex)	< 0.090	µg/L	0	GE
		2,4,5-TP (Silvex)	< 0.090	µg/L	0	GE
		1,2,4-Trichlorobenzene	< 10	µg/L	0	GE
		1,2,4-Trichlorobenzene	< 10	µg/L	0	GE
		1,1,1-Trichloroethane	< 1.0	µg/L	0	GE
		1,1,1-Trichloroethane	< 1.0	µg/L	0	GE
		1,1,2-Trichloroethane	< 1.0	µg/L	0	GE
		1,1,2-Trichloroethane	< 1.0	µg/L	0	GE
		Trichloroethylene	< 1.0	µg/L	0	GE
		Trichloroethylene	< 1.0	µg/L	0	GE
		Trichlorofluoromethane	< 1.0	µg/L	0	GE
		Trichlorofluoromethane	< 1.0	µg/L	0	GE
		2,4,6-Trichlorophenol	< 10	µg/L	0	GE
		2,4,6-Trichlorophenol	< 10	µg/L	0	GE
		Zinc	8.9	µg/L	0	GE
		Zinc	8.4	µg/L	0	GE
		Gross alpha	2.5E+00 ± 1.3E+00	pCi/L	0	GE
		Gross alpha	< 2.0E+00	pCi/L	0	GE
		Nonvolatile beta	1.3E+01 ± 2.2E+00	pCi/L	0	GE
		Nonvolatile beta	< 2.0E+00	pCi/L	0	GE
		Total radium	< 1.0E+00	pCi/L	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 1 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Total radium	< 1.0E+00	pCi/L	0	GE
		Tritium	3.3E+00 ± 7.0E-01	pCi/mL	0	GE
		Tritium	2.8E+00 ± 7.0E-01	pCi/mL	0	GE

WELL KAC 2

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53255.5	33.213191 °N	225.4-195.4 ft msl	257.5 ft msl	4" PVC	Water Table
E42677.2	81.657873 °W				

MEASUREMENTS CONDUCTED IN THE FIELD

Sample date: 11/18/91
 Depth to water: 34.58 ft (10.54 m) below TOC
 Water elevation: 222.92 ft (67.95 m) msl
 Sp. conductance: 368 µS/cm
 Water evacuated before sampling: 72 gal

Time: 12:05
 pH: 5.9
 Alkalinity: 23 mg/L
 Water temperature: 19.1°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	6.4	pH	0	GE
		Specific conductance	350	µS/cm	1	GE
		Turbidity	34	NTU	0	GE
		Arsenic	< 2.0	µg/L	0	GE
		Barium	< 3.0	µg/L	0	GE
		Cadmium	< 2.0	µg/L	0	GE
		Calcium	309	µg/L	0	GE
		Chloride	6,250	µg/L	0	GE
		Chromium	< 4.0	µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	< 0.30	µg/L	0	GE
		Endrin	< 0.0060	µg/L	0	GE
		Fluoride	< 100	µg/L	0	GE
		Iron	49	µg/L	0	GE
		Lead	< 3.0	µg/L	0	GE
		Lindane	< 0.0050	µg/L	0	GE
		Magnesium	159	µg/L	0	GE
		Manganese	< 2.0	µg/L	0	GE
		Mercury	< 0.20	µg/L	0	GE
		Methoxychlor	< 0.50	µg/L	0	GE
		Nitrate as nitrogen	210	µg/L	0	GE
		Phenols	< 5.0	µg/L	0	GE
		Potassium	< 500	µg/L	0	GE
		Selenium	5.8	µg/L	0	GE
		Silica	6,550	µg/L	0	GE
		Silver	< 2.0	µg/L	0	GE
		Sodium	67,900	µg/L	0	GE
		Total dissolved solids	229,000	µg/L	0	GE
		Total organic carbon	< 1,000	µg/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 2 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Total organic halogens	19	µg/L	0	GE
		Total phosphates (as P)	60	µg/L	0	GE
		Toxaphene	<0.24	µg/L	0	GE
		2,4,5-TP (Silvex)	<0.090	µg/L	0	GE
		Gross alpha	5.0E+00 ± 1.7E+00	pCi/L	0	GE
		Nonvolatile beta	3.9E+00 ± 1.8E+00	pCi/L	0	GE
		Total radium	<1.0E+00	pCi/L	0	GE
		Tritium	5.7E+00 ± 7.0E-01	pCi/mL	0	GE

WELL KAC 3

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53201.8	33.213148 °N	225.8-195.8 ft msl	257.8 ft msl	4" PVC	Water Table
E42723.9	81.657646 °W				

MEASUREMENTS CONDUCTED IN THE FIELD

Sample date: 11/18/91
 Depth to water: 34.60 ft (10.55 m) below TOC
 Water elevation: 223.20 ft (68.03 m) msl
 Sp. conductance: 259 µS/cm
 Water evacuated before sampling: 72 gal

Time: 11:25
 pH: 6.1
 Alkalinity: 27 mg/L
 Water temperature: 18.7°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	6.4	pH	0	GE
•		pH	6.5	pH	0	GE
•		pH	6.5	pH	0	GE
•		pH	6.5	pH	0	GE
		Specific conductance	220	µS/cm	0	GE
		Specific conductance	220	µS/cm	0	GE
		Specific conductance	225	µS/cm	0	GE
		Specific conductance	230	µS/cm	0	GE
		Turbidity	0.30	NTU	0	GE
		Acenaphthene	<10	µg/L	0	GE
		Acenaphthylene	<10	µg/L	0	GE
		Aldrin	<10	µg/L	0	GE
		Aluminum	<20	µg/L	0	GE
		Anthracene	<10	µg/L	0	GE
		Antimony	2.2	µg/L	0	GE
		Arsenic	<2.0	µg/L	0	GE
		Barium	4.2	µg/L	0	GE
		Benzene	<1.0	µg/L	0	GE
		alpha-Benzene hexachloride	<10	µg/L	0	GE
		beta-Benzene hexachloride	<10	µg/L	0	GE
		delta-Benzene hexachloride	<10	µg/L	0	GE
		Benzidine	<10	µg/L	0	GE
		Benzo[a]anthracene	<10	µg/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 3 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Benzo[a]pyrene	<10	µg/L	0	GE
		Benzo[b]fluoranthene	<10	µg/L	0	GE
		Benzo[g,h,i]perylene	<10	µg/L	0	GE
		Benzo[k]fluoranthene	<10	µg/L	0	GE
		Beryllium	<3.0	µg/L	0	GE
		Bis(2-chloroethoxy) methane	<10	µg/L	0	GE
		Bis(2-chloroethyl) ether	<10	µg/L	0	GE
		Bis(2-chloroisopropyl) ether	<10	µg/L	0	GE
		Bis(2-ethylhexyl) phthalate	<10	µg/L	0	GE
		Bromide	<1,000	µg/L	0	GE
		Bromodichloromethane	<1.0	µg/L	0	GE
		Bromoform	<1.0	µg/L	0	GE
		Bromomethane (Methyl bromide)	<1.0	µg/L	0	GE
		4-Bromophenyl phenyl ether	<10	µg/L	0	GE
		Butylbenzyl phthalate	<10	µg/L	0	GE
		Cadmium	<2.0	µg/L	0	GE
		Calcium	1,020	µg/L	0	GE
		Carbon tetrachloride	<1.0	µg/L	0	GE
		Chlordane	<10	µg/L	0	GE
		Chloride	8,500	µg/L	0	GE
		para-Chloro-meta-cresol	<10	µg/L	0	GE
		Chlorobenzene	<1.0	µg/L	0	GE
		Chloroethane	<1.0	µg/L	0	GE
		Chloroethene (Vinyl chloride)	<1.0	µg/L	0	GE
		2-Chloroethyl vinyl ether	<1.0	µg/L	0	GE
		Chloroform	<1.0	µg/L	0	GE
		Chloromethane (Methyl chloride)	<1.0	µg/L	0	GE
		2-Chloronaphthalene	<10	µg/L	0	GE
		2-Chlorophenol	<10	µg/L	0	GE
		4-Chlorophenyl phenyl ether	<10	µg/L	0	GE
		Chromium	<4.0	µg/L	0	GE
		Chrysene	<10	µg/L	0	GE
		Cobalt	<4.0	µg/L	0	GE
		Copper	9.5	µg/L	0	GE
		Cyanide	<5.0	µg/L	0	GE
		p,p'-DDD	<10	µg/L	0	GE
		p,p'-DDE	<10	µg/L	0	GE
		p,p'-DDT	<10	µg/L	0	GE
		Di-n-butyl phthalate	<10	µg/L	0	GE
		Di-n-octyl phthalate	<10	µg/L	0	GE
		Dibenz[a,h]anthracene	<10	µg/L	0	GE
		Dibromochloromethane	<1.0	µg/L	0	GE
		3,3'-Dichlorobenzidine	<10	µg/L	0	GE
		1,1-Dichloroethane	<1.0	µg/L	0	GE
		1,2-Dichloroethane	<1.0	µg/L	0	GE
		1,1-Dichloroethylene	<1.0	µg/L	0	GE
		trans-1,2-Dichloroethylene	<1.0	µg/L	0	GE
		Dichloromethane (Methylene chloride)	<1.0	µg/L	0	GE
		2,4-Dichlorophenol	<10	µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30	µg/L	0	GE
		1,2-Dichloropropane	<1.0	µg/L	0	GE
		trans-1,3-Dichloropropene	<1.0	µg/L	0	GE
		cis-1,3-Dichloropropene	<1.0	µg/L	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 3 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Dieldrin	< 10	µg/L	0	GE
		Diethyl phthalate	< 10	µg/L	0	GE
		2,4-Dimethyl phenol	< 10	µg/L	0	GE
		Dimethyl phthalate	< 10	µg/L	0	GE
		2,4-Dinitrophenol	< 45	µg/L	0	GE
		2,4-Dinitrotoluene	< 10	µg/L	0	GE
		2,6-Dinitrotoluene	< 10	µg/L	0	GE
		1,2-Diphenylhydrazine	< 10	µg/L	0	GE
		Endosulfan I	< 10	µg/L	0	GE
		Endosulfan II	< 10	µg/L	0	GE
		Endosulfan sulfate	< 10	µg/L	0	GE
		Endrin	< 10	µg/L	0	GE
		Endrin aldehyde	< 10	µg/L	0	GE
		Ethylbenzene	< 1.0	µg/L	0	GE
		Fluoranthene	< 10	µg/L	0	GE
		Fluorene	< 10	µg/L	0	GE
		Fluoride	< 100	µg/L	0	GE
		Heptachlor	< 10	µg/L	0	GE
		Heptachlor epoxide	< 10	µg/L	0	GE
		Hexachlorobenzene	< 10	µg/L	0	GE
		Hexachlorobutadiene	< 10	µg/L	0	GE
		Hexachlorocyclopentadiene	< 10	µg/L	0	GE
		Hexachloroethane	< 10	µg/L	0	GE
		Indeno[1,2,3-c,d]pyrene	< 10	µg/L	0	GE
		Iron	73	µg/L	0	GE
		Isophorone	< 10	µg/L	0	GE
		Lead	< 3.0	µg/L	0	GE
		Lindane	< 10	µg/L	0	GE
		Magnesium	350	µg/L	0	GE
		Manganese	< 2.0	µg/L	0	GE
		Mercury	< 0.20	µg/L	0	GE
		Methoxychlor	< 0.50	µg/L	0	GE
		2-Methyl-4,6-dinitrophenol	< 10	µg/L	0	GE
		N-Nitrosodi-propylamine	< 10	µg/L	0	GE
		N-Nitrosodimethylamine	< 10	µg/L	0	GE
		N-Nitrosodiphenylamine	< 10	µg/L	0	GE
		Naphthalene	< 10	µg/L	0	GE
		Nickel	< 4.0	µg/L	0	GE
		Nitrate as nitrogen	< 50	µg/L	0	GE
		Nitrobenzene	< 10	µg/L	0	GE
		2-Nitrophenol	< 10	µg/L	0	GE
		4-Nitrophenol	< 10	µg/L	0	GE
		PCB 1016	< 150	µg/L	0	GE
		PCB 1221	< 150	µg/L	0	GE
		PCB 1232	< 150	µg/L	0	GE
		PCB 1242	< 150	µg/L	0	GE
		PCB 1248	< 150	µg/L	0	GE
		PCB 1254	< 150	µg/L	0	GE
		PCB 1260	< 150	µg/L	0	GE
		Pentachlorophenol	< 10	µg/L	0	GE
		Phenanthrene	< 10	µg/L	0	GE
		Phenol	< 10	µg/L	0	GE
		Phenols	< 5.0	µg/L	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 3 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Potassium	<500	µg/L	0	GE
		Pyrene	<10	µg/L	0	GE
		Selenium	<2.0	µg/L	0	GE
		Silica	5,830	µg/L	0	GE
		Silver	<2.0	µg/L	0	GE
		Sodium	47,900	µg/L	0	GE
		1,1,2,2-Tetrachloroethane	<1.0	µg/L	0	GE
		Tetrachloroethylene	<1.0	µg/L	0	GE
		Thallium	<2.0	µg/L	0	GE
		Toluene	<1.0	µg/L	0	GE
		Total dissolved solids	148,000	µg/L	0	GE
		Total organic carbon	<1,000	µg/L	0	GE
		Total organic carbon	<1,000	µg/L	0	GE
		Total organic carbon	<1,000	µg/L	0	GE
		Total organic carbon	<1,000	µg/L	0	GE
		Total organic halogens	<5.0	µg/L	0	GE
		Total organic halogens	<5.0	µg/L	0	GE
		Total organic halogens	<5.0	µg/L	0	GE
		Total organic halogens	<5.0	µg/L	0	GE
		Total phosphates (as P)	<50	µg/L	0	GE
		Toxaphene	<10	µg/L	0	GE
		2,4,5-TP (Silvex)	<0.090	µg/L	0	GE
		1,2,4-Trichlorobenzene	<10	µg/L	0	GE
		1,1,1-Trichloroethane	<1.0	µg/L	0	GE
		1,1,2-Trichloroethane	<1.0	µg/L	0	GE
		Trichloroethylene	<1.0	µg/L	0	GE
		Trichlorofluoromethane	<1.0	µg/L	0	GE
		2,4,6-Trichlorophenol	<10	µg/L	0	GE
		Zinc	7.2	µg/L	0	GE
		Gross alpha	2.4E+00 ± 1.1E+00	pCi/L	0	GE
		Nonvolatile beta	<2.0E+00	pCi/L	0	GE
		Total radium	<1.0E+00	pCi/L	0	GE
		Tritium	3.3E+00 ± 7.0E-01	pCi/mL	0	GE

WELL KAC 4

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53053.5	33.212743 °N	208.0-178.0 ft msl	260.0 ft msl	4" PVC	Water Table
E42676.4	81.657484 °W				

MEASUREMENTS CONDUCTED IN THE FIELD

Sample date: 11/18/91
 Depth to water: 38.94 ft (11.87 m) below TOC
 Water elevation: 221.06 ft (67.38 m) msl
 Sp. conductance: 74 µS/cm
 Water evacuated before sampling: 113 gal

Time: 13:40
 pH: 5.0
 Alkalinity: 1 mg/L
 Water temperature: 18.3°C

● = exceeded holding time. ■ = exceeded primary drinking water standard.

LABORATORY ANALYSES for WELL KAC 4

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	5.4	pH	0	GE
		Specific conductance	70	µS/cm	0	GE
		Turbidity	2.8	NTU	0	GE
		Arsenic	<2.0	µg/L	0	GE
		Barium	4.2	µg/L	0	GE
		Cadmium	<2.0	µg/L	0	GE
		Calcium	347	µg/L	0	GE
		Chloride	8,600	µg/L	0	GE
		Chromium	<4.0	µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30	µg/L	0	GE
		Endrin	<0.0060	µg/L	0	GE
		Fluoride	<100	µg/L	0	GE
		Iron	5.0	µg/L	0	GE
		Lead	<3.0	µg/L	0	GE
		Lindane	<0.0050	µg/L	0	GE
		Magnesium	393	µg/L	0	GE
		Manganese	2.5	µg/L	0	GE
		Mercury	<0.20	µg/L	0	GE
		Methoxychlor	<0.50	µg/L	0	GE
		Nitrate as nitrogen	160	µg/L	0	GE
		Nitrate as nitrogen	160	µg/L	0	GE
		Phenols	<5.0	µg/L	0	GE
		Phenols	<5.0	µg/L	0	GE
		Potassium	<500	µg/L	0	GE
		Selenium	2.0	µg/L	0	GE
		Silica	6,390	µg/L	0	GE
		Silver	<2.0	µg/L	0	GE
		Sodium	11,600	µg/L	0	GE
		Total dissolved solids	54,000	µg/L	0	GE
		Total organic carbon	<1,000	µg/L	0	GE
		Total organic halogens	15	µg/L	0	GE
		Total phosphates (as P)	160	µg/L	0	GE
		Toxaphene	<0.24	µg/L	0	GE
		2,4,5-TP (Silvex)	<0.090	µg/L	0	GE
		Gross alpha	2.3E+00 ± 1.0E+00	pCi/L	0	GE
		Nonvolatile beta	<2.0E+00	pCi/L	0	GE
		Total radium	<1.0E+00	pCi/L	0	GE
		Tritium	2.1E+00 ± 7.0E-01	pCi/mL	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 5

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53161.7 E42716.3	33.213047 °N 81.657589 °W	224.3-204.3 ft msl	259.0 ft msl	4" PVC	Water Table

MEASUREMENTS CONDUCTED IN THE FIELD

Sample date: 11/18/91
 Depth to water: 35.94 ft (10.95 m) below TOC
 Water elevation: 223.06 ft (67.99 m) msl
 Sp. conductance: 54 μ S/cm
 Water evacuated before sampling: 49 gal

Time: 10:50
 pH: 5.4
 Alkalinity: 2 mg/L
 Water temperature: 19.0°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	5.5	pH	0	GE
•		pH	5.6	pH	0	GE
•		pH	5.7	pH	0	GE
•		pH	5.7	pH	0	GE
		Specific conductance	50	μ S/cm	0	GE
		Specific conductance	50	μ S/cm	0	GE
		Specific conductance	50	μ S/cm	0	GE
		Specific conductance	50	μ S/cm	0	GE
		Turbidity	7.9	NTU	0	GE
		Arsenic	<2.0	μ g/L	0	GE
		Barium	<3.0	μ g/L	0	GE
		Cadmium	<2.0	μ g/L	0	GE
		Calcium	353	μ g/L	0	GE
		Chloride	6,550	μ g/L	0	GE
		Chromium	<4.0	μ g/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30	μ g/L	0	GE
		Endrin	<0.0060	μ g/L	0	GE
		Fluoride	<100	μ g/L	0	GE
		Iron	123	μ g/L	0	GE
		Lead	<3.0	μ g/L	0	GE
		Lindane	<0.0050	μ g/L	0	GE
		Magnesium	206	μ g/L	0	GE
		Manganese	5.4	μ g/L	0	GE
		Mercury	<0.20	μ g/L	0	GE
		Methoxychlor	<0.50	μ g/L	0	GE
		Nitrate as nitrogen	<50	μ g/L	0	GE
		Phenols	<5.0	μ g/L	0	GE
		Potassium	<500	μ g/L	0	GE
		Selenium	2.2	μ g/L	0	GE
		Silica	5,700	μ g/L	0	GE
		Silver	<2.0	μ g/L	0	GE
		Sodium	8,310	μ g/L	0	GE
		Total dissolved solids	35,000	μ g/L	0	GE
		Total organic carbon	<1,000	μ g/L	0	GE
		Total organic carbon	<1,000	μ g/L	0	GE
		Total organic carbon	<1,000	μ g/L	0	GE
		Total organic carbon	<1,000	μ g/L	0	GE
		Total organic halogens	<5.0	μ g/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 5 collected on 11/18/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Total organic halogens	<5.0	µg/L	0	GE
		Total organic halogens	<5.0	µg/L	0	GE
		Total organic halogens	<5.0	µg/L	0	GE
		Total phosphates (as P)	<50	µg/L	0	GE
		Toxaphene	<0.24	µg/L	0	GE
		2,4,5-TP (Silvex)	<0.090	µg/L	0	GE
		Gross alpha	<2.0E+00	pCi/L	0	GE
		Nonvolatile beta	<2.0E+00	pCi/L	0	GE
		Total radium	1.3E+00 ± 1.8E+00	pCi/L	0	GE
		Tritium	<7.0E-01	pCi/mL	0	GE

WELL KAC 6

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53139.9	33.212962 °N	224.6-204.6 ft msl	259.0 ft msl	4" PVC	Water Table
E42693.5	81.657606 °W				

MEASUREMENTS CONDUCTED IN THE FIELD

Sample date: 11/19/91
 Depth to water: 35.86 ft (10.93 m) below TOC
 Water elevation: 223.14 ft (68.01 m) msl
 Sp. conductance: 90 µS/cm
 Water evacuated before sampling: 9 gal
 The well went dry during purging.

Time: 9:10
 pH: 5.3
 Alkalinity: 1 mg/L
 Water temperature: 18.2°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	5.7	pH	0	GE
		Specific conductance	80	µS/cm	0	GE
		Turbidity	31	NTU	0	GE
		Arsenic	<2.0	µg/L	0	GE
		Barium	3.8	µg/L	0	GE
		Cadmium	<2.0	µg/L	0	GE
		Calcium	290	µg/L	0	GE
		Chloride	6,200	µg/L	0	GE
		Chromium	<4.0	µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30	µg/L	0	GE
		Endrin	<0.0060	µg/L	0	GE
		Fluoride	<100	µg/L	0	GE
		Iron	126	µg/L	0	GE
		Lead	<3.0	µg/L	0	GE
		Lindane	<0.0050	µg/L	0	GE
		Magnesium	233	µg/L	0	GE
		Manganese	9.8	µg/L	0	GE
		Mercury	<0.20	µg/L	0	GE
		Methoxychlor	<0.50	µg/L	0	GE
		Nitrate as nitrogen	<50	µg/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 6 collected on 11/19/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Phenols	<5.0	µg/L	0	GE
		Potassium	<500	µg/L	0	GE
		Selenium	2.4	µg/L	0	GE
		Silica	6,200	µg/L	0	GE
		Silver	<2.0	µg/L	0	GE
		Sodium	11,800	µg/L	0	GE
		Total dissolved solids	45,000	µg/L	0	GE
		Total organic carbon	<1,000	µg/L	0	GE
		Total organic carbon	<1,000	µg/L	0	GE
		Total organic halogens	<5.0	µg/L	0	GE
		Total phosphates (as P)	<50	µg/L	0	GE
		Toxaphene	<0.24	µg/L	0	GE
		2,4,5-TP (Silvex)	<0.090	µg/L	0	GE
		Gross alpha	2.3E+00 ± 1.0E+00	pCi/L	0	GE
		Nonvolatile beta	<2.0E+00	pCi/L	0	GE
		Total radium	<1.0E+00	pCi/L	0	GE
		Tritium	9.9E-01 ± 7.0E-01	pCi/mL	0	GE

WELL KAC 7

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53252.9	33.213018 °N	223.0-203.0 ft msl	265.1 ft msl	4" PVC	Water Table
E42574.5	81.658139 °W				

MEASUREMENTS CONDUCTED IN THE FIELD

Sample date: 11/19/91
 Depth to water: 43.23 ft (13.18 m) below TOC
 Water elevation: 221.87 ft (67.63 m) msl
 Sp. conductance: 136 µS/cm
 Water evacuated before sampling: 9 gal
 The well went dry during purging.

Time: 8:55
 pH: 6.0
 Alkalinity: 35 mg/L
 Water temperature: 18.5°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	6.4	pH	0	GE
		Specific conductance	125	µS/cm	0	GE
		Turbidity	39	NTU	0	GE
		Turbidity	38	NTU	0	GE
		Arsenic	<2.0	µg/L	0	GE
		Barium	5.2	µg/L	0	GE
		Cadmium	<2.0	µg/L	0	GE
		Calcium	4,140	µg/L	0	GE
		Chloride	9,400	µg/L	0	GE
		Chromium	<4.0	µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30	µg/L	0	GE
		Endrin	<0.0060	µg/L	0	GE
		Fluoride	<100	µg/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 7 collected on 11/19/91, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Fluoride	< 100	µg/L	0	GE
		Iron	1,390	µg/L	2	GE
		Lead	3.5	µg/L	0	GE
		Lindane	< 0.0050	µg/L	0	GE
		Magnesium	110	µg/L	0	GE
		Manganese	12	µg/L	0	GE
		Mercury	< 0.20	µg/L	0	GE
		Methoxychlor	< 0.50	µg/L	0	GE
		Nitrate as nitrogen	1,820	µg/L	0	GE
		Phenols	< 5.0	µg/L	0	GE
		Potassium	< 500	µg/L	0	GE
		Selenium	< 2.0	µg/L	0	GE
		Silica	4,900	µg/L	0	GE
		Silver	< 2.0	µg/L	0	GE
		Sodium	23,700	µg/L	0	GE
		Total dissolved solids	72,000	µg/L	0	GE
		Total organic carbon	5,000	µg/L	1	GE
		Total organic halogens	55	µg/L	2	GE
		Total phosphates (as P)	150	µg/L	0	GE
		Toxaphene	< 0.24	µg/L	0	GE
		2,4,5-TP (Silvex)	< 0.090	µg/L	0	GE
		Gross alpha	< 2.0E + 00	pCi/L	0	GE
		Nonvolatile beta	< 2.0E + 00	pCi/L	0	GE
		Total radium	< 1.0E + 00	pCi/L	0	GE
		Tritium	7.5E + 00 ± 8.0E-01	pCi/mL	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

END

**DATE
FILMED**

2 / 18 / 93