DOE/PC/90505--T8

DOE/PC/90505--T8

MECHANISM OF SURFACE ENRICHMENT AND ADHESION

DE92 019743

OF COAL COMBUSTION PARTICULATES

DOE GRANT NO. DE-FG22-86PC90505

File KSA

Second Quarterly Report
September 1987

By:

F. Shadman
T.W. Peterson
J.O.L. Wendt
W.A. Punjak
G. Rizeq

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Department of Chemical Engineering
University of Arizona
Tucson, Arizona 85721

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Abstract

Following is an updated list of accomplishments:

1. Design of an experimental set up and development of experimental techniques for study of the adsorption and desorption of alkali on coal ash and potential additive particles.
2. Development of techniques for quantitative and qualitative characterization of alkali distribution in small additive particles using Scanning Auger Spectroscopy.
3. Completion of a set of adsorption experiments for measuring the rate, capacity and adsorption characteristics of alkali adsorption on bauxite, silica, lime and kaolin.
4. Design and set up of a micro-fluidized bed for study of the agglomeration kinetics and characteristics of ash and additive particles.
5. Completion of the first set of experiments on dependence of agglomeration characteristics on the alkali content of typical ash and potential additive particle..

Table of Content

	<u>page number</u>
1. Introduction	1
2. Alkali Adsorption	5
2.1 Experimental Set Up	5
2.2 Experimental Procedure	10
2.3 Results	12
3. Agglomeration Characteristics of Ash and Additive Particles	27
3.1 Method of Approach	27
3.2 Experimental Apparatus	27
3.3 Experimental Procedure	31
3.4 Results	34
4. References	43

1. Introduction

Although mechanisms of fouling are complex and not well understood, the fouling process is clearly related to the chemical composition of the airborne ash particles. Certain compounds like Ca, Fe, and alkali metals compounds can lower the melting point of mineral particulates and enhance the fouling. Alkali metals are particularly abundant in many coals, especially lignites, and are traditionally considered to be the most important cause of fouling.

The relationship between the fouling and the ash composition has been the subject of many studies. An important point which has been generally neglected in these studies is the fact that the adhesion tendency of the particles depends on the composition of the surface layer rather than the average bulk composition of the particles. This is important considering that ash particles have a highly nonuniform composition. In particular, the surface of the ash particles appears to be enriched in certain elements like K, Na, Li, Ca, Fe, Cr, Pb, S, V and Zn. Therefore, to understand and control fouling, the physical and chemical phenomena which lead to the surface enrichment should be studied in more detail.

Surface enrichment of coal ash particles has been attributed to two types of processes:

1. Adsorption/Condensation: Surface enrichment occurs because the trace and minor elements or their compounds are volatilized in the high temperature zone of the combustor and subsequently condensed or adsorbed on the surface of the solid ash particles.
2. Thermally-induced segregation: At the high combustion temperatures, certain trace and minor elements diffuse to the surface of the ash particles.

The subject of vaporization and condensation of alkali and trace metals has received considerable attention in recent years (1-4). Sodium in coal is

primarily in the silicate and chloride forms for most bituminous coals and in the organically bound forms (salts of organic acids) in most lignite and sub-bituminous coals. These compounds are rapidly devolatilized and/or dissociated in the flame. The specific species of sodium existing in the high temperature zone of the furnace is not known. Thermodynamic calculations are not sufficient to predict the forms because the processes are occurring over a short period of time and are kinetically controlled. Sodium in flame may exist for a short time as atomic metal and/or oxide. At lower temperatures, reactions with water, CO₂, SO₂ and SO₃ can produce hydroxide, carbonate and sulfate. Sodium sulfate is the predominant species in the ash particles when sulfur oxides are present. Potassium in coal is primarily present as nonvolatile aluminosilicates (muscovites and illites). As a result of reaction with volatilized sodium some of the potassium is also vaporized and subsequently condensed.

In addition to condensation from vapor onto the existing ash surface particles, alkali metals may also nucleate from the supersaturated vapor and form submicron particles. These small particles adhere to the other ash particles and to combustor surfaces by various mechanisms including thermophoresis. Nucleation and adhesion of these aerosols is an important cause of fouling.

Based on the above discussion, it appears that the fouling caused by alkali and trace metals depends strongly on the amount and the chemical form of the alkali and trace metals in the surface layer of the ash particles. The mechanisms and possible method of controlling the surface layer composition and properties are not understood and have not been explored. This is primarily because the large number of studies in this area have focused on the bulk properties of ash particles and the derivation of empirical correlations. These data and correlations are certainly very useful in practice, but cannot provide much insight into the mechanisms and the fundamental steps of fouling and its

control and/or prediction.

The overall objective of the this study is to focus on the properties of surface layers of alkali-laden particles. The main idea is to control the adhesion properties of this layer by using additives which react and /or interact with the condensed alkali to form "nonsticky" surface layers for minimum fouling.

Additives can potentially control the process of condensation and the properties of alkali-laden particles by chemical interactions with condensing alkali. Alkali metals at the high combustion temperatures are highly reactive. They can potentially react with suitable additives after condensation to form stable compounds with very low vapor pressures. With the proper choice of additives which have strong chemical affinity to alkali vapors, the fate of alkali compounds can be controlled to a great extent. Reactions forming alkali compounds with relatively high melting points can be promoted particularly in the surface layer of the additive particles; this will lower the fouling tendency of the particles .

Although the available data on the chemical effect of substrate are at temperatures lower than the typical combustion temperatures, they still present a very strong case for further exploration of chemically active additives. At very high temperatures close to the combustion flame, the alkali additive reactions may not be as fast as the condensation from a supersaturated vapor and may not control the overall condensation rate. However, the alkali substrate interactions continue over a much longer time scale after the flame zone. Once again, it is the interactions in the outer surface layer which count towards producing the above-mentioned desirable effects. These surface chemical interactions have not been systematically studied and are not understood.

The chemical interactions discussed above are the primary factors; however, the following additional potential properties of additives should also be

Figure 2.1: Schematic of the adsorption/desorption reactor system

Figure 2.2: Adsorption/desorption reactor details

down the reactor where it joins the carrier gas and exits out the exhaust port.

The carrier gas is generated by mixing nitrogen, air and carbon dioxide from gas cylinders. The gas is then passed through a water saturator to add water and the composition is adjusted to simulate a coal combustion flue gas. For experiments performed with just a N_2 carrier gas, only the N_2 flow is turned on and the saturator is bypassed. Just after the saturator a small amount of N_2 is bled in from a separate cylinder. This is done to make the carrier gas slightly undersaturated with water vapor so that water does not condense at any point downstream. To check the gas composition, part of the flow can be diverted at this point to a gas chromatograph (GC) and a nondispersive infrared analyzer (IR) to measure N_2 , O_2 , CO_2 and H_2O . The flow is then split into an alkali carrier stream and the dilution stream before entering the reactor. The flow rate in each stream, which is measured with mass flow meters, is adjusted with valves.

Unfortunately, the main stream carrier gas does not become saturated with alkali at the temperatures and flow rates used. In addition, the dilution gas backmixes to some extent, picking up additional alkali. Because of this the alkali concentration cannot be predicted from an equilibrium analysis and separate concentration calibration runs must be made for each temperature, alkali compound and flow rate used. A calibration run is made by putting a small quartz tube down the reactor in place of the microbalance wire, closing off the normal exhaust port, and directing the gases up the tube. As the alkali-containing gas cools in the upper zone of the furnace, the alkali condenses on the inner walls of the tube. After a given time has elapsed, the run is terminated. The tube is then washed in hydrofluoric acid and atomic absorption analysis is performed on the solution. The vapor phase alkali concentration is then determined from the AA analysis and the total collection time. Each run is then used to establish a

flow rate / concentration calibration curve.

Although quartz is not easily degraded by a vast majority of chemical species, it is susceptible to slow degradation by hot alkali compounds. In a $N_2/NaCl$ or air/ $NaCl$ atmosphere this degradation is quite slow, but it is accelerated considerably by the presence of water, requiring a new reactor more frequently. Originally the alkali reservoir was a quartz insert in the shape of a tube with the bottom end rounded off. The alkali compound was put in the insert to minimize contact between the condensed phase alkali and the reactor, thus extending the reactor's life. Duplication of several of the first runs with bauxite, however, showed the data to be irreproducible. Although part of this was attributed to a rotameter used for the dilution gas flow, a major portion was caused by the insert being in a slightly different position during each run. This altered the main carrier gas/dilution gas flow patterns enough to significantly change the vapor phase alkali concentration. It was decided at this point to put quartz wool between the insert and the reactor, thereby fixing its position. A set of calibration and bauxite/ $NaCl/N_2$ runs at 800 degrees C were made with acceptable reproducibility. When runs with kaolinite were initiated, however, reproducibility again became a problem, and investigation of the insert showed that the quartz wool had lost its integrity and the insert was able to move. Since many runs had already been made with the $NaCl/N_2$ atmosphere and the insert had not degraded too badly, it was decided to remove it and put the $NaCl$ directly in the bottom of the reactor. All subsequent runs with $NaCl$ at 800 degrees C were made this way.

When runs were attempted with KCl another problem developed with the alkali source. Since KCl melts at 760 degrees C, it was decided to investigate what effect molten alkali would have on the quartz by putting some KCl in one of the old inserts, heating it to 850 degrees C and then letting it cool to room

temperature (simulating the initiation, performance and termination of a run). KCl shrinks considerably when it cools from a liquid to a solid, and since it wets the quartz rather well, the insert cracked when it was cooled to room temperature. This is unsatisfactory, of course, since the insert would not be able to hold the KCl if it was melted again. Other materials and anti-wetting agents are currently being investigated to circumvent this problem.

2.2 Experimental Procedure:

In earlier studies (5,6) it was found that activated bauxite and kaolinite were effective adsorbents for KCl and NaCl with and without the presence of oxygen. Based on these results, those two adsorbents were chosen for further study.

Activated bauxite samples (Engelhard high alumina Porocel) were prepared by first crushing and then sieving to retain the fraction larger in diameter than 50 mesh. It was then devolatilized under nitrogen at 900 degrees C until all water and volatiles were desorbed, sieved to retain the 45 to 50 mesh fraction and then stored under vacuum until ready for use. The kaolinite (Burgess Pigment Co.) was made into a slurry with deionized water (60 ml of packed powder with 32 ml H₂O) and allowed to dry at room temperature in decanting dishes. Forty-five to fifty mesh particles were made the same way as was the bauxite: Sieve, devolatilize and resieve. Kaolinite flakes were made by cutting the dried slurry with a razor blade into pieces approximately 5 mm X 5 mm. Devolatilization was performed at the beginning of a run for the kaolinite flakes.

Prior to a run the samples were weighed with an analytical balance. The bauxite samples were between 10 and 76 mg, and the kaolinite samples were between 7 and 50 mg. The kaolinite flakes were about 30 mg with an external area between 0.41 and 0.90 cm². The samples were then loaded in the reactor and weighed with the microbalance. The adsorbents in particulate form were evenly distributed in

the bottom of a 0.5 inch diameter, 0.5 inch high platinum mesh basket while the kaolinite flakes were simply wrapped once with the platinum hangdown wire.

After connecting the gas lines and thermocouples, the gas flow was started and adjusted so that the sum of the main carrier gas stream and the dilution stream were 150 sccm. A sample of the gas was sent to the GC and IR for analysis and, if necessary, the individual gas cylinder flows were adjusted to yield 15.2% CO₂, 3.2% O₂, 79.3% N₂ and 2.2% H₂O for the simulated flue gas runs. For the nitrogen carrier gas runs, the gas was sampled with the GC after the reactor to check for oxygen leaks. The microbalance purge N₂ was kept at about 75 sccm.

Next the gas flow through the reactor was reversed by turning off the main carrier gas, opening the auxiliary vent (see Figure 1) and closing the normal vent. The dilution flow was maintained at 150 sccm and the purge N₂ was increased to 175 sccm. This was done so that during the initial heating of the reactor no alkali would come in contact with the adsorbent until all transients had disappeared. The furnace was then raised, and it usually took less than 90 minutes for the reactor temperature and adsorbent mass to stabilize.

Then the purge N₂ was decreased to 75 sccm, the main vent opened, the auxiliary vent closed, and the main carrier gas and dilution gas flows adjusted to achieve the desired alkali vapor concentration. For most of the runs only the initial adsorption rate was desired; in this case adsorption was continued only long enough so that a tangent to the weight profile could be determined. Noise in the microbalance signal and the slow rate of adsorption, however, usually required the adsorption to be continued for several hours. When it was desired to terminate a run, the furnace was lowered and the reactor allowed to cool to room temperature. The sample was then removed for analysis and the strip chart output analyzed.

Adsorption rates were determined by taking from the slope of the weight

profile. The mass of the particulate samples was taken directly from the strip chart; the external surface area of the kaolinite flakes was measured with a micrometer. Particulate samples were mounted for scanning Auger analysis by first breaking them in pieces between two microscope slides. Then they were put on a stainless steel disk by painting one side of the disk with colloidal graphite paint and sprinkling the particles on before it dried. The kaolinite flakes were simply broken in a few large pieces and held on the sample holder with a copper clip.

2.3 Results:

The first set of runs were made with activated bauxite at 800 degrees C in a $N_2/NaCl$ atmosphere, the results of which are shown in Table 2.1. These were the first runs made after quartz wool was put between the alkali reservoir insert and the reactor, so reproducibility was the first thing checked (runs B-1 through B-3) and was found to be acceptable.

In the next set of runs the alkali vapor concentration was varied (B-4 through B-9). In this case both the overall initial adsorption rate (R_0) and the initial adsorption rate per unit initial mass of adsorbent (r_0) increased with alkali concentration. Run B-9 was a repeat of B-4, made to check the reproducibility once again. In these two runs it was also desired to observe what effect a previous adsorption would have on the adsorption of alkali, so after several hours of adsorption, the alkali vapor concentration was reduced to zero by reversing the gas flow. Desorption was observed, and after the desorption rate approached zero, adsorption was again initiated by changing the gas flow to its normal direction and continued until another initial rate could be determined. Although the second initial rate for run B-4 was slightly lower than the first, a previous adsorption appeared to have little effect on

subsequent adsorption. Other investigators (7,8) have noted the reversibility of NaCl adsorption on alumina and activated bauxite.

It was decided to investigate the effect of any mass transport on the adsorption rate; so in the next set of runs (B-10 and B-11 to be compared with B-1 through B-3) the sample mass was changed and the alkali vapor concentration was kept constant. It can be seen that sample mass had no effect on the overall initial adsorption rate. It was concluded that transport of the alkali vapor from the top edge of the basket to the bauxite was completely controlling the adsorption rate under these experimental conditions. To see at what point the kinetics of adsorption would become important, several additional runs were made at a low alkali vapor concentration (B-12, B-13 and B-8). Here it can be seen that mass did have some effect on R_0 , but it was not a direct proportionality (r_0 was not constant), suggesting that under these conditions both kinetics and mass-transfer to the bauxite were important in determining the initial adsorption rate. Since additional modifications to the alkali reservoir would be required to further reduce the alkali vapor concentration (thus allowing kinetics to completely dominate the adsorption rate), it was decided to first do experiments with kaolinite particles with the reactor in its present configuration.

Several runs were made with the 45-50 mesh kaolinite at 800 degrees C in the $N_2/NaCl$ atmosphere. Reproducibility was checked first, and it was found to be poor. Examination of the reactor indicated that the quartz wool between the insert and the reactor had degraded to such a point as to allow the insert to move, thus changing the alkali concentration. At this point the insert was removed and NaCl was placed directly in the bottom of the reactor. This required more alkali vapor concentration calibration runs, but reproducibility and reliability were greatly improved.

While the calibration runs were being made, some of the kaolinite particles

Table 2.1

ADSORPTION OF SODIUM CHLORIDE BY ACTIVATED BAUXITE

	INITIAL	INITIAL	INITIAL	ALKALI
RUN	MASS (mg)	RATE (mg/hr)	RATE (mg/g-hr)	CONC (ppmv)
B-1	29.3	1.26	43.1	136
B-2	29.1	1.35	46.4	136
B-3	29.2	1.36	46.5	136
B-4	25.0	2.10, 1.87	83.8, 74.5	207
B-5	25.7	1.55	60.4	169
B-6	25.8	1.15	44.6	102
B-7	25.4	0.704	27.7	58
B-8	25.2	0.512	20.3	38
B-9	25.2	1.86, 1.81	73.9, 71.9	207
B-10	19.3	1.36	70.4	136
B-11	9.6	1.34	139.9	136
B-12	75.7	0.555	7.33	38
B-13	9.8	0.315	32.0	38

were broken apart and examined with a light microscope. It was found that after some adsorption had taken place, the particles turned from their characteristic white color to a dark brown. In addition, this dark material was confined only to the exposed surface area, suggesting that the particles were not adsorbing alkali (or the chlorine) uniformly throughout their volume. Based on this and the desire to remove any mass-transfer resistance due to the basket, it was decided to suspend kaolinite flakes directly from the hangdown wire. After the calibration runs several experiments were performed at 800 degrees C in the $N_2/NaCl$ atmosphere with different alkali vapor concentrations. The initial adsorption rate data are tabulated in Table 2.2. Since the reaction appeared to be taking place near the surface of the flakes, the initial adsorption rates were normalized to the flakes' external surface area. At the end of each run the external surface area of the flake was measured with a micrometer and then it was broken in half. In all cases, the dark brown layer was confined to the immediate surface region (less than 50 microns into the solid). To investigate the reversibility of NaCl adsorption on kaolinite, for one run the alkali was turned off (gas flow reversed) after some adsorption had taken place. Unlike the activated bauxite, no decrease in mass was noted, suggesting that the adsorption was irreversible.

Scanning Auger microscopy was performed on both the dark outer layer and the interior of one of the flakes to determine if the layer was actually a product layer. Because the kaolinite is an excellent insulator, very low beam currents had to be used in the analysis; in addition, alkali compounds are easily vaporized by electron bombardment. For these reasons, it was necessary to raster the beam over a rather large region (corresponding to low magnification). The analysis was performed with a 5.0 kV, 18 nA beam rastering over an area of 0.153 mm²; the resulting spectra are shown in Figure 2.3. It can be seen that the

Figure 2.3: Auger spectra of a kaolinite flake after NaCl adsorption. A: product layer, B: flake interior. Adsorption conditions: 800 °C, 150 sccm flow, N₂/258 ppmv NaCl atmosphere. Analysis conditions: 18 nA, 5.0 kV beam rastered over an area of 0.153 mm².

Figure 2.4: Initial alkali adsorption rate (determined from weight change data) as a function of alkali vapor concentration for kaolinite. Adsorption conditions: N₂/NaCl atmosphere, 800 °C, 150 sccm flow.

dark layer contains both chlorine and sodium, but the bulk of the flake contains virtually none of either one, suggesting that the brown layer is indeed a product layer. Because this layer is formed, and since the flake is porous, the adsorption rate must be controlled by either alkali transport through a gas film to the flake or by diffusion through the product layer. The initial adsorption rate per unit area of the flake is plotted as a function of alkali vapor concentration in Figure 2.4; there appears to be a linear relationship between the two.

Since other investigators (9) (Emathlite-Mid-Florida Mining Co.) noticed an increase in NaCl adsorption rate for a similar mineral in the presence of water, it was decided to do a series of experiments in a simulated flue gas environment that contains water. The gas consisted of 15.2% CO₂, 3.2% O₂, 79.3% N₂ and 2.2% H₂O. All other conditions were kept the same (800 °C, 150 sccm total flow). The initial rate data are given in Table 2.3 and a plot is given in Figure 2.5. Although there is more scatter, it appears that a linear relationship exists between the initial adsorption rate and alkali vapor concentration for these runs as well. Although the slopes of these plots are nearly the same, several differences were noticed between this set of runs and those done in the N₂/NaCl atmosphere. In all cases, the brown product layer was much lighter in color, but still noticeably there. For some runs the layer itself developed minute cracks, but not in others. It isn't clear at this point if the cracks developed at the termination of the run while the flake was cooling or if it happened during adsorption. In addition, the product layer was considerably thicker than comparable flakes that had adsorbed alkali in the N₂/NaCl atmosphere (same alkali vapor concentration, mass gain, temperature, flow rate).

The adsorption was found to be irreversible, just as it was for the N₂/NaCl kaolinite runs. In one run the adsorption was allowed to continue until there

Table 2.2

INITIAL RATE DATA FOR THE ADSORPTION OF
SODIUM CHLORIDE ON KAOLINITE FLAKES

N₂/NaCl/800 °C

	INITIAL	FLAKE	INITIAL	NaCl
<u>RUN</u>	<u>RATE(mg/hr)</u>	<u>AREA(cm²)</u>	<u>RATE(mg/hr-cm²)</u>	<u>CONC(ppmv)</u>
K-1	0.872	0.732	1.191	258
K-2	0.665	0.692	0.961	216
K-3	0.782	0.903	0.866	184
K-4	0.618	0.797	0.775	154
K-5	0.446	0.821	0.544	104

Table 2.3

INITIAL RATE DATA FOR THE ADSORPTION OF
SODIUM CHLORIDE ON KAOLINITE FLAKES

SIMULATED FLUE GAS/NaCl/800 °C

	INITIAL	FLAKE	INITIAL	NaCl
<u>RUN</u>	<u>RATE(mg/hr)</u>	<u>AREA(cm²)</u>	<u>RATE(mg/hr-cm²)</u>	<u>CONC(ppmv)</u>
K-6	0.752	0.585	1.286	258
K-7	0.722	0.588	1.227	214
K-8	0.675	0.741	0.910	183
K-9	0.561	0.812	0.691	157
K-10	0.302	0.439	0.688	122
K-11	0.269	0.412	0.653	107

was no further weight change. The weight/time profile for this run is shown in Figure 2.6. Fracturing the flake from this run revealed that no product layer was present, but the entire thickness of the flake was a light brown color, suggesting it was completely reacted.

Scanning Auger spectroscopy was performed on a broken flake from a run that was terminated before complete adsorption (a product layer was present) in the same manner as before (5.0 kV beam rastered over an area 0.153 mm^2) but it was necessary to use a lower beam current (6 nA) to avoid charging. Breaking the flake in half revealed that a crack separated the product layer from the flake's interior. This can be clearly seen in an SEM image of the flake's broken edge (Figure 2.7). Auger analysis of the product layer showed it to contain sodium (Figure 2.8), but chlorine was clearly absent, in contrast to the product layer formed in the N_2/NaCl experiments. Since the sodium signal was rather strong, an attempt was made to map sodium for the region of the SEM image in Figure 2.7. The map, shown in Figure 2.9, indicates a larger amount of sodium is present in the product layer than in the flake's interior (The brighter the dot, the higher the sodium Auger signal intensity) but a considerable amount of background noise is present. To be certain that the sodium was confined to the product layer, Auger spectra were collected at a higher magnification on each side of the boundary (Figure 2.10). The spectra reveal that sodium is indeed confined to the product layer.

Figure 2.6: Weight gain profile for a kaolinite flake. Calcined mass prior to adsorption: 21.6 mg. External surface area: 0.585 cm². Adsorption conditions: 15.2% CO₂, 3.2% O₂, 79.3% N₂, 2.2% H₂O/NaCl atmosphere, 800 °C, 150 sccm flow, 258 ppmv NaCl.

Figure 2.7: SEM image of the broken edge of a kaolinite flake after alkali adsorption showing product layer and the flake interior. The vertical crack in the left-center field of view coincides with the product layer/flake interior interface, the latter being on the left. The boxed regions on the right and left correspond to the areas from which the Auger spectra in Figures 2.10 A and B, respectively, were taken. Total weight gain: 1.69 mg. Adsorption conditions: 15.2% CO₂, 3.2% O₂, 79.3% N₂, 2.2% H₂O/NaCl atmosphere, 800 °C, 150 sccm flow.

Figure 2.8: Auger spectrum of the product layer for the kaolinite flake shown in Figure 2.7. Analysis conditions: 6 nA, 5.0 kV beam rastered over an area of 0.153 mm². Sample was tilted 30° from the beam normal.

Figure 2.9: Sodium Auger map of the region imaged in Figure 2.7. Brighter spots correspond to higher sodium signal intensities. Analysis conditions: 6 nA, 5.0 kV beam, sample normal to the beam. Collection time: 8.5 min.

Figure 2.10: Auger spectra of the broken kaolinite flake imaged in Figure 2.7. "A" is on the product layer near the product layer/interior interface and "B" is on the interior side of the interface. Analysis conditions: 6 nA, 5.0 kV beam rastered over an area of 0.0024 mm². Electron beam was normal to the sample surface.

3. Agglomeration Characteristics of Ash and Additive Particles

3.1 Method of Approach:

The primary goal of this study is to develop a reliable method for measuring the agglomeration tendency of the particles and relate this tendency to the chemical composition (and particularly the alkali content) of the particles. The information will be particularly valuable if the measurements are done in-situ without having to remove the sample for detection of agglomeration. The main idea behind the experimental approach has been to relate agglomeration to fluidization characteristics of the particles. These characteristics can be continuously monitored in-situ without removing the samples.

3.2 Experimental Apparatus

A fluidized bed has been designed which allows controlled adsorption of alkali while fluidization characteristics of the particles are monitored. The pressure drop across the bed is found to be a convenient fluidization parameter to be monitored. Since the bed consists of particles of approximately the same size, there is a noticeable change in pressure drop at the onset of agglomeration.

Several reactor configurations have been tried. The initial design of the reactor is shown in Figure 3.1. This set up consists of a U-tube shape quartz reactor with a larger diameter in one side. A quartz insert with a slightly smaller diameter can be inserted in and out of the reactor. The function of the insert is to contain the substrate over a 100-mesh stainless steel screen as well as the alkali quartz pan, shown also in Figure 3.1.

Using this reactor, we were able to obtain fluidization of the substrate and subject it to alkali vapor. However, in order to place the alkali pan inside the insert and have enough spacing around it for the gas flow, the diameter of the

Figure 3.1: Schematic of the initial reactor design
A, Connector; B, Quartz reactor;
C, Hook; D, Insert;
E, Fluidized Bed F, Screen
G, Alkali source in a quartz pan.

insert and one side of the reactor had to be large. Effectively the amount of substrate would be larger when the diameter increases for the same height of bed, and the fluidization gas flow increases since it depends on the (diameter/height) ratio of the bed.

The disadvantages of the high flow rate in this design is that the gas flow had to be split into two portions once it gets to the insert. Part of the flow passes through the insert to fluidize the substrate while the rest of the gas passes between the outer wall of the insert and the inner wall of the reactor. This latter part of the flow increases as the main flow increases and does not contribute to fluidization. Furthermore, measuring the flow needed for fluidization is not possible in this case since the flow meter measures the total gas flow. In addition, the flow passing through the sides carries some alkali vapor causing devitrification of the insert and the reactor walls. The advantage of this arrangement is that it is possible to replace the insert after a few runs without having to replace the entire reactor. The above observations suggested that a modification in design was needed to be able to measure the fluidization flow effectively.

The latest design is a U-tube shape reactor shown in Figure 3.1 with a 0.7 cm inner diameter which is approximately one-third of the insert diameter used in the original design. The substrate is supported by a 100-mesh stainless steel screen fitted inside the reactor. The alkali powder is placed on the bottom of the reactor in a quantity that would not plug the flow of the gas once it melts under high temperatures. The gas flow enters one side of the reactor carrying with it the alkali vapor and fluidizing the substrate.

The advantage of this set up is that the gas flow rate going through the bed can be measured directly by the flow meter. Moreover, the quantity of the substrate used is considerably less than what was used in the previous reactor.

Figure 3.2: Schematic of the experimental apparatus.
 A, Quartz reactor; B, Fluidized bed;
 C, Thermocouple; D, Alkali source;
 E, Electronic furnace with PID controller;
 F, Nitrogen; G, Air;
 ΔH , Pressure drop across the bed;
 I, Water manometer; J, Scale;
 K, Precision metering valve.

Measuring the pressure drop across the bed is easier in this system because there is no insert to obstruct the flow. Furthermore, This reactor is less expensive and can be replaced more frequently as it is devitrified due to exposure to alkali vapor.

A schematic diagram of the entire experimental apparatus is shown in Figure 3.2. Compressed gas cylinders provide the required gas which passes through a flow meter and then through a T-connection where one end is connected to a water manometer. The other end brings the gas flow to the inlet of the reactor. A precision metering valve controls the amount of gas flow needed to fluidize the bed. The gas flow leaving the reactor passes through another T-connection where one end is connected to the manometer so that the leaving gas pressure can be detected. The other end of the T-connection serves as a vent.

The location of the reactor is fixed on the furnace stand. The high temperature required for these experiments is provided by a vertical furnace which can be moved up and down around the reactor. The furnace temperature can be controlled by a PID controller. In addition, thermocouples are attached to the side of the reactor to determine the temperatures at the exact location of the fluidized bed and/or the alkali source.

The pressure drop through the fluidized bed is determined from the differences between the inlet and the outlet pressures of the gas flow in the reactor. This is indicated by the vertical distance (ΔH) determined from the scale attached to the manometer.

3.3 Experimental Procedure

Our goal in these sets of experiments was to determine the onset of agglomeration for different substrates subjected to alkali vapor as a function of temperature in a fluidized bed reactor.

The first task is to prepare the substrate in the form of particles ranging

in size from (60-80) mesh which can be supported on the 100-mesh screen. Thus, the particles for a given substrate are sieved to select the fraction between 60 and 80 mesh. Next, the screen is fitted tightly inside the reactor tube 22 cm above the bottom of the reactor. This distance allows the bed to be at an approximate temperature of 50°C lower than the temperature of the alkali source located at the bottom of the tube. The substrate is then placed over the screen in the tube to a bed height of two centimeters. This height, when the bed is fluidized, provides a detectable pressure drop across the bed by the ΔH indication in the manometer.

Before raising the furnace, the flow rate for fluidization of the substrate is adjusted by the precision metering valve to the desired value. Since the fluidization flow rate corresponds to the bed and the gas being at room temperature, a correction for this value must be calculated to account for the high temperature of the gas under running conditions. That is, we need to determine the flow rate needed for fluidization under the actual high temperature of the experiment.

The devolatilization of substrate is accomplished by setting the furnace temperature to the same bed temperature when the adsorption of alkali would be taking place. Devolatilization of the substrate before introducing the alkali is necessary in most substrates in order to volatilize all water vapor molecules from the bed or to let any reaction which would occur at that temperature go to completion before the introduction of alkali. This is useful so that we can conclude, when agglomeration occurs, that it is mainly due to alkali adsorption making the process easier to understand.

When devolatilization is completed, the alkali is introduced in powder form (potassium chloride, KCl, in these experiments) through the side of the reactor where the gas flow enters. The alkali settles at the bottom where the

temperature is high enough to melt and vaporize it. The vapor is carried by the gas flow, nitrogen, going through the fluidized bed. Reaction between the substrate and the alkali occurs at this step where all particles in the bed are uniformly subjected to the alkali vapor.

To determine the onset of agglomeration in our experiments we needed a criteria and a method to detect it. After several initial experiments, we found out that fluidization uniformity in the bed stays approximately the same before and after introducing the alkali for a certain period until defluidization occurs. "Defluidization" is the condition when the bed starts losing fluidization and particles stop moving freely. At this point, due to adsorption of alkali, particles start to adhere to each other until at some point tunnelling occurs in the bed where the gas flow creates an easier path to go through the particles.

Sieving experiments and optical microscopic detection showed that particles in the substrate at the point of defluidization actually started to stick to each other. In addition, part of the substrate that did not pass through the 60-mesh sieve showed agglomerates of particles sticking together due to alkali adsorption. From these evidences we decided to use the defluidization of the bed as a criteria for the onset of agglomeration in a given substrate (or minimum agglomeration). When the bed is uniformly fluidized a constant ΔH is apparent in the manometer with regular oscillations due to the movement of the particles. The pressure drop reading remains approximately the same until conditions in the fluidization change. This happens at the point of defluidization where tunnelling occurs through the bed. At this point, the gas flow finds a passage with the least resistance through the particles making the pressure across the bed drop suddenly. Furthermore, since the particles in the bed are not moving, the oscillations in ΔH die down. Hence, when the regular ΔH throughout an

experiment drops suddenly and oscillations cease to exist, the experiment is terminated and the furnace is lowered. The time for defluidization to occur varies with the type of substrate and temperature. Thus regular monitoring of ΔH is necessary since we need to know the content of alkali in the substrate at the onset of agglomeration.

After experiments are terminated, samples are subjected to atomic absorption analysis to determine the content of alkali in the substrate at a given temperature of minimum agglomeration. In addition, part of these samples are analyzed for their surface characteristics using the Scanning Auger Spectroscopy.

3.4 RESULTS:

Five different substrates were tested to determine the extent of agglomeration at a given temperature due to potassium chloride (KCl) adsorption. The minimum temperature was the temperature at which KCl condenses (approximately 750°C). If the fluidized bed is below this value, KCl vapor would condense on the walls of the reactor before it reacts with the substrate. Adsorption becomes very slow and minimum agglomeration would not take place in a reasonable amount of time. The upper temperature in these experiments were set by the furnace maximum temperature. This is 1100°C for the substrate location within the reactor.

Figures 3.3 through 3.7 show the experimental results for the dependence of onset of agglomeration (minimum agglomeration) temperature on potassium (K) content of the various substrates. The temperatures for agglomeration of the different substrates, which occurs due to initial melting and fusing of particles together (without KCl adsorption), were also determined. This was done by placing a fresh sample of a substrate into a quartz pan which in turn is placed in a high temperature furnace (max. 1600°C). At different temperatures the

Figure 3.3: Dependence of minimum agglomeration temperature on potassium (K) content of bauxite.

Figure 3.4: Dependence of minimum agglomeration temperature on potassium (K) content of kaolin.

Figure 3.5: Dependence of minimum agglomeration temperature on potassium (K) content of lime.

Figure 3.6: Dependence of minimum agglomeration temperature on potassium (K) content of Utah bituminous coal-ash.

Figure 3.7: Dependence of minimum agglomeration temperature on potassium (K) content of Beulah ash (low sodium)

sample is observed under optical microscope for initial fusing of particles. When this occurs, the experiment is terminated and the temperature recorded. The percent of alkali corresponding to this temperature is taken as the content of alkali in the fresh sample before it is placed into the high temperature furnace.

Figure 3.3 shows an increase in agglomeration temperature as K concentration decreases for bauxite. For this substrate, under KCl adsorption, the minimum temperature for onset of agglomeration we were able to detect in a reasonable amount of time (order of 10 hours) was 950°C. If the fluidized bed temperature were to be set below 950°C (between 750-950°C) under KCl adsorption conditions, agglomeration would eventually take place probably after a few days. Furthermore, this figure gives an idea of the bauxite capacity for adsorption of alkali (KCl in this case). A value of 24% K in bauxite was adsorbed at 950°C when minimum agglomeration of the particles took place. Surface analysis of some particles after adsorption was performed by the Auger Scanning Multiprobe. Concentrations maps of bauxite particles indicated that surfaces were covered with KCl. In addition, analysis of crushed particles showed that KCl was even adsorbed within the bulk of particles.

The time involved in each agglomeration experiment varies depending on the substrate and the fluidization temperature. In general, for all substrates tested, the time needed for agglomeration under KCl adsorption increased with a decrease in the fluidized bed temperature. Furthermore, at a given temperature, agglomeration time increases with substrates that have more capacity of adsorbing KCl, like bauxite.

Another good adsorbent of KCl vapor, which gave close results to bauxite, is kaolin. The agglomeration results for this substrate is shown in Figure 3.4 indicating the same trend of decreasing K content as temperature increases. In fact, at 950°C, potassium concentration was 24% which is the same result as the

bauxite tested.

Lime was not as good of an adsorbent as bauxite or kaolin. Figure 3.5 shows that at 850°C lime had adsorbed 3.6% of K at agglomeration. Comparing with bauxite and kaolin, lime contained approximately (0.5)% of K at 950°C for minimum agglomeration. This value is 98% lower than bauxite or kaolin. On the other hand, the curve for lime shows the same trend for the dependence of agglomeration temperature on K content.

Figure 3.6 shows the agglomeration results for Utah bituminous coal-ash. Here, the difference from the other substrates is that potassium is originally present in the fresh samples before adsorption experiments. Minimum agglomeration occurred much faster and at lower K concentrations than the other substrates. The maximum K concentration obtained for this ash was 1.0% at 750°C. This figure also shows a sharp rise in temperature from 865°C for the 0.5 K content of adsorption agglomeration run to 1075°C for the 0.46 K content of agglomeration of a fresh sample.

The Beulah ash (low sodium content) was also tested for agglomeration where the results are shown in Figure 4.5. The original fresh samples had 1.0% K concentrations which are almost double the amount of K in the bituminous ash. In addition, the Beulah ash showed a higher capacity for adsorbing the KCl alkali than the bituminous. This reached about 8.4% at 770°C. Though the trend of increasing agglomeration temperature as alkali content decreases is the same as the previous tested substrates, the best fit to the Beulah ash data points appeared to be a straight line for this range of experiments. This does not mean that there is a linear relation between agglomeration temperature and K concentration for Beulah ash. More experiments in the range of (900 to 1100)°C may help to verify the shape of curve.

In conclusion, the experiments using different substrates indicate a common

trend for the dependency of minimum agglomeration temperature on the potassium content. Future experiments using other alkali salts (NaCl for example) and the measurements of the surface layer concentrations would give a better understanding the fundamental relationships between agglomeration, bulk concentration and more importantly, the surface layer concentration.

4. References

1. Neville, M. Quann, R.J., Haynes, B.S. and Sarofim, A.F., 18th symp (intl) on Combustion, The Combustion Institute, Pittsburgh, PA, P 1267 (1981).
2. Neville, M. and Sarofim, A.F., 19th Symp (intl) on Combustion, The Combustion Institute, Pittsburgh, PA, p1441 (1982).
3. Linak, W.P. and Peterson, T.W., 21st Symp (intl) on Combustion, The Combustion Institute, Munich 1986.
4. Natusch, D.F.S. "Characterization of Fly Ash from Coal," NTIS C00-4347-4 (1978).
5. Shadman, F., Peterson, T.W., Wendt, J.O.L. and Punjak, W.A., quarterly Report to DOE, Contract DE-FG22-86PC90505, February 1987.
6. Shadman, F. and Punjak, W.A., paper presented at the Western States Section of the Combustion Institute Meeting, Tucson, AZ, October 1986.
7. Luthra K.L. and Le Blanc, O.H., Jr., J Phys. Chem. 88, 1896(1984).
8. Lee, S.H.D., Henry, R.F. and Myles, K.M., Argonne National Laboratory Report CONF-850351-3 (1985).
9. Bachovchin, D.M., Alvin, M.A. Dezubay, E.A. and Mulik, P.R., Westinghouse Research and Development Center, DOE Report No. DOE-MC-20050-2226. (1986).

**DATE
FILMED**

10 / 9 / 92