DECEMBER 1991

DOE/CE/27504--T1
DE93 005619

**SUSTAINABLE SYSTEMS
RATING PROGRAM**

**Marketing "Green" Building in
Austin, Texas**

**Energy Task Force
of the Urban Consortium**

**AUSTIN, TEXAS
Environmental and Conservation
Services Department**

PREFACE

1991 URBAN CONSORTIUM ENERGY TASK FORCE RESEARCH

THE URBAN CONSORTIUM (UC) is a special network of the Nation's largest cities and urban counties brought together by PTI to find new solutions to their common concerns. The UC provides a creative forum where elected and appointed officials can identify, test, and validate practical ways to improve the provision of public services while generating new revenue opportunities. With staff, management, and business services provided by PTI, the UC addresses the critical needs of large local governments through its three task forces: Energy, Environment, and Telecommunications and Information.

The Urban Consortium Energy Task (UCETF) has 20 members and was established to improve urban energy management and decision-making through applied research and technology transfer. The UCETF focuses on developing and sharing new approaches and innovative solutions to energy management problems with local governments. Projects are organized in thematic units and co-managed by a member of the Task Force.

A description of the 1991 program Units and projects are:

ALTERNATIVE VEHICLE FUELS AND TECHNOLOGIES (AVF)

Alternative vehicle fuels offer a very strong potential to aid in the reduction of U.S. dependence on foreign oil supplies, with the resulting benefits of decreased air pollution in urban areas. Local governments can play an instrumental role in realizing this potential through practical applied research and highly visible demonstrations of alternative fuels and technologies. Issues addressed this year include identifying (a) intensive and credible market development efforts based on an applied research and demonstration program that combines reliable technology with experience-tested applications, (b) environmental and energy diversity benefits, and (c) institutional and infrastructure barriers. The 1991 AVF unit consists of:

Broward County, FL -- *Dual-Fuel Conversion Demonstration and Technology Transfer Project*

New York City, NY -- *Alternative Fuel Vehicle: Financing Issues*

Denver, CO -- *Technical and Market Comparison Between H₂/CNG (Hythane), Electric Hybrid, and CNG Fueled Vehicles*

Denver, CO -- *An Alternative Fuels Fleet Evaluation System -- A Transfer Project*

Detroit, MI -- *Analysis of Institutional and International Limitations for Alternative Fuel Vehicles*

Washington, DC -- *Comparison of Energy Consumption, Energy Savings, and Environmental Effects of EV/PV vs. Conventional Gasoline Vehicle*

ELECTRICITY MANAGEMENT

Urban interests for electricity management focus on means to maintain stable, secure and reasonably priced supplies of electric energy. Approaches include procedures for better demand management, application of "least cost" planning concepts, appropriate use of decentralized and/or small power production facilities, improved end-use efficiency, and developing sound structures for cooperative action among municipalities and energy utilities. Urban strategies include support for decentralized "small" power production, along with better demand management and improved end-use energy efficiency. The successful development and implementation of such strategies will require close cooperation with the utility industry and will address topics in areas of institutional relations, source flexibility, and demand-side management. The 1991 Electricity Management Unit consists of:

Albuquerque, NM -- *Alternatives to Traditional Rate Setting*

Chicago, IL -- *Integrating Innovative Supply and Efficiency Techniques*

Chicago, IL -- *The Chicago Energy Management Cooperative*

Dade County, FL -- *Energy Cost Reduction Through Resource Recovery*

Detroit, MI -- Hydraulic Waste Energy Recovery (Phase II) City of Detroit Water Distribution System

San Jose, CA -- Utility/Local Government Partnership to Increase Energy Conservation in New Construction

ENERGY EFFICIENT FACILITIES

Activities involving energy efficient facilities are at present, part of a national effort to achieve maximum cost-effective energy productivity in the building sector. There exists a need for collaboration between local government officials responsible for energy and environmental programs and other local government officials responsible for facilities, as well as the Federal officials and private sector groups, e.g. utilities. New technologies and management/administration practices to advance energy efficiency in facilities require major partnership efforts and transfer programs. Multi-family housing that has a large concentration of low-income families presents a unique challenge to lowering energy costs and maintaining energy efficient facilities. Projects in this unit are:

Boston, MA -- Neighborhood Energy Efficiency Outreach Partnership

Columbus, OH -- Energy Efficiency and Indoor Air Quality: Solutions for Fire Stations

Louisville, KY -- Partnership Approach to Energy Efficiency in Non-Profit Facilities

Montgomery County, MD -- Technology Transfer of Building Energy Design Guidelines

New Orleans, LA -- Residential Utility Costs Comparative Study

Phoenix, AZ -- Variable Frequency Drive Applications Guide

Portland, OR -- Energy Savings Through Operation and Maintenance Training in the Low-Income Multi-Family Sector

Washington, DC -- Comparison of Two Techniques for Identifying Energy Conservation Measures in Low Income Homes

ENERGY, ENVIRONMENT and ECONOMIC DEVELOPMENT

This an area that has both visionary and immediate practical emphases on the definition and evaluation of realistic strategies and actions to support energy-sustainable and

environmentally responsible communities. Emphases include uses for renewable energy, practical domestic supply and conservation alternatives, and the synthesis of energy concerns with wider local government interests in economic development, environmental quality, and internal cost control. Urban strategies to improve energy-sustainability require attention to both broad based institutional changes, as well as specific projects designed to encourage the application of appropriate technology and community development practices. The "Sustainable Communities" project has involved three municipalities with State agency, Lawrence Berkeley National Laboratory, and a formal advisory committee with broad national representation. Projects under this unit are:

Austin, TX -- Energy Star Sustainable Rating Program

Phoenix, AZ -- Impact of Heat Island on Cooling and Environment: A Demonstration Project

Pima County, AZ -- Tucson Solar Village - Project Management

Portland, OR -- Sustainable City Transfer Project

San Francisco, CA -- Neighborhood Energy/Economic Development at South Bayshore

San Francisco, CA -- Sustainable City Transfer Project

San Jose, CA -- Sustainable City Transfer Project

Seattle, WA -- Coordination of Energy and Air Quality (CEAM)

Seattle, WA -- Bicycle Program -- Urban Trails System

Tucson, AZ -- Local Government Involvement in Long Term Resource Planning for Community Energy Services

Reports from each of these research projects, including this report, are specifically designed to aid the transfer of proven experience to other local governments. Readers interested in obtaining any additional reports or further information about the Urban Consortium Energy Task Force and the Urban Consortium should contact:

*Energy R&D Program
Public Technology, Inc.
1301 Pennsylvania Avenue, NW
Washington, DC 20004
1-800-852-4934*

ACKNOWLEDGEMENTS

Project staff wish to express their appreciation to the many individuals who have assisted in this effort.

Special thanks are due to the co-directors of the Center for Maximum Potential Building Systems, Gail Vittori and Pliny Fisk III, who served as partners in this project for their dedication and valuable contributions to its development; members of our advisory committee, Gail Borst, Jeanne Evans, Kenneth Foster, Nick Holland, William Moore, Mary Oetzel, M.J. O'Neal, Harry Savio, Tom Shefelman, for their evaluative assistance and encouragement; members of the Urban Consortium Energy Task Force and Public Technology Incorporated for their support and interest in this project.

We sincerely appreciate the cooperation and input of our colleagues - Beauford Anderson, Susan Barnett, Kevin Batt, Bert Brown, Tony Gregg, Oscar Ibarra, Mary McLeod, Lori Megdal, Antoinette Springs.

Our research assistants are warmly thanked for their long hours of high quality work: Lucia Athens, Alex MacGregor, Dhruba Sanyal.

Finally, we gratefully acknowledge the guidance and insight provided by our Project Director, Michael Myers, during this effort.

Project Staff

Doug Seiter

W. Laurence Doxsey

CONTENTS

	<u>Page</u>
CHAPTER 1 - - SUSTAINABLE SYSTEMS RATING PROGRAM OVERVIEW	
Abstract	1
Project Purpose	2
Report Organization	3
CHAPTER 2 - - THE CONCEPTUAL DEVELOPMENT OF MARKETING SUSTAINABILITY	
Introduction	5
The Marketing Approach to Change	7
Blending Sustainability and Marketing	10
The Sustainability Model	11
CHAPTER 3 - - DEVELOPMENT OF THE GREEN BUILDER PROGRAM	
Introduction	15
The Rating System	18
Resource Issues	
Subsystems	
Evaluative Criteria	
Conceptual Framework	
Self-Rating Systems	
Confining the Scope and Selecting Options	
Assigning Values	
Rating a Home	
Marketing	40
Advisory Committee	41
The Eco-Home Guide	41
Computer Software Review	42

CHAPTER 4 - - SUMMARY

Lessons Learned	44
Next Steps	45
Encouraging and Locating Exemplary Projects	
Professional Educational Outreach	
Transferability Issues	46
Burden of Proof	
Recent Research	
The Local Model	
Options and Values	
Summary of Transferability Considerations	
Concluding Remarks	50

BIBLIOGRAPHY	51
---------------------	----

APPENDICES

A - The Eco-Home Guide Rating Section and Glossary	55
B - Sustainable Systems Rating Evaluation Worksheets	83

ILLUSTRATIONS

Figure 2-1: Energy Star Logo	9
Figure 2-2: The Sustainability Model	12
Figure 3-1: Energy Guide Label	17
Figure 3-2: Residential Subsystems	21
Figure 3-3: Resource Integration Diagram	23
Figure 3-4: Relational Field Matrix	23
Figure 3-5: This Rating Procedure (Option A) Involves the Rater at a Basic Level of Inquiry	25
Figure 3-6: Rating Information Base (Option A)	26
Figure 3-7: Criteria for Rating	28
Figure 3-8: Sample Indoor Water Options from the Eco-Home Guide	28
Figure 3-9: Sample of Rating Format with Options, Point Values, and the Places for the User to Record their Score	38
Figure 3-10: Rating Summary Page	39

CHAPTER 1

SUSTAINABLE SYSTEMS RATING PROGRAM OVERVIEW

ABSTRACT

Within recent years, analytical efforts have aimed at understanding the balancing of basic human needs and economic activities with the underlying life support systems of the natural environment. While these relationships are studied, development continues with little recognition of sustainable building practices, due in part to a lack of usable information on the subject. Although sustainability could be considered common sense as much as a complex concept, building a home in our society has rarely been approached from a sensible point of view in terms of global and local resource impacts.

The Sustainable Systems Rating Program was designed to present an holistic analytical model based on the concept of sustainability, and incorporate it into a marketing program aimed at fostering sustainable (earth-friendly) construction practices for new homes. The City of Austin's Energy Star Rating Program was selected as being applicable to this project because of its success in improving the energy efficiency of new homes through marketing. Because the building industry is very supportive of this positive approach, it was seen as a viable mechanism for introducing the idea of sustainability to the public.

The project identified four major resource issues for home construction: water, energy, materials, and waste. A systems flow model was then developed that tracked the resource issues through interactive matrices in the areas of sourcing, processing,

using, and disposing or recycling. This model served as the basis for a rating system used in an educational and marketing tool called the Eco-Home Guide.

Intended for the general public and the building community, the Eco-Home Guide is the primary marketing product of this project. It incorporates a background presentation of the four resource issues and a rating system that presents options and assigns values to them based upon predetermined criteria. Builders and homeowners will be able to use the Guide to "rate" their prospective new home with regard to sustainability in the four major resource areas.

In developing the rating system for this project, a large gap in the availability of pertinent data or a tested analytical approach for quantifying environmental factors was encountered. A rating approach was thereby designed that will accommodate new information as it is developed. The rating system in its current form bases its values on a combination of quantitative and qualitative inputs.

Throughout the development process of this project, an advisory committee of in-house staff and citizens representing various components of the local building industry reviewed and provided input on the rating system and the marketing materials. The advisory committee's role provided a preliminary test marketing of the project's approach. This was extremely beneficial to the effort of simplifying the presentation of the complex subject of sustainability.

The next step for the program is to provide technical assistance to the building community for implementing options identified in the Eco-Home Guide. Concurrently, ongoing educational efforts through media articles and speaking engagements will be needed to reinforce the program's impact on building practices. The rating system will be adjusted as new information and market feedback dictate.

PROJECT PURPOSE

The purpose of this project was to develop a sustainability rating system that can be used as a marketing tool to encourage high levels of resource conservation, appropriate resource usage, and positive economic development through new residential homebuilding. Rating systems such as Austin's Energy Star Rating Program have become recognized as effective methods to bring about energy conservation. The City's sustainable rating system uses this precedent to lead homebuyers to look at and demand new homes that conserve all natural resources, minimize pollution, and positively affect the local economy.

The major tasks of this project entailed the following:

- Identify the key resource issues that are encompassed by a new residential building.
- Determine the evaluative criteria through which the resource issues can be considered.
- Develop a model through which measurable impacts can be ascertained.
- Translate the model into a simplified presentation and rating system that is usable by the general public as an educational tool and as an aid in evaluating current and new approaches in home design and construction.

This report describes the process of developing the rating system and the overall marketing program, and identifies issues, problems and successes throughout the process. The rating system, as part of a comprehensive marketing program, offers a transferable strategy to shift homebuying consciousness such that housing is generally improved and the local economy is strengthened without compromising the quality of the environment.

REPORT ORGANIZATION

This report presents the development of a sustainable rating system and the plan to implement it successfully.

Chapter 2 presents the conceptual underpinnings of sustainability and its potential as a new paradigm to achieve social, economic and environmental benefits. This chapter then discusses the marketing approach as a mechanism to successfully introduce and influence the use of sustainable building practices.

Chapter 3 describes the precedent established by the Energy Star Rating Program which served as a model for this project. The development process and the application strategies for this project are then presented. This includes the development of the rating system and its application in the Eco-Home Guide.

Chapter 4 presents a summary of the lessons learned during this project, and looks at the potential of this project and what is needed to be done to achieve full impact and viability. Transferability issues are then discussed, followed by concluding remarks.

Appendices include the Rating portion of the Eco-Home Guide (Appendix A) and the Evaluation Worksheet for determining points in the rating (Appendix B).

CHAPTER 2

THE CONCEPTUAL DEVELOPMENT OF MARKETING SUSTAINABILITY

INTRODUCTION

In selecting sustainability as the underlying premise for the issues associated with new residential housing, this project attempts to achieve a comprehensiveness that exceeds the scope of most analyses that enlist conventional economic models. Sustainability considers the human and natural environment to be intrinsically intertwined. This interrelationship must be balanced in such a manner that both the human and natural environment continue to have basic needs met, and their respective processes intact and operating in a sustaining manner. This implies that a society's economic model must account for this interrelationship on what can be regarded as a single balance sheet. The current economic models do not show the activities and effects on the natural environment as a "cost" but as externalities. The environmental costs must be counted in order to develop a sustainable society.

The sustainability premise vis-a-vis shelter (i.e. housing), strives to reach a balance with the regenerative capabilities (carrying capacity) of the natural environment to meet the associated resource requirements. This project stresses a decentralized perspective in addressing this activity, that requires an extensive understanding of the local ecology such as climate, flora and fauna, geology, hydrology, topography, and more. Interestingly, the reason for this local perspective is as much economical as it is ecological. Seeking to optimize our relationship with the local ecology to meet our basic needs can be associated with the recognized benefits of vertical integration

models and the increasingly common "buy local" approaches. In virtually all communities, this implies an emergence of businesses and "cottage industries" which diversify and help stabilize the local economy.

The natural environment offers a prime example of sustainable systems. Natural processes demonstrate cyclical flows with multi-levels of integration among different flows. Simply examining one component of the natural environment - plants - reveals an interplay of tremendous complexity. Plants play a role in hydronic cycles (creating humidity, preventing erosion, etc.), food cycles (for animals, fish, insects), energy cycles (absorbing and storing solar energy for fuel, feeding decomposition processes), atmospheric gases interactions (absorbing CO₂, releasing oxygen) and more. This integrative aspect of all natural processes not only creates a resilient and interdependent nature but offers a model valuable to consider in designing an analytical approach encompassing sustainability. The natural systems model encourages an interactive systems flow analysis (described in Chapter 3) as the most appropriate tool for designing a rating system that evaluates the relationship of natural processes (the environment) and human activities.

It should be recognized, however, that holistic analyses such as life cycle assessments (and the work in this project) are in their infancy. Due to incomplete statistical research and a lack of agreed upon scientific methodology, each potential user of this approach needs to validate underlying assumptions, such as the sustainability premise indicated above. The ramifications of these assumptions were judged valid by this working group. Nevertheless, the user must understand that both quantitative and qualitative inputs served as the basis for this project.

In following this course, a blend of conservation and energy efficiency, affordability, economic development, personal health, and environmental impact considerations all play strategic roles. The value for public policy to consider this approach becomes most obvious as we all face, in varying degrees, housing shortages and affordability, economic instability, personal health threats, diminishing energy and material resource bases, and pollution as ever increasing liabilities to our communities' quality of life.

In the following section, we will review the reasons for choosing a marketing approach to meet these challenges and the methodology used to develop the content of the marketing program.

THE MARKETING APPROACH TO CHANGE

In evaluating the potential appeal of sustainability for this project the following points about our local area were considered:

1. Value-based actions by the local citizenry are quite common: a strong voluntary recycling program exists, and social, humanitarian, and environmental causes are actively supported.
2. Environmental policy is vigorously debated and often dominates local politics.
3. The local citizenry has an above average educational background.
4. Extensive energy conservation programs provided by the city have a successful history.
5. The Energy Star Rating Program has been successful in raising the demand and subsequent supply of energy conserving homes.
6. A number of environmental award programs exist.
7. A regular weekly supplement to the local newspaper, "Project Earth," promotes environmental awareness.
8. A prevalent understanding of sustainability does not exist within our area.
9. There is not a financial payback to sustainability in a conventional sense.

Concurrent with a rapid increase in local environmental consciousness and activity, national efforts reflecting similar sensibilities have become prominent. The American Institute of Architects (AIA) and the National Association of Homebuilders (NAHB) have engaged in well publicized evaluations and calls for responsible practices in the building industry. The AIA's Environmental Resource Guide (ERG) is a particularly ambitious multi-year project that examines the embodied energy and environmental impacts of essentially all building materials. Both organizations have dedicated a complete issue of their main journals (AIA's Architecture and NAHB's Builder) to "green" building within the past year.

Statistics cited in Builder magazine show that 79% of Americans consider themselves environmentalists; 78% want a major national effort to improve the environment; 76% want businesses to do more; and the environmentally aware individual is willing to pay up to 20% more for environmentally safe products. Overall, the local and national trends indicate that a receptive audience to sustainability ideas exists.

In this project, a marketing approach was selected as the best method to reach this audience and influence positive change in building practices. The reasons for doing this is best understood after briefly reviewing the alternatives.

(1) Financial incentives, such as rebates, have been a common and effective mechanism for promoting energy conservation. Austin has seen the availability of lower efficiency air conditioners (efficiency ratings below rebate minimum qualifying levels) all but disappear from the market. However, the sustainability premise recognizes values outside of conventional economic analysis by internalizing external costs. In a situation where standard return on investment calculations are invalid, the rebate approach is not practical. For example, the direct and indirect costs per kilowatt to provide a rebate on an improved efficiency air conditioner must be the same as or less than the cost per kilowatt to generate new energy, yet adequate to be an incentive. However, a rebate on non-toxic paint does not have a similar benchmark.

Additionally, the high cost of financial incentives specifically for high cost purchases can seemingly hinder the short term financial strength of a public entity.

(2) Award programs serve as an incentive for change in a somewhat limited sense. Beautification and Xeriscape awards, for example, have traditionally appealed to a small sector of the Austin community. A promotional award activity involving sustainability would be hampered by the enormity of the scope. Although the award incentive can only realistically focus on certain aspects of sustainability at this point in time, it is, nevertheless, a viable approach for promoting sustainability due to the educational value of marketing.

(3) Regulatory actions mandating sustainable practices in housing construction would undoubtedly lead to modifications in current practices sooner than through voluntary incentives. Code enforcement and zoning regulations impart immediate long term changes. However, the political forces that must interact to bring about even minor adjustments can result in a time-consuming and difficult process. Additionally, a regulatory approach to change has little effect on cultural assimilation, or inherent understanding of sustainability issues, and in fact may tend to foster resistance to those ideas.

(4) Education programs such as manuals, curricula, public presentations, videos and the like are generally most effective in conjunction with programs that can indicate measured progress. As a stand-alone strategy to foster change, they reach mostly people that already profess interest in the topic, and peripheral beneficial effects develop more slowly than with regulatory or financial incentives. However, an

educational component is highly desirable and beneficial, particularly in tandem with very new ideas and approaches.

(5) A marketing program is a plan to influence and redirect people's buying and selling activities in the marketplace. Marketing program strategies center around a strong educational component and employ a combination of advertising, public relations, point of purchase materials , and the like to affect people's preferences.

The Energy Star Rating Program is a marketing approach that gives new home buyers a mechanism (a rating system) with which they can appraise the energy performance of a home they are considering. The program then puts interested buyers in contact with the builders who provide the rating information on their homes. This approach does not force the building community to adhere to new regulations but, conversely, creates a new selling point for their homes. The Austin Energy Code specifies conservation practices that must be enforced; in contrast, the Austin Energy Star Rating Program has reinforced, over a period of a few years, a conservation ethic (mostly based on economic considerations) in the homebuying public. This has inspired the building community to adjust their building practices to exceed energy code requirements in competitive fashion. This method uses the positive potential of the classical supply and demand system, in which the demand for higher efficiency in homes is driven by the Energy Star marketing and advertising.

Figure 2-1
Energy Star Logo

The rating aspect of the Energy Star marketing approach has proven to be a successful initiative that is being implemented in various versions nationwide. The degree of the success of such programs can be recognized in the fact that a national collaborative for developing a national Home Energy Rating System (HERS) and Energy

Efficient Mortgage (EEM) Program was recently convened by the Department of Energy and the National Renewable Energy Laboratory (formerly SERI).

In summary, the positive points of a marketing/rating approach are:

- **Avoidance of the potential political debate and adversarial relations with the building industry in the adoption of regulations**
- **Financial incentives are not used, therefore reducing program costs**
- **An educational approach can successfully stimulate cultural assimilation**
- **A mechanism for comparison is supplied**
- **A positive, value-laden opportunity (for rating comparative sustainability and having the choice of homes built to reflect environmental concerns) is provided for the local citizenry**

In the next section, we will examine how this project attempts to combine a marketing strategy that is influenced by the Energy Star Rating Program approach with the larger more comprehensive issues of sustainability.

BLENDING SUSTAINABILITY AND MARKETING

The sustainability premise, as stated earlier, is an holistic view that acknowledges extensive interrelationships within and among the human and natural environments. Resource issues are not a matter of only scarcity and economics, but also involve personal health and a full range of environmental impacts. To understand the direction that this project needed to go in order to develop a home rating system, there needs to be a clear understanding of how the issues of sustainability relate to housing.

First of all, it was determined that four resource issues --- energy, water, materials, and waste --- were all basic components of the built environment and should be evaluated similarly. For example, energy efficiency, dealt with exclusively in a variety of programs, becomes a part of a strategy that considers equally the relationships, activities and effects with water, energy, material, and waste life cycles. Within these life cycles, numerous and various environmental impacts occur. Strictly linear relationships within the various life cycles do not exist as there is an interplay among them of varying degrees of complexity. Interestingly, these symbiotic relationships can create new opportunities for optimized resource use. In this project, the secondary and

tertiary effects (interrelationships) during a resource life cycle are termed "integration". This will be discussed in more detail in Chapter 3.

The life cycle view of resources is still only part of the sustainability picture. Each resource has an economic relationship with a community that plays a significant role in the long-term well-being of the community. When resources are obtained over great distances, the economic outlay for the resources tracks back over the distance and essentially depletes the local community of financial resources. Most importantly, the potential economic multiplier effect of local business transactions is eliminated.

In addition to the economic factors, health issues for users and providers should be considered. For example, a building material may use recycled materials but be manufactured in a manner that creates toxic outgassing. "Healthy" home issues can actually conflict directly with resource-friendly options. Balancing health implications with environmental and economic issues adds another level of complexity that can challenge efforts to simplify public outreach.

As can be seen, the sustainable approach introduces new ways of thinking that present problems of accessibility and usefulness for a public that, in large part, is only barely grasping the notions of conservation. To deal with this situation, a marketing plan must acknowledge varying degrees of interest and capacity in the public to understand sustainability. The challenge is to simplify but not overly dilute the subject. Although the Austin area contains a significant number of environmentally conscious citizens, there should be a range of marketing materials that provides an evolutionary approach to the concepts of sustainability.

THE SUSTAINABILITY MODEL

For this project, a model that presents an overview of the cycle needed to place a technology in a sustainable sequence and identify roles for the major players was developed. This model is useful for establishing a balanced relationship with natural resources from the region, byproducts from the urban area, and the human needs of the community. An idealized sustainability model can be viewed as a relationship of the four basic components shown in Figure 2-2.

Figure 2-2
The Sustainability Model

- (1) A defined environment with respect to resource use, availability, and carrying capacity.
- (2) The identification of the local life support requirements.
- (3) A monitoring technique to sense environmental tolerances regarding natural resource use and replenishment techniques.
- (4) The amount of resources needed by people and by the environment in order to retain balance between use and regeneration.

The Sustainability Model serves to illustrate the idealized conceptual relationship between resource use and human needs. Each natural resource and technological process involved in meeting the needs of human society should be monitored to ensure a balanced relationship with the environment's regenerative capacities. A sustainable interplay is achieved when the balanced relationship takes into account the output (byproducts) of human society returning to the environment. Monitoring the give and take between human activities and the environment in the model is an objective process that seeks long term sustainability.

The public sector role in this model is to serve as the representative or caretaker for the environment. In this role, a governmental body coordinates the analysis of the carrying capacity of the resource base and monitors the use of the resources. The

private sector acts in the area of providing the human needs of the public. This idealized model can serve quite well for successful sustainable planning and actions.

In the following chapter, we will present an overview of the current city programs and the political and social environment relating to this project, and then the specific development and application process.

CHAPTER 3

DEVELOPMENT OF THE GREEN BUILDER PROGRAM

INTRODUCTION

The Austin Energy Star Rating Program was developed in 1984 as one of several demand side management (DSM) programs for the City of Austin collectively designed to promote energy conservation in order to curb rising utility rates and the need for costly facility expansions in a community that was experiencing unprecedented growth. The idea of encouraging energy efficiency improvements in new homes through marketing was presented to the local homebuilders association to complement the development of a new energy code for the City of Austin. In short, the rating was offered as an alternative to a more stringent code, with the expectation that the rating would effectively pull levels of efficiency beyond a minimum standard that was palatable to the homebuilding industry.

The energy rating has evolved from a manual worksheet to a sophisticated computer analysis which predicts energy savings and costs with respectable accuracy. Throughout this evolution, however, the fundamental "look" of the rating has been consistent to avoid confusion in the marketplace. The basic criteria of accuracy, simplicity, and usefulness were the standards for improving the program over the past seven years. Points reflect energy cost savings, and rating reports give information on the rated home's physical characteristics and energy (kilowatt-hour) and demand

(kilowatt) savings. To simplify the presentation, three levels of efficiency are denoted by one, two, and three stars, indicating cost savings thresholds of 5%, 12.5%, and 20%, respectively.

An added feature of the Energy Star Rating Program has been the Energy Guide Label, introduced in the spring of 1991. Designed to resemble the yellow labels found on appliances, the Energy Guide Label (shown in Figure 3-1) has been accepted by builders and buyers alike, providing information on heating, cooling, and water heating costs, and a comparison with other area homes.

There are currently about fifty builders enrolled in the Energy Star Program. Due in part to the increased efforts of program staff to regularly contact and serve participating builders, the success of the program is growing. Support from the builders has been steadily increasing, as indicated by the recent highlighting of the Energy Star Program in the annual Parade of Homes.

It is in this environment that the Sustainable Systems Rating Program (which is being introduced to the public as the "Green Builder Program") was initiated. This rating was conceived as a presentation of sustainable building, using the Energy Star Rating as a model for expanding the scope of features to be found in new homes, and providing information and a rating mechanism in the form of the Eco-Home Guide. The Eco-Home Guide (detailed later in this report and shown in Appendix A) is the primary marketing piece. It introduces sustainability, tells builders how to participate in the Green Builder Program, gives information on options to current building practices that may be requested by potential buyers and provided by participating builders, and provides a rating sheet for buyers and builders. The rating sheet gives the potential homebuyer the ability to compare and establish a ranking of different home's sustainability.

The Green Builder Program was first introduced to an advisory committee made up of private sector building professionals, including representatives of the builders association. Since then, various individuals have reviewed the Eco-Home Guide. The response has been consistently supportive and criticisms have been constructive. While modifications are expected in this program, particularly as methodologies emerge that further quantify the value of sustainability, the general acceptance of both the need and the mechanism for achieving change is encouraging.

Although there are significant differences between the technical development of an energy rating for new homes and a rating system for sustainable building products and practices, the fundamental marketing strategy holds true for both. Builders respond to market demand. Informed buyers will seek those builders who provide the desired

Figure 3-1

Energy Guide Label

Estimated annual energy cost for heating, cooling, and water heating will be

THIS HOUSE IS ESTIMATED TO CONSUME % OF THE AVERAGE ENERGY USED FOR COOLING, HEATING AND HOT WATER UNDER AVERAGE WEATHER AND OCCUPANCY CONDITIONS

Your house →

Average house →

product. If the market believes that energy efficiency (or sustainability) is an important feature of a new home, and have access to a credible program that identifies builders who will provide the desired features in their homes, those builders will generally have an advantage in buyer traffic.

As a case in point, when the participating Energy Star builders are listed in print advertising, there is consistently an increase in the activity of builders either joining the program or rating homes, which indicates that builders see the value in the marketing aspects of the program without added financial incentive. To their credit, the majority of builders would prefer to build the most resource efficient home possible, but they are limited by the demands of the buyers. There is little reason for builders to oppose a program that attempts to create that demand.

Because of politically active citizens and their awareness of Austin's natural resources, most development projects, particularly those in environmentally sensitive areas, are met with strong resistance. Austin is clearly polarized by the growth/no-growth factions. Given this division, it is significant that the local builders association has supported the Green Builder Program in its early development. The primary reason given for the support is that the builders are aware of the environmental challenges being faced, and appreciate an opportunity to participate in the solutions in a positive way, helping to inform the public and learning in the process, as opposed to the less palatable regulatory route.

THE RATING SYSTEM

The Sustainable Systems Rating Program was jointly conceived with the Center for Maximum Potential Building Systems (CMPBS), an Austin-based non-profit research and educational organization, who served as partners in this project. An initial working group consisting of City of Austin and CMPBS employees started meeting in January, 1991. This working group started the conceptual development process which initially revolved around grasping the breadth of sustainability and determining the depth of field for the inquiry and analysis that this project could support.

A primary goal for the working group was to ascertain the status of current and past efforts that relate to sustainability. A literature search of periodicals, studies, and government data sources was conducted. Of particular interest at this point were embodied energy analyses that indicate the energy consumption of materials through their life cycle. The most comprehensive work, Energy Use for Building Construction, by Richard Stein and Associates, was prepared for the U.S. Energy Research and

Development Administration (ERDA) in 1976. With input/output data provided by the Center for Advanced Computation at the University of Illinois, embodied energy per unit of building material was calculated. Unfortunately, the information generated in 1976 does not reflect current energy profiles of materials due to production efficiency improvements, or include many new materials now commonly used. A review of the calculation methods used in the report for possible imitation proved discouraging. The project's budget, number of available personnel, and equipment needs precluded a large primary research endeavor.

Early in the project, we became aware of the American Institute of Architects' (AIA) intention to develop an Environmental Resource Guide (ERG). AIA's ERG is a four year project to calculate the embodied energy and environmental impacts for all building materials and determine the most environmentally friendly alternatives. This information, combined with the understanding of the effort required to duplicate the ERDA study, reinforced the notion that our project should rather seek to accommodate the results of a study such as AIA's.

In reviewing current writings on sustainability, we were able to locate designs, recommendations, and planning strategies mainly on the community scale. There were no efforts geared at examining individual living units or any specific quantification analyses pertaining to sustainability. The fact that essentially all sustainability research and writings oriented around community based planning was recognized as a legitimate approach. However, we felt that there is value in focusing on individual living units as an important adjunct to community-based sustainability planning.

In a truly sustainable society, ideally, every level of human activity should be taken into account. The focus on individual homes in this project was to affect the greater scope of community issues through incremental and more readily attainable changes in single family homes. The sum of the incremental changes affected by the single family focus of this project will undoubtedly affect community-based planning.

Concurrent with the investigation of preceding and current work in the field of sustainability, an effort directed at developing a conceptual framework for the rating system was initiated. The following tasks resulted:

- (1) Identify building subsystems.
- (2) Develop evaluative criteria.
- (3) Design a conceptual framework for the rating system.

Resource Issues

The first task, identifying building subsystems, led to consideration of the primary resource issues of a house. By qualifying the scope of inquiry to the building on a lot, it was determined that water, energy, materials, and waste were the dominant issues. Siting was acknowledged as a critical aspect affecting resources in regard to a large range of proximity issues, including transportation factors such as distance to work, stores, schools, public transit access, effect on infrastructure, solar orientation, etc. (Robin Vieira's "Checklist for Sustainable Developments" is helpful in this regard). However, siting is centered on the energy implications of orientation, as it was decided to focus the main rating analysis on the house proper and address the broader aspects of siting in a separate informational format.

As mentioned earlier in Chapter 2, a politically charged atmosphere over the issues surrounding growth and development exists in Austin. Siting and proximity issues are major points of contention in these debates. A rating value established by this department for site and proximity issues could be used in these confrontations placing the city on one side over another. An informational presentation of site and proximity avoids a stated position in this debate.

Subsystems

With the primary resource issues selected, we next investigated building subsystems by examining existing building subsystem classifications. The obvious candidate was the Construction Specifications Institute (CSI) MasterFormat. The CSI MasterFormat breaks down all the construction processes into 16 major categories. Within each category virtually every construction process, system, and building material is subdivided. This system is the standard format used in the building business for cost estimating. The advantage to using this subsystem breakout is its common usage by building professionals. The disadvantages are the extent of detail and seeming complexity to the nonprofessional.

An exercise was conducted to identify environmentally conscious alternatives included in and in addition to MasterFormat listings. The information from that exercise contributed to the development of a Regional Resource Assessment. However, the MasterFormat presentation was rejected as a method to initially introduce the public to subsystems that can be related to sustainability because the subsystem presentation needed to present the functional elements of a house in common terms. Since the project is a marketing program, user friendliness is a key consideration. Also, the large volume of information that relates to the four resource areas needed to

be condensed into the most easily understood aspects. The final subsystem breakout is shown in Figure 3-2

Figure 3-2
Residential Subsystems

Evaluative Criteria

The next aspect to consider was a common method of evaluating options in each of the subsystems. With materials in mind, an initial list of evaluative criteria was developed. The general categories were: **embodied energy, environmental impact, economic development, health, durability, and maintainability.**

As mentioned earlier, the methodology and research needs of just embodied energy studies, particularly in light of the thousands of material options, were beyond the

capacity of this project. Also, each of the evaluative criteria can be subdivided into many levels. Since much of the primary research is yet to be done and is years away from completion, the depth of the analysis that can be covered in the sustainable rating system is limited.

Conceptual Framework

Returning to a basic understanding of sustainability as a complex series of reinforcing interrelationships, a systems-oriented approach seems the best mechanism to serve as a framework for analyzing and presenting the key issues. This approach stresses the importance of the relationship between technologies. Single-use efficiencies and energy input/output efficiencies play less of a role in a systems-oriented approach. The "systems" approach is achieved through a sequential breakdown of a particular resource in the following manner:

- Source (where a resource comes from)
- Process (the transformation of the resource by manufacturing, formulation, or treatment)
- Use (the application of the transformed resource)
- Recycle/dispose (the post-use phase of a resource)

Between each stage transportation activities occur, and at each stage, (aside from a multiplicity of intersecting resource issues), there exist opportunities for what is termed integration. Every stage produces byproducts that can potentially serve secondary or tertiary purposes. An excellent example is coal-fired power plants. The purpose of the coal combustion is to boil water to run generators that produce electricity. However, the flyash that is created in the combustion process makes an excellent substitute for Portland cement and the hot water byproduct of the process holds large potential for low grade heat applications. An additional example is using graywater as irrigation water. Opportunities for integration reflect the interrelationships that need to be recognized as basic to sustainable systems. This approach is shown diagrammatically in Figure 3-3.

Figure 3-3
Resource Integration Diagram

The sequential breakdown above illustrates the life cycle of a resource applied to human use. By transferring this sequence into a relational field matrix (Figure 3-4), we can develop a presentation of this sequence that illustrates the multiplicity of options that can occur at each stage. In Figure 3-4, we show the four sequences as four connected boxes. The four boxes contain the options that can occur at each stage of the sequence. We have highlighted one box within each stage to illustrate how a sequential path is isolated diagrammatically. The highlighted boxes (options) are then critically examined employing evaluative criteria (i.e. embodied energy, environmental impact, etc.) to understand the sustainability potential of the selected sequence of options. This sequence can be accessed at any stage and examined backwards or forwards. The relational field matrix offers the ability to see the sequential result of a chosen option and then examine and evaluate the option's environmental effects.

Figure 3-4
Relational Field Matrix

Self Rating Systems

To initiate the sustainable rating system, a self-rating format was used, based on a conceptual framework that can be expanded as the program evolves. As with the early stages of many home energy rating systems, a manual rating format was selected as a starting point. As changes are made to improve the manual or self-rating system, less cost associated with trial and error is incurred, as opposed to adjustments to early stages of a computer-based system.

Two approaches to self-rating were considered for this project. One approach (Option A) involved the user in totaling the points using the sequence of **source, process, use, recycle/dispose and integration**. Figure 3-5 shows a diagram developed by the Center for Maximum Potential Building Systems (CMPBS) which illustrates this approach. In this method, the user would evaluate building options by asking questions relating to source, process, use, etc. in relationship to themes that express sustainable criteria. For example, the themes would include : **indigenous materials** (regional wood) **are used**; **renewable energy sources are used**; **site resource use such as rainwater, solar energy, graywater, prevailing breezes are optimized**, and more. This method could potentially

develop a strong understanding of sustainability by the user since the user is actually involved in the scoring process. Note that the auditing (conducting a cost/benefit analysis) of the process is also valued in this approach.

To successfully use this approach beyond an examination of themes that express sustainability, a rating information base needs to be available to the user. Figures 3-5 and 3-6 illustrate the extensive use of graphics entailed in this approach. These graphical representations or icon sequences are important components to the CMPBS self rating approach. Figure 3-6 illustrates how a rating information base might be illustrated and recorded. The attractiveness of this approach is the success such methods have achieved in applications that have involved training and complex interactive design problems. This method also lays the groundwork for the eventual use of Object Oriented Programming (or "OOPs"). The extensive use of iconography characteristic of OOPs is considered to be a dominant trend for the next generation of computer software.

Figure 3-5

This rating procedure (option A) involves the rater at basic level of inquiry.

(c) 1991 THE CENTER FOR
MAXIMUM POTENTIAL
BUILDING SYSTEMS

Figure 3-6
Rating Information Base(Option A)

RATING INFORMATION BASE

RATING INFORMATION BASE

(c) 1991 THE CENTER FOR MAXIMUM POTENTIAL BUILDING SYSTEMS - RIGHTS RESERVED

The second approach (Option B) provides the rater with values for a list of building options. This means that the user of the system must ask about listed options and record if they are present in the home they are considering. The individual (rater) then totals the points of the options they have checked and locates their total on a scale that indicates the "Sustainability Score" of the house under consideration. The final product, or rating, for the user is a relative scale that they can use when evaluating homes.

We elected to use the second option (Option B) for the following reasons:

- (1) Insufficient data and understanding of the local resource base makes the rating information base unavailable for the first approach.
- (2) Developing representative icons is a very large undertaking that cannot be undertaken at this time.
- (3) The first approach initially stresses themes and would not give specific options which are valuable to builders wishing to act immediately.
- (4) The specific options offered in the selected approach raises the likelihood of directed actions that can rapidly affect the marketplace.
- (5) The experience gained with the Energy Star Rating Program indicates that the public generally prefers marketing programs that do not involve them in the basic levels of inquiry and analysis.

In the next sections of the report, the selected self-rating approach for this project will be examined.

Confining the Scope and Selecting Options

The scope of the presentation to the public was limited due to the enormity of options that are available and the newness of the underlying concept. The goal of the project is to have a rating system that can impart a sense of value to sustainable options. This can be achieved by (1) rating every possible option and allowing the points comparison to point out what is best or (2) by selecting examples of acknowledged "better" choices and showing a comparison within them. The second option of comparing only the "better" choices was selected for this project since it (1) limited the volume, (2) provided a compendium of "better" approaches, and (3) still reflected a conceptual framework that can be expanded.

Figure 3-7
Criteria for Rating

These criteria were selected to determine the building processes and materials that would be included in the initial rating list:

1. Optimize the use of site resources.
2. Be highly conserving of resources.
3. Encourage recycling and the use of recycled materials.
4. Encourage the use of local resources.
5. Stimulate the regional economy.
6. Have reduced embodied energy.
7. Reduce environmental impacts.
8. Simulate natural processes.
9. Minimize health threats to building occupants.

The building options that were selected to be rated presented one or more (not necessarily all) of the above aspects. Figure 3-8 shows a sample of options from the Eco-Home Guide that were selected relating to indoor uses of water. All appropriate options are not listed in the Eco-Home Guide; however, a substantial listing of "good" options can be presented in the context of stimulating the identification and use of worthy alternatives to standard practice. (A complete list can be found in the Eco-Home Guide, Appendix A.)

Figure 3-8
Sample Indoor Water Option List From The Eco-Home Guide

OPTION

1. A harvested rainwater system is used for indoor water uses
2. Copper piping is used for all potable water lines
3. Potable water is tested at the tap and treated as needed
4. Faucet flow is 2.0 gpm (gallons per minute) or less
5. Shower flow is 2.5 gpm or less
6. Toilet water usage is 1.5 gpf (gallons per flush) or less
7. Composting toilet (If this applies, you also score points for "Toilet water usage is 1.5 gpf or less")

A major issue pertaining to options that are included in the rating is their "real world" applicability. For instance, included in the previous Figure 3-8 is the option of using captured rainwater as a source for indoor water needs. Captured rainwater

technology has not achieved the level of sophistication one finds in mainstream building systems in terms of range of methods, market availability of systems, plumbing and mechanical expertise, or even general awareness in the public. Should this option therefore be excluded since it can not be readily implemented? Such options were included for the following reasons:

- (1) They are viable from a sustainability perspective.
- (2) An educational value exists.
- (3) Placing them in a marketing program promotes their consideration and encourages entrepreneurial efforts and market response.
- (4) Creativity is stimulated toward evaluation of new resource-friendly building options.
- (5) Local examples of the option do exist.

Interestingly, in the process of doing this project, individuals have been located that are preparing to incorporate some of the more difficult options into their homes. The fact that the City (Environmental and Conservation Services Department) supports their choices and is able to lend assistance has resulted in positive feedback to the relevance of the department's efforts.

Assigning Values

As mentioned earlier, there are gaps in the available information that can be used to precisely quantify certain evaluative criteria. We elected to estimate values in certain criteria using a peer review process. As we had limited the options in the rating list to "better" options, we similarly sought to give points to only the positive aspects of the building options. Negative points were not assigned to undesirable aspects.

To achieve this goal, seven major categories were developed for assigning values to the options presented in the rating list. The basis for the seven categories included the sequential process of source, process, use, and recycle/dispose (referred to as Post-use in this section) discussed earlier in this chapter. Subdivisions in these four categories incorporated evaluative criteria (embodied energy, environmental impact, etc.), discussed earlier plus criteria derived from sustainable themes. Additionally, categories for assigning points for integration, difficulty, and use factor were developed. *Each option that was selected to be rated was subjected to an evaluation using the seven categories with each applicable characteristic being worth one (1) point (except when noted otherwise).* The following is a listing of the seven categories, their respective subdivisions, scoring information, and pertinent explanation.

1. Source points: (manifestation of the resource):

Site The resource is inherent to the site. (i.e. rain, sun, wind, earth at the site)

Recycled The resource consists of over 50% recycled content (i.e. recycled plastic lumber, cellulose insulation)

Renewable Relatively fast natural processes bring this resource into being. (i.e. wood, rain, sun, wind; not coal, clay, caliche, etc.)

Regional A regional resource is considered to have a positive economic impact and a lowered embodied energy in transportation factors.(i.e. caliche, brick, stone)

State A resource is considered to have a positive economic impact if from within the state. (Note: a "regional" point gains a "state" point automatically. This reflects the additional value imparted by local economic activities.)

2. Process points: (transformation of the resource)

Embodied Energy The process uses energy frugally to transform the resource (if transformed at all). (As noted earlier, statistical data for embodied energy is dated or unavailable. Only a process that was well known to have low embodied energy in its comparative family was valued in the rating.)

Environmental Impact Essentially, the environmental impact and embodied energy of a process can be considered to parallel each other - the greater the embodied energy, the greater the environmental impact. However, this is also an area that requires extensive primary research since the effects will extend beyond energy related effects (externalities). This is beyond the capacity of this project and, as a result, was handled similarly to embodied energy.

Regional The process takes place regionally giving positive economic impact.

State The process takes place in-state giving positive economic impact. (Note- if "regional" applies, so does "state" for scoring purposes.)

Each of the above sections is worth one point each.

3. Use points: (application of the transformed resource)

Quantity Point(s) are scored if the use is highly conserving of resources. Certain building methods, systems, and materials are more conserving than others on a relative scale. For example, a solar water heater that provides over 50% of a home's hot water needs should be more highly valued than a solar hot water heater that provides 20% of the home's requirement. To account for these differences, the assigned point values in the rating system is as follows: **1 point** if the system or device saves up to 33%; **2 points** if the amount saved is up to 67%; **3 points** if the amount conserved exceeds 67%.

Health The use of the material or system is specifically non-deleterious to occupants in the short or long term. "Healthy" home issues are legitimate concerns and certain methods and materials are marketed to counter known health impairing materials. Although many other materials selected for the rating list could be classified as non-deleterious to health, only those that are acknowledged and recommended in current material health advisements were valued for a health "point".

Durable The material or method is long lived and low maintenance in its functional class (for example, a 30-50 year life roof is durable compared to 20 year roofing; in proper installation a material such as wood lasts indefinitely in a dry location; brick siding is durable and low maintenance compared to wood siding.)

4. Post-use (post-life) points: (disposal of the transformed resource)

Easy to Recycle The material can be used again with processing through established systems or reused. An estimated range of ease of recycling of 1 - 3 was considered in this section. The highest point (3) is for material that is able to be reused with minimum reprocessing (such as removing nails from used hardwood flooring) and is also fairly highly valued. The midrange (2) is for material that could be reused but is often insufficiently valued to encourage reuse. It can also be reprocessed readily (clay roofing for example). The single point (1) is for materials that are rarely recycled but still retain some limited value (plywood underlayment is an example).

Proper Disposal The material is handled appropriately to be non-polluting or is readily compostable. (This category addresses the

resource issues of Materials and Waste and was not considered an aspect of Water and Energy. The integration category addresses "recycling" aspects of Energy and Water.)

5. Integration The ability of the system/resource option to achieve several functions. (i.e. a brick wall on the interior of a house serves as a structural support or divider and as thermal mass supporting a thermal flywheel effect in the house; a graywater/irrigation system removes water from the wastewater system and irrigates the landscape.)

More than one point could be scored if multiple integration takes place.

6. Difficulty Many good options from an environmental standpoint are difficult to implement due to poor availability and other factors. This category gives value to the extra effort that a builder must put into implementing or installing these options, such as:

Extra cost

The need for special skills or assistance, such as

design

engineering

installation

regulatory demands

material access

Value perception (This implies that the builder and/or homebuyer has acted upon knowledge not commonly understood by the general public as resource conserving and essentially has taken a risk. This would also apply to options selected that have long paybacks in the conventional economic sense.)

Scores in this category were estimated, although quantification can be established. A total of 1 point is available from this category.

7. Use Factor A building option may be applicable to more than one use category. For example, a passive solar design that impacts the heating and cooling of a home has affected two areas--- heating and cooling. If harvested rainwater is used for all indoor water uses (potable needs, washing, toilet flushing), a use factor of 3 occurs. (The indoor water category is divided into 3 sections- see the previous section, "Subsystems".) The Use Factor is multiplied by the total of the other categories.

The assigning of values is an important component of this project. The methodology employed in this project is subject to continuing review. Four examples follow that show how points are determined for options listed in the Eco-Home Guide (Appendix A).

EXAMPLE 1	
Option: A harvested rainwater system is used for indoor water uses.	

Source: Rainwater in this option is considered a **site** resource and a **renewable** resource.

2 points

Process: In this category points are scored for **low embodied energy** and **low environmental impact**.

2 points

Use: No points are credited in this category. Rainwater harvesting as stated in the option does not imply that water is conserved (**quantity**) from a use standpoint, nor is **health** addressed by this option. The **durability** aspect of this system is unknown and can not be valued.

0 points

Post-use: The option does not address or imply what happens to the water after use. The **easy to recycle** and **disposal** sections contribute no points.

0 points

Integration: The option does not imply that any integration will occur.

0 points

Difficulty: A point is scored in this category since the technology is mostly unknown and there is large expense involved.

1 point

Use factor: The option states that the harvested rainwater will be used for indoor uses. There are 3 groups of indoor uses - potable needs, washing, and toilet flushing. The use factor of three is multiplied times the previous points.

Factor 3

Total $2 + 2 + 0 + 0 + 0 + 1 = 5$

$5 \times 3 = 15$

Point total for EXAMPLE 1 option is 15

EXAMPLE 2

Option: Passive solar design is the primary strategy for maintaining comfort, providing at least 50% of the home's heating and cooling needs.

- Source:** The option uses a **site** resource and is a **renewable** resource.
2 points
- Process:** **Low embodied energy** and **low environmental impact** is considered characteristic of this option.
2 points
- Use:** Two points are scored in the **quantity** section of this category since the option states the load contribution of the technique. Nothing can be implied about **health** or **durability** in the option.
2 points
- Post-use:** There are no points to score in this category.
0 points
- Integration:** Passive solar heating and cooling techniques rely on well-placed windows. This quality should impact positively on natural lighting and a point is credited.
1 point
- Difficulty:** A point is scored in this category as passive solar techniques are not well known in this area.
1 point
- Use Factor:** The option states that 2 areas, heating and cooling, are effected.
Factor 2

Total $2 + 2 + 2 + 0 + 1 + 1 = 8$

$8 \times 2 = 16$

Point total for EXAMPLE 2 option is 16

EXAMPLE 3

Option: Continuous ridge and soffit venting.

- Source:** This is credited as a **site** resource.
1 point
- Process:** The process is considered to have **low embodied energy** and **low environmental impact**.
2 points

Use: The ridge and soffit vents will reduce the cooling load to a minor extent and only one point is credited (**quantity**). Nothing can be credited for the **health** and **durability** sections.

1 point

Post-use: No points are scored.

0 points

Integration: No points are scored.

0 points

Difficulty: A ridge and soffit system is not difficult in any way.

0 points

Use factor: The option is effective for cooling interests.

Factor 1

Total: $1 + 2 + 1 + 0 + 0 + 0 = 4$

$4 \times 1 = 4$

Point total for EXAMPLE 3 option is 4

EXAMPLE 4
Option: Regional mesquite hardwood flooring is used without toxic glues or synthetic backing material.

Source: Mesquite trees are common in our region. Points are scored since it is a **regional** resource and also a **state** resource. (By having both choices - regional and state - note that we can gain a point if the resource comes from our state and not our region. This reflects the positive impact economic activity in our state has on our local region through a strengthened state tax base.) The mesquite tree is also considered a **renewable** resource.

3 points

Process: An analysis has not been done on the **embodied energy** of mesquite wood harvesting and processing in our region. It is possible that it is quite high. The **environmental impact** is considered low since the mesquite tree is considered a nuisance species and is subjected to extreme control efforts. The processing of mesquite lumber occurs in our **region** (and thus in our **state**).

3 points

Use: The option addresses specific **health** concerns by avoiding toxic glues and synthetic backing. Mesquite flooring is also considered **durable**.

2 points

Post-use: Mesquite flooring is considered highly valued as a recycled material. It is expected that great effort would be exerted to reuse it.

3 points

Integration: No points are scored in this category.

0 points

Difficulty: Mesquite flooring is very expensive and available only in select locations.

1 point

Use Factor: The use factor is one since the option is considered for flooring only.

Factor 1

Total: $3 + 3 + 2 + 3 + 0 = 11$

$11 \times 1 = 11$

Point total for EXAMPLE 4 option is 11

Rating a Home

With assigned values for the options in the four resource issues, an overall rating for a home can be achieved. In the initial rating process it was realized that, since each resource issue of Water, Energy, Materials, and Waste contained a different number of options, there needed to be an adjustment to give equal weight to each of the four areas. If the option points were simply totaled, the areas with the largest number of options could influence the total. The result could be a house that scores high in an area such as Energy but poorly in the three other areas, ultimately gaining a high overall rating. Each resource issue must be examined and rated to establish a separate rating score, then the four separate rating scores are totalled to reach an overall rating score for the house. Thus, each resource issue is given equal influence on the final rating regardless of the number of options and available points an individual resource area may contain.

A committee of staff members that included persons unfamiliar with the project and several with building experience was convened to examine each option in the four areas and determine the range of impact and difficulty each option implies. Four levels were developed for this examination--- Fair, Good, Excellent, and Superior. (These four

levels would also be used to indicate the total rating score in each resource area.) The four levels were used to establish value to the effort required to implement the different options and, thereby, set ranges for different rating point totals.

In our preceding examples, the committee determined the following levels:

EXAMPLE 1: A "rainwater harvesting system that uses the water for indoor uses" was determined to be a "Superior" effort because of the lack of precedent in the local building industry, and the relatively high commitment expected for a builder to provide this option.

EXAMPLE 2: A "passive design that contributes 50% to a home's heating and cooling needs" was judged "Superior," also because it is outside the typical building practice, and implies very strong commitment to energy design.

EXAMPLE 3: Ridge and soffit venting was considered "Fair," since some builders regularly incorporate this feature.

EXAMPLE 4: Using mesquite flooring was deemed "Excellent." An example of a "Good" option would be using "sealed plywood as floor underlayment."

As a result of this effort, the options in each resource area were effectively ranked relative to each other, establishing the baseline for how much must be done to achieve a Fair, Good, Excellent, and Superior rating in each resource area. By totaling the identified "Fair" options in the area of Water, for example, the upper limit of the "Fair" rating range for that home's water use pattern was ascertained. The committee then decided what the minimum point level for reaching a "Fair" rating should be. This was done to avoid the possibility that a home could contain an option worth one point and receive a "Fair" rating while a home with 25 points might still be in the "Fair" range. With a realistic minimum score and upper limit established, the result was a "Fair" range for Water. The "Good" range was determined by adding the "Good" options to determine the upper limit. The lower end of the "Good" range was set by the top of the "Fair" range. The pattern was repeated for the "Excellent" level. Point totals above the "Excellent" range were "Superior."

Each resource area was examined in similar fashion. The result was four levels within each resource area that determined the total points the options must reach to gain a rating of "Fair," "Good," "Excellent," and "Superior." (Figure 3-10 shows the point ranges for the four resource issues.)

In the rating list developed for this project, there are a large number of options in the Energy and Materials section that serve the same function within a home. Caution

must be exercised in totaling the options when ascertaining the "Fair," "Good," and "Excellent" ranges. For example, in Materials, regarding floor underlayment, exterior grade plywood and solid wood underlayment are both considered "Fair" choices. However, one or the other would be done in a house and therefore only one should be added to reach the "Fair" range total. In this situation, adding only one option must be done choosing the higher point option. In this example, the "plywood" option is valued at 4 points and the "solid wood" option is valued at 5 points. This means that the "solid wood" point value would be added to determine the top limit of the "Fair" range.

With the ranges established in each resource area, the user of the rating system will be able to proceed in the following manner:

- (1) The user reads each option and records the points if that option is valid for the house under consideration.
- (2) The recorded points in each resource area of Water, Energy, Materials, and Waste are then added to reach a total for each resource.
- (3) The user locates their total in the four ranges that are provided for each resource. (The ranges are determined by adding the "Fair," "Good," and "Excellent" options as discussed above.)
- (4) The ranges in each resource have an assigned number between 1 and 4. This number indicates how well the house rated in each resource area and relates directly to the "Fair," "Good," "Excellent," and "Superior" levels.
- (5) The user then adds the four assigned number subtotals (1, 2, 3, or 4). The grand total of that sum indicates the overall sustainability rating of the house.

Figure 3-9 shows examples of the rating format with options, point values, and the places for the user to record their score.

Figure 3-9

Indoor Uses	Option	Points	Your Score
	1. A <i>harvested rainwater</i> system is used for indoor water uses	15	
	2. Copper piping is used for all <i>potable</i> water lines	1	
	3. <i>Potable</i> water is tested at the tap and treated as needed	2	
	4. Faucet flow is 2.0 gpm (gallons per minute) or less	1	
	5. Shower flow is 2.5 gpm or less	2	
	6. Toilet water usage is 1.5 gpf (gallons per flush) or less	2	
	7. <i>Composting toilet</i> (If this applies, you also score points for "Toilet water usage is 1.5 gpf or less")	7	

Figure 3-10 shows the summary page where the user locates their point total for each resource. (See the beginning of this section for how the ranges were developed.)

Figure 3-10

Rating Summary Page

WATER TOTAL _____

WATER TOTAL 5-9 POINTS	⇒ ⇒ ⇒	1
WATER TOTAL 10-16 POINTS	⇒ ⇒ ⇒	2
WATER TOTAL 17-29 POINTS	⇒ ⇒ ⇒	3
WATER TOTAL 30+ POINTS	⇒ ⇒ ⇒	4

WATER SUSTAINABILITY SCORE _____

ENERGY TOTAL _____

ENERGY TOTAL 8-31 POINTS	⇒ ⇒ ⇒	1
ENERGY TOTAL 32-53 POINTS	⇒ ⇒ ⇒	2
ENERGY TOTAL 54-109 POINTS	⇒ ⇒ ⇒	3
ENERGY TOTAL 110+ POINTS	⇒ ⇒ ⇒	4

ENERGY SUSTAINABILITY SCORE _____

MATERIALS TOTAL _____

MATERIALS TOTAL 22-46 POINTS	⇒ ⇒ ⇒	1
MATERIALS TOTAL 47-116 POINTS	⇒ ⇒ ⇒	2
MATERIALS TOTAL 117-170 POINTS	⇒ ⇒ ⇒	3
MATERIALS TOTAL 171+ POINTS	⇒ ⇒ ⇒	4

MATERIALS SUSTAINABILITY SCORE _____

WASTE TOTAL _____

WASTE TOTAL 4-6 POINTS	⇒ ⇒ ⇒	1
WASTE TOTAL 7-17 POINTS	⇒ ⇒ ⇒	2
WASTE TOTAL 18-32 POINTS	⇒ ⇒ ⇒	3
WASTE TOTAL 33+ POINTS	⇒ ⇒ ⇒	4

WASTE SUSTAINABILITY SCORE _____

WATER SUSTAINABILITY SCORE _____

ENERGY SUSTAINABILITY SCORE _____

MATERIALS SUSTAINABILITY SCORE _____

WASTE SUSTAINABILITY SCORE _____

TOTAL SUSTAINABILITY SCORE _____

At the bottom of the preceding illustration, the four subtotals for each resource area are added. The final figure gives an overall rating number to the house (step 5 above). This final score allows the house to be classified as a "Fair," "Good," "Excellent," or "Superior" home from a "green building" perspective (called an Eco-Home in this program). The following scale was developed for that purpose.

A score between 4-6, the Eco-Home rating is FAIR.

A score between 7-10, the Eco-Home rating is GOOD.

A score between 11-14, the Eco-Home rating is EXCELLENT.

A score between 15-16, the Eco-Home rating is SUPERIOR.

MARKETING

As stated earlier, simplification of the presentation of the information is critical in order to reach the widest audience. Additionally, to achieve maximum public understanding there needs to be an especially strong educational component to the marketing approach. The best approach to achieve effective communication appeared to be in a guide written to capture the essence of sustainability without overwhelming the audience.

The guide that was developed for this project was designed to systematically introduce the concept of sustainability and reasons for its importance, present the rating system, and provide a feedback mechanism for comments and market analysis. The guide is named **The Eco-Home Guide**. The program name for this project was subsequently called **The Green Builder Program**. Both names were selected as easy to recognize and as indicative of the project's underlying concepts. The Eco-Home Guide and a brochure make up the written marketing material.

The introduction of the Green Builder Program and the Eco-Home Guide will initially go to the builders enrolled in the Energy Star Program and local environmental organizations. The first group has experience with the marketing advantages of a rating system, while the second group is interested in the environmental goals.

To reinforce the educational outreach, public speaking engagements and news articles play an important role. Presentations have been made to the Southwest Regional Audubon Conference and the Colorado River Watershed Bioregional Summer Conference. These presentations generated highly favorable comments. In both

(presentations) attendees easily grasped the systematic view of the life cycle sequence of the four resource issues as presented in the Eco-Home Guide.

ADVISORY COMMITTEE

An advisory committee was convened at approximately the midpoint of this project. This group consisted of twelve persons representing a cross-section of the building industry --- architects, real estate professionals, consultants, professional builders familiar with the Energy Star Rating Program, and others who have strong interests in improving the environment.

The advisory committee was established to serve two important functions: (1) provide perspective on the readiness of the marketplace to engage in sustainable building practices; (2) give feedback on the program's rating system and marketing materials.

The builders in the group reported that approximately 30% of their customers express an interest in the energy and environmental aspects of a house. They indicated, along with the real estate professional, that there has been an increase within the last year in the level of interest. As a whole, the advisory group expressed strong personal interest in the goals of the project and reinforced the notion that a substantial segment of the public was ready for this type of project.

The advisory committee served as the initial test group for the marketing approach. The committee played an active role in providing feedback on the marketing approach and rating system. Their comments and suggestions were instrumental in achieving the final version of the Eco-Home Guide.

THE ECO-HOME GUIDE

The Eco-Home Guide with the rating system is the primary marketing tool for the Green Builder Program, and the main product of this project. The guide uses the four resource issues of water, energy, materials, and waste as the basis of its organization.

Each resource issue in the Eco-Home Guide is examined through the following subtopics: the **Austin Profile** (an overview of the topic as it relates to Austin); **Facts** (that give a local and global perspective); **Eco-Themes** (general alternatives to general building practices). In the rating section, the four resource issues also serve to subdivide the rating analysis.

The Eco-Home Guide is being formatted to introduce graphic symbols in a limited sense. This includes a drawing of a representative house with labels pointing out sustainable building options. As more graphic symbols are developed, they will be added to the text in subsequent versions of the guide. The eventual result will be a guide that minimizes text and highlights graphic representations of sustainability life cycles.

The goal of the presentation format for the Guide is to be brief and succinct. This is a difficult task in light of the range of knowledge among potential users. However, the amount of support in the general media in terms of coverage of environmental issues seems to be substantial enough to provide strong reinforcement. If the Guide merely stimulates more inquiry among its readers, we would characterize it as successful.

COMPUTER SOFTWARE REVIEW

The Energy Star Program establishes an energy efficiency rating for homes by inputting building specification data into a computer program, the Building Energy Thermal Analysis (BETA) Program. The ability to modify BETA to accommodate sustainable options was an original goal for the project. However, the sustainability conceptual format that was developed did not fit the BETA format in any way.

A review of four software options was therefore conducted. The options were Timberline Precision Extended and MasterSpec estimating software; LabVIEW 2, a virtual instrument for generalized scientific computing; MacSMARTS Professional, a hypermedia-based, expert system tool.

The estimating software offers the opportunity to list options in a database that ties directly to the CSI Masterformat. This is a valuable capability for estimating purposes, accessing sourcing information, and direct comparison of alternatives. However, the sustainability-related information required to take advantage of the capacity of the estimating software is still being compiled.

LabVIEW 2 and MacSMARTS Professional offer large potential to absorb and organize the interrelationships characteristic of a sustainability based analysis and presentation. The potential to use a graphics-driven system was evaluated in light of the capabilities of these two programs. Sustainable design and planning could take advantage of Object-Oriented Programming (OOP) for user friendliness and broader

applications in the building industry. These two programs appear to have that potential. A further exploration of this opportunity is being evaluated by our project partner and consultants, CMPBS, and the Advanced Visualization Laboratory at Rice University, a leader in the research and development of Object Oriented Programming. This effort is a very large undertaking and beyond the capacity of this project. The City of Austin will maintain contact with the effort and look for future opportunities for implementation.

CHAPTER 4

SUMMARY

LESSONS LEARNED

When the Sustainable Systems Rating Program was initially conceived, the immense scope of the task was underestimated. The project has consequently seen adjustments in areas that are quite important. Most notably, the logistical and technical support needed by the building community to implement the approaches recommended by this project has necessarily been isolated for a separate project (The Sustainable Building Sourcebook, a Year 13 project). The lack of relevant data in useful quantified form created a similar potential project opportunity. In retrospect, a better grasp of the state of the field of sustainability related research would have led to a more modest undertaking.

The newness of sustainability based approaches required a substantial effort in developing a conceptual basis for this project, much more than originally perceived as necessary. However, the consequence of entering new territory was rewarding and new manners of perception and analysis were gained as a result.

Enthusiasm was expressed by virtually everyone we came in contact with regarding this project. Interest and support came from all sectors --- citizens, traditionally conservative building community members, government officials, academia, and researchers in the field of sustainability issues. However, we certainly feel that more

work is necessary and worthwhile. Due to the newness of the application of this methodology, time is needed to test its effectiveness.

Although we attempted a link up with academia (The University of Texas at Austin) for assistance in the conceptual development and research, it would have been better to have established that linkage at the inception of the project. The resources of a multi-disciplinary research team of several people would have been most helpful. That type of arrangement requires more lead time and funding than we allowed for and, as a result, we were unable to enlist as much support as could have been used.

NEXT STEPS

Encouraging and Locating Exemplary Projects

The benefit of having examples of Eco-Homes carries with it some challenges. First of all, cost and availability issues will be able to be documented. The current supply network appears inadequate to provide many of the resource sensitive items and procedures that are recommended in the Eco-Home Guide. The responsiveness of the supply system to match non-conventional demands should reflect the suppliers' perception of the long term market potential and capabilities to access non-conventional materials and systems. It is anticipated that the supply gaps will present economic development opportunities in the local area. A tie-in with local agencies and associations that support new business startups will be an important aspect of future activities for this program.

Costs for an Eco-Home are expected to be higher than conventional homes and the earliest projects should indicate the extent of the willingness of the public to pay more. Informal surveys taken at recent public presentations about the Green Builder Program showed willingness to go to 30% above conventional costs. However, it will be important to examine the lending community's response to this willingness by the buyers, and to monitor the less desirable potential to associate Eco-Homes as an option only for wealthy homebuyers.

Eco-Home options that have lower costs currently have the largest number of availability and regulatory hurdles to overcome. An example of this is straw bale construction, a technique currently being used for public housing in France. However, it requires special approval to serve as a building material and the development of a distribution infrastructure here. A short term goal associated with encouraging the

building of Eco-Homes is to strongly promote a low cost technique such as straw bale building in higher priced homes in order to short circuit stigmatizing such techniques and establish a regulatory track record.

It is likely that the initial projects will be custom homes. However, it will be important to establish early contact with volume builders. Volume builders currently are active participants in the Energy Star Rating Program. Although this group will receive early notification of the Green Builder Program, personal contact will be important to ascertain real and perceived obstacles as well as identify opportunities that are unique to the volume building business.

Professional Educational Outreach

Identifying and encouraging sustainable building practices is only a part of the effort required to bring about actual implementation. The design elements, systems integration, material sources, and skills needed for Eco-Home construction are mostly unknown within the building industry. The need for training and guidance at the implementation level is critical.

A Sustainable Building Sourcebook is now being developed to provide specific technical guidance useful to the builders and architects that wish to build and design Eco-Homes. The Sourcebook will include material sources, design guidance, a listing of resource people and organizations, and regulatory guidance. This "how-to" manual will be cross-referenced to the four resource issues of the Eco-Home Guide and the CSI MasterFormat.

Concurrent with the writing of the Sourcebook, training seminars will be offered on the material content of the Sourcebook as different sections are completed. This will facilitate dissemination of the information for direct feedback from building professionals, which should contribute to a more useful final product.

TRANSFERABILITY ISSUES

Burden of Proof

An important factor to consider in the Sustainable Systems Rating pertains to the burden of proof in assigning values. In the approach used in this project, the City has assigned the values to the options that essentially indicate that one option is better than another. This could be construed as showing favoritism and opens up the

methodology to intense scrutiny. In a situation where a third party's scientifically approved methodology has been employed, this is not as great a potential problem.

The issue of the burden of proof came to light most strikingly in early October in a press release from the Environmental Defense Fund (EDF) which was endorsed by Environmental Action Foundation, the Natural Resources Defense Council, Sierra Club, and U.S. Public Interest Research Group. In the release, EDF announces a report that questions the "greenness" of Green Cross's certification of products. The report is particularly critical of Green Cross's intention to award products a general environmental "seal of approval" based on the "nascent methodology of life-cycle assessment." The chief scientist for EDF, Dr. Richard Dennison, states:

"Green Cross's claim to be capable of conducting life-cycle assessments (LCA's) is at odds with virtually every expert in the field and grossly overstates the enormous complexity and highly controversial nature of LCA's. This claim is harmful to current efforts to promote the responsible development and use of life-cycle methodologies - an area fraught with enormous abuse by individual companies and trade associations."

Although this project is not technically a "certification" effort, it could be construed as such in the area of assigning values in a rating system that acknowledges a life-cycle approach, and possibly be similarly criticized. Direct contact with Dr. Dennison at EDF resulted in the following guidelines that any jurisdiction wishing to emulate this project should be aware of:

- (1) Avoid calling the conceptual methodology a Life-Cycle Assessment. This gives the guise of scientific method.
- (2) Acknowledge the methodology to be a mixture of quantitative and qualitative inputs if that is indeed the case. If value judgements are involved, that is not a problem if acknowledged.
- (3) Make available for public review and comment the criteria and methodology that was employed.

A discussion regarding this project indicated that we did not have a problem with the rating system as we were following the above suggestions. Additionally, the rating process is voluntary and has been reviewed in an ongoing manner with an advisory group of local citizens.

Recent Research

Research in life-cycle methodologies has been recently coordinated by the Society of Environmental Toxicology and Chemistry (SETAC). An international team from industry, government, and environmental organizations met in a workshop from which was developed the report, A Technical Framework for Life-Cycle Assessment (listed in the bibliography). This is a valuable resource for those considering similar projects. The sequential framework of our project is similarly reflected in this report.

The report prepared by the Center for Maximum Potential Building Systems, Sustainable Rating System: A Conceptual and Contextual Overview for the City of Austin, is also a valuable resource for those considering emulation of this project. The two reports, in addition to this document, afford the most comprehensive information pertinent to developing a sustainable systems rating program.

It is recommended that those considering a sustainable systems rating program follow the ongoing research of SETAC and the AIA's Environmental Resource Guide referred to earlier.

The Local Model

The sustainability premise employed in this project placed value in the optimization of local resource use without jeopardizing the local environment. As a result, values assigned to certain options reflect local conditions that may be unique to Austin. Duplication of Austin's efforts by other jurisdictions should include a local resource assessment that indicates priorities and opportunities unique to that area.

For example, the Austin area was recognized as a non-timber producing region; consequently, earth materials were stressed as an appropriate building material. This focus would obviously be different in a timber producing area. Also, climatic qualities in different regions can influence the viability of energy options. Sunspaces were not stressed in our list of options but would certainly be viable in a colder region.

Options and Values

As indicated above, local conditions can influence the range of options most appropriate for inclusion in a rating list. Similarly, the point totals for options selected for Austin can be different in another region. This difference will be most obvious in scoring points for economic impact. The example of mesquite flooring which was scored in Chapter 3 reflects this point.

Mesquite flooring is sourced and processed on the local level in Austin. This accounted for 4 of the 11 points attributed to that option (2 for the regional and state subdivisions in the Source category and 2 for the regional and state subdivisions of the Process category). Another region that does not have mesquite trees locally or within the state would not gain those 4 points. Also, another region of Texas without mesquite trees would not gain 2 of those 4 points. Similarly, another jurisdiction outside Texas implementing a sustainable rating system may select a local tree species and assign point values that would not be available in Texas.

Recognizing that the point totals for similar options in other jurisdictions will probably be different, we endorse the method of determining the points and the format of this project as readily transferable. The methodology of evaluating the elements of Source, Process, Use, Recycle/Dispose, Integration, and Difficulty can be used by anyone wishing to attribute points to building options. The system we employed to create a sustainability range of "Fair", "Good", "Excellent", and "Superior" for the point totals is similarly applicable for others.

Summary of Transferability Considerations

The conceptual framework developed for this project is readily transferable but should be evaluated in light of ongoing research in life-cycle assessments. Particular attention should be given to following the progress of the AIA's Environmental Resource Guide. The data and recommendations derived from that study will fill many of the gaps in information we faced in this project. Even though the AIA ERG is a multi-year project, information will be released from it as it is developed.

Secondly, the marketing format with rating system as a vehicle for introducing sustainable concepts is recommended as being very useful to others. The primary advantage is that it is not particularly threatening to businesses most affected by it. It is presented as a positive method to reach new markets and consequently bring about financial return. It can also lead to new business opportunities.

Finally, the rating system's list of options and the values assigned to them as found in our Eco-Home Guide should not be considered wholly transferable. Many of the options are universally applicable. However, each region should expect to develop a list of sustainable options that reflects the character of their area. Calculation of the points might be done in a manner similar to our method. The diversity of each region should be directly mirrored by the best strategies for living sustainably within them. The point values will reflect those differences as well.

CONCLUDING REMARKS

This project developed into a greater learning experience than anyone anticipated at its inception. Each person intuitively recognized the value of sustainability as a concept; however, the extent of its relevance certainly became much more apparent through this effort. The lack of precedents in the field that could be applied to rating systems added greatly to the amount of work and similarly to the amount of interest and excitement in the project.

The focus of this project on the individual home provided insight to the complexity that is involved in sustainability and, paradoxically, to the common sense that it entails. It is certainly legitimate to consider that sustainability within the built environment has the most potential to create long term positive benefits to community planning and design. Indeed, a major shift in general understanding toward creating a sustainable world may begin with local efforts such as this project.

BIBLIOGRAPHY

American Institute of Architects, "Making a Difference: The Environmental Resource Guide - An Introduction", AIA, November, 1990.

Architects for Social Responsibility, "A Sourcebook for Environmentally Responsible Design", Boston Society of Architects, April, 1991.

Best, Don, "Building With Borate", Popular Science, March, 1990.

Bower, John, The Healthy House, Carol Communications, N.Y., N.Y., 1989.

Boyd, Conor B and Koch, Peter et al, "Wood For Structural and Architectural Purposes", Wood and Fiber, Spring, 1976.

"Building Green", Builder, NAHB, entire issue, July, 1991.

Center for Maximum Potential Building Systems, "Sustainable Rating System: A Conceptual and Contextual Overview for the City of Austin", Austin, Texas, July, 1991.

City of Austin, "Environmental Impacts of Austin Energy Conservation Programs", ECSD, 1991.

City of Austin, "Grey Water", Resource Management Department, 1984.

City of Austin, "Grey Water Task Force Report", Resource Management Department, 1985.

City of Austin, "1991 Water Management Plan", ECSD, January, 1991.

City of Austin, "Official Statement City of Austin", June, 1991.

Chapman, P.F., "The Energy Costs of Materials", Energy Policy, March, 1975.

Department of Engineering And Public Policy, "Electric and Magnetic Fields from 60 Hertz Electric Power: What Do We Know About Possible Health Risks?", Carnegie Mellon University, Pittsburgh, PA, 1989.

Dobbs, David and Talarico, Wendy, "Turning Trash Into Cash", Journal of Light Construction, March, 1991.

Eberling, Walter and Forbes, Charles F., "Sand Barriers for Subterranean Termite Control", IPM Practitioner, May, 1988.

Good, Clint, The Healthful House, Guaranty Press, Bethesda, MD, 1988.

"Green Architecture", Architecture, AIA, entire issue, May, 1991.

HUD, "Residential Water Conservation Projects - Summary Report", 1985.

Loken, Steve et al, "G.R.E.B.E. Guide to Resource Efficient Building Elements", Center for Resourceful Building Technology", Missoula, MT, 1991.

Lord, Roger G., "Harvest Trends 1989", Texas Forest Service, March, 1990.

Matlock, W. Gerald, "Water Harvesting for Urban Landscapes", Agriculture Engineering Department, University of Arizona, 1985.

McWilliams, William H. and Lord, Roger G., "Forest Resources of East Texas", Southern Forest Experiment Station, Resource Bulletin SO-136, July, 1988.

Office of Arid Lands Studies, College of Agriculture, University of Arizona, "Summary Report on Phase I - Casa Del Agua: A Community Water Conservation Demonstration and Evaluation Project", for Tucson Water and Pima County Wastewater Management, Tucson, Arizona, July, 1986.

Office of Arid Lands Studies, College of Agriculture, University of Arizona, "Summary Report on Phase 3 - Casa Del Agua: A Community Water Conservation Demonstration and Evaluation Project", for Tucson Water and Pima County Wastewater Management, Tucson, Arizona, October, 1989.

Olkowski, William, "Formosan Termite Management: Sand Barriers and Other Techniques", IPM Practitioner, October, 1988.

Pace University Center for Environmental Legal Studies, "The Environmental Costs of Electricity", for New York State Energy Research and Development Authority, 1990.

Rocky Mountain Institute, "Water Productivity and Development: Strategies for More Efficient Use", RMI, May, 1990.

Rogers, Ken E., "Lumber and Clear Cutting Recovery from Mesquite Logs", Texas Forest Service, March, 1989.

Rousseau, David, Your Home. Your Health. and Well-Being, Ten Speed Press, Berkeley, CA, 1988.

Society of Environmental Toxicology and Chemistry and SETAC Foundation for Environmental Education, Inc., A Technical Framework for Life Cycle Assessment, Washington, DC, January, 1991.

Stein, Richard G. and Associates, Architects and Energy Research Group, Center for Advanced Computation, University of Illinois at Urbana-Champaign, "Energy Use in Building Construction", prepared for ERDA No. EY-76-S-02-2791, December, 1976.

Texas Water Development Board, "Water for Texas Today and Tomorrow", Austin, Texas, July, 1990.

The Resources Agency, Department of Water Resources, "Captured Rainfall: Small-Scale Water Supply Systems", State of California, May, 1981.

US Forest Service, "RPA Assessment of the Forest and Rangeland Situation in the United States, 1989", US Department of Agriculture, October, 1989.

Wellner, Pamela and Dickey, Eugene, "The Wood Users Guide", Rainforest Action Network, San Francisco, CA, 1991.

Woods, Paul and Choudhury, Iftekhar, "Potential for Residential Use of Rainwater in Texas", Texas A & M University, 1991.

APPENDIX A

ECO-HOME GUIDE RATING SECTION

Appendix A presents the "Rating Your Home" section of the Eco-Home Guide. (The complete Eco-Home Guide containing introductory material, glossary, survey, and Green Builder enrollment instructions is too large to accompany this report.) This is a self-rating worksheet to be used by homebuyers and builders to compare the relative "sustainability" of each rated home. It is meant to educate both builders and buyers as to the options available in new home construction that reflect the goals of sustainable urban development.

APPENDIX A

Rating Your Home

The **Rating Your Home** section is divided into the 4 resource areas similar to the previous **Resource Guide** section. Each resource area is broken down into the common uses of that resource in the home. Below each of the uses are **Eco-Options** [environmentally sensitive choices] that have assigned number values. Review and discuss the **Eco-Options** with your builder to see which ones are or can be available in your home.

Rating Values:

The assigned values to the **Eco-Options** take into consideration the difficulty in incorporating that option into your home as well as the calculated environmental merit of that option. You score points from each of the listed choices that applies to your home.

Special Symbols:

Certain **Eco-Options**, marked with an **H** for easy identification, avoid potential health threats to the house's occupants that may come about from conventional building practices and materials.

Eco-Options with a indicate choices that a builder would best be able to provide.

Those choices marked with a could be added later or relate to your personal lifestyle.

How to Proceed:

1. To the right of each **Eco-Option** is the number value for that choice. If the option applies to your home, copy the number into the "Your Score" column.

Add only those options that have the "builder" symbol ( ). Numbers in "outline" print (4) indicate options done by the homeowner ( ) and should not be used in rating the attributes of the home.

2. At the end of each resource section, enter your total for that section.
3. Examine the Scoring Chart, located at the end of this section, for each resource section and locate where your total falls. Record the assigned number for your total [there is a range that your total will fall within].

4. Add up the resource section assigned numbers to get a Grand Total*.
5. Compare your Grand Total on the final page called Understanding Your Score for your Eco-Home Rating.

*Note that any points reflect positively on the house's impact on the environment and very likely on your personal health.

Important Notes on Rating Your Home

Some products or systems found in your house that are not included in our rating sheets may also be valid Eco-Options. Contact our office for information on how to rate these.

Several Eco-Options are currently very difficult to access and provide. Building professionals and homeowners should recognize that this is an early stage in the development of Eco-Home product availability. It is your request for such products and technologies that will bring them about.

Potential Homeowners: Note that you will need to discuss the Eco-Options presented in this section with the builder in order to determine if they are present in the home since many Eco-Options are not obvious in a completed home.

Building Professionals: Builders that are offering an Eco-Home can complete the **Rating Your Home** section before showing the home or as a guide in evaluating a custom design. This will facilitate answering customers questions. All building professionals are welcome to contact our office for assistance in completing this section.

This program was designed with newly constructed homes in mind. However, owners wanting to retrofit existing homes can certainly take advantage of the information presented here.

A "Sustainable Building Resource Guide" is currently being developed by the Green Builder Program staff which will provide sources, resources, procedural guidelines, and technical design information on the Eco-Options presented here. Scheduled for final distribution in Fall 1992, building professionals can contact our office for earlier technical assistance.

W-1
Rating Your Home

Water

Water use can be broken into 2 basic categories: **Indoor** and **Outdoor**. Indoor uses include *potable* needs, washing and cleaning, and toilet flushing. Outdoor needs pertain to keeping our landscape healthy and vibrant.

Indoor Uses	Option	Points	Your Score
1. A <i>harvested rainwater</i> system is used for indoor water uses	15
2. Copper piping is used for all <i>potable</i> water lines	1
3. <i>Potable</i> water is tested at the tap and <i>treated</i> as needed (i.e. rainwater, greywater systems)	2
4. Faucet flow is 2.0 gpm (gallons per minute) or less	1
5. Shower flow is 2.5 gpm or less	2
6. Toilet water usage is 1.5 gpf (gallons per flush) or less	2
7. <i>Composting toilet</i> (If this applies, you also score points for "Toilet water usage is 1.5 gpf or less")	7	
Outdoor uses	Options	Points	Your Score
8. Terracing and/or plantings on slopes to conserve moisture and control runoff	5
9. <i>Pervious materials</i> for walkways, patios and driveways.	5	

SUBTOTAL PAGE W-1 _____

W-2
Rating Your Home

Water

Outdoor uses	Options	Points	Your Score
10. A graywater/irrigation system	16
11. Rainwater from roof and/or landscape is captured for irrigation purposes	8
12. Xeriscape landscape is incorporated with graywater irrigation distributed to the water tolerant areas of landscape. OR	9
13. Xeriscape landscape requiring <u>no</u> irrigation OR	7
14. Xeriscape landscape is incorporated with harvested rainwater system as irrigation water distributed to water tolerant areas of landscape	7
15. Automatic irrigation consists of: a. Timer with rain override set for early A.M. every 5-7 days b. Drip irrigation, soaker hoses, and bubblers c. Irrigation system zoned according to the plants' demands	4
16. Hand watering	4	

SUBTOTAL PAGE W-2 _____

SUBTOTAL PAGE W-1 _____

Total Water _____

E-1
Rating Your Home

Energy

There are 3 general categories of energy use in the home selected for this rating: **Space Heating and Cooling, Lighting & Appliance Operation, and Water Heating.** Note that several Eco-Options have multiple benefits and may be listed in several use categories. Points are scored each time that Eco-Option appears if it applies to your house.

	Option Space Heating and Cooling: Thermal Envelope Options	Points	Your Score
1. Three-Star <i>Energy Star</i> Rating OR	18
2. Two-Star <i>Energy Star</i> Rating OR	12
3. One-Star <i>Energy Star</i> Rating	8
4. <i>Passive solar</i> design is the primary strategy for maintaining comfort, providing at least 50% of the home's heating and cooling needs OR	16
5. <i>Earth-sheltered</i> design reduces cooling and heating needs by at least 30%	12
6. Interior <i>thermal mass</i> sized to assist in heating and cooling the house	10
7. Operable windows in all living areas with south and north windows for natural air flow	6
8. Continuous ridge and soffit venting	4
9. <i>Wingwalls</i> increase natural ventilation	4
10. <i>Thermal chimney</i> increases natural ventilation	6	

SUBTOTAL PAGE E-1 _____

E-2
Rating Your Home

Energy

	Option Space Heating and Cooling: Mechanical System Options	Points	Your Score
11. <i>Energy Recovery Ventilator (ERV)</i> OR	4
12. <i>Energy Recovery Ventilator (ERV) with humidity regulation</i>	6
13. <i>"Smart House"</i> control technology is used to regulate heating, cooling, and lighting.	12
14. <i>Whole-house fan</i> with winter insulation	2
15. Ceiling fans installed in primary spaces (bedrooms, living areas)	2
16. Active solar heating system provides 40-65% of the home's heating needs	6
17. <i>Active solar system</i> for space cooling	5
18. High efficiency wood-burning equipment with a <i>catalytic converter</i> or is a <i>high mass unit</i> . Proper safety and ventilation is provided.	5	
	Landscape/ Exterior Options
19. <i>Deciduous</i> shade plants on east and west sides of the house will block summer sun and admit winter sun	6
20. Northwest and north sides of the house have a planted or natural windbreak	6	

SUBTOTAL PAGE E-2 _____

E-3
Rating Your Home

Energy

	Option	Points	Your Score
	Space Heating and Cooling: Landscape/ Exterior Options
21. Reflective and heat absorbing materials (i.e. unshaded white gravel, concrete patios) do not adjoin the house	3	
	Lighting, Appliance General Electrical Needs
22. <i>Daylighting strategies</i> reduce the need for artificial lighting	6
23. Interior colors are light shades	4
24. Task lighting is available	1
25. <i>Full spectrum lights</i> are used	1
26. A <i>photovoltaic system</i> generates over 30% of the home's electrical needs	15
27. A <i>wind machine</i> provides at least 30% of the home's electrical needs	15
28. <i>DC lighting</i>	2
29. <i>Energy efficient exterior lighting</i> (see glossary)	1	

SUBTOTAL PAGE E-3 _____

E-4
Rating Your Home

Energy

	Option	Points	Your Score
	Lighting, Appliance and General Electrical Needs		
☐	30. Refrigerator uses 35 kilowatt hours or less annually per cubic foot (see glossary)	2	
☐	31. Clothes are dried primarily (75% of the time) outside	5
H	32. Electromagnetic fields (EMF's) are minimized in the living areas (see glossary)	2	
	Water heating
☐	33. Passive solar water heater provides at least 50% of the hot water OR	7
☐	34. Active solar water heater provides at least 50% of the hot water	6	
☐	35. Heat exchanger captures flue gas heat from wood- burning appliances to heat water	5
36. High efficiency (83%+) gas water heater also produces space heat. Proper ventilation is used.	2
37. Graywater heat reclaimer supplements water heater	5	

SUBTOTAL PAGE E-4 _____

SUBTOTAL PAGE E-3 _____

SUBTOTAL PAGE E-2 _____

SUBTOTAL PAGE E-1 _____

TOTAL ENERGY _____

M-1
Rating Your Home

Materials

Eight general material categories are examined in this section: **Structural Frame, Foundation, Floor, Roof, Wall, Windows/Doors/Trim, Finishes/Adhesives, Insulation.** There are many options and variations that can occur in material selections depending on the style/design of the house. This rating section will look at only the most health and environmentally pertinent options that should be evaluated. As in the energy section, there will be overlaps of options.

	Option	Points	Your Score
	Structural Frame
1. Wood from " <i>certified</i> " sustainably managed forests	6
2. Borate treated lumber instead of pressure treated lumber where applicable	6
3. recycled plastic lumber (100% post-consumer content) where applicable	4
4. Yellow Pine for dimensional lumber	5
5. Avoid woods from <i>old-growth</i> forests such as Redwood	3	
	Foundation
6. Western coal flyash concrete OR	9
7. Indigenous stone (If from your site add 1 point) OR	9
8. Caliche block (If from your site add 1 point) OR	9	

SUBTOTAL PAGE M-1 _____

M-2
Rating Your Home
Materials

	Option Foundation	Points	Your Score
9. Regionally produced bricks	8
10. <i>Sand barrier termite prevention</i> technique and termite shields	7	
	Floor
11. Western coal flyash concrete	10
12. Underlayment is formaldehyde free cellulose-based material OR	5
13. <i>Exterior grade</i> plywood for underlayment OR	4
14. Sealed plywood for underlayment OR	5
15. Solid wood underlayment	5
16. Locally produced brick OR	9
17. Indigenous stone OR	10
18. <i>Caliche</i> material. (See glossary)	10
19. Regional <i>mesquite</i> hardwood flooring without glues or synthetic backing material OR	11
20. Domestic hardwood flooring without glues or synthetic backing material OR	6
21. Reused wood flooring	9	

SUBTOTAL PAGE M-2 _____

M-3
Rating Your Home

Materials

	Option Floor	Points	Your Score
H	22. Natural linoleum flooring applied with non- toxic glues	5
H	23. Carpeting/area rugs are natural untreated materials with natural material backings; tacked, not glued	5
24. Recycled content carpeting.	3
H	25. Ceramic tile with a mortar base	6	
	Roof
26. Clay or cementitious roof material	4
27. Recycled content asphalt shingles.	3
28. 30-50 year (or greater) roof material	1
29. Recycled content cellulose-based decking.	4	

SUBTOTAL PAGE M-3 _____

M-4
Rating Your Home

Materials

	Option Wall	Points	Your Score
30. <i>Agricultural waste based products</i> such as straw. (see glossary)	12
31. Locally produced brick for the interior side covering, at least 25% of net wall area. OR	9
32. <i>Indigenous stone</i> for the interior side covering, at least 25% of the net wall area.	10
33. Gypsum wallboard with non-toxic joint compound. OR	4
34. <i>Gypsum/cellulose</i> wallboard products.	5
35. Western coal <i>flyash</i> concrete is the primary wall component for at least 25% of the net wall area.	10
36. Plastered walls-concrete or gypsum OR	4
37. Recycled gypsum plaster	6
38. Solid domestic hardwood paneling (i.e. tongue & groove)	6
39. Regional stone on the exterior is the primary wall covering (at least 70%) OR	9
40. Caliche block on the exterior is the primary wall covering OR	9
41. Regional brick on the exterior is the primary wall covering	8	

SUBTOTAL PAGE M-4 _____

M-5
Rating Your Home

Materials

	Option	Points	Your Score
	Windows/Doors/Trim
42. Wood windows	2
43. Doors are made with domestic hardwood	5
44. Solid wood panel doors	5
45. Recycled doors	7
46. Domestic hardwood trim material	3
47. No tropical hardwood (see glossary)	2
48. Solid domestic hardwood cabinets	6	
	Finishes/Adhesives
49. Natural paints, sealers and finishes	4
50. Paints do not contain mercury	2
51. Paints and finishes contain minimal V.O.C.'s (volatile organic compounds)	3
52. Low-biocide paints are used.	2
53. Low toxicity water-based adhesives	2	

SUBTOTAL PAGE M-5 _____

M-6
Rating Your Home

Materials

	Option	Points	Your Score
	Insulation
54. Cellulose insulation with borates (see glossary)	5
H	55. Cementitious foam insulation	5
56. No CFC or HCFC insulation	4
57. Perlite insulation	3	

SUBTOTAL PAGE M-6 _____

SUBTOTAL PAGE M-5 _____

SUBTOTAL PAGE M-4 _____

SUBTOTAL PAGE M-3 _____

SUBTOTAL PAGE M-2 _____

SUBTOTAL PAGE M-1 _____

TOTAL MATERIALS _____

W-1
Rating Your Home

Waste

The primary focus of this section is on the two sources of home wastes, the **home** and **yard**.

	Option	Points	Your Score
	Home
1. <i>Compost-connected disposal</i>	4
2. Compost system for food waste	6
3. <i>Kitchen recycling center</i> is built into the house	6
4. Hazardous material storage cabinet (lockable and vented to the exterior) is available	4
5. A built-in recycling holding center is available	5
6. Builder recycles construction waste	6
7. <i>"Pay As You Throw"</i> garbage service is used (if available)	3
8. Recycling pickup service is used OR	5
9. Recycling pickup service is made available	6	
	Yard
10. A compost area is set aside for yard waste	7	

TOTAL WASTE

Rating Your Home Summary Page

WATER TOTAL _____

WATER TOTAL 5-9 POINTS	⇒ ⇒ ⇒	1
WATER TOTAL 10-16 POINTS	⇒ ⇒ ⇒	2
WATER TOTAL 17-29 POINTS	⇒ ⇒ ⇒	3
WATER TOTAL 30+ POINTS	⇒ ⇒ ⇒	4

WATER SUSTAINABILITY SCORE

ENERGY TOTAL _____

ENERGY TOTAL 8-31 POINTS	⇒ ⇒ ⇒	1
ENERGY TOTAL 32-53 POINTS	⇒ ⇒ ⇒	2
ENERGY TOTAL 54-109 POINTS	⇒ ⇒ ⇒	3
ENERGY TOTAL 110+ POINTS	⇒ ⇒ ⇒	4

ENERGY SUSTAINABILITY SCORE

MATERIALS TOTAL _____

MATERIALS TOTAL 22-46 POINTS	⇒ ⇒ ⇒	1
MATERIALS TOTAL 47-116 POINTS	⇒ ⇒ ⇒	2
MATERIALS TOTAL 117-170 POINTS	⇒ ⇒ ⇒	3
MATERIALS TOTAL 171+ POINTS	⇒ ⇒ ⇒	4

MATERIALS SUSTAINABILITY SCORE

WASTE TOTAL _____

WASTE TOTAL 4-6 POINTS	⇒ ⇒ ⇒	1
WASTE TOTAL 7-17 POINTS	⇒ ⇒ ⇒	2
WASTE TOTAL 18-32 POINTS	⇒ ⇒ ⇒	3
WASTE TOTAL 33+ POINTS	⇒ ⇒ ⇒	4

WASTE SUSTAINABILITY SCORE

WATER SUSTAINABILITY SCORE _____
 ENERGY SUSTAINABILITY SCORE _____
 MATERIALS SUSTAINABILITY SCORE _____
 WASTE SUSTAINABILITY SCORE _____

TOTAL SUSTAINABILITY SCORE _____

UNDERSTANDING YOUR SCORE:

Enter your Total Sustainability Score from the previous page _____

If your score is between 3-6, your Eco-Home rating is **FAIR**.

If your score is between 7-10, your Eco-Home rating is **GOOD**.

If your score is between 11-14, your Eco-Home rating is **EXCELLENT**.

If your score is between 15-16, your Eco-Home rating is **SUPERIOR**.

GLOSSARY

H Identification symbol for Eco-Options that specifically avoid potential health threats to the house's occupants that may come about from conventional building practices and materials.

Identification symbol indicating Eco-Options that a builder would be able to provide most easily.

Identification symbol for Eco-Options that could be added later or relate to lifestyle.

Active solar heating - Heat from the sun is absorbed by collectors and transferred by pumps or fans to a storage unit for later use or to the house interior directly. Controls regulating the operation are needed.

Active solar water heater - Heat from the sun is absorbed by collectors and transferred by pumps to a storage unit. The heated fluid in the storage unit conveys its heat to the domestic hot water of the house through a heat exchanger. Controls regulating the operation are needed.

Agricultural by-products - Products developed in agriculture that were not the primary goal of the agricultural activity. The most common used as a building product is straw which is used in wall panels or as bales in a technique called straw bale construction with the bales used as building blocks. The straw bale construction method was common in the plains states at the turn of the century and is currently being revived in Europe and the U.S.

Asbestos - A mineral fiber that has been commonly used in many building construction materials for insulation and as a fire-retardant. Invisible fibers of asbestos can be inhaled and have been connected to lung diseases and cancer.

Borate-treated wood - Mineral product derived from borax. The treating of wood with borates has been done in Australia and New Zealand for many years for insect and moisture protection. Commercial applicability in the U.S. is being researched with projected availability within two years. Borate coatings that can be added at the site are available now.

Built environment - Refers to human-built structures. In the Green Builder Program, the built environment pertains to single family homes.

Caliche - Calcium carbonate, common to semi-arid parts of Central Texas. It makes especially hard brick without firing and is a common roadbed material. It is not commercially available at this time. However, small manufacturing operations have been set up in central Texas for special projects.

Carbon dioxide (CO₂) - A colorless, odorless incombustible gas that is attributed with being a major contributor to global warming. It is a by-product of all combustion processes.

Carbon monoxide (CO) - A colorless, odorless gas that comes from incomplete combustion. Gas stoves, fireplaces, kerosene appliances, tobacco smoke, and automobile exhaust are potential indoor sources. Proper ventilation is important to prevent negative health effects such as fatigue, dizziness, and nausea.

Catalytic converter - A reaction chamber where exhaust gases are oxidized from carbon monoxide and hydrocarbons to carbon dioxide and water. Common in automobiles.

Cellulose - The fibrous part of plants used in making paper and textiles. Most building products with the word cellulose imply that paper was used in the manufacture.

Cellulose insulation with borates - Cellulose insulation is made from recycled newspaper. The borates provide fire and vermin protection. Most cellulose insulation now uses chemical fire retardants as opposed to the natural borates. Environmentally sensitive persons should avoid cellulose insulation. The ink and formaldehyde in the newspaper can cause allergic reactions.

Cementitious foam insulation - A magnesium oxide based material blown with air to create an inert, effective insulation. It is especially good for people with chemical sensitivities. It is not readily available in Texas at this time. It requires certified installers.

Certified sustainably managed - Some certifying organizations have been established that oversee the harvesting of wood for lumber. The underlying guideline is preservation of a diverse sustainable forest that exhibits the same ecological characteristics as a healthy natural forest. Few wood products are presently being certified.

CFC/HCFC - Chlorofluorocarbon and hydrogen chlorofluorocarbon are attributed as major contributors to the destruction of the earth's ozone layer. HCFC is 1/20th as potent as CFC in its ozone-destroying capacity. However, any additional threat to the ozone layer can be calamitous due to the long term potency of CFC's. The current ozone damage is generally attributed to CFCs released ten to fifteen years ago. Twenty percent of ozone damage is caused by CFCs in insulation.

Composite materials - A complex material made up of two or more complementary substances. They are difficult or impossible to recycle. Plastic laminates are an example.

Compost-connected disposal - A disposal that grinds food waste into a container to be used for compost rather than sending it into the wastewater system. This product is available.

Composting toilet - Several commercial composting toilets are available that effectively compost human waste. The process requires no water and does not create a health or odor problem when the toilet is properly installed.

Compost system - Converts organic waste (food, plant material) into a rich fertilizer. Several commercial models are available that prevent odors and thwart animals.

Daylighting strategies - Methods to use natural light to full advantage minimizing the need for artificial lighting during the day. Strategies include: a clerestory that allows natural light into a building interior through a raised section of roof with vertical glass. Shading of the glass allows light in while minimizing heat gain. Louvers on the exterior of vertical glass on a house can reflect natural light into the interior without the excessive heat gain associated with harsh, direct sunlight. Horizontal light shelves, located high on a wall with glass above (and possibly below) and projecting into the interior and typically to the exterior as well, are excellent devices for bouncing daylight deep into a room.

- DC lighting** - Direct current (DC) lighting can operate on site-generated electricity and creates less EMFs. There is DC lighting available for conventional AC (alternating current) systems.
- Deciduous** - Trees and plants that shed their leaves at the end of the growing season.
- 'Dillo dirt** - The composted sludge produced from Austin's wastewater and yard waste. It is a rich fertilizer commercially available for use in landscapes, but not in vegetable gardens.
- Drip irrigation** - Above-ground, low-pressure watering system with flexible tubing that releases small steady amounts of water through emitters placed near individual plants.
- Domestic hardwood** - Deciduous trees that grow in the United States. This is the only type of wood in the U.S. where on a general scale the growth of new trees easily exceeds the removal rate.
- Earth sheltered design** - Home design that is partially or totally below ground, either by digging into existing topography or filling over parts of the structure. Earth sheltered design uses the constant temperature of the soil to improve energy efficiency and can be beneficial for use on hilly sites to decrease maintenance and environmental impact.
- Earth's thermal energy** - A short distance below the surface, the Earth maintains a mostly constant temperature very close to the human comfort range. This can be used advantageously for certain heating and cooling systems. The higher temperatures found in the Earth are also used for producing electricity in some areas.
- Efficient fixtures and appliances** - Fixtures and appliances that use the least amount of energy and water and accomplish the task. For example, horizontal axis clothes washers use one-third of the water used by the more common vertical axis clothes washers to wash the same size laundry load.
- Electromagnetic fields (EMFs)** - Electric and magnetic fields are common in nature and in all living things. Electric power produces fields that have a possible association with health risks. Continuing health risk evaluation is occurring but avoiding excessive exposure is recommended. Placing electric meters and panels on walls of empty rooms is a simple method to minimize exposure to EMFs.
- Embodied energy** - The energy invested in bringing a product or material into existence.
- Energy efficient exterior lighting** - Motion sensors and photo switches that activate exterior lights only when needed. Energy efficient bulbs and reflectors reduce the energy when lit.
- Energy Star Rating** - The City of Austin rates the energy efficiency of homes. A three-star home is the highest rating for energy efficiency. The rating considers shading, R-values, building exterior colors, lighting and equipment efficiencies. Energy Star Rated-homes all exceed energy code requirements.
- Energy recovery ventilator (ERV)** - A mechanical device that draws stale air from the house and transfers the heat or coolness in that air to the air being pulled into the house. This can help reduce energy costs and dilute indoor pollutants.

Energy recovery ventilator (ERV) with humidity regulation - This mechanical device creates decreased or increased humidity as needed in the incoming air using the outgoing air as the source. A particularly appropriate feature for Austin's conditions.

Exterior grade plywood - Uses phenol formaldehyde as an adhesive which is released in much smaller amounts compared to urea formaldehyde which is used in interior grade plywood and particleboard.

Formaldehyde - Colorless, pungent smelling, toxic material used as an adhering component of glues in many wood products. It can cause respiratory problems, cancer, and chemical sensitivity.

Flyash - The ash residue from high temperature combustion processes. Electric power plants using western coal such as Austin's Fayette plant produce a non-toxic flyash that because of its high calcium content can be a substitute for Portland Cement (the common binding material in concrete).

Full spectrum lights - These lights come closer to the natural light spectrum and are considered more healthy.

Graywater - Water that has been used for showering, clothes washing, and faucet uses. This water has excellent potential to be reused as irrigation for yards.

Graywater heat reclaimer- Most water used for washing and showering is heated. The graywater heat reclaimer is a heat exchanger that captures much of the heat in the outgoing graywater and transfers it to the incoming water needed for hot water.

Gypsum/cellulose - A commercially available drywall product that uses cellulose from recycled newspapers with gypsum.

Harvested rainwater - The rain that falls on a roof or yard and is channeled by gutters or channels to a storage tank or cistern. The first wash of water on a roof is discarded and the subsequent rainfall is captured for use. Good quality water is available by this method in most areas away from extremely busy roadways.

Healthy home - A "healthy home" is built from non-toxic building materials and is designed to support and contribute to a healthy indoor environment.

High mass unit - A wood burning unit that permits complete and rapid combustion of the fuel. This minimizes pollutants and optimizes the heat output. It is typically constructed of massive materials such as brick, stone or water tanks in a manner so the heat is absorbed by the "mass" and then radiates over a long period of time into the space - long after the fire is out.

High quality duct system- Duct tape is not used in any part of the system. All ducts are sealed using a fibrated latex mastic and fiberglass tape, or metal tape meeting SMACNA standard 181. Inner and outer linings of the duct are both sealed. The air handler, support platform, and return plenum are sealed air tight at all joints. The system can be performance tested to ensure proper installation. Contact ECSD for instructions.

Indigenous stone - Stone from the Austin area such as limestone or marble.

Kilowatt-hour - A measure of electric usage equivalent to the use of 1,000 watts for one hour.

Kitchen recycling center - A built-in section of the kitchen cabinetry that allows convenient separation of recyclable materials.

Lead - A harmful environmental pollutant that is typically in the home in lead-based paints and in lead solder used in plumbing. Lead is toxic to many organs and can cause serious damage to the brain, kidneys, and nervous system.

Life-cycle assessment- A life cycle assessment (LCA) is an objective process to evaluate all the environmental burdens of a product or process through its entire existence. This encompasses extracting and processing raw materials, manufacturing, transportation, distribution, use and maintenance, recycling and final disposal.

Low biocide - Many paints have added fungicides and pesticides. A low-biocide paint does not include such additives.

Mesquite - This type of tree grows readily in Central Texas and is considered a nuisance by many. It produces a beautiful hard wood in short lengths. It is also an excellent wood for fuel.

Methane (CH₄) - An odorless, colorless, flammable gas that is a major component of natural gas. It is a more powerful global warming agent than carbon dioxide.

Natural linoleum - Cork is the primary material in natural linoleum. Cork is from the bark of the cork tree and is harvested without destroying the trees.

Natural paints - Paints and finishes made from plant and mineral material. There are several commercially available lines from Germany.

Nitrogen oxide (NO_x) - A colorless, poisonous gas. It is a by-product of gas combustion.

Nuclear waste - The radioactive by-products and contaminated materials produced in nuclear powered generating facilities. There is no proven method for safely disposing of these wastes some of which are extremely toxic for thousands of years.

Old-growth - Wood from trees found in mature forests. In many cases, the trees have never been exposed to logging operations. In the Northwest, only about 10% of these biologically rich areas are left. It is difficult to know which wood is from old-growth areas when buying wood locally. However, using Yellow Pine and avoiding Redwood (which is easily distinguishable) assures you of not supporting the cutting of old-growth trees.

Organic waste - Natural materials, food and yard waste that decompose naturally.

Outgas - The emitting of fumes into the air.

Particulate matter - Solid material that escapes from combustion processes.

Passive design - In home construction, the building design and placement permits the use of natural processes such as radiation, convection, absorption, and conduction to support comfort levels.

Passive cooling - The building's structure (or an element of it) is designed to permit increased ventilation and retention of coolness within the building components. The intention is to minimize or eliminate the need for mechanical means of cooling.

- Passive heating** - The building's structure (or an element of it) is designed to allow natural thermal energy flows such as radiation, conduction and natural convection generated by the sun to provide heat. The home relies solely or primarily on non-mechanical means of heating.
- Passive solar water heater** - A water heating system thatw does not require mechanical pumps or controls to create hot water for domestic use. There are several types available commercially.
- "Pay as you Throw"** - A garbage service that charges the user according to the amount of garbage generated.
- Perlite** - A natural volcanic glass that expands with heat and transforms into a fluffy form that can be used for insulation purposes.
- Pervious paving** - Paving material that allows water to penetrate to the soil below.
- Photovoltaic** - The process of converting sunlight directly into electricity. The electricity can be used immediately, stored in batteries, or sold to a utility. The cost continues to drop and the efficiency is improving for this technology. Austin has favorable sun conditions for using photovoltaics.
- Potable water** - Drinkable water.
- Pre-cycle** - Selecting products that minimize both garbage and recycling content.
- Pressure-treated wood** - Wood that is chemically preserved to prevent moisture decay. The process uses environmentally dangerous chemicals, and there is a health danger from working with, or coming into contact with the material.
- Proper ventilation** - Gases are vented completely to the outdoors. Combustion gases that escape into a living space can pose a health hazard.
- Radon** - A radioactive, colorless, odorless gas that occurs naturally. When trapped in buildings, concentrations build up, and it can cause health hazards such as lung cancer.
- Rain sensor** - Simple, inexpensive device that measures rainfall and prevents unnecessary irrigation with an automatic controller.
- Recycled plastic lumber** - Recycled plastic made into lumber. There are several manufacturers of this material in the U.S. which is workable like lumber. It is insect and water resistant.
- Refrigerator**- New refrigerators display Energy Guide Labels that indicate the average operating costs of the particular model. To calculate the amount of energy used per cubic foot for the model, use the following formula: divide the annual operating cost given on the Energy Label by the cost per kilowatt hour (kwh) that was used in reaching the annual cost amount. (The cost per kwh is typically found in the upper portion of the label.) Then divide that figure by the cubic foot size (that is also stated on the Energy Label). The result is the amount of energy consumed per cubic foot each year.

$$\text{annual energy cost} / \text{cost per kwh} / \text{cubic feet} = \text{kwh per cubic foot}$$
- Run-off** - Water from rainfall or irrigation that is allowed to flow off the property. Run-off can be thought of as a lost resource.

Sand barrier termite prevention - A shallow trench around the perimeter of the house foundation that is filled with sand. Termites cannot pass through the barrier because their tunnels cave in.

Smart house - Consists of programmable electronic controls and sensors that can regulate heating, cooling, lighting, appliance and equipment operation in an energy conserving and climatically responsive manner.

Soaker hose - A Low-flow watering device with small holes throughout the surface of the hose. Good for plant beds and gardens.

Soil moisture sensor - A device that can be attached to any automatic irrigation system that monitors the water available to plants and allows irrigation only when the soil moisture level drops below the desired level.

Sludge - The sediment extracted from wastewater.

Sulphur dioxide (SO₂) - A colorless, extremely irritating gas that is a primary cause of acid rain.

Thermal chimney - A section of a building where solar heat or thermal currents are controlled in a manner that stimulates an updraft and the exhaust of heated air. This draws in fresh air to occupied areas of the building through open windows or vents and is a passive cooling method.

Thermal envelope - The shell of a building that essentially creates a barrier from the elements. A highly insulated thermal envelope allows maximum control of interior temperatures without outdoor influence.

Thermal mass - Materials that absorb heat or coolness and store it for a long period of time. Water and masonry materials can provide thermal mass. Such materials react slowly to temperature variations and are important aspects of any passive solar heating or cooling system.

Tropical hardwood - Wood products harvested from tropical rainforests. Tropical forests are not being harvested in a well-managed manner except in a few isolated cases. Certification efforts indicating sustainably harvested woods are just beginning. Luaun (a tropical hard wood plywood) doors are common in the U.S.

Vapor retarder - A continuous membrane that surrounds the entire thermal envelope of a house. The membrane will stop moisture penetration into the walls.

Volatile organic compounds (VOC) - A large family of chemicals including all organic compounds (containing hydrogen and carbon) that vaporize at room temperature and pressure. They are found in many indoor sources, including many common household products and building materials. Finishes that contain VOCs can function as sealants preventing outgassing of other toxic substances. There are commercial brands of finishes available as a result of an environmental initiative in Canada that minimize the VOC content. Only these brands should be used and care must be taken in their application. Once thoroughly dried they do not pose a health threat.

Waste heat - Heat that escapes to the atmosphere during combustion processes. Minimizing and recapturing waste heat is a valuable energy conserving strategy. For example, there is heat in graywater, flues from woodburning stoves, and heat pump fluids that can be captured for other uses such as preheating domestic hot water.

Wastewater treatment - Wastewater is treated through a series of separation and aeration processes. A small amount of chlorine is added to Austin's wastewater before it enters the Colorado River.

Water conserving irrigation system - Drip irrigation, soaker hoses, bubblers and low-trajectory spray heads for water distribution; zoning irrigation for different water-demand plant types; electronic timers with five-day programming and rain override devices; irrigation schedules for early-morning watering every five to seven days, soil moisture sensors.

Watt - A unit of power indicating the rate at which work is done. The faster the rate an agent can do work the more powerful it is. Consequently, the wattage is higher.

Whole-house fan - A fan that is typically centrally located in the ceiling of the house. It pulls house air up into the attic area where it vents to the outdoors. The house air is replaced by outdoor air through open windows and screen doors. When outside temperatures have cooled down in the evening this is a less costly way financially and environmentally to cool down the house. It is important to be able to seal and insulate the fan opening during the winter when the fan is not needed.

Wind machine - Machine that generates electricity by the wind typically turning a generator-connected wind propeller. Austin is not a prime area for wind machines due to low annual wind speeds. However, new models that perform at lower wind speeds are becoming available.

Wingwalls - These are small exterior walls on a building set perpendicular to an exterior wall with windows on both sides of the wingwall. A negative pressure zone is created by the wingwalls stimulating breeze through the windows.

Xeriscape - Creative landscaping for water and energy efficiency and lower maintenance. The seven Xeriscape principles are: good planning and design; practical lawn areas; efficient irrigation; soil improvement; use of mulches; low water demand plants; good maintenance.

APPENDIX B

POINT EVALUATION WORKSHEET

Appendix B illustrates the development of points that were scored in their respective categories for the options shown in Appendix A. The "item" column is the number of the option from Appendix A preceded by "W" for Water, "E" for Energy, "M" for Materials, and "WS" for Waste. See Chapter 3, the section titled "Assigning Values," for information and discussion on how the scoring was conducted. The Point Evaluation Worksheets record how the option points are totaled for in-house purposes and is not presented to the public as part of the Eco-Home Guide.

APPENDIX B, POINT EVALUATION WORKSHEET

ITEM	SITE RESOURCE	SOURCE POINTS			PROCESS POINTS			USE POINTS			POST-USE (POST-LIFE)		INTEGRATION	DIFFICULTY FACTOR	USE FACTOR	TOTAL
		RECYCLED RESOURCE	RENEWABLE RESOURCE	REGIONAL	STATE	LOW EMBEDDED ENERGY	LOW ENVIRONMENTAL IMPACT	REGIONAL	STATE	QUANTITY	HEALTH	DURABILITY				
W1	1		1			1	1							1	3	15
W2											1				1	1
W3											1			1	1	2
W4										1					1	1
W5										2					1	2
W6										2					1	2
W7							1			3			1	1	7	7
W8						1	1			1					1	5
W9						1	1			1					1	5
W10		1					1			3		1			2	16
W11	1		1							3		1			7	7
W12		1				1	1			3		1			1	9
W13						1	1			3		1			7	7
W14						1	1			1					1	5
W15						1	1			2		1			1	4
W16						1	1			2					1	4
E1															1	18
E2																12
E3																8
E4	1		1			1	1			2		1			2	16
E5	1					1	1			1		1			2	12
E6						1	1			1		1			2	10
E7	1		1			1	1			1		1			1	6
E8	1					1	1			1					4	4
E9	1					1	1			1					1	4
E10	1		1			1	1			1					1	6
E11										1		1			1	6
E12										1					2	4
E13							1			1		1			3	6
E14							1			1					2	12
E15							1			1					1	2
E16	1		1				1			2					1	6
E17	1		1				1			1					1	5
E18							1			1					1	6
E19	1		1			1	1			1		1			1	5
E20	1		1			1	1			1		1			1	6
E21						1	1			1					1	3
E22	1		1			1	1			1					1	6
E23						1	1			1		1			1	4
E24										1					1	1
E25												1			1	1
E26	1		1			1	1								3	16
E27	1		1			1	1								3	15
E28										1					1	2
E29										1					1	1
E30										1					1	2
E31	1		1			1	1			1					1	2
E32															1	5
E33	1		1			1	1			2		1			1	2
E34	1		1			1	1								1	7
E35										1					1	6

APPENDIX B, POINT EVALUATION WORKSHEET

ITEM	SOURCE POINTS			PROCESS POINTS			USE POINTS			POST-USE (POST-LIFE)		INTEGRATION	DIFFICULTY FACTOR	USE FACTOR	TOTAL
	SITE RESOURCE	RECYCLED RESOURCE	RENEWABLE RESOURCE	REGIONAL	STATE	LOW EMBEDDED ENERGY	LOW ENV IMPACT	REGIONAL	STATE	QUANTITY	HEALTH	DURABILITY	POINTS EASY TO RECYCLE	POINTS DISPOSAL	
E36										1					2
E37		1				1				1				1	5
M1			1				1							1	8
M2			1											1	8
M3		1												1	4
M4			1		1									1	5
M5			1				1							1	3
M6		1		1	1	1		1	1					1	9
M7			1	1	1	1		1	1					1	9
M8			1	1	1	1		1	1					1	8
M9				1	1	1		1	1					1	7
M10			1	1	1	1		1	1					1	10
M11		1		1	1	1		1	1					1	5
M12		1					1							1	4
M13			1											1	5
M14			1											1	5
M15			1											1	9
M16				1	1			1	1					1	10
M17			1	1	1	1		1	1					1	10
M18		1		1	1	1		1	1					1	11
M19		1		1	1	1		1	1					1	6
M20		1				1								1	5
M21		1				1								1	5
M22			1											1	3
M23		1					1							1	6
M24														1	4
M25														1	4
M26		1												1	3
M27														1	1
M28		1												1	4
M29		1				1								1	12
M30			1				1							1	9
M31				1	1			1	1					1	10
M32				1	1	1		1	1					1	4
M33														1	5
M34		1				1								1	10
M35		1		1	1	1		1	1					1	4
M36														1	6
M37		1				1								1	6
M38			1											1	9
M39				1	1	1		1	1					1	8
M40				1	1	1		1	1					1	5
M41				1	1			1	1					1	2
M42														1	5
M43														1	7
M44														1	3
M45						1		1						1	2
M46														1	6
M47														1	4
M48														1	4
M49							1							1	4

ITEM	SOURCE POINTS			PROCESS POINTS			USE POINTS			POST-USE (POST-LIFE)		INTEGRATION	DIFFICULTY FACTOR	USE FACTOR	TOTAL
	SITE RESOURCE	RECYCLED RESOURCE	RENEWABLE RESOURCE	REGIONAL	STATE	LOW EMBEDDED ENERGY	LOW ENV IMPACT	REGIONAL	STATE	QUANTITY	HEALTH	DURABILITY	POINTS EASY TO RECYCLE	DISPOSAL	
M50							1							1	2
M51							1				1			1	3
M52											1			1	2
M53											1			1	2
M54		1				1					1			1	5
M55						1					1	1		1	5
M56							1				1			1	4
M57							1							1	3
WS1										1			1		4
WS2						1								1	6
WS3						1				2				1	6
WS4							1			1				1	4
WS5							1			2			1	1	5
WS6							1			2			1	1	6
WS7							1			1				1	3
WS8							1			2			1	1	5
WS9							1			2			1	1	6
WS10						1				3			1	1	7

REPORT AND INFORMATION SOURCES

Additional copies of this report, "Sustainable Systems Rating Program: Marketing "Green" Building in Austin, Texas," are available from:

Publications and Distribution
Public Technology, Inc.
1301 Pennsylvania Avenue, NW
Washington, D.C. 20004

For additional information on the process and the results of the work described in this report or for information on the overall energy management programs in Austin, Texas, please contact:

Michael Myers
Energy Services Division Manager
Environmental and Conservation Services Department
206 East 9th Street, Suite 17.102
Austin, Texas 78701

DG/91-302
05/92-150

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
90-331	Hydraulic Waste Energy Recovery: A Technical Report	15.00
90-318	A Regulatory Framework for Alternative Fuels and Transportation Management Services	15.00
90-316	Alternative Vehicle Fuels: A Demonstration Project	15.00
90-314	Energy Efficiency in Public Housing	15.00
89-330	Analysis of Programmatic Fleet Conversion to Ethanol Blends	15.00
89-325	An Alternative Fuels Evaluation System for Fleet Vehicles	15.00
89-323	Dual Fuel Conversion Demonstration and Technology Transfer Project	10.00
89-321	Summary of Low and Moderate Income Residential Energy Conservation Programs	15.00
89-315	A Case Study in the Pursuit of Urban Energy Efficiency	15.00
89-314	Communicating with the Public About Environmental Health Risks: A Case Study	13.00
89-313	Evaluation and Comparison of Selected Household Hazardous Waste Collection Facilities	15.00
89-311	Yard Waste Recycling Study: A Pilot Study	15.00
89-310	Sludge Storage Lagoon Biogas Recovery and Use, Volume 1	15.00
89-307	Proceeding: 1989 Electric Utility Franchise Conference	20.00
89-306	Reducing Electricity Demand Through Energy-Related Efficient Construction	15.00
89-304	Modernization of Lighting in Municipal Auditoriums	15.00
89-303	Wastewater Treatment Process Energy Optimization	13.00
89-301	Implementation of Alternative Technologies through the Assessment of Energy Markets	14.00
88-322	Marketing Energy Efficiency Programs to Commercial and Industrial Firms: Lighting Incentives and	15.00
88-321	Urban Energy Management Today: Ten Year Compendium of UCETF Programs	10.00
88-319	Integrating Energy Efficiency Into Municipal Purchasing Decisions: Computerizing Procurement	15.00
88-318	Household Hazardous Waste: Implementation of a Permanent Collection Facility	20.00
88-317	Hazardous Waste as an Energy Manager's Issue	15.00
88-316	Household Hazardous Waste Management Planning	15.00
88-312	Summary of Small Business Energy Conservation Programs	15.00
88-310	The Earth-Coupled Heat Pump: Utilizing Innovative Technology in Single Family Rehabilitation	15.00
88-309	Energy Planning for Economic Development	18.00
88-308	Conversion of Resource Recovery Steam to Hot and Chilled Water Systems	10.00
88-306	HVAC Equipment Replacement for Best Size and Efficiency, Transfer Report	15.00
88-305	Cogeneration and Cooling in Small Scale Applications	15.00
88-304	Energy Master Planning: Innovative Design and Energy Analysis Services for New Commercial	22.00
88-303	Energy Efficient Building Design: Guidelines for Local Government	15.00
88-302	Direct Digital Control of Air Washer Cooling System	15.00
88-301	Feasibility Study of Transportation Management Strategies in the Poplar Corridor, Memphis, Tennessee	18.00
87-327	Energy Efficient Urban Cooling Technologies: 1st National Conf.	20.00
87-324	Memphis Area Rideshare	15.00
87-317	Joint City Government/Utility Partnerships to Reduce Business Costs	15.00
87-314	The Impact of Budgetary Incentives on Energy Management	15.00

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
87-313	Computer Assisted Control for Municipal Water Systems, Phase II	20.00
87-312	Economic Development Through Energy Technology Transfer	15.00
87-311	Electric Utility Franchise Guide	20.00
87-310	Hidden Link: The Energy and Economic Development, Phase II	15.00
87-307	Municipal Underground Storage Tanks: An Energy Manager's Guide	18.00
87-306	Integrating Energy Efficiency into Mun. Purchasing Decisions	20.00
87-305	Energy Enhancement in New Residential Construction	40.00
87-302	Thermal Energy Storage: Application Guide for Local Governments	20.00
87-301	HVAC Equipment Replacement for Best Size & Efficiency	20.00
86-315	Balancing Single Pipe Steam Heating Systems	20.00
86-314	Inhibition of Respiration in Activated Sludge by High Carbon Dioxide Concentration	7.50
86-313	Water Supply System Energy Conservation Through Computer Control	18.00
86-312	Energy Cost Reduction Through Wastewater Flow Equalization	20.00
86-311	High Efficiency Gas Furnace Modification in Low Income Housing	15.00
86-310	Hidden Link: Energy and Economic Development, Phase I	15.00
86-307	Disposal Techniques with Energy Recovery for Scrapped Vehicle Tires	20.00
86-306	District Heating Marketing: Analysis of a Twelve City Survey	20.00
86-305	Technology Transfer for Residential Energy Programs in New Construction and Existing Housing	15.00
86-304	Technology Transfer for Residential Energy Efficiency	15.00
86-302	Neighborhood Energy Efficiency & Reinvestment	15.00
86-301	On-Site Municipal Fuel Cell Power Plan: Feasibility and Application Guide	15.00
85-326	Resource Recovery for Urban Yard Waste	18.00
85-323	Energy Monitoring and Controlling in Municipal Facilities	10.00
85-320	Transportation Management for Business Relocation	15.00
85-319	District Heating in Denmark	10.00
85-318	Computer-Assisted Control for Municipal Water Systems, Phase I	18.00
85-317	Financing Energy Efficient Housing as a Community Economic Development Tool	15.00
85-316	Modular District Heating Planning as a Development Tool	15.00
85-314	Alternative Techniques for Dev. of Energy Efficient Residences	15.00
85-312	Shared Savings and Low Income Homeowners	18.00
85-311	Measures and Investment Options for Community Energy Conservation	18.00
85-310	Planning for Energy Efficiency in New Commercial Buildings	15.00
85-308	Residential Space Heating with Wood	15.00
85-307	Thermal Storage Strategies for Energy Cost Reduction	18.00
84-325	Shared Savings in the Residential Market	20.00
84-324	Methanol Use in Vehicle Fleet Operations: Barriers	15.00
84-322	Energy Management and Technology for Urban Governments	15.00
84-321	Hydrate Process for Waste Water Treatment Plant Sludge Dewatering	15.00

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
84-320	Development of Computerized Inventory and Maintenance System for Municipal Street Lights	15.00
84-315	Facilities Energy Monitoring System	15.00
84-314	Application of Mini-Van Technology to Vanpool Services	18.00
84-312	Implementation Methods for an Integrated Energy System	10.00
84-311	Feasibility of Water-Based District Heating and Cooling	15.00
84-310	Budgetary Incentives for Municipal Energy Management	22.00
84-309	Central Energy Systems Applications to Economic Development	20.00
84-308	On-Site Cogeneration for Office Buildings	15.00
84-306	Analysis of Municipal Bus Operations for the Advancement of Fuel Cell Technology	15.00
84-305	Computer Based Maintenance	15.00
84-304	Innovative Finance Plans for Privately Owned Waste/Vol. 2	15.00
84-303	Innovative Finance Plans for Privately Owned Waste/ Vol. 1	15.00
84-301	Coordinating Preventive Maintenance with Energy Management	15.00
83-319	The Rehabilitation and Retrofit of Older Houses to Superinsulated Standards	15.00
83-318	Developing Sources and Techniques for Alternative Financing of Energy Conservation	20.00
83-316	Hydrate Process for Dewatering Sewage Sludge	10.00
83-315	Financial Planning for District Heating: Brooklyn Navy Yard	15.00
83-314	Memphis Area Rideshare On-Line Information System	18.00
83-313	Renovation Opportunities for Steam District Heating Systems	18.00
83-312	Initial Assessment of District Heating and Cooling	20.00
83-311	Energy Conservation Through Computerized Automation	18.00
83-309	Development of an Energy Park: Issues and Implementation Options	15.00
83-308	Alternative Uses for Digester Methane Gas	25.00
83-307	Innovative Financing and Incentive Package to Reduce Energy	15.00
83-305	Multi-Jurisdictional Planning for District Heating and Cooling	10.00
83-303	Improving Energy Management and Accountability in Municipal Operations	15.00
82-320	Utilization of Felled City Trees as Supplemental Boiler Fuel	7.50
82-319	Methanol Use in Vehicle Fleet Operations: Comparisons	15.00
82-317	Microcomputer Tools for Trans. and Residential Energy Conservation	20.00
82-316	Reduction of Impediments to Alternative Energy Use	20.00
82-315	Reducing Regulatory and Financial Impediments to Energy Conservation	20.00
82-314	Integrating Energy Management with Economic Development	20.00
82-313	Energy Conservation and Economic Development	10.00
82-310	Municipal Technologies	20.00
82-307	Strategies to Improve Community Energy Use Practices	10.00
82-306	Energy Conservation In Water Treatment	
82-305	Development of an Energy Action Plan: Participating Approach	15.00
82-303	Energy Economic Development	20.00

Publications Price List--UCETF Reports

ITEM #	TITLE	PRICE
82-302	Public Housing Energy Efficiency Through Private Financing	10.00
82-300	Developing an Energy Management Tracking System	
81-328	Matching End Use Energy Needs to Source Possibilities	20.00
81-327	Development of a Hydrogen-Fueled Mass Transit Vehicle s	15.00
81-326	Operational and Maintenance Guidelines for Reducing Energy Consumption	
81-324	Energy Management for Small Business	10.00
81-320	Energy Data Gathering, Analysis, and Review System	20.00
81-318	Fuel Management and Planning System for Local Government	25.00
81-316	Production of Ethanol from Cellulosic Fraction	
81-313	Metro-Dade County Comprehensive Energy Emergency Plan	
81-311	Developing Energy Emergency Preparedness	15.00
81-310	Simplified Methodology for Community Energy Management	20.00
81-309	Energy Management: The Public Sector	15.00
81-307	Municipal Technical Assistance-Energy Monitoring	6.00
81-306	New Technology Demonstration	10.00
81-305	Technology Transfer: Unit Report from the Energy Task Force	15.00
81-304	Development of Local Energy Management Preparedness	10.00
81-303	Municipal Energy Management	10.00
80-314	Methodology for Energy Impact Analysis of Urban Development Projects	15.00
80-313	Evaluation of Landfill Gas as an Energy Source	15.00
80-309	Decision Process for the Retrofit of Municipal Buildings	20.00
80-308	Primary Urban Energy Management Planning Methodology	7.50
80-306	Local Government Use of Thermography for Energy	15.00
79-300	Planning for and Purchasing Computer Technology	6.50

END

**DATE
FILMED**

2 / 9 / 93