rec'd 8/12/88

DOE/P_c DOE/PC/88859--T12

DE92 019207

FORMATION AND DESTRUCTION OF NITROGEN
OXIDES IN COAL COMBUSTION

Second Quarterly Report

Received by OSTI

AUG 17 1992

April 1, 1988 - June 30, 1988

Wei-Yin Chen
Thomas W. Lester
Lucia Babcock

Louisiana State University
Baton Rouge, LA 70803

Submitted to:

Diane Madden
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Work Performed Under the Contract DE-AC22-88PC88859

RECEIVED
USDOE/PETC
92 JUL 21 AM 10:22
KIMMEL 3 ASSISTANT DIR.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States, nor United States Department of Energy, nor any of their employees, makes an warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product, or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

This report has been reproduced directly from the best available copy.

Available from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161.

Price: Paper Copy

Microfiche

Acknowledgement

Substantial contributions to the work described in this report were made by Dr. Jan-Ku Chen, Tommy Burch and Roger Conray. The authors wish to acknowledge Ms. Bonnie McBride of NASA Lewis Research Center who kindly provided us CET86.

Table of Contents

I. Introduction.....	1
II. Technical Progress.....	2
A. Work Accomplished.....	2
1. Shock Tube.....	2
2. Flow Reactor.....	4
3. Downfired Furnace.....	5
4. Chemical Equilibrium Composition.....	5
a. Calculation Procedure.....	5
b. Results and Discussion.....	7
1. Effects of Stoichiometric Ratio.....	7
2. Effect of Fuel Properties.....	7
3. Effect of Input NO Concentration.....	8
c. Conclusion.....	8
B. Work Forecast.....	10
C. References.....	11

I. Introduction

This program addresses the sequential elucidation of the reactions (mechanism, thermodynamics and kinetics) between fuels (coal, oil and gas) and flue gases under fuel-rich conditions. The program simulates the reburning environment of a coal-fired boiler to identify reaction pathways of the nitrogen compounds (in the fuel and flue gas). The interactions between NO and hydrocarbon constituents in the fuel, and the fate of fuel nitrogen are the focal points of this research. Isotope doped ^{15}NO is used for tracing the reaction pathways. For environmental reasons, the project aims at demonstrating reduced emissions of total fixed nitrogen (all nitrogen compounds except N_2) based on both experimental evidence and theoretical analyses.

Three different experimental apparatus will be used to acquire data under different ranges of operation conditions. A shock tube and a bench scale flow reactor will be used to investigate the interaction between NO and various gas, liquid and solid fuels. The shock tube operates at high temperatures (1000 to 2500°K) and short reaction times (1.0 to 2.5 ms), while the flow reactor is designed for the investigation of long reaction times (about 1 sec) and relatively low temperatures (up to 1100°C).

Experiments will also be performed with a 30 Kw/hour downfired furnace, which was previously constructed by one of the co-principal investigators of this program at Kansas State University (KSU). During this quarter, this furnace was moved to the LSU campus.

Two computer codes, NASA CET86 and CHEMKIN, have been acquired for the chemical equilibrium and kinetics computation.

II. Technical Progress

A. Work Accomplished

1. Shock Tube

The work performed during this reporting period was directed toward gathering baseline data and developing various techniques for sampling, handling, and analyzing product gases. During the course of this work several problems were encountered and successfully overcome. The following is a review of the most significant of these problems and their solutions.

The most troublesome problem experienced thus far is sample contamination by atmospheric air. Nitric oxide (NO) is known to be converted, rapidly to nitrogen dioxide (NO₂) when exposed to oxygen. The dilute NO samples (nominally 1500 ppm) resulting from shock tube experiments are easily contaminated by minute quantities of air. Thus, special care must be taken to minimize the sample exposure from charging the shock tube with test gas to injection of the sample into the gas chromatograph (GC) for analysis.

The most significant sources of contamination were found to be air links into the gas sampling manifold of the shock tube and air contained in the syringe and needle used for GC injection. After carefully researching the joints and fittings of the gas manifold, the leak rate was reduced to an acceptable level such that the maximum error expected from this source is approximately 0.5%.

Eliminating air contamination from the syringe and needle required more elaborate measures. Calculations showed that the volume of the needle (estimated to be .01 cc) could contain enough air to eliminate 5% of the NO contained in the typical 100cc sample bottle. Thus, each successive extraction from the small bottle resulted in further contamination at unacceptable levels. Further, the needle is necessarily exposed to the air between extracting the sample from the sample bottle and injecting the sample into the GC. Thus any variation in exposure time or procedure resulted in significant variations in the quantity of NO actually measured by the GC.

Each of the sample bottles was modified as shown in figure 1.1 in order to eliminate sampler contamination. The main feature of the modification is the double septum arrangement with the septa separated by a helium reservoir contained in the EPA sample bag at atmospheric pressure. By preparing the syringe with helium then flushing the syringe with helium from the helium reservoir before extracting a sample from the sample bottle, the estimated contamination was reduced to 5×10^{-5}

percent per extraction. Air exposure of the sample contained in the syringe was also eliminated by compressing the sample to the desired quantity and venting to the helium reservoir rather than air. The syringe valve was then closed and the sample transported to the GC. After inserting the needle into the GC septum, sufficient time was accounted for scrubbing of the needle by the helium carrier gas and column clearing before the injection was made. By incorporating these steps, any possible exposure to air was eliminated allowing multiple injections from the same sample bottle with no loss of reproducibility.

Another problem which appears to be specific to these experiments is the apparent sensitivity of the GC response factor (moles of species/area counts) to the concentration on total moles of each injection. The sensitivity is noticeable with nitrogen and substantial with NO as shown in figure 1.2. Culpability in this case seems to rest in the poor separation of the N₂ and NO leaks from the mother peak of argon as shown in figure 1.3. Since the concentration of argon is so dominant (ie typically 95% of the sample), the 6 ft. x 1/8 in. MS-5A column was unable to adequately separate these compounds. Consequently, the areas of the N₂ and NO peaks were made using a tangent "baseline" drawn from the mother peak of argon. Although the area counts were repeatable for a given sample, the tangent calculation attributed too few area counts to the N₂ and NO peaks. Thus, as the N₂ and NO concentrations changed from sample to sample the apparent response factor also changed. This problem was multiplied in that for shock tube samples, part of the dilution of the test gas was with helium (driver gas) instead of argon. This resulted in variation in shape of the argon peak which in turn changed the tangent calculations of the N₂ and NO peak areas.

In order to improve the separation of gas species, an additional 6ft. x 1/8 in. MS 5A column was added in series with the first column. The resulting chromatography shown in figure 1.4 shows excellent separation of all peaks. This allows a true baseline calculation of N₂ and NO peak areas and substantially reduces the variations in response factor.

One remaining problem with analysis lies in the substantial tailing of the NO peak. Dietz (1968) reported a pretreatment procedure for MS 5A columns to saturate "active" sites in the column and eliminate NO tailing. A modified Dietz method proposed by Clay and Lynn (1975) will be used to pretreat the columns used in this work. Also, a new 12 ft. x 1/8 in. MS 5A column has been ordered to eliminate existing dead space between the present columns.

Previous work by Kirsch (1986) with this shock tube facility showed substantial loss of NO in test gases shock heated above 1550°K. The NO recovery curve reported by Kirsch is shown in figure 1.5. This is thought to be caused primarily by hydrocarbons which hide in the rough interior surfaces of the shock tube. In order to eliminate the hiding places and facilitate cleaning of the shock tube between runs, plans have been made to have the shock tube honed.

Following the shock tube honing and GC column pretreatment, improved NO recovery and GC response factor curves will be generated. This should provide a stable foundation on which future experiments can be based.

2. Flow Reactor

The research with a flow reactor focuses on the long reaction time kinetics and the analysis of nitrogen compounds in the tar. An isotope tracing technique is to be used.

The flow reactor described in the first quarterly report was constructed (Figure 2.1) and tested in this quarter. The features of this reactor include a rapid coal injection port, a surge cylinder for dumping the pressure pulse, and an online cold trap/thermal desorption unit.

Temperature - programmed desorption (TPD) has been used in the EPA standard methods of analysis of semi-volatile compounds in the flue gas (Harris, et. al., 1984). During this quarter, we attempted to extend this approach to the analysis of the gaseous components in the flue gas with a thermal desorption unit interfaced with an online mass spectrometer (MS). Test runs were conducted under coal pyrolysis conditions. The volatiles derived from Illinois No. 6 coal were collected in a U-tube immersed in liquid nitrogen. Silica gel with size 10/20 meshes was used as sorbent. The carrier He gas passes the U-tube and is evacuated by a vacuum pump.

The U-tube was then placed in a TPD/MS system for analysis. The U-tube was cooled at - 184°C initially and gradually heated up to 300°C with 5°C and 10°/min rates. Major gaseous products were analyzed by monitoring ten selected mass numbers 15, 16, 17, 18, 26, 27, 28, 29, 30, and 44. The products of interests in this task include CH₄, C₂H₄, C₂H₆, H₂O, NH₃, CO₂, CO, HCN, and C₃H₈.

The results of a series of test runs indicates that the separation of peaks strongly depends on the sample size, carrier gas flow rate, heating rate, and the type of sorbents. Due to the lengthy time required for the study of these variables and the development of a TPD/MS procedure, we plan to divide the analytical scheme into two

routes. The first route involves the "classical" approach of collecting the gas and liquid samples in glass bulbs (or stainless cylinder) and on the sorbent in a $\bar{U}$ -tube immersed in iced water, respectively. The gas sample will then be analyzed by GC/MS. The liquid sample will be separated into acid/base fractions, and analyzed by GC/MS (Novotny, et. al., 1981). During this program period, we will continuously explore the feasibility of using TPD/MS for gas analysis.

3. Downfired Furnace

The downfired furnace was relocated to the LSU campus during this quarter. The furnace is expected to be put into operation during the next quarter.

4. Chemical Equilibrium Composition

Reduction of NO_x by hydrocarbons in the flame is kinetically controlled (Sarofim, et. al., 1976). The chemical equilibrium analysis provides information concerning the stoichiometric constraints and it is part of our effort of evaluating reburning potential. The equilibrium analysis described below has the following objectives.

- * to study the effects of reburning fuel properties and stoichiometric constraints on equilibrium NO concentrations,
- * to study the effect of nitrogen content of reburning fuel.

a. Calculation Procedure

The NASA computer code CET86 (Gordon and McBride, 1976) was used to obtain the chemical equilibrium concentrations of the reburning stage under various feed compositions. CET86 minimizes the total Gibbs' free energy of the reaction system and uses the Newton-Ralphson method in the iteration.

The reburning stage, as defined by this investigation, includes three feed streams: flue gas from the primary combustion zone, reburning fuel, and oxidant used in reburning. Each of these feed streams are discussed below. The calculation procedure was designed to investigate the following variables: nature of reburning fuel, NO concentration of the flue gas, nitrogen content of the reburning fuel, and stoichiometric ratio.

In practice, reburning fuel accounts for 10 to 20 percent of total energy output. The amount of reburning fuel varies to adjust the stoichiometric ratio (air-to-

fuel) of the two combined stages (commonly designated as SR2). To amplify the characteristic combustion properties of the fuel we used 20 percent reburning fuel as the total energy output (at the high end of the range). Air was added in the reburning stage to adjust SR2. This calculation procedure should not affect the study of SR2 and other variables such as NO concentration in the flue gas and nitrogen content of reburning fuel.

Flue gas composition was also calculated using NASA's CET86. We assumed that Illinois No. 6 coal was used as the primary combustion fuel. The composition of this coal is shown in Table 1, and can be represented in elemental form: $C_{100}H_{76}N_{1.5}S_{2.7}O_{12.0}$ (dry and ash free basis). With 8% excess air, CEC76 provided the following equilibrium molar compositions of the flue gas at 1700°K and under 1 atm: $N_2=75.158\%$, $CO_2=16.577\%$, $H_2O=6.759\%$, $O_2=1.431\%$, and $NO=0.074\%$. Oxygen in the coal was also considered as an oxidant in the calculation of required air. This flue gas composition was used as one stream of reburning feed. The flue gas entered the burning stage at 1700°K.

Four classes of chemicals were chosen as reburning fuel:

- * Coals: Illinois No. 6, Wyodak coal, North Dakota lignite, Utah coal and Rosa coal (Table 1 lists some properties of these coals),
- * C_1 to C_8 straight chain aliphatic hydrocarbons,
- * Aromatics: benzene, naphthalene, anthracene and phenanthrene,
- * Carbon monoxide and ammonia.

In order to compare the reducing efficiency of these fuels, a common basis must be chosen among quantity, price and heat of combustion. Unit price and heat of combustion vary greatly among these substances, therefore NO reduction efficiency based on equivalent weights of these substances does not directly correlate with cost-effectiveness. In this study we chose the heat of combustion at 298°K as the reference base. Assuming the reburning stage produced 20 percent of the total energy output in the first two stages (a common practice, see reburning literature cited above), the required amounts of reburning fuel were calculated from their heat of combustion. These quantities are shown in Table 2.

We assumed that reburning fuels were fed into the combustor at 298°K. Enthalpies of the coals were calculated from the enthalpies of products ($H_2O + CO_2$) and heat of combustion of coal.

Air used in the reburning stage determined the stoichiometric ratio and is a major variable under investigation. Air entered the reburning zone at 298°K. As

discussed above, this stream was added to allow variation of SR2 and, at the same time, to amplify the characteristic combustion properties of the fuel. From a thermodynamic aspect, this should not affect the study of other stoichiometric variables.

The reaction of the three streams at 1 atm was adiabatic. The equilibrium concentrations were calculated by CET86.

b. Results and Discussion

1. Effects of Stoichiometric Ratio

Stoichiometric ratio (SR2) was the most important variable for all types of reburning fuel. Figures 4.1 to 4.5 demonstrate the effects of SR2 on NO reduction efficiency in a variety of reburning systems. The ratios of total fixed nitrogen (TFN, all nitrogen-containing compounds except molecular nitrogen) in the products to feed NO are plotted against SR2. Within the SR2 range, NO was the major component of TFN. Only small amounts of NH_3 and NO appeared for low and high SR2.

In most cases, NO was reduced to less than 1% when the air to fuel ratio decreased from 1.0 to 0.9. This high reduction was consistent with the chemical equilibrium calculation under fuel-rich conditions presented by Sarofim *et al.*, in 1976. The actual NO level in the reburning stage remains to be confirmed experimentally. Most reburning literature report the NO concentration after the burnout stage. Due to the burning of residual reburning fuel in the burnout stage, additional NO formed. Greene *et al.*, (1985) reported that $\text{SR2}=0.9$ is the optimal condition for NO reduction.

As we stated in the Introduction, it is expected that kinetic limitations can be overcome by the heat carried by the flue gas. From this respect, reburning is strongly correlated to air staging with air-preheat.

2. Effect of Fuel Properties

Figures 4.1 to 4.5 present NO reduction efficiency in a variety of reburning fuels: C_1 to C_8 straight chain hydrocarbons, aromatics, five coals, carbon monoxide and ammonia. It is interesting to note that, based on the same energy output (described in the Calculation Procedure section), the reburning fuels showed very similar reducing capability. Within the narrow range of observed differences, methane appeared to be the best reducing agent, and the following trend of reduction efficiencies was established: methane > ethane, NH_3 > butane > aromatics, coal > CO. This result differs from Myerson's (1974) observation, which may indicate kinetic limitations in his system. It should also be mentioned that recent literature has

suggested that NO can be reduced by soot (Seeker *et al.*, 1981) and by char (DeSoete, 1980). The present chemical equilibrium calculation does not take these facts into consideration.

We attempted to correlate NO emissions with coal rank and coal nitrogen content. Figures 4.6 and 4.7 present these limited data, and both appear to be increasing curves. It has been generally accepted that the nitrogen content in coal plays a critical role in reburning technology. The results shown in Figure 8 demonstrate the high TFN value derived from coal under equilibrium conditions in comparison to a "clean" reburning fuel, methane. Again, the roles of char and the nitrogen in the unburned char (not considered in the equilibrium calculation) may have a profound effect on reduction efficiency.

3. Effect of Input NO Concentration

Figures 4.8 and 4.9 present the effect of NO level at the inlet on the TFN emission. Flue gas with three NO concentrations, 240, 740 and 1240 ppm, were tested. Methane and Illinois No. 6 coal were used as reburning fuels. These results demonstrate that the equilibrium TFN concentration is insensitive to inlet NO level, a proven merit of reburning technology noted by Mitsubishi Heavy Industries (Takahashi *et al.*, 1982).

We have mentioned that the heat carried by the flue gas could push NO reduction closer to equilibrium conditions. Further verification would be required concerning the correlation of our calculated results with the promising data by Takahashi *et al.*

c. Conclusion

The study of stoichiometric constraints under equilibrium conditions provides us with the following information related to reburning as a NO reduction technology:

1. The stoichiometry of air to fuel is the most important stoichiometric variable for reburning,
2. Based on equivalent energy production, the comparative reduction efficiencies of the reburning fuels follow the trend: methane > ethane, ammonia > butane > aromatics, coal > CO,
3. The nitrogen in burning coals causes increases in equilibrium NO,
4. Equilibrium TFN is not very sensitive in inlet NO concentration,

5. The heat carried by the flue gas in reburning could push the NO reduction toward equilibrium. If so, reburning has a strong correlation with air staging with air preheat. Further experimental verification is required.

B. Work Forecast

A major effort in the next quarter will be devoted to the development of GC and GC/MS procedures. After adequate method development, the interaction of methane and other hydrocarbons with NO will be explored with the shock tube and the flow reactor. The downfired furnace will be refabricated in a combustion laboratory at LSU.

C. References

- Clay, D.T. and S. Lynn, "Pretreatment of molecular sieve 5A to eliminate tailing of nitric oxide", *Analytical Chemistry* **47**: 1205-1206, (1975).
- DeSoete, G.G., "Mechanism of NO Reduction on Solid Particles", EPA Workshop on Fundamental Combustion Research Applied to Pollution Control, Newport Beach, CA, Ja. 23-25, (1980).
- Dietz, R.N., "Gas chromatographic determination of nitric oxide on treated molecular sieve", *Analytical Chemistry*, **40**: 1576-1578, (1968).
- Gordon, S. and B.J. McBride, "Computer Program for Calculation of Complex Chemical Equilibrium Compositions. Rocket Performance Incident and Reflected Shocks, and Chapman-Jouguet Detonations", NASA SP-273, (1976).
- Green, S.B., S.L. Chen, D.W. Pershing, M.P. Heap and W.R. Seeker, "Bench Scale Process Evaluation of Reburning for in Furnace NO_x Reduction", EPA Report EPA/600/7-85/012, (March, 1985).
- Harris, J.C., D.J. Larsen, C.E. Rechsteiner, and K.E. Thrun, "Sampling and Analysis Methods for Hazardous Waste Compounds", U.S. EPA, EPA-60/8-84-002, PB 84-155845, (February 1984).
- Kirsch, M.J., "Kinetics of nitric oxide removal on carbon blacks under high temperatures", M.S. Thesis, Louisiana State University, (1986).
- Myerson, A.L., "The Reduction of Nitric Oxide in Simulated Combustion Effluents by Hydrocarbon-Oxygen Mixtures", *Proceedings 15th Symp. (Int'l) on Combustion*, The Combustion Institute, Pittsburgh, PA, p. 1085, (1974).
- Novoty, M., J.W. Strand, S.L. Smith, D. Wiesler and F.J. Schwende, "Compositional Studies of Coal Tar by Gas Chromatography/Mass Spectrometry", *Fuel*, **60**(3), 213, (1981).
- Sarofim, A.F., J.H. Pohl, and B.R. Taylor, "Strategies for Controlling Nitrogen Oxide Emissions During Combustion of Nitrogen-Bearing Fuels", Paper Presented at AIChE Annual Meeting, Chicago, Illinois, (November 30, 1976).
- Seeker, W.R., G.S. Samuelsen, M.P. Heap, and J.D. Trolinger, "The Thermal Decomposition of Pulverized Coal Particles", *Proceedings 18th Symp. (Int'l) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 1213, (1981).
- Takahashi, Y., M. Sakai, T. Kunimoto, S. Ohme, H. Haneda, T. Kawamura and S. Kaneko, "Development of MACT In-Furnace NO_x Removal Process for Steam Generators",

Proceedings of the 1982 Joint Symp. on Stationary Combustion NO_x Control, EPRI
Report CS-3182, (July 1983).

Table 1. Properties of Coals

Sample	PSOC-1351	PSOC-1405P	PSOC-1460P	Rosa	Utah
Rank	HVCB	SUBB	Lignite	MV	HVB
State	Illinois	Wyoming	N. Dakota	Alabama	Utah
Moisture	8.08	19.82	29.64	8.02	6.39
Ash	10.56	7.15	8.23	6.79	7.40
Volatile matter	37.08	38.23	31.32	21.81	38.89
Fixed carbon	44.28	34.89	30.80	63.38	47.32
C,daf,%	76.26	74.44	67.72	87.70	79.45
H,daf,%	4.85	5.46	4.97	5.11	6.03
N,daf,%	1.32	1.34	1.40	1.88	1.67
S,daf,%	5.31	2.03	1.33	1.12	0.72
O,(% by diff.)	12.26	16.73	24.58	4.19	12.14
H/C (atomic)	0.76	0.88	0.88	0.70	0.91

Table 2. Reburning Fuel Used in Computation

Reburning Fuel	Heat of Combustion at 25°C, kcal/g-mole	Amount Used in Reburning g-mole
CH ₄ (g)	-212.80	0.188
C ₂ H ₆ (g)	-372.82	0.107
C ₃ H ₈ (g)	-530.60	0.075
C ₄ H ₁₀ (g)	-687.64	0.058
C ₅ H ₁₂ (l)	-838.78	0.048
C ₆ H ₁₄ (l)	-995.01	0.040
C ₇ H ₁₆ (l)	-1149.90	0.035
C ₈ H ₁₈ (l)	-1302.70	0.033

C ₆ H ₆ , benzene (l)	-372.82	0.051
C ₁₀ H ₈ , naphthalene (s)	-1231.80	0.032
C ₁₄ H ₁₀ , anthracene (s)	-1712.00	0.023
C ₁₄ H ₁₀ , phenanthrene (s)	-1685.60	0.024

CO (g)	-67.64	0.590
NH ₃ (g)	-91.44	0.437

Illinois No. 6 Coal	-159.71*	4.965g*
Wyodak Coal	-129.23*	5.546g*
N.D. Lignite	-129.49*	4.310g*
Utah Coal	-131.28*	5.010g*
Rosa Coal	-171.41*	4.508g*

*Dry and ash free basis.

>Based on 20% of total energy output produced in the primary stage and reburning zone. In the primary combustion zone, 19.54 g Illinois No. 6 coal is burned.

Figure 1.1 Modified sample bottle with helium purge.

Figure 1.2 Gas chromatograph response factors for NO, N₂, and NE.

Figure 1.3 Chromatogram from injection of 2.0cc (atmospheric pressure) of sample containing 0.25% NE, 99.16% AR, 0.42% N₂, and 0.17% NO with a 6ft. x 1/8 in. MS 5A column.

Figure 1.4 Chromatogram from injection of 2.0 cc (Atmospheric pressure) of sample containing 1.5% NE, 95.0% AR, 2.5% N₂, 1.0% NO with a 12 ft. x 1/8 in. MS 5A column.

NO recovery

Figure 1.5 NO recovery from shock tube as a function of shock temperature.

Figure 2.1 Flow Reactor

Figure 4.1 Effects of SR2 and Reburning Fuel
(C₁ to C₄ Aliphatics)

Figure 4.2 Effects of SR2 and Reburning Fuel
(C_5 to C_8 Aliphatics)

Figure 4.3 Effects of SR2 and Reburning Fuels (NH_3 , CO and CH_4).

Figure 4.4 Effects of SR2 and Reburning Fuels (Benzene, Naphthalene, Anthracene, Phenanthrene and Methane).

Figure 4.5 Effects of SR2 and Coals.

Figure 4.6 Coal Rank Effect.

Figure 4.7 Effect of Coal Nitrogen Content.

Figure 4.8 Effect of Input NO (CH₄ Used as Reburning Fuel).

Figure 4.9 Effect of Input NO (Coal Used as Reburning Fuel).

**DATE
FILMED**

10 / 9 / 92