**Geology, Reservoir Engineering and
Methane Hydrate Potential of the
Walakpa Gas Field, North Slope, Alaska**

Final Report

**Richard K. Glenn
William W. Allen**

Work Performed Under Contract No.: DE-FG21-91MC28131

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
North Slope Borough
Barrow Gas Fields Development Project
P.O. Box 1120
Barrow, Alaska 99723**

December 1992

ABSTRACT

The Walakpa Gas Field, located near the city of Barrow on Alaska's North Slope, has been proven to be methane-bearing at depths of 2000 - 2550 feet below sea level. The producing formation is a laterally continuous, south-dipping, Lower Cretaceous shelf sandstone. The updip extent of the reservoir has not been determined by drilling, but probably extends to at least 1900 feet below sea level. Reservoir temperatures in the updip portion of the reservoir may be low enough to allow the presence of in situ methane hydrates. Reservoir net pay however, decreases to the north. Depths to the base of permafrost in the area average 940 feet.

Drilling techniques and production configuration in the Walakpa field were designed to minimize formation damage to the reservoir sandstone and to eliminate methane hydrates formed during production. Drilling development of the Walakpa field was a sequential updip and lateral stepout from a previously drilled, structurally lower confirmation well. Reservoir temperature, pressure, and gas chemistry data from the development wells confirm that they have been drilled in the free-methane portion of the reservoir. Future studies in the Walakpa field are planned to determine whether or not a component of the methane production is due to the dissociation of updip in situ hydrates.

ACKNOWLEDGEMENTS

This report could not be possible without the cooperation between the North Slope Borough Department of Industrial Development and the Morgantown Energy Technology Center of the U.S. Department of Energy. Special thanks to Joanne Attungana and Gayle Dawson for word processing, to Marie Ireland for computer drafting, and to Beverly Harness for her assistance from the Morgantown Energy Technology Center.

TABLE OF CONTENTS

	Page
Abstract	ii
Acknowledgements	iii
Table of Contents	iv
List of Figures	v
List of Tables	vi
OBJECTIVES	1
PROJECT DESCRIPTION AND METHODOLOGY	4
RESULTS	7
Structure	7
Walakpa Sandstone	7
Walakpa Field Gas Chemistry	13
Permafrost and Reservoir Temperature	17
Methane Hydrate Stability Field	21
Design Considerations	21
Drilling Strategy	21
Completion Strategy	23
Production Strategy	23
Production	25
FUTURE WORK	25
REFERENCES	26

LIST OF FIGURES

	Page
Figure 1. Index Map of the Walakpa area, North Slope, Alaska	2
Figure 2. Area map, Walakpa gas field	3
Figure 3. Stratigraphic table of the Walakpa area	5
Figure 4. Seismic structural map of the Walakpa gas field	8
Figure 5. Walakpa gas field structure	9
Figure 6. Gross pay map of the Walakpa Sandstone	11
Figure 7. Net pay map of the Walakpa Sandstone	12
Figure 8. Bulk porosity map of the Walakpa Sandstone	14
Figure 9. Estimated reservoir permability of the Walakpa field	15
Figure 10. Estimated maximum permafrost thickness, Walakpa gas field	19
Figure 11. Estimated reservoir temperature of the Walakpa field	20
Figure 12. Estimated methane hydrate stability field, Walakpa gas field	22
Figure 13. Schematic wellbore diagram, Walakpa gas field	24

LIST OF TABLES

	Page
Table 1a. Summary of Reservoir Data: Walakpa Nos. 1-5, Walakpa Gas Field, Alaska	10
Table 1b. Summary of Reservoir Data: Walakpa Nos. 6-10, Walakpa Gas Field, Alaska	10
Table 2. Walakpa Field Gas Chemistry, Molecular Composition (Mole %)	16
Table 3a. Geothermal Data for the Walakpa Gas Field, Alaska	18
Table 3b. Geothermal Data for the Walakpa Gas Field, Alaska	18

OBJECTIVES

The goal of the North Slope Hydrate Study is to evaluate the methane hydrate potential of the Walakpa gas field, a shallow gas field located near Barrow, Alaska. Understanding the reservoir potential and predicting the production characteristics of the Walakpa Fields is accomplished by analysis of the reservoir geology, production test data, as well as field-scale geothermal studies.

BACKGROUND INFORMATION

Barrow is a city of about 3,400 people, located at the northern tip of Alaska's North Slope (fig. 1). It is the largest city in the North Slope Borough (NSB), and contains one of the largest American settlements of Inupiat Eskimos. The community of Barrow has depended on natural gas for its heating and electrical generation needs since 1964. Until recently, the nearby South and East Barrow gas fields have accommodated the needs of the community. With tapering production from these fields and increasing demand, it became necessary to find new deliverable gas reserves for Barrow.

The Walakpa gas field is located about 18 miles southwest of Barrow, Alaska (fig. 2). The field is about 3 miles south of Walakpa Bay, a shallow estuary which flows northwest into the Chukchi Sea. The terrain of the area is swampy tundra lowlands, frozen for much of the year, with abundant oriented lakes. The Walakpa area has no roads, and was accessible by ice road during the winters of 1990-1991 and 1991-1992.

In the Walakpa region the tundra is underlain by a thin veneer of unconsolidated shallow marine and nonmarine deposits of the Quaternary Gubik Formation. The Gubik Formation unconformably overlies a stratigraphic section consisting of: south-dipping Ordovician and Silurian argillite basement, onlapping and shallow-dipping Upper Triassic to Lower Jurassic clastic shelf strata, and organic-rich Lower Cretaceous shale, mudstone and siltstone (fig. 3). A good review of the Barrow area structure and stratigraphy can be found in Kirschner and others (1992). Development wells in the Walakpa gas field penetrate only as deep as the Upper Jurassic, and encounter pay at a Lower Cretaceous unconformity (LCU) sandstone, named the Walakpa sandstone.

The discovery well of the Walakpa gas field, Walakpa No. 1, was drilled by the U.S. Geological Survey in the winter of 1979-1980 in order to test a stratigraphic trap formed by the LCU truncating an Upper Jurassic sandstone unit (Hewitt, 1982). Drilling of the No. 1 well instead encountered pay above the LCU in the Walakpa sandstone at a depth of 2023 feet subsea. The entire Walakpa sandstone interval was cored and consisted of good reservoir sandstone. The well flowed dry gas at approximately 325 Mcf/day on a 14/64" choke for a short duration before freezing off. Downhole shut-in reservoir pressure in the No. 1 well was 1,026 psia.

The Walakpa No. 2 well was drilled by the U.S. Geological Survey as a confirmation well 4.75 miles southwest of the No. 1 well (Patterson and others, 1982). Structurally, the No. 2 well was 550 feet lower than the No. 1 well, and encountered a thicker and more

Figure 1. Index map the Walakpa area, North Slope, Alaska.

EXPLANATION

Scale:
0 0.5 1.0 2.0 Statute Miles

GAS WELL

ABANDONED GAS WELL

Figure 2. Area map, Walakpa gas field.

permeable pay zone in the Walakpa sandstone. The well was drilled into basement to a total depth of 4,360 feet and plugged back to 2,721 feet. The Walakpa sandstone in the No. 2 well tested dry gas and flowed at rates as high as 2,293 Mcf/day through perforations before the well was suspended. Downhole shut-in pressures of the No. 2 well were 1025-1060 psia. The Walakpa sandstone in the No. 2 well had a calculated skin of 72, indicating that the formation could potentially flow at much higher rates in the absence of formation damage.

The discovery and confirmation wells in the Walakpa field identified a minimum gas column of 550 feet, assuming lateral continuity of the Walakpa sandstone. Regional seismic data indicated structural closure to the east and west. The U.S. Geological Survey identified the accumulation as a potential gas source for Barrow and the area remained undeveloped until the advent of the North Slope Borough's Walakpa Development Program.

Structurally, the accumulation is situated on the south side of an elongate, east-west trending dome, and is overlain by permafrost. Permafrost thickness in the region ranges from 600 to 1500 feet. In the Walakpa area itself, measured depths to the base of permafrost average 936 feet. The relatively cold thermal regime of the Walakpa area could allow the presence of naturally occurring methane hydrates in the updip portions of the Walakpa structure.

Hydrates are crystalline substances, composed of water and methane, in which an ice lattice accommodates gas molecules in a cage-like structure (Collett and Bird, 1988). The presence of methane hydrates would affect all aspects of natural gas development, from drilling to production. Their presence could also significantly increase the reserves of a gas field, because a given volume of methane hydrate contains as much as 160 times more methane as the same volume of free natural gas (Sloan, 1990).

In the winter of 1990-1991, following a two-year seismic exploration program, the North Slope Borough (NSB) began the drilling development of the Walakpa gas field to supply Barrow with a long-term natural gas source. The drilling development of this accumulation was accomplished during the winters of 1990-1991 and 1991-1992.

PROJECT DESCRIPTION AND METHODOLOGY

The North Slope Hydrate study was a cooperative research effort, funded by the United States Department of Energy and Alaska's North Slope Borough. This project involved a reservoir study of the Walakpa gas field, based on wellsite geological and engineering reports of the Walakpa field wells and previous geological and geophysical studies. In the North Slope Hydrate Study, particular attention was paid to the methane hydrate potential of the Walakpa gas field. This potential was determined by a two-fold process: First, a conventional analysis of the Walakpa reservoir was completed. Second, the geothermal regime of the field needed to be determined to identify gas-bearing portions of the reservoir cold enough to allow the presence of in situ methane hydrates.

The reservoir structure of the Walakpa sandstone was determined in a previous study by correlation of regional and local seismic data with existing well control (Paris and others,

STRATIGRAPHIC TABLE OF THE WALAKPA DEVELOPMENT AREA

MAX. DEPTH	MIN. DEPTH	LITHOLOGY	FORMATION	AGE	
100		sandstone, shale and conglomerate	Gubik Formation	Quaternary	
		light grey silty claystone with rare, thin (0 - 1 ft.) silty sand layers	Nanushuk Group	Albian - Aptian	Lower Cretaceous
1000	400	grey shale with carbonaceous silty beds	Torok Formation		
2200	1600	fissile to blocky carbonaceous black shale	'pebble shale'	Neocomian	
2550	2020	light brown-grey silty sandstone, massive sandstone, and basal conglomerate	Walakpa Sandstone		
2580	2040	dark brown-grey shale with thin (<10 ft.) silty beds	Kingak Shale		
2780	2240	Total Depth Drilled			

Figure 3. Stratigraphic table of the Walakpa area.

1990). Prior to the drilling by the Borough, only the Walakpa discovery and confirmation wells were used for seismic correlation. From these two wells, a rough velocity gradient was calculated throughout the field, and an initial conversion from time to depth to the top of the Walakpa sandstone was calculated. This approximation of the reservoir structure was continually updated as more wells were drilled in the field.

Because the Walakpa sandstone is relatively thin (less than thirty feet thick throughout much of the field), its lateral continuity could not be determined from seismic data alone. This was instead accomplished by well log correlation of the Walakpa field wells, along with other wells drilled in the region. Reservoir parameters, including gross pay, net pay, porosity, water saturation and permeability were determined from well log studies and production tests.

The geothermal regime of the Walakpa field was determined by wireline temperature surveys of the Walakpa wells. Each temperature survey yielded a profile, from which the geothermal gradient, depth to base of permafrost, and reservoir temperature could be determined. For each well, shut-in reservoir pressure and gas chemistry data were obtained during the production tests of the wells. Based on temperature, pressure, and gas chemistry data obtained in the Walakpa field, a methane hydrate formation temperature was calculated. Portions of the reservoir interpreted to be at or below the methane hydrate formation temperature may contain in situ methane hydrates.

The drilling, completion and production methods were designed to minimize any harmful effects of methane hydrates on the future producibility of the field. First, the initial drilling development was an updip stepout from the structurally lowest (hence, warmest) well. Second, drilling and completion methods were designed to minimize formation damage to the reservoir. Finally, the Walakpa wellbore configuration was designed to minimize the potential for hydrate formation in the production string.

In general, the aim of the North Slope Borough's Walakpa development Program was to find and develop the free-methane portion of the Walakpa reservoir. The North Slope Hydrate study used the information obtained from the development program to determine what portion, if any, of the Walakpa reservoir contained methane hydrates, and how they could be developed.

RESULTS

Structure

Seismic exploration of the Walakpa field was conducted by the NSB in the winter of 1988-1989. The NSB seismic program consisted of about 125 miles of data on a 1-mile grid, and covered the entire Walakpa field. The data was evaluated and reviewed favorably as a future development area by ASCG, Incorporated in June, 1990 (Paris and others, 1990).

Prior to drilling, regional trends in the Walakpa reservoir were estimated from the evaluation of the NSB seismic data, regional well correlation and the local well control provided by Walakpa Nos. 1 and 2 (Paris and others, 1990). Follow-up mapping was completed after the first and second drilling seasons as new well control was established.

Seismic data, corroborated by development drilling, indicates that the Walakpa gas field is situated on the south side of an elongate, west-plunging domal structure (figs. 4 and 5). At the crest of the dome the depth to the top of the Walakpa sandstone is about 1700 feet subsea. On the southern limb, all strata are relatively uniformly south-dipping. At the southern edge of the Walakpa field, depth to the top of the Walakpa sandstone is approximately 2550 feet subsea. The south-dipping trend continues south beyond the Walakpa area; the ARCO Brontosaurus well, drilled 14 miles southwest of the Walakpa area, encountered the Walakpa sandstone at a depth of 4300 feet subsea.

The south limb of the domal structure is dissected by two normal faults, east and southeast trending. The down-to-the-north faults are of relatively minor offset, with approximately 30 feet, maximum stratigraphic displacement, interpreted from seismic data. Displacement on the faults tapers to zero at their east and west ends, according to seismic data. The Walakpa discovery well, Walakpa No. 1, was drilled in the wedge-shaped region between the two normal faults. All other Walakpa wells were drilled south of the two faults.

West of the Walakpa field, seismic contours wrap around to the northwest, indicating a change from south-dipping to southwest- and west-dipping strata. Structure contours are interpreted to continue offshore, and back onshore to the north, becoming north-dipping. This structural trend is indicated by the 400, 450, and 500 millisecond contours of figure 4, and the 1700 through 2000 foot subsea contours of figure 5.

Walakpa Sandstone

The Walakpa sandstone is the basal member of the informally named Lower Cretaceous "pebble shale unit". The pebble shale unit is an organic-rich, black shale unit which is 350 to 400 feet thick in the Walakpa area.

Net pay thickness, porosity, and permeability data for the Walakpa field wells are summarized in Tables 1a and 1b. The Walakpa sandstone averages about 30 feet in gross thickness in the Walakpa field, and thins to the northeast and thickens to the southwest (fig. 6). This trend continues to the southwest, where the ARCO Brontosaurus well encountered

EXPLANATION

Scale:
0 0.5 1.0 2.0 Statute Miles

Two way travel time, milliseconds
Contour Interval: 50 Milliseconds

— 450 — SEISMIC CONTOUR,
— — — FAULT
○ GAS WELL
⊘ ABANDONED GAS WELL

Figure 4. Seismic structural map of the Walakpa gas field.

EXPLANATION

Scale:
0 0.5 1.0 2.0 Statute Miles

Vertical Datum: Sea Level
Contour Interval: 100 Feet

— 2500 — CONTOUR
 ——— FAULT, HATCHURED ON DOWNTOWN SIDE
 ○ GAS WELL
 ∅ ABANDONED GAS WELL

Figure 5. Walakpa gas field structure.

Table 1a. Summary of Reservoir Data: Walakpa Nos. 1-5, Walakpa Gas Field, Alaska

Well No.	1	2	3	4	5
Subsea Depth (ft), Walakpa sandstone	2020	2555	2325	2120	2121
Thickness (ft), Walakpa sandstone	20	37	28	26	25
Net Pay (ft)	16	29	24	23	22
Avg. Porosity (%)	21	21	21	21	21
Avg. Permeability (md)	62	116	187	175	171

Table 1b. Summary of Reservoir Data: Walakpa Nos. 6-10, Walakpa Gas Field, Alaska

Well No.	6	7	8	9	10
Subsea Depth (ft), Walakpa sandstone	2401	2210	2350	2346	2180
Thickness (ft), Walakpa sandstone	30	30	33	32	28
Net Pay (ft)	25	23	26	28	24
Avg. Porosity (%)	20	24	23	22	23
Avg. Permeability (md)	109	*	*	*	*

* - Not Available

EXPLANATION

Scale:
0 0.5 1.0 2.0 Statute Miles

Contour Interval: 5 Feet

— 25 — CONTOUR, FT

○ GAS WELL
⊗ ABANDONED GAS WELL

Figure 6. Gross pay map of the Walakpa Sandstone.

EXPLANATION

Scale:
0 0.5 10 20 Statute Miles

— 25 — CONTOUR, FT

Contour Interval: 5 Feet

○ GAS WELL
⊗ ABANDONED GAS WELL

Figure 7. Net pay map of the Walakpa Sandstone.

the wet Walakpa sandstone with a thickness of about 50 feet. In core samples and well logs, the formation can usually be divided into three main units: an upper laminated fine-grained sandstone and siltstone, a middle massive, fine-grained sandstone, and a lower coarse, tight conglomerate. The Walakpa sandstone locally contains isolated zones of increased cementation, probably of siderite and calcite.

Net pay thickness of the Walakpa sandstone averages about 25 feet in the Walakpa field (fig. 7). Net pay to gross pay ratios average 0.8 for the Walakpa field wells. Changes in this ratio for each well are depend on the thickness of the basal tight conglomerate and the thickness and abundance of the zones of increased cementation.

The Walakpa sandstone is a light brown, fine- to very fine-grained, moderately sorted calcareous to sideritic sandstone. Grains of the sandstone are predominantly clear quartz. Accessory grains include: shell fragments, pyrite pseudomorphs after Inoceramus, chert, glauconite, and minor tuff and bentonite.

Average porosity of the net pay intervals of the Walakpa sandstone averages 22% for the Walakpa field (fig. 8), as calculated from well logs. In general, porosity increases from southeast to northwest. The local tight zones within the Walakpa sandstone are characterized in core tests by low porosity, and in well log response by sharp decreases in density porosity values.

Permeability trends are interpreted to broadly parallel the porosity trends. Reservoir permeability, calculated from core tests of Walakpa Nos. 1 and 2, and from production tests of Nos. 3, 4, 5, and 6, are shown in figure 9. None of the wells drilled in the second drilling season (Nos. 7, 8, 9, and 10) have yet been tested for permeability. As is shown, there is a significant permeability change between the No. 1 well and the rest of the field. The average permeability of the reservoir interval in the No. 1 well, calculated from core tests, is 62 millidarcies, while the rest of the field probably averages about 150 millidarcies.

Walakpa Field Gas Chemistry

Gas samples from the Walakpa Nos. 3 - 6 wells were collected in evacuated cylinders during production tests and sent to Exxon Company USA laboratories for chemical analysis. Gas chemistry data for the Nos. 1 and 2 wells were obtained from the U.S. Geological Survey geological reports for each well (Hewitt, 1982; Patterson and others, 1982). The geochemical data is shown in Table 2. Reservoir pressures for the field average 1027 psia; maximum deviation from this average is 10 psia. Based on the gas chemistry and reservoir pressure data, the maximum methane hydrate formation temperature for the Walakpa field gas is 56.3° F (Dr. V. Kamath, University of Alaska, pers. comm. 1990). Where naturally occurring reservoir temperatures are cooler than this temperature, in situ methane hydrates are potentially present in the Walakpa reservoir.

EXPLANATION

Scale:
0 0.5 1.0 2.0 Statute Miles

Contour Interval: 1 Percent

— 25 — CONTOUR, % LOG POROSITY

○ GAS WELL
⊗ ABANDONED GAS WELL

Figure 8. Bulk porosity map of the Walakpa Sandstone.

EXPLANATION

Scale:
0 0.5 10 2.0 Statute Miles

Contour Interval: 50 md

- 200 — PERMEABILITY CONTOUR, md
- / — FAULT, PERMEABILITY BARRIER
- GAS WELL
- ⊗ ABANDONED GAS WELL

Figure 9. Estimated reservoir permeability of the Walakpa field.

Table 2. Walakpa Field Gas Chemistry, Molecular Composition (Mole %)

Walakpa Well No.	1	2	3	4	5	6
Methane	98.72	97.08	97.173	97.778	98.101	96.438
Ethane	0.01	2.13	1.946	1.911	-ND-	2.689
Propane	-TR-	0.48	0.291	0.288	-ND-	0.119
i-Butane	-TR-	0.08	0.004	0.004	-ND-	-ND-
n-Butane	-TR-	0.09	0.006	0.006	-ND-	-ND-
i-Pentane	-TR-	-TR-	0.002	0.001	-ND-	-ND-
n-Pentane	-TR-	-TR-	-ND-	-ND-	-ND-	-ND-
Nitrogen	1.27	0.14	5.991*	5.532*	6.573*	1.250
Carbon Dioxide	-NT-	-TR-	0.001	0.006	-ND-	-ND-

TR - Trace

NT - Not Tested

ND - Not Detected

*Nitrogen results are recognized to be too high because of instrumental problems.

Permafrost and Reservoir Temperature

Wireline temperature surveys were conducted in seven of the ten Walakpa field wells, using a digital temperature/pressure bomb supplied by C.A. White Wireline Services, of Casper, Wyoming. Initial temperature and pressure surveys were run in the Walakpa field wells 20 to 60 days after drilling, casing and cementing operations were completed. On some wells (Walakpa Nos. 3 and 5) additional temperature surveys were run the following year, for corroboration of the initial surveys. Temperature readings were taken at 500 foot stations, and just above the well perforations.

From the surveys the general temperature profile of each well was calculated (Table 3). The temperature profile was then used to calculate a reservoir temperature and depth to base of permafrost (depth to the 32 degree Fahrenheit isotherm). The geothermal gradients measured in this study compare well with similar measurements taken in the region (Lachenbruch and others, 1987; Lantz, 1981). The stratigraphic section of the Walakpa field is predominantly shale; hence, the geothermal gradient was assumed to be the same above and below the base of permafrost.

Based on the Walakpa temperature surveys, a map was made showing the estimated maximum permafrost depth for the Walakpa field (fig. 10). Depth to base of permafrost in the Walakpa field averages about 940 feet below sea level. In general the permafrost seems to thicken to the northeast. The Walakpa No. 5 well encountered the deepest permafrost measured in the Walakpa field, at 975 feet below sea level. Just northeast of the area shown in figure 10, Brewer (unpublished) conducted a shallow temperature survey (600 ft) of the South Barrow No. 3 well, and calculated a depth to base of permafrost of over 1300 feet below sea level for that well.

The west end of the Walakpa field contains the thinnest measured permafrost in the field. Depth to the base of permafrost is 820 feet and 839 feet below sea level in the Walakpa Nos. 7 and 8 wells, respectively. A possible explanation for the thinner permafrost at these two wells is that they were drilled in an area that was once covered by a lake. Based on aerial photo interpretation, the Nos. 7 and 8 wells are interpreted to be located in or near a drained lakebed. If the lake did not freeze to the bottom during the winter months, the mean annual surface temperature would be above freezing in these areas, causing a thinning of the permafrost. As is shown in figure 10 the areas of the large lakes of the Walakpa area (hatched areas) which do not freeze to the bottom may contain thinner permafrost, or no permafrost at all (Andersland and Anderson, 1978; Brewer, 1958).

Reservoir temperatures of the Walakpa sandstone average about 65° F for the Walakpa field (fig. 11). Measured temperatures range from a minimum of 57° F at Walakpa No. 5 to a maximum of 72° F at Walakpa No. 2. In the Walakpa No. 1 well, the formation temperature of the Walakpa sandstone is estimated to be 50-55° F, more than 10 degrees lower than the 65° F measured during the drill stem test of that well (Hewitt, 1982). It was reported (Hewitt, 1982) that the upper 1400 feet of the No. 1 well was left filled with a diesel-based fluid (Arctic pack) to facilitate future temperature studies. Attempts to reenter the No. 1 well with a wireline unit in this study were unsuccessful; the Arctic pack had

Table 3a. Geothermal Data for the Walakpa Gas Field, Alaska

Well No.	2	3	4	5	6
Depth to Base of Permafrost (ft, subsea)	896	898	928	1004	914
Reservoir Temperature (° F)	72.0	64.5	60.4	57.4	66.1
Geothermal Gradient (° F/100 ft)	2.32	2.25	2.36	2.25	2.27

Table 3b. Geothermal Data for the Walakpa Gas Field, Alaska

Well No.	7	8	9	10
Depth to Base of Permafrost (ft, subsea)	820	839	875*	890*
Reservoir Temperature (° F)	65.3	67.7	67*	62*
Geothermal Gradient (° F/100 ft)	2.25	2.03	-	-
* - estimated

EXPLANATION

Scale:
0 0.5 10 20 Statute Miles

Shaded Region - Large lakes with continuous unfrozen lake bottom, little or no permafrost (after Mellor, 1985)

Hatchure Lines - Drained lakebeds, potential thin permafrost (detail limited to Walakpa Development Area)

Contours dashed where extrapolated.

1200 CONTOUR, FT
○ GAS WELL
⊘ ABANDONED GAS WELL
839 MEASURED PERMAFROST THICKNESS

Contour Interval: 50 Feet
Vertical Datum: Sea Level

Figure 10. Estimated maximum permafrost thickness, Walakpa gas field.

EXPLANATION

Scale:
0 0.5 1.0 2.0 Statute Miles

Contour Interval: 5° Fahrenheit

— 20 — CONTOUR, °F

○ GAS WELL
⊗ ABANDONED GAS WELL

Figure 11. Estimated reservoir temperature of the Walakpa field.

evidently frozen off near the surface.

Methane Hydrate Stability Field

Based on the reservoir pressure, gas chemistry and temperature data gathered in this study, the methane hydrate stability field for the Walakpa sandstone was calculated (fig. 12). This area represents all portions of the Walakpa sandstone greater than 10 feet in net pay thickness with an estimated reservoir temperature of 56.3° F or lower. As shown in figure 12, all of the wells drilled in the NSB Walakpa development program were drilled in the free methane portion of the reservoir. Only the Walakpa No. 1 well, drilled by the U.S. Geological Survey, was drilled in a potential area of methane hydrate stability in the Walakpa sandstone. Early reservoir analysis of the No. 1 drill stem tests indicated that in situ hydrates, and hydrate formation in the production string may have caused the low flow rates and subsequent freezing off of the well during the tests (Hewitt, 1982; Patterson and others, 1982).

Design Considerations

The development of the Walakpa field required special design considerations and strategy. Environmental impact was minimized by drilling in the winter off of ice pads. A closed mud system eliminated the use of reserve pits. The relatively thick permafrost interval presented potential freezing problems which had to be considered in the well design.

The drilling, completion and production operations were engineered in a manner to minimize pressure and temperature reductions across the wellbore of the producing formation, the Walakpa sandstone. This was necessary to prevent the formation of methane hydrates across the perforations, which impede the productivity of the well.

Drilling Strategy

The drilling strategy of the NSB in the Walakpa field was a progressive lateral and updip stepout from the Walakpa No. 2 well. Drilling was conducted on 640-acre spacing. The goal of the first year's drilling season was to prove up the lateral continuity of the favorable reservoir conditions encountered at the Walakpa No. 2 well. At this well, the Walakpa sandstone was thicker, warmer, and more permeable than at the Walakpa No. 1 well. Once lateral continuity of the reservoir was established, wells were located high enough on structure to maximize gas recovery, yet not high enough to encounter formation temperatures at or below the methane hydrate formation temperature (56.3° F).

The wellbore schematic of a typical Walakpa well is shown in figure 13. A fresh-water mud was used to drill the 12-1/4" hole to around 1200 feet. This allowed the setting and cementing of 9-5/8" casing to about 200 feet below the base of permafrost. A closed mud system had to be used since a reserve pit was not permitted. Solids control equipment consisted of a shale shaker, mud cleaner and centrifuge. Mud cuttings were captured and buried below the active layer in an excavated pit.

Figure 12. Estimated methane hydrate stability field, Walakpa gas field.

A non-dispersed KCl/polymer mud was used to drill an 8-1/2" hole from 1200 feet total depth. Mud weight, viscosity and water loss properties were continually monitored and adjusted as needed. Chlorides were maintained between 8,000 and 10,000 ppm to minimize the swelling of clays. It was found that a higher chloride concentration hampered the dewatering process. The mud weight, 9.0 - 9.5 pounds per gallon, was maintained just high enough to contain formation pressures. Prior to drilling through the Walakpa sandstone, the hole was conditioned and the mud properties verified.

The 8-1/2" hole was drilled to at least 100 feet below the pay zone, and 7" casing was set. An F.O. tool was placed in the casing string at about 1150 feet to facilitate pumping an Arctic Pack between the 7" and 9-5/8" casing. The 7" casing was cemented conventionally to about 600 feet above the top of the pay zone to effectively isolate the formation. Cementing of the casing was designed so that the combined hydrostatic and pumping pressure caused while pumping the cement would not cause invasion or fracture the formation.

Completion Strategy

The drilling mud was displaced from the 7" casing with diesel. An effective underbalance for perforating was achieved by using diesel since the hydrostatic pressure of the diesel column was approximately 200 psi less than formation pressure. Perforating underbalanced is an effective way to open up the reservoir and minimize formation damage. A 2-3/8" tubing string was run from surface to the pay zone. Tubing-conveyed perforating guns were run on the tubing and spaced out over the pay zone. A 1/4" stainless steel tubing was strapped to the 2-3/8" tubing to provide methanol injection capability in case of methane hydrate formation in the 7" by 2-3/8" production annulus. The wells were perforated after installation of the Christmas tree by dropping a bar down the tubing, discharging the perforating guns.

Perforation spacing was usually 12 shots per foot, to minimize flow restriction into the wellbore. Initially, the wells were produced up the tubing to clean up the wellbore. During production, the wells will flow gas through the casing-tubing annulus.

Production Strategy

Production in the nearby Barrow gas fields has shown that the well must be shut in when hydrates form across the perforations, causing interruption in gas flow. Therefore, to insure reliable gas flow during peak demand, all producible wells will be contributing to the flow to spread the load and minimize the pressure drop across the formation of each well. Methanol injection in the wellbore and at various points in the gathering system will be used to combat hydrate formation in the production string. Catalytic heaters have been installed on regulators, control valves, wellhouses, and manifolds to combat freezing problems during extreme winter temperatures.

WALAKPA WELLBORE SCHEMATIC

Typical Well (Walakpa No. 3)

Figure 13. Schematic wellbore diagram, Walakpa gas field.

Production Feasibility

In the drilling development of the Walakpa field, steps were taken by the contracted petroleum engineers (Allen and Crouch, Petroleum Engineers, of Casper Wyoming) to minimize formation damage to the reservoir. Any damage would cause an increase in the pressure drop across the perforations, which results in increased Joule-Thomson cooling. In reservoirs with already cool temperatures, this cooling could cause methane hydrate accumulation at the perforation surface and result in freezing of the well. The wells were drilled with near-balance mud weights to minimize mud filtrate invasion. Cement columns were high enough to safely isolate the producing zone, but not too high to cause formation breakdown. Perforations were high-density (12 shots per foot) to maximize communication with the reservoir.

Wells were designed to produce through the tubing/casing annulus. Production of the wells through the greater cross-sectional area of the annulus results in overall lower gas velocities toward the wellhead. This lower velocity allows production fluids, if any, to fall to the bottom of the well. The wells are then periodically blown through the tubing. This production technique has proven to be effective in combatting the accumulation of water in the wellbore.

The updip wells drilled by the NSB in the Walakpa field may be situated to produce methane from hydrates in the structurally higher portions of the reservoir, should any exist. These wells would do so by producing the free methane, creating a pressure sink. This pressure reduction would be compensated for by the dissociation of hydrates updip in the formation in order to maintain equilibrium. Production of hydrates by depletion of the underlying free methane is the technique shown to be the most efficient by the Russians in the Messoyakha field, located in western Siberia (Makogon, in Sloan, 1990).

FUTURE WORK

Work remaining to be done in the Walakpa gas field includes the remainder of reservoir testing for the wells drilled in the second drilling season. Final analysis of all the reservoir temperature, pressure, and chemistry data, along with seismic and geologic information, should be completed by December, 1993. Following the tie-in of the field to the local gas distribution system, long-term production tests can be designed and implemented. Long term tests would include determining how much of a component, if any, of the production is from an in situ methane hydrate source.

REFERENCES

- Andersland, O.B., and Anderson, D.M., 1978, *Geotechnical Engineering for Cold Regions*, McGraw-Hill Co., St. Louis, Missouri.
- Brewer, M.C., (circa 1951), Comparison of thermal profiles at Barrow Core Test No. 1, South Barrow No. 1, and South Barrow No. 3, unpublished figure.
- Brewer, M.C., 1958, Some results of geothermal investigations of permafrost in northern Alaska, *Transactions, American Geophysical Union*, V. 39, No. 1, pp. 19-26.
- Collett, T.S., and Bird, K.J., 1988, Freezing-point depression at the base of ice-bearing permafrost on the North Slope of Alaska. In: *Permafrost: Fifth International Conference Proceedings*, ed. K. Senneset, 50 - 55, Vol. 1, Trondheim, Norway, Tapir Publishers.
- Hewitt, S.L., ed., 1982, *History of Drilling Operations, Walakpa Test Well No. 1, Husky Oil NPR Operations*, Anchorage, Alaska.
- Kirschner, C.E., Grantz, A., and Mullen, M.W., 1992, Impact origin of the Avak structure, Arctic Alaska, and genesis of the Barrow gas fields, *AAPG Bulletin*, V. 76, No. 5, pp. 651-679.
- Lachenbruch, A.H., Sass, J.H., Lawyer, L.A., Brewer, M.C., Marshall, B.V., Munroe, R.J., Kennelly, J.P. Jr., Galanis, S.P. Jr., Moses, T.H. Jr., 1987, Temperature and depth of permafrost on the Alaskan North Slope. In: *Alaskan North Slope Geology*, eds. I.L. Tailleux and P. Weimer, 95 - 107. Vol. 1, Bakersfield, California, SEPM, Pacific Section, and the Alaskan Geological Society.
- Lantz, R.J., 1981, Barrow gas fields-North Slope, Alaska, *Oil and Gas Journal*, V. 79, No. 13, pp. 197-200.
- Mellor, J.C., 1985, Radar-interpreted arctic lake depths, BLM-AK-PT-85-020-7200-029 (Map report).
- Paris, C., Borah, J., and Glenn, R., 1990, Geoscience evaluation of the Walakpa gas development program, report for the North Slope Borough Barrow Gas Field Development Project, Barrow, Alaska, 74p.
- Patterson, S.O., Sullivan, D.A., Trunz, J.P. Jr., Aertker, S.R., Allard, B.R., Mangus, M.D., and Palenske, A., 1982, Technical Services Contract 1981 Exploration Program, Vol. 2, Drilling, Geological, and Geophysical Reports, Tetra Tech Inc., Contract No. 14-08-0001-20203, Tetra Tech Report No. 8202, Houston, Texas.
- Sloan, E.D. Jr., 1990, *Clathrate Hydrates of Natural Gases*, New York, Marcel Dekker, Inc., 641 pp.

END

**DATE
FILMED**

6 / 1 / 93