PNL--8470

DE93 007180

**SOLID WASTE INITIATIVE
MACRO MATERIAL FLOW MODELING
CONCEPTUAL DESCRIPTION AND REQUIREMENTS**

**G. M. Holter
D. C. Stapp**

January 1993

**Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Richland, Washington 99352**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

SUMMARY

This report describes a Macro Material Flow Modeling (MMFM) concept and approach that are being adopted to develop a predictive modeling capability that can be used as the basis for evaluating potential impacts from various solid waste management system configurations and operating scenarios, as well as the impacts of various policies on solid waste quantities and compositions. This capability, as part of a broader Solid Waste Initiative at Pacific Northwest Laboratory, is intended to provide an increased understanding of solid waste as a disposal, energy, and resource problem on a national and global scale, particularly over the long term. The results of this increased understanding will eventually have an impact on a variety of U.S. federal government activities, as well as on the activities of other entities. This increased understanding will also help provide the basis for subsequent activities under the Solid Waste Initiative.

The report describes current solid waste management practices and their context, defines questions of interest relating to these practices, and proposes an approach that could be employed to analyze these practices and possible alternatives to them. A preliminary review, analysis, and summary of available data to support this approach are also provided.

To include all of the relevant drivers that affect solid waste production, management, and disposition options, the proposed approach extends beyond the solid waste management system to also encompass the whole materials production and use cycle. This allows consideration of policies and approaches that directly impact material and waste flows (e.g., material use and/or transportation bans and bottle bills) as well as those that indirectly impact material and waste flows (e.g., via economic and indirect regulatory drivers). Thus, the MMFM capability should prove useful to a broad range of people with interests in solid waste, including state solid waste planners, policy makers, regulators, engineers, and economists.

The report is intended to provide the basis for the development of a specific modeling architecture, including input/output specifications, data flows, and code structures, to achieve the MMFM concept. A simple demonstration prototype of the model is also planned, simulating major portions of the model functionality, to provide a basis for presenting and refining the model concept, confirming the operability of the model and the usefulness of the results, and facilitating liaison activities with prospective clients.

Subsequent reports in this series will report on the development and application of the MMFM concept.

ACKNOWLEDGMENTS

This report and the modeling concept described in it could not have been developed without the contributions of a number of individuals. The authors are grateful for these numerous contributions and wish to specifically acknowledge the following.

Jack McElroy and Gary McNair of the PNL Waste Technology Center have consistently provided strong management support for the Solid Waste Initiative. Without their support, the Initiative would probably not have been undertaken.

The Global Studies program at PNL provided important guidance and direction in the initial development of the Solid Waste Initiative. Within this group, the authors specifically wish to recognize the guidance and encouragement received from Gerry Stokes, John Clarke, and Brad Ashton.

An internal PNL workshop was held during the development of this modeling concept to gather broader input from throughout the Laboratory. Participants in this workshop were Mike White, Jim Thomas, Mark Whiting, Joe Roop, Jim Buelt, Nancy Hassig, and John Tixier. Besides participating in this workshop, Mike White served as a sounding board and critical reviewer for the authors throughout the development of the ideas presented in this report.

The literature search and review support provided by Melissa Peffers and Michele DeWeese and the editorial support provided by Dave Payson are gratefully acknowledged.

CONTENTS

SUMMARY	iii
ACKNOWLEDGMENTS	v
1.0 INTRODUCTION	1
2.0 PERSPECTIVES ON SOLID WASTES AND SOLID WASTE MANAGEMENT	5
2.1 THE "SOLID WASTE PROBLEM"	5
2.2 NEEDS RELATING TO SOLID WASTE	7
2.3 QUESTIONS OF INTEREST	8
2.3.1 Waste Quantities and Timing	9
2.3.2 Waste Compositions	9
2.3.3 System Costs and Economics	10
2.3.4 Long-Term Environmental Impacts	10
2.3.5 Opportunities for System Improvements	11
2.3.6 Indirect Impacts of Policy Alternatives on Solid Waste	11
2.4 NEED FOR MACRO MATERIAL FLOW MODELING	12
3.0 DESCRIPTION OF THE MATERIALS PRODUCTION AND USE AND SOLID WASTE SYSTEMS	15
3.1 SYSTEM DESCRIPTION	15
3.2 MODELING THE SYSTEM	19
4.0 DEVELOPMENT AND IMPLEMENTATION OF THE MACRO MATERIAL FLOW MODEL	21
4.1 MODEL UTILITY	21
4.2 GENERAL STRATEGY FOR DEVELOPMENT AND IMPLEMENTATION	22
4.2.1 Modeling Scope	22
4.2.2 Model Structure	23

4.3	STEPS IN MODEL DEVELOPMENT AND IMPLEMENTATION	24
4.3.1	Describe Problem	26
4.3.2	Isolate System	26
4.3.3	Adopt Supporting Theory	27
4.3.4	Formulate Model	27
4.3.5	Analyze Data Requirements/Collect Data	29
4.3.6	Develop Computer Program	30
4.3.7	Debug Computer Program	31
4.3.8	Verification	31
4.3.9	Develop Alternative Solutions	31
4.3.10	Evaluate Model Output/Results	32
4.3.11	Present Results/Plans	33
4.3.12	Develop Model Maintenance Procedures	33
4.3.13	Model Validation	33
4.3.14	Transfer System to Users	33
4.4	SCHEDULE FOR DEVELOPMENT OF THE MACRO MATERIAL FLOW MODEL . . .	34
APPENDIX A	- GLOSSARY	A.1
APPENDIX B	- BIBLIOGRAPHY	B.1
APPENDIX C	- PRELIMINARY REVIEW OF AVAILABLE SOLID WASTE CHARACTERIZATION DATA	C.1

FIGURES

1	Landfill Emissions and Their Environmental Impacts	6
2	Conceptual Schematic of MMFM Interaction with Other Models	13
3	Traditional View of Materials Production and Use System and Associated Solid Waste Management System	15
4	Materials Production and Use System and Associated Solid Waste Management System Incorporating Recovery and Recycling	16
5	Simplified Representation of the Materials and Solid Waste Systems Incorporating Recovery and Recycling	18
6	Matrix of Solid Waste Origins	18
7	Material Flow Results	19
8	Simplified Model of Processes in Macro Material Flow Modeling Approach	20
9	Scope Limitations on Current Modeling Efforts	22
10	Basic Steps in the Modeling Process	25
11	Basic Code Development Process for the MMFM	30
12	Major FY-93 Milestones for the Solid Waste Initiative	34

"I see the solution to each problem as being detectable in the pattern and web of the whole. The connections between causes and effects are often much more subtle and complex than we with our rough and ready understanding of the physical world might naturally suppose ..."

Dirk Gently in
Dirk Gently's Holistic Detective Agency
by Douglas Adams

1.0 INTRODUCTION

In Fiscal Year 1992 (FY-92), a Solid Waste Initiative was undertaken within the Pacific Northwest Laboratory (PNL). This action was partly in response to a perceived increase in the frequency and severity of impacts associated with solid waste issues at all levels. It also recognized the limited effectiveness of previous approaches to the solid waste issue in addressing the broader impacts resulting from solid waste.

In establishing and developing the Solid Waste Initiative, PNL recognized that the diversity and complexity of solid waste issues and responses to these issues have resulted in the lack of a coherent, integrated approach to the solution of present waste problems and/or prevention of future ones. No clear leadership focus exists in the area of solid waste. Approaches to solid waste management have generally been responsive (or reactive) to particular problems in particular locations, and compartmentalized to match the specific responsibilities of the particular groups involved, without consideration of the broader implications of these approaches.

Therefore, initial efforts under the Solid Waste Initiative were directed at providing the basis for a multidisciplinary science and technology approach that can be used by the U.S. federal government, in concert with industry, academia, state and local governments, and the public, to establish the leadership needed to solve the broad range of problems associated with solid wastes. The Initiative was designed to utilize PNL's broad capabilities in systems development, evaluation and analysis coupled with technical insights into materials and engineering to develop a methodology and tools to formulate impactful solutions for solid waste management. This would be further reinforced by PNL's understanding of the human dimension and how it impacts on the application of technology to resolve human problems.

Current efforts under the Solid Waste Initiative are being carried out specifically to provide an increased understanding of solid waste as a disposal, energy, and resource problem on a national and global scale, particularly over the long term. The results of this increased understanding will eventually have an impact on a variety of U.S. federal government activities, as well as on the activities of other entities. This increased understanding will also help provide the basis for other, subsequent activities under the Solid Waste Initiative.

The development and/or adaptation of a predictive modeling capability that can be used as the basis for evaluating potential impacts from various system configurations and operating scenarios was identified as a key element in providing the needed understanding of the solid waste system. Conversely, this capability can also be useful for evaluating the impacts of various policies on solid waste quantities and compositions.

This report is the first step in the development of this predictive modeling capability. The report describes current solid waste management practices and their context, and defines questions of interest relating to

these practices. It then proposes an approach that could be employed to analyze these practices and possible alternatives to them. A preliminary review, analysis, and summary of available data to support this approach are also provided.

Solid waste issues relate to the entire materials cycle, from the mining of raw materials through the production of goods and services to the ultimate disposition in a landfill or incinerator. Therefore, to include all of the relevant processes and drivers that affect solid waste production, management, and disposition options, the proposed approach extends beyond the solid waste management system to encompass the whole materials production and use cycle. This allows consideration of the full range of policies and approaches with potential impacts on solid waste, from those that directly impact material and waste flows (e.g., material use and/or transportation bans and bottle bills) to those that indirectly impact material and waste flows (e.g., via economic and indirect regulatory drivers). Thus, the Macro Material Flow Modeling (MMFM) capability should prove useful to a broad range of people with interests in various aspects of solid waste, including state solid waste planners, policy makers, regulators, engineers, and economists.

This report is intended to provide the basis for the development in FY-93 of a specific modeling architecture, including input/output specifications, data flows, and code structures, to achieve the concept. In addition, a simple demonstration prototype model (simulating major portions of the model functionality) will be developed to provide a basis for presenting and refining the model concept, confirming the operability of the model and the usefulness of the results, and facilitating liaison activities with prospective clients.

The Solid Waste Initiative activities discussed in this report are being carried out in collaboration with PNL's Global Studies Program, which has already developed and applied similar modeling techniques to predict various global impacts of human activities. This coordination allows a "leveraged" development of the methodology and tools to assess this type of problem area. It also recognizes the linkages between solid waste issues and other global environmental areas, and the potential this provides for the sharing of input and output information among the various models. These linkages are discussed further in later sections of this report.

To reduce the problem being addressed to a more approachable level, current Solid Waste Initiative efforts have been primarily focused on Municipal Solid Waste (MSW) for which data are readily available; however, the ultimate goal is to expand these efforts to include the full breadth of solid wastes. In addition, the initial data collection and modeling focus is on solid waste practices within the U.S. and Canada; nevertheless, the methodology will be developed in such a way as to allow expansion to other regions of the world as needed.

Section 2 of this report provides perspectives on solid wastes and solid waste management that are needed to provide a basis for the development of an appropriate modeling concept. The solid waste and associated materials production and use cycles are described and discussed in Section 3.

Implementation of the MMFM concept is discussed in Section 4. A glossary and bibliography (including cited references as well as other pertinent publications) are provided as appendixes to the main report. Also included as an appendix is a preliminary review of available solid waste characterization data.

Future reports in this series will be issued at appropriate intervals to report on the development and application of the MMFM concept.

2.0 PERSPECTIVES ON SOLID WASTES AND SOLID WASTE MANAGEMENT

This section provides a discussion of the general problems associated with solid wastes, and the specific needs associated with these problems. This serves as an introduction to the identification and discussion of the specific questions that will be addressed in following sections of this report.

2.1 THE "SOLID WASTE PROBLEM"

In recent years, there has been considerable discussion about the "solid waste problem." There appears to be a vague but growing perception on the part of the public and the press that serious solid waste management and disposal problems exist. This perception apparently stems from increasing waste management and disposal costs, concerns about decreasing landfill availability, and a general concern for environmental degradation and resource destruction that may be occurring as a result of current practices. In addition, rising prices for various materials that are contained within the solid waste stream have motivated interest in materials reclamation and reuse, although technological, economic, and sociological barriers still constrain such practices. These concerns are representative of the various visible facets of the solid waste problem.

At the same time, there has been an increasing interest and emphasis placed on sustainable development and the use of sustainable technologies. Thus, there is emerging a recognition that environmentally sound solid waste management must not only consider the disposal or recovery of waste materials, but also must address the root causes of solid waste management problems by evaluating and attempting to remedy unsustainable patterns of material production and consumption. The issues associated with sustainable development received considerable attention at the United Nations Conference on Environment and Development (UNCED) held in Rio de Janeiro in 1992.

Governments and private entities have been implementing a variety of solutions to their specific solid waste problems, starting at the local level and moving up to the county and state levels. Prominent among these activities have been various recycling programs, integrated waste management programs and planning, and construction of waste-to-energy facilities. These entities have cooperated with each other on these solutions when cooperation has been perceived as advantageous to them, but many attempts at such cooperation have been thwarted when the interests of the various groups involved were not perfectly aligned.

Most solid waste management decisions continue to be made and implemented at the local or county level, predominantly with a short-term focus to respond to relatively immediate pressures of landfill shortages, funding problems, and the like. Many of these decisions are being made with relatively little time for consideration, and some could even be classified as panic or crisis situations. In addition, there is often considerable political and/or economic pressure involved. This usually results in a high

degree of urgency for those involved in the decision making process to focus on and resolve the immediately apparent problem, and to do so quickly.

In this rush to address the immediate local problems, little effort is being expended to address potential impacts, either short- or long-term, at the national and international levels resulting from solid waste management practices. This is despite the fact that, more and more, the cumulative impacts from local decisions concerning solid waste management are beginning to manifest themselves in broader, longer-term impacts than are being addressed by the decision makers or, at the very least, presenting a greater and greater potential for such impacts. These impacts occur in the broad areas of environment, energy, and economics (or resources). As an example, Figure 1 is adapted from Tent [1992] and shows an overview of the air-related emissions from landfill activities and operations, together with the resulting environmental impacts. Other pathways (e.g., water migration) and other portions of the solid waste management cycle also result in a range of environmental impacts.

Beyond the traditional regulatory role of the federal government, U.S. federal government policy in the area of solid waste management has largely been one of providing support and guidance to the local decision makers, to encourage them to find solutions to their own problems. But no clear responsibility exists within the federal government hierarchy for evaluating and addressing the long-term impacts from solid waste management practices

FIGURE 1. Landfill Emissions and Their Environmental Impacts

within the U.S. This is because the need for such activities at the federal level is still emerging, and the government has yet to fully respond to this emerging need.

As a result, there is no clear recognition in the U.S. (or probably in the rest of the world) of the long-term impacts of solid waste management practices. Nor is there a clear recognition of how other activities within society are interlinked with solid waste management and, thus, can contribute to or help to mitigate such impacts. Furthermore, there is no established framework or methodology for identifying and assessing these impacts or for evaluating the changes in these impacts that would result from various alternative scenarios. To be truly effective, such a methodology would have to be based on a systems life-cycle approach, to ensure that all of the relevant considerations are taken into account when evaluating solid waste strategies and decisions [Zandi 1991; Hunt, Sellers, and Franklin 1992].

There is considerable historical precedent in the U.S. (and also in other countries) for ignoring potential long-term impacts until they become imminent or acute. This occurred with regard to such currently recognized environmental problems as air pollution and control (e.g., acid precipitation), hazardous waste, and minerals industry wastes. Our basic societal approach to these problems has been reactive, addressing impacts only after they arise and are widely acknowledged.

Even after impacts are recognized, society's ability to react appropriately has been hampered by lack of a true and complete understanding of what needs to be done to adequately respond to the impacts. Therefore, many actions are forced to take the form of an incremental improvement to the current situation, without a clear idea of what might be required to totally solve the particular problem. This, inevitably, leads to a situation in which society is constantly trying to catch up to the problem, rather than getting ahead of the situation and providing comprehensive solutions.

2.2 NEEDS RELATING TO SOLID WASTE

Based on the information in the preceding section, and on a review of current solid waste problems and issues, the U.S. and the world have several fundamental needs relating to understanding and evaluating solid waste and solid waste management on a large scale (i.e., regional, national, or global):

- There is a strong need to reach a better understanding of the solid waste system and how it relates to other activities within our society. This includes the need to be able to separate and clearly delineate the specific issues involved and the relationships between these issues. It also includes understanding the relationship between the solid waste system and other broader systems (such as the materials production and use system and the energy system) that operate within society, because these systems are interlinked and tend to drive many aspects of each other.

- Improved analytical capabilities are needed to assess and predict the results of proposed changes in the system, to allow for a more active approach to circumvent solid waste problems. These capabilities must provide reasonable mechanisms for making comparisons among alternate system configurations and operational strategies, or among the results for various policy decisions, to provide an improved information base for policy development and decision making.

Inherent in such an improvement in analytical capability is the development of an appropriate system of measurement to apply to the system, to ensure that necessary and sufficient information is contained within the capability to support its intended uses. The important measures of solid waste system performance need to be clearly delineated, understood, and used consistently by analysts evaluating solid waste problems.

- Effective methods are needed for communicating findings to the various policy makers, regulators, industry leaders, technologists, and members of the public that can benefit from this improved information base. Without effective communications, the ability to benefit from and act on the information being developed will be severely impaired.

Inherent in establishing better communications is the specific determination of who needs to be included in this communication and what information they feel they need to effectively carry out their role relative to solid waste.

These needs provide much of the basis for the establishment of the specific objectives of this project.

2.3 QUESTIONS OF INTEREST

To develop an effective response to the needs outlined above, it is important to understand the types of questions that may be of interest relating to solid waste and solid waste management. There are at least two types, or levels, of solid waste decisions or concerns [Gottinger 1991]:

- The first is the type of immediate or near-term management decisions or concerns discussed previously. They most frequently involve planning and operation of facilities and equipment within an existing institutional and policy framework. These are the types of issues generally dealt with by local officials, such as siting new landfill space, forestalling the need for new landfill space by instituting material recovery activities, siting and licensing solid waste incinerators and waste-to-energy facilities, and the like. There are currently many efforts under way to address these near-term issues, within the U.S. and abroad.
- The second type of decision or concern is related to what might be termed the long-range policy issues. Included at this level are decisions relating to such things as national resource management

policy, long-term land use decisions, cumulative long-term environmental changes, long-term sustainability of materials use and disposal practices, long-term economic impact, etc.

The focus of this report, and of the modeling approach described in it, is on the latter type of decision or concern: the long-range policy issues.

There are a variety of different types of long-range policy questions that may be of interest pertaining to solid waste management and planning. These questions can be grouped into a relatively concise set of question categories, as discussed below.

2.3.1 Waste Quantities and Timing

What quantities of solid wastes will be produced, and when will production of these wastes occur? This type of information is important to gauge the magnitude of the problem, the relevant trends over time, and the appropriate types and capacities of facilities and infrastructural elements (such as transportation capabilities) that will be needed to cope with the waste material. At the local level, such information is also useful for determining how waste flows should be routed from the sources through the various components of the solid waste management system [Gottinger 1991].

In order to understand waste quantities and timing, it will also be important to understand the functions that result in the production of the wastes. These functions are discussed further in Section 3 of this report.

The waste quantity information must be available in a form that allows a breakdown of the information into appropriate categories to study particular issues. Such categories might include the type of the waste (either by regulatory designation or physical/chemical characteristics), the sector or sub-sector of the economy generating the wastes, and the region or population group from which the waste is anticipated to arise. Further discussion of the breakdown of the wastes into appropriate categories is included in Section 3.

2.3.2 Waste Compositions

What are the physical and chemical components of the solid wastes? Into what regulatory categories can the wastes be classified? How uniform or heterogeneous are the wastes? Such information is needed to determine potential impacts of the wastes, to define appropriate management and disposal options, to evaluate the potential effectiveness of different options, to determine potential regulatory constraints, and to provide a basis for examining alternate system configurations and strategies (see below).

The waste composition information must support a further breakdown into appropriate categories in the same way as the waste quantity information discussed above. Further discussion of this breakdown is included in Section 3.

2.3.3 System Costs and Economics

What are the costs associated with operation of the solid waste management system, and of the related elements of the materials production and use system and the energy system? How are those costs allocated among the various system functions? How can they best be balanced within the system, given the waste quantities and compositions to be handled? Such questions are important in determining the relative economic efficiency and financial viability of the current system and of various alternate system configurations and strategies. Although these costs are often an overriding consideration in near-term decisions, little emphasis is currently given to long-term economic considerations, particularly at the broader level. This is because current solutions are primarily being developed locally, to respond specifically to local needs.

2.3.4 Long-Term Environmental Impacts

What are the impacts associated with the operation of the solid waste system, and how can these impacts be mitigated? What is the ultimate fate of various constituents of interest (such as heavy metals or released gases) either contained in the wastes or resulting from decomposition of the wastes? What are the trends for the future, based on the current system configuration? Such questions address the potential long-term environmental and ecological impacts that may occur as a result of various solid waste practices and, indirectly, the sustainability of the current practices over the long term.

Another variation on this question is: How might current and future solid waste practices contribute to other major environmental problems or concerns? Because of the way the solid waste system interconnects with essentially all societal activities, it is affected by and affects a number of other issues of concern. As an example, solid waste issues are interconnected with global climate issues in several ways:

- 1) Combustible solid wastes may be used as a fuel to replace or supplement conventional fuels (either directly in a waste-to-energy plant or after being processed into an improved form such as refuse-derived fuel [RDF]). This hastens the conversion of the carbon within the material to carbon dioxide, as compared to land-filling, but may replace some fossil fuel use that would also contribute to increasing the global inventory of carbon dioxide; the net impact on carbon dioxide release would depend on the specifics of this tradeoff. Furthermore, the other pollutants released by the burning of solid waste will be somewhat different than those released by burning fossil fuels. At the same time, the use of combustible solid wastes as fuel would reduce landfill requirements somewhat, and would change the form of the waste being landfilled by replacing the material used for fuel with a much smaller volume of ash.

On the other hand, as materials reuse technologies improve and markets grow, much of this combustible solid waste may also be in demand as a source of recoverable, reusable material. Thus, this

material reuse may be in direct economic competition with the use of the material as a fuel source.

2) Decomposition within landfills produces methane and other gases which are most often slowly released to the atmosphere. This methane could, in many cases, be collected for use as a fuel. This landfill methane, which often is released unused, could then replace other fuels, thus reducing the total carbon release to the atmosphere.

3) Improper management of specific wastes can result in the release to the environment of harmful or potentially harmful materials (e.g., chloro-fluorocarbons or CFCs, heavy metals, or PCBs). Thus, solid waste management can contribute to, or help to mitigate, potential global environmental impacts.

2.3.5 Opportunities for System Improvements

While an important part of the needed analytical capability is to assess the current solid waste system, it is also highly desirable to be able to postulate and assess changes from this baseline configuration. Several types of changes that may provide system improvements are important to consider:

a) What potential opportunities exist (or may exist in the future) for material diversion? Such material diversions may be undertaken for a variety of reasons, including waste volume minimization, resource and/or energy recovery, and isolation of specific waste types for special handling or treatment.

b) What potential opportunities exist (or may exist in the future) for improvements in the basic technology elements within the system? How would such improvements affect the basic costs and impacts associated with the system? Which improvements, in which combinations, would provide the greatest benefits? What are the sensitivities of these opportunities to changes in the underlying configuration or operation of the system? Answers to such questions would provide considerable guidance to technology developers seeking to develop and deploy improved technologies for use within the solid waste and associated material flow systems.

c) What aspects of the solid waste system operation represent the greatest impacts on the environment, and how can these functions be better performed to reduce these impacts? Improved methods for performing the needed solid waste management functions could at least partially mitigate the impacts resulting from the system. Understanding those portions of the system that cause the greatest impact will provide a better focus for improvement efforts.

2.3.6 Indirect Impacts of Policy Alternatives on Solid Waste

What will be the impacts on solid waste quantities, compositions, or practices of various policy alternatives being considered? Many policy

decisions or alternatives that are not directly aimed at solid waste or materials production and use will still have impacts in these areas. Examples of these are economic or regulatory policies that have the result of shifting industry or consumer preferences for various types of products or materials. Understanding the relationships and the dependencies between the solid waste system and other societal activities would provide a capability for predicting how solid waste activities would be affected by these indirect influences.

2.4 NEED FOR MACRO MATERIAL FLOW MODELING

To effectively address any of the types of questions discussed above, a minimum need is to be able to calculate and predict material flows throughout the material production and use and associated solid waste system. Therefore, the development of a Macro Material Flow Model (MMFM) was selected as the primary initial objective of the Solid Waste Initiative. To include all of the relevant drivers that affect solid waste production, management, and disposition options, the MMFM must extend beyond just the components of the solid waste management system to encompass the whole materials production and use cycle. Development of the MMFM will provide the basis for a predictive capability to address solid waste problems and issues at the higher, policy level.

Although the MMFM or similar capability is necessary to answer any of the types of questions discussed above, it is not sufficient in and of itself to directly provide answers to many of these questions. Therefore, some additional capability will be required to extend the MMFM to evaluate specific types of impacts. This additional capability might potentially be incorporated in a suite of external processing routines to accompany the model, or might be carried out entirely separately from the model. At this time, no specific decision regarding the implementation of these extended capabilities is required, as long as appropriate flexibility is incorporated in the approach taken.

In addition, it may be desirable to link the MMFM to other models such as the Global Environmental Change Program Second Generation Model (SGM). The MMFM could thus obtain independent variable input data (such as GNPs, population data, etc.) from the SGM, and could provide the SGM with information on the quantities and compositions of solid waste materials available for use in energy production.

Figure 2 is a schematic diagram illustrating the potential use of the MMFM in conjunction with other models and capabilities to predict impacts from solid waste. Note that many of the indirect parameters required by the MMFM could be supplied by the SGM, if an appropriate linkage is created between the two models. The figure represents a general concept; specifics of the eventual implementation have not yet been decided. Issues associated with the implementation of this concept are discussed further in subsequent sections of this report.

FIGURE 2. Conceptual Schematic of MMFM Interaction with Other Models

3.0 DESCRIPTION OF THE MATERIALS PRODUCTION AND USE AND SOLID WASTE SYSTEMS

To provide a sound basis for developing an effective tool to model the solid waste management system and its relationships to the larger materials production and use system, an adequate description of these systems needs to be developed. This section discusses these issues.

3.1 SYSTEM DESCRIPTION

Traditionally, in the U.S. as well as abroad, the materials production and use system and the associated solid waste management system have been viewed as depicted schematically in Figure 3. Raw materials are harvested or extracted to provide feedstocks for production and manufacturing and also for energy production. The use of the products that are produced, as well as the production of energy, results in waste materials which are eventually disposed of into the environment. (Note that this disposal can take the form of simply leaving the material out in the environment to eventually degrade and

FIGURE 3. Traditional View of Materials Production and Use System and Associated Solid Waste Management System

decompose, in the way that many old automobiles were deserted in the past; thus, in many cases, disposal is simply a lack of action rather than a specific conscious action.)

The boxes in Figure 3 represent states of matter, and the arrows represent processes that transform matter from one state into another. All of the processes except energy production are net energy users; thus, energy production is marked with a symbol to identify it as an energy producer.

Figure 3 is simplified somewhat for clarity. As an example, each of the processes in the figure produces relatively small amounts of waste that are a subsidiary to the process. These have not been shown because their flows are more minor than those represented; however, they cannot be neglected in modeling the system without endangering the accuracy of the overall system representation.

A more accurate and current representation of these systems, incorporating recovery and recycling of materials and energy from the waste, is shown in Figure 4. Three major processes have been added to the previous figure.

FIGURE 4. Materials Production and Use System and Associated Solid Waste Management System Incorporating Recovery and Recycling

Two of these involve recovery from the waste materials. Materials recovery recycles material back into production and manufacturing for reuse. Energy recovery, a second net energy producing process, uses waste material to produce useful forms of energy, returning the resulting transformed wastes back into the waste materials state. (Thus, the concept of waste materials is akin to the concept of weeds; waste materials are materials that are not currently useful, just as weeds are plants for which we do not have a use.)

A process is also added for mining of materials from disposal sites to provide additional feed materials for the system. Although this process remains somewhat speculative at this time, there are at least some instances of this practice in the U.S. [Lancaster County Solid Waste Management Authority 1992; Morelli 1992]. Part of the motivation for this practice is the economic benefit derived from reducing landfill space requirements and thus postponing the need for new landfill space. This, in combination with the economic value of the material recovered, either as a fuel for energy production or as a source of raw materials, is sufficient to justify such operations and can be expected to become even more attractive in the future as landfill costs increase.

This latter system view (incorporating recovery and recycling) can be alternately represented as shown in Figure 5.e In this view, energy is thought of as a product like any other and, thus, the processes specifically involved with energy production and recovery have been omitted. This simplified view, however, eliminates the explicit identification and distinction of the processes as either net energy users or producers.

Solid wastes are not produced uniformly throughout society and the economy, neither in quantity nor in content. Thus, it is useful to consider this model of materials production and use and the associated waste generation broken down by sectors (and, as necessary, subsectors) of the economy. Furthermore, wastes within a given sector vary widely. However, within a given sector, solid wastes produced are generally representative of the functions that generated them. This combination of sector and function can be used to define a matrix of solid waste origins, as shown in Figure 6.

The matrix shown in the figure is only representative of the eventual matrix that will be defined. It is expected that, based on information such as that currently being collected on waste generation (see Appendix C), the lists of both the prospective sectors and waste generating functions will be refined. However, this type of matrix remains a valid mechanism to identify activities that can be reasonably expected to be predictable based on various input information.

Another pertinent observation about solid wastes is that they are basically managed in two different ways. There are Collectively Managed Solid Wastes (CMSW); Municipal Solid Waste (MSW) is a good example of these. Information on CMSW is fairly well available as a result of the needs for accurate information to plan for this collective management. However, there are also a number of Independently Managed Solid Wastes (IMSW). These wastes, including a variety of industrial and agricultural wastes, come from much more diverse sources than the CMSW. At the same time, accurate information on IMSW

FIGURE 5. Simplified Representation of the Materials and Solid Waste Systems Incorporating Recovery and Recycling

<u>Functional Waste Types</u>	<u>Sectors</u>									
	Household/Res.	Industrial	Commercial	Energy	Construction	Ag./Forestry	Medical	Government	Transportation	Mining
Packaging										
Conversion Loss/Scrap										
Used/Failed/Defective										
Processing Residuals										
Debris										
Food Waste										
Yard Waste										
General Trash										

FIGURE 6. Matrix of Solid Waste Origins

is generally harder to obtain. (At least, the characterization information for IMSW is not as publicly available as that for CMSW.) Thus, the available data on solid wastes vary considerably depending on the current approach being used to manage them. This will have important implications on the development of the MMFM.

In addressing solid waste management issues, some types of decisions or policy actions are effective on particular sectors of the economy (e.g., co-mingling or separation of solid wastes from different sectors at disposal facilities). Other decisions or actions relate more specifically to the functional waste types involved (e.g., packaging legislation). Thus, in terms of the matrix of solid waste origin, illustrated in Figure 6, some types of decisions or issues will cut vertically through the matrix, while others will cut horizontally across the matrix. The approach used must accommodate analysis of both of these.

3.2 MODELING THE SYSTEM

Based on the foregoing, and taking into account the objectives of the MMFM, each combination in the sector/functional waste type matrix can be modeled separately, as illustrated in Figure 7. The results from each "cell" in the matrix can then be accumulated as needed to cover the entire situation being evaluated.

To calculate the results for each cell, each of the processes in the materials production and use system and the associated solid waste system can be modeled schematically in a relatively straightforward manner. Material enters the process and is transformed by the process into output material.

FIGURE 7. Material Flow Results

Energy and other resource requirements are used by the process, and some inefficiencies inherent in the process result in a solid waste side-stream. To model such a process, the output of the process for a given time period must be defined as a function of:

- the input material
- a set of independent variables, such as gross national product, per capita income, population or population density, regulatory factors, and/or climate
- activity of related processes in other sector/functional waste type categories
- past outputs of the process.

This is illustrated in Figure 8.

For each of the major processes with the system, the results from each sector/functional waste type category can then be aggregated across the matrix in Figure 7, as needed. The primary variables that would be aggregated across the matrix include the material quantities, timing, and compositions; energy input/output; and costs. Other impacts resulting from each process could then be derived from these primary variables.

Construction of a computer model to carry out these calculations, and collecting and organizing the data that will be needed to drive such a model, are discussed in the following section.

FIGURE 8. Simplified Model of Processes in Macro Material Flow Modeling Approach

4.0 DEVELOPMENT AND IMPLEMENTATION OF THE MACRO MATERIAL FLOW MODEL

In this section, a brief discussion of model utility is presented to introduce the development and implementation of the MMFM. Following this, the general strategy that has been established for the development and implementation of the model is discussed. The specific steps to be undertaken to develop and implement the model are then identified and discussed. Finally, a tentative schedule for development is presented.

4.1 MODEL UTILITY

Modeling is undertaken to provide an effective tool for analysis of particular problems or issues. As discussed by Gass [1983], the basic utility of a model depends not only on its being useful and usable, but also on its actually being used.

"A model can be considered *useful* if it shows promise of attaining the objectives initially established for it." [Gass 1983] Thus, the MMFM will be useful if it provides an improved understanding of material flows, at the macro scale, within the solid waste management system and the associated materials production and use system, and of how these material flows change in response to various inputs or modifications to the structure of the systems themselves. A further measure of usefulness will be the ability to use results from the model as input to calculations of various impacts from solid wastes, as discussed previously.

"A model can be considered *usable* if it is understandable and plausible to both technicians and policy makers, economic to solve in terms of data collection and computation, and accessible to those who wish to use it." [Gass 1983] Thus, in order for the MMFM to be considered usable, several conditions will have to be met:

- The concepts incorporated in the model will need to be accepted and believed to appropriately represent the systems being modeled and their actions in response to the input information, at the level of detail chosen for the model.
- A strictly empirical approach to the modeling would require too detailed a system model and too much data to be economic or practical to solve. Therefore, the system definition incorporated in the model will need to be refined to incorporate the major features and actions of the system but to avoid unnecessary detail that might obscure the usability of the model. Likewise, the data will need to be correlated to reduce the volume to a usable, manageable quantity. (See Appendix C for further discussion of the data.)
- Eventually, provisions will need to be made to provide access for prospective users to the model and its results. At this time, it is too early in the development of the MMFM model to be overly concerned about eventual access provisions. However, it is intended to develop the

model in a standard computing environment and, if possible, to complete the model implementation on a desktop computer of the type that is commonly used as standard office equipment. This type of computing platform should facilitate eventual access for prospective users.

If a model meets the tests of usefulness and usability, then "it stands a chance of being used." [Gass 1983] The ability to use the MMFM for analytic purposes to support changes in the solid waste system is the ultimate goal of the modeling effort.

4.2 GENERAL STRATEGY FOR DEVELOPMENT AND IMPLEMENTATION

Several basic decisions have been made about the strategy to be pursued in the development and implementation of the MMFM. These general strategy elements are discussed here.

4.2.1 Modeling Scope

To reduce the scope of the problem currently being addressed to a more approachable level, several limitations have been placed on the initial modeling efforts, as discussed in the following paragraphs and depicted schematically in Figure 9.

The initial focus of Solid Waste Initiative modeling efforts has been placed on Municipal Solid Waste (MSW) and, to a lesser extent, other

FIGURE 9. Scope Limitations on Current Modeling Efforts

Collectively Managed Solid Wastes (CMSW). This is because of the relative accessibility of information on these wastes. However, the ultimate goal is to expand these efforts to include the full breadth of solid waste, including Industrial Solid Wastes and other Independently Managed Solid Wastes (IMSW). Therefore, the basic foundation and framework for the MMFM will need to be defined in such a way that they are compatible with the later addition of these other forms of solid waste.

In addition, the initial focus of the data collection and modeling efforts is on solid waste practices within the U.S. and Canada. This is partly because of the relative availability and comparability of data for these countries, in contrast to other countries; it also recognizes the more immediate usefulness to U.S. federal and regional officials of information on these countries. Nevertheless, the MMFM and the associated methodology will be developed in such a way as to allow expansion to other regions of the world as needed in the future. Thus, it will be necessary to ensure that the mechanisms included in the model for defining the relationships between waste generation and the various functional drivers are sufficiently flexible to allow for situations that are far different than those encountered in the U.S. and Canada.

4.2.2 Model Structure

It is currently anticipated that the MMFM will be developed as a logistics simulation, using computer simulation techniques. There are other modeling techniques that might be applied to this particular problem, but simulation currently appears to be the best-suited approach to the specific needs of this project. This assumption will be revisited at various stages during the model development process to ensure that it still remains valid.

Although full details of the modeling structure have not yet been defined, some general decisions regarding implementation of the model have been reached, as discussed in the following paragraphs.

Because of the potential level of complexity and detail in the eventual full implementation of the MMFM, and because of limitations on available resources, the development of the MMFM is likely to take several years. Thus, it is impractical to delay its use for analysis until full implementation of the model is achieved. Therefore, the model will be implemented in stages, with each stage adding functionality to provide a more fully developed version.

It is planned to initiate model development at a highly aggregated level, with only as much detail as necessary to illustrate and validate the model concept. Later, additional detail will be incorporated into the model as needed to provide a more detailed representation of the system and to answer specific questions.

To facilitate this stage-wise model development, the code will be modular. As the needs are identified for improved algorithms or more detailed results for a particular portion of the model (e.g., a particular combination of sector and functional waste type), the current working module can be

replaced with an improved one that provides the enhanced functionality. Of course, as these modules are replaced, it will be necessary to verify that the code operates as expected.

Model coding and data development will be carried out in parallel. There is a considerable amount of data to obtain and correlate, and the available information presents some challenges in terms of proper interpretation and correlation (see Appendix C). It would require an inordinate amount of time to do the coding and the data development in sequence. Even more important, however, is that the data development and the coding efforts are each expected to provide valuable input to the other as they progress, in terms of more detailed understanding of needs and requirements, limitations and constraints imposed by the currently available information and techniques. Thus, if a sequential development path was pursued, it would still require several iterations to properly complete.

As indicated previously in Section 2 of this report, the MMFM provides the core of the needed capability to assess the solid waste management system, but it is expected that other supplemental capabilities will also be needed eventually to assess specific types of impacts. Whether it is decided to incorporate these supplemental capabilities into the MMFM structure or to develop and operate them as separate modules, it will be necessary for the input data to the MMFM, and the calculated results from the MMFM, to be available to these additional capabilities. Further, some of these additional capabilities may provide results which then feed back into the MMFM. Therefore, in structuring the MMFM, such possible future input and output requirements will have to be taken into account.

Also as discussed in Section 2, it may well be desirable to link the MMFM to the Global Environmental Change Program Second Generation Model (SGM). Such a linkage would allow the MMFM to obtain from the SGM needed independent variable input data (such as GNPs, population data, etc.) that are either already used by or generated by the SGM. The SGM also could use information on the quantities and compositions of solid waste materials from the MMFM as part of its input information on available waste material for use in energy production. Therefore, in structuring the MMFM, it will be necessary to allow for this potential sharing of information with the SGM.

Because the development of the MMFM will take some time, it is also planned to develop a simple demonstration prototype model, illustrating major portions of the model functionality. This prototype will be implemented relatively early in the development cycle of the MMFM to provide a basis for presenting and refining the overall model concept, confirming the operability of the model and the usefulness of the results, further defining the model interface requirements, and facilitating liaison activities with prospective clients and other users.

4.3 STEPS IN MODEL DEVELOPMENT AND IMPLEMENTATION

Figure 10 illustrates the basic steps in the modeling process, and is adapted from a figure developed by the U.S. General Accounting Office [1979]

FIGURE 10. Basic Steps in the Modeling Process

and reported in Gass [1983]. Because the actual process is not anticipated to be carried out in quite such a sequential fashion as indicated in the figure, development of the MMFM will not progress exactly according to these steps. However, the basic process steps remain valid, so the discussion that follows is structured based on the steps in the figure.

4.3.1 Describe Problem

One of the primary goals of this report is to clearly identify the solid waste management problem that the Solid Waste Initiative intends to address. Section 2 of this report discusses the solid waste problem and our analytical needs relating to solid waste management, as they are currently defined and understood. In particular, the discussion of the types of questions that are relevant to understanding the solid waste management system is aimed at focusing the problem to be addressed by the Solid Waste Initiative. This problem description will continue to be expanded, modified, and refined as the model development activities progress.

There are basically six types of questions of interest relating to long-term policy issues associated with solid waste management. They include questions that relate to:

- waste quantities and timing
- waste compositions
- system costs and economics
- long-term environmental impacts
- opportunities for system improvements
- indirect impacts of policy alternatives on solid waste.

The ability to address any of these questions requires the capability to project overall material flows throughout the relevant portions of the solid waste management system and, because of its interconnectedness, the associated materials production and use system. (Some of these questions will also require additional capabilities to be used in conjunction with the material flow information.)

4.3.2 Isolate System

Solid waste issues relate to the entire materials cycle, from the mining of raw materials through the production of goods and services to the ultimate disposition of the waste products in the environment. Therefore, to effectively address all of the types of questions identified above, the system to be considered needs to be broader than just the traditional "end-of-pipe" view of the solid waste system. It needs to include the entire life-cycle of the major materials that are eventually identified as wastes, with consideration of the patterns of production and consumption that give rise to the wastes. Also, to evaluate and manage the large amounts of data describing the system and its operation, a systematic structure and approach are needed.

The solid waste management system and the associated materials production and use systems have been identified as the basis for the needed modeling effort. The basic structure and operation of these systems, as they will be modeled, are depicted in the figures presented in Section 3 of this report.

These system definitions/descriptions may change as the modeling efforts progress. Some possible reasons for changes might include lack of available data to support the concept as defined, or an inability to validate the model as proposed with observed responses in the real world. However, at this stage in the development, even recognition that such changes are needed would be an indication of increased understanding of the solid waste management and associated materials systems, and would thus represent progress towards our goals.

4.3.3 Adopt Supporting Theory

The theory being adopted as the basis for the modeling effort, as described in Section 3, is that the movement of materials through the systems being evaluated can be defined and calculated in terms of mathematical functions of such parameters as:

- quantities and compositions of input material into a process
- independent variables (e.g., GNP)
- operation of related processes not directly operating on the input or output material of the process in question
- previous outputs from the process being modeled.

The other major premise of the theory being adopted is that the various types of impacts for which predictions are desired can be calculated, at the macro level, from the output results from the MMFM coupled with other independent variables. However, at the current time, the main effort is being focused on the modeling of the material flows and only minimal attention is being addressed to extending these results to the projection of the broader impacts.

As discussed previously in Section 2, development and implementation of the MMFM is not specifically intended to address immediate or near-term solid waste management decisions or concerns. However, it is possible that the model, once implemented, might be useful in addressing some near-term issues.

4.3.4 Formulate Model

It has tentatively been determined that simulation techniques can be used to model the system operation in a way that will provide the desired material flow results. The specific simulation techniques to be employed have not been selected at this time.

The system will be modeled at the macro level, with a minimum of detail as required to support the combination categories of sector/functional waste origin, as described previously in Section 3. Additional detail will then be introduced as needed, either to refine the relationships being modeled or to

expand the level of detail in specific areas to allow for more in-depth analysis.

Mathematical functions will be defined that represent and simulate the operation of the various processes within the system. These functions will define the quantities and compositions of the materials leaving the processes. These processes are generally expected to be driven by selected external variables (i.e., uncontrolled variables) that can be supplied to the model as input.

Examples of the kinds of external variables that are anticipated to be involved include the following:

- Many material and waste production activities are expected to be linked to levels of economic activity. Therefore, such measures as GNP and per capita income are expected to be potentially useful in modeling these processes.
- The output from other activities, particularly in the Household/Residential sector, is likely to be more closely tied to the number of people or the number of households involved. For these activities, populations or population densities and numbers of households are likely to be included in the functional definition.
- Some material and waste production processes are likely to be strongly influenced by natural setting or environment (e.g., climate) [Franklin Associates, Ltd. 1985]. Some mechanism for incorporating climatological or other environmental factors may become important for these processes, depending on the level of detail and the geopolitical range being considered.
- Political factors such as regulations (e.g., bottle bills), policies, and general societal orientation could also have a significant impact on the actions of some material and waste production processes, and will need to be taken into account as the model implementation becomes more detailed.

It is planned to proceed by developing hypothetical functional relationships for each combination of sector and functional waste type in the waste origins matrix (see Figure 6), and then testing these hypothetical relationships using the data being collected. Several iterations may be required to get these defined functions to correspond reasonably with the data.

The model simulation will be based on appropriate increments of time. Although the specific time increment to be used has not yet been defined, it is anticipated that to meet the purposes of the MMFM described previously, a "time-slice" of one year should provide sufficient time resolution under almost any circumstances. For many analyses, time-slices of five or even ten years may provide sufficient resolution, and should substantially reduce the calculational load and the corresponding run-times of the model. The model will be implemented in such a way that the time-slice to be used can be easily

adjusted as needed to meet the specific requirements of the analysis being carried out.

4.3.5 Analyze Data Requirements/Collect Data

Data collection and evaluation efforts thus far have focused specifically on waste quantity and composition information, and predominantly only for MSW. However, other types of data will also be required to support the MMFM. Specific data needs will have to be identified for each of the major processes in the solid waste and materials systems, as depicted previously in Figure 5. These data needs will generally fall into categories as discussed in the following paragraphs.

Data on material flow rates and compositions are needed to support the definition and testing of appropriate functions to model each of the six basic processes in the system. Furthermore, these data must provide sufficient resolution to further subdivide each process to cover each combination of sector and functional waste type in the waste origins matrix. It is also possible that there are significant interlinks between different processes, and data will be needed to confirm or disprove such interlinks. The preliminary review of available solid waste characterization data presented in Appendix C covers only part of the characterization information that will be needed to support the MMFM.

Data are also needed for the independent external (i.e., uncontrolled) variables that are anticipated to be used in the functions for each process, such as GNP, populations, and the like. These data must be able to be correlated with the characterization data described in the previous paragraph. In addition, because of the interest in modeling long-term effects, both the characterization data and the independent variables data need to cover sufficient periods of time to allow establishment of trends over time. These trends will be important in the development of functional relationships that maintain their validity during changing conditions.

Material passing through the system remains resident within a given process for some length of time. These hold-up or residence times range from several days or weeks for some materials (e.g., use of disposable paper products) to many decades (e.g., for building components, white goods, furniture, automobiles, etc.). An adequate representation of these hold-up or residence times will be needed to model the processes with reasonable accuracy; data characterizing these residence times (at least in approximate terms) will thus be required.

It is important that the various types of data discussed above are developed from a comparable basis. Thus, attention will need to be paid to the source and basis of the various data that are collected, to ensure their comparability.

To focus data collection and development efforts (as well as coding efforts), a "sample problem" will be defined during FY-93, to be representative of the types of problems that will be addressed using the MMFM. This

sample problem will also be useful for verification and validation activities (see below).

4.3.6 Develop Computer Program

As indicated previously, two separate computer programs or models are planned for development. One is the MMFM, which will take considerable time and effort to complete. The other is a simple demonstration prototype model that will simulate major portions of the MMFM functionality; this prototype can be developed in much less time than the MMFM, and will be useful to obtain feedback on concept, functionality, and usability that will be incorporated into the development of the MMFM.

The prototype model will be aimed at providing a simplified demonstration of the model concepts and operation to prospective users and clients. This will provide a basis for explaining and refining the overall MMFM concept, confirming the operability of the model and the usefulness of the type of results that will be produced, and facilitating liaison activities with prospective clients. The prototype will be developed to operate on a desktop or portable lap-top computer, to facilitate demonstrations. Rapid prototyping techniques will be used to develop the prototype model [Mullin 1990].

The basic code development process anticipated to be used in developing the full MMFM is shown in Figure 11. This process is briefly discussed here.

FIGURE 11. Basic Code Development Process for the MMFM

The code development process begins with the formal definition of model requirements, which will be documented as a set of specifications for the completed model. This definition of requirements will build on the concepts and ideas presented in this report, and also on the experience of the rapid prototyping development process for the demonstration prototype.

Following the definition of the model requirements, high-level code design and allocation of the basic software functions can be performed to meet these requirements.

Development of the code segments to implement the model is accompanied by the development of unit test drivers to test the operation of the various code modules. These two activities lead to unit testing of the various segments of code and resolution of any problems identified during the unit testing.

Once code development has been satisfactorily completed, the code can be verified (see below) in preparation for putting it into use.

4.3.7 Debug Computer Program

Code testing and debugging are considered to be part of the development of the computer program and, therefore, are discussed as part of the previous section.

4.3.8 Verification

Verification of a computer model refers to the act of determining that the model performs as expected, i.e., that the code does what it was intended to do [Gass 1983]. This should not be confused with validation, discussed below, which refers to a model's correspondence to the real world.

A standard method for model verification is to construct one or more example problems to exercise the capabilities of the model, and then to test the results the model produces from these example problems to results obtained, for example, by hand calculation. It is anticipated that the example problem to be defined during FY-93 (see Section 4.4 below) will be used in the verification of the MMFM; additional test cases may also be needed to fully test the range of capabilities to be included in the model.

Because it is intended to add on to the model in stages, to develop the complete capability, verification will be required as each stage of the model is completed.

4.3.9 Develop Alternative Solutions

A predictive model such as the MMFM will always be subject to some errors in the accuracy of its results. This limits the usefulness of results from a single isolated analysis. However, provided the model is properly constructed, many of these errors will cancel out when comparing alternative cases or scenarios. Thus, a model such as the MMFM is most useful and powerful when used to compare alternative scenarios.

When the model is completed and ready to be used, alternative cases for configuration and/or operation of the solid waste management and materials systems will be defined to determine the relative impacts that would result from such changes. Definition of the full range of potential alternative cases is beyond the scope of this report. However, examples of the kinds of changes that are likely to be analyzed include:

- increased recovery and reuse of specific types of materials in the solid waste stream
- increased pressures (e.g., financial, regulatory, or political) to reduce solid waste volumes, either in total or for specific waste types
- changes in fundamental manufacturing and commercial practices (e.g., material substitutions or revised packaging practices) or in economic or regulatory policies (e.g., taxes or regulations on specific materials) that could substantially alter the solid waste stream.

Definition of alternative cases of interest for analysis will proceed in parallel with the development of the MMFM.

4.3.10 Evaluate Model Output/Results

In the context of the MMFM, there are two relevant meanings for the evaluation of the model output and results. The first refers to the direct use of the results in addressing a particular problem or question, while the second refers more generally to the usefulness or utility of the results in the form in which they are provided to the user.

As indicated in previous sections of this report, it is believed that the results that will be generated by the MMFM will be a necessary part of evaluating the impacts of any specific scenario, but additional capabilities are also likely to be required to extend these results and calculate specific types of impacts. These additional capabilities could eventually be added to the MMFM as extension modules, or they could be operated separately using the input data used by and the results generated by the MMFM; no decision on this is needed at this time. In either case, the use of the results will be within the context of an analytical study or inquiry, and this larger context will provide the bases and assumptions that make the interpretation of the results meaningful. Note that, until the model has been validated (see below), caution must be observed in the use of results from the model.

Providing results to a user is one thing, providing these results in a useful format that can easily be modified or incorporated into other parts of an analytical effort is often another. The design for the MMFM will cover the user interface and the specification and handling of the output. However, in designing such a model, it is impossible to anticipate all of the possible uses and needs that it will be called on to meet. Therefore, it will be necessary to generally evaluate the output and results of the model during the actual use phase to determine if modifications or additions would be appropriate to improve their general applicability or ease of use.

4.3.11 Present Results/Plans

At this stage, it is premature to place too much emphasis on eventual presentation of results from the MMFM. The key issue here is the identification and linking with appropriate users of this information, both inside and outside the federal government, as discussed previously.

4.3.12 Develop Model Maintenance Procedures

Standard model maintenance procedures as applied as part of the PNL Good Practices Standards [Pacific Northwest Laboratory 1992] will be used.

4.3.13 Model Validation

"For decision-aiding models, a model is useful only when the decision maker believes (rightly or wrongly) that it is valid." [Gass 1983]

The purpose of model validation is to verify that the model is realistic, i.e., produces results that reflect the real world to a reasonable degree. It is particularly important to determine that the model provides reasonable comparisons of alternative scenarios because, as previously explained, models such as the MMFM are more often used for such comparisons than for stand-alone predictions of future conditions. A major challenge in validating the MMFM will be in obtaining the necessary data for the validation.

Models such as the MMFM that are based on assumptions about the future are difficult to validate [GAO 1979]. It will be necessary to compare model output for appropriate cases with historical data, where such relevant data exist. Where data do not exist to corroborate the results of the model, the validation activity will have to rest more on the following considerations:

- **face validity**, which is a measure of the general credibility of the model's realism
- **variable or parameter validity**, which is a measure of the ability of the model to interpret variations in input parameters [GAO 1979].

Because the MMFM will be developed modularly, with increasing breadth and depth of detail added as needed, validation of the MMFM will need to be carried out continuously, in parallel with model development.

4.3.14 Transfer System to Users

At this stage in the development of the MMFM, concerns about the transfer of the system to other users are, appropriately, remote. However, as noted previously, it is intended that the model will be implemented on a desktop or lap-top computer of the type that is commonly used as standard office equipment. This should facilitate access for prospective users, when the appropriate time comes.

4.4 SCHEDULE FOR DEVELOPMENT OF THE MACRO MATERIAL FLOW MODEL

Based on the information and concepts discussed in this report, a specific modeling architecture will be defined in FY-93, including input/output specifications, data flows, and code structures to achieve the concept. In addition, as discussed above, a simple demonstration prototype model illustrating major portions of the model functionality will be developed. This prototype will provide an improved basis for presenting and refining the model concept, confirming the operability of the model and the usefulness of the results, and facilitating liaison activities with prospective clients.

Concurrently, the development of the data and the functional relationships to support the modeling will continue. Information currently being collected about quantities and compositions of solid waste materials (see Appendix C) needs to be correlated with the origins of these wastes in terms of sector of the economy and function producing the wastes. The information that has already been collected needs to be extended and analyzed to arrive at functional relationships that allow calculation of future waste quantities and compositions. This effort will continue during FY-93 at a level sufficient to ensure that the model architecture and data input/output structures are developed in a manner that will allow consistency with the data that will eventually be available. However, the current funding does not allow for complete collection and development of all of the data that will be required to support the model, nor does it allow for complete definition of the functional relationships driving solid waste generation.

Major FY-93 milestones for the Solid Waste Initiative are currently defined as shown in Figure 12.

Availability of additional funding for the MMFM development activities would provide for identification and participation of additional key staff members and more rapid development of the model and associated data.

Solid Waste Initiative	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
Identify/Define Sample Problem for Analysis							▲					
Develop Demonstration Prototype MMFM										▲		

FIGURE 12. Major FY-93 Milestones for the Solid Waste Initiative

APPENDIX A

GLOSSARY

APPENDIX A

GLOSSARY

Biodegradable Material - Material which can be broken down by microorganisms into simple, stable compounds such as carbon dioxide and water. Most organic wastes such as food wastes and paper are biodegradable.

Bottle Bill - A law requiring deposits on beverage containers.

CMSW - Collectively Managed Solid Wastes, wastes collected from a number of sources for management as a collective group; e.g., Municipal Solid Waste.

Combustible - Various materials in the solid waste stream which can be burned, such as paper, plastic, lawn clippings, leaves, and other organic materials.

Commercial Solid Waste - All types of solid waste generated by stores, offices, restaurants, warehouses, and other nonmanufacturing activities, excluding residential and industrial wastes [40 CFR 258].

Composting - The controlled biological decomposition of organic solid waste materials under aerobic conditions. The resulting material can be used as a soil amendment or mulch.

Construction and Demolition Waste - Materials resulting from the construction, remodeling, repair or demolition of buildings, bridges, pavements and other structures [U.S. EPA].

Controllable Variables - Variables whose values can be determined by the decision process.

Disposal - The discharge, deposit, injection, dumping, spilling, leaking, or placing of any solid waste into or on any land or water so that such solid waste or any constituent thereof may enter the environment or be emitted into the air or discharged into any waters, including ground waters [RCRA].

Domestic Waste - see Household Waste.

Energy Recovery - A form of resource recovery in which the combustible portion of the solid waste is used as a fuel to produce some form of usable energy, such as steam or electricity.

Heavy Metals - Hazardous elements including cadmium, mercury, and lead which may be found in the waste stream as part of discarded items such as batteries, lighting fixtures, colorants and inks.

Household Waste - Any solid waste (including garbage, trash, and sanitary waste in septic tanks) derived from households (including single and

multiple residences, hotels and motels, bunkhouses, ranger stations, crew quarters, campgrounds, picnic grounds, and day-use recreation areas [40 CFR 258].

HSWA - Hazardous and Solid Waste Amendments of 1984, amending RCRA.

IMSW - Independently Managed Solid Wastes, wastes managed independently from collective waste management systems, usually by the entity generating the waste or its agent; e.g., most industrial solid wastes.

Incinerator - A facility for the controlled burning of a waste material, such as MSW. (See also Waste-to-Energy.)

Industrial Solid Waste - Solid waste generated by manufacturing or industrial processes that is not a hazardous waste regulated under subtitle C of RCRA. Mining waste and oil and gas waste are usually excluded from the category of industrial solid waste.

Inorganic Waste - Waste composed of matter other than plant or animal (i.e., contains no carbon).

Institutional Wastes - Waste materials originating in schools, hospitals, prisons, research institutions and other public buildings.

Integrated Solid waste Management - A practice of using several alternative waste management techniques to manage and dispose of specific components of the solid waste stream. The waste management alternatives include source reduction, recycling, composting, energy recovery, and land-filling [U.S. EPA].

Landfill - A facility for the disposal of solid waste materials by burying them under a shallow layer of ground. See also "Sanitary Landfill."

macro - Large scale and/or long range, with reduced attention to detail, as contrasted with micro.

MRF - Materials Recovery Facility.

MSW - Municipal Solid Waste.

Municipal Solid Waste - As used in this report, any solid waste managed collectively by and/or for a municipality. In contrast, some definitions of Municipal Solid Waste exclude certain types of waste, such as construction or demolition debris and automobile scrap. Various types of industrial, agricultural, and mining wastes are not considered to be part of the municipal solid waste.

Putrescible Waste - Solid wastes which are capable of being decomposed by microorganisms with sufficient rapidity to cause nuisances from odors or gases and capable of providing food for, or attracting, animals and disease vectors.

RCRA - Resource Conservation and Recovery Act, as amended.

RDF - Refuse-Derived Fuel.

Recovered Material - Waste material and byproducts which have been recovered or diverted from solid waste, but not including those materials and byproducts generated from, and commonly reused within, an original manufacturing process [RCRA].

Recycling - The reintroduction of a material back into the process by which it was formed. In common usage, recycling means using discarded or waste materials and objects in original or reprocessed form rather than wasting them. There are several different approaches to recycling of materials from solid waste. Commonly recycled materials from municipal solid wastes include newspaper and other paper products, aluminum, glass, some types of plastic, steel and other metals. Efforts are also under way to recycle various materials from other solid waste sources such as aggregates and wood fibers from construction debris, and various kinds of materials from industrial wastes.

Refuse-Derived Fuel - Fuel produced by processing waste materials into a form better suited for use in combination with or as a replacement for other fuels.

Resource Conservation - Reduction of the amounts of solid waste that are generated, reduction of overall resource consumption, and utilization of recovered resources [RCRA].

Reuse - The use of a product more than once in its same form for the same purpose (e.g., refillable soft-drink bottles are reused) [U.S. EPA].

Sanitary Landfill - A facility for the land disposal of solid waste that meets applicable criteria (e.g., RCRA section 4004). Waste is spread in thin layers, compacted, and covered with a fresh layer of soil each day to minimize pest, aesthetic, disease, air pollution, and water pollution problems.

SGM - Global Environmental Change Program Second Generation Model [Edmonds et al. 1991].

Simulation - Construction and operation of a model of a real system in order to analyze the operation of the system and the impacts resulting from changing system conditions or operating parameters. In this report, this term is used to refer to computer simulations.

Solid Waste - "Any garbage, refuse, sludge, from a waste treatment plant, water supply treatment plant, or air pollution control facility and other discarded material including solid, liquid, semisolid, or contained gaseous material resulting from industrial, commercial, mining, and agricultural operations, and from community activities, but does not include solid or dissolved material in domestic sewage, or solid or dissolved materials in irrigation return flows or industrial

discharges which are point sources subject to permits under section 402 of the Federal Waste Pollution Control Act, as amended (86 Stat. 880), or source, special nuclear, or byproduct material as defined by the Atomic Energy Act of 1954, as amended (68 Stat. 923)." [RCRA]

Other definitions for solid waste are basically similar in that they pretty much include all wastes that are not flowing liquids or gases and for which the same general handling techniques can be used as for other "solid" materials.

Solid Waste Management - "The systematic administration of activities which provide for the collection, source separation, storage, transportation, transfer, processing, treatment and disposal of solid waste." [O'Reilly]

Sustainable Development - The concept that economic development should be carried out in such a way that it can be sustained in the same manner over long periods of time without sacrificing natural resources or the environment for short-term gain. As applied to solid waste, this concept would require that solid waste management practices be carried out in a manner that is sustainable over the long-term.

Uncontrolled Variables - Variables in a situation that are not under the control of the decision maker. Uncontrolled variables include physical phenomena, variables resulting from the actions of others, or certain economic parameters [Gass and Sisson].

Waste-to-Energy - A strategy of using waste materials, either directly or after processing into an improved form, to replace conventional fuels for the production of energy. In some cases, these materials are combined with other fuels (i.e., co-fired), while in others facilities are specifically designed and constructed to be fueled by the wastes.

White Goods - Large household appliances such as refrigerators, freezers, stoves, washing machines, and the like.

Yard Wastes - Leaves, grass clippings, prunings, and other natural organic matter from yards, gardens, parks, campgrounds, etc. Yard waste may also include stumps and brush, but these materials are not normally handled at composting facilities.

APPENDIX B

BIBLIOGRAPHY

APPENDIX B

BIBLIOGRAPHY

This bibliography contains references that are cited in the report as well as other pertinent publications. It is broken down into sections corresponding with the major topic areas addressed in this report.

B.1 GENERAL BACKGROUND

40 CFR 258. 1991. U.S. Environmental Protection Agency, "Criteria for Municipal Solid Waste Landfills." U.S. Code of Federal Regulations.

Bogner, J., and K. Spokas. *Landfill CH₄: Rates, Fates, and Role in Global Carbon Cycle*. ANL/CP-75733. Argonne National Laboratory, Argonne, Illinois, 1992.

Gore, Al. "The Wasteland," pp. 145-163 in *Earth in the Balance*. Houghton Mifflin Company, 1992.

Haney, Mark, and Jane Casler. *RCRA Handbook*. ENSR Consulting and Engineering, Acton, Massachusetts, 1990.

Hunt, Robert G., Jere D. Sellers, and William E. Franklin. "Resource and Environmental Profile Analysis: A Life Cycle Environmental Assessment for Products and Procedures." *Environmental Impact Assessment Review*. 1992:12, pp. 245-269.

O'Reilly, James T. *State and Local Government Solid Waste Planning*, Chapter 3. Clark Boardman Callagan, 1991.

Repetto, Robert. "Accounting for Environmental Assets." In *Scientific American*, pp. 94-100, June 1992.

Resource Conservation and Recovery Act (RCRA) of 1976. 42 USC 6901 et seq., as amended.

Robins, Renee J., Kari Gardey, and Stephanie Pollack. *Waste Not: Garbage as an Economic Resource for the Northeast*. Conservation Law Foundation, Boston, Massachusetts, December 1991.

Tent, Johan, and Jan J. van den Berg. "Emissions and Emission Control at Landfill Sites." In *Proceedings of the 9th World Clean Air Congress Volume 1: Waste Management*. IU-4A.10. Montreal, Quebec, Canada, 1992.

U.S. Congress, Office of Technology Assessment. *Facing America's Trash: What Next for Municipal Solid Waste*. OTA-O-424. Washington, D.C., October 1989.

U.S. EPA. *Decision-Makers Guide to Solid Waste Management*. EPA/530-SW-89-072, Office of Solid Waste, U.S. Environmental Protection Agency, Washington, D.C., November 1989.

B.2 MODELING AND ANALYSIS

Barfield, B. J., J. F. Clarke, O. J. Loewer, and M. Collins. *Identification and Assessment of Critical Issues Relative to Modeling Biomass Energy Production: A Response to Potential Climate Change*. Proceedings of the Global Biomass Workshop, September 9-11, 1991. University of Kentucky, Lexington, Kentucky, and Battelle, Pacific Northwest Laboratories, Washington, D.C.

Clymer, A. Ben. "Some Specifications for Simulations in Planet Planning." In *Simulation*, 59:4, October 1992, pp. 275-280. Society for Computer Simulation, San Diego, California.

Cohan, David, Kenneth R. Wapman, W. Corey Trench, and Mary McLearn. "Beyond Waste Minimization: A Life-Cycle Cost Approach to Managing Chemicals and Materials." Presented at the *Air & Waste Management Association 85th Annual Meeting & Exhibition*, Kansas City, Missouri, June 21-26, 1992.

Edmonds, J. A., et al. "Modeling Future Greenhouse Gas Emissions: The Second Generation Model Description." In *Proceedings of the United Nations University Conference on Global Change and Modeling* (Forthcoming), Tokyo, Japan, October 1991.

Gass, Saul I. "Decision-Aiding Models: Validation, Assessment, and Related Issues for Policy Analysis." In *Operations Research*, 31:4, July-August 1983, pp. 603-631. Operations Research Society of America, Baltimore, Maryland.

Gass, Saul I., and Roger L. Sisson. *A Guide to Models in Governmental Planning and Operations*. Sauger Books, Potomac, Maryland. 1975.

Gottinger, Hans-Werner. *Economic Models and Applications of Solid Waste Management*. Gordon and Breach Science Publishers, New York, New York. 1991.

Hirschhorn, Joel S. "Product Lifecycle Analysis Promotes Multimedia Pollution Prevention." Presented at the *Air & Waste Management Association 85th Annual Meeting & Exhibition*, Kansas City, Missouri, June 21-26, 1992.

Majone, Giandomenico, and Edward S. Quade. *Pitfalls of Analysis*. International Institute for Applied Systems Analysis. 1980.

Miller, D. R., Gail Butler, and Lise Bramall. "Validation of Ecological System Models." In *Journal of Environmental Management*, 4:4, October 1976, pp. 383-401. Academic Press.

Mullin, Mark. *Rapid Prototyping for Object-Oriented Systems*. Addison-Wesley Publishing Company, Inc. July 1990.

Pacific Northwest Laboratory. *Quality Assurance Manual Part 2: Good Practices Standard*. PNL-MA-70, Part 2. Richland, Washington. July 1992.

Ream, Timothy J. "Life Cycle Assessment: A Tool for Addressing Environmental Problems." Presented at the *Air & Waste Management Association 85th Annual Meeting and Exhibition*, Kansas City, Missouri, June 1992.

U.S. General Accounting Office (GAO). *Guidelines for Model Evaluation*, PAD-79-17. Washington, D.C. 1979.

Zandi, Iraj. "Major Issues Facing Solid Waste Management in the 1990's." In *The Journal of Resource Management and Technology*, 19:4, December 1991, pp.169-170. University of Pennsylvania, Philadelphia, Pennsylvania.

B.3 SOLID WASTE QUANTITIES AND COMPOSITIONS

Dernbach, John C. "Industrial Waste Management." Presented at the *Second United States Conference on Municipal Solid Waste Management: Moving Ahead*, Arlington, Virginia, June 2-5, 1992.

Energy Systems Research Group. *Managing Municipal Solid Waste: A Comparative Risk Analysis of Landfill and Resource Recovery Facilities*, ESRG Report No. 87-103, pp. 6-10, November 1988.

Ferguson, R. G., "The 3Rs (Reduce, Reuse, Recycle) of Solid Waste Management in Metropolitan Toronto and the Province of Ontario: The Trend from Traditional Disposal to Waste Diversion in the 1980s." In *International Solid Wastes Association (ISWA) Times*, No. 2, pp 17-19, 1992.

Field, Charles R. "Compost: A Windrow of Opportunity?" In *World Wastes*, pp. 28-31, 35:9, September 1992.

Franklin Associates Ltd. *A Study to Develop a Predictive Technique for the Estimation of Collectible Solid Waste in the United States*. ANL/CNSV-TM-171. Prepared for Argonne National Laboratory. January 1985.

Franklin Associates, Ltd. and The Garbage Project. *Estimates of the Volume of Municipal Solid Waste and Selected Components*. Prepared for The Council for Solid Waste Solutions, October 19, 1989.

Friege, Henning. "Waste Incineration and Waste Management - The German Experience." In *Proceedings of the 9th World Clean Air Congress Volume 1: Waste Management*. IU-2B.04. Montreal, Quebec, Canada, 1992.

Glenn, Jim. "Curbside Recycling Reaches 40 Million." In *BioCycle*, pp. 30-37, July 1990.

Hendrickson, Mark. "EPA Reports: U. S. Recycling Rates Rise." In *Integrated Waste Management* newsletter, August 19, 1992.

Hickman, H. Lanier Jr. "Looking at Municipal Solid Waste Composition and Mandatory Removal Rates in North America." In *International Solid Wastes Association (ISWA) Times*, No.2, pp. 2,3, & 13, 1992.

Jones, R. C. *Feasibility Study for Managing a Small-Scale Solid Waste Resource Recovery Facility*. NSF/ISP-81009, prepared for the National Science Foundation, February 1981.

Karau, John. "Waste Management and the London Dumping Convention." In *Proceedings of the 9th World Clean Air Congress Volume 1: Waste Management*. IU-3.10. Montreal, Quebec, Canada, 1992.

Kelly, W. Robert. "Buried Treasure." In *Civil Engineering*, pp. 52-54, April 1990.

Kinman, R. W., J. Rickabaugh, G. Berg, D. L. Nutini, and W. L. Rathje, "Analysis of 20 Year-Old Refuse from the Mallard North Landfill in Chicago, IL." Presented at the *44th Purdue Industrial Waste Conference*, May 9-11, 1989.

Lancaster County Solid Waste Management Authority. *Landfill Reclamation*. Lancaster, Pennsylvania. April 1992.

Lawrence, LaWanda A. "Solid Waste: Addressing the Issues with an Integrated Approach." Presented at the *Air and Waste Management Association 85th Annual Meeting and Exhibition*, Kansas City, Missouri, June 21-26, 1992.

Lindorff, Dave. "The Paper Chase." In *Governing*, pp. 34-40, March 1990.

McGuire, R. H. "Recycling - Great Expectations and Garbage Outcomes." In *American Behavioral Scientist*, 28:1, September-October 1984.

McGuire, R. H., W. W. Hughes, and W. L. Rathje. *Garbage Project on Recycling Behavior*. NSF/CEE-82145, prepared for the National Science Foundation, February 1982.

Morelli, John. "Landfill Reclamation: Findings of the Edinburg Project." Presented at the *Second United States Conference on Municipal Solid Waste Management: Moving Ahead*, Arlington, Virginia, June 2-5, 1992.

Morelli, John. "Landfill Reuse Strategies." In *BioCycle*, pp. 40-43, 62, March 1990.

Petersen, Terry, and David Luneke. *Metro Waste Characterization Study: 1989-90 Final Report*. Metropolitan Service District, Portland, Oregon, June 1990.

Rathje, W. L. "The Three Faces of Garbage." In *Journal of Resource Management and Technology*, Vol. 7, No. 2, pp. 61-66, April 1989.

Rathje, W. L. *Comments on S.1112 and S.1113 - The Solid Waste Disposal Act, 101 Congress, 1st Session*, testimony before Senate Committee on Environment and Public Works, June 21, 1989.

Rathje, W. L. "Rubbish." In *The Atlantic Monthly*, pp. 1-10, December 1989.

Rathje, W. L. "Archaeologists Bust Myths About Solid Waste and Society." *The History of Garbage - The Practical Journal for the Environment*, pp. 32-39, September/October 1990.

Rathje, W. L. "Once and Future Landfills." In *National Geographic*, Vol. 179, No. 5, pp. 134-161, May 1991.

Rathje, W. L. "Name It and Claim It." In *Garbage*, pp. 20-21, July/August 1992.

Rathje, William L., and Barry Thompson. *The Milwaukee Garbage Project*, prepared for the Solid Waste Council of the Paper Industry Report, March 1981.

Rathje, W. L., D. C. Wilson, V. W. Lambou, and R. C. Herdon. *Characterization of Household Hazardous Waste from Marin County, CA, and New Orleans, LA.* EPA/600/4-87/025. U.S. Environmental Protection Agency, Washington, D.C. August 1987.

Rathje, W. L., et al. *The Phoenix Recycling Project - A Characterization of Recyclable Materials in Residential Solid Wastes: Initial Results.* Prepared for The City of Phoenix, Arizona Department of Public Works, May 25, 1988.

Rathje, W. L., et al. "Source Reduction and Landfill Myths." *ASTSWMO National Solid Waste Forum on Integrated Municipal Waste Management*, Lake Buena Vista, FL, July 17-20, 1988.

Rathje, W. L., et al. "Inside Landfills - A Preliminary Report of the Garbage Project's 1987-88 Excavations at Five Landfills." Presented at the *Municipal Solid Waste Technology Conference*, San Diego, January 1989.

Rugg, Mack, and Nabil K. Hanna. "Metals Concentrations in Compostable and Noncompostable Components of Municipal Solid Waste in Cape May County, New Jersey." Presented at the *Second United States Conference on Municipal Solid Waste Management: Moving Ahead*, Arlington, Virginia, June 2-5, 1992.

Selby, M., J. Crruth, and B. Golob. "End Use Markets for Municipal Solid Waste Compost." In *BioCycle*, Vol. 30 (11), pp. 56-58, 1989.

Smith, D. G., and B. W. Baetz. "A Comprehensive Costing Methodology for Assessment of Solid Waste Management Alternatives." In *Journal of Resource Management and Technology*, Vol. 19, No. 4, pp. 140-147, December 1991.

Taubert, Ulrich. "Management of By-Products from Hard Coal Fired Power Plants in Germany." In *Proceedings of the 9th World Clean Air Congress Volume 1: Waste Management.* IU-4A.03. Montreal, Quebec, Canada, 1992.

U.S. Congress, Office of Technology Assessment (OTA). *Facing America's Trash*, Washington, D.C. 1989.

U.S. Congress, Office of Technology Assessment (OTA). *Managing Industrial Solid Wastes From Manufacturing, Mining, Oil and Gas Production, and Utility Coal Combustion*, OTA-BP-O-82. Washington, D.C. February 1992.

U.S. EPA. *Recycling Works! State and Local Solutions to Solid Waste Management Problems*. EPA/530-SW-89-014, Office of Solid Waste, U.S. Environmental Protection Agency, Washington, D.C. January 1989.

U.S. EPA. *The Solid Waste Dilemma: An Agenda for Action*. EPA/530-SW-89-019, Office of Solid Waste, U.S. Environmental Protection Agency, Washington, D.C. February 1989.

Weddle, Bruce R. "EPA Addresses Plastic Wastes." In *Waste Age*, pp. 260-270, April 1990.

Williams, John F. "Tracking Progress with Recycling via Waste Composition Analysis." Presented at the *Air and Waste Management Association 85th Annual Meeting and Exhibition*, Kansas City, Missouri, June 21-26, 1992.

Wilson, D. C. "Ancient Trash, Modern Solid Wastes: An Archaeologist's Perspective on Reuse, Recycling, Waste, and Landfill Degradation." *The National Solid Waste Management Symposium*, Prescott, Arizona, April 10, 1988.

Wilson, D. C. "Lead and Archaeology Methods to Quantify Lead in Modern Residential Refuse." Prepared for the *Lead Industries' Annual Meeting*, Orlando, Florida, May 11, 1989.

Wilson, D. C. "The Hazardousness of Cleaner Products in Household Refuse: Characteristics and Evaluation." In *Journal of Resource Management and Technology*, 18:1, March 1990.

Wilson, Douglas C., and William L. Rathje. "Structure and Dynamics of Household Hazardous Wastes." In *Journal of Resource Management and Technology*, Vol. 17, No. 4, Dec. 1989.

B.4 FUNCTIONAL DRIVERS FOR SOLID WASTE GENERATION

Franklin Associates Ltd. *A Study to Develop a Predictive Technique for the Estimation of Collectible Solid Waste in the United States*. ANL/CNSV-TM-171. Prepared for Argonne National Laboratory. January 1985.

Government of Canada. *Economic Instruments for Environmental Protection: Discussion Paper*, Cat. No. En21-119/1992E. Ottawa, Canada. 1992

Heidig, Edward G. "California's Beverage Container Law: How AB 2020 Reached 80% Recycling at a Quarter-Billion-Dollar Annual Savings Over a Traditional Bottle Bill." In *Proceedings of the Seventh International Conference on Solid Waste Management and Secondary Materials*, Philadelphia, Pennsylvania, December 1991.

APPENDIX C

PRELIMINARY REVIEW OF AVAILABLE SOLID WASTE CHARACTERIZATION DATA

APPENDIX C

PRELIMINARY REVIEW OF AVAILABLE SOLID WASTE CHARACTERIZATION DATA

This appendix provides a preliminary review of available solid waste characterization data. Data collection and correlation activities for the Solid Waste Initiative are continuing in parallel with the Macro Material Flow Model (MMFM) development activities.

As interest in the solid waste problem increases, and as more communities and industrial concerns are faced with increasing solid waste management costs and decreasing options, additional solid waste characterization data are expected to become available. As an important example, the United Nations Conference on Environment and Development (UNCED) held in Rio de Janeiro in 1992 is expected to lead to considerable efforts to develop improved data gathering and analysis methods to support the development of better solid waste management strategies at national and international levels. The Solid Waste Initiative will continue to monitor the progress of these activities.

It is important to recognize that, for the purposes of the MMFM effort, the major need for data is to be able to draw out the functional relationships that drive the materials production and use system and the associated solid waste management system. This will ensure that the model being developed is reasonably representative of the real world (i.e., valid). Absolute, complete, and exhaustive data on waste quantities and compositions in a variety of locations and situations are not required; however, the data used must be sufficiently complete and representative to ensure model validity.

In terms of how they are managed, there are two distinct types of solid wastes (as discussed in Section 3.1):

- Collectively Managed Solid Wastes (CMSW), typified by Municipal Solid Waste (MSW)
- Independently Managed Solid Wastes (IMSW), such as many industrial and agricultural wastes.

Because of the differences in how they are managed, the amount and type of available data vary considerably between the two types of solid waste. Therefore, they are discussed separately in this appendix.

C.1 COLLECTIVELY MANAGED SOLID WASTES

CMSW, and more particularly MSW, has been the major focus of the Solid Waste Initiative data collection efforts to this point; furthermore, these efforts have focused primarily on the U.S. and Canada.

In terms of the sectors of society defined in Section 3 of this report, CMSW typically includes solid wastes predominantly from household/residential and commercial sources. It may also include some wastes from certain indus-

trial (particularly light industrial), medical, and government sources. In addition, even though usually excluded from the definition of MSW, construction and demolition debris are often disposed of in MSW landfills, and so debris may be either included or excluded from particular data sources depending on the type of analysis done in the particular case.

Because of the way CMSW is managed, accurate information on waste quantities and characteristics is needed by the system operators for planning, to ensure that all of the customers of the waste service can be adequately served. Thus, there is a substantial body of data on CMSW, at least for communities that have recently been involved in planning for new or changed solid waste management systems. Also, because much of the management of the CMSW is carried out or controlled by municipalities, the data that have been collected are generally available to others. Consequently, the data available for CMSW are, in general, considerably more available than for IMSW.

It is important to note that there are various definitions for MSW, and many types of wastes are included in some definitions but not in others. This complicates data comparisons among different sources considerably.

Even though data on CMSW are much more available than for IMSW, the available data are still somewhat sparse, being available generally only for communities that have performed studies to determine how they should proceed on some aspect of their solid waste management. In addition, these data are generally tuned specifically to the purpose of the study that was made. Thus, it will be difficult to generalize from much of the available data.

Among the data that are available from various sources and locations within the U.S. and Canada, there are considerable variations in per-capita amounts [U.S. Congress 1989, p. 77] and also in the compositions of the solid wastes. Also, because of the way much of the data are recorded, it is difficult to determine which functional waste types or origins (see Section 3) account for what quantity and composition of waste.

The factors discussed in the preceding paragraphs are likely to hinder somewhat the ability to validate hypothesized functional relationships for processes within the MMFM. However, some studies have already been conducted to determine similar functional relationships [Franklin Associates Ltd. 1985], and the results of these studies will help provide guidance for the effort.

Tables C.1 through C.4 summarize important sources of information on CMSW. These information sources are sorted into four general categories:

- overview
- landfill and MSW stream
- recycling and diversion
- hazardous household waste.

The tables summarize key features of each information source and provide comments that clarify the content or usefulness of the information included.

Table C.1 Overview References on Municipal Solid Waste (MSW)

Reference	Key Features	Notes & Comments
U.S. EPA February 1989	overview of solid waste, its impacts, recycling & reduction plans and goals, the household hazardous waste issue; a few basic waste composition graphs	composition data cited from Franklin Associates report, 1988
Rathje April 1989	informal interviews of gov't officials, environmental groups, and businessmen greatly exaggerated the estimates of plastic and fast-food packaging in solid waste	
Selby et al. 1989	discusses the market for MSW compost; three primary markets - gravel pits, commercial landscaping, and sanitary landfills	based on interviews and questionnaires
U.S. Congress October 1989	options for a national policy on MSW prevention and management; discusses the MSW system, generation & composition, prevention, recycling, incineration, landfilling, and government planning & programs	good overview tables and figures
Williams June 1992	four and a half year study of field sampling and observation of Titon Falls landfill, recycling records, and demographic information; large amounts of data and graphs; dollars affect recycling the most	Limited to Monmouth County, NJ, waste stream

Table C.2 Landfill and MSW Stream References

Reference	Key Features	Notes & Comments
Franklin Associates Ltd., 1985	MSW generation rates for 18 cities across the U.S., relational information about waste generation rates and household and local economic conditions	no waste composition data included
Hickman 1992	breakdown of MSW composition into residential (RSW), commercial (CSW), and industrial (ISW); definitions and tables on composition and removal rates	waste composition data and removal rate illustrations limited to New Castle County, Delaware
Jones February 1981	two weeks observation of a sanitary landfill including composition, volume, and daily weight; feasibility of recovering marketable items	limited to Crawford County, OH, over a short time
Kinman, et al. May 1989	good breakdown of waste composition in the landfill at a big city; good data on microorganisms and biodegradation in landfills	limited to the Mallard North Landfill in Chicago, IL
Lawrence June 1992	attempt to reduce solid waste stream at Tinker Air Force Base by attacking subparts by source reduction, recycling, treating, and removing off-base; summary table of solid waste stream including characteristics, composition, generating type, 1990 recycled amounts, and reduction goals	limited to air base in Oklahoma City, OK
Morelli March 1990	discusses characteristics of landfills including composition inputs	composition data from Franklin Assoc. report, 1988

Table C.2 Landfill and MSW Stream References

Reference	Key Features	Notes & Comments
Morelli June 1992	resource recovery of landfill material; landfill received MSW from 1969-1991; addresses feasibility, costs, regulations, and safety; discusses benefits as well as costs associated with reclamation	small landfill (5 acre) in Edinburg, New York; in service 1969-91
Petersen & Luneke June 1990	waste characterization based on four seasonal sorts at three facilities; discusses waste generation rates, comparison to past (1987) data, and per capita disposal rates; good definitions, data, and graphs	limited to Portland, OR, area
Rathje July 1988 December 1989	emphasis on landfill myths, specifically composition breakdown, and how these myths impact current source reduction efforts	limited data and statistics included
Rathje, et al. January 1989	five landfills thoroughly studied for waste composition breakdowns; large amounts of data and graphs; includes the southwest, west and midwest	
Rathje & Thompson March 1989	effects and links of general household income levels with the solid waste they discard; impact of disposal fees on the household disposal pattern	limited to Milwaukee population
Rathje September/October 1990	general discussion of landfill realities: polystyrene, fast-food packaging, & diapers are small contributors; plastic is not a big problem (paper accounts for about 40%); biodegradation is minimal	limited data and statistics included

Table C.2 Landfill and MSW Stream References		
Reference	Key Features	Notes & Comments
Rathje May 1991	discusses myths and reality of U.S. landfill compositions, focuses on the Fresh Kills Landfill on Staten Island; contains some breakdown numbers	data and statistics included of little use for defining functional relationships
Rathje July/August 1992	includes consideration of construction/debris in landfill, previously ignored but now identified as a significant contributor	short, focused on construction/debris
Weddle April 1990	general composition and volumetric breakdown of the waste stream; discusses growth trends and future waste management options for plastics; compares plastics to other waste stream materials	specifically focused on plastic wastes

Table C.3 Recycling and Diversion References

Reference	Key Features	Notes & Comments
Energy Systems Research Group November 1988	waste stream and waste shed characteristics of a model facility; tables containing a summary of solid waste characteristics for the waste shed, and composition of solid waste with and without recycling	the model facility is based on findings of a comprehensive study completed in 1983 of Essex County, New Jersey; the study used actual solid waste sampling data to characterize the county's residential and commercial wastes
EPA January 1989	overview of recycling, what is recyclable, and how communities have started recycling programs across the U. S.; good contact references	data limited
Ferguson 1992	trends (from the 1980s to today) in recycling for Ontario; discusses "blue box" recycling program & contains 1991 wt. breakdown of MSW diversion for six areas in Ontario	based on 6 municipalities in Ontario: York, East York, North York, Etobicoke, Scarborough, and Toronto
Glenn July 1990	discusses current curbside collection programs operating across the U.S. and the materials that they remove from the waste stream; tables depicting program characteristics/results, and collection rates/results	
Hendrickson August 1992	reports increases in recycling and waste-to-energy over the period 1988-90; discusses trends	limited data

Table C.3 Recycling and Diversion References

Reference	Key Features	Notes & Comments
Kelly April 1990	overview of landfill mining; Nov. 1990 landfill mining feasibility studies of 2 landfills; general breakdown of landfill compositions	limited to 25-acre landfill in Kingston, New Hampshire, and 12-acre landfill in Newbury, Massachusetts; limited data
Lancaster County April, 1992	discusses a landfill reclamation project; includes flow diagram depicting weight and volumes diverted to different streams and energy yielded from recovery	based on 18 acre landfill in Lancaster, PA that operated for 16 months; 2839 tons excavated
Lindorff March 1990	overview of the collapse of the recycled newspaper market; 1988 recycling rates for PET and HDPE plastics	limited data
McGuire, et al. February 1982	newspaper and aluminum can recycling are the same for significantly differing socio-economic households; interview and survey data don't match actual disposal and recycle data (people overestimate what they recycle); money is largest recycling incentive	limited to Tucson group
Rathje May 1988	describes the Phoenix Recycling Project which characterizes and show breakdowns of recyclable material in residential waste	
Rugg & Hanna 1992	metals in compostables & noncompostables; composition data by weight percent and moisture content over four seasons (1990-91)	based on Cape May County, PA, landfill
Smith & Baetz December 1991	breakdown of MSW composition and diversion factors for Ontario's waste stream	hard to interpret data; limited to Ontario, Canada; composition data cited from Resource Integration Systems Ltd. report, 1989

Table C.4 Hazardous Household Waste (HHW) References

Reference	Key Features	Notes & Comments
Rathje September 1987 & EPA August 1987	642 metric tons per year of Hazardous Household Waste (HHW) is put in New Orleans Landfill, 259 metric tons per year in Marin County, CA; both are less than 1% of the total, but are significant; EPA report has breakdown of chemicals in HHW	
Wilson May 1989	lead in SW (mainly in oil, newspapers, and magazines); data on amounts and per household	
Wilson & Rathje December 1989	factors that affect HHW: differences between cities, within census tracks within cities (urban/rural), socioeconomic; very good data and functional relationship information	based on data from Phoenix, AZ, Tucson, AZ, Marin County, CA, and New Orleans, LA
Wilson March 1990	evaluative study of one HHW cleaner	Limited study

As Solid Waste Initiative data collection efforts continue, these tables will be expanded to include information from additional sources within the U.S. and Canada, as well as from other countries.

The data presented in the preceding tables represent 34 separate locations in North America, as depicted in Figure C.1.

FIGURE C.1 Locations of CMSW Data Presented in This Appendix

Typical composition breakdowns for MSW are shown in Figures C.2 and C.3.

FIGURE C.2 Composition of Wastes in Municipal Landfills [Rathje 1991]

FIGURE C.3 Average MSW Composition in the U.S. [EPA]

Note that there are some significant differences between the two figures.

Figure C.2 is based on information obtained through assessments of waste materials in landfills [Rathje 1991]. Note that there is a large fraction labeled as "Miscellaneous;" this fraction is mostly construction debris but also includes tires, textiles, rubber, disposable diapers, and the like. Because this figure is representative of materials in the landfills, it may include wastes that are not usually listed as MSW because they are collected separately from normal garbage collection.

Figure C.3 is based on gross discards, by weight, of MSW material in 1986, as reported by the U.S. EPA in EPA/530-SW-89-019 [1989]. These data are reported to be representative of average compositions for MSW in the U.S.

C.2 INDEPENDENTLY MANAGED SOLID WASTES

IMSW represents a much larger quantity of material than CMSW, while at the same time there is less generally available characterization information on it. Major sources of IMSW are the Industrial and Agricultural sectors. Additionally, many wastes from the other sectors are also managed independently of collectively managed systems.

Nonhazardous industrial waste is a considerably larger problem than is commonly recognized. Industrial waste represents 94% of the municipal, industrial, and hazardous waste generated annually in the U.S. [Dernbach 1992]. Agricultural and forestry wastes also account for considerable volumes of material.

While IMSW is a very important waste category, it has not been a major focus of Solid Waste Initiative efforts to date. This is primarily because of the relative abundance of information on CMSW, but also because of the limited availability of time and resources for data collection and correlation. However, as functional relationships are worked out for the CMSW, additional time and attention will be turned to IMSW.

Additional sources of data on IMSW are also expected to emerge. As an example, the London Dumping Convention and ten other international organizations initiated a Global Waste Survey that is to be completed by 1994 [Karau]. The Survey will provide:

- a global inventory of industrial wastes
- an assessment of existing waste management practices
- an identification of environmentally sound technologies and processes for dealing with these wastes.

The UNCED is also expected to lead to significant efforts in this area.

Because data collection efforts for IMSW have been limited to date, review and summarization of data sources has been restricted to those presented in Table C.5.

Table C.5 Independently Managed Solid Waste (IMSW) References		
Reference	Key Features	Notes & Comments
Office of Technology Assessment February 1992	broad overview of RCRA and how it affects the management of industrial solid wastes from manufacturing, mining, oil and gas production, and utility coal combustion	good breakdowns on RCRA Subtitle D information
Täubert 1992	discusses residual materials and quantities from coal power stations; includes uses of the residual material in a variety of ways such as in construction materials.	based on a 750 MW Coal Fired Power Station in the Federal Republic of Germany

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

94   Pacific Northwest Laboratory

12   DOE/Office of Scientific and
         Technical Information

Jess W. Everett
Assistant Professor
University of Oklahoma
202 West Boyd, Room 334
Norman, OK 73019-0631

Ron Kucera
Deputy Director
Missouri Department of
Natural Resources
P.O. Box 176
Jefferson City, MO 65102

David P. Kunz
Hazardous and Solid Waste
Division
Oregon Department of
Environmental Quality
811 S.W. Sixth Avenue
Portland, OR 97204

Marianne Langridge
220 South 33rd Street
Towne Building
Department of Systems
University of Pennsylvania
Philadelphia, PA 19104-6315

Dr. Iraj Zandi
220 South 33rd Street
Towne Building
Department of Systems
University of Pennsylvania
Philadelphia, PA 19104

ONSITE

DOE Richland Field Office

D. R. Segna, A5-90

W. B. Ashton, BW0
J. E. Beck, K6-26
J. M. Buelt, P7-41
R. S. Butner, K2-40
C. C. Chapman, P7-41
J. F. Clarke, BW0
J. A. Edmonds, BW0
M. M. DeWeese, K7-97
B. A. Garrett, K7-82
G. M. Holter, K7-97 (50)
N. L. Hassig, K7-34
K. K. Humphreys, K6-61
J. A. Jaksch, K6-55
P. S. Kaae, K6-61
A. Khawaja, K7-97
D. K. Kreid, K1-22
T. L. Kuusinen, K6-26
R. A. Lundgren, P7-39
J. L. McElroy, P7-46
G. W. McNair, K7-90
D. R. Payson, K7-90
M. S. Peffers, K7-94
K. A. Pennock, K7-22
H. M. Pitcher, BW0
R. W. Reilly, K7-82
J. M. Roop, K6-57
J. L. Scott, P7-34
M. J. Scott, K6-57
S. R. Shaver, K6-61
M. R. Shay, K6-94
D. C. Stapp, K7-97
G. M. Stokes, K1-74
J. J. Thomas, K7-02
J. S. Tixier, P7-34
R. C. Walling, K7-97
M. K. White, K7-94
M. A. Whiting, K7-22
M. L. Wilkins, K7-28
A. J. Villegas, K7-97
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED**

5 / 28 / 93