Effects of Catalytic Mineral Matter CO/CO₂ Ratio on Temperature and Burning Time for Char Combustion

John P. Longwell
Adel F. Sarofim
Leonardo Tognotti
Zhiyou Du

Quarterly Progress Report No. 1

October - December 1989

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Prepared for

U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania
Technical Project Officer - S. Akhtar
Grant No. DE-FG22-89PC89774

by

Massachusetts Institute of Technology
Department of Chemical Engineering
Cambridge, MA 02139

MASTER

RECEIVED
DOE/PC/ETC
50 JUN 29 AM 8:05
ACQUISITION & ASSISTANCE DIV.

rf

Introduction

The high temperature oxidation of char is of interest in a number of applications in which coal must be burned in confined spaces. These include: the conversion of oil-fired boilers to coal using coal-water slurries, the development of a new generation of pulverized-coal-fired cyclone burners, the injection of coal into the tuyeres of blast furnaces, the use of coal as a fuel in direct-fired gas turbines and in large-bore low-speed diesels, and entrained flow gasifiers. In addition there is a need to better understand the temperature history of char particles in conventional pulverized-coal-fired boilers in order to better understand the processes governing the formation of pollutants and the transformation of mineral matter.

The temperature of a char particle burning in an oxygen containing atmosphere is the product of a strongly coupled balance between particle size and physical properties, heat transfer from the particle, surface reactivity, CO/CO₂ ratio and gas phase diffusion in the surrounding boundary layer and within the particle. In addition to its effects on burning rate, particle temperature has major effects on ash properties and mineral matter vaporization. Measurements of the temperature of individual burning char particles have become available in recent years (1,2,3,4) and have clearly demonstrated large particle to particle temperature variations which depend strongly on particle size and on particle composition. These studies, done with pulverized coal, do not allow direct determination of the CO/CO₂ ratio produced at the char surface or the catalytic effects of mineral matter in the individual char particles and it has generally been assumed that CO is the only

product of the carbon-oxygen reaction and that CO₂ is formed by subsequent gas phase reaction (1,2,3,4). More recent work, however, has pointed out the need to take CO₂ production into consideration in order to account for observed particle temperatures (5,6,7,19).

The importance of the CO/CO₂ ratio of carbon oxidation products is illustrated by examination of the heats of reaction for formation of these two products

The heat released by formation of CO₂ is a factor of 3.5 higher than for CO so the temperature of a particle will depend strongly on the CO/CO₂ ratio produced. If gas diffusion through the boundary layer is fast, increased direct production of CO₂ produces a higher temperature and a higher burning rate. If the supply of oxygen to the surface is limited by diffusion through the boundary layer, production of CO₂ consumes half as much carbon as production of CO so carbon consumption rate is reduced even though temperature may be somewhat higher. Models of these complex interaction have been developed; however, the CO/CO₂ ratio produced by the carbon-oxygen reaction must, at present be assumed or inferred from measurement of particle temperature.

CO/CO₂ rates can be strongly influenced by catalytic material in the carbon and by the char temperature. In this program we are measuring the CO/CO₂ ratio for both catalyzed and uncatalyzed chars over a wide range of temperature. These results will then be used to develop predictive models for char temperature and burning rates.

Experimental

The measurements reported here were carried out in the MIT Electrodynamic Balance where a charged particle is suspended in an electric field and is heated by a CO₂ laser. Since the particle is surrounded by cold gas the CO burned near the surface is not oxidized in the bulk gas as it is in combustion systems. This makes possible direct measurement of the combustion products at or near the particle surface.

The electrodynamic balance (EDB) consists of three electrodes in a hyperboloidal configuration, the theory of which is described by Wuerker et al. (10), Davis and Ray (11), Philip (12), and Spjut (13). A dynamic electric field is created in the chamber that is capable of suspending a single, charged particle with a characteristic size less than 250 μm . The ring electrode provides lateral stability to the particle through an imposed AC field, ± 2000 volts, oscillating sinusoidally at 100 Hz. A DC field is superimposed across the top and bottom electrodes to balance the gravitational force on the particle. A position control system can be used to adjust the DC field strength to automatically maintain the particle at the center of the chamber. An optical microscope is used for viewing the particle and for manual control of the particle position. The microscope allows the measurement of the particle diameter to $\pm 5 \mu\text{m}$. A 20 w CO₂ laser supplies energy to the suspended particle and a two-color infrared (2 and 4 μm) pyrometry is used for temperature measurement. A gas flow system allows for particles to be reacted in various gaseous environments. Additional details on the experimental apparatus and procedures can be found in Spjut et al. (14, 15), Bar-Ziv et al. (16), Dudek et al. (17, 18). The EDB is capable of measuring the diameter, weight, density, porosity, excess charge, and Dubinin-Polyani surface area of a single levitated particle (17-19).

After capture in the EDB, each particle is weighed and its diameter measured. The oxygen concentration is set at values of 5, 20, or 100 percent oxygen by flowing calibrated gases through the chamber, after which the chamber is sealed. The experiments were carried out in two principal modes. In the first, the particle is heated by the laser to a desired temperature measured by two-color pyrometry, and the balancing voltage recorded continuously to determine weight loss from which measurements the rate of the reaction can be determined. After a minimum 50 percent of the particle mass is reacted, the laser heating is discontinued, and a gas sample is withdrawn for analysis after a five-minute interval to allow the gas products to diffuse throughout the chamber. In the second mode of operation the particle is heated to above its ignition temperature and the temperature is recorded continuously. An example of such a record is provided in Fig. 1 for the case of a Spherocarb particle heated in pure oxygen with the laser heating turned off just after ignition. For such a run, charge loss by thermionic emission prevents the measurement of the rate of reaction from the balancing voltage. In principle, the rate could be determined from the temperature history but this would require knowledge of the instantaneous CO_2/CO ratio at all times. The gases from this mode of operation are collected to obtain the CO and CO_2 concentrations averaged over the particle's combustion history.

The gases are analyzed by means of a Perkin-Elmer Sigma 2 gas chromatograph with a differential thermal conductivity bridge detector. A Poropak Q column operating at 25°C is used for CO_2 detection while a 5A molecular sieve column operated at 50°C is employed to separate the CO. At least two concentration measurements for each sample were made. The GC detector is calibrated periodically by injecting known amounts of CO and CO_2 (100 ppm of each) in nitrogen. For a typical run the CO + CO_2 concentration was

in the range of 300 to 500 ppm. The EDB chamber volume is 10 ml.

The model char used in this quarter is Spherocarb, a spherical microporous carbon sold by Analabs, Inc. The 60/80 mesh (180-240 μm) commercial fraction was used. This synthetic char has also been used in several previous studies (7, 18-20) because of its relatively low ash content and its sphericity. The physical properties of Spherocarb are: 180-240 μm diameter, 0.63 g/cc apparent bulk density, 1.33g/cc skeletal density, 860 m^2g BET surface area. Its ultimate analysis is: 96.84% C, 0.73% H, 2.43% O, 760 ppm ash.

RESULTS

Figs. 2 to 4 present the CO_2/CO concentration ratio as a function of $1/T$ for the 5, 20, and 100% oxygen concentrations studied. The CO_2/CO ratios decreased from a maximum of 1.5 at 700 K and 100% oxygen to a minimum of 0.06 at 1430 K and 5% oxygen.

A constant pseudo activation energy describes the data quite well up to some threshold temperature above which the CO_2/CO shows a rapid deviation from the straight line Arrhenius type relationship. This is especially apparent in Fig. 4, for 100% oxygen concentration, where the sudden increase in the CO_2/CO took place for particle temperatures above a threshold of 1100 K.

For 5% oxygen (Fig. 2) there was no evidence of such an increase at the maximum temperature of 1430 K. Also shown on Figs. 2 to 4 are least square fit straight lines for temperatures below the threshold values. The pseudo activation energies for the change in CO_2/CO ratio with temperature, tabulated in Table 1, are 5.9, 6.1, and 6.1 kcal for 5, 20, and 100% oxygen respectively.

The particle temperature as a function of time for a laser intensity that led to ignition in 100% oxygen is presented in Fig. 1. When the temperature reached about 1300 K, the heating laser was turned off; the following induction period followed by a steep rise in temperature is characteristic of particle ignition. The following slow rise in temperature that follows is that of the particle burning in the predominantly mass transfer controlled regime, and the temperature then begins to fall as the particle size decreases towards the value of the extinction diameter. Thus the CO_2/CO ratio measured at the end of runs experiencing ignition, is the average of contributions at different temperatures, from 1500 K to 2500 K. The CO_2/CO ratios measured for those runs in which the particle ignition had occurred in pure oxygen are shown on the high temperature end of Fig. 4. The error bars cover the temperature range of the particles during the runs. The CO_2/CO ratio is much higher than the value at the upper end of the values for non-ignited particles (1250 K). Furthermore, the CO_2/CO ratio for particles that had ignited increases with the maximum temperature reached by the particles during combustion. This additional amount of CO_2 is believed to be the result of the gas-phase oxidation of part of the CO in the boundary layer. In order to check the hypothesis of homogeneous conversion of CO to CO_2 , some runs were carried out in oxygen and air that had been previously saturated with water vapor at room temperature ($P_w = 0.035$), since it is well known that water vapor catalyzes the homogeneous oxidation of CO (25,26). The data reported in Figs. 3 and 4 clearly demonstrate that the addition of water results in a substantial decrease in the threshold temperature above which the CO_2/CO ratio shows a rapid departure from the Arrhenius type correlations.

The time, in seconds, for reaction of 50% of the particle mass, $t_{0.5}$, is shown in Fig. 5 as function of $1/T$ for the three oxygen concentrations studied. As illustrated in the next section, these results provide the kinetic data which can be used in combination with the CO_2/CO data to calculate particle ignition temperatures.

DISCUSSION

Products of Heterogeneous Reaction

The CO_2/CO ratios produced by heterogeneous oxidation of carbons can be summarized by an Arrhenius type expression

$$\text{CO}_2/\text{CO} = A \exp (E/RT)$$

where $A = A_0(P_{\text{O}_2})^n$, with P_{O_2} in atmospheres

The CO_2/CO ratio can be considered (27) to be the consequence of the parallel reactions leading to CO_2 and CO . The values of E/R and the exponent n then represent the differences between the activation energies and the order with respect to oxygen for the reactions leading to CO_2 and CO . The value of E/R and the value for n are consistent with results of a detailed study of the carbon oxygen reactions (27).

Table 1 presents a comparison of the experimental conditions and results of various investigations in the literature with those of the present study. The experimental temperature dependence of CO_2/CO was described by an E/R of approximately 3000/K. This value of E/R is in agreement with the values reported by Bonnetain (22) Otterbein (23) and Phillips (24); however, the values reported by Arthur (2) and by Rossberg (21) are higher by approximately a factor of two. This difference in activation energy could be due to differences in the types of active sites on the carbon because of the presence of catalytic impurities. In the case of Arthur's work the presence of POCl_3 might have effected the

results.

CO_2/CO ratio was found to increase with increasing oxygen partial pressure. For this work an order of 0.21 was found which compares with literature values ranging from 0.18 to 0.27.

At 870 K and oxygen pressure 0.2 bar our CO_2/CO was found to be 0.51. The work of Otterbein (23) reports $\text{CO}_2/\text{CO} = .37$ for these conditions. It is expected that, at low temperature, this ratio will vary considerably between carbons because of differences in catalysis and degree of graphitization; however, the effect of catalysis and char structure is expected to diminish as temperature is increased to typical combustion temperatures.

The present results on CO_2/CO ratio extends reported results for uncatalyzed carbons from 945 K to 1670 K at which temperatures, for 20% oxygen, the CO_2/CO ratio decreases to 0.1. The following sections discuss the effect of water vapor on the CO_2/CO ratio and some practical implications.

Oxidation of the Primary CO Product

The EDB was selected for a study of the CO_2/CO ratio because the amount of CO oxidation as it diffuses away from the particle should be minimized by the sharp decline in the gas temperature. However, the departures of the measured CO_2/CO from the pseudo Arrhenius correlations are considered to be a consequence of the homogeneous oxidation of the primary CO product. Calculations using a standard kinetic code (including the reactions of H, H_2 , H_2O , HO, H_2O_2 , HCO, CO, CO_2 , O, OH, O_2 and the effect of N_2 on recombination) were used to estimate the time required to convert 10 percent of the CO to CO_2 by homogeneous gas-phase reactions. By comparing the characteristic reaction times with diffusion times the plausibility of gas phase reactions was evaluated.

In pure dry oxygen, the CO_2/CO ratio increased markedly after the Spherocarb particle ignited (see Figs 1 and 4). For this case most of the mass consumption occurs in the period of steady burning at temperatures about 2000 K. The calculated CO reaction time at 2000 K is 0.04 milliseconds independent of the initial CO concentration. Since the characteristic diffusion time for CO through the boundary layer of a 200 μm particle is of the order 0.03 milliseconds significant gas-phase conversion of the CO can be expected. Since the reaction times increase to several milliseconds by 1500 K and to of the order of 100 milliseconds at 1200 K, it is expected that the oxidation of CO will be confined to a small volume near the surface in which the temperature is about 1500 K.

The effect of adding water vapor further reinforces this view. The temperatures at which 10 percent conversion of CO to CO_2 occurred within a millisecond in the presence of a mole fraction of 0.035 of water vapor was found to fall to about 1220 K for pure oxygen; for air saturated with water vapor the value was about 1250 K. These are close to the temperatures at which substantial deviations from the Arrhenius-type correlations were observed in the presence of water vapor (Figs. 3 and 4). The agreement is qualitative since the CO reaction times in the presence of water vapor are dependent upon the CO level, and the boundary layer calculations should be coupled to a char oxidation model. Such detailed calculations are beyond the scope of the present paper. The calculations of characteristic reaction times, however, tend to support the hypothesis that the increase in CO_2/CO ratio post-char ignition in the absence of water vapor and prior to char ignition in the presence of water vapor are a consequence of homogeneous oxidation of the CO.

A potential complication of any model of the CO oxidation is the possibility that some of the oxidation may occur within the pores. Evidence for such reactions have been

reported in the literature for the oxidation of larger carbon particles (29). These reactions could be catalyzed offering a possible explanation of the effect of mineral matter on the amount of CO_2 produced at or near a particle surface inferred by Niksa and Young (6).

Practical Implications

The data on the CO_2/CO ratio combined with the kinetics of char oxidation permit the calculation of the char ignition temperature. The measured CO_2/CO ratio was used to calculate the heat of reaction in the vicinity of the observed ignition temperature. In pure O_2 , the effective heat release per kilogram of carbon decreases from 14,300 KJ/Kg at 1200 K to 13,600 KJ/Kg at 1300 K. The rate of carbon oxidation in pure oxygen is found from our measurements to be $8.32 \times 10^5 \text{ d}^3 \text{p} \exp(-16,980/T) \text{ g/s}$. At these temperatures external and pore diffusion are negligible (see Fig. 5) so that the rate of heat generation is obtained from the product of the reaction rate and the heat release. The heat loss is dominated by conduction and is readily evaluated; by equating the rate of heat generation to the rate of heat loss, we obtained a temperature 2340 K for the ignition of a $200 \mu\text{m}$ Spherocarb particle in pure oxygen, consistent with the experimental findings.

The fractional conversion of CO to CO_2 above the ignition or threshold temperatures was found, in this work, to be as high as .55. Waters (7) in studies of Spherocarb oxidation concluded that his data on burning rates and particle temperature were best fitted by a CO_2/CO ratio of $.54 \pm 0.12$. Mitchell (5), burning 75-125 μm bituminous coal particles, concluded that for particle temperatures in the 1600 to 1700 K temperature range a best fit for the burning rate was obtained with a CO_2/CO ratio of 0.17. Clearly knowledge of this ratio, as governed by both surface and gas phase reactions, is important. The present results show that the EDB is useful in separating the gas and solid contributions but more

research will be needed with different chars to be able to provide further generalizations.

CONCLUSIONS

The electrodynamic balance provides a useful tool for obtaining CO_2/CO ratios produced at or near a particle surface during carbon oxidation, values that are important for determining the ignition temperature or the burning temperature of char particles. At lower temperatures the ratio is determined by competing surface reactions which result in an exponential decrease in the CO_2/CO ratio with increasing temperature with a pseudo activation energy of 6 kcal and a pressure exponent on oxygen of 0.2. At normal combustion temperatures the ratio of the heterogeneous products is less than 0.1. Partial conversion of CO to CO_2 at higher temperatures occurs by gas reactions that are augmented by the presence of water vapor. These reactions take place close to the surface, even in a gas maintained at room temperature, and will therefore have an important impact on surface temperature.

Future Program

During the next quarter studies of carbons catalyzed by calcium will be carried out in a conventional TGA to tie in with past work on mechanism of carbon oxidation. The electrodynamic TGA is currently being upgraded by inclusion of improved temperature control measurement. A new chamber which allow control of atmospheric composition and pressure will also be installed.

REFERENCES

1. Ayling, A.B. and Smith, I.W.: *Combust. Flame* 18, 173 (1972).
2. Arthur, J.: *Trans. Faraday Soc.* 47, 164 (1951).
3. Mitchell, R.E. and Madsen, O.H.: *Twenty-first Symposium (International) on Combustion*, p. 173, The Combustion Institute, 1986.
4. Niksa, S., Mitchell, R.E., Henken, K.R. and Tichenor, D.A.: *Comb. Flame* 60, 183 (1984).
5. Mitchell, R.E.: *Twenty-second Symposium (International) on Combustion*, p. 69, The Combustion Institute, 1988.
6. Young, B.C. and Niksa, S.: *Fuel* 67, 157 (1988).
7. Waters, B.J., Squires, R.G., Laurendau, N.M. and Mitchell, R.E.: *Comb. Flame* 74, 91 (1988).
8. McCollor, D.P., Jones, M.L., Benson S.A. and Young, B.C.: *Twenty-second Symposium (International) on Combustion*, p. 59, The Combustion Institute, 1988.
9. Smith, I.W.: *Nineteenth Symposium (International) on Combustion*, p. 1045, The Combustion Institute, 1982.
10. Wuerker, R.F., Shelton, H. and Langmuir, R.V.: *J. App. Phys.* 3, 342 (1959).
11. Davis, E.J. and Ray, A.K.: *J. Colloid Interface Sci.* 75, 566 (1980).
12. Philips, M.A.: "An Absolute Method for Aerosol Particle Mass Measurement" *Massachusetts Institute of Technology, M.S. Thesis* (1981).
13. Spjut, R.E.: "Heat Transfer to and Position Control of Electrodynamically Suspended Micron-Sized Particles", *Massachusetts Institute of Technology, PhD Thesis* (1985).
14. Spjut, R.E., Bar-Ziv, E., Sarofim, A.F. and Longwell, J.P.: *Rev. Sc. Instr.* 57, 1604 (1986).
15. Spjut, R.E., Sarofim, A.F. and Longwell, J.P.: *Langmuir* 1, 355 (1985).
16. Bar-Ziv, E., Jones, D.B., Spjut, R.E., Dudek, D.R., Sarofim, A.F. and Longwell, J.P.: *Comb. Flame* 75, 81 (1989).
17. Dudek, D.R.: "Single Particle, High Temperature, Gas-Solid Reactions in an

Electrodynamic Balance", Massachusetts Institute of Technology, PhD Thesis (1988).

18. Dudek, D.R., Sarofim, A.F., and Longwell, J.P.: Energy and Fuels 3, 24 (1988).
19. D'Amore, M., Dudek, D.R., Sarofim, A.F., and Longwell, J.P.: Powder Technology 56, 129 (1988).
20. Hurt, R.H., Dudek, D.R., Longwell, J.P. and Sarofim, A.F.: Carbon (1987).
21. Rossberg, M.Z.: Elektrochem. 60, 952 (1956).
22. Bonnetain, L., Duval, D., and Letort, M.: Proc. Fourth Carbon Conf., p. 107, Pergamon Press, Oxford 1960.
23. Otterbain, M. and Bonnetain, L.: Carbon 6, 877 (1968).
24. Phillips, R., Vastola, F.J., and Walker, P.L., Carbon 8, 205 (1970).
25. Dryer, F.L., and Glassmann, L.: Fourteenth Symposium (International) on Combustion, p. 987, The Combustion Institute, 1973.
26. Howard, J.B., Williams, G.C. and Fine, D.H.: Fourteenth Symposium (International) on Combustion, p. 975, The Combustion Institute, 1973.
27. Du, Z., PhD Thesis, "Kinetic Modeling of Carbon Oxidation", Massachusetts Institute of Technology, January 1990.
28. Kee, R.J., Miller, J.A. and Jefferson, J.H.: "CHEMKIN: A General-Purpose, Problem Independent, Transportable, Fortran Chemical Kinetic Code" Sandia Laboratories Report available from National Technical Information Service, U.S. Dept. of Commerce, Springfield, VA.
29. Kurylko, L., and Essenhigh, R.H., Fourteenth Symposium (International) on Combustion, pp 1375-1386, The Combustion Institute, 1973.

Table I

Summary of Results for Heterogeneous Oxidation

Reference	Material	System	Temperature K	P _{O2} Bar	$\frac{R}{R}$ K	n
This Work	Spherocarb	EDB	670-	.05	2980	0.21
			1670	.20	3070	
				1.0	3070	
Osterbein (23)	Vitreous Carbon	Flow System	770-	.025-	3000	.18
			920	.15		
Phillips (24)	Graphon	Static System	800-	.013x10 ⁻³	3200	.22
			950	.26x10 ⁻³		
Du (27)	Soot	TGA	670-890	.05-1.0	3200	.27
Arthur (2)	Natur. Graphite, Coal Char	Flow System +POCl ₂	730-	.05-	6240	
			1170	.25		
Rossberg (21)	Electrode Carbons	Flow System	790-		7200	
			1690		9260	

$$\text{CO}_2/\text{CO} = A \exp(-E/RT) A-A P_o^n$$

Figure 1. Particle temperature as a function of time for 100% oxygen under ignition conditions.

Figure 2. CO_2/CO ratio as a function of inverse temperature for 5% oxygen.

Figure 3. CO_2/CO ratio as a function of inverse temperature for 20% oxygen for dry gas and in the presence of 3.5% water.

Figure 4. CO_2/CO ratio as a function of inverse temperature for 100% oxygen for dry gas and in the presence of 3.5 mol % water.

END

**DATE
FILMED**

3 / 31 / 93